

The L^AT_EX3 Sources

The L^AT_EX3 Project*

Released 2019-01-13

Abstract

This is the reference documentation for the `expl3` programming environment. The `expl3` modules set up an experimental naming scheme for L^AT_EX commands, which allow the L^AT_EX programmer to systematically name functions and variables, and specify the argument types of functions.

The T_EX and ϵ -T_EX primitives are all given a new name according to these conventions. However, in the main direct use of the primitives is not required or encouraged: the `expl3` modules define an independent low-level L^AT_EX3 programming language.

At present, the `expl3` modules are designed to be loaded on top of L^AT_EX 2 ϵ . In time, a L^AT_EX3 format will be produced based on this code. This allows the code to be used in L^AT_EX 2 ϵ packages *now* while a stand-alone L^AT_EX3 is developed.

While `expl3` is still experimental, the bundle is now regarded as broadly stable. The syntax conventions and functions provided are now ready for wider use. There may still be changes to some functions, but these will be minor when compared to the scope of `expl3`.

New modules will be added to the distributed version of `expl3` as they reach maturity.

*E-mail: latex-team@latex-project.org

Contents

I	Introduction to <code>expl3</code> and this document	1
1	Naming functions and variables	1
1.1	Terminological inexactitude	3
2	Documentation conventions	3
3	Formal language conventions which apply generally	5
4	<code>TeX</code> concepts not supported by <code>LaTeX3</code>	5
II	The <code>l3bootstrap</code> package: Bootstrap code	6
1	Using the <code>LaTeX3</code> modules	6
III	The <code>l3names</code> package: Namespace for primitives	7
1	Setting up the <code>LaTeX3</code> programming language	7
IV	The <code>l3basics</code> package: Basic definitions	8
1	No operation functions	8
2	Grouping material	8
3	Control sequences and functions	9
3.1	Defining functions	9
3.2	Defining new functions using parameter text	10
3.3	Defining new functions using the signature	11
3.4	Copying control sequences	14
3.5	Deleting control sequences	14
3.6	Showing control sequences	14
3.7	Converting to and from control sequences	15
4	Analysing control sequence names	16
5	Using or removing tokens and arguments	16
5.1	Selecting tokens from delimited arguments	18
6	Predicates and conditionals	19
6.1	Tests on control sequences	20
6.2	Primitive conditionals	20
V	The <code>l3expan</code> package: Argument expansion	22

1	Defining new variants	22
2	Methods for defining variants	23
3	Introducing the variants	24
4	Manipulating the first argument	26
5	Manipulating two arguments	28
6	Manipulating three arguments	29
7	Unbraced expansion	30
8	Preventing expansion	31
9	Controlled expansion	32
10	Internal functions	34
VI	The <code>l3tl</code> package: Token lists	35
1	Creating and initialising token list variables	35
2	Adding data to token list variables	36
3	Modifying token list variables	37
4	Reassigning token list category codes	37
5	Token list conditionals	38
6	Mapping to token lists	40
7	Using token lists	42
8	Working with the content of token lists	43
9	The first token from a token list	44
10	Using a single item	47
11	Viewing token lists	49
12	Constant token lists	49
13	Scratch token lists	50
VII	The <code>l3str</code> package: Strings	51
1	Building strings	51

2	Adding data to string variables	52
3	Modifying string variables	53
4	String conditionals	53
5	Mapping to strings	55
6	Working with the content of strings	57
7	String manipulation	60
8	Viewing strings	61
9	Constant token lists	62
10	Scratch strings	62
 VIII The l3quark package: Quarks		 63
1	Quarks	63
2	Defining quarks	63
3	Quark tests	64
4	Recursion	64
5	An example of recursion with quarks	65
6	Scan marks	66
 IX The l3seq package: Sequences and stacks		 68
1	Creating and initialising sequences	68
2	Appending data to sequences	69
3	Recovering items from sequences	69
4	Recovering values from sequences with branching	71
5	Modifying sequences	72
6	Sequence conditionals	72
7	Mapping to sequences	73
8	Using the content of sequences directly	74
9	Sequences as stacks	75

10	Sequences as sets	76
11	Constant and scratch sequences	77
12	Viewing sequences	78
X	The <code>l3int</code> package: Integers	79
1	Integer expressions	79
2	Creating and initialising integers	80
3	Setting and incrementing integers	81
4	Using integers	82
5	Integer expression conditionals	82
6	Integer expression loops	84
7	Integer step functions	86
8	Formatting integers	87
9	Converting from other formats to integers	88
10	Random integers	89
11	Viewing integers	89
12	Constant integers	90
13	Scratch integers	90
	13.1 Direct number expansion	91
14	Primitive conditionals	91
XI	The <code>l3flag</code> package: Expandable flags	93
1	Setting up flags	93
2	Expandable flag commands	94
XII	The <code>l3prg</code> package: Control structures	95
1	Defining a set of conditional functions	95
2	The boolean data type	97
3	Boolean expressions	99

4	Logical loops	101
5	Producing multiple copies	102
6	Detecting TeX's mode	102
7	Primitive conditionals	102
8	Nestable recursions and mappings	103
	8.1 Simple mappings	103
9	Internal programming functions	104
XIII The l3sys package: System/runtime functions		105
1	The name of the job	105
2	Date and time	105
3	Engine	105
4	Output format	106
XIV The l3clist package: Comma separated lists		107
1	Creating and initialising comma lists	107
2	Adding data to comma lists	109
3	Modifying comma lists	109
4	Comma list conditionals	110
5	Mapping to comma lists	111
6	Using the content of comma lists directly	113
7	Comma lists as stacks	113
8	Using a single item	115
9	Viewing comma lists	115
10	Constant and scratch comma lists	116
XV The l3token package: Token manipulation		117
1	Creating character tokens	117
2	Manipulating and interrogating character tokens	119

3	Generic tokens	122
4	Converting tokens	122
5	Token conditionals	123
6	Peeking ahead at the next token	126
7	Decomposing a macro definition	128
8	Description of all possible tokens	129
 XVI The <code>l3prop</code> package: Property lists		132
1	Creating and initialising property lists	132
2	Adding entries to property lists	133
3	Recovering values from property lists	133
4	Modifying property lists	134
5	Property list conditionals	134
6	Recovering values from property lists with branching	135
7	Mapping to property lists	135
8	Viewing property lists	136
9	Scratch property lists	137
10	Constants	137
 XVII The <code>l3msg</code> package: Messages		138
1	Creating new messages	138
2	Contextual information for messages	139
3	Issuing messages	140
4	Redirecting messages	142
 XVIII The <code>l3file</code> package: File and I/O operations		144
1	Input–output stream management	144
1.1	Reading from files	146

2	Writing to files	148
2.1	Wrapping lines in output	150
2.2	Constant input-output streams, and variables	151
2.3	Primitive conditionals	151
3	File operation functions	151
XIX	The l3skip package: Dimensions and skips	153
1	Creating and initialising dim variables	153
2	Setting dim variables	154
3	Utilities for dimension calculations	154
4	Dimension expression conditionals	155
5	Dimension expression loops	157
6	Dimension step functions	158
7	Using dim expressions and variables	159
8	Viewing dim variables	160
9	Constant dimensions	161
10	Scratch dimensions	161
11	Creating and initialising skip variables	161
12	Setting skip variables	162
13	Skip expression conditionals	163
14	Using skip expressions and variables	163
15	Viewing skip variables	163
16	Constant skips	164
17	Scratch skips	164
18	Inserting skips into the output	164
19	Creating and initialising muskip variables	165
20	Setting muskip variables	165
21	Using muskip expressions and variables	166
22	Viewing muskip variables	166

23	Constant muskips	167
24	Scratch muskips	167
25	Primitive conditional	167
XX	The l3keys package: Key–value interfaces	168
1	Creating keys	169
2	Sub-dividing keys	173
3	Choice and multiple choice keys	173
4	Setting keys	176
5	Handling of unknown keys	176
6	Selective key setting	177
7	Utility functions for keys	178
8	Low-level interface for parsing key–val lists	179
XXI	The l3intarray package: fast global integer arrays	181
1	l3intarray documentation	181
1.1	Implementation notes	182
XXII	The l3fp package: Floating points	183
1	Creating and initialising floating point variables	184
2	Setting floating point variables	185
3	Using floating points	185
4	Floating point conditionals	187
5	Floating point expression loops	188
6	Some useful constants, and scratch variables	190
7	Floating point exceptions	191
8	Viewing floating points	192

9	Floating point expressions	192
9.1	Input of floating point numbers	192
9.2	Precedence of operators	194
9.3	Operations	194
10	Disclaimer and roadmap	201
XXIII	The l3fparray package: fast global floating point arrays	204
1	l3fparray documentation	204
XXIV	The l3sort package: Sorting functions	205
1	Controlling sorting	205
XXV	The l3tl-analysis package: Analysing token lists	206
1	l3tl-analysis documentation	206
XXVI	The l3regex package: Regular expressions in T_EX	207
1	Syntax of regular expressions	207
2	Syntax of the replacement text	212
3	Pre-compiling regular expressions	214
4	Matching	214
5	Submatch extraction	215
6	Replacement	216
7	Constants and variables	216
8	Bugs, misfeatures, future work, and other possibilities	217
XXVII	The l3box package: Boxes	220
1	Creating and initialising boxes	220
2	Using boxes	221
3	Measuring and setting box dimensions	222
4	Box conditionals	222
5	The last box inserted	223

6	Constant boxes	223
7	Scratch boxes	223
8	Viewing box contents	223
9	Boxes and color	224
10	Horizontal mode boxes	224
11	Vertical mode boxes	225
12	Affine transformations	227
13	Primitive box conditionals	229
 XXVIII The <code>l3coffins</code> package: Coffin code layer		231
1	Creating and initialising coffins	231
2	Setting coffin content and poles	231
3	Joining and using coffins	232
4	Measuring coffins	233
5	Coffin diagnostics	233
6	Constants and variables	234
 XXIX The <code>l3color-base</code> package: Color support		235
1	Color in boxes	235
 XXX The <code>l3luatex</code> package: Lua_{TeX}-specific functions		236
1	Breaking out to Lua	236
2	Lua interfaces	237
 XXXI The <code>l3unicode</code> package: Unicode support functions		238
 XXXII The <code>l3candidates</code> package: Experimental additions to <code>l3kernel</code>		239
1	Important notice	239
2	Additions to <code>l3basics</code>	240

3	Additions to l3box	241
3.1	Viewing part of a box	241
4	Additions to l3coffins	241
5	Additions to l3expan	242
6	Additions to l3fp	242
7	Additions to l3farray	242
8	Additions to l3file	243
9	Additions to l3flag	244
10	Additions to l3int	244
11	Additions to l3intarray	245
11.1	Working with contents of integer arrays	245
12	Additions to l3msg	245
13	Additions to l3prg	246
14	Additions to l3prop	247
15	Additions to l3seq	248
16	Additions to l3skip	249
17	Additions to l3sys	250
18	Additions to l3tl	251
19	Additions to l3token	257
XXXIII	The l3drivers package: Drivers	259
1	Box clipping	259
2	Box rotation and scaling	260
3	Color support	260
4	Drawing	260
4.1	Path construction	261
4.2	Stroking and filling	262
4.3	Stroke options	263
4.4	Color	263
4.5	Inserting T _E X material	264
4.6	Coordinate system transformations	264

5	PDF Features	264
5.1	PDF Objects	264
5.2	PDF structure	265
XXXIV	Implementation	265
1	l3bootstrap implementation	265
1.1	Format-specific code	265
1.2	The <code>\pdfstrcmp</code> primitive in $\text{X}_{\text{T}}\text{E}\text{X}$	266
1.3	Loading support Lua code	267
1.4	Engine requirements	267
1.5	Extending allocators	269
1.6	Character data	270
1.7	The $\text{L}\text{A}\text{T}\text{E}\text{X}3$ code environment	271
2	l3names implementation	273
2.1	Deprecated functions	296
3	Internal kernel functions	308
4	l3basics implementation	313
4.1	Renaming some TEX primitives (again)	313
4.2	Defining some constants	315
4.3	Defining functions	316
4.4	Selecting tokens	316
4.5	Gobbling tokens from input	318
4.6	Debugging and patching later definitions	318
4.7	Conditional processing and definitions	326
4.8	Dissecting a control sequence	332
4.9	Exist or free	335
4.10	Preliminaries for new functions	336
4.11	Defining new functions	338
4.12	Copying definitions	339
4.13	Undefining functions	340
4.14	Generating parameter text from argument count	340
4.15	Defining functions from a given number of arguments	341
4.16	Using the signature to define functions	342
4.17	Checking control sequence equality	344
4.18	Diagnostic functions	345
4.19	Doing nothing functions	346
4.20	Breaking out of mapping functions	346

5	l3expan implementation	347
5.1	General expansion	347
5.2	Hand-tuned definitions	350
5.3	Definitions with the automated technique	353
5.4	Last-unbraced versions	354
5.5	Preventing expansion	357
5.6	Controlled expansion	358
5.7	Emulating e-type expansion	358
5.8	Defining function variants	364
6	l3tl implementation	373
6.1	Functions	373
6.2	Constant token lists	375
6.3	Adding to token list variables	376
6.4	Reassigning token list category codes	378
6.5	Modifying token list variables	381
6.6	Token list conditionals	384
6.7	Mapping to token lists	389
6.8	Using token lists	390
6.9	Working with the contents of token lists	391
6.10	Token by token changes	393
6.11	The first token from a token list	395
6.12	Using a single item	400
6.13	Viewing token lists	403
6.14	Scratch token lists	404
7	l3str implementation	404
7.1	Creating and setting string variables	404
7.2	Modifying string variables	405
7.3	String comparisons	407
7.4	Mapping to strings	410
7.5	Accessing specific characters in a string	411
7.6	Counting characters	416
7.7	The first character in a string	417
7.8	String manipulation	419
7.9	Viewing strings	420
7.10	Deprecated functions	420
8	l3quark implementation	421
8.1	Quarks	421
8.2	Scan marks	424

9	l3seq implementation	425
9.1	Allocation and initialisation	426
9.2	Appending data to either end	428
9.3	Modifying sequences	429
9.4	Sequence conditionals	432
9.5	Recovering data from sequences	432
9.6	Mapping to sequences	436
9.7	Using sequences	439
9.8	Sequence stacks	439
9.9	Viewing sequences	440
9.10	Scratch sequences	441
10	l3int implementation	441
10.1	Integer expressions	442
10.2	Creating and initialising integers	444
10.3	Setting and incrementing integers	446
10.4	Using integers	447
10.5	Integer expression conditionals	448
10.6	Integer expression loops	452
10.7	Integer step functions	453
10.8	Formatting integers	455
10.9	Converting from other formats to integers	460
10.10	Viewing integer	463
10.11	Random integers	464
10.12	Constant integers	464
10.13	Scratch integers	464
10.14	Deprecated	465
11	l3flag implementation	466
11.1	Non-expandable flag commands	466
11.2	Expandable flag commands	467
12	l3prg implementation	468
12.1	Primitive conditionals	468
12.2	Defining a set of conditional functions	468
12.3	The boolean data type	469
12.4	Boolean expressions	471
12.5	Logical loops	475
12.6	Producing multiple copies	476
12.7	Detecting T _E X's mode	478
12.8	Internal programming functions	479
12.9	Deprecated functions	479
13	l3sys implementation	480
13.1	The name of the job	480
13.2	Time and date	480
13.3	Detecting the engine	481
13.4	Detecting the output	481
13.5	Randomness	482

14	l3clist implementation	482
14.1	Removing spaces around items	483
14.2	Allocation and initialisation	484
14.3	Adding data to comma lists	486
14.4	Comma lists as stacks	487
14.5	Modifying comma lists	489
14.6	Comma list conditionals	492
14.7	Mapping to comma lists	493
14.8	Using comma lists	496
14.9	Using a single item	497
14.10	Viewing comma lists	499
14.11	Scratch comma lists	499
15	l3token implementation	500
15.1	Manipulating and interrogating character tokens	500
15.2	Creating character tokens	502
15.3	Generic tokens	506
15.4	Token conditionals	507
15.5	Peeking ahead at the next token	514
15.6	Decomposing a macro definition	519
16	l3prop implementation	520
16.1	Allocation and initialisation	521
16.2	Accessing data in property lists	523
16.3	Property list conditionals	527
16.4	Recovering values from property lists with branching	529
16.5	Mapping to property lists	529
16.6	Viewing property lists	530
17	l3msg implementation	530
17.1	Creating messages	531
17.2	Messages: support functions and text	532
17.3	Showing messages: low level mechanism	533
17.4	Displaying messages	535
17.5	Kernel-specific functions	544
17.6	Expandable errors	552
18	l3file implementation	555
18.1	Input operations	555
18.1.1	Variables and constants	555
18.1.2	Stream management	556
18.1.3	Reading input	559
18.2	Output operations	561
18.2.1	Variables and constants	561
18.3	Stream management	562
18.3.1	Deferred writing	564
18.3.2	Immediate writing	564
18.3.3	Special characters for writing	565
18.3.4	Hard-wrapping lines to a character count	565
18.4	File operations	575

18.5	Messages	581
19	l3skip implementation	582
19.1	Length primitives renamed	582
19.2	Creating and initialising <code>dim</code> variables	582
19.3	Setting <code>dim</code> variables	584
19.4	Utilities for dimension calculations	585
19.5	Dimension expression conditionals	586
19.6	Dimension expression loops	588
19.7	Dimension step functions	589
19.8	Using <code>dim</code> expressions and variables	591
19.9	Viewing <code>dim</code> variables	592
19.10	Constant dimensions	593
19.11	Scratch dimensions	593
19.12	Creating and initialising <code>skip</code> variables	593
19.13	Setting <code>skip</code> variables	594
19.14	Skip expression conditionals	595
19.15	Using <code>skip</code> expressions and variables	596
19.16	Inserting skips into the output	596
19.17	Viewing <code>skip</code> variables	597
19.18	Constant skips	597
19.19	Scratch skips	597
19.20	Creating and initialising <code>muskip</code> variables	598
19.21	Setting <code>muskip</code> variables	599
19.22	Using <code>muskip</code> expressions and variables	600
19.23	Viewing <code>muskip</code> variables	600
19.24	Constant muskips	601
19.25	Scratch muskips	601
20	l3keys Implementation	601
20.1	Low-level interface	601
20.2	Constants and variables	605
20.3	The key defining mechanism	607
20.4	Turning properties into actions	609
20.5	Creating key properties	614
20.6	Setting keys	618
20.7	Utilities	624
20.8	Messages	625
21	l3intarray implementation	626
21.1	Allocating arrays	626
21.2	Array items	627
21.3	Working with contents of integer arrays	630
21.4	Random arrays	631
22	l3fp implementation	633

23	l3fp-aux implementation	633
23.1	Access to primitives	633
23.2	Internal representation	633
23.3	Using arguments and semicolons	634
23.4	Constants, and structure of floating points	635
23.5	Overflow, underflow, and exact zero	637
23.6	Expanding after a floating point number	637
23.7	Other floating point types	639
23.8	Packing digits	642
23.9	Decimate (dividing by a power of 10)	644
23.10	Functions for use within primitive conditional branches	646
23.11	Integer floating points	648
23.12	Small integer floating points	648
23.13	x-like expansion expandably	649
23.14	Fast string comparison	649
23.15	Name of a function from its l3fp-parse name	650
23.16	Messages	650
24	l3fp-traps Implementation	650
24.1	Flags	651
24.2	Traps	651
24.3	Errors	654
24.4	Messages	655
25	l3fp-round implementation	655
25.1	Rounding tools	656
25.2	The round function	660
26	l3fp-parse implementation	663
26.1	Work plan	663
26.1.1	Storing results	665
26.1.2	Precedence and infix operators	666
26.1.3	Prefix operators, parentheses, and functions	669
26.1.4	Numbers and reading tokens one by one	669
26.2	Main auxiliary functions	671
26.3	Helpers	672
26.4	Parsing one number	673
26.4.1	Numbers: trimming leading zeros	679
26.4.2	Number: small significand	681
26.4.3	Number: large significand	683
26.4.4	Number: beyond 16 digits, rounding	685
26.4.5	Number: finding the exponent	687
26.5	Constants, functions and prefix operators	690
26.5.1	Prefix operators	690
26.5.2	Constants	693
26.5.3	Functions	695
26.6	Main functions	695
26.7	Infix operators	697
26.7.1	Closing parentheses and commas	698
26.7.2	Usual infix operators	700

	26.7.3 Juxtaposition	701
	26.7.4 Multi-character cases	701
	26.7.5 Ternary operator	702
	26.7.6 Comparisons	702
	26.8 Tools for functions	704
	26.9 Messages	706
27	l3fp-assign implementation	707
	27.1 Assigning values	707
	27.2 Updating values	708
	27.3 Showing values	709
	27.4 Some useful constants and scratch variables	709
28	l3fp-logic Implementation	710
	28.1 Syntax of internal functions	710
	28.2 Existence test	710
	28.3 Comparison	710
	28.4 Floating point expression loops	713
	28.5 Extrema	717
	28.6 Boolean operations	718
	28.7 Ternary operator	719
29	l3fp-basics Implementation	720
	29.1 Addition and subtraction	721
	29.1.1 Sign, exponent, and special numbers	721
	29.1.2 Absolute addition	723
	29.1.3 Absolute subtraction	725
	29.2 Multiplication	730
	29.2.1 Signs, and special numbers	730
	29.2.2 Absolute multiplication	731
	29.3 Division	733
	29.3.1 Signs, and special numbers	733
	29.3.2 Work plan	734
	29.3.3 Implementing the significand division	737
	29.4 Square root	742
	29.5 About the sign and exponent	749
	29.6 Operations on tuples	750
30	l3fp-extended implementation	751
	30.1 Description of fixed point numbers	751
	30.2 Helpers for numbers with extended precision	752
	30.3 Multiplying a fixed point number by a short one	753
	30.4 Dividing a fixed point number by a small integer	753
	30.5 Adding and subtracting fixed points	755
	30.6 Multiplying fixed points	755
	30.7 Combining product and sum of fixed points	757
	30.8 Extended-precision floating point numbers	759
	30.9 Dividing extended-precision numbers	761
	30.10 Inverse square root of extended precision numbers	764
	30.11 Converting from fixed point to floating point	766

31	l3fp-expo implementation	768
31.1	Logarithm	769
31.1.1	Work plan	769
31.1.2	Some constants	769
31.1.3	Sign, exponent, and special numbers	770
31.1.4	Absolute ln	770
31.2	Exponential	777
31.2.1	Sign, exponent, and special numbers	777
31.3	Power	781
32	l3fp-trig Implementation	788
32.1	Direct trigonometric functions	789
32.1.1	Filtering special cases	789
32.1.2	Distinguishing small and large arguments	792
32.1.3	Small arguments	793
32.1.4	Argument reduction in degrees	793
32.1.5	Argument reduction in radians	794
32.1.6	Computing the power series	802
32.2	Inverse trigonometric functions	804
32.2.1	Arctangent and arccotangent	805
32.2.2	Arcsine and arccosine	810
32.2.3	Arccosecant and arcsecant	812
33	l3fp-convert implementation	813
33.1	Dealing with tuples	813
33.2	Trimming trailing zeros	814
33.3	Scientific notation	814
33.4	Decimal representation	816
33.5	Token list representation	818
33.6	Formatting	819
33.7	Convert to dimension or integer	819
33.8	Convert from a dimension	820
33.9	Use and eval	821
33.10	Convert an array of floating points to a comma list	821
34	l3fp-random Implementation	822
34.1	Engine support	822
34.2	Random floating point	826
34.3	Random integer	826
35	l3fparray implementation	831
35.1	Allocating arrays	832
35.2	Array items	833

36	l3sort implementation	836
36.1	Variables	836
36.2	Finding available \toks registers	837
36.3	Protected user commands	839
36.4	Merge sort	841
36.5	Expandable sorting	844
36.6	Messages	849
37	l3tl-analysis implementation	850
37.1	Internal functions	850
37.2	Internal format	851
37.3	Variables and helper functions	851
37.4	Plan of attack	853
37.5	Disabling active characters	854
37.6	First pass	855
37.7	Second pass	860
37.8	Mapping through the analysis	863
37.9	Showing the results	863
37.10	Messages	866
37.11	Deprecated functions	866
38	l3regex implementation	866
38.1	Plan of attack	866
38.2	Helpers	868
38.2.1	Constants and variables	869
38.2.2	Testing characters	870
38.2.3	Character property tests	874
38.2.4	Simple character escape	876
38.3	Compiling	881
38.3.1	Variables used when compiling	882
38.3.2	Generic helpers used when compiling	883
38.3.3	Mode	884
38.3.4	Framework	887
38.3.5	Quantifiers	889
38.3.6	Raw characters	892
38.3.7	Character properties	894
38.3.8	Anchoring and simple assertions	895
38.3.9	Character classes	896
38.3.10	Groups and alternations	899
38.3.11	Catcodes and csnames	902
38.3.12	Raw token lists with \u	905
38.3.13	Other	907
38.3.14	Showing regexes	908
38.4	Building	912
38.4.1	Variables used while building	912
38.4.2	Framework	912
38.4.3	Helpers for building an NFA	914
38.4.4	Building classes	916
38.4.5	Building groups	917
38.4.6	Others	922

38.5	Matching	923
38.5.1	Variables used when matching	924
38.5.2	Matching: framework	926
38.5.3	Using states of the NFA	930
38.5.4	Actions when matching	931
38.6	Replacement	933
38.6.1	Variables and helpers used in replacement	933
38.6.2	Query and brace balance	934
38.6.3	Framework	936
38.6.4	Submatches	938
38.6.5	Csnames in replacement	939
38.6.6	Characters in replacement	940
38.6.7	An error	944
38.7	User functions	944
38.7.1	Variables and helpers for user functions	946
38.7.2	Matching	947
38.7.3	Extracting submatches	948
38.7.4	Replacement	951
38.7.5	Storing and showing compiled patterns	953
38.8	Messages	953
38.9	Code for tracing	959
39	l3box implementation	960
39.1	Support code	960
39.2	Creating and initialising boxes	960
39.3	Measuring and setting box dimensions	961
39.4	Using boxes	962
39.5	Box conditionals	962
39.6	The last box inserted	963
39.7	Constant boxes	963
39.8	Scratch boxes	963
39.9	Viewing box contents	963
39.10	Horizontal mode boxes	964
39.11	Vertical mode boxes	967
39.12	Affine transformations	970
40	l3coffins Implementation	977
40.1	Coffins: data structures and general variables	978
40.2	Basic coffin functions	979
40.3	Measuring coffins	983
40.4	Coffins: handle and pole management	983
40.5	Coffins: calculation of pole intersections	986
40.6	Aligning and typesetting of coffins	989
40.7	Coffin diagnostics	994
40.8	Messages	999
41	l3color-base Implementation	1000

42	l3luatex implementation	1001
42.1	Breaking out to Lua	1001
42.2	Messages	1002
42.3	Deprecated functions	1002
42.4	Lua functions for internal use	1003
42.5	Generic Lua and font support	1006
43	l3unicode implementation	1006
44	l3candidates Implementation	1009
44.1	Additions to l3basics	1010
44.2	Additions to l3box	1010
44.2.1	Viewing part of a box	1010
44.3	Additions to l3coffins	1012
44.3.1	Rotating coffins	1012
44.3.2	Resizing coffins	1017
44.4	Additions to l3fp-convert	1019
44.5	Additions to l3file	1019
44.6	Additions to l3flag	1021
44.7	Additions to l3msg	1022
44.8	Additions to l3msg	1022
44.9	Additions to l3prg	1023
44.10	Additions to l3prop	1024
44.11	Additions to l3seq	1025
44.12	Additions to l3skip	1029
44.13	Additions to l3sys	1030
44.14	Additions to l3tl	1033
44.14.1	Unicode case changing	1037
44.14.2	Building a token list	1059
44.14.3	Other additions to l3tl	1063
44.15	Additions to l3token	1063
45	l3drivers Implementation	1066
45.1	Color support	1067
45.1.1	dvips-style	1067
45.1.2	pdfmode	1069
45.2	dvips driver	1071
45.2.1	Basics	1071
45.2.2	Box operations	1072
45.2.3	Images	1073
45.2.4	Drawing	1073
45.2.5	PDF Features	1079
45.3	pdfmode driver	1081
45.3.1	Basics	1081
45.3.2	Box operations	1082
45.3.3	Images	1083
45.3.4	PDF Objects	1085
45.3.5	PDF Structure	1086
45.4	dvipdfmx driver	1087
45.4.1	Basics	1087

45.4.2	Box operations	1087
45.4.3	Images	1089
45.4.4	PDF Objects	1091
45.4.5	PDF Structure	1092
45.5	xdvipdfmx driver	1092
45.5.1	Images	1092
45.6	Drawing commands: pdfmode and (x)dvipdfmx	1093
45.6.1	Drawing	1094
45.7	dvisvgm driver	1100
45.7.1	Basics	1100
45.7.2	Driver-specific auxiliaries	1100
45.7.3	Box operations	1100
45.7.4	Images	1103
45.7.5	PDF Features	1103
45.7.6	Drawing	1103
46	l3deprecation implementation	1110
	Index	1114

Part I

Introduction to expl3 and this document

This document is intended to act as a comprehensive reference manual for the expl3 language. A general guide to the L^AT_EX3 programming language is found in [expl3.pdf](#).

1 Naming functions and variables

L^AT_EX3 does not use `@` as a “letter” for defining internal macros. Instead, the symbols `_` and `:` are used in internal macro names to provide structure. The name of each *function* is divided into logical units using `_`, while `:` separates the *name* of the function from the *argument specifier* (“arg-spec”). This describes the arguments expected by the function. In most cases, each argument is represented by a single letter. The complete list of arg-spec letters for a function is referred to as the *signature* of the function.

Each function name starts with the *module* to which it belongs. Thus apart from a small number of very basic functions, all expl3 function names contain at least one underscore to divide the module name from the descriptive name of the function. For example, all functions concerned with comma lists are in module `clist` and begin `\clist_`.

Every function must include an argument specifier. For functions which take no arguments, this will be blank and the function name will end `:`. Most functions take one or more arguments, and use the following argument specifiers:

- D** The **D** specifier means *do not use*. All of the T_EX primitives are initially `\let` to a **D** name, and some are then given a second name. Only the kernel team should use anything with a **D** specifier!
- N and n** These mean *no manipulation*, of a single token for **N** and of a set of tokens given in braces for **n**. Both pass the argument through exactly as given. Usually, if you use a single token for an **n** argument, all will be well.
- c** This means *csname*, and indicates that the argument will be turned into a *csname* before being used. So `\foo:c {ArgumentOne}` will act in the same way as `\foo:N \ArgumentOne`.
- V and v** These mean *value of variable*. The **V** and **v** specifiers are used to get the content of a variable without needing to worry about the underlying T_EX structure containing the data. A **V** argument will be a single token (similar to **N**), for example `\foo:V \MyVariable`; on the other hand, using **v** a *csname* is constructed first, and then the value is recovered, for example `\foo:v {MyVariable}`.
- o** This means *expansion once*. In general, the **V** and **v** specifiers are favoured over **o** for recovering stored information. However, **o** is useful for correctly processing information with delimited arguments.
- x** The **x** specifier stands for *exhaustive expansion*: every token in the argument is fully expanded until only unexpandable ones remain. The T_EX `\edef` primitive carries out this type of expansion. Functions which feature an **x**-type argument are in general *not* expandable, unless specifically noted.

- f** The **f** specifier stands for *full expansion*, and in contrast to **x** stops at the first non-expandable item (reading the argument from left to right) without trying to expand it. For example, when setting a token list variable (a macro used for storage), the sequence

```
\tl_set:Nn \l_my_a_tl { A }
\tl_set:Nn \l_my_b_tl { B }
\tl_set:Nf \l_my_a_tl { \l_my_a_tl \l_my_b_tl }
```

will leave `\l_my_a_tl` with the content `A\l_my_b_tl`, as `A` cannot be expanded and so terminates expansion before `\l_my_b_tl` is considered.

- T and F** For logic tests, there are the branch specifiers **T** (*true*) and **F** (*false*). Both specifiers treat the input in the same way as **n** (no change), but make the logic much easier to see.

- p** The letter **p** indicates *TeX parameters*. Normally this will be used for delimited functions as `expl3` provides better methods for creating simple sequential arguments.

- w** Finally, there is the **w** specifier for *weird* arguments. This covers everything else, but mainly applies to delimited values (where the argument must be terminated by some arbitrary string).

Notice that the argument specifier describes how the argument is processed prior to being passed to the underlying function. For example, `\foo:c` will take its argument, convert it to a control sequence and pass it to `\foo:N`.

Variables are named in a similar manner to functions, but begin with a single letter to define the type of variable:

- c** Constant: global parameters whose value should not be changed.

- g** Parameters whose value should only be set globally.

- l** Parameters whose value should only be set locally.

Each variable name is then build up in a similar way to that of a function, typically starting with the module¹ name and then a descriptive part. Variables end with a short identifier to show the variable type:

bool Either true or false.

box Box register.

clist Comma separated list.

coffin a “box with handles” — a higher-level data type for carrying out **box** alignment operations.

dim “Rigid” lengths.

fp floating-point values;

¹The module names are not used in case of generic scratch registers defined in the data type modules, e.g., the `int` module contains some scratch variables called `\l_tmpa_int`, `\l_tmpb_int`, and so on. In such a case adding the module name up front to denote the module and in the back to indicate the type, as in `\l_int_tmpa_int` would be very unreadable.

int Integer-valued count register.

prop Property list.

seq “Sequence”: a data-type used to implement lists (with access at both ends) and stacks.

skip “Rubber” lengths.

stream An input or output stream (for reading from or writing to, respectively).

tl Token list variables: placeholder for a token list.

1.1 Terminological inexactitude

A word of warning. In this document, and others referring to the `expl3` programming modules, we often refer to “variables” and “functions” as if they were actual constructs from a real programming language. In truth, `TeX` is a macro processor, and functions are simply macros that may or may not take arguments and expand to their replacement text. Many of the common variables are *also* macros, and if placed into the input stream will simply expand to their definition as well — a “function” with no arguments and a “token list variable” are in truth one and the same. On the other hand, some “variables” are actually registers that must be initialised and their values set and retrieved with specific functions.

The conventions of the `expl3` code are designed to clearly separate the ideas of “macros that contain data” and “macros that contain code”, and a consistent wrapper is applied to all forms of “data” whether they be macros or actually registers. This means that sometimes we will use phrases like “the function returns a value”, when actually we just mean “the macro expands to something”. Similarly, the term “execute” might be used in place of “expand” or it might refer to the more specific case of “processing in `TeX`’s stomach” (if you are familiar with the `TeXbook` parlance).

If in doubt, please ask; chances are we’ve been hasty in writing certain definitions and need to be told to tighten up our terminology.

2 Documentation conventions

This document is typeset with the experimental `l3doc` class; several conventions are used to help describe the features of the code. A number of conventions are used here to make the documentation clearer.

Each group of related functions is given in a box. For a function with a “user” name, this might read:

```
\ExplSyntaxOn
\ExplSyntaxOff
```

```
\ExplSyntaxOn ... \ExplSyntaxOff
```

The textual description of how the function works would appear here. The syntax of the function is shown in mono-spaced text to the right of the box. In this example, the function takes no arguments and so the name of the function is simply reprinted.

For programming functions, which use `_` and `:` in their name there are a few additional conventions: If two related functions are given with identical names but different argument specifiers, these are termed *variants* of each other, and the latter functions are printed in grey to show this more clearly. They will carry out the same function but will take different types of argument:

<code>\seq_new:N</code>	<code>\seq_new:N <sequence></code>
<code>\seq_new:c</code>	

When a number of variants are described, the arguments are usually illustrated only for the base function. Here, `<sequence>` indicates that `\seq_new:N` expects the name of a sequence. From the argument specifier, `\seq_new:c` also expects a sequence name, but as a name rather than as a control sequence. Each argument given in the illustration should be described in the following text.

Fully expandable functions Some functions are fully expandable, which allows them to be used within an **x**-type argument (in plain \TeX terms, inside an `\edef`), as well as within an **f**-type argument. These fully expandable functions are indicated in the documentation by a star:

<code>\cs_to_str:N</code> ★	<code>\cs_to_str:N <cs></code>
-----------------------------	--------------------------------------

As with other functions, some text should follow which explains how the function works. Usually, only the star will indicate that the function is expandable. In this case, the function expects a `<cs>`, shorthand for a `<control sequence>`.

Restricted expandable functions A few functions are fully expandable but cannot be fully expanded within an **f**-type argument. In this case a hollow star is used to indicate this:

<code>\seq_map_function:NN</code> ☆	<code>\seq_map_function:NN <seq> <function></code>
-------------------------------------	--

Conditional functions Conditional (**if**) functions are normally defined in three variants, with **T**, **F** and **TF** argument specifiers. This allows them to be used for different “true”/“false” branches, depending on which outcome the conditional is being used to test. To indicate this without repetition, this information is given in a shortened form:

<code>\sys_if_engine_xetex:TF</code> ★	<code>\sys_if_engine_xetex:TF {<true code>} {<false code>}</code>
--	---

The underlining and italic of **TF** indicates that three functions are available:

- `\sys_if_engine_xetex:T`
- `\sys_if_engine_xetex:F`
- `\sys_if_engine_xetex:TF`

Usually, the illustration will use the **TF** variant, and so both `<true code>` and `<false code>` will be shown. The two variant forms **T** and **F** take only `<true code>` and `<false code>`, respectively. Here, the star also shows that this function is expandable. With some minor exceptions, *all* conditional functions in the `expl3` modules should be defined in this way.

Variables, constants and so on are described in a similar manner:

<code>\l_tmpa_tl</code>	
-------------------------	--

A short piece of text will describe the variable: there is no syntax illustration in this case.

In some cases, the function is similar to one in $\text{\LaTeX 2}_{\epsilon}$ or plain \TeX . In these cases, the text will include an extra “ **\TeX hackers note**” section:

<code>\token_to_str:N</code> ★	<code>\token_to_str:N</code> $\langle token \rangle$
--------------------------------	--

The normal description text.

T_EXhackers note: Detail for the experienced T_EX or L^AT_EX 2_ε programmer. In this case, it would point out that this function is the T_EX primitive `\string`.

Changes to behaviour When new functions are added to `expl3`, the date of first inclusion is given in the documentation. Where the documented behaviour of a function changes after it is first introduced, the date of the update will also be given. This means that the programmer can be sure that any release of `expl3` after the date given will contain the function of interest with expected behaviour as described. Note that changes to code internals, including bug fixes, are not recorded in this way *unless* they impact on the expected behaviour.

3 Formal language conventions which apply generally

As this is a formal reference guide for L^AT_EX3 programming, the descriptions of functions are intended to be reasonably “complete”. However, there is also a need to avoid repetition. Formal ideas which apply to general classes of function are therefore summarised here.

For tests which have a **TF** argument specification, the test is evaluated to give a logically **TRUE** or **FALSE** result. Depending on this result, either the $\langle true\ code \rangle$ or the $\langle false\ code \rangle$ will be left in the input stream. In the case where the test is expandable, and a predicate (`_p`) variant is available, the logical value determined by the test is left in the input stream: this will typically be part of a larger logical construct.

4 T_EX concepts not supported by L^AT_EX3

The T_EX concept of an “`\outer`” macro is *not supported* at all by L^AT_EX3. As such, the functions provided here may break when used on top of L^AT_EX 2_ε if `\outer` tokens are used in the arguments.

Part II

The l3bootstrap package

Bootstrap code

1 Using the L^AT_EX3 modules

The modules documented in `source3` are designed to be used on top of L^AT_EX 2_ε and are loaded all as one with the usual `\usepackage{expl3}` or `\RequirePackage{expl3}` instructions. These modules will also form the basis of the L^AT_EX3 format, but work in this area is incomplete and not included in this documentation at present.

As the modules use a coding syntax different from standard L^AT_EX 2_ε it provides a few functions for setting it up.

`\ExplSyntaxOn`
`\ExplSyntaxOff`
 Updated: 2011-08-13

`\ExplSyntaxOn` *<code>* `\ExplSyntaxOff`

The `\ExplSyntaxOn` function switches to a category code régime in which spaces are ignored and in which the colon (:) and underscore (_) are treated as “letters”, thus allowing access to the names of code functions and variables. Within this environment, ~ is used to input a space. The `\ExplSyntaxOff` reverts to the document category code régime.

`\ProvidesExplPackage`
`\ProvidesExplClass`
`\ProvidesExplFile`
 Updated: 2017-03-19

`\RequirePackage{expl3}`
`\ProvidesExplPackage` *<package>* *<date>* *<version>* *<description>*

These functions act broadly in the same way as the corresponding L^AT_EX 2_ε kernel functions `\ProvidesPackage`, `\ProvidesClass` and `\ProvidesFile`. However, they also implicitly switch `\ExplSyntaxOn` for the remainder of the code with the file. At the end of the file, `\ExplSyntaxOff` will be called to reverse this. (This is the same concept as L^AT_EX 2_ε provides in turning on `\makeatletter` within package and class code.) The *<date>* should be given in the format *<year>/<month>/<day>*. If the *<version>* is given then it will be prefixed with v in the package identifier line.

`\GetIdInfo`
 Updated: 2012-06-04

`\RequirePackage{l3bootstrap}`
`\GetIdInfo` *\$Id: <SVN info field> \$* *<description>*

Extracts all information from a SVN field. Spaces are not ignored in these fields. The information pieces are stored in separate control sequences with `\ExplFileName` for the part of the file name leading up to the period, `\ExplFileDate` for date, `\ExplFileVersion` for version and `\ExplFileDescription` for the description.

To summarize: Every single package using this syntax should identify itself using one of the above methods. Special care is taken so that every package or class file loaded with `\RequirePackage` or similar are loaded with usual L^AT_EX 2_ε category codes and the L^AT_EX3 category code scheme is reloaded when needed afterwards. See implementation for details. If you use the `\GetIdInfo` command you can use the information when loading a package with

```
\ProvidesExplPackage{\ExplFileName}
  {\ExplFileDate}{\ExplFileVersion}{\ExplFileDescription}
```

Part III

The l3names package

Namespace for primitives

1 Setting up the L^AT_EX3 programming language

This module is at the core of the L^AT_EX3 programming language. It performs the following tasks:

- defines new names for all T_EX primitives;
- switches to the category code régime for programming;
- provides support settings for building the code as a T_EX format.

This module is entirely dedicated to primitives, which should not be used directly within L^AT_EX3 code (outside of “kernel-level” code). As such, the primitives are not documented here: *The T_EXbook*, *T_EX by Topic* and the manuals for pdfT_EX, X_YT_EX, LuaT_EX, pT_EX and upT_EX should be consulted for details of the primitives. These are named `\tex_⟨name⟩:D`, typically based on the primitive’s *⟨name⟩* in pdfT_EX and omitting a leading `pdf` when the primitive is not related to pdf output.

Part IV

The l3basics package

Basic definitions

As the name suggest this package holds some basic definitions which are needed by most or all other packages in this set.

Here we describe those functions that are used all over the place. With that we mean functions dealing with the construction and testing of control sequences. Furthermore the basic parts of conditional processing are covered; conditional processing dealing with specific data types is described in the modules specific for the respective data types.

1 No operation functions

`\prg_do_nothing:` ★**`\prg_do_nothing:`**

An expandable function which does nothing at all: leaves nothing in the input stream after a single expansion.

`\scan_stop:`**`\scan_stop:`**

A non-expandable function which does nothing. Does not vanish on expansion but produces no typeset output.

2 Grouping material

`\group_begin:`
`\group_end:`**`\group_begin:`**
`\group_end:`

These functions begin and end a group for definition purposes. Assignments are local to groups unless carried out in a global manner. (A small number of exceptions to this rule will be noted as necessary elsewhere in this document.) Each **`\group_begin:`** must be matched by a **`\group_end:`**, although this does not have to occur within the same function. Indeed, it is often necessary to start a group within one function and finish it within another, for example when seeking to use non-standard category codes.

`\group_insert_after:N`**`\group_insert_after:N`** *<token>*

Adds *<token>* to the list of *<tokens>* to be inserted when the current group level ends. The list of *<tokens>* to be inserted is empty at the beginning of a group: multiple applications of **`\group_insert_after:N`** may be used to build the inserted list one *<token>* at a time. The current group level may be closed by a **`\group_end:`** function or by a token with category code 2 (close-group), namely a `}` if standard category codes apply.

3 Control sequences and functions

As \TeX is a macro language, creating new functions means creating macros. At point of use, a function is replaced by the replacement text (“code”) in which each parameter in the code ($\#1$, $\#2$, *etc.*) is replaced the appropriate arguments absorbed by the function. In the following, *code* is therefore used as a shorthand for “replacement text”.

Functions which are not “protected” are fully expanded inside an \mathbf{x} expansion. In contrast, “protected” functions are not expanded within \mathbf{x} expansions.

3.1 Defining functions

Functions can be created with no requirement that they are declared first (in contrast to variables, which must always be declared). Declaring a function before setting up the code means that the name chosen is checked and an error raised if it is already in use. The name of a function can be checked at the point of definition using the `\cs_new...` functions: this is recommended for all functions which are defined for the first time.

There are three ways to define new functions. All classes define a function to expand to the substitution text. Within the substitution text the actual parameters are substituted for the formal parameters ($\#1$, $\#2$, ...).

new Create a new function with the **new** scope, such as `\cs_new:Npn`. The definition is global and results in an error if it is already defined.

set Create a new function with the **set** scope, such as `\cs_set:Npn`. The definition is restricted to the current \TeX group and does not result in an error if the function is already defined.

gset Create a new function with the **gset** scope, such as `\cs_gset:Npn`. The definition is global and does not result in an error if the function is already defined.

Within each set of scope there are different ways to define a function. The differences depend on restrictions on the actual parameters and the expandability of the resulting function.

nopar Create a new function with the **nopar** restriction, such as `\cs_set_nopar:Npn`. The parameter may not contain `\par` tokens.

protected Create a new function with the **protected** restriction, such as `\cs_set_protected:Npn`. The parameter may contain `\par` tokens but the function will not expand within an \mathbf{x} -type expansion.

Finally, the functions in Subsections 3.2 and 3.3 are primarily meant to define *base functions* only. Base functions can only have the following argument specifiers:

N and n No manipulation.

T and F Functionally equivalent to **n** (you are actually encouraged to use the family of `\prg_new_conditional:` functions described in Section 1).

p and w These are special cases.

The `\cs_new:` functions below (and friends) do not stop you from using other argument specifiers in your function names, but they do not handle expansion for you. You should define the base function and then use `\cs_generate_variant:Nn` to generate custom variants as described in Section 2.

3.2 Defining new functions using parameter text

<code>\cs_new:Npn</code>	<code>\cs_new:Npn <function> <parameters> {<code>}</code>
<code>\cs_new:cpn</code>	Creates <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the
<code>\cs_new:Npx</code>	<i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_new:cpx</code>	definition is global and an error results if the <i><function></i> is already defined.

<code>\cs_new_nopar:Npn</code>	<code>\cs_new_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_nopar:cpn</code>	Creates <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the
<code>\cs_new_nopar:Npx</code>	<i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. When the
<code>\cs_new_nopar:cpx</code>	<i><function></i> is used the <i><parameters></i> absorbed cannot contain <code>\par</code> tokens. The definition
	is global and an error results if the <i><function></i> is already defined.

<code>\cs_new_protected:Npn</code>	<code>\cs_new_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected:cpn</code>	Creates <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the
<code>\cs_new_protected:Npx</code>	<i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_new_protected:cpx</code>	<i><function></i> will not expand within an x-type argument. The definition is global and an
	error results if the <i><function></i> is already defined.

<code>\cs_new_protected_nopar:Npn</code>	<code>\cs_new_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_new_protected_nopar:cpn</code>	
<code>\cs_new_protected_nopar:Npx</code>	
<code>\cs_new_protected_nopar:cpx</code>	

Creates *<function>* to expand to *<code>* as replacement text. Within the *<code>*, the *<parameters>* (#1, #2, etc.) will be replaced by those absorbed by the function. When the *<function>* is used the *<parameters>* absorbed cannot contain `\par` tokens. The *<function>* will not expand within an x-type argument. The definition is global and an error results if the *<function>* is already defined.

<code>\cs_set:Npn</code>	<code>\cs_set:Npn <function> <parameters> {<code>}</code>
<code>\cs_set:cpn</code>	Sets <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the
<code>\cs_set:Npx</code>	<i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_set:cpx</code>	assignment of a meaning to the <i><function></i> is restricted to the current \TeX group level.

<code>\cs_set_nopar:Npn</code>	<code>\cs_set_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_nopar:cpn</code>	Sets <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the
<code>\cs_set_nopar:Npx</code>	<i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. When the
<code>\cs_set_nopar:cpx</code>	<i><function></i> is used the <i><parameters></i> absorbed cannot contain <code>\par</code> tokens. The assignment
	of a meaning to the <i><function></i> is restricted to the current \TeX group level.

<code>\cs_set_protected:Npn</code>	<code>\cs_set_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected:cpn</code>	Sets <i><function></i> to expand to <i><code></i> as replacement text. Within the <i><code></i> , the
<code>\cs_set_protected:Npx</code>	<i><parameters></i> (#1, #2, etc.) will be replaced by those absorbed by the function. The
<code>\cs_set_protected:cpx</code>	assignment of a meaning to the <i><function></i> is restricted to the current \TeX group level.
	The <i><function></i> will not expand within an x-type argument.

<code>\cs_set_protected_nopar:Npn</code>	<code>\cs_set_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_set_protected_nopar:cpn</code>	
<code>\cs_set_protected_nopar:Npx</code>	
<code>\cs_set_protected_nopar:cpx</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level. The $\langle function \rangle$ will not expand within an x -type argument.

<code>\cs_gset:Npn</code>	<code>\cs_gset:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset:cpn</code>	
<code>\cs_gset:Npx</code>	
<code>\cs_gset:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

<code>\cs_gset_nopar:Npn</code>	<code>\cs_gset_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_nopar:cpn</code>	
<code>\cs_gset_nopar:Npx</code>	
<code>\cs_gset_nopar:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

<code>\cs_gset_protected:Npn</code>	<code>\cs_gset_protected:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_protected:cpn</code>	
<code>\cs_gset_protected:Npx</code>	
<code>\cs_gset_protected:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global. The $\langle function \rangle$ will not expand within an x -type argument.

<code>\cs_gset_protected_nopar:Npn</code>	<code>\cs_gset_protected_nopar:Npn <function> <parameters> {<code>}</code>
<code>\cs_gset_protected_nopar:cpn</code>	
<code>\cs_gset_protected_nopar:Npx</code>	
<code>\cs_gset_protected_nopar:cpx</code>	

Globally sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is *not* restricted to the current \TeX group level: the assignment is global. The $\langle function \rangle$ will not expand within an x -type argument.

3.3 Defining new functions using the signature

<code>\cs_new:Nn</code>	<code>\cs_new:Nn <function> {<code>}</code>
<code>\cs_new:(cn Nx cx)</code>	

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, etc.) will be replaced by those absorbed by the function. The definition is global and an error results if the $\langle function \rangle$ is already defined.

`\cs_new_nopar:Nn`
`\cs_new_nopar:(cn|Nx|cx)`

`\cs_new_nopar:Nn <function> {<code>}`

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The definition is global and an error results if the $\langle function \rangle$ is already defined.

`\cs_new_protected:Nn`
`\cs_new_protected:(cn|Nx|cx)`

`\cs_new_protected:Nn <function> {<code>}`

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error results if the $\langle function \rangle$ is already defined.

`\cs_new_protected_nopar:Nn`
`\cs_new_protected_nopar:(cn|Nx|cx)`

`\cs_new_protected_nopar:Nn <function> {<code>}`

Creates $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an x-type argument. The definition is global and an error results if the $\langle function \rangle$ is already defined.

`\cs_set:Nn`
`\cs_set:(cn|Nx|cx)`

`\cs_set:Nn <function> {<code>}`

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.

`\cs_set_nopar:Nn`
`\cs_set_nopar:(cn|Nx|cx)`

`\cs_set_nopar:Nn <function> {<code>}`

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.

`\cs_set_protected:Nn`
`\cs_set_protected:(cn|Nx|cx)`

`\cs_set_protected:Nn <function> {<code>}`

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an x-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current \TeX group level.

<code>\cs_set_protected_nopar:Nn</code>	<code>\cs_set_protected_nopar:Nn <function> {<code>}</code>
<code>\cs_set_protected_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an *x*-type argument. The assignment of a meaning to the $\langle function \rangle$ is restricted to the current TeX group level.

<code>\cs_gset:Nn</code>	<code>\cs_gset:Nn <function> {<code>}</code>
<code>\cs_gset:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_nopar:Nn</code>	<code>\cs_gset_nopar:Nn <function> {<code>}</code>
<code>\cs_gset_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_protected:Nn</code>	<code>\cs_gset_protected:Nn <function> {<code>}</code>
<code>\cs_gset_protected:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. The $\langle function \rangle$ will not expand within an *x*-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_gset_protected_nopar:Nn</code>	<code>\cs_gset_protected_nopar:Nn <function> {<code>}</code>
<code>\cs_gset_protected_nopar:(cn Nx cx)</code>	

Sets $\langle function \rangle$ to expand to $\langle code \rangle$ as replacement text. Within the $\langle code \rangle$, the number of $\langle parameters \rangle$ is detected automatically from the function signature. These $\langle parameters \rangle$ ($\#1$, $\#2$, *etc.*) will be replaced by those absorbed by the function. When the $\langle function \rangle$ is used the $\langle parameters \rangle$ absorbed cannot contain `\par` tokens. The $\langle function \rangle$ will not expand within an *x*-type argument. The assignment of a meaning to the $\langle function \rangle$ is global.

<code>\cs_generate_from_arg_count:NNnn</code>	<code>\cs_generate_from_arg_count:NNnn <function> <creator> {<number>}</code>
<code>\cs_generate_from_arg_count:(cNnn Ncnn)</code>	<code>{<code>}</code>

Updated: 2012-01-14

Uses the $\langle creator \rangle$ function (which should have signature Npn , for example `\cs_new:Npn`) to define a $\langle function \rangle$ which takes $\langle number \rangle$ arguments and has $\langle code \rangle$ as replacement text. The $\langle number \rangle$ of arguments is an integer expression, evaluated as detailed for `\int_eval:n`.

3.4 Copying control sequences

Control sequences (not just functions as defined above) can be set to have the same meaning using the functions described here. Making two control sequences equivalent means that the second control sequence is a *copy* of the first (rather than a pointer to it). Thus the old and new control sequence are not tied together: changes to one are not reflected in the other.

In the following text “cs” is used as an abbreviation for “control sequence”.

```
\cs_new_eq:NN
\cs_new_eq:(Nc|cN|cc)
```

```
\cs_new_eq:NN <cs1> <cs2>
\cs_new_eq:NN <cs1> <token>
```

Globally creates $\langle control\ sequence_1 \rangle$ and sets it to have the same meaning as $\langle control\ sequence_2 \rangle$ or $\langle token \rangle$. The second control sequence may subsequently be altered without affecting the copy.

```
\cs_set_eq:NN
\cs_set_eq:(Nc|cN|cc)
```

```
\cs_set_eq:NN <cs1> <cs2>
\cs_set_eq:NN <cs1> <token>
```

Sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is restricted to the current \TeX group level.

```
\cs_gset_eq:NN
\cs_gset_eq:(Nc|cN|cc)
```

```
\cs_gset_eq:NN <cs1> <cs2>
\cs_gset_eq:NN <cs1> <token>
```

Globally sets $\langle control\ sequence_1 \rangle$ to have the same meaning as $\langle control\ sequence_2 \rangle$ (or $\langle token \rangle$). The second control sequence may subsequently be altered without affecting the copy. The assignment of a meaning to the $\langle control\ sequence_1 \rangle$ is *not* restricted to the current \TeX group level: the assignment is global.

3.5 Deleting control sequences

There are occasions where control sequences need to be deleted. This is handled in a very simple manner.

```
\cs_undefine:N
\cs_undefine:c
```

Updated: 2011-09-15

```
\cs_undefine:N <control\ sequence>
```

Sets $\langle control\ sequence \rangle$ to be globally undefined.

3.6 Showing control sequences

```
\cs_meaning:N ★
\cs_meaning:c ★
```

Updated: 2011-12-22

```
\cs_meaning:N <control\ sequence>
```

This function expands to the *meaning* of the $\langle control\ sequence \rangle$ control sequence. For a macro, this includes the $\langle replacement\ text \rangle$.

\TeX hackers note: This is \TeX ’s $\backslash meaning$ primitive. For tokens that are not control sequences, it is more logical to use $\backslash token_to_meaning:N$. The c variant correctly reports undefined arguments.

`\cs_show:N`
`\cs_show:c`

Updated: 2017-02-14

`\cs_show:N` $\langle control\ sequence \rangle$
Displays the definition of the $\langle control\ sequence \rangle$ on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

`\cs_log:N`
`\cs_log:c`

New: 2014-08-22
Updated: 2017-02-14

`\cs_log:N` $\langle control\ sequence \rangle$
Writes the definition of the $\langle control\ sequence \rangle$ in the log file. See also `\cs_show:N` which displays the result in the terminal.

3.7 Converting to and from control sequences

`\use:c` ★

`\use:c` $\{\langle control\ sequence\ name \rangle\}$

Expands the $\langle control\ sequence\ name \rangle$ until only characters remain, and then converts this into a control sequence. This process requires two expansions. As in other `c`-type arguments the $\langle control\ sequence\ name \rangle$ must, when fully expanded, consist of character tokens, typically a mixture of category code 10 (space), 11 (letter) and 12 (other).

T_EXhackers note: Protected macros that appear in a `c`-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

As an example of the `\use:c` function, both

`\use:c { a b c }`

and

`\tl_new:N \l_my_tl`
`\tl_set:Nn \l_my_tl { a b c }`
`\use:c { \tl_use:N \l_my_tl }`

would be equivalent to

`\abc`

after two expansions of `\use:c`.

`\cs_if_exist_use:N` ★
`\cs_if_exist_use:c` ★
`\cs_if_exist_use:NTF` ★
`\cs_if_exist_use:cTF` ★

New: 2012-11-10

`\cs_if_exist_use:N` $\langle control\ sequence \rangle$
`\cs_if_exist_use:NTF` $\langle control\ sequence \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests whether the $\langle control\ sequence \rangle$ is currently defined according to the conditional `\cs_if_exist:NTF` (whether as a function or another control sequence type), and if it is inserts the $\langle control\ sequence \rangle$ into the input stream followed by the $\langle true\ code \rangle$. Otherwise the $\langle false\ code \rangle$ is used.

<code>\cs:w</code>	★	<code>\cs:w</code> <i><control sequence name></i> <code>\cs_end:</code>
<code>\cs_end:</code>	★	

Converts the given *<control sequence name>* into a single control sequence token. This process requires one expansion. The content for *<control sequence name>* may be literal material or from other expandable functions. The *<control sequence name>* must, when fully expanded, consist of character tokens which are not active: typically of category code 10 (space), 11 (letter) or 12 (other), or a mixture of these.

TeXhackers note: These are the TeX primitives `\csname` and `\endcsname`.

As an example of the `\cs:w` and `\cs_end:` functions, both

`\cs:w a b c \cs_end:`

and

```
\tl_new:N \l_my_tl
\tl_set:Nn \l_my_tl { a b c }
\cs:w \tl_use:N \l_my_tl \cs_end:
```

would be equivalent to

`\abc`

after one expansion of `\cs:w`.

<code>\cs_to_str:N</code>	★	<code>\cs_to_str:N</code> <i><control sequence></i>
---------------------------	---	---

Converts the given *<control sequence>* into a series of characters with category code 12 (other), except spaces, of category code 10. The result does *not* include the current escape token, contrarily to `\token_to_str:N`. Full expansion of this function requires exactly 2 expansion steps, and so an *x*-type expansion, or two *o*-type expansions are required to convert the *<control sequence>* to a sequence of characters in the input stream. In most cases, an *f*-expansion is correct as well, but this loses a space at the start of the result.

4 Analysing control sequence names

<code>\cs_split_function:N</code>	★	<code>\cs_split_function:N</code> <i><function></i>
-----------------------------------	---	---

New: 2018-04-06

Splits the *<function>* into the *<name>* (*i.e.* the part before the colon) and the *<signature>* (*i.e.* after the colon). This information is then placed in the input stream in three parts: the *<name>*, the *<signature>* and a logic token indicating if a colon was found (to differentiate variables from function names). The *<name>* does not include the escape character, and both the *<name>* and *<signature>* are made up of tokens with category code 12 (other).

5 Using or removing tokens and arguments

Tokens in the input can be read and used or read and discarded. If one or more tokens are wrapped in braces then when absorbing them the outer set is removed. At the same time, the category code of each token is set when the token is read by a function (if it is read more than once, the category code is determined by the situation in force when first function absorbs the token).

<code>\use:n</code>	★	<code>\use:n</code>	$\{\langle group_1 \rangle\}$
<code>\use:nn</code>	★	<code>\use:nn</code>	$\{\langle group_1 \rangle\} \{\langle group_2 \rangle\}$
<code>\use:nnn</code>	★	<code>\use:nnn</code>	$\{\langle group_1 \rangle\} \{\langle group_2 \rangle\} \{\langle group_3 \rangle\}$
<code>\use:nnnn</code>	★	<code>\use:nnnn</code>	$\{\langle group_1 \rangle\} \{\langle group_2 \rangle\} \{\langle group_3 \rangle\} \{\langle group_4 \rangle\}$

As illustrated, these functions absorb between one and four arguments, as indicated by the argument specifier. The braces surrounding each argument are removed and the remaining tokens are left in the input stream. The category code of these tokens is also fixed by this process (if it has not already been by some other absorption). All of these functions require only a single expansion to operate, so that one expansion of

`\use:nn { abc } { { def } }`

results in the input stream containing

`abc { def }`

i.e. only the outer braces are removed.

<code>\use_i:nn</code>	★	<code>\use_i:nn</code>	$\{\langle arg_1 \rangle\} \{\langle arg_2 \rangle\}$
<code>\use_ii:nn</code>	★		

These functions absorb two arguments from the input stream. The function `\use_i:nn` discards the second argument, and leaves the content of the first argument in the input stream. `\use_ii:nn` discards the first argument and leaves the content of the second argument in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

<code>\use_i:nnn</code>	★	<code>\use_i:nnn</code>	$\{\langle arg_1 \rangle\} \{\langle arg_2 \rangle\} \{\langle arg_3 \rangle\}$
<code>\use_ii:nnn</code>	★		
<code>\use_iii:nnn</code>	★		

These functions absorb three arguments from the input stream. The function `\use_i:nnn` discards the second and third arguments, and leaves the content of the first argument in the input stream. `\use_ii:nnn` and `\use_iii:nnn` work similarly, leaving the content of second or third arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

<code>\use_i:nnnn</code>	★	<code>\use_i:nnnn</code>	$\{\langle arg_1 \rangle\} \{\langle arg_2 \rangle\} \{\langle arg_3 \rangle\} \{\langle arg_4 \rangle\}$
<code>\use_ii:nnnn</code>	★		
<code>\use_iii:nnnn</code>	★		
<code>\use_iv:nnnn</code>	★		

These functions absorb four arguments from the input stream. The function `\use_i:nnnn` discards the second, third and fourth arguments, and leaves the content of the first argument in the input stream. `\use_ii:nnnn`, `\use_iii:nnnn` and `\use_iv:nnnn` work similarly, leaving the content of second, third or fourth arguments in the input stream, respectively. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the functions to take effect.

<code>\use_i_ii:nnn</code>	★	<code>\use_i_ii:nnn {\langle arg_1 \rangle} {\langle arg_2 \rangle} {\langle arg_3 \rangle}</code>
----------------------------	---	--

This function absorbs three arguments and leaves the content of the first and second in the input stream. The category code of these tokens is also fixed (if it has not already been by some other absorption). A single expansion is needed for the function to take effect. An example:

`\use_i_ii:nnn { abc } { { def } } { ghi }`

results in the input stream containing

`abc { def }`

i.e. the outer braces are removed and the third group is removed.

<code>\use_none:n</code>	★	<code>\use_none:n {\langle group_1 \rangle}</code>
<code>\use_none:nn</code>	★	
<code>\use_none:nnn</code>	★	
<code>\use_none:nnnn</code>	★	
<code>\use_none:nnnnn</code>	★	
<code>\use_none:nnnnnn</code>	★	
<code>\use_none:nnnnnnn</code>	★	
<code>\use_none:nnnnnnnn</code>	★	
<code>\use_none:nnnnnnnnn</code>	★	

These functions absorb between one and nine groups from the input stream, leaving nothing on the resulting input stream. These functions work after a single expansion. One or more of the `n` arguments may be an unbraced single token (*i.e.* an `N` argument).

<code>\use:e</code>	★	<code>\use:e {\langle expandable tokens \rangle}</code>
---------------------	---	---

New: 2018-06-18

Fully expands the `\langle token list \rangle` in an `x`-type manner, *but* the function remains fully expandable, and parameter character (usually `#`) need not be doubled.

T_EXhackers note: `\use:e` the a wrapper around the primitive `\expanded` where it is available: it requires two expansions to complete its action.

<code>\use:x</code>		<code>\use:x {\langle expandable tokens \rangle}</code>
---------------------	--	---

Updated: 2011-12-31

Fully expands the `\langle expandable tokens \rangle` and inserts the result into the input stream at the current location. Any hash characters (`#`) in the argument must be doubled.

5.1 Selecting tokens from delimited arguments

A different kind of function for selecting tokens from the token stream are those that use delimited arguments.

<code>\use_none_delimit_by_q_nil:w</code>	★	<code>\use_none_delimit_by_q_nil:w \langle balanced text \rangle \q_nil</code>
<code>\use_none_delimit_by_q_stop:w</code>	★	<code>\use_none_delimit_by_q_stop:w \langle balanced text \rangle \q_stop</code>
<code>\use_none_delimit_by_q_recursion_stop:w</code>	★	<code>\use_none_delimit_by_q_recursion_stop:w \langle balanced text \rangle \q_recursion_stop</code>

Absorb the `\langle balanced text \rangle` from the input stream delimited by the marker given in the function name, leaving nothing in the input stream.

<code>\use_i_delimit_by_q_nil:nw</code>	★	<code>\use_i_delimit_by_q_nil:nw {\langle inserted tokens \rangle} \langle balanced text \rangle</code>
<code>\use_i_delimit_by_q_stop:nw</code>	★	<code>\q_nil</code>
<code>\use_i_delimit_by_q_recursion_stop:nw</code>	★	<code>\use_i_delimit_by_q_stop:nw {\langle inserted tokens \rangle} \langle balanced text \rangle \q_stop</code>
		<code>\use_i_delimit_by_q_recursion_stop:nw {\langle inserted tokens \rangle} \langle balanced text \rangle \q_recursion_stop</code>

Absorb the $\langle balanced\ text \rangle$ form the input stream delimited by the marker given in the function name, leaving $\langle inserted\ tokens \rangle$ in the input stream for further processing.

6 Predicates and conditionals

LaTeX3 has three concepts for conditional flow processing:

Branching conditionals Functions that carry out a test and then execute, depending on its result, either the code supplied as the $\langle true\ code \rangle$ or the $\langle false\ code \rangle$. These arguments are denoted with T and F, respectively. An example would be

`\cs_if_free:cTF {abc} {\langle true code \rangle} {\langle false code \rangle}`

a function that turns the first argument into a control sequence (since it’s marked as c) then checks whether this control sequence is still free and then depending on the result carries out the code in the second argument (true case) or in the third argument (false case).

These type of functions are known as “conditionals”; whenever a TF function is defined it is usually accompanied by T and F functions as well. These are provided for convenience when the branch only needs to go a single way. Package writers are free to choose which types to define but the kernel definitions always provide all three versions.

Important to note is that these branching conditionals with $\langle true\ code \rangle$ and/or $\langle false\ code \rangle$ are always defined in a way that the code of the chosen alternative can operate on following tokens in the input stream.

These conditional functions may or may not be fully expandable, but if they are expandable they are accompanied by a “predicate” for the same test as described below.

Predicates “Predicates” are functions that return a special type of boolean value which can be tested by the boolean expression parser. All functions of this type are expandable and have names that end with `_p` in the description part. For example,

`\cs_if_free_p:N`

would be a predicate function for the same type of test as the conditional described above. It would return “true” if its argument (a single token denoted by N) is still free for definition. It would be used in constructions like

`\bool_if:nTF {
\cs_if_free_p:N \l_tmpz_tl || \cs_if_free_p:N \g_tmpz_tl
} {\langle true code \rangle} {\langle false code \rangle}`

For each predicate defined, a “branching conditional” also exists that behaves like a conditional described above.

Primitive conditionals There is a third variety of conditional, which is the original concept used in plain $\text{T}_{\text{E}}\text{X}$ and $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X} 2_{\epsilon}$. Their use is discouraged in `expl3` (although still used in low-level definitions) because they are more fragile and in many cases require more expansion control (hence more code) than the two types of conditionals described above.

<code>\c_true_bool</code>	Constants that represent <code>true</code> and <code>false</code> , respectively. Used to implement predicates.
<code>\c_false_bool</code>	

6.1 Tests on control sequences

<code>\cs_if_eq_p:NN</code>	★	<code>\cs_if_eq_p:NN</code>	$\langle cs_1 \rangle$	$\langle cs_2 \rangle$		
<code>\cs_if_eq:NNTF</code>	★	<code>\cs_if_eq:NNTF</code>	$\langle cs_1 \rangle$	$\langle cs_2 \rangle$	$\{\langle true\ code \rangle\}$	$\{\langle false\ code \rangle\}$

Compares the definition of two $\langle control\ sequence \rangle$ and is logically `true` if they are the same, *i.e.* if they have exactly the same definition when examined with `\cs_show:N`.

<code>\cs_if_exist_p:N</code>	★	<code>\cs_if_exist_p:N</code>	$\langle control\ sequence \rangle$		
<code>\cs_if_exist_p:c</code>	★	<code>\cs_if_exist:NNTF</code>	$\langle control\ sequence \rangle$	$\{\langle true\ code \rangle\}$	$\{\langle false\ code \rangle\}$
<code>\cs_if_exist:NNTF</code>	★	Tests whether the $\langle control\ sequence \rangle$ is currently defined (whether as a function or another control sequence type). Any definition of $\langle control\ sequence \rangle$ other than <code>\relax</code> evaluates as <code>true</code> .			
<code>\cs_if_exist:cTF</code>	★				

<code>\cs_if_free_p:N</code>	★	<code>\cs_if_free_p:N</code>	$\langle control\ sequence \rangle$		
<code>\cs_if_free_p:c</code>	★	<code>\cs_if_free:NNTF</code>	$\langle control\ sequence \rangle$	$\{\langle true\ code \rangle\}$	$\{\langle false\ code \rangle\}$
<code>\cs_if_free:NNTF</code>	★	Tests whether the $\langle control\ sequence \rangle$ is currently free to be defined. This test is <code>false</code> if the $\langle control\ sequence \rangle$ currently exists (as defined by <code>\cs_if_exist:N</code>).			
<code>\cs_if_free:cTF</code>	★				

6.2 Primitive conditionals

The $\epsilon\text{-T}_{\text{E}}\text{X}$ engine itself provides many different conditionals. Some expand whatever comes after them and others don't. Hence the names for these underlying functions often contains a `:w` part but higher level functions are often available. See for instance `\int_compare_p:nNn` which is a wrapper for `\if_int_compare:w`.

Certain conditionals deal with specific data types like boxes and fonts and are described there. The ones described below are either the universal conditionals or deal with control sequences. We prefix primitive conditionals with `\if_`.

<code>\if_true:</code>	★	<code>\if_true:</code>	$\langle true\ code \rangle$	<code>\else:</code>	$\langle false\ code \rangle$	<code>\fi:</code>
<code>\if_false:</code>	★	<code>\if_false:</code>	$\langle true\ code \rangle$	<code>\else:</code>	$\langle false\ code \rangle$	<code>\fi:</code>
<code>\else:</code>	★	<code>\reverse_if:N</code>	$\langle primitive\ conditional \rangle$			
<code>\fi:</code>	★	<code>\if_true:</code> always executes $\langle true\ code \rangle$, while <code>\if_false:</code> always executes $\langle false\ code \rangle$.				
<code>\reverse_if:N</code>	★	<code>\reverse_if:N</code> reverses any two-way primitive conditional. <code>\else:</code> and <code>\fi:</code> delimit the branches of the conditional. The function <code>\or:</code> is documented in <code>l3int</code> and used in case switches.				

$\text{T}_{\text{E}}\text{X}$ hackers note: These are equivalent to their corresponding $\text{T}_{\text{E}}\text{X}$ primitive conditionals; `\reverse_if:N` is $\epsilon\text{-T}_{\text{E}}\text{X}$'s `\unless`.

<code>\if_meaning:w</code>	★	<code>\if_meaning:w <arg₁> <arg₂> <true code> \else: <false code> \fi:</code>
----------------------------	---	---

`\if_meaning:w` executes *<true code>* when *<arg₁>* and *<arg₂>* are the same, otherwise it executes *<false code>*. *<arg₁>* and *<arg₂>* could be functions, variables, tokens; in all cases the *unexpanded* definitions are compared.

T_EXhackers note: This is T_EX's `\ifx`.

<code>\if:w</code>	★	<code>\if:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_charcode:w</code>	★	<code>\if_catcode:w <token₁> <token₂> <true code> \else: <false code> \fi:</code>
<code>\if_catcode:w</code>	★	

These conditionals expand any following tokens until two unexpandable tokens are left. If you wish to prevent this expansion, prefix the token in question with `\exp_not:N`. `\if_catcode:w` tests if the category codes of the two tokens are the same whereas `\if:w` tests if the character codes are identical. `\if_charcode:w` is an alternative name for `\if:w`.

<code>\if_cs_exist:N</code>	★	<code>\if_cs_exist:N <cs> <true code> \else: <false code> \fi:</code>
<code>\if_cs_exist:w</code>	★	<code>\if_cs_exist:w <tokens> \cs_end: <true code> \else: <false code> \fi:</code>

Check if *<cs>* appears in the hash table or if the control sequence that can be formed from *<tokens>* appears in the hash table. The latter function does not turn the control sequence in question into `\scan_stop:!` This can be useful when dealing with control sequences which cannot be entered as a single token.

<code>\if_mode_horizontal:</code>	★	<code>\if_mode_horizontal: <true code> \else: <false code> \fi:</code>
<code>\if_mode_vertical:</code>	★	
<code>\if_mode_math:</code>	★	
<code>\if_mode_inner:</code>	★	

Execute *<true code>* if currently in horizontal mode, otherwise execute *<false code>*. Similar for the other functions.

Part V

The l3expan package

Argument expansion

This module provides generic methods for expanding T_EX arguments in a systematic manner. The functions in this module all have prefix `exp`.

Not all possible variations are implemented for every base function. Instead only those that are used within the L^AT_EX3 kernel or otherwise seem to be of general interest are implemented. Consult the module description to find out which functions are actually defined. The next section explains how to define missing variants.

1 Defining new variants

The definition of variant forms for base functions may be necessary when writing new functions or when applying a kernel function in a situation that we haven't thought of before.

Internally preprocessing of arguments is done with functions of the form `\exp_....`. They all look alike, an example would be `\exp_args:NNo`. This function has three arguments, the first and the second are a single tokens, while the third argument should be given in braces. Applying `\exp_args:NNo` expands the content of third argument once before any expansion of the first and second arguments. If `\seq_gpush:No` was not defined it could be coded in the following way:

```
\exp_args:NNo \seq_gpush:Nn
  \g_file_name_stack
  { \l_tmpa_tl }
```

In other words, the first argument to `\exp_args:NNo` is the base function and the other arguments are preprocessed and then passed to this base function. In the example the first argument to the base function should be a single token which is left unchanged while the second argument is expanded once. From this example we can also see how the variants are defined. They just expand into the appropriate `\exp_` function followed by the desired base function, *e.g.*

```
\cs_generate_variant:Nn \seq_gpush:Nn { No }
```

results in the definition of `\seq_gpush:No`

```
\cs_new:Npn \seq_gpush:No { \exp_args:NNo \seq_gpush:Nn }
```

Providing variants in this way in style files is safe as the `\cs_generate_variant:Nn` function will only create new definitions if there is not already one available. Therefore adding such definition to later releases of the kernel will not make such style files obsolete.

The steps above may be automated by using the function `\cs_generate_variant:Nn`, described next.

2 Methods for defining variants

We recall the set of available argument specifiers.

- `N` is used for single-token arguments while `c` constructs a control sequence from its name and passes it to a parent function as an `N`-type argument.
- Many argument types extract or expand some tokens and provide it as an `n`-type argument, namely a braced multiple-token argument: `V` extracts the value of a variable, `v` extracts the value from the name of a variable, `n` uses the argument as it is, `o` expands once, `f` expands fully the front of the token list, `e` and `x` expand fully all tokens (differences are explained later).
- A few odd argument types remain: `T` and `F` for conditional processing, otherwise identical to `n`-type arguments, `p` for the parameter text in definitions, `w` for arguments with a specific syntax, and `D` to denote primitives that should not be used directly.

`\cs_generate_variant:Nn`
`\cs_generate_variant:cn`

Updated: 2017-11-28

`\cs_generate_variant:Nn` \langle parent control sequence \rangle $\{$ \langle variant argument specifiers \rangle $\}$

This function is used to define argument-specifier variants of the \langle parent control sequence \rangle for L^AT_EX3 code-level macros. The \langle parent control sequence \rangle is first separated into the \langle base name \rangle and \langle original argument specifier \rangle . The comma-separated list of \langle variant argument specifiers \rangle is then used to define variants of the \langle original argument specifier \rangle if these are not already defined. For each \langle variant \rangle given, a function is created that expands its arguments as detailed and passes them to the \langle parent control sequence \rangle . So for example

```
\cs_set:Npn \foo:Nn #1#2 { code here }
\cs_generate_variant:Nn \foo:Nn { c }
```

creates a new function `\foo:cn` which expands its first argument into a control sequence name and passes the result to `\foo:Nn`. Similarly

```
\cs_generate_variant:Nn \foo:Nn { NV , cV }
```

generates the functions `\foo:NV` and `\foo:cV` in the same way. The `\cs_generate_variant:Nn` function can only be applied if the \langle parent control sequence \rangle is already defined. If the \langle parent control sequence \rangle is protected or if the \langle variant \rangle involves any `x` argument, then the \langle variant control sequence \rangle is also protected. The \langle variant \rangle is created globally, as is any `\exp_args:N` \langle variant \rangle function needed to carry out the expansion.

Only `n` and `N` arguments can be changed to other types. The only allowed changes are

- `c` variant of an `N` parent;
- `o`, `V`, `v`, `f`, `e`, or `x` variant of an `n` parent;
- `N`, `n`, `T`, `F`, or `p` argument unchanged.

This means the \langle parent \rangle of a \langle variant \rangle form is always unambiguous, even in cases where both an `n`-type parent and an `N`-type parent exist, such as for `\tl_count:n` and `\tl_count:N`.

For backward compatibility it is currently possible to make `n`, `o`, `V`, `v`, `f`, `e`, or `x`-type variants of an `N`-type argument or `N` or `c`-type variants of an `n`-type argument. Both are deprecated. The first because passing more than one token to an `N`-type argument will typically break the parent function's code. The second because programmers who use that most often want to access the value of a variable given its name, hence should use a `V`-type or `v`-type variant instead of `c`-type. In those cases, using the lower-level `\exp_args:No` or `\exp_args:Nc` functions explicitly is preferred to defining confusing variants.

3 Introducing the variants

The `V` type returns the value of a register, which can be one of `tl`, `clist`, `int`, `skip`, `dim`, `muskip`, or built-in T_EX registers. The `v` type is the same except it first creates a control sequence out of its argument before returning the value.

In general, the programmer should not need to be concerned with expansion control. When simply using the content of a variable, functions with a `V` specifier should be used. For those referred to by (cs)name, the `v` specifier is available for the same purpose. Only

when specific expansion steps are needed, such as when using delimited arguments, should the lower-level functions with `o` specifiers be employed.

The `e` type expands all tokens fully, starting from the first. More precisely the expansion is identical to that of T_EX’s `\message` (in particular `#` needs not be doubled). It was added in May 2018. In recent enough engines (starting around 2019) it relies on the primitive `\expanded` hence is fast. In older engines it is very much slower. As a result it should only be used in performance critical code if typical users will have a recent installation of the T_EX ecosystem.

The `x` type expands all tokens fully, starting from the first. In contrast to `e`, all macro parameter characters `#` must be doubled, and omitting this leads to low-level errors. In addition this type of expansion is not expandable, namely functions that have `x` in their signature do not themselves expand when appearing inside `x` or `e` expansion.

The `f` type is so special that it deserves an example. It is typically used in contexts where only expandable commands are allowed. Then `x`-expansion cannot be used, and `f`-expansion provides an alternative that expands the front of the token list as much as can be done in such contexts. For instance, say that we want to evaluate the integer expression $3 + 4$ and pass the result 7 as an argument to an expandable function `\example:n`. For this, one should define a variant using `\cs_generate_variant:Nn \example:n { f }`, then do

```
\example:f { \int_eval:n { 3 + 4 } }
```

Note that `x`-expansion would also expand `\int_eval:n` fully to its result 7, but the variant `\example:x` cannot be expandable. Note also that `o`-expansion would not expand `\int_eval:n` fully to its result since that function requires several expansions. Besides the fact that `x`-expansion is protected rather than expandable, another difference between `f`-expansion and `x`-expansion is that `f`-expansion expands tokens from the beginning and stops as soon as a non-expandable token is encountered, while `x`-expansion continues expanding further tokens. Thus, for instance

```
\example:f { \int_eval:n { 1 + 2 } , \int_eval:n { 3 + 4 } }
```

results in the call

```
\example:n { 3 , \int_eval:n { 3 + 4 } }
```

while using `\example:x` or `\example:e` instead results in

```
\example:n { 3 , 7 }
```

at the cost of being protected (for `x` type) or very much slower in old engines (for `e` type). If you use `f` type expansion in conditional processing then you should stick to using TF type functions only as the expansion does not finish any `\if... \fi`: itself!

It is important to note that both `f`- and `o`-type expansion are concerned with the expansion of tokens from left to right in their arguments. In particular, `o`-type expansion applies to the first *token* in the argument it receives: it is conceptually similar to

```
\exp_after:wN <base function> \exp_after:wN { <argument> }
```

At the same time, `f`-type expansion stops at the *first* non-expandable token. This means for example that both

```
\tl_set:No \l_tmpa_tl { { \g_tmpb_tl } }
```

and

```
\tl_set:Nf \l_tmpa_tl { { \g_tmpb_tl } }
```

leave `\g_tmpb_tl` unchanged: `{` is the first token in the argument and is non-expandable. It is usually best to keep the following in mind when using variant forms.

- Variants with `x`-type arguments (that are fully expanded before being passed to the `n`-type base function) are never expandable even when the base function is. Such variants cannot work correctly in arguments that are themselves subject to expansion. Consider using `f` or `e` expansion.
- In contrast, `e` expansion (full expansion, almost like `x` except for the treatment of `#`) does not prevent variants from being expandable (if the base function is). The drawback is that `e` expansion is very much slower in old engines (before 2019). Consider using `f` expansion if that type of expansion is sufficient to perform the required expansion, or `x` expansion if the variant will not itself need to be expandable.
- Finally `f` expansion only expands the front of the token list, stopping at the first non-expandable token. This may fail to fully expand the argument.

When speed is essential (for functions that do very little work and whose variants are used numerous times in a document) the following considerations apply because internal functions for argument expansion come in two flavours, some faster than others.

- Arguments that might need expansion should come first in the list of arguments.
- Arguments that should consist of single tokens `N`, `c`, `V`, or `v` should come first among these.
- Arguments that appear after the first multi-token argument `n`, `f`, `e`, or `o` require slightly slower special processing to be expanded. Therefore it is best to use the optimized functions, namely those that contain only `N`, `c`, `V`, and `v`, and, in the last position, `o`, `f`, `e`, with possible trailing `N` or `n` or `T` or `F`, which are not expanded. Any `x`-type argument causes slightly slower processing.

4 Manipulating the first argument

These functions are described in detail: expansion of multiple tokens follows the same rules but is described in a shorter fashion.

<code>\exp_args:Nc</code>	★	<code>\exp_args:Nc <function> {<tokens>}</code>
<code>\exp_args:cc</code>	★	

This function absorbs two arguments (the `<function>` name and the `<tokens>`). The `<tokens>` are expanded until only characters remain, and are then turned into a control sequence. The result is inserted into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

The `:cc` variant constructs the `<function>` name in the same manner as described for the `<tokens>`.

T_EXhackers note: Protected macros that appear in a `c`-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

`\exp_args:No` ★ `\exp_args:No <function> {<tokens>} ...`

This function absorbs two arguments (the `<function>` name and the `<tokens>`). The `<tokens>` are expanded once, and the result is inserted in braces into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

`\exp_args:Nv` ★ `\exp_args:Nv <function> <variable>`

This function absorbs two arguments (the names of the `<function>` and the `<variable>`). The content of the `<variable>` are recovered and placed inside braces into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

`\exp_args:Nv` ★ `\exp_args:Nv <function> {<tokens>}`

This function absorbs two arguments (the `<function>` name and the `<tokens>`). The `<tokens>` are expanded until only characters remain, and are then turned into a control sequence. This control sequence should be the name of a `<variable>`. The content of the `<variable>` are recovered and placed inside braces into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

TeXhackers note: Protected macros that appear in a v-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

`\exp_args:Ne` ★ `\exp_args:Ne <function> {<tokens>}`

New: 2018-05-15

This function absorbs two arguments (the `<function>` name and the `<tokens>`) and exhaustively expands the `<tokens>`. The result is inserted in braces into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

TeXhackers note: This relies on the `\expanded` primitive when available (in LuaTeX and starting around 2019 in other engines). Otherwise it uses some fall-back code that is very much slower. As a result it should only be used in performance-critical code if typical users have a recent installation of the TeX ecosystem.

`\exp_args:Nf` ★ `\exp_args:Nf <function> {<tokens>}`

This function absorbs two arguments (the `<function>` name and the `<tokens>`). The `<tokens>` are fully expanded until the first non-expandable token is found (if that is a space it is removed), and the result is inserted in braces into the input stream *after* reinsertion of the `<function>`. Thus the `<function>` may take more than one argument: all others are left unchanged.

<code>\exp_args:Nx</code>	<code>\exp_args:Nx</code>	<code>\langle function \rangle \{\langle tokens \rangle\}</code>
---------------------------	---------------------------	--

This function absorbs two arguments (the `\langle function \rangle` name and the `\langle tokens \rangle`) and exhaustively expands the `\langle tokens \rangle`. The result is inserted in braces into the input stream *after* reinsertion of the `\langle function \rangle`. Thus the `\langle function \rangle` may take more than one argument: all others are left unchanged.

5 Manipulating two arguments

<code>\exp_args:NNc</code>	<code>\exp_args:NNc</code>	<code>\langle token_1 \rangle \langle token_2 \rangle \{\langle tokens \rangle\}</code>
----------------------------	----------------------------	---

These optimized functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments.

`\exp_args:NNc` ★
`\exp_args:NNo` ★
`\exp_args:NNV` ★
`\exp_args:NNv` ★
`\exp_args:NNe` ★
`\exp_args:NNf` ★
`\exp_args:Ncc` ★
`\exp_args:Nco` ★
`\exp_args:NcV` ★
`\exp_args:Ncv` ★
`\exp_args:Ncf` ★
`\exp_args:NVV` ★

Updated: 2018-05-15

<code>\exp_args:Nnc</code>	<code>\exp_args:Nno</code>	<code>\langle token \rangle \{\langle tokens_1 \rangle\} \{\langle tokens_2 \rangle\}</code>
----------------------------	----------------------------	--

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions need slower processing.

`\exp_args:Nnc` ★
`\exp_args:Nno` ★
`\exp_args:NnV` ★
`\exp_args:Nnv` ★
`\exp_args:Nne` ★
`\exp_args:Nnf` ★
`\exp_args:Noc` ★
`\exp_args:Noo` ★
`\exp_args:Nof` ★
`\exp_args:NVo` ★
`\exp_args:Nfo` ★
`\exp_args:Nff` ★

Updated: 2018-05-15

<code>\exp_args:NNx</code>	<code>\exp_args:NNx</code>	<code>\langle token_1 \rangle \langle token_2 \rangle \{\langle tokens \rangle\}</code>
----------------------------	----------------------------	---

These functions absorb three arguments and expand the second and third as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments. These functions are not expandable due to their x-type argument.

6 Manipulating three arguments

<code>\exp_args:NNNo</code>	★	<code>\exp_args:NNNo</code>	$\langle token_1 \rangle \langle token_2 \rangle \langle token_3 \rangle \{\langle tokens \rangle\}$
<code>\exp_args:NNNV</code>	★	These optimized functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i>	
<code>\exp_args:Nccc</code>	★		
<code>\exp_args:NcNc</code>	★		
<code>\exp_args:NcNo</code>	★		
<code>\exp_args:Ncco</code>	★		

<code>\exp_args:NNcf</code>	★	<code>\exp_args:NNoo</code>	$\langle token_1 \rangle \langle token_2 \rangle \{\langle token_3 \rangle\} \{\langle tokens \rangle\}$
<code>\exp_args:NNno</code>	★	These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i> These functions need slower processing.	
<code>\exp_args:NNnV</code>	★		
<code>\exp_args:NNoo</code>	★		
<code>\exp_args:NNVV</code>	★		
<code>\exp_args:Ncno</code>	★		
<code>\exp_args:NcnV</code>	★		
<code>\exp_args:Ncoo</code>	★		
<code>\exp_args:NcVV</code>	★		
<code>\exp_args:Nnnc</code>	★		
<code>\exp_args:Nnno</code>	★		
<code>\exp_args:Nnnf</code>	★		
<code>\exp_args:Nnff</code>	★		
<code>\exp_args:Nooo</code>	★		
<code>\exp_args:Noof</code>	★		
<code>\exp_args:Nffo</code>	★		

<code>\exp_args:NNNx</code>	<code>\exp_args:NNNx</code>	$\langle token_1 \rangle \langle token_2 \rangle \{\langle tokens_1 \rangle\} \{\langle tokens_2 \rangle\}$
<code>\exp_args:NNnx</code>	These functions absorb four arguments and expand the second, third and fourth as detailed by their argument specifier. The first argument of the function is then the next item on the input stream, followed by the expansion of the second argument, <i>etc.</i>	
<code>\exp_args:NNox</code>		
<code>\exp_args:Nccx</code>		
<code>\exp_args:Ncnx</code>		
<code>\exp_args:NNnx</code>		
<code>\exp_args:Nnox</code>		
<code>\exp_args:Noox</code>		

New: 2015-08-12

7 Unbraced expansion

<code>\exp_last_unbraced:No</code>	★	<code>\exp_last_unbraced:Nno</code> $\langle token \rangle$ $\{\langle tokens_1 \rangle\}$ $\{\langle tokens_2 \rangle\}$
<code>\exp_last_unbraced:(NV Nv Nf)</code>	★	
<code>\exp_last_unbraced:Ne</code>	★	
<code>\exp_last_unbraced:NNo</code>	★	
<code>\exp_last_unbraced:(NNV NNf Nco NcV)</code>	★	
<code>\exp_last_unbraced:Nno</code>	★	
<code>\exp_last_unbraced:(Noo Nfo)</code>	★	
<code>\exp_last_unbraced:NNNo</code>	★	
<code>\exp_last_unbraced:(NNNV NNNf)</code>	★	
<code>\exp_last_unbraced:NnNo</code>	★	
<code>\exp_last_unbraced:NNNNo</code>	★	
<code>\exp_last_unbraced:NNNNf</code>	★	

Updated: 2018-05-15

These functions absorb the number of arguments given by their specification, carry out the expansion indicated and leave the results in the input stream, with the last argument not surrounded by the usual braces. Of these, the `:Nno`, `:Noo`, `:Nfo` and `:NnNo` variants need slower processing.

T_EXhackers note: As an optimization, the last argument is unbraced by some of those functions before expansion. This can cause problems if the argument is empty: for instance, `\exp_last_unbraced:Nf \foo_bar:w { } \q_stop` leads to an infinite loop, as the quark is `f`-expanded.

<code>\exp_last_unbraced:Nx</code>	<code>\exp_last_unbraced:Nx</code> $\langle function \rangle$ $\{\langle tokens \rangle\}$
------------------------------------	--

This function fully expands the $\langle tokens \rangle$ and leaves the result in the input stream after reinsertion of the $\langle function \rangle$. This function is not expandable.

<code>\exp_last_two_unbraced:Noo</code>	★	<code>\exp_last_two_unbraced:Noo</code> $\langle token \rangle$ $\{\langle tokens_1 \rangle\}$ $\{\langle tokens_2 \rangle\}$
---	---	---

This function absorbs three arguments and expands the second and third once. The first argument of the function is then the next item on the input stream, followed by the expansion of the second and third arguments, which are not wrapped in braces. This function needs special (slower) processing.

<code>\exp_after:wN</code>	★	<code>\exp_after:wN</code> $\langle token_1 \rangle$ $\langle token_2 \rangle$
----------------------------	---	--

Carries out a single expansion of $\langle token_2 \rangle$ (which may consume arguments) prior to the expansion of $\langle token_1 \rangle$. If $\langle token_2 \rangle$ has no expansion (for example, if it is a character) then it is left unchanged. It is important to notice that $\langle token_1 \rangle$ may be *any* single token, including group-opening and -closing tokens (`{` or `}` assuming normal T_EX category codes). Unless specifically required this should be avoided: expansion should be carried out using an appropriate argument specifier variant or the appropriate `\exp_arg:N` function.

T_EXhackers note: This is the T_EX primitive `\expandafter` renamed.

8 Preventing expansion

Despite the fact that the following functions are all about preventing expansion, they're designed to be used in an expandable context and hence are all marked as being 'expandable' since they themselves disappear after the expansion has completed.

<hr/> <hr/> <code>\exp_not:N</code> ★	<code>\exp_not:N <token></code>	Prevents expansion of the $\langle token \rangle$ in a context where it would otherwise be expanded, for example an x -type argument or the first token in an o or e or f argument.
	TeXhackers note: This is the TeX <code>\noexpand</code> primitive. It only prevents expansion. At the beginning of an f -type argument, a space $\langle token \rangle$ is removed even if it appears as <code>\exp_not:N \c_space_token</code> . In an x -expanding definition (<code>\cs_new:Npx</code>), a macro parameter introduces an argument even if it appears as <code>\exp_not:N # 1</code> . This differs from <code>\exp_not:n</code> .	
<hr/> <hr/> <code>\exp_not:c</code> ★	<code>\exp_not:c <tokens></code>	Expands the $\langle tokens \rangle$ until only characters remain, and then converts this into a control sequence. Further expansion of this control sequence is then inhibited using <code>\exp_not:N</code> .
	TeXhackers note: Protected macros that appear in a c -type argument are expanded despite being protected; <code>\exp_not:n</code> also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.	
<hr/> <hr/> <code>\exp_not:n</code> ★	<code>\exp_not:n <tokens></code>	Prevents expansion of the $\langle tokens \rangle$ in an e or x -type argument. In all other cases the $\langle tokens \rangle$ continue to be expanded, for example in the input stream or in other types of arguments such as c , f , v . The argument of <code>\exp_not:n</code> <i>must</i> be surrounded by braces.
	TeXhackers note: This is the ε -TeX <code>\unexpanded</code> primitive. In an x -expanding definition (<code>\cs_new:Npx</code>), <code>\exp_not:n {#1}</code> is equivalent to <code>##1</code> rather than to <code>#1</code> , namely it inserts the two characters <code>#</code> and <code>1</code> . In an e -type argument <code>\exp_not:n {#}</code> is equivalent to <code>#</code> , namely it inserts the character <code>#</code> .	
<hr/> <hr/> <code>\exp_not:o</code> ★	<code>\exp_not:o <tokens></code>	Expands the $\langle tokens \rangle$ once, then prevents any further expansion in x -type arguments using <code>\exp_not:n</code> .
<hr/> <hr/> <code>\exp_not:V</code> ★	<code>\exp_not:V <variable></code>	Recovers the content of the $\langle variable \rangle$, then prevents expansion of this material in x -type arguments using <code>\exp_not:n</code> .

`\exp_not:v` ★ `\exp_not:v {⟨tokens⟩}`

Expands the *⟨tokens⟩* until only characters remains, and then converts this into a control sequence which should be a *⟨variable⟩* name. The content of the *⟨variable⟩* is recovered, and further expansion in *x*-type arguments is prevented using `\exp_not:n`.

T_EXhackers note: Protected macros that appear in a *v*-type argument are expanded despite being protected; `\exp_not:n` also has no effect. An internal error occurs if non-characters or active characters remain after full expansion, as the conversion to a control sequence is not possible.

`\exp_not:e` ★ `\exp_not:e {⟨tokens⟩}`

Expands *⟨tokens⟩* exhaustively, then protects the result of the expansion (including any tokens which were not expanded) from further expansion in *e* or *x*-type arguments using `\exp_not:n`. This is very rarely useful but is provided for consistency.

`\exp_not:f` ★ `\exp_not:f {⟨tokens⟩}`

Expands *⟨tokens⟩* fully until the first unexpandable token is found (if it is a space it is removed). Expansion then stops, and the result of the expansion (including any tokens which were not expanded) is protected from further expansion in *x*-type arguments using `\exp_not:n`.

`\exp_stop_f:` ★ `\foo_bar:f { ⟨tokens⟩ \exp_stop_f: ⟨more tokens⟩ }`

Updated: 2011-06-03

This function terminates an *f*-type expansion. Thus if a function `\foo_bar:f` starts an *f*-type expansion and all of *⟨tokens⟩* are expandable `\exp_stop_f:` terminates the expansion of tokens even if *⟨more tokens⟩* are also expandable. The function itself is an implicit space token. Inside an *x*-type expansion, it retains its form, but when typeset it produces the underlying space (␣).

9 Controlled expansion

The `expl3` language makes all efforts to hide the complexity of T_EX expansion from the programmer by providing concepts that evaluate/expand arguments of functions prior to calling the “base” functions. Thus, instead of using many `\expandafter` calls and other trickery it is usually a matter of choosing the right variant of a function to achieve a desired result.

Of course, deep down T_EX is using expansion as always and there are cases where a programmer needs to control that expansion directly; typical situations are basic data manipulation tools. This section documents the functions for that level. These commands are used throughout the kernel code, but we hope that outside the kernel there will be little need to resort to them. Instead the argument manipulation methods document above should usually be sufficient.

While `\exp_after:wN` expands one token (out of order) it is sometimes necessary to expand several tokens in one go. The next set of commands provide this functionality. Be aware that it is absolutely required that the programmer has full control over the tokens to be expanded, i.e., it is not possible to use these functions to expand unknown input as part of *⟨expandable-tokens⟩* as that will break badly if unexpandable tokens are encountered in that place!

`\exp:w` ★
`\exp_end:` ★

New: 2015-08-23

`\exp:w` $\langle expandable\ tokens \rangle$ `\exp_end:`

Expands $\langle expandable-tokens \rangle$ until reaching `\exp_end:` at which point expansion stops. The full expansion of $\langle expandable\ tokens \rangle$ has to be empty. If any token in $\langle expandable\ tokens \rangle$ or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end:` will be misinterpreted later on.²

In typical use cases the `\exp_end:` is hidden somewhere in the replacement text of $\langle expandable-tokens \rangle$ rather than being on the same expansion level than `\exp:w`, e.g., you may see code such as

`\exp:w \@@_case:NnTF #1 {#2} { } { }`

where somewhere during the expansion of `\@@_case:NnTF` the `\exp_end:` gets generated.

T_EXhackers note: The current implementation uses `\romannumeral` hence ignores space tokens and explicit signs + and - in the expansion of the $\langle expandable\ tokens \rangle$, but this should not be relied upon.

`\exp:w` ★
`\exp_end_continue_f:w` ★

New: 2015-08-23

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end_continue_f:w` $\langle further-tokens \rangle$

Expands $\langle expandable-tokens \rangle$ until reaching `\exp_end_continue_f:w` at which point expansion continues as an f-type expansion expanding $\langle further-tokens \rangle$ until an unexpandable token is encountered (or the f-type expansion is explicitly terminated by `\exp_stop_f:`). As with all f-type expansions a space ending the expansion gets removed.

The full expansion of $\langle expandable-tokens \rangle$ has to be empty. If any token in $\langle expandable-tokens \rangle$ or any token generated by expanding the tokens therein is not expandable the expansion will end prematurely and as a result `\exp_end_continue_f:w` will be misinterpreted later on.³

In typical use cases $\langle expandable-tokens \rangle$ contains no tokens at all, e.g., you will see code such as

`\exp_after:wN { \exp:w \exp_end_continue_f:w #2 }`

where the `\exp_after:wN` triggers an f-expansion of the tokens in #2. For technical reasons this has to happen using two tokens (if they would be hidden inside another command `\exp_after:wN` would only expand the command but not trigger any additional f-expansion).

You might wonder why there are two different approaches available, after all the effect of

`\exp:w` $\langle expandable-tokens \rangle$ `\exp_end:`

can be alternatively achieved through an f-type expansion by using `\exp_stop_f:`, i.e.

`\exp:w \exp_end_continue_f:w` $\langle expandable-tokens \rangle$ `\exp_stop_f:`

The reason is simply that the first approach is slightly faster (one less token to parse and less expansion internally) so in places where such performance really matters and where we want to explicitly stop the expansion at a defined point the first form is preferable.

²Due to the implementation you might get the character in position 0 in the current font (typically “”) in the output without any error message!

³In this particular case you may get a character into the output as well as an error message.

<code>\exp:w</code>	★
<code>\exp_end_continue_f:nw</code>	★

New: 2015-08-23

`\exp:w` *<expandable-tokens>* `\exp_end_continue_f:nw` *<further-tokens>*

The difference to `\exp_end_continue_f:w` is that we first we pick up an argument which is then returned to the input stream. If *<further-tokens>* starts with space tokens then these space tokens are removed while searching for the argument. If it starts with a brace group then the braces are removed. Thus such spaces or braces will not terminate the f-type expansion.

10 Internal functions

`\::n` `\cs_new:Npn \exp_args:Ncof { \::c \::o \::f \:: }`

`\::N` Internal forms for the base expansion types. These names do *not* conform to the general \LaTeX 3 approach as this makes them more readily visible in the log and so forth. They should not be used outside this module.

`\::c`
`\::o`
`\::e`
`\::f`
`\::x`
`\::v`
`\::V`
`\::`

`\::o_unbraced` `\cs_new:Npn \exp_last_unbraced:Nno { \::n \::o_unbraced \:: }`

`\::e_unbraced` Internal forms for the expansion types which leave the terminal argument unbraced. These names do *not* conform to the general \LaTeX 3 approach as this makes them more readily visible in the log and so forth. They should not be used outside this module.

`\::f_unbraced`
`\::x_unbraced`
`\::v_unbraced`
`\::V_unbraced`

Part VI

The l3tl package

Token lists

T_EX works with tokens, and L^AT_EX3 therefore provides a number of functions to deal with lists of tokens. Token lists may be present directly in the argument to a function:

```
\foo:n { a collection of \tokens }
```

or may be stored in a so-called “token list variable”, which have the suffix `tl`: a token list variable can also be used as the argument to a function, for example

```
\foo:N \l_some_tl
```

In both cases, functions are available to test and manipulate the lists of tokens, and these have the module prefix `tl`. In many cases, functions which can be applied to token list variables are paired with similar functions for application to explicit lists of tokens: the two “views” of a token list are therefore collected together here.

A token list (explicit, or stored in a variable) can be seen either as a list of “items”, or a list of “tokens”. An item is whatever `\use:n` would grab as its argument: a single non-space token or a brace group, with optional leading explicit space characters (each item is thus itself a token list). A token is either a normal `N` argument, or `␣`, `{`, or `}` (assuming normal T_EX category codes). Thus for example

```
{ Hello } ~ world
```

contains six items (Hello, w, o, r, l and d), but thirteen tokens (`{`, H, e, l, l, o, `}`, `␣`, w, o, r, l and d). Functions which act on items are often faster than their analogue acting directly on tokens.

1 Creating and initialising token list variables

```
\tl_new:N \tl_new:N <tl var>
```

```
\tl_new:c
```

Creates a new `<tl var>` or raises an error if the name is already taken. The declaration is global. The `<tl var>` is initially empty.

```
\tl_const:Nn \tl_const:Nn <tl var> {<token list>}
```

```
\tl_const:(Nx|cn|cx)
```

Creates a new constant `<tl var>` or raises an error if the name is already taken. The value of the `<tl var>` is set globally to the `<token list>`.

```
\tl_clear:N \tl_clear:N <tl var>
```

```
\tl_clear:c
```

```
\tl_gclear:N
```

```
\tl_gclear:c
```

Clears all entries from the `<tl var>`.

<hr/>	
<code>\tl_clear_new:N</code>	<code>\tl_clear_new:N <tl var></code>
<code>\tl_clear_new:c</code>	
<code>\tl_gclear_new:N</code>	Ensures that the $\langle tl\ var \rangle$ exists globally by applying <code>\tl_new:N</code> if necessary, then applies
<code>\tl_gclear_new:c</code>	<code>\tl_(g)clear:N</code> to leave the $\langle tl\ var \rangle$ empty.
<hr/>	
<code>\tl_set_eq:NN</code>	<code>\tl_set_eq:NN <tl var₁> <tl var₂></code>
<code>\tl_set_eq:(cN Nc cc)</code>	Sets the content of $\langle tl\ var_1 \rangle$ equal to that of $\langle tl\ var_2 \rangle$.
<code>\tl_gset_eq:NN</code>	
<code>\tl_gset_eq:(cN Nc cc)</code>	
<hr/>	
<code>\tl_concat:NNN</code>	<code>\tl_concat:NNN <tl var₁> <tl var₂> <tl var₃></code>
<code>\tl_concat:ccc</code>	
<code>\tl_gconcat:NNN</code>	Concatenates the content of $\langle tl\ var_2 \rangle$ and $\langle tl\ var_3 \rangle$ together and saves the result in
<code>\tl_gconcat:ccc</code>	$\langle tl\ var_1 \rangle$. The $\langle tl\ var_2 \rangle$ is placed at the left side of the new token list.
<hr/>	
New: 2012-05-18	
<hr/>	
<code>\tl_if_exist_p:N *</code>	<code>\tl_if_exist_p:N <tl var></code>
<code>\tl_if_exist_p:c *</code>	<code>\tl_if_exist:NTF <tl var> {\true code} {\false code}</code>
<code>\tl_if_exist:NTF *</code>	
<code>\tl_if_exist:cTF *</code>	Tests whether the $\langle tl\ var \rangle$ is currently defined. This does not check that the $\langle tl\ var \rangle$ really is a token list variable.
<hr/>	
New: 2012-03-03	

2 Adding data to token list variables

<hr/>	
<code>\tl_set:Nn</code>	<code>\tl_set:Nn <tl var> {\tokens}</code>
<code>\tl_set:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<code>\tl_gset:Nn</code>	
<code>\tl_gset:(NV Nv No Nf Nx cn cV cv co cf cx)</code>	
<hr/>	
Sets $\langle tl\ var \rangle$ to contain $\langle tokens \rangle$, removing any previous content from the variable.	
<hr/>	
<code>\tl_put_left:Nn</code>	<code>\tl_put_left:Nn <tl var> {\tokens}</code>
<code>\tl_put_left:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_left:Nn</code>	
<code>\tl_gput_left:(NV No Nx cn cV co cx)</code>	
<hr/>	
Appends $\langle tokens \rangle$ to the left side of the current content of $\langle tl\ var \rangle$.	
<hr/>	
<code>\tl_put_right:Nn</code>	<code>\tl_put_right:Nn <tl var> {\tokens}</code>
<code>\tl_put_right:(NV No Nx cn cV co cx)</code>	
<code>\tl_gput_right:Nn</code>	
<code>\tl_gput_right:(NV No Nx cn cV co cx)</code>	
<hr/>	
Appends $\langle tokens \rangle$ to the right side of the current content of $\langle tl\ var \rangle$.	

3 Modifying token list variables

```
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
```

Updated: 2011-08-11

```
\tl_replace_once:Nnn <tl var> {<old tokens>} {<new tokens>}
```

Replaces the first (leftmost) occurrence of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
```

Updated: 2011-08-11

```
\tl_replace_all:Nnn <tl var> {<old tokens>} {<new tokens>}
```

Replaces all occurrences of *<old tokens>* in the *<tl var>* with *<new tokens>*. *<Old tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<old tokens>* may remain after the replacement (see `\tl_remove_all:Nn` for an example).

```
\tl_remove_once:Nn
\tl_remove_once:cn
\tl_gremove_once:Nn
\tl_gremove_once:cn
```

Updated: 2011-08-11

```
\tl_remove_once:Nn <tl var> {<tokens>}
```

Removes the first (leftmost) occurrence of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

```
\tl_remove_all:Nn
\tl_remove_all:cn
\tl_gremove_all:Nn
\tl_gremove_all:cn
```

Updated: 2011-08-11

```
\tl_remove_all:Nn <tl var> {<tokens>}
```

Removes all occurrences of *<tokens>* from the *<tl var>*. *<Tokens>* cannot contain `{`, `}` or `#` (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6). As this function operates from left to right, the pattern *<tokens>* may remain after the removal, for instance,

```
\tl_set:Nn \l_tmpa_tl {abbccd} \tl_remove_all:Nn \l_tmpa_tl {bc}
```

results in `\l_tmpa_tl` containing `abcd`.

4 Reassigning token list category codes

These functions allow the rescanning of tokens: re-apply T_EX's tokenization process to apply category codes different from those in force when the tokens were absorbed. Whilst this functionality is supported, it is often preferable to find alternative approaches to achieving outcomes rather than rescanning tokens (for example construction of token lists token-by-token with intervening category code changes).

<code>\tl_set_rescan:Nnn</code>	<code>\tl_set_rescan:Nnn <tl var> {<setup>} {<tokens>}</code>
<code>\tl_set_rescan:(Nno Nnx cnn cno cnx)</code>	
<code>\tl_gset_rescan:Nnn</code>	
<code>\tl_gset_rescan:(Nno Nnx cnn cno cnx)</code>	

Updated: 2015-08-11

Sets $\langle tl\ var \rangle$ to contain $\langle tokens \rangle$, applying the category code régime specified in the $\langle setup \rangle$ before carrying out the assignment. (Category codes applied to tokens not explicitly covered by the $\langle setup \rangle$ are those in force at the point of use of `\tl_set_rescan:Nnn`.) This allows the $\langle tl\ var \rangle$ to contain material with category codes other than those that apply when $\langle tokens \rangle$ are absorbed. The $\langle setup \rangle$ is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_rescan:nn`.

T_EXhackers note: The $\langle tokens \rangle$ are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user $\langle setup \rangle$), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file.

<code>\tl_rescan:nn</code>	<code>\tl_rescan:nn {<setup>} {<tokens>}</code>
----------------------------	---

Updated: 2015-08-11

Rescans $\langle tokens \rangle$ applying the category code régime specified in the $\langle setup \rangle$, and leaves the resulting tokens in the input stream. (Category codes applied to tokens not explicitly covered by the $\langle setup \rangle$ are those in force at the point of use of `\tl_rescan:nn`.) The $\langle setup \rangle$ is run within a group and may contain any valid input, although only changes in category codes are relevant. See also `\tl_set_rescan:Nnn`, which is more robust than using `\tl_set:Nn` in the $\langle tokens \rangle$ argument of `\tl_rescan:nn`.

T_EXhackers note: The $\langle tokens \rangle$ are first turned into a string (using `\tl_to_str:n`). If the string contains one or more characters with character code `\newlinechar` (set equal to `\endlinechar` unless that is equal to 32, before the user $\langle setup \rangle$), then it is split into lines at these characters, then read as if reading multiple lines from a file, ignoring spaces (catcode 10) at the beginning and spaces and tabs (character code 32 or 9) at the end of every line. Otherwise, spaces (and tabs) are retained at both ends of the single-line string, as if it appeared in the middle of a line read from a file.

5 Token list conditionals

<code>\tl_if_blank_p:n</code>	★	<code>\tl_if_blank_p:n {<token list>}</code>
<code>\tl_if_blank_p:(V o)</code>	★	<code>\tl_if_blank:nTF {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_blank:nTF</code>	★	
<code>\tl_if_blank:(V o)TF</code>	★	

Tests if the $\langle token\ list \rangle$ consists only of blank spaces (*i.e.* contains no item). The test is **true** if $\langle token\ list \rangle$ is zero or more explicit space characters (explicit tokens with character code 32 and category code 10), and is **false** otherwise.

<code>\tl_if_empty_p:N</code>	★	<code>\tl_if_empty_p:N <tl var></code>
<code>\tl_if_empty_p:c</code>	★	<code>\tl_if_empty:NNTF <tl var> {<true code>} {<false code>}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i><token list variable></i> is entirely empty (<i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:cTF</code>	★	

<code>\tl_if_empty_p:n</code>	★	<code>\tl_if_empty_p:n {<token list>}</code>
<code>\tl_if_empty_p:(V o)</code>	★	<code>\tl_if_empty:NNTF {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_empty:nTF</code>	★	Tests if the <i><token list></i> is entirely empty (<i>i.e.</i> contains no tokens at all).
<code>\tl_if_empty:(V o)TF</code>	★	

New: 2012-05-24
Updated: 2012-06-05

<code>\tl_if_eq_p:NN</code>	★	<code>\tl_if_eq_p:NN <tl var₁> <tl var₂></code>
<code>\tl_if_eq_p:(Nc cN cc)</code>	★	<code>\tl_if_eq:NNTF <tl var₁> <tl var₂> {<true code>} {<false code>}</code>
<code>\tl_if_eq:NNTF</code>	★	Compares the content of two <i><token list variables></i> and is logically true if the two contain the same list of tokens (<i>i.e.</i> identical in both the list of characters they contain and the category codes of those characters). Thus for example
<code>\tl_if_eq:(Nc cN cc)TF</code>	★	

```

\tl_set:Nn \l_tmpa_tl { abc }
\tl_set:Nx \l_tmpb_tl { \tl_to_str:n { abc } }
\tl_if_eq:NNTF \l_tmpa_tl \l_tmpb_tl { true } { false }

```

yields **false**.

<code>\tl_if_eq:nnTF</code>	★	<code>\tl_if_eq:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code>
-----------------------------	---	--

Tests if *<token list₁>* and *<token list₂>* contain the same list of tokens, both in respect of character codes and category codes.

<code>\tl_if_in:NnTF</code>	★	<code>\tl_if_in:NnTF <tl var> {<token list>} {<true code>} {<false code>}</code>
<code>\tl_if_in:cnTF</code>	★	Tests if the <i><token list></i> is found in the content of the <i><tl var></i> . The <i><token list></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

<code>\tl_if_in:nnTF</code>	★	<code>\tl_if_in:nnTF {<token list₁>} {<token list₂>} {<true code>} {<false code>}</code>
<code>\tl_if_in:(Vn on no)TF</code>	★	Tests if <i><token list₂></i> is found inside <i><token list₁></i> . The <i><token list₂></i> cannot contain the tokens <code>{</code> , <code>}</code> or <code>#</code> (more precisely, explicit character tokens with category code 1 (begin-group) or 2 (end-group), and tokens with category code 6).

<code>\tl_if_noval_p:n</code>	★	<code>\tl_if_noval_p:n {<token list>}</code>
<code>\tl_if_noval_p:nTF</code>	★	<code>\tl_if_noval_p:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2017-11-14

Tests if the *<token list>* is exactly equal to the special `\c_noval_p_tl` marker. This function is intended to allow construction of flexible document interface structures in which missing optional arguments are detected.

<code>\tl_if_single_p:N</code> ★	<code>\tl_if_single_p:N <tl var></code>
<code>\tl_if_single_p:c</code> ★	<code>\tl_if_single:NNTF <tl var> {<true code>} {<false code>}</code>
<code>\tl_if_single:NNTF</code> ★	Tests if the content of the <code><tl var></code> consists of a single item, <i>i.e.</i> is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to <code>\tl_count:N</code> .
<code>\tl_if_single:cNTF</code> ★	
<hr/> Updated: 2011-08-13 <hr/>	

<code>\tl_if_single_p:n</code> ★	<code>\tl_if_single_p:n {<token list>}</code>
<code>\tl_if_single:nNTF</code> ★	<code>\tl_if_single:nNTF {<token list>} {<true code>} {<false code>}</code>
Updated: 2011-08-13	
Tests if the <i><token list></i> has exactly one item, <i>i.e.</i> is a single normal token (neither an explicit space character nor a begin-group character) or a single brace group, surrounded by optional spaces on both sides. In other words, such a token list has token count 1 according to <code>\tl_count:n</code> .	

<code>\tl_case:Nn</code> ★	<code>\tl_case:NnNTF <test token list variable></code>
<code>\tl_case:cn</code> ★	<code>{</code>
<code>\tl_case:NnNTF</code> ★	<code> <token list variable case₁> {<code case₁>}</code>
<code>\tl_case:cnNTF</code> ★	<code> <token list variable case₂> {<code case₂>}</code>
New: 2013-07-24	
<code> ...</code>	
<code> <token list variable case_n> {<code case_n>}</code>	
<code>}</code>	
<code>{<true code>}</code>	
<code>{<false code>}</code>	

This function compares the *<test token list variable>* in turn with each of the *<token list variable cases>*. If the two are equal (as described for `\tl_if_eq:NNTF`) then the associated *<code>* is left in the input stream and other cases are discarded. If any of the cases are matched, the *<true code>* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *<false code>* is inserted. The function `\tl_case:Nn`, which does nothing if there is no match, is also available.

6 Mapping to token lists

<code>\tl_map_function:NN</code> ☆	<code>\tl_map_function:NN <tl var> <function></code>
<code>\tl_map_function:cN</code> ☆	Applies <i><function></i> to every <i><item></i> in the <i><tl var></i> . The <i><function></i> receives one argument for each iteration. This may be a number of tokens if the <i><item></i> was stored within braces. Hence the <i><function></i> should anticipate receiving <i>n</i> -type arguments. See also <code>\tl_map_function:nN</code> .
Updated: 2012-06-29	

<code>\tl_map_function:nN</code> ☆	<code>\tl_map_function:nN {<token list>} <function></code>
Updated: 2012-06-29	
Applies <i><function></i> to every <i><item></i> in the <i><token list></i> , The <i><function></i> receives one argument for each iteration. This may be a number of tokens if the <i><item></i> was stored within braces. Hence the <i><function></i> should anticipate receiving <i>n</i> -type arguments. See also <code>\tl_map_function:NN</code> .	

<code>\tl_map_inline:Nn</code>	<code>\tl_map_inline:Nn <tl var> {<inline function>}</code>
<code>\tl_map_inline:cn</code>	Applies the <i><inline function></i> to every <i><item></i> stored within the <i><tl var></i> . The <i><inline function></i> should consist of code which receives the <i><item></i> as #1. See also <code>\tl_map_function:NN</code> .
Updated: 2012-06-29	

<hr/> <code>\tl_map_inline:nn</code> <hr/>	<code>\tl_map_inline:nn {<token list>} {<inline function>}</code>
Updated: 2012-06-29	Applies the <i><inline function></i> to every <i><item></i> stored within the <i><token list></i> . The <i><inline function></i> should consist of code which receives the <i><item></i> as #1. See also <code>\tl_map_function:nn</code> .
<hr/> <code>\tl_map_variable:NNn</code> <code>\tl_map_variable:cNn</code> <hr/>	<code>\tl_map_variable:NNn <tl var> <variable> {<code>}</code>
Updated: 2012-06-29	Stores each <i><item></i> of the <i><tl var></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\tl_map_inline:Nn</code> .
<hr/> <code>\tl_map_variable:nNn</code> <hr/>	<code>\tl_map_variable:nNn {<token list>} <variable> {<code>}</code>
Updated: 2012-06-29	Stores each <i><item></i> of the <i><token list></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\tl_map_inline:nn</code> .
<hr/> <code>\tl_map_break: ☆</code> <hr/>	<code>\tl_map_break:</code>
Updated: 2012-06-29	Used to terminate a <code>\tl_map...</code> function before all entries in the <i><token list variable></i> have been processed. This normally takes place within a conditional statement, for example <pre> \tl_map_inline:Nn \l_my_tl { \str_if_eq:nnT { #1 } { bingo } { \tl_map_break: } % Do something useful }</pre> <p>See also <code>\tl_map_break:n</code>. Use outside of a <code>\tl_map...</code> scenario leads to low level TeX errors.</p> <p>TeXhackers note: When the mapping is broken, additional tokens may be inserted before the <i><tokens></i> are inserted into the input stream. This depends on the design of the mapping function.</p>

`\tl_map_break:n` ☆

Updated: 2012-06-29

`\tl_map_break:n {<code>}`

Used to terminate a `\tl_map...` function before all entries in the *<token list variable>* have been processed, inserting the *<code>* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\tl_map_inline:Nn \l_my_tl
{
  \str_if_eq:nnT { #1 } { bingo }
  { \tl_map_break:n { <code> } }
  % Do something useful
}
```

Use outside of a `\tl_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *<code>* is inserted into the input stream. This depends on the design of the mapping function.

7 Using token lists

`\tl_to_str:n` ☆

`\tl_to_str:V` ☆

`\tl_to_str:n {<token list>}`

Converts the *<token list>* to a *<string>*, leaving the resulting character tokens in the input stream. A *<string>* is a series of tokens with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This function requires only a single expansion. Its argument *must* be braced.

TeXhackers note: This is the ϵ -TeX primitive `\detokenize`. Converting a *<token list>* to a *<string>* yields a concatenation of the string representations of every token in the *<token list>*. The string representation of a control sequence is

- an escape character, whose character code is given by the internal parameter `\escapechar`, absent if the `\escapechar` is negative or greater than the largest character code;
- the control sequence name, as defined by `\cs_to_str:N`;
- a space, unless the control sequence name is a single character whose category at the time of expansion of `\tl_to_str:n` is not “letter”.

The string representation of an explicit character token is that character, doubled in the case of (explicit) macro parameter characters (normally `#`). In particular, the string representation of a token list may depend on the category codes in effect when it is evaluated, and the value of the `\escapechar`: for instance `\tl_to_str:n {\a}` normally produces the three character “backslash”, “lower-case a”, “space”, but it may also produce a single “lower-case a” if the escape character is negative and `a` is currently not a letter.

`\tl_to_str:N` ☆

`\tl_to_str:c` ☆

`\tl_to_str:N <tl var>`

Converts the content of the *<tl var>* into a series of characters with category code 12 (other) with the exception of spaces, which retain category code 10 (space). This *<string>* is then left in the input stream. For low-level details, see the notes given for `\tl_to_str:n`.

<code>\tl_use:N</code>	★	<code>\tl_use:N <tl var></code>
------------------------	---	---------------------------------------

<code>\tl_use:c</code>	★	
------------------------	---	--

Recovers the content of a $\langle tl\ var\rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a $\langle tl\ var\rangle$ directly without an accessor function.

8 Working with the content of token lists

<code>\tl_count:n</code>	★	<code>\tl_count:n {\tokens}</code>
--------------------------	---	------------------------------------

<code>\tl_count:(V o)</code>	★	
------------------------------	---	--

New: 2012-05-13

Counts the number of $\langle items\rangle$ in $\langle tokens\rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group $\{\dots\}$. This process ignores any unprotected spaces within $\langle tokens\rangle$. See also `\tl_count:N`. This function requires three expansions, giving an $\langle integer\ denotation\rangle$.

<code>\tl_count:N</code>	★	<code>\tl_count:N <tl var></code>
--------------------------	---	---

<code>\tl_count:c</code>	★	
--------------------------	---	--

New: 2012-05-13

Counts the number of token groups in the $\langle tl\ var\rangle$ and leaves this information in the input stream. Unbraced tokens count as one element as do each token group $\{\dots\}$. This process ignores any unprotected spaces within the $\langle tl\ var\rangle$. See also `\tl_count:n`. This function requires three expansions, giving an $\langle integer\ denotation\rangle$.

<code>\tl_reverse:n</code>	★	<code>\tl_reverse:n {\token list}</code>
----------------------------	---	--

<code>\tl_reverse:(V o)</code>	★	
--------------------------------	---	--

Updated: 2012-01-08

Reverses the order of the $\langle items\rangle$ in the $\langle token\ list\rangle$, so that $\langle item_1\rangle\langle item_2\rangle\langle item_3\rangle\dots\langle item_n\rangle$ becomes $\langle item_n\rangle\dots\langle item_3\rangle\langle item_2\rangle\langle item_1\rangle$. This process preserves unprotected space within the $\langle token\ list\rangle$. Tokens are not reversed within braced token groups, which keep their outer set of braces. In situations where performance is important, consider `\tl_reverse_items:n`. See also `\tl_reverse:N`.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_reverse:N</code>		<code>\tl_reverse:N <tl var></code>
----------------------------	--	---

<code>\tl_reverse:c</code>		
----------------------------	--	--

<code>\tl_greverse:N</code>		
-----------------------------	--	--

<code>\tl_greverse:c</code>		
-----------------------------	--	--

Updated: 2012-01-08

Reverses the order of the $\langle items\rangle$ stored in $\langle tl\ var\rangle$, so that $\langle item_1\rangle\langle item_2\rangle\langle item_3\rangle\dots\langle item_n\rangle$ becomes $\langle item_n\rangle\dots\langle item_3\rangle\langle item_2\rangle\langle item_1\rangle$. This process preserves unprotected spaces within the $\langle token\ list\ variable\rangle$. Braced token groups are copied without reversing the order of tokens, but keep the outer set of braces. See also `\tl_reverse:n`, and, for improved performance, `\tl_reverse_items:n`.

<code>\tl_reverse_items:n</code>	★	<code>\tl_reverse_items:n {\token list}</code>
----------------------------------	---	--

New: 2012-01-08

Reverses the order of the $\langle items\rangle$ stored in $\langle tl\ var\rangle$, so that $\{\langle item_1\rangle\}\{\langle item_2\rangle\}\{\langle item_3\rangle\}\dots\{\langle item_n\rangle\}$ becomes $\{\langle item_n\rangle\}\dots\{\langle item_3\rangle\}\{\langle item_2\rangle\}\{\langle item_1\rangle\}$. This process removes any unprotected space within the $\langle token\ list\rangle$. Braced token groups are copied without reversing the order of tokens, and keep the outer set of braces. Items which are initially not braced are copied with braces in the result. In cases where preserving spaces is important, consider the slower function `\tl_reverse:n`.

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_trim_spaces:n</code> ★	<code>\tl_trim_spaces:n {⟨token list⟩}</code>
<code>\tl_trim_spaces:o</code> ★	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the <i>⟨token list⟩</i> and leaves the result in the input stream.
New: 2011-07-09 Updated: 2012-06-25	

TeXhackers note: The result is returned within `\unexpanded`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_trim_spaces_apply:nN</code> ★	<code>\tl_trim_spaces_apply:nN {⟨token list⟩} ⟨function⟩</code>
<code>\tl_trim_spaces_apply:oN</code> ★	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the <i>⟨token list⟩</i> and passes the result to the <i>⟨function⟩</i> as an <i>n</i> -type argument.
New: 2018-04-12	

<code>\tl_trim_spaces:N</code>	<code>\tl_trim_spaces:N ⟨tl var⟩</code>
<code>\tl_trim_spaces:c</code>	Removes any leading and trailing explicit space characters (explicit tokens with character code 32 and category code 10) from the content of the <i>⟨tl var⟩</i> . Note that this therefore <i>resets</i> the content of the variable.
<code>\tl_gtrim_spaces:N</code>	
<code>\tl_gtrim_spaces:c</code>	
New: 2011-07-09	

<code>\tl_sort:Nn</code>	<code>\tl_sort:Nn ⟨tl var⟩ {⟨comparison code⟩}</code>
<code>\tl_sort:cn</code>	Sorts the items in the <i>⟨tl var⟩</i> according to the <i>⟨comparison code⟩</i> , and assigns the result to <i>⟨tl var⟩</i> . The details of sorting comparison are described in Section 1.
<code>\tl_gsort:Nn</code>	
<code>\tl_gsort:cn</code>	
New: 2017-02-06	

<code>\tl_sort:nN</code> ★	<code>\tl_sort:nN {⟨token list⟩} ⟨conditional⟩</code>
New: 2017-02-06	
	Sorts the items in the <i>⟨token list⟩</i> , using the <i>⟨conditional⟩</i> to compare items, and leaves the result in the input stream. The <i>⟨conditional⟩</i> should have signature <code>:nnTF</code> , and return <code>true</code> if the two items being compared should be left in the same order, and <code>false</code> if the items should be swapped. The details of sorting comparison are described in Section 1.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

9 The first token from a token list

Functions which deal with either only the very first item (balanced text or single normal token) in a token list, or the remaining tokens.

<code>\tl_head:N</code>	★	<code>\tl_head:n {⟨token list⟩}</code>
<code>\tl_head:n</code>	★	
<code>\tl_head:(V v f)</code>	★	Leaves in the input stream the first <i>⟨item⟩</i> in the <i>⟨token list⟩</i> , discarding the rest of the <i>⟨token list⟩</i> . All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded; for example
Updated: 2012-09-09		

`\tl_head:n { abc }`

and

`\tl_head:n { ~ abc }`

both leave `a` in the input stream. If the “head” is a brace group, rather than a single token, the braces are removed, and so

`\tl_head:n { ~ { ~ ab } c }`

yields `▯ab`. A blank *⟨token list⟩* (see `\tl_if_blank:nTF`) results in `\tl_head:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_head:w</code>	★	<code>\tl_head:w ⟨token list⟩ { } \q_stop</code>
-------------------------	---	--

Leaves in the input stream the first *⟨item⟩* in the *⟨token list⟩*, discarding the rest of the *⟨token list⟩*. All leading explicit space characters (explicit tokens with character code 32 and category code 10) are discarded. A blank *⟨token list⟩* (which consists only of space characters) results in a low-level TeX error, which may be avoided by the inclusion of an empty group in the input (as shown), without the need for an explicit test. Alternatively, `\tl_if_blank:nF` may be used to avoid using the function with a “blank” argument. This function requires only a single expansion, and thus is suitable for use within an *o*-type expansion. In general, `\tl_head:n` should be preferred if the number of expansions is not critical.

<code>\tl_tail:N</code>	★	<code>\tl_tail:n {⟨token list⟩}</code>
<code>\tl_tail:n</code>	★	
<code>\tl_tail:(V v f)</code>	★	Discards all leading explicit space characters (explicit tokens with character code 32 and category code 10) and the first <i>⟨item⟩</i> in the <i>⟨token list⟩</i> , and leaves the remaining tokens in the input stream. Thus for example
Updated: 2012-09-01		

`\tl_tail:n { a ~ {bc} d }`

and

`\tl_tail:n { ~ a ~ {bc} d }`

both leave `▯{bc}d` in the input stream. A blank *⟨token list⟩* (see `\tl_if_blank:nTF`) results in `\tl_tail:n` leaving nothing in the input stream.

TeXhackers note: The result is returned within `\exp_not:n`, which means that the token list does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_if_head_eq_catcode_p:nN</code>	★	<code>\tl_if_head_eq_catcode_p:nN {<token list>} <test token></code>
<code>\tl_if_head_eq_catcode:nNTF</code>	★	<code>\tl_if_head_eq_catcode:nNTF {<token list>} <test token></code>
		<code>{<true code>} {<false code>}</code>

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same category code as the *<test token>*. In the case where the *<token list>* is empty, the test is always **false**.

<code>\tl_if_head_eq_charcode_p:nN</code>	★	<code>\tl_if_head_eq_charcode_p:nN {<token list>} <test token></code>
<code>\tl_if_head_eq_charcode_p:fN</code>	★	<code>\tl_if_head_eq_charcode:nNTF {<token list>} <test token></code>
<code>\tl_if_head_eq_charcode:nNTF</code>	★	<code>{<true code>} {<false code>}</code>
<code>\tl_if_head_eq_charcode:fNTF</code>	★	

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same character code as the *<test token>*. In the case where the *<token list>* is empty, the test is always **false**.

<code>\tl_if_head_eq_meaning_p:nN</code>	★	<code>\tl_if_head_eq_meaning_p:nN {<token list>} <test token></code>
<code>\tl_if_head_eq_meaning:nNTF</code>	★	<code>\tl_if_head_eq_meaning:nNTF {<token list>} <test token></code>
		<code>{<true code>} {<false code>}</code>

Updated: 2012-07-09

Tests if the first *<token>* in the *<token list>* has the same meaning as the *<test token>*. In the case where *<token list>* is empty, the test is always **false**.

<code>\tl_if_head_is_group_p:n</code>	★	<code>\tl_if_head_is_group_p:n {<token list>}</code>
<code>\tl_if_head_is_group:nTF</code>	★	<code>\tl_if_head_is_group:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2012-07-08

Tests if the first *<token>* in the *<token list>* is an explicit begin-group character (with category code 1 and any character code), in other words, if the *<token list>* starts with a brace group. In particular, the test is **false** if the *<token list>* starts with an implicit token such as `\c_group_begin_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

<code>\tl_if_head_is_N_type_p:n</code>	★	<code>\tl_if_head_is_N_type_p:n {<token list>}</code>
<code>\tl_if_head_is_N_type:nTF</code>	★	<code>\tl_if_head_is_N_type:nTF {<token list>} {<true code>} {<false code>}</code>

New: 2012-07-08

Tests if the first *<token>* in the *<token list>* is a normal N-type argument. In other words, it is neither an explicit space character (explicit token with character code 32 and category code 10) nor an explicit begin-group character (with category code 1 and any character code). An empty argument yields **false**, as it does not have a “normal” first token. This function is useful to implement actions on token lists on a token by token basis.

<code>\tl_if_head_is_space_p:n</code>	★	<code>\tl_if_head_is_space_p:n {<token list>}</code>
<code>\tl_if_head_is_space:nTF</code>	★	<code>\tl_if_head_is_space:nTF {<token list>} {<true code>} {<false code>}</code>

Updated: 2012-07-08

Tests if the first *<token>* in the *<token list>* is an explicit space character (explicit token with character code 12 and category code 10). In particular, the test is **false** if the *<token list>* starts with an implicit token such as `\c_space_token`, or if it is empty. This function is useful to implement actions on token lists on a token by token basis.

10 Using a single item

<code>\tl_item:nn</code> ★	<code>\tl_item:nn {(token list)} {(integer expression)}</code>
<code>\tl_item:Nn</code> ★	Indexing items in the $\langle token list \rangle$ from 1 on the left, this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the $\langle token list \rangle$ in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the right of the token list, starting at -1 for the right-most item. If the index is out of bounds, then the function expands to nothing.
<code>\tl_item:cn</code> ★	

New: 2014-07-17

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_rand_item:N</code> ★	<code>\tl_rand_item:N {tl var}</code>
<code>\tl_rand_item:c</code> ★	<code>\tl_rand_item:n {(token list)}</code>
<code>\tl_rand_item:n</code> ★	Selects a pseudo-random item of the $\langle token list \rangle$. If the $\langle token list \rangle$ is blank, the result is empty. This is not available in older versions of XeTeX.

New: 2016-12-06

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an `x`-type argument expansion.

<code>\tl_range:Nnn</code> ★ <code>\tl_range:nnn</code> ★	<code>\tl_range:Nnn <tl var> {<start index>} {<end index>}</code> <code>\tl_range:nnn {<token list>} {<start index>} {<end index>}</code>
--	--

New: 2017-02-17
Updated: 2017-07-15

Leaves in the input stream the items from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive. Spaces and braces are preserved between the items returned (but never at either end of the list).

Here $\langle start\ index \rangle$ and $\langle end\ index \rangle$ should be integer denotations. For describing in detail the functions' behavior, let m and n be the start and end index respectively. If either is 0, the result is empty. A positive index means 'start counting from the left end', a negative index means 'start counting from the right end'. Let l be the count of the token list.

The *actual start point* is determined as $M = m$ if $m > 0$ and as $M = l + m + 1$ if $m < 0$. Similarly the *actual end point* is $N = n$ if $n > 0$ and $N = l + n + 1$ if $n < 0$. If $M > N$, the result is empty. Otherwise it consists of all items from position M to position N inclusive; for the purpose of this rule, we can imagine that the token list extends at infinity on either side, with void items at positions s for $s \leq 0$ or $s > l$.

Spaces in between items in the actual range are preserved. Spaces at either end of the token list will be removed anyway (think to the token list being passed to `\tl_trim_spaces:n` to begin with).

Thus, with $l = 7$ as in the examples below, all of the following are equivalent and result in the whole token list

```
\tl_range:nnn { abcd~{e{}}fg } { 1 } { 7 }
\tl_range:nnn { abcd~{e{}}fg } { 1 } { 12 }
\tl_range:nnn { abcd~{e{}}fg } { -7 } { 7 }
\tl_range:nnn { abcd~{e{}}fg } { -12 } { 7 }
```

Here are some more interesting examples. The calls

```
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { 2 } { 5 } }
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { 2 } { -3 } }
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { -6 } { 5 } }
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { -6 } { -3 } }
```

are all equivalent and will print `bcd{e{}}` on the terminal; similarly

```
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { 2 } { 5 } }
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { 2 } { -3 } }
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { -6 } { 5 } }
\iow_term:x { \tl_range:nnn { abcd~{e{}}fg } { -6 } { -3 } }
```

are all equivalent and will print `bcd {e{}}` on the terminal (note the space in the middle). To the contrary,

```
\tl_range:nnn { abcd~{e{}}f } { 2 } { 4 }
```

will discard the space after 'd'.

If we want to get the items from the third to the last, the call is `\tl_range:nnn { <tl> } { 3 } { -`. Similarly, for discarding the last item, we can do `\tl_range:nnn { <tl> } { 1 } { -2 }`.

The behavior of `\tl_range:Nnn` is exactly the same, acting on the contents of the `tl` variable.

For improved performance, see `\tl_range_braced:nnn` and `\tl_range_unbraced:nnn`.

T_EXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an `x`-type argument expansion.

11 Viewing token lists

`\tl_show:N`
`\tl_show:c`

Updated: 2015-08-01

`\tl_show:N <tl var>`

Displays the content of the `<tl var>` on the terminal.

T_EXhackers note: This is similar to the T_EX primitive `\show`, wrapped to a fixed number of characters per line.

`\tl_show:n`

Updated: 2015-08-07

`\tl_show:n {(token list)}`

Displays the `<token list>` on the terminal.

T_EXhackers note: This is similar to the ϵ -T_EX primitive `\showtokens`, wrapped to a fixed number of characters per line.

`\tl_log:N`
`\tl_log:c`

New: 2014-08-22
Updated: 2015-08-01

`\tl_log:N <tl var>`

Writes the content of the `<tl var>` in the log file. See also `\tl_show:N` which displays the result in the terminal.

`\tl_log:n`

New: 2014-08-22
Updated: 2015-08-07

`\tl_log:n {(token list)}`

Writes the `<token list>` in the log file. See also `\tl_show:n` which displays the result in the terminal.

12 Constant token lists

`\c_empty_tl`

Constant that is always empty.

`\c_novalue_tl`

New: 2017-11-14

A marker for the absence of an argument. This constant `tl` can safely be typeset (*cf.* `\q_nil`), with the result being `-NoValue-`. It is important to note that `\c_novalue_tl` is constructed such that it will *not* match the simple text input `-NoValue-`, *i.e.* that

`\tl_if_eq:VnTF \c_novalue_tl { -NoValue- }`

is logically **false**. The `\c_novalue_tl` marker is intended for use in creating document-level interfaces, where it serves as an indicator that an (optional) argument was omitted. In particular, it is distinct from a simple empty `tl`.

`\c_space_tl`

An explicit space character contained in a token list (compare this with `\c_space_token`). For use where an explicit space is required.

13 Scratch token lists

<code>\l_tmpa_tl</code>	Scratch token lists for local assignment. These are never used by the kernel code, and so are safe for use with any <code>L^AT_EX3</code> -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_tl</code>	

<code>\g_tmpa_tl</code>	Scratch token lists for global assignment. These are never used by the kernel code, and so are safe for use with any <code>L^AT_EX3</code> -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_tl</code>	

Part VII

The l3str package: Strings

TeX associates each character with a category code: as such, there is no concept of a “string” as commonly understood in many other programming languages. However, there are places where we wish to manipulate token lists while in some sense “ignoring” category codes: this is done by treating token lists as strings in a TeX sense.

A TeX string (and thus an expl3 string) is a series of characters which have category code 12 (“other”) with the exception of space characters which have category code 10 (“space”). Thus at a technical level, a TeX string is a token list with the appropriate category codes. In this documentation, these are simply referred to as strings.

String variables are simply specialised token lists, but by convention should be named with the suffix `...str`. Such variables should contain characters with category code 12 (other), except spaces, which have category code 10 (blank space). All the functions in this module which accept a token list argument first convert it to a string using `\tl_to_str:n` for internal processing, and do not treat a token list or the corresponding string representation differently.

As a string is a subset of the more general token list, it is sometimes unclear when one should be used over the other. Use a string variable for data that isn’t primarily intended for typesetting and for which a level of protection from unwanted expansion is suitable. This data type simplifies comparison of variables since there are no concerns about expansion of their contents.

The functions `\cs_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N` and `\token_to_str:N` (and variants) generate strings from the appropriate input: these are documented in `l3basics`, `l3tl` and `l3token`, respectively.

Most expandable functions in this module come in three flavours:

- `\str_...:N`, which expect a token list or string variable as their argument;
- `\str_...:n`, taking any token list (or string) as an argument;
- `\str_..._ignore_spaces:n`, which ignores any space encountered during the operation: these functions are typically faster than those which take care of escaping spaces appropriately.

1 Building strings

`\str_new:N``\str_new:c`

New: 2015-09-18

`\str_new:N <str var>`

Creates a new `<str var>` or raises an error if the name is already taken. The declaration is global. The `<str var>` is initially empty.

`\str_const:Nn``\str_const:(NV|Nx|cn|cV|cx)`

New: 2015-09-18Updated: 2018-07-28

`\str_const:Nn <str var> {<token list>}`

Creates a new constant `<str var>` or raises an error if the name is already taken. The value of the `<str var>` is set globally to the `<token list>`, converted to a string.

<code>\str_clear:N</code>	<code>\str_clear:N</code> $\langle str\ var \rangle$
<code>\str_clear:c</code>	
<code>\str_gclear:N</code>	Clears the content of the $\langle str\ var \rangle$.
<code>\str_gclear:c</code>	
<hr/>	
New: 2015-09-18	

<code>\str_clear_new:N</code>	<code>\str_clear_new:N</code> $\langle str\ var \rangle$
<code>\str_clear_new:c</code>	
	Ensures that the $\langle str\ var \rangle$ exists globally by applying <code>\str_new:N</code> if necessary, then applies <code>\str_(g)clear:N</code> to leave the $\langle str\ var \rangle$ empty.
<hr/>	
New: 2015-09-18	

<code>\str_set_eq:NN</code>	<code>\str_set_eq:NN</code> $\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$
<code>\str_set_eq:(cN Nc cc)</code>	
<code>\str_gset_eq:NN</code>	Sets the content of $\langle str\ var_1 \rangle$ equal to that of $\langle str\ var_2 \rangle$.
<code>\str_gset_eq:(cN Nc cc)</code>	
<hr/>	
New: 2015-09-18	

<code>\str_concat:NNN</code>	<code>\str_concat:NNN</code> $\langle str\ var_1 \rangle$ $\langle str\ var_2 \rangle$ $\langle str\ var_3 \rangle$
<code>\str_concat:ccc</code>	
<code>\str_gconcat:NNN</code>	Concatenates the content of $\langle str\ var_2 \rangle$ and $\langle str\ var_3 \rangle$ together and saves the result in $\langle str\ var_1 \rangle$. The $\langle str\ var_2 \rangle$ is placed at the left side of the new string variable. The $\langle str\ var_2 \rangle$ and $\langle str\ var_3 \rangle$ must indeed be strings, as this function does not convert their contents to a string.
<code>\str_gconcat:ccc</code>	
<hr/>	
New: 2017-10-08	

2 Adding data to string variables

<code>\str_set:Nn</code>	<code>\str_set:Nn</code> $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
<code>\str_set:(NV Nx cn cV cx)</code>	
<code>\str_gset:Nn</code>	Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and stores the result in $\langle str\ var \rangle$.
<code>\str_gset:(NV Nx cn cV cx)</code>	
<hr/>	
New: 2015-09-18	
Updated: 2018-07-28	

<code>\str_put_left:Nn</code>	<code>\str_put_left:Nn</code> $\langle str\ var \rangle$ $\{ \langle token\ list \rangle \}$
<code>\str_put_left:(NV Nx cn cV cx)</code>	
<code>\str_gput_left:Nn</code>	
<code>\str_gput_left:(NV Nx cn cV cx)</code>	
<hr/>	
New: 2015-09-18	
Updated: 2018-07-28	

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and prepends the result to $\langle str\ var \rangle$. The current contents of the $\langle str\ var \rangle$ are not automatically converted to a string.

<code>\str_put_right:Nn</code>	<code>\str_put_right:Nn <str var> {(token list)}</code>
<code>\str_put_right:(NV Nx cn cV cx)</code>	
<code>\str_gput_right:Nn</code>	
<code>\str_gput_right:(NV Nx cn cV cx)</code>	

New: 2015-09-18

Updated: 2018-07-28

Converts the $\langle token list \rangle$ to a $\langle string \rangle$, and appends the result to $\langle str var \rangle$. The current contents of the $\langle str var \rangle$ are not automatically converted to a string.

3 Modifying string variables

<code>\str_replace_once:Nnn</code>	<code>\str_replace_once:Nnn <str var> {<old>} {<new>}</code>
<code>\str_replace_once:cnn</code>	
<code>\str_greplace_once:Nnn</code>	
<code>\str_greplace_once:cnn</code>	

New: 2017-10-08

Converts the $\langle old \rangle$ and $\langle new \rangle$ token lists to strings, then replaces the first (leftmost) occurrence of $\langle old string \rangle$ in the $\langle str var \rangle$ with $\langle new string \rangle$.

<code>\str_replace_all:Nnn</code>	<code>\str_replace_all:Nnn <str var> {<old>} {<new>}</code>
<code>\str_replace_all:cnn</code>	
<code>\str_greplace_all:Nnn</code>	
<code>\str_greplace_all:cnn</code>	

New: 2017-10-08

Converts the $\langle old \rangle$ and $\langle new \rangle$ token lists to strings, then replaces all occurrences of $\langle old string \rangle$ in the $\langle str var \rangle$ with $\langle new string \rangle$. As this function operates from left to right, the pattern $\langle old string \rangle$ may remain after the replacement (see `\str_remove_all:Nn` for an example).

<code>\str_remove_once:Nn</code>	<code>\str_remove_once:Nn <str var> {(token list)}</code>
<code>\str_remove_once:cn</code>	
<code>\str_gremove_once:Nn</code>	
<code>\str_gremove_once:cn</code>	

New: 2017-10-08

Converts the $\langle token list \rangle$ to a $\langle string \rangle$ then removes the first (leftmost) occurrence of $\langle string \rangle$ from the $\langle str var \rangle$.

<code>\str_remove_all:Nn</code>	<code>\str_remove_all:Nn <str var> {(token list)}</code>
<code>\str_remove_all:cn</code>	
<code>\str_gremove_all:Nn</code>	
<code>\str_gremove_all:cn</code>	

New: 2017-10-08

Converts the $\langle token list \rangle$ to a $\langle string \rangle$ then removes all occurrences of $\langle string \rangle$ from the $\langle str var \rangle$. As this function operates from left to right, the pattern $\langle string \rangle$ may remain after the removal, for instance,

```
\str_set:Nn \l_tmpa_str {abbccd} \str_remove_all:Nn \l_tmpa_str
{bc}
```

results in `\l_tmpa_str` containing `abcd`.

4 String conditionals

<code>\str_if_exist_p:N</code> ★	<code>\str_if_exist_p:N <str var></code>
<code>\str_if_exist_p:c</code> ★	<code>\str_if_exist:NTF <str var> {(true code)} {(false code)}</code>
<code>\str_if_exist:NTF</code> ★	
<code>\str_if_exist:cTF</code> ★	

New: 2015-09-18

Tests whether the $\langle str var \rangle$ is currently defined. This does not check that the $\langle str var \rangle$ really is a string.

<code>\str_if_empty_p:N</code>	★	<code>\str_if_empty_p:N <str var></code>
<code>\str_if_empty_p:c</code>	★	<code>\str_if_empty:NNTF <str var> {<true code>} {<false code>}</code>
<code>\str_if_empty:NNTF</code>	★	Tests if the <i><string variable></i> is entirely empty (<i>i.e.</i> contains no characters at all).
<code>\str_if_empty:cTF</code>	★	

New: 2015-09-18

<code>\str_if_eq_p:NN</code>	★	<code>\str_if_eq_p:NN <str var₁> <str var₂></code>
<code>\str_if_eq_p:(Nc cN cc)</code>	★	<code>\str_if_eq:NNTF <str var₁> <str var₂> {<true code>} {<false code>}</code>
<code>\str_if_eq:NNTF</code>	★	Compares the content of two <i><str variables></i> and is logically true if the two contain the same characters in the same order.
<code>\str_if_eq:(Nc cN cc)TF</code>	★	

New: 2015-09-18

<code>\str_if_eq_p:nn</code>	★	<code>\str_if_eq_p:nn {<tl₁>} {<tl₂>}</code>
<code>\str_if_eq_p:(Vn on no nV VV vn nv)</code>	★	<code>\str_if_eq:nnTF {<tl₁>} {<tl₂>} {<true code>} {<false code>}</code>
<code>\str_if_eq:nnTF</code>	★	
<code>\str_if_eq:(Vn on no nV VV vn nv)TF</code>	★	
<code>\str_if_eq_p:ee</code>	★	
<code>\str_if_eq:eeTF</code>	★	

Updated: 2018-06-18

Compares the two *<token lists>* on a character by character basis (namely after converting them to strings), and is **true** if the two *<strings>* contain the same characters in the same order. Thus for example

`\str_if_eq_p:no { abc } { \tl_to_str:n { abc } }`

is logically **true**.

<code>\str_if_in:NnTF</code>	★	<code>\str_if_in:NnTF <str var> {<token list>} {<true code>} {<false code>}</code>
<code>\str_if_in:cnTF</code>	★	Converts the <i><token list></i> to a <i><string></i> and tests if that <i><string></i> is found in the content of the <i><str var></i> .

New: 2017-10-08

<code>\str_if_in:nnTF</code>	★	<code>\str_if_in:nnTF <tl₁> {<tl₂>} {<true code>} {<false code>}</code>
		Converts both <i><token lists></i> to <i><strings></i> and tests whether <i><string_{2 is found inside <i><string_{1.}</i>}</i>

New: 2017-10-08

<code>\str_case:nn</code> ★	<code>\str_case:nnTF {⟨test string⟩}</code>
<code>\str_case:(on nV nv)</code> ★	{
<code>\str_case:nnTF</code> ★	{⟨string case ₁ ⟩} {⟨code case ₁ ⟩}
<code>\str_case:(on nV nv)TF</code> ★	{⟨string case ₂ ⟩} {⟨code case ₂ ⟩}
	...
	{⟨string case _n ⟩} {⟨code case _n ⟩}
	}
	{⟨true code⟩}
	{⟨false code⟩}

New: 2013-07-24
Updated: 2015-02-28

Compares the *⟨test string⟩* in turn with each of the *⟨string cases⟩* (all token lists are converted to strings). If the two are equal (as described for `\str_if_eq:nnTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case:nn`, which does nothing if there is no match, is also available.

<code>\str_case_e:nn</code> ★	<code>\str_case_e:nnTF {⟨test string⟩}</code>
<code>\str_case_e:nnTF</code> ★	{
	{⟨string case ₁ ⟩} {⟨code case ₁ ⟩}
	{⟨string case ₂ ⟩} {⟨code case ₂ ⟩}
	...
	{⟨string case _n ⟩} {⟨code case _n ⟩}
	}
	{⟨true code⟩}
	{⟨false code⟩}

New: 2018-06-19

Compares the full expansion of the *⟨test string⟩* in turn with the full expansion of the *⟨string cases⟩* (all token lists are converted to strings). If the two full expansions are equal (as described for `\str_if_eq:nnTF`) then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\str_case_e:nn`, which does nothing if there is no match, is also available. The *⟨test string⟩* is expanded in each comparison, and must always yield the same result: for example, random numbers must not be used within this string.

5 Mapping to strings

<code>\str_map_function:NN</code> ★	<code>\str_map_function:NN ⟨str var⟩ ⟨function⟩</code>
<code>\str_map_function:cN</code> ★	Applies <i>⟨function⟩</i> to every <i>⟨character⟩</i> in the <i>⟨str var⟩</i> including spaces. See also <code>\str_map_function:nN</code> .
<code>\str_map_function:nN</code> ★	<code>\str_map_function:nN {⟨token list⟩} ⟨function⟩</code>
	Converts the <i>⟨token list⟩</i> to a <i>⟨string⟩</i> then applies <i>⟨function⟩</i> to every <i>⟨character⟩</i> in the <i>⟨string⟩</i> including spaces. See also <code>\str_map_function:NN</code> .

New: 2017-11-14

New: 2017-11-14

<hr/> <code>\str_map_inline:Nn</code> <code>\str_map_inline:cn</code> <hr/> New: 2017-11-14	<code>\str_map_inline:Nn <str var> {<inline function>}</code> Applies the <i><inline function></i> to every <i><character></i> in the <i><str var></i> including spaces. The <i><inline function></i> should consist of code which receives the <i><character></i> as #1. See also <code>\str_map_function:NN</code> .
<hr/> <code>\str_map_inline:nn</code> <hr/> New: 2017-11-14	<code>\str_map_inline:nn {<token list>} {<inline function>}</code> Converts the <i><token list></i> to a <i><string></i> then applies the <i><inline function></i> to every <i><character></i> in the <i><string></i> including spaces. The <i><inline function></i> should consist of code which receives the <i><character></i> as #1. See also <code>\str_map_function:NN</code> .
<hr/> <code>\str_map_variable:NNn</code> <code>\str_map_variable:cNn</code> <hr/> New: 2017-11-14	<code>\str_map_variable:NNn <str var> <variable> {<code>}</code> Stores each <i><character></i> of the <i><string></i> (including spaces) in turn in the (string or token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\str_map_inline:Nn</code> .
<hr/> <code>\str_map_variable:nNn</code> <hr/> New: 2017-11-14	<code>\str_map_variable:nNn {<token list>} <variable> {<code>}</code> Converts the <i><token list></i> to a <i><string></i> then stores each <i><character></i> in the <i><string></i> (including spaces) in turn in the (string or token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. See also <code>\str_map_inline:Nn</code> .
<hr/> <code>\str_map_break: ☆</code> <hr/> New: 2017-10-08	<code>\str_map_break:</code> Used to terminate a <code>\str_map...</code> function before all characters in the <i><string></i> have been processed. This normally takes place within a conditional statement, for example <pre> \str_map_inline:Nn \l_my_str { \str_if_eq:nnT { #1 } { bingo } { \str_map_break: } % Do something useful } </pre> <p>See also <code>\str_map_break:n</code>. Use outside of a <code>\str_map...</code> scenario leads to low level \TeX errors.</p> <p>\TeXhackers note: When the mapping is broken, additional tokens may be inserted before continuing with the code that follows the loop. This depends on the design of the mapping function.</p>

`\str_map_break:n` ☆

New: 2017-10-08

`\str_map_break:n {⟨code⟩}`

Used to terminate a `\str_map...` function before all characters in the *⟨string⟩* have been processed, inserting the *⟨code⟩* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\str_map_inline:Nn \l_my_str
{
  \str_if_eq:nnT { #1 } { bingo }
  { \str_map_break:n { <code> } }
  % Do something useful
}
```

Use outside of a `\str_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *⟨code⟩* is inserted into the input stream. This depends on the design of the mapping function.

6 Working with the content of strings

`\str_use:N` ☆

`\str_use:c` ☆

New: 2015-09-18

`\str_use:N ⟨str var⟩`

Recovers the content of a *⟨str var⟩* and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Note that it is possible to use a *⟨str⟩* directly without an accessor function.

`\str_count:N`

☆ `\str_count:n {⟨token list⟩}`

`\str_count:c`

☆

`\str_count:n`

☆

`\str_count_ignore_spaces:n` ☆

New: 2015-09-18

Leaves in the input stream the number of characters in the string representation of *⟨token list⟩*, as an integer denotation. The functions differ in their treatment of spaces. In the case of `\str_count:N` and `\str_count:n`, all characters including spaces are counted. The `\str_count_ignore_spaces:n` function leaves the number of non-space characters in the input stream.

`\str_count_spaces:N` ☆

`\str_count_spaces:c` ☆

`\str_count_spaces:n` ☆

New: 2015-09-18

`\str_count_spaces:n {⟨token list⟩}`

Leaves in the input stream the number of space characters in the string representation of *⟨token list⟩*, as an integer denotation. Of course, this function has no `_ignore_spaces` variant.

<code>\str_head:N</code>	★	<code>\str_head:n {⟨token list⟩}</code>
<code>\str_head:c</code>	★	
<code>\str_head:n</code>	★	
<code>\str_head_ignore_spaces:n</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ into a $\langle string \rangle$. The first character in the $\langle string \rangle$ is then left in the input stream, with category code “other”. The functions differ if the first character is a space: `\str_head:N` and `\str_head:n` return a space token with category code 10 (blank space), while the `\str_head_ignore_spaces:n` function ignores this space character and leaves the first non-space character in the input stream. If the $\langle string \rangle$ is empty (or only contains spaces in the case of the `_ignore_spaces` function), then nothing is left on the input stream.

<code>\str_tail:N</code>	★	<code>\str_tail:n {⟨token list⟩}</code>
<code>\str_tail:c</code>	★	
<code>\str_tail:n</code>	★	
<code>\str_tail_ignore_spaces:n</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, removes the first character, and leaves the remaining characters (if any) in the input stream, with category codes 12 and 10 (for spaces). The functions differ in the case where the first character is a space: `\str_tail:N` and `\str_tail:n` only trim that space, while `\str_tail_ignore_spaces:n` removes the first non-space character and any space before it. If the $\langle token\ list \rangle$ is empty (or blank in the case of the `_ignore_spaces` variant), then nothing is left on the input stream.

<code>\str_item:Nn</code>	★	<code>\str_item:nn {⟨token list⟩} {⟨integer expression⟩}</code>
<code>\str_item:nn</code>	★	
<code>\str_item_ignore_spaces:nn</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the character in position $\langle integer\ expression \rangle$ of the $\langle string \rangle$, starting at 1 for the first (left-most) character. In the case of `\str_item:Nn` and `\str_item:nn`, all characters including spaces are taken into account. The `\str_item_ignore_spaces:nn` function skips spaces when counting characters. If the $\langle integer\ expression \rangle$ is negative, characters are counted from the end of the $\langle string \rangle$. Hence, -1 is the right-most character, *etc.*

<code>\str_range:Nnn</code>	★	<code>\str_range:nnn {⟨token list⟩} {⟨start index⟩} {⟨end index⟩}</code>
<code>\str_range:cnn</code>	★	
<code>\str_range:nnn</code>	★	
<code>\str_range_ignore_spaces:nnn</code>	★	

New: 2015-09-18

Converts the $\langle token\ list \rangle$ to a $\langle string \rangle$, and leaves in the input stream the characters from the $\langle start\ index \rangle$ to the $\langle end\ index \rangle$ inclusive. Spaces are preserved and counted as items (contrast this with `\tl_range:nnn` where spaces are not counted as items and are possibly discarded from the output).

Here $\langle start\ index \rangle$ and $\langle end\ index \rangle$ should be integer denotations. For describing in detail the functions' behavior, let m and n be the start and end index respectively. If either is 0, the result is empty. A positive index means 'start counting from the left end', a negative index means 'start counting from the right end'. Let l be the count of the token list.

The *actual start point* is determined as $M = m$ if $m > 0$ and as $M = l + m + 1$ if $m < 0$. Similarly the *actual end point* is $N = n$ if $n > 0$ and $N = l + n + 1$ if $n < 0$. If $M > N$, the result is empty. Otherwise it consists of all items from position M to position N inclusive; for the purpose of this rule, we can imagine that the token list extends at infinity on either side, with void items at positions s for $s \leq 0$ or $s > l$. For instance,

```
\iow_term:x { \str_range:nnn { abcdef } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdef } { -4 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { -2 } { -1 } }
\iow_term:x { \str_range:nnn { abcdef } { 0 } { -1 } }
```

prints bcde, cdef, ef, and an empty line to the terminal. The $\langle start\ index \rangle$ must always be smaller than or equal to the $\langle end\ index \rangle$: if this is not the case then no output is generated. Thus

```
\iow_term:x { \str_range:nnn { abcdef } { 5 } { 2 } }
\iow_term:x { \str_range:nnn { abcdef } { -1 } { -4 } }
```

both yield empty strings.

The behavior of `\str_range_ignore_spaces:nnn` is similar, but spaces are removed before starting the job. The input

```
\iow_term:x { \str_range:nnn { abcdefg } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abcdefg } { 2 } { -3 } }
\iow_term:x { \str_range:nnn { abcdefg } { -6 } { 5 } }
\iow_term:x { \str_range:nnn { abcdefg } { -6 } { -3 } }

\iow_term:x { \str_range:nnn { abc~efg } { 2 } { 5 } }
\iow_term:x { \str_range:nnn { abc~efg } { 2 } { -3 } }
\iow_term:x { \str_range:nnn { abc~efg } { -6 } { 5 } }
\iow_term:x { \str_range:nnn { abc~efg } { -6 } { -3 } }

\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { 2 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { 2 } { -3 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { -6 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcdefg } { -6 } { -3 } }

\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { 2 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { 2 } { -3 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { -6 } { 5 } }
\iow_term:x { \str_range_ignore_spaces:nnn { abcd~efg } { -6 } { -3 } }
```

will print four instances of bcde, four instances of bc e and eight instances of bcde.

7 String manipulation

<code>\str_lower_case:n</code>	★	<code>\str_lower_case:n {⟨tokens⟩}</code>
<code>\str_lower_case:f</code>	★	<code>\str_upper_case:n {⟨tokens⟩}</code>
<code>\str_upper_case:n</code>	★	
<code>\str_upper_case:f</code>	★	

New: 2015-03-01

Converts the input `⟨tokens⟩` to their string representation, as described for `\tl_to_str:n`, and then to the lower or upper case representation using a one-to-one mapping as described by the Unicode Consortium file `UnicodeData.txt`.

These functions are intended for case changing programmatic data in places where upper/lower case distinctions are meaningful. One example would be automatically generating a function name from user input where some case changing is needed. In this situation the input is programmatic, not textual, case does have meaning and a language-independent one-to-one mapping is appropriate. For example

```
\cs_new_protected:Npn \myfunc:nn #1#2
{
  \cs_set_protected:cpn
  {
    user
    \str_upper_case:f { \tl_head:n {#1} }
    \str_lower_case:f { \tl_tail:n {#1} }
  }
  { #2 }
}
```

would be used to generate a function with an auto-generated name consisting of the upper case equivalent of the supplied name followed by the lower case equivalent of the rest of the input.

These functions should *not* be used for

- Caseless comparisons: use `\str_fold_case:n` for this situation (case folding is distinct from lower casing).
- Case changing text for typesetting: see the `\tl_lower_case:n(n)`, `\tl_upper_case:n(n)` and `\tl_mixed_case:n(n)` functions which correctly deal with context-dependence and other factors appropriate to text case changing.

TeXhackers note: As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfTeX *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both XeTeX and LuaTeX.

`\str_fold_case:n` ★ `\str_fold_case:n {(tokens)}`

`\str_fold_case:V` ★

New: 2014-06-19

Updated: 2016-03-07

Converts the input $\langle tokens \rangle$ to their string representation, as described for `\tl_to_str:n`, and then folds the case of the resulting $\langle string \rangle$ to remove case information. The result of this process is left in the input stream.

String folding is a process used for material such as identifiers rather than for “text”. The folding provided by `\str_fold_case:n` follows the mappings provided by the [Unicode Consortium](#), who [state](#):

Case folding is primarily used for caseless comparison of text, such as identifiers in a computer program, rather than actual text transformation. Case folding in Unicode is based on the lowercase mapping, but includes additional changes to the source text to help make it language-insensitive and consistent. As a result, case-folded text should be used solely for internal processing and generally should not be stored or displayed to the end user.

The folding approach implemented by `\str_fold_case:n` follows the “full” scheme defined by the Unicode Consortium (*e.g.* `SS` folds to `ss`). As case-folding is a language-insensitive process, there is no special treatment of Turkic input (*i.e.* `I` always folds to `i` and not to `ı`).

TeXhackers note: As with all `expl3` functions, the input supported by `\str_fold_case:n` is *engine-native* characters which are or interoperate with UTF-8. As such, when used with pdfTeX *only* the Latin alphabet characters A–Z are case-folded (*i.e.* the ASCII range which coincides with UTF-8). Full UTF-8 support is available with both XeTeX and LuaTeX, subject only to the fact that XeTeX in particular has issues with characters of code above hexadecimal 0xFFFF when interacting with `\tl_to_str:n`.

8 Viewing strings

`\str_show:N` `\str_show:N <str var>`

`\str_show:c`

`\str_show:n`

New: 2015-09-18

Displays the content of the $\langle str var \rangle$ on the terminal.

9 Constant token lists

`\c_ampersand_str`
`\c_atsign_str`
`\c_backslash_str`
`\c_left_brace_str`
`\c_right_brace_str`
`\c_circumflex_str`
`\c_colon_str`
`\c_dollar_str`
`\c_hash_str`
`\c_percent_str`
`\c_tilde_str`
`\c_underscore_str`

Constant strings, containing a single character token, with category code 12.

New: 2015-09-19

10 Scratch strings

`\l_tmpa_str`
`\l_tmpb_str`

Scratch strings for local assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_str`
`\g_tmpb_str`

Scratch strings for global assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part VIII

The l3quark package

Quarks

Two special types of constants in L^AT_EX3 are “quarks” and “scan marks”. By convention all constants of type quark start out with `\q_`, and scan marks start with `\s_`.

1 Quarks

Quarks are control sequences that expand to themselves and should therefore *never* be executed directly in the code. This would result in an endless loop!

They are meant to be used as delimiter in weird functions, the most common use case being the ‘stop token’ (*i.e.* `\q_stop`). For example, when writing a macro to parse a user-defined date

```
\date_parse:n {19/June/1981}
```

one might write a command such as

```
\cs_new:Npn \date_parse:n #1 { \date_parse_aux:w #1 \q_stop }
\cs_new:Npn \date_parse_aux:w #1 / #2 / #3 \q_stop
{ <do something with the date> }
```

Quarks are sometimes also used as error return values for functions that receive erroneous input. For example, in the function `\prop_get:NnN` to retrieve a value stored in some key of a property list, if the key does not exist then the return value is the quark `\q_no_value`. As mentioned above, such quarks are extremely fragile and it is imperative when using such functions that code is carefully written to check for pathological cases to avoid leakage of a quark into an uncontrolled environment.

Quarks also permit the following ingenious trick when parsing tokens: when you pick up a token in a temporary variable and you want to know whether you have picked up a particular quark, all you have to do is compare the temporary variable to the quark using `\tl_if_eq:NNTF`. A set of special quark testing functions is set up below. All the quark testing functions are expandable although the ones testing only single tokens are much faster. An example of the quark testing functions and their use in recursion can be seen in the implementation of `\clist_map_function:NN`.

2 Defining quarks

`\quark_new:N`

`\quark_new:N <quark>`

Creates a new `<quark>` which expands only to `<quark>`. The `<quark>` is defined globally, and an error message is raised if the name was already taken.

`\q_stop`

Used as a marker for delimited arguments, such as

```
\cs_set:Npn \tmp:w #1#2 \q_stop {#1}
```

<u><u>\q_mark</u></u>	Used as a marker for delimited arguments when <code>\q_stop</code> is already in use.
<u><u>\q_nil</u></u>	Quark to mark a null value in structured variables or functions. Used as an end delimiter when this may itself need to be tested (in contrast to <code>\q_stop</code> , which is only ever used as a delimiter).
<u><u>\q_no_value</u></u>	A canonical value for a missing value, when one is requested from a data structure. This is therefore used as a “return” value by functions such as <code>\prop_get:NnN</code> if there is no data to return.

3 Quark tests

The method used to define quarks means that the single token (N) tests are faster than the multi-token (n) tests. The latter should therefore only be used when the argument can definitely take more than a single token.

<u><u>\quark_if_nil_p:N</u></u> *	<code>\quark_if_nil_p:N <token></code>
<u><u>\quark_if_nil:NTF</u></u> *	<code>\quark_if_nil:NTF <token> {\true code} {\false code}</code>

Tests if the `<token>` is equal to `\q_nil`.

<u><u>\quark_if_nil_p:n</u></u> *	<code>\quark_if_nil_p:n {\token list}</code>
<u><u>\quark_if_nil_p:(o V)</u></u> *	<code>\quark_if_nil:nTF {\token list} {\true code} {\false code}</code>
<u><u>\quark_if_nil:nTF</u></u> *	Tests if the <code><token list></code> contains only <code>\q_nil</code> (distinct from <code><token list></code> being empty or containing <code>\q_nil</code> plus one or more other tokens).
<u><u>\quark_if_nil:(o V)TF</u></u> *	

<u><u>\quark_if_no_value_p:N</u></u> *	<code>\quark_if_no_value_p:N <token></code>
<u><u>\quark_if_no_value_p:c</u></u> *	<code>\quark_if_no_value:NTF <token> {\true code} {\false code}</code>
<u><u>\quark_if_no_value:NTF</u></u> *	Tests if the <code><token></code> is equal to <code>\q_no_value</code> .
<u><u>\quark_if_no_value:cTF</u></u> *	

<u><u>\quark_if_no_value_p:n</u></u> *	<code>\quark_if_no_value_p:n {\token list}</code>
<u><u>\quark_if_no_value:nTF</u></u> *	<code>\quark_if_no_value:nTF {\token list} {\true code} {\false code}</code>

Tests if the `<token list>` contains only `\q_no_value` (distinct from `<token list>` being empty or containing `\q_no_value` plus one or more other tokens).

4 Recursion

This module provides a uniform interface to intercepting and terminating loops as when one is doing tail recursion. The building blocks follow below and an example is shown in Section 5.

<u><u>\q_recursion_tail</u></u>	This quark is appended to the data structure in question and appears as a real element there. This means it gets any list separators around it.
<u><u>\q_recursion_stop</u></u>	This quark is added <i>after</i> the data structure. Its purpose is to make it possible to terminate the recursion at any point easily.

`\quark_if_recursion_tail_stop:N` `\quark_if_recursion_tail_stop:N <token>`

Tests if *<token>* contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

`\quark_if_recursion_tail_stop:n` `\quark_if_recursion_tail_stop:n {<token list>}`
`\quark_if_recursion_tail_stop:o`

Updated: 2011-09-06

Tests if the *<token list>* contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items.

`\quark_if_recursion_tail_stop_do:Nn` `\quark_if_recursion_tail_stop_do:Nn <token> {<insertion>}`

Tests if *<token>* contains only the marker `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The *<insertion>* code is then added to the input stream after the recursion has ended.

`\quark_if_recursion_tail_stop_do:nn` `\quark_if_recursion_tail_stop_do:nn {<token list>} {<insertion>}`
`\quark_if_recursion_tail_stop_do:on`

Updated: 2011-09-06

Tests if the *<token list>* contains only `\q_recursion_tail`, and if so uses `\use_none_delimit_by_q_recursion_stop:w` to terminate the recursion that this belongs to. The recursion input must include the marker tokens `\q_recursion_tail` and `\q_recursion_stop` as the last two items. The *<insertion>* code is then added to the input stream after the recursion has ended.

`\quark_if_recursion_tail_break:NN` `\quark_if_recursion_tail_break:nn {<token list>} \<type>_map_break:`
`\quark_if_recursion_tail_break:nN`

New: 2018-04-10

Tests if *<token list>* contains only `\q_recursion_tail`, and if so terminates the recursion using `\<type>_map_break:.` The recursion end should be marked by `\prg_break_point:Nn \<type>_map_break:.`

5 An example of recursion with quarks

Quarks are mainly used internally in the `expl3` code to define recursion functions such as `\tl_map_inline:nn` and so on. Here is a small example to demonstrate how to use quarks in this fashion. We shall define a command called `\my_map_dbl:nn` which takes a token list and applies an operation to every *pair* of tokens. For example, `\my_map_dbl:nn {abcd} {[--#1--#2--]} ~` would produce “`[-a-b-] [-c-d-]`”. Using quarks to define such functions simplifies their logic and ensures robustness in many cases.

Here's the definition of `\my_map_dbl:nn`. First of all, define the function that does the processing based on the inline function argument `#2`. Then initiate the recursion using an internal function. The token list `#1` is terminated using `\q_recursion_tail`, with delimiters according to the type of recursion (here a pair of `\q_recursion_tail`), concluding with `\q_recursion_stop`. These quarks are used to mark the end of the token list being operated upon.

```
\cs_new:Npn \my_map_dbl:nn #1#2
{
  \cs_set:Npn \__my_map_dbl_fn:nn ##1 ##2 {#2}
  \__my_map_dbl:nn #1 \q_recursion_tail \q_recursion_tail
  \q_recursion_stop
}
```

The definition of the internal recursion function follows. First check if either of the input tokens are the termination quarks. Then, if not, apply the inline function to the two arguments.

```
\cs_new:Nn \__my_map_dbl:nn
{
  \quark_if_recursion_tail_stop:n {#1}
  \quark_if_recursion_tail_stop:n {#2}
  \__my_map_dbl_fn:nn {#1} {#2}
}
```

Finally, recurse:

```
\__my_map_dbl:nn
}
```

Note that contrarily to L^AT_EX3 built-in mapping functions, this mapping function cannot be nested, since the second map would overwrite the definition of `__my_map_dbl_fn:nn`.

6 Scan marks

Scan marks are control sequences set equal to `\scan_stop:`, hence never expand in an expansion context and are (largely) invisible if they are encountered in a typesetting context.

Like quarks, they can be used as delimiters in weird functions and are often safer to use for this purpose. Since they are harmless when executed by T_EX in non-expandable contexts, they can be used to mark the end of a set of instructions. This allows to skip to that point if the end of the instructions should not be performed (see l3regex).

<code>\scan_new:N</code>	<code>\scan_new:N</code> <i><scan mark></i>
--------------------------	---

New: 2018-04-01	Creates a new <i><scan mark></i> which is set equal to <code>\scan_stop:</code> . The <i><scan mark></i> is defined globally, and an error message is raised if the name was already taken by another scan mark.
-----------------	--

<code>\s_stop</code>	Used at the end of a set of instructions, as a marker that can be jumped to using <code>\use_none_delimit_by_s_stop:w</code> .
----------------------	--

New: 2018-04-01

<code>\use_none_delimit_by_s_stop:w</code>	<code>\use_none_delimit_by_s_stop:w</code> $\langle tokens \rangle$ <code>\s_stop</code>
--	--

New: 2018-04-01

Removes the $\langle tokens \rangle$ and `\s_stop` from the input stream. This leads to a low-level T_EX error if `\s_stop` is absent.

Part IX

The l3seq package

Sequences and stacks

L^AT_EX3 implements a “sequence” data type, which contain an ordered list of entries which may contain any *⟨balanced text⟩*. It is possible to map functions to sequences such that the function is applied to every item in the sequence.

Sequences are also used to implement stack functions in L^AT_EX3. This is achieved using a number of dedicated stack functions.

1 Creating and initialising sequences

<code>\seq_new:N</code>	<code>\seq_new:N</code>
<code>\seq_new:c</code>	<code>\seq_new:c</code>

`\seq_new:N` *⟨sequence⟩*

Creates a new *⟨sequence⟩* or raises an error if the name is already taken. The declaration is global. The *⟨sequence⟩* initially contains no items.

<code>\seq_clear:N</code>	<code>\seq_clear:N</code>
<code>\seq_clear:c</code>	<code>\seq_clear:c</code>
<code>\seq_gclear:N</code>	<code>\seq_gclear:N</code>
<code>\seq_gclear:c</code>	<code>\seq_gclear:c</code>

`\seq_clear:N` *⟨sequence⟩*

Clears all items from the *⟨sequence⟩*.

<code>\seq_clear_new:N</code>	<code>\seq_clear_new:N</code>
<code>\seq_clear_new:c</code>	<code>\seq_clear_new:c</code>
<code>\seq_gclear_new:N</code>	<code>\seq_gclear_new:N</code>
<code>\seq_gclear_new:c</code>	<code>\seq_gclear_new:c</code>

`\seq_clear_new:N` *⟨sequence⟩*

Ensures that the *⟨sequence⟩* exists globally by applying `\seq_new:N` if necessary, then applies `\seq_(g)clear:N` to leave the *⟨sequence⟩* empty.

<code>\seq_set_eq:NN</code>	<code>\seq_set_eq:NN</code>
<code>\seq_set_eq:(cN Nc cc)</code>	<code>\seq_set_eq:(cN Nc cc)</code>
<code>\seq_gset_eq:NN</code>	<code>\seq_gset_eq:NN</code>
<code>\seq_gset_eq:(cN Nc cc)</code>	<code>\seq_gset_eq:(cN Nc cc)</code>

`\seq_set_eq:NN` *⟨sequence₁⟩* *⟨sequence₂⟩*

Sets the content of *⟨sequence₁⟩* equal to that of *⟨sequence₂⟩*.

<code>\seq_set_from_clist:NN</code>	<code>\seq_set_from_clist:NN</code>
<code>\seq_set_from_clist:(cN Nc cc)</code>	<code>\seq_set_from_clist:(cN Nc cc)</code>
<code>\seq_set_from_clist:Nn</code>	<code>\seq_set_from_clist:Nn</code>
<code>\seq_set_from_clist:cn</code>	<code>\seq_set_from_clist:cn</code>
<code>\seq_gset_from_clist:NN</code>	<code>\seq_gset_from_clist:NN</code>
<code>\seq_gset_from_clist:(cN Nc cc)</code>	<code>\seq_gset_from_clist:(cN Nc cc)</code>
<code>\seq_gset_from_clist:Nn</code>	<code>\seq_gset_from_clist:Nn</code>
<code>\seq_gset_from_clist:cn</code>	<code>\seq_gset_from_clist:cn</code>

`\seq_set_from_clist:NN` *⟨sequence⟩* *⟨comma-list⟩*

New: 2014-07-17

Converts the data in the *⟨comma list⟩* into a *⟨sequence⟩*: the original *⟨comma list⟩* is unchanged.

```
\seq_set_split:Nnn
\seq_set_split:NnV
\seq_gset_split:Nnn
\seq_gset_split:NnV
```

New: 2011-08-15
Updated: 2012-07-02

```
\seq_set_split:Nnn <sequence> {<delimiter>} {<token list>}
```

Splits the $\langle token list \rangle$ into $\langle items \rangle$ separated by $\langle delimiter \rangle$, and assigns the result to the $\langle sequence \rangle$. Spaces on both sides of each $\langle item \rangle$ are ignored, then one set of outer braces is removed (if any); this space trimming behaviour is identical to that of `l3clist` functions. Empty $\langle items \rangle$ are preserved by `\seq_set_split:Nnn`, and can be removed afterwards using `\seq_remove_all:Nn <sequence> {<>}`. The $\langle delimiter \rangle$ may not contain `{`, `}` or `#` (assuming \TeX 's normal category code régime). If the $\langle delimiter \rangle$ is empty, the $\langle token list \rangle$ is split into $\langle items \rangle$ as a $\langle token list \rangle$.

```
\seq_concat:NNN
\seq_concat:ccc
\seq_gconcat:NNN
\seq_gconcat:ccc
```

```
\seq_concat:NNN <sequence1> <sequence2> <sequence3>
```

Concatenates the content of $\langle sequence_2 \rangle$ and $\langle sequence_3 \rangle$ together and saves the result in $\langle sequence_1 \rangle$. The items in $\langle sequence_2 \rangle$ are placed at the left side of the new sequence.

```
\seq_if_exist_p:N *
\seq_if_exist_p:c *
\seq_if_exist:NTF *
\seq_if_exist:cTF *
```

New: 2012-03-03

```
\seq_if_exist_p:N <sequence>
```

```
\seq_if_exist:NNTF <sequence> {<true code>} {<false code>}
```

Tests whether the $\langle sequence \rangle$ is currently defined. This does not check that the $\langle sequence \rangle$ really is a sequence variable.

2 Appending data to sequences

```
\seq_put_left:Nn
\seq_put_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_left:Nn
\seq_gput_left:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
```

```
\seq_put_left:Nn <sequence> {<item>}
```

Appends the $\langle item \rangle$ to the left of the $\langle sequence \rangle$.

```
\seq_put_right:Nn
\seq_put_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
\seq_gput_right:Nn
\seq_gput_right:(NV|Nv|No|Nx|cn|cV|cv|co|cx)
```

```
\seq_put_right:Nn <sequence> {<item>}
```

Appends the $\langle item \rangle$ to the right of the $\langle sequence \rangle$.

3 Recovering items from sequences

Items can be recovered from either the left or the right of sequences. For implementation reasons, the actions at the left of the sequence are faster than those acting on the right. These functions all assign the recovered material locally, *i.e.* setting the $\langle token list variable \rangle$ used with `\tl_set:Nn` and *never* `\tl_gset:Nn`.

```
\seq_get_left:NN
\seq_get_left:cN
```

Updated: 2012-05-14

```
\seq_get_left:NN <sequence> <token list variable>
```

Stores the left-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker `\q_no_value`.

<code>\seq_get_right:NN</code> <code>\seq_get_right:cn</code> <hr/> Updated: 2012-05-19	<code>\seq_get_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Stores the right-most item from a $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token list variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
---	--

<code>\seq_pop_left:NN</code> <code>\seq_pop_left:cn</code> <hr/> Updated: 2012-05-14	<code>\seq_pop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
---	---

<code>\seq_gpop_left:NN</code> <code>\seq_gpop_left:cn</code> <hr/> Updated: 2012-05-14	<code>\seq_gpop_left:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
---	---

<code>\seq_pop_right:NN</code> <code>\seq_pop_right:cn</code> <hr/> Updated: 2012-05-19	<code>\seq_pop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
---	---

<code>\seq_gpop_right:NN</code> <code>\seq_gpop_right:cn</code> <hr/> Updated: 2012-05-19	<code>\seq_gpop_right:NN</code> $\langle sequence \rangle$ $\langle token list variable \rangle$ Pops the right-most item from a $\langle sequence \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the sequence and stores it in the $\langle token list variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local. If $\langle sequence \rangle$ is empty the $\langle token list variable \rangle$ is set to the special marker <code>\q_no_value</code> .
---	---

<code>\seq_item:Nn</code> ★ <code>\seq_item:cn</code> ★ <hr/> New: 2014-07-17	<code>\seq_item:Nn</code> $\langle sequence \rangle$ $\{ \langle integer expression \rangle \}$ Indexing items in the $\langle sequence \rangle$ from 1 at the top (left), this function evaluates the $\langle integer expression \rangle$ and leaves the appropriate item from the sequence in the input stream. If the $\langle integer expression \rangle$ is negative, indexing occurs from the bottom (right) of the sequence. If the $\langle integer expression \rangle$ is larger than the number of items in the $\langle sequence \rangle$ (as calculated by <code>\seq_count:N</code>) then the function expands to nothing.
---	--

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

<code>\seq_rand_item:N</code> ★ <code>\seq_rand_item:c</code> ★ <hr/> New: 2016-12-06	<code>\seq_rand_item:N</code> $\langle seq var \rangle$ Selects a pseudo-random item of the $\langle sequence \rangle$. If the $\langle sequence \rangle$ is empty the result is empty. This is not available in older versions of XeTeX.
---	---

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle item \rangle$ does not expand further when appearing in an x-type argument expansion.

4 Recovering values from sequences with branching

The functions in this section combine tests for non-empty sequences with recovery of an item from the sequence. They offer increased readability and performance over separate testing and recovery phases.

`\seq_get_left:NNTF`
`\seq_get_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_get_left:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the left-most item from the $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$, then leaves the $\langle true code \rangle$ in the input stream. The $\langle token list variable \rangle$ is assigned locally.

`\seq_get_right:NNTF`
`\seq_get_right:cNTF`

New: 2012-05-19

`\seq_get_right:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the right-most item from the $\langle sequence \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle sequence \rangle$, then leaves the $\langle true code \rangle$ in the input stream. The $\langle token list variable \rangle$ is assigned locally.

`\seq_pop_left:NNTF`
`\seq_pop_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_pop_left:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the left-most item from the $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from the $\langle sequence \rangle$, then leaves the $\langle true code \rangle$ in the input stream. Both the $\langle sequence \rangle$ and the $\langle token list variable \rangle$ are assigned locally.

`\seq_gpop_left:NNTF`
`\seq_gpop_left:cNTF`

New: 2012-05-14
Updated: 2012-05-19

`\seq_gpop_left:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the left-most item from the $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from the $\langle sequence \rangle$, then leaves the $\langle true code \rangle$ in the input stream. The $\langle sequence \rangle$ is modified globally, while the $\langle token list variable \rangle$ is assigned locally.

`\seq_pop_right:NNTF`
`\seq_pop_right:cNTF`

New: 2012-05-19

`\seq_pop_right:NNTF` $\langle sequence \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the right-most item from the $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from the $\langle sequence \rangle$, then leaves the $\langle true code \rangle$ in the input stream. Both the $\langle sequence \rangle$ and the $\langle token list variable \rangle$ are assigned locally.

```
\seq_gpop_right:NNTF
\seq_gpop_right:cNTF
```

New: 2012-05-19

```
\seq_gpop_right:NNTF <sequence> <token list variable> {\true code} {\false code}
```

If the $\langle sequence \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, pops the right-most item from the $\langle sequence \rangle$ in the $\langle token list variable \rangle$, *i.e.* removes the item from the $\langle sequence \rangle$, then leaves the $\langle true code \rangle$ in the input stream. The $\langle sequence \rangle$ is modified globally, while the $\langle token list variable \rangle$ is assigned locally.

5 Modifying sequences

While sequences are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update sequences, while retaining the order of the unaffected entries.

```
\seq_remove_duplicates:N
\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
```

```
\seq_remove_duplicates:N <sequence>
```

Removes duplicate items from the $\langle sequence \rangle$, leaving the left most copy of each item in the $\langle sequence \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

TeXhackers note: This function iterates through every item in the $\langle sequence \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large sequences.

```
\seq_remove_all:Nn
\seq_remove_all:cn
\seq_gremove_all:Nn
\seq_gremove_all:cn
```

```
\seq_remove_all:Nn <sequence> {\item}
```

Removes every occurrence of $\langle item \rangle$ from the $\langle sequence \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nnTF`.

```
\seq_reverse:N
\seq_reverse:c
\seq_greverse:N
\seq_greverse:c
```

New: 2014-07-18

```
\seq_reverse:N <sequence>
```

Reverses the order of the items stored in the $\langle sequence \rangle$.

```
\seq_sort:Nn
\seq_sort:cn
\seq_gsort:Nn
\seq_gsort:cn
```

New: 2017-02-06

```
\seq_sort:Nn <sequence> {\comparison code}
```

Sorts the items in the $\langle sequence \rangle$ according to the $\langle comparison code \rangle$, and assigns the result to $\langle sequence \rangle$. The details of sorting comparison are described in Section 1.

6 Sequence conditionals

```
\seq_if_empty_p:N ★
\seq_if_empty_p:c ★
\seq_if_empty:NNTF ★
\seq_if_empty:cNTF ★
```

```
\seq_if_empty_p:N <sequence>
```

```
\seq_if_empty:NNTF <sequence> {\true code} {\false code}
```

Tests if the $\langle sequence \rangle$ is empty (containing no items).

<code>\seq_if_in:NnTF</code>	<code>\seq_if_in:NnTF <sequence> {(item)} {(true code)} {(false code)}</code>
<code>\seq_if_in:(NV Nv No Nx cn cV cv co cx)TF</code>	

Tests if the $\langle item \rangle$ is present in the $\langle sequence \rangle$.

7 Mapping to sequences

<code>\seq_map_function:NN</code>	☆
<code>\seq_map_function:cN</code>	☆

Updated: 2012-06-29

`\seq_map_function:NN <sequence> <function>`

Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle sequence \rangle$. The $\langle function \rangle$ will receive one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function `\seq_map_inline:Nn` is faster than `\seq_map_function:NN` for sequences with more than about 10 items.

<code>\seq_map_inline:Nn</code>	
<code>\seq_map_inline:cn</code>	

Updated: 2012-06-29

`\seq_map_inline:Nn <sequence> {(inline function)}`

Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence \rangle$. The $\langle inline function \rangle$ should consist of code which will receive the $\langle item \rangle$ as #1. The $\langle items \rangle$ are returned from left to right.

<code>\seq_map_variable:NNn</code>	
<code>\seq_map_variable:(Ncn cNn ccn)</code>	

Updated: 2012-06-29

`\seq_map_variable:NNn <sequence> <variable> {(code)}`

Stores each $\langle item \rangle$ of the $\langle sequence \rangle$ in turn in the (token list) $\langle variable \rangle$ and applies the $\langle code \rangle$. The $\langle code \rangle$ will usually make use of the $\langle variable \rangle$, but this is not enforced. The assignments to the $\langle variable \rangle$ are local. The $\langle items \rangle$ are returned from left to right.

<code>\seq_map_break:</code>	☆
------------------------------	---

Updated: 2012-06-29

`\seq_map_break:`

Used to terminate a `\seq_map...` function before all entries in the $\langle sequence \rangle$ have been processed. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

`\seq_map_break:n` ☆

Updated: 2012-06-29

`\seq_map_break:n {⟨code⟩}`

Used to terminate a `\seq_map...` function before all entries in the *⟨sequence⟩* have been processed, inserting the *⟨code⟩* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\seq_map_inline:Nn \l_my_seq
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \seq_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\seq_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *⟨code⟩* is inserted into the input stream. This depends on the design of the mapping function.

`\seq_count:N` ☆

`\seq_count:c` ☆

New: 2012-07-13

`\seq_count:N ⟨sequence⟩`

Leaves the number of items in the *⟨sequence⟩* in the input stream as an *⟨integer denotation⟩*. The total number of items in a *⟨sequence⟩* includes those which are empty and duplicates, *i.e.* every item in a *⟨sequence⟩* is unique.

8 Using the content of sequences directly

`\seq_use:Nnnn` ☆

`\seq_use:cnnn` ☆

New: 2013-05-26

`\seq_use:Nnnn ⟨seq var⟩ {⟨separator between two⟩}`

`{⟨separator between more than two⟩} {⟨separator between final two⟩}`

Places the contents of the *⟨seq var⟩* in the input stream, with the appropriate *⟨separator⟩* between the items. Namely, if the sequence has more than two items, the *⟨separator between more than two⟩* is placed between each pair of items except the last, for which the *⟨separator between final two⟩* is used. If the sequence has exactly two items, then they are placed in the input stream separated by the *⟨separator between two⟩*. If the sequence has a single item, it is placed in the input stream, and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nnnn \l_tmpa_seq { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the sequence has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *⟨items⟩* do not expand further when appearing in an x-type argument expansion.

`\seq_use:Nn` ★

`\seq_use:cn` ★

New: 2013-05-26

`\seq_use:Nn` $\langle seq\ var \rangle$ $\{\langle separator \rangle\}$

Places the contents of the $\langle seq\ var \rangle$ in the input stream, with the $\langle separator \rangle$ between the items. If the sequence has a single item, it is placed in the input stream with no $\langle separator \rangle$, and an empty sequence produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\seq_set_split:Nnn \l_tmpa_seq { | } { a | b | c | {de} | f }
\seq_use:Nn \l_tmpa_seq { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle items \rangle$ do not expand further when appearing in an `x`-type argument expansion.

9 Sequences as stacks

Sequences can be used as stacks, where data is pushed to and popped from the top of the sequence. (The left of a sequence is the top, for performance reasons.) The stack functions for sequences are not intended to be mixed with the general ordered data functions detailed in the previous section: a sequence should either be used as an ordered data type or as a stack, but not in both ways.

`\seq_get:NN`

`\seq_get:cn`

Updated: 2012-05-14

`\seq_get:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Reads the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token\ list\ variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ is set to the special marker `\q_no_value`.

`\seq_pop:NN`

`\seq_pop:cn`

Updated: 2012-05-14

`\seq_pop:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Pops the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$. Both of the variables are assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ is set to the special marker `\q_no_value`.

`\seq_gpop:NN`

`\seq_gpop:cn`

Updated: 2012-05-14

`\seq_gpop:NN` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$

Pops the top item from a $\langle sequence \rangle$ into the $\langle token\ list\ variable \rangle$. The $\langle sequence \rangle$ is modified globally, while the $\langle token\ list\ variable \rangle$ is assigned locally. If $\langle sequence \rangle$ is empty the $\langle token\ list\ variable \rangle$ is set to the special marker `\q_no_value`.

`\seq_get:NNTF`

`\seq_get:cNTF`

New: 2012-05-14

Updated: 2012-05-19

`\seq_get:NNTF` $\langle sequence \rangle$ $\langle token\ list\ variable \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

If the $\langle sequence \rangle$ is empty, leaves the $\langle false\ code \rangle$ in the input stream. The value of the $\langle token\ list\ variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle sequence \rangle$ is non-empty, stores the top item from a $\langle sequence \rangle$ in the $\langle token\ list\ variable \rangle$ without removing it from the $\langle sequence \rangle$. The $\langle token\ list\ variable \rangle$ is assigned locally.

`\seq_pop:NNTF`
`\seq_pop:cNTF`
 New: 2012-05-14
 Updated: 2012-05-19

`\seq_pop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. Both the `<sequence>` and the `<token list variable>` are assigned locally.

`\seq_gpop:NNTF`
`\seq_gpop:cNTF`
 New: 2012-05-14
 Updated: 2012-05-19

`\seq_gpop:NNTF <sequence> <token list variable> {\true code} {\false code}`

If the `<sequence>` is empty, leaves the `<false code>` in the input stream. The value of the `<token list variable>` is not defined in this case and should not be relied upon. If the `<sequence>` is non-empty, pops the top item from the `<sequence>` in the `<token list variable>`, *i.e.* removes the item from the `<sequence>`. The `<sequence>` is modified globally, while the `<token list variable>` is assigned locally.

`\seq_push:Nn`
`\seq_push:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`
`\seq_gpush:Nn`
`\seq_gpush:(NV|Nv|No|Nx|cn|cV|cv|co|cx)`

`\seq_push:Nn <sequence> {\item}`

Adds the `{\item}` to the top of the `<sequence>`.

10 Sequences as sets

Sequences can also be used as sets, such that all of their items are distinct. Usage of sequences as sets is not currently widespread, hence no specific set function is provided. Instead, it is explained here how common set operations can be performed by combining several functions described in earlier sections. When using sequences to implement sets, one should be careful not to rely on the order of items in the sequence representing the set.

Sets should not contain several occurrences of a given item. To make sure that a `<sequence variable>` only has distinct items, use `\seq_remove_duplicates:N <sequence variable>`. This function is relatively slow, and to avoid performance issues one should only use it when necessary.

Some operations on a set `<seq var>` are straightforward. For instance, `\seq_count:N <seq var>` expands to the number of items, while `\seq_if_in:NnTF <seq var> {\item}` tests if the `<item>` is in the set.

Adding an `<item>` to a set `<seq var>` can be done by appending it to the `<seq var>` if it is not already in the `<seq var>`:

```
\seq_if_in:NnF <seq var> {\item}
{ \seq_put_right:Nn <seq var> {\item} }
```

Removing an `<item>` from a set `<seq var>` can be done using `\seq_remove_all:Nn`,

```
\seq_remove_all:Nn <seq var> {\item}
```

The intersection of two sets `<seq var1 and <seq var2 can be stored into <seq var3 by collecting items of <seq var1 which are in <seq var2.`

```

\seq_clear:N <seq var3>
\seq_map_inline:Nn <seq var1>
{
\seq_if_in:NnT <seq var2> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The code as written here only works if $\langle seq\ var_3 \rangle$ is different from the other two sequence variables. To cover all cases, items should first be collected in a sequence $\backslash l_ \langle pkg \rangle_internal_seq$, then $\langle seq\ var_3 \rangle$ should be set equal to this internal sequence. The same remark applies to other set functions.

The union of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ through

```

\seq_concat:NNN <seq var3> <seq var1> <seq var2>
\seq_remove_duplicates:N <seq var3>

```

or by adding items to (a copy of) $\langle seq\ var_1 \rangle$ one by one

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{
\seq_if_in:NnF <seq var3> {#1}
{ \seq_put_right:Nn <seq var3> {#1} }
}

```

The second approach is faster than the first when the $\langle seq\ var_2 \rangle$ is short compared to $\langle seq\ var_1 \rangle$.

The difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by removing items of the $\langle seq\ var_2 \rangle$ from (a copy of) the $\langle seq\ var_1 \rangle$ one by one.

```

\seq_set_eq:NN <seq var3> <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn <seq var3> {#1} }

```

The symmetric difference of two sets $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ can be stored into $\langle seq\ var_3 \rangle$ by computing the difference between $\langle seq\ var_1 \rangle$ and $\langle seq\ var_2 \rangle$ and storing the result as $\backslash l_ \langle pkg \rangle_internal_seq$, then the difference between $\langle seq\ var_2 \rangle$ and $\langle seq\ var_1 \rangle$, and finally concatenating the two differences to get the symmetric differences.

```

\seq_set_eq:NN \l\_ \langle pkg \rangle\_internal\_seq <seq var1>
\seq_map_inline:Nn <seq var2>
{ \seq_remove_all:Nn \l\_ \langle pkg \rangle\_internal\_seq {#1} }
\seq_set_eq:NN <seq var3> <seq var2>
\seq_map_inline:Nn <seq var1>
{ \seq_remove_all:Nn <seq var3> {#1} }
\seq_concat:NNN <seq var3> <seq var3> \l\_ \langle pkg \rangle\_internal\_seq

```

11 Constant and scratch sequences

$\backslash c_empty_seq$ Constant that is always empty.

New: 2012-07-02

`\l_tmpa_seq`
`\l_tmpb_seq`

New: 2012-04-26

Scratch sequences for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_seq`
`\g_tmpb_seq`

New: 2012-04-26

Scratch sequences for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

12 Viewing sequences

`\seq_show:N`
`\seq_show:c`

Updated: 2015-08-01

`\seq_show:N` $\langle sequence \rangle$
Displays the entries in the $\langle sequence \rangle$ in the terminal.

`\seq_log:N`
`\seq_log:c`

New: 2014-08-12
Updated: 2015-08-01

`\seq_log:N` $\langle sequence \rangle$
Writes the entries in the $\langle sequence \rangle$ in the log file.

Part X

The l3int package

Integers

Calculation and comparison of integer values can be carried out using literal numbers, `int` registers, constants and integers stored in token list variables. The standard operators `+`, `-`, `/` and `*` and parentheses can be used within such expressions to carry arithmetic operations. This module carries out these functions on *integer expressions* (“`intexpr`”).

1 Integer expressions

`\int_eval:n` ★ `\int_eval:n {⟨integer expression⟩}`

Evaluates the *⟨integer expression⟩*, expanding any integer and token list variables within the *⟨expression⟩* to their content (without requiring `\int_use:N/\tl_use:N`) and applying the standard mathematical rules. For example both

`\int_eval:n { 5 + 4 * 3 - (3 + 4 * 5) }`

and

`\tl_new:N \l_my_tl`
`\tl_set:Nn \l_my_tl { 5 }`
`\int_new:N \l_my_int`
`\int_set:Nn \l_my_int { 4 }`
`\int_eval:n { \l_my_tl + \l_my_int * 3 - (3 + 4 * 5) }`

both evaluate to -6 . The *⟨integer expression⟩* may contain the operators `+`, `-`, `*` and `/`, along with parenthesis `(` and `)`. Any functions within the expressions should expand to an *⟨integer denotation⟩*: a sequence of a sign and digits matching the regex `\-?[0-9]+`. After expansion `\int_eval:n` yields an *⟨integer denotation⟩* which is left in the input stream.

T_EXhackers note: Exactly two expansions are needed to evaluate `\int_eval:n`. The result is *not* an *⟨internal integer⟩*, and therefore requires suitable termination if used in a T_EX-style integer assignment.

`\int_eval:w` ★ `\int_eval:w {⟨integer expression⟩}`

New: 2018-03-30

Evaluates the *⟨integer expression⟩* as described for `\int_eval:n`. The end of the expression is the first token encountered that cannot form part of such an expression. If that token is `\scan_stop`: it is removed, otherwise not. Spaces do *not* terminate the expression.

`\int_abs:n` ★ `\int_abs:n {⟨integer expression⟩}`

Updated: 2012-09-26

Evaluates the *⟨integer expression⟩* as described for `\int_eval:n` and leaves the absolute value of the result in the input stream as an *⟨integer denotation⟩* after two expansions.

<hr/>	
<code>\int_div_round:nn</code> ★	<code>\int_div_round:nn {\langle integer \rangle} {\langle integer \rangle}</code>
Updated: 2012-09-26	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result to the closest integer. Ties are rounded away from zero. Note that this is identical to using <code>/</code> directly in an $\langle integer expression \rangle$. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.
<hr/>	
<code>\int_div_truncate:nn</code> ★	<code>\int_div_truncate:nn {\langle integer \rangle} {\langle integer \rangle}</code>
Updated: 2012-02-09	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then divides the first value by the second, and rounds the result towards zero. Note that division using <code>/</code> rounds to the closest integer instead. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.
<hr/>	
<code>\int_max:nn</code> ★	<code>\int_max:nn {\langle integer \rangle} {\langle integer \rangle}</code>
<code>\int_min:nn</code> ★	<code>\int_min:nn {\langle integer \rangle} {\langle integer \rangle}</code>
Updated: 2012-09-26	Evaluates the $\langle integer expressions \rangle$ as described for <code>\int_eval:n</code> and leaves either the larger or smaller value in the input stream as an $\langle integer denotation \rangle$ after two expansions.
<hr/>	
<code>\int_mod:nn</code> ★	<code>\int_mod:nn {\langle integer \rangle} {\langle integer \rangle}</code>
Updated: 2012-09-26	Evaluates the two $\langle integer expressions \rangle$ as described earlier, then calculates the integer remainder of dividing the first expression by the second. This is obtained by subtracting <code>\int_div_truncate:nn {\langle integer \rangle} {\langle integer \rangle}</code> times $\langle integer \rangle$ from $\langle integer \rangle$. Thus, the result has the same sign as $\langle integer \rangle$ and its absolute value is strictly less than that of $\langle integer \rangle$. The result is left in the input stream as an $\langle integer denotation \rangle$ after two expansions.

2 Creating and initialising integers

<hr/>	
<code>\int_new:N</code>	<code>\int_new:N \langle integer \rangle</code>
<code>\int_new:c</code>	Creates a new $\langle integer \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle integer \rangle$ is initially equal to 0.
<hr/>	
<code>\int_const:Nn</code>	<code>\int_const:Nn \langle integer \rangle {\langle integer expression \rangle}</code>
<code>\int_const:cn</code>	Creates a new constant $\langle integer \rangle$ or raises an error if the name is already taken. The value of the $\langle integer \rangle$ is set globally to the $\langle integer expression \rangle$.
Updated: 2011-10-22	
<hr/>	
<code>\int_zero:N</code>	<code>\int_zero:N \langle integer \rangle</code>
<code>\int_zero:c</code>	Sets $\langle integer \rangle$ to 0.
<code>\int_gzero:N</code>	
<code>\int_gzero:c</code>	
<hr/>	
<code>\int_zero_new:N</code>	<code>\int_zero_new:N \langle integer \rangle</code>
<code>\int_zero_new:c</code>	Ensures that the $\langle integer \rangle$ exists globally by applying <code>\int_new:N</code> if necessary, then applies <code>\int_(g)zero:N</code> to leave the $\langle integer \rangle$ set to zero.
<code>\int_gzero_new:N</code>	
<code>\int_gzero_new:c</code>	
New: 2011-12-13	

```

\int_set_eq:NN
\int_set_eq:(cN|Nc|cc)
\int_gset_eq:NN
\int_gset_eq:(cN|Nc|cc)

```

`\int_set_eq:NN` $\langle integer_1 \rangle$ $\langle integer_2 \rangle$
Sets the content of $\langle integer_1 \rangle$ equal to that of $\langle integer_2 \rangle$.

```

\int_if_exist_p:N ★
\int_if_exist_p:c ★
\int_if_exist:NTF ★
\int_if_exist:cTF ★

```

`\int_if_exist_p:N` $\langle int \rangle$
`\int_if_exist:NTF` $\langle int \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
Tests whether the $\langle int \rangle$ is currently defined. This does not check that the $\langle int \rangle$ really is an integer variable.

New: 2012-03-03

3 Setting and incrementing integers

```

\int_add:Nn
\int_add:cn
\int_gadd:Nn
\int_gadd:cn

```

`\int_add:Nn` $\langle integer \rangle$ $\{\langle integer\ expression \rangle\}$
Adds the result of the $\langle integer\ expression \rangle$ to the current content of the $\langle integer \rangle$.

Updated: 2011-10-22

```

\int_decr:N
\int_decr:c
\int_gdecr:N
\int_gdecr:c

```

`\int_decr:N` $\langle integer \rangle$
Decreases the value stored in $\langle integer \rangle$ by 1.

```

\int_incr:N
\int_incr:c
\int_gincr:N
\int_gincr:c

```

`\int_incr:N` $\langle integer \rangle$
Increases the value stored in $\langle integer \rangle$ by 1.

```

\int_set:Nn
\int_set:cn
\int_gset:Nn
\int_gset:cn

```

`\int_set:Nn` $\langle integer \rangle$ $\{\langle integer\ expression \rangle\}$
Sets $\langle integer \rangle$ to the value of $\langle integer\ expression \rangle$, which must evaluate to an integer (as described for `\int_eval:n`).

Updated: 2011-10-22

```

\int_sub:Nn
\int_sub:cn
\int_gsub:Nn
\int_gsub:cn

```

`\int_sub:Nn` $\langle integer \rangle$ $\{\langle integer\ expression \rangle\}$
Subtracts the result of the $\langle integer\ expression \rangle$ from the current content of the $\langle integer \rangle$.

Updated: 2011-10-22

4 Using integers

<code>\int_use:N</code>	★
<code>\int_use:c</code>	★

Updated: 2011-10-22

`\int_use:N` $\langle integer \rangle$

Recovers the content of an $\langle integer \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where an $\langle integer \rangle$ is required (such as in the first and third arguments of `\int_compare:nNnTF`).

T_EXhackers note: `\int_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

5 Integer expression conditionals

<code>\int_compare_p:nNn</code>	★
<code>\int_compare:nNnTF</code>	★

`\int_compare_p:nNn` $\{\langle intexpr_1 \rangle\}$ $\langle relation \rangle$ $\{\langle intexpr_2 \rangle\}$

`\int_compare:nNnTF`
 $\{\langle intexpr_1 \rangle\}$ $\langle relation \rangle$ $\{\langle intexpr_2 \rangle\}$
 $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

This function first evaluates each of the $\langle integer\ expressions \rangle$ as described for `\int_eval:n`. The two results are then compared using the $\langle relation \rangle$:

Equal	=
Greater than	>
Less than	<

<code>\int_compare_p:n</code> ★ <code>\int_compare:nTF</code> ★ <hr/> Updated: 2013-01-13	<pre> \int_compare_p:n { <intexpr₁> <relation₁> ... <intexpr_N> <relation_N> <intexpr_{N+1}> } \int_compare:nTF { <intexpr₁> <relation₁> ... <intexpr_N> <relation_N> <intexpr_{N+1}> } {<true code>} {<false code>} </pre>
---	---

This function evaluates the *<integer expressions>* as described for `\int_eval:n` and compares consecutive result using the corresponding *<relation>*, namely it compares *<intexpr₁>* and *<intexpr₂>* using the *<relation₁>*, then *<intexpr₂>* and *<intexpr₃>* using the *<relation₂>*, until finally comparing *<intexpr_N>* and *<intexpr_{N+1}>* using the *<relation_N>*. The test yields **true** if all comparisons are **true**. Each *<integer expression>* is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is **false**, then no other *<integer expression>* is evaluated and no other comparison is performed. The *<relations>* can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

<code>\int_case:nn</code> ★	<code>\int_case:nnTF {⟨test integer expression⟩}</code>
<code>\int_case:nnTF</code> ★	<code>{</code>
	<code>{⟨intexpr case₁⟩} {⟨code case₁⟩}</code>
	<code>{⟨intexpr case₂⟩} {⟨code case₂⟩}</code>
	<code>...</code>
	<code>{⟨intexpr case_n⟩} {⟨code case_n⟩}</code>
	<code>}</code>
	<code>{⟨true code⟩}</code>
	<code>{⟨false code⟩}</code>

New: 2013-07-24

This function evaluates the *⟨test integer expression⟩* and compares this in turn to each of the *⟨integer expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\int_case:nn`, which does nothing if there is no match, is also available. For example

```
\int_case:nnF
{ 2 * 5 }
{
  { 5 }      { Small }
  { 4 + 6 }   { Medium }
  { -2 * 10 } { Negative }
}
{ No idea! }
```

leaves “Medium” in the input stream.

<code>\int_if_even_p:n</code> ★	<code>\int_if_odd_p:n {⟨integer expression⟩}</code>
<code>\int_if_even:nTF</code> ★	<code>\int_if_odd:nTF {⟨integer expression⟩}</code>
<code>\int_if_odd_p:n</code> ★	<code>{⟨true code⟩} {⟨false code⟩}</code>
<code>\int_if_odd:nTF</code> ★	

This function first evaluates the *⟨integer expression⟩* as described for `\int_eval:n`. It then evaluates if this is odd or even, as appropriate.

6 Integer expression loops

<code>\int_do_until:nNnn</code> ☆	<code>\int_do_until:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

<code>\int_do_while:nNnn</code> ☆	<code>\int_do_while:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨integer expressions⟩* as described for `\int_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<hr/> <code>\int_until_do:nNnn</code> ☆ <hr/>	<code>\int_until_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\int_while_do:nNnn</code> ☆ <hr/>	<code>\int_while_do:nNnn {⟨intexpr₁⟩} ⟨relation⟩ {⟨intexpr₂⟩} {⟨code⟩}</code>
	Evaluates the relationship between the two <i>⟨integer expressions⟩</i> as described for <code>\int_compare:nNnTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\int_do_until:nn</code> ☆ <hr/>	<code>\int_do_until:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is false then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is true .
<hr/> <code>\int_do_while:nn</code> ☆ <hr/>	<code>\int_do_while:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Places the <i>⟨code⟩</i> in the input stream for T _E X to process, and then evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> . If the test is true then the <i>⟨code⟩</i> is inserted into the input stream again and a loop occurs until the <i>⟨relation⟩</i> is false .
<hr/> <code>\int_until_do:nn</code> ☆ <hr/>	<code>\int_until_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is false . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\int_while_do:nn</code> ☆ <hr/>	<code>\int_while_do:nn {⟨integer relation⟩} {⟨code⟩}</code>
Updated: 2013-01-13	Evaluates the <i>⟨integer relation⟩</i> as described for <code>\int_compare:nTF</code> , and then places the <i>⟨code⟩</i> in the input stream if the <i>⟨relation⟩</i> is true . After the <i>⟨code⟩</i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

7 Integer step functions

<code>\int_step_function:nN</code>	☆	<code>\int_step_function:nN {⟨final value⟩} ⟨function⟩</code>
<code>\int_step_function:nnN</code>	☆	<code>\int_step_function:nnN {⟨initial value⟩} {⟨final value⟩} ⟨function⟩</code>
<code>\int_step_function:nnnN</code>	☆	<code>\int_step_function:nnnN {⟨initial value⟩} {⟨step⟩} {⟨final value⟩} ⟨function⟩</code>

New: 2012-06-04
Updated: 2018-04-22

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. The $\langle function \rangle$ is then placed in front of each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$). The $\langle step \rangle$ must be non-zero. If the $\langle step \rangle$ is positive, the loop stops when the $\langle value \rangle$ becomes larger than the $\langle final\ value \rangle$. If the $\langle step \rangle$ is negative, the loop stops when the $\langle value \rangle$ becomes smaller than the $\langle final\ value \rangle$. The $\langle function \rangle$ should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\int_step_function:nnnN { 1 } { 1 } { 5 } \my_func:n
```

would print

```
[I saw 1]   [I saw 2]   [I saw 3]   [I saw 4]   [I saw 5]
```

The functions `\int_step_function:nN` and `\int_step_function:nnN` both use a fixed $\langle step \rangle$ of 1, and in the case of `\int_step_function:nN` the $\langle initial\ value \rangle$ is also fixed as 1. These functions are provided as simple short-cuts for code clarity.

<code>\int_step_inline:nn</code>	<code>\int_step_inline:nn {⟨final value⟩} {⟨code⟩}</code>
<code>\int_step_inline:nnn</code>	<code>\int_step_inline:nnn {⟨initial value⟩} {⟨final value⟩} {⟨code⟩}</code>
<code>\int_step_inline:nnnn</code>	<code>\int_step_inline:nnnn {⟨initial value⟩} {⟨step⟩} {⟨final value⟩} {⟨code⟩}</code>

New: 2012-06-04
Updated: 2018-04-22

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream with `#1` replaced by the current $\langle value \rangle$. Thus the $\langle code \rangle$ should define a function of one argument (`#1`).

The functions `\int_step_inline:nn` and `\int_step_inline:nnn` both use a fixed $\langle step \rangle$ of 1, and in the case of `\int_step_inline:nn` the $\langle initial\ value \rangle$ is also fixed as 1. These functions are provided as simple short-cuts for code clarity.

<code>\int_step_variable:nNn</code>	<code>\int_step_variable:nNn {⟨final value⟩} ⟨tl var⟩ {⟨code⟩}</code>
<code>\int_step_variable:nnNn</code>	<code>\int_step_variable:nnNn {⟨initial value⟩} {⟨final value⟩} ⟨tl var⟩ {⟨code⟩}</code>
<code>\int_step_variable:nnnNn</code>	<code>\int_step_variable:nnnNn {⟨initial value⟩} {⟨step⟩} {⟨final value⟩} ⟨tl var⟩ {⟨code⟩}</code>

New: 2012-06-04
Updated: 2018-04-22

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be integer expressions. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl\ var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl\ var \rangle$.

The functions `\int_step_variable:nNn` and `\int_step_variable:nnNn` both use a fixed $\langle step \rangle$ of 1, and in the case of `\int_step_variable:nNn` the $\langle initial\ value \rangle$ is also fixed as 1. These functions are provided as simple short-cuts for code clarity.

8 Formatting integers

Integers can be placed into the output stream with formatting. These conversions apply to any integer expressions.

<code>\int_to_arabic:n</code> ★	<code>\int_to_arabic:n {⟨integer expression⟩}</code>
---------------------------------	--

Updated: 2011-10-22

Places the value of the *⟨integer expression⟩* in the input stream as digits, with category code 12 (other).

<code>\int_to_alph:n</code> ★	<code>\int_to_alph:n {⟨integer expression⟩}</code>
<code>\int_to_Alph:n</code> ★	

Updated: 2011-09-17

Evaluates the *⟨integer expression⟩* and converts the result into a series of letters, which are then left in the input stream. The conversion rule uses the 26 letters of the English alphabet, in order, adding letters when necessary to increase the total possible range of representable numbers. Thus

```
\int_to_alph:n { 1 }
```

places a in the input stream,

```
\int_to_alph:n { 26 }
```

is represented as z and

```
\int_to_alph:n { 27 }
```

is converted to aa. For conversions using other alphabets, use `\int_to_symbols:nnn` to define an alphabet-specific function. The basic `\int_to_alph:n` and `\int_to_Alph:n` functions should not be modified. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

<code>\int_to_symbols:nnn</code> ★	<code>\int_to_symbols:nnn</code> <code>{⟨integer expression⟩} {⟨total symbols⟩}</code> <code>{⟨value to symbol mapping⟩}</code>
------------------------------------	---

Updated: 2011-09-17

This is the low-level function for conversion of an *⟨integer expression⟩* into a symbolic form (often letters). The *⟨total symbols⟩* available should be given as an integer expression. Values are actually converted to symbols according to the *⟨value to symbol mapping⟩*. This should be given as *⟨total symbols⟩* pairs of entries, a number and the appropriate symbol. Thus the `\int_to_alph:n` function is defined as

```
\cs_new:Npn \int_to_alph:n #1
{
  \int_to_symbols:nnn {#1} { 26 }
  {
    { 1 } { a }
    { 2 } { b }
    ...
    { 26 } { z }
  }
}
```

<hr/>	
<code>\int_to_bin:n</code> ★	<code>\int_to_bin:n {⟨integer expression⟩}</code>
<hr/>	
New: 2014-02-11	Calculates the value of the <i>⟨integer expression⟩</i> and places the binary representation of the result in the input stream.
<hr/>	
<code>\int_to_hex:n</code> ★	<code>\int_to_hex:n {⟨integer expression⟩}</code>
<code>\int_to_Hex:n</code> ★	
<hr/>	
New: 2014-02-11	Calculates the value of the <i>⟨integer expression⟩</i> and places the hexadecimal (base 16) representation of the result in the input stream. Letters are used for digits beyond 9: lower case letters for <code>\int_to_hex:n</code> and upper case ones for <code>\int_to_Hex:n</code> . The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
<hr/>	
<code>\int_to_oct:n</code> ★	<code>\int_to_oct:n {⟨integer expression⟩}</code>
<hr/>	
New: 2014-02-11	Calculates the value of the <i>⟨integer expression⟩</i> and places the octal (base 8) representation of the result in the input stream. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).
<hr/>	
<code>\int_to_base:nn</code> ★	<code>\int_to_base:nn {⟨integer expression⟩} {⟨base⟩}</code>
<code>\int_to_Base:nn</code> ★	
<hr/>	
Updated: 2014-02-11	Calculates the value of the <i>⟨integer expression⟩</i> and converts it into the appropriate representation in the <i>⟨base⟩</i> ; the later may be given as an integer expression. For bases greater than 10 the higher “digits” are represented by letters from the English alphabet: lower case letters for <code>\int_to_base:n</code> and upper case ones for <code>\int_to_Base:n</code> . The maximum <i>⟨base⟩</i> value is 36. The resulting tokens are digits with category code 12 (other) and letters with category code 11 (letter).

TeXhackers note: This is a generic version of `\int_to_bin:n`, etc.

<hr/>	
<code>\int_to_roman:n</code> ☆	<code>\int_to_roman:n {⟨integer expression⟩}</code>
<code>\int_to_Roman:n</code> ☆	
<hr/>	
Updated: 2011-10-22	Places the value of the <i>⟨integer expression⟩</i> in the input stream as Roman numerals, either lower case (<code>\int_to_roman:n</code>) or upper case (<code>\int_to_Roman:n</code>). The Roman numerals are letters with category code 11 (letter).

9 Converting from other formats to integers

<hr/>	
<code>\int_from_alph:n</code> ★	<code>\int_from_alph:n {⟨letters⟩}</code>
<hr/>	
Updated: 2014-08-25	Converts the <i>⟨letters⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨letters⟩</i> are first converted to a string, with no expansion. Lower and upper case letters from the English alphabet may be used, with “a” equal to 1 through to “z” equal to 26. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_alph:n</code> and <code>\int_to_Alph:n</code> .
<hr/>	
<code>\int_from_bin:n</code> ★	<code>\int_from_bin:n {⟨binary number⟩}</code>
<hr/>	
New: 2014-02-11	Converts the <i>⟨binary number⟩</i> into the integer (base 10) representation and leaves this in the input stream. The <i>⟨binary number⟩</i> is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by binary digits. This is the inverse function of <code>\int_to_bin:n</code> .
Updated: 2014-08-25	

<hr/> <code>\int_from_hex:n</code> ★	<code>\int_from_hex:n</code> $\{\langle hexadecimal\ number\rangle\}$
New: 2014-02-11 Updated: 2014-08-25	Converts the $\langle hexadecimal\ number\rangle$ into the integer (base 10) representation and leaves this in the input stream. Digits greater than 9 may be represented in the $\langle hexadecimal\ number\rangle$ by upper or lower case letters. The $\langle hexadecimal\ number\rangle$ is first converted to a string, with no expansion. The function also accepts a leading sign, made of + and -. This is the inverse function of <code>\int_to_hex:n</code> and <code>\int_to_Hex:n</code> .

<hr/> <code>\int_from_oct:n</code> ★	<code>\int_from_oct:n</code> $\{\langle octal\ number\rangle\}$
New: 2014-02-11 Updated: 2014-08-25	Converts the $\langle octal\ number\rangle$ into the integer (base 10) representation and leaves this in the input stream. The $\langle octal\ number\rangle$ is first converted to a string, with no expansion. The function accepts a leading sign, made of + and -, followed by octal digits. This is the inverse function of <code>\int_to_oct:n</code> .

<hr/> <code>\int_from_roman:n</code> ★	<code>\int_from_roman:n</code> $\{\langle roman\ numeral\rangle\}$
Updated: 2014-08-25	Converts the $\langle roman\ numeral\rangle$ into the integer (base 10) representation and leaves this in the input stream. The $\langle roman\ numeral\rangle$ is first converted to a string, with no expansion. The $\langle roman\ numeral\rangle$ may be in upper or lower case; if the numeral contains characters besides mdclxvi or MDCLXVI then the resulting value is -1. This is the inverse function of <code>\int_to_roman:n</code> and <code>\int_to_Roman:n</code> .

<hr/> <code>\int_from_base:nn</code> ★	<code>\int_from_base:nn</code> $\{\langle number\rangle\}$ $\{\langle base\rangle\}$
Updated: 2014-08-25	Converts the $\langle number\rangle$ expressed in $\langle base\rangle$ into the appropriate value in base 10. The $\langle number\rangle$ is first converted to a string, with no expansion. The $\langle number\rangle$ should consist of digits and letters (either lower or upper case), plus optionally a leading sign. The maximum $\langle base\rangle$ value is 36. This is the inverse function of <code>\int_to_base:nn</code> and <code>\int_to_Base:nn</code> .

10 Random integers

<hr/> <code>\int_rand:nn</code> ★	<code>\int_rand:nn</code> $\{\langle intexpr_1\rangle\}$ $\{\langle intexpr_2\rangle\}$
New: 2016-12-06 Updated: 2018-04-27	Evaluates the two $\langle integer\ expressions\rangle$ and produces a pseudo-random number between the two (with bounds included). This is not available in older versions of X _Y TeX.

<hr/> <code>\int_rand:n</code> ★	<code>\int_rand:n</code> $\{\langle intexpr\rangle\}$
New: 2018-05-05	Evaluates the $\langle integer\ expression\rangle$ then produces a pseudo-random number between 1 and the $\langle intexpr\rangle$ (included). This is not available in older versions of X _Y TeX.

11 Viewing integers

<hr/> <code>\int_show:N</code> <code>\int_show:c</code>	<code>\int_show:N</code> $\langle integer\rangle$ Displays the value of the $\langle integer\rangle$ on the terminal.
--	--

<hr/> <code>\int_show:n</code> <hr/>	<code>\int_show:n {⟨integer expression⟩}</code>
New: 2011-11-22 Updated: 2015-08-07	Displays the result of evaluating the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\int_log:N</code> <code>\int_log:c</code> <hr/>	<code>\int_log:N ⟨integer⟩</code>
New: 2014-08-22 Updated: 2015-08-03	Writes the value of the <i>⟨integer⟩</i> in the log file.
<hr/> <code>\int_log:n</code> <hr/>	<code>\int_log:n {⟨integer expression⟩}</code>
New: 2014-08-22 Updated: 2015-08-07	Writes the result of evaluating the <i>⟨integer expression⟩</i> in the log file.

12 Constant integers

<hr/> <code>\c_zero_int</code> <code>\c_one_int</code> <hr/>	Integer values used with primitive tests and assignments: their self-terminating nature makes these more convenient and faster than literal numbers.
New: 2018-05-07	
<hr/> <code>\c_max_int</code> <hr/>	The maximum value that can be stored as an integer.
<hr/> <code>\c_max_register_int</code> <hr/>	Maximum number of registers.
<hr/> <code>\c_max_char_int</code> <hr/>	Maximum character code completely supported by the engine.

13 Scratch integers

<hr/> <code>\l_tmpa_int</code> <code>\l_tmpb_int</code> <hr/>	Scratch integer for local assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_int</code> <code>\g_tmpb_int</code> <hr/>	Scratch integer for global assignment. These are never used by the kernel code, and so are safe for use with any $\text{\LaTeX}3$ -defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

13.1 Direct number expansion

`\int_value:w` ★
 New: 2018-03-27

`\int_value:w` $\langle integer \rangle$
`\int_value:w` $\langle integer\ denotation \rangle$ $\langle optional\ space \rangle$

Expands the following tokens until an $\langle integer \rangle$ is formed, and leaves a normalized form (no leading sign except for negative numbers, no leading digit 0 except for zero) in the input stream as category code 12 (other) characters. The $\langle integer \rangle$ can consist of any number of signs (with intervening spaces) followed by

- an integer variable (in fact, any T_EX register except `\toks`) or
- explicit digits (or by ‘ $\langle octal\ digits \rangle$ ’ or “ $\langle hexadecimal\ digits \rangle$ ” or ‘ $\langle character \rangle$ ’).

In this last case expansion stops once a non-digit is found; if that is a space it is removed as in `f`-expansion, and so `\exp_stop_f:` may be employed as an end marker. Note that protected functions *are* expanded by this process.

This function requires exactly one expansion to produce a value, and so is suitable for use in cases where a number is required “directly”. In general, `\int_eval:n` is the preferred approach to generating numbers.

T_EXhackers note: This is the T_EX primitive `\number`.

14 Primitive conditionals

`\if_int_compare:w` ★

`\if_int_compare:w` $\langle integer_1 \rangle$ $\langle relation \rangle$ $\langle integer_2 \rangle$
 $\langle true\ code \rangle$
`\else:`
 $\langle false\ code \rangle$
`\fi:`

Compare two integers using $\langle relation \rangle$, which must be one of =, < or > with category code 12. The `\else:` branch is optional.

T_EXhackers note: These are both names for the T_EX primitive `\ifnum`.

`\if_case:w` ★
`\or:` ★

`\if_case:w` $\langle integer \rangle$ $\langle case_0 \rangle$
 $\langle or: \langle case_1 \rangle$
 $\langle or: \dots$
 $\langle else: \langle default \rangle$
`\fi:`

Selects a case to execute based on the value of the $\langle integer \rangle$. The first case ($\langle case_0 \rangle$) is executed if $\langle integer \rangle$ is 0, the second ($\langle case_1 \rangle$) if the $\langle integer \rangle$ is 1, *etc.* The $\langle integer \rangle$ may be a literal, a constant or an integer expression (*e.g.* using `\int_eval:n`).

T_EXhackers note: These are the T_EX primitives `\ifcase` and `\or`.

`\if_int_odd:w` ★ `\if_int_odd:w` $\langle tokens \rangle$ $\langle optional\ space \rangle$
 $\langle true\ code \rangle$
`\else:`
 $\langle true\ code \rangle$
`\fi:`

Expands $\langle tokens \rangle$ until a non-numeric token or a space is found, and tests whether the resulting $\langle integer \rangle$ is odd. If so, $\langle true\ code \rangle$ is executed. The `\else:` branch is optional.

TeXhackers note: This is the TeX primitive `\ifodd`.

Part XI

The l3flag package: Expandable flags

Flags are the only data-type that can be modified in expansion-only contexts. This module is meant mostly for kernel use: in almost all cases, booleans or integers should be preferred to flags because they are very significantly faster.

A flag can hold any non-negative value, which we call its $\langle height \rangle$. In expansion-only contexts, a flag can only be “raised”: this increases the $\langle height \rangle$ by 1. The $\langle height \rangle$ can also be queried expandably. However, decreasing it, or setting it to zero requires non-expandable assignments.

Flag variables are always local. They are referenced by a $\langle flag name \rangle$ such as `str_missing`. The $\langle flag name \rangle$ is used as part of `\use:c` constructions hence is expanded at point of use. It must expand to character tokens only, with no spaces.

A typical use case of flags would be to keep track of whether an exceptional condition has occurred during expandable processing, and produce a meaningful (non-expandable) message after the end of the expandable processing. This is exemplified by `l3str-convert`, which for performance reasons performs conversions of individual characters expandably and for readability reasons produces a single error message describing incorrect inputs that were encountered.

Flags should not be used without carefully considering the fact that raising a flag takes a time and memory proportional to its height. Flags should not be used unless unavoidable.

1 Setting up flags

<code>\flag_new:n</code>	<code>\flag_new:n {$\langle flag name \rangle$}</code>
--------------------------	---

Creates a new flag with a name given by $\langle flag name \rangle$, or raises an error if the name is already taken. The $\langle flag name \rangle$ may not contain spaces. The declaration is global, but flags are always local variables. The $\langle flag \rangle$ initially has zero height.

<code>\flag_clear:n</code>	<code>\flag_clear:n {$\langle flag name \rangle$}</code>
----------------------------	---

The $\langle flag \rangle$ ’s height is set to zero. The assignment is local.

<code>\flag_clear_new:n</code>	<code>\flag_clear_new:n {$\langle flag name \rangle$}</code>
--------------------------------	---

Ensures that the $\langle flag \rangle$ exists globally by applying `\flag_new:n` if necessary, then applies `\flag_clear:n`, setting the height to zero locally.

<code>\flag_show:n</code>	<code>\flag_show:n {$\langle flag name \rangle$}</code>
---------------------------	--

Displays the $\langle flag \rangle$ ’s height in the terminal.

<code>\flag_log:n</code>	<code>\flag_log:n {$\langle flag name \rangle$}</code>
--------------------------	---

Writes the $\langle flag \rangle$ ’s height to the log file.

2 Expandable flag commands

<hr/> <code>\flag_if_exist:n</code> ★	<code>\flag_if_exist:n {⟨flag name⟩}</code>
<hr/> <code>\flag_if_exist:n</code> <u><code>TF</code></u> ★	This function returns <code>true</code> if the <code>⟨flag name⟩</code> references a flag that has been defined previously, and <code>false</code> otherwise.
<hr/> <code>\flag_if_raised:n</code> ★	<code>\flag_if_raised:n {⟨flag name⟩}</code>
<hr/> <code>\flag_if_raised:n</code> <u><code>TF</code></u> ★	This function returns <code>true</code> if the <code>⟨flag⟩</code> has non-zero height, and <code>false</code> if the <code>⟨flag⟩</code> has zero height.
<hr/> <code>\flag_height:n</code> ★	<code>\flag_height:n {⟨flag name⟩}</code>
	Expands to the height of the <code>⟨flag⟩</code> as an integer denotation.
<hr/> <code>\flag_raise:n</code> ★	<code>\flag_raise:n {⟨flag name⟩}</code>
	The <code>⟨flag⟩</code> 's height is increased by 1 locally.

Part XII

The l3prg package

Control structures

Conditional processing in L^AT_EX3 is defined as something that performs a series of tests, possibly involving assignments and calling other functions that do not read further ahead in the input stream. After processing the input, a *state* is returned. The states returned are *⟨true⟩* and *⟨false⟩*.

L^AT_EX3 has two forms of conditional flow processing based on these states. The first form is predicate functions that turn the returned state into a boolean *⟨true⟩* or *⟨false⟩*. For example, the function `\cs_if_free_p:N` checks whether the control sequence given as its argument is free and then returns the boolean *⟨true⟩* or *⟨false⟩* values to be used in testing with `\if_predicate:w` or in functions to be described below. The second form is the kind of functions choosing a particular argument from the input stream based on the result of the testing as in `\cs_if_free:NTF` which also takes one argument (the *N*) and then executes either **true** or **false** depending on the result.

T_EXhackers note: The arguments are executed after exiting the underlying `\if... \fi:` structure.

1 Defining a set of conditional functions

```
\prg_new_conditional:Npnn
\prg_set_conditional:Npnn
\prg_new_conditional:Nnn
\prg_set_conditional:Nnn
```

Updated: 2012-02-06

```
\prg_new_conditional:Npnn \<name>:<arg spec> <parameters> {\<conditions>} {\<code>}
\prg_new_conditional:Nnn \<name>:<arg spec> {\<conditions>} {\<code>}
```

These functions create a family of conditionals using the same *{⟨code⟩}* to perform the test created. Those conditionals are expandable if *⟨code⟩* is. The **new** versions check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** versions do no check and perform assignments locally (cf. `\cs_set:Npn`). The conditionals created are dependent on the comma-separated list of *⟨conditions⟩*, which should be one or more of **p**, **T**, **F** and **TF**.

```
\prg_new_protected_conditional:Npnn \prg_new_protected_conditional:Npnn \<name>:<arg spec> <parameters>
\prg_set_protected_conditional:Npnn {\<conditions>} {\<code>}
\prg_new_protected_conditional:Nnn \prg_new_protected_conditional:Nnn \<name>:<arg spec>
\prg_set_protected_conditional:Nnn {\<conditions>} {\<code>}
```

Updated: 2012-02-06

These functions create a family of protected conditionals using the same *{⟨code⟩}* to perform the test created. The *⟨code⟩* does not need to be expandable. The **new** version check for existing definitions and perform assignments globally (cf. `\cs_new:Npn`) whereas the **set** version do not (cf. `\cs_set:Npn`). The conditionals created are depended on the comma-separated list of *⟨conditions⟩*, which should be one or more of **T**, **F** and **TF** (not **p**).

The conditionals are defined by `\prg_new_conditional:Npnn` and friends as:

- `\<name>_p:<arg spec>` — a predicate function which will supply either a logical `true` or logical `false`. This function is intended for use in cases where one or more logical tests are combined to lead to a final outcome. This function cannot be defined for `protected` conditionals.
- `\<name>:<arg spec>T` — a function with one more argument than the original `<arg spec>` demands. The `<true branch>` code in this additional argument will be left on the input stream only if the test is `true`.
- `\<name>:<arg spec>F` — a function with one more argument than the original `<arg spec>` demands. The `<false branch>` code in this additional argument will be left on the input stream only if the test is `false`.
- `\<name>:<arg spec>TF` — a function with two more argument than the original `<arg spec>` demands. The `<true branch>` code in the first additional argument will be left on the input stream if the test is `true`, while the `<false branch>` code in the second argument will be left on the input stream if the test is `false`.

The `<code>` of the test may use `<parameters>` as specified by the second argument to `\prg_set_conditional:Npnn`: this should match the `<argument specification>` but this is not enforced. The `Nnn` versions infer the number of arguments from the argument specification given (cf. `\cs_new:Nn`, etc.). Within the `<code>`, the functions `\prg_return_true:` and `\prg_return_false:` are used to indicate the logical outcomes of the test.

An example can easily clarify matters here:

```
\prg_set_conditional:Npnn \foo_if_bar:NN #1#2 { p , T , TF }
{
  \if_meaning:w \l_tmpa_tl #1
  \prg_return_true:
\else:
  \if_meaning:w \l_tmpa_tl #2
  \prg_return_true:
\else:
  \prg_return_false:
\fi:
\fi:
}
```

This defines the function `\foo_if_bar_p:NN`, `\foo_if_bar:NNTF` and `\foo_if_bar:NNT` but not `\foo_if_bar:NNF` (because `F` is missing from the `<conditions>` list). The return statements take care of resolving the remaining `\else:` and `\fi:` before returning the state. There must be a return statement for each branch; failing to do so will result in erroneous output if that branch is executed.

<code>\prg_new_eq_conditional:Nnn</code>	<code>\prg_new_eq_conditional:Nnn \<name1>:<arg spec1> \<name2>:<arg spec2></code>
<code>\prg_set_eq_conditional:Nnn</code>	<code>{<conditions>}</code>

These functions copy a family of conditionals. The `new` version checks for existing definitions (cf. `\cs_new_eq:NN`) whereas the `set` version does not (cf. `\cs_set_eq:NN`). The conditionals copied are depended on the comma-separated list of `<conditions>`, which should be one or more of `p`, `T`, `F` and `TF`.

<code>\prg_return_true:</code>	★	<code>\prg_return_true:</code>
<code>\prg_return_false:</code>	★	<code>\prg_return_false:</code>

These “return” functions define the logical state of a conditional statement. They appear within the code for a conditional function generated by `\prg_set_conditional:Npnn`, *etc.*, to indicate when a true or false branch should be taken. While they may appear multiple times each within the code of such conditionals, the execution of the conditional must result in the expansion of one of these two functions *exactly once*.

The return functions trigger what is internally an **f**-expansion process to complete the evaluation of the conditional. Therefore, after `\prg_return_true:` or `\prg_return_false:` there must be no non-expandable material in the input stream for the remainder of the expansion of the conditional code. This includes other instances of either of these functions.

2 The boolean data type

This section describes a boolean data type which is closely connected to conditional processing as sometimes you want to execute some code depending on the value of a switch (*e.g.*, draft/final) and other times you perhaps want to use it as a predicate function in an `\if_predicate:w` test. The problem of the primitive `\if_false:` and `\if_true:` tokens is that it is not always safe to pass them around as they may interfere with scanning for termination of primitive conditional processing. Therefore, we employ two canonical booleans: `\c_true_bool` or `\c_false_bool`. Besides preventing problems as described above, it also allows us to implement a simple boolean parser supporting the logical operations And, Or, Not, *etc.* which can then be used on both the boolean type and predicate functions.

All conditional `\bool_` functions except assignments are expandable and expect the input to also be fully expandable (which generally means being constructed from predicate functions and booleans, possibly nested).

T_EXhackers note: The `bool` data type is not implemented using the `\iffalse/\iftrue` primitives, in contrast to `\newif`, *etc.*, in plain T_EX, L^AT_EX 2_ε and so on. Programmers should not base use of `bool` switches on any particular expectation of the implementation.

<code>\bool_new:N</code>	<code>\bool_new:N</code>	<code><boolean></code>
<code>\bool_new:c</code>		

Creates a new `<boolean>` or raises an error if the name is already taken. The declaration is global. The `<boolean>` is initially **false**.

<code>\bool_set_false:N</code>	<code>\bool_set_false:N</code>	<code><boolean></code>
<code>\bool_set_false:c</code>		
<code>\bool_gset_false:N</code>		
<code>\bool_gset_false:c</code>		

Sets `<boolean>` logically **false**.

<code>\bool_set_true:N</code>	<code>\bool_set_true:N</code>	<code><boolean></code>
<code>\bool_set_true:c</code>		
<code>\bool_gset_true:N</code>		
<code>\bool_gset_true:c</code>		

Sets `<boolean>` logically **true**.

```
\bool_set_eq:NN
\bool_set_eq:(cN|Nc|cc)
\bool_gset_eq:NN
\bool_gset_eq:(cN|Nc|cc)
```

`\bool_set_eq:NN` $\langle boolean_1 \rangle$ $\langle boolean_2 \rangle$
Sets $\langle boolean_1 \rangle$ to the current value of $\langle boolean_2 \rangle$.

```
\bool_set:Nn
\bool_set:cn
\bool_gset:Nn
\bool_gset:cn
```

`\bool_set:Nn` $\langle boolean \rangle$ $\{\langle boolexpr \rangle\}$
Evaluates the $\langle boolean expression \rangle$ as described for `\bool_if:nTF`, and sets the $\langle boolean \rangle$ variable to the logical truth of this evaluation.

Updated: 2017-07-15

```
\bool_if_p:N *
\bool_if_p:c *
\bool_if:NTF *
\bool_if:cTF *
```

`\bool_if_p:N` $\langle boolean \rangle$
`\bool_if:NTF` $\langle boolean \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
Tests the current truth of $\langle boolean \rangle$, and continues expansion based on this result.

Updated: 2017-07-15

```
\bool_show:N
\bool_show:c
```

`\bool_show:N` $\langle boolean \rangle$
Displays the logical truth of the $\langle boolean \rangle$ on the terminal.

New: 2012-02-09

Updated: 2015-08-01

```
\bool_show:n
```

`\bool_show:n` $\{\langle boolean expression \rangle\}$

New: 2012-02-09

Updated: 2017-07-15

```
\bool_log:N
\bool_log:c
```

`\bool_log:N` $\langle boolean \rangle$
Writes the logical truth of the $\langle boolean \rangle$ in the log file.

New: 2014-08-22

Updated: 2015-08-03

```
\bool_log:n
```

`\bool_log:n` $\{\langle boolean expression \rangle\}$

New: 2014-08-22

Updated: 2017-07-15

```
\bool_if_exist_p:N *
\bool_if_exist_p:c *
\bool_if_exist:NTF *
\bool_if_exist:cTF *
```

`\bool_if_exist_p:N` $\langle boolean \rangle$
`\bool_if_exist:NTF` $\langle boolean \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
Tests whether the $\langle boolean \rangle$ is currently defined. This does not check that the $\langle boolean \rangle$ really is a boolean variable.

New: 2012-03-03

```
\l_tmpa_bool
\l_tmpb_bool
```

A scratch boolean for local assignment. It is never used by the kernel code, and so is safe for use with any L^AT_EX3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.

`\g_tmpa_bool`
`\g_tmpb_bool`

A scratch boolean for global assignment. It is never used by the kernel code, and so is safe for use with any L^AT_EX3-defined function. However, it may be overwritten by other non-kernel code and so should only be used for short-term storage.

3 Boolean expressions

As we have a boolean datatype and predicate functions returning boolean $\langle true \rangle$ or $\langle false \rangle$ values, it seems only fitting that we also provide a parser for $\langle boolean\ expressions \rangle$.

A boolean expression is an expression which given input in the form of predicate functions and boolean variables, return boolean $\langle true \rangle$ or $\langle false \rangle$. It supports the logical operations And, Or and Not as the well-known infix operators `&&` and `||` and prefix `!` with their usual precedences (namely, `&&` binds more tightly than `||`). In addition to this, parentheses can be used to isolate sub-expressions. For example,

```
\int_compare_p:n { 1 = 1 } &&
(
  \int_compare_p:n { 2 = 3 } ||
  \int_compare_p:n { 4 <= 4 } ||
  \str_if_eq_p:nn { abc } { def }
) &&
! \int_compare_p:n { 2 = 4 }
```

is a valid boolean expression.

Contrarily to some other programming languages, the operators `&&` and `||` evaluate both operands in all cases, even when the first operand is enough to determine the result. This “eager” evaluation should be contrasted with the “lazy” evaluation of `\bool_lazy_...` functions.

T_EXhackers note: The eager evaluation of boolean expressions is unfortunately necessary in T_EX. Indeed, a lazy parser can get confused if `&&` or `||` or parentheses appear as (unbraced) arguments of some predicates. For instance, the innocuous-looking expression below would break (in a lazy parser) if `#1` were a closing parenthesis and `\l_tmpa_bool` were `true`.

```
( \l_tmpa_bool || \token_if_eq_meaning_p:NN X #1 )
```

Minimal (lazy) evaluation can be obtained using the conditionals `\bool_lazy_all:nTF`, `\bool_lazy_and:nnTF`, `\bool_lazy_any:nTF`, or `\bool_lazy_or:nnTF`, which only evaluate their boolean expression arguments when they are needed to determine the resulting truth value. For example, when evaluating the boolean expression

```
\bool_lazy_and_p:nn
{
  \bool_lazy_any_p:n
  {
    { \int_compare_p:n { 2 = 3 } }
    { \int_compare_p:n { 4 <= 4 } }
    { \int_compare_p:n { 1 = \error } } % skipped
  }
}
{ ! \int_compare_p:n { 2 = 4 } }
```

the line marked with `skipped` is not expanded because the result of `\bool_lazy_any_p:n` is known once the second boolean expression is found to be logically `true`. On the other hand, the last line is expanded because its logical value is needed to determine the result of `\bool_lazy_and_p:nn`.

<code>\bool_if_p:n</code> ★ <code>\bool_if:nTF</code> ★ <hr/> Updated: 2017-07-15	<code>\bool_if_p:n {⟨boolean expression⟩}</code> <code>\bool_if:nTF {⟨boolean expression⟩} {⟨true code⟩} {⟨false code⟩}</code>
---	---

Tests the current truth of *⟨boolean expression⟩*, and continues expansion based on this result. The *⟨boolean expression⟩* should consist of a series of predicates or boolean variables with the logical relationship between these defined using `&&` (“And”), `||` (“Or”), `!` (“Not”) and parentheses. The logical Not applies to the next predicate or group.

<code>\bool_lazy_all_p:n</code> ★ <code>\bool_lazy_all:nTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_all_p:n { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} }</code> <code>\bool_lazy_all:nTF { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} } {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “And” operation on the *⟨boolean expressions⟩*, hence is `true` if all of them are `true` and `false` if any of them is `false`. Contrarily to the infix operator `&&`, only the *⟨boolean expressions⟩* which are needed to determine the result of `\bool_lazy_all:nTF` are evaluated. See also `\bool_lazy_and:nnTF` when there are only two *⟨boolean expressions⟩*.

<code>\bool_lazy_and_p:nn</code> ★ <code>\bool_lazy_and:nnTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_and_p:nn {⟨boolexpr₁⟩} {⟨boolexpr₂⟩}</code> <code>\bool_lazy_and:nnTF {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “And” operation between two boolean expressions, hence is `true` if both are `true`. Contrarily to the infix operator `&&`, the *⟨boolexpr₂⟩* is only evaluated if it is needed to determine the result of `\bool_lazy_and:nnTF`. See also `\bool_lazy_all:nTF` when there are more than two *⟨boolean expressions⟩*.

<code>\bool_lazy_any_p:n</code> ★ <code>\bool_lazy_any:nTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_any_p:n { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} }</code> <code>\bool_lazy_any:nTF { {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} ... {⟨boolexpr_N⟩} } {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “Or” operation on the *⟨boolean expressions⟩*, hence is `true` if any of them is `true` and `false` if all of them are `false`. Contrarily to the infix operator `||`, only the *⟨boolean expressions⟩* which are needed to determine the result of `\bool_lazy_any:nTF` are evaluated. See also `\bool_lazy_or:nnTF` when there are only two *⟨boolean expressions⟩*.

<code>\bool_lazy_or_p:nn</code> ★ <code>\bool_lazy_or:nnTF</code> ★ <hr/> New: 2015-11-15 Updated: 2017-07-15	<code>\bool_lazy_or_p:nn {⟨boolexpr₁⟩} {⟨boolexpr₂⟩}</code> <code>\bool_lazy_or:nnTF {⟨boolexpr₁⟩} {⟨boolexpr₂⟩} {⟨true code⟩} {⟨false code⟩}</code>
--	---

Implements the “Or” operation between two boolean expressions, hence is `true` if either one is `true`. Contrarily to the infix operator `||`, the *⟨boolexpr₂⟩* is only evaluated if it is needed to determine the result of `\bool_lazy_or:nnTF`. See also `\bool_lazy_any:nTF` when there are more than two *⟨boolean expressions⟩*.

<code>\bool_not_p:n</code> ★ <hr/> Updated: 2017-07-15	<code>\bool_not_p:n {⟨boolean expression⟩}</code> Function version of <code>!(⟨boolean expression⟩)</code> within a boolean expression.
---	--

<code>\bool_xor_p:nn</code> ☆	<code>\bool_xor_p:nn {<boolexpr₁>} {<boolexpr₂>}</code>
<code>\bool_xor:nnTF</code> ☆	<code>\bool_xor:nnTF {<boolexpr₁>} {<boolexpr₂>} {<true code>} {<false code>}</code>
New: 2018-05-09	Implements an “exclusive or” operation between two boolean expressions. There is no infix operation for this logical operation.

4 Logical loops

Loops using either boolean expressions or stored boolean values.

<code>\bool_do_until:Nn</code> ☆	<code>\bool_do_until:Nn <boolean> {<code>}</code>
<code>\bool_do_until:cn</code> ☆	Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean></i> . If it is false then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean></i> is true .
Updated: 2017-07-15	
<code>\bool_do_while:Nn</code> ☆	<code>\bool_do_while:Nn <boolean> {<code>}</code>
<code>\bool_do_while:cn</code> ☆	Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean></i> . If it is true then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean></i> is false .
Updated: 2017-07-15	
<code>\bool_until_do:Nn</code> ☆	<code>\bool_until_do:Nn <boolean> {<code>}</code>
<code>\bool_until_do:cn</code> ☆	This function firsts checks the logical value of the <i><boolean></i> . If it is false the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean></i> is re-evaluated. The process then loops until the <i><boolean></i> is true .
Updated: 2017-07-15	
<code>\bool_while_do:Nn</code> ☆	<code>\bool_while_do:Nn <boolean> {<code>}</code>
<code>\bool_while_do:cn</code> ☆	This function firsts checks the logical value of the <i><boolean></i> . If it is true the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean></i> is re-evaluated. The process then loops until the <i><boolean></i> is false .
Updated: 2017-07-15	
<code>\bool_do_until:nn</code> ☆	<code>\bool_do_until:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean expression></i> as described for <code>\bool_if:nTF</code> . If it is false then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean expression></i> evaluates to true .
<code>\bool_do_while:nn</code> ☆	<code>\bool_do_while:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	Places the <i><code></i> in the input stream for T _E X to process, and then checks the logical value of the <i><boolean expression></i> as described for <code>\bool_if:nTF</code> . If it is true then the <i><code></i> is inserted into the input stream again and the process loops until the <i><boolean expression></i> evaluates to false .
<code>\bool_until_do:nn</code> ☆	<code>\bool_until_do:nn {<boolean expression>} {<code>}</code>
Updated: 2017-07-15	This function firsts checks the logical value of the <i><boolean expression></i> (as described for <code>\bool_if:nTF</code>). If it is false the <i><code></i> is placed in the input stream and expanded. After the completion of the <i><code></i> the truth of the <i><boolean expression></i> is re-evaluated. The process then loops until the <i><boolean expression></i> is true .

`\bool_while_do:nn` ★

Updated: 2017-07-15

`\bool_while_do:nn` $\{\langle\textit{boolean expression}\rangle\}$ $\{\langle\textit{code}\rangle\}$

This function firsts checks the logical value of the $\langle\textit{boolean expression}\rangle$ (as described for `\bool_if:nTF`). If it is `true` the $\langle\textit{code}\rangle$ is placed in the input stream and expanded. After the completion of the $\langle\textit{code}\rangle$ the truth of the $\langle\textit{boolean expression}\rangle$ is re-evaluated. The process then loops until the $\langle\textit{boolean expression}\rangle$ is `false`.

5 Producing multiple copies

`\prg_replicate:nn` ★

Updated: 2011-07-04

`\prg_replicate:nn` $\{\langle\textit{integer expression}\rangle\}$ $\{\langle\textit{tokens}\rangle\}$

Evaluates the $\langle\textit{integer expression}\rangle$ (which should be zero or positive) and creates the resulting number of copies of the $\langle\textit{tokens}\rangle$. The function is both expandable and safe for nesting. It yields its result after two expansion steps.

6 Detecting T_EX's mode

`\mode_if_horizontal_p:` ★

`\mode_if_horizontal:TF` ★

`\mode_if_horizontal_p:`

`\mode_if_horizontal:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in horizontal mode.

`\mode_if_inner_p:` ★

`\mode_if_inner:TF` ★

`\mode_if_inner_p:`

`\mode_if_inner:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in inner mode.

`\mode_if_math_p:` ★

`\mode_if_math:TF` ★

`\mode_if_math:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in maths mode.

Updated: 2011-09-05

`\mode_if_vertical_p:` ★

`\mode_if_vertical:TF` ★

`\mode_if_vertical_p:`

`\mode_if_vertical:TF` $\{\langle\textit{true code}\rangle\}$ $\{\langle\textit{false code}\rangle\}$

Detects if T_EX is currently in vertical mode.

7 Primitive conditionals

`\if_predicate:w` ★

`\if_predicate:w` $\langle\textit{predicate}\rangle$ $\langle\textit{true code}\rangle$ `\else:` $\langle\textit{false code}\rangle$ `\fi:`

This function takes a predicate function and branches according to the result. (In practice this function would also accept a single boolean variable in place of the $\langle\textit{predicate}\rangle$ but to make the coding clearer this should be done through `\if_bool:N`.)

`\if_bool:N` ★

`\if_bool:N` $\langle\textit{boolean}\rangle$ $\langle\textit{true code}\rangle$ `\else:` $\langle\textit{false code}\rangle$ `\fi:`

This function takes a boolean variable and branches according to the result.

8 Nestable recursions and mappings

There are a number of places where recursion or mapping constructs are used in `expl3`. At a low-level, these typically require insertion of tokens at the end of the content to allow “clean up”. To support such mappings in a nestable form, the following functions are provided.

<code>\prg_break_point:Nn</code> ★	<code>\prg_break_point:Nn \<type>_map_break: {\<code>}</code>
New: 2018-03-26	Used to mark the end of a recursion or mapping: the functions <code>\<type>_map_break:</code> and <code>\<type>_map_break:n</code> use this to break out of the loop (see <code>\prg_map_break:Nn</code> for how to set these up). After the loop ends, the <code>\<code></code> is inserted into the input stream. This occurs even if the break functions are <i>not</i> applied: <code>\prg_break_point:Nn</code> is functionally-equivalent in these cases to <code>\use_ii:nn</code> .

<code>\prg_map_break:Nn</code> ★	<code>\prg_map_break:Nn \<type>_map_break: {\<user code>}</code>
New: 2018-03-26	... <code>\prg_break_point:Nn \<type>_map_break: {\<ending code>}</code>
	Breaks a recursion in mapping contexts, inserting in the input stream the <code>\<user code></code> after the <code>\<ending code></code> for the loop. The function breaks loops, inserting their <code>\<ending code></code> , until reaching a loop with the same <code>\<type></code> as its first argument. This <code>\<type>_map_break:</code> argument must be defined; it is simply used as a recognizable marker for the <code>\<type></code> .

For types with mappings defined in the kernel, `\<type>_map_break:` and `\<type>_map_break:n` are defined as `\prg_map_break:Nn \<type>_map_break: {}` and the same with `{}` omitted.

8.1 Simple mappings

In addition to the more complex mappings above, non-nestable mappings are used in a number of locations and support is provided for these.

<code>\prg_break_point:</code> ★	This copy of <code>\prg_do_nothing:</code> is used to mark the end of a fast short-term recursion: the function <code>\prg_break:n</code> uses this to break out of the loop.
New: 2018-03-27	
<code>\prg_break:</code> ★	<code>\prg_break:n {\<code>} ... \prg_break_point:</code>
<code>\prg_break:n</code> ★	Breaks a recursion which has no <code>\<ending code></code> and which is not a user-breakable mapping (see for instance <code>\prop_get:Nn</code>), and inserts the <code>\<code></code> in the input stream.
New: 2018-03-27	

9 Internal programming functions

<code>\group_align_safe_begin:</code>	★	<code>\group_align_safe_begin:</code>
<code>\group_align_safe_end:</code>	★	<code>...</code>
		<code>\group_align_safe_end:</code>

Updated: 2011-08-11

These functions are used to enclose material in a \TeX alignment environment within a specially-constructed group. This group is designed in such a way that it does not add brace groups to the output but does act as a group for the `&` token inside `\halign`. This is necessary to allow grabbing of tokens for testing purposes, as \TeX uses group level to determine the effect of alignment tokens. Without the special grouping, the use of a function such as `\peek_after:Nw` would result in a forbidden comparison of the internal `\endtemplate` token, yielding a fatal error. Each `\group_align_safe_begin:` must be matched by a `\group_align_safe_end:`, although this does not have to occur within the same function.

Part XIII

The l3sys package: System/runtime functions

1 The name of the job

`\c_sys_jobname_str`

New: 2015-09-19

Constant that gets the “job name” assigned when T_EX starts.

T_EXhackers note: This copies the contents of the primitive `\jobname`. It is a constant that is set by T_EX and should not be overwritten by the package.

2 Date and time

`\c_sys_minute_int`
`\c_sys_hour_int`
`\c_sys_day_int`
`\c_sys_month_int`
`\c_sys_year_int`

New: 2015-09-22

The date and time at which the current job was started: these are all reported as integers.

T_EXhackers note: Whilst the underlying primitives can be altered by the user, this interface to the time and date is intended to be the “real” values.

3 Engine

`\sys_if_engine luatex_p:` ★
`\sys_if_engine luatex:` *TF* ★
`\sys_if_engine pdftex_p:` ★
`\sys_if_engine pdftex:` *TF* ★
`\sys_if_engine ptex_p:` ★
`\sys_if_engine ptex:` *TF* ★
`\sys_if_engine uptex_p:` ★
`\sys_if_engine uptex:` *TF* ★
`\sys_if_engine xetex_p:` ★
`\sys_if_engine xetex:` *TF* ★

New: 2015-09-07

`\sys_if_engine pdftex:TF` *{(true code)}* *{(false code)}*

Conditionals which allow engine-specific code to be used. The names follow naturally from those of the engine binaries: note that the (u)pt_EX tests are for ε -pT_EX and ε -upT_EX as expl3 requires the ε -T_EX extensions. Each conditional is true for *exactly one* supported engine. In particular, `\sys_if_engine ptex_p:` is true for ε -pT_EX but false for ε -upT_EX.

`\c_sys_engine_str`

New: 2015-09-19

The current engine given as a lower case string: one of `luatex`, `pdftex`, `ptex`, `uptex` or `xetex`.

4 Output format

<code>\sys_if_output_dvi_p:</code>	★	<code>\sys_if_output_dvi:TF</code>	<code>{\true code}</code>	<code>{\false code}</code>
<code>\sys_if_output_dvi:</code>	<u>TF</u> ★	Conditionals which give the current output mode the TeX run is operating in. This is always one of two outcomes, DVI mode or PDF mode. The two sets of conditionals are thus complementary and are both provided to allow the programmer to emphasise the most appropriate case.		
<code>\sys_if_output_pdf_p:</code>	★			
<code>\sys_if_output_pdf:</code>	<u>TF</u> ★			
New: 2015-09-19				

<code>\c_sys_output_str</code>	The current output mode given as a lower case string: one of <code>dvi</code> or <code>pdf</code> .
New: 2015-09-19	

Part XIV

The `l3clist` package

Comma separated lists

Comma lists contain ordered data where items can be added to the left or right end of the list. This data type allows basic list manipulations such as adding/removing items, applying a function to every item, removing duplicate items, extracting a given item, using the comma list with specified separators, and so on. Sequences (defined in `l3seq`) are safer, faster, and provide more features, so they should often be preferred to comma lists. Comma lists are mostly useful when interfacing with L^AT_EX 2_ε or other code that expects or provides comma list data.

Several items can be added at once. To ease input of comma lists from data provided by a user outside an `\ExplSyntaxOn ... \ExplSyntaxOff` block, spaces are removed from both sides of each comma-delimited argument upon input. Blank arguments are ignored, to allow for trailing commas or repeated commas (which may otherwise arise when concatenating comma lists “by hand”). In addition, a set of braces is removed if the result of space-trimming is braced: this allows the storage of any item in a comma list. For instance,

```
\clist_new:N \l_my_clist
\clist_put_left:Nn \l_my_clist { ~a~ , ~{b}~ , c~\d }
\clist_put_right:Nn \l_my_clist { ~{e}~ , , {{f}} , }
```

results in `\l_my_clist` containing `a,b,c~\d,{e~},{{f}}` namely the five items `a`, `b`, `c~\d`, `e~` and `{f}`. Comma lists normally do not contain empty items so the following gives an empty comma list:

```
\clist_clear_new:N \l_my_clist
\clist_put_right:Nn \l_my_clist { , ~ , , }
\clist_if_empty:NTF \l_my_clist { true } { false }
```

and it leaves `true` in the input stream. To include an “unsafe” item (empty, or one that contains a comma, or starts or ends with a space, or is a single brace group), surround it with braces.

Almost all operations on comma lists are noticeably slower than those on sequences so converting the data to sequences using `\seq_set_from_clist:Nn` (see `l3seq`) may be advisable if speed is important. The exception is that `\clist_if_in:NnTF` and `\clist_remove_duplicates:N` may be faster than their sequence analogues for large lists. However, these functions work slowly for “unsafe” items that must be braced, and may produce errors when their argument contains `{`, `}` or `#` (assuming the usual T_EX category codes apply). In addition, comma lists cannot store quarks `\q_mark` or `\q_stop`. The sequence data type should thus certainly be preferred to comma lists to store such items.

1 Creating and initialising comma lists

<code>\clist_new:N</code>	<code>\clist_new:N <comma list></code>
<code>\clist_new:c</code>	

Creates a new *<comma list>* or raises an error if the name is already taken. The declaration is global. The *<comma list>* initially contains no items.

<hr/> <code>\clist_const:Nn</code> <code>\clist_const:(Nx cn cx)</code> <hr/> New: 2014-07-05	<code>\clist_const:Nn <clist var> {{<comma list>}}</code> Creates a new constant <i><clist var></i> or raises an error if the name is already taken. The value of the <i><clist var></i> is set globally to the <i><comma list></i> .
<hr/> <code>\clist_clear:N</code> <code>\clist_clear:c</code> <code>\clist_gclear:N</code> <code>\clist_gclear:c</code> <hr/>	<code>\clist_clear:N <comma list></code> Clears all items from the <i><comma list></i> .
<hr/> <code>\clist_clear_new:N</code> <code>\clist_clear_new:c</code> <code>\clist_gclear_new:N</code> <code>\clist_gclear_new:c</code> <hr/>	<code>\clist_clear_new:N <comma list></code> Ensures that the <i><comma list></i> exists globally by applying <code>\clist_new:N</code> if necessary, then applies <code>\clist_(g)clear:N</code> to leave the list empty.
<hr/> <code>\clist_set_eq:NN</code> <code>\clist_set_eq:(cN Nc cc)</code> <code>\clist_gset_eq:NN</code> <code>\clist_gset_eq:(cN Nc cc)</code> <hr/>	<code>\clist_set_eq:NN <comma list₁> <comma list₂></code> Sets the content of <i><comma list₁></i> equal to that of <i><comma list₂></i> .
<hr/> <code>\clist_set_from_seq:NN</code> <code>\clist_set_from_seq:(cN Nc cc)</code> <code>\clist_gset_from_seq:NN</code> <code>\clist_gset_from_seq:(cN Nc cc)</code> <hr/> New: 2014-07-17	<code>\clist_set_from_seq:NN <comma list> <sequence></code> Converts the data in the <i><sequence></i> into a <i><comma list></i> : the original <i><sequence></i> is unchanged. Items which contain either spaces or commas are surrounded by braces.
<hr/> <code>\clist_concat:NNN</code> <code>\clist_concat:ccc</code> <code>\clist_gconcat:NNN</code> <code>\clist_gconcat:ccc</code> <hr/>	<code>\clist_concat:NNN <comma list₁> <comma list₂> <comma list₃></code> Concatenates the content of <i><comma list₂></i> and <i><comma list₃></i> together and saves the result in <i><comma list₁></i> . The items in <i><comma list₂></i> are placed at the left side of the new comma list.
<hr/> <code>\clist_if_exist_p:N</code> ★ <code>\clist_if_exist_p:c</code> ★ <code>\clist_if_exist:NTF</code> ★ <code>\clist_if_exist:cTF</code> ★ <hr/> New: 2012-03-03	<code>\clist_if_exist_p:N <comma list></code> <code>\clist_if_exist:NTF <comma list> {{<true code>}} {{<false code>}}</code> Tests whether the <i><comma list></i> is currently defined. This does not check that the <i><comma list></i> really is a comma list.

2 Adding data to comma lists

<code>\clist_set:Nn</code>	<code>\clist_set:Nn <comma list> {\<item_1>, ..., \<item_n>}</code>
<code>\clist_set:(NV No Nx cn cV co cx)</code>	
<code>\clist_gset:Nn</code>	
<code>\clist_gset:(NV No Nx cn cV co cx)</code>	

New: 2011-09-06

Sets $\langle comma list \rangle$ to contain the $\langle items \rangle$, removing any previous content from the variable. Blank items are omitted, spaces are removed from both sides of each item, then a set of braces is removed if the resulting space-trimmed item is braced. To store some $\langle tokens \rangle$ as a single $\langle item \rangle$ even if the $\langle tokens \rangle$ contain commas or spaces, add a set of braces: `\clist_set:Nn <comma list> { {\<tokens>} }`.

<code>\clist_put_left:Nn</code>	<code>\clist_put_left:Nn <comma list> {\<item_1>, ..., \<item_n>}</code>
<code>\clist_put_left:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_left:Nn</code>	
<code>\clist_gput_left:(NV No Nx cn cV co cx)</code>	

Updated: 2011-09-05

Appends the $\langle items \rangle$ to the left of the $\langle comma list \rangle$. Blank items are omitted, spaces are removed from both sides of each item, then a set of braces is removed if the resulting space-trimmed item is braced. To append some $\langle tokens \rangle$ as a single $\langle item \rangle$ even if the $\langle tokens \rangle$ contain commas or spaces, add a set of braces: `\clist_put_left:Nn <comma list> { {\<tokens>} }`.

<code>\clist_put_right:Nn</code>	<code>\clist_put_right:Nn <comma list> {\<item_1>, ..., \<item_n>}</code>
<code>\clist_put_right:(NV No Nx cn cV co cx)</code>	
<code>\clist_gput_right:Nn</code>	
<code>\clist_gput_right:(NV No Nx cn cV co cx)</code>	

Updated: 2011-09-05

Appends the $\langle items \rangle$ to the right of the $\langle comma list \rangle$. Blank items are omitted, spaces are removed from both sides of each item, then a set of braces is removed if the resulting space-trimmed item is braced. To append some $\langle tokens \rangle$ as a single $\langle item \rangle$ even if the $\langle tokens \rangle$ contain commas or spaces, add a set of braces: `\clist_put_right:Nn <comma list> { {\<tokens>} }`.

3 Modifying comma lists

While comma lists are normally used as ordered lists, it may be necessary to modify the content. The functions here may be used to update comma lists, while retaining the order of the unaffected entries.

<code>\clist_remove_duplicates:N</code>	<code>\clist_remove_duplicates:N <comma list></code>
<code>\clist_remove_duplicates:c</code>	
<code>\clist_gremove_duplicates:N</code>	
<code>\clist_gremove_duplicates:c</code>	

Removes duplicate items from the $\langle comma list \rangle$, leaving the left most copy of each item in the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

T_EXhackers note: This function iterates through every item in the $\langle comma list \rangle$ and does a comparison with the $\langle items \rangle$ already checked. It is therefore relatively slow with large comma lists. Furthermore, it may fail if any of the items in the $\langle comma list \rangle$ contains `{`, `}`, or `#` (assuming the usual T_EX category codes apply).

<code>\clist_remove_all:Nn</code>	<code>\clist_remove_all:Nn <comma list> {<item>}</code>
<code>\clist_remove_all:cn</code>	
<code>\clist_gremove_all:Nn</code>	
<code>\clist_gremove_all:cn</code>	

Removes every occurrence of $\langle item \rangle$ from the $\langle comma list \rangle$. The $\langle item \rangle$ comparison takes place on a token basis, as for `\tl_if_eq:nn(TF)`.

Updated: 2011-09-06

T_EXhackers note: The function may fail if the $\langle item \rangle$ contains `{`, `}`, or `#` (assuming the usual T_EX category codes apply).

<code>\clist_reverse:N</code>	<code>\clist_reverse:N <comma list></code>
<code>\clist_reverse:c</code>	
<code>\clist_greverse:N</code>	
<code>\clist_greverse:c</code>	

New: 2014-07-18

Reverses the order of items stored in the $\langle comma list \rangle$.

<code>\clist_reverse:n</code>	<code>\clist_reverse:n {<comma list>}</code>
-------------------------------	--

New: 2014-07-18

Leaves the items in the $\langle comma list \rangle$ in the input stream in reverse order. Contrarily to other what is done for other n-type $\langle comma list \rangle$ arguments, braces and spaces are preserved by this process.

T_EXhackers note: The result is returned within `\unexpanded`, which means that the comma list does not expand further when appearing in an x-type argument expansion.

<code>\clist_sort:Nn</code>	<code>\clist_sort:Nn <clist var> {<comparison code>}</code>
<code>\clist_sort:cn</code>	
<code>\clist_gsort:Nn</code>	
<code>\clist_gsort:cn</code>	

New: 2017-02-06

Sorts the items in the $\langle clist var \rangle$ according to the $\langle comparison code \rangle$, and assigns the result to $\langle clist var \rangle$. The details of sorting comparison are described in Section 1.

4 Comma list conditionals

<code>\clist_if_empty_p:N</code> ★	<code>\clist_if_empty_p:N <comma list></code>
<code>\clist_if_empty_p:c</code> ★	<code>\clist_if_empty_p:NTF <comma list> {<true code>} {<false code>}</code>
<code>\clist_if_empty:N\underline{TF}</code> ★	
<code>\clist_if_empty:c\underline{TF}</code> ★	Tests if the $\langle comma list \rangle$ is empty (containing no items).

<code>\clist_if_empty_p:n</code> ★	<code>\clist_if_empty_p:n {⟨comma list⟩}</code>
<code>\clist_if_empty:nTF</code> ★	<code>\clist_if_empty:nTF {⟨comma list⟩} {⟨true code⟩} {⟨false code⟩}</code>

New: 2014-07-05

Tests if the $\langle comma list \rangle$ is empty (containing no items). The rules for space trimming are as for other n -type comma-list functions, hence the comma list $\{\sim, \sim, \sim\}$ (without outer braces) is empty, while $\{\sim, \{\}, \}$ (without outer braces) contains one element, which happens to be empty: the comma-list is not empty.

<code>\clist_if_in:NnTF</code>	<code>\clist_if_in:NnTF ⟨comma list⟩ {⟨item⟩} {⟨true code⟩} {⟨false code⟩}</code>
<code>\clist_if_in:(NV No cn cV co)TF</code>	
<code>\clist_if_in:nnTF</code>	
<code>\clist_if_in:(nV no)TF</code>	

Updated: 2011-09-06

Tests if the $\langle item \rangle$ is present in the $\langle comma list \rangle$. In the case of an n -type $\langle comma list \rangle$, the usual rules of space trimming and brace stripping apply. Hence,

`\clist_if_in:nnTF { a , {b}~ , {b} , c } { b } {true} {false}`

yields `true`.

T_EXhackers note: The function may fail if the $\langle item \rangle$ contains $\{$, $\}$, or $\#$ (assuming the usual T_EX category codes apply).

5 Mapping to comma lists

The functions described in this section apply a specified function to each item of a comma list.

When the comma list is given explicitly, as an n -type argument, spaces are trimmed around each item. If the result of trimming spaces is empty, the item is ignored. Otherwise, if the item is surrounded by braces, one set is removed, and the result is passed to the mapped function. Thus, if the comma list that is being mapped is $\{a_{\square},_{\square}\{b\}_{\square},_{\square},\{\},_{\square}\{c\},\}$ then the arguments passed to the mapped function are ‘ a ’, ‘ b ’, an empty argument, and ‘ c ’.

When the comma list is given as an N -type argument, spaces have already been trimmed on input, and items are simply stripped of one set of braces if any. This case is more efficient than using n -type comma lists.

<code>\clist_map_function:NN</code> ★	<code>\clist_map_function:NN ⟨comma list⟩ ⟨function⟩</code>
---------------------------------------	---

`\clist_map_function:cN` ★

`\clist_map_function:nN` ★

Updated: 2012-06-29

Applies $\langle function \rangle$ to every $\langle item \rangle$ stored in the $\langle comma list \rangle$. The $\langle function \rangle$ receives one argument for each iteration. The $\langle items \rangle$ are returned from left to right. The function `\clist_map_inline:Nn` is in general more efficient than `\clist_map_function:NN`.

<code>\clist_map_inline:Nn</code>	<code>\clist_map_inline:Nn ⟨comma list⟩ {⟨inline function⟩}</code>
-----------------------------------	--

`\clist_map_inline:cn`

`\clist_map_inline:nn`

Updated: 2012-06-29

Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle comma list \rangle$. The $\langle inline function \rangle$ should consist of code which receives the $\langle item \rangle$ as $\#1$. The $\langle items \rangle$ are returned from left to right.

<code>\clist_map_variable:NNn</code>	<code>\clist_map_variable:NNn <comma list> <variable> {<code>}</code>
<code>\clist_map_variable:cNn</code>	Stores each <i><item></i> of the <i><comma list></i> in turn in the (token list) <i><variable></i> and applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced.
<code>\clist_map_variable:nNn</code>	The assignments to the <i><variable></i> are local. The <i><items></i> are returned from left to right.
Updated: 2012-06-29	

<code>\clist_map_break:</code> ☆	<code>\clist_map_break:</code>
Updated: 2012-06-29	Used to terminate a <code>\clist_map...</code> function before all entries in the <i><comma list></i> have been processed. This normally takes place within a conditional statement, for example

```

\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break: }
  {
    % Do something useful
  }
}

```

Use outside of a `\clist_map...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

<code>\clist_map_break:n</code> ☆	<code>\clist_map_break:n {<code>}</code>
Updated: 2012-06-29	Used to terminate a <code>\clist_map...</code> function before all entries in the <i><comma list></i> have been processed, inserting the <i><code></i> after the mapping has ended. This normally takes place within a conditional statement, for example

```

\clist_map_inline:Nn \l_my_clist
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \clist_map_break:n { <code> } }
  {
    % Do something useful
  }
}

```

Use outside of a `\clist_map...` scenario leads to low level T_EX errors.

T_EXhackers note: When the mapping is broken, additional tokens may be inserted before the *<code>* is inserted into the input stream. This depends on the design of the mapping function.

<code>\clist_count:N</code> ☆	<code>\clist_count:N <comma list></code>
<code>\clist_count:c</code> ☆	Leaves the number of items in the <i><comma list></i> in the input stream as an <i><integer denotation></i> . The total number of items in a <i><comma list></i> includes those which are duplicates, <i>i.e.</i> every item in a <i><comma list></i> is counted.
<code>\clist_count:n</code> ☆	
New: 2012-07-13	

6 Using the content of comma lists directly

<code>\clist_use:Nnnn</code> ★ <code>\clist_use:cnnn</code> ★	<code>\clist_use:Nnnn <clist var> {<separator between two>}</code> <code>{<separator between more than two>} {<separator between final two>}</code>
--	--

New: 2013-05-26

Places the contents of the $\langle\textit{clist var}\rangle$ in the input stream, with the appropriate $\langle\textit{separator}\rangle$ between the items. Namely, if the comma list has more than two items, the $\langle\textit{separator between more than two}\rangle$ is placed between each pair of items except the last, for which the $\langle\textit{separator between final two}\rangle$ is used. If the comma list has exactly two items, then they are placed in the input stream separated by the $\langle\textit{separator between two}\rangle$. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nnnn \l_tmpa_clist { ~and~ } { ,~ } { ,~and~ }
```

inserts “a, b, c, de, and f” in the input stream. The first separator argument is not used in this case because the comma list has more than 2 items.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle\textit{items}\rangle$ do not expand further when appearing in an x-type argument expansion.

<code>\clist_use:Nn</code> ★ <code>\clist_use:cn</code> ★	<code>\clist_use:Nn <clist var> {<separator>}</code>
--	--

New: 2013-05-26

Places the contents of the $\langle\textit{clist var}\rangle$ in the input stream, with the $\langle\textit{separator}\rangle$ between the items. If the comma list has a single item, it is placed in the input stream, and a comma list with no items produces no output. An error is raised if the variable does not exist or if it is invalid.

For example,

```
\clist_set:Nn \l_tmpa_clist { a , b , , c , {de} , f }
\clist_use:Nn \l_tmpa_clist { ~and~ }
```

inserts “a and b and c and de and f” in the input stream.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle\textit{items}\rangle$ do not expand further when appearing in an x-type argument expansion.

7 Comma lists as stacks

Comma lists can be used as stacks, where data is pushed to and popped from the top of the comma list. (The left of a comma list is the top, for performance reasons.) The stack functions for comma lists are not intended to be mixed with the general ordered data functions detailed in the previous section: a comma list should either be used as an ordered data type or as a stack, but not in both ways.

<u>\clist_get:NN</u> <u>\clist_get:cN</u> <hr/> Updated: 2012-05-14	<u>\clist_get:NN</u> $\langle comma list \rangle$ $\langle token list variable \rangle$ Stores the left-most item from a $\langle comma list \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle comma list \rangle$. The $\langle token list variable \rangle$ is assigned locally. If the $\langle comma list \rangle$ is empty the $\langle token list variable \rangle$ is set to the marker value $\backslash q_no_value$.
---	--

<u>\clist_get:NNTF</u> <u>\clist_get:cNTF</u> <hr/> New: 2012-05-14	<u>\clist_get:NNTF</u> $\langle comma list \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ If the $\langle comma list \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle comma list \rangle$ is non-empty, stores the top item from the $\langle comma list \rangle$ in the $\langle token list variable \rangle$ without removing it from the $\langle comma list \rangle$. The $\langle token list variable \rangle$ is assigned locally.
---	--

<u>\clist_pop:NN</u> <u>\clist_pop:cN</u> <hr/> Updated: 2011-09-06	<u>\clist_pop:NN</u> $\langle comma list \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle comma list \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the comma list and stores it in the $\langle token list variable \rangle$. Both of the variables are assigned locally.
---	---

<u>\clist_gpop:NN</u> <u>\clist_gpop:cN</u>	<u>\clist_gpop:NN</u> $\langle comma list \rangle$ $\langle token list variable \rangle$ Pops the left-most item from a $\langle comma list \rangle$ into the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the comma list and stores it in the $\langle token list variable \rangle$. The $\langle comma list \rangle$ is modified globally, while the assignment of the $\langle token list variable \rangle$ is local.
--	---

<u>\clist_pop:NNTF</u> <u>\clist_pop:cNTF</u> <hr/> New: 2012-05-14	<u>\clist_pop:NNTF</u> $\langle comma list \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ If the $\langle comma list \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle comma list \rangle$ is non-empty, pops the top item from the $\langle comma list \rangle$ in the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the $\langle comma list \rangle$. Both the $\langle comma list \rangle$ and the $\langle token list variable \rangle$ are assigned locally.
---	--

<u>\clist_gpop:NNTF</u> <u>\clist_gpop:cNTF</u> <hr/> New: 2012-05-14	<u>\clist_gpop:NNTF</u> $\langle comma list \rangle$ $\langle token list variable \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$ If the $\langle comma list \rangle$ is empty, leaves the $\langle false code \rangle$ in the input stream. The value of the $\langle token list variable \rangle$ is not defined in this case and should not be relied upon. If the $\langle comma list \rangle$ is non-empty, pops the top item from the $\langle comma list \rangle$ in the $\langle token list variable \rangle$, <i>i.e.</i> removes the item from the $\langle comma list \rangle$. The $\langle comma list \rangle$ is modified globally, while the $\langle token list variable \rangle$ is assigned locally.
---	---

<u>\clist_push:Nn</u> <u>\clist_push:(NV No Nx cn cV co cx)</u> <u>\clist_gpush:Nn</u> <u>\clist_gpush:(NV No Nx cn cV co cx)</u>	<u>\clist_push:Nn</u> $\langle comma list \rangle$ $\{\langle items \rangle\}$
--	--

Adds the $\{\langle items \rangle\}$ to the top of the $\langle comma list \rangle$. Spaces are removed from both sides of each item as for any *n*-type comma list.

8 Using a single item

<hr/>	
<code>\clist_item:Nn</code> ★	<code>\clist_item:Nn <comma list> {<integer expression>}</code>
<code>\clist_item:cn</code> ★	
<code>\clist_item:nn</code> ★	
<hr/>	
New: 2014-07-17	Indexing items in the <i><comma list></i> from 1 at the top (left), this function evaluates the <i><integer expression></i> and leaves the appropriate item from the comma list in the input stream. If the <i><integer expression></i> is negative, indexing occurs from the bottom (right) of the comma list. When the <i><integer expression></i> is larger than the number of items in the <i><comma list></i> (as calculated by <code>\clist_count:N</code>) then the function expands to nothing.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

<hr/>	
<code>\clist_rand_item:N</code> ★	<code>\clist_rand_item:N <clist var></code>
<code>\clist_rand_item:c</code> ★	<code>\clist_rand_item:n {<comma list>}</code>
<code>\clist_rand_item:n</code> ★	
<hr/>	
New: 2016-12-06	Selects a pseudo-random item of the <i><comma list></i> . If the <i><comma list></i> has no item, the result is empty.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an x-type argument expansion.

9 Viewing comma lists

<hr/>	
<code>\clist_show:N</code>	<code>\clist_show:N <comma list></code>
<code>\clist_show:c</code>	
<hr/>	
Updated: 2015-08-03	Displays the entries in the <i><comma list></i> in the terminal.

<hr/>	
<code>\clist_show:n</code>	<code>\clist_show:n {<tokens>}</code>
<hr/>	
Updated: 2013-08-03	Displays the entries in the comma list in the terminal.

<hr/>	
<code>\clist_log:N</code>	<code>\clist_log:N <comma list></code>
<code>\clist_log:c</code>	
<hr/>	
New: 2014-08-22	
Updated: 2015-08-03	Writes the entries in the <i><comma list></i> in the log file. See also <code>\clist_show:N</code> which displays the result in the terminal.

<hr/>	
<code>\clist_log:n</code>	<code>\clist_log:n {<tokens>}</code>
<hr/>	
New: 2014-08-22	Writes the entries in the comma list in the log file. See also <code>\clist_show:n</code> which displays the result in the terminal.

10 Constant and scratch comma lists

<code>\c_empty_clist</code>	Constant that is always empty.
-----------------------------	--------------------------------

New: 2012-07-02

<code>\l_tmpa_clist</code> <code>\l_tmpb_clist</code>	Scratch comma lists for local assignment. These are never used by the kernel code, and so are safe for use with any \LaTeX 3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

New: 2011-09-06

<code>\g_tmpa_clist</code> <code>\g_tmpb_clist</code>	Scratch comma lists for global assignment. These are never used by the kernel code, and so are safe for use with any \LaTeX 3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

New: 2011-09-06

Part XV

The l3token package

Token manipulation

This module deals with tokens. Now this is perhaps not the most precise description so let's try with a better description: When programming in T_EX, it is often desirable to know just what a certain token is: is it a control sequence or something else. Similarly one often needs to know if a control sequence is expandable or not, a macro or a primitive, how many arguments it takes etc. Another thing of great importance (especially when it comes to document commands) is looking ahead in the token stream to see if a certain character is present and maybe even remove it or disregard other tokens while scanning. This module provides functions for both and as such has two primary function categories: `\token_` for anything that deals with tokens and `\peek_` for looking ahead in the token stream.

Most functions we describe here can be used on control sequences, as those are tokens as well.

It is important to distinguish two aspects of a token: its “shape” (for lack of a better word), which affects the matching of delimited arguments and the comparison of token lists containing this token, and its “meaning”, which affects whether the token expands or what operation it performs. One can have tokens of different shapes with the same meaning, but not the converse.

For instance, `\if:w`, `\if_charcode:w`, and `\tex_if:D` are three names for the same internal operation of T_EX, namely the primitive testing the next two characters for equality of their character code. They have the same meaning hence behave identically in many situations. However, T_EX distinguishes them when searching for a delimited argument. Namely, the example function `\show_until_if:w` defined below takes everything until `\if:w` as an argument, despite the presence of other copies of `\if:w` under different names.

```
\cs_new:Npn \show_until_if:w #1 \if:w { \tl_show:n {#1} }
\show_until_if:w \tex_if:D \if_charcode:w \if:w
```

A list of all possible shapes and a list of all possible meanings are given in section 8.

1 Creating character tokens

```
\char_set_active_eq:NN
\char_set_active_eq:Nc
\char_gset_active_eq:NN
\char_gset_active_eq:Nc
```

Updated: 2015-11-12

```
\char_set_active_eq:NN <char> <function>
```

Sets the behaviour of the `<char>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

```
\char_set_active_eq:nN
\char_set_active_eq:nc
\char_gset_active_eq:nN
\char_gset_active_eq:nc
```

New: 2015-11-12

```
\char_set_active_eq:nN {<integer expression>} <function>
```

Sets the behaviour of the `<char>` which has character code as given by the `<integer expression>` in situations where it is active (category code 13) to be equivalent to that of the `<function>`. The category code of the `<char>` is *unchanged* by this process. The `<function>` may itself be an active character.

<hr/> <code>\char_generate:nn</code> ★ <hr/>	<code>\char_generate:nn {<charcode>} {<catcode>}</code>
New: 2015-09-09 Updated: 2018-04-19	Generates a character token of the given $\langle charcode \rangle$ and $\langle catcode \rangle$ (both of which may be integer expressions). The $\langle catcode \rangle$ may be one of

- 1 (begin group)
- 2 (end group)
- 3 (math toggle)
- 4 (alignment)
- 6 (parameter)
- 7 (math superscript)
- 8 (math subscript)
- 11 (letter)
- 12 (other)
- 13 (active)

and other values raise an error. The $\langle charcode \rangle$ may be any one valid for the engine in use. Active characters cannot be generated in older versions of X_YTeX.

<hr/> <code>\c_catcode_other_space_tl</code> <hr/>	Token list containing one character with category code 12, (“other”), and character code 32 (space).
New: 2011-09-05	

2 Manipulating and interrogating character tokens

<code>\char_set_catcode_escape:N</code>	<code>\char_set_catcode_letter:N</code> $\langle character \rangle$
<code>\char_set_catcode_group_begin:N</code>	
<code>\char_set_catcode_group_end:N</code>	
<code>\char_set_catcode_math_toggle:N</code>	
<code>\char_set_catcode_alignment:N</code>	
<code>\char_set_catcode_end_line:N</code>	
<code>\char_set_catcode_parameter:N</code>	
<code>\char_set_catcode_math_superscript:N</code>	
<code>\char_set_catcode_math_subscript:N</code>	
<code>\char_set_catcode_ignore:N</code>	
<code>\char_set_catcode_space:N</code>	
<code>\char_set_catcode_letter:N</code>	
<code>\char_set_catcode_other:N</code>	
<code>\char_set_catcode_active:N</code>	
<code>\char_set_catcode_comment:N</code>	
<code>\char_set_catcode_invalid:N</code>	

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ to that indicated in the function name. Depending on the current category code of the $\langle token \rangle$ the escape token may also be needed:

`\char_set_catcode_other:N \%`

The assignment is local.

<code>\char_set_catcode_escape:n</code>	<code>\char_set_catcode_letter:n</code> $\{ \langle integer\ expression \rangle \}$
<code>\char_set_catcode_group_begin:n</code>	
<code>\char_set_catcode_group_end:n</code>	
<code>\char_set_catcode_math_toggle:n</code>	
<code>\char_set_catcode_alignment:n</code>	
<code>\char_set_catcode_end_line:n</code>	
<code>\char_set_catcode_parameter:n</code>	
<code>\char_set_catcode_math_superscript:n</code>	
<code>\char_set_catcode_math_subscript:n</code>	
<code>\char_set_catcode_ignore:n</code>	
<code>\char_set_catcode_space:n</code>	
<code>\char_set_catcode_letter:n</code>	
<code>\char_set_catcode_other:n</code>	
<code>\char_set_catcode_active:n</code>	
<code>\char_set_catcode_comment:n</code>	
<code>\char_set_catcode_invalid:n</code>	

Updated: 2015-11-11

Sets the category code of the $\langle character \rangle$ which has character code as given by the $\langle integer\ expression \rangle$. This version can be used to set up characters which cannot otherwise be given (*cf.* the N-type variants). The assignment is local.

<hr/> <code>\char_set_catcode:nn</code> <hr/>	<code>\char_set_catcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
<hr/> Updated: 2015-11-11 <hr/>	These functions set the category code of the <i>⟨character⟩</i> which has character code as given by the <i>⟨integer expression⟩</i> . The first <i>⟨integer expression⟩</i> is the character code and the second is the category code to apply. The setting applies within the current T _E X group. In general, the symbolic functions <code>\char_set_catcode_⟨type⟩</code> should be preferred, but there are cases where these lower-level functions may be useful.
<hr/> <code>\char_value_catcode:n</code> ★ <hr/>	<code>\char_value_catcode:n {⟨integer expression⟩}</code>
	Expands to the current category code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_catcode:n</code> <hr/>	<code>\char_show_value_catcode:n {⟨integer expression⟩}</code>
	Displays the current category code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_lccode:nn</code> <hr/>	<code>\char_set_lccode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
<hr/> Updated: 2015-08-06 <hr/>	Sets up the behaviour of the <i>⟨character⟩</i> when found inside <code>\tl_lower_case:n</code> , such that <i>⟨character₁⟩</i> will be converted into <i>⟨character₂⟩</i> . The two <i>⟨characters⟩</i> may be specified using an <i>⟨integer expression⟩</i> for the character code concerned. This may include the T _E X ‘ <i>⟨character⟩</i> ’ method for converting a single character into its character code:
	<pre> \char_set_lccode:nn { ‘\A } { ‘\a } % Standard behaviour \char_set_lccode:nn { ‘\A } { ‘\A + 32 } \char_set_lccode:nn { 50 } { 60 } </pre>
	The setting applies within the current T _E X group.
<hr/> <code>\char_value_lccode:n</code> ★ <hr/>	<code>\char_value_lccode:n {⟨integer expression⟩}</code>
	Expands to the current lower case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> .
<hr/> <code>\char_show_value_lccode:n</code> <hr/>	<code>\char_show_value_lccode:n {⟨integer expression⟩}</code>
	Displays the current lower case code of the <i>⟨character⟩</i> with character code given by the <i>⟨integer expression⟩</i> on the terminal.
<hr/> <code>\char_set_uccode:nn</code> <hr/>	<code>\char_set_uccode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
<hr/> Updated: 2015-08-06 <hr/>	Sets up the behaviour of the <i>⟨character⟩</i> when found inside <code>\tl_upper_case:n</code> , such that <i>⟨character₁⟩</i> will be converted into <i>⟨character₂⟩</i> . The two <i>⟨characters⟩</i> may be specified using an <i>⟨integer expression⟩</i> for the character code concerned. This may include the T _E X ‘ <i>⟨character⟩</i> ’ method for converting a single character into its character code:
	<pre> \char_set_uccode:nn { ‘\a } { ‘\A } % Standard behaviour \char_set_uccode:nn { ‘\A } { ‘\A - 32 } \char_set_uccode:nn { 60 } { 50 } </pre>
	The setting applies within the current T _E X group.

<hr/> <hr/> <code>\char_value_uccode:n</code> ★	<code>\char_value_uccode:n {⟨integer expression⟩}</code>
	Expands to the current upper case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$.
<hr/> <hr/> <code>\char_show_value_uccode:n</code>	<code>\char_show_value_uccode:n {⟨integer expression⟩}</code>
	Displays the current upper case code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <hr/> <code>\char_set_mathcode:nn</code>	<code>\char_set_mathcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-08-06	This function sets up the math code of $\langle character \rangle$. The $\langle character \rangle$ is specified as an $\langle integer expression \rangle$ which will be used as the character code of the relevant character. The setting applies within the current T _E X group.
<hr/> <hr/> <code>\char_value_mathcode:n</code> ★	<code>\char_value_mathcode:n {⟨integer expression⟩}</code>
	Expands to the current math code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$.
<hr/> <hr/> <code>\char_show_value_mathcode:n</code>	<code>\char_show_value_mathcode:n {⟨integer expression⟩}</code>
	Displays the current math code of the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <hr/> <code>\char_set_sfcode:nn</code>	<code>\char_set_sfcode:nn {⟨intexpr₁⟩} {⟨intexpr₂⟩}</code>
Updated: 2015-08-06	This function sets up the space factor for the $\langle character \rangle$. The $\langle character \rangle$ is specified as an $\langle integer expression \rangle$ which will be used as the character code of the relevant character. The setting applies within the current T _E X group.
<hr/> <hr/> <code>\char_value_sfcode:n</code> ★	<code>\char_value_sfcode:n {⟨integer expression⟩}</code>
	Expands to the current space factor for the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$.
<hr/> <hr/> <code>\char_show_value_sfcode:n</code>	<code>\char_show_value_sfcode:n {⟨integer expression⟩}</code>
	Displays the current space factor for the $\langle character \rangle$ with character code given by the $\langle integer expression \rangle$ on the terminal.
<hr/> <hr/> <code>\l_char_active_seq</code>	Used to track which tokens may require special handling at the document level as they are (or have been at some point) of category $\langle active \rangle$ (catcode 13). Each entry in the sequence consists of a single escaped token, for example <code>\~</code> . Active tokens should be added to the sequence when they are defined for general document use.
New: 2012-01-23 Updated: 2015-11-11	
<hr/> <hr/> <code>\l_char_special_seq</code>	Used to track which tokens will require special handling when working with verbatim-like material at the document level as they are not of categories $\langle letter \rangle$ (catcode 11) or $\langle other \rangle$ (catcode 12). Each entry in the sequence consists of a single escaped token, for example <code>\</code> for the backslash or <code>\{</code> for an opening brace. Escaped tokens should be added to the sequence when they are defined for general document use.
New: 2012-01-23 Updated: 2015-11-11	

3 Generic tokens

```
\c_group_begin_token
\c_group_end_token
\c_math_toggle_token
\c_alignment_token
\c_parameter_token
\c_math_superscript_token
\c_math_subscript_token
\c_space_token
```

These are implicit tokens which have the category code described by their name. They are used internally for test purposes but are also available to the programmer for other uses.

```
\c_catcode_letter_token
\c_catcode_other_token
```

These are implicit tokens which have the category code described by their name. They are used internally for test purposes and should not be used other than for category code tests.

```
\c_catcode_active_tl
```

A token list containing an active token. This is used internally for test purposes and should not be used other than in appropriately-constructed category code tests.

4 Converting tokens

```
\token_to_meaning:N ★
\token_to_meaning:c ★
```

`\token_to_meaning:N` $\langle token \rangle$

Inserts the current meaning of the $\langle token \rangle$ into the input stream as a series of characters of category code 12 (other). This is the primitive \TeX description of the $\langle token \rangle$, thus for example both functions defined by `\cs_set_nopar:Npn` and token list variables defined using `\tl_new:N` are described as **macros**.

\TeX hackers note: This is the \TeX primitive `\meaning`. The $\langle token \rangle$ can thus be an explicit space tokens or an explicit begin-group or end-group character token (`{` or `}` when normal \TeX category codes apply) even though these are not valid \N -type arguments.

```
\token_to_str:N ★
\token_to_str:c ★
```

`\token_to_str:N` $\langle token \rangle$

Converts the given $\langle token \rangle$ into a series of characters with category code 12 (other). If the $\langle token \rangle$ is a control sequence, this will start with the current escape character with category code 12 (the escape character is part of the $\langle token \rangle$). This function requires only a single expansion.

\TeX hackers note: `\token_to_str:N` is the \TeX primitive `\string` renamed. The $\langle token \rangle$ can thus be an explicit space tokens or an explicit begin-group or end-group character token (`{` or `}` when normal \TeX category codes apply) even though these are not valid \N -type arguments.

5 Token conditionals

<code>\token_if_group_begin_p:N</code>	★	<code>\token_if_group_begin_p:N</code>	$\langle token \rangle$
<code>\token_if_group_begin:NTF</code>	★	<code>\token_if_group_begin:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a begin group token (`{` when normal \TeX category codes are in force). Note that an explicit begin group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_group_end_p:N</code>	★	<code>\token_if_group_end_p:N</code>	$\langle token \rangle$
<code>\token_if_group_end:NTF</code>	★	<code>\token_if_group_end:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an end group token (`}` when normal \TeX category codes are in force). Note that an explicit end group token cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_math_toggle_p:N</code>	★	<code>\token_if_math_toggle_p:N</code>	$\langle token \rangle$
<code>\token_if_math_toggle:NTF</code>	★	<code>\token_if_math_toggle:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a math shift token (`$` when normal \TeX category codes are in force).

<code>\token_if_alignment_p:N</code>	★	<code>\token_if_alignment_p:N</code>	$\langle token \rangle$
<code>\token_if_alignment:NTF</code>	★	<code>\token_if_alignment:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an alignment token (`&` when normal \TeX category codes are in force).

<code>\token_if_parameter_p:N</code>	★	<code>\token_if_parameter_p:N</code>	$\langle token \rangle$
<code>\token_if_parameter:NTF</code>	★	<code>\token_if_parameter:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a macro parameter token (`#` when normal \TeX category codes are in force).

<code>\token_if_math_superscript_p:N</code>	★	<code>\token_if_math_superscript_p:N</code>	$\langle token \rangle$
<code>\token_if_math_superscript:NTF</code>	★	<code>\token_if_math_superscript:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a superscript token (`^` when normal \TeX category codes are in force).

<code>\token_if_math_subscript_p:N</code>	★	<code>\token_if_math_subscript_p:N</code>	$\langle token \rangle$
<code>\token_if_math_subscript:NTF</code>	★	<code>\token_if_math_subscript:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a subscript token (`_` when normal \TeX category codes are in force).

<code>\token_if_space_p:N</code>	★	<code>\token_if_space_p:N</code>	$\langle token \rangle$
<code>\token_if_space:NTF</code>	★	<code>\token_if_space:NTF</code>	$\langle token \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a space token. Note that an explicit space token with character code 32 cannot be tested in this way, as it is not a valid N-type argument.

<code>\token_if_letter_p:N</code>	★	<code>\token_if_letter_p:N</code>	$\langle token \rangle$
<code>\token_if_letter:NTF</code>	★	<code>\token_if_letter:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if $\langle token \rangle$ has the category code of a letter token.

<code>\token_if_other_p:N</code>	★	<code>\token_if_other_p:N</code>	$\langle token \rangle$
<code>\token_if_other:NTF</code>	★	<code>\token_if_other:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an “other” token.

<code>\token_if_active_p:N</code>	★	<code>\token_if_active_p:N</code>	$\langle token \rangle$
<code>\token_if_active:NTF</code>	★	<code>\token_if_active:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if $\langle token \rangle$ has the category code of an active character.

<code>\token_if_eq_catcode_p:NN</code>	★	<code>\token_if_eq_catcode_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_catcode:NNTF</code>	★	<code>\token_if_eq_catcode:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the two $\langle tokens \rangle$ have the same category code.

<code>\token_if_eq_charcode_p:NN</code>	★	<code>\token_if_eq_charcode_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_charcode:NNTF</code>	★	<code>\token_if_eq_charcode:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the two $\langle tokens \rangle$ have the same character code.

<code>\token_if_eq_meaning_p:NN</code>	★	<code>\token_if_eq_meaning_p:NN</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$
<code>\token_if_eq_meaning:NNTF</code>	★	<code>\token_if_eq_meaning:NNTF</code>	$\langle token_1 \rangle$ $\langle token_2 \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the two $\langle tokens \rangle$ have the same meaning when expanded.

<code>\token_if_macro_p:N</code>	★	<code>\token_if_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_macro:NTF</code>	★	<code>\token_if_macro:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2011-05-23

Tests if the $\langle token \rangle$ is a T_EX macro.

<code>\token_if_cs_p:N</code>	★	<code>\token_if_cs_p:N</code>	$\langle token \rangle$
<code>\token_if_cs:NTF</code>	★	<code>\token_if_cs:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the $\langle token \rangle$ is a control sequence.

<code>\token_if_expandable_p:N</code>	★	<code>\token_if_expandable_p:N</code>	$\langle token \rangle$
<code>\token_if_expandable:NTF</code>	★	<code>\token_if_expandable:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the $\langle token \rangle$ is expandable. This test returns $\langle false \rangle$ for an undefined token.

<code>\token_if_long_macro_p:N</code>	★	<code>\token_if_long_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_long_macro:NTF</code>	★	<code>\token_if_long_macro:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a long macro.

<code>\token_if_protected_macro_p:N</code>	★	<code>\token_if_protected_macro_p:N</code>	$\langle token \rangle$
<code>\token_if_protected_macro:NTF</code>	★	<code>\token_if_protected_macro:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is a protected macro: for a macro which is both protected and long this returns **false**.

<code>\token_if_protected_long_macro_p:N</code>	<code>*</code>	<code>\token_if_protected_long_macro_p:N</code>	<code><token></code>
<code>\token_if_protected_long_macro:NTF</code>	<code>*</code>	<code>\token_if_protected_long_macro:NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the `<token>` is a protected long macro.

<code>\token_if_chardef_p:N</code>	<code>*</code>	<code>\token_if_chardef_p:N</code>	<code><token></code>
<code>\token_if_chardef:NTF</code>	<code>*</code>	<code>\token_if_chardef:NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the `<token>` is defined to be a chardef.

T_EXhackers note: Booleans, boxes and small integer constants are implemented as `\chardefs`.

<code>\token_if_mathchardef_p:N</code>	<code>*</code>	<code>\token_if_mathchardef_p:N</code>	<code><token></code>
<code>\token_if_mathchardef:NTF</code>	<code>*</code>	<code>\token_if_mathchardef:NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the `<token>` is defined to be a mathchardef.

<code>\token_if_dim_register_p:N</code>	<code>*</code>	<code>\token_if_dim_register_p:N</code>	<code><token></code>
<code>\token_if_dim_register:NTF</code>	<code>*</code>	<code>\token_if_dim_register:NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the `<token>` is defined to be a dimension register.

<code>\token_if_int_register_p:N</code>	<code>*</code>	<code>\token_if_int_register_p:N</code>	<code><token></code>
<code>\token_if_int_register:NTF</code>	<code>*</code>	<code>\token_if_int_register:NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the `<token>` is defined to be a integer register.

T_EXhackers note: Constant integers may be implemented as integer registers, `\chardefs`, or `\mathchardefs` depending on their value.

<code>\token_if_muskip_register_p:N</code>	<code>*</code>	<code>\token_if_muskip_register_p:N</code>	<code><token></code>
<code>\token_if_muskip_register:NTF</code>	<code>*</code>	<code>\token_if_muskip_register:NTF</code>	<code><token> {\true code} {\false code}</code>

New: 2012-02-15

Tests if the `<token>` is defined to be a muskip register.

<code>\token_if_skip_register_p:N</code>	<code>*</code>	<code>\token_if_skip_register_p:N</code>	<code><token></code>
<code>\token_if_skip_register:NTF</code>	<code>*</code>	<code>\token_if_skip_register:NTF</code>	<code><token> {\true code} {\false code}</code>

Updated: 2012-01-20

Tests if the `<token>` is defined to be a skip register.

<code>\token_if_toks_register_p:N</code>	★	<code>\token_if_toks_register_p:N</code>	$\langle token \rangle$
<code>\token_if_toks_register:NTF</code>	★	<code>\token_if_toks_register:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2012-01-20

Tests if the $\langle token \rangle$ is defined to be a toks register (not used by L^AT_EX3).

<code>\token_if_primitive_p:N</code>	★	<code>\token_if_primitive_p:N</code>	$\langle token \rangle$
<code>\token_if_primitive:NTF</code>	★	<code>\token_if_primitive:NTF</code>	$\langle token \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Updated: 2011-05-23

Tests if the $\langle token \rangle$ is an engine primitive.

6 Peeking ahead at the next token

There is often a need to look ahead at the next token in the input stream while leaving it in place. This is handled using the “peek” functions. The generic `\peek_after:Nw` is provided along with a family of predefined tests for common cases. As peeking ahead does *not* skip spaces the predefined tests include both a space-respecting and space-skipping version.

<code>\peek_after:Nw</code>	<code>\peek_after:Nw</code>	$\langle function \rangle$	$\langle token \rangle$
-----------------------------	-----------------------------	----------------------------	-------------------------

Locally sets the test variable `\l_peek_token` equal to $\langle token \rangle$ (as an implicit token, *not* as a token list), and then expands the $\langle function \rangle$. The $\langle token \rangle$ remains in the input stream as the next item after the $\langle function \rangle$. The $\langle token \rangle$ here may be \sqcup , $\{$ or $\}$ (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

<code>\peek_gafter:Nw</code>	<code>\peek_gafter:Nw</code>	$\langle function \rangle$	$\langle token \rangle$
------------------------------	------------------------------	----------------------------	-------------------------

Globally sets the test variable `\g_peek_token` equal to $\langle token \rangle$ (as an implicit token, *not* as a token list), and then expands the $\langle function \rangle$. The $\langle token \rangle$ remains in the input stream as the next item after the $\langle function \rangle$. The $\langle token \rangle$ here may be \sqcup , $\{$ or $\}$ (assuming normal T_EX category codes), *i.e.* it is not necessarily the next argument which would be grabbed by a normal function.

<code>\l_peek_token</code>	Token set by <code>\peek_after:Nw</code> and available for testing as described above.
----------------------------	--

<code>\g_peek_token</code>	Token set by <code>\peek_gafter:Nw</code> and available for testing as described above.
----------------------------	---

<code>\peek_catcode:NTF</code>	<code>\peek_catcode:NTF</code>	$\langle test\ token \rangle$	$\{\langle true\ code \rangle\}$	$\{\langle false\ code \rangle\}$
--------------------------------	--------------------------------	-------------------------------	----------------------------------	-----------------------------------

Updated: 2012-12-20

Tests if the next $\langle token \rangle$ in the input stream has the same category code as the $\langle test\ token \rangle$ (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the $\langle token \rangle$ is left in the input stream after the $\langle true\ code \rangle$ or $\langle false\ code \rangle$ (as appropriate to the result of the test).

<code>\peek_catcode_ignore_spaces:NTF</code>	<code>\peek_catcode_ignore_spaces:NTF <test token> {(true code)} {(false code)}</code>
--	--

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_catcode_remove:NTF</code>	<code>\peek_catcode_remove:NTF <test token> {(true code)} {(false code)}</code>
---------------------------------------	---

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_catcode_remove_ignore_spaces:NTF</code>	<code>\peek_catcode_remove_ignore_spaces:NTF <test token> {(true code)} {(false code)}</code>
---	---

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same category code as the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<code>\peek_charcode:NTF</code>	<code>\peek_charcode:NTF <test token> {(true code)} {(false code)}</code>
---------------------------------	---

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_charcode_ignore_spaces:NTF</code>	<code>\peek_charcode_ignore_spaces:NTF <test token> {(true code)} {(false code)}</code>
---	---

Updated: 2012-12-20

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_charcode_remove:NTF</code>	<code>\peek_charcode_remove:NTF <test token> {(true code)} {(false code)}</code>
--	--

Updated: 2012-12-20

Tests if the next *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<u><code>\peek_charcode_remove_ignore_spaces:NTF</code></u>	<code>\peek_charcode_remove_ignore_spaces:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2012-12-20	

Tests if the next non-space *<token>* in the input stream has the same character code as the *<test token>* (as defined by the test `\token_if_eq_charcode:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<u><code>\peek_meaning:NTF</code></u>	<code>\peek_meaning:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2011-07-02	

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<u><code>\peek_meaning_ignore_spaces:NTF</code></u>	<code>\peek_meaning_ignore_spaces:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2012-12-05	

Tests if the next non-space *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<u><code>\peek_meaning_remove:NTF</code></u>	<code>\peek_meaning_remove:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2011-07-02	

Tests if the next *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Spaces are respected by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

<u><code>\peek_meaning_remove_ignore_spaces:NTF</code></u>	<code>\peek_meaning_remove_ignore_spaces:NTF <test token> {<true code>} {<false code>}</code>
Updated: 2012-12-05	

Tests if the next non-space *<token>* in the input stream has the same meaning as the *<test token>* (as defined by the test `\token_if_eq_meaning:NNTF`). Explicit and implicit space tokens (with character code 32 and category code 10) are ignored and removed by the test and the *<token>* is removed from the input stream if the test is true. The function then places either the *<true code>* or *<false code>* in the input stream (as appropriate to the result of the test).

7 Decomposing a macro definition

These functions decompose \TeX macros into their constituent parts: if the *<token>* passed is not a macro then no decomposition can occur. In the latter case, all three functions leave `\scan_stop:` in the input stream.

`\token_get_arg_spec:N` ★

`\token_get_arg_spec:N` $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the primitive \TeX argument specification in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1 y #2 }`

leaves `#1#2` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` is left in the input stream.

\TeX hackers note: If the arg spec. contains the string `->`, then the `spec` function produces incorrect results.

`\token_get_replacement_spec:N` ★

`\token_get_replacement_spec:N` $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the replacement text in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1~y #2 }`

leaves `x#1 y#2` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` is left in the input stream.

\TeX hackers note: If the arg spec. contains the string `->`, then the `spec` function produces incorrect results.

`\token_get_prefix_spec:N` ★

`\token_get_prefix_spec:N` $\langle token \rangle$

If the $\langle token \rangle$ is a macro, this function leaves the \TeX prefixes applicable in input stream as a string of tokens of category code 12 (with spaces having category code 10). Thus for example for a token `\next` defined by

`\cs_set:Npn \next #1#2 { x #1~y #2 }`

leaves `\long` in the input stream. If the $\langle token \rangle$ is not a macro then `\scan_stop:` is left in the input stream

8 Description of all possible tokens

Let us end by reviewing every case that a given token can fall into. This section is quite technical and some details are only meant for completeness. We distinguish the meaning of the token, which controls the expansion of the token and its effect on \TeX 's state, and its shape, which is used when comparing token lists such as for delimited arguments. Two tokens of the same shape must have the same meaning, but the converse does not hold.

A token has one of the following shapes.

- A control sequence, characterized by the sequence of characters that constitute its name: for instance, `\use:n` is a five-letter control sequence.

- An active character token, characterized by its character code (between 0 and 1114111 for LuaTeX and XeTeX and less for other engines) and category code 13.
- A character token, characterized by its character code and category code (one of 1, 2, 3, 4, 6, 7, 8, 10, 11 or 12 whose meaning is described below).⁴

There are also a few internal tokens. The following list may be incomplete in some engines.

- Expanding `\the\font` results in a token that looks identical to the command that was used to select the current font (such as `\tenrm`) but it differs from it in shape.
- A “frozen” `\relax`, which differs from the primitive in shape (but has the same meaning), is inserted when the closing `\fi` of a conditional is encountered before the conditional is evaluated.
- Expanding `\noexpand <token>` (when the `<token>` is expandable) results in an internal token, displayed (temporarily) as `\notexpanded: <token>`, whose shape coincides with the `<token>` and whose meaning differs from `\relax`.
- An `\outer endtemplate:` can be encountered when peeking ahead at the next token; this expands to another internal token, `end of alignment template`.
- Tricky programming might access a frozen `\endwrite`.
- Some frozen tokens can only be accessed in interactive sessions: `\cr`, `\right`, `\endgroup`, `\fi`, `\inaccessible`.

The meaning of a (non-active) character token is fixed by its category code (and character code) and cannot be changed. We call these tokens *explicit* character tokens. Category codes that a character token can have are listed below by giving a sample output of the TeX primitive `\meaning`, together with their L^AT_EX3 names and most common example:

- 1 begin-group character (`group_begin`, often `{`),
- 2 end-group character (`group_end`, often `}`),
- 3 math shift character (`math_toggle`, often `$`),
- 4 alignment tab character (`alignment`, often `&`),
- 6 macro parameter character (`parameter`, often `#`),
- 7 superscript character (`math_superscript`, often `^`),
- 8 subscript character (`math_subscript`, often `_`),
- 10 blank space (`space`, often character code 32),
- 11 the letter (`letter`, such as `A`),
- 12 the character (`other`, such as `0`).

⁴In LuaTeX, there is also the case of “bytes”, which behave as character tokens of category code 12 (other) and character code between 1114112 and 1114366. They are used to output individual bytes to files, rather than UTF-8.

Category code 13 (**active**) is discussed below. Input characters can also have several other category codes which do not lead to character tokens for later processing: 0 (**escape**), 5 (**end_line**), 9 (**ignore**), 14 (**comment**), and 15 (**invalid**).

The meaning of a control sequence or active character can be identical to that of any character token listed above (with any character code), and we call such tokens *implicit* character tokens. The meaning is otherwise in the following list:

- a macro, used in L^AT_EX3 for most functions and some variables (**tl**, **fp**, **seq**, ...),
- a primitive such as **\def** or **\topmark**, used in L^AT_EX3 for some functions,
- a register such as **\count123**, used in L^AT_EX3 for the implementation of some variables (**int**, **dim**, ...),
- a constant integer such as **\char"56** or **\mathchar"121**,
- a font selection command,
- undefined.

Macros be **\protected** or not, **\long** or not (the opposite of what L^AT_EX3 calls **nopar**), and **\outer** or not (unused in L^AT_EX3). Their **\meaning** takes the form

⟨properties⟩ macro:⟨parameters⟩->⟨replacement⟩

where *⟨properties⟩* is among **\protected****\long****\outer**, *⟨parameters⟩* describes parameters that the macro expects, such as **#1#2#3**, and *⟨replacement⟩* describes how the parameters are manipulated, such as **#2/#1/#3**.

Now is perhaps a good time to mention some subtleties relating to tokens with category code 10 (space). Any input character with this category code (normally, space and tab characters) becomes a normal space, with character code 32 and category code 10.

When a macro takes an undelimited argument, explicit space characters (with character code 32 and category code 10) are ignored. If the following token is an explicit character token with category code 1 (begin-group) and an arbitrary character code, then T_EX scans ahead to obtain an equal number of explicit character tokens with category code 1 (begin-group) and 2 (end-group), and the resulting list of tokens (with outer braces removed) becomes the argument. Otherwise, a single token is taken as the argument for the macro: we call such single tokens “N-type”, as they are suitable to be used as an argument for a function with the signature :N.

Part XVI

The l3prop package

Property lists

L^AT_EX3 implements a “property list” data type, which contain an unordered list of entries each of which consists of a $\langle key \rangle$ and an associated $\langle value \rangle$. The $\langle key \rangle$ and $\langle value \rangle$ may both be any $\langle balanced\ text \rangle$. It is possible to map functions to property lists such that the function is applied to every key–value pair within the list.

Each entry in a property list must have a unique $\langle key \rangle$: if an entry is added to a property list which already contains the $\langle key \rangle$ then the new entry overwrites the existing one. The $\langle keys \rangle$ are compared on a string basis, using the same method as `\str_if_eq:nn`.

Property lists are intended for storing key-based information for use within code. This is in contrast to key–value lists, which are a form of *input* parsed by the `keys` module.

1 Creating and initialising property lists

<code>\prop_new:N</code>
<code>\prop_new:c</code>

`\prop_new:N` $\langle property\ list \rangle$

Creates a new $\langle property\ list \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle property\ list \rangle$ initially contains no entries.

<code>\prop_clear:N</code>
<code>\prop_clear:c</code>
<code>\prop_gclear:N</code>
<code>\prop_gclear:c</code>

`\prop_clear:N` $\langle property\ list \rangle$

Clears all entries from the $\langle property\ list \rangle$.

<code>\prop_clear_new:N</code>
<code>\prop_clear_new:c</code>
<code>\prop_gclear_new:N</code>
<code>\prop_gclear_new:c</code>

`\prop_clear_new:N` $\langle property\ list \rangle$

Ensures that the $\langle property\ list \rangle$ exists globally by applying `\prop_new:N` if necessary, then applies `\prop_(g)clear:N` to leave the list empty.

<code>\prop_set_eq:NN</code>
<code>\prop_set_eq:(cN Nc cc)</code>
<code>\prop_gset_eq:NN</code>
<code>\prop_gset_eq:(cN Nc cc)</code>

`\prop_set_eq:NN` $\langle property\ list_1 \rangle$ $\langle property\ list_2 \rangle$

Sets the content of $\langle property\ list_1 \rangle$ equal to that of $\langle property\ list_2 \rangle$.

2 Adding entries to property lists

<code>\prop_put:Nnn</code> <code>\prop_put: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code> <code>\prop_gput:Nnn</code> <code>\prop_gput: (NnV Nno Nnx NVn NVV Non Noo cnn cnV cno cnx cVn cVV con coo)</code>	<code>\prop_put:Nnn <property list></code> <code>{<key>} {<value>}</code>
--	--

Updated: 2012-07-09

Adds an entry to the *<property list>* which may be accessed using the *<key>* and which has *<value>*. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored. If the *<key>* is already present in the *<property list>*, the existing entry is overwritten by the new *<value>*.

<code>\prop_put_if_new:Nnn</code> <code>\prop_put_if_new:cnn</code> <code>\prop_gput_if_new:Nnn</code> <code>\prop_gput_if_new:cnn</code>	<code>\prop_put_if_new:Nnn <property list> {<key>} {<value>}</code>
--	---

If the *<key>* is present in the *<property list>* then no action is taken. If the *<key>* is not present in the *<property list>* then a new entry is added. Both the *<key>* and *<value>* may contain any *<balanced text>*. The *<key>* is stored after processing with `\tl_to_str:n`, meaning that category codes are ignored.

3 Recovering values from property lists

<code>\prop_get:NnN</code> <code>\prop_get: (NVN NoN cnN cVN coN)</code>	<code>\prop_get:NnN <property list> {<key>} <tl var></code>
---	---

Updated: 2011-08-28

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<token list variable>* is set within the current TeX group. See also `\prop_get:NnNTF`.

<code>\prop_pop:NnN</code> <code>\prop_pop: (NoN cnN coN)</code>	<code>\prop_pop:NnN <property list> {<key>} <tl var></code>
---	---

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. Both assignments are local. See also `\prop_pop:NnNTF`.

<code>\prop_gpop:NnN</code> <code>\prop_gpop: (NoN cnN coN)</code>	<code>\prop_gpop:NnN <property list> {<key>} <tl var></code>
---	--

Updated: 2011-08-18

Recovers the *<value>* stored with *<key>* from the *<property list>*, and places this in the *<token list variable>*. If the *<key>* is not found in the *<property list>* then the *<token list variable>* is set to the special marker `\q_no_value`. The *<key>* and *<value>* are then deleted from the property list. The *<property list>* is modified globally, while the assignment of the *<token list variable>* is local. See also `\prop_gpop:NnNTF`.

<code>\prop_item:Nn</code> ★	<code>\prop_item:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$
------------------------------	--

<code>\prop_item:cn</code> ★

New: 2014-07-17

Expands to the $\langle value \rangle$ corresponding to the $\langle key \rangle$ in the $\langle property list \rangle$. If the $\langle key \rangle$ is missing, this has an empty expansion.

TeXhackers note: This function is slower than the non-expandable analogue `\prop_get:NnN`. The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ does not expand further when appearing in an `x`-type argument expansion.

4 Modifying property lists

<code>\prop_remove:Nn</code>

<code>\prop_remove:(NV cn cV)</code>

<code>\prop_gremove:Nn</code>

<code>\prop_gremove:(NV cn cV)</code>

New: 2012-05-12

<code>\prop_remove:Nn</code> $\langle property list \rangle$ $\{\langle key \rangle\}$
--

Removes the entry listed under $\langle key \rangle$ from the $\langle property list \rangle$. If the $\langle key \rangle$ is not found in the $\langle property list \rangle$ no change occurs, *i.e* there is no need to test for the existence of a key before deleting it.

5 Property list conditionals

<code>\prop_if_exist_p:N</code> ★

<code>\prop_if_exist_p:c</code> ★

<code>\prop_if_exist:NnTF</code> ★

<code>\prop_if_exist:cTF</code> ★

New: 2012-03-03

<code>\prop_if_exist_p:N</code> $\langle property list \rangle$

<code>\prop_if_exist:NnTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests whether the $\langle property list \rangle$ is currently defined. This does not check that the $\langle property list \rangle$ really is a property list variable.

<code>\prop_if_empty_p:N</code> ★

<code>\prop_if_empty_p:c</code> ★

<code>\prop_if_empty:NnTF</code> ★

<code>\prop_if_empty:cTF</code> ★

<code>\prop_if_empty_p:N</code> $\langle property list \rangle$

<code>\prop_if_empty:NnTF</code> $\langle property list \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$

Tests if the $\langle property list \rangle$ is empty (containing no entries).

<code>\prop_if_in_p:Nn</code>	★	<code>\prop_if_in:NnTF</code> $\langle property list \rangle$ $\{\langle key \rangle\}$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
-------------------------------	---	--

<code>\prop_if_in_p:(NV No cn cV co)</code>	★
---	---

<code>\prop_if_in:NnTF</code>	★
-------------------------------	---

<code>\prop_if_in:(NV No cn cV co)TF</code>	★
---	---

Updated: 2011-09-15

Tests if the $\langle key \rangle$ is present in the $\langle property list \rangle$, making the comparison using the method described by `\str_if_eq:nnTF`.

TeXhackers note: This function iterates through every key–value pair in the $\langle property list \rangle$ and is therefore slower than using the non-expandable `\prop_get:NnNTF`.

6 Recovering values from property lists with branching

The functions in this section combine tests for the presence of a key in a property list with recovery of the associated valued. This makes them useful for cases where different cases follow dependent on the presence or absence of a key in a property list. They offer increased readability and performance over separate testing and recovery phases.

<u>\prop_get:NnNTF</u>	<u>\prop_get:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$
<u>\prop_get:(NVN NoN cnN cVN coN)TF</u>	<u>\prop_get:(NVN NoN cnN cVN coN)TF</u> $\{\langle \text{true code} \rangle\}$ $\{\langle \text{false code} \rangle\}$
Updated: 2012-05-19	

If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$, leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$, stores the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$ without removing it from the $\langle \text{property list} \rangle$, then leaves the $\langle \text{true code} \rangle$ in the input stream. The $\langle \text{token list variable} \rangle$ is assigned locally.

<u>\prop_pop:NnNTF</u>	<u>\prop_pop:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$ $\{\langle \text{true code} \rangle\}$
<u>\prop_pop:cnNTF</u>	<u>\prop_pop:cnNTF</u> $\{\langle \text{false code} \rangle\}$
New: 2011-08-18	If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$, leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$, pops the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$, <i>i.e.</i> removes the item from the $\langle \text{property list} \rangle$. Both the $\langle \text{property list} \rangle$ and the $\langle \text{token list variable} \rangle$ are assigned locally.
Updated: 2012-05-19	

<u>\prop_gpop:NnNTF</u>	<u>\prop_gpop:NnNTF</u> $\langle \text{property list} \rangle$ $\{\langle \text{key} \rangle\}$ $\langle \text{token list variable} \rangle$ $\{\langle \text{true code} \rangle\}$
<u>\prop_gpop:cnNTF</u>	<u>\prop_gpop:cnNTF</u> $\{\langle \text{false code} \rangle\}$
New: 2011-08-18	If the $\langle \text{key} \rangle$ is not present in the $\langle \text{property list} \rangle$, leaves the $\langle \text{false code} \rangle$ in the input stream. The value of the $\langle \text{token list variable} \rangle$ is not defined in this case and should not be relied upon. If the $\langle \text{key} \rangle$ is present in the $\langle \text{property list} \rangle$, pops the corresponding $\langle \text{value} \rangle$ in the $\langle \text{token list variable} \rangle$, <i>i.e.</i> removes the item from the $\langle \text{property list} \rangle$. The $\langle \text{property list} \rangle$ is modified globally, while the $\langle \text{token list variable} \rangle$ is assigned locally.
Updated: 2012-05-19	

7 Mapping to property lists

<u>\prop_map_function:NN</u> ☆	<u>\prop_map_function:NN</u> $\langle \text{property list} \rangle$ $\langle \text{function} \rangle$
<u>\prop_map_function:cN</u> ☆	Applies $\langle \text{function} \rangle$ to every $\langle \text{entry} \rangle$ stored in the $\langle \text{property list} \rangle$. The $\langle \text{function} \rangle$ receives two arguments for each iteration: the $\langle \text{key} \rangle$ and associated $\langle \text{value} \rangle$. The order in which $\langle \text{entries} \rangle$ are returned is not defined and should not be relied upon.
Updated: 2013-01-28	

<u>\prop_map_inline:Nn</u>	<u>\prop_map_inline:Nn</u> $\langle \text{property list} \rangle$ $\{\langle \text{inline function} \rangle\}$
<u>\prop_map_inline:cn</u>	Applies $\langle \text{inline function} \rangle$ to every $\langle \text{entry} \rangle$ stored within the $\langle \text{property list} \rangle$. The $\langle \text{inline function} \rangle$ should consist of code which receives the $\langle \text{key} \rangle$ as #1 and the $\langle \text{value} \rangle$ as #2. The order in which $\langle \text{entries} \rangle$ are returned is not defined and should not be relied upon.
Updated: 2013-01-08	

\prop_map_break: ☆

Updated: 2012-06-29

\prop_map_break:

Used to terminate a `\prop_map...` function before all entries in the *property list* have been processed. This normally takes place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break: }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.

\prop_map_break:n ☆

Updated: 2012-06-29

\prop_map_break:n {<code>}

Used to terminate a `\prop_map...` function before all entries in the *property list* have been processed, inserting the *code* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\prop_map_inline:Nn \l_my_prop
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \prop_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\prop_map...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *code* is inserted into the input stream. This depends on the design of the mapping function.

8 Viewing property lists

\prop_show:N

\prop_show:c

Updated: 2015-08-01

\prop_show:N *property list*

Displays the entries in the *property list* in the terminal.

<hr/> <code>\prop_log:N</code>	<code>\prop_log:N</code> \langle <i>property list</i> \rangle
<code>\prop_log:c</code> <hr/>	Writes the entries in the \langle <i>property list</i> \rangle in the log file.
<hr/> New: 2014-08-12 Updated: 2015-08-01 <hr/>	

9 Scratch property lists

<hr/> <code>\l_tmpa_prop</code>	Scratch property lists for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_prop</code> <hr/>	
<hr/> New: 2012-06-23 <hr/>	

<hr/> <code>\g_tmpa_prop</code>	Scratch property lists for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_prop</code> <hr/>	
<hr/> New: 2012-06-23 <hr/>	

10 Constants

<hr/> <code>\c_empty_prop</code> <hr/>	A permanently-empty property list used for internal comparisons.
--	--

Part XVII

The l3msg package

Messages

Messages need to be passed to the user by modules, either when errors occur or to indicate how the code is proceeding. The `l3msg` module provides a consistent method for doing this (as opposed to writing directly to the terminal or log).

The system used by `l3msg` to create messages divides the process into two distinct parts. Named messages are created in the first part of the process; at this stage, no decision is made about the type of output that the message will produce. The second part of the process is actually producing a message. At this stage a choice of message *class* has to be made, for example `error`, `warning` or `info`.

By separating out the creation and use of messages, several benefits are available. First, the messages can be altered later without needing details of where they are used in the code. This makes it possible to alter the language used, the detail level and so on. Secondly, the output which results from a given message can be altered. This can be done on a message class, module or message name basis. In this way, message behaviour can be altered and messages can be entirely suppressed.

1 Creating new messages

All messages have to be created before they can be used. The text of messages is automatically wrapped to the length available in the console. As a result, formatting is only needed where it helps to show meaning. In particular, `\\` may be used to force a new line and `_` forces an explicit space. Additionally, `\{`, `\#`, `\}`, `\%` and `\~` can be used to produce the corresponding character.

Messages may be subdivided *by one level* using the `/` character. This is used within the message filtering system to allow for example the L^AT_EX kernel messages to belong to the module `LaTeX` while still being filterable at a more granular level. Thus for example

```
\msg_new:nnnn { mymodule } { submodule / message } ...
```

will allow to filter out specifically messages from the `submodule`.

```
\msg_new:nnnn
\msg_new:nnn
Updated: 2011-08-16
```

```
\msg_new:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Creates a *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied at the time the message is used. An error is raised if the *<message>* already exists.

```
\msg_set:nnnn
\msg_set:nnn
\msg_gset:nnnn
\msg_gset:nnn
```

```
\msg_set:nnnn {<module>} {<message>} {<text>} {<more text>}
```

Sets up the text for a *<message>* for a given *<module>*. The message is defined to first give *<text>* and then *<more text>* if the user requests it. If no *<more text>* is available then a standard text is given instead. Within *<text>* and *<more text>* four parameters (**#1** to **#4**) can be used: these will be supplied at the time the message is used.

<code>\msg_if_exist_p:nn</code> ★	<code>\msg_if_exist_p:nn {<module>} {<message>}</code>
<code>\msg_if_exist:nnTF</code> ★	<code>\msg_if_exist:nnTF {<module>} {<message>} {<true code>} {<false code>}</code>
New: 2012-03-03	Tests whether the <i><message></i> for the <i><module></i> is currently defined.

2 Contextual information for messages

<code>\msg_line_context:</code> ☆	<code>\msg_line_context:</code>
	Prints the current line number when a message is given, and thus suitable for giving context to messages. The number itself is preceded by the text <code>on line</code> .

<code>\msg_line_number:</code> ★	<code>\msg_line_number:</code>
	Prints the current line number when a message is given.

<code>\msg_fatal_text:n</code> ★	<code>\msg_fatal_text:n {<module>}</code>
	Produces the standard text
	Fatal Package <i><module></i> Error
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<code>\msg_critical_text:n</code> ★	<code>\msg_critical_text:n {<module>}</code>
	Produces the standard text
	Critical Package <i><module></i> Error
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<code>\msg_error_text:n</code> ★	<code>\msg_error_text:n {<module>}</code>
	Produces the standard text
	Package <i><module></i> Error
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included.

<code>\msg_warning_text:n</code> ★	<code>\msg_warning_text:n {<module>}</code>
	Produces the standard text
	Package <i><module></i> Warning
	This function can be redefined to alter the language in which the message is given, using #1 as the name of the <i><module></i> to be included. The <i><type></i> of <i><module></i> may be adjusted: Package is the standard outcome: see <code>\msg_module_type:n</code> .

<code>\msg_info_text:n</code> ★	<code>\msg_info_text:n {⟨module⟩}</code>
---------------------------------	--

Produces the standard text:

`Package ⟨module⟩ Info`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `⟨module⟩` to be included. The `⟨type⟩` of `⟨module⟩` may be adjusted: `Package` is the standard outcome: see `\msg_module_type:n`.

<code>\msg_module_name:n</code> ★	<code>\msg_module_name:n {⟨module⟩}</code>
-----------------------------------	--

New: 2018-10-10

Expands to the public name of the `⟨module⟩` as defined by `\g_msg_module_name_prop` (or otherwise leaves the `⟨module⟩` unchanged).

<code>\msg_module_type:n</code> ★	<code>\msg_module_type:n {⟨module⟩}</code>
-----------------------------------	--

New: 2018-10-10

Expands to the description which applies to the `⟨module⟩`, for example a `Package` or `Class`. The information here is defined in `\g_msg_module_type_prop`, and will default to `Package` if an entry is not present.

<code>\msg_see_documentation_text:n</code> ★	<code>\msg_see_documentation_text:n {⟨module⟩}</code>
--	---

Updated: 2018-09-30

Produces the standard text

`See the ⟨module⟩ documentation for further information.`

This function can be redefined to alter the language in which the message is given, using #1 as the name of the `⟨module⟩` to be included. The name of the `⟨module⟩` may be altered by use of `\g_msg_module_documentation_prop`

<code>\g_msg_module_name_prop</code>

New: 2018-10-10

Provides a mapping between the module name used for messages, and that for documentation. For example, L^AT_EX3 core messages are stored in the reserved L^AT_EX tree, but are printed as L^AT_EX3.

<code>\g_msg_module_type_prop</code>

New: 2018-10-10

Provides a mapping between the module name used for messages, and that type of module. For example, for L^AT_EX3 core messages, an empty entry is set here meaning that they are not described using the standard `Package` text.

3 Issuing messages

Messages behave differently depending on the message class. In all cases, the message may be issued supplying 0 to 4 arguments. If the number of arguments supplied here does not match the number in the definition of the message, extra arguments are ignored, or empty arguments added (of course the sense of the message may be impaired). The four arguments are converted to strings before being added to the message text: the `x`-type variants should be used to expand material.

```

\msg_fatal:nnnnnn
\msg_fatal:nnxxxx
\msg_fatal:nnnnn
\msg_fatal:nnxxx
\msg_fatal:nnnn
\msg_fatal:nnxx
\msg_fatal:nnn
\msg_fatal:nnx
\msg_fatal:nn

```

Updated: 2012-08-11

```

\msg_fatal:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. After issuing a fatal error the T_EX run halts.

```

\msg_critical:nnnnnn
\msg_critical:nnxxxx
\msg_critical:nnnnn
\msg_critical:nnxxx
\msg_critical:nnnn
\msg_critical:nnxx
\msg_critical:nnn
\msg_critical:nnx
\msg_critical:nn

```

Updated: 2012-08-11

```

\msg_critical:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. After issuing a critical error, T_EX stops reading the current input file. This may halt the T_EX run (if the current file is the main file) or may abort reading a sub-file.

T_EXhackers note: The T_EX `\endinput` primitive is used to exit the file. In particular, the rest of the current line remains in the input stream.

```

\msg_error:nnnnnn
\msg_error:nnxxxx
\msg_error:nnnnn
\msg_error:nnxxx
\msg_error:nnnn
\msg_error:nnxx
\msg_error:nnn
\msg_error:nnx
\msg_error:nn

```

Updated: 2012-08-11

```

\msg_error:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ error $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The error interrupts processing and issues the text at the terminal. After user input, the run continues.

```

\msg_warning:nnnnnn
\msg_warning:nnxxxx
\msg_warning:nnnnn
\msg_warning:nnxxx
\msg_warning:nnnn
\msg_warning:nnxx
\msg_warning:nnn
\msg_warning:nnx
\msg_warning:nn

```

Updated: 2012-08-11

```

\msg_warning:nnxxxx {\module} {\message} {\arg one} {\arg two} {\arg three}
{\arg four}

```

Issues $\langle module \rangle$ warning $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The warning text is added to the log file and the terminal, but the T_EX run is not interrupted.

<hr/>	
<code>\msg_info:nnnnnn</code>	<code>\msg_info:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_info:nnxxxx</code>	
<code>\msg_info:nnnnn</code>	Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text is added to the log file.
<code>\msg_info:nnxxx</code>	
<code>\msg_info:nnnn</code>	
<code>\msg_info:nnxx</code>	
<code>\msg_info:nnn</code>	
<code>\msg_info:nnx</code>	
<code>\msg_info:nn</code>	
<hr/>	
Updated: 2012-08-11	
<hr/>	
<code>\msg_log:nnnnnn</code>	<code>\msg_log:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_log:nnxxxx</code>	
<code>\msg_log:nnnnn</code>	Issues <i><module></i> information <i><message></i> , passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The information text is added to the log file: the output is briefer than <code>\msg_info:nnnnnn</code> .
<code>\msg_log:nnxxx</code>	
<code>\msg_log:nnnn</code>	
<code>\msg_log:nnxx</code>	
<code>\msg_log:nnn</code>	
<code>\msg_log:nnx</code>	
<code>\msg_log:nn</code>	
<hr/>	
Updated: 2012-08-11	
<hr/>	
<code>\msg_none:nnnnnn</code>	<code>\msg_none:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code>
<code>\msg_none:nnxxxx</code>	
<code>\msg_none:nnnnn</code>	Does nothing: used as a message class to prevent any output at all (see the discussion of message redirection).
<code>\msg_none:nnxxx</code>	
<code>\msg_none:nnnn</code>	
<code>\msg_none:nnxx</code>	
<code>\msg_none:nnn</code>	
<code>\msg_none:nnx</code>	
<code>\msg_none:nn</code>	
<hr/>	
Updated: 2012-08-11	

4 Redirecting messages

Each message has a “name”, which can be used to alter the behaviour of the message when it is given. Thus we might have

```
\msg_new:nnnn { module } { my-message } { Some-text } { Some-more-text }
```

to define a message, with

```
\msg_error:nn { module } { my-message }
```

when it is used. With no filtering, this raises an error. However, we could alter the behaviour with

```
\msg_redirect_class:nn { error } { warning }
```

to turn all errors into warnings, or with

```
\msg_redirect_module:nnn { module } { error } { warning }
```

to alter only messages from that module, or even

```
\msg_redirect_name:nnn { module } { my-message } { warning }
```

to target just one message. Redirection applies first to individual messages, then to messages from one module and finally to messages of one class. Thus it is possible to select out an individual message for special treatment even if the entire class is already redirected.

Multiple redirections are possible. Redirections can be cancelled by providing an empty argument for the target class. Redirection to a missing class raises an error immediately. Infinite loops are prevented by eliminating the redirection starting from the target of the redirection that caused the loop to appear. Namely, if redirections are requested as $A \rightarrow B$, $B \rightarrow C$ and $C \rightarrow A$ in this order, then the $A \rightarrow B$ redirection is cancelled.

```
\msg_redirect_class:nn
```

Updated: 2012-04-27

```
\msg_redirect_class:nn {<class one>} {<class two>}
```

Changes the behaviour of messages of *<class one>* so that they are processed using the code for those of *<class two>*.

```
\msg_redirect_module:nnn
```

Updated: 2012-04-27

```
\msg_redirect_module:nnn {<module>} {<class one>} {<class two>}
```

Redirects message of *<class one>* for *<module>* to act as though they were from *<class two>*. Messages of *<class one>* from sources other than *<module>* are not affected by this redirection. This function can be used to make some messages “silent” by default. For example, all of the **warning** messages of *<module>* could be turned off with:

```
\msg_redirect_module:nnn { module } { warning } { none }
```

```
\msg_redirect_name:nnn
```

Updated: 2012-04-27

```
\msg_redirect_name:nnn {<module>} {<message>} {<class>}
```

Redirects a specific *<message>* from a specific *<module>* to act as a member of *<class>* of messages. No further redirection is performed. This function can be used to make a selected message “silent” without changing global parameters:

```
\msg_redirect_name:nnn { module } { annoying-message } { none }
```

Part XVIII

The l3file package

File and I/O operations

This module provides functions for working with external files. Some of these functions apply to an entire file, and have prefix `\file_...`, while others are used to work with files on a line by line basis and have prefix `\ior_...` (reading) or `\iow_...` (writing).

It is important to remember that when reading external files T_EX attempts to locate them using both the operating system path and entries in the T_EX file database (most T_EX systems use such a database). Thus the “current path” for T_EX is somewhat broader than that for other programs.

For functions which expect a *<file name>* argument, this argument may contain both literal items and expandable content, which should on full expansion be the desired file name. Active characters (as declared in `\l_char_active_seq`) are *not* expanded, allowing the direct use of these in file names. File names are quoted using `"` tokens if they contain spaces: as a result, `"` tokens are *not* permitted in file names.

1 Input–output stream management

As T_EX engines have a limited number of input and output streams, direct use of the streams by the programmer is not supported in L^AT_EX3. Instead, an internal pool of streams is maintained, and these are allocated and deallocated as needed by other modules. As a result, the programmer should close streams when they are no longer needed, to release them for other processes.

Note that I/O operations are global: streams should all be declared with global names and treated accordingly.

<code>\ior_new:N</code>	<code>\ior_new:N <stream></code>
<code>\ior_new:c</code>	<code>\ior_new:c <stream></code>
<code>\iow_new:N</code>	
<code>\iow_new:c</code>	
<hr/> New: 2011-09-26 Updated: 2011-12-27	
<hr/>	
<code>\ior_open:Nn</code>	<code>\ior_open:Nn <stream> {<file name>}</code>
<code>\ior_open:cn</code>	
<hr/> Updated: 2012-02-10	
<hr/>	
Globally reserves the name of the <i><stream></i> , either for reading or for writing as appropriate. The <i><stream></i> is not opened until the appropriate <code>\..._open:Nn</code> function is used. Attempting to use a <i><stream></i> which has not been opened is an error, and the <i><stream></i> will behave as the corresponding <code>\c_term_....</code>	
Opens <i><file name></i> for reading using <i><stream></i> as the control sequence for file access. If the <i><stream></i> was already open it is closed before the new operation begins. The <i><stream></i> is available for access immediately and will remain allocated to <i><file name></i> until a <code>\ior_close:N</code> instruction is given or the T _E X run ends. If the file is not found, an error is raised.	

<hr/> <code>\ior_open:NnTF</code> <code>\ior_open:cnTF</code> <hr/> New: 2013-01-12	<code>\ior_open:NnTF <stream> {<file name>} {<true code>} {<false code>}</code> <p>Opens <i><file name></i> for reading using <i><stream></i> as the control sequence for file access. If the <i><stream></i> was already open it is closed before the new operation begins. The <i><stream></i> is available for access immediately and will remain allocated to <i><file name></i> until a <code>\ior_close:N</code> instruction is given or the T_EX run ends. The <i><true code></i> is then inserted into the input stream. If the file is not found, no error is raised and the <i><false code></i> is inserted into the input stream.</p>
<hr/> <code>\iow_open:Nn</code> <code>\iow_open:cn</code> <hr/> Updated: 2012-02-09	<code>\iow_open:Nn <stream> {<file name>}</code> <p>Opens <i><file name></i> for writing using <i><stream></i> as the control sequence for file access. If the <i><stream></i> was already open it is closed before the new operation begins. The <i><stream></i> is available for access immediately and will remain allocated to <i><file name></i> until a <code>\iow_close:N</code> instruction is given or the T_EX run ends. Opening a file for writing clears any existing content in the file (<i>i.e.</i> writing is <i>not</i> additive).</p>
<hr/> <code>\ior_close:N</code> <code>\ior_close:c</code> <code>\iow_close:N</code> <code>\iow_close:c</code> <hr/> Updated: 2012-07-31	<code>\ior_close:N <stream></code> <code>\iow_close:N <stream></code> <p>Closes the <i><stream></i>. Streams should always be closed when they are finished with as this ensures that they remain available to other programmers.</p>
<hr/> <code>\ior_show_list:</code> <code>\ior_log_list:</code> <code>\iow_show_list:</code> <code>\iow_log_list:</code> <hr/> New: 2017-06-27	<code>\ior_show_list:</code> <code>\ior_log_list:</code> <code>\iow_show_list:</code> <code>\iow_log_list:</code> <p>Display (to the terminal or log file) a list of the file names associated with each open (read or write) stream. This is intended for tracking down problems.</p>

1.1 Reading from files

<code>\ior_get:NN</code>	<code>\ior_get:NN <stream> <token list variable></code>
--------------------------	---

New: 2012-06-24

Function that reads one or more lines (until an equal number of left and right braces are found) from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material read from the *<stream>* is tokenized by T_EX according to the category codes and `\endlinechar` in force when the function is used. Assuming normal settings, any lines which do not end in a comment character % have the line ending converted to a space, so for example input

```
a b c
```

results in a token list `a_b_c_`. Any blank line is converted to the token `\par`. Therefore, blank lines can be skipped by using a test such as

```
\ior_get:NN \l_my_stream \l_tmpa_tl
\tl_set:Nn \l_tmpb_tl { \par }
\tl_if_eq:NMF \l_tmpa_tl \l_tmpb_tl
...
```

Also notice that if multiple lines are read to match braces then the resulting token list can contain `\par` tokens.

T_EXhackers note: This protected macro is a wrapper around the T_EX primitive `\read`. Regardless of settings, T_EX replaces trailing space and tab characters (character codes 32 and 9) in each line by an end-of-line character (character code `\endlinechar`, omitted if `\endlinechar` is negative or too large) before turning characters into tokens according to current category codes. With default settings, spaces appearing at the beginning of lines are also ignored.

<code>\ior_str_get:NN</code>	<code>\ior_str_get:NN <stream> <token list variable></code>
------------------------------	---

New: 2016-12-04

Function that reads one line from the input *<stream>* and stores the result locally in the *<token list>* variable. If the *<stream>* is not open, input is requested from the terminal. The material is read from the *<stream>* as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). Multiple whitespace characters are retained by this process. It always only reads one line and any blank lines in the input result in the *<token list variable>* being empty. Unlike `\ior_get:NN`, line ends do not receive any special treatment. Thus input

```
a b c
```

results in a token list `a b c` with the letters `a`, `b`, and `c` having category code 12.

T_EXhackers note: This protected macro is a wrapper around the ε -T_EX primitive `\readline`. Regardless of settings, T_EX removes trailing space and tab characters (character codes 32 and 9). However, the end-line character normally added by this primitive is not included in the result of `\ior_str_get:NN`.

<hr/> <code>\ior_map_inline:Nn</code> <hr/>	<code>\ior_map_inline:Nn <stream> {<inline function>}</code>
<hr/> New: 2012-02-11 <hr/>	Applies the <i><inline function></i> to each set of <i><lines></i> obtained by calling <code>\ior_get:NN</code> until reaching the end of the file. T _E X ignores any trailing new-line marker from the file it reads. The <i><inline function></i> should consist of code which receives the <i><line></i> as #1.
<hr/> <code>\ior_str_map_inline:Nn</code> <hr/>	<code>\ior_str_map_inline:Nn <stream> {<inline function>}</code>
<hr/> New: 2012-02-11 <hr/>	Applies the <i><inline function></i> to every <i><line></i> in the <i><stream></i> . The material is read from the <i><stream></i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i><inline function></i> should consist of code which receives the <i><line></i> as #1. Note that T _E X removes trailing space and tab characters (character codes 32 and 9) from every line upon input. T _E X also ignores any trailing new-line marker from the file it reads.
<hr/> <code>\ior_map_break:</code> <hr/>	<code>\ior_map_break:</code>
<hr/> New: 2012-06-29 <hr/>	Used to terminate a <code>\ior_map...</code> function before all lines from the <i><stream></i> have been processed. This normally takes place within a conditional statement, for example <pre> \ior_map_inline:Nn \l_my_ior { \str_if_eq:nnTF { #1 } { bingo } { \ior_map_break: } { % Do something useful } } </pre> <p>Use outside of a <code>\ior_map...</code> scenario leads to low level T_EX errors.</p> <p>T_EXhackers note: When the mapping is broken, additional tokens may be inserted before further items are taken from the input stream. This depends on the design of the mapping function.</p>

\ior_map_break:n

New: 2012-06-29

\ior_map_break:n {<code>}

Used to terminate a `\ior_map_...` function before all lines in the *<stream>* have been processed, inserting the *<code>* after the mapping has ended. This normally takes place within a conditional statement, for example

```
\ior_map_inline:Nn \l_my_ior
{
  \str_if_eq:nnTF { #1 } { bingo }
  { \ior_map_break:n { <code> } }
  {
    % Do something useful
  }
}
```

Use outside of a `\ior_map_...` scenario leads to low level TeX errors.

TeXhackers note: When the mapping is broken, additional tokens may be inserted before the *<code>* is inserted into the input stream. This depends on the design of the mapping function.

\ior_if_eof_p:N ★**\ior_if_eof:NTF** ★

Updated: 2012-02-10

\ior_if_eof_p:N <stream>**\ior_if_eof:NTF** <stream> {<true code>} {<false code>}

Tests if the end of a *<stream>* has been reached during a reading operation. The test also returns a `true` value if the *<stream>* is not open.

2 Writing to files

\iow_now:Nn**\iow_now:(Nx|cn|cx)**

Updated: 2012-06-05

\iow_now:Nn <stream> {<tokens>}

This functions writes *<tokens>* to the specified *<stream>* immediately (*i.e.* the write operation is called on expansion of `\iow_now:Nn`).

\iow_log:n**\iow_log:x****\iow_log:n** {<tokens>}

This function writes the given *<tokens>* to the log (transcript) file immediately: it is a dedicated version of `\iow_now:Nn`.

\iow_term:n**\iow_term:x****\iow_term:n** {<tokens>}

This function writes the given *<tokens>* to the terminal file immediately: it is a dedicated version of `\iow_now:Nn`.

<hr/> <code>\iow_shipout:Nn</code> <code>\iow_shipout:(Nx cn cx)</code> <hr/>	<code>\iow_shipout:Nn <stream> {<tokens>}</code> This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (<i>i.e.</i> at shipout). The x -type variants expand the $\langle tokens \rangle$ at the point where the function is used but <i>not</i> when the resulting tokens are written to the $\langle stream \rangle$ (<i>cf.</i> <code>\iow_shipout_x:Nn</code>). <p>T_EXhackers note: When using <code>expl3</code> with a format other than L^AT_EX, new line characters inserted using <code>\iow_newline:</code> or using the line-wrapping code <code>\iow_wrap:nnnN</code> are not recognized in the argument of <code>\iow_shipout:Nn</code>. This may lead to the insertion of additional unwanted line-breaks.</p>
<hr/> <code>\iow_shipout_x:Nn</code> <code>\iow_shipout_x:(Nx cn cx)</code> <hr/> <div>Updated: 2012-09-08</div> <hr/>	<code>\iow_shipout_x:Nn <stream> {<tokens>}</code> This functions writes $\langle tokens \rangle$ to the specified $\langle stream \rangle$ when the current page is finalised (<i>i.e.</i> at shipout). The $\langle tokens \rangle$ are expanded at the time of writing in addition to any expansion when the function is used. This makes these functions suitable for including material finalised during the page building process (such as the page number integer). <p>T_EXhackers note: This is a wrapper around the T_EX primitive <code>\write</code>. When using <code>expl3</code> with a format other than L^AT_EX, new line characters inserted using <code>\iow_newline:</code> or using the line-wrapping code <code>\iow_wrap:nnnN</code> are not recognized in the argument of <code>\iow_shipout:Nn</code>. This may lead to the insertion of additional unwanted line-breaks.</p>
<hr/> <code>\iow_char:N</code> ★ <hr/>	<code>\iow_char:N \<char></code> Inserts $\langle char \rangle$ into the output stream. Useful when trying to write difficult characters such as %, {, }, <i>etc.</i> in messages, for example: <code>\iow_now:Nx \g_my_iow { \iow_char:N \{ text \iow_char:N \} }</code> The function has no effect if writing is taking place without expansion (<i>e.g.</i> in the second argument of <code>\iow_now:Nn</code>).
<hr/> <code>\iow_newline:</code> ★ <hr/>	<code>\iow_newline:</code> Function to add a new line within the $\langle tokens \rangle$ written to a file. The function has no effect if writing is taking place without expansion (<i>e.g.</i> in the second argument of <code>\iow_now:Nn</code>). <p>T_EXhackers note: When using <code>expl3</code> with a format other than L^AT_EX, the character inserted by <code>\iow_newline:</code> is not recognized by T_EX, which may lead to the insertion of additional unwanted line-breaks. This issue only affects <code>\iow_shipout:Nn</code>, <code>\iow_shipout_x:Nn</code> and direct uses of primitive operations.</p>

2.1 Wrapping lines in output

<code>\iow_wrap:nnnN</code>	<code>\iow_wrap:nxnN</code>	<code>\iow_wrap:nnnN</code>	<code>{\text}</code>	<code>{\run-on text}</code>	<code>{\set up}</code>	<code>\function</code>
-----------------------------	-----------------------------	-----------------------------	----------------------	-----------------------------	------------------------	------------------------

New: 2012-06-28

Updated: 2017-12-04

This function wraps the $\langle text \rangle$ to a fixed number of characters per line. At the start of each line which is wrapped, the $\langle run-on text \rangle$ is inserted. The line character count targeted is the value of `\l_iow_line_count_int` minus the number of characters in the $\langle run-on text \rangle$ for all lines except the first, for which the target number of characters is simply `\l_iow_line_count_int` since there is no run-on text. The $\langle text \rangle$ and $\langle run-on text \rangle$ are exhaustively expanded by the function, with the following substitutions:

- `\` or `\iow_newline`: may be used to force a new line,
- `_` may be used to represent a forced space (for example after a control sequence),
- `\#`, `\%`, `\{`, `\}`, `\~` may be used to represent the corresponding character,
- `\iow_allow_break`: may be used to allow a line-break without inserting a space (this is experimental),
- `\iow_indent:n` may be used to indent a part of the $\langle text \rangle$ (not the $\langle run-on text \rangle$).

Additional functions may be added to the wrapping by using the $\langle set up \rangle$, which is executed before the wrapping takes place: this may include overriding the substitutions listed.

Any expandable material in the $\langle text \rangle$ which is not to be expanded on wrapping should be converted to a string using `\token_to_str:N`, `\tl_to_str:n`, `\tl_to_str:N`, etc.

The result of the wrapping operation is passed as a braced argument to the $\langle function \rangle$, which is typically a wrapper around a write operation. The output of `\iow_wrap:nnnN` (i.e. the argument passed to the $\langle function \rangle$) consists of characters of category “other” (category code 12), with the exception of spaces which have category “space” (category code 10). This means that the output does *not* expand further when written to a file.

TeXhackers note: Internally, `\iow_wrap:nnnN` carries out an x-type expansion on the $\langle text \rangle$ to expand it. This is done in such a way that `\exp_not:N` or `\exp_not:n` could be used to prevent expansion of material. However, this is less conceptually clear than conversion to a string, which is therefore the supported method for handling expandable material in the $\langle text \rangle$.

<code>\iow_indent:n</code>	<code>\iow_indent:n</code>	<code>{\text}</code>
----------------------------	----------------------------	----------------------

New: 2011-09-21

In the first argument of `\iow_wrap:nnnN` (for instance in messages), indents $\langle text \rangle$ by four spaces. This function does not cause a line break, and only affects lines which start within the scope of the $\langle text \rangle$. In case the indented $\langle text \rangle$ should appear on separate lines from the surrounding text, use `\` to force line breaks.

<code>\l_iow_line_count_int</code>

New: 2012-06-24

The maximum number of characters in a line to be written by the `\iow_wrap:nnnN` function. This value depends on the TeX system in use: the standard value is 78, which is typically correct for unmodified TeXlive and MiKTeX systems.

2.2 Constant input–output streams, and variables

<code>\c_term_ior</code>	Constant input stream for reading from the terminal. Reading from this stream using <code>\ior_get:NN</code> or similar results in a prompt from T _E X of the form
--------------------------	---

`<tl>=`

<code>\g_tmpa_ior</code> <code>\g_tmpb_ior</code>	Scratch input stream for global use. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

New: 2017-12-11

<code>\c_log_ior</code> <code>\c_term_ior</code>	Constant output streams for writing to the log and to the terminal (plus the log), respectively.
---	--

<code>\g_tmpa_ior</code> <code>\g_tmpb_ior</code>	Scratch output stream for global use. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

New: 2017-12-11

2.3 Primitive conditionals

<code>\if_eof:w</code> ★	<pre> \if_eof:w <stream> <true code> \else: <false code> \fi: </pre> <p>Tests if the <code><stream></code> returns “end of file”, which is true for non-existent files. The <code>\else:</code> branch is optional.</p>
--------------------------	---

T_EXhackers note: This is the T_EX primitive `\ifeof`.

3 File operation functions

<code>\g_file_curr_dir_str</code> <code>\g_file_curr_name_str</code> <code>\g_file_curr_ext_str</code>	Contain the directory, name and extension of the current file. The directory is empty if the file was loaded without an explicit path (<i>i.e.</i> if it is in the T _E X search path), and does <i>not</i> end in / other than the case that it is exactly equal to the root directory. The <code><name></code> and <code><ext></code> parts together make up the file name, thus the <code><name></code> part may be thought of as the “job name” for the current file. Note that T _E X does not provide information on the <code><ext></code> part for the main (top level) file and that this file always has an empty <code><dir></code> component. Also, the <code><name></code> here will be equal to <code>\c_sys_jobname_str</code> , which may be different from the real file name (if set using <code>--jobname</code> , for example).
--	--

New: 2017-06-21

`\l_file_search_path_seq`

New: 2017-06-18

Each entry is the path to a directory which should be searched when seeking a file. Each path can be relative or absolute, and should not include the trailing slash. The entries are not expanded when used so may contain active characters but should not feature any variable content. Spaces need not be quoted.

TeXhackers note: When working as a package in L^AT_EX 2_ε, `expl3` will automatically append the current `\input@path` to the set of values from `\l_file_search_path_seq`.

`\file_if_exist:nTF`

Updated: 2012-02-10

`\file_if_exist:nTF {<file name>} {<true code>} {<false code>}`

Searches for `<file name>` using the current T_EX search path and the additional paths controlled by `\l_file_search_path_seq`.

`\file_get_full_name:nN`
`\file_get_full_name:VN`

Updated: 2017-06-26

`\file_get_full_name:nN {<file name>} <str var>`

Searches for `<file name>` in the path as detailed for `\file_if_exist:nTF`, and if found sets the `<str var>` the fully-qualified name of the file, *i.e.* the path and file name. This includes an extension `.tex` when the given `<file name>` has no extension but the file found has that extension. If the file is not found then the `<str var>` is empty.

`\file_parse_full_name:nNNN`

New: 2017-06-23
Updated: 2017-06-26

`\file_parse_full_name:nNNN {<full name>} <dir> <name> <ext>`

Parses the `<full name>` and splits it into three parts, each of which is returned by setting the appropriate local string variable:

- The `<dir>`: everything up to the last / (path separator) in the `<file path>`. As with system PATH variables and related functions, the `<dir>` does *not* include the trailing / unless it points to the root directory. If there is no path (only a file name), `<dir>` is empty.
- The `<name>`: everything after the last / up to the last ., where both of those characters are optional. The `<name>` may contain multiple . characters. It is empty if `<full name>` consists only of a directory name.
- The `<ext>`: everything after the last . (including the dot). The `<ext>` is empty if there is no . after the last /.

This function does not expand the `<full name>` before turning it to a string. It assume that the `<full name>` either contains no quote (") characters or is surrounded by a pair of quotes.

`\file_input:n`

Updated: 2017-06-26

`\file_input:n {<file name>}`

Searches for `<file name>` in the path as detailed for `\file_if_exist:nTF`, and if found reads in the file as additional L^AT_EX source. All files read are recorded for information and the file name stack is updated by this function. An error is raised if the file is not found.

`\file_show_list:`
`\file_log_list:`

`\file_show_list:`
`\file_log_list:`

These functions list all files loaded by L^AT_EX 2_ε commands that populate `\@filelist` or by `\file_input:n`. While `\file_show_list:` displays the list in the terminal, `\file_log_list:` outputs it to the log file only.

Part XIX

The l3skip package

Dimensions and skips

L^AT_EX3 provides two general length variables: `dim` and `skip`. Lengths stored as `dim` variables have a fixed length, whereas `skip` lengths have a rubber (stretch/shrink) component. In addition, the `muskip` type is available for use in math mode: this is a special form of `skip` where the lengths involved are determined by the current math font (in μ). There are common features in the creation and setting of length variables, but for clarity the functions are grouped by variable type.

1 Creating and initialising `dim` variables

<code>\dim_new:N</code>
<code>\dim_new:c</code>

`\dim_new:N` $\langle dimension \rangle$

Creates a new $\langle dimension \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle dimension \rangle$ is initially equal to 0pt.

<code>\dim_const:Nn</code>
<code>\dim_const:cn</code>

`\dim_const:Nn` $\langle dimension \rangle$ $\{ \langle dimension expression \rangle \}$

Creates a new constant $\langle dimension \rangle$ or raises an error if the name is already taken. The value of the $\langle dimension \rangle$ is set globally to the $\langle dimension expression \rangle$.

New: 2012-03-05

<code>\dim_zero:N</code>
<code>\dim_zero:c</code>
<code>\dim_gzero:N</code>
<code>\dim_gzero:c</code>

`\dim_zero:N` $\langle dimension \rangle$

Sets $\langle dimension \rangle$ to 0pt.

<code>\dim_zero_new:N</code>
<code>\dim_zero_new:c</code>
<code>\dim_gzero_new:N</code>
<code>\dim_gzero_new:c</code>

`\dim_zero_new:N` $\langle dimension \rangle$

Ensures that the $\langle dimension \rangle$ exists globally by applying `\dim_new:N` if necessary, then applies `\dim_(g)zero:N` to leave the $\langle dimension \rangle$ set to zero.

New: 2012-01-07

<code>\dim_if_exist_p:N</code>	★
<code>\dim_if_exist_p:c</code>	★
<code>\dim_if_exist:NTF</code>	★
<code>\dim_if_exist:cTF</code>	★

`\dim_if_exist_p:N` $\langle dimension \rangle$

`\dim_if_exist:NTF` $\langle dimension \rangle$ $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$

Tests whether the $\langle dimension \rangle$ is currently defined. This does not check that the $\langle dimension \rangle$ really is a dimension variable.

New: 2012-03-03

2 Setting dim variables

<code>\dim_add:Nn</code>	<code>\dim_add:Nn <dimension> {<dimension expression>}</code>
<code>\dim_add:cn</code>	
<code>\dim_gadd:Nn</code>	Adds the result of the $\langle dimension\ expression \rangle$ to the current content of the $\langle dimension \rangle$.
<code>\dim_gadd:cn</code>	

Updated: 2011-10-22

<code>\dim_set:Nn</code>	<code>\dim_set:Nn <dimension> {<dimension expression>}</code>
<code>\dim_set:cn</code>	
<code>\dim_gset:Nn</code>	Sets $\langle dimension \rangle$ to the value of $\langle dimension\ expression \rangle$, which must evaluate to a length with units.
<code>\dim_gset:cn</code>	

Updated: 2011-10-22

<code>\dim_set_eq:NN</code>	<code>\dim_set_eq:NN <dimension₁> <dimension₂></code>
<code>\dim_set_eq:(cN Nc cc)</code>	
<code>\dim_gset_eq:NN</code>	Sets the content of $\langle dimension_1 \rangle$ equal to that of $\langle dimension_2 \rangle$.
<code>\dim_gset_eq:(cN Nc cc)</code>	

<code>\dim_sub:Nn</code>	<code>\dim_sub:Nn <dimension> {<dimension expression>}</code>
<code>\dim_sub:cn</code>	
<code>\dim_gsub:Nn</code>	Subtracts the result of the $\langle dimension\ expression \rangle$ from the current content of the $\langle dimension \rangle$.
<code>\dim_gsub:cn</code>	

Updated: 2011-10-22

3 Utilities for dimension calculations

<code>\dim_abs:n</code>	★ <code>\dim_abs:n {<dimexpr>}</code>
Updated: 2012-09-26	Converts the $\langle dimexpr \rangle$ to its absolute value, leaving the result in the input stream as a $\langle dimension\ denotation \rangle$.

<code>\dim_max:nn</code>	★ <code>\dim_max:nn {<dimexpr₁>} {<dimexpr₂>}</code>
<code>\dim_min:nn</code>	★ <code>\dim_min:nn {<dimexpr₁>} {<dimexpr₂>}</code>
New: 2012-09-09	
Updated: 2012-09-26	Evaluates the two $\langle dimension\ expressions \rangle$ and leaves either the maximum or minimum value in the input stream as appropriate, as a $\langle dimension\ denotation \rangle$.

`\dim_ratio:nn` ☆

Updated: 2011-10-22

`\dim_ratio:nn` { $\langle dimexpr_1 \rangle$ } { $\langle dimexpr_2 \rangle$ }

Parses the two $\langle dimension expressions \rangle$ and converts the ratio of the two to a form suitable for use inside a $\langle dimension expression \rangle$. This ratio is then left in the input stream, allowing syntax such as

```
\dim_set:Nn \l_my_dim
{ 10 pt * \dim_ratio:nn { 5 pt } { 10 pt } }
```

The output of `\dim_ratio:nn` on full expansion is a ratio expression between two integers, with all distances converted to scaled points. Thus

```
\tl_set:Nx \l_my_tl { \dim_ratio:nn { 5 pt } { 10 pt } }
\tl_show:N \l_my_tl
```

displays 327680/655360 on the terminal.

4 Dimension expression conditionals

`\dim_compare_p:nNn` ☆

`\dim_compare:nNnTF` ☆

`\dim_compare_p:nNn` { $\langle dimexpr_1 \rangle$ } $\langle relation \rangle$ { $\langle dimexpr_2 \rangle$ }

`\dim_compare:nNnTF`

{ $\langle dimexpr_1 \rangle$ } $\langle relation \rangle$ { $\langle dimexpr_2 \rangle$ }

{ $\langle true code \rangle$ } { $\langle false code \rangle$ }

This function first evaluates each of the $\langle dimension expressions \rangle$ as described for `\dim_eval:n`. The two results are then compared using the $\langle relation \rangle$:

Equal	=
Greater than	>
Less than	<

<code>\dim_compare_p:n</code> ★ <code>\dim_compare:nTF</code> ★	<code>\dim_compare_p:n</code> { $\langle dimexpr_1 \rangle$ $\langle relation_1 \rangle$... $\langle dimexpr_N \rangle$ $\langle relation_N \rangle$ $\langle dimexpr_{N+1} \rangle$ } <code>\dim_compare:nTF</code> { $\langle dimexpr_1 \rangle$ $\langle relation_1 \rangle$... $\langle dimexpr_N \rangle$ $\langle relation_N \rangle$ $\langle dimexpr_{N+1} \rangle$ } { $\langle true\ code \rangle$ } { $\langle false\ code \rangle$ }
--	--

Updated: 2013-01-13

This function evaluates the $\langle dimension\ expressions \rangle$ as described for `\dim_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle dimexpr_1 \rangle$ and $\langle dimexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle dimexpr_2 \rangle$ and $\langle dimexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle dimexpr_N \rangle$ and $\langle dimexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields `true` if all comparisons are `true`. Each $\langle dimension\ expression \rangle$ is evaluated only once, and the evaluation is lazy, in the sense that if one comparison is `false`, then no other $\langle dimension\ expression \rangle$ is evaluated and no other comparison is performed. The $\langle relations \rangle$ can be any of the following:

Equal	= or ==
Greater than or equal to	>=
Greater than	>
Less than or equal to	<=
Less than	<
Not equal	!=

<code>\dim_case:nn</code> ★	<code>\dim_case:nnTF {⟨test dimension expression⟩}</code>
<code>\dim_case:nnTF</code> ★	<code>{</code> <code> {⟨dimexpr case₁⟩} {⟨code case₁⟩}</code> <code> {⟨dimexpr case₂⟩} {⟨code case₂⟩}</code> <code> ...</code> <code> {⟨dimexpr case_n⟩} {⟨code case_n⟩}</code> <code>}</code> <code>{⟨true code⟩}</code> <code>{⟨false code⟩}</code>

New: 2013-07-24

This function evaluates the *⟨test dimension expression⟩* and compares this in turn to each of the *⟨dimension expression cases⟩*. If the two are equal then the associated *⟨code⟩* is left in the input stream and other cases are discarded. If any of the cases are matched, the *⟨true code⟩* is also inserted into the input stream (after the code for the appropriate case), while if none match then the *⟨false code⟩* is inserted. The function `\dim_case:nn`, which does nothing if there is no match, is also available. For example

```

\dim_set:Nn \l_tmpa_dim { 5 pt }
\dim_case:nnF
{ 2 \l_tmpa_dim }
{
  { 5 pt }      { Small }
  { 4 pt + 6 pt } { Medium }
  { - 10 pt }   { Negative }
}
{ No idea! }
```

leaves “Medium” in the input stream.

5 Dimension expression loops

<code>\dim_do_until:nNnn</code> ☆	<code>\dim_do_until:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **false** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **true**.

<code>\dim_do_while:nNnn</code> ☆	<code>\dim_do_while:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Places the *⟨code⟩* in the input stream for T_EX to process, and then evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`. If the test is **true** then the *⟨code⟩* is inserted into the input stream again and a loop occurs until the *⟨relation⟩* is **false**.

<code>\dim_until_do:nNnn</code> ☆	<code>\dim_until_do:nNnn {⟨dimexpr₁⟩} ⟨relation⟩ {⟨dimexpr₂⟩} {⟨code⟩}</code>
-----------------------------------	---

Evaluates the relationship between the two *⟨dimension expressions⟩* as described for `\dim_compare:nNnTF`, and then places the *⟨code⟩* in the input stream if the *⟨relation⟩* is **false**. After the *⟨code⟩* has been processed by T_EX the test is repeated, and a loop occurs until the test is **true**.

<hr/> <code>\dim_while_do:nNnn</code> ☆ <hr/>	<code>\dim_while_do:nNnn {<dimexpr1>} <relation> {<dimexpr2>} {<code>}</code>
	Evaluates the relationship between the two <i><dimension expressions></i> as described for <code>\dim_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\dim_do_until:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_do_until:nn {<dimension relation>} {<code>}</code>
	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<hr/> <code>\dim_do_while:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_do_while:nn {<dimension relation>} {<code>}</code>
	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<hr/> <code>\dim_until_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_until_do:nn {<dimension relation>} {<code>}</code>
	Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\dim_while_do:nn</code> ☆ <hr/> <div>Updated: 2013-01-13</div>	<code>\dim_while_do:nn {<dimension relation>} {<code>}</code>
	Evaluates the <i><dimension relation></i> as described for <code>\dim_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

6 Dimension step functions

<hr/> <code>\dim_step_function:nnnN</code> ☆ <hr/> <div>New: 2018-02-18</div>	<code>\dim_step_function:nnnN {<initial value>} {<step>} {<final value>} <function></code>
	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be dimension expressions. The <i><function></i> is then placed in front of each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>). The <i><step></i> must be non-zero. If the <i><step></i> is positive, the loop stops when the <i><value></i> becomes larger than the <i><final value></i> . If the <i><step></i> is negative, the loop stops when the <i><value></i> becomes smaller than the <i><final value></i> . The <i><function></i> should absorb one argument.
<hr/> <code>\dim_step_inline:nnnn</code> <hr/> <div>New: 2018-02-18</div>	<code>\dim_step_inline:nnnn {<initial value>} {<step>} {<final value>} {<code>}</code>
	This function first evaluates the <i><initial value></i> , <i><step></i> and <i><final value></i> , all of which should be dimension expressions. Then for each <i><value></i> from the <i><initial value></i> to the <i><final value></i> in turn (using <i><step></i> between each <i><value></i>), the <i><code></i> is inserted into the input stream with #1 replaced by the current <i><value></i> . Thus the <i><code></i> should define a function of one argument (#1).

`\dim_step_variable:nnnNn`
 New: 2018-02-18

`\dim_step_variable:nnnNn`
`{\langle initial value \rangle}{\langle step \rangle}{\langle final value \rangle}{\langle tl var \rangle}{\langle code \rangle}`

This function first evaluates the $\langle initial value \rangle$, $\langle step \rangle$ and $\langle final value \rangle$, all of which should be dimension expressions. Then for each $\langle value \rangle$ from the $\langle initial value \rangle$ to the $\langle final value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl var \rangle$.

7 Using dim expressions and variables

`\dim_eval:n` ★
 Updated: 2011-10-22

`\dim_eval:n {\langle dimension expression \rangle}`

Evaluates the $\langle dimension expression \rangle$, expanding any dimensions and token list variables within the $\langle expression \rangle$ to their content (without requiring `\dim_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a $\langle dimension denotation \rangle$ after two expansions. This is expressed in points (`pt`), and requires suitable termination if used in a \TeX -style assignment as it is *not* an $\langle internal dimension \rangle$.

`\dim_use:N` ★
`\dim_use:c` ★

`\dim_use:N \langle dimension \rangle`

Recovers the content of a $\langle dimension \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a $\langle dimension \rangle$ is required (such as in the argument of `\dim_eval:n`).

\TeX hackers note: `\dim_use:N` is the \TeX primitive `\the`: this is one of several \LaTeX 3 names for this primitive.

`\dim_to_decimal:n` ★
 New: 2014-07-15

`\dim_to_decimal:n {\langle dimexpr \rangle}`

Evaluates the $\langle dimension expression \rangle$, and leaves the result, expressed in points (`pt`) in the input stream, with *no units*. The result is rounded by \TeX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

`\dim_to_decimal:n { 1bp }`

leaves 1.00374 in the input stream, *i.e.* the magnitude of one “big point” when converted to (\TeX) points.

<code>\dim_to_decimal_in_bp:n</code> ★	<code>\dim_to_decimal_in_bp:n {⟨dimexpr⟩}</code>
New: 2014-07-15	Evaluates the <i>⟨dimension expression⟩</i> , and leaves the result, expressed in big points (bp) in the input stream, with <i>no units</i> . The result is rounded by T _E X to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

```
\dim_to_decimal_in_bp:n { 1pt }
```

leaves 0.99628 in the input stream, *i.e.* the magnitude of one (T_EX) point when converted to big points.

<code>\dim_to_decimal_in_sp:n</code> ★	<code>\dim_to_decimal_in_sp:n {⟨dimexpr⟩}</code>
New: 2015-05-18	Evaluates the <i>⟨dimension expression⟩</i> , and leaves the result, expressed in scaled points (sp) in the input stream, with <i>no units</i> . The result is necessarily an integer.

<code>\dim_to_decimal_in_unit:nn</code> ★	<code>\dim_to_decimal_in_unit:nn {⟨dimexpr₁⟩} {⟨dimexpr₂⟩}</code>
New: 2014-07-15	

Evaluates the *⟨dimension expressions⟩*, and leaves the value of *⟨dimexpr₁⟩*, expressed in a unit given by *⟨dimexpr₂⟩*, in the input stream. The result is a decimal number, rounded by T_EX to four or five decimal places. If the decimal part of the result is zero, it is omitted, together with the decimal marker.

For example

```
\dim_to_decimal_in_unit:nn { 1bp } { 1mm }
```

leaves 0.35277 in the input stream, *i.e.* the magnitude of one big point when converted to millimetres.

Note that this function is not optimised for any particular output and as such may give different results to `\dim_to_decimal_in_bp:n` or `\dim_to_decimal_in_sp:n`. In particular, the latter is able to take a wider range of input values as it is not limited by the ability to calculate a ratio using ε -T_EX primitives, which is required internally by `\dim_to_decimal_in_unit:nn`.

<code>\dim_to_fp:n</code> ★	<code>\dim_to_fp:n {⟨dimexpr⟩}</code>
New: 2012-05-08	Expands to an internal floating point number equal to the value of the <i>⟨dimexpr⟩</i> in pt. Since dimension expressions are evaluated much faster than their floating point equivalent, <code>\dim_to_fp:n</code> can be used to speed up parts of a computation where a low precision and a smaller range are acceptable.

8 Viewing dim variables

<code>\dim_show:N</code>	<code>\dim_show:N ⟨dimension⟩</code>
<code>\dim_show:c</code>	Displays the value of the <i>⟨dimension⟩</i> on the terminal.

<hr/> <code>\dim_show:n</code> <hr/>	<code>\dim_show:n {⟨<i>dimension expression</i>⟩}</code>
New: 2011-11-22 Updated: 2015-08-07	Displays the result of evaluating the $\langle dimension expression \rangle$ on the terminal.
<hr/> <code>\dim_log:N</code> <code>\dim_log:c</code> <hr/>	<code>\dim_log:N ⟨<i>dimension</i>⟩</code>
New: 2014-08-22 Updated: 2015-08-03	Writes the value of the $\langle dimension \rangle$ in the log file.
<hr/> <code>\dim_log:n</code> <hr/>	<code>\dim_log:n {⟨<i>dimension expression</i>⟩}</code>
New: 2014-08-22 Updated: 2015-08-07	Writes the result of evaluating the $\langle dimension expression \rangle$ in the log file.

9 Constant dimensions

<hr/> <code>\c_max_dim</code> <hr/>	The maximum value that can be stored as a dimension. This can also be used as a component of a skip.
<hr/> <code>\c_zero_dim</code> <hr/>	A zero length as a dimension. This can also be used as a component of a skip.

10 Scratch dimensions

<hr/> <code>\l_tmpa_dim</code> <code>\l_tmpb_dim</code> <hr/>	Scratch dimension for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_dim</code> <code>\g_tmpb_dim</code> <hr/>	Scratch dimension for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

11 Creating and initialising skip variables

<hr/> <code>\skip_new:N</code> <code>\skip_new:c</code> <hr/>	<code>\skip_new:N ⟨<i>skip</i>⟩</code>
	Creates a new $\langle skip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle skip \rangle$ is initially equal to 0 pt.
<hr/> <code>\skip_const:Nn</code> <code>\skip_const:cn</code> <hr/>	<code>\skip_const:Nn ⟨<i>skip</i>⟩ {⟨<i>skip expression</i>⟩}</code>
New: 2012-03-05	Creates a new constant $\langle skip \rangle$ or raises an error if the name is already taken. The value of the $\langle skip \rangle$ is set globally to the $\langle skip expression \rangle$.

<code>\skip_zero:N</code>	<code>\skip_zero:N</code> $\langle skip \rangle$
<code>\skip_zero:c</code>	
<code>\skip_gzero:N</code>	Sets $\langle skip \rangle$ to 0 pt.
<code>\skip_gzero:c</code>	

<code>\skip_zero_new:N</code>	<code>\skip_zero_new:N</code> $\langle skip \rangle$
<code>\skip_zero_new:c</code>	
<code>\skip_gzero_new:N</code>	Ensures that the $\langle skip \rangle$ exists globally by applying <code>\skip_new:N</code> if necessary, then applies
<code>\skip_gzero_new:c</code>	<code>\skip_(g)zero:N</code> to leave the $\langle skip \rangle$ set to zero.

New: 2012-01-07

<code>\skip_if_exist_p:N</code> ★	<code>\skip_if_exist_p:N</code> $\langle skip \rangle$
<code>\skip_if_exist_p:c</code> ★	<code>\skip_if_exist:NTF</code> $\langle skip \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\skip_if_exist:NTF</code> ★	
<code>\skip_if_exist:cTF</code> ★	Tests whether the $\langle skip \rangle$ is currently defined. This does not check that the $\langle skip \rangle$ really is a skip variable.

New: 2012-03-03

12 Setting skip variables

<code>\skip_add:Nn</code>	<code>\skip_add:Nn</code> $\langle skip \rangle$ $\{\langle skip\ expression \rangle\}$
<code>\skip_add:cn</code>	
<code>\skip_gadd:Nn</code>	Adds the result of the $\langle skip\ expression \rangle$ to the current content of the $\langle skip \rangle$.
<code>\skip_gadd:cn</code>	

Updated: 2011-10-22

<code>\skip_set:Nn</code>	<code>\skip_set:Nn</code> $\langle skip \rangle$ $\{\langle skip\ expression \rangle\}$
<code>\skip_set:cn</code>	
<code>\skip_gset:Nn</code>	Sets $\langle skip \rangle$ to the value of $\langle skip\ expression \rangle$, which must evaluate to a length with units
<code>\skip_gset:cn</code>	and may include a rubber component (for example 1 cm plus 0.5 cm).

Updated: 2011-10-22

<code>\skip_set_eq:NN</code>	<code>\skip_set_eq:NN</code> $\langle skip_1 \rangle$ $\langle skip_2 \rangle$
<code>\skip_set_eq:(cN Nc cc)</code>	
<code>\skip_gset_eq:NN</code>	Sets the content of $\langle skip_1 \rangle$ equal to that of $\langle skip_2 \rangle$.
<code>\skip_gset_eq:(cN Nc cc)</code>	

<code>\skip_sub:Nn</code>	<code>\skip_sub:Nn</code> $\langle skip \rangle$ $\{\langle skip\ expression \rangle\}$
<code>\skip_sub:cn</code>	
<code>\skip_gsub:Nn</code>	Subtracts the result of the $\langle skip\ expression \rangle$ from the current content of the $\langle skip \rangle$.
<code>\skip_gsub:cn</code>	

Updated: 2011-10-22

13 Skip expression conditionals

<code>\skip_if_eq_p:nn</code> ★	<code>\skip_if_eq_p:nn {\langle skipexpr_1 \rangle} {\langle skipexpr_2 \rangle}</code>
<code>\skip_if_eq:nnTF</code> ★	<code>\skip_if_eq:nnTF</code> <code>{\langle skipexpr_1 \rangle} {\langle skipexpr_2 \rangle}</code> <code>{\langle true code \rangle} {\langle false code \rangle}</code>

This function first evaluates each of the $\langle skip\ expressions \rangle$ as described for `\skip_eval:n`. The two results are then compared for exact equality, *i.e.* both the fixed and rubber components must be the same for the test to be true.

<code>\skip_if_finite_p:n</code> ★	<code>\skip_if_finite_p:n {\langle skipexpr \rangle}</code>
<code>\skip_if_finite:nTF</code> ★	<code>\skip_if_finite:nTF {\langle skipexpr \rangle} {\langle true code \rangle} {\langle false code \rangle}</code>

New: 2012-03-05

Evaluates the $\langle skip\ expression \rangle$ as described for `\skip_eval:n`, and then tests if all of its components are finite.

14 Using skip expressions and variables

<code>\skip_eval:n</code> ★	<code>\skip_eval:n {\langle skip expression \rangle}</code>
-----------------------------	---

Updated: 2011-10-22

Evaluates the $\langle skip\ expression \rangle$, expanding any skips and token list variables within the $\langle expression \rangle$ to their content (without requiring `\skip_use:N/\tl_use:N`) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a $\langle glue\ denotation \rangle$ after two expansions. This is expressed in points (pt), and requires suitable termination if used in a T_EX-style assignment as it is *not* an $\langle internal\ glue \rangle$.

<code>\skip_use:N</code> ★	<code>\skip_use:N \langle skip \rangle</code>
<code>\skip_use:c</code> ★	

Recovers the content of a $\langle skip \rangle$ and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a $\langle dimension \rangle$ or $\langle skip \rangle$ is required (such as in the argument of `\skip_eval:n`).

T_EXhackers note: `\skip_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

15 Viewing skip variables

<code>\skip_show:N</code>	<code>\skip_show:N \langle skip \rangle</code>
<code>\skip_show:c</code>	

Updated: 2015-08-03

Displays the value of the $\langle skip \rangle$ on the terminal.

<code>\skip_show:n</code>	<code>\skip_show:n {\langle skip expression \rangle}</code>
---------------------------	---

New: 2011-11-22

Updated: 2015-08-07

Displays the result of evaluating the $\langle skip\ expression \rangle$ on the terminal.

<code>\skip_log:N</code>	<code>\skip_log:N <skip></code>
<code>\skip_log:c</code>	Writes the value of the $\langle skip \rangle$ in the log file.
New: 2014-08-22	
Updated: 2015-08-03	

<code>\skip_log:n</code>	<code>\skip_log:n {\langle skip expression \rangle}</code>
	Writes the result of evaluating the $\langle skip expression \rangle$ in the log file.
New: 2014-08-22	
Updated: 2015-08-07	

16 Constant skips

<code>\c_max_skip</code>	The maximum value that can be stored as a skip (equal to <code>\c_max_dim</code> in length), with no stretch nor shrink component.
Updated: 2012-11-02	

<code>\c_zero_skip</code>	A zero length as a skip, with no stretch nor shrink component.
Updated: 2012-11-01	

17 Scratch skips

<code>\l_tmpa_skip</code> <code>\l_tmpb_skip</code>	Scratch skip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

<code>\g_tmpa_skip</code> <code>\g_tmpb_skip</code>	Scratch skip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

18 Inserting skips into the output

<code>\skip_horizontal:N</code>	<code>\skip_horizontal:N <skip></code>
<code>\skip_horizontal:c</code>	<code>\skip_horizontal:n {\langle skipexpr \rangle}</code>
<code>\skip_horizontal:n</code>	Inserts a horizontal $\langle skip \rangle$ into the current list. The argument can also be a $\langle dim \rangle$.
Updated: 2011-10-22	

T_EXhackers note: `\skip_horizontal:N` is the T_EX primitive `\hskip` renamed.

<code>\skip_vertical:N</code>	<code>\skip_vertical:N <skip></code>
<code>\skip_vertical:c</code>	<code>\skip_vertical:n {\langle skipexpr \rangle}</code>
<code>\skip_vertical:n</code>	Inserts a vertical $\langle skip \rangle$ into the current list. The argument can also be a $\langle dim \rangle$.
Updated: 2011-10-22	

T_EXhackers note: `\skip_vertical:N` is the T_EX primitive `\vskip` renamed.

19 Creating and initialising muskip variables

`\muskip_new:N`
`\muskip_new:c`

`\muskip_new:N` $\langle muskip \rangle$

Creates a new $\langle muskip \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle muskip \rangle$ is initially equal to 0 mu.

`\muskip_const:Nn`
`\muskip_const:cn`

`\muskip_const:Nn` $\langle muskip \rangle$ $\{ \langle muskip expression \rangle \}$

Creates a new constant $\langle muskip \rangle$ or raises an error if the name is already taken. The value of the $\langle muskip \rangle$ is set globally to the $\langle muskip expression \rangle$.

New: 2012-03-05

`\muskip_zero:N`
`\muskip_zero:c`
`\muskip_gzero:N`
`\muskip_gzero:c`

`\skip_zero:N` $\langle muskip \rangle$

Sets $\langle muskip \rangle$ to 0 mu.

`\muskip_zero_new:N`
`\muskip_zero_new:c`
`\muskip_gzero_new:N`
`\muskip_gzero_new:c`

`\muskip_zero_new:N` $\langle muskip \rangle$

Ensures that the $\langle muskip \rangle$ exists globally by applying `\muskip_new:N` if necessary, then applies `\muskip_(g)zero:N` to leave the $\langle muskip \rangle$ set to zero.

New: 2012-01-07

`\muskip_if_exist_p:N` ★
`\muskip_if_exist_p:c` ★
`\muskip_if_exist:N \underline{TF}` ★
`\muskip_if_exist:c \underline{TF}` ★

`\muskip_if_exist_p:N` $\langle muskip \rangle$

`\muskip_if_exist:NTF` $\langle muskip \rangle$ $\{ \langle true code \rangle \} \{ \langle false code \rangle \}$

Tests whether the $\langle muskip \rangle$ is currently defined. This does not check that the $\langle muskip \rangle$ really is a muskip variable.

New: 2012-03-03

20 Setting muskip variables

`\muskip_add:Nn`
`\muskip_add:cn`
`\muskip_gadd:Nn`
`\muskip_gadd:cn`

`\muskip_add:Nn` $\langle muskip \rangle$ $\{ \langle muskip expression \rangle \}$

Adds the result of the $\langle muskip expression \rangle$ to the current content of the $\langle muskip \rangle$.

Updated: 2011-10-22

`\muskip_set:Nn`
`\muskip_set:cn`
`\muskip_gset:Nn`
`\muskip_gset:cn`

`\muskip_set:Nn` $\langle muskip \rangle$ $\{ \langle muskip expression \rangle \}$

Sets $\langle muskip \rangle$ to the value of $\langle muskip expression \rangle$, which must evaluate to a math length with units and may include a rubber component (for example 1 mu plus 0.5 mu).

Updated: 2011-10-22

`\muskip_set_eq:NN`
`\muskip_set_eq:(cN|Nc|cc)`
`\muskip_gset_eq:NN`
`\muskip_gset_eq:(cN|Nc|cc)`

`\muskip_set_eq:NN` $\langle muskip_1 \rangle$ $\langle muskip_2 \rangle$

Sets the content of $\langle muskip_1 \rangle$ equal to that of $\langle muskip_2 \rangle$.

<hr/> <code>\muskip_sub:Nn</code>	<code>\muskip_sub:Nn <muskip> {<muskip expression>}</code>
<code>\muskip_sub:cn</code>	
<code>\muskip_gsub:Nn</code>	Subtracts the result of the <i><muskip expression></i> from the current content of the <i><skip></i> .
<code>\muskip_gsub:cn</code>	
<hr/> Updated: 2011-10-22 <hr/>	

21 Using muskip expressions and variables

<hr/> <code>\muskip_eval:n</code> ★	<code>\muskip_eval:n {<muskip expression>}</code>
<code>\muskip_eval:cn</code>	
<hr/> Updated: 2011-10-22 <hr/>	
	Evaluates the <i><muskip expression></i> , expanding any skips and token list variables within the <i><expression></i> to their content (without requiring <code>\muskip_use:N/\tl_use:N</code>) and applying the standard mathematical rules. The result of the calculation is left in the input stream as a <i><mu glue denotation></i> after two expansions. This is expressed in <code>\mu</code> , and requires suitable termination if used in a T _E X-style assignment as it is <i>not</i> an <i><internal mu glue></i> .

<hr/> <code>\muskip_use:N</code> ★	<code>\muskip_use:N <muskip></code>
<code>\muskip_use:cn</code> ★	
<hr/>	
	Recovers the content of a <i><skip></i> and places it directly in the input stream. An error is raised if the variable does not exist or if it is invalid. Can be omitted in places where a <i><dimension></i> is required (such as in the argument of <code>\muskip_eval:n</code>).

T_EXhackers note: `\muskip_use:N` is the T_EX primitive `\the`: this is one of several L^AT_EX3 names for this primitive.

22 Viewing muskip variables

<hr/> <code>\muskip_show:N</code>	<code>\muskip_show:N <muskip></code>
<code>\muskip_show:cn</code>	
<hr/> Updated: 2015-08-03 <hr/>	
	Displays the value of the <i><muskip></i> on the terminal.

<hr/> <code>\muskip_show:n</code>	<code>\muskip_show:n {<muskip expression>}</code>
<code>\muskip_show:cn</code>	
<hr/> New: 2011-11-22 <hr/> Updated: 2015-08-07 <hr/>	
	Displays the result of evaluating the <i><muskip expression></i> on the terminal.

<hr/> <code>\muskip_log:N</code>	<code>\muskip_log:N <muskip></code>
<code>\muskip_log:cn</code>	
<hr/> New: 2014-08-22 <hr/> Updated: 2015-08-03 <hr/>	
	Writes the value of the <i><muskip></i> in the log file.

<hr/> <code>\muskip_log:n</code>	<code>\muskip_log:n {<muskip expression>}</code>
<code>\muskip_log:cn</code>	
<hr/> New: 2014-08-22 <hr/> Updated: 2015-08-07 <hr/>	
	Writes the result of evaluating the <i><muskip expression></i> in the log file.

23 Constant muskip

<code>\c_max_muskip</code>	The maximum value that can be stored as a muskip, with no stretch nor shrink component.
----------------------------	---

<code>\c_zero_muskip</code>	A zero length as a muskip, with no stretch nor shrink component.
-----------------------------	--

24 Scratch muskip

<code>\l_tmpa_muskip</code> <code>\l_tmpb_muskip</code>	Scratch muskip for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	--

<code>\g_tmpa_muskip</code> <code>\g_tmpb_muskip</code>	Scratch muskip for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
--	---

25 Primitive conditional

<code>\if_dim:w</code>	<code>\if_dim:w <dimen₁> <relation> <dimen₂></code> <code><true code></code> <code>\else:</code> <code><false></code> <code>\fi:</code>
------------------------	---

Compare two dimensions. The *<relation>* is one of *<*, *=* or *>* with category code 12.

T_EXhackers note: This is the T_EX primitive `\ifdim`.

Part XX

The l3keys package

Key–value interfaces

The key–value method is a popular system for creating large numbers of settings for controlling function or package behaviour. The system normally results in input of the form

```
\MyModuleSetup{
  key-one = value one,
  key-two = value two
}
```

or

```
\MyModuleMacro[
  key-one = value one,
  key-two = value two
]{argument}
```

for the user.

The high level functions here are intended as a method to create key–value controls. Keys are themselves created using a key–value interface, minimising the number of functions and arguments required. Each key is created by setting one or more *properties* of the key:

```
\keys_define:nn { mymodule }
{
  key-one .code:n = code including parameter #1,
  key-two .tl_set:N = \l_mymodule_store_tl
}
```

These values can then be set as with other key–value approaches:

```
\keys_set:nn { mymodule }
{
  key-one = value one,
  key-two = value two
}
```

At a document level, `\keys_set:nn` is used within a document function, for example

```
\DeclareDocumentCommand \MyModuleSetup { m }
{ \keys_set:nn { mymodule } { #1 } }
\DeclareDocumentCommand \MyModuleMacro { o m }
{
  \group_begin:
    \keys_set:nn { mymodule } { #1 }
    % Main code for \MyModuleMacro
  \group_end:
}
```


Key names may contain any tokens, as they are handled internally using `\tl_to_str:n`. As discussed in section 2, it is suggested that the character `/` is reserved for sub-division of keys into logical groups. Functions and variables are *not* expanded when creating key names, and so

```
\tl_set:Nn \l_mymodule_tmp_tl { key }
\keys_define:nn { mymodule }
{
  \l_mymodule_tmp_tl .code:n = code
}
```

creates a key called `\l_mymodule_tmp_tl`, and not one called `key`.

1 Creating keys

`\keys_define:nn`

Updated: 2017-11-14

`\keys_define:nn {<module>} {<keyval list>}`

Parses the *<keyval list>* and defines the keys listed there for *<module>*. The *<module>* name should be a text value, but there are no restrictions on the nature of the text. In practice the *<module>* should be chosen to be unique to the module in question (unless deliberately adding keys to an existing module).

The *<keyval list>* should consist of one or more key names along with an associated key *property*. The properties of a key determine how it acts. The individual properties are described in the following text; a typical use of `\keys_define:nn` might read

```
\keys_define:nn { mymodule }
{
  keyname .code:n = Some~code~using~#1,
  keyname .value_required:n = true
}
```

where the properties of the key begin from the `.` after the key name.

The various properties available take either no arguments at all, or require one or more arguments. This is indicated in the name of the property using an argument specification. In the following discussion, each property is illustrated attached to an arbitrary *<key>*, which when used may be supplied with a *<value>*. All key *definitions* are local.

Key properties are applied in the reading order and so the ordering is significant. Key properties which define “actions”, such as `.code:n`, `.tl_set:N`, *etc.*, override one another. Some other properties are mutually exclusive, notably `.value_required:n` and `.value_forbidden:n`, and so they replace one another. However, properties covering non-exclusive behaviours may be given in any order. Thus for example the following definitions are equivalent.

```
\keys_define:nn { mymodule }
{
  keyname .code:n          = Some~code~using~#1,
  keyname .value_required:n = true
}
\keys_define:nn { mymodule }
```

```

{
  keyname .value_required:n = true,
  keyname .code:n           = Some~code~using~#1
}

```

Note that with the exception of the special `.undefine:` property, all key properties define the key within the current \TeX scope.

```

.bool_set:N
.bool_set:c
.bool_gset:N
.bool_gset:c

```

Updated: 2013-07-08

$\langle key \rangle$.bool_set:N = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to $\langle value \rangle$ (which must be either `true` or `false`). If the variable does not exist, it will be created globally at the point that the key is set up.

```

.bool_set_inverse:N
.bool_set_inverse:c
.bool_gset_inverse:N
.bool_gset_inverse:c

```

New: 2011-08-28

Updated: 2013-07-08

$\langle key \rangle$.bool_set_inverse:N = $\langle boolean \rangle$

Defines $\langle key \rangle$ to set $\langle boolean \rangle$ to the logical inverse of $\langle value \rangle$ (which must be either `true` or `false`). If the $\langle boolean \rangle$ does not exist, it will be created globally at the point that the key is set up.

```

.choice:

```

$\langle key \rangle$.choice:

Sets $\langle key \rangle$ to act as a choice key. Each valid choice for $\langle key \rangle$ must then be created, as discussed in section 3.

```

.choices:nn
.choices:(Vn|on|xn)

```

New: 2011-08-21

Updated: 2013-07-10

$\langle key \rangle$.choices:nn = $\{\langle choices \rangle\}$ $\{\langle code \rangle\}$

Sets $\langle key \rangle$ to act as a choice key, and defines a series $\langle choices \rangle$ which are implemented using the $\langle code \rangle$. Inside $\langle code \rangle$, `\l_keys_choice_tl` will be the name of the choice made, and `\l_keys_choice_int` will be the position of the choice in the list of $\langle choices \rangle$ (indexed from 1). Choices are discussed in detail in section 3.

```

.clist_set:N
.clist_set:c
.clist_gset:N
.clist_gset:c

```

New: 2011-09-11

$\langle key \rangle$.clist_set:N = $\langle comma list variable \rangle$

Defines $\langle key \rangle$ to set $\langle comma list variable \rangle$ to $\langle value \rangle$. Spaces around commas and empty items will be stripped. If the variable does not exist, it is created globally at the point that the key is set up.

```

.code:n

```

Updated: 2013-07-10

$\langle key \rangle$.code:n = $\{\langle code \rangle\}$

Stores the $\langle code \rangle$ for execution when $\langle key \rangle$ is used. The $\langle code \rangle$ can include one parameter (`#1`), which will be the $\langle value \rangle$ given for the $\langle key \rangle$.

`.default:n`
`.default:(V|o|x)`
Updated: 2013-07-09

`<key> .default:n = {<default>}`

Creates a *<default>* value for *<key>*, which is used if no value is given. This will be used if only the key name is given, but not if a blank *<value>* is given:

```
\keys_define:nn { mymodule }
{
  key .code:n      = Hello~#1,
  key .default:n = World
}
\keys_set:nn { mymodule }
{
  key = Fred, % Prints 'Hello Fred'
  key,      % Prints 'Hello World'
  key = ,    % Prints 'Hello '
}
```

The default does not affect keys where values are required or forbidden. Thus a required value cannot be supplied by a default value, and giving a default value for a key which cannot take a value does not trigger an error.

`.dim_set:N`
`.dim_set:c`
`.dim_gset:N`
`.dim_gset:c`

`<key> .dim_set:N = <dimension>`

Defines *<key>* to set *<dimension>* to *<value>* (which must a dimension expression). If the variable does not exist, it is created globally at the point that the key is set up.

`.fp_set:N`
`.fp_set:c`
`.fp_gset:N`
`.fp_gset:c`

`<key> .fp_set:N = <floating point>`

Defines *<key>* to set *<floating point>* to *<value>* (which must a floating point expression). If the variable does not exist, it is created globally at the point that the key is set up.

`.groups:n`
New: 2013-07-14

`<key> .groups:n = {<groups>}`

Defines *<key>* as belonging to the *<groups>* declared. Groups provide a “secondary axis” for selectively setting keys, and are described in Section 6.

`.inherit:n`
New: 2016-11-22

`<key> .inherit:n = {<parents>}`

Specifies that the *<key>* path should inherit the keys listed as *<parents>*. For example, after setting

```
\keys_define:n { foo } { test .code:n = \tl_show:n {#1} }
\keys_define:n { } { bar .inherit:n = foo }
```

setting

```
\keys_set:n { bar } { test = a }
```

will be equivalent to

```
\keys_set:n { foo } { test = a }
```

<hr/> <code>.initial:n</code> <hr/>	<code><key> .initial:n = {<value>}</code>
<code>.initial:(V o x)</code>	Initialises the <code><key></code> with the <code><value></code> , equivalent to
<hr/> Updated: 2013-07-09 <hr/>	<code>\keys_set:nn {<module>} { <key> = <value> }</code>
<hr/> <code>.int_set:N</code> <hr/>	<code><key> .int_set:N = <integer></code>
<code>.int_set:c</code>	Defines <code><key></code> to set <code><integer></code> to <code><value></code> (which must be an integer expression). If the variable does not exist, it is created globally at the point that the key is set up.
<code>.int_gset:N</code>	
<code>.int_gset:c</code> <hr/>	
<hr/> <code>.meta:n</code> <hr/>	<code><key> .meta:n = {<keyval list>}</code>
<hr/> Updated: 2013-07-10 <hr/>	Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go. The <code><keyval list></code> can refer as <code>#1</code> to the value given at the time the <code><key></code> is used (or, if no value is given, the <code><key></code> 's default value).
<hr/> <code>.meta:nn</code> <hr/>	<code><key> .meta:nn = {<path>} {<keyval list>}</code>
<hr/> New: 2013-07-10 <hr/>	Makes <code><key></code> a meta-key, which will set <code><keyval list></code> in one go using the <code><path></code> in place of the current one. The <code><keyval list></code> can refer as <code>#1</code> to the value given at the time the <code><key></code> is used (or, if no value is given, the <code><key></code> 's default value).
<hr/> <code>.multichoice:</code> <hr/>	<code><key> .multichoice:</code>
<hr/> New: 2011-08-21 <hr/>	Sets <code><key></code> to act as a multiple choice key. Each valid choice for <code><key></code> must then be created, as discussed in section 3.
<hr/> <code>.multichoices:nn</code> <hr/>	<code><key> .multichoices:nn {<choices>} {<code>}</code>
<code>.multichoices:(Vn on xn)</code>	Sets <code><key></code> to act as a multiple choice key, and defines a series <code><choices></code> which are implemented using the <code><code></code> . Inside <code><code></code> , <code>\l_keys_choice_tl</code> will be the name of the choice made, and <code>\l_keys_choice_int</code> will be the position of the choice in the list of <code><choices></code> (indexed from 1). Choices are discussed in detail in section 3.
<hr/> New: 2011-08-21 <hr/>	
<hr/> Updated: 2013-07-10 <hr/>	
<hr/> <code>.skip_set:N</code> <hr/>	<code><key> .skip_set:N = <skip></code>
<code>.skip_set:c</code>	Defines <code><key></code> to set <code><skip></code> to <code><value></code> (which must be a skip expression). If the variable does not exist, it is created globally at the point that the key is set up.
<code>.skip_gset:N</code>	
<code>.skip_gset:c</code> <hr/>	
<hr/> <code>.tl_set:N</code> <hr/>	<code><key> .tl_set:N = <token list variable></code>
<code>.tl_set:c</code>	Defines <code><key></code> to set <code><token list variable></code> to <code><value></code> . If the variable does not exist, it is created globally at the point that the key is set up.
<code>.tl_gset:N</code>	
<code>.tl_gset:c</code> <hr/>	
<hr/> <code>.tl_set_x:N</code> <hr/>	<code><key> .tl_set_x:N = <token list variable></code>
<code>.tl_set_x:c</code>	Defines <code><key></code> to set <code><token list variable></code> to <code><value></code> , which will be subjected to an x-type expansion (<i>i.e.</i> using <code>\tl_set:Nx</code>). If the variable does not exist, it is created globally at the point that the key is set up.
<code>.tl_gset_x:N</code>	
<code>.tl_gset_x:c</code> <hr/>	

<code>.undefine:</code>	<code><key> .undefine:</code>
-------------------------	-------------------------------------

New: 2015-07-14	Removes the definition of the <code><key></code> within the current scope.
-----------------	--

<code>.value_forbidden:n</code>	<code><key> .value_forbidden:n = true false</code>
---------------------------------	--

New: 2015-07-14	Specifies that <code><key></code> cannot receive a <code><value></code> when used. If a <code><value></code> is given then an error will be issued. Setting the property <code>false</code> cancels the restriction.
-----------------	--

<code>.value_required:n</code>	<code><key> .value_required:n = true false</code>
--------------------------------	---

New: 2015-07-14	Specifies that <code><key></code> must receive a <code><value></code> when used. If a <code><value></code> is not given then an error will be issued. Setting the property <code>false</code> cancels the restriction.
-----------------	--

2 Sub-dividing keys

When creating large numbers of keys, it may be desirable to divide them into several sub-groups for a given module. This can be achieved either by adding a sub-division to the module name:

```
\keys_define:nn { module / subgroup }
{ key .code:n = code }
```

or to the key name:

```
\keys_define:nn { mymodule }
{ subgroup / key .code:n = code }
```

As illustrated, the best choice of token for sub-dividing keys in this way is `/`. This is because of the method that is used to represent keys internally. Both of the above code fragments set the same key, which has full name `module/subgroup/key`.

As illustrated in the next section, this subdivision is particularly relevant to making multiple choices.

3 Choice and multiple choice keys

The `l3keys` system supports two types of choice key, in which a series of pre-defined input values are linked to varying implementations. Choice keys are usually created so that the various values are mutually-exclusive: only one can apply at any one time. “Multiple” choice keys are also supported: these allow a selection of values to be chosen at the same time.

Mutually-exclusive choices are created by setting the `.choice:` property:

```
\keys_define:nn { mymodule }
{ key .choice: }
```

For keys which are set up as choices, the valid choices are generated by creating sub-keys of the choice key. This can be carried out in two ways.

In many cases, choices execute similar code which is dependant only on the name of the choice or the position of the choice in the list of all possibilities. Here, the keys can share the same code, and can be rapidly created using the `.choices:nn` property.

```

\keys_define:nn { mymodule }
{
  key .choices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~\int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}

```

The index `\l_keys_choice_int` in the list of choices starts at 1.

`\l_keys_choice_int`
`\l_keys_choice_tl`

Inside the code block for a choice generated using `.choices:nn`, the variables `\l_keys_choice_tl` and `\l_keys_choice_int` are available to indicate the name of the current choice, and its position in the comma list. The position is indexed from 1. Note that, as with standard key code generated using `.code:n`, the value passed to the key (i.e. the choice name) is also available as `#1`.

On the other hand, it is sometimes useful to create choices which use entirely different code from one another. This can be achieved by setting the `.choice:` property of a key, then manually defining sub-keys.

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}

```

It is possible to mix the two methods, but manually-created choices should *not* use `\l_keys_choice_tl` or `\l_keys_choice_int`. These variables do not have defined behaviour when used outside of code created using `.choices:nn` (i.e. anything might happen).

It is possible to allow choice keys to take values which have not previously been defined by adding code for the special `unknown` choice. The general behavior of the `unknown` key is described in Section 5. A typical example in the case of a choice would be to issue a custom error message:

```

\keys_define:nn { mymodule }
{
  key .choice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
  key / unknown .code:n =
    \msg_error:nnxxx { mymodule } { unknown-choice }
    { key } % Name of choice key
    { choice-a , choice-b , choice-c } % Valid choices
    { \exp_not:n {#1} } % Invalid choice given
}

```

```
%
%
}
```

Multiple choices are created in a very similar manner to mutually-exclusive choices, using the properties `.multichoice:` and `.multichoices:nn`. As with mutually exclusive choices, multiple choices are define as sub-keys. Thus both

```
\keys_define:nn { mymodule }
{
  key .multichoices:nn =
    { choice-a, choice-b, choice-c }
    {
      You~gave~choice~'\tl_use:N \l_keys_choice_tl',~
      which~is~in~position~
      \int_use:N \l_keys_choice_int \c_space_tl
      in~the~list.
    }
}
```

and

```
\keys_define:nn { mymodule }
{
  key .multichoice:,
  key / choice-a .code:n = code-a,
  key / choice-b .code:n = code-b,
  key / choice-c .code:n = code-c,
}
```

are valid.

When a multiple choice key is set

```
\keys_set:nn { mymodule }
{
  key = { a , b , c } % 'key' defined as a multiple choice
}
```

each choice is applied in turn, equivalent to a `clist` mapping or to applying each value individually:

```
\keys_set:nn { mymodule }
{
  key = a ,
  key = b ,
  key = c ,
}
```

Thus each separate choice will have passed to it the `\l_keys_choice_tl` and `\l_keys_choice_int` in exactly the same way as described for `.choices:nn`.

4 Setting keys

```
\keys_set:nn
\keys_set:(nV|nv|no)
```

Updated: 2017-11-14

```
\keys_set:nn {<module>} {<keyval list>}
```

Parses the *<keyval list>*, and sets those keys which are defined for *<module>*. The behaviour on finding an unknown key can be set by defining a special **unknown** key: this is illustrated later.

```
\l_keys_key_tl
\l_keys_path_tl
\l_keys_value_tl
```

Updated: 2015-07-14

For each key processed, information of the full *path* of the key, the *name* of the key and the *value* of the key is available within three token list variables. These may be used within the code of the key.

The *value* is everything after the =, which may be empty if no value was given. This is stored in `\l_keys_value_tl`, and is not processed in any way by `\keys_set:nn`.

The *path* of the key is a “full” description of the key, and is unique for each key. It consists of the module and full key name, thus for example

```
\keys_set:nn { mymodule } { key-a = some-value }
```

has path `mymodule/key-a` while

```
\keys_set:nn { mymodule } { subset / key-a = some-value }
```

has path `mymodule/subset/key-a`. This information is stored in `\l_keys_path_tl`, and will have been processed by `\tl_to_str:n`.

The *name* of the key is the part of the path after the last /, and thus is not unique. In the preceding examples, both keys have name `key-a` despite having different paths. This information is stored in `\l_keys_key_tl`, and will have been processed by `\tl_to_str:n`.

5 Handling of unknown keys

If a key has not previously been defined (is unknown), `\keys_set:nn` looks for a special **unknown** key for the same module, and if this is not defined raises an error indicating that the key name was unknown. This mechanism can be used for example to issue custom error texts.

```
\keys_define:nn { mymodule }
{
  unknown .code:n =
    You~tried~to~set~key~'\l_keys_key_tl'~to~'#1'.
}
```

```

\keys_set_known:nnN      \keys_set_known:nnN {<module>} {<keyval list>} {<tl>}
\keys_set_known:(nVN|nvN|noN)
\keys_set_known:nn
\keys_set_known:(nV|nv|no)

```

New: 2011-08-23
Updated: 2017-05-27

In some cases, the desired behavior is to simply ignore unknown keys, collecting up information on these for later processing. The `\keys_set_known:nnN` function parses the `<keyval list>`, and sets those keys which are defined for `<module>`. Any keys which are unknown are not processed further by the parser. The key-value pairs for each *unknown* key name are stored in the `<tl>` in a comma-separated form (*i.e.* an edited version of the `<keyval list>`). The `\keys_set_known:nn` version skips this stage.

Use of `\keys_set_known:nnN` can be nested, with the correct residual `<keyval list>` returned at each stage.

6 Selective key setting

In some cases it may be useful to be able to select only some keys for setting, even though these keys have the same path. For example, with a set of keys defined using

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-two   .tl_set:N = \l_my_a_tl         ,
  key-three .tl_set:N = \l_my_b_tl         ,
  key-four  .fp_set:N = \l_my_a_fp         ,
}

```

the use of `\keys_set:nn` attempts to set all four keys. However, in some contexts it may only be sensible to set some keys, or to control the order of setting. To do this, keys may be assigned to *groups*: arbitrary sets which are independent of the key tree. Thus modifying the example to read

```

\keys define:nn { mymodule }
{
  key-one   .code:n   = { \my_func:n {#1} } ,
  key-one   .groups:n = { first }           ,
  key-two   .tl_set:N = \l_my_a_tl         ,
  key-two   .groups:n = { first }           ,
  key-three .tl_set:N = \l_my_b_tl         ,
  key-three .groups:n = { second }          ,
  key-four  .fp_set:N = \l_my_a_fp         ,
}

```

assigns `key-one` and `key-two` to group `first`, `key-three` to group `second`, while `key-four` is not assigned to a group.

Selective key setting may be achieved either by selecting one or more groups to be made “active”, or by marking one or more groups to be ignored in key setting.

<code>\keys_set_filter:nnnN</code>	<code>\keys_set_filter:nnnN {<module>} {<groups>} {<keyval list>} <tl></code>
<code>\keys_set_filter:(nnVN nnvN nnoN)</code>	
<code>\keys_set_filter:nnn</code>	
<code>\keys_set_filter:(nnV nnv nno)</code>	

New: 2013-07-14

Updated: 2017-05-27

Activates key filtering in an “opt-out” sense: keys assigned to any of the $\langle groups \rangle$ specified are ignored. The $\langle groups \rangle$ are given as a comma-separated list. Unknown keys are not assigned to any group and are thus always set. The key-value pairs for each key which is filtered out are stored in the $\langle tl \rangle$ in a comma-separated form (*i.e.* an edited version of the $\langle keyval list \rangle$). The `\keys_set_filter:nnn` version skips this stage.

Use of `\keys_set_filter:nnnN` can be nested, with the correct residual $\langle keyval list \rangle$ returned at each stage.

<code>\keys_set_groups:nnn</code>	<code>\keys_set_groups:nnn {<module>} {<groups>} {<keyval list>}</code>
<code>\keys_set_groups:(nnV nnv nno)</code>	

New: 2013-07-14

Updated: 2017-05-27

Activates key filtering in an “opt-in” sense: only keys assigned to one or more of the $\langle groups \rangle$ specified are set. The $\langle groups \rangle$ are given as a comma-separated list. Unknown keys are not assigned to any group and are thus never set.

7 Utility functions for keys

<code>\keys_if_exist_p:nn</code> ★	<code>\keys_if_exist_p:nn {<module>} {<key>}</code>
<code>\keys_if_exist:nnTF</code> ★	<code>\keys_if_exist:nnTF {<module>} {<key>} {<true code>} {<false code>}</code>

Updated: 2017-11-14 Tests if the $\langle key \rangle$ exists for $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle$.

<code>\keys_if_choice_exist_p:nnn</code> ★	<code>\keys_if_choice_exist_p:nnn {<module>} {<key>} {<choice>}</code>
<code>\keys_if_choice_exist:nnnTF</code> ★	<code>\keys_if_choice_exist:nnnTF {<module>} {<key>} {<choice>} {<true code>} {<false code>}</code>

New: 2011-08-21

Updated: 2017-11-14

Tests if the $\langle choice \rangle$ is defined for the $\langle key \rangle$ within the $\langle module \rangle$, *i.e.* if any code has been defined for $\langle key \rangle / \langle choice \rangle$. The test is **false** if the $\langle key \rangle$ itself is not defined.

<code>\keys_show:nn</code>	<code>\keys_show:nn {<module>} {<key>}</code>
----------------------------	---

Updated: 2015-08-09

Displays in the terminal the information associated to the $\langle key \rangle$ for a $\langle module \rangle$, including the function which is used to actually implement it.

<code>\keys_log:nn</code>	<code>\keys_log:nn {<module>} {<key>}</code>
---------------------------	--

New: 2014-08-22

Updated: 2015-08-09

Writes in the log file the information associated to the $\langle key \rangle$ for a $\langle module \rangle$. See also `\keys_show:nn` which displays the result in the terminal.

8 Low-level interface for parsing key–val lists

To re-cap from earlier, a key–value list is input of the form

```
KeyOne = ValueOne ,  
KeyTwo = ValueTwo ,  
KeyThree
```

where each key–value pair is separated by a comma from the rest of the list, and each key–value pair does not necessarily contain an equals sign or a value! Processing this type of input correctly requires a number of careful steps, to correctly account for braces, spaces and the category codes of separators.

While the functions described earlier are used as a high-level interface for processing such input, in special circumstances you may wish to use a lower-level approach. The low-level parsing system converts a *key–value list* into *keys* and associated *values*. After the parsing phase is completed, the resulting keys and values (or keys alone) are available for further processing. This processing is not carried out by the low-level parser itself, and so the parser requires the names of two functions along with the key–value list. One function is needed to process key–value pairs (it receives two arguments), and a second function is required for keys given without any value (it is called with a single argument).

The parser does not double # tokens or expand any input. Active tokens = and , appearing at the outer level of braces are converted to category “other” (12) so that the parser does not “miss” any due to category code changes. Spaces are removed from the ends of the keys and values. Keys and values which are given in braces have exactly one set removed (after space trimming), thus

```
key = {value here},
```

and

```
key = value here,
```

are treated identically.

\keyval_parse:NNn

Updated: 2011-09-08

\keyval_parse:NNn $\langle function_1 \rangle$ $\langle function_2 \rangle$ { $\langle key-value list \rangle$ }

Parses the $\langle key-value list \rangle$ into a series of $\langle keys \rangle$ and associated $\langle values \rangle$, or keys alone (if no $\langle value \rangle$ was given). $\langle function_1 \rangle$ should take one argument, while $\langle function_2 \rangle$ should absorb two arguments. After **\keyval_parse:NNn** has parsed the $\langle key-value list \rangle$, $\langle function_1 \rangle$ is used to process keys given with no value and $\langle function_2 \rangle$ is used to process keys given with a value. The order of the $\langle keys \rangle$ in the $\langle key-value list \rangle$ is preserved. Thus

```
\keyval_parse:NNn \function:n \function:nn
{ key1 = value1 , key2 = value2, key3 = , key4 }
```

is converted into an input stream

```
\function:nn { key1 } { value1 }
\function:nn { key2 } { value2 }
\function:nn { key3 } { }
\function:n { key4 }
```

Note that there is a difference between an empty value (an equals sign followed by nothing) and a missing value (no equals sign at all). Spaces are trimmed from the ends of the $\langle key \rangle$ and $\langle value \rangle$, then one *outer* set of braces is removed from the $\langle key \rangle$ and $\langle value \rangle$ as part of the processing.

Part XXI

The l3intarray package: fast global integer arrays

1 l3intarray documentation

For applications requiring heavy use of integers, this module provides arrays which can be accessed in constant time (contrast l3seq, where access time is linear). These arrays have several important features

- The size of the array is fixed and must be given at point of initialisation
- The absolute value of each entry has maximum $2^{30} - 1$ (*i.e.* one power lower than the usual `\c_max_int` ceiling of $2^{31} - 1$)

The use of `intarray` data is therefore recommended for cases where the need for fast access is of paramount importance.

<hr/> <code>\intarray_new:Nn</code> <hr/>	<code>\intarray_new:Nn <intarray var> {<size>}</code>
New: 2018-03-29	Evaluates the integer expression <code><size></code> and allocates an <i><integer array variable></i> with that number of (zero) entries. The variable name should start with <code>\g_</code> because assignments are always global.
<hr/> <code>\intarray_count:N *</code> <hr/>	<code>\intarray_count:N <intarray var></code>
New: 2018-03-29	Expands to the number of entries in the <i><integer array variable></i> . Contrarily to <code>\seq_count:N</code> this is performed in constant time.
<hr/> <code>\intarray_gset:Nnn</code> <hr/>	<code>\intarray_gset:Nnn <intarray var> {<position>} {<value>}</code>
New: 2018-03-29	Stores the result of evaluating the integer expression <code><value></code> into the <i><integer array variable></i> at the (integer expression) <code><position></code> . If the <code><position></code> is not between 1 and the <code>\intarray_count:N</code> , or the <code><value></code> 's absolute value is bigger than $2^{30} - 1$, an error occurs. Assignments are always global.
<hr/> <code>\intarray_gzero:N</code> <hr/>	<code>\intarray_gzero:N <intarray var></code>
New: 2018-05-04	Sets all entries of the <i><integer array variable></i> to zero. Assignments are always global.
<hr/> <code>\intarray_item:Nn *</code> <hr/>	<code>\intarray_item:Nn <intarray var> {<position>}</code>
New: 2018-03-29	Expands to the integer entry stored at the (integer expression) <code><position></code> in the <i><integer array variable></i> . If the <code><position></code> is not between 1 and the <code>\intarray_count:N</code> , an error occurs.
<hr/> <code>\intarray_rand_item:N *</code> <hr/>	<code>\intarray_rand_item:N <intarray var></code>
New: 2018-05-05	Selects a pseudo-random item of the <i><integer array></i> . If the <i><integer array></i> is empty, produce an error.

1.1 Implementation notes

It is a wrapper around the `\fontdimen` primitive, used to store arrays of integers (with a restricted range: absolute value at most $2^{30} - 1$). In contrast to `l3seq` sequences the access to individual entries is done in constant time rather than linear time, but only integers can be stored. More precisely, the primitive `\fontdimen` stores dimensions but the `l3intarray` package transparently converts these from/to integers. Assignments are always global.

While LuaTeX's memory is extensible, other engines can “only” deal with a bit less than 4×10^6 entries in all `\fontdimen` arrays combined (with default TeXLive settings).

Part XXII

The l3fp package: Floating points

A decimal floating point number is one which is stored as a significand and a separate exponent. The module implements expandably a wide set of arithmetic, trigonometric, and other operations on decimal floating point numbers, to be used within floating point expressions. Floating point expressions support the following operations with their usual precedence.

- Basic arithmetic: addition $x + y$, subtraction $x - y$, multiplication $x * y$, division x / y , square root \sqrt{x} , and parentheses.
- Comparison operators: $x < y$, $x \leq y$, $x > y$, $x \neq y$ etc.
- Boolean logic: sign $\text{sign } x$, negation $!x$, conjunction $x \&\& y$, disjunction $x || y$, ternary operator $x ? y : z$.
- Exponentials: $\exp x$, $\ln x$, x^y .
- Trigonometry: $\sin x$, $\cos x$, $\tan x$, $\cot x$, $\sec x$, $\csc x$ expecting their arguments in radians, and $\text{sind } x$, $\text{cosd } x$, $\text{tand } x$, $\text{cotd } x$, $\text{secd } x$, $\text{cscd } x$ expecting their arguments in degrees.
- Inverse trigonometric functions: $\text{asin } x$, $\text{acos } x$, $\text{atan } x$, $\text{acot } x$, $\text{asec } x$, $\text{acsc } x$ giving a result in radians, and $\text{asind } x$, $\text{acosd } x$, $\text{atand } x$, $\text{acotd } x$, $\text{asecd } x$, $\text{acscd } x$ giving a result in degrees.

(not yet) Hyperbolic functions and their inverse functions: $\sinh x$, $\cosh x$, $\tanh x$, $\coth x$, $\text{sech } x$, $\text{csch } x$, and $\text{asinh } x$, $\text{acosh } x$, $\text{atanh } x$, $\text{acoth } x$, $\text{asech } x$, $\text{acsch } x$.

- Extrema: $\max(x_1, x_2, \dots)$, $\min(x_1, x_2, \dots)$, $\text{abs}(x)$.
- Rounding functions, controlled by two optional values, n (number of places, 0 by default) and t (behavior on a tie, NaN by default):
 - $\text{trunc}(x, n)$ rounds towards zero,
 - $\text{floor}(x, n)$ rounds towards $-\infty$,
 - $\text{ceil}(x, n)$ rounds towards $+\infty$,
 - $\text{round}(x, n, t)$ rounds to the closest value, with ties rounded to an even value by default, towards zero if $t = 0$, towards $+\infty$ if $t > 0$ and towards $-\infty$ if $t < 0$.

And (not yet) modulo, and “quantize”.

- Random numbers: $\text{rand}()$, $\text{randint}(m, n)$.
- Constants: pi , deg (one degree in radians).
- Dimensions, automatically expressed in points, e.g., pc is 12.
- Automatic conversion (no need for $\backslash\langle\text{type}\rangle_use:N$) of integer, dimension, and skip variables to floating point numbers, expressing dimensions in points and ignoring the stretch and shrink components of skips.

- Tuples: (x_1, \dots, x_n) that can be stored in variables, added together, multiplied or divided by a floating point number, and nested.

Floating point numbers can be given either explicitly (in a form such as $1.234\text{e-}34$, or $-.0001$), or as a stored floating point variable, which is automatically replaced by its current value. A “floating point” is a floating point number or a tuple thereof. See section 9.1 for a description of what a floating point is, section 9.2 for details about how an expression is parsed, and section 9.3 to know what the various operations do. Some operations may raise exceptions (error messages), described in section 7.

An example of use could be the following.

`\LaTeX{} can now compute: $\frac{\sin(3.5)}{2} + 2 \cdot 10^{-3}$`
`= \ExplSyntaxOn \fp_to_decimal:n {\sin(3.5)/2 + 2e-3} $.`

The operation `round` can be used to limit the result’s precision. Adding `+0` avoids the possibly undesirable output `-0`, replacing it by `+0`. However, the `l3fp` module is mostly meant as an underlying tool for higher-level commands. For example, one could provide a function to typeset nicely the result of floating point computations.

```
\documentclass{article}
\usepackage{xparse, siunitx}
\ExplSyntaxOn
\NewDocumentCommand { \calcnun } { m }
{ \num { \fp_to_scientific:n {#1} } }
\ExplSyntaxOff
\begin{document}
\calcnun { 2 pi * sin ( 2.3 ^ 5 ) }
\end{document}
```

See the documentation of `siunitx` for various options of `\num`.

1 Creating and initialising floating point variables

<code>\fp_new:N</code> <code>\fp_new:c</code>	<code>\fp_new:N <fp var></code>
Updated: 2012-05-08	Creates a new <code><fp var></code> or raises an error if the name is already taken. The declaration is global. The <code><fp var></code> is initially <code>+0</code> .
<code>\fp_const:Nn</code> <code>\fp_const:cn</code>	<code>\fp_const:Nn <fp var> {<floating point expression>}</code>
Updated: 2012-05-08	Creates a new constant <code><fp var></code> or raises an error if the name is already taken. The <code><fp var></code> is set globally equal to the result of evaluating the <code><floating point expression></code> .
<code>\fp_zero:N</code> <code>\fp_zero:c</code> <code>\fp_gzero:N</code> <code>\fp_gzero:c</code>	<code>\fp_zero:N <fp var></code> Sets the <code><fp var></code> to <code>+0</code> .
Updated: 2012-05-08	

<code>\fp_zero_new:N</code>	<code>\fp_zero_new:N <fp var></code>
<code>\fp_zero_new:c</code>	
<code>\fp_gzero_new:N</code>	Ensures that the $\langle fp\ var \rangle$ exists globally by applying <code>\fp_new:N</code> if necessary, then applies
<code>\fp_gzero_new:c</code>	<code>\fp_(g)zero:N</code> to leave the $\langle fp\ var \rangle$ set to +0.
Updated: 2012-05-08	

2 Setting floating point variables

<code>\fp_set:Nn</code>	<code>\fp_set:Nn <fp var> {(floating point expression)}</code>
<code>\fp_set:cn</code>	
<code>\fp_gset:Nn</code>	Sets $\langle fp\ var \rangle$ equal to the result of computing the $\langle floating\ point\ expression \rangle$.
<code>\fp_gset:cn</code>	
Updated: 2012-05-08	

<code>\fp_set_eq:NN</code>	<code>\fp_set_eq:NN <fp var₁> <fp var₂></code>
<code>\fp_set_eq:(cN Nc cc)</code>	
<code>\fp_gset_eq:NN</code>	Sets the floating point variable $\langle fp\ var_1 \rangle$ equal to the current value of $\langle fp\ var_2 \rangle$.
<code>\fp_gset_eq:(cN Nc cc)</code>	
Updated: 2012-05-08	

<code>\fp_add:Nn</code>	<code>\fp_add:Nn <fp var> {(floating point expression)}</code>
<code>\fp_add:cn</code>	
<code>\fp_gadd:Nn</code>	Adds the result of computing the $\langle floating\ point\ expression \rangle$ to the $\langle fp\ var \rangle$. This also
<code>\fp_gadd:cn</code>	applies if $\langle fp\ var \rangle$ and $\langle floating\ point\ expression \rangle$ evaluate to tuples of the same size.
Updated: 2012-05-08	

<code>\fp_sub:Nn</code>	<code>\fp_sub:Nn <fp var> {(floating point expression)}</code>
<code>\fp_sub:cn</code>	
<code>\fp_gsub:Nn</code>	Subtracts the result of computing the $\langle floating\ point\ expression \rangle$ from the $\langle fp\ var \rangle$. This
<code>\fp_gsub:cn</code>	also applies if $\langle fp\ var \rangle$ and $\langle floating\ point\ expression \rangle$ evaluate to tuples of the same size.
Updated: 2012-05-08	

3 Using floating points

<code>\fp_eval:n</code> ★	<code>\fp_eval:n {(floating point expression)}</code>
New: 2012-05-08	
Updated: 2012-07-08	Evaluates the $\langle floating\ point\ expression \rangle$ and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. For a tuple, each item is converted using <code>\fp_eval:n</code> and they are combined as $(\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle)$ if $n > 1$ and $(\langle fp_1 \rangle,)$ or $()$ for fewer items. This function is identical to <code>\fp_to_decimal:n</code> .

<code>\fp_to_decimal:N</code>	★	<code>\fp_to_decimal:N <fp var></code>
<code>\fp_to_decimal:c</code>	★	<code>\fp_to_decimal:n {\floating point expression}</code>
<code>\fp_to_decimal:n</code>	★	Evaluates the <i><floating point expression></i> and expresses the result as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed, and integers are expressed without a decimal separator. The values $\pm\infty$ and NaN trigger an “invalid operation” exception. For a tuple, each item is converted using <code>\fp_to_decimal:n</code> and they are combined as $(\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle)$ if $n > 1$ and $(\langle fp_1 \rangle,)$ or $()$ for fewer items.

New: 2012-05-08
Updated: 2012-07-08

<code>\fp_to_dim:N</code>	★	<code>\fp_to_dim:N <fp var></code>
<code>\fp_to_dim:c</code>	★	<code>\fp_to_dim:n {\floating point expression}</code>
<code>\fp_to_dim:n</code>	★	Evaluates the <i><floating point expression></i> and expresses the result as a dimension (in pt) suitable for use in dimension expressions. The output is identical to <code>\fp_to_decimal:n</code> , with an additional trailing <code>pt</code> (both letter tokens). In particular, the result may be outside the range $[-2^{14} + 2^{-17}, 2^{14} - 2^{-17}]$ of valid T _E X dimensions, leading to overflow errors if used as a dimension. Tuples, as well as the values $\pm\infty$ and NaN, trigger an “invalid operation” exception.

Updated: 2016-03-22

<code>\fp_to_int:N</code>	★	<code>\fp_to_int:N <fp var></code>
<code>\fp_to_int:c</code>	★	<code>\fp_to_int:n {\floating point expression}</code>
<code>\fp_to_int:n</code>	★	Evaluates the <i><floating point expression></i> , and rounds the result to the closest integer, rounding exact ties to an even integer. The result may be outside the range $[-2^{31} + 1, 2^{31} - 1]$ of valid T _E X integers, leading to overflow errors if used in an integer expression. Tuples, as well as the values $\pm\infty$ and NaN, trigger an “invalid operation” exception.

Updated: 2012-07-08

<code>\fp_to_scientific:N</code>	★	<code>\fp_to_scientific:N <fp var></code>
<code>\fp_to_scientific:c</code>	★	<code>\fp_to_scientific:n {\floating point expression}</code>
<code>\fp_to_scientific:n</code>	★	Evaluates the <i><floating point expression></i> and expresses the result in scientific notation:

New: 2012-05-08
Updated: 2016-03-22

<optional -><digit> . <15 digits> e <optional sign> <exponent>

The leading *<digit>* is non-zero except in the case of ± 0 . The values $\pm\infty$ and NaN trigger an “invalid operation” exception. Normal category codes apply: thus the `e` is category code 11 (a letter). For a tuple, each item is converted using `\fp_to_scientific:n` and they are combined as $(\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle)$ if $n > 1$ and $(\langle fp_1 \rangle,)$ or $()$ for fewer items.

<code>\fp_to_tl:N</code>	★	<code>\fp_to_tl:N <fp var></code>
<code>\fp_to_tl:c</code>	★	<code>\fp_to_tl:n {\floating point expression}</code>
<code>\fp_to_tl:n</code>	★	Evaluates the <i><floating point expression></i> and expresses the result in (almost) the shortest possible form. Numbers in the ranges $(0, 10^{-3})$ and $[10^{16}, \infty)$ are expressed in scientific notation with trailing zeros trimmed and no decimal separator when there is a single significant digit (this differs from <code>\fp_to_scientific:n</code>). Numbers in the range $[10^{-3}, 10^{16})$ are expressed in a decimal notation without exponent, with trailing zeros trimmed, and no decimal separator for integer values (see <code>\fp_to_decimal:n</code>). Negative numbers start with <code>-</code> . The special values ± 0 , $\pm\infty$ and NaN are rendered as <code>0</code> , <code>-0</code> , <code>inf</code> , <code>-inf</code> , and <code>nan</code> respectively. Normal category codes apply and thus <code>inf</code> or <code>nan</code> , if produced, are made up of letters. For a tuple, each item is converted using <code>\fp_to_tl:n</code> and they are combined as $(\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle)$ if $n > 1$ and $(\langle fp_1 \rangle,)$ or $()$ for fewer items.

Updated: 2016-03-22

<hr/>	
<code>\fp_use:N</code> ★	<code>\fp_use:N <fp var></code>
<code>\fp_use:c</code> ★	
<hr/>	
Updated: 2012-07-08	Inserts the value of the <code><fp var></code> into the input stream as a decimal number with no exponent. Leading or trailing zeros may be inserted to compensate for the exponent. Non-significant trailing zeros are trimmed. Integers are expressed without a decimal separator. The values $\pm\infty$ and <code>NaN</code> trigger an “invalid operation” exception. For a tuple, each item is converted using <code>\fp_to_decimal:n</code> and they are combined as $(\langle fp_1 \rangle, \sqcup \langle fp_2 \rangle, \sqcup \dots \langle fp_n \rangle)$ if $n > 1$ and $(\langle fp_1 \rangle,)$ or $()$ for fewer items. This function is identical to <code>\fp_to_decimal:N</code> .
<hr/>	

4 Floating point conditionals

<hr/>	
<code>\fp_if_exist_p:N</code> ★	<code>\fp_if_exist_p:N <fp var></code>
<code>\fp_if_exist_p:c</code> ★	<code>\fp_if_exist:NTF <fp var> {<true code>} {<false code>}</code>
<code>\fp_if_exist:NTF</code> ★	
<code>\fp_if_exist:cTF</code> ★	Tests whether the <code><fp var></code> is currently defined. This does not check that the <code><fp var></code> really is a floating point variable.
<hr/>	
Updated: 2012-05-08	
<hr/>	

<hr/>	
<code>\fp_compare_p:nNn</code> ★	<code>\fp_compare_p:nNn {<fpexpr₁>} <relation> {<fpexpr₂>}</code>
<code>\fp_compare:nNnTF</code> ★	<code>\fp_compare:nNnTF {<fpexpr₁>} <relation> {<fpexpr₂>} {<true code>} {<false code>}</code>
<hr/>	
Updated: 2012-05-08	Compares the <code><fpexpr₁></code> and the <code><fpexpr₂></code> , and returns <code>true</code> if the <code><relation></code> is obeyed. Two floating points x and y may obey four mutually exclusive relations: $x < y$, $x = y$, $x > y$, or $x?y$ (“not ordered”). The last case occurs exactly if one or both operands is <code>NaN</code> or is a tuple, unless they are equal tuples. Note that a <code>NaN</code> is distinct from any value, even another <code>NaN</code> , hence $x = x$ is not true for a <code>NaN</code> . To test if a value is <code>NaN</code> , compare it to an arbitrary number with the “not ordered” relation.
<hr/>	

```

\fp_compare:nNnTF { <value> } ? { 0 }
{ } % <value> is nan
{ } % <value> is not nan

```

Tuples are equal if they have the same number of items and items compare equal (in particular there must be no `NaN`). At present any other comparison with tuples yields ? (not ordered). This is experimental.

<code>\fp_compare_p:n</code> ☆	<code>\fp_compare_p:n</code>
<code>\fp_compare:nTF</code> ☆	{
Updated: 2013-12-14	$\langle fpexpr_1 \rangle$ $\langle relation_1 \rangle$
	...
	$\langle fpexpr_N \rangle$ $\langle relation_N \rangle$
	$\langle fpexpr_{N+1} \rangle$
	}
	<code>\fp_compare:nTF</code>
	{
	$\langle fpexpr_1 \rangle$ $\langle relation_1 \rangle$
	...
	$\langle fpexpr_N \rangle$ $\langle relation_N \rangle$
	$\langle fpexpr_{N+1} \rangle$
	}
	{ $\langle true\ code \rangle$ } { $\langle false\ code \rangle$ }

Evaluates the $\langle floating\ point\ expressions \rangle$ as described for `\fp_eval:n` and compares consecutive result using the corresponding $\langle relation \rangle$, namely it compares $\langle intexpr_1 \rangle$ and $\langle intexpr_2 \rangle$ using the $\langle relation_1 \rangle$, then $\langle intexpr_2 \rangle$ and $\langle intexpr_3 \rangle$ using the $\langle relation_2 \rangle$, until finally comparing $\langle intexpr_N \rangle$ and $\langle intexpr_{N+1} \rangle$ using the $\langle relation_N \rangle$. The test yields **true** if all comparisons are **true**. Each $\langle floating\ point\ expression \rangle$ is evaluated only once. Contrarily to `\int_compare:nTF`, all $\langle floating\ point\ expressions \rangle$ are computed, even if one comparison is **false**. Two floating points x and y may obey four mutually exclusive relations: $x < y$, $x = y$, $x > y$, or $x?y$ (“not ordered”). The last case occurs exactly if one or both operands is NaN or is a tuple, unless they are equal tuples. Each $\langle relation \rangle$ can be any (non-empty) combination of $<$, $=$, $>$, and $?$, plus an optional leading $!$ (which negates the $\langle relation \rangle$), with the restriction that the $\langle relation \rangle$ may not start with $?$, as this symbol has a different meaning (in combination with $:$) within floating point expressions. The comparison $x \langle relation \rangle y$ is then **true** if the $\langle relation \rangle$ does not start with $!$ and the actual relation ($<$, $=$, $>$, or $?$) between x and y appears within the $\langle relation \rangle$, or on the contrary if the $\langle relation \rangle$ starts with $!$ and the relation between x and y does not appear within the $\langle relation \rangle$. Common choices of $\langle relation \rangle$ include \geq (greater or equal), \neq (not equal), $!?$ or \leq (comparable).

5 Floating point expression loops

<code>\fp_do_until:nNnn</code> ☆	<code>\fp_do_until:nNnn {$\langle fpexpr_1 \rangle$} $\langle relation \rangle$ {$\langle fpexpr_2 \rangle$} {$\langle code \rangle$}</code>
New: 2012-08-16	Places the $\langle code \rangle$ in the input stream for T _E X to process, and then evaluates the relationship between the two $\langle floating\ point\ expressions \rangle$ as described for <code>\fp_compare:nNnTF</code> . If the test is false then the $\langle code \rangle$ is inserted into the input stream again and a loop occurs until the $\langle relation \rangle$ is true .
<code>\fp_do_while:nNnn</code> ☆	<code>\fp_do_while:nNnn {$\langle fpexpr_1 \rangle$} $\langle relation \rangle$ {$\langle fpexpr_2 \rangle$} {$\langle code \rangle$}</code>
New: 2012-08-16	Places the $\langle code \rangle$ in the input stream for T _E X to process, and then evaluates the relationship between the two $\langle floating\ point\ expressions \rangle$ as described for <code>\fp_compare:nNnTF</code> . If the test is true then the $\langle code \rangle$ is inserted into the input stream again and a loop occurs until the $\langle relation \rangle$ is false .

<hr/> <code>\fp_until_do:nNnn</code> ☆ <hr/>	<code>\fp_until_do:nNnn {<fpexpr1>} <relation> {<fpexpr2>} {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\fp_while_do:nNnn</code> ☆ <hr/>	<code>\fp_while_do:nNnn {<fpexpr1>} <relation> {<fpexpr2>} {<code>}</code>
New: 2012-08-16	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nNnTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .
<hr/> <code>\fp_do_until:nn</code> ☆ <hr/>	<code>\fp_do_until:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is false then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is true .
<hr/> <code>\fp_do_while:nn</code> ☆ <hr/>	<code>\fp_do_while:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Places the <i><code></i> in the input stream for T _E X to process, and then evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> . If the test is true then the <i><code></i> is inserted into the input stream again and a loop occurs until the <i><relation></i> is false .
<hr/> <code>\fp_until_do:nn</code> ☆ <hr/>	<code>\fp_until_do:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is false . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is true .
<hr/> <code>\fp_while_do:nn</code> ☆ <hr/>	<code>\fp_while_do:nn { <fpexpr1> <relation> <fpexpr2> } {<code>}</code>
New: 2012-08-16 Updated: 2013-12-14	Evaluates the relationship between the two <i><floating point expressions></i> as described for <code>\fp_compare:nTF</code> , and then places the <i><code></i> in the input stream if the <i><relation></i> is true . After the <i><code></i> has been processed by T _E X the test is repeated, and a loop occurs until the test is false .

`\fp_step_function:nnnN` ☆
`\fp_step_function:nnnc` ☆

New: 2016-11-21
Updated: 2016-12-06

`\fp_step_function:nnnN` { $\langle initial\ value \rangle$ } { $\langle step \rangle$ } { $\langle final\ value \rangle$ } $\langle function \rangle$

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, each of which should be a floating point expression evaluating to a floating point number, not a tuple. The $\langle function \rangle$ is then placed in front of each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$). The $\langle step \rangle$ must be non-zero. If the $\langle step \rangle$ is positive, the loop stops when the $\langle value \rangle$ becomes larger than the $\langle final\ value \rangle$. If the $\langle step \rangle$ is negative, the loop stops when the $\langle value \rangle$ becomes smaller than the $\langle final\ value \rangle$. The $\langle function \rangle$ should absorb one numerical argument. For example

```
\cs_set:Npn \my_func:n #1 { [I~saw~#1] \quad }
\fp_step_function:nnnN { 1.0 } { 0.1 } { 1.5 } \my_func:n
```

would print

```
[I saw 1.0]   [I saw 1.1]   [I saw 1.2]   [I saw 1.3]   [I saw 1.4]   [I saw 1.5]
```

TpXhackers note: Due to rounding, it may happen that adding the $\langle step \rangle$ to the $\langle value \rangle$ does not change the $\langle value \rangle$; such cases give an error, as they would otherwise lead to an infinite loop.

`\fp_step_inline:nnnn`

New: 2016-11-21
Updated: 2016-12-06

`\fp_step_inline:nnnn` { $\langle initial\ value \rangle$ } { $\langle step \rangle$ } { $\langle final\ value \rangle$ } { $\langle code \rangle$ }

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be floating point expressions evaluating to a floating point number, not a tuple. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream with `#1` replaced by the current $\langle value \rangle$. Thus the $\langle code \rangle$ should define a function of one argument (`#1`).

`\fp_step_variable:nnnNn`

New: 2017-04-12

`\fp_step_variable:nnnNn`
{ $\langle initial\ value \rangle$ } { $\langle step \rangle$ } { $\langle final\ value \rangle$ } $\langle tl\ var \rangle$ { $\langle code \rangle$ }

This function first evaluates the $\langle initial\ value \rangle$, $\langle step \rangle$ and $\langle final\ value \rangle$, all of which should be floating point expressions evaluating to a floating point number, not a tuple. Then for each $\langle value \rangle$ from the $\langle initial\ value \rangle$ to the $\langle final\ value \rangle$ in turn (using $\langle step \rangle$ between each $\langle value \rangle$), the $\langle code \rangle$ is inserted into the input stream, with the $\langle tl\ var \rangle$ defined as the current $\langle value \rangle$. Thus the $\langle code \rangle$ should make use of the $\langle tl\ var \rangle$.

6 Some useful constants, and scratch variables

`\c_zero_fp`
`\c_minus_zero_fp`

New: 2012-05-08

Zero, with either sign.

`\c_one_fp`

New: 2012-05-08

One as an fp: useful for comparisons in some places.

<hr/> <code>\c_inf_fp</code> <code>\c_minus_inf_fp</code> <hr/>	Infinity, with either sign. These can be input directly in a floating point expression as <code>inf</code> and <code>-inf</code> .
<hr/> New: 2012-05-08 <hr/>	
<hr/> <code>\c_e_fp</code> <hr/>	The value of the base of the natural logarithm, $e = \exp(1)$.
<hr/> Updated: 2012-05-08 <hr/>	
<hr/> <code>\c_pi_fp</code> <hr/>	The value of π . This can be input directly in a floating point expression as <code>pi</code> .
<hr/> Updated: 2013-11-17 <hr/>	
<hr/> <code>\c_one_degree_fp</code> <hr/>	The value of 1° in radians. Multiply an angle given in degrees by this value to obtain a result in radians. Note that trigonometric functions expecting an argument in radians or in degrees are both available. Within floating point expressions, this can be accessed as <code>deg</code> .
<hr/> New: 2012-05-08 Updated: 2013-11-17 <hr/>	
<hr/> <code>\l_tmpa_fp</code> <code>\l_tmpb_fp</code> <hr/>	Scratch floating points for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<hr/> <code>\g_tmpa_fp</code> <code>\g_tmpb_fp</code> <hr/>	Scratch floating points for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

7 Floating point exceptions

The functions defined in this section are experimental, and their functionality may be altered or removed altogether.

“Exceptions” may occur when performing some floating point operations, such as `0 / 0`, or `10 ** 1e9999`. The relevant IEEE standard defines 5 types of exceptions, of which we implement 4.

- *Overflow* occurs whenever the result of an operation is too large to be represented as a normal floating point number. This results in $\pm\infty$.
- *Underflow* occurs whenever the result of an operation is too close to 0 to be represented as a normal floating point number. This results in ± 0 .
- *Invalid operation* occurs for operations with no defined outcome, for instance `0/0` or `sin(∞)`, and results in a NaN. It also occurs for conversion functions whose target type does not have the appropriate infinite or NaN value (*e.g.*, `\fp_to_dim:n`).
- *Division by zero* occurs when dividing a non-zero number by 0, or when evaluating functions at poles, *e.g.*, `ln(0)` or `cot(0)`. This results in $\pm\infty$.

(*not yet*) *Inexact* occurs whenever the result of a computation is not exact, in other words, almost always. At the moment, this exception is entirely ignored in L^AT_EX3.

To each exception we associate a “flag”: `fp_overflow`, `fp_underflow`, `fp_invalid_operation` and `fp_division_by_zero`. The state of these flags can be tested and modified with commands from `l3flag`

By default, the “invalid operation” exception triggers an (expandable) error, and raises the corresponding flag. Other exceptions raise the corresponding flag but do not trigger an error. The behaviour when an exception occurs can be modified (using `\fp_trap:nn`) to either produce an error and raise the flag, or only raise the flag, or do nothing at all.

<code>\fp_trap:nn</code>	<code>\fp_trap:nn {<exception>} {<trap type>}</code>
New: 2012-07-19 Updated: 2017-02-13	All occurrences of the <i><exception></i> (<code>overflow</code> , <code>underflow</code> , <code>invalid_operation</code> or <code>division_by_zero</code>) within the current group are treated as <i><trap type></i> , which can be

- **none**: the *<exception>* will be entirely ignored, and leave no trace;
- **flag**: the *<exception>* will turn the corresponding flag on when it occurs;
- **error**: additionally, the *<exception>* will halt the T_EX run and display some information about the current operation in the terminal.

This function is experimental, and may be altered or removed.

```
flag_fp_overflow
flag_fp_underflow
flag_fp_invalid_operation
flag_fp_division_by_zero
```

Flags denoting the occurrence of various floating-point exceptions.

8 Viewing floating points

<code>\fp_show:N</code>	<code>\fp_show:N <fp var></code>
<code>\fp_show:c</code>	<code>\fp_show:n {<floating point expression>}</code>
<code>\fp_show:n</code>	Evaluates the <i><floating point expression></i> and displays the result in the terminal.
New: 2012-05-08 Updated: 2015-08-07	

<code>\fp_log:N</code>	<code>\fp_log:N <fp var></code>
<code>\fp_log:c</code>	<code>\fp_log:n {<floating point expression>}</code>
<code>\fp_log:n</code>	Evaluates the <i><floating point expression></i> and writes the result in the log file.
New: 2014-08-22 Updated: 2015-08-07	

9 Floating point expressions

9.1 Input of floating point numbers

We support four types of floating point numbers:

- $\pm m \cdot 10^n$, a floating point number, with integer $1 \leq m \leq 10^{16}$, and $-10000 \leq n \leq 10000$;

- ± 0 , zero, with a given sign;
- $\pm \infty$, infinity, with a given sign;
- NaN, is “not a number”, and can be either quiet or signalling (*not yet*: this distinction is currently unsupported);

Normal floating point numbers are stored in base 10, with up to 16 significant figures.

On input, a normal floating point number consists of:

- $\langle sign \rangle$: a possibly empty string of + and - characters;
- $\langle significand \rangle$: a non-empty string of digits together with zero or one dot;
- $\langle exponent \rangle$ optionally: the character **e**, followed by a possibly empty string of + and - tokens, and a non-empty string of digits.

The sign of the resulting number is + if $\langle sign \rangle$ contains an even number of -, and - otherwise, hence, an empty $\langle sign \rangle$ denotes a non-negative input. The stored significand is obtained from $\langle significand \rangle$ by omitting the decimal separator and leading zeros, and rounding to 16 significant digits, filling with trailing zeros if necessary. In particular, the value stored is exact if the input $\langle significand \rangle$ has at most 16 digits. The stored $\langle exponent \rangle$ is obtained by combining the input $\langle exponent \rangle$ (0 if absent) with a shift depending on the position of the significand and the number of leading zeros.

A special case arises if the resulting $\langle exponent \rangle$ is either too large or too small for the floating point number to be represented. This results either in an overflow (the number is then replaced by $\pm \infty$), or an underflow (resulting in ± 0).

The result is thus ± 0 if and only if $\langle significand \rangle$ contains no non-zero digit (*i.e.*, consists only in characters 0, and an optional period), or if there is an underflow. Note that a single dot is currently a valid floating point number, equal to +0, but that is not guaranteed to remain true.

The $\langle significand \rangle$ must be non-empty, so **e1** and **e-1** are not valid floating point numbers. Note that the latter could be mistaken with the difference of “e” and 1. To avoid confusions, the base of natural logarithms cannot be input as **e** and should be input as **exp(1)** or **\c_e_fp**.

Special numbers are input as follows:

- **inf** represents $+\infty$, and can be preceded by any $\langle sign \rangle$, yielding $\pm \infty$ as appropriate.
- **nan** represents a (quiet) non-number. It can be preceded by any sign, but that sign is ignored.
- Any unrecognizable string triggers an error, and produces a NaN.
- Note that commands such as **\infty**, **\pi**, or **\sin** *do not* work in floating point expressions. They may silently be interpreted as completely unexpected numbers, because integer constants (allowed in expressions) are commonly stored as mathematical characters.

9.2 Precedence of operators

We list here all the operations supported in floating point expressions, in order of decreasing precedence: operations listed earlier bind more tightly than operations listed below them.

- Function calls (`sin`, `ln`, *etc*).
- Binary `**` and `^` (right associative).
- Unary `+`, `-`, `!`.
- Binary `*`, `/`, and implicit multiplication by juxtaposition (`2pi`, `3(4+5)`, *etc*).
- Binary `+` and `-`.
- Comparisons `>=`, `!=`, `<?`, *etc*.
- Logical `and`, denoted by `&&`.
- Logical `or`, denoted by `||`.
- Ternary operator `?:` (right associative).
- Comma (to build tuples).

The precedence of operations can be overridden using parentheses. In particular, those precedences imply that

$$\begin{aligned}\text{sin2pi} &= \sin(2)\pi! = 0, \\ 2^{\text{2max}(3,5)} &= 2^2 \max(3,5) = 20.\end{aligned}$$

Functions are called on the value of their argument, contrarily to `TeX` macros.

9.3 Operations

We now present the various operations allowed in floating point expressions, from the lowest precedence to the highest. When used as a truth value, a floating point expression is `false` if it is ± 0 , and `true` otherwise, including when it is `NaN` or a tuple such as `(0,0)`. Tuples are only supported to some extent by operations that work with truth values (`?:`, `||`, `&&`, `!`), by comparisons (`!<=>?`), and by `+`, `-`, `*`, `/`. Unless otherwise specified, providing a tuple as an argument of any other operation yields the “invalid operation” exception and a `NaN` result.

```
?: \fp_eval:n { <operand1> ? <operand2> : <operand3> }
```

The ternary operator `?:` results in $\langle operand_2 \rangle$ if $\langle operand_1 \rangle$ is true (not ± 0), and $\langle operand_3 \rangle$ if $\langle operand_1 \rangle$ is false (± 0). All three $\langle operands \rangle$ are evaluated in all cases; they may be tuples. The operator is right associative, hence

```
\fp_eval:n
{
  1 + 3 > 4 ? 1 :
  2 + 4 > 5 ? 2 :
  3 + 5 > 6 ? 3 : 4
}
```

first tests whether $1 + 3 > 4$; since this isn't true, the branch following `:` is taken, and $2 + 4 > 5$ is compared; since this is true, the branch before `:` is taken, and everything else is (evaluated then) ignored. That allows testing for various cases in a concise manner, with the drawback that all computations are made in all cases.

```
|| \fp_eval:n { <operand1> || <operand2> }
```

If $\langle operand_1 \rangle$ is true (not ± 0), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases; they may be tuples. In $\langle operand_1 \rangle || \langle operand_2 \rangle || \dots || \langle operand_n \rangle$, the first true (nonzero) $\langle operand \rangle$ is used and if all are zero the last one (± 0) is used.

```
&& \fp_eval:n { <operand1> && <operand2> }
```

If $\langle operand_1 \rangle$ is false (equal to ± 0), use that value, otherwise the value of $\langle operand_2 \rangle$. Both $\langle operands \rangle$ are evaluated in all cases; they may be tuples. In $\langle operand_1 \rangle \&\& \langle operand_2 \rangle \&\& \dots \&\& \langle operand_n \rangle$, the first false (± 0) $\langle operand \rangle$ is used and if none is zero the last one is used.

```
< \fp_eval:n
= {
>   <operand1> <relation1>
?   ...
Updated: 2013-12-14   <operand_N> <relation_N>
                      <operand_{N+1}>
                      }
```

Each $\langle relation \rangle$ consists of a non-empty string of `<`, `=`, `>`, and `?`, optionally preceded by `!`, and may not start with `?`. This evaluates to $+1$ if all comparisons $\langle operand_i \rangle \langle relation_i \rangle \langle operand_{i+1} \rangle$ are true, and $+0$ otherwise. All $\langle operands \rangle$ are evaluated (once) in all cases. See `\fp_compare:nTF` for details.

```
+ \fp_eval:n { <operand1> + <operand2> }
- \fp_eval:n { <operand1> - <operand2> }
```

Computes the sum or the difference of its two $\langle operands \rangle$. The “invalid operation” exception occurs for $\infty - \infty$. “Underflow” and “overflow” occur when appropriate. These operations supports the itemwise addition or subtraction of two tuples, but if they have a different number of items the “invalid operation” exception occurs and the result is NaN.

```

* \fp_eval:n { <operand1> * <operand2> }
/ \fp_eval:n { <operand1> / <operand2> }

```

Computes the product or the ratio of its two $\langle \text{operands} \rangle$. The “invalid operation” exception occurs for ∞/∞ , $0/0$, or $0 * \infty$. “Division by zero” occurs when dividing a finite non-zero number by ± 0 . “Underflow” and “overflow” occur when appropriate. When $\langle \text{operand}_1 \rangle$ is a tuple and $\langle \text{operand}_2 \rangle$ is a floating point number, each item of $\langle \text{operand}_1 \rangle$ is multiplied or divided by $\langle \text{operand}_2 \rangle$. Multiplication also supports the case where $\langle \text{operand}_1 \rangle$ is a floating point number and $\langle \text{operand}_2 \rangle$ a tuple. Other combinations yield an “invalid operation” exception and a NaN result.

```

+ \fp_eval:n { + <operand> }
- \fp_eval:n { - <operand> }
! \fp_eval:n { ! <operand> }

```

The unary $+$ does nothing, the unary $-$ changes the sign of the $\langle \text{operand} \rangle$ (for a tuple, of all its components), and $!$ $\langle \text{operand} \rangle$ evaluates to 1 if $\langle \text{operand} \rangle$ is false (is ± 0) and 0 otherwise (this is the `not` boolean function). Those operations never raise exceptions.

```

** \fp_eval:n { <operand1> ** <operand2> }
^ \fp_eval:n { <operand1> ^ <operand2> }

```

Raises $\langle \text{operand}_1 \rangle$ to the power $\langle \text{operand}_2 \rangle$. This operation is right associative, hence $2 ** 2 ** 3$ equals $2^{2^3} = 256$. If $\langle \text{operand}_1 \rangle$ is negative or -0 then: the result’s sign is $+$ if the $\langle \text{operand}_2 \rangle$ is infinite and $(-1)^p$ if the $\langle \text{operand}_2 \rangle$ is $p/5^q$ with p, q integers; the result is $+0$ if $\text{abs}(\langle \text{operand}_1 \rangle)^{\langle \text{operand}_2 \rangle}$ evaluates to zero; in other cases the “invalid operation” exception occurs because the sign cannot be determined. “Division by zero” occurs when raising ± 0 to a finite strictly negative power. “Underflow” and “overflow” occur when appropriate. If either operand is a tuple, “invalid operation” occurs.

```

abs \fp_eval:n { abs( <fpexpr> ) }

```

Computes the absolute value of the $\langle \text{fpexpr} \rangle$. If the operand is a tuple, “invalid operation” occurs. This operation does not raise exceptions in other cases. See also `\fp_abs:n`.

```

exp \fp_eval:n { exp( <fpexpr> ) }

```

Computes the exponential of the $\langle \text{fpexpr} \rangle$. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

```

ln \fp_eval:n { ln( <fpexpr> ) }

```

Computes the natural logarithm of the $\langle \text{fpexpr} \rangle$. Negative numbers have no (real) logarithm, hence the “invalid operation” is raised in that case, including for $\ln(-0)$. “Division by zero” occurs when evaluating $\ln(+0) = -\infty$. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

```

max \fp_eval:n { max( <fpexpr1> , <fpexpr2> , ... ) }
min \fp_eval:n { min( <fpexpr1> , <fpexpr2> , ... ) }

```

Evaluates each $\langle \text{fpexpr} \rangle$ and computes the largest (smallest) of those. If any of the $\langle \text{fpexpr} \rangle$ is a NaN or tuple, the result is NaN. If any operand is a tuple, “invalid operation” occurs; these operations do not raise exceptions in other cases.

<code>round</code>	<code>\fp_eval:n { round (<fpexpr>) }</code>
<code>trunc</code>	<code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂>) }</code>
<code>ceil</code>	<code>\fp_eval:n { round (<fpexpr₁> , <fpexpr₂> , <fpexpr₃>) }</code>
<code>floor</code>	

New: 2013-12-14
Updated: 2015-08-08

Only `round` accepts a third argument. Evaluates $\langle fpexpr_1 \rangle = x$ and $\langle fpexpr_2 \rangle = n$ and $\langle fpexpr_3 \rangle = t$ then rounds x to n places. If n is an integer, this rounds x to a multiple of 10^{-n} ; if $n = +\infty$, this always yields x ; if $n = -\infty$, this yields one of ± 0 , $\pm\infty$, or NaN; if n is neither $\pm\infty$ nor an integer, then an “invalid operation” exception is raised. When $\langle fpexpr_2 \rangle$ is omitted, $n = 0$, *i.e.*, $\langle fpexpr_1 \rangle$ is rounded to an integer. The rounding direction depends on the function.

- `round` yields the multiple of 10^{-n} closest to x , with ties (x half-way between two such multiples) rounded as follows. If t is `nan` or not given the even multiple is chosen (“ties to even”), if $t = \pm 0$ the multiple closest to 0 is chosen (“ties to zero”), if t is positive/negative the multiple closest to $\infty/-\infty$ is chosen (“ties towards positive/negative infinity”).
- `floor` yields the largest multiple of 10^{-n} smaller or equal to x (“round towards negative infinity”);
- `ceil` yields the smallest multiple of 10^{-n} greater or equal to x (“round towards positive infinity”);
- `trunc` yields a multiple of 10^{-n} with the same sign as x and with the largest absolute value less than that of x (“round towards zero”).

“Overflow” occurs if x is finite and the result is infinite (this can only happen if $\langle fpexpr_2 \rangle < -9984$). If any operand is a tuple, “invalid operation” occurs.

<code>sign</code>	<code>\fp_eval:n { sign(<fpexpr>) }</code>
-------------------	--

Evaluates the $\langle fpexpr \rangle$ and determines its sign: +1 for positive numbers and for $+\infty$, -1 for negative numbers and for $-\infty$, ± 0 for ± 0 , and NaN for NaN. If the operand is a tuple, “invalid operation” occurs. This operation does not raise exceptions in other cases.

<code>sin</code>	<code>\fp_eval:n { sin(<fpexpr>) }</code>
<code>cos</code>	<code>\fp_eval:n { cos(<fpexpr>) }</code>
<code>tan</code>	<code>\fp_eval:n { tan(<fpexpr>) }</code>
<code>cot</code>	<code>\fp_eval:n { cot(<fpexpr>) }</code>
<code>csc</code>	<code>\fp_eval:n { csc(<fpexpr>) }</code>
<code>sec</code>	<code>\fp_eval:n { sec(<fpexpr>) }</code>

Updated: 2013-11-17

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in radians. For arguments given in degrees, see `sind`, `cosd`, *etc.* Note that since π is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<code>sind</code>	<code>\fp_eval:n { sind(<fpexpr>) }</code>
<code>cosd</code>	<code>\fp_eval:n { cosd(<fpexpr>) }</code>
<code>tand</code>	<code>\fp_eval:n { tand(<fpexpr>) }</code>
<code>cotd</code>	<code>\fp_eval:n { cotd(<fpexpr>) }</code>
<code>cscd</code>	<code>\fp_eval:n { cscd(<fpexpr>) }</code>
<code>secd</code>	<code>\fp_eval:n { secd(<fpexpr>) }</code>

New: 2013-11-02

Computes the sine, cosine, tangent, cotangent, cosecant, or secant of the $\langle fpexpr \rangle$ given in degrees. For arguments given in radians, see `sin`, `cos`, *etc.* Note that since π is irrational, `sin(8pi)` is not quite zero, while its analogue `sind(8 × 180)` is exactly zero. The trigonometric functions are undefined for an argument of $\pm\infty$, leading to the “invalid operation” exception. Additionally, evaluating tangent, cotangent, cosecant, or secant at one of their poles leads to a “division by zero” exception. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<code>asin</code>	<code>\fp_eval:n { asin(<fpexpr>) }</code>
<code>acos</code>	<code>\fp_eval:n { acos(<fpexpr>) }</code>
<code>acsc</code>	<code>\fp_eval:n { acsc(<fpexpr>) }</code>
<code>asec</code>	<code>\fp_eval:n { asec(<fpexpr>) }</code>

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in radians, in the range $[-\pi/2, \pi/2]$ for `asin` and `acsc` and $[0, \pi]$ for `acos` and `asec`. For a result in degrees, use `asind`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

<code>asind</code>	<code>\fp_eval:n { asind(<fpexpr>) }</code>
<code>acosd</code>	<code>\fp_eval:n { acosd(<fpexpr>) }</code>
<code>acscd</code>	<code>\fp_eval:n { acscd(<fpexpr>) }</code>
<code>asecd</code>	<code>\fp_eval:n { asecd(<fpexpr>) }</code>

New: 2013-11-02

Computes the arcsine, arccosine, arccosecant, or arcsecant of the $\langle fpexpr \rangle$ and returns the result in degrees, in the range $[-90, 90]$ for `asin` and `acsc` and $[0, 180]$ for `acos` and `asec`. For a result in radians, use `asin`, *etc.* If the argument of `asin` or `acos` lies outside the range $[-1, 1]$, or the argument of `acsc` or `asec` inside the range $(-1, 1)$, an “invalid operation” exception is raised. “Underflow” and “overflow” occur when appropriate. If the operand is a tuple, “invalid operation” occurs.

atan	<code>\fp_eval:n { atan(<fpexpr>) }</code>
acot	<code>\fp_eval:n { atan(<fpexpr₁> , <fpexpr₂>) }</code>
	<code>\fp_eval:n { acot(<fpexpr>) }</code>
New: 2013-11-02	<code>\fp_eval:n { acot(<fpexpr₁> , <fpexpr₂>) }</code>

Those functions yield an angle in radians: **atand** and **acotd** are their analogs in degrees. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-\pi/2, \pi/2]$, and arccotangent in the range $[0, \pi]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by π . Both two-argument functions take values in the wider range $[-\pi, \pi]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm\pi/4, \pm 3\pi/4\}$ depending on signs. The “underflow” exception can occur. If any operand is a tuple, “invalid operation” occurs.

atand	<code>\fp_eval:n { atand(<fpexpr>) }</code>
acotd	<code>\fp_eval:n { atand(<fpexpr₁> , <fpexpr₂>) }</code>
	<code>\fp_eval:n { acotd(<fpexpr>) }</code>
New: 2013-11-02	<code>\fp_eval:n { acotd(<fpexpr₁> , <fpexpr₂>) }</code>

Those functions yield an angle in degrees: **atand** and **acotd** are their analogs in radians. The one-argument versions compute the arctangent or arccotangent of the $\langle fpexpr \rangle$: arctangent takes values in the range $[-90, 90]$, and arccotangent in the range $[0, 180]$. The two-argument arctangent computes the angle in polar coordinates of the point with Cartesian coordinates $(\langle fpexpr_2 \rangle, \langle fpexpr_1 \rangle)$: this is the arctangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180 depending on the signs of $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$. The two-argument arccotangent computes the angle in polar coordinates of the point $(\langle fpexpr_1 \rangle, \langle fpexpr_2 \rangle)$, equal to the arccotangent of $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$, possibly shifted by 180. Both two-argument functions take values in the wider range $[-180, 180]$. The ratio $\langle fpexpr_1 \rangle / \langle fpexpr_2 \rangle$ need not be defined for the two-argument arctangent: when both expressions yield ± 0 , or when both yield $\pm \infty$, the resulting angle is one of $\{\pm 45, \pm 135\}$ depending on signs. The “underflow” exception can occur. If any operand is a tuple, “invalid operation” occurs.

sqrt	<code>\fp_eval:n { sqrt(<fpexpr>) }</code>
-------------	--

New: 2013-12-14 Computes the square root of the $\langle fpexpr \rangle$. The “invalid operation” is raised when the $\langle fpexpr \rangle$ is negative or is a tuple; no other exception can occur. Special values yield $\sqrt{-0} = -0$, $\sqrt{+0} = +0$, $\sqrt{+\infty} = +\infty$ and $\sqrt{\text{NaN}} = \text{NaN}$.

<hr/> rand <hr/>	<code>\fp_eval:n { rand() }</code>
<hr/> New: 2016-12-05 <hr/>	Produces a pseudo-random floating-point number (multiple of 10^{-16}) between 0 included and 1 excluded. This is not available in older versions of \TeX . The random seed can be queried using <code>\sys_rand_seed:</code> and set using <code>\sys_gset_rand_seed:n</code> .

\TeX hackers note: This is based on pseudo-random numbers provided by the engine’s primitive `\pdfuniformdeviate` in \pdfTeX , \pTeX , \upTeX and `\uniformdeviate` in \LuaTeX and \XeTeX . The underlying code is based on Metapost, which follows an additive scheme recommended in Section 3.6 of “The Art of Computer Programming, Volume 2”.

While we are more careful than `\uniformdeviate` to preserve uniformity of the underlying stream of 28-bit pseudo-random integers, these pseudo-random numbers should of course not be relied upon for serious numerical computations nor cryptography.

<hr/> randint <hr/>	<code>\fp_eval:n { randint(<fpexpr>) }</code>
<hr/> New: 2016-12-05 <hr/>	<code>\fp_eval:n { randint(<fpexpr₁₂</code>
	Produces a pseudo-random integer between 1 and $\langle fpexpr \rangle$ or between $\langle fpexpr_1 \rangle$ and $\langle fpexpr_2 \rangle$ inclusive. The bounds must be integers in the range $(-10^{16}, 10^{16})$ and the first must be smaller or equal to the second. See rand for important comments on how these pseudo-random numbers are generated.

<hr/> inf nan <hr/>	The special values $+\infty$, $-\infty$, and NaN are represented as <code>inf</code> , <code>-inf</code> and <code>nan</code> (see <code>\c_minus_inf_fp</code> , <code>\c_minus_inf_fp</code> and <code>\c_nan_fp</code>).
--------------------------------------	--

<hr/> pi <hr/>	The value of π (see <code>\c_pi_fp</code>).
-----------------------	--

<hr/> deg <hr/>	The value of 1° in radians (see <code>\c_one_degree_fp</code>).
------------------------	---

<hr/> em ex in pt pc cm mm dd cc nd nc bp sp <hr/>	Those units of measurement are equal to their values in pt , namely <div style="margin-left: 100px;"> $1\text{in} = 72.27\text{pt}$ $1\text{pt} = 1\text{pt}$ $1\text{pc} = 12\text{pt}$ $1\text{cm} = \frac{1}{2.54}\text{in} = 28.45275590551181\text{pt}$ $1\text{mm} = \frac{1}{25.4}\text{in} = 2.845275590551181\text{pt}$ $1\text{dd} = 0.376065\text{mm} = 1.07000856496063\text{pt}$ $1\text{cc} = 12\text{dd} = 12.84010277952756\text{pt}$ $1\text{nd} = 0.375\text{mm} = 1.066978346456693\text{pt}$ $1\text{nc} = 12\text{nd} = 12.80374015748031\text{pt}$ $1\text{bp} = \frac{1}{72}\text{in} = 1.00375\text{pt}$ $1\text{sp} = 2^{-16}\text{pt} = 1.52587890625e - 5\text{pt}.$ </div>
---	--

The values of the (font-dependent) units **em** and **ex** are gathered from \TeX when the surrounding floating point expression is evaluated.

<hr/> true false <hr/>	Other names for 1 and +0.
<hr/> \fp_abs:n ★ <small>New: 2012-05-14 Updated: 2012-07-08</small> <hr/>	\fp_abs:n { <i>floating point expression</i> } Evaluates the <i>floating point expression</i> as described for \fp_eval:n and leaves the absolute value of the result in the input stream. If the argument is a tuple, “invalid operation” occurs, but no other case raises exceptions. Within floating point expressions, abs() can be used.
<hr/> \fp_max:nn ★ \fp_min:nn ★ <small>New: 2012-09-26</small> <hr/>	\fp_max:nn { <i>fp expression 1</i> } { <i>fp expression 2</i> } Evaluates the <i>floating point expressions</i> as described for \fp_eval:n and leaves the resulting larger (max) or smaller (min) value in the input stream. If the argument is a tuple, “invalid operation” occurs, but no other case raises exceptions. Within floating point expressions, max() and min() can be used.

10 Disclaimer and roadmap

The package may break down if the escape character is among 0123456789_+, or if it receives a \TeX primitive conditional affected by **\exp_not:N**.

The following need to be done. I'll try to time-order the items.

- Function to count items in a tuple (and to determine if something is a tuple).
- Decide what exponent range to consider.
- Support signalling **nan**.
- Modulo and remainder, and rounding function **quantize** (and its friends analogous to **trunc**, **ceil**, **floor**).
- **\fp_format:nn** {*fpexpr*} {*format*}, but what should *format* be? More general pretty printing?
- Add **and**, **or**, **xor**? Perhaps under the names **all**, **any**, and **xor**?
- Add $\log(x, b)$ for logarithm of x in base b .
- **hypot** (Euclidean length). Cartesian-to-polar transform.
- Hyperbolic functions **cosh**, **sinh**, **tanh**.
- Inverse hyperbolics.
- Base conversion, input such as **0xAB.CDEF**.
- Factorial (not with **!**), gamma function.
- Improve coefficients of the **sin** and **tan** series.
- Treat upper and lower case letters identically in identifiers, and ignore underscores.
- Add an **array(1,2,3)** and **i=complex(0,1)**.

- Provide an experimental `map` function? Perhaps easier to implement if it is a single character, `@sin(1,2)?`
- Provide `\fp_if_nan:nTF`, and an `isnan` function?
- Support keyword arguments?

`Pgfmath` also provides box-measurements (depth, height, width), but boxes are not possible expandably.

Bugs, and tests to add.

- Check that functions are monotonic when they should.
- Add exceptions to `?:`, `!<=>?`, `&&`, `||`, and `!`.
- Logarithms of numbers very close to 1 are inaccurate.
- When rounding towards $-\infty$, `\dim_to_fp:n {0pt}` should return -0 , not $+0$.
- The result of $(\pm 0) + (\pm 0)$, of $x + (-x)$, and of $(-x) + x$ should depend on the rounding mode.
- `0e9999999999` gives a T_EX “number too large” error.
- Subnormals are not implemented.

Possible optimizations/improvements.

- Document that `l3trial/l3fp-types` introduces tools for adding new types.
- In subsection 9.1, write a grammar.
- It would be nice if the `parse` auxiliaries for each operation were set up in the corresponding module, rather than centralizing in `l3fp-parse`.
- Some functions should get an `_o` ending to indicate that they expand after their result.
- More care should be given to distinguish expandable/restricted expandable (auxiliary and internal) functions.
- The code for the `ternary` set of functions is ugly.
- There are many `~` missing in the doc to avoid bad line-breaks.
- The algorithm for computing the logarithm of the significand could be made to use a 5 terms Taylor series instead of 10 terms by taking $c = 2000/(\lfloor 200x \rfloor + 1) \in [10, 95]$ instead of $c \in [1, 10]$. Also, it would then be possible to simplify the computation of t . However, we would then have to hard-code the logarithms of 44 small integers instead of 9.
- Improve notations in the explanations of the division algorithm (`l3fp-basics`).
- Understand and document `__fp_basics_pack_weird_low:NNNNw` and `__fp_basics_pack_weird_high:NNNNNNNNw` better. Move the other `basics_pack` auxiliaries to `l3fp-aux` under a better name.

- Find out if underflow can really occur for trigonometric functions, and redoc as appropriate.
- Add bibliography. Some of Kahan’s articles, some previous T_EX fp packages, the international standards,...
- Also take into account the “inexact” exception?
- Support multi-character prefix operators (*e.g.*, @/ or whatever)?

Part XXIII

The `l3farray` package: fast global floating point arrays

1 `l3farray` documentation

For applications requiring heavy use of floating points, this module provides arrays which can be accessed in constant time (contrast `l3seq`, where access time is linear). The interface is very close to that of `l3intarray`. The size of the array is fixed and must be given at point of initialisation

Currently *all* functions in this module are candidates. Their documentation can be found in `l3candidates`.

Part XXIV

The l3sort package

Sorting functions

1 Controlling sorting

L^AT_EX3 comes with a facility to sort list variables (sequences, token lists, or comma-lists) according to some user-defined comparison. For instance,

```
\clist_set:Nn \l_foo_clist { 3 , 01 , -2 , 5 , +1 }
\clist_sort:Nn \l_foo_clist
{
  \int_compare:nNnTF { #1 } > { #2 }
  { \sort_return_swapped: }
  { \sort_return_same: }
}
```

results in `\l_foo_clist` holding the values `{ -2 , 01 , +1 , 3 , 5 }` sorted in non-decreasing order.

The code defining the comparison should call `\sort_return_swapped:` if the two items given as `#1` and `#2` are not in the correct order, and otherwise it should call `\sort_return_same:` to indicate that the order of this pair of items should not be changed.

For instance, a *comparison code* consisting only of `\sort_return_same:` with no test yields a trivial sort: the final order is identical to the original order. Conversely, using a *comparison code* consisting only of `\sort_return_swapped:` reverses the list (in a fairly inefficient way).

T_EXhackers note: The current implementation is limited to sorting approximately 20000 items (40000 in LuaT_EX), depending on what other packages are loaded.

Internally, the code from l3sort stores items in `\toks` registers allocated locally. Thus, the *comparison code* should not call `\newtoks` or other commands that allocate new `\toks` registers. On the other hand, altering the value of a previously allocated `\toks` register is not a problem.

```
\sort_return_same:
\sort_return_swapped:
```

New: 2017-02-06

```
\seq_sort:Nn <seq var>
{ ... \sort_return_same: or \sort_return_swapped: ... }
```

Indicates whether to keep the order or swap the order of two items that are compared in the sorting code. Only one of the `\sort_return_...` functions should be used by the code, according to the results of some tests on the items `#1` and `#2` to be compared.

Part XXV

The l3tl-analysis package: Analysing token lists

1 l3tl-analysis documentation

This module mostly provides internal functions for use in the l3regex module. However, it provides as a side-effect a user debugging function, very similar to the \ShowTokens macro from the ted package.

\tl_analysis_show:N	\tl_analysis_show:n {<token list>}
\tl_analysis_show:n	

New: 2018-04-09

Displays to the terminal the detailed decomposition of the <token list> into tokens, showing the category code of each character token, the meaning of control sequences and active characters, and the value of registers.

\tl_analysis_map_inline:nn	\tl_analysis_map_inline:nn {<token list>} {<inline function>}
\tl_analysis_map_inline:Nn	

New: 2018-04-09

Applies the <inline function> to each individual <token> in the <token list>. The <inline function> receives three arguments:

- <tokens>, which both o-expand and x-expand to the <token>. The detailed form of <token> may change in later releases.
- <char code>, a decimal representation of the character code of the token, −1 if it is a control sequence (with <catcode> 0).
- <catcode>, a capital hexadecimal digit which denotes the category code of the <token> (0: control sequence, 1: begin-group, 2: end-group, 3: math shift, 4: alignment tab, 6: parameter, 7: superscript, 8: subscript, A: space, B: letter, C:other, D:active).

Part XXVI

The `l3regex` package: Regular expressions in `TEX`

The `l3regex` package provides regular expression testing, extraction of submatches, splitting, and replacement, all acting on token lists. The syntax of regular expressions is mostly a subset of the PCRE syntax (and very close to POSIX), with some additions due to the fact that `TEX` manipulates tokens rather than characters. For performance reasons, only a limited set of features are implemented. Notably, back-references are not supported.

Let us give a few examples. After

```
\tl_set:Nn \l_my_tl { That~cat. }
\regex_replace_once:nnN { at } { is } \l_my_tl
```

the token list variable `\l_my_tl` holds the text “`This cat.`”, where the first occurrence of “`at`” was replaced by “`is`”. A more complicated example is a pattern to emphasize each word and add a comma after it:

```
\regex_replace_all:nnN { \w+ } { \c{emph}\cB\{ \0 \cE\} , } \l_my_tl
```

The `\w` sequence represents any “word” character, and `+` indicates that the `\w` sequence should be repeated as many times as possible (at least once), hence matching a word in the input token list. In the replacement text, `\0` denotes the full match (here, a word). The command `\emph` is inserted using `\c{emph}`, and its argument `\0` is put between braces `\cB\{` and `\cE\}`.

If a regular expression is to be used several times, it can be compiled once, and stored in a regex variable using `\regex_const:Nn`. For example,

```
\regex_const:Nn \c_foo_regex { \c{begin} \cB. (\c[~BE].*) \cE. }
```

stores in `\c_foo_regex` a regular expression which matches the starting marker for an environment: `\begin`, followed by a begin-group token (`\cB.`), then any number of tokens which are neither begin-group nor end-group character tokens (`\c[~BE].*`), ending with an end-group token (`\cE.`). As explained in the next section, the parentheses “capture” the result of `\c[~BE].*`, giving us access to the name of the environment when doing replacements.

1 Syntax of regular expressions

We start with a few examples, and encourage the reader to apply `\regex_show:n` to these regular expressions.

- `Cat` matches the word “Cat” capitalized in this way, but also matches the beginning of the word “Cattle”: use `\bCat\b` to match a complete word only.
- `[abc]` matches one letter among “a”, “b”, “c”; the pattern `(a|b|c)` matches the same three possible letters (but see the discussion of submatches below).
- `[A-Za-z]*` matches any number (due to the quantifier `*`) of Latin letters (not accented).

- `\c{[A-Za-z]*}` matches a control sequence made of Latin letters.
- `_[^\\]*\\` matches an underscore, any number of characters other than underscore, and another underscore; it is equivalent to `_.*?_` where `.` matches arbitrary characters and the lazy quantifier `*?` means to match as few characters as possible, thus avoiding matching underscores.
- `[\+\\-]?\\d+` matches an explicit integer with at most one sign.
- `[\+\\-_]*\\d+_*` matches an explicit integer with any number of `+` and `-` signs, with spaces allowed except within the mantissa, and surrounded by spaces.
- `[\+\\-_]*(\\d+|\\d*\\.\\d+)_*` matches an explicit integer or decimal number; using `[.,]` instead of `\\.` would allow the comma as a decimal marker.
- `[\+\\-_]*(\\d+|\\d*\\.\\d+)_*(\\(?i\\)pt|in|[cem]m|ex|[bs]p|[dn]d|[pcn]c)_*` matches an explicit dimension with any unit that T_EX knows, where `(?i)` means to treat lowercase and uppercase letters identically.
- `[\+\\-_]*(\\(?i\\)nan|inf|(\\d+|\\d*\\.\\d+)(_.*e[\\+\\-_]*\\d+)?)_*` matches an explicit floating point number or the special values `nan` and `inf` (with signs and spaces allowed).
- `[\+\\-_]*(\\d+|\\dC.)_*` matches an explicit integer or control sequence (without checking whether it is an integer variable).
- `\\G.*?\\K` at the beginning of a regular expression matches and discards (due to `\\K`) everything between the end of the previous match (`\\G`) and what is matched by the rest of the regular expression; this is useful in `\\regex_replace_all:nnN` when the goal is to extract matches or submatches in a finer way than with `\\regex_extract_all:nnN`.

While it is impossible for a regular expression to match only integer expressions, `[\+\\-\\(\\)*\\d+\\)([\\+\\-*/][\\+\\-\\(\\)*\\d+\\)]*` matches among other things all valid integer expressions (made only with explicit integers). One should follow it with further testing.

Most characters match exactly themselves, with an arbitrary category code. Some characters are special and must be escaped with a backslash (*e.g.*, `*` matches a star character). Some escape sequences of the form backslash-letter also have a special meaning (for instance `\\d` matches any digit). As a rule,

- every alphanumeric character (`A-Z`, `a-z`, `0-9`) matches exactly itself, and should not be escaped, because `\\A`, `\\B`, ... have special meanings;
- non-alphanumeric printable ascii characters can (and should) always be escaped: many of them have special meanings (*e.g.*, use `\\(`, `\\)`, `\\?`, `\\.`);
- spaces should always be escaped (even in character classes);
- any other character may be escaped or not, without any effect: both versions match exactly that character.

[**^...**] Negative character class. Matches any token other than the specified characters.

x-y Within a character class, this denotes a range (can be used with escaped characters).

[:**<name>**:] Within a character class (one more set of brackets), this denotes the POSIX character class **<name>**, which can be **alnum**, **alpha**, **ascii**, **blank**, **cntrl**, **digit**, **graph**, **lower**, **print**, **punct**, **space**, **upper**, **word**, or **xdigit**.

[:**~<name>**:] Negative POSIX character class.

For instance, [**a-oq-z\cC.**] matches any lowercase latin letter except **p**, as well as control sequences (see below for a description of **\c**).

Quantifiers (repetition).

? 0 or 1, greedy.

?? 0 or 1, lazy.

***** 0 or more, greedy.

***?** 0 or more, lazy.

+ 1 or more, greedy.

+? 1 or more, lazy.

{n} Exactly *n*.

{n,} *n* or more, greedy.

{n,}? *n* or more, lazy.

{n,m} At least *n*, no more than *m*, greedy.

{n,m}? At least *n*, no more than *m*, lazy.

Anchors and simple assertions.

\b Word boundary: either the previous token is matched by **\w** and the next by **\W**, or the opposite. For this purpose, the ends of the token list are considered as **\W**.

\B Not a word boundary: between two **\w** tokens or two **\W** tokens (including the boundary).

^ or **\A** Start of the subject token list.

\$, **\Z** or **\z** End of the subject token list.

\G Start of the current match. This is only different from **^** in the case of multiple matches: for instance **\regex_count:nnN { \G a } { aaba } \l_tmpa_int** yields 2, but replacing **\G** by **^** would result in **\l_tmpa_int** holding the value 1.

Alternation and capturing groups.

A|B|C Either one of **A**, **B**, or **C**.

(...) Capturing group.

(?:...) Non-capturing group.

(?<|...) Non-capturing group which resets the group number for capturing groups in each alternative. The following group is numbered with the first unused group number.

The `\c` escape sequence allows to test the category code of tokens, and match control sequences. Each character category is represented by a single uppercase letter:

- C for control sequences;
- B for begin-group tokens;
- E for end-group tokens;
- M for math shift;
- T for alignment tab tokens;
- P for macro parameter tokens;
- U for superscript tokens (up);
- D for subscript tokens (down);
- S for spaces;
- L for letters;
- O for others; and
- A for active characters.

The `\c` escape sequence is used as follows.

`\c{<regex>}` A control sequence whose *cname* matches the *<regex>*, anchored at the beginning and end, so that `\c{begin}` matches exactly `\begin`, and nothing else.

`\cX` Applies to the next object, which can be a character, character property, class, or group, and forces this object to only match tokens with category **X** (any of CBEMTPUDSLOA). For instance, `\cL[A-Z\d]` matches uppercase letters and digits of category code letter, `\cC.` matches any control sequence, and `\cO(abc)` matches `abc` where each character has category other.

`\c[XYZ]` Applies to the next object, and forces it to only match tokens with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[LSO](..)` matches two tokens of category letter, space, or other.

`\c[^XYZ]` Applies to the next object and prevents it from matching any token with category **X**, **Y**, or **Z** (each being any of CBEMTPUDSLOA). For instance, `\c[^O]\d` matches digits which have any category different from other.

The category code tests can be used inside classes; for instance, `[\cO\d \c[LO][A-F]]` matches what \TeX considers as hexadecimal digits, namely digits with category other, or uppercase letters from **A** to **F** with category either letter or other. Within a group affected by a category code test, the outer test can be overridden by a nested test: for instance, `\cL(ab\cO*cd)` matches `ab*cd` where all characters are of category letter, except `*` which has category other.

The `\u` escape sequence allows to insert the contents of a token list directly into a regular expression or a replacement, avoiding the need to escape special characters.

Namely, `\u{<tl var name>}` matches the exact contents of the token list `<tl var>`. Within a `\c{...}` control sequence matching, the `\u` escape sequence only expands its argument once, in effect performing `\tl_to_str:v`. Quantifiers are not supported directly: use a group.

The option `(?i)` makes the match case insensitive (identifying A–Z with a–z; no Unicode support yet). This applies until the end of the group in which it appears, and can be reverted using `(?-i)`. For instance, in `(?i)(a(?-i)b|c)d`, the letters `a` and `d` are affected by the `i` option. Characters within ranges and classes are affected individually: `(?i)[Y-\]` is equivalent to `[YZ\[\]yz]`, and `(?i)[^aeiou]` matches any character which is not a vowel. Neither character properties, nor `\c{...}` nor `\u{...}` are affected by the `i` option.

In character classes, only `[`, `^`, `-`, `]`, `\` and spaces are special, and should be escaped. Other non-alphanumeric characters can still be escaped without harm. Any escape sequence which matches a single character (`\d`, `\D`, *etc.*) is supported in character classes. If the first character is `^`, then the meaning of the character class is inverted; `^` appearing anywhere else in the range is not special. If the first character (possibly following a leading `^`) is `]` then it does not need to be escaped since ending the range there would make it empty. Ranges of characters can be expressed using `-`, for instance, `[\D 0–5]` and `[^6–9]` are equivalent.

Capturing groups are a means of extracting information about the match. Parenthesized groups are labelled in the order of their opening parenthesis, starting at 1. The contents of those groups corresponding to the “best” match (leftmost longest) can be extracted and stored in a sequence of token lists using for instance `\regex_extract_once:nnTF`.

The `\K` escape sequence resets the beginning of the match to the current position in the token list. This only affects what is reported as the full match. For instance,

```
\regex_extract_all:nnN { a \K . } { a123aaxyz } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{1}` and `{a}`: the true matches are `{a1}` and `{aa}`, but they are trimmed by the use of `\K`. The `\K` command does not affect capturing groups: for instance,

```
\regex_extract_once:nnN { (. \K c)+ \d } { acbc3 } \l_foo_seq
```

results in `\l_foo_seq` containing the items `{c3}` and `{bc}`: the true match is `{acbc3}`, with first submatch `{bc}`, but `\K` resets the beginning of the match to the last position where it appears.

2 Syntax of the replacement text

Most of the features described in regular expressions do not make sense within the replacement text. Backslash introduces various special constructions, described further below:

- `\0` is the whole match;
- `\1` is the submatch that was matched by the first (capturing) group `(...)`; similarly for `\2`, ..., `\9` and `\g{<number>}`;
- `_` inserts a space (spaces are ignored when not escaped);

- `\a, \e, \f, \n, \r, \t, \xhh, \x{hhh}` correspond to single characters as in regular expressions;
- `\c{<cs name>}` inserts a control sequence;
- `\c{<category>}<character>` (see below);
- `\u{<tl var name>}` inserts the contents of the `<tl var>` (see below).

Characters other than backslash and space are simply inserted in the result (but since the replacement text is first converted to a string, one should also escape characters that are special for \TeX , for instance use `\#`). Non-alphanumeric characters can always be safely escaped with a backslash.

For instance,

```
\tl_set:Nn \l_my_tl { Hello,~world! }
\regex_replace_all:nnN { ([er]?l|o) . } { (\0--\1) } \l_my_tl
```

results in `\l_my_tl` holding `H(e1l--e1)(o,--o) w(or--o)(ld--l)!`

The submatches are numbered according to the order in which the opening parenthesis of capturing groups appear in the regular expression to match. The n -th submatch is empty if there are fewer than n capturing groups or for capturing groups that appear in alternatives that were not used for the match. In case a capturing group matches several times during a match (due to quantifiers) only the last match is used in the replacement text. Submatches always keep the same category codes as in the original token list.

The characters inserted by the replacement have category code 12 (other) by default, with the exception of space characters. Spaces inserted through `_` have category code 10, while spaces inserted through `\x20` or `\x{20}` have category code 12. The escape sequence `\c` allows to insert characters with arbitrary category codes, as well as control sequences.

`\cX(...)` Produces the characters “...” with category `X`, which must be one of `CBEMTPUDSLOA` as in regular expressions. Parentheses are optional for a single character (which can be an escape sequence). When nested, the innermost category code applies, for instance `\cL(Hello\cS\ world)!` gives this text with standard category codes.

`\c{<text>}` Produces the control sequence with csname `<text>`. The `<text>` may contain references to the submatches `\0`, `\1`, and so on, as in the example for `\u` below.

The escape sequence `\u{<tl var name>}` allows to insert the contents of the token list with name `<tl var name>` directly into the replacement, giving an easier control of category codes. When nested in `\c{...}` and `\u{...}` constructions, the `\u` and `\c` escape sequences perform `\tl_to_str:v`, namely extract the value of the control sequence and turn it into a string. Matches can also be used within the arguments of `\c` and `\u`. For instance,

```
\tl_set:Nn \l_my_one_tl { first }
\tl_set:Nn \l_my_two_tl { \emph{second} }
\tl_set:Nn \l_my_tl { one , two , one , one }
\regex_replace_all:nnN { [,]+ } { \u{1_my_\0_tl} } \l_my_tl
```

results in `\l_my_tl` holding `first,\emph{second},first,first`.

3 Pre-compiling regular expressions

If a regular expression is to be used several times, it is better to compile it once rather than doing it each time the regular expression is used. The compiled regular expression is stored in a variable. All of the `l3regex` module's functions can be given their regular expression argument either as an explicit string or as a compiled regular expression.

`\regex_new:N`

New: 2017-05-26

`\regex_new:N` $\langle regex\ var \rangle$

Creates a new $\langle regex\ var \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle regex\ var \rangle$ is initially such that it never matches.

`\regex_set:Nn`
`\regex_gset:Nn`
`\regex_const:Nn`

New: 2017-05-26

`\regex_set:Nn` $\langle regex\ var \rangle$ $\{ \langle regex \rangle \}$

Stores a compiled version of the $\langle regular\ expression \rangle$ in the $\langle regex\ var \rangle$. For instance, this function can be used as

```
\regex_new:N \l_my_regex
\regex_set:Nn \l_my_regex { my\ (simple\ )? reg(ex|ular\ expression) }
```

The assignment is local for `\regex_set:Nn` and global for `\regex_gset:Nn`. Use `\regex_const:Nn` for compiled expressions which never change.

`\regex_show:n`
`\regex_show:N`

New: 2017-05-26

`\regex_show:n` $\{ \langle regex \rangle \}$

Shows how `l3regex` interprets the $\langle regex \rangle$. For instance, `\regex_show:n { \A X|Y }` shows

```
+--branch
  anchor at start (\A)
  char code 88
+--branch
  char code 89
```

indicating that the anchor `\A` only applies to the first branch: the second branch is not anchored to the beginning of the match.

4 Matching

All regular expression functions are available in both `:n` and `:N` variants. The former require a “standard” regular expression, while the later require a compiled expression as generated by `\regex_(g)set:Nn`.

`\regex_match:nnTF`
`\regex_match:NnTF`

New: 2017-05-26

`\regex_match:nnTF` $\{ \langle regex \rangle \}$ $\{ \langle token\ list \rangle \}$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$

Tests whether the $\langle regular\ expression \rangle$ matches any part of the $\langle token\ list \rangle$. For instance,

```
\regex_match:nnTF { b [cde]* } { abecdex } { TRUE } { FALSE }
\regex_match:nnTF { [b-dq-w] } { example } { TRUE } { FALSE }
```

leaves `TRUE` then `FALSE` in the input stream.

```
\regex_count:nnN
\regex_count:NnN
```

New: 2017-05-26

```
\regex_count:nnN {<regex>} {<token list>} <int var>
```

Sets *<int var>* within the current T_EX group level equal to the number of times *<regular expression>* appears in *<token list>*. The search starts by finding the left-most longest match, respecting greedy and lazy (non-greedy) operators. Then the search starts again from the character following the last character of the previous match, until reaching the end of the token list. Infinite loops are prevented in the case where the regular expression can match an empty token list: then we count one match between each pair of characters. For instance,

```
\int_new:N \l_foo_int
\regex_count:nnN { (b+|c) } { abbababcb } \l_foo_int
```

results in `\l_foo_int` taking the value 5.

5 Submatch extraction

```
\regex_extract_once:nnN
\regex_extract_once:nnNTF
\regex_extract_once:NnN
\regex_extract_once:NnNTF
```

New: 2017-05-26

```
\regex_extract_once:nnN {<regex>} {<token list>} <seq var>
\regex_extract_once:nnNTF {<regex>} {<token list>} <seq var> {<true code>} {<false code>}
```

Finds the first match of the *<regular expression>* in the *<token list>*. If it exists, the match is stored as the first item of the *<seq var>*, and further items are the contents of capturing groups, in the order of their opening parenthesis. The *<seq var>* is assigned locally. If there is no match, the *<seq var>* is cleared. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise.

For instance, assume that you type

```
\regex_extract_once:nnNTF { \A(La)?TeX(!*)\Z } { LaTeX!!! } \l_foo_seq
{ true } { false }
```

Then the regular expression (anchored at the start with `\A` and at the end with `\Z`) must match the whole token list. The first capturing group, `(La)?`, matches `La`, and the second capturing group, `(!*)`, matches `!!!`. Thus, `\l_foo_seq` contains as a result the items `{LaTeX!!!}`, `{La}`, and `{!!!}`, and the `true` branch is left in the input stream. Note that the n -th item of `\l_foo_seq`, as obtained using `\seq_item:Nn`, correspond to the submatch numbered $(n - 1)$ in functions such as `\regex_replace_once:nnN`.

```
\regex_extract_all:nnN
\regex_extract_all:nnNTF
\regex_extract_all:NnN
\regex_extract_all:NnNTF
```

New: 2017-05-26

```
\regex_extract_all:nnN {<regex>} {<token list>} <seq var>
\regex_extract_all:nnNTF {<regex>} {<token list>} <seq var> {<true code>} {<false code>}
```

Finds all matches of the *<regular expression>* in the *<token list>*, and stores all the submatch information in a single sequence (concatenating the results of multiple `\regex_extract_once:nnN` calls). The *<seq var>* is assigned locally. If there is no match, the *<seq var>* is cleared. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For instance, assume that you type

```
\regex_extract_all:nnNTF { \w+ } { Hello,~world! } \l_foo_seq
{ true } { false }
```

Then the regular expression matches twice, the resulting sequence contains the two items `{Hello}` and `{world}`, and the `true` branch is left in the input stream.

```
\regex_split:nnN
\regex_split:nnNTF
\regex_split:NnN
\regex_split:NnNTF
```

New: 2017-05-26

```
\regex_split:nnN {<regular expression>} {<token list>} <seq var>
\regex_split:nnNTF {<regular expression>} {<token list>} <seq var> {<true code>}
{<false code>}
```

Splits the *<token list>* into a sequence of parts, delimited by matches of the *<regular expression>*. If the *<regular expression>* has capturing groups, then the token lists that they match are stored as items of the sequence as well. The assignment to *<seq var>* is local. If no match is found the resulting *<seq var>* has the *<token list>* as its sole item. If the *<regular expression>* matches the empty token list, then the *<token list>* is split into single tokens. The testing versions insert the *<true code>* into the input stream if a match was found, and the *<false code>* otherwise. For example, after

```
\seq_new:N \l_path_seq
\regex_split:nnNTF { / } { the/path/for/this/file.tex } \l_path_seq
{ true } { false }
```

the sequence *\l_path_seq* contains the items {the}, {path}, {for}, {this}, and {file.tex}, and the **true** branch is left in the input stream.

6 Replacement

```
\regex_replace_once:nnN
\regex_replace_once:nnNTF
\regex_replace_once:NnN
\regex_replace_once:NnNTF
```

New: 2017-05-26

```
\regex_replace_once:nnN {<regular expression>} {<replacement>} <tl var>
\regex_replace_once:nnNTF {<regular expression>} {<replacement>} <tl var> {<true
code>} {<false code>}
```

Searches for the *<regular expression>* in the *<token list>* and replaces the first match with the *<replacement>*. The result is assigned locally to *<tl var>*. In the *<replacement>*, *\0* represents the full match, *\1* represent the contents of the first capturing group, *\2* of the second, *etc.*

```
\regex_replace_all:nnN
\regex_replace_all:nnNTF
\regex_replace_all:NnN
\regex_replace_all:NnNTF
```

New: 2017-05-26

```
\regex_replace_all:nnN {<regular expression>} {<replacement>} <tl var>
\regex_replace_all:nnNTF {<regular expression>} {<replacement>} <tl var> {<true
code>} {<false code>}
```

Replaces all occurrences of the *\regular expression* in the *<token list>* by the *<replacement>*, where *\0* represents the full match, *\1* represent the contents of the first capturing group, *\2* of the second, *etc.* Every match is treated independently, and matches cannot overlap. The result is assigned locally to *<tl var>*.

7 Constants and variables

```
\l_tmpa_regex
\l_tmpb_regex
```

New: 2017-12-11

Scratch regex for local assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

```
\g_tmpa_regex
\g_tmpb_regex
```

New: 2017-12-11

Scratch regex for global assignment. These are never used by the kernel code, and so are safe for use with any L^AT_EX3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

8 Bugs, misfeatures, future work, and other possibilities

The following need to be done now.

- Rewrite the documentation in a more ordered way, perhaps add a BNF?
Additional error-checking to come.
- Clean up the use of messages.
- Cleaner error reporting in the replacement phase.
- Add tracing information.
- Detect attempts to use back-references and other non-implemented syntax.
- Test for the maximum register `\c_max_register_int`.
- Find out whether the fact that `\W` and friends match the end-marker leads to bugs.
Possibly update `__regex_item_reverse:n`.
- The empty `cs` should be matched by `\c{}`, not by `\c{csname.?endcsname\s?}`.

Code improvements to come.

- Shift arrays so that the useful information starts at position 1.
- Only build `.,` once.
- Use arrays for the left and right state stacks when compiling a regex.
- Should `__regex_action_free_group:n` only be used for greedy `{n,}` quantifier? (I think not.)
- Quantifiers for `\u` and assertions.
- When matching, keep track of an explicit stack of `current_state` and `current_submatches`.
- If possible, when a state is reused by the same thread, kill other subthreads.
- Use an array rather than `\l__regex_balance_tl` to build the function `__regex_replacement_balance_one_match:n`.
- Reduce the number of epsilon-transitions in alternatives.
- Optimize simple strings: use less states (`abcade` should give two states, for `abc` and `ade`). [Does that really make sense?]
- Optimize groups with no alternative.
- Optimize states with a single `__regex_action_free:n`.
- Optimize the use of `__regex_action_success:` by inserting it in state 2 directly instead of having an extra transition.
- Optimize the use of `\int_step...` functions.

- Groups don't capture within regexes for csnames; optimize and document.
- Better “show” for anchors, properties, and catcode tests.
- Does \K really need a new state for itself?
- When compiling, use a boolean `in_cs` and less magic numbers.
- Instead of checking whether the character is special or alphanumeric using its character code, check if it is special in regexes with `\cs_if_exist` tests.

The following features are likely to be implemented at some point in the future.

- General look-ahead/behind assertions.
- Regex matching on external files.
- Conditional subpatterns with look ahead/behind: “if what follows is [...], then [...]”.
- `(*..)` and `(?..)` sequences to set some options.
- UTF-8 mode for pdfTeX.
- Newline conventions are not done. In particular, we should have an option for `.` not to match newlines. Also, `\A` should differ from `^`, and `\Z`, `\z` and `$` should differ.
- Unicode properties: `\p{..}` and `\P{..}`; `\X` which should match any “extended” Unicode sequence. This requires to manipulate a lot of data, probably using tree-boxes.
- Provide a syntax such as `\ur{1_my_regex}` to use an already-compiled regex in a more complicated regex. This makes regexes more easily composable.
- Allowing `\u{1_my_t1}` in more places, for instance as the number of repetitions in a quantifier.

The following features of PCRE or Perl may or may not be implemented.

- Callout with `(?C...)` or other syntax: some internal code changes make that possible, and it can be useful for instance in the replacement code to stop a regex replacement when some marker has been found; this raises the question of a potential `\regex_break`: and then of playing well with `\t1_map_break`: called from within the code in a regex. It also raises the question of nested calls to the regex machinery, which is a problem since `\fontdimen` are global.
- Conditional subpatterns (other than with a look-ahead or look-behind condition): this is non-regular, isn't it?
- Named subpatterns: TeX programmers have lived so far without any need for named macro parameters.

The following features of PCRE or Perl will definitely not be implemented.

- Back-references: non-regular feature, this requires backtracking, which is prohibitively slow.

- Recursion: this is a non-regular feature.
- Atomic grouping, possessive quantifiers: those tools, mostly meant to fix catastrophic backtracking, are unnecessary in a non-backtracking algorithm, and difficult to implement.
- Subroutine calls: this syntactic sugar is difficult to include in a non-backtracking algorithm, in particular because the corresponding group should be treated as atomic.
- Backtracking control verbs: intrinsically tied to backtracking.
- `\ddd`, matching the character with octal code `ddd`: we already have `\x{...}` and the syntax is confusingly close to what we could have used for backreferences (`\1`, `\2`, ...), making it harder to produce useful error message.
- `\cx`, similar to $\mathrm{T}_{\mathrm{E}}\mathrm{X}$'s own `\^^x`.
- Comments: $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ already has its own system for comments.
- `\Q...\E` escaping: this would require to read the argument verbatim, which is not in the scope of this module.
- `\C` single byte in UTF-8 mode: $\mathrm{X}_{\mathrm{Y}}\mathrm{T}_{\mathrm{E}}\mathrm{X}$ and $\mathrm{LuaT}_{\mathrm{E}}\mathrm{X}$ serve us characters directly, and splitting those into bytes is tricky, encoding dependent, and most likely not useful anyways.

Part XXVII

The l3box package

Boxes

There are three kinds of box operations: horizontal mode denoted with prefix `\hbox_`, vertical mode with prefix `\vbox_`, and the generic operations working in both modes with prefix `\box_`.

1 Creating and initialising boxes

<code>\box_new:N</code>	<code>\box_new:N</code> $\langle box \rangle$
<code>\box_new:c</code>	Creates a new $\langle box \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle box \rangle$ is initially void.

<code>\box_clear:N</code>	<code>\box_clear:N</code> $\langle box \rangle$
<code>\box_clear:c</code>	Clears the content of the $\langle box \rangle$ by setting the box equal to <code>\c_empty_box</code> .
<code>\box_gclear:N</code>	
<code>\box_gclear:c</code>	

<code>\box_clear_new:N</code>	<code>\box_clear_new:N</code> $\langle box \rangle$
<code>\box_clear_new:c</code>	Ensures that the $\langle box \rangle$ exists globally by applying <code>\box_new:N</code> if necessary, then applies <code>\box_(g)clear:N</code> to leave the $\langle box \rangle$ empty.
<code>\box_gclear_new:N</code>	
<code>\box_gclear_new:c</code>	

<code>\box_set_eq:NN</code>	<code>\box_set_eq:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_set_eq:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$.
<code>\box_gset_eq:NN</code>	
<code>\box_gset_eq:(cN Nc cc)</code>	

<code>\box_set_eq_clear:NN</code>	<code>\box_set_eq_clear:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_set_eq_clear:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ within the current TeX group equal to that of $\langle box_2 \rangle$, then clears $\langle box_2 \rangle$ globally.

<code>\box_gset_eq_clear:NN</code>	<code>\box_gset_eq_clear:NN</code> $\langle box_1 \rangle$ $\langle box_2 \rangle$
<code>\box_gset_eq_clear:(cN Nc cc)</code>	Sets the content of $\langle box_1 \rangle$ equal to that of $\langle box_2 \rangle$, then clears $\langle box_2 \rangle$. These assignments are global.

<code>\box_if_exist_p:N</code> ★	<code>\box_if_exist_p:N</code> $\langle box \rangle$
<code>\box_if_exist_p:c</code> ★	<code>\box_if_exist:NTF</code> $\langle box \rangle$ $\{ \langle true\ code \rangle \}$ $\{ \langle false\ code \rangle \}$
<code>\box_if_exist:NTF</code> ★	Tests whether the $\langle box \rangle$ is currently defined. This does not check that the $\langle box \rangle$ really is a box.
<code>\box_if_exist:cTF</code> ★	

New: 2012-03-03

2 Using boxes

<code>\box_use:N</code>	<code>\box_use:N <box></code>
<code>\box_use:c</code>	

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting. An error is raised if the variable does not exist or if it is invalid.

T_EXhackers note: This is the T_EX primitive `\copy`.

<code>\box_use_drop:N</code>	<code>\box_use_drop:N <box></code>
<code>\box_use_drop:c</code>	

Inserts the current content of the $\langle box \rangle$ onto the current list for typesetting. An error is raised if the variable does not exist or if it is invalid.

The $\langle box \rangle$ is then cleared at the group level the box was set at, *i.e.* the current content is “dropped” entirely. For example, with

```
\hbox_set:Nn \l_tmpa_box { A }
\group_begin:
  \hbox_set:Nn \l_tmpa_box { B }
\group_begin:
  \box_use_drop:N \l_tmpa_box
\group_end:
  \box_show:N \l_tmpa_box
\group_end:
  \box_show:N \l_tmpa_box
```

the first use of `\box_show:N` will show an entirely cleared (void) box, and the second will show the letter A in the box.

This function is useful as boxes can contain an open-ended amount of material. As such, they can have a significant memory impact on T_EX. At the same time, it is often the case that once a box has been inserted, it is no longer needed at all. Using `\box_use_drop:N` in these circumstances therefore offers improved memory use and performance. It should therefore be preferred over `\box_use:N` where it is clear that the content is no longer needed in the variable.

T_EXhackers note: This is the T_EX primitive `\box`.

<code>\box_move_right:nn</code>	<code>\box_move_right:nn {<dimexpr>} {<box function>}</code>
<code>\box_move_left:nn</code>	

This function operates in vertical mode, and inserts the material specified by the $\langle box \text{ function} \rangle$ such that its reference point is displaced horizontally by the given $\langle dimexpr \rangle$ from the reference point for typesetting, to the right or left as appropriate. The $\langle box \text{ function} \rangle$ should be a box operation such as `\box_use:N <box>` or a “raw” box specification such as `\vbox:n { xyz }`.

<code>\box_move_up:nn</code>	<code>\box_move_up:nn {<dimexpr>} {<box function>}</code>
<code>\box_move_down:nn</code>	

This function operates in horizontal mode, and inserts the material specified by the $\langle box \text{ function} \rangle$ such that its reference point is displaced vertically by the given $\langle dimexpr \rangle$ from the reference point for typesetting, up or down as appropriate. The $\langle box \text{ function} \rangle$ should be a box operation such as `\box_use:N <box>` or a “raw” box specification such as `\vbox:n { xyz }`.

3 Measuring and setting box dimensions

<code>\box_dp:N</code>	<code>\box_dp:N</code> $\langle box \rangle$
<code>\box_dp:c</code>	Calculates the depth (below the baseline) of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

T_EXhackers note: This is the T_EX primitive `\dp`.

<code>\box_ht:N</code>	<code>\box_ht:N</code> $\langle box \rangle$
<code>\box_ht:c</code>	Calculates the height (above the baseline) of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

T_EXhackers note: This is the T_EX primitive `\ht`.

<code>\box_wd:N</code>	<code>\box_wd:N</code> $\langle box \rangle$
<code>\box_wd:c</code>	Calculates the width of the $\langle box \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

T_EXhackers note: This is the T_EX primitive `\wd`.

<code>\box_set_dp:Nn</code>	<code>\box_set_dp:Nn</code> $\langle box \rangle$ $\{\langle dimension expression \rangle\}$
<code>\box_set_dp:cn</code>	Set the depth (below the baseline) of the $\langle box \rangle$ to the value of the $\{\langle dimension expression \rangle\}$. This is a global assignment.
<small>Updated: 2011-10-22</small>	

<code>\box_set_ht:Nn</code>	<code>\box_set_ht:Nn</code> $\langle box \rangle$ $\{\langle dimension expression \rangle\}$
<code>\box_set_ht:cn</code>	Set the height (above the baseline) of the $\langle box \rangle$ to the value of the $\{\langle dimension expression \rangle\}$. This is a global assignment.
<small>Updated: 2011-10-22</small>	

<code>\box_set_wd:Nn</code>	<code>\box_set_wd:Nn</code> $\langle box \rangle$ $\{\langle dimension expression \rangle\}$
<code>\box_set_wd:cn</code>	Set the width of the $\langle box \rangle$ to the value of the $\{\langle dimension expression \rangle\}$. This is a global assignment.
<small>Updated: 2011-10-22</small>	

4 Box conditionals

<code>\box_if_empty_p:N</code> *	<code>\box_if_empty_p:N</code> $\langle box \rangle$
<code>\box_if_empty_p:c</code> *	<code>\box_if_empty:N</code> $\langle box \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
<code>\box_if_empty:NTF</code> *	Tests if $\langle box \rangle$ is a empty (equal to <code>\c_empty_box</code>).
<code>\box_if_empty:cTF</code> *	

<code>\box_if_horizontal_p:N</code> *	<code>\box_if_horizontal_p:N</code> $\langle box \rangle$
<code>\box_if_horizontal_p:c</code> *	<code>\box_if_horizontal:N</code> $\langle box \rangle$ $\{\langle true code \rangle\}$ $\{\langle false code \rangle\}$
<code>\box_if_horizontal:NTF</code> *	Tests if $\langle box \rangle$ is a horizontal box.
<code>\box_if_horizontal:cTF</code> *	

<code>\box_if_vertical_p:N</code>	★	<code>\box_if_vertical_p:N</code>	$\langle box \rangle$
<code>\box_if_vertical_p:c</code>	★	<code>\box_if_vertical:NTF</code>	$\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\box_if_vertical:NTF</code>	★		Tests if $\langle box \rangle$ is a vertical box.
<code>\box_if_vertical:cTF</code>	★		

5 The last box inserted

<code>\box_set_to_last:N</code>	<code>\box_set_to_last:N</code>	$\langle box \rangle$
<code>\box_set_to_last:c</code>		Sets the $\langle box \rangle$ equal to the last item (box) added to the current partial list, removing the item from the list at the same time. When applied to the main vertical list, the $\langle box \rangle$ is always void as it is not possible to recover the last added item.
<code>\box_gset_to_last:N</code>		
<code>\box_gset_to_last:c</code>		

6 Constant boxes

<code>\c_empty_box</code>	This is a permanently empty box, which is neither set as horizontal nor vertical.
Updated: 2012-11-04	TeXhackers note: At the TeX level this is a void box.

7 Scratch boxes

<code>\l_tmpa_box</code>	Scratch boxes for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\l_tmpb_box</code>	
Updated: 2012-11-04	

<code>\g_tmpa_box</code>	Scratch boxes for global assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.
<code>\g_tmpb_box</code>	

8 Viewing box contents

<code>\box_show:N</code>	<code>\box_show:N</code>	$\langle box \rangle$
<code>\box_show:c</code>		Shows full details of the content of the $\langle box \rangle$ in the terminal.
Updated: 2012-05-11		
<code>\box_show:Nnn</code>	<code>\box_show:Nnn</code>	$\langle box \rangle$ $\{\langle intexpr_1 \rangle\}$ $\{\langle intexpr_2 \rangle\}$
<code>\box_show:cnn</code>		Display the contents of $\langle box \rangle$ in the terminal, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.
New: 2012-05-11		

<code>\box_log:N</code>	<code>\box_log:N</code> $\langle box \rangle$
<code>\box_log:c</code>	Writes full details of the content of the $\langle box \rangle$ to the log.
New: 2012-05-11	

<code>\box_log:Nnn</code>	<code>\box_log:Nnn</code> $\langle box \rangle$ $\{\langle intexpr_1 \rangle\}$ $\{\langle intexpr_2 \rangle\}$
<code>\box_log:cnn</code>	Writes the contents of $\langle box \rangle$ to the log, showing the first $\langle intexpr_1 \rangle$ items of the box, and descending into $\langle intexpr_2 \rangle$ group levels.
New: 2012-05-11	

9 Boxes and color

All L^AT_EX3 boxes are “color safe”: a color set inside the box stops applying after the end of the box has occurred.

10 Horizontal mode boxes

<code>\hbox:n</code>	<code>\hbox:n</code> $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of natural width and then includes this box in the current list for typesetting.

<code>\hbox_to_wd:nn</code>	<code>\hbox_to_wd:nn</code> $\{\langle dimexpr \rangle\}$ $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of width $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.

<code>\hbox_to_zero:n</code>	<code>\hbox_to_zero:n</code> $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width and then includes this box in the current list for typesetting.

<code>\hbox_set:Nn</code>	<code>\hbox_set:Nn</code> $\langle box \rangle$ $\{\langle contents \rangle\}$
<code>\hbox_set:cn</code>	Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$.
<code>\hbox_gset:Nn</code>	
<code>\hbox_gset:cn</code>	
Updated: 2017-04-05	

<code>\hbox_set_to_wd:Nnn</code>	<code>\hbox_set_to_wd:Nnn</code> $\langle box \rangle$ $\{\langle dimexpr \rangle\}$ $\{\langle contents \rangle\}$
<code>\hbox_set_to_wd:cnn</code>	Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$.
<code>\hbox_gset_to_wd:Nnn</code>	
<code>\hbox_gset_to_wd:cnn</code>	
Updated: 2017-04-05	

<code>\hbox_overlap_right:n</code>	<code>\hbox_overlap_right:n</code> $\{\langle contents \rangle\}$
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the right of the insertion point.

<hr/> <code>\hbox_overlap_left:n</code> <hr/>	<code>\hbox_overlap_left:n {\langle contents \rangle}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a horizontal box of zero width such that material protrudes to the left of the insertion point.
<hr/> <code>\hbox_set:Nw</code> <code>\hbox_set:cw</code> <code>\hbox_set_end:</code> <code>\hbox_gset:Nw</code> <code>\hbox_gset:cw</code> <code>\hbox_gset_end:</code> <hr/>	<code>\hbox_set:Nw \langle box \rangle \langle contents \rangle \hbox_set_end:</code> Typesets the $\langle contents \rangle$ at natural width and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
Updated: 2017-04-05	
<hr/> <code>\hbox_set_to_wd:Nnw</code> <code>\hbox_set_to_wd:cnw</code> <code>\hbox_gset_to_wd:Nnw</code> <code>\hbox_gset_to_wd:cnw</code> <hr/>	<code>\hbox_set_to_wd:Nnw \langle box \rangle {\langle dimexpr \rangle} \langle contents \rangle \hbox_set_end:</code> Typesets the $\langle contents \rangle$ to the width given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. In contrast to <code>\hbox_set_to_wd:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
New: 2017-06-08	
<hr/> <code>\hbox_unpack:N</code> <code>\hbox_unpack:c</code> <hr/>	<code>\hbox_unpack:N \langle box \rangle</code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set.
	TeXhackers note: This is the TeX primitive <code>\unhcopy</code> .
<hr/> <code>\hbox_unpack_clear:N</code> <code>\hbox_unpack_clear:c</code> <hr/>	<code>\hbox_unpack_clear:N \langle box \rangle</code> Unpacks the content of the horizontal $\langle box \rangle$, retaining any stretching or shrinking applied when the $\langle box \rangle$ was set. The $\langle box \rangle$ is then cleared globally.
	TeXhackers note: This is the TeX primitive <code>\unhbox</code> .

11 Vertical mode boxes

Vertical boxes inherit their baseline from their contents. The standard case is that the baseline of the box is at the same position as that of the last item added to the box. This means that the box has no depth unless the last item added to it had depth. As a result most vertical boxes have a large height value and small or zero depth. The exception are `_top` boxes, where the reference point is that of the first item added. These tend to have a large depth and small height, although the latter is typically non-zero.

<hr/> <code>\vbox:n</code> <hr/>	<code>\vbox:n {\langle contents \rangle}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting.
<hr/> <code>\vbox_top:n</code> <hr/>	<code>\vbox_top:n {\langle contents \rangle}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of natural height and includes this box in the current list for typesetting. The baseline of the box is equal to that of the <i>first</i> item added to the box.

<hr/> <code>\vbox_to_ht:n</code> <hr/>	<code>\vbox_to_ht:n {<dimexpr>} {<contents>}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of height $\langle dimexpr \rangle$ and then includes this box in the current list for typesetting.
<hr/> <code>\vbox_to_zero:n</code> <hr/>	<code>\vbox_to_zero:n {<contents>}</code>
Updated: 2017-04-05	Typesets the $\langle contents \rangle$ into a vertical box of zero height and then includes this box in the current list for typesetting.
<hr/> <code>\vbox_set:Nn</code> <code>\vbox_set:cn</code> <code>\vbox_gset:Nn</code> <code>\vbox_gset:cn</code> <hr/>	<code>\vbox_set:Nn <box> {<contents>}</code> Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$.
Updated: 2017-04-05	
<hr/> <code>\vbox_set_top:Nn</code> <code>\vbox_set_top:cn</code> <code>\vbox_gset_top:Nn</code> <code>\vbox_gset_top:cn</code> <hr/>	<code>\vbox_set_top:Nn <box> {<contents>}</code> Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. The baseline of the box is equal to that of the <i>first</i> item added to the box.
Updated: 2017-04-05	
<hr/> <code>\vbox_set_to_ht:Nnn</code> <code>\vbox_set_to_ht:cnn</code> <code>\vbox_gset_to_ht:Nnn</code> <code>\vbox_gset_to_ht:cnn</code> <hr/>	<code>\vbox_set_to_ht:Nnn <box> {<dimexpr>} {<contents>}</code> Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$.
Updated: 2017-04-05	
<hr/> <code>\vbox_set:Nw</code> <code>\vbox_set:cw</code> <code>\vbox_set_end:</code> <code>\vbox_gset:Nw</code> <code>\vbox_gset:cw</code> <code>\vbox_gset_end:</code> <hr/>	<code>\vbox_set:Nw <box> <contents> \vbox_set_end:</code> Typesets the $\langle contents \rangle$ at natural height and then stores the result inside the $\langle box \rangle$. In contrast to <code>\vbox_set:Nn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument.
Updated: 2017-04-05	
<hr/> <code>\vbox_set_to_ht:Nnw</code> <code>\vbox_set_to_ht:cnw</code> <code>\vbox_gset_to_ht:Nnw</code> <code>\vbox_gset_to_ht:cnw</code> <hr/>	<code>\vbox_set_to_ht:Nnw <box> {<dimexpr>} <contents> \vbox_set_end:</code> Typesets the $\langle contents \rangle$ to the height given by the $\langle dimexpr \rangle$ and then stores the result inside the $\langle box \rangle$. In contrast to <code>\vbox_set_to_ht:Nnn</code> this function does not absorb the argument when finding the $\langle content \rangle$, and so can be used in circumstances where the $\langle content \rangle$ may not be a simple argument
New: 2017-06-08	
<hr/> <code>\vbox_set_split_to_ht:NNn</code> <code>\vbox_set_split_to_ht:(cNn Ncn ccn)</code> <code>\vbox_gset_split_to_ht:NNn</code> <code>\vbox_gset_split_to_ht:(cNn Ncn ccn)</code> <hr/>	<code>\vbox_set_split_to_ht:NNn <box₁₂</code>
Updated: 2018-12-29	

Sets $\langle box_1 \rangle$ to contain material to the height given by the $\langle dimexpr \rangle$ by removing content from the top of $\langle box_2 \rangle$ (which must be a vertical box).

<hr/> <code>\vbox_unpack:N</code>	<code>\vbox_unpack:N <box></code>
<hr/> <code>\vbox_unpack:c</code>	Unpacks the content of the vertical <code><box></code> , retaining any stretching or shrinking applied when the <code><box></code> was set.

T_EXhackers note: This is the T_EX primitive `\unvcopy`.

<hr/> <code>\vbox_unpack_clear:N</code>	<code>\vbox_unpack:N <box></code>
<hr/> <code>\vbox_unpack_clear:c</code>	Unpacks the content of the vertical <code><box></code> , retaining any stretching or shrinking applied when the <code><box></code> was set. The <code><box></code> is then cleared globally.

T_EXhackers note: This is the T_EX primitive `\unvbox`.

12 Affine transformations

Affine transformations are changes which (informally) preserve straight lines. Simple translations are affine transformations, but are better handled in T_EX by doing the translation first, then inserting an unmodified box. On the other hand, rotation and resizing of boxed material can best be handled by modifying boxes. These transformations are described here.

<hr/> <code>\box_autosize_to_wd_and_ht:Nnn</code>	<code>\box_autosize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}</code>
<hr/> <code>\box_autosize_to_wd_and_ht:cnn</code>	

New: 2017-04-04

Resizes the `<box>` to fit within the given `<x-size>` (horizontally) and `<y-size>` (vertically); both of the sizes are dimension expressions. The `<y-size>` is the height only: it does not include any depth. The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the resizing is applied. The final size of the `<box>` is the smaller of `{<x-size>}` and `{<y-size>}`, *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the `<box>` to be reversed in direction, but the reference point of the `<box>` is unchanged. Thus a negative `<y-size>` results in the `<box>` having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T_EX group level.

<hr/> <code>\box_autosize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_autosize_to_wd_and_ht_plus_dp:Nnn <box> {<x-size>}</code>
<hr/> <code>\box_autosize_to_wd_and_ht_plus_dp:cnn</code>	<code>{<y-size>}</code>

New: 2017-04-04

Resizes the `<box>` to fit within the given `<x-size>` (horizontally) and `<y-size>` (vertically); both of the sizes are dimension expressions. The `<y-size>` is the total vertical size (height plus depth). The updated `<box>` is an `hbox`, irrespective of the nature of the `<box>` before the resizing is applied. The final size of the `<box>` is the smaller of `{<x-size>}` and `{<y-size>}`, *i.e.* the result fits within the dimensions specified. Negative sizes cause the material in the `<box>` to be reversed in direction, but the reference point of the `<box>` is unchanged. Thus a negative `<y-size>` results in the `<box>` having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current T_EX group level.

`\box_resize_to_ht:Nn` `\box_resize_to_ht:Nn <box> {<y-size>}`

`\box_resize_to_ht:cn`

Resizes the $\langle box \rangle$ to $\langle y-size \rangle$ (vertically), scaling the horizontal size by the same amount; $\langle y-size \rangle$ is a dimension expression. The $\langle y-size \rangle$ is the height only: it does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle y-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

`\box_resize_to_ht_plus_dp:Nn` `\box_resize_to_ht_plus_dp:Nn <box> {<y-size>}`

`\box_resize_to_ht_plus_dp:cn`

Resizes the $\langle box \rangle$ to $\langle y-size \rangle$ (vertically), scaling the horizontal size by the same amount; $\langle y-size \rangle$ is a dimension expression. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle y-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

`\box_resize_to_wd:Nn` `\box_resize_to_wd:Nn <box> {<x-size>}`

`\box_resize_to_wd:cn`

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally), scaling the vertical size by the same amount; $\langle x-size \rangle$ is a dimension expression. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. A negative $\langle x-size \rangle$ causes the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle x-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

`\box_resize_to_wd_and_ht:Nnn` `\box_resize_to_wd_and_ht:Nnn <box> {<x-size>} {<y-size>}`

`\box_resize_to_wd_and_ht:cnn`

New: 2014-07-03

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically): both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the height only and does not include any depth. The updated $\langle box \rangle$ is an `hbox`, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

<code>\box_resize_to_wd_and_ht_plus_dp:Nnn</code>	<code>\box_resize_to_wd_and_ht_plus_dp:Nnn <box> {(x-size)} {(y-size)}</code>
<code>\box_resize_to_wd_and_ht_plus_dp:cnn</code>	

New: 2017-04-06

Resizes the $\langle box \rangle$ to $\langle x-size \rangle$ (horizontally) and $\langle y-size \rangle$ (vertically): both of the sizes are dimension expressions. The $\langle y-size \rangle$ is the total vertical size (height plus depth). The updated $\langle box \rangle$ is an **hbox**, irrespective of the nature of the $\langle box \rangle$ before the resizing is applied. Negative sizes cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-size \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

<code>\box_rotate:Nn</code>	<code>\box_rotate:Nn <box> {(angle)}</code>
<code>\box_rotate:cn</code>	

Rotates the $\langle box \rangle$ by $\langle angle \rangle$ (in degrees) anti-clockwise about its reference point. The reference point of the updated box is moved horizontally such that it is at the left side of the smallest rectangle enclosing the rotated material. The updated $\langle box \rangle$ is an **hbox**, irrespective of the nature of the $\langle box \rangle$ before the rotation is applied. The rotation applies within the current \TeX group level.

<code>\box_scale:Nnn</code>	<code>\box_scale:Nnn <box> {(x-scale)} {(y-scale)}</code>
<code>\box_scale:cnn</code>	

Scales the $\langle box \rangle$ by factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively (both scales are integer expressions). The updated $\langle box \rangle$ is an **hbox**, irrespective of the nature of the $\langle box \rangle$ before the scaling is applied. Negative scalings cause the material in the $\langle box \rangle$ to be reversed in direction, but the reference point of the $\langle box \rangle$ is unchanged. Thus a negative $\langle y-scale \rangle$ results in the $\langle box \rangle$ having a depth dependent on the height of the original and *vice versa*. The resizing applies within the current \TeX group level.

13 Primitive box conditionals

<code>\if_hbox:N</code> ★	<code>\if_hbox:N <box></code> <code> <true code></code> <code>\else:</code> <code> <false code></code> <code>\fi:</code>
---------------------------	--

Tests if $\langle box \rangle$ is a horizontal box.

\TeX hackers note: This is the \TeX primitive `\ifhbox`.

<code>\if_vbox:N</code> ★	<code>\if_vbox:N <box></code> <code> <true code></code> <code>\else:</code> <code> <false code></code> <code>\fi:</code>
---------------------------	--

Tests if $\langle box \rangle$ is a vertical box.

\TeX hackers note: This is the \TeX primitive `\ifvbox`.

`\if_box_empty:N` ★

```
\if_box_empty:N <box>
  <true code>
\else:
  <false code>
\fi:
```

Tests if `<box>` is an empty (void) box.

TeXhackers note: This is the TeX primitive `\ifvoid`.

Part XXVIII

The l3coffins package

Coffin code layer

The material in this module provides the low-level support system for coffins. For details about the design concept of a coffin, see the xcoffins module (in the l3experimental bundle).

1 Creating and initialising coffins

`\coffin_new:N`
`\coffin_new:c`
 New: 2011-08-17

`\coffin_new:N` $\langle coffin \rangle$
 Creates a new $\langle coffin \rangle$ or raises an error if the name is already taken. The declaration is global. The $\langle coffin \rangle$ is initially empty.

`\coffin_clear:N`
`\coffin_clear:c`
 New: 2011-08-17

`\coffin_clear:N` $\langle coffin \rangle$
 Clears the content of the $\langle coffin \rangle$ within the current T_EX group level.

`\coffin_set_eq:NN`
`\coffin_set_eq:(Nc|cN|cc)`
 New: 2011-08-17

`\coffin_set_eq:NN` $\langle coffin_1 \rangle$ $\langle coffin_2 \rangle$
 Sets both the content and poles of $\langle coffin_1 \rangle$ equal to those of $\langle coffin_2 \rangle$ within the current T_EX group level.

`\coffin_if_exist_p:N` ★
`\coffin_if_exist_p:c` ★
`\coffin_if_exist:NTF` ★
`\coffin_if_exist:cTF` ★
 New: 2012-06-20

`\coffin_if_exist_p:N` $\langle box \rangle$
`\coffin_if_exist:NTF` $\langle box \rangle$ $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
 Tests whether the $\langle coffin \rangle$ is currently defined.

2 Setting coffin content and poles

All coffin functions create and manipulate coffins locally within the current T_EX group level.

`\hcoffin_set:Nn`
`\hcoffin_set:cn`
 New: 2011-08-17
 Updated: 2011-09-03

`\hcoffin_set:Nn` $\langle coffin \rangle$ $\{\langle material \rangle\}$
 Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

`\hcoffin_set:Nw`
`\hcoffin_set:cw`
`\hcoffin_set_end:`
 New: 2011-09-10

`\hcoffin_set:Nw` $\langle coffin \rangle$ $\langle material \rangle$ `\hcoffin_set_end:`
 Typesets the $\langle material \rangle$ in horizontal mode, storing the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

`\vcoffin_set:Nnn`
`\vcoffin_set:cnn`
 New: 2011-08-17
 Updated: 2012-05-22

`\vcoffin_set:Nnn` $\langle coffin \rangle$ $\{\langle width \rangle\}$ $\{\langle material \rangle\}$
 Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material.

`\vcoffin_set:Nnw`
`\vcoffin_set:cnw`
`\vcoffin_set_end:`
 New: 2011-09-10
 Updated: 2012-05-22

`\vcoffin_set:Nnw` $\langle coffin \rangle$ $\{\langle width \rangle\}$ $\langle material \rangle$ `\vcoffin_set_end:`
 Typesets the $\langle material \rangle$ in vertical mode constrained to the given $\langle width \rangle$ and stores the result in the $\langle coffin \rangle$. The standard poles for the $\langle coffin \rangle$ are then set up based on the size of the typeset material. These functions are useful for setting the entire contents of an environment in a coffin.

`\coffin_set_horizontal_pole:Nnn` `\coffin_set_horizontal_pole:Nnn` $\langle coffin \rangle$
`\coffin_set_horizontal_pole:cnn` $\{\langle pole \rangle\}$ $\{\langle offset \rangle\}$
 New: 2012-07-20

Sets the $\langle pole \rangle$ to run horizontally through the $\langle coffin \rangle$. The $\langle pole \rangle$ is placed at the $\langle offset \rangle$ from the bottom edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

`\coffin_set_vertical_pole:Nnn` `\coffin_set_vertical_pole:Nnn` $\langle coffin \rangle$ $\{\langle pole \rangle\}$ $\{\langle offset \rangle\}$
`\coffin_set_vertical_pole:cnn`
 New: 2012-07-20

Sets the $\langle pole \rangle$ to run vertically through the $\langle coffin \rangle$. The $\langle pole \rangle$ is placed at the $\langle offset \rangle$ from the left-hand edge of the bounding box of the $\langle coffin \rangle$. The $\langle offset \rangle$ should be given as a dimension expression.

3 Joining and using coffins

`\coffin_attach:NnnNnnnn` `\coffin_attach:NnnNnnnn`
`\coffin_attach:(cnnNnnnn|Nnnncnnnn|cnnncnnnn)` $\langle coffin_1 \rangle$ $\{\langle coffin_1-pole_1 \rangle\}$ $\{\langle coffin_1-pole_2 \rangle\}$
 $\langle coffin_2 \rangle$ $\{\langle coffin_2-pole_1 \rangle\}$ $\{\langle coffin_2-pole_2 \rangle\}$
 $\{\langle x-offset \rangle\}$ $\{\langle y-offset \rangle\}$

This function attaches $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ is not altered, *i.e.* $\langle coffin_2 \rangle$ can protrude outside of the bounding box of the coffin. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_join:NnnNnnnn
\coffin_join:(cnnNnnnn|Nnnncnnnn|cnnncnnnn)
```

```
\coffin_join:NnnNnnnn
  <coffin_1> {<coffin_1-pole_1>} {<coffin_1-pole_2>}
  <coffin_2> {<coffin_2-pole_1>} {<coffin_2-pole_2>}
  {<x-offset>} {<y-offset>}
```

This function joins $\langle coffin_2 \rangle$ to $\langle coffin_1 \rangle$ such that the bounding box of $\langle coffin_1 \rangle$ may expand. The new bounding box covers the area containing the bounding boxes of the two original coffins. The alignment is carried out by first calculating $\langle handle_1 \rangle$, the point of intersection of $\langle coffin_1-pole_1 \rangle$ and $\langle coffin_1-pole_2 \rangle$, and $\langle handle_2 \rangle$, the point of intersection of $\langle coffin_2-pole_1 \rangle$ and $\langle coffin_2-pole_2 \rangle$. $\langle coffin_2 \rangle$ is then attached to $\langle coffin_1 \rangle$ such that the relationship between $\langle handle_1 \rangle$ and $\langle handle_2 \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions.

```
\coffin_typeset:Nnnnn
\coffin_typeset:cnnnn
```

Updated: 2012-07-20

```
\coffin_typeset:Nnnnn <coffin> {<pole_1>} {<pole_2>}
  {<x-offset>} {<y-offset>}
```

Typesetting is carried out by first calculating $\langle handle \rangle$, the point of intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. The coffin is then typeset in horizontal mode such that the relationship between the current reference point in the document and the $\langle handle \rangle$ is described by the $\langle x-offset \rangle$ and $\langle y-offset \rangle$. The two offsets should be given as dimension expressions. Typesetting a coffin is therefore analogous to carrying out an alignment where the “parent” coffin is the current insertion point.

4 Measuring coffins

```
\coffin_dp:N
\coffin_dp:c
```

```
\coffin_dp:N <coffin>
```

Calculates the depth (below the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_ht:N
\coffin_ht:c
```

```
\coffin_ht:N <coffin>
```

Calculates the height (above the baseline) of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

```
\coffin_wd:N
\coffin_wd:c
```

```
\coffin_wd:N <coffin>
```

Calculates the width of the $\langle coffin \rangle$ in a form suitable for use in a $\langle dimension expression \rangle$.

5 Coffin diagnostics

```
\coffin_display_handles:Nn
\coffin_display_handles:cn
```

Updated: 2011-09-02

```
\coffin_display_handles:Nn <coffin> {<color>}
```

This function first calculates the intersections between all of the $\langle poles \rangle$ of the $\langle coffin \rangle$ to give a set of $\langle handles \rangle$. It then prints the $\langle coffin \rangle$ at the current location in the source, with the position of the $\langle handles \rangle$ marked on the coffin. The $\langle handles \rangle$ are labelled as part of this process: the locations of the $\langle handles \rangle$ and the labels are both printed in the $\langle color \rangle$ specified.

<hr/> <code>\coffin_mark_handle:Nnnn</code> <code>\coffin_mark_handle:cnnn</code> <hr/> Updated: 2011-09-02 <hr/>	<code>\coffin_mark_handle:Nnnn <coffin> {<pole₁>} {<pole₂>} {<color>}</code> <p>This function first calculates the $\langle handle \rangle$ for the $\langle coffin \rangle$ as defined by the intersection of $\langle pole_1 \rangle$ and $\langle pole_2 \rangle$. It then marks the position of the $\langle handle \rangle$ on the $\langle coffin \rangle$. The $\langle handle \rangle$ are labelled as part of this process: the location of the $\langle handle \rangle$ and the label are both printed in the $\langle color \rangle$ specified.</p>
<hr/> <code>\coffin_show_structure:N</code> <code>\coffin_show_structure:c</code> <hr/> Updated: 2015-08-01 <hr/>	<code>\coffin_show_structure:N <coffin></code> <p>This function shows the structural information about the $\langle coffin \rangle$ in the terminal. The width, height and depth of the typeset material are given, along with the location of all of the poles of the coffin.</p> <p>Notice that the poles of a coffin are defined by four values: the x and y co-ordinates of a point that the pole passes through and the x- and y-components of a vector denoting the direction of the pole. It is the ratio between the later, rather than the absolute values, which determines the direction of the pole.</p>
<hr/> <code>\coffin_log_structure:N</code> <code>\coffin_log_structure:c</code> <hr/> New: 2014-08-22 Updated: 2015-08-01 <hr/>	<code>\coffin_log_structure:N <coffin></code> <p>This function writes the structural information about the $\langle coffin \rangle$ in the log file. See also <code>\coffin_show_structure:N</code> which displays the result in the terminal.</p>

6 Constants and variables

<hr/> <code>\c_empty_coffin</code> <hr/>	A permanently empty coffin.
<hr/> <code>\l_tmpa_coffin</code> <code>\l_tmpp_coffin</code> <hr/> New: 2012-06-19 <hr/>	Scratch coffins for local assignment. These are never used by the kernel code, and so are safe for use with any L ^A T _E X3-defined function. However, they may be overwritten by other non-kernel code and so should only be used for short-term storage.

Part XXIX

The `l3color-base` package

Color support

This module provides support for color in L^AT_EX3. At present, the material here is mainly intended to support a small number of low-level requirements in other `l3kernel` modules.

1 Color in boxes

Controlling the color of text in boxes requires a small number of control functions, so that the boxed material uses the color at the point where it is set, rather than where it is used.

`\color_group_begin:`
`\color_group_end:`

New: 2011-09-03

`\color_group_begin:`
...
`\color_group_end:`

Creates a color group: one used to “trap” color settings.

`\color_ensure_current:`

New: 2011-09-03

`\color_ensure_current:`

Ensures that material inside a box uses the foreground color at the point where the box is set, rather than that in force when the box is used. This function should usually be used within a `\color_group_begin: ... \color_group_end:` group.

Part XXX

The l3luatex package: LuaTeX-specific functions

The LuaTeX engine provides access to the Lua programming language, and with it access to the “internals” of TeX. In order to use this within the framework provided here, a family of functions is available. When used with pdfTeX, pTeX, upTeX or XeTeX these raise an error: use `\sys_if_engine_luatex:T` to avoid this. Details on using Lua with the LuaTeX engine are given in the LuaTeX manual.

1 Breaking out to Lua

<code>\lua_now:n</code>	★	<code>\lua_now:n {⟨token list⟩}</code>
-------------------------	---	--

<code>\lua_now:e</code>	★
-------------------------	---

New: 2018-06-18

The *⟨token list⟩* is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter for processing. Each `\lua_now:n` block is treated by Lua as a separate chunk. The Lua interpreter executes the *⟨Lua input⟩* immediately, and in an expandable manner.

TeXhackers note: `\lua_now:e` is a macro wrapper around `\directlua:` when LuaTeX is in use two expansions are required to yield the result of the Lua code.

<code>\lua_shipout_e:n</code>

<code>\lua_shipout:n</code>

New: 2018-06-18

`\lua_shipout:n {⟨token list⟩}`

The *⟨token list⟩* is first tokenized by TeX, which includes converting line ends to spaces in the usual TeX manner and which respects currently-applicable TeX category codes. The resulting *⟨Lua input⟩* is passed to the Lua interpreter when the current page is finalised (*i.e.* at shipout). Each `\lua_shipout:n` block is treated by Lua as a separate chunk. The Lua interpreter will execute the *⟨Lua input⟩* during the page-building routine: no TeX expansion of the *⟨Lua input⟩* will occur at this stage.

In the case of the `\lua_shipout_e:n` version the input is fully expanded by TeX in an e-type manner during the shipout operation.

TeXhackers note: At a TeX level, the *⟨Lua input⟩* is stored as a “whatsit”.

<code>\lua_escape:n</code>	★	<code>\lua_escape:n {⟨token list⟩}</code>
----------------------------	---	---

<code>\lua_escape:e</code>	★
----------------------------	---

New: 2015-06-29

Converts the *⟨token list⟩* such that it can safely be passed to Lua: embedded backslashes, double and single quotes, and newlines and carriage returns are escaped. This is done by prepending an extra token consisting of a backslash with category code 12, and for the line endings, converting them to `\n` and `\r`, respectively.

TeXhackers note: `\lua_escape:e` is a macro wrapper around `\luaescapestring:` when LuaTeX is in use two expansions are required to yield the result of the Lua code.

2 Lua interfaces

As well as interfaces for T_EX, there are a small number of Lua functions provided here.

<u>l3kernel</u>	All public interfaces provided by the module are stored within the <code>l3kernel</code> table.
<u>l3kernel.charcat</u>	<p><code>l3kernel.charcat(<charcode>, <catcode>)</code></p> <p>Constructs a character of <i><charcode></i> and <i><catcode></i> and returns the result to T_EX.</p>
<u>l3kernel.elapsedtime</u>	<p><code>l3kernel.elapsedtime()</code></p> <p>Returns the time in <i><scaled seconds></i> since the start of the T_EX run or since <code>l3kernel.resettimer</code> was issued.</p>
<u>l3kernel.filemdfivesum</u>	<p><code>l3kernel.filemdfivesum(<file>)</code></p> <p>Returns the of the MD5 sum of the file contents read as bytes; note that the result will depend on the nature of the line endings used in the file, in contrast to normal T_EX behaviour. If the <i><file></i> is not found, nothing is returned with <i>no error raised</i>.</p>
<u>l3kernel.filemoddate</u>	<p><code>l3kernel.filemoddate(<file>)</code></p> <p>Returns the of the date/time of last modification of the <i><file></i> in the format</p> <p style="text-align: center;"><code>D:<year><month><day><hour><minute><second><offset></code></p> <p>where the latter may be Z (UTC) or <i><plus-minus><hours>'<minutes>'</i>. If the <i><file></i> is not found, nothing is returned with <i>no error raised</i>.</p>
<u>l3kernel.filesize</u>	<p><code>l3kernel.filesize(<file>)</code></p> <p>Returns the size of the <i><file></i> in bytes. If the <i><file></i> is not found, nothing is returned with <i>no error raised</i>.</p>
<u>l3kernel.resettimer</u>	<p><code>l3kernel.resettimer()</code></p> <p>Resets the timer used by <code>l3kernel.elapsedtime</code>.</p>
<u>l3kernel.strcmp</u>	<p><code>l3kernel.strcmp(<str one>, <str two>)</code></p> <p>Compares the two strings and returns 0 to T_EX if the two are identical.</p>

Part XXXI

The l3unicode package: Unicode support functions

This module provides Unicode-specific functions along with loading data from a range of Unicode Consortium files. At present, it provides no public functions.

Part XXXII

The l3candidates package

Experimental additions to l3kernel

1 Important notice

This module provides a space in which functions can be added to l3kernel (expl3) while still being experimental.

As such, the functions here may not remain in their current form, or indeed at all, in l3kernel in the future.

In contrast to the material in l3experimental, the functions here are all *small* additions to the kernel. We encourage programmers to test them out and report back on the **LaTeX-L** mailing list.

Thus, if you intend to use any of these functions from the candidate module in a public package offered to others for productive use (e.g., being placed on CTAN) please consider the following points carefully:

- Be prepared that your public packages might require updating when such functions are being finalized.
- Consider informing us that you use a particular function in your public package, e.g., by discussing this on the **LaTeX-L** mailing list. This way it becomes easier to coordinate any updates necessary without issues for the users of your package.
- Discussing and understanding use cases for a particular addition or concept also helps to ensure that we provide the right interfaces in the final version so please give us feedback if you consider a certain candidate function useful (or not).

We only add functions in this space if we consider them being serious candidates for a final inclusion into the kernel. However, real use sometimes leads to better ideas, so functions from this module are **not necessarily stable** and we may have to adjust them!

2 Additions to l3basics

`\debug_on:n`
`\debug_off:n`

New: 2017-07-16
Updated: 2017-08-02

`\debug_on:n { <comma-separated list> }`
`\debug_off:n { <comma-separated list> }`

Turn on and off within a group various debugging code, some of which is also available as expl3 load-time options. The items that can be used in the *<list>* are

- **check-declarations** that checks all expl3 variables used were previously declared and that local/global variables (based on their name or on their first assignment) are only locally/globally assigned;
- **check-expressions** that checks integer, dimension, skip, and muskip expressions are not terminated prematurely;
- **deprecation** that makes soon-to-be-deprecated commands produce errors;
- **log-functions** that logs function definitions;
- **all** that does all of the above.

Providing these as switches rather than options allows testing code even if it relies on other packages: load all other packages, call `\debug_on:n`, and load the code that one is interested in testing. These functions can only be used in L^AT_EX 2_ε package mode loaded with **enable-debug** or another option implying it.

`\debug_suspend:`
`\debug_resume:`

New: 2017-11-28

`\debug_suspend: ... \debug_resume:`

Suppress (locally) errors and logging from **debug** commands, except for the **deprecation** errors or warnings. These pairs of commands can be nested. This can be used around pieces of code that are known to fail checks, if such failures should be ignored. See for instance **l3coffins**.

`\mode_leave_vertical:`

New: 2017-07-04

`\mode_leave_vertical:`

Ensures that T_EX is not in vertical (inter-paragraph) mode. In horizontal or math mode this command has no effect, in vertical mode it switches to horizontal mode, and inserts a box of width `\parindent`, followed by the `\everypar` token list.

T_EXhackers note: This results in the contents of the `\everypar` token register being inserted, after `\mode_leave_vertical:` is complete. Notice that in contrast to the L^AT_EX 2_ε `\leavevmode` approach, no box is used by the method implemented here.

3 Additions to l3box

3.1 Viewing part of a box

<code>\box_clip:N</code>	<code>\box_clip:N <box></code>
<code>\box_clip:c</code>	

Clips the $\langle box \rangle$ in the output so that only material inside the bounding box is displayed in the output. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the clipping is applied. The clipping applies within the current \TeX group level.

These functions require the $\text{\LaTeX 2}_{\epsilon}$ native drivers: they do not work with the $\text{\LaTeX 2}_{\epsilon}$ graphics drivers!

\TeX hackers note: Clipping is implemented by the driver, and as such the full content of the box is placed in the output file. Thus clipping does not remove any information from the raw output, and hidden material can therefore be viewed by direct examination of the file.

<code>\box_trim:Nnnnn</code>	<code>\box_trim:Nnnnn <box> {\langle left \rangle} {\langle bottom \rangle} {\langle right \rangle} {\langle top \rangle}</code>
<code>\box_trim:cnnnn</code>	

Adjusts the bounding box of the $\langle box \rangle$ $\langle left \rangle$ is removed from the left-hand edge of the bounding box, $\langle right \rangle$ from the right-hand edge and so fourth. All adjustments are $\langle dimension expressions \rangle$. Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the trim operation is applied. The adjustment applies within the current \TeX group level. The behavior of the operation where the trims requested is greater than the size of the box is undefined.

<code>\box_viewport:Nnnnn</code>	<code>\box_viewport:Nnnnn <box> {\langle llx \rangle} {\langle lly \rangle} {\langle urx \rangle} {\langle ury \rangle}</code>
<code>\box_viewport:cnnnn</code>	

Adjusts the bounding box of the $\langle box \rangle$ such that it has lower-left co-ordinates ($\langle llx \rangle$, $\langle lly \rangle$) and upper-right co-ordinates ($\langle urx \rangle$, $\langle ury \rangle$). All four co-ordinate positions are $\langle dimension expressions \rangle$. Material outside of the bounding box is still displayed in the output unless `\box_clip:N` is subsequently applied. The updated $\langle box \rangle$ is an hbox, irrespective of the nature of the $\langle box \rangle$ before the viewport operation is applied. The adjustment applies within the current \TeX group level.

4 Additions to l3coffins

<code>\coffin_resize:Nnn</code>	<code>\coffin_resize:Nnn <coffin> {\langle width \rangle} {\langle total-height \rangle}</code>
<code>\coffin_resize:cnn</code>	

Resized the $\langle coffin \rangle$ to $\langle width \rangle$ and $\langle total-height \rangle$, both of which should be given as dimension expressions.

<code>\coffin_rotate:Nn</code>	<code>\coffin_rotate:Nn <coffin> {\langle angle \rangle}</code>
<code>\coffin_rotate:cn</code>	

Rotates the $\langle coffin \rangle$ by the given $\langle angle \rangle$ (given in degrees counter-clockwise). This process rotates both the coffin content and poles. Multiple rotations do not result in the bounding box of the coffin growing unnecessarily.

<code>\coffin_scale:Nnn</code>	<code>\coffin_scale:Nnn <coffin> {\langle x-scale \rangle} {\langle y-scale \rangle}</code>
<code>\coffin_scale:cnn</code>	

Scales the $\langle coffin \rangle$ by a factors $\langle x-scale \rangle$ and $\langle y-scale \rangle$ in the horizontal and vertical directions, respectively. The two scale factors should be given as real numbers.

5 Additions to l3expan

<hr/> <code>\prg_generate_conditional_variant:Nnn</code> <hr/>	<code>\prg_generate_conditional_variant:Nnn \langle name \rangle:\langle arg spec \rangle</code> <code>\{\langle variant argument specifiers \rangle\} \{\langle condition specifiers \rangle\}</code>
<hr/> New: 2017-12-12 <hr/>	
Defines argument-specifier variants of conditionals. This is equivalent to running <code>\cs_generate_variant:Nn \langle conditional \rangle \{\langle variant argument specifiers \rangle\}</code> on each <i>\langle conditional \rangle</i> described by the <i>\langle condition specifiers \rangle</i> . These base-form <i>\langle conditionals \rangle</i> are obtained from the <i>\langle name \rangle</i> and <i>\langle arg spec \rangle</i> as described for <code>\prg_new_conditional:Npnn</code> , and they should be defined.	

<hr/> <code>\exp_args_generate:n</code> <hr/>	<code>\exp_args_generate:n \{\langle variant argument specifiers \rangle\}</code>
<hr/> New: 2018-04-04 <hr/>	
Defines <code>\exp_args:N\langle variant \rangle</code> functions for each <i>\langle variant \rangle</i> given in the comma list <i>\{\langle variant argument specifiers \rangle\}</i> . Each <i>\langle variant \rangle</i> should consist of the letters N, c, n, V, v, o, f, x, p and the resulting function is protected if the letter x appears in the <i>\langle variant \rangle</i> . This is only useful for cases where <code>\cs_generate_variant:Nn</code> is not applicable.	

6 Additions to l3fp

<hr/> <code>logb</code> ★ <hr/>	<code>\fp_eval:n { logb(\langle fpexpr \rangle) }</code>
<hr/> New: 2018-11-03 <hr/>	
Determines the exponent of the <i>\langle fpexpr \rangle</i> , namely the floor of the base-10 logarithm of its absolute value. “Division by zero” occurs when evaluating $\log_b(\pm 0) = -\infty$. Other special values are $\log_b(\pm \infty) = +\infty$ and $\log_b(\text{NaN}) = \text{NaN}$. If the operand is a tuple or is NaN, then “invalid operation” occurs and the result is NaN.	

<hr/> <code>\fp_sign:n</code> ★ <hr/>	<code>\fp_sign:n \{\langle fpexpr \rangle\}</code>
<hr/> New: 2018-11-03 <hr/>	
Evaluates the <i>\langle fpexpr \rangle</i> and leaves its sign in the input stream using <code>\fp_eval:n \{sign(\langle result \rangle)\}</code> : +1 for positive numbers and for $+\infty$, -1 for negative numbers and for $-\infty$, ± 0 for ± 0 . If the operand is a tuple or is NaN, then “invalid operation” occurs and the result is 0.	

7 Additions to l3fparray

<hr/> <code>\fparray_new:Nn</code> <hr/>	<code>\fparray_new:Nn \langle fparray var \rangle \{\langle size \rangle\}</code>
<hr/> New: 2018-05-05 <hr/>	
Evaluates the integer expression <i>\langle size \rangle</i> and allocates an <i>\langle floating point array variable \rangle</i> with that number of (zero) entries. The variable name should start with <code>\g_</code> because assignments are always global.	

<hr/> <code>\fparray_count:N</code> ★ <hr/>	<code>\fparray_count:N \langle fparray var \rangle</code>
<hr/> New: 2018-05-05 <hr/>	
Expands to the number of entries in the <i>\langle floating point array variable \rangle</i> . This is performed in constant time.	

<hr/> <code>\fpararray_gset:Nnn</code> <hr/>	<code>\fpararray_gset:Nnn <fpararray var> {<position>} {<value>}</code>
<code>New: 2018-05-05</code>	Stores the result of evaluating the floating point expression <i><value></i> into the <i><floating point array variable></i> at the (integer expression) <i><position></i> . If the <i><position></i> is not between 1 and the <code>\fpararray_count:N</code> , an error occurs. Assignments are always global.

<hr/> <code>\fpararray_gzero:N</code> <hr/>	<code>\fpararray_gzero:N <fpararray var></code>
<code>New: 2018-05-05</code>	Sets all entries of the <i><floating point array variable></i> to +0. Assignments are always global.

<hr/> <code>\fpararray_item:Nn</code> ★	<code>\fpararray_item:Nn <fpararray var> {<position>}</code>
<code>\fpararray_item_to_tl:Nn</code> ★	Applies <code>\fp_use:N</code> or <code>\fp_to_tl:N</code> (respectively) to the floating point entry stored at the (integer expression) <i><position></i> in the <i><floating point array variable></i> . If the <i><position></i> is not between 1 and the <code>\fpararray_count:N</code> , an error occurs.
<code>New: 2018-05-05</code>	

8 Additions to l3file

<hr/> <code>\file_get_md5five_hash:nN</code> <hr/>	<code>\file_get_md5five_hash:nN {<file name>} <str var></code>
<code>New: 2017-07-11</code>	Searches for <i><file name></i> using the current T _E X search path and the additional paths controlled by <code>\file_path_include:n</code> . If found, sets the <i><str var></i> to the MD5 sum generated from the content of the file. The file is read as bytes, which means that in contrast to most T _E X behaviour there will be a difference in result depending on the line endings used in text files. The same file will produce the same result between different engines: the algorithm used is the same in all cases. Where the file is not found, the <i><str var></i> will be empty.

<hr/> <code>\file_get_size:nN</code> <hr/>	<code>\file_get_size:nN {<file name>} <str var></code>
<code>New: 2017-07-09</code>	Searches for <i><file name></i> using the current T _E X search path and the additional paths controlled by <code>\file_path_include:n</code> . If found, sets the <i><str var></i> to the size of the file in bytes. Where the file is not found, the <i><str var></i> will be empty. This is not available in older versions of X _Ǝ T _E X.

<hr/> <code>\file_get_timestamp:nN</code> <hr/>	<code>\file_get_timestamp:nN {<file name>} <str var></code>
<code>New: 2017-07-09</code>	Searches for <i><file name></i> using the current T _E X search path and the additional paths controlled by <code>\file_path_include:n</code> . If found, sets the <i><str var></i> to the modification timestamp of the file in the form D:<year><month><day><hour><minute><second><offset>, where the latter may be Z (UTC) or <plus-minus><hours>'<minutes>'. Where the file is not found, the <i><str var></i> will be empty. This is not available in older versions of X _Ǝ T _E X.

<hr/> <code>\file_if_exist_input:n</code>	<code>\file_if_exist_input:n {<file name>}</code>
<code>\file_if_exist_input:nF</code>	<code>\file_if_exist_input:nF {<file name>} {<false code>}</code>
<code>New: 2014-07-02</code>	Searches for <i><file name></i> using the current T _E X search path and the additional paths controlled by <code>\file_path_include:n</code> . If found then reads in the file as additional L ^A T _E X source as described for <code>\file_input:n</code> , otherwise inserts the <i><false code></i> . Note that these functions do not raise an error if the file is not found, in contrast to <code>\file_input:n</code> .

<hr/> <code>\file_input_stop:</code> <hr/>	<code>\file_input_stop:</code>
<hr/> New: 2017-07-07 <hr/>	Ends the reading of a file started by <code>\file_input:n</code> or similar before the end of the file is reached. Where the file reading is being terminated due to an error, <code>\msg_critical:nn(nn)</code> should be preferred.

TeXhackers note: This function must be used on a line on its own: TeX reads files line-by-line and so any additional tokens in the “current” line will still be read.

This is also true if the function is hidden inside another function (which will be the normal case), i.e., all tokens on the same line in the source file are still processed. Putting it on a line by itself in the definition doesn’t help as it is the line where it is used that counts!

<hr/> <code>\ior_map_variable:NNn</code> <hr/>	<code>\ior_map_variable:NNn <stream> <tl var> {<code>}</code>
<hr/> New: 2019-01-13 <hr/>	For each set of <i><lines></i> obtained by calling <code>\ior_get:NN</code> until reaching the end of the file, stores the <i><lines></i> in the <i><tl var></i> then applies the <i><code></i> . The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. TeX ignores any trailing new-line marker from the file it reads. This function is typically faster than <code>\ior_map_inline:Nn</code> .

<hr/> <code>\ior_str_map_variable:NNn</code> <hr/>	<code>\ior_str_map_variable:NNn <stream> <tl var> {<code>}</code>
<hr/> New: 2019-01-13 <hr/>	For each <i><line></i> in the <i><stream></i> , stores the <i><line></i> in the <i><tl var></i> then applies the <i><code></i> . The material is read from the <i><stream></i> as a series of tokens with category code 12 (other), with the exception of space characters which are given category code 10 (space). The <i><code></i> will usually make use of the <i><variable></i> , but this is not enforced. The assignments to the <i><variable></i> are local. Note that TeX removes trailing space and tab characters (character codes 32 and 9) from every line upon input. TeX also ignores any trailing new-line marker from the file it reads. This function is typically faster than <code>\ior_str_map_inline:Nn</code> .

<hr/> <code>\iow_allow_break:</code> <hr/>	<code>\iow_allow_break:</code>
<hr/> New: 2018-12-29 <hr/>	In the first argument of <code>\iow_wrap:nnnN</code> (for instance in messages), inserts a break-point that allows a line break. In other words this is a zero-width breaking space.

9 Additions to l3flag

<hr/> <code>\flag_raise_if_clear:n ★</code> <hr/>	<code>\flag_raise_if_clear:n {<flag name>}</code>
<hr/> New: 2018-04-02 <hr/>	Ensures the <i><flag></i> is raised by making its height at least 1, locally.

10 Additions to l3int

<hr/> <code>\int_sign:n ★</code> <hr/>	<code>\int_sign:n {<intexpr>}</code>
<hr/> New: 2018-11-03 <hr/>	Evaluates the <i><integer expression></i> then leaves 1 or 0 or −1 in the input stream according to the sign of the result.

11 Additions to l3intarray

`\intarray_gset_rand:Nnn`
`\intarray_gset_rand:Nn`

New: 2018-05-05

`\intarray_gset_rand:Nnn` $\langle\textit{intarray var}\rangle$ $\{\langle\textit{minimum}\rangle\}$ $\{\langle\textit{maximum}\rangle\}$
`\intarray_gset_rand:Nn` $\langle\textit{intarray var}\rangle$ $\{\langle\textit{maximum}\rangle\}$

Evaluates the integer expressions $\langle\textit{minimum}\rangle$ and $\langle\textit{maximum}\rangle$ then sets each entry (independently) of the $\langle\textit{integer array variable}\rangle$ to a pseudo-random number between the two (with bounds included). If the absolute value of either bound is bigger than $2^{30} - 1$, an error occurs. Entries are generated in the same way as repeated calls to `\int_rand:nn` or `\int_rand:n` respectively, in particular for the second function the $\langle\textit{minimum}\rangle$ is 1. Assignments are always global. This is not available in older versions of X_ƎTeX.

11.1 Working with contents of integer arrays

`\intarray_const_from_clist:Nn` ☆

New: 2018-05-04

`\intarray_const_from_clist:Nn` $\langle\textit{intarray var}\rangle$ $\langle\textit{intexpr clist}\rangle$

Creates a new constant $\langle\textit{integer array variable}\rangle$ or raises an error if the name is already taken. The $\langle\textit{integer array variable}\rangle$ is set (globally) to contain as its items the results of evaluating each $\langle\textit{integer expression}\rangle$ in the $\langle\textit{comma list}\rangle$.

`\intarray_to_clist:N` ☆

New: 2018-05-04

`\intarray_to_clist:N` $\langle\textit{intarray var}\rangle$

Converts the $\langle\textit{intarray}\rangle$ to integer denotations separated by commas. All tokens have category code other. If the $\langle\textit{intarray}\rangle$ has no entry the result is empty; otherwise the result has one fewer comma than the number of items.

`\intarray_show:N`
`\intarray_log:N`

New: 2018-05-04

`\intarray_show:N` $\langle\textit{intarray var}\rangle$
`\intarray_log:N` $\langle\textit{intarray var}\rangle$

Displays the items in the $\langle\textit{integer array variable}\rangle$ in the terminal or writes them in the log file.

12 Additions to l3msg

In very rare cases it may be necessary to produce errors in an expansion-only context. The functions in this section should only be used if there is no alternative approach using `\msg_error:nnnnnn` or other non-expandable commands from the previous section. Despite having a similar interface as non-expandable messages, expandable errors must be handled internally very differently from normal error messages, as none of the tools to print to the terminal or the log file are expandable. As a result, the message text and arguments are not expanded, and messages must be very short (with default settings, they are truncated after approximately 50 characters). It is advisable to ensure that the message is understandable even when truncated. Another particularity of expandable messages is that they cannot be redirected or turned off by the user.

<code>\msg_expandable_error:nnnnnn</code>	★	<code>\msg_expandable_error:nnnnnn {<module>} {<message>} {<arg one>} {<arg</code>
<code>\msg_expandable_error:nnffff</code>	★	<code>two}> {<arg three>} {<arg four>}</code>
<code>\msg_expandable_error:nnnnn</code>	★	
<code>\msg_expandable_error:nnfff</code>	★	
<code>\msg_expandable_error:nnnn</code>	★	
<code>\msg_expandable_error:nnff</code>	★	
<code>\msg_expandable_error:nnn</code>	★	
<code>\msg_expandable_error:nnf</code>	★	
<code>\msg_expandable_error:nn</code>	★	

New: 2015-08-06

Issues an “Undefined error” message from T_EX itself using the undefined control sequence `\::error` then prints “! <module>: ”<error message>, which should be short. With default settings, anything beyond approximately 60 characters long (or bytes in some engines) is cropped. A leading space might be removed as well.

<code>\msg_show_eval:Nn</code>	<code>\msg_show_eval:Nn <function> {<expression>}</code>
<code>\msg_log_eval:Nn</code>	

New: 2017-12-04

Shows or logs the <expression> (turned into a string), an equal sign, and the result of applying the <function> to the {<expression>} (with f-expansion). For instance, if the <function> is `\int_eval:n` and the <expression> is `1+2` then this logs `> 1+2=3`.

<code>\msg_show:nnnnnn</code>	<code>\msg_show:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg</code>
<code>\msg_show:nnxxxx</code>	<code>four}></code>
<code>\msg_show:nnnnn</code>	
<code>\msg_show:nnxxx</code>	
<code>\msg_show:nnnn</code>	
<code>\msg_show:nnxx</code>	
<code>\msg_show:nnn</code>	
<code>\msg_show:nnx</code>	
<code>\msg_show:nn</code>	

New: 2017-12-04

Issues <module> information <message>, passing <arg one> to <arg four> to the text-creating functions. The information text is shown on the terminal and the T_EX run is interrupted in a manner similar to `\tl_show:n`. This is used in conjunction with `\msg_show_item:n` and similar functions to print complex variable contents completely. If the formatted text does not contain `>~` at the start of a line, an additional line `>~`. will be put at the end. In addition, a final period is added if not present.

<code>\msg_show_item:n</code>	★	<code>\seq_map_function:NN <seq> \msg_show_item:n</code>
<code>\msg_show_item_unbraced:n</code>	★	<code>\prop_map_function:NN <prop> \msg_show_item:nn</code>
<code>\msg_show_item:nn</code>	★	
<code>\msg_show_item_unbraced:nn</code>	★	

New: 2017-12-04

Used in the text of messages for `\msg_show:nnxxxx` to show or log a list of items or key-value pairs. The one-argument functions are used for sequences, clist or token lists and the others for property lists. These functions turn their arguments to strings.

13 Additions to l3prg

<code>\bool_const:Nn</code>	<code>\bool_const:Nn <boolean> {<boolexpr>}</code>
<code>\bool_const:cn</code>	

New: 2017-11-28

Creates a new constant <boolean> or raises an error if the name is already taken. The value of the <boolean> is set globally to the result of evaluating the <boolexpr>.

```
\bool_set_inverse:N
\bool_set_inverse:c
\bool_gset_inverse:N
\bool_gset_inverse:c
```

New: 2018-05-10

```
\bool_set_inverse:N <boolean>
```

Toggles the $\langle boolean \rangle$ from `true` to `false` and conversely: sets it to the inverse of its current value.

14 Additions to l3prop

```
\prop_count:N ★
\prop_count:c ★
```

```
\prop_count:N <property list>
```

Leaves the number of key–value pairs in the $\langle property list \rangle$ in the input stream as an $\langle integer denotation \rangle$.

```
\prop_map_tokens:Nn ★
\prop_map_tokens:cn ★
```

```
\prop_map_tokens:Nn <property list> {<code>}
```

Analogue of `\prop_map_function:NN` which maps several tokens instead of a single function. The $\langle code \rangle$ receives each key–value pair in the $\langle property list \rangle$ as two trailing brace groups. For instance,

```
\prop_map_tokens:Nn \l_my_prop { \str_if_eq:nnT { mykey } }
```

expands to the value corresponding to `mykey`: for each pair in `\l_my_prop` the function `\str_if_eq:nnT` receives `mykey`, the $\langle key \rangle$ and the $\langle value \rangle$ as its three arguments. For that specific task, `\prop_item:Nn` is faster.

```
\prop_rand_key_value:N ★
\prop_rand_key_value:c ★
```

New: 2016-12-06

```
\prop_rand_key_value:N <prop var>
```

Selects a pseudo-random key–value pair from the $\langle property list \rangle$ and returns $\{\langle key \rangle\}$ and $\{\langle value \rangle\}$. If the $\langle property list \rangle$ is empty the result is empty. This is not available in older versions of Xe_{La}TeX.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the $\langle value \rangle$ does not expand further when appearing in an `x`-type argument expansion.

```
\prop_set_from_keyval:Nn
\prop_set_from_keyval:cn
\prop_gset_from_keyval:Nn
\prop_gset_from_keyval:cn
```

New: 2017-11-28

```
\prop_set_from_keyval:Nn <prop var>
```

```
{
<key1> = <value1> ,
<key2> = <value2> , ...
}
```

Sets $\langle prop var \rangle$ to contain key–value pairs given in the second argument.

```
\prop_const_from_keyval:Nn
\prop_const_from_keyval:cn
```

New: 2017-11-28

```
\prop_const_from_keyval:Nn <prop var>
```

```
{
<key1> = <value1> ,
<key2> = <value2> , ...
}
```

Creates a new constant $\langle prop var \rangle$ or raises an error if the name is already taken. The $\langle prop var \rangle$ is set globally to contain key–value pairs given in the second argument.

15 Additions to l3seq

<code>\seq_mapthread_function:NNN</code>	☆	<code>\seq_mapthread_function:NNN <seq1> <seq2> <function></code>
<code>\seq_mapthread_function:(NcN cNN ccN)</code>	☆	

Applies $\langle function \rangle$ to every pair of items $\langle seq_1-item \rangle$ – $\langle seq_2-item \rangle$ from the two sequences, returning items from both sequences from left to right. The $\langle function \rangle$ receives two `n`-type arguments for each iteration. The mapping terminates when the end of either sequence is reached (*i.e.* whichever sequence has fewer items determines how many iterations occur).

<code>\seq_set_filter:NNn</code>	<code>\seq_set_filter:NNn <sequence1> <sequence2> {\inline boolexpr}</code>
<code>\seq_gset_filter:NNn</code>	

Evaluates the $\langle inline boolexpr \rangle$ for every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline boolexpr \rangle$ receives the $\langle item \rangle$ as `#1`. The sequence of all $\langle items \rangle$ for which the $\langle inline boolexpr \rangle$ evaluated to `true` is assigned to $\langle sequence_1 \rangle$.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

<code>\seq_set_map:NNn</code>	<code>\seq_set_map:NNn <sequence1> <sequence2> {\inline function}</code>
<code>\seq_gset_map:NNn</code>	

New: 2011-12-22

Applies $\langle inline function \rangle$ to every $\langle item \rangle$ stored within the $\langle sequence_2 \rangle$. The $\langle inline function \rangle$ should consist of code which will receive the $\langle item \rangle$ as `#1`. The sequence resulting from `x`-expanding $\langle inline function \rangle$ applied to each $\langle item \rangle$ is assigned to $\langle sequence_1 \rangle$. As such, the code in $\langle inline function \rangle$ should be expandable.

TeXhackers note: Contrarily to other mapping functions, `\seq_map_break:` cannot be used in this function, and would lead to low-level TeX errors.

<code>\seq_const_from_clist:Nn</code>	<code>\seq_const_from_clist:Nn <seq var> {\comma-list}</code>
<code>\seq_const_from_clist:cn</code>	

New: 2017-11-28

Creates a new constant $\langle seq var \rangle$ or raises an error if the name is already taken. The $\langle seq var \rangle$ is set globally to contain the items in the $\langle comma list \rangle$.

<code>\seq_set_from_function:NnN</code>	<code>\seq_set_from_function:NnN <seq var> {\loop code} <function></code>
<code>\seq_gset_from_function:NnN</code>	

New: 2018-04-06

Sets the $\langle seq var \rangle$ equal to a sequence whose items are obtained by `x`-expanding $\langle loop code \rangle$ $\langle function \rangle$. This expansion must result in successive calls to the $\langle function \rangle$ with no nonexpandable tokens in between. More precisely the $\langle function \rangle$ is replaced by a wrapper function that inserts the appropriate separators between items in the sequence. The $\langle loop code \rangle$ must be expandable; it can be for example `\tl_map_function:NN <tl var>` or `\clist_map_function:nN {\clist}` or `\int_step_function:nnnN {\initial value} {\step} {\final value}`.

<code>\seq_set_from_inline_x:Nnn</code>	<code>\seq_set_from_inline_x:Nnn <seq var> {(loop code)} {(inline code)}</code>
<code>\seq_gset_from_inline_x:Nnn</code>	

New: 2018-04-06

Sets the $\langle seq var \rangle$ equal to a sequence whose items are obtained by **x**-expanding $\langle loop code \rangle$ applied to a $\langle function \rangle$ derived from the $\langle inline code \rangle$. A $\langle function \rangle$ is defined, that takes one argument, **x**-expands the $\langle inline code \rangle$ with that argument as #1, then adds appropriate separators to turn the result into an item of the sequence. The **x**-expansion of $\langle loop code \rangle$ $\langle function \rangle$ must result in successive calls to the $\langle function \rangle$ with no nonexpandable tokens in between. The $\langle loop code \rangle$ must be expandable; it can be for example `\tl_map_function:NN <tl var>` or `\clist_map_function:nN {(clist)}` or `\int_step_function:nnnN {(initial value)} {(step)} {(final value)}`, but not the analogous “inline” mappings.

<code>\seq_shuffle:N</code>	<code>\seq_shuffle:N <seq var></code>
<code>\seq_gshuffle:N</code>	

New: 2018-04-29

Sets the $\langle seq var \rangle$ to the result of placing the items of the $\langle seq var \rangle$ in a random order. Each item is (roughly) as likely to end up in any given position.

TeXhackers note: For sequences with more than 13 items or so, only a small proportion of all possible permutations can be reached, because the random seed `\sys_rand_seed` only has 28-bits. The use of `\toks` internally means that sequences with more than 32767 or 65535 items (depending on the engine) cannot be shuffled.

<code>\seq_indexed_map_function:NN</code>	<code>\seq_indexed_map_function:NN <seq var> <function></code>
---	--

New: 2018-05-03

Applies $\langle function \rangle$ to every entry in the $\langle sequence variable \rangle$. The $\langle function \rangle$ should have signature `:nn`. It receives two arguments for each iteration: the $\langle index \rangle$ (namely 1 for the first entry, then 2 and so on) and the $\langle item \rangle$.

<code>\seq_indexed_map_inline:Nn</code>	<code>\seq_indexed_map_inline:Nn <seq var> {(inline function)}</code>
---	---

New: 2018-05-03

Applies $\langle inline function \rangle$ to every entry in the $\langle sequence variable \rangle$. The $\langle inline function \rangle$ should consist of code which receives the $\langle index \rangle$ (namely 1 for the first entry, then 2 and so on) as #1 and the $\langle item \rangle$ as #2.

16 Additions to l3skip

<code>\dim_sign:n</code> ★	<code>\dim_sign:n {(dimexpr)}</code>
----------------------------	--------------------------------------

New: 2018-11-03

Evaluates the $\langle dimexpr \rangle$ then leaves 1 or 0 or -1 in the input stream according to the sign of the result.

<code>\skip_split_finite_else_action:nnNN</code>	<code>\skip_split_finite_else_action:nnNN {(skipexpr)} {(action)}</code>
	$\langle dimen_1 \rangle$ $\langle dimen_2 \rangle$

Checks if the $\langle skipexpr \rangle$ contains finite glue. If it does then it assigns $\langle dimen_1 \rangle$ the stretch component and $\langle dimen_2 \rangle$ the shrink component. If it contains infinite glue set $\langle dimen_1 \rangle$ and $\langle dimen_2 \rangle$ to 0pt and place #2 into the input stream: this is usually an error or warning message of some sort.

17 Additions to l3sys

<code>\c_sys_engine_version_str</code>
New: 2018-05-02

The version string of the current engine, in the same form as given in the banner issued when running a job. For pdfTeX and LuaTeX this is of the form

$$\langle major \rangle . \langle minor \rangle . \langle revision \rangle$$

For XeTeX, the form is

$$\langle major \rangle . \langle minor \rangle$$

For pTeX and upTeX, only releases since TeX Live 2018 make the data available, and the form is more complex, as it comprises the pTeX version, the upTeX version and the e-pTeX version.

$$p \langle major \rangle . \langle minor \rangle . \langle revision \rangle - u \langle major \rangle . \langle minor \rangle - \langle epTeX \rangle$$

where the `u` part is only present for upTeX.

<code>\sys_if_rand_exist_p:</code> ★
<code>\sys_if_rand_exist:TF</code> ★
New: 2017-05-27

`\sys_if_rand_exist_p:`
`\sys_if_rand_exist:TF` $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$

Tests if the engine has a pseudo-random number generator. Currently this is the case in pdfTeX, LuaTeX, pTeX and upTeX.

<code>\sys_rand_seed:</code> ★
New: 2017-05-27

`\sys_rand_seed:`

Expands to the current value of the engine's random seed, a non-negative integer. In engines without random number support this expands to 0.

<code>\sys_gset_rand_seed:n</code>
New: 2017-05-27

`\sys_gset_rand_seed:n` $\{\langle intexpr \rangle\}$

Globally sets the seed for the engine's pseudo-random number generator to the $\langle integer\ expression \rangle$. This random seed affects all `\..._rand` functions (such as `\int_rand:nn` or `\clist_rand_item:n`) as well as other packages relying on the engine's random number generator. In engines without random number support this produces an error.

TeXhackers note: While a 32-bit (signed) integer can be given as a seed, only the absolute value is used and any number beyond 2^{28} is divided by an appropriate power of 2. We recommend using an integer in $[0, 2^{28} - 1]$.

<code>\sys_if_platform_unix_p:</code> ★	<code>\sys_if_platform_unix:TF</code> $\{\langle true\ code \rangle\}$ $\{\langle false\ code \rangle\}$
<code>\sys_if_platform_unix:TF</code> ★	
<code>\sys_if_platform_windows_p:</code> ★	
<code>\sys_if_platform_windows:TF</code> ★	
New: 2018-07-27	

Conditionals which allow platform-specific code to be used. The names follow the Lua `os.type()` function, *i.e.* all Unix-like systems are `unix` (including Linux and MacOS).

<code>\c_sys_platform_str</code>
New: 2018-07-27

The current platform given as a lower case string: one of `unix`, `windows` or `unknown`.

<code>\c_sys_shell_escape_int</code>	This variable exposes the internal triple of the shell escape status. The possible values are
New: 2017-05-27	

- 0 Shell escape is disabled
- 1 Unrestricted shell escape is enabled
- 2 Restricted shell escape is enabled

<code>\sys_if_shell_p: *</code>	<code>\sys_if_shell_p:</code>
<code>\sys_if_shell:TF *</code>	<code>\sys_if_shell:TF {⟨true code⟩} {⟨false code⟩}</code>
New: 2017-05-27	Performs a check for whether shell escape is enabled. This returns true if either of restricted or unrestricted shell escape is enabled.

<code>\sys_if_shell_unrestricted_p: *</code>	<code>\sys_if_shell_unrestricted_p:</code>
<code>\sys_if_shell_unrestricted:TF *</code>	<code>\sys_if_shell_unrestricted:TF {⟨true code⟩} {⟨false code⟩}</code>
New: 2017-05-27	

Performs a check for whether *unrestricted* shell escape is enabled.

<code>\sys_if_shell_restricted_p: *</code>	<code>\sys_if_shell_restricted_p:</code>
<code>\sys_if_shell_restricted:TF *</code>	<code>\sys_if_shell_restricted:TF {⟨true code⟩} {⟨false code⟩}</code>
New: 2017-05-27	

Performs a check for whether *restricted* shell escape is enabled. This returns false if unrestricted shell escape is enabled. Unrestricted shell escape is not considered a superset of restricted shell escape in this case. To find whether any shell escape is enabled use `\sys_if_shell:`.

<code>\sys_shell_now:n</code>	<code>\sys_shell_now:n {⟨tokens⟩}</code>
<code>\sys_shell_now:x</code>	Execute <code>⟨tokens⟩</code> through shell escape immediately.
New: 2017-05-27	

<code>\sys_shell_shipout:n</code>	<code>\sys_shell_shipout:n {⟨tokens⟩}</code>
<code>\sys_shell_shipout:x</code>	Execute <code>⟨tokens⟩</code> through shell escape at shipout.
New: 2017-05-27	

18 Additions to l3tl

<code>\tl_if_single_token_p:n *</code>	<code>\tl_if_single_token_p:n {⟨token list⟩}</code>
<code>\tl_if_single_token:nTF *</code>	<code>\tl_if_single_token:nTF {⟨token list⟩} {⟨true code⟩} {⟨false code⟩}</code>

Tests if the token list consists of exactly one token, *i.e.* is either a single space character or a single “normal” token. Token groups (`{...}`) are not single tokens.

<code>\tl_reverse_tokens:n</code>	<code>\tl_reverse_tokens:n {<tokens>}</code>
-----------------------------------	--

This function, which works directly on \TeX tokens, reverses the order of the $\langle tokens \rangle$: the first becomes the last and the last becomes first. Spaces are preserved. The reversal also operates within brace groups, but the braces themselves are not exchanged, as this would lead to an unbalanced token list. For instance, `\tl_reverse_tokens:n {a~{b()}}` leaves `{() (b)~a` in the input stream. This function requires two steps of expansion.

\TeX hackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the token list does not expand further when appearing in an x-type argument expansion.

<code>\tl_count_tokens:n</code>	<code>\tl_count_tokens:n {<tokens>}</code>
---------------------------------	--

Counts the number of \TeX tokens in the $\langle tokens \rangle$ and leaves this information in the input stream. Every token, including spaces and braces, contributes one to the total; thus for instance, the token count of `a~{bc}` is 6. This function requires three expansions, giving an $\langle integer denotation \rangle$.

<code>\tl_lower_case:n</code>	<code>\tl_upper_case:n {<tokens>}</code>
<code>\tl_upper_case:n</code>	<code>\tl_upper_case:nn {<language>} {<tokens>}</code>
<code>\tl_mixed_case:n</code>	
<code>\tl_lower_case:nn</code>	
<code>\tl_upper_case:nn</code>	
<code>\tl_mixed_case:nn</code>	

New: 2014-06-30
Updated: 2016-01-12

These functions are intended to be applied to input which may be regarded broadly as “text”. They traverse the $\langle tokens \rangle$ and change the case of characters as discussed below. The character code of the characters replaced may be arbitrary: the replacement characters have standard document-level category codes (11 for letters, 12 for letter-like characters which can also be case-changed). Begin-group and end-group characters in the $\langle tokens \rangle$ are normalized and become `{` and `}`, respectively.

Importantly, notice that these functions are intended for working with user text for typesetting. For case changing programmatic data see the `l3str` module and discussion there of `\str_lower_case:n`, `\str_upper_case:n` and `\str_fold_case:n`.

The functions perform expansion on the input in most cases. In particular, input in the form of token lists or expandable functions is expanded *unless* it falls within one of the special handling classes described below. This expansion approach means that in general the result of case changing matches the “natural” outcome expected from a “functional” approach to case modification. For example

```
\tl_set:Nn \l_tmpa_tl { hello }
\tl_upper_case:n { \l_tmpa_tl \c_space_tl world }
```

produces

HELLO WORLD

The expansion approach taken means that in package mode any $\LaTeX 2_{\epsilon}$ “robust” commands which may appear in the input should be converted to engine-protected versions using for example the `\robustify` command from the `etoolbox` package.

`\l_tl_case_change_math_tl`

Case changing does not take place within math mode material so for example

```
\tl_upper_case:n { Some~text~$y = mx + c$~with~{Braces} }
```

becomes

```
SOME TEXT $y = mx + c$ WITH {BRACES}
```

Material inside math mode is left entirely unchanged: in particular, no expansion is undertaken.

Detection of math mode is controlled by the list of tokens in `\l_tl_case_change_math_tl`, which should be in open-close pairs. In package mode the standard settings is

```
$ $ \ ( \)
```

Note that while expansion occurs when searching the text it does not apply to math mode material (which should be unaffected by case changing). As such, whilst the opening token for math mode may be “hidden” inside a command/macro, the closing one cannot be as this is being searched for in math mode. Typically, in the types of “text” the case changing functions are intended to apply to this should not be an issue.

`\l_tl_case_change_exclude_tl`

Case changing can be prevented by using any command on the list `\l_tl_case_change_exclude_tl`. Each entry should be a function to be followed by one argument: the latter will be preserved as-is with no expansion. Thus for example following

```
\tl_put_right:Nn \l_tl_case_change_exclude_tl { \NoChangeCase }
```

the input

```
\tl_upper_case:n  
{ Some~text~$y = mx + c$~with~\NoChangeCase {Protection} }
```

will result in

```
SOME TEXT $y = mx + c$ WITH \NoChangeCase {Protection}
```

Notice that the case changing mapping preserves the inclusion of the escape functions: it is left to other code to provide suitable definitions (typically equivalent to `\use:n`). In particular, the result of case changing is returned protected by `\exp_not:n`.

When used with $\text{\LaTeX} 2_{\epsilon}$ the commands `\cite`, `\ensuremath`, `\label` and `\ref` are automatically included in the list for exclusion from case changing.

`\l_t1_case_change_accents_t1`

This list specifies accent commands which should be left unexpanded in the output. This allows for example

```
\tl_upper_case:n { \" { a } }
```

to yield

```
\" { A }
```

irrespective of the expandability of `\"`.

The standard contents of this variable is `\", \', \., \^, \', \~, \c, \H, \k, \r, \t, \u` and `\v`.

“Mixed” case conversion may be regarded informally as converting the first character of the *<tokens>* to upper case and the rest to lower case. However, the process is more complex than this as there are some situations where a single lower case character maps to a special form, for example *ij* in Dutch which becomes *IJ*. As such, `\tl_mixed_case:n(n)` implement a more sophisticated mapping which accounts for this and for modifying accents on the first letter. Spaces at the start of the *<tokens>* are ignored when finding the first “letter” for conversion.

```
\tl_mixed_case:n { hello~WORLD } % => "Hello world"
\tl_mixed_case:n { ~hello~WORLD } % => " Hello world"
\tl_mixed_case:n { {hello}~WORLD } % => "{Hello} world"
```

When finding the first “letter” for this process, any content in math mode or covered by `\l_t1_case_change_exclude_t1` is ignored.

(Note that the Unicode Consortium describe this as “title case”, but that in English title case applies on a word-by-word basis. The “mixed” case implemented here is a lower level concept needed for both “title” and “sentence” casing of text.)

`\l_t1_mixed_case_ignore_t1`

The list of characters to ignore when searching for the first “letter” in mixed-casing is determined by `\l_t1_mixed_change_ignore_t1`. This has the standard setting

```
( [ { ' -
```

where comparisons are made on a character basis.

As is generally true for `expl3`, these functions are designed to work with Unicode input only. As such, UTF-8 input is assumed for *all* engines. When used with `XƎTeX` or `LuaTeX` a full range of Unicode transformations are enabled. Specifically, the standard mappings here follow those defined by the [Unicode Consortium](#) in `UnicodeData.txt` and `SpecialCasing.txt`. In the case of 8-bit engines, mappings are provided for characters which can be represented in output typeset using the `T1` font encoding. Thus for example `ä` can be case-changed using `pdfTeX`. For `pTeX` only the ASCII range is covered as the engine treats input outside of this range as east Asian.

Context-sensitive mappings are enabled: language-dependent cases are discussed below. Context detection expands input but treats any unexpandable control sequences as “failures” to match a context.

Language-sensitive conversions are enabled using the *<language>* argument, and follow Unicode Consortium guidelines. Currently, the languages recognised for special handling are as follows.

- Azeri and Turkish (**az** and **tr**). The case pairs I/i-dotless and I-dot/i are activated for these languages. The combining dot mark is removed when lower casing I-dot and introduced when upper casing i-dotless.
- German (**de-alt**). An alternative mapping for German in which the lower case *Eszett* maps to a *großes Eszett*.
- Lithuanian (**lt**). The lower case letters i and j should retain a dot above when the accents grave, acute or tilde are present. This is implemented for lower casing of the relevant upper case letters both when input as single Unicode codepoints and when using combining accents. The combining dot is removed when upper casing in these cases. Note that *only* the accents used in Lithuanian are covered: the behaviour of other accents are not modified.
- Dutch (**nl**). Capitalisation of ij at the beginning of mixed cased input produces IJ rather than Ij. The output retains two separate letters, thus this transformation *is* available using pdfTeX.

Creating additional context-sensitive mappings requires knowledge of the underlying mapping implementation used here. The team are happy to add these to the kernel where they are well-documented (*e.g.* in Unicode Consortium or relevant government publications).

```
\tl_set_from_file:Nnn
\tl_set_from_file:cnn
\tl_gset_from_file:Nnn
\tl_gset_from_file:cnn
```

New: 2014-06-25

```
\tl_set_from_file:Nnn <tl> {<setup>} {<filename>}
```

Defines $\langle tl \rangle$ to the contents of $\langle filename \rangle$. Category codes may need to be set appropriately via the $\langle setup \rangle$ argument.

```
\tl_set_from_file_x:Nnn
\tl_set_from_file_x:cnn
\tl_gset_from_file_x:Nnn
\tl_gset_from_file_x:cnn
```

New: 2014-06-25

```
\tl_set_from_file_x:Nnn <tl> {<setup>} {<filename>}
```

Defines $\langle tl \rangle$ to the contents of $\langle filename \rangle$, expanding the contents of the file as it is read. Category codes and other definitions may need to be set appropriately via the $\langle setup \rangle$ argument.

```
\tl_set_from_shell:Nnn
\tl_set_from_shell:cnn
\tl_gset_from_shell:Nnn
\tl_gset_from_shell:cnn
```

New: 2018-07-23

```
\tl_set_from_shell:Nnn <tl var> {<setup>} {<shell command>}
```

Defines $\langle tl \rangle$ to the text returned by the $\langle shell command \rangle$. Category codes may need to be set appropriately via the $\langle setup \rangle$ argument. If shell escape is disabled, the $\langle tl var \rangle$ will be empty. Note that quote characters (") *cannot* be used inside the $\langle shell command \rangle$.

<code>\tl_range_braced:Nnn</code>	★	<code>\tl_range_braced:Nnn <tl var> {(start index)} {(end index)}</code>
<code>\tl_range_braced:cnn</code>	★	<code>\tl_range_braced:nnn {(token list)} {(start index)} {(end index)}</code>
<code>\tl_range_braced:nnn</code>	★	<code>\tl_range_unbraced:Nnn <tl var> {(start index)} {(end index)}</code>
<code>\tl_range_unbraced:Nnn</code>	★	<code>\tl_range_unbraced:nnn {(token list)} {(start index)} {(end index)}</code>
<code>\tl_range_unbraced:cnn</code>	★	Leaves in the input stream the items from the <i><start index></i> to the <i><end index></i> inclusive, using the same indexing as <code>\tl_range:nnn</code> . Spaces are ignored. Regardless of whether items appear with or without braces in the <i><token list></i> , the <code>\tl_range_braced:nnn</code> function wraps each item in braces, while <code>\tl_range_unbraced:nnn</code> does not (overall it removes an outer set of braces). For instance,
<code>\tl_range_unbraced:nnn</code>	★	

New: 2017-07-15

```

\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { 2 } { 5 } }
\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { -4 } { -1 } }
\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { -2 } { -1 } }
\tl_iow_term:x { \tl_range_braced:nnn { abcd~{e}}f } { 0 } { -1 } }

```

prints `{b}{c}{d}{e}`, `{c}{d}{e}{f}`, `{e}{f}`, and an empty line to the terminal, while

```

\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { 2 } { 5 } }
\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { -4 } { -1 } }
\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { -2 } { -1 } }
\tl_iow_term:x { \tl_range_unbraced:nnn { abcd~{e}}f } { 0 } { -1 } }

```

prints `bcde{}`, `cde{f}`, `e{f}`, and an empty line to the terminal. Because braces are removed, the result of `\tl_range_unbraced:nnn` may have a different number of items as for `\tl_range:nnn` or `\tl_range_braced:nnn`. In cases where preserving spaces is important, consider the slower function `\tl_range:nnn`.

TeXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the *<item>* does not expand further when appearing in an *x*-type argument expansion.

<code>\tl_build_begin:N</code>	<code>\tl_build_begin:N <tl var></code>
<code>\tl_build_gbegin:N</code>	Clears the <i><tl var></i> and sets it up to support other <code>\tl_build_...</code> functions, which allow accumulating large numbers of tokens piece by piece much more efficiently than standard <code>\l3tl</code> functions. Until <code>\tl_build_end:N <tl var></code> is called, applying any function from <code>\l3tl</code> other than <code>\tl_build_...</code> will lead to incorrect results. The <code>begin</code> and <code>gbegin</code> functions must be used for local and global <i><tl var></i> respectively.
New: 2018-04-01	
<code>\tl_build_clear:N</code>	<code>\tl_build_clear:N <tl var></code>
<code>\tl_build_gclear:N</code>	Clears the <i><tl var></i> and sets it up to support other <code>\tl_build_...</code> functions. The <code>clear</code> and <code>gclear</code> functions must be used for local and global <i><tl var></i> respectively.
New: 2018-04-01	

```

\tl_build_put_left:Nn
\tl_build_put_left:Nx
\tl_build_gput_left:Nn
\tl_build_gput_left:Nx
\tl_build_put_right:Nn
\tl_build_put_right:Nx
\tl_build_gput_right:Nn
\tl_build_gput_right:Nx

```

New: 2018-04-01

```

\tl_build_get:NN

```

New: 2018-04-01

```

\tl_build_end:N
\tl_build_gend:N

```

New: 2018-04-01

```

\tl_build_put_left:Nn <tl var> {<tokens>}
\tl_build_put_right:Nn <tl var> {<tokens>}

```

Adds *<tokens>* to the left or right side of the current contents of *<tl var>*. The *<tl var>* must have been set up with `\tl_build_begin:N` or `\tl_build_gbegin:N`. The `put` and `gput` functions must be used for local and global *<tl var>* respectively. The `right` functions are about twice faster than the `left` functions.

```

\tl_build_get:N <tl var1> <tl var2>

```

Stores the contents of the *<tl var₁>* in the *<tl var₂>*. The *<tl var₁>* must have been set up with `\tl_build_begin:N` or `\tl_build_gbegin:N`. The *<tl var₂>* is a “normal” token list variable, assigned locally using `\tl_set:Nn`.

```

\tl_build_end:N <tl var>

```

Gets the contents of *<tl var>* and stores that into the *<tl var>* using `\tl_set:Nn`. The *<tl var>* must have been set up with `\tl_build_begin:N` or `\tl_build_gbegin:N`. The `end` and `gend` functions must be used for local and global *<tl var>* respectively. These functions completely remove the setup code that enabled *<tl var>* to be used for other `\tl_build_...` functions.

19 Additions to l3token

```

\c_catcode_active_space_tl

```

New: 2017-08-07

Token list containing one character with category code 13, (“active”), and character code 32 (space).

```

\char_lower_case:N ★
\char_upper_case:N ★
\char_mixed_case:N ★
\char_fold_case:N ★

```

New: 2018-04-06

```

\char_lower_case:N <char>

```

Converts the *<char>* to the equivalent case-changed character as detailed by the function name (see `\str_fold_case:n` and `\tl_mixed_case:n` for details of these terms). The case mapping is carried out with no context-dependence (*cf.* `\tl_upper_case:n`, *etc.*)

```

\char_codepoint_to_bytes:n ★

```

New: 2018-06-01

```

\char_codepoint_to_bytes:n {<codepoint>}

```

Converts the (Unicode) *<codepoint>* to UTF-8 bytes. The expansion of this function comprises four brace groups, each of which will contain a hexadecimal value: the appropriate byte. As UTF-8 is a variable-length, one or more of the groups may be empty: the bytes read in the logical order, such that a two-byte codepoint will have groups **#1** and **#2** filled and **#3** and **#4** empty.

<code>\peek_N_type:TF</code>	<code>\peek_N_type:TF {<true code>} {<false code>}</code>
------------------------------	---

Updated: 2012-12-20

Tests if the next *<token>* in the input stream can be safely grabbed as an N-type argument. The test is *<false>* if the next *<token>* is either an explicit or implicit begin-group or end-group token (with any character code), or an explicit or implicit space character (with character code 32 and category code 10), or an outer token (never used in L^AT_EX3) and *<true>* in all other cases. Note that a *<true>* result ensures that the next *<token>* is a valid N-type argument. However, if the next *<token>* is for instance `\c_space_token`, the test takes the *<false>* branch, even though the next *<token>* is in fact a valid N-type argument. The *<token>* is left in the input stream after the *<true code>* or *<false code>* (as appropriate to the result of the test).

<code>\peek_catcode_collect_inline:Nn</code>	<code>\peek_catcode_collect_inline:Nn <test token> {<inline code>}</code>
<code>\peek_charcode_collect_inline:Nn</code>	<code>\peek_charcode_collect_inline:Nn <test token> {<inline code>}</code>
<code>\peek_meaning_collect_inline:Nn</code>	<code>\peek_meaning_collect_inline:Nn <test token> {<inline code>}</code>

New: 2018-09-23

Collects and removes tokens from the input stream until finding a token that does not match the *<test token>* (as defined by the test `\token_if_eq_catcode:NNTF` or `\token_if_eq_charcode:NNTF` or `\token_if_eq_meaning:NNTF`). The collected tokens are passed to the *<inline code>* as #1. When begin-group or end-group tokens (usually { or }) are collected they are replaced by implicit `\c_group_begin_token` and `\c_group_end_token`, and when spaces (including `\c_space_token`) are collected they are replaced by explicit spaces.

For example the following code prints “Hello” to the terminal and leave “, world!” in the input stream.

```
\peek_catcode_collect_inline:Nn A { \iow_term:n {#1} } Hello,~world!
```

Another example is that the following code tests if the next token is *, ignoring intervening spaces, but putting them back using #1 if there is no *.

```
\peek_meaning_collect_inline:Nn \c_space_token
{ \peek_charcode:NTF * { star } { no~star #1 } }
```

<code>\peek_remove_spaces:n</code>	<code>\peek_remove_spaces:n {<code>}</code>
------------------------------------	---

New: 2018-10-01

Removes explicit and implicit space tokens (category code 10 and character code 32) from the input stream, then inserts *<code>*.

Part XXXIII

The l3drivers package

Drivers

T_EX relies on drivers in order to carry out a number of tasks, such as using color, including graphics and setting up hyper-links. The nature of the code required depends on the exact driver in use. Currently, L^AT_EX3 is aware of the following drivers:

- **pdfmode**: The “driver” for direct PDF output by *both* pdfT_EX and LuaT_EX (no separate driver is used in this case: the engine deals with PDF creation itself).
- **dvips**: The dvips program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode.
- **dvipdfmx**: The dvipdfmx program, which works in conjugation with pdfT_EX or LuaT_EX in DVI mode.
- **dvisvgm**: The dvisvgm program, which works in conjugation with pdfT_EX or LuaT_EX when run in DVI mode as well as with (u)pT_EX and X_YT_EX.
- **xdvipdfmx**: The driver used by X_YT_EX.

This module provides code closely tied to the exact driver in use: broadly, the functions here are implemented entirely independently for each case. As such, they often rely on higher-level code to provide necessary but shared operations. For example, in box rotation and scaling the functions here do not correct the final size of the box: this will always be required and thus is handled in the `box` module.

Several of the operations here are low-level, and so may be used only in restricted contexts. Some also require understanding of PostScript/PDF concepts to be used correctly as they take “raw” arguments, similar in format to those used by the underlying driver.

The functions in this module should be regarded as experimental with the following exceptions:

- ...

1 Box clipping

`\driver_box_use_clip:N`

New: 2017-12-13

`\driver_box_use_clip:N` $\langle box \rangle$

Inserts the content of the $\langle box \rangle$ at the current insertion point such that any material outside of the bounding box is not displayed by the driver. The material in the $\langle box \rangle$ is still placed in the output stream: the clipping takes place at a driver level.

2 Box rotation and scaling

`\driver_box_use_rotate:Nn`

New: 2017-12-13
Updated: 2018-04-26

`\driver_box_use_rotate:Nn <box> {<angle>}`

Inserts the content of the `<box>` at the current insertion point rotated by the `<angle>` (an *fp expression*) expressed in degrees). The material is rotated such the the $\mathrm{T\!E\!X}$ reference point of the box is the center of rotation and remains the reference point after rotation. It is the responsibility of the code using this function to adjust the apparent size of the inserted material.

`\driver_box_use_scale:Nnn`

New: 2017-12-13
Updated: 2018-04-26

`\driver_box_use_scale:Nnn <box> {<x-scale>} {<y-scale>}`

Inserts the content of the `<box>` at the current insertion point scale by the `<x-scale>` and `<y-scale>` (both *fp expressions*). The reference point of the material will be unchanged. It is the responsibility of the code using this function to adjust the apparent size of the inserted material.

3 Color support

`\driver_color_cmyk:nnnn`

New: 2018-02-20

`\driver_color_cmyk:nnnn {<cyan>} {<magenta>} {<yellow>} {<black>}`

Sets the color to the CMYK values specified, all of which are fp denotations in the range 0 and 1. For drawing colors, see `\driver_draw_stroke_cmyk:nnnn`, *etc.*

`\driver_color_gray:n`

New: 2018-02-20

`\driver_color_gray:n {<gray>}`

Sets the color to the grayscale value specified, which is fp denotations in the range 0 and 1. For drawing colors, see `\driver_draw_stroke_gray:n`, *etc.*

`\driver_color_rgb:nnn`

New: 2018-02-20

`\driver_color_rgb:nnn {<red>} {<green>} {<blue>}`

Sets the color to the RGB values specified, all of which are fp denotations in the range 0 and 1. For drawing colors, see `\driver_draw_stroke_rgb:nnn`, *etc.*

`\driver_color_pickup:N`

New: 2018-02-20

`\driver_color_pickup:N <tl>`

In $\mathrm{L\!A\!T\!E\!X}\ 2_{\epsilon}$ package mode, collects data on the current color from `\current@color` and stores it in the low-level format used by `expl3` in the `<tl>`.

4 Drawing

The drawing functions provided here are *highly* experimental. They are inspired heavily by the system layer of `pgf` (most have the same interface as the same functions in the latter's `\pgfsys@...` namespace). They are intended to form the basis for higher level drawing interfaces, which themselves are likely to be further abstracted for user access. Again, this model is heavily inspired by `pgf` and `Tikz`.

These low level drawing interfaces abstract from the driver raw requirements but still require an appreciation of the concepts of PostScript/PDF/SVG graphic creation.

<hr/> <hr/>	<code>\driver_draw_begin:</code> <code>\driver_draw_end:</code> <code>\driver_draw_end:</code>	<code>\driver_draw_begin:</code> <code>\driver_draw_end:</code> <code>\driver_draw_end:</code>	<p>Defines a drawing environment. This is a scope for the purposes of the graphics state. Depending on the driver, other set up may or may not take place here. The natural size of the <code>\content</code> should be zero from the T_EX perspective: allowance for the size of the content must be made at a higher level (or indeed this can be skipped if the content is to overlap other material).</p>
<hr/> <hr/>	<code>\driver_draw_scope_begin:</code> <code>\driver_draw_scope_end:</code> <code>\driver_draw_scope_end:</code>	<code>\driver_draw_scope_begin:</code> <code>\driver_draw_scope_end:</code> <code>\driver_draw_scope_end:</code>	<p>Defines a scope for drawing settings and so on. Changes to the graphic state and concepts such as color or linewidth are localised to a scope. This function pair must never be used if an partial path is under construction: such paths must be entirely contained at one unbroken scope level. Note that scopes do not form T_EX groups and may not be aligned with them.</p>
<h2>4.1 Path construction</h2>			
<hr/> <hr/>	<code>\driver_draw_moveto:nn</code>	<code>\driver_draw_move:nn {<x>} {<y>}</code>	Moves the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$; any active transformation matrix applies.
<hr/> <hr/>	<code>\driver_draw_lineto:nn</code>	<code>\driver_draw_lineto:nn {<x>} {<y>}</code>	Adds a path from the current drawing reference point to $(\langle x \rangle, \langle y \rangle)$; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<hr/> <hr/>	<code>\driver_draw_curveto:nnnnnn</code>	<code>\driver_draw_curveto:nnnnnn {<x₁>} {<y₁>} {<x₂>} {<y₂>} {<x₃>} {<y₃>}</code>	Adds a Bezier curve path from the current drawing reference point to $(\langle x_3 \rangle, \langle y_3 \rangle)$, using $(\langle x_1 \rangle, \langle y_1 \rangle)$ and $(\langle x_2 \rangle, \langle y_2 \rangle)$ as control points; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<hr/> <hr/>	<code>\driver_draw_rectangle:nnnn</code>	<code>\driver_draw_rectangle:nnnn {<x>} {<y>} {<width>} {<height>}</code>	Adds rectangular path from $(\langle x_1 \rangle, \langle y_1 \rangle)$ of $\langle height \rangle$ and $\langle width \rangle$; any active transformation matrix applies. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.
<hr/> <hr/>	<code>\driver_draw_closepath:</code>	<code>\driver_draw_closepath:</code>	Closes an existing path, adding a line from the current point to the start of path. Note that nothing is drawn until a fill or stroke operation is applied, and that the path may be discarded or used as a clip without appearing itself.

4.2 Stroking and filling

<code>\driver_draw_stroke:</code>	<code><path construction></code>
<code>\driver_draw_closestroke:</code>	<code>\driver_draw_stroke:</code>

Draws a line along the current path, which is also closed in the case of `\driver_draw_closestroke:`. The nature of the line drawn is influenced by settings for

- Line thickness
- Stroke color (or the current color if no specific stroke color is set)
- Line capping (how non-closed line ends should look)
- Join style (how a bend in the path should be rendered)
- Dash pattern

The path may also be used for clipping.

<code>\driver_draw_fill:</code>	<code><path construction></code>
<code>\driver_draw_fillstroke:</code>	<code>\driver_draw_fill:</code>

Fills the area surrounded by the current path: this will be closed prior to filling if it is not already. The `fillstroke` version also strokes the path as described for `\driver_draw_stroke:`. The fill is influenced by the setting for fill color (or the current color if no specific stroke color is set). The path may also be used for clipping. For paths which are self-intersecting or comprising multiple parts, the determination of which areas are inside the path is made using the non-zero winding number rule unless the even-odd rule is active.

<code>\driver_draw_nonzero_rule:</code>	<code>\driver_draw_nonzero_rule:</code>
<code>\driver_draw_evenodd_rule:</code>	

Active either the non-zero winding number or the even-odd rule, respectively, for determining what is inside a fill or clip area. For technical reasons, these command are not influenced by scoping and apply on an ongoing basis.

<code>\driver_draw_clip:</code>	<code><path construction></code>
	<code>\driver_draw_clip:</code>

Indicates that the current path should be used for clipping, such that any subsequent material outside of the path (but within the current scope) will not be shown. This command should be given once a path is complete but before it is stroked or filled (if appropriate). This command is *not* affected by scoping: it applies to exactly one path as shown.

<code>\driver_draw_discardpath:</code>	<code><path construction></code>
	<code>\driver_draw_discardpath:</code>

Discards the current path without stroking or filling. This is primarily useful for paths constructed purely for clipping, as this alone does not end the paths existence.

4.3 Stroke options

<code>\driver_draw_linewidth:n</code>	<code>\driver_draw_linewidth:n {<dimexpr>}</code>
---------------------------------------	---

Sets the width to be used for stroking to *<dimexpr>*.

<code>\driver_draw_dash_pattern:nn</code>	<code>\driver_draw_dash:nn {<dash pattern>} {<phase>}</code>
---	--

Sets the pattern of dashing to be used when stroking a line. The *<dash pattern>* should be a comma-separated list of dimension expressions. This is then interpreted as a series of pairs of line-on and line-off lengths. For example `3pt, 4pt` means that 3pt on, 4pt off, 3pt on, and so on. A more complex pattern will also repeat: `3pt, 4pt, 1pt, 2pt` results in 3pt on, 4pt off, 1pt on, 2pt off, 3pt on, and so on. An odd number of entries means that the last is repeated, for example `3pt` is equal to `3pt, 3pt`. An empty pattern yields a solid line.

The *<phase>* specifies an offset at the start of the cycle. For example, with a pattern `3pt` a phase of `1pt` means that the output is 2pt on, 3pt off, 3pt on, 3pt on, *etc.*

<code>\driver_draw_cap_but:</code>	<code>\driver_draw_cap_but:</code>
<code>\driver_draw_cap_rectangle:</code>	
<code>\driver_draw_cap_round:</code>	

Sets the style of terminal stroke position to one of butt, rectangle or round.

<code>\driver_draw_join_bevel:</code>	<code>\driver_draw_cap_but:</code>
<code>\driver_draw_join_miter:</code>	
<code>\driver_draw_join_round:</code>	

Sets the style of stroke joins to one of bevel, miter or round.

<code>\driver_draw_miterlimit:n</code>	<code>\driver_draw_miterlimit:n {<factor>}</code>
--	---

Sets the miter limit of lines joined as a miter, as described in the PDF and PostScript manuals. The *<factor>* here is an *<fp expression>*.

4.4 Color

<code>\driver_draw_color_fill_cmyk:nnnn</code>	<code>\driver_draw_color_fill_cmyk:nnnn {<cyan>} {<magenta>} {<yellow>}</code>
<code>\driver_draw_color_stroke_cmyk:nnnn</code>	<code>{<black>}</code>

Sets the color for drawing to the CMYK values specified, all of which are fp denotations in the range 0 and 1.

<code>\driver_draw_color_fill_gray:n</code>	<code>\driver_draw_color_fill_gray:n {<gray>}</code>
<code>\driver_draw_color_stroke_gray:n</code>	

Sets the color for drawing to the grayscale value specified, which is fp denotations in the range 0 and 1.

<code>\driver_draw_color_fill_rgb:nnn</code>	<code>\driver_draw_color_fill_rgb:nnn {<red>} {<green>} {<blue>}</code>
<code>\driver_draw_color_stroke_rgb:nnn</code>	

Sets the color for drawing to the RGB values specified, all of which are fp denotations in the range 0 and 1.

4.5 Inserting T_EX material

`\driver_draw_box_use:Nnnnn`

`\driver_draw_box:Nnnnnnn <box>`
`{<a>} {} {<c>} {<d>} {<x>} {<y>}`

Inserts the `<box>` as an hbox with the box reference point placed at (x, y) . The transformation matrix $[abcd]$ is applied to the box, allowing it to be in synchronisation with any scaling, rotation or skewing applying more generally. Note that T_EX material should not be inserted directly into a drawing as it would not be in the correct location. Also note that as for other drawing elements the box here has no size from a T_EX perspective.

4.6 Coordinate system transformations

`\driver_draw_cm:nnnn`

`\driver_draw_cm:nnnn {<a>} {} {<c>} {<d>}`

Applies the transformation matrix $[abcd]$ to the current graphic state. This affects any subsequent items in the same scope but not those already given.

5 PDF Features

A range of PDF features are exposed by pdfT_EX and LuaT_EX in direct PDF output mode, and the vast majority of these are also controllable using the (x)dvipdfmx driver (as DVI instructions are converted directly to PDF). Some of these functions are also available for cases where PDFs are generated by dvips: this depends on being able to pass information through correctly.

5.1 PDF Objects

Objects are used to provide a range of data structures in a PDF. At the driver level, different PDF object types are declared separately. Objects are only *written* to the PDF when referenced.

`\driver_pdf_object_new:nn`

`\driver_pdf_object_new:n {<name>} {<type>}`

Declares `<name>` as a PDF object. The `type` should be one of `array` or `dict`, `fstream` or `stream`.

`\driver_pdf_object_ref:n ★`

`\driver_pdf_object_ref:n {<object>}`

Inserts the appropriate information to reference the `<object>` in for example page resource allocation.

`\driver_pdf_object_write:nn` `\driver_pdf_object_write:nn` $\{\langle name \rangle\}$ $\{\langle data \rangle\}$

Writes the $\langle data \rangle$ as content of the $\langle object \rangle$. Depending on the $\langle type \rangle$ declared for the object, the format required for the $\langle data \rangle$ will vary

array A space-separated list of values

dict Key-value pairs in the form $/\langle key \rangle$ $\langle value \rangle$

fstream Two brace groups: $\langle content \rangle$ and $\langle file name \rangle$

stream Two brace groups: $\langle content \rangle$ and $\langle additional attributes \rangle$

5.2 PDF structure

`\driver_pdf_compresslevel:n` `\driver_pdf_compresslevel:n` $\{\langle level \rangle\}$

Sets the degree of compression used for PDF files: the $\langle level \rangle$ should be in the range 0 to 9 (higher is more compression). Typically, either compression is disabled (0) or maximised (9). When used with `(x)dvipdfmx`, this setting may only be applied globally: it should be set only once.

`\driver_pdf_objects_enable:` `\driver_pdf_objects_disable:`
`\driver_pdf_objects_disable:`

Enables or disables the creation of PDF objects. These objects are used to reduce the size of PDFs, and typically are enabled as standard. When used with `(x)dvipdfmx`, object creation can be disabled but not re-enabled, and this setting may only be applied globally: it should be set only once.

Part XXXIV

Implementation

1 l3bootstrap implementation

```
1 \*initex | package
2 \@@=kernel
```

1.1 Format-specific code

The very first thing to do is to bootstrap the \TeX system so that everything else will actually work. \TeX does not start with some pretty basic character codes set up.

```
3 \*initex
4 \catcode '\{ = 1 %
5 \catcode '\} = 2 %
6 \catcode '\# = 6 %
7 \catcode '\^ = 7 %
8 \end{initex}
```

Tab characters should not show up in the code, but to be on the safe side.

```

9 <*initex>
10 \catcode '\^^I = 10 %
11 </initex>

```

For LuaTeX, the extra primitives need to be enabled. This is not needed in package mode: common formats have the primitives enabled.

```

12 <*initex>
13 \begingroup\expandafter\expandafter\expandafter\endgroup
14 \expandafter\ifx\csname directlua\endcsname\relax
15 \else
16 \directlua{tex.enableprimitives("", tex.extraprimitives())}%
17 \fi
18 </initex>

```

Depending on the versions available, the L^AT_EX format may not have the raw `\Umath` primitive names available. We fix that globally: it should cause no issues. Older LuaTeX versions do not have a pre-built table of the primitive names here so sort one out ourselves. These end up globally-defined but at that is true with a newer format anyway and as they all start `\U` this should be reasonably safe.

```

19 <*package>
20 \begingroup
21 \expandafter\ifx\csname directlua\endcsname\relax
22 \else
23 \directlua{%
24     local i
25     local t = { }
26     for _,i in pairs(tex.extraprimitives("luatex")) do
27         if string.match(i,"^U") then
28             if not string.match(i,"^Uchar$") then %$
29                 table.insert(t,i)
30             end
31         end
32     end
33     tex.enableprimitives("", t)
34 }%
35 \fi
36 \endgroup
37 </package>

```

1.2 The `\pdfstrcmp` primitive in X_YTeX

Only pdfTeX has a primitive called `\pdfstrcmp`. The X_YTeX version is just `\strcmp`, so there is some shuffling to do. As this is still a real primitive, using the pdfTeX name is “safe”.

```

38 \begingroup\expandafter\expandafter\expandafter\endgroup
39 \expandafter\ifx\csname pdfstrcmp\endcsname\relax
40 \let\pdfstrcmp\strcmp
41 \fi

```

1.3 Loading support Lua code

When LuaTeX is used there are various pieces of Lua code which need to be loaded. The code itself is defined in `l3luatex` and is extracted into a separate file. Thus here the task is to load the Lua code both now and (if required) at the start of each job.

```
42 \begingroup\expandafter\expandafter\expandafter\endgroup
43 \expandafter\ifx\csname directlua\endcsname\relax
44 \else
45   \ifnum\luatexversion<70 %
46   \else
```

In package mode a category code table is needed: either use a pre-loaded allocator or provide one using the L^AT_EX 2_ε-based generic code. In format mode the table used here can be hard-coded into the Lua.

```
47 (*package)
48   \begingroup\expandafter\expandafter\expandafter\endgroup
49   \expandafter\ifx\csname newcatcodetable\endcsname\relax
50     \input{ltluatex}%
51   \fi
52   \newcatcodetable\ucharcat@table
53   \directlua{
54     l3kernel = l3kernel or { }
55     local charcat_table = \number\ucharcat@table\space
56     l3kernel.charcat_table = charcat_table
57   }%
58 \endpackage
59   \directlua{require("expl3")}%
```

As the user might be making a custom format, no assumption is made about matching package mode with only loading the Lua code once. Instead, a query to Lua reveals what mode is in operation.

```
60   \ifnum 0%
61     \directlua{
62       if status.ini_version then
63         tex.write("1")
64       end
65     }>0 %
66     \everyjob\expandafter{%
67       \the\expandafter\everyjob
68       \csname\detokenize{lua_now:n}\endcsname{require("expl3")}%
69     }%
70   \fi
71 \fi
72 \fi
```

1.4 Engine requirements

The code currently requires ε -T_EX and functionality equivalent to `\pdfstrcmp`, and also driver and Unicode character support. This is available in a reasonably-wide range of engines.

```
73 \begingroup
74 \def\next{\endgroup}%
75 \def\ShortText{Required primitives not found}%
76 \def\LongText%
```

```

77  {%
78    LaTeX3 requires the e-TeX primitives and additional functionality as
79    described in the README file.
80    \LineBreak
81    These are available in the engines\LineBreak
82    - pdfTeX v1.40\LineBreak
83    - XeTeX v0.99992\LineBreak
84    - LuaTeX v0.76\LineBreak
85    - e-(u)pTeX mid-2012\LineBreak
86    or later.\LineBreak
87    \LineBreak
88  }%
89  \ifnum0%
90    \expandafter\ifx\csname pdfstrcmp\endcsname\relax
91    \else
92      \expandafter\ifx\csname pdftexversion\endcsname\relax
93        \expandafter\ifx\csname Ucharcat\endcsname\relax
94          \expandafter\ifx\csname kanjiskip\endcsname\relax
95            \else
96              1%
97            \fi
98          \else
99            1%
100          \fi
101        \else
102          \ifnum\pdftexversion<140 \else 1\fi
103        \fi
104      \fi
105      \expandafter\ifx\csname directlua\endcsname\relax
106      \else
107        \ifnum\luatexversion<76 \else 1\fi
108      \fi
109      =0 %
110      \newlinechar'\^^J %
111  \<{*initex}
112    \def\LineBreak{^^J}%
113    \edef\next
114      {%
115        \errhelp
116        {%
117          \LongText
118          For pdfTeX and XeTeX the '-etex' command-line switch is also
119          needed.\LineBreak
120          \LineBreak
121          Format building will abort!\LineBreak
122        }%
123        \errmessage{\ShortText}%
124      \endgroup
125      \noexpand\end
126    }%
127  \</initex}
128  \<{*package}
129    \def\LineBreak{\noexpand\MessageBreak}%
130    \expandafter\ifx\csname PackageError\endcsname\relax

```

```

131     \def\LineBreak{^^J}%
132     \def\PackageError#1#2#3%
133     {%
134         \errhelp{#3}%
135         \errmessage{#1 Error: #2}%
136     }%
137 \fi
138 \edef\next
139 {%
140     \noexpand\PackageError{expl3}{\ShortText}
141     {\LongText Loading of expl3 will abort!}%
142     \endgroup
143     \noexpand\endinput
144 }%
145 \</package>
146 \fi
147 \next

```

1.5 Extending allocators

In format mode, allocating registers is handled by `l3alloc`. However, in package mode it’s much safer to rely on more general code. For example, the ability to extend \TeX ’s allocation routine to allow for $\varepsilon\text{-}\text{\TeX}$ has been around since 1997 in the `etex` package.

Loading this support is delayed until here as we are now sure that the $\varepsilon\text{-}\text{\TeX}$ extensions and `\pdfstrcmp` or equivalent are available. Thus there is no danger of an “uncontrolled” error if the engine requirements are not met.

For $\text{\LaTeX}2_{\varepsilon}$ we need to make sure that the extended pool is being used: `expl3` uses a lot of registers. For formats from 2015 onward there is nothing to do as this is automatic. For older formats, the `etex` package needs to be loaded to do the job. In that case, some inserts are reserved also as these have to be from the standard pool. Note that `\reserveinserts` is `\outer` and so is accessed here by `csname`. In earlier versions, loading `etex` was done directly and so `\reserveinserts` appeared in the code: this then required a `\relax` after `\RequirePackage` to prevent an error with “unsafe” definitions as seen for example with `capoptions`. The optional loading here is done using a group and `\ifx` test as we are not quite in the position to have a single name for `\pdfstrcmp` just yet.

```

148 \<*package>
149 \begingroup
150   \def\@tempa{LaTeX2e}%
151   \def\next{}%
152   \ifx\fmtname\@tempa
153     \expandafter\ifx\csname extrafloats\endcsname\relax
154       \def\next
155       {%
156         \RequirePackage{etex}%
157         \csname reserveinserts\endcsname{32}%
158       }%
159   \fi
160   \fi
161 \expandafter\endgroup
162 \next
163 \</package>

```

1.6 Character data

T_EX needs various pieces of data to be set about characters, in particular which ones to treat as letters and which \lccode values apply as these affect hyphenation. It makes most sense to set this and related information up in one place. Whilst for LuaT_EX hyphenation patterns can be read anywhere, other engines have to build them into the format and so we *must* do this set up before reading the patterns. For the Unicode engines, there are shared loaders available to obtain the relevant information directly from the Unicode Consortium data files. These need standard (Ini)T_EX category codes and primitive availability and must therefore be loaded *very* early. This has a knock-on effect on the 8-bit set up: it makes sense to do the definitions for those here as well so it is all in one place.

For X_YT_EX and LuaT_EX, which are natively Unicode engines, simply load the Unicode data.

```
164 <*initex>
165 \ifdefined\Umathcode
166   \input load-unicode-data %
167   \input load-unicode-math-classes %
168 \else
```

For the 8-bit engines a font encoding scheme must be chosen. At present, this is the EC (T1) scheme, with the assumption that languages for which this is not appropriate will be used with one of the Unicode engines.

```
169 \begingroup
```

Lower case chars: map to themselves when lower casing and down by "20 when upper casing. (The characters a–z are set up correctly by iniT_EX.)

```
170   \def\temp{%
171     \ifnum\count0>\count2 %
172     \else
173       \global\lccode\count0 = \count0 %
174       \global\uccode\count0 = \numexpr\count0 - "20\relax
175       \advance\count0 by 1 %
176       \expandafter\temp
177     \fi
178   }
179   \count0 = "A0 %
180   \count2 = "BC %
181   \temp
182   \count0 = "E0 %
183   \count2 = "FF %
184   \temp
```

Upper case chars: map up by "20 when lower casing, to themselves when upper casing and require an \sfcode of 999. (The characters A–Z are set up correctly by iniT_EX.)

```
185   \def\temp{%
186     \ifnum\count0>\count2 %
187     \else
188       \global\lccode\count0 = \numexpr\count0 + "20\relax
189       \global\uccode\count0 = \count0 %
190       \global\sfcode\count0 = 999 %
191       \advance\count0 by 1 %
192       \expandafter\temp
193     \fi
```

```

194 }
195 \count0 = "80 %
196 \count2 = "9C %
197 \temp
198 \count0 = "C0 %
199 \count2 = "DF %
200 \temp

```

A few special cases where things are not as one might expect using the above pattern: dotless-I, dotless-J, dotted-I and d-bar.

```

201 \global\lccode'\^Y = '\^Y %
202 \global\uccode'\^Y = '\I %
203 \global\lccode'\^Z = '\^Z %
204 \global\uccode'\^Y = '\J %
205 \global\lccode"9D = '\i %
206 \global\uccode"9D = "9D %
207 \global\lccode"9E = "9E %
208 \global\uccode"9E = "D0 %

```

Allow hyphenation at a zero-width glyph (used to break up ligatures or to place accents between characters).

```

209 \global\lccode23 = 23 %
210 \endgroup
211 \fi
212 </initex>

```

1.7 The L^AT_EX3 code environment

The code environment is now set up.

\ExplSyntaxOff Before changing any category codes, in package mode we need to save the situation before loading. Note the set up here means that once applied **\ExplSyntaxOff** becomes a “do nothing” command until **\ExplSyntaxOn** is used. For format mode, there is no need to save category codes so that step is skipped.

```

213 \protected\def\ExplSyntaxOff{}%
214 <*package>
215 \protected\edef\ExplSyntaxOff
216   {%
217     \protected\def\ExplSyntaxOff{}%
218     \catcode 9 = \the\catcode 9\relax
219     \catcode 32 = \the\catcode 32\relax
220     \catcode 34 = \the\catcode 34\relax
221     \catcode 38 = \the\catcode 38\relax
222     \catcode 58 = \the\catcode 58\relax
223     \catcode 94 = \the\catcode 94\relax
224     \catcode 95 = \the\catcode 95\relax
225     \catcode 124 = \the\catcode 124\relax
226     \catcode 126 = \the\catcode 126\relax
227     \endlinechar = \the\endlinechar\relax
228     \chardef\csname\detokenize{l__kernel_expl_bool}\endcsname = 0\relax
229   }%
230 </package>

```

(End definition for \ExplSyntaxOff. This function is documented on page 6.)

The code environment is now set up.

```

231 \catcode 9 = 9\relax
232 \catcode 32 = 9\relax
233 \catcode 34 = 12\relax
234 \catcode 38 = 4\relax
235 \catcode 58 = 11\relax
236 \catcode 94 = 7\relax
237 \catcode 95 = 11\relax
238 \catcode 124 = 12\relax
239 \catcode 126 = 10\relax
240 \endlinechar = 32\relax

```

\l__kernel_expl_bool The status for experimental code syntax: this is on at present.

```

241 \chardef\l__kernel_expl_bool = 1\relax

```

(End definition for \l__kernel_expl_bool.)

\ExplSyntaxOn The idea here is that multiple \ExplSyntaxOn calls are not going to mess up category codes, and that multiple calls to \ExplSyntaxOff are also not wasting time. Applying \ExplSyntaxOn alters the definition of \ExplSyntaxOff and so in package mode this function should not be used until after the end of the loading process!

```

242 \protected \def \ExplSyntaxOn
243 {
244   \bool_if:NF \l__kernel_expl_bool
245   {
246     \cs_set_protected:Npx \ExplSyntaxOff
247     {
248       \char_set_catcode:nn { 9 } { \char_value_catcode:n { 9 } }
249       \char_set_catcode:nn { 32 } { \char_value_catcode:n { 32 } }
250       \char_set_catcode:nn { 34 } { \char_value_catcode:n { 34 } }
251       \char_set_catcode:nn { 38 } { \char_value_catcode:n { 38 } }
252       \char_set_catcode:nn { 58 } { \char_value_catcode:n { 58 } }
253       \char_set_catcode:nn { 94 } { \char_value_catcode:n { 94 } }
254       \char_set_catcode:nn { 95 } { \char_value_catcode:n { 95 } }
255       \char_set_catcode:nn { 124 } { \char_value_catcode:n { 124 } }
256       \char_set_catcode:nn { 126 } { \char_value_catcode:n { 126 } }
257       \tex_endlinechar:D =
258       \tex_the:D \tex_endlinechar:D \scan_stop:
259       \bool_set_false:N \l__kernel_expl_bool
260       \cs_set_protected:Npn \ExplSyntaxOff { }
261     }
262   }
263   \char_set_catcode_ignore:n { 9 } % tab
264   \char_set_catcode_ignore:n { 32 } % space
265   \char_set_catcode_other:n { 34 } % double quote
266   \char_set_catcode_alignment:n { 38 } % ampersand
267   \char_set_catcode_letter:n { 58 } % colon
268   \char_set_catcode_math_superscript:n { 94 } % circumflex
269   \char_set_catcode_letter:n { 95 } % underscore
270   \char_set_catcode_other:n { 124 } % pipe
271   \char_set_catcode_space:n { 126 } % tilde
272   \tex_endlinechar:D = 32 \scan_stop:
273   \bool_set_true:N \l__kernel_expl_bool

```



```
274 }
```

(End definition for `\Exp1Syntax0n`. This function is documented on page 6.)

```
275 </initex | package>
```

2 l3names implementation

```
276 <*initex | package>
```

The prefix here is `kernel`. A few places need `@@` to be left as is; this is obtained as `@@@`.

```
277 <@@=kernel>
```

The code here simply renames all of the primitives to new, internal, names. In format mode, it also deletes all of the existing names (although some do come back later).

The `\let` primitive is renamed by hand first as it is essential for the entire process to follow. This also uses `\global`, as that way we avoid leaving an unneeded csname in the hash table.

```
278 \let \tex_global:D \global
```

```
279 \let \tex_let:D \let
```

Everything is inside a (rather long) group, which keeps `_kernel_primitive:NN` trapped.

```
280 \begingroup
```

`_kernel_primitive:NN` A temporary function to actually do the renaming. This also allows the original names to be removed in format mode.

```
281 \long \def \_kernel_primitive:NN #1#2
282 {
283   \tex_global:D \tex_let:D #2 #1
284 <*initex>
285   \tex_global:D \tex_let:D #1 \tex_undefined:D
286 </initex>
287 }
```

(End definition for `_kernel_primitive:NN`.)

To allow extracting “just the names”, a bit of DocStrip fiddling.

```
288 </initex | package>
289 <*initex | names | package>
```

In the current incarnation of this package, all `TEX` primitives are given a new name of the form `\tex_oldname:D`. But first three special cases which have symbolic original names. These are given modified new names, so that they may be entered without catcode tricks.

```
290 \_kernel_primitive:NN \tex_space:D
291 \_kernel_primitive:NN \tex_italiccorrection:D
292 \_kernel_primitive:NN \tex_hyphen:D
```

Now all the other primitives.

```
293 \_kernel_primitive:NN \tex_above:D
294 \_kernel_primitive:NN \tex_abovedisplayshortskip \tex_abovedisplayshortskip:D
295 \_kernel_primitive:NN \tex_abovedisplayshortskip \tex_abovedisplayshortskip:D
296 \_kernel_primitive:NN \tex_abovewithdelims \tex_abovewithdelims:D
297 \_kernel_primitive:NN \tex_accent:D
298 \_kernel_primitive:NN \tex_adjdemerits:D
```

299	_kernel_primitive:NN	\advance	\tex_advance:D
300	_kernel_primitive:NN	\afterassignment	\tex_afterassignment:D
301	_kernel_primitive:NN	\aftergroup	\tex_aftergroup:D
302	_kernel_primitive:NN	\atop	\tex_atop:D
303	_kernel_primitive:NN	\atopwithdelims	\tex_atopwithdelims:D
304	_kernel_primitive:NN	\badness	\tex_badness:D
305	_kernel_primitive:NN	\baselineskip	\tex_baselineskip:D
306	_kernel_primitive:NN	\batchmode	\tex_batchmode:D
307	_kernel_primitive:NN	\begingroup	\tex_begingroup:D
308	_kernel_primitive:NN	\belowdisplayshortskip	\tex_belowdisplayshortskip:D
309	_kernel_primitive:NN	\belowdisplayskip	\tex_belowdisplayskip:D
310	_kernel_primitive:NN	\binoppenalty	\tex_binoppenalty:D
311	_kernel_primitive:NN	\botmark	\tex_botmark:D
312	_kernel_primitive:NN	\box	\tex_box:D
313	_kernel_primitive:NN	\boxmaxdepth	\tex_boxmaxdepth:D
314	_kernel_primitive:NN	\brokenpenalty	\tex_brokenpenalty:D
315	_kernel_primitive:NN	\catcode	\tex_catcode:D
316	_kernel_primitive:NN	\char	\tex_char:D
317	_kernel_primitive:NN	\chardef	\tex_chardef:D
318	_kernel_primitive:NN	\cleaders	\tex_cleaders:D
319	_kernel_primitive:NN	\closein	\tex_closein:D
320	_kernel_primitive:NN	\closeout	\tex_closeout:D
321	_kernel_primitive:NN	\clubpenalty	\tex_clubpenalty:D
322	_kernel_primitive:NN	\copy	\tex_copy:D
323	_kernel_primitive:NN	\count	\tex_count:D
324	_kernel_primitive:NN	\countdef	\tex_countdef:D
325	_kernel_primitive:NN	\cr	\tex_cr:D
326	_kernel_primitive:NN	\crrcr	\tex_crrcr:D
327	_kernel_primitive:NN	\csname	\tex_csname:D
328	_kernel_primitive:NN	\day	\tex_day:D
329	_kernel_primitive:NN	\deadcycles	\tex_deadcycles:D
330	_kernel_primitive:NN	\def	\tex_def:D
331	_kernel_primitive:NN	\defaultthyphenchar	\tex_defaultthyphenchar:D
332	_kernel_primitive:NN	\defaultskewchar	\tex_defaultskewchar:D
333	_kernel_primitive:NN	\delcode	\tex_delcode:D
334	_kernel_primitive:NN	\delimiter	\tex_delimiter:D
335	_kernel_primitive:NN	\delimiterfactor	\tex_delimiterfactor:D
336	_kernel_primitive:NN	\delimitershortfall	\tex_delimitershortfall:D
337	_kernel_primitive:NN	\dimen	\tex_dimen:D
338	_kernel_primitive:NN	\dimendef	\tex_dimendef:D
339	_kernel_primitive:NN	\discretionary	\tex_discretionary:D
340	_kernel_primitive:NN	\displayindent	\tex_displayindent:D
341	_kernel_primitive:NN	\displaylimits	\tex_displaylimits:D
342	_kernel_primitive:NN	\displaystyle	\tex_displaystyle:D
343	_kernel_primitive:NN	\displaywidowpenalty	\tex_displaywidowpenalty:D
344	_kernel_primitive:NN	\displaywidth	\tex_displaywidth:D
345	_kernel_primitive:NN	\divide	\tex_divide:D
346	_kernel_primitive:NN	\doublehyphendemerits	\tex_doublehyphendemerits:D
347	_kernel_primitive:NN	\dp	\tex_dp:D
348	_kernel_primitive:NN	\dump	\tex_dump:D
349	_kernel_primitive:NN	\edef	\tex_edef:D
350	_kernel_primitive:NN	\else	\tex_else:D
351	_kernel_primitive:NN	\emergencystretch	\tex_emergencystretch:D
352	_kernel_primitive:NN	\end	\tex_end:D

353	_kernel_primitive:NN	\endcsname	\tex_endcsname:D
354	_kernel_primitive:NN	\endgroup	\tex_endgroup:D
355	_kernel_primitive:NN	\endinput	\tex_endinput:D
356	_kernel_primitive:NN	\endlinechar	\tex_endlinechar:D
357	_kernel_primitive:NN	\eqno	\tex_eqno:D
358	_kernel_primitive:NN	\errhelp	\tex_errhelp:D
359	_kernel_primitive:NN	\errmessage	\tex_errmessage:D
360	_kernel_primitive:NN	\errorcontextlines	\tex_errorcontextlines:D
361	_kernel_primitive:NN	\errorstopmode	\tex_errorstopmode:D
362	_kernel_primitive:NN	\escapechar	\tex_escapechar:D
363	_kernel_primitive:NN	\everycr	\tex_everycr:D
364	_kernel_primitive:NN	\everydisplay	\tex_everydisplay:D
365	_kernel_primitive:NN	\everyhbox	\tex_everyhbox:D
366	_kernel_primitive:NN	\everyjob	\tex_everyjob:D
367	_kernel_primitive:NN	\everymath	\tex_everymath:D
368	_kernel_primitive:NN	\everypar	\tex_everypar:D
369	_kernel_primitive:NN	\everyvbox	\tex_everyvbox:D
370	_kernel_primitive:NN	\exhyphenpenalty	\tex_exhyphenpenalty:D
371	_kernel_primitive:NN	\expandafter	\tex_expandafter:D
372	_kernel_primitive:NN	\fam	\tex_fam:D
373	_kernel_primitive:NN	\fi	\tex_fi:D
374	_kernel_primitive:NN	\finalhyphendemerits	\tex_finalhyphendemerits:D
375	_kernel_primitive:NN	\firstmark	\tex_firstmark:D
376	_kernel_primitive:NN	\floatingpenalty	\tex_floatingpenalty:D
377	_kernel_primitive:NN	\font	\tex_font:D
378	_kernel_primitive:NN	\fontdimen	\tex_fontdimen:D
379	_kernel_primitive:NN	\fontname	\tex_fontname:D
380	_kernel_primitive:NN	\futurelet	\tex_futurelet:D
381	_kernel_primitive:NN	\gdef	\tex_gdef:D
382	_kernel_primitive:NN	\global	\tex_global:D
383	_kernel_primitive:NN	\globaldefs	\tex_globaldefs:D
384	_kernel_primitive:NN	\halign	\tex_halign:D
385	_kernel_primitive:NN	\hangafter	\tex_hangafter:D
386	_kernel_primitive:NN	\hangindent	\tex_hangindent:D
387	_kernel_primitive:NN	\hbadness	\tex_hbadness:D
388	_kernel_primitive:NN	\hbox	\tex_hbox:D
389	_kernel_primitive:NN	\hfil	\tex_hfil:D
390	_kernel_primitive:NN	\hfill	\tex_hfill:D
391	_kernel_primitive:NN	\hfilneg	\tex_hfilneg:D
392	_kernel_primitive:NN	\hfuzz	\tex_hfuzz:D
393	_kernel_primitive:NN	\hoffset	\tex_hoffset:D
394	_kernel_primitive:NN	\holdinginserts	\tex_holdinginserts:D
395	_kernel_primitive:NN	\hrule	\tex_hrule:D
396	_kernel_primitive:NN	\hsize	\tex_hsize:D
397	_kernel_primitive:NN	\hskip	\tex_hskip:D
398	_kernel_primitive:NN	\hss	\tex_hss:D
399	_kernel_primitive:NN	\ht	\tex_ht:D
400	_kernel_primitive:NN	\hyphenation	\tex_hyphenation:D
401	_kernel_primitive:NN	\hyphenchar	\tex_hyphenchar:D
402	_kernel_primitive:NN	\hyphenpenalty	\tex_hyphenpenalty:D
403	_kernel_primitive:NN	\if	\tex_if:D
404	_kernel_primitive:NN	\ifcase	\tex_ifcase:D
405	_kernel_primitive:NN	\ifcat	\tex_ifcat:D
406	_kernel_primitive:NN	\ifdim	\tex_ifdim:D

407	_kernel_primitive:NN \ifeof	\tex_ifeof:D
408	_kernel_primitive:NN \iffalse	\tex_iffalse:D
409	_kernel_primitive:NN \ifhbox	\tex_ifhbox:D
410	_kernel_primitive:NN \ifhmode	\tex_ifhmode:D
411	_kernel_primitive:NN \ifinner	\tex_ifinner:D
412	_kernel_primitive:NN \ifmmode	\tex_ifmmode:D
413	_kernel_primitive:NN \ifnum	\tex_ifnum:D
414	_kernel_primitive:NN \ifodd	\tex_ifodd:D
415	_kernel_primitive:NN \iftrue	\tex_iftrue:D
416	_kernel_primitive:NN \ifvbox	\tex_ifvbox:D
417	_kernel_primitive:NN \ifvmode	\tex_ifvmode:D
418	_kernel_primitive:NN \ifvoid	\tex_ifvoid:D
419	_kernel_primitive:NN \ifx	\tex_ifx:D
420	_kernel_primitive:NN \ignorespaces	\tex_ignorespaces:D
421	_kernel_primitive:NN \immediate	\tex_immediate:D
422	_kernel_primitive:NN \indent	\tex_indent:D
423	_kernel_primitive:NN \input	\tex_input:D
424	_kernel_primitive:NN \inputlineno	\tex_inputlineno:D
425	_kernel_primitive:NN \insert	\tex_insert:D
426	_kernel_primitive:NN \insertpenalties	\tex_insertpenalties:D
427	_kernel_primitive:NN \interlinepenalty	\tex_interlinepenalty:D
428	_kernel_primitive:NN \jobname	\tex_jobname:D
429	_kernel_primitive:NN \kern	\tex_kern:D
430	_kernel_primitive:NN \language	\tex_language:D
431	_kernel_primitive:NN \lastbox	\tex_lastbox:D
432	_kernel_primitive:NN \lastkern	\tex_lastkern:D
433	_kernel_primitive:NN \lastpenalty	\tex_lastpenalty:D
434	_kernel_primitive:NN \lastskip	\tex_lastskip:D
435	_kernel_primitive:NN \lccode	\tex_lccode:D
436	_kernel_primitive:NN \leaders	\tex_leaders:D
437	_kernel_primitive:NN \left	\tex_left:D
438	_kernel_primitive:NN \lefthyphenmin	\tex_lefthyphenmin:D
439	_kernel_primitive:NN \leftskip	\tex_leftskip:D
440	_kernel_primitive:NN \leqno	\tex_leqno:D
441	_kernel_primitive:NN \let	\tex_let:D
442	_kernel_primitive:NN \limits	\tex_limits:D
443	_kernel_primitive:NN \linepenalty	\tex_linepenalty:D
444	_kernel_primitive:NN \lineskip	\tex_lineskip:D
445	_kernel_primitive:NN \lineskiplimit	\tex_lineskiplimit:D
446	_kernel_primitive:NN \long	\tex_long:D
447	_kernel_primitive:NN \looseness	\tex_looseness:D
448	_kernel_primitive:NN \lower	\tex_lower:D
449	_kernel_primitive:NN \lowercase	\tex_lowercase:D
450	_kernel_primitive:NN \mag	\tex_mag:D
451	_kernel_primitive:NN \mark	\tex_mark:D
452	_kernel_primitive:NN \mathaccent	\tex_mathaccent:D
453	_kernel_primitive:NN \mathbin	\tex_mathbin:D
454	_kernel_primitive:NN \mathchar	\tex_mathchar:D
455	_kernel_primitive:NN \mathchardef	\tex_mathchardef:D
456	_kernel_primitive:NN \mathchoice	\tex_mathchoice:D
457	_kernel_primitive:NN \mathclose	\tex_mathclose:D
458	_kernel_primitive:NN \mathcode	\tex_mathcode:D
459	_kernel_primitive:NN \mathinner	\tex_mathinner:D
460	_kernel_primitive:NN \mathop	\tex_mathop:D

461	_kernel_primitive:NN	\mathopen	\tex_mathopen:D
462	_kernel_primitive:NN	\mathord	\tex_mathord:D
463	_kernel_primitive:NN	\mathpunct	\tex_mathpunct:D
464	_kernel_primitive:NN	\mathrel	\tex_mathrel:D
465	_kernel_primitive:NN	\mathsurround	\tex_mathsurround:D
466	_kernel_primitive:NN	\maxdeadcycles	\tex_maxdeadcycles:D
467	_kernel_primitive:NN	\maxdepth	\tex_maxdepth:D
468	_kernel_primitive:NN	\meaning	\tex_meaning:D
469	_kernel_primitive:NN	\medmuskip	\tex_medmuskip:D
470	_kernel_primitive:NN	\message	\tex_message:D
471	_kernel_primitive:NN	\mkern	\tex_mkern:D
472	_kernel_primitive:NN	\month	\tex_month:D
473	_kernel_primitive:NN	\moveleft	\tex_moveleft:D
474	_kernel_primitive:NN	\moveright	\tex_moveright:D
475	_kernel_primitive:NN	\mskip	\tex_mskip:D
476	_kernel_primitive:NN	\multiply	\tex_multiply:D
477	_kernel_primitive:NN	\muskip	\tex_muskip:D
478	_kernel_primitive:NN	\muskipdef	\tex_muskipdef:D
479	_kernel_primitive:NN	\newlinechar	\tex_newlinechar:D
480	_kernel_primitive:NN	\noalign	\tex_noalign:D
481	_kernel_primitive:NN	\noboundary	\tex_noboundary:D
482	_kernel_primitive:NN	\noexpand	\tex_noexpand:D
483	_kernel_primitive:NN	\noindent	\tex_noindent:D
484	_kernel_primitive:NN	\nolimits	\tex_nolimits:D
485	_kernel_primitive:NN	\nonscript	\tex_nonscript:D
486	_kernel_primitive:NN	\nonstopmode	\tex_nonstopmode:D
487	_kernel_primitive:NN	\nulldelimiterspace	\tex_nulldelimiterspace:D
488	_kernel_primitive:NN	\nullfont	\tex_nullfont:D
489	_kernel_primitive:NN	\number	\tex_number:D
490	_kernel_primitive:NN	\omit	\tex_omit:D
491	_kernel_primitive:NN	\openin	\tex_openin:D
492	_kernel_primitive:NN	\openout	\tex_openout:D
493	_kernel_primitive:NN	\or	\tex_or:D
494	_kernel_primitive:NN	\outer	\tex_outer:D
495	_kernel_primitive:NN	\output	\tex_output:D
496	_kernel_primitive:NN	\outputpenalty	\tex_outputpenalty:D
497	_kernel_primitive:NN	\over	\tex_over:D
498	_kernel_primitive:NN	\overfullrule	\tex_overfullrule:D
499	_kernel_primitive:NN	\overline	\tex_overline:D
500	_kernel_primitive:NN	\overwithdelims	\tex_overwithdelims:D
501	_kernel_primitive:NN	\pagedepth	\tex_pagedepth:D
502	_kernel_primitive:NN	\pagefilllstretch	\tex_pagefilllstretch:D
503	_kernel_primitive:NN	\pagefillstretch	\tex_pagefillstretch:D
504	_kernel_primitive:NN	\pagefilstretch	\tex_pagefilstretch:D
505	_kernel_primitive:NN	\pagegoal	\tex_pagegoal:D
506	_kernel_primitive:NN	\pageshrink	\tex_pageshrink:D
507	_kernel_primitive:NN	\pagestretch	\tex_pagestretch:D
508	_kernel_primitive:NN	\pagetotal	\tex_pagetotal:D
509	_kernel_primitive:NN	\par	\tex_par:D
510	_kernel_primitive:NN	\parfillskip	\tex_parfillskip:D
511	_kernel_primitive:NN	\parindent	\tex_parindent:D
512	_kernel_primitive:NN	\parshape	\tex_parshape:D
513	_kernel_primitive:NN	\parskip	\tex_parskip:D
514	_kernel_primitive:NN	\patterns	\tex_patterns:D

515	_kernel_primitive:NN	\pausing	\tex_pausing:D
516	_kernel_primitive:NN	\penalty	\tex_penalty:D
517	_kernel_primitive:NN	\postdisplaypenalty	\tex_postdisplaypenalty:D
518	_kernel_primitive:NN	\predisdisplaypenalty	\tex_predisdisplaypenalty:D
519	_kernel_primitive:NN	\predisplaysize	\tex_predisplaysize:D
520	_kernel_primitive:NN	\pretolerance	\tex_pretolerance:D
521	_kernel_primitive:NN	\prevdepth	\tex_prevdepth:D
522	_kernel_primitive:NN	\prevgraf	\tex_prevgraf:D
523	_kernel_primitive:NN	\radical	\tex_radical:D
524	_kernel_primitive:NN	\raise	\tex_raise:D
525	_kernel_primitive:NN	\read	\tex_read:D
526	_kernel_primitive:NN	\relax	\tex_relax:D
527	_kernel_primitive:NN	\relpenalty	\tex_relpenalty:D
528	_kernel_primitive:NN	\right	\tex_right:D
529	_kernel_primitive:NN	\righthyphenmin	\tex_righthyphenmin:D
530	_kernel_primitive:NN	\rightskip	\tex_rightskip:D
531	_kernel_primitive:NN	\romannumeral	\tex_romannumeral:D
532	_kernel_primitive:NN	\scriptfont	\tex_scriptfont:D
533	_kernel_primitive:NN	\scriptscriptfont	\tex_scriptscriptfont:D
534	_kernel_primitive:NN	\scriptscriptstyle	\tex_scriptscriptstyle:D
535	_kernel_primitive:NN	\scriptspace	\tex_scriptspace:D
536	_kernel_primitive:NN	\scriptstyle	\tex_scriptstyle:D
537	_kernel_primitive:NN	\scrollmode	\tex_scrollmode:D
538	_kernel_primitive:NN	\setbox	\tex_setbox:D
539	_kernel_primitive:NN	\setlanguage	\tex_setlanguage:D
540	_kernel_primitive:NN	\sfcode	\tex_sfcode:D
541	_kernel_primitive:NN	\shipout	\tex_shipout:D
542	_kernel_primitive:NN	\show	\tex_show:D
543	_kernel_primitive:NN	\showbox	\tex_showbox:D
544	_kernel_primitive:NN	\showboxbreadth	\tex_showboxbreadth:D
545	_kernel_primitive:NN	\showboxdepth	\tex_showboxdepth:D
546	_kernel_primitive:NN	\showlists	\tex_showlists:D
547	_kernel_primitive:NN	\showthe	\tex_showthe:D
548	_kernel_primitive:NN	\skewchar	\tex_skewchar:D
549	_kernel_primitive:NN	\skip	\tex_skip:D
550	_kernel_primitive:NN	\skipdef	\tex_skipdef:D
551	_kernel_primitive:NN	\spacefactor	\tex_spacefactor:D
552	_kernel_primitive:NN	\spaceskip	\tex_spaceskip:D
553	_kernel_primitive:NN	\span	\tex_span:D
554	_kernel_primitive:NN	\special	\tex_special:D
555	_kernel_primitive:NN	\splitbotmark	\tex_splitbotmark:D
556	_kernel_primitive:NN	\splitfirstmark	\tex_splitfirstmark:D
557	_kernel_primitive:NN	\splitmaxdepth	\tex_splitmaxdepth:D
558	_kernel_primitive:NN	\splittopskip	\tex_splittopskip:D
559	_kernel_primitive:NN	\string	\tex_string:D
560	_kernel_primitive:NN	\tabskip	\tex_tabskip:D
561	_kernel_primitive:NN	\textfont	\tex_textfont:D
562	_kernel_primitive:NN	\textstyle	\tex_textstyle:D
563	_kernel_primitive:NN	\the	\tex_the:D
564	_kernel_primitive:NN	\thickmuskip	\tex_thickmuskip:D
565	_kernel_primitive:NN	\thinmuskip	\tex_thinmuskip:D
566	_kernel_primitive:NN	\time	\tex_time:D
567	_kernel_primitive:NN	\toks	\tex_toks:D
568	_kernel_primitive:NN	\toksdef	\tex_toksdef:D

569	<code>__kernel_primitive:NN \tolerance</code>	<code>\tex_tolerance:D</code>
570	<code>__kernel_primitive:NN \topmark</code>	<code>\tex_topmark:D</code>
571	<code>__kernel_primitive:NN \topskip</code>	<code>\tex_topskip:D</code>
572	<code>__kernel_primitive:NN \tracingcommands</code>	<code>\tex_tracingcommands:D</code>
573	<code>__kernel_primitive:NN \tracinglostchars</code>	<code>\tex_tracinglostchars:D</code>
574	<code>__kernel_primitive:NN \tracingmacros</code>	<code>\tex_tracingmacros:D</code>
575	<code>__kernel_primitive:NN \tracingonline</code>	<code>\tex_tracingonline:D</code>
576	<code>__kernel_primitive:NN \tracingoutput</code>	<code>\tex_tracingoutput:D</code>
577	<code>__kernel_primitive:NN \tracingpages</code>	<code>\tex_tracingpages:D</code>
578	<code>__kernel_primitive:NN \tracingparagraphs</code>	<code>\tex_tracingparagraphs:D</code>
579	<code>__kernel_primitive:NN \tracingrestores</code>	<code>\tex_tracingrestores:D</code>
580	<code>__kernel_primitive:NN \tracingstats</code>	<code>\tex_tracingstats:D</code>
581	<code>__kernel_primitive:NN \uccode</code>	<code>\tex_uccode:D</code>
582	<code>__kernel_primitive:NN \uchyph</code>	<code>\tex_uchyph:D</code>
583	<code>__kernel_primitive:NN \underline</code>	<code>\tex_underline:D</code>
584	<code>__kernel_primitive:NN \unhbox</code>	<code>\tex_unhbox:D</code>
585	<code>__kernel_primitive:NN \unhcopy</code>	<code>\tex_unhcopy:D</code>
586	<code>__kernel_primitive:NN \unkern</code>	<code>\tex_unkern:D</code>
587	<code>__kernel_primitive:NN \unpenalty</code>	<code>\tex_unpenalty:D</code>
588	<code>__kernel_primitive:NN \unskip</code>	<code>\tex_unskip:D</code>
589	<code>__kernel_primitive:NN \unvbox</code>	<code>\tex_unvbox:D</code>
590	<code>__kernel_primitive:NN \unvcopy</code>	<code>\tex_unvcopy:D</code>
591	<code>__kernel_primitive:NN \uppercase</code>	<code>\tex_uppercase:D</code>
592	<code>__kernel_primitive:NN \vadjust</code>	<code>\tex_vadjust:D</code>
593	<code>__kernel_primitive:NN \valign</code>	<code>\tex_valign:D</code>
594	<code>__kernel_primitive:NN \vbadness</code>	<code>\tex_vbadness:D</code>
595	<code>__kernel_primitive:NN \vbox</code>	<code>\tex_vbox:D</code>
596	<code>__kernel_primitive:NN \vcenter</code>	<code>\tex_vcenter:D</code>
597	<code>__kernel_primitive:NN \vfil</code>	<code>\tex_vfil:D</code>
598	<code>__kernel_primitive:NN \vfill</code>	<code>\tex_vfill:D</code>
599	<code>__kernel_primitive:NN \vfilneg</code>	<code>\tex_vfilneg:D</code>
600	<code>__kernel_primitive:NN \vfuzz</code>	<code>\tex_vfuzz:D</code>
601	<code>__kernel_primitive:NN \voffset</code>	<code>\tex_voffset:D</code>
602	<code>__kernel_primitive:NN \vrule</code>	<code>\tex_vrule:D</code>
603	<code>__kernel_primitive:NN \vsize</code>	<code>\tex_vsize:D</code>
604	<code>__kernel_primitive:NN \vskip</code>	<code>\tex_vskip:D</code>
605	<code>__kernel_primitive:NN \vsplit</code>	<code>\tex_vsplit:D</code>
606	<code>__kernel_primitive:NN \vss</code>	<code>\tex_vss:D</code>
607	<code>__kernel_primitive:NN \vtop</code>	<code>\tex_vtop:D</code>
608	<code>__kernel_primitive:NN \wd</code>	<code>\tex_wd:D</code>
609	<code>__kernel_primitive:NN \widowpenalty</code>	<code>\tex_widowpenalty:D</code>
610	<code>__kernel_primitive:NN \write</code>	<code>\tex_write:D</code>
611	<code>__kernel_primitive:NN \xdef</code>	<code>\tex_xdef:D</code>
612	<code>__kernel_primitive:NN \xleaders</code>	<code>\tex_xleaders:D</code>
613	<code>__kernel_primitive:NN \xspaceskip</code>	<code>\tex_xspaceskip:D</code>
614	<code>__kernel_primitive:NN \year</code>	<code>\tex_year:D</code>

Primitives introduced by ε -T_EX.

615	<code>__kernel_primitive:NN \beginL</code>	<code>\tex_beginL:D</code>
616	<code>__kernel_primitive:NN \beginR</code>	<code>\tex_beginR:D</code>
617	<code>__kernel_primitive:NN \botmarks</code>	<code>\tex_botmarks:D</code>
618	<code>__kernel_primitive:NN \clubpenalties</code>	<code>\tex_clubpenalties:D</code>
619	<code>__kernel_primitive:NN \currentgrouplevel</code>	<code>\tex_currentgrouplevel:D</code>
620	<code>__kernel_primitive:NN \currentgrouptype</code>	<code>\tex_currentgrouptype:D</code>
621	<code>__kernel_primitive:NN \currentifbranch</code>	<code>\tex_currentifbranch:D</code>

622	_kernel_primitive:NN	\currentiflevel	\tex_currentiflevel:D
623	_kernel_primitive:NN	\currentifttype	\tex_currentifttype:D
624	_kernel_primitive:NN	\detokenize	\tex_detokenize:D
625	_kernel_primitive:NN	\dimexpr	\tex_dimexpr:D
626	_kernel_primitive:NN	\displaywidowpenalties	\tex_displaywidowpenalties:D
627	_kernel_primitive:NN	\endL	\tex_endL:D
628	_kernel_primitive:NN	\endR	\tex_endR:D
629	_kernel_primitive:NN	\eTeXrevision	\tex_eTeXrevision:D
630	_kernel_primitive:NN	\eTeXversion	\tex_eTeXversion:D
631	_kernel_primitive:NN	\everyeof	\tex_everyeof:D
632	_kernel_primitive:NN	\firstmarks	\tex_firstmarks:D
633	_kernel_primitive:NN	\fontchardp	\tex_fontchardp:D
634	_kernel_primitive:NN	\fontcharht	\tex_fontcharht:D
635	_kernel_primitive:NN	\fontcharic	\tex_fontcharic:D
636	_kernel_primitive:NN	\fontcharwd	\tex_fontcharwd:D
637	_kernel_primitive:NN	\glueexpr	\tex_glueexpr:D
638	_kernel_primitive:NN	\glueshrink	\tex_glueshrink:D
639	_kernel_primitive:NN	\glueshrinkorder	\tex_glueshrinkorder:D
640	_kernel_primitive:NN	\gluestretch	\tex_gluestretch:D
641	_kernel_primitive:NN	\gluestretchorder	\tex_gluestretchorder:D
642	_kernel_primitive:NN	\gluetomu	\tex_gluetomu:D
643	_kernel_primitive:NN	\ifcsname	\tex_ifcsname:D
644	_kernel_primitive:NN	\ifdefined	\tex_ifdefined:D
645	_kernel_primitive:NN	\iffontchar	\tex_iffontchar:D
646	_kernel_primitive:NN	\interactionmode	\tex_interactionmode:D
647	_kernel_primitive:NN	\interlinepenalties	\tex_interlinepenalties:D
648	_kernel_primitive:NN	\lastlinefit	\tex_lastlinefit:D
649	_kernel_primitive:NN	\lastnodetype	\tex_lastnodetype:D
650	_kernel_primitive:NN	\marks	\tex_marks:D
651	_kernel_primitive:NN	\middle	\tex_middle:D
652	_kernel_primitive:NN	\muexpr	\tex_muexpr:D
653	_kernel_primitive:NN	\mutoglua	\tex_mutoglua:D
654	_kernel_primitive:NN	\numexpr	\tex_numexpr:D
655	_kernel_primitive:NN	\pagediscards	\tex_pagediscards:D
656	_kernel_primitive:NN	\parshapedimen	\tex_parshapedimen:D
657	_kernel_primitive:NN	\parshapeindent	\tex_parshapeindent:D
658	_kernel_primitive:NN	\parshapelength	\tex_parshapelength:D
659	_kernel_primitive:NN	\predisplaydirection	\tex_predisplaydirection:D
660	_kernel_primitive:NN	\protected	\tex_protected:D
661	_kernel_primitive:NN	\readline	\tex_readline:D
662	_kernel_primitive:NN	\savinghyphcodes	\tex_savinghyphcodes:D
663	_kernel_primitive:NN	\savingvdiscards	\tex_savingvdiscards:D
664	_kernel_primitive:NN	\scantokens	\tex_scantokens:D
665	_kernel_primitive:NN	\showgroups	\tex_showgroups:D
666	_kernel_primitive:NN	\showifs	\tex_showifs:D
667	_kernel_primitive:NN	\showtokens	\tex_showtokens:D
668	_kernel_primitive:NN	\splitbotmarks	\tex_splitbotmarks:D
669	_kernel_primitive:NN	\splitdiscards	\tex_splitdiscards:D
670	_kernel_primitive:NN	\splitfirstmarks	\tex_splitfirstmarks:D
671	_kernel_primitive:NN	\TeXXeTstate	\tex_TeXXeTstate:D
672	_kernel_primitive:NN	\topmarks	\tex_topmarks:D
673	_kernel_primitive:NN	\tracingassigns	\tex_tracingassigns:D
674	_kernel_primitive:NN	\tracinggroups	\tex_tracinggroups:D
675	_kernel_primitive:NN	\tracingifs	\tex_tracingifs:D

676	<code>_kernel_primitive:NN</code>	<code>\tracingnesting</code>	<code>\tex_tracingnesting:D</code>
677	<code>_kernel_primitive:NN</code>	<code>\tracingscantokens</code>	<code>\tex_tracingscantokens:D</code>
678	<code>_kernel_primitive:NN</code>	<code>\unexpanded</code>	<code>\tex_unexpanded:D</code>
679	<code>_kernel_primitive:NN</code>	<code>\unless</code>	<code>\tex_unless:D</code>
680	<code>_kernel_primitive:NN</code>	<code>\widowpenalties</code>	<code>\tex_widowpenalties:D</code>

Post- ϵ -TeX primitives do not always end up with the same name in all engines, if indeed they are available cross-engine anyway. We therefore take the approach of preferring the shortest name that makes sense. First, we deal with the primitives introduced by pdfTeX which directly relate to PDF output: these are copied with the names unchanged.

681	<code>_kernel_primitive:NN</code>	<code>\pdfannot</code>	<code>\tex_pdfannot:D</code>
682	<code>_kernel_primitive:NN</code>	<code>\pdfcatalog</code>	<code>\tex_pdfcatalog:D</code>
683	<code>_kernel_primitive:NN</code>	<code>\pdfcompresslevel</code>	<code>\tex_pdfcompresslevel:D</code>
684	<code>_kernel_primitive:NN</code>	<code>\pdfcolorstack</code>	<code>\tex_pdfcolorstack:D</code>
685	<code>_kernel_primitive:NN</code>	<code>\pdfcolorstackinit</code>	<code>\tex_pdfcolorstackinit:D</code>
686	<code>_kernel_primitive:NN</code>	<code>\pdfcreationdate</code>	<code>\tex_pdfcreationdate:D</code>
687	<code>_kernel_primitive:NN</code>	<code>\pdfdecimaldigits</code>	<code>\tex_pdfdecimaldigits:D</code>
688	<code>_kernel_primitive:NN</code>	<code>\pdfdest</code>	<code>\tex_pdfdest:D</code>
689	<code>_kernel_primitive:NN</code>	<code>\pdfdestmargin</code>	<code>\tex_pdfdestmargin:D</code>
690	<code>_kernel_primitive:NN</code>	<code>\pdfendlink</code>	<code>\tex_pdfendlink:D</code>
691	<code>_kernel_primitive:NN</code>	<code>\pdfendthread</code>	<code>\tex_pdfendthread:D</code>
692	<code>_kernel_primitive:NN</code>	<code>\pdffontattr</code>	<code>\tex_pdffontattr:D</code>
693	<code>_kernel_primitive:NN</code>	<code>\pdffontname</code>	<code>\tex_pdffontname:D</code>
694	<code>_kernel_primitive:NN</code>	<code>\pdffontobjnum</code>	<code>\tex_pdffontobjnum:D</code>
695	<code>_kernel_primitive:NN</code>	<code>\pdfgamma</code>	<code>\tex_pdfgamma:D</code>
696	<code>_kernel_primitive:NN</code>	<code>\pdfimageapplygamma</code>	<code>\tex_pdfimageapplygamma:D</code>
697	<code>_kernel_primitive:NN</code>	<code>\pdfimagegamma</code>	<code>\tex_pdfimagegamma:D</code>
698	<code>_kernel_primitive:NN</code>	<code>\pdfgentounicode</code>	<code>\tex_pdfgentounicode:D</code>
699	<code>_kernel_primitive:NN</code>	<code>\pdfglyphtounicode</code>	<code>\tex_pdfglyphtounicode:D</code>
700	<code>_kernel_primitive:NN</code>	<code>\pdfhorigin</code>	<code>\tex_pdfhorigin:D</code>
701	<code>_kernel_primitive:NN</code>	<code>\pdfimagehicolor</code>	<code>\tex_pdfimagehicolor:D</code>
702	<code>_kernel_primitive:NN</code>	<code>\pdfimageresolution</code>	<code>\tex_pdfimageresolution:D</code>
703	<code>_kernel_primitive:NN</code>	<code>\pdfincludechars</code>	<code>\tex_pdfincludechars:D</code>
704	<code>_kernel_primitive:NN</code>	<code>\pdfinclusioncopyfonts</code>	<code>\tex_pdfinclusioncopyfonts:D</code>
705	<code>_kernel_primitive:NN</code>	<code>\pdfinclusionerrorlevel</code>	
706		<code>\tex_pdfinclusionerrorlevel:D</code>	
707	<code>_kernel_primitive:NN</code>	<code>\pdfinfo</code>	<code>\tex_pdfinfo:D</code>
708	<code>_kernel_primitive:NN</code>	<code>\pdflastannot</code>	<code>\tex_pdflastannot:D</code>
709	<code>_kernel_primitive:NN</code>	<code>\pdflastlink</code>	<code>\tex_pdflastlink:D</code>
710	<code>_kernel_primitive:NN</code>	<code>\pdflastobj</code>	<code>\tex_pdflastobj:D</code>
711	<code>_kernel_primitive:NN</code>	<code>\pdflastxform</code>	<code>\tex_pdflastxform:D</code>
712	<code>_kernel_primitive:NN</code>	<code>\pdflastximage</code>	<code>\tex_pdflastximage:D</code>
713	<code>_kernel_primitive:NN</code>	<code>\pdflastximagecolordepth</code>	
714		<code>\tex_pdflastximagecolordepth:D</code>	
715	<code>_kernel_primitive:NN</code>	<code>\pdflastximagepages</code>	<code>\tex_pdflastximagepages:D</code>
716	<code>_kernel_primitive:NN</code>	<code>\pdflinkmargin</code>	<code>\tex_pdflinkmargin:D</code>
717	<code>_kernel_primitive:NN</code>	<code>\pdfliteral</code>	<code>\tex_pdfliteral:D</code>
718	<code>_kernel_primitive:NN</code>	<code>\pdfminorversion</code>	<code>\tex_pdfminorversion:D</code>
719	<code>_kernel_primitive:NN</code>	<code>\pdfnames</code>	<code>\tex_pdfnames:D</code>
720	<code>_kernel_primitive:NN</code>	<code>\pdfobj</code>	<code>\tex_pdfobj:D</code>
721	<code>_kernel_primitive:NN</code>	<code>\pdfobjcompresslevel</code>	<code>\tex_pdfobjcompresslevel:D</code>
722	<code>_kernel_primitive:NN</code>	<code>\pdfoutline</code>	<code>\tex_pdfoutline:D</code>
723	<code>_kernel_primitive:NN</code>	<code>\pdfoutput</code>	<code>\tex_pdfoutput:D</code>
724	<code>_kernel_primitive:NN</code>	<code>\pdfpageattr</code>	<code>\tex_pdfpageattr:D</code>

725	_kernel_primitive:NN	\pdfpagebox	\tex_pdfpagebox:D
726	_kernel_primitive:NN	\pdfpageref	\tex_pdfpageref:D
727	_kernel_primitive:NN	\pdfpageresources	\tex_pdfpageresources:D
728	_kernel_primitive:NN	\pdfpagesattr	\tex_pdfpagesattr:D
729	_kernel_primitive:NN	\pdfrefobj	\tex_pdfrefobj:D
730	_kernel_primitive:NN	\pdfrefxform	\tex_pdfrefxform:D
731	_kernel_primitive:NN	\pdfrefximage	\tex_pdfrefximage:D
732	_kernel_primitive:NN	\pdfrestore	\tex_pdfrestore:D
733	_kernel_primitive:NN	\pdfretval	\tex_pdfretval:D
734	_kernel_primitive:NN	\pdfsave	\tex_pdfsave:D
735	_kernel_primitive:NN	\pdfsetmatrix	\tex_pdfsetmatrix:D
736	_kernel_primitive:NN	\pdfstartlink	\tex_pdfstartlink:D
737	_kernel_primitive:NN	\pdfstartthread	\tex_pdfstartthread:D
738	_kernel_primitive:NN	\pdfsuppressptexinfo	\tex_pdfsuppressptexinfo:D
739	_kernel_primitive:NN	\pdfthread	\tex_pdfthread:D
740	_kernel_primitive:NN	\pdfthreadmargin	\tex_pdfthreadmargin:D
741	_kernel_primitive:NN	\pdftrailer	\tex_pdftrailer:D
742	_kernel_primitive:NN	\pdfuniqueresname	\tex_pdfuniqueresname:D
743	_kernel_primitive:NN	\pdfvorigin	\tex_pdfvorigin:D
744	_kernel_primitive:NN	\pdfxform	\tex_pdfxform:D
745	_kernel_primitive:NN	\pdfxformattr	\tex_pdfxformattr:D
746	_kernel_primitive:NN	\pdfxformname	\tex_pdfxformname:D
747	_kernel_primitive:NN	\pdfxformresources	\tex_pdfxformresources:D
748	_kernel_primitive:NN	\pdfximage	\tex_pdfximage:D
749	_kernel_primitive:NN	\pdfximagebbox	\tex_pdfximagebbox:D

These are not related to PDF output and either already appear in other engines without the \pdf prefix, or might reasonably do so at some future stage. We therefore drop the leading pdf here.

750	_kernel_primitive:NN	\ifpdfabsdim	\tex_ifabsdim:D
751	_kernel_primitive:NN	\ifpdfabsnum	\tex_ifabsnum:D
752	_kernel_primitive:NN	\ifpdfprimitive	\tex_ifprimitive:D
753	_kernel_primitive:NN	\pdfadjustspacing	\tex_adjustspacing:D
754	_kernel_primitive:NN	\pdfcopyfont	\tex_copyfont:D
755	_kernel_primitive:NN	\pdfdraftmode	\tex_draftmode:D
756	_kernel_primitive:NN	\pdfeachlinedepth	\tex_eachlinedepth:D
757	_kernel_primitive:NN	\pdfeachlineheight	\tex_eachlineheight:D
758	_kernel_primitive:NN	\pdfelapsedtime	\tex_elapsedtime:D
759	_kernel_primitive:NN	\pdffiledump	\tex_filedump:D
760	_kernel_primitive:NN	\pdffilemoddate	\tex_filemoddate:D
761	_kernel_primitive:NN	\pdffilesize	\tex_filesize:D
762	_kernel_primitive:NN	\pdffirstlineheight	\tex_firstlineheight:D
763	_kernel_primitive:NN	\pdffontexpand	\tex_fontexpand:D
764	_kernel_primitive:NN	\pdffontsize	\tex_fontsize:D
765	_kernel_primitive:NN	\pdfignoreddimen	\tex_ignoreddimen:D
766	_kernel_primitive:NN	\pdfinsertht	\tex_insertht:D
767	_kernel_primitive:NN	\pdflastlinedepth	\tex_lastlinedepth:D
768	_kernel_primitive:NN	\pdflastxpos	\tex_lastxpos:D
769	_kernel_primitive:NN	\pdflastypos	\tex_lastypos:D
770	_kernel_primitive:NN	\pdfmapfile	\tex_mapfile:D
771	_kernel_primitive:NN	\pdfmapline	\tex_mapline:D
772	_kernel_primitive:NN	\pdfmdfivesum	\tex_mdfivesum:D
773	_kernel_primitive:NN	\pdfnoligatures	\tex_noligatures:D
774	_kernel_primitive:NN	\pdfnormaldeviate	\tex_normaldeviate:D

```

775 \__kernel_primitive:NN \pdfpageheight \tex_pageheight:D
776 \__kernel_primitive:NN \pdfpagewidth \tex_pagewidth:D
777 \__kernel_primitive:NN \pdfpkmode \tex_pkmode:D
778 \__kernel_primitive:NN \pdfpkresolution \tex_pkresolution:D
779 \__kernel_primitive:NN \pdfprimitive \tex_primitive:D
780 \__kernel_primitive:NN \pdfprotrudechars \tex_protrudechars:D
781 \__kernel_primitive:NN \pdfpxdimen \tex_pxdimen:D
782 \__kernel_primitive:NN \pdfrandomseed \tex_randomseed:D
783 \__kernel_primitive:NN \pdfresettimer \tex_resettimer:D
784 \__kernel_primitive:NN \pdfsavepos \tex_savepos:D
785 \__kernel_primitive:NN \pdfstrcmp \tex_strcmp:D
786 \__kernel_primitive:NN \pdfsetrandomseed \tex_setrandomseed:D
787 \__kernel_primitive:NN \pdfshellescape \tex_shellescape:D
788 \__kernel_primitive:NN \pdftracingfonts \tex_tracingfonts:D
789 \__kernel_primitive:NN \pdfuniformdeviate \tex_uniformdeviate:D

```

The version primitives are not related to PDF mode but are pdfTeX-specific, so again are carried forward unchanged.

```

790 \__kernel_primitive:NN \pdfTeXbanner \tex_pdfTeXbanner:D
791 \__kernel_primitive:NN \pdfTeXrevision \tex_pdfTeXrevision:D
792 \__kernel_primitive:NN \pdfTeXversion \tex_pdfTeXversion:D

```

These ones appear in pdfTeX but don't have pdf in the name at all: no decisions to make.

```

793 \__kernel_primitive:NN \efcode \tex_efcode:D
794 \__kernel_primitive:NN \ifincsname \tex_ifincsname:D
795 \__kernel_primitive:NN \leftmarginkern \tex_leftmarginkern:D
796 \__kernel_primitive:NN \letterspacefont \tex_letterspacefont:D
797 \__kernel_primitive:NN \lpcode \tex_lpcode:D
798 \__kernel_primitive:NN \quitvmode \tex_quitvmode:D
799 \__kernel_primitive:NN \rightmarginkern \tex_rightmarginkern:D
800 \__kernel_primitive:NN \rpcode \tex_rpcode:D
801 \__kernel_primitive:NN \synctex \tex_synctex:D
802 \__kernel_primitive:NN \tagcode \tex_tagcode:D

```

Post pdfTeX primitive availability gets more complex. Both XeTeX and LuaTeX have varying names for some primitives from pdfTeX. Particularly for LuaTeX tracking all of that would be hard. Instead, we now check that we only save primitives if they actually exist.

```

803 </initex | names | package>
804 <*initex | package>
805 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
806 \tex_long:D \tex_def:D \use_none:n #1 { }
807 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
808 {
809 \tex_ifdefined:D #1
810 \tex_expandafter:D \use_ii:nn
811 \tex_fi:D
812 \use_none:n { \tex_global:D \tex_let:D #2 #1 }
813 <*initex>
814 \tex_global:D \tex_let:D #1 \tex_undefined:D
815 </initex>
816 }
817 </initex | package>
818 <*initex | names | package>

```

X_YTeX-specific primitives. Note that X_YTeX's `\strcmp` is handled earlier and is “rolled up” into `\pdfstrcmp`. A few cross-compatibility names which lack the pdf of the original are handled later.

```

819 \__kernel_primitive:NN \suppressfontnotfounderror
820 \tex_suppressfontnotfounderror:D
821 \__kernel_primitive:NN \XeTeXcharclass \tex_XeTeXcharclass:D
822 \__kernel_primitive:NN \XeTeXcharglyph \tex_XeTeXcharglyph:D
823 \__kernel_primitive:NN \XeTeXcountfeatures \tex_XeTeXcountfeatures:D
824 \__kernel_primitive:NN \XeTeXcountglyphs \tex_XeTeXcountglyphs:D
825 \__kernel_primitive:NN \XeTeXcountselectors \tex_XeTeXcountselectors:D
826 \__kernel_primitive:NN \XeTeXcountvariations \tex_XeTeXcountvariations:D
827 \__kernel_primitive:NN \XeTeXdefaultencoding \tex_XeTeXdefaultencoding:D
828 \__kernel_primitive:NN \XeTeXdashbreakstate \tex_XeTeXdashbreakstate:D
829 \__kernel_primitive:NN \XeTeXfeaturecode \tex_XeTeXfeaturecode:D
830 \__kernel_primitive:NN \XeTeXfeaturename \tex_XeTeXfeaturename:D
831 \__kernel_primitive:NN \XeTeXfindfeaturebyname
832 \tex_XeTeXfindfeaturebyname:D
833 \__kernel_primitive:NN \XeTeXfindselectorbyname
834 \tex_XeTeXfindselectorbyname:D
835 \__kernel_primitive:NN \XeTeXfindvariationbyname
836 \tex_XeTeXfindvariationbyname:D
837 \__kernel_primitive:NN \XeTeXfirstfontchar \tex_XeTeXfirstfontchar:D
838 \__kernel_primitive:NN \XeTeXfonttype \tex_XeTeXfonttype:D
839 \__kernel_primitive:NN \XeTeXgenerateactualtext
840 \tex_XeTeXgenerateactualtext:D
841 \__kernel_primitive:NN \XeTeXglyph \tex_XeTeXglyph:D
842 \__kernel_primitive:NN \XeTeXglyphbounds \tex_XeTeXglyphbounds:D
843 \__kernel_primitive:NN \XeTeXglyphindex \tex_XeTeXglyphindex:D
844 \__kernel_primitive:NN \XeTeXglyphname \tex_XeTeXglyphname:D
845 \__kernel_primitive:NN \XeTeXinputencoding \tex_XeTeXinputencoding:D
846 \__kernel_primitive:NN \XeTeXinputnormalization
847 \tex_XeTeXinputnormalization:D
848 \__kernel_primitive:NN \XeTeXinterchartokenstate
849 \tex_XeTeXinterchartokenstate:D
850 \__kernel_primitive:NN \XeTeXinterchartoks \tex_XeTeXinterchartoks:D
851 \__kernel_primitive:NN \XeTeXisdefaultselector
852 \tex_XeTeXisdefaultselector:D
853 \__kernel_primitive:NN \XeTeXisexclusivefeature
854 \tex_XeTeXisexclusivefeature:D
855 \__kernel_primitive:NN \XeTeXlastfontchar \tex_XeTeXlastfontchar:D
856 \__kernel_primitive:NN \XeTeXlinebreakskip \tex_XeTeXlinebreakskip:D
857 \__kernel_primitive:NN \XeTeXlinebreaklocale \tex_XeTeXlinebreaklocale:D
858 \__kernel_primitive:NN \XeTeXlinebreakpenalty \tex_XeTeXlinebreakpenalty:D
859 \__kernel_primitive:NN \XeTeXOTcountfeatures \tex_XeTeXOTcountfeatures:D
860 \__kernel_primitive:NN \XeTeXOTcountlanguages \tex_XeTeXOTcountlanguages:D
861 \__kernel_primitive:NN \XeTeXOTcountscripts \tex_XeTeXOTcountscripts:D
862 \__kernel_primitive:NN \XeTeXOTfeaturetag \tex_XeTeXOTfeaturetag:D
863 \__kernel_primitive:NN \XeTeXOTlanguagetag \tex_XeTeXOTlanguagetag:D
864 \__kernel_primitive:NN \XeTeXOTscripttag \tex_XeTeXOTscripttag:D
865 \__kernel_primitive:NN \XeTeXpdffile \tex_XeTeXpdffile:D
866 \__kernel_primitive:NN \XeTeXpdfpagecount \tex_XeTeXpdfpagecount:D
867 \__kernel_primitive:NN \XeTeXpicfile \tex_XeTeXpicfile:D
868 \__kernel_primitive:NN \XeTeXrevision \tex_XeTeXrevision:D
869 \__kernel_primitive:NN \XeTeXselectorname \tex_XeTeXselectorname:D

```

870	<code>__kernel_primitive:NN</code>	<code>\XeTeXtracingfonts</code>	<code>\tex_XeTeXtracingfonts:D</code>
871	<code>__kernel_primitive:NN</code>	<code>\XeTeXupwardsmode</code>	<code>\tex_XeTeXupwardsmode:D</code>
872	<code>__kernel_primitive:NN</code>	<code>\XeTeXuseglyphmetrics</code>	<code>\tex_XeTeXuseglyphmetrics:D</code>
873	<code>__kernel_primitive:NN</code>	<code>\XeTeXvariation</code>	<code>\tex_XeTeXvariation:D</code>
874	<code>__kernel_primitive:NN</code>	<code>\XeTeXvariationdefault</code>	<code>\tex_XeTeXvariationdefault:D</code>
875	<code>__kernel_primitive:NN</code>	<code>\XeTeXvariationmax</code>	<code>\tex_XeTeXvariationmax:D</code>
876	<code>__kernel_primitive:NN</code>	<code>\XeTeXvariationmin</code>	<code>\tex_XeTeXvariationmin:D</code>
877	<code>__kernel_primitive:NN</code>	<code>\XeTeXvariationname</code>	<code>\tex_XeTeXvariationname:D</code>
878	<code>__kernel_primitive:NN</code>	<code>\XeTeXversion</code>	<code>\tex_XeTeXversion:D</code>

Primitives from pdf \TeX that X \TeX renames: also helps with Lua \TeX .

879	<code>__kernel_primitive:NN</code>	<code>\creationdate</code>	<code>\tex_creationdate:D</code>
880	<code>__kernel_primitive:NN</code>	<code>\elapsedtime</code>	<code>\tex_elapsedtime:D</code>
881	<code>__kernel_primitive:NN</code>	<code>\filedump</code>	<code>\tex_filedump:D</code>
882	<code>__kernel_primitive:NN</code>	<code>\filemoddate</code>	<code>\tex_filemoddate:D</code>
883	<code>__kernel_primitive:NN</code>	<code>\filesize</code>	<code>\tex_filesize:D</code>
884	<code>__kernel_primitive:NN</code>	<code>\mdfivesum</code>	<code>\tex_mdfivesum:D</code>
885	<code>__kernel_primitive:NN</code>	<code>\ifprimitive</code>	<code>\tex_ifprimitive:D</code>
886	<code>__kernel_primitive:NN</code>	<code>\primitive</code>	<code>\tex_primitive:D</code>
887	<code>__kernel_primitive:NN</code>	<code>\resettimer</code>	<code>\tex_resettimer:D</code>
888	<code>__kernel_primitive:NN</code>	<code>\shellescape</code>	<code>\tex_shellescape:D</code>

Primitives from Lua \TeX , some of which have been ported back to X \TeX .

889	<code>__kernel_primitive:NN</code>	<code>\alignmark</code>	<code>\tex_alignmark:D</code>
890	<code>__kernel_primitive:NN</code>	<code>\aligntab</code>	<code>\tex_aligntab:D</code>
891	<code>__kernel_primitive:NN</code>	<code>\attribute</code>	<code>\tex_attribute:D</code>
892	<code>__kernel_primitive:NN</code>	<code>\attributedef</code>	<code>\tex_attributedef:D</code>
893	<code>__kernel_primitive:NN</code>	<code>\automaticdiscretionary</code>	
894		<code>\tex_automaticdiscretionary:D</code>	
895	<code>__kernel_primitive:NN</code>	<code>\automatichyphenmode</code>	<code>\tex_automatichyphenmode:D</code>
896	<code>__kernel_primitive:NN</code>	<code>\automatichyphenpenalty</code>	
897		<code>\tex_automatichyphenpenalty:D</code>	
898	<code>__kernel_primitive:NN</code>	<code>\beginscname</code>	<code>\tex_beginscname:D</code>
899	<code>__kernel_primitive:NN</code>	<code>\bodydir</code>	<code>\tex_bodydir:D</code>
900	<code>__kernel_primitive:NN</code>	<code>\bodydirection</code>	<code>\tex_bodydirection:D</code>
901	<code>__kernel_primitive:NN</code>	<code>\boxdir</code>	<code>\tex_boxdir:D</code>
902	<code>__kernel_primitive:NN</code>	<code>\boxdirection</code>	<code>\tex_boxdirection:D</code>
903	<code>__kernel_primitive:NN</code>	<code>\breakafterdirmode</code>	<code>\tex_breakafterdirmode:D</code>
904	<code>__kernel_primitive:NN</code>	<code>\catcodetable</code>	<code>\tex_catcodetable:D</code>
905	<code>__kernel_primitive:NN</code>	<code>\clearmarks</code>	<code>\tex_clearmarks:D</code>
906	<code>__kernel_primitive:NN</code>	<code>\crampeddisplaystyle</code>	<code>\tex_crampeddisplaystyle:D</code>
907	<code>__kernel_primitive:NN</code>	<code>\crampedscriptscriptstyle</code>	
908		<code>\tex_crampedscriptscriptstyle:D</code>	
909	<code>__kernel_primitive:NN</code>	<code>\crampedscriptstyle</code>	<code>\tex_crampedscriptstyle:D</code>
910	<code>__kernel_primitive:NN</code>	<code>\crampedtextstyle</code>	<code>\tex_crampedtextstyle:D</code>
911	<code>__kernel_primitive:NN</code>	<code>\csstring</code>	<code>\tex_csstring:D</code>
912	<code>__kernel_primitive:NN</code>	<code>\directlua</code>	<code>\tex_directlua:D</code>
913	<code>__kernel_primitive:NN</code>	<code>\dviextension</code>	<code>\tex_dviextension:D</code>
914	<code>__kernel_primitive:NN</code>	<code>\dvifedback</code>	<code>\tex_dvifedback:D</code>
915	<code>__kernel_primitive:NN</code>	<code>\dvivariable</code>	<code>\tex_dvivariable:D</code>
916	<code>__kernel_primitive:NN</code>	<code>\etoksapp</code>	<code>\tex_etoksapp:D</code>
917	<code>__kernel_primitive:NN</code>	<code>\etokspre</code>	<code>\tex_etokspre:D</code>
918	<code>__kernel_primitive:NN</code>	<code>\exceptionpenalty</code>	<code>\tex_exceptionpenalty:D</code>
919	<code>__kernel_primitive:NN</code>	<code>\explicithyphenpenalty</code>	<code>\tex_explicithyphenpenalty:D</code>
920	<code>__kernel_primitive:NN</code>	<code>\expanded</code>	<code>\tex_expanded:D</code>

921	_kernel_primitive:NN	\explicitdiscretionary	\tex_explicitdiscretionary:D
922	_kernel_primitive:NN	\firstvalidlanguage	\tex_firstvalidlanguage:D
923	_kernel_primitive:NN	\fontid	\tex_fontid:D
924	_kernel_primitive:NN	\formatname	\tex_formatname:D
925	_kernel_primitive:NN	\hjcode	\tex_hjcode:D
926	_kernel_primitive:NN	\hpack	\tex_hpack:D
927	_kernel_primitive:NN	\hyphenationbounds	\tex_hyphenationbounds:D
928	_kernel_primitive:NN	\hyphenationmin	\tex_hyphenationmin:D
929	_kernel_primitive:NN	\hyphenpenaltymode	\tex_hyphenpenaltymode:D
930	_kernel_primitive:NN	\gleaders	\tex_gleaders:D
931	_kernel_primitive:NN	\ifcondition	\tex_ifcondition:D
932	_kernel_primitive:NN	\immediateassigned	\tex_immediateassigned:D
933	_kernel_primitive:NN	\immediateassignment	\tex_immediateassignment:D
934	_kernel_primitive:NN	\initcatcodetable	\tex_initcatcodetable:D
935	_kernel_primitive:NN	\lastnamedcs	\tex_lastnamedcs:D
936	_kernel_primitive:NN	\latelua	\tex_latelua:D
937	_kernel_primitive:NN	\lateluafunction	\tex_lateluafunction:D
938	_kernel_primitive:NN	\leftghost	\tex_leftghost:D
939	_kernel_primitive:NN	\letcharcode	\tex_letcharcode:D
940	_kernel_primitive:NN	\linedir	\tex_linedir:D
941	_kernel_primitive:NN	\linedirection	\tex_linedirection:D
942	_kernel_primitive:NN	\localbrokenpenalty	\tex_localbrokenpenalty:D
943	_kernel_primitive:NN	\localinterlinepenalty	\tex_localinterlinepenalty:D
944	_kernel_primitive:NN	\luabytecode	\tex_luabytecode:D
945	_kernel_primitive:NN	\luabytecodecall	\tex_luabytecodecall:D
946	_kernel_primitive:NN	\luacopyinputnodes	\tex_luacopyinputnodes:D
947	_kernel_primitive:NN	\luadef	\tex_luadef:D
948	_kernel_primitive:NN	\llocalleftbox	\tex_llocalleftbox:D
949	_kernel_primitive:NN	\llocalrightbox	\tex_llocalrightbox:D
950	_kernel_primitive:NN	\luaescapestring	\tex_luaescapestring:D
951	_kernel_primitive:NN	\luafunction	\tex_luafunction:D
952	_kernel_primitive:NN	\luafunctioncall	\tex_luafunctioncall:D
953	_kernel_primitive:NN	\luatexbanner	\tex_luatexbanner:D
954	_kernel_primitive:NN	\luatexrevision	\tex_luatexrevision:D
955	_kernel_primitive:NN	\luatexversion	\tex_luatexversion:D
956	_kernel_primitive:NN	\mathdelimitersmode	\tex_mathdelimitersmode:D
957	_kernel_primitive:NN	\mathdir	\tex_mathdir:D
958	_kernel_primitive:NN	\mathdirection	\tex_mathdirection:D
959	_kernel_primitive:NN	\mathdisplayskipmode	\tex_mathdisplayskipmode:D
960	_kernel_primitive:NN	\matheqnogapstep	\tex_matheqnogapstep:D
961	_kernel_primitive:NN	\mathnolimitsmode	\tex_mathnolimitsmode:D
962	_kernel_primitive:NN	\mathoption	\tex_mathoption:D
963	_kernel_primitive:NN	\mathpenaltiesmode	\tex_mathpenaltiesmode:D
964	_kernel_primitive:NN	\mathrulesfam	\tex_mathrulesfam:D
965	_kernel_primitive:NN	\mathscriptsmode	\tex_mathscriptsmode:D
966	_kernel_primitive:NN	\mathscriptboxmode	\tex_mathscriptboxmode:D
967	_kernel_primitive:NN	\mathscriptcharmode	\tex_mathscriptcharmode:D
968	_kernel_primitive:NN	\mathstyle	\tex_mathstyle:D
969	_kernel_primitive:NN	\mathsurroundmode	\tex_mathsurroundmode:D
970	_kernel_primitive:NN	\mathsurroundskip	\tex_mathsurroundskip:D
971	_kernel_primitive:NN	\nohrule	\tex_nohrule:D
972	_kernel_primitive:NN	\nokerns	\tex_nokerns:D
973	_kernel_primitive:NN	\noligs	\tex_noligs:D
974	_kernel_primitive:NN	\nospaces	\tex_nospaces:D

975	_kernel_primitive:NN	\novrule	\tex_novrule:D
976	_kernel_primitive:NN	\outputbox	\tex_outputbox:D
977	_kernel_primitive:NN	\pagebottomoffset	\tex_pagebottomoffset:D
978	_kernel_primitive:NN	\pagedir	\tex_pagedir:D
979	_kernel_primitive:NN	\pagedirection	\tex_pagedirection:D
980	_kernel_primitive:NN	\pageleftoffset	\tex_pageleftoffset:D
981	_kernel_primitive:NN	\pagerightoffset	\tex_pagerightoffset:D
982	_kernel_primitive:NN	\pagetopoffset	\tex_pagetopoffset:D
983	_kernel_primitive:NN	\pardir	\tex_pardir:D
984	_kernel_primitive:NN	\pardirection	\tex_pardirection:D
985	_kernel_primitive:NN	\pdfextension	\tex_pdfextension:D
986	_kernel_primitive:NN	\pdffeedback	\tex_pdffeedback:D
987	_kernel_primitive:NN	\pdfvariable	\tex_pdfvariable:D
988	_kernel_primitive:NN	\postexhyphenchar	\tex_postexhyphenchar:D
989	_kernel_primitive:NN	\posthyphenchar	\tex_posthyphenchar:D
990	_kernel_primitive:NN	\prebinoppenalty	\tex_prebinoppenalty:D
991	_kernel_primitive:NN	\predisplaygapfactor	\tex_predisplaygapfactor:D
992	_kernel_primitive:NN	\preexhyphenchar	\tex_preexhyphenchar:D
993	_kernel_primitive:NN	\prehyphenchar	\tex_prehyphenchar:D
994	_kernel_primitive:NN	\prerelpenalty	\tex_prerelpenalty:D
995	_kernel_primitive:NN	\rightghost	\tex_rightghost:D
996	_kernel_primitive:NN	\savecatcodetable	\tex_savecatcodetable:D
997	_kernel_primitive:NN	\scantextokens	\tex_scantextokens:D
998	_kernel_primitive:NN	\setfontid	\tex_setfontid:D
999	_kernel_primitive:NN	\shapemode	\tex_shapemode:D
1000	_kernel_primitive:NN	\suppressifcsnameerror	\tex_suppressifcsnameerror:D
1001	_kernel_primitive:NN	\suppresslongerror	\tex_suppresslongerror:D
1002	_kernel_primitive:NN	\suppressmathparerror	\tex_suppressmathparerror:D
1003	_kernel_primitive:NN	\suppressoutererror	\tex_suppressoutererror:D
1004	_kernel_primitive:NN	\suppressprimitiveerror	\tex_suppressprimitiveerror:D
1005	_kernel_primitive:NN	\textdir	\tex_textdir:D
1006	_kernel_primitive:NN	\tex_textdir	\tex_textdir:D
1007	_kernel_primitive:NN	\tex_texdirection	\tex_texdirection:D
1008	_kernel_primitive:NN	\toksapp	\tex_toksapp:D
1009	_kernel_primitive:NN	\tokspre	\tex_tokspre:D
1010	_kernel_primitive:NN	\tpack	\tex_tpack:D
1011	_kernel_primitive:NN	\vpack	\tex_vpack:D

Primitives from pdfTeX that LuaTeX renames.

1012	_kernel_primitive:NN	\adjustspacing	\tex_adjustspacing:D
1013	_kernel_primitive:NN	\copyfont	\tex_copyfont:D
1014	_kernel_primitive:NN	\draftmode	\tex_draftmode:D
1015	_kernel_primitive:NN	\expandglyphsinfont	\tex_fontexpand:D
1016	_kernel_primitive:NN	\ifabsdim	\tex_ifabsdim:D
1017	_kernel_primitive:NN	\ifabsnum	\tex_ifabsnum:D
1018	_kernel_primitive:NN	\ignoreligaturesinfont	\tex_ignoreligaturesinfont:D
1019	_kernel_primitive:NN	\insertht	\tex_insertht:D
1020	_kernel_primitive:NN	\lastsavedboxresourceindex	\tex_pdfastxform:D
1021	_kernel_primitive:NN	\lastsavedboxresourceindex	\tex_pdfastxform:D
1022	_kernel_primitive:NN	\lastsavedimageresourceindex	\tex_pdfastximage:D
1023	_kernel_primitive:NN	\lastsavedimageresourceindex	\tex_pdfastximage:D
1024	_kernel_primitive:NN	\lastsavedimageresourcepages	\tex_pdfastximagepages:D
1025	_kernel_primitive:NN	\lastxpos	\tex_lastxpos:D
1026	_kernel_primitive:NN	\lastypos	\tex_lastypos:D
1027	_kernel_primitive:NN	\lastypos	\tex_lastypos:D

1028	<code>__kernel_primitive:NN</code>	<code>\normaldeviate</code>	<code>\tex_normaldeviate:D</code>
1029	<code>__kernel_primitive:NN</code>	<code>\outputmode</code>	<code>\tex_pdfoutput:D</code>
1030	<code>__kernel_primitive:NN</code>	<code>\pageheight</code>	<code>\tex_pageheight:D</code>
1031	<code>__kernel_primitive:NN</code>	<code>\pagewidth</code>	<code>\tex_pagewidth:D</code>
1032	<code>__kernel_primitive:NN</code>	<code>\protrudechars</code>	<code>\tex_protrudechars:D</code>
1033	<code>__kernel_primitive:NN</code>	<code>\pxdimen</code>	<code>\tex_pxdimen:D</code>
1034	<code>__kernel_primitive:NN</code>	<code>\randomseed</code>	<code>\tex_randomseed:D</code>
1035	<code>__kernel_primitive:NN</code>	<code>\useboxresource</code>	<code>\tex_pdfrefxform:D</code>
1036	<code>__kernel_primitive:NN</code>	<code>\useimageresource</code>	<code>\tex_pdfrefximage:D</code>
1037	<code>__kernel_primitive:NN</code>	<code>\savepos</code>	<code>\tex_savepos:D</code>
1038	<code>__kernel_primitive:NN</code>	<code>\saveboxresource</code>	<code>\tex_pdfxform:D</code>
1039	<code>__kernel_primitive:NN</code>	<code>\saveimageresource</code>	<code>\tex_pdfximage:D</code>
1040	<code>__kernel_primitive:NN</code>	<code>\setrandomseed</code>	<code>\tex_setrandomseed:D</code>
1041	<code>__kernel_primitive:NN</code>	<code>\tracingfonts</code>	<code>\tex_tracingfonts:D</code>
1042	<code>__kernel_primitive:NN</code>	<code>\uniformdeviate</code>	<code>\tex_uniformdeviate:D</code>

The set of Unicode math primitives were introduced by XeTeX and LuaTeX in a somewhat complex fashion: a few first as `\XeTeX...` which were then renamed with LuaTeX having a lot more. These names now all start `\U...` and mainly `\Umath...`.

1043	<code>__kernel_primitive:NN</code>	<code>\Uchar</code>	<code>\tex_Uchar:D</code>
1044	<code>__kernel_primitive:NN</code>	<code>\Ucharcat</code>	<code>\tex_Ucharcat:D</code>
1045	<code>__kernel_primitive:NN</code>	<code>\Udelcode</code>	<code>\tex_Udelcode:D</code>
1046	<code>__kernel_primitive:NN</code>	<code>\Udelcodenum</code>	<code>\tex_Udelcodenum:D</code>
1047	<code>__kernel_primitive:NN</code>	<code>\Udelimiter</code>	<code>\tex_Udelimiter:D</code>
1048	<code>__kernel_primitive:NN</code>	<code>\Udelimiterover</code>	<code>\tex_Udelimiterover:D</code>
1049	<code>__kernel_primitive:NN</code>	<code>\Udelimiterunder</code>	<code>\tex_Udelimiterunder:D</code>
1050	<code>__kernel_primitive:NN</code>	<code>\Uhextensible</code>	<code>\tex_Uhextensible:D</code>
1051	<code>__kernel_primitive:NN</code>	<code>\Umathaccent</code>	<code>\tex_Umathaccent:D</code>
1052	<code>__kernel_primitive:NN</code>	<code>\Umathaxis</code>	<code>\tex_Umathaxis:D</code>
1053	<code>__kernel_primitive:NN</code>	<code>\Umathbinbinspacing</code>	<code>\tex_Umathbinbinspacing:D</code>
1054	<code>__kernel_primitive:NN</code>	<code>\Umathbinclosespacing</code>	<code>\tex_Umathbinclosespacing:D</code>
1055	<code>__kernel_primitive:NN</code>	<code>\Umathbininnerspacing</code>	<code>\tex_Umathbininnerspacing:D</code>
1056	<code>__kernel_primitive:NN</code>	<code>\Umathbinopenspacing</code>	<code>\tex_Umathbinopenspacing:D</code>
1057	<code>__kernel_primitive:NN</code>	<code>\Umathbinopspacing</code>	<code>\tex_Umathbinopspacing:D</code>
1058	<code>__kernel_primitive:NN</code>	<code>\Umathbinordspacing</code>	<code>\tex_Umathbinordspacing:D</code>
1059	<code>__kernel_primitive:NN</code>	<code>\Umathbinpunctspacing</code>	<code>\tex_Umathbinpunctspacing:D</code>
1060	<code>__kernel_primitive:NN</code>	<code>\Umathbinrelspacing</code>	<code>\tex_Umathbinrelspacing:D</code>
1061	<code>__kernel_primitive:NN</code>	<code>\Umathchar</code>	<code>\tex_Umathchar:D</code>
1062	<code>__kernel_primitive:NN</code>	<code>\Umathcharclass</code>	<code>\tex_Umathcharclass:D</code>
1063	<code>__kernel_primitive:NN</code>	<code>\Umathchardef</code>	<code>\tex_Umathchardef:D</code>
1064	<code>__kernel_primitive:NN</code>	<code>\Umathcharfam</code>	<code>\tex_Umathcharfam:D</code>
1065	<code>__kernel_primitive:NN</code>	<code>\Umathcharnum</code>	<code>\tex_Umathcharnum:D</code>
1066	<code>__kernel_primitive:NN</code>	<code>\Umathcharnumdef</code>	<code>\tex_Umathcharnumdef:D</code>
1067	<code>__kernel_primitive:NN</code>	<code>\Umathcharslot</code>	<code>\tex_Umathcharslot:D</code>
1068	<code>__kernel_primitive:NN</code>	<code>\Umathclosebinspacing</code>	<code>\tex_Umathclosebinspacing:D</code>
1069	<code>__kernel_primitive:NN</code>	<code>\Umathcloseclosespacing</code>	<code>\tex_Umathcloseclosespacing:D</code>
1070		<code>\tex_Umathcloseclosespacing:D</code>	
1071	<code>__kernel_primitive:NN</code>	<code>\Umathcloseinnerspacing</code>	
1072		<code>\tex_Umathcloseinnerspacing:D</code>	
1073	<code>__kernel_primitive:NN</code>	<code>\Umathcloseopenspacing</code>	<code>\tex_Umathcloseopenspacing:D</code>
1074	<code>__kernel_primitive:NN</code>	<code>\Umathcloseopspacing</code>	<code>\tex_Umathcloseopspacing:D</code>
1075	<code>__kernel_primitive:NN</code>	<code>\Umathcloseordspacing</code>	<code>\tex_Umathcloseordspacing:D</code>
1076	<code>__kernel_primitive:NN</code>	<code>\Umathclosepunctspacing</code>	
1077		<code>\tex_Umathclosepunctspacing:D</code>	


```

1078 \__kernel_primitive:NN \Umathcloserelspacing \tex_Umathcloserelspacing:D
1079 \__kernel_primitive:NN \Umathcode \tex_Umathcode:D
1080 \__kernel_primitive:NN \Umathcodenum \tex_Umathcodenum:D
1081 \__kernel_primitive:NN \Umathconnectoroverlapmin
1082 \tex_Umathconnectoroverlapmin:D
1083 \__kernel_primitive:NN \Umathfractiondelsize \tex_Umathfractiondelsize:D
1084 \__kernel_primitive:NN \Umathfractiondenomdown
1085 \tex_Umathfractiondenomdown:D
1086 \__kernel_primitive:NN \Umathfractiondenomvgap
1087 \tex_Umathfractiondenomvgap:D
1088 \__kernel_primitive:NN \Umathfractionnumup \tex_Umathfractionnumup:D
1089 \__kernel_primitive:NN \Umathfractionnumvgap \tex_Umathfractionnumvgap:D
1090 \__kernel_primitive:NN \Umathfractionrule \tex_Umathfractionrule:D
1091 \__kernel_primitive:NN \Umathinnerbinspacing \tex_Umathinnerbinspacing:D
1092 \__kernel_primitive:NN \Umathinnerclosespacing
1093 \tex_Umathinnerclosespacing:D
1094 \__kernel_primitive:NN \Umathinnerinnerspacing
1095 \tex_Umathinnerinnerspacing:D
1096 \__kernel_primitive:NN \Umathinneropenspacing \tex_Umathinneropenspacing:D
1097 \__kernel_primitive:NN \Umathinneropspacing \tex_Umathinneropspacing:D
1098 \__kernel_primitive:NN \Umathinnerordspacing \tex_Umathinnerordspacing:D
1099 \__kernel_primitive:NN \Umathinnerpunctspacing
1100 \tex_Umathinnerpunctspacing:D
1101 \__kernel_primitive:NN \Umathinnerrelspacing \tex_Umathinnerrelspacing:D
1102 \__kernel_primitive:NN \Umathlimitabovebgap \tex_Umathlimitabovebgap:D
1103 \__kernel_primitive:NN \Umathlimitabovekern \tex_Umathlimitabovekern:D
1104 \__kernel_primitive:NN \Umathlimitabovevgap \tex_Umathlimitabovevgap:D
1105 \__kernel_primitive:NN \Umathlimitbelowbgap \tex_Umathlimitbelowbgap:D
1106 \__kernel_primitive:NN \Umathlimitbelowkern \tex_Umathlimitbelowkern:D
1107 \__kernel_primitive:NN \Umathlimitbelowvgap \tex_Umathlimitbelowvgap:D
1108 \__kernel_primitive:NN \Umathnolimitsubfactor \tex_Umathnolimitsubfactor:D
1109 \__kernel_primitive:NN \Umathnolimitsupfactor \tex_Umathnolimitsupfactor:D
1110 \__kernel_primitive:NN \Umathopbinspacing \tex_Umathopbinspacing:D
1111 \__kernel_primitive:NN \Umathopclosespacing \tex_Umathopclosespacing:D
1112 \__kernel_primitive:NN \Umathopenbinspacing \tex_Umathopenbinspacing:D
1113 \__kernel_primitive:NN \Umathopenclosespacing \tex_Umathopenclosespacing:D
1114 \__kernel_primitive:NN \Umathopeninnerspacing \tex_Umathopeninnerspacing:D
1115 \__kernel_primitive:NN \Umathopenopenspacing \tex_Umathopenopenspacing:D
1116 \__kernel_primitive:NN \Umathopenopspacing \tex_Umathopenopspacing:D
1117 \__kernel_primitive:NN \Umathopenordspacing \tex_Umathopenordspacing:D
1118 \__kernel_primitive:NN \Umathopenpunctspacing \tex_Umathopenpunctspacing:D
1119 \__kernel_primitive:NN \Umathopenrelspacing \tex_Umathopenrelspacing:D
1120 \__kernel_primitive:NN \Umathoperatorsize \tex_Umathoperatorsize:D
1121 \__kernel_primitive:NN \Umathopinnerspacing \tex_Umathopinnerspacing:D
1122 \__kernel_primitive:NN \Umathopopenspacing \tex_Umathopopenspacing:D
1123 \__kernel_primitive:NN \Umathopopspacing \tex_Umathopopspacing:D
1124 \__kernel_primitive:NN \Umathopordspacing \tex_Umathopordspacing:D
1125 \__kernel_primitive:NN \Umathoppunctspacing \tex_Umathoppunctspacing:D
1126 \__kernel_primitive:NN \Umathoprelspacing \tex_Umathoprelspacing:D
1127 \__kernel_primitive:NN \Umathordbinspacing \tex_Umathordbinspacing:D
1128 \__kernel_primitive:NN \Umathordclosespacing \tex_Umathordclosespacing:D
1129 \__kernel_primitive:NN \Umathordinnerspacing \tex_Umathordinnerspacing:D
1130 \__kernel_primitive:NN \Umathordopenspacing \tex_Umathordopenspacing:D
1131 \__kernel_primitive:NN \Umathordopspacing \tex_Umathordopspacing:D

```

1132	_kernel_primitive:NN	\Umathordordspacing	\tex_Umathordordspacing:D
1133	_kernel_primitive:NN	\Umathordpunctspacing	\tex_Umathordpunctspacing:D
1134	_kernel_primitive:NN	\Umathordrelspacing	\tex_Umathordrelspacing:D
1135	_kernel_primitive:NN	\Umathoverbarkern	\tex_Umathoverbarkern:D
1136	_kernel_primitive:NN	\Umathoverbarrule	\tex_Umathoverbarrule:D
1137	_kernel_primitive:NN	\Umathoverbarvgap	\tex_Umathoverbarvgap:D
1138	_kernel_primitive:NN	\Umathoverdelimeterbgap	
1139		\tex_Umathoverdelimeterbgap:D	
1140	_kernel_primitive:NN	\Umathoverdelimitervgap	
1141		\tex_Umathoverdelimitervgap:D	
1142	_kernel_primitive:NN	\Umathpunctbinspacing	\tex_Umathpunctbinspacing:D
1143	_kernel_primitive:NN	\Umathpunctclosespacing	
1144		\tex_Umathpunctclosespacing:D	
1145	_kernel_primitive:NN	\Umathpunctinnerspacing	
1146		\tex_Umathpunctinnerspacing:D	
1147	_kernel_primitive:NN	\Umathpunctopenspacing	\tex_Umathpunctopenspacing:D
1148	_kernel_primitive:NN	\Umathpuncttopspacing	\tex_Umathpuncttopspacing:D
1149	_kernel_primitive:NN	\Umathpunctordspacing	\tex_Umathpunctordspacing:D
1150	_kernel_primitive:NN	\Umathpunctpunctspacing	
1151		\tex_Umathpunctpunctspacing:D	
1152	_kernel_primitive:NN	\Umathpunctrelspacing	\tex_Umathpunctrelspacing:D
1153	_kernel_primitive:NN	\Umathquad	\tex_Umathquad:D
1154	_kernel_primitive:NN	\Umathradicaldegreeafter	
1155		\tex_Umathradicaldegreeafter:D	
1156	_kernel_primitive:NN	\Umathradicaldegreebefore	
1157		\tex_Umathradicaldegreebefore:D	
1158	_kernel_primitive:NN	\Umathradicaldegreeraise	
1159		\tex_Umathradicaldegreeraise:D	
1160	_kernel_primitive:NN	\Umathradicalkern	\tex_Umathradicalkern:D
1161	_kernel_primitive:NN	\Umathradicalrule	\tex_Umathradicalrule:D
1162	_kernel_primitive:NN	\Umathradicalvgap	\tex_Umathradicalvgap:D
1163	_kernel_primitive:NN	\Umathrelbinspacing	\tex_Umathrelbinspacing:D
1164	_kernel_primitive:NN	\Umathrelclosespacing	\tex_Umathrelclosespacing:D
1165	_kernel_primitive:NN	\Umathrelinnerspacing	\tex_Umathrelinnerspacing:D
1166	_kernel_primitive:NN	\Umathrelopenspacing	\tex_Umathrelopenspacing:D
1167	_kernel_primitive:NN	\Umathreltopspacing	\tex_Umathreltopspacing:D
1168	_kernel_primitive:NN	\Umathrelordspacing	\tex_Umathrelordspacing:D
1169	_kernel_primitive:NN	\Umathrelpunctspacing	\tex_Umathrelpunctspacing:D
1170	_kernel_primitive:NN	\Umathrelrelspacing	\tex_Umathrelrelspacing:D
1171	_kernel_primitive:NN	\Umathskewedfractionhgap	
1172		\tex_Umathskewedfractionhgap:D	
1173	_kernel_primitive:NN	\Umathskewedfractionvgap	
1174		\tex_Umathskewedfractionvgap:D	
1175	_kernel_primitive:NN	\Umathspaceafterscript	\tex_Umathspaceafterscript:D
1176	_kernel_primitive:NN	\Umathstackdenomdown	\tex_Umathstackdenomdown:D
1177	_kernel_primitive:NN	\Umathstacknumup	\tex_Umathstacknumup:D
1178	_kernel_primitive:NN	\Umathstackvgap	\tex_Umathstackvgap:D
1179	_kernel_primitive:NN	\Umathsubshiftdown	\tex_Umathsubshiftdown:D
1180	_kernel_primitive:NN	\Umathsubshiftdrop	\tex_Umathsubshiftdrop:D
1181	_kernel_primitive:NN	\Umathsubsupshiftdown	\tex_Umathsubsupshiftdown:D
1182	_kernel_primitive:NN	\Umathsubsupvgap	\tex_Umathsubsupvgap:D
1183	_kernel_primitive:NN	\Umathsubtopmax	\tex_Umathsubtopmax:D
1184	_kernel_primitive:NN	\Umathsupbottommin	\tex_Umathsupbottommin:D
1185	_kernel_primitive:NN	\Umathsupshiftdrop	\tex_Umathsupshiftdrop:D

1186	_kernel_primitive:NN	\Umathsupshiftup	\tex_Umathsupshiftup:D
1187	_kernel_primitive:NN	\Umathsupsubbottommax	\tex_Umathsupsubbottommax:D
1188	_kernel_primitive:NN	\Umathunderbarkern	\tex_Umathunderbarkern:D
1189	_kernel_primitive:NN	\Umathunderbarrule	\tex_Umathunderbarrule:D
1190	_kernel_primitive:NN	\Umathunderbarvgap	\tex_Umathunderbarvgap:D
1191	_kernel_primitive:NN	\Umathunderdelimitervgap	
1192		\tex_Umathunderdelimitervgap:D	
1193	_kernel_primitive:NN	\Umathunderdelimitervgap	
1194		\tex_Umathunderdelimitervgap:D	
1195	_kernel_primitive:NN	\Unosubscript	\tex_Unosubscript:D
1196	_kernel_primitive:NN	\Unosuperscript	\tex_Unosuperscript:D
1197	_kernel_primitive:NN	\Uoverdelimiter	\tex_Uoverdelimiter:D
1198	_kernel_primitive:NN	\Uradical	\tex_Uradical:D
1199	_kernel_primitive:NN	\Uroot	\tex_Uroot:D
1200	_kernel_primitive:NN	\Uskewed	\tex_Uskewed:D
1201	_kernel_primitive:NN	\Uskewedwithdelims	\tex_Uskewedwithdelims:D
1202	_kernel_primitive:NN	\Ustack	\tex_Ustack:D
1203	_kernel_primitive:NN	\Ustartdisplaymath	\tex_Ustartdisplaymath:D
1204	_kernel_primitive:NN	\Ustartmath	\tex_Ustartmath:D
1205	_kernel_primitive:NN	\Ustopdisplaymath	\tex_Ustopdisplaymath:D
1206	_kernel_primitive:NN	\Ustopmath	\tex_Ustopmath:D
1207	_kernel_primitive:NN	\Usubscript	\tex_Usubscript:D
1208	_kernel_primitive:NN	\Usuperscript	\tex_Usuperscript:D
1209	_kernel_primitive:NN	\Uunderdelimiter	\tex_Uunderdelimiter:D
1210	_kernel_primitive:NN	\Uvextensible	\tex_Uvextensible:D

Primitives from pTeX.

1211	_kernel_primitive:NN	\autospaceing	\tex_autospaceing:D
1212	_kernel_primitive:NN	\autoxspaceing	\tex_autoxspaceing:D
1213	_kernel_primitive:NN	\dtou	\tex_dtou:D
1214	_kernel_primitive:NN	\epTeXinputencoding	\tex_epTeXinputencoding:D
1215	_kernel_primitive:NN	\epTeXversion	\tex_epTeXversion:D
1216	_kernel_primitive:NN	\euc	\tex_euc:D
1217	_kernel_primitive:NN	\ifdbbox	\tex_ifdbbox:D
1218	_kernel_primitive:NN	\ifddir	\tex_ifddir:D
1219	_kernel_primitive:NN	\ifmdir	\tex_ifmdir:D
1220	_kernel_primitive:NN	\iftbox	\tex_iftbox:D
1221	_kernel_primitive:NN	\iftdir	\tex_iftdir:D
1222	_kernel_primitive:NN	\ifybox	\tex_ifybox:D
1223	_kernel_primitive:NN	\ifydir	\tex_ifydir:D
1224	_kernel_primitive:NN	\inhibitglue	\tex_inhibitglue:D
1225	_kernel_primitive:NN	\inhibitxspcode	\tex_inhibitxspcode:D
1226	_kernel_primitive:NN	\jcharwidowpenalty	\tex_jcharwidowpenalty:D
1227	_kernel_primitive:NN	\jfam	\tex_jfam:D
1228	_kernel_primitive:NN	\jfont	\tex_jfont:D
1229	_kernel_primitive:NN	\jis	\tex_jis:D
1230	_kernel_primitive:NN	\kanjiskip	\tex_kanjiskip:D
1231	_kernel_primitive:NN	\kansuji	\tex_kansuji:D
1232	_kernel_primitive:NN	\kansujichar	\tex_kansujichar:D
1233	_kernel_primitive:NN	\kcatcode	\tex_kcatcode:D
1234	_kernel_primitive:NN	\kuten	\tex_kuten:D
1235	_kernel_primitive:NN	\noautospaceing	\tex_noautospaceing:D
1236	_kernel_primitive:NN	\noautoxspaceing	\tex_noautoxspaceing:D
1237	_kernel_primitive:NN	\postbreakpenalty	\tex_postbreakpenalty:D
1238	_kernel_primitive:NN	\prebreakpenalty	\tex_prebreakpenalty:D

1239	<code>__kernel_primitive:NN \ptexminorversion</code>	<code>\tex_ptexminorversion:D</code>
1240	<code>__kernel_primitive:NN \ptexrevision</code>	<code>\tex_ptexrevision:D</code>
1241	<code>__kernel_primitive:NN \ptexversion</code>	<code>\tex_ptexversion:D</code>
1242	<code>__kernel_primitive:NN \showmode</code>	<code>\tex_showmode:D</code>
1243	<code>__kernel_primitive:NN \sjis</code>	<code>\tex_sjis:D</code>
1244	<code>__kernel_primitive:NN \tate</code>	<code>\tex_tate:D</code>
1245	<code>__kernel_primitive:NN \tbaselineshift</code>	<code>\tex_tbaselineshift:D</code>
1246	<code>__kernel_primitive:NN \tfont</code>	<code>\tex_tfont:D</code>
1247	<code>__kernel_primitive:NN \xkanjiskip</code>	<code>\tex_xkanjiskip:D</code>
1248	<code>__kernel_primitive:NN \xspcode</code>	<code>\tex_xspcode:D</code>
1249	<code>__kernel_primitive:NN \ybaselineshift</code>	<code>\tex_ybaselineshift:D</code>
1250	<code>__kernel_primitive:NN \yoko</code>	<code>\tex_yoko:D</code>

Primitives from upL^AT_EX.

1251	<code>__kernel_primitive:NN \disablecjktoken</code>	<code>\tex_disablecjktoken:D</code>
1252	<code>__kernel_primitive:NN \enablecjktoken</code>	<code>\tex_enablecjktoken:D</code>
1253	<code>__kernel_primitive:NN \forcecjktoken</code>	<code>\tex_forcecjktoken:D</code>
1254	<code>__kernel_primitive:NN \kchar</code>	<code>\tex_kchar:D</code>
1255	<code>__kernel_primitive:NN \kchardef</code>	<code>\tex_kchardef:D</code>
1256	<code>__kernel_primitive:NN \kuten</code>	<code>\tex_kuten:D</code>
1257	<code>__kernel_primitive:NN \ucs</code>	<code>\tex_ucs:D</code>
1258	<code>__kernel_primitive:NN \uptexrevision</code>	<code>\tex_uptexrevision:D</code>
1259	<code>__kernel_primitive:NN \uptexversion</code>	<code>\tex_uptexversion:D</code>

End of the “just the names” part of the source.

```
1260 </initex | names | package>
1261 <*initex | package>
```

The job is done: close the group (using the primitive renamed!).

```
1262 \tex_endgroup:D
```

L^AT_EX 2_ε moves a few primitives, so these are sorted out. A convenient test for L^AT_EX 2_ε is the `\@@end` saved primitive.

```
1263 <*package>
1264 \tex_ifdefined:D \@@end
1265 \tex_let:D \tex_end:D \@@end
1266 \tex_let:D \tex_everydisplay:D \frozen@everydisplay
1267 \tex_let:D \tex_everymath:D \frozen@everymath
1268 \tex_let:D \tex_hyphen:D \@@hyph
1269 \tex_let:D \tex_input:D \@@input
1270 \tex_let:D \tex_italiccorrection:D \@@italiccorr
1271 \tex_let:D \tex_underline:D \@@underline
```

The `\shipout` primitive is particularly tricky as a number of packages want to hook in here. First, we see if a sufficiently-new kernel has saved a copy: if it has, just use that. Otherwise, we need to check each of the possible packages/classes that might move it: here, we are looking for those which do *not* delay action to the `\AtBeginDocument` hook. (We cannot use `\primitive` as that doesn’t allow us to make a direct copy of the primitive *itself*.) As we know that L^AT_EX 2_ε is in use, we use its `\@tfor` loop here.

```
1272 \tex_ifdefined:D \@@shipout
1273 \tex_let:D \tex_shipout:D \@@shipout
1274 \tex_fi:D
1275 \tex_begingroup:D
1276 \tex_edef:D \l_tmpa_tl { \tex_string:D \shipout }
1277 \tex_edef:D \l_tmpb_tl { \tex_meaning:D \shipout }
```

```

1278 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1279 \tex_else:D
1280 \tex_expandafter:D \@tfor \tex_expandafter:D \@tempa \tex_string:D :=
1281 \CROP@shipout
1282 \dup@shipout
1283 \GPTorg@shipout
1284 \LL@shipout
1285 \mem@oldshipout
1286 \opem@shipout
1287 \pgfpages@originalshipout
1288 \pr@shipout
1289 \Shipout
1290 \verso@orig@shipout
1291 \do
1292 {
1293 \tex_edef:D \l_tmpb_tl
1294 { \tex_expandafter:D \tex_meaning:D \@tempa }
1295 \tex_ifx:D \l_tmpa_tl \l_tmpb_tl
1296 \tex_global:D \tex_expandafter:D \tex_let:D
1297 \tex_expandafter:D \tex_shipout:D \@tempa
1298 \tex_fi:D
1299 }
1300 \tex_fi:D
1301 \tex_endgroup:D

```

Some tidying up is needed for `\(pdf)tracingfonts`. Newer LuaTeX has this simply as `\tracingfonts`, but that is overwritten by the L^AT_EX 2_ε kernel. So any spurious definition has to be removed, then the real version saved either from the pdfTeX name or from LuaTeX. In the latter case, we leave `\@@tracingfonts` available: this might be useful and almost all L^AT_EX 2_ε users will have expl3 loaded by fontspec. (We follow the usual kernel convention that @@ is used for saved primitives.)

```

1302 \tex_let:D \tex_tracingfonts:D \tex_undefined:D
1303 \tex_ifdefined:D \pdftracingfonts
1304 \tex_let:D \tex_tracingfonts:D \pdftracingfonts
1305 \tex_else:D
1306 \tex_ifdefined:D \tex_directlua:D
1307 \tex_directlua:D { tex.enableprimitives("@@", {"tracingfonts"}) }
1308 \tex_let:D \tex_tracingfonts:D \luatextracingfonts
1309 \tex_fi:D
1310 \tex_fi:D
1311 \tex_fi:D

```

That is also true for the LuaTeX primitives under L^AT_EX 2_ε (depending on the format-building date). There are a few primitives that get the right names anyway so are missing here!

```

1312 \tex_ifdefined:D \luatexsuppressfontnotfounderror
1313 \tex_let:D \tex_alignmark:D \luatexalignmark
1314 \tex_let:D \tex_aligntab:D \luatexaligntab
1315 \tex_let:D \tex_attribute:D \luatexattribute
1316 \tex_let:D \tex_attributedef:D \luatexattributedef
1317 \tex_let:D \tex_catcodetable:D \luatexcatcodetable
1318 \tex_let:D \tex_clearmarks:D \luatexclearmarks
1319 \tex_let:D \tex_crampeddisplaystyle:D \luatexcrampeddisplaystyle
1320 \tex_let:D \tex_crampedscriptscriptstyle:D

```

```

1321 \luatexcrampedscriptscriptstyle
1322 \tex_let:D \tex_crampedscriptstyle:D \luatexcrampedscriptstyle
1323 \tex_let:D \tex_crampedtextstyle:D \luatexcrampedtextstyle
1324 \tex_let:D \tex_fontid:D \luatexfontid
1325 \tex_let:D \tex_formatname:D \luatexformatname
1326 \tex_let:D \tex_gleaders:D \luatexgleaders
1327 \tex_let:D \tex_initcatcodetable:D \luatexinitcatcodetable
1328 \tex_let:D \tex_latelua:D \luatexlatelua
1329 \tex_let:D \tex_luaescapestring:D \luatexluaescapestring
1330 \tex_let:D \tex_luafunction:D \luatexluafunction
1331 \tex_let:D \tex_mathstyle:D \luatexmathstyle
1332 \tex_let:D \tex_nokerns:D \luatexnokerns
1333 \tex_let:D \tex_noligs:D \luatexnoligs
1334 \tex_let:D \tex_outputbox:D \luatexoutputbox
1335 \tex_let:D \tex_pageleftoffset:D \luatexpageleftoffset
1336 \tex_let:D \tex_pagetopoffset:D \luatexpagetopoffset
1337 \tex_let:D \tex_postexhyphenchar:D \luatexpostexhyphenchar
1338 \tex_let:D \tex_posthyphenchar:D \luatexposthyphenchar
1339 \tex_let:D \tex_preexhyphenchar:D \luatexpreexhyphenchar
1340 \tex_let:D \tex_prehyphenchar:D \luatexprehyphenchar
1341 \tex_let:D \tex_savecatcodetable:D \luatexsavecatcodetable
1342 \tex_let:D \tex_scantextokens:D \luatexscantextokens
1343 \tex_let:D \tex_suppressifcsnameerror:D
1344 \luatexsuppressifcsnameerror
1345 \tex_let:D \tex_suppresslongerror:D \luatexsuppresslongerror
1346 \tex_let:D \tex_suppressmathparerror:D
1347 \luatexsuppressmathparerror
1348 \tex_let:D \tex_suppressoutererror:D \luatexsuppressoutererror
1349 \tex_let:D \tex_Uchar:D \luatexUchar
1350 \tex_let:D \tex_suppressfontnotfounderror:D
1351 \luatexsuppressfontnotfounderror

```

Which also covers those slightly odd ones.

```

1352 \tex_let:D \tex_bodydir:D \luatexbodydir
1353 \tex_let:D \tex_boxdir:D \luatexboxdir
1354 \tex_let:D \tex_leftghost:D \luatexleftghost
1355 \tex_let:D \tex_localbrokenpenalty:D \luatexlocalbrokenpenalty
1356 \tex_let:D \tex_localinterlinepenalty:D
1357 \luatexlocalinterlinepenalty
1358 \tex_let:D \tex_localleftbox:D \luatexlocalleftbox
1359 \tex_let:D \tex_localrightbox:D \luatexlocalrightbox
1360 \tex_let:D \tex_mathdir:D \luatexmathdir
1361 \tex_let:D \tex_pagebottomoffset:D \luatexpagebottomoffset
1362 \tex_let:D \tex_pagedir:D \luatexpagedir
1363 \tex_let:D \tex_pageheight:D \luatexpageheight
1364 \tex_let:D \tex_pagerightoffset:D \luatexpagerightoffset
1365 \tex_let:D \tex_pagewidth:D \luatexpagewidth
1366 \tex_let:D \tex_pardir:D \luatexpardir
1367 \tex_let:D \tex_rightghost:D \luatexrightghost
1368 \tex_let:D \tex_textdir:D \luatextextdir
1369 \tex_fi:D

```

Only pdfTeX and LuaTeX define \pdfmapfile and \pdfmapline: Tidy up the fact that some format-building processes leave a couple of questionable decisions about that!

```

1370 \tex_ifnum:D 0

```

```

1371 \tex_ifdefined:D \tex_pdftexversion:D 1 \tex_fi:D
1372 \tex_ifdefined:D \tex_luatexversion:D 1 \tex_fi:D
1373 = 0 %
1374 \tex_let:D \tex_mapfile:D \tex_undefined:D
1375 \tex_let:D \tex_mapline:D \tex_undefined:D
1376 \tex_fi:D
1377 </package>

```

Up to v0.80, LuaTeX defines the pdfTeX version data: rather confusing. Removing them means that `\tex_pdftexversion:D` is a marker for pdfTeX alone: useful in engine-dependent code later.

```

1378 <*initex | package>
1379 \tex_ifdefined:D \tex_luatexversion:D
1380 \tex_let:D \tex_pdftexbanner:D \tex_undefined:D
1381 \tex_let:D \tex_pdftexrevision:D \tex_undefined:D
1382 \tex_let:D \tex_pdftexversion:D \tex_undefined:D
1383 \tex_fi:D
1384 </initex | package>

```

For ConTeXt, two tests are needed. Both Mark II and Mark IV move several primitives: these are all covered by the first test, again using `\end` as a marker. For Mark IV, a few more primitives are moved: they are implemented using some Lua code in the current ConTeXt.

```

1385 <*package>
1386 \tex_ifdefined:D \normalend
1387 \tex_let:D \tex_end:D \normalend
1388 \tex_let:D \tex_everyjob:D \normaleveryjob
1389 \tex_let:D \tex_input:D \normalinput
1390 \tex_let:D \tex_language:D \normallanguage
1391 \tex_let:D \tex_mathop:D \normalmathop
1392 \tex_let:D \tex_month:D \normalmonth
1393 \tex_let:D \tex_outer:D \normalouter
1394 \tex_let:D \tex_over:D \normalover
1395 \tex_let:D \tex_vcenter:D \normalvcenter
1396 \tex_let:D \tex_unexpanded:D \normalunexpanded
1397 \tex_let:D \tex_expanded:D \normalexpanded
1398 \tex_fi:D
1399 \tex_ifdefined:D \normalitaliccorrection
1400 \tex_let:D \tex_hoffset:D \normalhoffset
1401 \tex_let:D \tex_italiccorrection:D \normalitaliccorrection
1402 \tex_let:D \tex_voffset:D \normalvoffset
1403 \tex_let:D \tex_showtokens:D \normalshowtokens
1404 \tex_let:D \tex_bodydir:D \spac_directions_normal_body_dir
1405 \tex_let:D \tex_pagedir:D \spac_directions_normal_page_dir
1406 \tex_fi:D
1407 \tex_ifdefined:D \normalleft
1408 \tex_let:D \tex_left:D \normalleft
1409 \tex_let:D \tex_middle:D \normalmiddle
1410 \tex_let:D \tex_right:D \normalright
1411 \tex_fi:D
1412 </package>

```

2.1 Deprecated functions

Older versions of expl3 divided up primitives by “source”: that becomes very tricky with multiple parallel engine developments, so has been dropped. To cover the transition, we provide the older names here for a limited period (until the end of 2019).

To allow `\debug_on:n {<deprecation>}` to work we save the list of primitives into `__kernel_primitives:`

```

1413 (*package)
1414 \tex_begingroup:D
1415 \tex_long:D \tex_def:D \use_ii:nn #1#2 {#2}
1416 \tex_long:D \tex_def:D \use_none:n #1 { }
1417 \tex_long:D \tex_def:D \__kernel_primitive:NN #1#2
1418 {
1419     \tex_ifdefined:D #1
1420     \tex_expandafter:D \use_ii:nn
1421     \tex_fi:D
1422     \use_none:n { \tex_global:D \tex_let:D #2 #1 }
1423 }
1424 \tex_xdef:D \__kernel_primitives:
1425 {
1426     \tex_unexpanded:D
1427     {
1428         \__kernel_primitive:NN \beginL           \etex_beginL:D
1429         \__kernel_primitive:NN \beginR           \etex_beginR:D
1430         \__kernel_primitive:NN \botmarks          \etex_botmarks:D
1431         \__kernel_primitive:NN \clubpenalties     \etex_clubpenalties:D
1432         \__kernel_primitive:NN \currentgrouplevel \etex_currentgrouplevel:D
1433         \__kernel_primitive:NN \currentgrouptype \etex_currentgrouptype:D
1434         \__kernel_primitive:NN \currentifbranch   \etex_currentifbranch:D
1435         \__kernel_primitive:NN \currentiflevel    \etex_currentiflevel:D
1436         \__kernel_primitive:NN \currentiftyping   \etex_currentiftyping:D
1437         \__kernel_primitive:NN \detokenize        \etex_detokenize:D
1438         \__kernel_primitive:NN \dimexpr           \etex_dimexpr:D
1439         \__kernel_primitive:NN \displaywidowpenalties \etex_displaywidowpenalties:D
1440         \etex_displaywidowpenalties:D
1441         \__kernel_primitive:NN \endL             \etex_endL:D
1442         \__kernel_primitive:NN \endR             \etex_endR:D
1443         \__kernel_primitive:NN \eTeXrevision      \etex_eTeXrevision:D
1444         \__kernel_primitive:NN \eTeXversion       \etex_eTeXversion:D
1445         \__kernel_primitive:NN \everyeof          \etex_everyeof:D
1446         \__kernel_primitive:NN \firstmarks        \etex_firstmarks:D
1447         \__kernel_primitive:NN \fontchardp        \etex_fontchardp:D
1448         \__kernel_primitive:NN \fontcharht        \etex_fontcharht:D
1449         \__kernel_primitive:NN \fontcharic        \etex_fontcharic:D
1450         \__kernel_primitive:NN \fontcharwd        \etex_fontcharwd:D
1451         \__kernel_primitive:NN \glueexpr          \etex_glueexpr:D
1452         \__kernel_primitive:NN \glueshrink        \etex_glueshrink:D
1453         \__kernel_primitive:NN \glueshrinkorder    \etex_glueshrinkorder:D
1454         \__kernel_primitive:NN \gluestretch       \etex_gluestretch:D
1455         \__kernel_primitive:NN \gluestretchorder   \etex_gluestretchorder:D
1456         \__kernel_primitive:NN \gluetomu         \etex_gluetomu:D
1457         \__kernel_primitive:NN \ifcsname         \etex_ifcsname:D
1458         \__kernel_primitive:NN \ifdefined         \etex_ifdefined:D
1459         \__kernel_primitive:NN \iffontchar        \etex_iffontchar:D

```


1460	_kernel_primitive:NN	\interactionmode	\etex_interactionmode:D
1461	_kernel_primitive:NN	\interlinepenalties	\etex_interlinepenalties:D
1462	_kernel_primitive:NN	\lastlinefit	\etex_lastlinefit:D
1463	_kernel_primitive:NN	\lastnodetype	\etex_lastnodetype:D
1464	_kernel_primitive:NN	\marks	\etex_marks:D
1465	_kernel_primitive:NN	\middle	\etex_middle:D
1466	_kernel_primitive:NN	\muexpr	\etex_muexpr:D
1467	_kernel_primitive:NN	\mutoglua	\etex_mutoglua:D
1468	_kernel_primitive:NN	\numexpr	\etex_numexpr:D
1469	_kernel_primitive:NN	\pagediscards	\etex_pagediscards:D
1470	_kernel_primitive:NN	\parshapedimen	\etex_parshapedimen:D
1471	_kernel_primitive:NN	\parshapeindent	\etex_parshapeindent:D
1472	_kernel_primitive:NN	\parshaplength	\etex_parshaplength:D
1473	_kernel_primitive:NN	\predisplaydirection	\etex_predisplaydirection:D
1474	_kernel_primitive:NN	\protected	\etex_protected:D
1475	_kernel_primitive:NN	\readline	\etex_readline:D
1476	_kernel_primitive:NN	\savinghyphcodes	\etex_savinghyphcodes:D
1477	_kernel_primitive:NN	\savingvdiscards	\etex_savingvdiscards:D
1478	_kernel_primitive:NN	\scantokens	\etex_scantokens:D
1479	_kernel_primitive:NN	\showgroups	\etex_showgroups:D
1480	_kernel_primitive:NN	\showifs	\etex_showifs:D
1481	_kernel_primitive:NN	\showtokens	\etex_showtokens:D
1482	_kernel_primitive:NN	\splitbotmarks	\etex_splitbotmarks:D
1483	_kernel_primitive:NN	\splitdiscards	\etex_splitdiscards:D
1484	_kernel_primitive:NN	\splitfirstmarks	\etex_splitfirstmarks:D
1485	_kernel_primitive:NN	\TeXeTstate	\etex_TeXeTstate:D
1486	_kernel_primitive:NN	\topmarks	\etex_topmarks:D
1487	_kernel_primitive:NN	\tracingassigns	\etex_tracingassigns:D
1488	_kernel_primitive:NN	\tracinggroups	\etex_tracinggroups:D
1489	_kernel_primitive:NN	\tracingifs	\etex_tracingifs:D
1490	_kernel_primitive:NN	\tracingnesting	\etex_tracingnesting:D
1491	_kernel_primitive:NN	\tracingscantokens	\etex_tracingscantokens:D
1492	_kernel_primitive:NN	\unexpanded	\etex_unexpanded:D
1493	_kernel_primitive:NN	\unless	\etex_unless:D
1494	_kernel_primitive:NN	\widowpenalties	\etex_widowpenalties:D
1495	_kernel_primitive:NN	\pdfannot	\pdfetex_pdfannot:D
1496	_kernel_primitive:NN	\pdfcatalog	\pdfetex_pdfcatalog:D
1497	_kernel_primitive:NN	\pdfcompresslevel	\pdfetex_pdfcompresslevel:D
1498	_kernel_primitive:NN	\pdfcolorstack	\pdfetex_pdfcolorstack:D
1499	_kernel_primitive:NN	\pdfcolorstackinit	\pdfetex_pdfcolorstackinit:D
1500	_kernel_primitive:NN	\pdfcreationdate	\pdfetex_pdfcreationdate:D
1501	_kernel_primitive:NN	\pdfdecimaldigits	\pdfetex_pdfdecimaldigits:D
1502	_kernel_primitive:NN	\pdfdest	\pdfetex_pdfdest:D
1503	_kernel_primitive:NN	\pdfdestmargin	\pdfetex_pdfdestmargin:D
1504	_kernel_primitive:NN	\pdfendlink	\pdfetex_pdfendlink:D
1505	_kernel_primitive:NN	\pdfendthread	\pdfetex_pdfendthread:D
1506	_kernel_primitive:NN	\pdffontattr	\pdfetex_pdffontattr:D
1507	_kernel_primitive:NN	\pdffontname	\pdfetex_pdffontname:D
1508	_kernel_primitive:NN	\pdffontobjnum	\pdfetex_pdffontobjnum:D
1509	_kernel_primitive:NN	\pdfgamma	\pdfetex_pdfgamma:D
1510	_kernel_primitive:NN	\pdfimageapplygamma	\pdfetex_pdfimageapplygamma:D
1511	_kernel_primitive:NN	\pdfimagegamma	\pdfetex_pdfimagegamma:D
1512	_kernel_primitive:NN	\pdfgentounicode	\pdfetex_pdfgentounicode:D
1513	_kernel_primitive:NN	\pdfglyphtounicode	\pdfetex_pdfglyphtounicode:D

1514	_kernel_primitive:NN	\\pdfhorigin	\\pdfTEX_pdfhorigin:D
1515	_kernel_primitive:NN	\\pdfimagehicolor	\\pdfTEX_pdfimagehicolor:D
1516	_kernel_primitive:NN	\\pdfimageresolution	\\pdfTEX_pdfimageresolution:D
1517	_kernel_primitive:NN	\\pdfincludechars	\\pdfTEX_pdfincludechars:D
1518	_kernel_primitive:NN	\\pdfinclusioncopyfonts	
1519		\\pdfTEX_pdfinclusioncopyfonts:D	
1520	_kernel_primitive:NN	\\pdfinclusionerrorlevel	
1521		\\pdfTEX_pdfinclusionerrorlevel:D	
1522	_kernel_primitive:NN	\\pdfinfo	\\pdfTEX_pdfinfo:D
1523	_kernel_primitive:NN	\\pdflastannot	\\pdfTEX_pdflastannot:D
1524	_kernel_primitive:NN	\\pdflastlink	\\pdfTEX_pdflastlink:D
1525	_kernel_primitive:NN	\\pdflastobj	\\pdfTEX_pdflastobj:D
1526	_kernel_primitive:NN	\\pdflastxform	\\pdfTEX_pdflastxform:D
1527	_kernel_primitive:NN	\\pdflastximage	\\pdfTEX_pdflastximage:D
1528	_kernel_primitive:NN	\\pdflastximagecolordepth	
1529		\\pdfTEX_pdflastximagecolordepth:D	
1530	_kernel_primitive:NN	\\pdflastximagepages	\\pdfTEX_pdflastximagepages:D
1531	_kernel_primitive:NN	\\pdflinkmargin	\\pdfTEX_pdflinkmargin:D
1532	_kernel_primitive:NN	\\pdfliteral	\\pdfTEX_pdfliteral:D
1533	_kernel_primitive:NN	\\pdfminorversion	\\pdfTEX_pdfminorversion:D
1534	_kernel_primitive:NN	\\pdfnames	\\pdfTEX_pdfnames:D
1535	_kernel_primitive:NN	\\pdfobj	\\pdfTEX_pdfobj:D
1536	_kernel_primitive:NN	\\pdfobjcompresslevel	
1537		\\pdfTEX_pdfobjcompresslevel:D	
1538	_kernel_primitive:NN	\\pdfoutline	\\pdfTEX_pdfoutline:D
1539	_kernel_primitive:NN	\\pdfoutput	\\pdfTEX_pdfoutput:D
1540	_kernel_primitive:NN	\\pdfpageattr	\\pdfTEX_pdfpageattr:D
1541	_kernel_primitive:NN	\\pdfpagebox	\\pdfTEX_pdfpagebox:D
1542	_kernel_primitive:NN	\\pdfpageref	\\pdfTEX_pdfpageref:D
1543	_kernel_primitive:NN	\\pdfpageresources	\\pdfTEX_pdfpageresources:D
1544	_kernel_primitive:NN	\\pdfpagesattr	\\pdfTEX_pdfpagesattr:D
1545	_kernel_primitive:NN	\\pdfrefobj	\\pdfTEX_pdfrefobj:D
1546	_kernel_primitive:NN	\\pdfrefxform	\\pdfTEX_pdfrefxform:D
1547	_kernel_primitive:NN	\\pdfrefximage	\\pdfTEX_pdfrefximage:D
1548	_kernel_primitive:NN	\\pdfrestore	\\pdfTEX_pdfrestore:D
1549	_kernel_primitive:NN	\\pdfretval	\\pdfTEX_pdfretval:D
1550	_kernel_primitive:NN	\\pdfsave	\\pdfTEX_pdfsave:D
1551	_kernel_primitive:NN	\\pdfsetmatrix	\\pdfTEX_pdfsetmatrix:D
1552	_kernel_primitive:NN	\\pdfstartlink	\\pdfTEX_pdfstartlink:D
1553	_kernel_primitive:NN	\\pdfstartthread	\\pdfTEX_pdfstartthread:D
1554	_kernel_primitive:NN	\\pdfsuppressptexinfo	
1555		\\pdfTEX_pdfsuppressptexinfo:D	
1556	_kernel_primitive:NN	\\pdfthread	\\pdfTEX_pdfthread:D
1557	_kernel_primitive:NN	\\pdfthreadmargin	\\pdfTEX_pdfthreadmargin:D
1558	_kernel_primitive:NN	\\pdftrailer	\\pdfTEX_pdftrailer:D
1559	_kernel_primitive:NN	\\pdfuniquestring	\\pdfTEX_pdfuniquestring:D
1560	_kernel_primitive:NN	\\pdfvorigin	\\pdfTEX_pdfvorigin:D
1561	_kernel_primitive:NN	\\pdfxform	\\pdfTEX_pdfxform:D
1562	_kernel_primitive:NN	\\pdfxformattr	\\pdfTEX_pdfxformattr:D
1563	_kernel_primitive:NN	\\pdfxformname	\\pdfTEX_pdfxformname:D
1564	_kernel_primitive:NN	\\pdfxformresources	\\pdfTEX_pdfxformresources:D
1565	_kernel_primitive:NN	\\pdfximage	\\pdfTEX_pdfximage:D
1566	_kernel_primitive:NN	\\pdfximagebbox	\\pdfTEX_pdfximagebbox:D
1567	_kernel_primitive:NN	\\ifpdfabsdim	\\pdfTEX_ifabsdim:D

1568	_kernel_primitive:NN	\ifpdfabsnum	\pdfTEX_ifabsnum:D
1569	_kernel_primitive:NN	\ifpdfprimitive	\pdfTEX_ifprimitive:D
1570	_kernel_primitive:NN	\pdfadjustspacing	\pdfTEX_adjustspacing:D
1571	_kernel_primitive:NN	\pdfcopyfont	\pdfTEX_copyfont:D
1572	_kernel_primitive:NN	\pdfdraftmode	\pdfTEX_draftmode:D
1573	_kernel_primitive:NN	\pdfeachlinedepth	\pdfTEX_eachlinedepth:D
1574	_kernel_primitive:NN	\pdfeachlineheight	\pdfTEX_eachlineheight:D
1575	_kernel_primitive:NN	\pdffilemoddate	\pdfTEX_filemoddate:D
1576	_kernel_primitive:NN	\pdffilesizes	\pdfTEX_filesizes:D
1577	_kernel_primitive:NN	\pdffirstlineheight	\pdfTEX_firstlineheight:D
1578	_kernel_primitive:NN	\pdffontexpand	\pdfTEX_fontexpand:D
1579	_kernel_primitive:NN	\pdffontsize	\pdfTEX_fontsize:D
1580	_kernel_primitive:NN	\pdfignoreddimen	\pdfTEX_ignoreddimen:D
1581	_kernel_primitive:NN	\pdfinsertht	\pdfTEX_insertht:D
1582	_kernel_primitive:NN	\pdflastlinedepth	\pdfTEX_lastlinedepth:D
1583	_kernel_primitive:NN	\pdflastxpos	\pdfTEX_lastxpos:D
1584	_kernel_primitive:NN	\pdflastypos	\pdfTEX_lastypos:D
1585	_kernel_primitive:NN	\pdfmapfile	\pdfTEX_mapfile:D
1586	_kernel_primitive:NN	\pdfmapline	\pdfTEX_mapline:D
1587	_kernel_primitive:NN	\pdfmdfivesum	\pdfTEX_mdfivesum:D
1588	_kernel_primitive:NN	\pdfnoligatures	\pdfTEX_noligatures:D
1589	_kernel_primitive:NN	\pdfnormaldeviate	\pdfTEX_normaldeviate:D
1590	_kernel_primitive:NN	\pdfpageheight	\pdfTEX_pageheight:D
1591	_kernel_primitive:NN	\pdfpagewidth	\pdfTEX_pagewidth:D
1592	_kernel_primitive:NN	\pdfpkmode	\pdfTEX_pkmode:D
1593	_kernel_primitive:NN	\pdfpkrresolution	\pdfTEX_pkrresolution:D
1594	_kernel_primitive:NN	\pdfprimitive	\pdfTEX_primitive:D
1595	_kernel_primitive:NN	\pdfprotrudechars	\pdfTEX_protrudechars:D
1596	_kernel_primitive:NN	\pdfpxdimen	\pdfTEX_pxdimen:D
1597	_kernel_primitive:NN	\pdfrandomseed	\pdfTEX_randomseed:D
1598	_kernel_primitive:NN	\pdfsavepos	\pdfTEX_savepos:D
1599	_kernel_primitive:NN	\pdfstrcmp	\pdfTEX_strcmp:D
1600	_kernel_primitive:NN	\pdfsetrandomseed	\pdfTEX_setrandomseed:D
1601	_kernel_primitive:NN	\pdfshellescape	\pdfTEX_shellescape:D
1602	_kernel_primitive:NN	\pdftracingfonts	\pdfTEX_tracingfonts:D
1603	_kernel_primitive:NN	\pdfuniformdeviate	\pdfTEX_uniformdeviate:D
1604	_kernel_primitive:NN	\pdfTeXbanner	\pdfTEX_pdfTeXbanner:D
1605	_kernel_primitive:NN	\pdfTeXrevision	\pdfTEX_pdfTeXrevision:D
1606	_kernel_primitive:NN	\pdfTeXversion	\pdfTEX_pdfTeXversion:D
1607	_kernel_primitive:NN	\efcode	\pdfTEX_efcode:D
1608	_kernel_primitive:NN	\ifincsname	\pdfTEX_ifincsname:D
1609	_kernel_primitive:NN	\leftmargin kern	\pdfTEX_leftmargin kern:D
1610	_kernel_primitive:NN	\letterspacefont	\pdfTEX_letterspacefont:D
1611	_kernel_primitive:NN	\lpcode	\pdfTEX_lpcode:D
1612	_kernel_primitive:NN	\quitvmode	\pdfTEX_quitvmode:D
1613	_kernel_primitive:NN	\rightmargin kern	\pdfTEX_rightmargin kern:D
1614	_kernel_primitive:NN	\rpcode	\pdfTEX_rpcode:D
1615	_kernel_primitive:NN	\synctex	\pdfTEX_synctex:D
1616	_kernel_primitive:NN	\tagcode	\pdfTEX_tagcode:D
1617	_kernel_primitive:NN	\mdfivesum	\pdfTEX_mdfivesum:D
1618	_kernel_primitive:NN	\ifprimitive	\pdfTEX_ifprimitive:D
1619	_kernel_primitive:NN	\primitive	\pdfTEX_primitive:D
1620	_kernel_primitive:NN	\shellescape	\pdfTEX_shellescape:D
1621	_kernel_primitive:NN	\adjustspacing	\pdfTEX_adjustspacing:D

```

1622 \__kernel_primitive:NN \copyfont \pdfTeX_copyfont:D
1623 \__kernel_primitive:NN \draftmode \pdfTeX_draftmode:D
1624 \__kernel_primitive:NN \expandglyphsinfont \pdfTeX_fontexpand:D
1625 \__kernel_primitive:NN \ifabsdim \pdfTeX_ifabsdim:D
1626 \__kernel_primitive:NN \ifabsnum \pdfTeX_ifabsnum:D
1627 \__kernel_primitive:NN \ignoreligaturesinfont
1628 \pdfTeX_ignoreligaturesinfont:D
1629 \__kernel_primitive:NN \insertht \pdfTeX_insertht:D
1630 \__kernel_primitive:NN \lastsavedboxresourceindex
1631 \pdfTeX_pdflastxform:D
1632 \__kernel_primitive:NN \lastsavedimageresourceindex
1633 \pdfTeX_pdflastximage:D
1634 \__kernel_primitive:NN \lastsavedimageresourcepages
1635 \pdfTeX_pdflastximagepages:D
1636 \__kernel_primitive:NN \lastxpos \pdfTeX_lastxpos:D
1637 \__kernel_primitive:NN \lastypos \pdfTeX_lastypos:D
1638 \__kernel_primitive:NN \normaldeviate \pdfTeX_normaldeviate:D
1639 \__kernel_primitive:NN \outputmode \pdfTeX_pdfoutput:D
1640 \__kernel_primitive:NN \pageheight \pdfTeX_pageheight:D
1641 \__kernel_primitive:NN \pagewidth \pdfTeX_pagewidth:D
1642 \__kernel_primitive:NN \protrudechars \pdfTeX_protrudechars:D
1643 \__kernel_primitive:NN \pxdimen \pdfTeX_pxdimen:D
1644 \__kernel_primitive:NN \randomseed \pdfTeX_randomseed:D
1645 \__kernel_primitive:NN \useboxresource \pdfTeX_pdfrefxform:D
1646 \__kernel_primitive:NN \useimageresource \pdfTeX_pdfrefximage:D
1647 \__kernel_primitive:NN \savepos \pdfTeX_savepos:D
1648 \__kernel_primitive:NN \saveboxresource \pdfTeX_pdfxform:D
1649 \__kernel_primitive:NN \saveimageresource \pdfTeX_pdfximage:D
1650 \__kernel_primitive:NN \setrandomseed \pdfTeX_setrandomseed:D
1651 \__kernel_primitive:NN \tracingfonts \pdfTeX_tracingfonts:D
1652 \__kernel_primitive:NN \uniformdeviate \pdfTeX_uniformdeviate:D
1653 \__kernel_primitive:NN \suppressfontnotfounderror
1654 \xetex_suppressfontnotfounderror:D
1655 \__kernel_primitive:NN \XeTeXcharclass \xetex_charclass:D
1656 \__kernel_primitive:NN \XeTeXcharglyph \xetex_charglyph:D
1657 \__kernel_primitive:NN \XeTeXcountfeatures \xetex_countfeatures:D
1658 \__kernel_primitive:NN \XeTeXcountglyphs \xetex_countglyphs:D
1659 \__kernel_primitive:NN \XeTeXcountselectors \xetex_countselectors:D
1660 \__kernel_primitive:NN \XeTeXcountvariations \xetex_countvariations:D
1661 \__kernel_primitive:NN \XeTeXdefaultencoding \xetex_defaultencoding:D
1662 \__kernel_primitive:NN \XeTeXdashbreakstate \xetex_dashbreakstate:D
1663 \__kernel_primitive:NN \XeTeXfeaturecode \xetex_featurecode:D
1664 \__kernel_primitive:NN \XeTeXfeaturename \xetex_featurename:D
1665 \__kernel_primitive:NN \XeTeXfindfeaturebyname
1666 \xetex_findfeaturebyname:D
1667 \__kernel_primitive:NN \XeTeXfindselectorbyname
1668 \xetex_findselectorbyname:D
1669 \__kernel_primitive:NN \XeTeXfindvariationbyname
1670 \xetex_findvariationbyname:D
1671 \__kernel_primitive:NN \XeTeXfirstfontchar \xetex_firstfontchar:D
1672 \__kernel_primitive:NN \XeTeXfonttype \xetex_fonttype:D
1673 \__kernel_primitive:NN \XeTeXgenerateactualtext
1674 \xetex_generateactualtext:D
1675 \__kernel_primitive:NN \XeTeXglyph \xetex_glyph:D

```

```

1676 \__kernel_primitive:NN \XeTeXglyphbounds \xetex_glyphbounds:D
1677 \__kernel_primitive:NN \XeTeXglyphindex \xetex_glyphindex:D
1678 \__kernel_primitive:NN \XeTeXglyphname \xetex_glyphname:D
1679 \__kernel_primitive:NN \XeTeXinputencoding \xetex_inputencoding:D
1680 \__kernel_primitive:NN \XeTeXinputnormalization
1681 \xetex_inputnormalization:D
1682 \__kernel_primitive:NN \XeTeXinterchartokenstate
1683 \xetex_interchartokenstate:D
1684 \__kernel_primitive:NN \XeTeXinterchartoks \xetex_interchartoks:D
1685 \__kernel_primitive:NN \XeTeXisdefaultselector
1686 \xetex_isdefaultselector:D
1687 \__kernel_primitive:NN \XeTeXisexclusivefeature
1688 \xetex_isexclusivefeature:D
1689 \__kernel_primitive:NN \XeTeXlastfontchar \xetex_lastfontchar:D
1690 \__kernel_primitive:NN \XeTeXlinebreakskip \xetex_linebreakskip:D
1691 \__kernel_primitive:NN \XeTeXlinebreaklocale \xetex_linebreaklocale:D
1692 \__kernel_primitive:NN \XeTeXlinebreakpenalty \xetex_linebreakpenalty:D
1693 \__kernel_primitive:NN \XeTeXOTcountfeatures \xetex_OTcountfeatures:D
1694 \__kernel_primitive:NN \XeTeXOTcountlanguages \xetex_OTcountlanguages:D
1695 \__kernel_primitive:NN \XeTeXOTcountscripts \xetex_OTcountscripts:D
1696 \__kernel_primitive:NN \XeTeXOTfeaturetag \xetex_OTfeaturetag:D
1697 \__kernel_primitive:NN \XeTeXOTlanguagetag \xetex_OTlanguagetag:D
1698 \__kernel_primitive:NN \XeTeXOTscripttag \xetex_OTscripttag:D
1699 \__kernel_primitive:NN \XeTeXpdffile \xetex_pdffile:D
1700 \__kernel_primitive:NN \XeTeXpdfpagecount \xetex_pdfpagecount:D
1701 \__kernel_primitive:NN \XeTeXpicfile \xetex_picfile:D
1702 \__kernel_primitive:NN \XeTeXselectorname \xetex_selectorname:D
1703 \__kernel_primitive:NN \XeTeXtracingfonts \xetex_tracingfonts:D
1704 \__kernel_primitive:NN \XeTeXupwardsmode \xetex_upwardsmode:D
1705 \__kernel_primitive:NN \XeTeXuseglyphmetrics \xetex_useglyphmetrics:D
1706 \__kernel_primitive:NN \XeTeXvariation \xetex_variation:D
1707 \__kernel_primitive:NN \XeTeXvariationdefault \xetex_variationdefault:D
1708 \__kernel_primitive:NN \XeTeXvariationmax \xetex_variationmax:D
1709 \__kernel_primitive:NN \XeTeXvariationmin \xetex_variationmin:D
1710 \__kernel_primitive:NN \XeTeXvariationname \xetex_variationname:D
1711 \__kernel_primitive:NN \XeTeXrevision \xetex_XeTeXrevision:D
1712 \__kernel_primitive:NN \XeTeXversion \xetex_XeTeXversion:D
1713 \__kernel_primitive:NN \alignmark \luatex_alignmark:D
1714 \__kernel_primitive:NN \aligntab \luatex_aligntab:D
1715 \__kernel_primitive:NN \attribute \luatex_attribute:D
1716 \__kernel_primitive:NN \attributedef \luatex_attributedef:D
1717 \__kernel_primitive:NN \automaticdiscretionary
1718 \luatex_automaticdiscretionary:D
1719 \__kernel_primitive:NN \automatichyphenmode
1720 \luatex_automatichyphenmode:D
1721 \__kernel_primitive:NN \automatichyphenpenalty
1722 \luatex_automatichyphenpenalty:D
1723 \__kernel_primitive:NN \beginscname \luatex_beginscname:D
1724 \__kernel_primitive:NN \breakafterdirmode \luatex_breakafterdirmode:D
1725 \__kernel_primitive:NN \catcodetable \luatex_catcodetable:D
1726 \__kernel_primitive:NN \clearmarks \luatex_clearmarks:D
1727 \__kernel_primitive:NN \crampeddisplaystyle
1728 \luatex_crampeddisplaystyle:D
1729 \__kernel_primitive:NN \crampedscriptscriptstyle

```

1730	<code>\luatex_crampedscriptscriptstyle:D</code>	
1731	<code>__kernel_primitive:NN \crampedscriptstyle</code>	<code>\luatex_crampedscriptstyle:D</code>
1732	<code>__kernel_primitive:NN \crampedtextstyle</code>	<code>\luatex_crampedtextstyle:D</code>
1733	<code>__kernel_primitive:NN \directlua</code>	<code>\luatex_directlua:D</code>
1734	<code>__kernel_primitive:NN \dviextension</code>	<code>\luatex_dviextension:D</code>
1735	<code>__kernel_primitive:NN \dvifedback</code>	<code>\luatex_dvifedback:D</code>
1736	<code>__kernel_primitive:NN \dvivariable</code>	<code>\luatex_dvivariable:D</code>
1737	<code>__kernel_primitive:NN \etoksapp</code>	<code>\luatex_etoksapp:D</code>
1738	<code>__kernel_primitive:NN \etokspre</code>	<code>\luatex_etokspre:D</code>
1739	<code>__kernel_primitive:NN \explicitthyphenpenalty</code>	
1740	<code>\luatex_explicitthyphenpenalty:D</code>	
1741	<code>__kernel_primitive:NN \expanded</code>	<code>\luatex_expanded:D</code>
1742	<code>__kernel_primitive:NN \explicitdiscretionary</code>	
1743	<code>\luatex_explicitdiscretionary:D</code>	
1744	<code>__kernel_primitive:NN \firstvalidlanguage</code>	<code>\luatex_firstvalidlanguage:D</code>
1745	<code>__kernel_primitive:NN \fontid</code>	<code>\luatex_fontid:D</code>
1746	<code>__kernel_primitive:NN \formatname</code>	<code>\luatex_formatname:D</code>
1747	<code>__kernel_primitive:NN \hjcode</code>	<code>\luatex_hjcode:D</code>
1748	<code>__kernel_primitive:NN \hpack</code>	<code>\luatex_hpack:D</code>
1749	<code>__kernel_primitive:NN \hyphenationbounds</code>	<code>\luatex_hyphenationbounds:D</code>
1750	<code>__kernel_primitive:NN \hyphenationmin</code>	<code>\luatex_hyphenationmin:D</code>
1751	<code>__kernel_primitive:NN \hyphenpenaltymode</code>	<code>\luatex_hyphenpenaltymode:D</code>
1752	<code>__kernel_primitive:NN \gleaders</code>	<code>\luatex_gleaders:D</code>
1753	<code>__kernel_primitive:NN \initcatcodetable</code>	<code>\luatex_initcatcodetable:D</code>
1754	<code>__kernel_primitive:NN \lastnamedcs</code>	<code>\luatex_lastnamedcs:D</code>
1755	<code>__kernel_primitive:NN \latelua</code>	<code>\luatex_latelua:D</code>
1756	<code>__kernel_primitive:NN \letcharcode</code>	<code>\luatex_letcharcode:D</code>
1757	<code>__kernel_primitive:NN \luaescapestring</code>	<code>\luatex_luaescapestring:D</code>
1758	<code>__kernel_primitive:NN \luafunction</code>	<code>\luatex_luafunction:D</code>
1759	<code>__kernel_primitive:NN \luatexbanner</code>	<code>\luatex_luatexbanner:D</code>
1760	<code>__kernel_primitive:NN \luatexrevision</code>	<code>\luatex_luatexrevision:D</code>
1761	<code>__kernel_primitive:NN \luatexversion</code>	<code>\luatex_luatexversion:D</code>
1762	<code>__kernel_primitive:NN \mathdelimitersmode</code>	<code>\luatex_mathdelimitersmode:D</code>
1763	<code>__kernel_primitive:NN \mathdisplayskipmode</code>	
1764	<code>\luatex_mathdisplayskipmode:D</code>	
1765	<code>__kernel_primitive:NN \matheqnogapstep</code>	<code>\luatex_matheqnogapstep:D</code>
1766	<code>__kernel_primitive:NN \mathnolimitsmode</code>	<code>\luatex_mathnolimitsmode:D</code>
1767	<code>__kernel_primitive:NN \mathoption</code>	<code>\luatex_mathoption:D</code>
1768	<code>__kernel_primitive:NN \mathpenaltiesmode</code>	<code>\luatex_mathpenaltiesmode:D</code>
1769	<code>__kernel_primitive:NN \mathrulesfam</code>	<code>\luatex_mathrulesfam:D</code>
1770	<code>__kernel_primitive:NN \mathscriptsmode</code>	<code>\luatex_mathscriptsmode:D</code>
1771	<code>__kernel_primitive:NN \mathscriptboxmode</code>	<code>\luatex_mathscriptboxmode:D</code>
1772	<code>__kernel_primitive:NN \mathstyle</code>	<code>\luatex_mathstyle:D</code>
1773	<code>__kernel_primitive:NN \mathsurroundmode</code>	<code>\luatex_mathsurroundmode:D</code>
1774	<code>__kernel_primitive:NN \mathsurroundskip</code>	<code>\luatex_mathsurroundskip:D</code>
1775	<code>__kernel_primitive:NN \nohrule</code>	<code>\luatex_nohrule:D</code>
1776	<code>__kernel_primitive:NN \nokerns</code>	<code>\luatex_nokerns:D</code>
1777	<code>__kernel_primitive:NN \noligs</code>	<code>\luatex_noligs:D</code>
1778	<code>__kernel_primitive:NN \nospaces</code>	<code>\luatex_nospaces:D</code>
1779	<code>__kernel_primitive:NN \novrule</code>	<code>\luatex_novrule:D</code>
1780	<code>__kernel_primitive:NN \outputbox</code>	<code>\luatex_outputbox:D</code>
1781	<code>__kernel_primitive:NN \pagebottomoffset</code>	<code>\luatex_pagebottomoffset:D</code>
1782	<code>__kernel_primitive:NN \pageleftoffset</code>	<code>\luatex_pageleftoffset:D</code>
1783	<code>__kernel_primitive:NN \pagerightoffset</code>	<code>\luatex_pagerightoffset:D</code>

1784	_kernel_primitive:NN	\pagetopoffset	\luatex_pagetopoffset:D
1785	_kernel_primitive:NN	\pdfextension	\luatex_pdfextension:D
1786	_kernel_primitive:NN	\pdffeedback	\luatex_pdffeedback:D
1787	_kernel_primitive:NN	\pdfvariable	\luatex_pdfvariable:D
1788	_kernel_primitive:NN	\postexhyphenchar	\luatex_postexhyphenchar:D
1789	_kernel_primitive:NN	\posthyphenchar	\luatex_posthyphenchar:D
1790	_kernel_primitive:NN	\prebinoppenalty	\luatex_prebinoppenalty:D
1791	_kernel_primitive:NN	\predisplaygapfactor	\luatex_predisplaygapfactor:D
1792	_kernel_primitive:NN	\preexhyphenchar	\luatex_preexhyphenchar:D
1794	_kernel_primitive:NN	\prehyphenchar	\luatex_prehyphenchar:D
1795	_kernel_primitive:NN	\prerelpenalty	\luatex_prerelpenalty:D
1796	_kernel_primitive:NN	\savecatcodetable	\luatex_savecatcodetable:D
1797	_kernel_primitive:NN	\scantextokens	\luatex_scantextokens:D
1798	_kernel_primitive:NN	\setfontid	\luatex_setfontid:D
1799	_kernel_primitive:NN	\shapemode	\luatex_shapemode:D
1800	_kernel_primitive:NN	\suppressifcsnameerror	\luatex_suppressifcsnameerror:D
1802	_kernel_primitive:NN	\suppresslongerror	\luatex_suppresslongerror:D
1803	_kernel_primitive:NN	\suppressmathparerror	\luatex_suppressmathparerror:D
1805	_kernel_primitive:NN	\suppressoutererror	\luatex_suppressoutererror:D
1806	_kernel_primitive:NN	\suppressprimitiveerror	\luatex_suppressprimitiveerror:D
1808	_kernel_primitive:NN	\toksapp	\luatex_toksapp:D
1809	_kernel_primitive:NN	\tokspre	\luatex_tokspre:D
1810	_kernel_primitive:NN	\tpack	\luatex_tpack:D
1811	_kernel_primitive:NN	\vpack	\luatex_vpack:D
1812	_kernel_primitive:NN	\bodydir	\luatex_bodydir:D
1813	_kernel_primitive:NN	\boxdir	\luatex_boxdir:D
1814	_kernel_primitive:NN	\leftghost	\luatex_leftghost:D
1815	_kernel_primitive:NN	\linedir	\luatex_linedir:D
1816	_kernel_primitive:NN	\localbrokenpenalty	\luatex_localbrokenpenalty:D
1817	_kernel_primitive:NN	\localinterlinepenalty	\luatex_localinterlinepenalty:D
1819	_kernel_primitive:NN	\localleftbox	\luatex_localleftbox:D
1820	_kernel_primitive:NN	\localrightbox	\luatex_localrightbox:D
1821	_kernel_primitive:NN	\mathdir	\luatex_mathdir:D
1822	_kernel_primitive:NN	\pagedir	\luatex_pagedir:D
1823	_kernel_primitive:NN	\pardir	\luatex_pardir:D
1824	_kernel_primitive:NN	\rightghost	\luatex_rightghost:D
1825	_kernel_primitive:NN	\textdir	\luatex_textdir:D
1826	_kernel_primitive:NN	\Uchar	\utex_char:D
1827	_kernel_primitive:NN	\Ucharcat	\utex_charcat:D
1828	_kernel_primitive:NN	\Udelcode	\utex_delcode:D
1829	_kernel_primitive:NN	\Udelcodenum	\utex_delcodenum:D
1830	_kernel_primitive:NN	\Udelimiter	\utex_delimiter:D
1831	_kernel_primitive:NN	\Udelimiterover	\utex_delimiterover:D
1832	_kernel_primitive:NN	\Udelimiterunder	\utex_delimiterunder:D
1833	_kernel_primitive:NN	\Uhextensible	\utex_hextensible:D
1834	_kernel_primitive:NN	\Umathaccent	\utex_mathaccent:D
1835	_kernel_primitive:NN	\Umathaxis	\utex_mathaxis:D
1836	_kernel_primitive:NN	\Umathbinbinspacing	\utex_binbinspacing:D
1837	_kernel_primitive:NN	\Umathbinclosespacing	\utex_binclosespacing:D

```

1838 \__kernel_primitive:NN \Umathbininnerspacing \utex_bininnerspacing:D
1839 \__kernel_primitive:NN \Umathbinopenspacing \utex_binopenspacing:D
1840 \__kernel_primitive:NN \Umathbinopspacing \utex_binopspacing:D
1841 \__kernel_primitive:NN \Umathbinordspacing \utex_binordspacing:D
1842 \__kernel_primitive:NN \Umathbinpunctspacing \utex_binpunctspacing:D
1843 \__kernel_primitive:NN \Umathbinrelspacing \utex_binrelspacing:D
1844 \__kernel_primitive:NN \Umathchar \utex_mathchar:D
1845 \__kernel_primitive:NN \Umathcharclass \utex_mathcharclass:D
1846 \__kernel_primitive:NN \Umathchardef \utex_mathchardef:D
1847 \__kernel_primitive:NN \Umathcharfam \utex_mathcharfam:D
1848 \__kernel_primitive:NN \Umathcharnum \utex_mathcharnum:D
1849 \__kernel_primitive:NN \Umathcharnumdef \utex_mathcharnumdef:D
1850 \__kernel_primitive:NN \Umathcharslot \utex_mathcharslot:D
1851 \__kernel_primitive:NN \Umathclosebinspacing \utex_closebinspacing:D
1852 \__kernel_primitive:NN \Umathcloseclosespacing
1853 \utex_closeclosespacing:D
1854 \__kernel_primitive:NN \Umathcloseinnerspacing
1855 \utex_closeinnerspacing:D
1856 \__kernel_primitive:NN \Umathcloseopenspacing \utex_closeopenspacing:D
1857 \__kernel_primitive:NN \Umathcloseopspacing \utex_closeopspacing:D
1858 \__kernel_primitive:NN \Umathcloseordspacing \utex_closeordspacing:D
1859 \__kernel_primitive:NN \Umathclosepunctspacing
1860 \utex_closepunctspacing:D
1861 \__kernel_primitive:NN \Umathcloserelspacing \utex_closerelspacing:D
1862 \__kernel_primitive:NN \Umathcode \utex_mathcode:D
1863 \__kernel_primitive:NN \Umathcodenum \utex_mathcodenum:D
1864 \__kernel_primitive:NN \Umathconnectoroverlapmin
1865 \utex_connectoroverlapmin:D
1866 \__kernel_primitive:NN \Umathfractiondelsize \utex_fractiondelsize:D
1867 \__kernel_primitive:NN \Umathfractiondenomdown
1868 \utex_fractiondenomdown:D
1869 \__kernel_primitive:NN \Umathfractiondenomvgap
1870 \utex_fractiondenomvgap:D
1871 \__kernel_primitive:NN \Umathfractionnumup \utex_fractionnumup:D
1872 \__kernel_primitive:NN \Umathfractionnumvgap \utex_fractionnumvgap:D
1873 \__kernel_primitive:NN \Umathfractionrule \utex_fractionrule:D
1874 \__kernel_primitive:NN \Umathinnerbinspacing \utex_innerbinspacing:D
1875 \__kernel_primitive:NN \Umathinnerclosespacing
1876 \utex_innerclosespacing:D
1877 \__kernel_primitive:NN \Umathinnerinnerspacing
1878 \utex_innerinnerspacing:D
1879 \__kernel_primitive:NN \Umathinneropenspacing \utex_inneropenspacing:D
1880 \__kernel_primitive:NN \Umathinneropspacing \utex_inneropspacing:D
1881 \__kernel_primitive:NN \Umathinnerordspacing \utex_innerordspacing:D
1882 \__kernel_primitive:NN \Umathinnerpunctspacing
1883 \utex_innerpunctspacing:D
1884 \__kernel_primitive:NN \Umathinnerrelspacing \utex_innerrelspacing:D
1885 \__kernel_primitive:NN \Umathlimitabovebgap \utex_limitabovebgap:D
1886 \__kernel_primitive:NN \Umathlimitabovekern \utex_limitabovekern:D
1887 \__kernel_primitive:NN \Umathlimitabovevgap \utex_limitabovevgap:D
1888 \__kernel_primitive:NN \Umathlimitbelowbgap \utex_limitbelowbgap:D
1889 \__kernel_primitive:NN \Umathlimitbelowkern \utex_limitbelowkern:D
1890 \__kernel_primitive:NN \Umathlimitbelowvgap \utex_limitbelowvgap:D
1891 \__kernel_primitive:NN \Umathnolimitsubfactor \utex_nolimitsubfactor:D

```


1892 __kernel_primitive:NN \Umathnolimitsupfactor \utex_nolimitsupfactor:D
1893 __kernel_primitive:NN \Umathopbinspacing \utex_opbinspacing:D
1894 __kernel_primitive:NN \Umathopclosespacing \utex_opclosespacing:D
1895 __kernel_primitive:NN \Umathopenbinspacing \utex_openbinspacing:D
1896 __kernel_primitive:NN \Umathopenclosespacing \utex_openclosespacing:D
1897 __kernel_primitive:NN \Umathopeninnerspacing \utex_openinnerspacing:D
1898 __kernel_primitive:NN \Umathopenopenspacing \utex_openopenspacing:D
1899 __kernel_primitive:NN \Umathopenopspacing \utex_openopspacing:D
1900 __kernel_primitive:NN \Umathopenordspacing \utex_openordspacing:D
1901 __kernel_primitive:NN \Umathopenpunctspacing \utex_openpunctspacing:D
1902 __kernel_primitive:NN \Umathopenrelspacing \utex_openrelspacing:D
1903 __kernel_primitive:NN \Umathoperatorsize \utex_operatorsize:D
1904 __kernel_primitive:NN \Umathopinnerspacing \utex_opinnerspacing:D
1905 __kernel_primitive:NN \Umathopopenspacing \utex_opopenspacing:D
1906 __kernel_primitive:NN \Umathopopspacing \utex_opopspacing:D
1907 __kernel_primitive:NN \Umathopordspacing \utex_opordspacing:D
1908 __kernel_primitive:NN \Umathoppunctspacing \utex_oppunctspacing:D
1909 __kernel_primitive:NN \Umathoprelspacing \utex_oprelspacing:D
1910 __kernel_primitive:NN \Umathordbinspacing \utex_ordbinspacing:D
1911 __kernel_primitive:NN \Umathordclosespacing \utex_ordclosespacing:D
1912 __kernel_primitive:NN \Umathordinnerspacing \utex_ordinnerspacing:D
1913 __kernel_primitive:NN \Umathordopenspacing \utex_ordopenspacing:D
1914 __kernel_primitive:NN \Umathordopspacing \utex_ordopspacing:D
1915 __kernel_primitive:NN \Umathordordspacing \utex_ordordspacing:D
1916 __kernel_primitive:NN \Umathordpunctspacing \utex_ordpunctspacing:D
1917 __kernel_primitive:NN \Umathordreldspacing \utex_ordrelspacing:D
1918 __kernel_primitive:NN \Umathoverbarkern \utex_overbarkern:D
1919 __kernel_primitive:NN \Umathoverbarrule \utex_overbarrule:D
1920 __kernel_primitive:NN \Umathoverbarvgap \utex_overbarvgap:D
1921 __kernel_primitive:NN \Umathoverdelimeterbgap
1922 \utex_overdelimeterbgap:D
1923 __kernel_primitive:NN \Umathoverdelimitervgap
1924 \utex_overdelimitervgap:D
1925 __kernel_primitive:NN \Umathpunctbinspacing \utex_punctbinspacing:D
1926 __kernel_primitive:NN \Umathpunctclosespacing
1927 \utex_punctclosespacing:D
1928 __kernel_primitive:NN \Umathpunctinnerspacing
1929 \utex_punctinnerspacing:D
1930 __kernel_primitive:NN \Umathpunctopenspacing \utex_punctopenspacing:D
1931 __kernel_primitive:NN \Umathpunctopspacing \utex_punctopspacing:D
1932 __kernel_primitive:NN \Umathpunctordspacing \utex_punctordspacing:D
1933 __kernel_primitive:NN \Umathpunctpunctspacing \utex_punctpunctspacing:D
1934 __kernel_primitive:NN \Umathpunctrelspacing \utex_punctrelspacing:D
1935 __kernel_primitive:NN \Umathquad \utex_quad:D
1936 __kernel_primitive:NN \Umathradicaldegreeafter
1937 \utex_radicaldegreeafter:D
1938 __kernel_primitive:NN \Umathradicaldegreebefore
1939 \utex_radicaldegreebefore:D
1940 __kernel_primitive:NN \Umathradicaldegreeraise
1941 \utex_radicaldegreeraise:D
1942 __kernel_primitive:NN \Umathradicalkern \utex_radicalkern:D
1943 __kernel_primitive:NN \Umathradicalrule \utex_radicalrule:D
1944 __kernel_primitive:NN \Umathradicalvgap \utex_radicalvgap:D
1945 __kernel_primitive:NN \Umathrelbinspacing \utex_relbinspacing:D

1946	<code>__kernel_primitive:NN \Umathrelclosespacing</code>	<code>\utex_relclosespacing:D</code>
1947	<code>__kernel_primitive:NN \Umathrelinnerspacing</code>	<code>\utex_relinnerspacing:D</code>
1948	<code>__kernel_primitive:NN \Umathrelopenspacing</code>	<code>\utex_relopenspacing:D</code>
1949	<code>__kernel_primitive:NN \Umathrellopspacing</code>	<code>\utex_relopspacing:D</code>
1950	<code>__kernel_primitive:NN \Umathrelordspacing</code>	<code>\utex_relordspacing:D</code>
1951	<code>__kernel_primitive:NN \Umathrelpunctspacing</code>	<code>\utex_relpunctspacing:D</code>
1952	<code>__kernel_primitive:NN \Umathrelrelspacing</code>	<code>\utex_relrelspacing:D</code>
1953	<code>__kernel_primitive:NN \Umathskewedfractionhgap</code>	
1954	<code>\utex_skewedfractionhgap:D</code>	
1955	<code>__kernel_primitive:NN \Umathskewedfractionvgap</code>	
1956	<code>\utex_skewedfractionvgap:D</code>	
1957	<code>__kernel_primitive:NN \Umathspaceafterscript</code>	<code>\utex_spaceafterscript:D</code>
1958	<code>__kernel_primitive:NN \Umathstackdenomdown</code>	<code>\utex_stackdenomdown:D</code>
1959	<code>__kernel_primitive:NN \Umathstacknumup</code>	<code>\utex_stacknumup:D</code>
1960	<code>__kernel_primitive:NN \Umathstackvgap</code>	<code>\utex_stackvgap:D</code>
1961	<code>__kernel_primitive:NN \Umathsubshiftdown</code>	<code>\utex_subshiftdown:D</code>
1962	<code>__kernel_primitive:NN \Umathsubshiftdrop</code>	<code>\utex_subshiftdrop:D</code>
1963	<code>__kernel_primitive:NN \Umathsubsupshiftdown</code>	<code>\utex_subsupshiftdown:D</code>
1964	<code>__kernel_primitive:NN \Umathsubsupvgap</code>	<code>\utex_subsupvgap:D</code>
1965	<code>__kernel_primitive:NN \Umathsubtopmax</code>	<code>\utex_subtopmax:D</code>
1966	<code>__kernel_primitive:NN \Umathsupbottommin</code>	<code>\utex_supbottommin:D</code>
1967	<code>__kernel_primitive:NN \Umathsupshiftdrop</code>	<code>\utex_supshiftdrop:D</code>
1968	<code>__kernel_primitive:NN \Umathsupshiftdown</code>	<code>\utex_supshiftdown:D</code>
1969	<code>__kernel_primitive:NN \Umathsupsubbottommax</code>	<code>\utex_supsubbottommax:D</code>
1970	<code>__kernel_primitive:NN \Umathunderbarkern</code>	<code>\utex_underbarkern:D</code>
1971	<code>__kernel_primitive:NN \Umathunderbarrule</code>	<code>\utex_underbarrule:D</code>
1972	<code>__kernel_primitive:NN \Umathunderbarvgap</code>	<code>\utex_underbarvgap:D</code>
1973	<code>__kernel_primitive:NN \Umathunderdelimeterbgap</code>	
1974	<code>\utex_underdelimeterbgap:D</code>	
1975	<code>__kernel_primitive:NN \Umathunderdelimitervgap</code>	
1976	<code>\utex_underdelimitervgap:D</code>	
1977	<code>__kernel_primitive:NN \Unosubscript</code>	<code>\utex_nosubscript:D</code>
1978	<code>__kernel_primitive:NN \Unosuperscript</code>	<code>\utex_nosuperscript:D</code>
1979	<code>__kernel_primitive:NN \Uoverdelimeter</code>	<code>\utex_overdelimeter:D</code>
1980	<code>__kernel_primitive:NN \Uradical</code>	<code>\utex_radical:D</code>
1981	<code>__kernel_primitive:NN \Uroot</code>	<code>\utex_root:D</code>
1982	<code>__kernel_primitive:NN \Uskewed</code>	<code>\utex_skewed:D</code>
1983	<code>__kernel_primitive:NN \Uskewedwithdelims</code>	<code>\utex_skewedwithdelims:D</code>
1984	<code>__kernel_primitive:NN \Ustack</code>	<code>\utex_stack:D</code>
1985	<code>__kernel_primitive:NN \Ustartdisplaymath</code>	<code>\utex_startdisplaymath:D</code>
1986	<code>__kernel_primitive:NN \Ustartmath</code>	<code>\utex_startmath:D</code>
1987	<code>__kernel_primitive:NN \Ustopdisplaymath</code>	<code>\utex_stopdisplaymath:D</code>
1988	<code>__kernel_primitive:NN \Ustopmath</code>	<code>\utex_stopmath:D</code>
1989	<code>__kernel_primitive:NN \Usubscript</code>	<code>\utex_subscript:D</code>
1990	<code>__kernel_primitive:NN \Usuperscript</code>	<code>\utex_superscript:D</code>
1991	<code>__kernel_primitive:NN \Uunderdelimeter</code>	<code>\utex_underdelimeter:D</code>
1992	<code>__kernel_primitive:NN \Uvextensible</code>	<code>\utex_vextensible:D</code>
1993	<code>__kernel_primitive:NN \autospacing</code>	<code>\ptex_autospacing:D</code>
1994	<code>__kernel_primitive:NN \autoxspacing</code>	<code>\ptex_autoxspacing:D</code>
1995	<code>__kernel_primitive:NN \dtou</code>	<code>\ptex_dtou:D</code>
1996	<code>__kernel_primitive:NN \epTeXinputencoding</code>	<code>\ptex_inputencoding:D</code>
1997	<code>__kernel_primitive:NN \epTeXversion</code>	<code>\ptex_epTeXversion:D</code>
1998	<code>__kernel_primitive:NN \euc</code>	<code>\ptex_euc:D</code>
1999	<code>__kernel_primitive:NN \ifdbbox</code>	<code>\ptex_ifdbbox:D</code>

```

2000 \__kernel_primitive:NN \ifddir \ptex_ifddir:D
2001 \__kernel_primitive:NN \ifmdir \ptex_ifmdir:D
2002 \__kernel_primitive:NN \iftbox \ptex_iftbox:D
2003 \__kernel_primitive:NN \iftdir \ptex_iftdir:D
2004 \__kernel_primitive:NN \ifybox \ptex_ifybox:D
2005 \__kernel_primitive:NN \ifydir \ptex_ifydir:D
2006 \__kernel_primitive:NN \inhibitglue \ptex_inhibitglue:D
2007 \__kernel_primitive:NN \inhibitxspcode \ptex_inhibitxspcode:D
2008 \__kernel_primitive:NN \jcharwidowpenalty \ptex_jcharwidowpenalty:D
2009 \__kernel_primitive:NN \jfam \ptex_jfam:D
2010 \__kernel_primitive:NN \jfont \ptex_jfont:D
2011 \__kernel_primitive:NN \jis \ptex_jis:D
2012 \__kernel_primitive:NN \kanjiskip \ptex_kanjiskip:D
2013 \__kernel_primitive:NN \kansuji \ptex_kansuji:D
2014 \__kernel_primitive:NN \kansujichar \ptex_kansujichar:D
2015 \__kernel_primitive:NN \kcatcode \ptex_kcatcode:D
2016 \__kernel_primitive:NN \kuten \ptex_kuten:D
2017 \__kernel_primitive:NN \noautospace \ptex_noautospace:D
2018 \__kernel_primitive:NN \noautoxspace \ptex_noautoxspace:D
2019 \__kernel_primitive:NN \postbreakpenalty \ptex_postbreakpenalty:D
2020 \__kernel_primitive:NN \prebreakpenalty \ptex_prebreakpenalty:D
2021 \__kernel_primitive:NN \ptexminorversion \ptex_ptexminorversion:D
2022 \__kernel_primitive:NN \ptexrevision \ptex_ptexrevision:D
2023 \__kernel_primitive:NN \ptexversion \ptex_ptexversion:D
2024 \__kernel_primitive:NN \showmode \ptex_showmode:D
2025 \__kernel_primitive:NN \sjis \ptex_sjis:D
2026 \__kernel_primitive:NN \tate \ptex_tate:D
2027 \__kernel_primitive:NN \tbaselineshift \ptex_tbaselineshift:D
2028 \__kernel_primitive:NN \tfont \ptex_tfont:D
2029 \__kernel_primitive:NN \xkanjiskip \ptex_xkanjiskip:D
2030 \__kernel_primitive:NN \xspcode \ptex_xspcode:D
2031 \__kernel_primitive:NN \ybaselineshift \ptex_ybaselineshift:D
2032 \__kernel_primitive:NN \yoko \ptex_yoko:D
2033 \__kernel_primitive:NN \disablecjktoken \uptex_disablecjktoken:D
2034 \__kernel_primitive:NN \enablecjktoken \uptex_enablecjktoken:D
2035 \__kernel_primitive:NN \forcecjktoken \uptex_forcecjktoken:D
2036 \__kernel_primitive:NN \kchar \uptex_kchar:D
2037 \__kernel_primitive:NN \kchardef \uptex_kchardef:D
2038 \__kernel_primitive:NN \kuten \uptex_kuten:D
2039 \__kernel_primitive:NN \ucs \uptex_ucs:D
2040 \__kernel_primitive:NN \uptexrevision \uptex_uptexrevision:D
2041 \__kernel_primitive:NN \uptexversion \uptex_uptexversion:D
2042 }
2043 }
2044 \__kernel_primitives:
2045 \tex_endgroup:D
2046 </package>
2047 </initex | package>

```

3 Internal kernel functions

<hr/> <code>_kernel_chk_cs_exist:N</code> <hr/> <code>_kernel_chk_cs_exist:c</code> <hr/>	<code>_kernel_chk_cs_exist:N <cs></code> This function is only created if debugging is enabled. It checks that <code><cs></code> exists according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error.
<hr/> <code>_kernel_chk_defined:NT</code> <hr/>	<code>_kernel_chk_defined:NT <variable> {<true code>}</code> If <code><variable></code> is not defined (according to <code>\cs_if_exist:NTF</code>), this triggers an error, otherwise the <code><true code></code> is run.
<hr/> <code>_kernel_chk_expr:nNnN</code> <hr/>	<code>_kernel_chk_expr:nNnN {<expr>} <eval> {<convert>} <caller></code> This function is only created if debugging is enabled. By default it is equivalent to <code>\use_i:nNnn</code> . When expression checking is enabled, it leaves in the input stream the result of <code>\tex_the:D <eval> <expr> \tex_relax:D</code> after checking that no token was left over. If any token was not taken as part of the expression, there is an error message displaying the result of the evaluation as well as the <code><caller></code> . For instance <code><eval></code> can be <code>_int_eval:w</code> and <code><caller></code> can be <code>\int_eval:n</code> or <code>\int_set:Nn</code> . The argument <code><convert></code> is empty except for mu expressions where it is <code>\tex_mutoglue:D</code> , used for internal purposes.
<hr/> <code>_kernel_chk_var_exist:N</code> <hr/>	<code>_kernel_chk_var_exist:N <var></code> This function is only created if debugging is enabled. It checks that <code><var></code> is defined according to the criteria for <code>\cs_if_exist_p:N</code> , and if not raises a kernel-level error.
<hr/> <code>_kernel_chk_var_scope:NN</code> <hr/>	<code>_kernel_chk_var_scope:NN <scope> <var></code> Checks the <code><var></code> has the correct <code><scope></code> , and if not raises a kernel-level error. This function is only created if debugging is enabled. The <code><scope></code> is a single letter <code>l</code> , <code>g</code> , <code>c</code> denoting local variables, global variables, or constants. More precisely, if the variable name starts with a letter and an underscore (normal <code>expl3</code> convention) the function checks that this single letter matches the <code><scope></code> . Otherwise the function cannot know the scope <code><var></code> the first time: instead, it defines <code>_debug_chk_<var name></code> to store that information for the next call. Thus, if a given <code><var></code> is subject to assignments of different scopes a kernel error will result.
<hr/> <code>_kernel_chk_var_local:N</code> <hr/> <code>_kernel_chk_var_global:N</code> <hr/>	<code>_kernel_chk_var_local:N <var></code> <code>_kernel_chk_var_global:N <var></code> Applies <code>_kernel_chk_var_exist:N <var></code> , and assuming that is true applies <code>_kernel_chk_var_scope:NN <scope> <var></code> , where <code><scope></code> is <code>l</code> or <code>g</code> .
<hr/> <code>_kernel_cs_parm_from_arg_count:nnF</code> <hr/>	<code>_kernel_cs_parm_from_arg_count:nnF {<follow-on>} {<args>} {<false code>}</code> Evaluates the number of <code><args></code> and leaves the <code><follow-on></code> code followed by a brace group containing the required number of primitive parameter markers (<code>#1</code> , <i>etc.</i>). If the number of <code><args></code> is outside the range <code>[0, 9]</code> , the <code><false code></code> is inserted <i>instead</i> of the <code><follow-on></code> .

<u><code>_kernel_deprecation_code:nn</code></u>	<code>_kernel_deprecation_code:nn {⟨error code⟩} {⟨working code⟩}</code>	Stores both an <i>⟨error⟩</i> and <i>⟨working⟩</i> definition for given material such that they can be exchanged by <code>\debug_on:</code> and <code>\debug_off:</code> .
<u><code>_kernel_if_debug:TF</code></u>	<code>_kernel_if_debug:TF {⟨true code⟩} {⟨false code⟩}</code>	Runs the <i>⟨true code⟩</i> if debugging is enabled, namely only in L ^A T _E X 2 _ε package mode with one of the options <code>check-declarations</code> , <code>enable-debug</code> , or <code>log-functions</code> . Otherwise runs the <i>⟨false code⟩</i> . The T and F variants are not provided for this low-level conditional.
<u><code>_kernel_debug_log:x</code></u>	<code>_kernel_debug_log:x {⟨message text⟩}</code>	If the <code>log-functions</code> option is active, this function writes the <i>⟨message text⟩</i> to the log file using <code>\iow_log:x</code> . Otherwise, the <i>⟨message text⟩</i> is ignored using <code>\use_none:n</code> . This function is only created if debugging is enabled.
<u><code>_kernel_exp_not:w ★</code></u>	<code>_kernel_exp_not:w ⟨expandable tokens⟩ {⟨content⟩}</code>	Carries out expansion on the <i>⟨expandable tokens⟩</i> before preventing further expansion of the <i>⟨content⟩</i> as for <code>\exp_not:n</code> . Typically, the <i>⟨expandable tokens⟩</i> will alter the nature of the <i>⟨content⟩</i> , <i>i.e.</i> allow it to be generated in some way.
<code>\l_kernel_expl_bool</code>		A boolean which records the current code syntax status: <code>true</code> if currently inside a code environment. This variable should only be set by <code>\ExplSyntaxOn/\ExplSyntaxOff</code> . (End definition for <code>\l_kernel_expl_bool</code> .)
<u><code>_kernel_file_missing:n</code></u>	<code>_kernel_file_missing:n {⟨name⟩}</code>	Expands the <i>⟨name⟩</i> as per <code>_kernel_file_name_sanitize:nN</code> then produces an error message indicating that that file was not found.
<u><code>_kernel_file_name_sanitize:nN</code></u>	<code>_kernel_file_name_sanitize:nN {⟨name⟩} ⟨str var⟩</code>	For converting a <i>⟨name⟩</i> to a string where active characters are treated as strings.
<u><code>_kernel_file_input_push:n</code></u> <u><code>_kernel_file_input_pop:</code></u>	<code>_kernel_file_input_push:n {⟨name⟩}</code> <code>_kernel_file_input_pop:</code>	Used to push and pop data from the internal file stack: needed only in package mode, where interfacing with the L ^A T _E X 2 _ε kernel is necessary.
<u><code>_kernel_int_add:nnn ★</code></u>	<code>_kernel_int_add:nnn {⟨integer₁⟩} {⟨integer₂⟩} {⟨integer₃⟩}</code>	Expands to the result of adding the three <i>⟨integers⟩</i> (which must be suitable input for <code>\int_eval:w</code>), avoiding intermediate overflow. Overflow occurs only if the overall result is outside $[-2^{31}+1, 2^{31}-1]$. The <i>⟨integers⟩</i> may be of the form <code>\int_eval:w ... \scan_stop:</code> but may be evaluated more than once.

<hr/> <code>_kernel_ior_open:Nn</code> <code>_kernel_ior_open:No</code> <hr/>	<code>_kernel_ior_open:Nn <stream> {<file name>}</code> <p>This function has identical syntax to the public version. However, it does not take precautions against active characters in the <i><file name></i>, and it does not attempt to add a <i><path></i> to the <i><file name></i>: it is therefore intended to be used by higher-level functions which have already fully expanded the <i><file name></i> and which need to perform multiple open or close operations. See for example the implementation of <code>\file_get_full_name:nN</code>,</p>
<hr/> <code>_kernel_iow_with:Nnn</code> <hr/>	<code>_kernel_iow_with:Nnn <integer> {<value>} {<code>}</code> <p>If the <i><integer></i> is equal to the <i><value></i> then this function simply runs the <i><code></i>. Otherwise it saves the current value of the <i><integer></i>, sets it to the <i><value></i>, runs the <i><code></i>, and restores the <i><integer></i> to its former value. This is used to ensure that the <code>\newlinechar</code> is 10 when writing to a stream, which lets <code>\iow_newline:</code> work, and that <code>\errorcontextlines</code> is -1 when displaying a message.</p>
<hr/> <code>_kernel_msg_new:nnnn</code> <code>_kernel_msg_new:nnn</code> <hr/>	<code>_kernel_msg_new:nnnn {<module>} {<message>} {<text>} {<more text>}</code> <p>Creates a kernel <i><message></i> for a given <i><module></i>. The message is defined to first give <i><text></i> and then <i><more text></i> if the user requests it. If no <i><more text></i> is available then a standard text is given instead. Within <i><text></i> and <i><more text></i> four parameters (#1 to #4) can be used: these will be supplied and expanded at the time the message is used. An error is raised if the <i><message></i> already exists.</p>
<hr/> <code>_kernel_msg_set:nnnn</code> <code>_kernel_msg_set:nnn</code> <hr/>	<code>_kernel_msg_set:nnnn {<module>} {<message>} {<text>} {<more text>}</code> <p>Sets up the text for a kernel <i><message></i> for a given <i><module></i>. The message is defined to first give <i><text></i> and then <i><more text></i> if the user requests it. If no <i><more text></i> is available then a standard text is given instead. Within <i><text></i> and <i><more text></i> four parameters (#1 to #4) can be used: these will be supplied and expanded at the time the message is used.</p>
<hr/> <code>_kernel_msg_fatal:nnnnnn</code> <code>_kernel_msg_fatal:nnxxxx</code> <code>_kernel_msg_fatal:nnnnn</code> <code>_kernel_msg_fatal:nnxxx</code> <code>_kernel_msg_fatal:nnnn</code> <code>_kernel_msg_fatal:nnxx</code> <code>_kernel_msg_fatal:nnn</code> <code>_kernel_msg_fatal:nnx</code> <code>_kernel_msg_fatal:nn</code> <hr/>	<code>_kernel_msg_fatal:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> <p>Issues kernel <i><module></i> error <i><message></i>, passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. After issuing a fatal error the T_EX run halts. Cannot be redirected.</p>
<hr/> <code>_kernel_msg_error:nnnnnn</code> <code>_kernel_msg_error:nnxxxx</code> <code>_kernel_msg_error:nnnnn</code> <code>_kernel_msg_error:nnxxx</code> <code>_kernel_msg_error:nnnn</code> <code>_kernel_msg_error:nnxx</code> <code>_kernel_msg_error:nnn</code> <code>_kernel_msg_error:nnx</code> <code>_kernel_msg_error:nn</code> <hr/>	<code>_kernel_msg_error:nnnnnn {<module>} {<message>} {<arg one>} {<arg two>} {<arg three>} {<arg four>}</code> <p>Issues kernel <i><module></i> error <i><message></i>, passing <i><arg one></i> to <i><arg four></i> to the text-creating functions. The error stops processing and issues the text at the terminal. After user input, the run continues. Cannot be redirected.</p>

```

\__kernel_msg_warning:nnnnnn \__kernel_msg_warning:nnnnnn {\module} {\message} {\arg one} {\arg
\__kernel_msg_warning:nnxxxx two} {\arg three} {\arg four}
\__kernel_msg_warning:nnnnn
\__kernel_msg_warning:nnxxx
\__kernel_msg_warning:nnnn
\__kernel_msg_warning:nnxx
\__kernel_msg_warning:nnn
\__kernel_msg_warning:nnx
\__kernel_msg_warning:nn

```

Issues kernel $\langle module \rangle$ warning $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The warning text is added to the log file, but the \TeX run is not interrupted.

```

\__kernel_msg_info:nnnnnn \__kernel_msg_info:nnnnnn {\module} {\message} {\arg one} {\arg two} {\arg
\__kernel_msg_info:nnxxxx three} {\arg four}
\__kernel_msg_info:nnnnn
\__kernel_msg_info:nnxxx
\__kernel_msg_info:nnnn
\__kernel_msg_info:nnxx
\__kernel_msg_info:nnn
\__kernel_msg_info:nnx
\__kernel_msg_info:nn

```

Issues kernel $\langle module \rangle$ information $\langle message \rangle$, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The information text is added to the log file.

```

\__kernel_msg_expandable_error:nnnnnn * \__kernel_msg_expandable_error:nnnnnn {\module} {\message}
\__kernel_msg_expandable_error:nnffff * {\arg one} {\arg two} {\arg three} {\arg four}
\__kernel_msg_expandable_error:nnnnn *
\__kernel_msg_expandable_error:nnfff *
\__kernel_msg_expandable_error:nnnn *
\__kernel_msg_expandable_error:nnff *
\__kernel_msg_expandable_error:nnn *
\__kernel_msg_expandable_error:nnf *
\__kernel_msg_expandable_error:nn *

```

Issues an error, passing $\langle arg one \rangle$ to $\langle arg four \rangle$ to the text-creating functions. The resulting string must be much shorter than a line, otherwise it is cropped.

```

\__kernel_patch:nnNNpn \__kernel_patch:nnNNpn {\before} {\after}
\__kernel_patch:nnNNpn {\definition} {\function} {\parameters} {\code}

```

If debugging is not enabled, this function ignores the $\langle before \rangle$ and $\langle after \rangle$ code and performs the $\langle definition \rangle$ with no patching. Otherwise it replaces $\langle code \rangle$ by $\langle before \rangle \langle code \rangle \langle after \rangle$ (which can involve $\#1$ and so on) in the $\langle definition \rangle$ that follows. The $\langle definition \rangle$ must start with \cs_new:Npn or \cs_set:Npn or \cs_gset:Npn or their $_protected$ counterparts. Other cases can be added as needed.

```

\__kernel_patch_conditional:nnNNpnn \__kernel_patch_conditional:nnNNpnn {\before}
\__kernel_patch_conditional:nnNNpnn {\definition} {\conditional} {\parameters} {\type} {\code}

```

Similar to $\text{__kernel_patch:nnNNpn}$ for conditionals, namely $\langle definition \rangle$ must be $\text{\prg_new_conditional:Npnn}$ or its $_protected$ counterpart. There is no $\langle after \rangle$ code because that would interfere with the action of the conditional.

<code>__kernel_patch_deprecation:nnNNpn</code>	<code>__kernel_patch_deprecation:nnNNpn {<before>} {<after>}</code> <code><definition> <function> <parameters> {<type>} {<code>}</code>
---	---

Similar to `__kernel_patch:nnNNpn` for deprecated functions.

<code>__kernel_patch_args:nnNpn</code>	<code>__kernel_patch_args:nnNpn {<arguments>}</code>
<code>__kernel_patch_conditional_args:nnNpnn</code>	<code><definition> <function> <parameters> {<code>}</code>

Like `__kernel_patch:nnNNpn`, this tweaks the following definition, but from the “inside out” (and if debugging is not enabled, the `<arguments>` are ignored). It replaces `#1`, `#2` and so on in the `<code>` of the definition as indicated by the `<arguments>`. More precisely, a temporary function is defined using the `<definition>` with the `<parameters>` and `<code>`, then the result of expanding that function once in front of the `<arguments>` is used instead of the `<code>` when defining the actual function. For instance,

```
\__kernel_patch_args:nnNpn { { (#1) } }
\cs_new:Npn \int_eval:n #1
{ \int_value:w \__int_eval:w #1 \__int_eval_end: }
```

would replace `#1` by `(#1)` in the definition of `\int_eval:n` when debugging is enabled. This fails if the `<code>` contains `##`. The `__kernel_patch_conditional_args:nnNpnn` function is for use before `\prg_new_conditional:Npnn` or its `_protected` counterpart.

<code>__kernel_patch_args:nnnNNpn</code>	<code>__kernel_patch_args:nnnNNpn {<before>} {<after>}</code>
<code>__kernel_patch_conditional_args:nnnNNpnn</code>	<code>{<arguments>}</code> <code><definition> <function> <parameters> {<code>}</code>

A combination of `__kernel_patch:nnNNpn` and `__kernel_patch_args:nnNpn`.

`\g__kernel_prg_map_int` This integer is used by non-expandable mapping functions to track the level of nesting in force. The functions `\<type>_map_1:w`, `\<type>_map_2:w`, *etc.*, labelled by `\g__kernel_prg_map_int` hold functions to be mapped over various list datatypes in inline and variable mappings.

(End definition for `\g__kernel_prg_map_int`.)

`\c__kernel_randint_max_int` Maximal allowed argument to `__kernel_randint:n`. Equal to $2^{17} - 1$.

(End definition for `\c__kernel_randint_max_int`.)

<code>__kernel_randint:n</code>	<code>__kernel_randint:n {<max>}</code>
----------------------------------	--

Used in an integer expression this gives a pseudo-random number between 1 and `<max>` included. One must have $\langle max \rangle \leq 2^{17} - 1$. The `<max>` must be suitable for `\int_value:w` (and any `\int_eval:w` must be terminated by `\scan_stop:` or equivalent).

<code>__kernel_randint:nn</code>	<code>__kernel_randint:nn {<min>} {<max>}</code>
-----------------------------------	---

Used in an integer expression this gives a pseudo-random number between `<min>` and `<max>` included. The `<min>` and `<max>` must be suitable for `\int_value:w` (and any `\int_eval:w` must be terminated by `\scan_stop:` or equivalent). For small ranges $R = \langle max \rangle - \langle min \rangle + 1 \leq 2^{17} - 1$, $\langle min \rangle - 1 + __kernel_randint:n\{R\}$ is faster.

<hr/> <code>_kernel_register_show:N</code> <hr/>	<code>_kernel_register_show:N <register></code>
<code>_kernel_register_show:c</code> <hr/>	Used to show the contents of a T _E X register at the terminal, formatted such that internal parts of the mechanism are not visible.
<hr/> <code>_kernel_register_log:N</code> <hr/>	<code>_kernel_register_log:N <register></code>
<code>_kernel_register_log:c</code> <hr/>	Used to write the contents of a T _E X register to the log file in a form similar to <code>_kernel_register_show:N</code> .
<hr/> <code>_kernel_str_to_other:n ☆</code> <hr/>	<code>_kernel_str_to_other:n <{token list}></code> Converts the <i><token list></i> to a <i><other string></i> , where spaces have category code “other”. This function can be f-expanded without fear of losing a leading space, since spaces do not have category code 10 in its result. It takes a time quadratic in the character count of the string.
<hr/> <code>_kernel_str_to_other_fast:n ☆</code> <hr/>	<code>_kernel_str_to_other_fast:n <{token list}></code> Same behaviour <code>_kernel_str_to_other:n</code> but only restricted-expandable. It takes a time linear in the character count of the string.
<hr/> <code>_kernel_tl_to_str:w ☆</code> <hr/>	<code>_kernel_tl_to_str:w <expandable tokens> <{tokens}></code> Carries out expansion on the <i><expandable tokens></i> before conversion of the <i><tokens></i> to a string as describe for <code>\tl_to_str:n</code> . Typically, the <i><expandable tokens></i> will alter the nature of the <i><tokens></i> , <i>i.e.</i> allow it to be generated in some way. This function requires only a single expansion.

4 l3basics implementation

2048 `<*initex | package>`

4.1 Renaming some T_EX primitives (again)

Having given all the T_EX primitives a consistent name, we need to give sensible names to the ones we actually want to use. These will be defined as needed in the appropriate modules, but we do a few now, just to get started.⁵

<code>\if_true:</code>	Then some conditionals.	
<code>\if_false:</code>	2049 <code>\tex_let:D \if_true:</code>	<code>\tex_iftrue:D</code>
<code>\or:</code>	2050 <code>\tex_let:D \if_false:</code>	<code>\tex_iffalse:D</code>
<code>\else:</code>	2051 <code>\tex_let:D \or:</code>	<code>\tex_or:D</code>
<code>\fi:</code>	2052 <code>\tex_let:D \else:</code>	<code>\tex_else:D</code>
<code>\reverse_if:N</code>	2053 <code>\tex_let:D \fi:</code>	<code>\tex_fi:D</code>
<code>\if:w</code>	2054 <code>\tex_let:D \reverse_if:N</code>	<code>\tex_unless:D</code>
<code>\if_charcode:w</code>	2055 <code>\tex_let:D \if:w</code>	<code>\tex_if:D</code>
<code>\if_catcode:w</code>	2056 <code>\tex_let:D \if_charcode:w</code>	<code>\tex_if:D</code>
<code>\if_meaning:w</code>	2057 <code>\tex_let:D \if_catcode:w</code>	<code>\tex_ifcat:D</code>
	2058 <code>\tex_let:D \if_meaning:w</code>	<code>\tex_ifx:D</code>

(End definition for `\if_true:` and others. These functions are documented on page 20.)

⁵This renaming gets expensive in terms of csname usage, an alternative scheme would be to just use the `\tex_...:D` name in the cases where no good alternative exists.

`\if_mode_math:` T_EX lets us detect some if its modes.

<code>\if_mode_horizontal:</code>	2059	<code>\tex_let:D \if_mode_math:</code>	<code>\tex_ifmmode:D</code>
<code>\if_mode_vertical:</code>	2060	<code>\tex_let:D \if_mode_horizontal:</code>	<code>\tex_ifhmode:D</code>
<code>\if_mode_inner:</code>	2061	<code>\tex_let:D \if_mode_vertical:</code>	<code>\tex_ifvmode:D</code>
	2062	<code>\tex_let:D \if_mode_inner:</code>	<code>\tex_ifinner:D</code>

(End definition for `\if_mode_math:` and others. These functions are documented on page 21.)

`\if_cs_exist:N` Building csnames and testing if control sequences exist.

<code>\if_cs_exist:w</code>	2063	<code>\tex_let:D \if_cs_exist:N</code>	<code>\tex_ifdefined:D</code>
<code>\cs:w</code>	2064	<code>\tex_let:D \if_cs_exist:w</code>	<code>\tex_ifcsname:D</code>
<code>\cs_end:</code>	2065	<code>\tex_let:D \cs:w</code>	<code>\tex_csname:D</code>
	2066	<code>\tex_let:D \cs_end:</code>	<code>\tex_endcsname:D</code>

(End definition for `\if_cs_exist:N` and others. These functions are documented on page 21.)

`\exp_after:wN` The five `\exp_` functions are used in the `l3expan` module where they are described.

<code>\exp_not:N</code>	2067	<code>\tex_let:D \exp_after:wN</code>	<code>\tex_expandafter:D</code>
<code>\exp_not:n</code>	2068	<code>\tex_let:D \exp_not:N</code>	<code>\tex_noexpand:D</code>
	2069	<code>\tex_let:D \exp_not:n</code>	<code>\tex_unexpanded:D</code>
	2070	<code>\tex_let:D \exp:w</code>	<code>\tex_romannumeral:D</code>
	2071	<code>\tex_chardef:D \exp_end:</code>	<code>= 0 ~</code>

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 30.)

`\token_to_meaning:N` Examining a control sequence or token.

<code>\cs_meaning:N</code>	2072	<code>\tex_let:D \token_to_meaning:N</code>	<code>\tex_meaning:D</code>
	2073	<code>\tex_let:D \cs_meaning:N</code>	<code>\tex_meaning:D</code>

(End definition for `\token_to_meaning:N` and `\cs_meaning:N`. These functions are documented on page 122.)

`\tl_to_str:n` Making strings.

<code>\token_to_str:N</code>	2074	<code>\tex_let:D \tl_to_str:n</code>	<code>\tex_detokenize:D</code>
<code>__kernel_tl_to_str:w</code>	2075	<code>\tex_let:D \token_to_str:N</code>	<code>\tex_string:D</code>
	2076	<code>\tex_let:D __kernel_tl_to_str:w</code>	<code>\tex_detokenize:D</code>

(End definition for `\tl_to_str:n`, `\token_to_str:N`, and `__kernel_tl_to_str:w`. These functions are documented on page 42.)

`\scan_stop:` The next three are basic functions for which there also exist versions that are safe inside alignments. These safe versions are defined in the `l3prg` module.

<code>\group_begin:</code>	2077	<code>\tex_let:D \scan_stop:</code>	<code>\tex_relax:D</code>
<code>\group_end:</code>	2078	<code>\tex_let:D \group_begin:</code>	<code>\tex_begingroup:D</code>
	2079	<code>\tex_let:D \group_end:</code>	<code>\tex_endgroup:D</code>

(End definition for `\scan_stop:`, `\group_begin:`, and `\group_end:`. These functions are documented on page 8.)

	2080	<code><@@=int></code>	
--	------	-----------------------------	--

`\if_int_compare:w` For integers.

<code>__int_to_roman:w</code>	2081	<code>\tex_let:D \if_int_compare:w</code>	<code>\tex_ifnum:D</code>
	2082	<code>\tex_let:D __int_to_roman:w</code>	<code>\tex_romannumeral:D</code>

(End definition for `\if_int_compare:w` and `__int_to_roman:w`. This function is documented on page 91.)

`\group_insert_after:N` Adding material after the end of a group.

```
2083 \tex_let:D \group_insert_after:N \tex_aftergroup:D
```

(End definition for `\group_insert_after:N`. This function is documented on page 8.)

`\exp_args:Nc` Discussed in `l3expan`, but needed much earlier.

`\exp_args:cc`

```
2084 \tex_long:D \tex_def:D \exp_args:Nc #1#2
2085 { \exp_after:wN #1 \cs:w #2 \cs_end: }
2086 \tex_long:D \tex_def:D \exp_args:cc #1#2
2087 { \cs:w #1 \exp_after:wN \cs_end: \cs:w #2 \cs_end: }
```

(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 26.)

`\token_to_meaning:c` A small number of variants defined by hand. Some of the necessary functions (`\use_i-
\token_to_str:c` `i:nn`, `\use_ii:nn`, and `\exp_args:Nnc`) are not defined at that point yet, but will be
`\cs_meaning:c` defined before those variants are used. The `\cs_meaning:c` command must check for an
undefined control sequence to avoid defining it mistakenly.

```
2088 \tex_def:D \token_to_str:c { \exp_args:Nc \token_to_str:N }
2089 \tex_long:D \tex_def:D \cs_meaning:c #1
2090 {
2091   \if_cs_exist:w #1 \cs_end:
2092   \exp_after:wN \use_i:nn
2093   \else:
2094     \exp_after:wN \use_ii:nn
2095   \fi:
2096   { \exp_args:Nc \cs_meaning:N {#1} }
2097   { \tl_to_str:n {undefined} }
2098 }
2099 \tex_let:D \token_to_meaning:c = \cs_meaning:c
```

(End definition for `\token_to_meaning:N`. This function is documented on page 122.)

4.2 Defining some constants

`\c_zero_int` We need the constant `\c_zero_int` which is used by some functions in the `l3alloc` module. The rest are defined in the `l3int` module – at least for the ones that can be defined with `\tex_chardef:D` or `\tex_mathchardef:D`. For other constants the `l3int` module is required but it can't be used until the allocation has been set up properly!

```
2100 \tex_chardef:D \c_zero_int = 0 ~
```

(End definition for `\c_zero_int`. This variable is documented on page 90.)

`\c_max_register_int` This is here as this particular integer is needed both in package mode and to bootstrap `l3alloc`, and is documented in `l3int`.

```
2101 \tex_ifdefined:D \tex_luaTeXversion:D
2102 \tex_chardef:D \c_max_register_int = 65 535 ~
2103 \tex_else:D
2104 \tex_mathchardef:D \c_max_register_int = 32 767 ~
2105 \tex_fi:D
```

(End definition for `\c_max_register_int`. This variable is documented on page 90.)

4.3 Defining functions

We start by providing functions for the typical definition functions. First the local ones.

<code>\cs_set_nopar:Npn</code>	All assignment functions in L ^A T _E X3 should be naturally protected; after all, the T _E X
<code>\cs_set_nopar:Npx</code>	primitives for assignments are and it can be a cause of problems if others aren't.
<code>\cs_set:Npn</code>	2106 <code>\tex_let:D \cs_set_nopar:Npn \tex_def:D</code>
<code>\cs_set:Npx</code>	2107 <code>\tex_let:D \cs_set_nopar:Npx \tex_edef:D</code>
<code>\cs_set_protected_nopar:Npn</code>	2108 <code>\tex_protected:D \tex_long:D \tex_def:D \cs_set:Npn</code>
<code>\cs_set_protected_nopar:Npx</code>	2109 <code>{ \tex_long:D \tex_def:D }</code>
<code>\cs_set_protected:Npn</code>	2110 <code>\tex_protected:D \tex_long:D \tex_def:D \cs_set:Npx</code>
<code>\cs_set_protected:Npx</code>	2111 <code>{ \tex_long:D \tex_edef:D }</code>
	2112 <code>\tex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npn</code>
	2113 <code>{ \tex_protected:D \tex_def:D }</code>
	2114 <code>\tex_protected:D \tex_long:D \tex_def:D \cs_set_protected_nopar:Npx</code>
	2115 <code>{ \tex_protected:D \tex_edef:D }</code>
	2116 <code>\tex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npn</code>
	2117 <code>{ \tex_protected:D \tex_long:D \tex_def:D }</code>
	2118 <code>\tex_protected:D \tex_long:D \tex_def:D \cs_set_protected:Npx</code>
	2119 <code>{ \tex_protected:D \tex_long:D \tex_edef:D }</code>

(End definition for `\cs_set_nopar:Npn` and others. These functions are documented on page 10.)

<code>\cs_gset_nopar:Npn</code>	Global versions of the above functions.
<code>\cs_gset_nopar:Npx</code>	2120 <code>\tex_let:D \cs_gset_nopar:Npn \tex_gdef:D</code>
<code>\cs_gset:Npn</code>	2121 <code>\tex_let:D \cs_gset_nopar:Npx \tex_xdef:D</code>
<code>\cs_gset:Npx</code>	2122 <code>\cs_set_protected:Npn \cs_gset:Npn</code>
<code>\cs_gset_protected_nopar:Npn</code>	2123 <code>{ \tex_long:D \tex_gdef:D }</code>
<code>\cs_gset_protected_nopar:Npx</code>	2124 <code>\cs_set_protected:Npn \cs_gset:Npx</code>
<code>\cs_gset_protected:Npn</code>	2125 <code>{ \tex_long:D \tex_xdef:D }</code>
<code>\cs_gset_protected:Npx</code>	2126 <code>\cs_set_protected:Npn \cs_gset_protected_nopar:Npn</code>
	2127 <code>{ \tex_protected:D \tex_gdef:D }</code>
	2128 <code>\cs_set_protected:Npn \cs_gset_protected_nopar:Npx</code>
	2129 <code>{ \tex_protected:D \tex_xdef:D }</code>
	2130 <code>\cs_set_protected:Npn \cs_gset_protected:Npn</code>
	2131 <code>{ \tex_protected:D \tex_long:D \tex_gdef:D }</code>
	2132 <code>\cs_set_protected:Npn \cs_gset_protected:Npx</code>
	2133 <code>{ \tex_protected:D \tex_long:D \tex_xdef:D }</code>

(End definition for `\cs_gset_nopar:Npn` and others. These functions are documented on page 11.)

4.4 Selecting tokens

2134 `<@@=exp>`

`\l__exp_internal_tl` Scratch token list variable for l3expan, used by `\use:x`, used in defining conditionals. We don't use `tl` methods because l3basics is loaded earlier.

2135 `\cs_set_nopar:Npn \l__exp_internal_tl { }`

(End definition for `\l__exp_internal_tl`.)

`\use:c` This macro grabs its argument and returns a csname from it.

2136 `\cs_set:Npn \use:c #1 { \cs:w #1 \cs_end: }`

(End definition for `\use:c`. This function is documented on page 15.)

\use:x Fully expands its argument and passes it to the input stream. Uses the reserved `\l__exp_internal_tl` which will be set up in `l3expan`.

```
2137 \cs_set_protected:Npn \use:x #1
2138 {
2139   \cs_set_nopar:Npx \l__exp_internal_tl {#1}
2140   \l__exp_internal_tl
2141 }
```

(End definition for `\use:x`. This function is documented on page 18.)

```
2142 <@@=use>
```

\use:e Currently LuaTeX-only: emulated for older engines.

```
2143 \cs_set:Npn \use:e #1 { \tex_expanded:D {#1} }
2144 \tex_ifdefined:D \tex_expanded:D \tex_else:D
2145   \cs_set:Npn \use:e #1 { \exp_args:Ne \use:n {#1} }
2146 \tex_fi:D
```

(End definition for `\use:e`. This function is documented on page 18.)

```
2147 <@@=exp>
```

\use:n These macros grab their arguments and return them back to the input (with outer braces removed).

```
\use:nnn 2148 \cs_set:Npn \use:n #1 {#1}
\use:nnnn 2149 \cs_set:Npn \use:nn #1#2 {#1#2}
2150 \cs_set:Npn \use:nnn #1#2#3 {#1#2#3}
2151 \cs_set:Npn \use:nnnn #1#2#3#4 {#1#2#3#4}
```

(End definition for `\use:n` and others. These functions are documented on page 17.)

\use_i:nn The equivalent to L^AT_EX 2_ε's `\@firstoftwo` and `\@secondoftwo`.

```
\use_ii:nn 2152 \cs_set:Npn \use_i:nn #1#2 {#1}
2153 \cs_set:Npn \use_ii:nn #1#2 {#2}
```

(End definition for `\use_i:nn` and `\use_ii:nn`. These functions are documented on page 17.)

\use_i:nnn We also need something for picking up arguments from a longer list.

```
\use_ii:nnn 2154 \cs_set:Npn \use_i:nnn #1#2#3 {#1}
\use_iii:nnn 2155 \cs_set:Npn \use_ii:nnn #1#2#3 {#2}
\use_i_ii:nnn 2156 \cs_set:Npn \use_iii:nnn #1#2#3 {#3}
\use_i:nnnn 2157 \cs_set:Npn \use_i_ii:nnn #1#2#3 {#1#2}
\use_ii:nnnn 2158 \cs_set:Npn \use_i:nnnn #1#2#3#4 {#1}
\use_iii:nnnn 2159 \cs_set:Npn \use_ii:nnnn #1#2#3#4 {#2}
\use_iv:nnnn 2160 \cs_set:Npn \use_iii:nnnn #1#2#3#4 {#3}
2161 \cs_set:Npn \use_iv:nnnn #1#2#3#4 {#4}
```

(End definition for `\use_i:nnn` and others. These functions are documented on page 17.)

\use_none_delimit_by_q_nil:w Functions that gobble everything until they see either `\q_nil`, `\q_stop`, or `\q_recursion_stop`, respectively.

```
\use_none_delimit_by_q_stop:w 2162 \cs_set:Npn \use_none_delimit_by_q_nil:w #1 \q_nil { }
\use_none_delimit_by_q_recursion_stop:w 2163 \cs_set:Npn \use_none_delimit_by_q_stop:w #1 \q_stop { }
2164 \cs_set:Npn \use_none_delimit_by_q_recursion_stop:w #1 \q_recursion_stop { }
```

(End definition for `\use_none_delimit_by_q_nil:w`, `\use_none_delimit_by_q_stop:w`, and `\use_none_delimit_by_q_recursion_stop:w`. These functions are documented on page 18.)

`\use_i_delimit_by_q_nil:nw` Same as above but execute first argument after gobbling. Very useful when you need to skip the rest of a mapping sequence but want an easy way to control what should be expanded next.

```
2165 \cs_set:Npn \use_i_delimit_by_q_nil:nw #1#2 \q_nil {#1}
2166 \cs_set:Npn \use_i_delimit_by_q_stop:nw #1#2 \q_stop {#1}
2167 \cs_set:Npn \use_i_delimit_by_q_recursion_stop:nw
2168 #1#2 \q_recursion_stop {#1}
```

(End definition for `\use_i_delimit_by_q_nil:nw`, `\use_i_delimit_by_q_stop:nw`, and `\use_i_delimit_by_q_recursion_stop:nw`. These functions are documented on page 19.)

4.5 Gobbling tokens from input

`\use_none:n` To gobble tokens from the input we use a standard naming convention: the number of tokens gobbled is given by the number of n's following the : in the name. Although we could define functions to remove ten arguments or more using separate calls of `\use_none:nnnnn`, this is very non-intuitive to the programmer who will assume that expanding such a function once takes care of gobbling all the tokens in one go.

```
\use_none:n      2169 \cs_set:Npn \use_none:n      #1      { }
\use_none:nn     2170 \cs_set:Npn \use_none:nn     #1#2    { }
\use_none:nnn    2171 \cs_set:Npn \use_none:nnn    #1#2#3   { }
\use_none:nnnn   2172 \cs_set:Npn \use_none:nnnn   #1#2#3#4  { }
\use_none:nnnnn  2173 \cs_set:Npn \use_none:nnnnn  #1#2#3#4#5  { }
\use_none:nnnnnn 2174 \cs_set:Npn \use_none:nnnnnn  #1#2#3#4#5#6  { }
\use_none:nnnnnnn 2175 \cs_set:Npn \use_none:nnnnnnn  #1#2#3#4#5#6#7  { }
\use_none:nnnnnnnn 2176 \cs_set:Npn \use_none:nnnnnnnn  #1#2#3#4#5#6#7#8  { }
\use_none:nnnnnnnnn 2177 \cs_set:Npn \use_none:nnnnnnnnn  #1#2#3#4#5#6#7#8#9 { }
```

(End definition for `\use_none:n` and others. These functions are documented on page 18.)

4.6 Debugging and patching later definitions

```
2178 <@@=debug>
```

`__kernel_if_debug:TF` A more meaningful test of whether debugging is enabled than messing up with guards. We can also more easily change the logic in one place then. At present, debugging is disabled in the format and in generic mode, while in $\text{\LaTeX}2_{\epsilon}$ mode it is enabled if one of the options `enable-debug`, `log-functions` or `check-declarations` was given.

```
2179 \cs_set_protected:Npn \__kernel_if_debug:TF #1#2 {#2}
2180 <*package>
2181 \tex_ifodd:D \l@expl@enable@debug@bool
2182 \cs_set_protected:Npn \__kernel_if_debug:TF #1#2 {#1}
2183 \fi:
2184 </package>
```

(End definition for `__kernel_if_debug:TF`.)

```
\debug_on:n
\debug_off:n  2185 \__kernel_if_debug:TF
\__debug_all_on: 2186 {
\__debug_all_off: 2187 \cs_set_protected:Npn \debug_on:n #1
```

```

2188     {
2189         \exp_args:No \clist_map_inline:nn { \tl_to_str:n {#1} }
2190         {
2191             \cs_if_exist_use:cF { __debug_ ##1 _on: }
2192             { \__kernel_msg_error:nnn { kernel } { debug } {##1} }
2193         }
2194     }
2195 \cs_set_protected:Npn \debug_off:n #1
2196 {
2197     \exp_args:No \clist_map_inline:nn { \tl_to_str:n {#1} }
2198     {
2199         \cs_if_exist_use:cF { __debug_ ##1 _off: }
2200         { \__kernel_msg_error:nnn { kernel } { debug } {##1} }
2201     }
2202 }
2203 \cs_set_protected:Npn \__debug_all_on:
2204 {
2205     \debug_on:n
2206     {
2207         check-declarations ,
2208         check-expressions ,
2209         deprecation ,
2210         log-functions ,
2211     }
2212 }
2213 \cs_set_protected:Npn \__debug_all_off:
2214 {
2215     \debug_off:n
2216     {
2217         check-declarations ,
2218         check-expressions ,
2219         deprecation ,
2220         log-functions ,
2221     }
2222 }
2223 }
2224 {
2225     \cs_set_protected:Npn \debug_on:n #1
2226     {
2227         \__kernel_msg_error:nnx { kernel } { enable-debug }
2228         { \tl_to_str:n { \debug_on:n {#1} } }
2229     }
2230     \cs_set_protected:Npn \debug_off:n #1
2231     {
2232         \__kernel_msg_error:nnx { kernel } { enable-debug }
2233         { \tl_to_str:n { \debug_off:n {#1} } }
2234     }
2235 }

```

(End definition for `\debug_on:n` and others. These functions are documented on page 240.)

\debug_suspend: Suspend and resume locally all debug-related errors and logging except deprecation errors.

\debug_resume: The `\debug_suspend:` and `\debug_resume:` pairs can be nested. We keep track of

```

    \__debug_suspended:T
    \l__debug_suspended_tl

```

nesting in a token list containing a number of periods. At first begin with the “non-suspended” version of `__debug_suspended:T`.

```

2236 \__kernel_if_debug:TF
2237 {
2238   \cs_set_nopar:Npn \l__debug_suspended_tl { }
2239   \cs_set_protected:Npn \debug_suspend:
2240     {
2241       \tl_put_right:Nn \l__debug_suspended_tl { . }
2242       \cs_set_eq:NN \__debug_suspended:T \use:n
2243     }
2244   \cs_set_protected:Npn \debug_resume:
2245     {
2246       \tl_set:Nx \l__debug_suspended_tl
2247         { \tl_tail:N \l__debug_suspended_tl }
2248       \tl_if_empty:NT \l__debug_suspended_tl
2249         {
2250           \cs_set_eq:NN \__debug_suspended:T \use_none:n
2251         }
2252     }
2253   \cs_set:Npn \__debug_suspended:T #1 { }
2254 }
2255 {
2256   \cs_set_protected:Npn \debug_suspend: { }
2257   \cs_set_protected:Npn \debug_resume: { }
2258 }

```

(End definition for `\debug_suspend:` and others. These functions are documented on page 240.)

When debugging is enabled these two functions set up functions that test their argument (when `check-declarations` is active)

- `__kernel_chk_var_exist:N` and `__kernel_chk_cs_exist:N`, two functions that test that their argument is defined;
- `__kernel_chk_var_scope:NN` that checks that its argument #2 has scope #1.
- `__kernel_chk_var_local:N` and `__kernel_chk_var_global:N` that perform both checks.

```

2259 \__kernel_if_debug:TF
2260 {
2261   \exp_args:Nc \cs_set_protected:Npn { __debug_check-declarations_on: }
2262   {
2263     \cs_set_protected:Npn \__kernel_chk_var_exist:N ##1
2264     {
2265       \__debug_suspended:T \use_none:nnn
2266       \cs_if_exist:NF ##1
2267       {
2268         \__kernel_msg_error:nnx { kernel } { non-declared-variable }
2269         { \token_to_str:N ##1 }
2270       }
2271     }
2272   \cs_set_protected:Npn \__kernel_chk_cs_exist:N ##1
2273   {
2274     \__debug_suspended:T \use_none:nnn

```



```

2275         \cs_if_exist:NF ##1
2276         {
2277             \__kernel_msg_error:nxx { kernel } { command-not-defined }
2278             { \token_to_str:N ##1 }
2279         }
2280     }
2281     \cs_set_protected:Npn \__kernel_chk_var_scope:NN
2282     {
2283         \__debug_suspended:T \use_none:nnn
2284         \__debug_chk_var_scope_aux:NN
2285     }
2286     \cs_set_protected:Npn \__kernel_chk_var_local:N ##1
2287     {
2288         \__debug_suspended:T \use_none:nnnnn
2289         \__kernel_chk_var_exist:N ##1
2290         \__debug_chk_var_scope_aux:NN l ##1
2291     }
2292     \cs_set_protected:Npn \__kernel_chk_var_global:N ##1
2293     {
2294         \__debug_suspended:T \use_none:nnnnn
2295         \__kernel_chk_var_exist:N ##1
2296         \__debug_chk_var_scope_aux:NN g ##1
2297     }
2298 }
2299 \exp_args:Nc \cs_set_protected:Npn { __debug_check-declarations_off: }
2300 {
2301     \cs_set_protected:Npn \__kernel_chk_var_exist:N ##1 { }
2302     \cs_set_protected:Npn \__kernel_chk_cs_exist:N ##1 { }
2303     \cs_set_protected:Npn \__kernel_chk_var_local:N ##1 { }
2304     \cs_set_protected:Npn \__kernel_chk_var_global:N ##1 { }
2305     \cs_set_protected:Npn \__kernel_chk_var_scope:NN ##1##2 { }
2306 }
2307 \cs_set_protected:Npn \__kernel_chk_cs_exist:c
2308 { \exp_args:Nc \__kernel_chk_cs_exist:N }
2309 \tex_ifodd:D \l@expl@check@declarations@bool
2310 \use:c { __debug_check-declarations_on: }
2311 \else:
2312 \use:c { __debug_check-declarations_off: }
2313 \fi:
2314 }
2315 { }

```

(End definition for `__debug_check-declarations_on:` and others.)

`__debug_chk_var_scope_aux:NN` First check whether the name of the variable #2 starts with $\langle letter \rangle_$. If it does then pass that letter, the $\langle scope \rangle$, and the variable name to `__debug_chk_var_scope_aux:NNn`.
`__debug_chk_var_scope_aux:Nn` That function compares the two letters and triggers an error if they differ (the `\scan_stop:` case is not reachable here). If the second character was not `_` then pass the same data to the same auxiliary, except for its first argument which is now a control sequence.
`__debug_chk_var_scope_aux:NNn` That control sequence is actually a token list (but to avoid triggering the checking code we manipulate it using `\cs_set_nopar:Npn`) containing a single letter $\langle scope \rangle$ according to what the first assignment to the given variable was.

```

2316 \__kernel_if_debug:TF
2317 {

```

```

2318 \cs_set_protected:Npn \__debug_chk_var_scope_aux:NN #1#2
2319 { \exp_args:NNf \__debug_chk_var_scope_aux:Nn #1 { \cs_to_str:N #2 } }
2320 \cs_set_protected:Npn \__debug_chk_var_scope_aux:Nn #1#2
2321 {
2322   \if:w _ \use_i:nn \use_i_delimit_by_q_stop:nw #2 ? ? \q_stop
2323   \exp_after:wN \__debug_chk_var_scope_aux:NNn
2324   \use_i_delimit_by_q_stop:nw #2 ? \q_stop
2325   #1 {#2}
2326   \else:
2327     \exp_args:Nc \__debug_chk_var_scope_aux:NNn
2328     { __debug_chk_/ #2 }
2329     #1 {#2}
2330   \fi:
2331 }
2332 \cs_set_protected:Npn \__debug_chk_var_scope_aux:NNn #1#2#3
2333 {
2334   \if:w #1 #2
2335   \else:
2336     \if:w #1 \scan_stop:
2337       \cs_gset_nopar:Npn #1 {#2}
2338     \else:
2339       \__kernel_msg_error:nxxxx { kernel } { local-global }
2340       {#1} {#2} { \iow_char:N \ \ #3 }
2341     \fi:
2342   \fi:
2343 }
2344 }
2345 { }

```

(End definition for `__debug_chk_var_scope_aux:NN`, `__debug_chk_var_scope_aux:Nn`, and `__debug_chk_var_scope_aux:NNn`.)

```

\__debug_check-expressions_on:
\__debug_check-expressions_off:
\__kernel_chk_expr:nNnN
\__debug_chk_expr_aux:nNnN

```

When debugging is enabled these two functions set `__kernel_chk_expr:nNnN` to test or not whether the given expression is valid. The idea is to evaluate the expression within a brace group (to catch trailing `\use_none:nn` or similar), then test that the result is what we expect. This is done by turning it to an integer and hitting that with `\tex_romannumeral:D` after replacing the first character by `-0`. If all goes well, that primitive finds a non-positive integer and gives an empty output. If the original expression evaluation stopped early it leaves a trailing `\tex_relax:D`, which stops the second evaluation (used to convert to integer) before it encounters the final `\tex_relax:D`. Since `\tex_romannumeral:D` does not absorb `\tex_relax:D` the output will be nonempty. Note that `#3` is empty except for mu expressions for which it is `\tex_mutogluue:D` to avoid an “incompatible glue units” error. Note also that if we had omitted the first `\tex_relax:D` then for instance `1+2\relax+3` would incorrectly be accepted as a valid integer expression.

```

2346 \__kernel_if_debug:TF
2347 {
2348   \exp_args:Nc \cs_set_protected:Npn { __debug_check-expressions_on: }
2349   {
2350     \cs_set:Npn \__kernel_chk_expr:nNnN ##1##2
2351     {
2352       \__debug_suspended:T { ##1 \use_none:nnnnnnn }
2353       \exp_after:wN \__debug_chk_expr_aux:nNnN

```

```

2354         \exp_after:wN { \tex_the:D ##2 ##1 \scan_stop: }
2355         ##2
2356     }
2357 }
2358 \exp_args:Nc \cs_set_protected:Npn { __debug_check-expressions_off: }
2359 { \cs_set:Npn \__kernel_chk_expr:nNnN ##1##2##3##4 {##1} }
2360 \use:c { __debug_check-expressions_off: }
2361 \cs_set:Npn \__debug_chk_expr_aux:nNnN #1#2#3#4
2362 {
2363     \tl_if_empty:oF
2364     {
2365         \tex_romannumeral:D - 0
2366         \exp_after:wN \use_none:n
2367         \int_value:w #3 #2 #1 \scan_stop:
2368     }
2369     {
2370         \__kernel_msg_expandable_error:nnnn
2371         { kernel } { expr } {#4} {#1}
2372     }
2373     #1
2374 }
2375 }
2376 { }

```

(End definition for `__debug_check-expressions_on:` and others.)

`__debug_log-functions_on:` These two functions (corresponding to the `expl3` option `log-functions`) control whether
`__debug_log-functions_off:` `__kernel_debug_log:x` writes to the log file or not. Since `\iow_log:x` does not yet
`__kernel_debug_log:x` have its final definition we do not use `\cs_set_eq:NN` (not defined yet anyway). Once
everything is defined, turn logging on or off depending on what option was given. When
debugging is not enabled, simply produce an error.

```

2377 \__kernel_if_debug:TF
2378 {
2379     \exp_args:Nc \cs_set_protected:Npn { __debug_log-functions_on: }
2380     {
2381         \cs_set_protected:Npn \__kernel_debug_log:x
2382         { \__debug_suspended:T \use_none:nn \iow_log:x }
2383     }
2384     \exp_args:Nc \cs_set_protected:Npn { __debug_log-functions_off: }
2385     { \cs_set_protected:Npn \__kernel_debug_log:x { \use_none:n } }
2386     \tex_ifodd:D \l@expl@log@functions@bool
2387     \use:c { __debug_log-functions_on: }
2388     \else:
2389     \use:c { __debug_log-functions_off: }
2390     \fi:
2391 }
2392 { }

```

(End definition for `__debug_log-functions_on:`, `__debug_log-functions_off:`, and `__kernel-debug_log:x`.)

`__debug_deprecation_on:` Some commands were more recently deprecated and not yet removed; only make these
`__debug_deprecation_off:` into errors if the user requests it. This relies on two token lists, mostly filled up by calls
`__kernel_deprecation_code:nn` to `__kernel_patch_deprecation:nnNNpn` in each module.

`\g__debug_deprecation_on_tl`
`\g__debug_deprecation_off_tl`

```

2393 \__kernel_if_debug:TF
2394 {
2395   \cs_set_protected:Npn \__debug_deprecation_on:
2396     { \g__debug_deprecation_on_tl }
2397   \cs_set_protected:Npn \__debug_deprecation_off:
2398     { \g__debug_deprecation_off_tl }
2399   \cs_set_nopar:Npn \g__debug_deprecation_on_tl { }
2400   \cs_set_nopar:Npn \g__debug_deprecation_off_tl { }
2401   \cs_set_protected:Npn \__kernel_deprecation_code:nn #1#2
2402     {
2403       \tl_gput_right:Nn \g__debug_deprecation_on_tl {#1}
2404       \tl_gput_right:Nn \g__debug_deprecation_off_tl {#2}
2405     }
2406   }
2407   {
2408     \cs_set_protected:Npn \__kernel_deprecation_code:nn #1#2 { }
2409   }

```

(End definition for __debug_deprecation_on: and others.)

__kernel_patch_deprecation:nnNNn
 __debug_deprecation_aux:nnNnn

Grab a definition (at present, must be \cs_new_protected:Npn or \cs_new:Npn). Add to \g__debug_deprecation_on_tl some code that makes the defined macro #3 outer (and defines it as an error). Add to \g__debug_deprecation_off_tl the definition itself. In both cases we undefine the token with \tex_let:D to avoid taking a potentially outer macro as the argument of some expl3 function. Finally, define the macro itself: if it is protected, make it produce a warning then redefine and call itself. The macro initially takes no parameters: together with the x-expanding assignment and \exp_not:n this gives a convenient way of storing the macro's definition in itself in order to only produce the warning once for each macro. If debugging is disabled, __kernel_patch_deprecation:nnNNn lets the definition happen.

```

2410 \__kernel_if_debug:TF
2411 {
2412   \cs_set_protected:Npn \__kernel_patch_deprecation:nnNNn #1#2#3#4#5#
2413     {
2414       \if_meaning:w \cs_new_protected:Npn #3
2415         \exp_after:wN \use_i:nn
2416       \else:
2417         \if_meaning:w \cs_new:Npn #3
2418         \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
2419       \else:
2420         \__kernel_msg_error:nnx { kernel } { debug-unpatchable }
2421         { \token_to_str:N #3 ~(for-deprecation) }
2422         \exp_after:wN \exp_after:wN \exp_after:wN \use_none:nn
2423       \fi:
2424       \fi:
2425       { \__debug_deprecation_aux:nnNnn {#1} {#2} #4 {#5} }
2426       { \__debug_deprecation_expandable:nnNnn {#1} {#2} #4 {#5} }
2427     }
2428   \cs_set_protected:Npn \__debug_deprecation_aux:nnNnn #1#2#3#4#5
2429     {
2430       \tl_gput_right:Nn \g__debug_deprecation_on_tl
2431         {
2432           \tex_let:D #3 \scan_stop:
2433           \__kernel_deprecation_error:Nnn #3 {#2} {#1}

```

```

2434     }
2435     \tl_gput_right:Nn \g__debug_deprecation_off_tl
2436     {
2437         \tex_let:D #3 \scan_stop:
2438         \cs_set_protected:Npn #3 #4 {#5}
2439     }
2440     \cs_new_protected:Npx #3
2441     {
2442         \exp_not:N \__kernel_msg_warning:nnxxx
2443         { kernel } { deprecated-command }
2444         {#1} { \token_to_str:N #3 } { \tl_to_str:n {#2} }
2445         \exp_not:n { \cs_gset_protected:Npn #3 #4 {#5} }
2446         \exp_not:N #3
2447     }
2448 }
2449 \cs_set_protected:Npn \__debug_deprecation_expandable:nnNnn #1#2#3#4#5
2450 {
2451     \tl_gput_right:Nn \g__debug_deprecation_on_tl
2452     {
2453         \tex_let:D #3 \scan_stop:
2454         \__kernel_deprecation_error:Nnn #3 {#2} {#1}
2455     }
2456     \tl_gput_right:Nn \g__debug_deprecation_off_tl
2457     {
2458         \tex_let:D #3 \scan_stop:
2459         \cs_set:Npn #3 #4 {#5}
2460     }
2461     \cs_new:Npn #3 #4 {#5}
2462 }
2463 }
2464 { \cs_set_protected:Npn \__kernel_patch_deprecation:nnNNpn #1#2 { } }

```

(End definition for __kernel_patch_deprecation:nnNNpn and __debug_deprecation_aux:nnNnn.)

__kernel_patch:nnNNpn When debugging is not enabled, __kernel_patch:nnNNpn and __kernel_patch_conditional:nnNpnn throw the patch away. Otherwise they can be followed by \cs_new:Npn (or similar), and \prg_new_conditional:Npnn (or similar), respectively. In each case, grab the name of the function to be defined and its parameters then insert tokens before and/or after the definition.

```

2465 \__kernel_if_debug:TF
2466 {
2467     \cs_set_protected:Npn \__kernel_patch:nnNNpn #1#2#3#4#5#
2468     { \__debug_patch_aux:nnnn {#1} {#2} { #3 #4 #5 } }
2469     \cs_set_protected:Npn \__kernel_patch_conditional:nnNpnn #1#2#3#4#
2470     { \__debug_patch_auxii:nnnn {#1} { #2 #3 #4 } }
2471     \cs_set_protected:Npn \__debug_patch_aux:nnnn #1#2#3#4
2472     { #3 { #1 #4 #2 } }
2473     \cs_set_protected:Npn \__debug_patch_auxii:nnnn #1#2#3#4
2474     { #2 {#3} { #1 #4 } }
2475 }
2476 {
2477     \cs_set_protected:Npn \__kernel_patch:nnNNpn #1#2 { }
2478     \cs_set_protected:Npn \__kernel_patch_conditional:nnNpnn #1 { }
2479 }

```

(End definition for `_kernel_patch:nNNp` and others.)

```

\_kernel_patch_args:nNNp
\_kernel_patch_conditional_args:nNNpnn
\_kernel_patch_args:nnnNNpnn
\_kernel_patch_conditional_args:nnnNNpnn
    \_debug_tmp:w
    \_debug_patch_args_aux:nnnNNnn
    \_debug_patch_args_aux:nnnNNnnn
\_debug_patch_args_aux:nnnn
2480 \cs_set_protected:Npn \_kernel_patch_args:nNNpnn
2481   { \_kernel_patch_args:nnnNNpnn { } { } }
2482 \cs_set_protected:Npn \_kernel_patch_conditional_args:nNNpnn
2483   { \_kernel_patch_conditional_args:nnnNNpnn { } { } }
2484 \_kernel_if_debug:TF
2485   {
2486     \cs_set_protected:Npn \_kernel_patch_args:nnnNNpnn #1#2#3#4#5#6#
2487       { \_debug_patch_args_aux:nnnNNnn {#1} {#2} {#3} #4 #5 {#6} }
2488     \cs_set_protected:Npn \_kernel_patch_conditional_args:nnnNNpnn
2489       #1#2#3#4#5#6#
2490       { \_debug_patch_args_aux:nnnNNnnn {#1} {#2} {#3} #4 #5 {#6} }
2491     \cs_set_protected:Npn \_debug_patch_args_aux:nnnNNnn #1#2#3#4#5#6#7
2492       {
2493         \cs_set:Npn \_debug_tmp:w #6 {#7}
2494         \exp_after:wN \_debug_patch_args_aux:nnnn \exp_after:wN
2495           { \_debug_tmp:w #3 } { #4 #5 #6 } {#1} {#2}
2496       }
2497     \cs_set_protected:Npn \_debug_patch_args_aux:nnnNNnnn #1#2#3#4#5#6#7#8
2498       {
2499         \cs_set:Npn \_debug_tmp:w #6 {#8}
2500         \exp_after:wN \_debug_patch_args_aux:nnnn \exp_after:wN
2501           { \_debug_tmp:w #3 } { #4 #5 #6 {#7} } {#1} {#2}
2502       }
2503     \cs_set_protected:Npn \_debug_patch_args_aux:nnnn #1#2#3#4
2504       { #2 { #3 #1 #4 } }
2505   }
2506   {
2507     \cs_set_protected:Npn \_kernel_patch_args:nnnNNpnn #1#2#3 { }
2508     \cs_set_protected:Npn \_kernel_patch_conditional_args:nnnNNpnn
2509       #1#2#3 { }
2510   }

```

(End definition for `_kernel_patch_args:nNNp` and others.)

4.7 Conditional processing and definitions

2511 `<@@=prg>`

Underneath any predicate function (`_p`) or other conditional forms (`TF`, etc.) is a built-in logic saying that it after all of the testing and processing must return the *<state>* this leaves `TeX` in. Therefore, a simple user interface could be something like

```

\_if_meaning:w #1#2
  \prg_return_true:
\_else:
  \if_meaning:w #1#3
    \prg_return_true:
  \else:
    \prg_return_false:

```

```

\fi:
\fi:

```

Usually, a T_EX programmer would have to insert a number of `\exp_after:wN`s to ensure the state value is returned at exactly the point where the last conditional is finished. However, that obscures the code and forces the T_EX programmer to prove that he/she knows the $2^n - 1$ table. We therefore provide the simpler interface.

`\prg_return_true:` The idea here is that `\exp:w` expands fully any `\else:` and `\fi:` that are waiting to be discarded, before reaching the `\exp_end:` which leaves an empty expansion. The code can then leave either the first or second argument in the input stream. This means that all of the branching code has to contain at least two tokens: see how the logical tests are actually implemented to see this.

```

2512 \cs_set:Npn \prg_return_true:
2513 { \exp_after:wN \use_i:nn \exp:w }
2514 \cs_set:Npn \prg_return_false:
2515 { \exp_after:wN \use_ii:nn \exp:w }

```

An extended state space could be implemented by including a more elaborate function in place of `\use_i:nn/\use_ii:nn`. Provided two arguments are absorbed then the code would work.

(End definition for \prg_return_true: and \prg_return_false:. These functions are documented on page 97.)

`\prg_set_conditional:Npnn` The user functions for the types using parameter text from the programmer. The various functions only differ by which function is used for the assignment. For those `Npnn` type functions, we must grab the parameter text, reading everything up to a left brace before continuing. Then split the base function into name and signature, and feed `{\<name>}` `{\<signature>}` `\<boolean>` `{\<set or new>}` `{\<maybe protected>}` `{\<parameters>}` `{TF,...}` `{\<code>}` to the auxiliary function responsible for defining all conditionals. Note that `e` stands for expandable and `p` for protected.

```

2516 \cs_set_protected:Npn \prg_set_conditional:Npnn
2517 { \prg_generate_conditional_parm:NNNpnn \cs_set:Npn e }
2518 \cs_set_protected:Npn \prg_new_conditional:Npnn
2519 { \prg_generate_conditional_parm:NNNpnn \cs_new:Npn e }
2520 \cs_set_protected:Npn \prg_set_protected_conditional:Npnn
2521 { \prg_generate_conditional_parm:NNNpnn \cs_set_protected:Npn p }
2522 \cs_set_protected:Npn \prg_new_protected_conditional:Npnn
2523 { \prg_generate_conditional_parm:NNNpnn \cs_new_protected:Npn p }
2524 \cs_set_protected:Npn \prg_generate_conditional_parm:NNNpnn #1#2#3#4#
2525 {
2526   \use:x
2527   {
2528     \prg_generate_conditional:nnNNNnnn
2529     \cs_split_function:N #3
2530   }
2531   #1 #2 {#4}
2532 }

```

(End definition for \prg_set_conditional:Npnn and others. These functions are documented on page 95.)

`\prg_set_conditional:Nnn`
`\prg_new_conditional:Nnn`
`\prg_set_protected_conditional:Nnn`
`\prg_new_protected_conditional:Nnn`
`__prg_generate_conditional_count:NNNnn`
`__prg_generate_conditional_count:nnNNNnn`

The user functions for the types automatically inserting the correct parameter text based on the signature. The various functions only differ by which function is used for the assignment. Split the base function into name and signature. The second auxiliary generates the parameter text from the number of letters in the signature. Then feed $\{\langle name \rangle\} \{\langle signature \rangle\} \langle boolean \rangle \{\langle set \text{ or } new \rangle\} \{\langle maybe \text{ protected} \rangle\} \{\langle parameters \rangle\} \{\text{TF}, \dots\} \{\langle code \rangle\}$ to the auxiliary function responsible for defining all conditionals. If the $\langle signature \rangle$ has more than 9 letters, the definition is aborted since T_EX macros have at most 9 arguments. The erroneous case where the function name contains no colon is captured later.

```

2533 \cs_set_protected:Npn \prg_set_conditional:Nnn
2534 { \__prg_generate_conditional_count:NNNnn \cs_set:Npn e }
2535 \cs_set_protected:Npn \prg_new_conditional:Nnn
2536 { \__prg_generate_conditional_count:NNNnn \cs_new:Npn e }
2537 \cs_set_protected:Npn \prg_set_protected_conditional:Nnn
2538 { \__prg_generate_conditional_count:NNNnn \cs_set_protected:Npn p }
2539 \cs_set_protected:Npn \prg_new_protected_conditional:Nnn
2540 { \__prg_generate_conditional_count:NNNnn \cs_new_protected:Npn p }
2541 \cs_set_protected:Npn \__prg_generate_conditional_count:NNNnn #1#2#3
2542 {
2543   \use:x
2544   {
2545     \__prg_generate_conditional_count:nnNNNnn
2546     \cs_split_function:N #3
2547   }
2548   #1 #2
2549 }
2550 \cs_set_protected:Npn \__prg_generate_conditional_count:nnNNNnn #1#2#3#4#5
2551 {
2552   \__kernel_cs_parm_from_arg_count:nnF
2553   { \__prg_generate_conditional:nnNNNnn {#1} {#2} #3 #4 #5 }
2554   { \tl_count:n {#2} }
2555   {
2556     \__kernel_msg_error:nxxx { kernel } { bad-number-of-arguments }
2557     { \token_to_str:c { #1 : #2 } }
2558     { \tl_count:n {#2} }
2559     \use_none:nn
2560   }
2561 }

```

(End definition for `\prg_set_conditional:Nnn` and others. These functions are documented on page 95.)

`__prg_generate_conditional:nnNNNnn`
`__prg_generate_conditional:NNnnnnNw`
`__prg_generate_conditional_test:w`
`__prg_generate_conditional_fast:nn`

The workhorse here is going through a list of desired forms, *i.e.*, p, TF, T and F. The first three arguments come from splitting up the base form of the conditional, which gives the name, signature and a boolean to signal whether or not there was a colon in the name. In the absence of a colon, we throw an error and don't define any conditional. The fourth and fifth arguments build up the defining function. The sixth is the parameters to use (possibly empty), the seventh is the list of forms to define, the eighth is the replacement text which we will augment when defining the forms. The use of `\tl_to_str:n` makes the later loop more robust.

A large number of our low-level conditionals look like $\langle code \rangle$ `\prg_return_true:` `\else:` `\prg_return_false:` `\fi:` so we optimize this special case by calling `__prg_`

generate_conditional_fast:nw *{code}*. This passes \use_i:nn instead of \use_i_ii:nnn to functions such as __prg_generate_p_form:wNNnnnnN.

```

2562 \cs_set_protected:Npn \__prg_generate_conditional:nnNNnnnn #1#2#3#4#5#6#7#8
2563 {
2564   \if_meaning:w \c_false_bool #3
2565   \__kernel_msg_error:nnx { kernel } { missing-colon }
2566   { \token_to_str:c {#1} }
2567   \exp_after:wN \use_none:nn
2568   \fi:
2569   \use:x
2570   {
2571     \exp_not:N \__prg_generate_conditional:NNnnnnNw
2572     \exp_not:n { #4 #5 {#1} {#2} {#6} }
2573     \__prg_generate_conditional_test:w
2574     #8 \q_mark
2575     \__prg_generate_conditional_fast:nw
2576     \prg_return_true: \else: \prg_return_false: \fi: \q_mark
2577     \use_none:n
2578     \exp_not:n { {#8} \use_i_ii:nnn }
2579     \tl_to_str:n {#7}
2580     \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
2581   }
2582 }
2583 \cs_set:Npn \__prg_generate_conditional_test:w
2584   #1 \prg_return_true: \else: \prg_return_false: \fi: \q_mark #2
2585   { #2 {#1} }
2586 \cs_set:Npn \__prg_generate_conditional_fast:nw #1#2 \exp_not:n #3
2587   { \exp_not:n { {#1} \use_i:nn } }

```

Looping through the list of desired forms. First are six arguments and seventh is the form. Use the form to call the correct type. If the form does not exist, the \use:c construction results in \relax, and the error message is displayed (unless the form is empty, to allow for {T, , F}), then \use_none:nnnnnnnn cleans up. Otherwise, the error message is removed by the variant form.

```

2588 \cs_set_protected:Npn \__prg_generate_conditional:NNnnnnNw #1#2#3#4#5#6#7#8 ,
2589 {
2590   \if_meaning:w \q_recursion_tail #8
2591   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2592   \fi:
2593   \use:c { __prg_generate_ #8 _form:wNNnnnnN }
2594   \tl_if_empty:nF {#8}
2595   {
2596     \__kernel_msg_error:nnxx
2597     { kernel } { conditional-form-unknown }
2598     {#8} { \token_to_str:c { #3 : #4 } }
2599   }
2600   \use_none:nnnnnnnn
2601   \q_stop
2602   #1 #2 {#3} {#4} {#5} {#6} #7
2603   \__prg_generate_conditional:NNnnnnNw #1 #2 {#3} {#4} {#5} {#6} #7
2604 }

```

(End definition for __prg_generate_conditional:nnNNnnnn and others.)

```

\__prg_generate_p_form:wNNnnnnN
\__prg_generate_TF_form:wNNnnnnN
\__prg_generate_T_form:wNNnnnnN
\__prg_generate_F_form:wNNnnnnN
\__prg_p_true:w

```

How to generate the various forms. Those functions take the following arguments: 1: junk, 2: `\cs_set:Npn` or similar, 3: `p` (for protected conditionals) or `e`, 4: function name, 5: signature, 6: parameter text, 7: replacement (possibly trimmed by `__prg_generate_conditional_fast:nw`), 8: `\use_i_ii:nnn` or `\use_i:nn` (for “fast” conditionals). Remember that the logic-returning functions expect two arguments to be present after `\exp_end::`: notice the construction of the different variants relies on this, and that the TF and F variants will be slightly faster than the T version. The `p` form is only valid for expandable tests, we check for that by making sure that the second argument is empty. For “fast” conditionals, #7 has an extra `\if_...`. To optimize a bit further we could replace `\exp_after:wN \use_ii:nnn` and similar by a single macro similar to `__prg_p_true:w`. The drawback is that if the T or F arguments are actually missing, the recovery from the runaway argument would not insert `\fi:` back, messing up nesting of conditionals.

```

2605 \cs_set_protected:Npn \__prg_generate_p_form:wNNnnnnN
2606   #1 \q_stop #2#3#4#5#6#7#8
2607   {
2608     \if_meaning:w e #3
2609     \exp_after:wN \use_i:nn
2610   \else:
2611     \exp_after:wN \use_ii:nn
2612   \fi:
2613     {
2614       #8
2615       { \exp_args:Nc #2 { #4 _p: #5 } #6 }
2616       { { #7 \exp_end: \c_true_bool \c_false_bool } }
2617       { #7 \__prg_p_true:w \fi: \c_false_bool }
2618     }
2619     {
2620       \__kernel_msg_error:nxx { kernel } { protected-predicate }
2621       { \token_to_str:c { #4 _p: #5 } }
2622     }
2623   }
2624 \cs_set_protected:Npn \__prg_generate_T_form:wNNnnnnN
2625   #1 \q_stop #2#3#4#5#6#7#8
2626   {
2627     #8
2628     { \exp_args:Nc #2 { #4 : #5 T } #6 }
2629     { { #7 \exp_end: \use:n \use_none:n } }
2630     { #7 \exp_after:wN \use_ii:nn \fi: \use_none:n }
2631   }
2632 \cs_set_protected:Npn \__prg_generate_F_form:wNNnnnnN
2633   #1 \q_stop #2#3#4#5#6#7#8
2634   {
2635     #8
2636     { \exp_args:Nc #2 { #4 : #5 F } #6 }
2637     { { #7 \exp_end: { } } }
2638     { #7 \exp_after:wN \use_none:nn \fi: \use:n }
2639   }
2640 \cs_set_protected:Npn \__prg_generate_TF_form:wNNnnnnN
2641   #1 \q_stop #2#3#4#5#6#7#8
2642   {
2643     #8
2644     { \exp_args:Nc #2 { #4 : #5 TF } #6 }

```

```

2645     { { #7 \exp_end: } }
2646     { #7 \exp_after:wN \use_ii:nnn \fi: \use_ii:nn }
2647   }
2648   \cs_set:Npn \__prg_p_true:w \fi: \c_false_bool { \fi: \c_true_bool }

```

(End definition for __prg_generate_p_form:wNNnnnnN and others.)

\prg_set_eq_conditional:NNn The setting-equal functions. Split both functions and feed $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$ $\langle boolean_1 \rangle$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$ $\langle boolean_2 \rangle$ $\langle copying\ function \rangle$ $\langle conditions \rangle$, **\prg_new_eq_conditional:NNn** $\langle recursion_tail \rangle$, $\langle q_recursion_stop \rangle$ to a first auxiliary.

```

2649 \cs_set_protected:Npn \prg_set_eq_conditional:NNn
2650   { \__prg_set_eq_conditional:NNnn \cs_set_eq:cc }
2651 \cs_set_protected:Npn \prg_new_eq_conditional:NNn
2652   { \__prg_set_eq_conditional:NNnn \cs_new_eq:cc }
2653 \cs_set_protected:Npn \__prg_set_eq_conditional:NNnn #1#2#3#4
2654   {
2655     \use:x
2656     {
2657       \exp_not:N \__prg_set_eq_conditional:nnNnnNNw
2658       \cs_split_function:N #2
2659       \cs_split_function:N #3
2660       \exp_not:N #1
2661       \tl_to_str:n {#4}
2662       \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
2663     }
2664   }

```

(End definition for \prg_set_eq_conditional:NNn, \prg_new_eq_conditional:NNn, and __prg_set_eq_conditional:NNnn. These functions are documented on page 96.)

__prg_set_eq_conditional:nnNnnNW Split the function to be defined, and setup a manual clist loop over argument #6 of the first auxiliary. The second auxiliary receives twice three arguments coming from splitting the function to be defined and the function to copy. Make sure that both functions contained a colon, otherwise we don't know how to build conditionals, hence abort. Call the looping macro, with arguments $\{\langle name_1 \rangle\}$ $\{\langle signature_1 \rangle\}$ $\{\langle name_2 \rangle\}$ $\{\langle signature_2 \rangle\}$ $\langle copying\ function \rangle$ and followed by the comma list. At each step in the loop, make sure that the conditional form we copy is defined, and copy it, otherwise abort.

```

2665 \cs_set_protected:Npn \__prg_set_eq_conditional:nnNnnNW #1#2#3#4#5#6
2666   {
2667     \if_meaning:w \c_false_bool #3
2668       \__kernel_msg_error:nnx { kernel } { missing-colon }
2669       { \token_to_str:c {#1} }
2670       \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2671       \fi:
2672     \if_meaning:w \c_false_bool #6
2673       \__kernel_msg_error:nnx { kernel } { missing-colon }
2674       { \token_to_str:c {#4} }
2675       \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2676       \fi:
2677     \__prg_set_eq_conditional_loop:nnnnNW {#1} {#2} {#4} {#5}
2678   }
2679 \cs_set_protected:Npn \__prg_set_eq_conditional_loop:nnnnNW #1#2#3#4#5#6 ,
2680   {
2681     \if_meaning:w \q_recursion_tail #6

```

```

2682 \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
2683 \fi:
2684 \use:c { __prg_set_eq_conditional_ #6 _form:wNnnnn }
2685 \tl_if_empty:nF {#6}
2686 {
2687 \__kernel_msg_error:nxxx
2688 { kernel } { conditional-form-unknown }
2689 {#6} { \token_to_str:c { #1 : #2 } }
2690 }
2691 \use_none:nnnnnn
2692 \q_stop
2693 #5 {#1} {#2} {#3} {#4}
2694 \__prg_set_eq_conditional_loop:nnnnNw {#1} {#2} {#3} {#4} #5
2695 }
2696 \__kernel_patch:nnNNpn
2697 { \__kernel_chk_cs_exist:c { #5 _p : #6 } } { }
2698 \cs_set:Npn \__prg_set_eq_conditional_p_form:wNnnnn #1 \q_stop #2#3#4#5#6
2699 { #2 { #3 _p : #4 } { #5 _p : #6 } }
2700 \__kernel_patch:nnNNpn
2701 { \__kernel_chk_cs_exist:c { #5 : #6 TF } } { }
2702 \cs_set:Npn \__prg_set_eq_conditional_TF_form:wNnnnn #1 \q_stop #2#3#4#5#6
2703 { #2 { #3 : #4 TF } { #5 : #6 TF } }
2704 \__kernel_patch:nnNNpn
2705 { \__kernel_chk_cs_exist:c { #5 : #6 T } } { }
2706 \cs_set:Npn \__prg_set_eq_conditional_T_form:wNnnnn #1 \q_stop #2#3#4#5#6
2707 { #2 { #3 : #4 T } { #5 : #6 T } }
2708 \__kernel_patch:nnNNpn
2709 { \__kernel_chk_cs_exist:c { #5 : #6 F } } { }
2710 \cs_set:Npn \__prg_set_eq_conditional_F_form:wNnnnn #1 \q_stop #2#3#4#5#6
2711 { #2 { #3 : #4 F } { #5 : #6 F } }

```

(End definition for `__prg_set_eq_conditional:nnNnnNw` and others.)

All that is left is to define the canonical boolean true and false. I think Michael originated the idea of expandable boolean tests. At first these were supposed to expand into either TT or TF to be tested using `\if:w` but this was later changed to 00 and 01, so they could be used in logical operations. Later again they were changed to being numerical constants with values of 1 for true and 0 for false. We need this from the get-go.

```

\c_true_bool Here are the canonical boolean values.
\c_false_bool
2712 \tex_chardef:D \c_true_bool = 1 ~
2713 \tex_chardef:D \c_false_bool = 0 ~

```

(End definition for `\c_true_bool` and `\c_false_bool`. These variables are documented on page 20.)

4.8 Dissecting a control sequence

```

2714 <@@=cs>

```

```

\__cs_count_signature:N \__cs_count_signature:N <function>

```

Splits the *<function>* into the *<name>* (i.e. the part before the colon) and the *<signature>* (i.e. after the colon). The *<number>* of tokens in the *<signature>* is then left in the input stream. If there was no *<signature>* then the result is the marker value `-1`.

`_cs_get_function_name:N` ★ `_cs_get_function_name:N` $\langle function \rangle$

Splits the $\langle function \rangle$ into the $\langle name \rangle$ (*i.e.* the part before the colon) and the $\langle signature \rangle$ (*i.e.* after the colon). The $\langle name \rangle$ is then left in the input stream without the escape character present made up of tokens with category code 12 (other).

`_cs_get_function_signature:N` ★ `_cs_get_function_signature:N` $\langle function \rangle$

Splits the $\langle function \rangle$ into the $\langle name \rangle$ (*i.e.* the part before the colon) and the $\langle signature \rangle$ (*i.e.* after the colon). The $\langle signature \rangle$ is then left in the input stream made up of tokens with category code 12 (other).

`_cs_tmp:w`

Function used for various short-term usages, for instance defining functions whose definition involves tokens which are hard to insert normally (spaces, characters with category other).

`\cs_to_str:N` This converts a control sequence into the character string of its name, removing the leading escape character. This turns out to be a non-trivial matter as there are different cases:

- The usual case of a printable escape character;
- the case of a non-printable escape characters, e.g., when the value of the `\escapechar` is negative;
- when the escape character is a space.

One approach to solve this is to test how many tokens result from `\token_to_str:N \a`. If there are two tokens, then the escape character is printable, while if it is non-printable then only one is present.

However, there is an additional complication: the control sequence itself may start with a space. Clearly that should *not* be lost in the process of converting to a string. So the approach adopted is a little more intricate still. When the escape character is printable, `\token_to_str:N _` yields the escape character itself and a space. The character codes are different, thus the `\if:w` test is false, and TeX reads `_cs_to_str:N` after turning the following control sequence into a string; this auxiliary removes the escape character, and stops the expansion of the initial `\tex_romannumeral:D`. The second case is that the escape character is not printable. Then the `\if:w` test is unfinished after reading a the space from `\token_to_str:N _`, and the auxiliary `_cs_to_str:w` is expanded, feeding – as a second character for the test; the test is false, and TeX skips to `\fi:`, then performs `\token_to_str:N`, and stops the `\tex_romannumeral:D` with `\c_zero_int`. The last case is that the escape character is itself a space. In this case, the `\if:w` test is true, and the auxiliary `_cs_to_str:w` comes into play, inserting `-\int_value:w`, which expands `\c_zero_int` to the character 0. The initial `\tex_romannumeral:D` then sees 0, which is not a terminated number, followed by the escape character, a space, which is removed, terminating the expansion of `\tex_romannumeral:D`. In all three cases, `\cs_to_str:N` takes two expansion steps to be fully expanded.

```

2715 \cs_set:Npn \cs_to_str:N
2716   {

```

We implement the expansion scheme using `\tex_romannumeral:D` terminating it with `\c_zero_int` rather than using `\exp:w` and `\exp_end:` as we normally do. The reason

is that the code heavily depends on terminating the expansion with `\c_zero_int` so we make this dependency explicit.

```

2717 \tex_romannumeral:D
2718 \if:w \token_to_str:N \ \_cs_to_str:w \fi:
2719 \exp_after:wN \_cs_to_str:N \token_to_str:N
2720 }
2721 \cs_set:Npn \_cs_to_str:N #1 { \c_zero_int }
2722 \cs_set:Npn \_cs_to_str:w #1 \_cs_to_str:N
2723 { - \int_value:w \fi: \exp_after:wN \c_zero_int }

```

If speed is a concern we could use `\csstring` in LuaTeX. For the empty csname that primitive gives an empty result while the current `\cs_to_str:N` gives incorrect results in all engines (this is impossible to fix without huge performance hit).

(End definition for `\cs_to_str:N`, `_cs_to_str:N`, and `_cs_to_str:w`. This function is documented on page 16.)

`\cs_split_function:N` This function takes a function name and splits it into name with the escape char removed and argument specification. In addition to this, a third argument, a boolean *⟨true⟩* or *⟨false⟩* is returned with *⟨true⟩* for when there is a colon in the function and *⟨false⟩* if there is not.

We cannot use `:` directly as it has the wrong category code so an x-type expansion is used to force the conversion.

First ensure that we actually get a properly evaluated string by expanding `\cs_to_str:N` twice. If the function contained a colon, the auxiliary takes as `#1` the function name, delimited by the first colon, then the signature `#2`, delimited by `\q_mark`, then `\c_true_bool` as `#3`, and `#4` cleans up until `\q_stop`. Otherwise, the `#1` contains the function name and `\q_mark \c_true_bool`, `#2` is empty, `#3` is `\c_false_bool`, and `#4` cleans up. The second auxiliary trims the trailing `\q_mark` from the function name if present (that is, if the original function had no colon).

```

2724 \cs_set_protected:Npn \_cs_tmp:w #1
2725 {
2726   \cs_set:Npn \cs_split_function:N ##1
2727   {
2728     \exp_after:wN \exp_after:wN \exp_after:wN
2729     \_cs_split_function_auxi:w
2730     \cs_to_str:N ##1 \q_mark \c_true_bool
2731     #1 \q_mark \c_false_bool \q_stop
2732   }
2733   \cs_set:Npn \_cs_split_function_auxi:w
2734   ##1 #1 ##2 \q_mark ##3##4 \q_stop
2735   { \_cs_split_function_auxii:w ##1 \q_mark \q_stop {##2} ##3 }
2736   \cs_set:Npn \_cs_split_function_auxii:w ##1 \q_mark ##2 \q_stop
2737   { {##1} }
2738 }
2739 \exp_after:wN \_cs_tmp:w \token_to_str:N :

```

(End definition for `\cs_split_function:N`, `_cs_split_function_auxi:w`, and `_cs_split_function_auxii:w`. This function is documented on page 16.)

4.9 Exist or free

A control sequence is said to *exist* (to be used) if has an entry in the hash table and its meaning is different from the primitive `\relax` token. A control sequence is said to be *free* (to be defined) if it does not already exist.

`\cs_if_exist_p:N` Two versions for checking existence. For the `N` form we firstly check for `\scan_stop:` and
`\cs_if_exist_p:c` then if it is in the hash table. There is no problem when inputting something like `\else:`
`\cs_if_exist:NTF` or `\fi:` as `TEX` will only ever skip input in case the token tested against is `\scan_stop:`.
`\cs_if_exist:cTF`

```

2740 \prg_set_conditional:Npnn \cs_if_exist:N #1 { p , T , F , TF }
2741 {
2742   \if_meaning:w #1 \scan_stop:
2743   \prg_return_false:
2744   \else:
2745     \if_cs_exist:N #1
2746     \prg_return_true:
2747     \else:
2748       \prg_return_false:
2749     \fi:
2750   \fi:
2751 }
```

For the `c` form we firstly check if it is in the hash table and then for `\scan_stop:` so that we do not add it to the hash table unless it was already there. Here we have to be careful as the text to be skipped if the first test is false may contain tokens that disturb the scanner. Therefore, we ensure that the second test is performed after the first one has concluded completely.

```

2752 \prg_set_conditional:Npnn \cs_if_exist:c #1 { p , T , F , TF }
2753 {
2754   \if_cs_exist:w #1 \cs_end:
2755   \exp_after:wN \use_i:nn
2756   \else:
2757     \exp_after:wN \use_ii:nn
2758   \fi:
2759   {
2760     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
2761     \prg_return_false:
2762     \else:
2763       \prg_return_true:
2764     \fi:
2765   }
2766   \prg_return_false:
2767 }
```

(End definition for `\cs_if_exist:NTF`. This function is documented on page 20.)

`\cs_if_free_p:N` The logical reversal of the above.

```

2768 \prg_set_conditional:Npnn \cs_if_free:N #1 { p , T , F , TF }
2769 {
2770   \if_meaning:w #1 \scan_stop:
2771   \prg_return_true:
2772   \else:
2773     \if_cs_exist:N #1
2774     \prg_return_false:

```

```

2775     \else:
2776       \prg_return_true:
2777     \fi:
2778   \fi:
2779 }
2780 \prg_set_conditional:Npnn \cs_if_free:c #1 { p , T , F , TF }
2781 {
2782   \if_cs_exist:w #1 \cs_end:
2783     \exp_after:wN \use_i:nn
2784   \else:
2785     \exp_after:wN \use_ii:nn
2786   \fi:
2787   {
2788     \exp_after:wN \if_meaning:w \cs:w #1 \cs_end: \scan_stop:
2789     \prg_return_true:
2790   \else:
2791     \prg_return_false:
2792   \fi:
2793 }
2794 { \prg_return_true: }
2795 }

```

(End definition for `\cs_if_free:NTF`. This function is documented on page 20.)

`\cs_if_exist_use:N` The `\cs_if_exist_use:...` functions cannot be implemented as conditionals because the true branch must leave both the control sequence itself and the true code in the input stream. For the `c` variants, we are careful not to put the control sequence in the hash table if it does not exist. In LuaTeX we could use the `\lastnamedcs` primitive.

```

2796 \cs_set:Npn \cs_if_exist_use:NTF #1#2
2797   { \cs_if_exist:NTF #1 { #1 #2 } }
2798 \cs_set:Npn \cs_if_exist_use:NF #1
2799   { \cs_if_exist:NTF #1 { #1 } }
2800 \cs_set:Npn \cs_if_exist_use:NT #1 #2
2801   { \cs_if_exist:NTF #1 { #1 #2 } { } }
2802 \cs_set:Npn \cs_if_exist_use:N #1
2803   { \cs_if_exist:NTF #1 { #1 } { } }
2804 \cs_set:Npn \cs_if_exist_use:cTF #1#2
2805   { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } }
2806 \cs_set:Npn \cs_if_exist_use:cF #1
2807   { \cs_if_exist:cTF {#1} { \use:c {#1} } }
2808 \cs_set:Npn \cs_if_exist_use:cT #1#2
2809   { \cs_if_exist:cTF {#1} { \use:c {#1} #2 } { } }
2810 \cs_set:Npn \cs_if_exist_use:c #1
2811   { \cs_if_exist:cTF {#1} { \use:c {#1} } { } }

```

(End definition for `\cs_if_exist_use:NTF`. This function is documented on page 15.)

4.10 Preliminaries for new functions

We provide two kinds of functions that can be used to define control sequences. On the one hand we have functions that check if their argument doesn't already exist, they are called `\..._new`. The second type of defining functions doesn't check if the argument is already defined.

Before we can define them, we need some auxiliary macros that allow us to generate error messages. The next few definitions here are only temporary, they will be redefined later on.

<pre> __kernel_msg_error:nxxx __kernel_msg_error:nxx __kernel_msg_error:nn </pre>	<p>If an internal error occurs before L^AT_EX3 has loaded <code>l3msg</code> then the code should issue a usable if terse error message and halt. This can only happen if a coding error is made by the team, so this is a reasonable response. Setting the <code>\newlinechar</code> is needed, to turn <code>^^J</code> into a proper line break in plain T_EX.</p>
--	---

```

2812 \cs_set_protected:Npn \__kernel_msg_error:nxxx #1#2#3#4
2813 {
2814   \tex_newlinechar:D = '\^^J \scan_stop:
2815   \tex_errmessage:D
2816     {
2817       !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!~! ^^J
2818       Argh,~internal~LaTeX3~error! ^^J ^^J
2819       Module ~ #1 , ~ message~name~"#2": ^^J
2820       Arguments~'#3'~and~'#4' ^^J ^^J
2821       This~is~one~for~The~LaTeX3~Project::~bailing-out
2822     }
2823   \tex_end:D
2824 }
2825 \cs_set_protected:Npn \__kernel_msg_error:nxx #1#2#3
2826 { \_kernel_msg_error:nxxx {#1} {#2} {#3} { } }
2827 \cs_set_protected:Npn \__kernel_msg_error:nn #1#2
2828 { \_kernel_msg_error:nxxx {#1} {#2} { } { } }

```

(End definition for \ kernel msg error:nxxx, \ kernel msg error:nxx, and \ kernel msg error:nn.)

`\msg_line_context:` Another one from `l3msg` which will be altered later.

```
2829 \cs_set:Npn \msg_line_context:
2830 { on~line~ \tex the:D \tex_inputlineno:D }
```

(End definition for `\msg_line_context`:. This function is documented on page 139.)

```
\iow_log:x We define a routine to write only to the log file. And a similar one for writing to both
\iow_term:x the log file and the terminal. These will be redefined later by \l3io.
```

```

2831 \cs_set_protected:Npn \iow_log:x
2832   { \tex_immediate:D \tex_write:D -1 }
2833 \cs_set_protected:Npn \iow_term:x
2834   { \tex_immediate:D \tex_write:D 16 }

```

(End definition for \iow_log:n. This function is documented on page 148.)

`__kernel_chk_if_free_cs:N` This command is called by `\cs_new_nopar:Npn` and `\cs_new_eq:NN` *etc.* to make sure
`__kernel_chk_if_free_cs:c` that the argument sequence is not already in use. If it is, an error is signalled. It checks
if $\langle csname \rangle$ is undefined or `\scan_stop:.` Otherwise an error message is issued. We have
to make sure we don't put the argument into the conditional processing since it may be
an `\if...` type function!

```

2835 \__kernel_patch:nnNNpn { }
2836 {
2837     \__kernel_debug_log:x
2838     { Defining-\token_to_str:N #1~ \msg_line_context: }
2839 }
2840 \cs set protected:Npn \__kernel_chk_if_free_cs:N #1

```

```

2841 {
2842   \cs_if_free:NF #1
2843   {
2844     \__kernel_msg_error:nxxx { kernel } { command-already-defined }
2845     { \token_to_str:N #1 } { \token_to_meaning:N #1 }
2846   }
2847 }
2848 \cs_set_protected:Npn \__kernel_chk_if_free_cs:c
2849 { \exp_args:Nc \__kernel_chk_if_free_cs:N }

```

(End definition for __kernel_chk_if_free_cs:N.)

4.11 Defining new functions

```

2850 <@@=cs>

```

\cs_new_nopar:Npn Function which check that the control sequence is free before defining it.

```

\cs_new_nopar:Npx
\cs_new:Npn
\cs_new:Npx
\cs_new_protected_nopar:Npn
\cs_new_protected_nopar:Npx
\cs_new_protected:Npn
\cs_new_protected:Npx
\__cs_tmp:w
2851 \cs_set:Npn \__cs_tmp:w #1#2
2852 {
2853   \cs_set_protected:Npn #1 ##1
2854   {
2855     \__kernel_chk_if_free_cs:N ##1
2856     #2 ##1
2857   }
2858 }
2859 \__cs_tmp:w \cs_new_nopar:Npn \cs_gset_nopar:Npn
2860 \__cs_tmp:w \cs_new_nopar:Npx \cs_gset_nopar:Npx
2861 \__cs_tmp:w \cs_new:Npn \cs_gset:Npn
2862 \__cs_tmp:w \cs_new:Npx \cs_gset:Npx
2863 \__cs_tmp:w \cs_new_protected_nopar:Npn \cs_gset_protected_nopar:Npn
2864 \__cs_tmp:w \cs_new_protected_nopar:Npx \cs_gset_protected_nopar:Npx
2865 \__cs_tmp:w \cs_new_protected:Npn \cs_gset_protected:Npn
2866 \__cs_tmp:w \cs_new_protected:Npx \cs_gset_protected:Npx

```

(End definition for \cs_new_nopar:Npn and others. These functions are documented on page 10.)

\cs_set_nopar:cpn Like \cs_set_nopar:Npn and \cs_new_nopar:Npn, except that the first argument consists of the sequence of characters that should be used to form the name of the desired control sequence (the c stands for csname argument, see the expansion module). Global versions are also provided.

\cs_new_nopar:cpn \cs_set_nopar:cpn<string><rep-text> turns <string> into a csname and then assigns <rep-text> to it by using \cs_set_nopar:Npn. This means that there might be a parameter string between the two arguments.

```

2867 \cs_set:Npn \__cs_tmp:w #1#2
2868 { \cs_new_protected_nopar:Npn #1 { \exp_args:Nc #2 } }
2869 \__cs_tmp:w \cs_set_nopar:cpn \cs_set_nopar:Npn
2870 \__cs_tmp:w \cs_set_nopar:cpx \cs_set_nopar:Npx
2871 \__cs_tmp:w \cs_gset_nopar:cpn \cs_gset_nopar:Npn
2872 \__cs_tmp:w \cs_gset_nopar:cpx \cs_gset_nopar:Npx
2873 \__cs_tmp:w \cs_new_nopar:cpn \cs_new_nopar:Npn
2874 \__cs_tmp:w \cs_new_nopar:cpx \cs_new_nopar:Npx

```

(End definition for \cs_set_nopar:Npn. This function is documented on page 10.)

<code>\cs_set:cpn</code>	2875	<code>__cs_tmp:w \cs_set:cpn \cs_set:Npn</code>	Variants of the <code>\cs_set:Npn</code> versions which make a csname out of the first arguments.
<code>\cs_set:cpx</code>			We may also do this globally.
<code>\cs_gset:cpn</code>	2876	<code>__cs_tmp:w \cs_set:cpx \cs_set:Npx</code>	
<code>\cs_gset:cpx</code>	2877	<code>__cs_tmp:w \cs_gset:cpn \cs_gset:Npn</code>	
<code>\cs_new:cpn</code>	2878	<code>__cs_tmp:w \cs_gset:cpx \cs_gset:Npx</code>	
<code>\cs_new:cpx</code>	2879	<code>__cs_tmp:w \cs_new:cpn \cs_new:Npn</code>	
	2880	<code>__cs_tmp:w \cs_new:cpx \cs_new:Npx</code>	

(End definition for `\cs_set:Npn`. This function is documented on page 10.)

<code>\cs_set_protected_nopar:cpn</code>	2881	<code>__cs_tmp:w \cs_set_protected_nopar:cpn \cs_set_protected_nopar:Npn</code>	Variants of the <code>\cs_set_protected_nopar:Npn</code> versions which make a csname out of the first arguments. We may also do this globally.
<code>\cs_set_protected_nopar:cpx</code>	2882	<code>__cs_tmp:w \cs_set_protected_nopar:cpx \cs_set_protected_nopar:Npx</code>	
<code>\cs_gset_protected_nopar:cpn</code>	2883	<code>__cs_tmp:w \cs_gset_protected_nopar:cpn \cs_gset_protected_nopar:Npn</code>	
<code>\cs_gset_protected_nopar:cpx</code>	2884	<code>__cs_tmp:w \cs_gset_protected_nopar:cpx \cs_gset_protected_nopar:Npx</code>	
<code>\cs_new_protected_nopar:cpn</code>	2885	<code>__cs_tmp:w \cs_new_protected_nopar:cpn \cs_new_protected_nopar:Npn</code>	
<code>\cs_new_protected_nopar:cpx</code>	2886	<code>__cs_tmp:w \cs_new_protected_nopar:cpx \cs_new_protected_nopar:Npx</code>	

(End definition for `\cs_set_protected_nopar:Npn`. This function is documented on page 11.)

<code>\cs_set_protected:cpn</code>	2887	<code>__cs_tmp:w \cs_set_protected:cpn \cs_set_protected:Npn</code>	Variants of the <code>\cs_set_protected:Npn</code> versions which make a csname out of the first arguments. We may also do this globally.
<code>\cs_set_protected:cpx</code>	2888	<code>__cs_tmp:w \cs_set_protected:cpx \cs_set_protected:Npx</code>	
<code>\cs_gset_protected:cpn</code>	2889	<code>__cs_tmp:w \cs_gset_protected:cpn \cs_gset_protected:Npn</code>	
<code>\cs_gset_protected:cpx</code>	2890	<code>__cs_tmp:w \cs_gset_protected:cpx \cs_gset_protected:Npx</code>	
<code>\cs_new_protected:cpn</code>	2891	<code>__cs_tmp:w \cs_new_protected:cpn \cs_new_protected:Npn</code>	
<code>\cs_new_protected:cpx</code>	2892	<code>__cs_tmp:w \cs_new_protected:cpx \cs_new_protected:Npx</code>	

(End definition for `\cs_set_protected:Npn`. This function is documented on page 10.)

4.12 Copying definitions

<code>\cs_set_eq:NN</code>	These macros allow us to copy the definition of a control sequence to another control sequence.
<code>\cs_set_eq:cN</code>	The = sign allows us to define funny char tokens like = itself or <code>_</code> with this function.
<code>\cs_set_eq:Nc</code>	For the definition of <code>\c_space_char{~}</code> to work we need the <code>~</code> after the =.
<code>\cs_set_eq:cc</code>	<code>\cs_set_eq:NN</code> is long to avoid problems with a literal argument of <code>\par</code> . While
<code>\cs_gset_eq:NN</code>	<code>\cs_new_eq:NN</code> will probably never be correct with a first argument of <code>\par</code> , define it
<code>\cs_gset_eq:cN</code>	long in order to throw an “already defined” error rather than “runaway argument”.
<code>\cs_gset_eq:Nc</code>	
<code>\cs_gset_eq:cc</code>	2893 <code>\cs_new_protected:Npn \cs_set_eq:NN #1 { \tex_let:D #1 =~ }</code>
<code>\cs_new_eq:NN</code>	2894 <code>\cs_new_protected:Npn \cs_set_eq:cN { \exp_args:Nc \cs_set_eq:NN }</code>
<code>\cs_new_eq:cN</code>	2895 <code>\cs_new_protected:Npn \cs_set_eq:Nc { \exp_args:NNc \cs_set_eq:NN }</code>
<code>\cs_new_eq:Nc</code>	2896 <code>\cs_new_protected:Npn \cs_set_eq:cc { \exp_args:Ncc \cs_set_eq:NN }</code>
<code>\cs_new_eq:cc</code>	2897 <code>\cs_new_protected:Npn \cs_gset_eq:NN { \tex_global:D \cs_set_eq:NN }</code>
	2898 <code>\cs_new_protected:Npn \cs_gset_eq:Nc { \exp_args:NNc \cs_gset_eq:NN }</code>
	2899 <code>\cs_new_protected:Npn \cs_gset_eq:cN { \exp_args:Nc \cs_gset_eq:NN }</code>
	2900 <code>\cs_new_protected:Npn \cs_gset_eq:cc { \exp_args:Ncc \cs_gset_eq:NN }</code>
	2901 <code>\cs_new_protected:Npn \cs_new_eq:NN #1</code>
	2902 <code>{</code>
	2903 <code>__kernel_chk_if_free_cs:N #1</code>

```

2904 \tex_global:D \cs_set_eq:NN #1
2905 }
2906 \cs_new_protected:Npn \cs_new_eq:cN { \exp_args:Nc \cs_new_eq:NN }
2907 \cs_new_protected:Npn \cs_new_eq:Nc { \exp_args:NNc \cs_new_eq:NN }
2908 \cs_new_protected:Npn \cs_new_eq:cc { \exp_args:Ncc \cs_new_eq:NN }

```

(End definition for `\cs_set_eq:NN`, `\cs_gset_eq:NN`, and `\cs_new_eq:NN`. These functions are documented on page 14.)

4.13 Undefined functions

`\cs_undefine:N` The following function is used to free the main memory from the definition of some function that isn't in use any longer. The `c` variant is careful not to add the control sequence to the hash table if it isn't there yet, and it also avoids nesting TeX conditionals in case #1 is unbalanced in this matter.

`\cs_undefine:c`

```

2909 \cs_new_protected:Npn \cs_undefine:N #1
2910 { \cs_gset_eq:NN #1 \tex_undefined:D }
2911 \cs_new_protected:Npn \cs_undefine:c #1
2912 {
2913   \if_cs_exist:w #1 \cs_end:
2914     \exp_after:wN \use:n
2915   \else:
2916     \exp_after:wN \use_none:n
2917   \fi:
2918   { \cs_gset_eq:cN {#1} \tex_undefined:D }
2919 }

```

(End definition for `\cs_undefine:N`. This function is documented on page 14.)

4.14 Generating parameter text from argument count

```

2920 <@@=cs>

```

`_kernel_cs_parm_from_arg_count:nnF`
`_cs_parm_from_arg_count_test:nnF`

L^AT_EX3 provides shorthands to define control sequences and conditionals with a simple parameter text, derived directly from the signature, or more generally from knowing the number of arguments, between 0 and 9. This function expands to its first argument, untouched, followed by a brace group containing the parameter text `{#1...#n}`, where n is the result of evaluating the second argument (as described in `\int_eval:n`). If the second argument gives a result outside the range $[0, 9]$, the third argument is returned instead, normally an error message. Some of the functions use here are not defined yet, but will be defined before this function is called.

```

2921 \cs_set_protected:Npn \_kernel_cs_parm_from_arg_count:nnF #1#2
2922 {
2923   \exp_args:Nx \_cs_parm_from_arg_count_test:nnF
2924   {
2925     \exp_after:wN \exp_not:n
2926     \if_case:w \int_eval:n {#2}
2927       { }
2928     \or: { ##1 }
2929     \or: { ##1##2 }
2930     \or: { ##1##2##3 }
2931     \or: { ##1##2##3##4 }
2932     \or: { ##1##2##3##4##5 }
2933     \or: { ##1##2##3##4##5##6 }

```

```

2934         \or: { ##1##2##3##4##5##6##7 }
2935         \or: { ##1##2##3##4##5##6##7##8 }
2936         \or: { ##1##2##3##4##5##6##7##8##9 }
2937         \else: { \c_false_bool }
2938         \fi:
2939     }
2940     {#1}
2941 }
2942 \cs_set_protected:Npn \__cs_parm_from_arg_count_test:nnF #1#2
2943 {
2944     \if_meaning:w \c_false_bool #1
2945     \exp_after:wN \use_ii:nn
2946     \else:
2947     \exp_after:wN \use_i:nn
2948     \fi:
2949     { #2 {#1} }
2950 }

```

(End definition for `__kernel_cs_parm_from_arg_count:nnF` and `__cs_parm_from_arg_count_test:nnF`.)

4.15 Defining functions from a given number of arguments

```

2951 <@@=cs>

```

`__cs_count_signature:N` Counting the number of tokens in the signature, *i.e.*, the number of arguments the function should take. Since this is not used in any time-critical function, we simply use `\tl_count:n` if there is a signature, otherwise `-1` arguments to signal an error. We need a variant form right away.

```

2952 \cs_new:Npn \__cs_count_signature:N #1
2953 { \exp_args:Nf \__cs_count_signature:n { \cs_split_function:N #1 } }
2954 \cs_new:Npn \__cs_count_signature:n #1
2955 { \int_eval:n { \__cs_count_signature:nnN #1 } }
2956 \cs_new:Npn \__cs_count_signature:nnN #1#2#3
2957 {
2958     \if_meaning:w \c_true_bool #3
2959     \tl_count:n {#2}
2960     \else:
2961     -1
2962     \fi:
2963 }
2964 \cs_new:Npn \__cs_count_signature:c
2965 { \exp_args:Nc \__cs_count_signature:N }

```

(End definition for `__cs_count_signature:N`, `__cs_count_signature:n`, and `__cs_count_signature:nnN`.)

```

\cs_generate_from_arg_count:NNnn
\cs_generate_from_arg_count:cNnn
\cs_generate_from_arg_count:Ncnn

```

We provide a constructor function for defining functions with a given number of arguments. For this we need to choose the correct parameter text and then use that when defining. Since \TeX supports from zero to nine arguments, we use a simple switch to choose the correct parameter text, ensuring the result is returned after finishing the conditional. If it is not between zero and nine, we throw an error.

1: function to define, 2: with what to define it, 3: the number of args it requires and 4: the replacement text

```

2966 \cs_new_protected:Npn \cs_generate_from_arg_count:NNnn #1#2#3#4
2967 {

```

```

2968     \__kernel_cs_parm_from_arg_count:nnF { \use:nnn #2 #1 } {#3}
2969     {
2970         \__kernel_msg_error:nnxx { kernel } { bad-number-of-arguments }
2971         { \token_to_str:N #1 } { \int_eval:n {#3} }
2972         \use_none:n
2973     }
2974     {#4}
2975 }

```

A variant form we need right away, plus one which is used elsewhere but which is most logically created here.

```

2976 \cs_new_protected:Npn \cs_generate_from_arg_count:cNnn
2977 { \exp_args:Nc \cs_generate_from_arg_count:NNnn }
2978 \cs_new_protected:Npn \cs_generate_from_arg_count:Ncnn
2979 { \exp_args:NNc \cs_generate_from_arg_count:NNnn }

```

(End definition for `\cs_generate_from_arg_count:NNnn`. This function is documented on page 13.)

4.16 Using the signature to define functions

```

2980 <@@=cs>

```

We can now combine some of the tools we have to provide a simple interface for defining functions, where the number of arguments is read from the signature. For instance, `\cs_set:Nn \foo_bar:nn {#1,#2}`.

We want to define `\cs_set:Nn` as

```

\cs_set:Nn
\cs_set:Nx
\cs_set_nopar:Nn
\cs_set_nopar:Nx
\cs_set_protected:Nn
\cs_set_protected:Nx
\cs_set_protected_nopar:Nn
\cs_set_protected_nopar:Nx
\cs_set_protected:Npn \cs_set:Nn #1#2
{
  \cs_generate_from_arg_count:NNnn #1 \cs_set:Npn
  { \@@_count_signature:N #1 } {#2}
}

```

In short, to define `\cs_set:Nn` we need just use `\cs_set:Npn`, everything else is the same for each variant. Therefore, we can make it simpler by temporarily defining a function to do this for us.

```

2981 \cs_set:Npn \__cs_tmp:w #1#2#3
2982 {
2983   \cs_new_protected:cpx { cs_ #1 : #2 }
2984   {
2985     \exp_not:N \__cs_generate_from_signature:NNn
2986     \exp_after:wN \exp_not:N \cs:w cs_ #1 : #3 \cs_end:
2987   }
2988 }
2989 \cs_new_protected:Npn \__cs_generate_from_signature:NNn #1#2
2990 {
2991   \use:x
2992   {
2993     \__cs_generate_from_signature:nnNNNn
2994     \cs_split_function:N #2
2995   }
2996   #1 #2
2997 }
2998 \cs_new_protected:Npn \__cs_generate_from_signature:nnNNNn #1#2#3#4#5#6

```

```

2999 {
3000   \bool_if:NTF #3
3001   {
3002     \str_if_eq:eeF { }
3003     { \tl_map_function:nN {#2} \__cs_generate_from_signature:n }
3004     {
3005       \__kernel_msg_error:nxx { kernel } { non-base-function }
3006       { \token_to_str:N #5 }
3007     }
3008     \cs_generate_from_arg_count:NNnn
3009     #5 #4 { \tl_count:n {#2} } {#6}
3010   }
3011   {
3012     \__kernel_msg_error:nxx { kernel } { missing-colon }
3013     { \token_to_str:N #5 }
3014   }
3015 }
3016 \cs_new:Npn \__cs_generate_from_signature:n #1
3017 {
3018   \if:w n #1 \else: \if:w N #1 \else:
3019   \if:w T #1 \else: \if:w F #1 \else: #1 \fi: \fi: \fi: \fi:
3020 }

```

Then we define the 24 variants beginning with N.

```

3021 \__cs_tmp:w { set } { Nn } { Npn }
3022 \__cs_tmp:w { set } { Nx } { Npx }
3023 \__cs_tmp:w { set_nopar } { Nn } { Npn }
3024 \__cs_tmp:w { set_nopar } { Nx } { Npx }
3025 \__cs_tmp:w { set_protected } { Nn } { Npn }
3026 \__cs_tmp:w { set_protected } { Nx } { Npx }
3027 \__cs_tmp:w { set_protected_nopar } { Nn } { Npn }
3028 \__cs_tmp:w { set_protected_nopar } { Nx } { Npx }
3029 \__cs_tmp:w { gset } { Nn } { Npn }
3030 \__cs_tmp:w { gset } { Nx } { Npx }
3031 \__cs_tmp:w { gset_nopar } { Nn } { Npn }
3032 \__cs_tmp:w { gset_nopar } { Nx } { Npx }
3033 \__cs_tmp:w { gset_protected } { Nn } { Npn }
3034 \__cs_tmp:w { gset_protected } { Nx } { Npx }
3035 \__cs_tmp:w { gset_protected_nopar } { Nn } { Npn }
3036 \__cs_tmp:w { gset_protected_nopar } { Nx } { Npx }
3037 \__cs_tmp:w { new } { Nn } { Npn }
3038 \__cs_tmp:w { new } { Nx } { Npx }
3039 \__cs_tmp:w { new_nopar } { Nn } { Npn }
3040 \__cs_tmp:w { new_nopar } { Nx } { Npx }
3041 \__cs_tmp:w { new_protected } { Nn } { Npn }
3042 \__cs_tmp:w { new_protected } { Nx } { Npx }
3043 \__cs_tmp:w { new_protected_nopar } { Nn } { Npn }
3044 \__cs_tmp:w { new_protected_nopar } { Nx } { Npx }

```

(End definition for \cs_set:Nn and others. These functions are documented on page 12.)

\cs_set:cn The 24 c variants simply use \exp_args:Nc.

\cs_set:cx 3045 \cs_set:Npn __cs_tmp:w #1#2

\cs_set_nopar:cn 3046 {

\cs_set_nopar:cx 3047 \cs_new_protected:cpx { cs_ #1 : c #2 }

\cs_set_protected:cn

\cs_set_protected:cx

\cs_set_protected_nopar:cn

\cs_set_protected_nopar:cx

\cs_gset:cn

\cs_gset:cx

\cs_gset_nopar:cn

\cs_gset_nopar:cx

\cs_gset_protected:cn

\cs_gset_protected:cx

```

3048     {
3049         \exp_not:N \exp_args:Nc
3050         \exp_after:wN \exp_not:N \cs:w cs_ #1 : N #2 \cs_end:
3051     }
3052 }
3053 \__cs_tmp:w { set } { n }
3054 \__cs_tmp:w { set } { x }
3055 \__cs_tmp:w { set_nopar } { n }
3056 \__cs_tmp:w { set_nopar } { x }
3057 \__cs_tmp:w { set_protected } { n }
3058 \__cs_tmp:w { set_protected } { x }
3059 \__cs_tmp:w { set_protected_nopar } { n }
3060 \__cs_tmp:w { set_protected_nopar } { x }
3061 \__cs_tmp:w { gset } { n }
3062 \__cs_tmp:w { gset } { x }
3063 \__cs_tmp:w { gset_nopar } { n }
3064 \__cs_tmp:w { gset_nopar } { x }
3065 \__cs_tmp:w { gset_protected } { n }
3066 \__cs_tmp:w { gset_protected } { x }
3067 \__cs_tmp:w { gset_protected_nopar } { n }
3068 \__cs_tmp:w { gset_protected_nopar } { x }
3069 \__cs_tmp:w { new } { n }
3070 \__cs_tmp:w { new } { x }
3071 \__cs_tmp:w { new_nopar } { n }
3072 \__cs_tmp:w { new_nopar } { x }
3073 \__cs_tmp:w { new_protected } { n }
3074 \__cs_tmp:w { new_protected } { x }
3075 \__cs_tmp:w { new_protected_nopar } { n }
3076 \__cs_tmp:w { new_protected_nopar } { x }

```

(End definition for `\cs_set:Nn`. This function is documented on page 12.)

4.17 Checking control sequence equality

`\cs_if_eq_p:NN` Check if two control sequences are identical.

```

\cs_if_eq_p:cN 3077 \prg_new_conditional:Npnn \cs_if_eq:NN #1#2 { p , T , F , TF }
\cs_if_eq_p:Nc 3078 {
\cs_if_eq_p:cc 3079     \if_meaning:w #1#2
\cs_if_eq:NNTF 3080     \prg_return_true: \else: \prg_return_false: \fi:
\cs_if_eq:cNTF 3081 }
\cs_if_eq:NcTF 3082 \cs_new:Npn \cs_if_eq_p:cN { \exp_args:Nc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 3083 \cs_new:Npn \cs_if_eq:cNTF { \exp_args:Nc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 3084 \cs_new:Npn \cs_if_eq:cNT { \exp_args:Nc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 3085 \cs_new:Npn \cs_if_eq:cNF { \exp_args:Nc \cs_if_eq:NNF }
\cs_if_eq:ccTF 3086 \cs_new:Npn \cs_if_eq_p:Nc { \exp_args:NNc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 3087 \cs_new:Npn \cs_if_eq:NcTF { \exp_args:NNc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 3088 \cs_new:Npn \cs_if_eq:NcT { \exp_args:NNc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 3089 \cs_new:Npn \cs_if_eq:NcF { \exp_args:NNc \cs_if_eq:NNF }
\cs_if_eq:ccTF 3090 \cs_new:Npn \cs_if_eq_p:cc { \exp_args:Ncc \cs_if_eq_p:NN }
\cs_if_eq:ccTF 3091 \cs_new:Npn \cs_if_eq:ccTF { \exp_args:Ncc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 3092 \cs_new:Npn \cs_if_eq:ccT { \exp_args:Ncc \cs_if_eq:NNTF }
\cs_if_eq:ccTF 3093 \cs_new:Npn \cs_if_eq:ccF { \exp_args:Ncc \cs_if_eq:NNF }

```

(End definition for `\cs_if_eq:NNTF`. This function is documented on page 20.)

4.18 Diagnostic functions

3094 `<@@=kernel>`

`__kernel_chk_defined:NT` Error if the variable #1 is not defined.

```
3095 \cs_new_protected:Npn \__kernel_chk_defined:NT #1#2
3096 {
3097   \cs_if_exist:NTF #1
3098   {#2}
3099   {
3100     \__kernel_msg_error:nnx { kernel } { variable-not-defined }
3101     { \token_to_str:N #1 }
3102   }
3103 }
```

(End definition for `__kernel_chk_defined:NT`.)

`__kernel_register_show:N` Simply using the `\showthe` primitive does not allow for line-wrapping, so instead use
`__kernel_register_show:c` `\tl_show:n` and `\tl_log:n` (defined in `l3tl` and that performs line-wrapping). This dis-
`__kernel_register_log:N` plays `>~<variable>=<value>`. We expand the value before-hand as otherwise some integers
`__kernel_register_log:c` (such as `\currentgrouplevel` or `\currentgrouptype`) altered by the line-wrapping code
`__kernel_register_show_aux:NN` would show wrong values.
`__kernel_register_show_aux:nnn`

```
3104 \cs_new_protected:Npn \__kernel_register_show:N
3105 { \__kernel_register_show_aux:NN \tl_show:n }
3106 \cs_new_protected:Npn \__kernel_register_show:c
3107 { \exp_args:Nc \__kernel_register_show:N }
3108 \cs_new_protected:Npn \__kernel_register_log:N
3109 { \__kernel_register_show_aux:NN \tl_log:n }
3110 \cs_new_protected:Npn \__kernel_register_log:c
3111 { \exp_args:Nc \__kernel_register_log:N }
3112 \cs_new_protected:Npn \__kernel_register_show_aux:NN #1#2
3113 {
3114   \__kernel_chk_defined:NT #2
3115   {
3116     \exp_args:No \__kernel_register_show_aux:nnn
3117     { \tex_the:D #2 } #2 #1
3118   }
3119 }
3120 \cs_new_protected:Npn \__kernel_register_show_aux:nnn #1#2#3
3121 { \exp_args:No #3 { \token_to_str:N #2 = #1 } }
```

(End definition for `__kernel_register_show:N` and others.)

`\cs_show:N` Some control sequences have a very long name or meaning. Thus, simply using TeX's
`\cs_show:c` primitive `\show` could lead to overlong lines. The output of this primitive is mimicked
`\cs_log:N` to some extent, then the re-built string is given to `\tl_show:n` or `\tl_log:n` for line-
`\cs_log:c` wrapping. We must expand the meaning before passing it to the wrapping code as
`__kernel_show:NN` otherwise we would wrongly see the definitions that are in place there. To get correct
escape characters, set the `\escapechar` in a group; this also localizes the assignment
performed by x-expansion. The `\cs_show:c` and `\cs_log:c` commands convert their
argument to a control sequence within a group to avoid showing `\relax` for undefined
control sequences.

```
3122 \cs_new_protected:Npn \cs_show:N { \__kernel_show:NN \tl_show:n }
3123 \cs_new_protected:Npn \cs_show:c
```

```

3124 { \group_begin: \exp_args:NNc \group_end: \cs_show:N }
3125 \cs_new_protected:Npn \cs_log:N { \__kernel_show:NN \tl_log:n }
3126 \cs_new_protected:Npn \cs_log:c
3127 { \group_begin: \exp_args:NNc \group_end: \cs_log:N }
3128 \cs_new_protected:Npn \__kernel_show:NN #1#2
3129 {
3130   \group_begin:
3131     \int_set:Nn \tex_escapechar:D { '\ }
3132     \exp_args:NNx
3133     \group_end:
3134     #1 { \token_to_str:N #2 = \cs_meaning:N #2 }
3135 }

```

(End definition for `\cs_show:N`, `\cs_log:N`, and `__kernel_show:NN`. These functions are documented on page 15.)

4.19 Doing nothing functions

`\prg_do_nothing:` This does not fit anywhere else!

```

3136 \cs_new:Npn \prg_do_nothing: { }

```

(End definition for `\prg_do_nothing:`. This function is documented on page 8.)

4.20 Breaking out of mapping functions

```

3137 <@@=prg>

```

`\prg_break_point:Nn` In inline mappings, the nesting level must be reset at the end of the mapping, even when the user decides to break out. This is done by putting the code that must be performed as an argument of `__prg_break_point:Nn`. The breaking functions are then defined to jump to that point and perform the argument of `__prg_break_point:Nn`, before the user's code (if any). There is a check that we close the correct loop, otherwise we continue breaking.

```

3138 \cs_new_eq:NN \prg_break_point:Nn \use_ii:nn
3139 \cs_new:Npn \prg_map_break:Nn #1#2#3 \prg_break_point:Nn #4#5
3140 {
3141   #5
3142   \if_meaning:w #1 #4
3143     \exp_after:wN \use_iii:nnn
3144   \fi:
3145   \prg_map_break:Nn #1 {#2}
3146 }

```

(End definition for `\prg_break_point:Nn` and `\prg_map_break:Nn`. These functions are documented on page 103.)

`\prg_break_point:` Very simple analogues of `\prg_break_point:Nn` and `\prg_map_break:Nn`, for use in fast short-term recursions which are not mappings, do not need to support nesting, and in which nothing has to be done at the end of the loop.

```

3147 \cs_new_eq:NN \prg_break_point: \prg_do_nothing:
3148 \cs_new:Npn \prg_break: #1 \prg_break_point: { }
3149 \cs_new:Npn \prg_break:n #1#2 \prg_break_point: {#1}

```

(End definition for `\prg_break_point:`, `\prg_break:`, and `\prg_break:n`. These functions are documented on page 103.)

```

3150 </initex | package>

```

5 l3expan implementation

3151 `*initex | package)`

3152 `\@@=exp)`

`\l__exp_internal_tl` The `\exp_` module has its private variable to temporarily store the result of `x`-type argument expansion. This is done to avoid interference with other functions using temporary variables.

(End definition for `\l__exp_internal_tl`.)

`\exp_after:wN` These are defined in `l3basics`, as they are needed “early”. This is just a reminder of that fact!

`\exp_not:N`

`\exp_not:n`

(End definition for `\exp_after:wN`, `\exp_not:N`, and `\exp_not:n`. These functions are documented on page 30.)

5.1 General expansion

In this section a general mechanism for defining functions that handle arguments is defined. These general expansion functions are expandable unless `x` is used. (Any version of `x` is going to have to use one of the L^AT_EX3 names for `\cs_set:Npx` at some point, and so is never going to be expandable.)

The definition of expansion functions with this technique happens in section 5.3. In section 5.2 some common cases are coded by a more direct method for efficiency, typically using calls to `\exp_after:wN`.

`\l__exp_internal_tl` This scratch token list variable is defined in `l3basics`.

(End definition for `\l__exp_internal_tl`.)

This code uses internal functions with names that start with `\::` to perform the expansions. All macros are `long` since the tokens undergoing expansion may be arbitrary user input.

An argument manipulator `\::⟨Z⟩` always has signature `#1\:::#2#3` where `#1` holds the remaining argument manipulations to be performed, `\:::` serves as an end marker for the list of manipulations, `#2` is the carried over result of the previous expansion steps and `#3` is the argument about to be processed. One exception to this rule is `\::p`, which has to grab an argument delimited by a left brace.

`__exp_arg_next:nnn` `#1` is the result of an expansion step, `#2` is the remaining argument manipulations and `#3` is the current result of the expansion chain. This auxiliary function moves `#1` back after `#3` in the input stream and checks if any expansion is left to be done by calling `#2`. In by far the most cases we need to add a set of braces to the result of an argument manipulation so it is more effective to do it directly here. Actually, so far only the `c` of the final argument manipulation variants does not require a set of braces.

3153 `\cs_new:Npn __exp_arg_next:nnn #1#2#3 { #2 \::: { #3 {#1} } }`

3154 `\cs_new:Npn __exp_arg_next:Nnn #1#2#3 { #2 \::: { #3 #1 } }`

(End definition for `__exp_arg_next:nnn` and `__exp_arg_next:Nnn`.)

`\:::` The end marker is just another name for the identity function.

3155 `\cs_new:Npn \::: #1 {#1}`

(End definition for `\:::`. This function is documented on page 34.)

\::n This function is used to skip an argument that doesn't need to be expanded.

```
3156 \cs_new:Npn \::n #1 \::: #2#3 { #1 \::: { #2 {#3} } }
```

(End definition for \::n. This function is documented on page 34.)

\::N This function is used to skip an argument that consists of a single token and doesn't need to be expanded.

```
3157 \cs_new:Npn \::N #1 \::: #2#3 { #1 \::: {#2#3} }
```

(End definition for \::N. This function is documented on page 34.)

\::p This function is used to skip an argument that is delimited by a left brace and doesn't need to be expanded. It is not wrapped in braces in the result.

```
3158 \cs_new:Npn \::p #1 \::: #2#3# { #1 \::: {#2#3} }
```

(End definition for \::p. This function is documented on page 34.)

\::c This function is used to skip an argument that is turned into a control sequence without expansion.

```
3159 \cs_new:Npn \::c #1 \::: #2#3
3160 { \exp_after:wN \__exp_arg_next:Nnn \cs:w #3 \cs_end: {#1} {#2} }
```

(End definition for \::c. This function is documented on page 34.)

\::o This function is used to expand an argument once.

```
3161 \cs_new:Npn \::o #1 \::: #2#3
3162 { \exp_after:wN \__exp_arg_next:nnn \exp_after:wN {#3} {#1} {#2} }
```

(End definition for \::o. This function is documented on page 34.)

\::e With the `\expanded` primitive available, just expand. Otherwise defer to `\exp_args:Ne` implemented later.

```
3163 \cs_if_exist:NTF \tex_expanded:D
3164 {
3165   \cs_new:Npn \::e #1 \::: #2#3
3166   { \tex_expanded:D { \exp_not:n { #1 \::: } { \exp_not:n {#2} {#3} } } }
3167 }
3168 {
3169   \cs_new:Npn \::e #1 \::: #2#3
3170   { \exp_args:Ne \__exp_arg_next:nnn {#3} {#1} {#2} }
3171 }
```

(End definition for \::e. This function is documented on page 34.)

\::f This function is used to expand a token list until the first unexpandable token is found. This is achieved through `\exp:w \exp_end_continue_f:w` that expands everything in its way following it. This scanning procedure is terminated once the expansion hits something non-expandable (if that is a space it is removed). We introduce `\exp_stop_f:` to mark such an end-of-expansion marker. For example, f-expanding `\cs_set_eq:Nc \aaa { b \l_tmpa_tl b }` where `\l_tmpa_tl` contains the characters `lur` gives `\tex_let:D \aaa = \blurb` which then turns out to start with the non-expandable token `\tex_let:D`. Since the expansion of `\exp:w \exp_end_continue_f:w` is empty, we wind up with a fully expanded list, only `TEX` has not tried to execute any of

the non-expandable tokens. This is what differentiates this function from the `x` argument type.

```

3172 \cs_new:Npn \::f #1 \::: #2#3
3173 {
3174   \exp_after:wN \__exp_arg_next:nnn
3175   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
3176   {#1} {#2}
3177 }
3178 \use:nn { \cs_new_eq:NN \exp_stop_f: } { ~ }
```

(End definition for `\::f` and `\exp_stop_f:`. These functions are documented on page 34.)

\::x This function is used to expand an argument fully. We build in the expansion of `__exp_arg_next:nnn`.

```

3179 \cs_new_protected:Npn \::x #1 \::: #2#3
3180 {
3181   \cs_set_nopar:Npx \l__exp_internal_tl
3182   { \exp_not:n { #1 \::: } { \exp_not:n {#2} {#3} } }
3183   \l__exp_internal_tl
3184 }
```

(End definition for `\::x`. This function is documented on page 34.)

\::v These functions return the value of a register, i.e., one of `tl`, `clist`, `int`, `skip`, `dim`, **\::V** `muskip`, or built-in TeX register. The `V` version expects a single token whereas `v` like `c` creates a cname from its argument given in braces and then evaluates it as if it was a `V`. The `\exp:w` sets off an expansion similar to an `f`-type expansion, which we terminate using `\exp_end:`. The argument is returned in braces.

```

3185 \cs_new:Npn \::V #1 \::: #2#3
3186 {
3187   \exp_after:wN \__exp_arg_next:nnn
3188   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3189   {#1} {#2}
3190 }
3191 \cs_new:Npn \::v #1 \::: #2#3
3192 {
3193   \exp_after:wN \__exp_arg_next:nnn
3194   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
3195   {#1} {#2}
3196 }
```

(End definition for `\::v` and `\::V`. These functions are documented on page 34.)

`__exp_eval_register:N` This function evaluates a register. Now a register might exist as one of two things: A parameter-less macro or a built-in TeX register such as `\count`. For the TeX registers we have to utilize a `\the` whereas for the macros we merely have to expand them once. The trick is to find out when to use `\the` and when not to. What we want here is to find out whether the token expands to something else when hit with `\exp_after:wN`. The technique is to compare the meaning of the token in question when it has been prefixed with `\exp_not:N` and the token itself. If it is a macro, the prefixed `\exp_not:N` temporarily turns it into the primitive `\scan_stop:`.

```

3197 \cs_new:Npn \__exp_eval_register:N #1
3198 {
3199   \exp_after:wN \if_meaning:w \exp_not:N #1 #1
```

If the token was not a macro it may be a malformed variable from a `c` expansion in which case it is equal to the primitive `\scan_stop:`. In that case we throw an error. We could let `TeX` do it for us but that would result in the rather obscure

```
! You can't use '\relax' after \the.
```

which while quite true doesn't give many hints as to what actually went wrong. We provide something more sensible.

```
3200     \if_meaning:w \scan_stop: #1
3201     \__exp_eval_error_msg:w
3202     \fi:
```

The next bit requires some explanation. The function must be initiated by `\exp:w` and we want to terminate this expansion chain by inserting the `\exp_end:` token. However, we have to expand the register `#1` before we do that. If it is a `TeX` register, we need to execute the sequence `\exp_after:wN \exp_end: \tex_the:D #1` and if it is a macro we need to execute `\exp_after:wN \exp_end: #1`. We therefore issue the longer of the two sequences and if the register is a macro, we remove the `\tex_the:D`.

```
3203     \else:
3204     \exp_after:wN \use_i_ii:nnn
3205     \fi:
3206     \exp_after:wN \exp_end: \tex_the:D #1
3207 }
3208 \cs_new:Npn \__exp_eval_register:c #1
3209 { \exp_after:wN \__exp_eval_register:N \cs:w #1 \cs_end: }
```

Clean up nicely, then call the undefined control sequence. The result is an error message looking like this:

```
! Undefined control sequence.
<argument> \LaTeX3 error:
                               Erroneous variable used!
1.55 \tl_set:Nv \l_tmpa_tl {undefined_tl}

3210 \cs_new:Npn \__exp_eval_error_msg:w #1 \tex_the:D #2
3211 {
3212     \fi:
3213     \fi:
3214     \__kernel_msg_expandable_error:nnn { kernel } { bad-variable } {#2}
3215     \exp_end:
3216 }
```

(End definition for `__exp_eval_register:N` and `__exp_eval_error_msg:w`.)

5.2 Hand-tuned definitions

One of the most important features of these functions is that they are fully expandable.

`\exp_args:Nc` In `l3basics`.

`\exp_args:cc` *(End definition for `\exp_args:Nc` and `\exp_args:cc`. These functions are documented on page 26.)*

`\exp_args:NNc` Here are the functions that turn their argument into csnames but are expandable.

```

3217 \cs_new:Npn \exp_args:NNc #1#2#3
3218 { \exp_after:wN #1 \exp_after:wN #2 \cs:w # 3\cs_end: }
3219 \cs_new:Npn \exp_args:Ncc #1#2#3
3220 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: \cs:w #3 \cs_end: }
3221 \cs_new:Npn \exp_args:Nccc #1#2#3#4
3222 {
3223   \exp_after:wN #1
3224   \cs:w #2 \exp_after:wN \cs_end:
3225   \cs:w #3 \exp_after:wN \cs_end:
3226   \cs:w #4 \cs_end:
3227 }
```

(End definition for `\exp_args:NNc`, `\exp_args:Ncc`, and `\exp_args:Nccc`. These functions are documented on page 28.)

`\exp_args:No` Those lovely runs of expansion!

```

3228 \cs_new:Npn \exp_args:No #1#2 { \exp_after:wN #1 \exp_after:wN {#2} }
3229 \cs_new:Npn \exp_args:NNo #1#2#3
3230 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN {#3} }
3231 \cs_new:Npn \exp_args:NNNo #1#2#3#4
3232 { \exp_after:wN #1 \exp_after:wN#2 \exp_after:wN #3 \exp_after:wN {#4} }
```

(End definition for `\exp_args:No`, `\exp_args:NNo`, and `\exp_args:NNNo`. These functions are documented on page 27.)

`\exp_args:Ne` When the `\expanded` primitive is available, use it. Otherwise use `__exp_e:nn`, defined later, to fully expand tokens.

```

3233 \cs_if_exist:NTF \tex_expanded:D
3234 {
3235   \cs_new:Npn \exp_args:Ne #1#2
3236   { \exp_after:wN #1 \tex_expanded:D { {#2} } }
3237 }
3238 {
3239   \cs_new:Npn \exp_args:Ne #1#2
3240   {
3241     \exp_after:wN #1 \exp_after:wN
3242     { \exp:w \__exp_e:nn {#2} { } }
3243   }
3244 }
```

(End definition for `\exp_args:Ne`. This function is documented on page 27.)

`\exp_args:Nf`

`\exp_args:NV`

`\exp_args:Nv`

```

3245 \cs_new:Npn \exp_args:Nf #1#2
3246 { \exp_after:wN #1 \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } }
3247 \cs_new:Npn \exp_args:Nv #1#2
3248 {
3249   \exp_after:wN #1 \exp_after:wN
3250   { \exp:w \__exp_eval_register:c {#2} }
3251 }
3252 \cs_new:Npn \exp_args:NV #1#2
3253 {
3254   \exp_after:wN #1 \exp_after:wN
3255   { \exp:w \__exp_eval_register:N #2 }
3256 }
```

(End definition for `\exp_args:Nf`, `\exp_args:Nv`, and `\exp_args:Nv`. These functions are documented on page 27.)

`\exp_args:NNV` Some more hand-tuned function with three arguments. If we forced that an `o` argument always has braces, we could implement `\exp_args:Nco` with less tokens and only two arguments.

```

3257 \cs_new:Npn \exp_args:NNV #1#2#3
3258 {
3259   \exp_after:wN #1
3260   \exp_after:wN #2
3261   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3262 }
3263 \cs_new:Npn \exp_args:NNv #1#2#3
3264 {
3265   \exp_after:wN #1
3266   \exp_after:wN #2
3267   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
3268 }
3269 \cs_if_exist:NTF \tex_expanded:D
3270 {
3271   \cs_new:Npn \exp_args:NNe #1#2#3
3272   {
3273     \exp_after:wN #1
3274     \exp_after:wN #2
3275     \tex_expanded:D { {#3} }
3276   }
3277 }
3278 { \cs_new:Npn \exp_args:NNe { \::N \::e \::: } }
3279 \cs_new:Npn \exp_args:NNf #1#2#3
3280 {
3281   \exp_after:wN #1
3282   \exp_after:wN #2
3283   \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
3284 }
3285 \cs_new:Npn \exp_args:Nco #1#2#3
3286 {
3287   \exp_after:wN #1
3288   \cs:w #2 \exp_after:wN \cs_end:
3289   \exp_after:wN {#3}
3290 }
3291 \cs_new:Npn \exp_args:NcV #1#2#3
3292 {
3293   \exp_after:wN #1
3294   \cs:w #2 \exp_after:wN \cs_end:
3295   \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3296 }
3297 \cs_new:Npn \exp_args:Ncv #1#2#3
3298 {
3299   \exp_after:wN #1
3300   \cs:w #2 \exp_after:wN \cs_end:
3301   \exp_after:wN { \exp:w \__exp_eval_register:c {#3} }
3302 }
3303 \cs_new:Npn \exp_args:Ncf #1#2#3
3304 {

```



```

3305     \exp_after:wN #1
3306     \cs:w #2 \exp_after:wN \cs_end:
3307     \exp_after:wN { \exp:w \exp_end_continue_f:w #3 }
3308   }
3309 \cs_new:Npn \exp_args:NNV #1#2#3
3310 {
3311     \exp_after:wN #1
3312     \exp_after:wN { \exp:w \exp_after:wN
3313         \__exp_eval_register:N \exp_after:wN #2 \exp_after:wN }
3314     \exp_after:wN { \exp:w \__exp_eval_register:N #3 }
3315 }

```

(End definition for `\exp_args:NNV` and others. These functions are documented on page 28.)

`\exp_args:NNNV` A few more that we can hand-tune.

```

\exp_args:NcNc 3316 \cs_new:Npn \exp_args:NNNV #1#2#3#4
\exp_args:NcNo 3317 {
\exp_args:Ncco 3318     \exp_after:wN #1
3319     \exp_after:wN #2
3320     \exp_after:wN #3
3321     \exp_after:wN { \exp:w \__exp_eval_register:N #4 }
3322 }
3323 \cs_new:Npn \exp_args:NcNc #1#2#3#4
3324 {
3325     \exp_after:wN #1
3326     \cs:w #2 \exp_after:wN \cs_end:
3327     \exp_after:wN #3
3328     \cs:w #4 \cs_end:
3329 }
3330 \cs_new:Npn \exp_args:NcNo #1#2#3#4
3331 {
3332     \exp_after:wN #1
3333     \cs:w #2 \exp_after:wN \cs_end:
3334     \exp_after:wN #3
3335     \exp_after:wN {#4}
3336 }
3337 \cs_new:Npn \exp_args:Ncco #1#2#3#4
3338 {
3339     \exp_after:wN #1
3340     \cs:w #2 \exp_after:wN \cs_end:
3341     \cs:w #3 \exp_after:wN \cs_end:
3342     \exp_after:wN {#4}
3343 }

```

(End definition for `\exp_args:NNNV` and others. These functions are documented on page 29.)

5.3 Definitions with the automated technique

Some of these could be done more efficiently, but the complexity of coding then becomes an issue. Notice that the auto-generated functions actually take no arguments themselves.

`\exp_args:Nx`

```

3344 \cs_new_protected:Npn \exp_args:Nx { \::x \::: }

```

(End definition for `\exp_args:Nx`. This function is documented on page 28.)

`\exp_args:Nnc` Here are the actual function definitions, using the helper functions above.

```

\exp_args:Nno 3345 \cs_new:Npn \exp_args:Nnc { \::n \::c \::: }
\exp_args:NnV 3346 \cs_new:Npn \exp_args:Nno { \::n \::o \::: }
\exp_args:NnV 3347 \cs_new:Npn \exp_args:NnV { \::n \::V \::: }
\exp_args:Nne 3348 \cs_new:Npn \exp_args:NnV { \::n \::v \::: }
\exp_args:Nnf 3349 \cs_new:Npn \exp_args:Nne { \::n \::e \::: }
\exp_args:Noc 3350 \cs_new:Npn \exp_args:Nnf { \::n \::f \::: }
\exp_args:Noo 3351 \cs_new:Npn \exp_args:Noc { \::o \::c \::: }
\exp_args:Nof 3352 \cs_new:Npn \exp_args:Noo { \::o \::o \::: }
\exp_args:NVo 3353 \cs_new:Npn \exp_args:Nof { \::o \::f \::: }
\exp_args:Nfo 3354 \cs_new:Npn \exp_args:NVo { \::V \::o \::: }
\exp_args:Nff 3355 \cs_new:Npn \exp_args:Nfo { \::f \::o \::: }
\exp_args:NNx 3356 \cs_new:Npn \exp_args:Nff { \::f \::f \::: }
\exp_args:Ncx 3357 \cs_new_protected:Npn \exp_args:NNx { \::N \::x \::: }
\exp_args:Nnx 3358 \cs_new_protected:Npn \exp_args:Ncx { \::c \::x \::: }
\exp_args:Nox 3359 \cs_new_protected:Npn \exp_args:Nnx { \::n \::x \::: }
\exp_args:Nxo 3360 \cs_new_protected:Npn \exp_args:Nox { \::o \::x \::: }
\exp_args:Nxx 3361 \cs_new_protected:Npn \exp_args:Nxo { \::x \::o \::: }
\exp_args:Nxx 3362 \cs_new_protected:Npn \exp_args:Nxx { \::x \::x \::: }

```

(End definition for `\exp_args:Nnc` and others. These functions are documented on page 28.)

```

\exp_args:NNcf 3363 \cs_new:Npn \exp_args:NNcf { \::N \::c \::f \::: }
\exp_args:NNno 3364 \cs_new:Npn \exp_args:NNcf { \::N \::n \::o \::: }
\exp_args:NNnV 3365 \cs_new:Npn \exp_args:NNno { \::N \::n \::V \::: }
\exp_args:NNoo 3366 \cs_new:Npn \exp_args:NNnV { \::N \::o \::o \::: }
\exp_args:NNVV 3367 \cs_new:Npn \exp_args:NNoo { \::N \::V \::V \::: }
\exp_args:Ncno 3368 \cs_new:Npn \exp_args:NNVV { \::N \::V \::V \::: }
\exp_args:NcnV 3369 \cs_new:Npn \exp_args:Ncno { \::c \::n \::o \::: }
\exp_args:Ncoo 3370 \cs_new:Npn \exp_args:NcnV { \::c \::n \::V \::: }
\exp_args:NcVV 3371 \cs_new:Npn \exp_args:Ncoo { \::c \::o \::o \::: }
\exp_args:Nnnc 3372 \cs_new:Npn \exp_args:NcVV { \::c \::V \::V \::: }
\exp_args:Nnno 3373 \cs_new:Npn \exp_args:Nnnc { \::n \::n \::c \::: }
\exp_args:Nnnf 3374 \cs_new:Npn \exp_args:Nnno { \::n \::n \::o \::: }
\exp_args:Nnff 3375 \cs_new:Npn \exp_args:Nnnf { \::n \::n \::f \::: }
\exp_args:Nooo 3376 \cs_new:Npn \exp_args:Nnff { \::n \::f \::f \::: }
\exp_args:Noof 3377 \cs_new:Npn \exp_args:Nooo { \::o \::o \::o \::: }
\exp_args:Nffo 3378 \cs_new:Npn \exp_args:Noof { \::o \::o \::f \::: }
\exp_args:NNNx 3379 \cs_new_protected:Npn \exp_args:Nffo { \::f \::f \::o \::: }
\exp_args:NNnx 3380 \cs_new_protected:Npn \exp_args:NNNx { \::N \::N \::x \::: }
\exp_args:NNox 3381 \cs_new_protected:Npn \exp_args:NNnx { \::N \::n \::x \::: }
\exp_args:Nccx 3382 \cs_new_protected:Npn \exp_args:NNox { \::N \::o \::x \::: }
\exp_args:Ncnx 3383 \cs_new_protected:Npn \exp_args:Nccx { \::n \::n \::x \::: }
\exp_args:Nnnx 3384 \cs_new_protected:Npn \exp_args:Ncnx { \::n \::o \::x \::: }
\exp_args:Nnox 3385 \cs_new_protected:Npn \exp_args:Nnnx { \::c \::c \::x \::: }
\exp_args:Noox 3386 \cs_new_protected:Npn \exp_args:Nnox { \::c \::n \::x \::: }
\exp_args:Noox 3386 \cs_new_protected:Npn \exp_args:Noox { \::o \::o \::x \::: }

```

(End definition for `\exp_args:NNcf` and others. These functions are documented on page 29.)

5.4 Last-unbraced versions

`__exp_arg_last_unbraced:nn` There are a few places where the last argument needs to be available unbraced. First some helper macros.

```

\::o_unbraced
\::V_unbraced
\::v_unbraced
\::e_unbraced
\::f_unbraced
\::x_unbraced

```

```

3387 \cs_new:Npn \__exp_arg_last_unbraced:nn #1#2 { #2#1 }
3388 \cs_new:Npn \::o_unbraced \::: #1#2
3389 { \exp_after:wN \__exp_arg_last_unbraced:nn \exp_after:wN {#2} {#1} }
3390 \cs_new:Npn \::V_unbraced \::: #1#2
3391 {
3392   \exp_after:wN \__exp_arg_last_unbraced:nn
3393   \exp_after:wN { \exp:w \__exp_eval_register:N #2 } {#1}
3394 }
3395 \cs_new:Npn \::v_unbraced \::: #1#2
3396 {
3397   \exp_after:wN \__exp_arg_last_unbraced:nn
3398   \exp_after:wN { \exp:w \__exp_eval_register:c {#2} } {#1}
3399 }
3400 \cs_if_exist:NTF \tex_expanded:D
3401 {
3402   \cs_new:Npn \::e_unbraced \::: #1#2
3403   { \tex_expanded:D { \exp_not:n {#1} #2 } }
3404 }
3405 {
3406   \cs_new:Npn \::e_unbraced \::: #1#2
3407   { \exp:w \__exp_e:nn {#2} {#1} }
3408 }
3409 \cs_new:Npn \::f_unbraced \::: #1#2
3410 {
3411   \exp_after:wN \__exp_arg_last_unbraced:nn
3412   \exp_after:wN { \exp:w \exp_end_continue_f:w #2 } {#1}
3413 }
3414 \cs_new_protected:Npn \::x_unbraced \::: #1#2
3415 {
3416   \cs_set_nopar:Npx \l__exp_internal_tl { \exp_not:n {#1} #2 }
3417   \l__exp_internal_tl
3418 }

```

(End definition for `__exp_arg_last_unbraced:nn` and others. These functions are documented on page 34.)

<pre> \exp_last_unbraced:No \exp_last_unbraced:Nv \exp_last_unbraced:Nv \exp_last_unbraced:Nf \exp_last_unbraced:NNo \exp_last_unbraced:NNv \exp_last_unbraced:NNf \exp_last_unbraced:Nco \exp_last_unbraced:NcV \exp_last_unbraced:NNNo \exp_last_unbraced:NNNV \exp_last_unbraced:NNNf \exp_last_unbraced:Nno \exp_last_unbraced:Noo \exp_last_unbraced:Nfo \exp_last_unbraced:NnNo \exp_last_unbraced:NNNNo \exp_last_unbraced:NNNNf \exp_last_unbraced:Nx </pre>	<p>Now the business end: most of these are hand-tuned for speed, but the general system is in place.</p> <pre> 3419 \cs_new:Npn \exp_last_unbraced:No #1#2 { \exp_after:wN #1 #2 } 3420 \cs_new:Npn \exp_last_unbraced:Nv #1#2 3421 { \exp_after:wN #1 \exp:w __exp_eval_register:N #2 } 3422 \cs_new:Npn \exp_last_unbraced:Nv #1#2 3423 { \exp_after:wN #1 \exp:w __exp_eval_register:c {#2} } 3424 \cs_if_exist:NTF \tex_expanded:D 3425 { 3426 \cs_new:Npn \exp_last_unbraced:Ne #1#2 3427 { \exp_after:wN #1 \tex_expanded:D {#2} } 3428 } 3429 { \cs_new:Npn \exp_last_unbraced:Ne { \::e_unbraced \::: } } 3430 \cs_new:Npn \exp_last_unbraced:Nf #1#2 3431 { \exp_after:wN #1 \exp:w \exp_end_continue_f:w #2 } 3432 \cs_new:Npn \exp_last_unbraced:NNo #1#2#3 3433 { \exp_after:wN #1 \exp_after:wN #2 #3 } 3434 \cs_new:Npn \exp_last_unbraced:NNv #1#2#3 </pre>
--	--

```

3435 {
3436   \exp_after:wN #1
3437   \exp_after:wN #2
3438   \exp:w \__exp_eval_register:N #3
3439 }
3440 \cs_new:Npn \exp_last_unbraced:NNf #1#2#3
3441 {
3442   \exp_after:wN #1
3443   \exp_after:wN #2
3444   \exp:w \exp_end_continue_f:w #3
3445 }
3446 \cs_new:Npn \exp_last_unbraced:Nco #1#2#3
3447 { \exp_after:wN #1 \cs:w #2 \exp_after:wN \cs_end: #3 }
3448 \cs_new:Npn \exp_last_unbraced:NcV #1#2#3
3449 {
3450   \exp_after:wN #1
3451   \cs:w #2 \exp_after:wN \cs_end:
3452   \exp:w \__exp_eval_register:N #3
3453 }
3454 \cs_new:Npn \exp_last_unbraced:NNNo #1#2#3#4
3455 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 #4 }
3456 \cs_new:Npn \exp_last_unbraced:NNNV #1#2#3#4
3457 {
3458   \exp_after:wN #1
3459   \exp_after:wN #2
3460   \exp_after:wN #3
3461   \exp:w \__exp_eval_register:N #4
3462 }
3463 \cs_new:Npn \exp_last_unbraced:NNNf #1#2#3#4
3464 {
3465   \exp_after:wN #1
3466   \exp_after:wN #2
3467   \exp_after:wN #3
3468   \exp:w \exp_end_continue_f:w #4
3469 }
3470 \cs_new:Npn \exp_last_unbraced:Nno { \::n \::o_unbraced \::: }
3471 \cs_new:Npn \exp_last_unbraced:Noo { \::o \::o_unbraced \::: }
3472 \cs_new:Npn \exp_last_unbraced:Nfo { \::f \::o_unbraced \::: }
3473 \cs_new:Npn \exp_last_unbraced:NnNo { \::n \::N \::o_unbraced \::: }
3474 \cs_new:Npn \exp_last_unbraced:NNNNo #1#2#3#4#5
3475 { \exp_after:wN #1 \exp_after:wN #2 \exp_after:wN #3 \exp_after:wN #4 #5 }
3476 \cs_new:Npn \exp_last_unbraced:NNNNf #1#2#3#4#5
3477 {
3478   \exp_after:wN #1
3479   \exp_after:wN #2
3480   \exp_after:wN #3
3481   \exp_after:wN #4
3482   \exp:w \exp_end_continue_f:w #5
3483 }
3484 \cs_new_protected:Npn \exp_last_unbraced:Nx { \::x_unbraced \::: }

```

(End definition for \exp_last_unbraced:No and others. These functions are documented on page 30.)

\exp_last_two_unbraced:Noo If #2 is a single token then this can be implemented as

__exp_last_two_unbraced:noN

```

\cs_new:Npn \exp_last_two_unbraced:Noo #1 #2 #3
{ \exp_after:wN \exp_after:wN \exp_after:wN #1 \exp_after:wN #2 #3 }

```

However, for robustness this is not suitable. Instead, a bit of a shuffle is used to ensure that #2 can be multiple tokens.

```

3485 \cs_new:Npn \exp_last_two_unbraced:Noo #1#2#3
3486 { \exp_after:wN \__exp_last_two_unbraced:noN \exp_after:wN {#3} {#2} #1 }
3487 \cs_new:Npn \__exp_last_two_unbraced:noN #1#2#3
3488 { \exp_after:wN #3 #2 #1 }

```

(End definition for `\exp_last_two_unbraced:Noo` and `__exp_last_two_unbraced:noN`. This function is documented on page 30.)

5.5 Preventing expansion

`__kernel_exp_not:w` At the kernel level, we need the primitive behaviour to allow expansion *before* the brace group.

```

3489 \cs_new_eq:NN \__kernel_exp_not:w \tex_unexpanded:D

```

(End definition for `__kernel_exp_not:w`.)

`\exp_not:c` All these except `\exp_not:c` call the kernel-internal `__kernel_exp_not:w` namely `\tex_unexpanded:D`.

```

\exp_not:o \tex_unexpanded:D.
\exp_not:e 3490 \cs_new:Npn \exp_not:c #1 { \exp_after:wN \exp_not:N \cs:w #1 \cs_end: }
\exp_not:f 3491 \cs_new:Npn \exp_not:o #1 { \__kernel_exp_not:w \exp_after:wN {#1} }
\exp_not:V 3492 \cs_if_exist:NTF \tex_expanded:D
\exp_not:v 3493 {
3494   \cs_new:Npn \exp_not:e #1
3495   { \__kernel_exp_not:w \tex_expanded:D { {#1} } }
3496 }
3497 {
3498   \cs_new:Npn \exp_not:e
3499   { \__kernel_exp_not:w \exp_args:Ne \prg_do_nothing: }
3500 }
3501 \cs_new:Npn \exp_not:f #1
3502 { \__kernel_exp_not:w \exp_after:wN { \exp:w \exp_end_continue_f:w #1 } }
3503 \cs_new:Npn \exp_not:V #1
3504 {
3505   \__kernel_exp_not:w \exp_after:wN
3506   { \exp:w \__exp_eval_register:N #1 }
3507 }
3508 \cs_new:Npn \exp_not:v #1
3509 {
3510   \__kernel_exp_not:w \exp_after:wN
3511   { \exp:w \__exp_eval_register:c {#1} }
3512 }

```

(End definition for `\exp_not:c` and others. These functions are documented on page 31.)

5.6 Controlled expansion

```
\exp:w
\exp_end:
\exp_end_continue_f:w
\exp_end_continue_f:nw
```

To trigger a sequence of “arbitrarily” many expansions we need a method to invoke T_EX’s expansion mechanism in such a way that (a) we are able to stop it in a controlled manner and (b) the result of what triggered the expansion in the first place is null, i.e., that we do not get any unwanted side effects. There aren’t that many possibilities in T_EX; in fact the one explained below might well be the only one (as normally the result of expansion is not null).

The trick here is to make use of the fact that `\tex_romannumeral:D` expands the tokens following it when looking for a number and that its expansion is null if that number turns out to be zero or negative. So we use that to start the expansion sequence: `\exp:w` is set equal to `\tex_romannumeral:D` in `l3basics`. To stop the expansion sequence in a controlled way all we need to provide is a constant integer zero as part of expanded tokens. As this is an integer constant it immediately stops `\tex_romannumeral:D`’s search for a number. Again, the definition of `\exp_end:` as the integer constant zero is in `l3basics`. (Note that according to our specification all tokens we expand initiated by `\exp:w` are supposed to be expandable (as well as their replacement text in the expansion) so we will not encounter a “number” that actually result in a roman numeral being generated. Or if we do then the programmer made a mistake.)

If on the other hand we want to stop the initial expansion sequence but continue with an `f`-type expansion we provide the alphabetic constant `^^@` that also represents 0 but this time T_EX’s syntax for a *⟨number⟩* continues searching for an optional space (and it continues expansion doing that) — see T_EXbook page 269 for details.

```
3513 \group_begin:
3514   \tex_catcode:D ‘^^@ = 13
3515   \cs_new_protected:Npn \exp_end_continue_f:w { ‘^^@ }
```

If the above definition ever appears outside its proper context the active character `^^@` will be executed so we turn this into an error. The test for existence covers the (unlikely) case that some other code has already defined `^^@`: this is true for example for `xmltex.tex`.

```
3516   \if_cs_exist:N ^^@
3517   \else:
3518     \cs_new:Npn ^^@
3519       { \__kernel_msg_expandable_error:nn { kernel } { bad-exp-end-f } }
3520   \fi:
```

The same but grabbing an argument to remove spaces and braces.

```
3521   \cs_new:Npn \exp_end_continue_f:nw #1 { ‘^^@ #1 }
3522 \group_end:
```

(End definition for `\exp:w` and others. These functions are documented on page 33.)

5.7 Emulating e-type expansion

When the `\expanded` primitive is available it is used to implement `e`-type expansion; otherwise we emulate it.

```
3523 \cs_if_exist:NF \tex_expanded:D
3524 {
```

`__exp_e:nn` Repeatedly expand tokens, keeping track of fully-expanded tokens in the second argument to `__exp_e:nn`; this function eventually calls `__exp_e_end:nn` to leave `\exp_end:` in

the input stream, followed by the result of the expansion. There are many special cases: spaces, brace groups, `\noexpand`, `\unexpanded`, `\the`, `\primitive`.

```

3525 \cs_new:Npn \__exp_e:nn #1
3526 {
3527   \if_false: { \fi:
3528     \tl_if_head_is_N_type:nTF {#1}
3529     { \__exp_e:N }
3530     {
3531       \tl_if_head_is_group:nTF {#1}
3532       { \__exp_e_group:n }
3533       {
3534         \tl_if_empty:nTF {#1}
3535         { \exp_after:wN \__exp_e_end:nn }
3536         { \exp_after:wN \__exp_e_space:nn }
3537         \exp_after:wN { \if_false: } \fi:
3538       }
3539     }
3540   #1
3541 }
3542 }
3543 \cs_new:Npn \__exp_e_end:nn #1#2 { \exp_end: #2 }

```

(End definition for `__exp_e:nn`.)

`__exp_e_space:nn` For an explicit space character, remove it by f-expansion and put it in the (future) output.

```

3544 \cs_new:Npn \__exp_e_space:nn #1#2
3545 { \exp_args:Nf \__exp_e:nn {#1} { #2 ~ } }

```

(End definition for `__exp_e_space:nn`.)

`__exp_e_group:n` For a group, expand its contents, wrap it in two pairs of braces, and call `__exp_e_put:nn`. This function places the first item (the double-brace wrapped result) into the output. Importantly, `\tl_head:n` works even if the input contains quarks.

```

3546 \cs_new:Npn \__exp_e_group:n #1
3547 {
3548   \exp_after:wN \__exp_e_put:nn
3549   \exp_after:wN { \exp_after:wN { \exp_after:wN {
3550     \exp:w \if_false: } \fi: \__exp_e:nn {#1} { } } }
3551 }
3552 \cs_new:Npn \__exp_e_put:nn #1
3553 {
3554   \exp_args:NNo \exp_args:No \__exp_e_put:nnn
3555   { \tl_head:n {#1} } {#1}
3556 }
3557 \cs_new:Npn \__exp_e_put:nnn #1#2#3
3558 { \exp_args:No \__exp_e:nn { \use_none:n #2 } { #3 #1 } }

```

(End definition for `__exp_e_group:n`, `__exp_e_put:nn`, and `__exp_e_put:nnn`.)

`__exp_e:N` For an N-type token, call `__exp_e:Nnn` with arguments the *⟨first token⟩*, the remaining tokens to expand and what's already been expanded. If the *⟨first token⟩* is non-expandable, including `\protected` (`\long` or not) macros, it is put in the result by

`__exp_e_protected:Nnn`. The four special primitives `\unexpanded`, `\noexpand`, `\the`, `\primitive` are detected; otherwise the token is expanded by `__exp_e_expandable:Nnn`.

```

3559 \cs_new:Npn \__exp_e:N #1
3560 {
3561   \exp_after:wN \__exp_e:Nnn
3562   \exp_after:wN #1
3563   \exp_after:wN { \if_false: } \fi:
3564 }
3565 \cs_new:Npn \__exp_e:Nnn #1
3566 {
3567   \if_case:w
3568     \exp_after:wN \if_meaning:w \exp_not:N #1 #1 1 ~ \fi:
3569     \token_if_protected_macro:NT #1 { 1 ~ }
3570     \token_if_protected_long_macro:NT #1 { 1 ~ }
3571     \if_meaning:w \exp_not:n #1 2 ~ \fi:
3572     \if_meaning:w \exp_not:N #1 3 ~ \fi:
3573     \if_meaning:w \tex_the:D #1 4 ~ \fi:
3574     \if_meaning:w \tex_primitive:D #1 5 ~ \fi:
3575     0 ~
3576     \exp_after:wN \__exp_e_expandable:Nnn
3577   \or: \exp_after:wN \__exp_e_protected:Nnn
3578   \or: \exp_after:wN \__exp_e_unexpanded:Nnn
3579   \or: \exp_after:wN \__exp_e_noexpand:Nnn
3580   \or: \exp_after:wN \__exp_e_the:Nnn
3581   \or: \exp_after:wN \__exp_e_primitive:Nnn
3582   \fi:
3583   #1
3584 }
3585 \cs_new:Npn \__exp_e_protected:Nnn #1#2#3
3586 { \__exp_e:nn {#2} { #3 #1 } }
3587 \cs_new:Npn \__exp_e_expandable:Nnn #1#2
3588 { \exp_args:No \__exp_e:nn { #1 #2 } }

```

(End definition for `__exp_e:N`.)

`__exp_e_primitive:Nnn` Quite rare. Will be implemented later.

```

3589 \cs_new:Npn \__exp_e_primitive:Nnn #1
3590 {
3591   \__kernel_msg_expandable_error:nnn { kernel } { e-type }
3592   { \primitive not-implemented }
3593   \__exp_e:nn
3594 }

```

(End definition for `__exp_e_primitive:Nnn`.)

`__exp_e_noexpand:Nnn` The `\noexpand` primitive has no effect when followed by a token that is not N-type; otherwise `__exp_e_put:nn` can grab the next token and put it in the result unchanged.

```

3595 \cs_new:Npn \__exp_e_noexpand:Nnn #1#2
3596 {
3597   \tl_if_head_is_N_type:nTF {#2}
3598   { \__exp_e_put:nn } { \__exp_e:nn } {#2}
3599 }

```

(End definition for `__exp_e_noexpand:Nnn`.)

`__exp_e_unexpanded:Nnn`
`__exp_e_unexpanded:nn`
`__exp_e_unexpanded:nN`
`__exp_e_unexpanded:N`

The `\unexpanded` primitive expands and ignores any space, `\scan_stop:`, or token affected by `\exp_not:N`, then expects a brace group. Since we only support brace-balanced token lists it is impossible to support the case where the argument of `\unexpanded` starts with an implicit brace. Even though we want to expand and ignore spaces we cannot blindly f-expand because tokens affected by `\exp_not:N` should be discarded without being expanded further.

As usual distinguish four cases: brace group (the normal case, where we just put the item in the result), space (just f-expand to remove the space), empty (an error), or N-type *<token>*. In the last case call `__exp_e_unexpanded:nN` triggered by an f-expansion. Having a non-expandable *<token>* after `\unexpanded` is an error (we recover by passing `{}` to `\unexpanded`; this is different from T_EX because the error recovery of `\unexpanded` changes the balance of braces), unless that *<token>* is `\scan_stop:` or a space (recall that we don't implement the case of an implicit begin-group token). An expandable *<token>* is instead expanded, unless it is `\noexpand`. That primitive can be followed by an expandable N-type token, to be removed, by a non-expandable one, kept (and later causing an error), by a space, removed by f-expansion, or by a brace group or nothing (later causing an error).

```

3600 \cs_new:Npn \__exp_e_unexpanded:Nnn #1 { \__exp_e_unexpanded:nn }
3601 \cs_new:Npn \__exp_e_unexpanded:nn #1
3602 {
3603   \tl_if_head_is_N_type:nTF {#1}
3604   {
3605     \exp_args:Nf \__exp_e_unexpanded:nn
3606     { \__exp_e_unexpanded:nN {#1} #1 }
3607   }
3608   {
3609     \tl_if_head_is_group:nTF {#1}
3610     { \__exp_e_put:nn }
3611     {
3612       \tl_if_empty:nTF {#1}
3613       {
3614         \__kernel_msg_expandable_error:nnn
3615         { kernel } { e-type }
3616         { \unexpanded missing~brace }
3617         \__exp_e_end:nn
3618       }
3619       { \exp_args:Nf \__exp_e_unexpanded:nn }
3620     }
3621     {#1}
3622   }
3623 }
3624 \cs_new:Npn \__exp_e_unexpanded:nN #1#2
3625 {
3626   \exp_after:wN \if_meaning:w \exp_not:N #2 #2
3627   \exp_after:wN \use_i:nn
3628   \else:
3629     \exp_after:wN \use_ii:nn
3630   \fi:
3631   {
3632     \token_if_eq_catcode:NNTF #2 \c_space_token
3633     { \exp_stop_f: }
3634     {

```

```

3635         \token_if_eq_meaning:NNTF #2 \scan_stop:
3636         { \exp_stop_f: }
3637         {
3638             \__kernel_msg_expandable_error:nnn
3639             { kernel } { e-type }
3640             { \unexpanded missing-brace }
3641             { }
3642         }
3643     }
3644 }
3645 {
3646     \token_if_eq_meaning:NNTF #2 \exp_not:N
3647     {
3648         \exp_args:No \tl_if_head_is_N_type:nT { \use_none:n #1 }
3649         { \__exp_e_unexpanded:N }
3650     }
3651     { \exp_after:wN \exp_stop_f: #2 }
3652 }
3653 }
3654 \cs_new:Npn \__exp_e_unexpanded:N #1
3655 {
3656     \exp_after:wN \if_meaning:w \exp_not:N #1 #1 \else:
3657     \exp_after:wN \use_i:nn
3658     \fi:
3659     \exp_stop_f: #1
3660 }

```

(End definition for `__exp_e_unexpanded:Nnn` and others.)

`__exp_e_the:Nnn`
`__exp_e_the:N`
`__exp_e_the_toks_reg:N`

Finally implement `\the`. Followed by anything other than an N-type *<token>* this causes an error (we just let T_EX make one), otherwise we test the *<token>*. If the *<token>* is expandable, expand it. Otherwise it could be any kind of register, or things like `\numexpr`, so there is no way to deal with all cases. Thankfully, only `\toks` data needs to be protected from expansion since everything else gives a string of characters. If the *<token>* is `\toks` we find a number and unpack using the `the_toks` functions. If it is a token register we unpack it in a brace group and call `__exp_e_put:nn` to move it to the result. Otherwise we unpack and continue expanding (useless but safe) since it is basically impossible to have a handle on where the result of `\the` ends.

```

3661     \cs_new:Npn \__exp_e_the:Nnn #1#2
3662     {
3663         \tl_if_head_is_N_type:nTF {#2}
3664         { \if_false: { \fi: \__exp_e_the:N #2 } }
3665         { \exp_args:No \__exp_e:nn { \tex_the:D #2 } }
3666     }
3667     \cs_new:Npn \__exp_e_the:N #1
3668     {
3669         \exp_after:wN \if_meaning:w \exp_not:N #1 #1
3670         \exp_after:wN \use_i:nn
3671         \else:
3672         \exp_after:wN \use_ii:nn
3673         \fi:
3674         {
3675             \if_meaning:w \tex_toks:D #1
3676             \exp_after:wN \__exp_e_the_toks:wnn \int_value:w

```

```

3677         \exp_after:wN \__exp_e_the_toks:n
3678         \exp_after:wN { \int_value:w \if_false: } \fi:
3679     \else:
3680         \__exp_e_if_toks_register:NTF #1
3681         { \exp_after:wN \__exp_e_the_toks_reg:N }
3682         {
3683             \exp_after:wN \__exp_e:nn \exp_after:wN {
3684                 \tex_the:D \if_false: } \fi:
3685         }
3686         \exp_after:wN #1
3687     \fi:
3688 }
3689 {
3690     \exp_after:wN \__exp_e_the:Nnn \exp_after:wN ?
3691     \exp_after:wN { \exp:w \if_false: } \fi:
3692     \exp_after:wN \exp_end: #1
3693 }
3694 }
3695 \cs_new:Npn \__exp_e_the_toks_reg:N #1
3696 {
3697     \exp_after:wN \__exp_e_put:nn \exp_after:wN {
3698         \exp_after:wN {
3699             \tex_the:D \if_false: } \fi: #1 }
3700 }

```

(End definition for `__exp_e_the:Nnn`, `__exp_e_the:N`, and `__exp_e_the_toks_reg:N`.)

`__exp_e_the_toks:wnn` The calling function has applied `\int_value:w` so we collect digits with `__exp_e_the_toks:n` (which gets the token list as an argument) and `__exp_e_the_toks:N` (which gets the first token in case it is N-type). The digits are themselves collected into an `\int_value:w` argument to `__exp_e_the_toks:wnn`. Then that function unpacks the `\toks<number>` into the result. We include `?` because `__exp_e_put:nnn` removes one item from its second argument. Note that our approach is rather crude: in cases like `\the\toks12~34` the first `\int_value:w` removes the space and we will incorrectly unpack the `\the\toks1234`.

```

3701     \cs_new:Npn \__exp_e_the_toks:wnn #1; #2
3702     {
3703         \exp_args:No \__exp_e_put:nnn
3704         { \tex_the:D \tex_toks:D #1 } { ? #2 }
3705     }
3706     \cs_new:Npn \__exp_e_the_toks:n #1
3707     {
3708         \tl_if_head_is_N_type:NTF {#1}
3709         { \exp_after:wN \__exp_e_the_toks:N \if_false: { \fi: #1 } }
3710         { ; {#1} }
3711     }
3712     \cs_new:Npn \__exp_e_the_toks:N #1
3713     {
3714         \if_int_compare:w 10 < 9 \token_to_str:N #1 \exp_stop_f:
3715         \exp_after:wN \use_i:nn
3716     \else:
3717         \exp_after:wN \use_ii:nn
3718     \fi:
3719     {

```

```

3720         #1
3721         \exp_after:wN \__exp_e_the_toks:n
3722     }
3723     { \exp_after:wN ; }
3724     \exp_after:wN { \if_false: } \fi:
3725 }

```

(End definition for __exp_e_the_toks:wnn, __exp_e_the_toks:n, and __exp_e_the_toks:N.)

__exp_e_if_toks_register:NTF We need to detect both \toks registers like \toks@ (in L^AT_EX 2_ε) and parameters such as \everypar, as the result of unpacking the register should not expand further. The list of parameters is finite so we just use a \cs_if_exist:cTF test to look up in a table. Registers are found by \token_if_toks_register:NTF by inspecting the meaning. We abuse \cs_to_str:N's ability to remove a leading escape character whatever it is.

```

3726     \prg_new_conditional:Npnn \__exp_e_if_toks_register:N #1 { TF }
3727     {
3728         \token_if_toks_register:NTF #1 { \prg_return_true: }
3729         {
3730             \cs_if_exist:cTF
3731             {
3732                 \__exp_e_the_
3733                 \exp_after:wN \cs_to_str:N
3734                 \token_to_meaning:N #1
3735                 :
3736             } { \prg_return_true: } { \prg_return_false: }
3737         }
3738     }
3739     \cs_new_eq:NN \__exp_e_the_XeTeXinterchartoks: ?
3740     \cs_new_eq:NN \__exp_e_the_errhelp: ?
3741     \cs_new_eq:NN \__exp_e_the_everycr: ?
3742     \cs_new_eq:NN \__exp_e_the_everydisplay: ?
3743     \cs_new_eq:NN \__exp_e_the_everyeof: ?
3744     \cs_new_eq:NN \__exp_e_the_everyhbox: ?
3745     \cs_new_eq:NN \__exp_e_the_everyjob: ?
3746     \cs_new_eq:NN \__exp_e_the_everymath: ?
3747     \cs_new_eq:NN \__exp_e_the_everypar: ?
3748     \cs_new_eq:NN \__exp_e_the_everyvbox: ?
3749     \cs_new_eq:NN \__exp_e_the_output: ?
3750     \cs_new_eq:NN \__exp_e_the_pdffpageattr: ?
3751     \cs_new_eq:NN \__exp_e_the_pdfpageresources: ?
3752     \cs_new_eq:NN \__exp_e_the_pdfpagesattr: ?
3753     \cs_new_eq:NN \__exp_e_the_pdfpkmode: ?

```

(End definition for __exp_e_if_toks_register:NTF.)

We are done emulating e-type argument expansion when \expanded is unavailable.

```

3754 }

```

5.8 Defining function variants

```

3755 <@@=cs>

```

\cs_generate_variant:Nn #1 : Base form of a function; e.g., \tl_set:Nn
\cs_generate_variant:cn

#2 : One or more variant argument specifiers; e.g., {Nx,c,cx}

After making sure that the base form exists, test whether it is protected or not and define `__cs_tmp:w` as either `\cs_new:Npx` or `\cs_new_protected:Npx`, which is then used to define all the variants (except those involving x-expansion, always protected). Split up the original base function only once, to grab its name and signature. Then we wish to iterate through the comma list of variant argument specifiers, which we first convert to a string: the reason is explained later.

```

3756 \__kernel_patch:nnNNpn { \__kernel_chk_cs_exist:N #1 } { }
3757 \cs_new_protected:Npn \cs_generate_variant:Nn #1#2
3758 {
3759   \__cs_generate_variant:N #1
3760   \use:x
3761   {
3762     \__cs_generate_variant:nnNN
3763     \cs_split_function:N #1
3764     \exp_not:N #1
3765     \tl_to_str:n {#2} ,
3766     \exp_not:N \scan_stop: ,
3767     \exp_not:N \q_recursion_stop
3768   }
3769 }
3770 \cs_new_protected:Npn \cs_generate_variant:cn
3771 { \exp_args:Nc \cs_generate_variant:Nn }

```

(End definition for `\cs_generate_variant:Nn`. This function is documented on page 24.)

```

\__cs_generate_variant:N
\__cs_generate_variant:ww
\__cs_generate_variant:wwNw

```

The goal here is to pick up protected parent functions. There are four cases: the parent function can be a primitive or a macro, and can be expandable or not. For non-expandable primitives, all variants should be protected; skipping the `\else:` branch is safe because non-expandable primitives cannot be TeX conditionals.

The other case where variants should be protected is when the parent function is a protected macro: then `protected` appears in the meaning before the first occurrence of `macro`. The `ww` auxiliary removes everything in the meaning string after the first `ma`. We use `ma` rather than the full `macro` because the meaning of the `\firstmark` primitive (and four others) can contain an arbitrary string after a leading `firstmark:`. Then, look for `pr` in the part we extracted: no need to look for anything longer: the only strings we can have are an empty string, `\long`, `\protected`, `\protected\long`, `\first`, `\top`, `\bot`, `\splittop`, or `\splitbot`, with `\` replaced by the appropriate escape character. If `pr` appears in the part before `ma`, the first `\q_mark` is taken as an argument of the `wwNw` auxiliary, and #3 is `\cs_new_protected:Npx`, otherwise it is `\cs_new:Npx`.

```

3772 \cs_new_protected:Npx \__cs_generate_variant:N #1
3773 {
3774   \exp_not:N \exp_after:wN \exp_not:N \if_meaning:w
3775   \exp_not:N \exp_not:N #1 #1
3776   \cs_set_eq:NN \exp_not:N \__cs_tmp:w \cs_new_protected:Npx
3777   \exp_not:N \else:
3778   \exp_not:N \exp_after:wN \exp_not:N \__cs_generate_variant:ww
3779   \exp_not:N \token_to_meaning:N #1 \tl_to_str:n { ma }
3780   \exp_not:N \q_mark
3781   \exp_not:N \q_mark \cs_new_protected:Npx
3782   \tl_to_str:n { pr }
3783   \exp_not:N \q_mark \cs_new:Npx

```

```

3784         \exp_not:N \q_stop
3785     \exp_not:N \fi:
3786 }
3787 \exp_last_unbraced:NNNNo
3788 \cs_new_protected:Npn \__cs_generate_variant:ww
3789     #1 { \tl_to_str:n { ma } } #2 \q_mark
3790     { \__cs_generate_variant:wwNw #1 }
3791 \exp_last_unbraced:NNNNo
3792 \cs_new_protected:Npn \__cs_generate_variant:wwNw
3793     #1 { \tl_to_str:n { pr } } #2 \q_mark #3 #4 \q_stop
3794     { \cs_set_eq:NN \__cs_tmp:w #3 }

```

(End definition for `__cs_generate_variant:N`, `__cs_generate_variant:ww`, and `__cs_generate_variant:wwNw`.)

`__cs_generate_variant:nnNN`

#1 : Base name.
 #2 : Base signature.
 #3 : Boolean.
 #4 : Base function.

If the boolean is `\c_false_bool`, the base function has no colon and we abort with an error; otherwise, set off a loop through the desired variant forms. The original function is retained as #4 for efficiency.

```

3795 \cs_new_protected:Npn \__cs_generate_variant:nnNN #1#2#3#4
3796 {
3797     \if_meaning:w \c_false_bool #3
3798         \__kernel_msg_error:nnx { kernel } { missing-colon }
3799         { \token_to_str:c {#1} }
3800     \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
3801     \fi:
3802     \__cs_generate_variant:Nnw #4 {#1}{#2}
3803 }

```

(End definition for `__cs_generate_variant:nnNN`.)

`__cs_generate_variant:Nnw`

#1 : Base function.
 #2 : Base name.
 #3 : Base signature.
 #4 : Beginning of variant signature.

First check whether to terminate the loop over variant forms. Then, for each variant form, construct a new function name using the original base name, the variant signature consisting of l letters and the last $k - l$ letters of the base signature (of length k). For example, for a base function `\prop_put:Nnn` which needs a `cV` variant form, we want the new signature to be `cVn`.

There are further subtleties:

- In `\cs_generate_variant:Nn \foo:nnTF {xxTF}`, we must define `\foo:xxTF` using `\exp_args:Nxx`, rather than a hypothetical `\exp_args:NxxTF`. Thus, we wish to trim a common trailing part from the base signature and the variant signature.
- In `\cs_generate_variant:Nn \foo:on {ox}`, the function `\foo:ox` must be defined using `\exp_args:Nnx`, not `\exp_args:Nox`, to avoid double `o` expansion.
- Lastly, `\cs_generate_variant:Nn \foo:on {xn}` must trigger an error, because we do not have a means to replace `o`-expansion by `x`-expansion. More generally, we can only convert `N` to `c`, or convert `n` to `V`, `v`, `o`, `f`, `x`.

All this boils down to a few rules. Only `n` and `N`-type arguments can be replaced by `\cs_generate_variant:Nn`. Other argument types are allowed to be passed unchanged from the base form to the variant: in the process they are changed to `n` except for `N` and `p`-type arguments. A common trailing part is ignored.

We compare the base and variant signatures one character at a time within `x`-expansion. The result is given to `__cs_generate_variant:wwNN` (defined later) in the form `<processed variant signature> \q_mark <errors> \q_stop <base function> <new function>`. If all went well, `<errors>` is empty; otherwise, it is a kernel error message and some clean-up code.

Note the space after `#3` and after the following brace group. Those are ignored by `TeX` when fetching the last argument for `__cs_generate_variant_loop:nNwN`, but can be used as a delimiter for `__cs_generate_variant_loop_end:nwwwNNnn`.

```

3804 \cs_new_protected:Npn \__cs_generate_variant:Nnnw #1#2#3#4 ,
3805 {
3806   \if_meaning:w \scan_stop: #4
3807   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
3808   \fi:
3809   \use:x
3810   {
3811     \exp_not:N \__cs_generate_variant:wwNN
3812     \__cs_generate_variant_loop:nNwN { }
3813     #4
3814     \__cs_generate_variant_loop_end:nwwwNNnn
3815     \q_mark
3816     #3 ~
3817     { ~ { } } \fi: \__cs_generate_variant_loop_long:wNNnn } ~
3818     { }
3819     \q_stop
3820     \exp_not:N #1 {#2} {#4}
3821   }
3822   \__cs_generate_variant:Nnnw #1 {#2} {#3}
3823 }
```

(End definition for `__cs_generate_variant:Nnnw`.)

<code>__cs_generate_variant_loop:nNwN</code>	#1 :	Last few consecutive letters common between the base and variant (more precisely,
<code>__cs_generate_variant_loop_base:N</code>		<code>__cs_generate_variant_same:N <letter></code> for each letter).
<code>__cs_generate_variant_loop_same:w</code>	#2 :	Next variant letter.
<code>__cs_generate_variant_loop_end:nwwwNNnn</code>	#3 :	Remainder of variant form.
<code>__cs_generate_variant_loop_long:wNNnn</code>	#4 :	Next base letter.

The first argument is populated by `__cs_generate_variant_loop_same:w` when a variant letter and a base letter match. It is flushed into the input stream whenever the two letters are different: if the loop ends before, the argument is dropped, which means that trailing common letters are ignored.

The case where the two letters are different is only allowed if the base is `N` and the variant is `c`, or when the base is `n` and the variant is `o`, `V`, `v`, `f` or `x`. Otherwise, call `__cs_generate_variant_loop_invalid:NNwNNnn` to remove the end of the loop, get arguments at the end of the loop, and place an appropriate error message as a second argument of `__cs_generate_variant:wwNN`. If the letters are distinct and the base letter is indeed `n` or `N`, leave in the input stream whatever argument `#1` was collected, and the next variant letter `#2`, then loop by calling `__cs_generate_variant_loop:nNwN`.

The loop can stop in three ways.

- If the end of the variant form is encountered first, #2 is `__cs_generate_variant_loop_end:nwwwNNnn` (expanded by the conditional `\if:w`), which inserts some tokens to end the conditional; grabs the *base name* as #7, the *variant signature* #8, the *next base letter* #1 and the part #3 of the base signature that wasn't read yet; and combines those into the *new function* to be defined.
- If the end of the base form is encountered first, #4 is `~{}~\fi:` which ends the conditional (with an empty expansion), followed by `__cs_generate_variant_loop_long:wNNnn`, which places an error as the second argument of `__cs_generate_variant:wvNN`.
- The loop can be interrupted early if the requested expansion is unavailable, namely when the variant and base letters differ and the base is not the right one (n or N to support the variant). In that case too an error is placed as the second argument of `__cs_generate_variant:wvNN`.

Note that if the variant form has the same length as the base form, #2 is as described in the first point, and #4 as described in the second point above. The `__cs_generate_variant_loop_end:nwwwNNnn` breaking function takes the empty brace group in #4 as its first argument: this empty brace group produces the correct signature for the full variant.

```

3824 \cs_new:Npn \__cs_generate_variant_loop:nNwN #1#2#3 \q_mark #4
3825 {
3826   \if:w #2 #4
3827     \exp_after:wN \__cs_generate_variant_loop_same:w
3828   \else:
3829     \if:w #4 \__cs_generate_variant_loop_base:N #2 \else:
3830       \if:w 0
3831         \if:w N #4 \else: \if:w n #4 \else: 1 \fi: \fi:
3832         \if:w \scan_stop: \__cs_generate_variant_loop_base:N #2 1 \fi:
3833         0
3834         \__cs_generate_variant_loop_special:NNwNNnn #4#2
3835       \else:
3836         \__cs_generate_variant_loop_invalid:NNwNNnn #4#2
3837       \fi:
3838     \fi:
3839   \fi:
3840   #1
3841   \prg_do_nothing:
3842   #2
3843   \__cs_generate_variant_loop:nNwN { } #3 \q_mark
3844 }
3845 \cs_new:Npn \__cs_generate_variant_loop_base:N #1
3846 {
3847   \if:w c #1 N \else:
3848     \if:w o #1 n \else:
3849       \if:w V #1 n \else:
3850         \if:w v #1 n \else:
3851           \if:w f #1 n \else:
3852             \if:w e #1 n \else:
3853               \if:w x #1 n \else:
3854                 \if:w n #1 n \else:
3855                   \if:w N #1 N \else:

```



```

3856             \scan_stop:
3857             \fi:
3858             \fi:
3859             \fi:
3860             \fi:
3861             \fi:
3862             \fi:
3863             \fi:
3864             \fi:
3865             \fi:
3866         }
3867 \cs_new:Npn \__cs_generate_variant_loop_same:w
3868     #1 \prg_do_nothing: #2#3#4
3869     { #3 { #1 \__cs_generate_variant_same:N #2 } }
3870 \cs_new:Npn \__cs_generate_variant_loop_end:nwwwNNnn
3871     #1#2 \q_mark #3 ~ #4 \q_stop #5#6#7#8
3872     {
3873         \scan_stop: \scan_stop: \fi:
3874         \exp_not:N \q_mark
3875         \exp_not:N \q_stop
3876         \exp_not:N #6
3877         \exp_not:c { #7 : #8 #1 #3 }
3878     }
3879 \cs_new:Npn \__cs_generate_variant_loop_long:wNNnn #1 \q_stop #2#3#4#5
3880     {
3881         \exp_not:n
3882         {
3883             \q_mark
3884             \__kernel_msg_error:nxxx { kernel } { variant-too-long }
3885             {#5} { \token_to_str:N #3 }
3886             \use_none:nnn
3887             \q_stop
3888             #3
3889             #3
3890         }
3891     }
3892 \cs_new:Npn \__cs_generate_variant_loop_invalid:NNwNNnn
3893     #1#2 \fi: \fi: \fi: #3 \q_stop #4#5#6#7
3894     {
3895         \fi: \fi: \fi:
3896         \exp_not:n
3897         {
3898             \q_mark
3899             \__kernel_msg_error:nxxxx { kernel } { invalid-variant }
3900             {#7} { \token_to_str:N #5 } {#1} {#2}
3901             \use_none:nnn
3902             \q_stop
3903             #5
3904             #5
3905         }
3906     }
3907 \cs_new:Npn \__cs_generate_variant_loop_special:NNwNNnn
3908     #1#2#3 \q_stop #4#5#6#7
3909     {

```

```

3910     #3 \q_stop #4 #5 {#6} {#7}
3911     \exp_not:n
3912     {
3913         \__kernel_msg_error:nxxxxx
3914         { kernel } { deprecated-variant }
3915         {#7} { \token_to_str:N #5 } {#1} {#2}
3916     }
3917 }

```

(End definition for __cs_generate_variant_loop:nNwN and others.)

__cs_generate_variant_same:N When the base and variant letters are identical, don't do any expansion. For most argument types, we can use the n-type no-expansion, but the N and p types require a slightly different behaviour with respect to braces. For V-type this function could output N to avoid adding useless braces but that is not a problem.

```

3918 \cs_new:Npn \__cs_generate_variant_same:N #1
3919 {
3920     \if:w N #1 N \else:
3921     \if:w p #1 p \else:
3922         n
3923     \if:w n #1 \else:
3924         \__cs_generate_variant_loop_special:NNwNnn #1#1
3925     \fi:
3926     \fi:
3927     \fi:
3928 }

```

(End definition for __cs_generate_variant_same:N.)

__cs_generate_variant:wwNN If the variant form has already been defined, log its existence (provided log-functions is active). Otherwise, make sure that the \exp_args:N #3 form is defined, and if it contains x, change __cs_tmp:w locally to \cs_new_protected:Npx. Then define the variant by combining the \exp_args:N #3 variant and the base function.

```

3929 \__kernel_patch:nnNNpn
3930 {
3931     \cs_if_free:NF #4
3932     {
3933         \__kernel_debug_log:x
3934         {
3935             Variant~\token_to_str:N #4~%
3936             already~defined;~ not~ changing~ it~ \msg_line_context:
3937         }
3938     }
3939 }
3940 { }
3941 \cs_new_protected:Npn \__cs_generate_variant:wwNN
3942 #1 \q_mark #2 \q_stop #3#4
3943 {
3944     #2
3945     \cs_if_free:NT #4
3946     {
3947         \group_begin:
3948         \__cs_generate_internal_variant:n {#1}
3949         \__cs_tmp:w #4 { \exp_not:c { exp_args:N #1 } \exp_not:N #3 }

```

```

3950     \group_end:
3951   }
3952 }

```

(End definition for `_cs_generate_variant:wwNN`.)

```

\_cs_generate_internal_variant:n
\_cs_generate_internal_variant:wwnw
\_cs_generate_internal_variant_loop:n

```

Test if `\exp_args:N #1` is already defined and if not define it via the `\::` commands using the chars in `#1`. If `#1` contains an `x` (this is the place where having converted the original comma-list argument to a string is very important), the result should be protected, and the next variant to be defined using that internal variant should be protected.

```

3953 \cs_new_protected:Npx \_cs_generate_internal_variant:n #1
3954 {
3955   \exp_not:N \_cs_generate_internal_variant:wwnNwnn
3956   #1 \exp_not:N \q_mark
3957   { \cs_set_eq:NN \exp_not:N \_cs_tmp:w \cs_new_protected:Npx }
3958   \cs_new_protected:cpx
3959   \token_to_str:N x \exp_not:N \q_mark
3960   { }
3961   \cs_new:cpx
3962   \exp_not:N \q_stop
3963   { exp_args:N #1 }
3964   {
3965     \exp_not:N \_cs_generate_internal_variant_loop:n #1
3966     { : \exp_not:N \use_i:nn }
3967   }
3968 }
3969 \exp_last_unbraced:NNNNo
3970 \cs_new_protected:Npn \_cs_generate_internal_variant:wwnNwnn #1
3971 { \token_to_str:N x } #2 \q_mark #3#4#5 \q_stop #6#7
3972 {
3973   #3
3974   \cs_if_free:cT {#6} { #4 {#6} {#7} }
3975 }

```

This command grabs char by char outputting `\::#1` (not expanded further). We avoid tests by putting a trailing `: \use_i:nn`, which leaves `\cs_end:` and removes the looping macro. The colon is in fact also turned into `\:::` so that the required structure for `\exp_args:N...` commands is correctly terminated.

```

3976 \cs_new:Npn \_cs_generate_internal_variant_loop:n #1
3977 {
3978   \exp_after:wN \exp_not:N \cs:w :: #1 \cs_end:
3979   \_cs_generate_internal_variant_loop:n
3980 }

```

(End definition for `_cs_generate_internal_variant:n`, `_cs_generate_internal_variant:wwnw`, and `_cs_generate_internal_variant_loop:n`.)

```

\prg_generate_conditional_variant:Nnn
\_cs_generate_variant:nnNnn
\_cs_generate_variant:w
\_cs_generate_variant:n
\_cs_generate_variant_p_form:nnn
\_cs_generate_variant_T_form:nnn
\_cs_generate_variant_F_form:nnn
\_cs_generate_variant_TF_form:nnn

```

```

3981 \cs_new_protected:Npn \prg_generate_conditional_variant:Nnn #1
3982 {
3983   \use:x
3984   {
3985     \_cs_generate_variant:nnNnn
3986     \cs_split_function:N #1

```

```

3987     }
3988 }
3989 \cs_new_protected:Npn \__cs_generate_variant:nnNnn #1#2#3#4#5
3990 {
3991   \if_meaning:w \c_false_bool #3
3992     \__kernel_msg_error:nnx { kernel } { missing-colon }
3993     { \token_to_str:c {#1} }
3994     \use_i_delimit_by_q_stop:nw
3995   \fi:
3996   \exp_after:wN \__cs_generate_variant:w
3997   \tl_to_str:n {#5} , \scan_stop: , \q_recursion_stop
3998   \use_none_delimit_by_q_stop:w \q_mark {#1} {#2} {#4} \q_stop
3999 }
4000 \cs_new_protected:Npn \__cs_generate_variant:w
4001   #1 , #2 \q_mark #3#4#5
4002 {
4003   \if_meaning:w \scan_stop: #1 \scan_stop:
4004     \if_meaning:w \q_nil #1 \q_nil
4005     \use_i:nnn
4006   \fi:
4007   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
4008   \else:
4009     \cs_if_exist_use:ctF { __cs_generate_variant_#1_form:nnn }
4010     { {#3} {#4} {#5} }
4011     {
4012       \__kernel_msg_error:nnxx
4013       { kernel } { conditional-form-unknown }
4014       {#1} { \token_to_str:c { #3 : #4 } }
4015     }
4016   \fi:
4017   \__cs_generate_variant:w #2 \q_mark {#3} {#4} {#5}
4018 }
4019 \cs_new_protected:Npn \__cs_generate_variant_p_form:nnn #1#2
4020 { \cs_generate_variant:cn { #1 _p : #2 } }
4021 \cs_new_protected:Npn \__cs_generate_variant_T_form:nnn #1#2
4022 { \cs_generate_variant:cn { #1 : #2 T } }
4023 \cs_new_protected:Npn \__cs_generate_variant_F_form:nnn #1#2
4024 { \cs_generate_variant:cn { #1 : #2 F } }
4025 \cs_new_protected:Npn \__cs_generate_variant_TF_form:nnn #1#2
4026 { \cs_generate_variant:cn { #1 : #2 TF } }

```

(End definition for \prg_generate_conditional_variant:Nnn and others. This function is documented on page 242.)

`\exp_args_generate:n`
`__cs_args_generate:Nn`
`__cs_args_generate:n`

This function is not used in the kernel hence we can use functions that are defined in later modules. It also does not need to be fast so use inline mappings. For each requested variant we check that there are no characters besides NnpcofVvx, in particular that there are no spaces. Then we loop through the variant specifier and convert each letter to \::<variant letter>, with a trailing \::.

```

4027 \cs_new_protected:Npn \exp_args_generate:n #1
4028 {
4029   \exp_args:No \clist_map_inline:nn { \tl_to_str:n {#1} }
4030   {
4031     \str_map_inline:nn {#1}

```

```

4032     {
4033       \str_if_in:nnF { NnpcofVvx } {####1}
4034       {
4035         \__kernel_msg_error:nnnn { kernel } { invalid-exp-args }
4036         {####1} {##1}
4037         \str_map_break:n { \use_none:nnnn }
4038       }
4039     }
4040     \exp_args:Nc \__cs_args_generate:Nn { exp_args:N ##1 } {##1}
4041   }
4042 }
4043 \cs_new_protected:Npn \__cs_args_generate:Nn #1#2
4044 {
4045   \cs_if_exist:NF #1
4046   {
4047     \str_if_in:nnTF {#2} { x } { \cs_new_protected:Npx } { \cs_new:Npx }
4048     #1 { \tl_map_function:nN { #2 : } \__cs_args_generate:n }
4049   }
4050 }
4051 \cs_new:Npn \__cs_args_generate:n #1 { \exp_not:c { :: #1 } }

```

(End definition for `\exp_args_generate:n`, `__cs_args_generate:Nn`, and `__cs_args_generate:n`. This function is documented on page [242](#).)

```

4052 </initex | package>

```

6 l3tl implementation

```

4053 <*initex | package>
4054 <@@=tl>

```

A token list variable is a $\text{T}_{\text{E}}\text{X}$ macro that holds tokens. By using the $\varepsilon\text{-T}_{\text{E}}\text{X}$ primitive `\unexpanded` inside a $\text{T}_{\text{E}}\text{X}$ `\edef` it is possible to store any tokens, including `#`, in this way.

6.1 Functions

`\tl_new:N` Creating new token list variables is a case of checking for an existing definition and doing the definition.

```

\tl_new:c
4055 \cs_new_protected:Npn \tl_new:N #1
4056 {
4057   \__kernel_chk_if_free_cs:N #1
4058   \cs_gset_eq:NN #1 \c_empty_tl
4059 }
4060 \cs_generate_variant:Nn \tl_new:N { c }

```

(End definition for `\tl_new:N`. This function is documented on page [35](#).)

`\tl_const:Nn` Constants are also easy to generate.

```

\tl_const:Nx
\tl_const:cn
\tl_const:cx
4061 \__kernel_patch:nnNpn { \__kernel_chk_var_scope:NN c #1 } { }
4062 \cs_new_protected:Npn \tl_const:Nn #1#2
4063 {
4064   \__kernel_chk_if_free_cs:N #1
4065   \cs_gset_nopar:Npx #1 { \exp_not:n {#2} }
4066 }

```

```

4067 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN c #1 } { }
4068 \cs_new_protected:Npn \tl_const:Nx #1#2
4069 {
4070     \__kernel_chk_if_free_cs:N #1
4071     \cs_gset_nopar:Npx #1 {#2}
4072 }
4073 \cs_generate_variant:Nn \tl_const:Nn { c }
4074 \cs_generate_variant:Nn \tl_const:Nx { c }

```

(End definition for `\tl_const:Nn`. This function is documented on page 35.)

\tl_clear:N Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

```

\tl_clear:c
\tl_gclear:N
\tl_gclear:c
4075 \cs_new_protected:Npn \tl_clear:N #1
4076 { \tl_set_eq:NN #1 \c_empty_tl }
4077 \cs_new_protected:Npn \tl_gclear:N #1
4078 { \tl_gset_eq:NN #1 \c_empty_tl }
4079 \cs_generate_variant:Nn \tl_clear:N { c }
4080 \cs_generate_variant:Nn \tl_gclear:N { c }

```

(End definition for `\tl_clear:N` and `\tl_gclear:N`. These functions are documented on page 35.)

\tl_clear_new:N Clearing a token list variable means setting it to an empty value. Error checking is sorted out by the parent function.

```

\tl_clear_new:c
\tl_gclear_new:N
\tl_gclear_new:c
4081 \cs_new_protected:Npn \tl_clear_new:N #1
4082 { \tl_if_exist:NTF #1 { \tl_clear:N #1 } { \tl_new:N #1 } }
4083 \cs_new_protected:Npn \tl_gclear_new:N #1
4084 { \tl_if_exist:NTF #1 { \tl_gclear:N #1 } { \tl_new:N #1 } }
4085 \cs_generate_variant:Nn \tl_clear_new:N { c }
4086 \cs_generate_variant:Nn \tl_gclear_new:N { c }

```

(End definition for `\tl_clear_new:N` and `\tl_gclear_new:N`. These functions are documented on page 36.)

\tl_set_eq:NN For setting token list variables equal to each other. When checking is turned on, make sure both variables exist.

```

\tl_set_eq:Nc
\tl_set_eq:cN
\tl_set_eq:cc
4087 \__kernel_if_debug:TF
4088 {
4089     \cs_new_protected:Npn \tl_set_eq:NN #1#2
4090     {
4091         \__kernel_chk_var_local:N #1
4092         \__kernel_chk_var_exist:N #2
4093         \cs_set_eq:NN #1 #2
4094     }
4095     \cs_new_protected:Npn \tl_gset_eq:NN #1#2
4096     {
4097         \__kernel_chk_var_global:N #1
4098         \__kernel_chk_var_exist:N #2
4099         \cs_gset_eq:NN #1 #2
4100     }
4101 }
4102 {
4103     \cs_new_eq:NN \tl_set_eq:NN \cs_set_eq:NN
4104     \cs_new_eq:NN \tl_gset_eq:NN \cs_gset_eq:NN
4105 }

```

```

4106 \cs_generate_variant:Nn \tl_set_eq:NN { cN, Nc, cc }
4107 \cs_generate_variant:Nn \tl_gset_eq:NN { cN, Nc, cc }

```

(End definition for `\tl_set_eq:NN` and `\tl_gset_eq:NN`. These functions are documented on page 36.)

`\tl_concat:NNN` Concatenating token lists is easy. When checking is turned on, all three arguments must be checked: a token list #2 or #3 equal to `\scan_stop:` would lead to problems later on.

```

\l_tl_concat:ccc
\l_tl_gconcat:NNN
4108 \__kernel_patch:nnNNpn
4109 {
4110   \__kernel_chk_var_exist:N #2
4111   \__kernel_chk_var_exist:N #3
4112 }
4113 { }
4114 \cs_new_protected:Npn \tl_concat:NNN #1#2#3
4115 { \tl_set:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
4116 \__kernel_patch:nnNNpn
4117 {
4118   \__kernel_chk_var_exist:N #2
4119   \__kernel_chk_var_exist:N #3
4120 }
4121 { }
4122 \cs_new_protected:Npn \tl_gconcat:NNN #1#2#3
4123 { \tl_gset:Nx #1 { \exp_not:o {#2} \exp_not:o {#3} } }
4124 \cs_generate_variant:Nn \tl_concat:NNN { ccc }
4125 \cs_generate_variant:Nn \tl_gconcat:NNN { ccc }

```

(End definition for `\tl_concat:NNN` and `\tl_gconcat:NNN`. These functions are documented on page 36.)

`\tl_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

```

\l_tl_if_exist_p:c
\l_tl_if_exist:NTF
\l_tl_if_exist:cTF
4126 \prg_new_eq_conditional:NNn \tl_if_exist:N \cs_if_exist:N { TF , T , F , p }
4127 \prg_new_eq_conditional:NNn \tl_if_exist:c \cs_if_exist:c { TF , T , F , p }

```

(End definition for `\tl_if_exist:NTF`. This function is documented on page 36.)

6.2 Constant token lists

`\c_empty_tl` Never full. We need to define that constant before using `\tl_new:N`.

```

4128 \tl_const:Nn \c_empty_tl { }

```

(End definition for `\c_empty_tl`. This variable is documented on page 49.)

`\c_novalue_tl` A special marker: as we don't have `\char_generate:nn` yet, has to be created the old-fashioned way.

```

4129 \group_begin:
4130 \tex_lccode:D 'A = '-
4131 \tex_lccode:D 'N = 'N
4132 \tex_lccode:D 'V = 'V
4133 \tex_lowercase:D
4134 {
4135   \group_end:
4136   \tl_const:Nn \c_novalue_tl { ANoValue- }
4137 }

```

(End definition for `\c_novalue_tl`. This variable is documented on page 49.)

\c_space_tl A space as a token list (as opposed to as a character).

```
4138 \tl_const:Nn \c_space_tl { ~ }
```

(End definition for \c_space_tl. This variable is documented on page 49.)

6.3 Adding to token list variables

\tl_set:Nn By using \exp_not:n token list variables can contain # tokens, which makes the token list registers provided by T_EX more or less redundant. The \tl_set:No version is done “by hand” as it is used quite a lot. Each definition is prefixed by a call to __kernel_patch:nnNNpn which adds an existence check to the definition.

```
4139 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4140 \cs_new_protected:Npn \tl_set:Nn #1#2
4141 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} } }
4142 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4143 \cs_new_protected:Npn \tl_set:No #1#2
4144 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} } }
4145 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4146 \cs_new_protected:Npn \tl_set:Nx #1#2
4147 { \cs_set_nopar:Npx #1 {#2} }
4148 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4149 \cs_new_protected:Npn \tl_gset:Nn #1#2
4150 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} } }
4151 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4152 \cs_new_protected:Npn \tl_gset:No #1#2
4153 { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} } }
4154 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4155 \cs_new_protected:Npn \tl_gset:Nx #1#2
4156 { \cs_gset_nopar:Npx #1 {#2} }
4157 \cs_generate_variant:Nn \tl_set:Nn { NV , Nv , Nf }
4158 \cs_generate_variant:Nn \tl_set:Nx { c }
4159 \cs_generate_variant:Nn \tl_set:Nn { c , co , cV , cv , cf }
4160 \cs_generate_variant:Nn \tl_gset:Nn { NV , Nv , Nf }
4161 \cs_generate_variant:Nn \tl_gset:Nx { c }
4162 \cs_generate_variant:Nn \tl_gset:Nn { c , co , cV , cv , cf }
```

(End definition for \tl_set:Nn and \tl_gset:Nn. These functions are documented on page 36.)

\tl_put_left:Nn Adding to the left is done directly to gain a little performance.

```
4163 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4164 \cs_new_protected:Npn \tl_put_left:Nn #1#2
4165 { \cs_set_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
4166 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4167 \cs_new_protected:Npn \tl_put_left:Nv #1#2
4168 { \cs_set_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
4169 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4170 \cs_new_protected:Npn \tl_put_left:No #1#2
4171 { \cs_set_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
4172 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
4173 \cs_new_protected:Npn \tl_put_left:Nx #1#2
4174 { \cs_set_nopar:Npx #1 { #2 \exp_not:o #1 } }
4175 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4176 \cs_new_protected:Npn \tl_gput_left:Nn #1#2
4177 { \cs_gset_nopar:Npx #1 { \exp_not:n {#2} \exp_not:o #1 } }
```



```

4178 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4179 \cs_new_protected:Npn \tl_gput_left:NV #1#2
4180   { \cs_gset_nopar:Npx #1 { \exp_not:V #2 \exp_not:o #1 } }
4181 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4182 \cs_new_protected:Npn \tl_gput_left:No #1#2
4183   { \cs_gset_nopar:Npx #1 { \exp_not:o {#2} \exp_not:o #1 } }
4184 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4185 \cs_new_protected:Npn \tl_gput_left:Nx #1#2
4186   { \cs_gset_nopar:Npx #1 { #2 \exp_not:o {#1} } }
4187 \cs_generate_variant:Nn \tl_put_left:Nn { c }
4188 \cs_generate_variant:Nn \tl_put_left:NV { c }
4189 \cs_generate_variant:Nn \tl_put_left:No { c }
4190 \cs_generate_variant:Nn \tl_put_left:Nx { c }
4191 \cs_generate_variant:Nn \tl_gput_left:Nn { c }
4192 \cs_generate_variant:Nn \tl_gput_left:NV { c }
4193 \cs_generate_variant:Nn \tl_gput_left:No { c }
4194 \cs_generate_variant:Nn \tl_gput_left:Nx { c }

```

(End definition for `\tl_put_left:Nn` and `\tl_gput_left:Nn`. These functions are documented on page 36.)

`\tl_put_right:Nn`

The same on the right.

```

\tl_put_right:NV 4195 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\tl_put_right:No 4196 \cs_new_protected:Npn \tl_put_right:Nn #1#2
\tl_put_right:Nx 4197   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
\tl_put_right:cn 4198 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\tl_put_right:cV 4199 \cs_new_protected:Npn \tl_put_right:NV #1#2
\tl_put_right:co 4200   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
\tl_put_right:cx 4201 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\tl_gput_right:Nn 4202 \cs_new_protected:Npn \tl_put_right:No #1#2
\tl_gput_right:NV 4203   { \cs_set_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
\tl_gput_right:No 4204 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\tl_gput_right:Nx 4205 \cs_new_protected:Npn \tl_put_right:Nx #1#2
\tl_gput_right:cn 4206   { \cs_set_nopar:Npx #1 { \exp_not:o #1 #2 } }
\tl_gput_right:cV 4207 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
\tl_gput_right:co 4208 \cs_new_protected:Npn \tl_gput_right:Nn #1#2
\tl_gput_right:cx 4209   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:n {#2} } }
4210 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4211 \cs_new_protected:Npn \tl_gput_right:NV #1#2
4212   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:V #2 } }
4213 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4214 \cs_new_protected:Npn \tl_gput_right:No #1#2
4215   { \cs_gset_nopar:Npx #1 { \exp_not:o #1 \exp_not:o {#2} } }
4216 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
4217 \cs_new_protected:Npn \tl_gput_right:Nx #1#2
4218   { \cs_gset_nopar:Npx #1 { \exp_not:o {#1} #2 } }
4219 \cs_generate_variant:Nn \tl_put_right:Nn { c }
4220 \cs_generate_variant:Nn \tl_put_right:NV { c }
4221 \cs_generate_variant:Nn \tl_put_right:No { c }
4222 \cs_generate_variant:Nn \tl_put_right:Nx { c }
4223 \cs_generate_variant:Nn \tl_gput_right:Nn { c }
4224 \cs_generate_variant:Nn \tl_gput_right:NV { c }
4225 \cs_generate_variant:Nn \tl_gput_right:No { c }
4226 \cs_generate_variant:Nn \tl_gput_right:Nx { c }

```

(End definition for `\tl_put_right:Nn` and `\tl_gput_right:Nn`. These functions are documented on page 36.)

6.4 Reassigning token list category codes

`\c__tl_rescan_marker_tl`

The rescanning code needs a special token list containing the same character (chosen here to be a colon) with two different category codes: it cannot appear in the tokens being rescanned since all colons have the same category code.

```
4227 \tl_const:Nx \c__tl_rescan_marker_tl { : \token_to_str:N : }
```

(End definition for `\c__tl_rescan_marker_tl`.)

```
\tl_set_rescan:Nnn
\tl_set_rescan:Nno
\tl_set_rescan:Nnx
\tl_set_rescan:cnn
\tl_set_rescan:cno
\tl_set_rescan:cnx
\tl_gset_rescan:Nnn
\tl_gset_rescan:Nno
\tl_gset_rescan:Nnx
\tl_gset_rescan:cnn
\tl_gset_rescan:cno
\tl_gset_rescan:cnx
\tl_rescan:nn
  \__tl_set_rescan:NNnn
  \__tl_set_rescan_multi:n
    \__tl_rescan:w
```

These functions use a common auxiliary. After some initial setup explained below, and the user setup #3 (followed by `\scan_stop:` to be safe), the tokens are rescanned by `__tl_set_rescan:n` and stored into `\l__tl_internal_a_tl`, then passed to #1#2 outside the group after expansion. The auxiliary `__tl_set_rescan:n` is defined later: in the simplest case, this auxiliary calls `__tl_set_rescan_multi:n`, whose code is included here to help understand the approach.

One difficulty when rescanning is that `\scantokens` treats the argument as a file, and without the correct settings a TeX error occurs:

```
! File ended while scanning definition of ...
```

The standard solution is to use an x-expanding assignment and set `\everyeof` to `\exp_not:N` to suppress the error at the end of the file. Since the rescanned tokens should not be expanded, they are taken as a delimited argument of an auxiliary which wraps them in `\exp_not:n` (in fact `\exp_not:o`, as there is a `\prg_do_nothing:` to avoid losing braces). The delimiter cannot appear within the rescanned token list because it contains twice the same character, with different catcodes.

The difference between single-line and multiple-line files complicates the story, as explained below.

```
4228 \cs_new_protected:Npn \tl_set_rescan:Nnn
4229   { \__tl_set_rescan:NNnn \tl_set:Nn }
4230 \cs_new_protected:Npn \tl_gset_rescan:Nnn
4231   { \__tl_set_rescan:NNnn \tl_gset:Nn }
4232 \cs_new_protected:Npn \tl_rescan:nn
4233   { \__tl_set_rescan:NNnn \prg_do_nothing: \use:n }
4234 \cs_new_protected:Npn \__tl_set_rescan:NNnn #1#2#3#4
4235   {
4236     \tl_if_empty:nTF {#4}
4237     {
4238       \group_begin:
4239         #3
4240       \group_end:
4241       #1 #2 { }
4242     }
4243     {
4244       \group_begin:
4245       \exp_args:No \tex_everyeof:D
4246       { \c__tl_rescan_marker_tl \exp_not:N }
4247       \int_compare:nNnT \tex_endlinechar:D = { 32 }
4248       { \int_set:Nn \tex_endlinechar:D { -1 } }
4249       \tex_newlinechar:D \tex_endlinechar:D
```

```

4250         #3 \scan_stop:
4251         \exp_args:No \__tl_set_rescan:n { \tl_to_str:n {#4} }
4252         \exp_args:NNo
4253         \group_end:
4254         #1 #2 \l__tl_internal_a_tl
4255     }
4256 }
4257 \cs_new_protected:Npn \__tl_set_rescan_multi:n #1
4258 {
4259     \tl_set:Nx \l__tl_internal_a_tl
4260     {
4261         \exp_after:wN \__tl_rescan:w
4262         \exp_after:wN \prg_do_nothing:
4263         \tex_scantokens:D {#1}
4264     }
4265 }
4266 \exp_args:Nno \use:nn
4267 { \cs_new:Npn \__tl_rescan:w #1 } \c__tl_rescan_marker_tl
4268 { \exp_not:o {#1} }
4269 \cs_generate_variant:Nn \tl_set_rescan:Nnn { Nno , Nnx }
4270 \cs_generate_variant:Nn \tl_set_rescan:Nnn { c , cno , cnx }
4271 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { Nno , Nnx }
4272 \cs_generate_variant:Nn \tl_gset_rescan:Nnn { c , cno }

```

(End definition for `\tl_set_rescan:Nnn` and others. These functions are documented on page 38.)

```

\__tl_set_rescan:n
\__tl_set_rescan:NnTF
\__tl_set_rescan_single:nn
\__tl_set_rescan_single_aux:nn

```

This function calls `__tl_set_rescan_multiple:n` or `__tl_set_rescan_single:nn` { ' } depending on whether its argument is a single-line fragment of code/data or is made of multiple lines by testing for the presence of a `\newlinechar` character. If `\newlinechar` is out of range, the argument is assumed to be a single line.

The case of multiple lines is a straightforward application of `\scantokens` as described above. The only subtlety is that `\newlinechar` should be equal to `\endlinechar` because `\newlinechar` characters become new lines and then become `\endlinechar` characters when writing to an abstract file and reading back. This equality is ensured by setting `\newlinechar` equal to `\endlinechar`. Prior to this, `\endlinechar` is set to -1 if it was 32 (in particular true after `\ExplSyntaxOn`) to avoid unreasonable line-breaks at every space for instance in error messages triggered by the user setup. Another side effect of reading back from the file is that spaces (catcode 10) are ignored at the beginning of lines, and spaces and tabs (character code 32 and 9) are ignored at the end of lines.

For a single line, no `\endlinechar` should be added, so it is set to -1, and spaces should not be removed.

Trailing spaces and tabs are a difficult matter, as `TeX` removes these at a very low level. The only way to preserve them is to rescan not the argument but the argument followed by a character with a reasonable category code. Here, 11 (letter), 12 (other) and 13 (active) are accepted, as these are suitable for delimiting an argument, and it is very unlikely that none of the ASCII characters are in one of these categories. To avoid selecting one particular character to put at the end, whose category code may have been modified, there is a loop through characters from ' (ASCII 39) to ~ (ASCII 127). The choice of starting point was made because this is the start of a very long range of characters whose standard category is letter or other, thus minimizing the number of steps needed by the loop (most often just a single one). Once a valid character is

found, run some code very similar to `__tl_set_rescan_multi:n`, except that `__tl_rescan:w` must be redefined to also remove the additional character (with the appropriate catcode). Getting the delimiter with the right catcode requires using `\scantokens` inside an `x`-expansion, hence using the previous definition of `__tl_rescan:w` as well. The odd `\exp_not:N \use:n` ensures that the trailing `\exp_not:N` in `\everyeof` does not prevent the expansion of `\c__tl_rescan_marker_tl`, but rather of a closing brace (this does nothing). If no valid character is found, similar code is ran, and the only difference is that trailing spaces are not preserved (bear in mind that this only happens if no character between 39 and 127 has catcode letter, other or active).

There is also some work to preserve leading spaces: test whether the first character (given by `\str_head:n`, with an extra space to circumvent a limitation of `f`-expansion) has catcode 10 and add what `TEX` would add in the middle of a line for any sequence of such characters: a single space with catcode 10 and character code 32.

```

4273 \group_begin:
4274   \tex_catcode:D '\^~@ = 12 \scan_stop:
4275   \cs_new_protected:Npn \__tl_set_rescan:n #1
4276   {
4277     \int_compare:nNnTF \tex_newlinechar:D < 0
4278     { \use_ii:nn }
4279     {
4280       \char_set_lccode:nn { 0 } { \tex_newlinechar:D }
4281       \tex_lowercase:D { \__tl_set_rescan:NnTF ^~@ } {#1}
4282     }
4283     { \__tl_set_rescan_multi:n }
4284     { \__tl_set_rescan_single:nn { ' } }
4285   {#1}
4286 }
4287 \cs_new_protected:Npn \__tl_set_rescan:NnTF #1#2
4288 { \tl_if_in:nnTF {#2} {#1} }
4289 \cs_new_protected:Npn \__tl_set_rescan_single:nn #1
4290 {
4291   \int_compare:nNnTF
4292   { \char_value_catcode:n { '#1 } / 3 } = 4
4293   { \__tl_set_rescan_single_aux:nn {#1} }
4294   {
4295     \int_compare:nNnTF { '#1 } < { '\~ }
4296     {
4297       \char_set_lccode:nn { 0 } { '#1 + 1 }
4298       \tex_lowercase:D { \__tl_set_rescan_single:nn { ^~@ } }
4299     }
4300     { \__tl_set_rescan_single_aux:nn { } }
4301   }
4302 }
4303 \cs_new_protected:Npn \__tl_set_rescan_single_aux:nn #1#2
4304 {
4305   \int_set:Nn \tex_endlinechar:D { -1 }
4306   \use:x
4307   {
4308     \exp_not:N \use:n
4309     {
4310       \exp_not:n { \cs_set:Npn \__tl_rescan:w ##1 }
4311       \exp_after:wN \__tl_rescan:w
4312       \exp_after:wN \prg_do_nothing:

```

```

4313         \tex_scantokens:D {#1}
4314     }
4315     \c__tl_rescan_marker_tl
4316 }
4317 { \exp_not:o {##1} }
4318 \tl_set:Nx \l__tl_internal_a_tl
4319 {
4320     \int_compare:nNnT
4321     {
4322         \char_value_catcode:n
4323         { \exp_last_unbraced:Nf ‘ { \str_head:n {#2} } ~ }
4324     }
4325     = { 10 } { ~ }
4326     \exp_after:wN \__tl_rescan:w
4327     \exp_after:wN \prg_do_nothing:
4328     \tex_scantokens:D { #2 #1 }
4329 }
4330 }
4331 \group_end:

```

(End definition for `__tl_set_rescan:n` and others.)

6.5 Modifying token list variables

`\tl_replace_all:Nnn` All of the replace functions call `__tl_replace:NnnNnn` with appropriate arguments. The first two arguments are explained later. The next controls whether the replacement function calls itself (`__tl_replace_next:w`) or stops (`__tl_replace_wrap:w`) after the first replacement. Next comes an x-type assignment function `\tl_set:Nx` or `\tl_gset:Nx` for local or global replacements. Finally, the three arguments $\langle tl\ var \rangle$ $\{ \langle pattern \rangle \}$ $\{ \langle replacement \rangle \}$ provided by the user. When describing the auxiliary functions below, we denote the contents of the $\langle tl\ var \rangle$ by $\langle token\ list \rangle$.

```

\tl_replace_all:Nnn
\tl_replace_all:cnn
\tl_greplace_all:Nnn
\tl_greplace_all:cnn
\tl_replace_once:Nnn
\tl_replace_once:cnn
\tl_greplace_once:Nnn
\tl_greplace_once:cnn
4332 \cs_new_protected:Npn \tl_replace_once:Nnn
4333 { \__tl_replace:NnnNnn \q_mark ? \__tl_replace_wrap:w \tl_set:Nx }
4334 \cs_new_protected:Npn \tl_greplace_once:Nnn
4335 { \__tl_replace:NnnNnn \q_mark ? \__tl_replace_wrap:w \tl_gset:Nx }
4336 \cs_new_protected:Npn \tl_replace_all:Nnn
4337 { \__tl_replace:NnnNnn \q_mark ? \__tl_replace_next:w \tl_set:Nx }
4338 \cs_new_protected:Npn \tl_greplace_all:Nnn
4339 { \__tl_replace:NnnNnn \q_mark ? \__tl_replace_next:w \tl_gset:Nx }
4340 \cs_generate_variant:Nn \tl_replace_once:Nnn { c }
4341 \cs_generate_variant:Nn \tl_greplace_once:Nnn { c }
4342 \cs_generate_variant:Nn \tl_replace_all:Nnn { c }
4343 \cs_generate_variant:Nn \tl_greplace_all:Nnn { c }

```

(End definition for `\tl_replace_all:Nnn` and others. These functions are documented on page 37.)

`__tl_replace:NnnNnn` To implement the actual replacement auxiliary `__tl_replace_auxii:NnnNnn` we need a $\langle delimiter \rangle$ with the following properties:

- all occurrences of the $\langle pattern \rangle$ #6 in “ $\langle token\ list \rangle$ $\langle delimiter \rangle$ ” belong to the $\langle token\ list \rangle$ and have no overlap with the $\langle delimiter \rangle$,
- the first occurrence of the $\langle delimiter \rangle$ in “ $\langle token\ list \rangle$ $\langle delimiter \rangle$ ” is the trailing $\langle delimiter \rangle$.

We first find the building blocks for the $\langle \text{delimiter} \rangle$, namely two tokens $\langle A \rangle$ and $\langle B \rangle$ such that $\langle A \rangle$ does not appear in $\#6$ and $\#6$ is not $\langle B \rangle$ (this condition is trivial if $\#6$ has more than one token). Then we consider the delimiters “ $\langle A \rangle$ ” and “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ”, for $n \geq 1$, where $\langle A \rangle^n$ denotes n copies of $\langle A \rangle$, and we choose as our $\langle \text{delimiter} \rangle$ the first one which is not in the $\langle \text{token list} \rangle$.

Every delimiter in the set obeys the first condition: $\#6$ does not contain $\langle A \rangle$ hence cannot be overlapping with the $\langle \text{token list} \rangle$ and the $\langle \text{delimiter} \rangle$, and it cannot be within the $\langle \text{delimiter} \rangle$ since it would have to be in one of the two $\langle B \rangle$ hence be equal to this single token (or empty, but this is an error case filtered separately). Given the particular form of these delimiters, for which no prefix is also a suffix, the second condition is actually a consequence of the weaker condition that the $\langle \text{delimiter} \rangle$ we choose does not appear in the $\langle \text{token list} \rangle$. Additionally, the set of delimiters is such that a $\langle \text{token list} \rangle$ of n tokens can contain at most $O(n^{1/2})$ of them, hence we find a $\langle \text{delimiter} \rangle$ with at most $O(n^{1/2})$ tokens in a time at most $O(n^{3/2})$. Bear in mind that these upper bounds are reached only in very contrived scenarios: we include the case “ $\langle A \rangle$ ” in the list of delimiters to try, so that the $\langle \text{delimiter} \rangle$ is simply $\backslash \text{q_mark}$ in the most common situation where neither the $\langle \text{token list} \rangle$ nor the $\langle \text{pattern} \rangle$ contains $\backslash \text{q_mark}$.

Let us now ahead, optimizing for this most common case. First, two special cases: an empty $\langle \text{pattern} \rangle$ $\#6$ is an error, and if $\#1$ is absent from both the $\langle \text{token list} \rangle$ $\#5$ and the $\langle \text{pattern} \rangle$ $\#6$ then we can use it as the $\langle \text{delimiter} \rangle$ through $\backslash _ \text{tl_replace_auxii:nNNNnn} \{ \#1 \}$. Otherwise, we end up calling $\backslash _ \text{tl_replace:NnNNNnn}$ repeatedly with the first two arguments $\backslash \text{q_mark} \{ ? \}$, $\backslash ? \{ ?? \}$, $\backslash ?? \{ ??? \}$, and so on, until $\#6$ does not contain the control sequence $\#1$, which we take as our $\langle A \rangle$. The argument $\#2$ only serves to collect $?$ characters for $\#1$. Note that the order of the tests means that the first two are done every time, which is wasteful (for instance, we repeatedly test for the emptiness of $\#6$). However, this is rare enough not to matter. Finally, choose $\langle B \rangle$ to be $\backslash \text{q_nil}$ or $\backslash \text{q_stop}$ such that it is not equal to $\#6$.

The $\backslash _ \text{tl_replace_auxi:NnnNNNnn}$ auxiliary receives $\{ \langle A \rangle \}$ and $\{ \langle A \rangle^n \langle B \rangle \}$ as its arguments, initially with $n = 1$. If “ $\langle A \rangle \langle A \rangle^n \langle B \rangle \langle A \rangle^n \langle B \rangle$ ” is in the $\langle \text{token list} \rangle$ then increase n and try again. Once it is not anymore in the $\langle \text{token list} \rangle$ we take it as our $\langle \text{delimiter} \rangle$ and pass this to the auxii auxiliary.

```

4344 \cs_new_protected:Npn \_tl_replace:NnNNNnn #1#2#3#4#5#6#7
4345 {
4346   \tl_if_empty:nTF {#6}
4347   {
4348     \_kernel_msg_error:nxx { kernel } { empty-search-pattern }
4349     { \tl_to_str:n {#7} }
4350   }
4351   {
4352     \tl_if_in:onTF { #5 #6 } {#1}
4353     {
4354       \tl_if_in:nnTF {#6} {#1}
4355       { \exp_args:Nc \_tl_replace:NnNNNnn {#2} {#2?} }
4356       {
4357         \quark_if_nil:nTF {#6}
4358         { \_tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_stop } }
4359         { \_tl_replace_auxi:NnnNNNnn #5 {#1} { #1 \q_nil } }
4360       }
4361     }
4362     { \_tl_replace_auxii:nNNNnn {#1} }
4363     #3#4#5 {#6} {#7}

```

```

4364     }
4365   }
4366   \cs_new_protected:Npn \__tl_replace_auxi:NnnNNNnn #1#2#3
4367   {
4368     \tl_if_in:NnTF #1 { #2 #3 #3 }
4369     { \__tl_replace_auxi:NnnNNNnn #1 { #2 #3 } {#2} }
4370     { \__tl_replace_auxii:nNNNnn { #2 #3 #3 } }
4371   }

```

The auxiliary `__tl_replace_auxii:nNNNnn` receives the following arguments:

```

{<delimiter>} <function> <assignment>
<tl var> {<pattern>} {<replacement>}

```

All of its work is done between `\group_align_safe_begin:` and `\group_align_safe_end:` to avoid issues in alignments. It does the actual replacement within `#3 #4 {...}`, an x-expanding `<assignment>` `#3` to the `<tl var>` `#4`. The auxiliary `__tl_replace_next:w` is called, followed by the `<token list>`, some tokens including the `<delimiter>` `#1`, followed by the `<pattern>` `#5`. This auxiliary finds an argument delimited by `#5` (the presence of a trailing `#5` avoids runaway arguments) and calls `__tl_replace_wrap:w` to test whether this `#5` is found within the `<token list>` or is the trailing one.

If on the one hand it is found within the `<token list>`, then `##1` cannot contain the `<delimiter>` `#1` that we worked so hard to obtain, thus `__tl_replace_wrap:w` gets `##1` as its own argument `##1`, and protects it against the x-expanding assignment. It also finds `\exp_not:n` as `##2` and does nothing to it, thus letting through `\exp_not:n {<replacement>}` into the assignment. Note that `__tl_replace_next:w` and `__tl_replace_wrap:w` are always called followed by two empty brace groups. These are safe because no delimiter can match them. They prevent losing braces when grabbing delimited arguments, but require the use of `\exp_not:o` and `\use_none:nn`, rather than simply `\exp_not:n`. Afterwards, `__tl_replace_next:w` is called to repeat the replacement, or `__tl_replace_wrap:w` if we only want a single replacement. In this second case, `##1` is the `<remaining tokens>` in the `<token list>` and `##2` is some `<ending code>` which ends the assignment and removes the trailing tokens `#5` using some `\if_false: { \fi: }` trickery because `#5` may contain any delimiter.

If on the other hand the argument `##1` of `__tl_replace_next:w` is delimited by the trailing `<pattern>` `#5`, then `##1` is “`{ } { } <token list> <delimiter> {<ending code>}`”, hence `__tl_replace_wrap:w` finds “`{ } { } <token list>`” as `##1` and the `<ending code>` as `##2`. It leaves the `<token list>` into the assignment and unbraces the `<ending code>` which removes what remains (essentially the `<delimiter>` and `<replacement>`).

```

4372 \cs_new_protected:Npn \__tl_replace_auxii:nNNNnn #1#2#3#4#5#6
4373 {
4374   \group_align_safe_begin:
4375   \cs_set:Npn \__tl_replace_wrap:w ##1 #1 ##2
4376   { \exp_not:o { \use_none:nn ##1 } ##2 }
4377   \cs_set:Npx \__tl_replace_next:w ##1 #5
4378   {
4379     \exp_not:N \__tl_replace_wrap:w ##1
4380     \exp_not:n { #1 }
4381     \exp_not:n { \exp_not:n {#6} }
4382     \exp_not:n { #2 { } { } }
4383   }
4384   #3 #4
4385   {

```

```

4386 \exp_after:wN \_tl_replace_next:w
4387 \exp_after:wN { \exp_after:wN }
4388 \exp_after:wN { \exp_after:wN }
4389 #4
4390 #1
4391 {
4392 \if_false: { \fi: }
4393 \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
4394 }
4395 #5
4396 }
4397 \group_align_safe_end:
4398 }
4399 \cs_new_eq:NN \_tl_replace_wrap:w ?
4400 \cs_new_eq:NN \_tl_replace_next:w ?

```

(End definition for `_tl_replace:NnNNNnn` and others.)

```

\tl_remove_once:Nn Removal is just a special case of replacement.
\tl_remove_once:cn 4401 \cs_new_protected:Npn \tl_remove_once:Nn #1#2
\tl_gremove_once:Nn 4402 { \tl_replace_once:Nnn #1 {#2} { } }
\tl_gremove_once:cn 4403 \cs_new_protected:Npn \tl_gremove_once:Nn #1#2
4404 { \tl_greplace_once:Nnn #1 {#2} { } }
4405 \cs_generate_variant:Nn \tl_remove_once:Nn { c }
4406 \cs_generate_variant:Nn \tl_gremove_once:Nn { c }

```

(End definition for `\tl_remove_once:Nn` and `\tl_gremove_once:Nn`. These functions are documented on page 37.)

```

\tl_remove_all:Nn Removal is just a special case of replacement.
\tl_remove_all:cn 4407 \cs_new_protected:Npn \tl_remove_all:Nn #1#2
\tl_gremove_all:Nn 4408 { \tl_replace_all:Nnn #1 {#2} { } }
\tl_gremove_all:cn 4409 \cs_new_protected:Npn \tl_gremove_all:Nn #1#2
4410 { \tl_greplace_all:Nnn #1 {#2} { } }
4411 \cs_generate_variant:Nn \tl_remove_all:Nn { c }
4412 \cs_generate_variant:Nn \tl_gremove_all:Nn { c }

```

(End definition for `\tl_remove_all:Nn` and `\tl_gremove_all:Nn`. These functions are documented on page 37.)

6.6 Token list conditionals

```

\tl_if_blank_p:n TeX skips spaces when reading a non-delimited arguments. Thus, a <token list> is blank
\tl_if_blank_p:V if and only if \use_none:n <token list> ? is empty after one expansion. The auxiliary
\tl_if_blank_p:o \_tl_if_empty_if:o is a fast emptyness test, converting its argument to a string (after
\tl_if_blank:nTF one expansion) and using the test \if_meaning:w \q_nil ... \q_nil.
\tl_if_blank:VTF 4413 \prg_new_conditional:Npnn \tl_if_blank:n #1 { p , T , F , TF }
\tl_if_blank:oTF 4414 {
\_tl_if_blank_p:NNw 4415 \_tl_if_empty_if:o { \use_none:n #1 ? }
4416 \prg_return_true:
4417 \else:
4418 \prg_return_false:
4419 \fi:
4420 }

```



```

4421 \prg_generate_conditional_variant:Nnn \tl_if_blank:n
4422 { V , o } { p , T , F , TF }

```

(End definition for `\tl_if_blank:nTF` and `__tl_if_blank_p:NNw`. This function is documented on page 38.)

`\tl_if_empty_p:N` These functions check whether the token list in the argument is empty and execute the proper code from their argument(s).

```

\__tl_if_empty_p:c
\__tl_if_empty:N $\overline{TF}$ 
\__tl_if_empty:c $\overline{TF}$ 
4423 \prg_new_conditional:Npnn \tl_if_empty:N #1 { p , T , F , TF }
4424 {
4425   \if_meaning:w #1 \c_empty_tl
4426   \prg_return_true:
4427   \else:
4428     \prg_return_false:
4429   \fi:
4430 }
4431 \prg_generate_conditional_variant:Nnn \tl_if_empty:N
4432 { c } { p , T , F , TF }

```

(End definition for `\tl_if_empty:N \overline{TF}` . This function is documented on page 39.)

`\tl_if_empty_p:n` Convert the argument to a string: this is empty if and only if the argument is. Then
`\tl_if_empty_p:V` `\if_meaning:w \q_nil ... \q_nil` is true if and only if the string ... is empty. It
`\tl_if_empty:n \overline{TF}` could be tempting to use `\if_meaning:w \q_nil #1 \q_nil` directly. This fails on a
`\tl_if_empty:V \overline{TF}` token list starting with `\q_nil` of course but more troubling is the case where argument
is a complete conditional such as `\if_true: a \else: b \fi:` because then `\if_true:`
is used by `\if_meaning:w`, the test turns out false, the `\else:` executes the false
branch, the `\fi:` ends it and the `\q_nil` at the end starts executing...

```

4433 \prg_new_conditional:Npnn \tl_if_empty:n #1 { p , TF , T , F }
4434 {
4435   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
4436   \tl_to_str:n {#1} \q_nil
4437   \prg_return_true:
4438   \else:
4439     \prg_return_false:
4440   \fi:
4441 }
4442 \prg_generate_conditional_variant:Nnn \tl_if_empty:n
4443 { V } { p , TF , T , F }

```

(End definition for `\tl_if_empty:n \overline{TF}` . This function is documented on page 39.)

`\tl_if_empty_p:o` The auxiliary function `__tl_if_empty_if:o` is for use in various token list conditionals
`\tl_if_empty:o \overline{TF}` which reduce to testing if a given token list is empty after applying a simple function to it.
`__tl_if_empty_if:o` The test for emptiness is based on `\tl_if_empty:n \overline{TF}` , but the expansion is hard-coded
for efficiency, as this auxiliary function is used in several places. We don't put `\prg_`
`return_true:` and so on in the definition of the auxiliary, because that would prevent
an optimization applied to conditionals that end with this code.

```

4444 \cs_new:Npn \__tl_if_empty_if:o #1
4445 {
4446   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
4447   \__kernel_tl_to_str:w \exp_after:wN {#1} \q_nil
4448 }
4449 \prg_new_conditional:Npnn \tl_if_empty:o #1 { p , TF , T , F }

```

```

4450 {
4451   \__tl_if_empty_if:o {#1}
4452   \prg_return_true:
4453   \else:
4454     \prg_return_false:
4455   \fi:
4456 }

```

(End definition for `\tl_if_empty:nTF` and `__tl_if_empty_if:o`. This function is documented on page 39.)

`\tl_if_eq_p:NN` Returns `\c_true_bool` if and only if the two token list variables are equal.

```

\tl_if_eq_p:Nc 4457 \prg_new_conditional:Npnn \tl_if_eq:NN #1#2 { p , T , F , TF }
\tl_if_eq_p:cN 4458 {
\tl_if_eq_p:cc 4459   \if_meaning:w #1 #2
\tl_if_eq:NNTF 4460   \prg_return_true:
\tl_if_eq:NcTF 4461   \else:
\tl_if_eq:cNTF 4462   \prg_return_false:
\tl_if_eq:ccTF 4463   \fi:
4464 }
4465 \prg_generate_conditional_variant:Nnn \tl_if_eq:NN
4466 { Nc , c , cc } { p , TF , T , F }

```

(End definition for `\tl_if_eq:NNTF`. This function is documented on page 39.)

`\tl_if_eq:nnTF` A simple store and compare routine.

```

\l__tl_internal_a_tl 4467 \prg_new_protected_conditional:Npnn \tl_if_eq:nn #1#2 { T , F , TF }
\l__tl_internal_b_tl 4468 {
4469   \group_begin:
4470     \tl_set:Nn \l__tl_internal_a_tl {#1}
4471     \tl_set:Nn \l__tl_internal_b_tl {#2}
4472     \exp_after:wN
4473   \group_end:
4474   \if_meaning:w \l__tl_internal_a_tl \l__tl_internal_b_tl
4475     \prg_return_true:
4476   \else:
4477     \prg_return_false:
4478   \fi:
4479 }
4480 \tl_new:N \l__tl_internal_a_tl
4481 \tl_new:N \l__tl_internal_b_tl

```

(End definition for `\tl_if_eq:nnTF`, `\l__tl_internal_a_tl`, and `\l__tl_internal_b_tl`. This function is documented on page 39.)

`\tl_if_in:NnTF` See `\tl_if_in:nnTF` for further comments. Here we simply expand the token list variable and pass it to `\tl_if_in:nnTF`.

```

\tl_if_in:cnTF 4482 \cs_new_protected:Npn \tl_if_in:NnT { \exp_args:No \tl_if_in:nnT }
4483 \cs_new_protected:Npn \tl_if_in:NnF { \exp_args:No \tl_if_in:nnF }
4484 \cs_new_protected:Npn \tl_if_in:NnTF { \exp_args:No \tl_if_in:nnTF }
4485 \prg_generate_conditional_variant:Nnn \tl_if_in:Nn
4486 { c } { T , F , TF }

```

(End definition for `\tl_if_in:NnTF`. This function is documented on page 39.)

`\tl_if_in:nnTF` Once more, the test relies on the emptiness test for robustness. The function `__tl_tmp:w` removes tokens until the first occurrence of #2. If this does not appear in #1, then the final #2 is removed, leaving an empty token list. Otherwise some tokens remain, and the test is `false`. See `\tl_if_empty:nTF` for details on the emptiness test.

Treating correctly cases like `\tl_if_in:nnTF {a state}{states}`, where #1#2 contains #2 before the end, requires special care. To cater for this case, we insert `{ }{ }` between the two token lists. This marker may not appear in #2 because of \TeX limitations on what can delimit a parameter, hence we are safe. Using two brace groups makes the test work also for empty arguments. The `\if_false:` constructions are a faster way to do `\group_align_safe_begin:` and `\group_align_safe_end:`.

```

4487 \prg_new_protected_conditional:Npnn \tl_if_in:nn #1#2 { T , F , TF }
4488 {
4489   \if_false: { \fi:
4490     \cs_set:Npn \__tl_tmp:w ##1 #2 { }
4491     \tl_if_empty:oTF { \__tl_tmp:w #1 {} {} #2 }
4492     { \prg_return_false: } { \prg_return_true: }
4493   \if_false: } \fi:
4494 }
4495 \prg_generate_conditional_variant:Nnn \tl_if_in:nn
4496 { V , o , no } { T , F , TF }

```

(End definition for `\tl_if_in:nnTF`. This function is documented on page 39.)

`\tl_if_novalue:p:n` Tests for `-NoValue-`: this is similar to `\tl_if_in:nn` but set up to be expandable and to check the value exactly. The question mark prevents the auxiliary from losing braces.

```

\__tl_if_novalue:w
4497 \cs_set_protected:Npn \__tl_tmp:w #1
4498 {
4499   \prg_new_conditional:Npnn \tl_if_novalue:n ##1
4500   { p , T , F , TF }
4501   {
4502     \str_if_eq:onTF
4503     { \__tl_if_novalue:w ? ##1 { } #1 }
4504     { ? { } #1 }
4505     { \prg_return_true: }
4506     { \prg_return_false: }
4507   }
4508   \cs_new:Npn \__tl_if_novalue:w ##1 #1 {##1}
4509 }
4510 \exp_args:No \__tl_tmp:w { \c_novalue_tl }

```

(End definition for `\tl_if_novalue:nTF` and `__tl_if_novalue:w`. This function is documented on page 39.)

`\tl_if_single:p:N` Expand the token list and feed it to `\tl_if_single:n`.

```

\__tl_if_single:p:n
4511 \cs_new:Npn \tl_if_single_p:N { \exp_args:No \tl_if_single_p:n }
4512 \cs_new:Npn \tl_if_single:NT { \exp_args:No \tl_if_single:nT }
4513 \cs_new:Npn \tl_if_single:NF { \exp_args:No \tl_if_single:nF }
4514 \cs_new:Npn \tl_if_single:NTF { \exp_args:No \tl_if_single:nTF }

```

(End definition for `\tl_if_single:NTF`. This function is documented on page 40.)

`\tl_if_single:p:n` This test is similar to `\tl_if_empty:nTF`. Expanding `\use_none:nn #1 ??` once yields an empty result if #1 is blank, a single ? if #1 has a single item, and otherwise yields some tokens ending with `??`. Then, `\tl_to_str:n` makes sure there are no odd category codes.

`__tl_if_single:nTF`

An earlier version would compare the result to a single ? using string comparison, but the Lua call is slow in LuaTeX. Instead, `__tl_if_single:nw` picks the second token in front of it. If #1 is empty, this token is the trailing ? and the catcode test yields `false`. If #1 has a single item, the token is ^ and the catcode test yields `true`. Otherwise, it is one of the characters resulting from `\tl_to_str:n`, and the catcode test yields `false`. Note that `\if_catcode:w` and `__kernel_tl_to_str:w` are primitives that take care of expansion.

```

4515 \prg_new_conditional:Npnn \tl_if_single:n #1 { p , T , F , TF }
4516 {
4517   \if_catcode:w ^ \exp_after:wN \__tl_if_single:nw
4518     \__kernel_tl_to_str:w
4519     \exp_after:wN { \use_none:nn #1 ?? } ^ ? \q_stop
4520   \prg_return_true:
4521   \else:
4522     \prg_return_false:
4523   \fi:
4524 }
4525 \cs_new:Npn \__tl_if_single:nw #1#2#3 \q_stop {#2}

```

(End definition for `\tl_if_single:nTF` and `__tl_if_single:nTF`. This function is documented on page 40.)

<code>\tl_case:Nn</code> <code>\tl_case:cn</code> <code>\tl_case:NnTF</code> <code>\tl_case:cnTF</code> <code>__tl_case:nnTF</code> <code>__tl_case:Nw</code> <code>__tl_case_end:nw</code>	The aim here is to allow the case statement to be evaluated using a known number of expansion steps (two), and without needing to use an explicit “end of recursion” marker. That is achieved by using the test input as the final case, as this is always true. The trick is then to tidy up the output such that the appropriate case code plus either the <code>true</code> or <code>false</code> branch code is inserted.	<pre> 4526 \cs_new:Npn \tl_case:Nn #1#2 4527 { 4528 \exp:w 4529 __tl_case:NnTF #1 {#2} { } { } 4530 } 4531 \cs_new:Npn \tl_case:NnT #1#2#3 4532 { 4533 \exp:w 4534 __tl_case:NnTF #1 {#2} {#3} { } 4535 } 4536 \cs_new:Npn \tl_case:NnF #1#2#3 4537 { 4538 \exp:w 4539 __tl_case:NnTF #1 {#2} { } {#3} 4540 } 4541 \cs_new:Npn \tl_case:NnTF #1#2 4542 { 4543 \exp:w 4544 __tl_case:NnTF #1 {#2} 4545 } 4546 \cs_new:Npn __tl_case:NnTF #1#2#3#4 4547 { __tl_case:Nw #1 #2 #1 { } \q_mark {#3} \q_mark {#4} \q_stop } 4548 \cs_new:Npn __tl_case:Nw #1#2#3 4549 { 4550 \tl_if_eq:NNTF #1 #2 4551 { __tl_case_end:nw {#3} } </pre>
--	---	---

```

4552     { \_tl\_case:Nw #1 }
4553   }
4554   \cs_generate_variant:Nn \tl\_case:Nn { c }
4555   \prg_generate_conditional_variant:Nnn \tl\_case:Nn
4556     { c } { T , F , TF }

```

To tidy up the recursion, there are two outcomes. If there was a hit to one of the cases searched for, then #1 is the code to insert, #2 is the *next* case to check on and #3 is all of the rest of the cases code. That means that #4 is the **true** branch code, and #5 tidies up the spare \q_mark and the **false** branch. On the other hand, if none of the cases matched then we arrive here using the “termination” case of comparing the search with itself. That means that #1 is empty, #2 is the first \q_mark and so #4 is the **false** code (the **true** code is mopped up by #3).

```

4557   \cs_new:Npn \_tl\_case\_end:nw #1#2#3 \q\_mark #4#5 \q\_stop
4558     { \exp\_end: #1 #4 }

```

(End definition for \tl_case:NnTF and others. This function is documented on page 40.)

6.7 Mapping to token lists

\tl_map_function:nN Expandable loop macro for token lists. These have the advantage of not needing to test if the argument is empty, because if it is, the stop marker is read immediately and the loop terminated.

```

\__tl\_map\_function:Nn
4559   \cs_new:Npn \tl\_map\_function:nN #1#2
4560   {
4561     \__tl\_map\_function:Nn #2 #1
4562     \q\_recursion\_tail
4563     \prg\_break\_point:Nn \tl\_map\_break: { }
4564   }
4565   \cs_new:Npn \tl\_map\_function:NN
4566     { \exp\_args:No \tl\_map\_function:nN }
4567   \cs_new:Npn \__tl\_map\_function:Nn #1#2
4568   {
4569     \quark\_if\_recursion\_tail\_break:nN {#2} \tl\_map\_break:
4570     #1 {#2} \__tl\_map\_function:Nn #1
4571   }
4572   \cs\_generate\_variant:Nn \tl\_map\_function:NN { c }

```

(End definition for \tl_map_function:nN, \tl_map_function:NN, and __tl_map_function:Nn. These functions are documented on page 40.)

\tl_map_inline:nn The inline functions are straight forward by now. We use a little trick with the counter **\g_kernel_prg_map_int** to make them nestable. We can also make use of **__tl_map_function:Nn** from before.

```

4573   \cs\_new\_protected:Npn \tl\_map\_inline:nn #1#2
4574   {
4575     \int\_gincr:N \g\_kernel\_prg\_map\_int
4576     \cs\_gset\_protected:cpn
4577       { \__tl\_map\_ \int\_use:N \g\_kernel\_prg\_map\_int :w } ##1 {#2}
4578     \exp\_args:Nc \__tl\_map\_function:Nn
4579       { \__tl\_map\_ \int\_use:N \g\_kernel\_prg\_map\_int :w }
4580     #1 \q\_recursion\_tail
4581     \prg\_break\_point:Nn \tl\_map\_break:
4582       { \int\_gdecr:N \g\_kernel\_prg\_map\_int }

```

```

4583 }
4584 \cs_new_protected:Npn \tl_map_inline:Nn
4585 { \exp_args:No \tl_map_inline:nn }
4586 \cs_generate_variant:Nn \tl_map_inline:Nn { c }

```

(End definition for `\tl_map_inline:nn` and `\tl_map_inline:Nn`. These functions are documented on page 41.)

`\tl_map_variable:nNn` `\tl_map_variable:nNn` $\langle token\ list \rangle$ $\langle temp \rangle$ $\langle action \rangle$ assigns $\langle temp \rangle$ to each element and executes $\langle action \rangle$.

```

\__tl_map_variable:Nnn
4587 \cs_new_protected:Npn \tl_map_variable:nNn #1#2#3
4588 {
4589   \__tl_map_variable:Nnn #2 {#3} #1
4590   \q_recursion_tail
4591   \prg_break_point:Nn \tl_map_break: { }
4592 }
4593 \cs_new_protected:Npn \tl_map_variable:NNn
4594 { \exp_args:No \tl_map_variable:nNn }
4595 \cs_new_protected:Npn \__tl_map_variable:Nnn #1#2#3
4596 {
4597   \tl_set:Nn #1 {#3}
4598   \quark_if_recursion_tail_break:NN #1 \tl_map_break:
4599   \use:n {#2}
4600   \__tl_map_variable:Nnn #1 {#2}
4601 }
4602 \cs_generate_variant:Nn \tl_map_variable:NNn { c }

```

(End definition for `\tl_map_variable:nNn`, `\tl_map_variable:NNn`, and `__tl_map_variable:Nnn`. These functions are documented on page 41.)

`\tl_map_break:` The break statements use the general `\prg_map_break:Nn`.

```

\tl_map_break:n
4603 \cs_new:Npn \tl_map_break:
4604 { \prg_map_break:Nn \tl_map_break: { } }
4605 \cs_new:Npn \tl_map_break:n
4606 { \prg_map_break:Nn \tl_map_break: }

```

(End definition for `\tl_map_break:` and `\tl_map_break:n`. These functions are documented on page 41.)

6.8 Using token lists

`\tl_to_str:n` Another name for a primitive: defined in `l3basics`.

```

\tl_to_str:V
4607 \cs_generate_variant:Nn \tl_to_str:n { V }

```

(End definition for `\tl_to_str:n`. This function is documented on page 42.)

`\tl_to_str:N` These functions return the replacement text of a token list as a string.

```

\tl_to_str:c
4608 \cs_new:Npn \tl_to_str:N #1 { \__kernel_tl_to_str:w \exp_after:wN {#1} }
4609 \cs_generate_variant:Nn \tl_to_str:N { c }

```

(End definition for `\tl_to_str:N`. This function is documented on page 42.)

\tl_use:N Token lists which are simply not defined give a clear TeX error here. No such luck for **\tl_use:c** ones equal to `\scan_stop`: so instead a test is made and if there is an issue an error is forced.

```

4610 \cs_new:Npn \tl_use:N #1
4611 {
4612   \tl_if_exist:NTF #1 {#1}
4613   {
4614     \__kernel_msg_expandable_error:nnn
4615     { kernel } { bad-variable } {#1}
4616   }
4617 }
4618 \cs_generate_variant:Nn \tl_use:N { c }

```

(End definition for `\tl_use:N`. This function is documented on page 43.)

6.9 Working with the contents of token lists

\tl_count:n Count number of elements within a token list or token list variable. Brace groups within the list are read as a single element. Spaces are ignored. `__tl_count:n` grabs the element and replaces it by +1. The 0 ensures that it works on an empty list.

```

4619 \cs_new:Npn \tl_count:n #1
4620 {
4621   \int_eval:n
4622   { 0 \tl_map_function:nN {#1} \__tl_count:n }
4623 }
4624 \cs_new:Npn \tl_count:N #1
4625 {
4626   \int_eval:n
4627   { 0 \tl_map_function:NN #1 \__tl_count:n }
4628 }
4629 \cs_new:Npn \__tl_count:n #1 { + 1 }
4630 \cs_generate_variant:Nn \tl_count:n { V , o }
4631 \cs_generate_variant:Nn \tl_count:N { c }

```

(End definition for `\tl_count:n`, `\tl_count:N`, and `__tl_count:n`. These functions are documented on page 43.)

\tl_reverse_items:n Reversal of a token list is done by taking one item at a time and putting it after `\q_stop`.

```

4632 \cs_new:Npn \tl_reverse_items:n #1
4633 {
4634   \__tl_reverse_items:nwNwn #1 ?
4635   \q_mark \__tl_reverse_items:nwNwn
4636   \q_mark \__tl_reverse_items:wn
4637   \q_stop { }
4638 }
4639 \cs_new:Npn \__tl_reverse_items:nwNwn #1 #2 \q_mark #3 #4 \q_stop #5
4640 {
4641   #3 #2
4642   \q_mark \__tl_reverse_items:nwNwn
4643   \q_mark \__tl_reverse_items:wn
4644   \q_stop { {#1} #5 }
4645 }
4646 \cs_new:Npn \__tl_reverse_items:wn #1 \q_stop #2
4647 { \exp_not:o { \use_none:nn #2 } }

```

(End definition for `\tl_reverse_items:n`, `__tl_reverse_items:nwNwn`, and `__tl_reverse_items:wn`. This function is documented on page 43.)

`\tl_trim_spaces:n` Trimming spaces from around the input is deferred to an internal function whose first argument is the token list to trim, augmented by an initial `\q_mark`, and whose second argument is a *<continuation>*, which receives as a braced argument `\use_none:n \q_mark <trimmed token list>`. In the case at hand, we take `\exp_not:o` as our continuation, so that space trimming behaves correctly within an x-type expansion.

```

\tl_trim_spaces:n 4648 \cs_new:Npn \tl_trim_spaces:n #1
\tl_trim_spaces:o 4649 { \__tl_trim_spaces:nn { \q_mark #1 } \exp_not:o }
\tl_trim_spaces_apply:nN 4650 \cs_generate_variant:Nn \tl_trim_spaces:n { o }
\tl_trim_spaces_apply:oN 4651 \cs_new:Npn \tl_trim_spaces_apply:nN #1#2
\tl_trim_spaces:N 4652 { \__tl_trim_spaces:nn { \q_mark #1 } { \exp_args:No #2 } }
\tl_trim_spaces:c 4653 \cs_generate_variant:Nn \tl_trim_spaces_apply:nN { o }
\tl_gtrim_spaces:N 4654 \cs_new_protected:Npn \tl_trim_spaces:N #1
\tl_gtrim_spaces:c 4655 { \tl_set:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
4656 \cs_new_protected:Npn \tl_gtrim_spaces:N #1
4657 { \tl_gset:Nx #1 { \exp_args:No \tl_trim_spaces:n {#1} } }
4658 \cs_generate_variant:Nn \tl_trim_spaces:N { c }
4659 \cs_generate_variant:Nn \tl_gtrim_spaces:N { c }
```

Trimming spaces from around the input is done using delimited arguments and quarks, and to get spaces at odd places in the definitions, we nest those in `__tl_tmp:w`, which then receives a single space as its argument: `#1` is `␣`. Removing leading spaces is done with `__tl_trim_spaces_auxi:w`, which loops until `\q_mark␣` matches the end of the token list: then `##1` is the token list and `##3` is `__tl_trim_spaces_auxii:w`. This hands the relevant tokens to the loop `__tl_trim_spaces_auxiii:w`, responsible for trimming trailing spaces. The end is reached when `␣ \q_nil` matches the one present in the definition of `\tl_trim_spaces:n`. Then `__tl_trim_spaces_auxiv:w` puts the token list into a group, with `\use_none:n` placed there to gobble a lingering `\q_mark`, and feeds this to the *<continuation>*.

```

4660 \cs_set:Npn \__tl_tmp:w #1
4661 {
4662   \cs_new:Npn \__tl_trim_spaces:nn ##1
4663   {
4664     \__tl_trim_spaces_auxi:w
4665     ##1
4666     \q_nil
4667     \q_mark #1 { }
4668     \q_mark \__tl_trim_spaces_auxii:w
4669     \__tl_trim_spaces_auxiii:w
4670     #1 \q_nil
4671     \__tl_trim_spaces_auxiv:w
4672     \q_stop
4673   }
4674   \cs_new:Npn \__tl_trim_spaces_auxi:w ##1 \q_mark #1 ##2 \q_mark ##3
4675   {
4676     ##3
4677     \__tl_trim_spaces_auxi:w
4678     \q_mark
4679     ##2
4680     \q_mark #1 {##1}
4681   }
```



```

4682 \cs_new:Npn \__tl_trim_spaces_auxii:w
4683 \__tl_trim_spaces_auxi:w \q_mark \q_mark ##1
4684 {
4685 \__tl_trim_spaces_auxiii:w
4686 ##1
4687 }
4688 \cs_new:Npn \__tl_trim_spaces_auxiii:w ##1 #1 \q_nil ##2
4689 {
4690 ##2
4691 ##1 \q_nil
4692 \__tl_trim_spaces_auxiii:w
4693 }
4694 \cs_new:Npn \__tl_trim_spaces_auxiv:w ##1 \q_nil ##2 \q_stop ##3
4695 { ##3 { \use_none:n ##1 } }
4696 }
4697 \__tl_tmp:w { ~ }

```

(End definition for `\tl_trim_spaces:n` and others. These functions are documented on page 44.)

`\tl_sort:Nn` Implemented in `l3sort`.

`\tl_sort:cn`

`\tl_gsort:Nn` (End definition for `\tl_sort:Nn`, `\tl_gsort:Nn`, and `\tl_sort:nN`. These functions are documented on page 44.)

`\tl_gsort:cn`

`\tl_sort:nN`

6.10 Token by token changes

`\q__tl_act_mark`

`\q__tl_act_stop`

The `__tl_act...` functions may be applied to any token list. Hence, we use two private quarks, to allow any token, even quarks, in the token list. Only `\q__tl_act_mark` and `\q__tl_act_stop` may not appear in the token lists manipulated by `__tl_act:NNNnn` functions. No quark module yet, so do things by hand.

```

4698 \cs_new_nopar:Npn \q__tl_act_mark { \q__tl_act_mark }
4699 \cs_new_nopar:Npn \q__tl_act_stop { \q__tl_act_stop }

```

(End definition for `\q__tl_act_mark` and `\q__tl_act_stop`.)

`__tl_act:NNNnn`

`__tl_act_output:n`

`__tl_act_reverse_output:n`

`__tl_act_loop:w`

`__tl_act_normal:NwnNNN`

`__tl_act_group:nwnNNN`

`__tl_act_space:wwnNNN`

`__tl_act_end:w`

To help control the expansion, `__tl_act:NNNnn` should always be proceeded by `\exp:w` and ends by producing `\exp_end:` once the result has been obtained. Then loop over tokens, groups, and spaces in #5. The marker `\q__tl_act_mark` is used both to avoid losing outer braces and to detect the end of the token list more easily. The result is stored as an argument for the dummy function `__tl_act_result:n`.

```

4700 \cs_new:Npn \__tl_act:NNNnn #1#2#3#4#5
4701 {
4702 \group_align_safe_begin:
4703 \__tl_act_loop:w #5 \q__tl_act_mark \q__tl_act_stop
4704 {#4} #1 #2 #3
4705 \__tl_act_result:n { }
4706 }

```

In the loop, we check how the token list begins and act accordingly. In the “normal” case, we may have reached `\q__tl_act_mark`, the end of the list. Then leave `\exp_end:` and the result in the input stream, to terminate the expansion of `\exp:w`. Otherwise, apply the relevant function to the “arguments”, #3 and to the head of the token list. Then repeat the loop. The scheme is the same if the token list starts with a group or with a space. Some extra work is needed to make `__tl_act_space:wwnNNN` gobble the space.

```

4707 \cs_new:Npn \__tl_act_loop:w #1 \q__tl_act_stop
4708 {
4709   \tl_if_head_is_N_type:nTF {#1}
4710   { \__tl_act_normal:NwnNNN }
4711   {
4712     \tl_if_head_is_group:nTF {#1}
4713     { \__tl_act_group:nwnNNN }
4714     { \__tl_act_space:wnnNNN }
4715   }
4716   #1 \q__tl_act_stop
4717 }
4718 \cs_new:Npn \__tl_act_normal:NwnNNN #1 #2 \q__tl_act_stop #3#4
4719 {
4720   \if_meaning:w \q__tl_act_mark #1
4721   \exp_after:wN \__tl_act_end:wn
4722   \fi:
4723   #4 {#3} #1
4724   \__tl_act_loop:w #2 \q__tl_act_stop
4725   {#3} #4
4726 }
4727 \cs_new:Npn \__tl_act_end:wn #1 \__tl_act_result:n #2
4728 { \group_align_safe_end: \exp_end: #2 }
4729 \cs_new:Npn \__tl_act_group:nwnNNN #1 #2 \q__tl_act_stop #3#4#5
4730 {
4731   #5 {#3} {#1}
4732   \__tl_act_loop:w #2 \q__tl_act_stop
4733   {#3} #4 #5
4734 }
4735 \exp_last_unbraced:NNo
4736 \cs_new:Npn \__tl_act_space:wnnNNN \c_space_tl #1 \q__tl_act_stop #2#3#4#5
4737 {
4738   #5 {#2}
4739   \__tl_act_loop:w #1 \q__tl_act_stop
4740   {#2} #3 #4 #5
4741 }

```

Typically, the output is done to the right of what was already output, using `__tl_act_output:n`, but for the `__tl_act_reverse` functions, it should be done to the left.

```

4742 \cs_new:Npn \__tl_act_output:n #1 #2 \__tl_act_result:n #3
4743 { #2 \__tl_act_result:n { #3 #1 } }
4744 \cs_new:Npn \__tl_act_reverse_output:n #1 #2 \__tl_act_result:n #3
4745 { #2 \__tl_act_result:n { #1 #3 } }

```

(End definition for `__tl_act:NNNnn` and others.)

`\tl_reverse:n` The goal here is to reverse without losing spaces nor braces. This is done using the
`\tl_reverse:o` general internal function `__tl_act:NNNnn`. Spaces and “normal” tokens are output on
`\tl_reverse:V` the left of the current output. Grouped tokens are output to the left but without any
`__tl_reverse_normal:nN` reversal within the group. All of the internal functions here drop one argument: this is
`__tl_reverse_group_preserve:nn` needed by `__tl_act:NNNnn` when changing case (to record which direction the change
`__tl_reverse_space:n` is in), but not when reversing the tokens.

```

4746 \cs_new:Npn \tl_reverse:n #1
4747 {
4748   \__kernel_exp_not:w \exp_after:wN

```

```

4749     {
4750       \exp:w
4751       \__tl_act:NNNnn
4752       \__tl_reverse_normal:nN
4753       \__tl_reverse_group_preserve:nn
4754       \__tl_reverse_space:n
4755       { }
4756       {#1}
4757     }
4758   }
4759   \cs_generate_variant:Nn \tl_reverse:n { o , V }
4760   \cs_new:Npn \__tl_reverse_normal:nN #1#2
4761     { \__tl_act_reverse_output:n {#2} }
4762   \cs_new:Npn \__tl_reverse_group_preserve:nn #1#2
4763     { \__tl_act_reverse_output:n { {#2} } }
4764   \cs_new:Npn \__tl_reverse_space:n #1
4765     { \__tl_act_reverse_output:n { ~ } }

```

(End definition for `\tl_reverse:n` and others. This function is documented on page 43.)

`\tl_reverse:N` This reverses the list, leaving `\exp_stop_f:` in front, which stops the `f`-expansion.

```

\tl_reverse:c 4766 \cs_new_protected:Npn \tl_reverse:N #1
\tl_greverse:N 4767   { \tl_set:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
\tl_greverse:c 4768 \cs_new_protected:Npn \tl_greverse:N #1
4769   { \tl_gset:Nx #1 { \exp_args:No \tl_reverse:n { #1 } } }
4770 \cs_generate_variant:Nn \tl_reverse:N { c }
4771 \cs_generate_variant:Nn \tl_greverse:N { c }

```

(End definition for `\tl_reverse:N` and `\tl_greverse:N`. These functions are documented on page 43.)

6.11 The first token from a token list

`\tl_head:N` Finding the head of a token list expandably always strips braces, which is fine as this is consistent with for example mapping to a list. The empty brace groups in `\tl_head:n` ensure that a blank argument gives an empty result. The result is returned within the `\unexpanded` primitive. The approach here is to use `\if_false:` to allow us to use `}` as the closing delimiter: this is the only safe choice, as any other token would not be able to parse it's own code. Using a marker, we can see if what we are grabbing is exactly the marker, or there is anything else to deal with. If there is, there is a loop. If not, tidy up and leave the item in the output stream. More detail in <http://tex.stackexchange.com/a/70168>.

```

\tl_head:w 4772 \cs_new:Npn \tl_head:n #1
\tl_head:V 4773   {
\tl_head:v 4774     \__kernel_exp_not:w
\tl_head:f 4775     \if_false: { \fi: \__tl_head_auxi:nw #1 { } \q_stop }
4776   }
4777 \cs_new:Npn \__tl_head_auxi:nw #1#2 \q_stop
4778   {
4779     \exp_after:wN \__tl_head_auxii:n \exp_after:wN {
4780       \if_false: } \fi: {#1}
4781     }
4782 \cs_new:Npn \__tl_head_auxii:n #1
4783   {

```

```

4784 \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
4785 \__kernel_tl_to_str:w \exp_after:wN { \use_none:n #1 } \q_nil
4786 \exp_after:wN \use_i:nn
4787 \else:
4788 \exp_after:wN \use_ii:nn
4789 \fi:
4790 {#1}
4791 { \if_false: { \fi: \__tl_head_auxi:nw #1 } }
4792 }
4793 \cs_generate_variant:Nn \tl_head:n { V , v , f }
4794 \cs_new:Npn \tl_head:w #1#2 \q_stop {#1}
4795 \cs_new:Npn \tl_head:N { \exp_args:No \tl_head:n }

```

To correctly leave the tail of a token list, it's important *not* to absorb any of the tail part as an argument. For example, the simple definition

```

\cs_new:Npn \tl_tail:n #1 { \tl_tail:w #1 \q_stop }
\cs_new:Npn \tl_tail:w #1#2 \q_stop

```

would give the wrong result for `\tl_tail:n { a { bc } }` (the braces would be stripped). Thus the only safe way to proceed is to first check that there is an item to grab (*i.e.* that the argument is not blank) and assuming there is to dispose of the first item. As with `\tl_head:n`, the result is protected from further expansion by `\unexpanded`. While we could optimise the test here, this would leave some tokens “banned” in the input, which we do not have with this definition.

```

4796 \cs_new:Npn \tl_tail:n #1
4797 {
4798 \__kernel_exp_not:w
4799 \tl_if_blank:nTF {#1}
4800 { { } }
4801 { \exp_after:wN { \use_none:n #1 } }
4802 }
4803 \cs_generate_variant:Nn \tl_tail:n { V , v , f }
4804 \cs_new:Npn \tl_tail:N { \exp_args:No \tl_tail:n }

```

(End definition for `\tl_head:N` and others. These functions are documented on page 45.)

<pre> \tl_if_head_eq_meaning_p:nN \tl_if_head_eq_meaning:nNTF \tl_if_head_eq_charcode_p:nN \tl_if_head_eq_charcode:nNTF \tl_if_head_eq_charcode_p:fN \tl_if_head_eq_charcode:fNTF \tl_if_head_eq_catcode_p:nN \tl_if_head_eq_catcode:nNTF </pre>	<p>Accessing the first token of a token list is tricky in three cases: when it has category code 1 (begin-group token), when it is an explicit space, with category code 10 and character code 32, or when the token list is empty (obviously).</p> <p>Forgetting temporarily about this issue we would use the following test in <code>\tl_if_head_eq_charcode:nN</code>. Here, <code>\tl_head:w</code> yields the first token of the token list, then passed to <code>\exp_not:N</code>.</p> <pre> \if_charcode:w \exp_after:wN \exp_not:N \tl_head:w #1 \q_nil \q_stop \exp_not:N #2 </pre>
--	--

The two first special cases are detected by testing if the token list starts with an N-type token (the extra ? sends empty token lists to the `true` branch of this test). In those cases, the first token is a character, and since we only care about its character code, we can use `\str_head:n` to access it (this works even if it is a space character). An empty argument results in `\tl_head:w` leaving two tokens: ? which is taken in the `\if_charcode:w` test,

and `\use_none:nn`, which ensures that `\prg_return_false:` is returned regardless of whether the charcode test was true or false.

```

4805 \prg_new_conditional:Npnn \tl_if_head_eq_charcode:nN #1#2 { p , T , F , TF }
4806 {
4807   \if_charcode:w
4808     \exp_not:N #2
4809     \tl_if_head_is_N_type:nTF { #1 ? }
4810     {
4811       \exp_after:wN \exp_not:N
4812       \tl_head:w #1 { ? \use_none:nn } \q_stop
4813     }
4814     { \str_head:n {#1} }
4815     \prg_return_true:
4816   \else:
4817     \prg_return_false:
4818   \fi:
4819 }
4820 \prg_generate_conditional_variant:Nnn \tl_if_head_eq_charcode:nN
4821 { f } { p , TF , T , F }

```

For `\tl_if_head_eq_catcode:nN`, again we detect special cases with a `\tl_if_head_is_N_type:n`. Then we need to test if the first token is a begin-group token or an explicit space token, and produce the relevant token, either `\c_group_begin_token` or `\c_space_token`. Again, for an empty argument, a hack is used, removing `\prg_return_true:` and `\else:` with `\use_none:nn` in case the catcode test with the (arbitrarily chosen) `?` is true.

```

4822 \prg_new_conditional:Npnn \tl_if_head_eq_catcode:nN #1 #2 { p , T , F , TF }
4823 {
4824   \if_catcode:w
4825     \exp_not:N #2
4826     \tl_if_head_is_N_type:nTF { #1 ? }
4827     {
4828       \exp_after:wN \exp_not:N
4829       \tl_head:w #1 { ? \use_none:nn } \q_stop
4830     }
4831     {
4832       \tl_if_head_is_group:nTF {#1}
4833       { \c_group_begin_token }
4834       { \c_space_token }
4835     }
4836     \prg_return_true:
4837   \else:
4838     \prg_return_false:
4839   \fi:
4840 }

```

For `\tl_if_head_eq_meaning:nN`, again, detect special cases. In the normal case, use `\tl_head:w`, with no `\exp_not:N` this time, since `\if_meaning:w` causes no expansion. With an empty argument, the test is true, and `\use_none:nnn` removes `#2` and the usual `\prg_return_true:` and `\else:`. In the special cases, we know that the first token is a character, hence `\if_charcode:w` and `\if_catcode:w` together are enough. We combine them in some order, hopefully faster than the reverse. Tests are not nested because the arguments may contain unmatched primitive conditionals.

```

4841 \prg_new_conditional:Npnn \tl_if_head_eq_meaning:nN #1#2 { p , T , F , TF }
4842 {
4843   \tl_if_head_is_N_type:nTF { #1 ? }
4844   { \__tl_if_head_eq_meaning_normal:nN }
4845   { \__tl_if_head_eq_meaning_special:nN }
4846   {#1} #2
4847 }
4848 \cs_new:Npn \__tl_if_head_eq_meaning_normal:nN #1 #2
4849 {
4850   \exp_after:wN \if_meaning:w
4851   \tl_head:w #1 { ?? \use_none:nnn } \q_stop #2
4852   \prg_return_true:
4853   \else:
4854   \prg_return_false:
4855   \fi:
4856 }
4857 \cs_new:Npn \__tl_if_head_eq_meaning_special:nN #1 #2
4858 {
4859   \if_charcode:w \str_head:n {#1} \exp_not:N #2
4860   \exp_after:wN \use:n
4861   \else:
4862   \prg_return_false:
4863   \exp_after:wN \use_none:n
4864   \fi:
4865   {
4866     \if_catcode:w \exp_not:N #2
4867     \tl_if_head_is_group:nTF {#1}
4868     { \c_group_begin_token }
4869     { \c_space_token }
4870     \prg_return_true:
4871     \else:
4872     \prg_return_false:
4873     \fi:
4874   }
4875 }

```

(End definition for `\tl_if_head_eq_meaning:nNTF` and others. These functions are documented on page 46.)

`\tl_if_head_is_N_type_p:n` A token list can be empty, can start with an explicit space character (catcode 10 and charcode 32), can start with a begin-group token (catcode 1), or start with an N-type argument. In the first two cases, the line involving `__tl_if_head_is_N_type:w` produces `~` (and otherwise nothing). In the third case (begin-group token), the lines involving `\exp_after:wN` produce a single closing brace. The category code test is thus true exactly in the fourth case, which is what we want. One cannot optimize by moving one of the `*` to the beginning: if `#1` contains primitive conditionals, all of its occurrences must be dealt with before the `\if_catcode:w` tries to skip the `true` branch of the conditional.

```

4876 \prg_new_conditional:Npnn \tl_if_head_is_N_type:n #1 { p , T , F , TF }
4877 {
4878   \if_catcode:w
4879   \if_false: { \fi: \__tl_if_head_is_N_type:w ? #1 ~ }
4880   \exp_after:wN \use_none:n
4881   \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
4882   * *

```

```

4883     \prg_return_true:
4884 \else:
4885     \prg_return_false:
4886 \fi:
4887 }
4888 \cs_new:Npn \__tl_if_head_is_N_type:w #1 ~
4889 {
4890     \tl_if_empty:oTF { \use_none:n #1 } { ^ } { }
4891     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
4892 }

```

(End definition for `\tl_if_head_is_N_type:nTF` and `__tl_if_head_is_N_type:w`. This function is documented on page 46.)

`\tl_if_head_is_group:p:n` Pass the first token of #1 through `\token_to_str:N`, then check for the brace balance.
`\tl_if_head_is_group:nTF` The extra ? caters for an empty argument.⁶

```

4893 \prg_new_conditional:Npnn \tl_if_head_is_group:n #1 { p , T , F , TF }
4894 {
4895     \if_catcode:w
4896         \exp_after:wN \use_none:n
4897         \exp_after:wN { \exp_after:wN { \token_to_str:N #1 ? } }
4898         * *
4899     \prg_return_false:
4900 \else:
4901     \prg_return_true:
4902 \fi:
4903 }

```

(End definition for `\tl_if_head_is_group:nTF`. This function is documented on page 46.)

`\tl_if_head_is_space:p:n` The auxiliary's argument is all that is before the first explicit space in `?#1?~`. If that
`\tl_if_head_is_space:nTF` is a single ? the test yields `true`. Otherwise, that is more than one token, and the
`__tl_if_head_is_space:w` test yields `false`. The work is done within braces (with an `\if_false: { \fi: ... }` construction) both to hide potential alignment tab characters from \TeX in a table, and to allow for removing what remains of the token list after its first space. The `\exp:w` and `\exp_end:` ensure that the result of a single step of expansion directly yields a balanced token list (no trailing closing brace).

```

4904 \prg_new_conditional:Npnn \tl_if_head_is_space:n #1 { p , T , F , TF }
4905 {
4906     \exp:w \if_false: { \fi:
4907         \__tl_if_head_is_space:w ? #1 ? ~ }
4908 }
4909 \cs_new:Npn \__tl_if_head_is_space:w #1 ~
4910 {
4911     \tl_if_empty:oTF { \use_none:n #1 }
4912     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_true: }
4913     { \exp_after:wN \exp_end: \exp_after:wN \prg_return_false: }
4914     \exp_after:wN \use_none:n \exp_after:wN { \if_false: } \fi:
4915 }

```

(End definition for `\tl_if_head_is_space:nTF` and `__tl_if_head_is_space:w`. This function is documented on page 46.)

⁶Bruno: this could be made faster, but we don't: if we hope to ever have an e-type argument, we need all brace "tricks" to happen in one step of expansion, keeping the token list brace balanced at all times.

6.12 Using a single item

`\tl_item:nn` The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then `\quark_if_recursion_tail_stop:n` terminates the loop, and returns nothing at all.

`\tl_item:Nn`

`\tl_item:cn`

`__tl_item_aux:nn`

`__tl_item:nn`

```

4916 \cs_new:Npn \tl_item:nn #1#2
4917 {
4918   \exp_args:Nf \__tl_item:nn
4919   { \exp_args:Nf \__tl_item_aux:nn { \int_eval:n {#2} } {#1} }
4920   #1
4921   \quark_if_recursion_tail
4922   \prg_break_point:
4923 }
4924 \cs_new:Npn \__tl_item_aux:nn #1#2
4925 {
4926   \int_compare:nNnTF {#1} < 0
4927   { \int_eval:n { \tl_count:n {#2} + 1 + #1 } }
4928   {#1}
4929 }
4930 \cs_new:Npn \__tl_item:Nn #1#2
4931 {
4932   \quark_if_recursion_tail_break:nN {#2} \prg_break:
4933   \int_compare:nNnTF {#1} = 1
4934   { \prg_break:n { \exp_not:n {#2} } }
4935   { \exp_args:Nf \__tl_item:nn { \int_eval:n { #1 - 1 } } }
4936 }
4937 \cs_new:Npn \tl_item:Nn { \exp_args:No \tl_item:nn }
4938 \cs_generate_variant:Nn \tl_item:Nn { c }

```

(End definition for `\tl_item:nn` and others. These functions are documented on page 47.)

`\tl_rand_item:n` Importantly `\tl_item:nn` only evaluates its argument once.

`\tl_rand_item:N`

`\tl_rand_item:c`

```

4939 \cs_new:Npn \tl_rand_item:n #1
4940 {
4941   \tl_if_blank:nF {#1}
4942   { \tl_item:nn {#1} { \int_rand:nn { 1 } { \tl_count:n {#1} } } }
4943 }
4944 \cs_new:Npn \tl_rand_item:N { \exp_args:No \tl_rand_item:n }
4945 \cs_generate_variant:Nn \tl_rand_item:N { c }

```

(End definition for `\tl_rand_item:n` and `\tl_rand_item:N`. These functions are documented on page 47.)

`\tl_range:Nnn` To avoid checking for the end of the token list at every step, start by counting the number l of items and “normalizing” the bounds, namely clamping them to the interval $[0, l]$ and dealing with negative indices. More precisely, `__tl_range_items:nnNn` receives the number of items to skip at the beginning of the token list, the index of the last item to keep, a function which is either `__tl_range:w` or the token list itself. If nothing should be kept, leave `{}`: this stops the f-expansion of `\tl_head:f` and that function produces an empty result. Otherwise, repeatedly call `__tl_range_skip:w` to delete $\#1$ items from the input stream (the extra brace group avoids an off-by-one shift). For the braced version `__tl_range_braced:w` sets up `__tl_range_collect_braced:w` which stores items one by one in an argument after the semicolon. Depending on the first token of the tail, either just move it (if it is a space) or also decrement the number of items left

`__tl_range:Nnnn`

`__tl_range:nnnNn`

`__tl_range:nnNn`

`__tl_range_skip:w`

`__tl_range:w`

`__tl_range_skip_spaces:n`

`__tl_range_collect:nn`

`__tl_range_collect:ff`

`__tl_range_collect_space:nw`

`__tl_range_collect_N:nN`

`__tl_range_collect_group:nN`

to find. Eventually, the result is a brace group followed by the rest of the token list, and `\tl_head:f` cleans up and gives the result in `\exp_not:n`.

```

4946 \cs_new:Npn \tl_range:Nnn { \exp_args:No \tl_range:nnn }
4947 \cs_generate_variant:Nn \tl_range:Nnn { c }
4948 \cs_new:Npn \tl_range:nnn { \tl_range:Nnnn \tl_range:w }
4949 \cs_new:Npn \tl_range:Nnnn #1#2#3#4
4950 {
4951   \tl_head:f
4952   {
4953     \exp_args:Nf \tl_range:nnnNn
4954     { \tl_count:n {#2} } {#3} {#4} #1 {#2}
4955   }
4956 }
4957 \cs_new:Npn \tl_range:nnnNn #1#2#3
4958 {
4959   \exp_args:Nff \tl_range:nnNn
4960   {
4961     \exp_args:Nf \tl_range_normalize:nn
4962     { \int_eval:n { #2 - 1 } } {#1}
4963   }
4964   {
4965     \exp_args:Nf \tl_range_normalize:nn
4966     { \int_eval:n {#3} } {#1}
4967   }
4968 }
4969 \cs_new:Npn \tl_range:nnNn #1#2#3#4
4970 {
4971   \if_int_compare:w #2 > #1 \exp_stop_f: \else:
4972     \exp_after:wN { \exp_after:wN }
4973   \fi:
4974   \exp_after:wN #3
4975   \int_value:w \int_eval:n { #2 - #1 } \exp_after:wN ;
4976   \exp_after:wN { \exp:w \tl_range_skip:w #1 ; { } #4 }
4977 }
4978 \cs_new:Npn \tl_range_skip:w #1 ; #2
4979 {
4980   \if_int_compare:w #1 > 0 \exp_stop_f:
4981     \exp_after:wN \tl_range_skip:w
4982     \int_value:w \int_eval:n { #1 - 1 } \exp_after:wN ;
4983   \else:
4984     \exp_after:wN \exp_end:
4985   \fi:
4986 }
4987 \cs_new:Npn \tl_range:w #1 ; #2
4988 {
4989   \exp_args:Nf \tl_range_collect:nn
4990   { \tl_range_skip_spaces:n {#2} } {#1}
4991 }
4992 \cs_new:Npn \tl_range_skip_spaces:n #1
4993 {
4994   \tl_if_head_is_space:nTF {#1}
4995   { \exp_args:Nf \tl_range_skip_spaces:n {#1} }
4996   { { } #1 }
4997 }

```

```

4998 \cs_new:Npn \__tl_range_collect:nn #1#2
4999 {
5000   \int_compare:nNnTF {#2} = 0
5001     {#1}
5002     {
5003       \exp_args:No \tl_if_head_is_space:nTF { \use_none:n #1 }
5004       {
5005         \exp_args:Nf \__tl_range_collect:nn
5006           { \__tl_range_collect_space:nw #1 }
5007           {#2}
5008       }
5009       {
5010         \__tl_range_collect:ff
5011         {
5012           \exp_args:No \tl_if_head_is_N_type:nTF { \use_none:n #1 }
5013           { \__tl_range_collect_N:nN }
5014           { \__tl_range_collect_group:nn }
5015           #1
5016         }
5017         { \int_eval:n { #2 - 1 } }
5018       }
5019     }
5020 }
5021 \cs_new:Npn \__tl_range_collect_space:nw #1 ~ { { #1 ~ } }
5022 \cs_new:Npn \__tl_range_collect_N:nN #1#2 { { #1 #2 } }
5023 \cs_new:Npn \__tl_range_collect_group:nn #1#2 { { #1 {#2} } }
5024 \cs_generate_variant:Nn \__tl_range_collect:nn { ff }

```

(End definition for `\tl_range:Nnn` and others. These functions are documented on page 48.)

`__tl_range_normalize:nn` This function converts an $\langle index \rangle$ argument into an explicit position in the token list (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the $\langle index \rangle$ #1 and the string count #2. If #1 is negative, replace it by $\#1 + \#2 + 1$, then limit to the range $[0, \#2]$.

```

5025 \cs_new:Npn \__tl_range_normalize:nn #1#2
5026 {
5027   \int_eval:n
5028   {
5029     \if_int_compare:w #1 < 0 \exp_stop_f:
5030     \if_int_compare:w #1 < -#2 \exp_stop_f:
5031     0
5032     \else:
5033       #1 + #2 + 1
5034     \fi:
5035     \else:
5036     \if_int_compare:w #1 < #2 \exp_stop_f:
5037     #1
5038     \else:
5039     #2
5040     \fi:
5041   \fi:
5042 }
5043 }

```

(End definition for `__tl_range_normalize:nn`.)

6.13 Viewing token lists

```

\!tl_show:N Showing token list variables is done after checking that the variable is defined (see \!tl_
\!tl_show:c kernel_register_show:N).
\!tl_log:N
\!tl_log:c
\!tl_show:NN
5044 \cs_new_protected:Npn \!tl_show:N { \!tl_show:NN \!tl_show:n }
5045 \cs_generate_variant:Nn \!tl_show:N { c }
5046 \cs_new_protected:Npn \!tl_log:N { \!tl_show:NN \!tl_log:n }
5047 \cs_generate_variant:Nn \!tl_log:N { c }
5048 \cs_new_protected:Npn \!tl_show:NN #1#2
5049 {
5050   \!kernel_chk_defined:NT #2
5051   { \exp_args:Nx #1 { \token_to_str:N #2 = \exp_not:o {#2} } }
5052 }

```

(End definition for `\!tl_show:N`, `\!tl_log:N`, and `\!tl_show:NN`. These functions are documented on page 49.)

```

\!tl_show:n Many show functions are based on \!tl_show:n. The argument of \!tl_show:n is line-
\!tl_show:n wrapped using \!ow_wrap:nnnN but with a leading >~ and trailing period, both removed
\!tl_show:w before passing the wrapped text to the \showtokens primitive. This primitive shows the
result with a leading >~ and trailing period.

```

The token list `\!tl_internal_a_tl` containing the result of all these manipulations is displayed to the terminal using `\tex_showtokens:D` and an odd `\exp_after:wN` which expand the closing brace to improve the output slightly. The calls to `\!kernel_!ow_with:Nnn` ensure that the `\newlinechar` is set to 10 so that the `\!ow_newline:` inserted by the line-wrapping code are correctly recognized by T_EX, and that `\errorcontextlines` is -1 to avoid printing irrelevant context.

```

5053 \cs_new_protected:Npn \!tl_show:n #1
5054 { \!ow_wrap:nnnN { >~ \!tl_to_str:n {#1} . } { } { } \!tl_show:n }
5055 \cs_new_protected:Npn \!tl_show:NN #1
5056 {
5057   \!tl_set:Nf \!tl_internal_a_tl { \!tl_show:w #1 \q_stop }
5058   \!kernel_!ow_with:Nnn \tex_newlinechar:D { 10 }
5059   {
5060     \!kernel_!ow_with:Nnn \tex_errorcontextlines:D { -1 }
5061     {
5062       \tex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
5063       { \exp_after:wN \!tl_internal_a_tl }
5064     }
5065   }
5066 }
5067 \cs_new:Npn \!tl_show:w #1 > #2 . \q_stop {#2}

```

(End definition for `\!tl_show:n`, `\!tl_show:NN`, and `\!tl_show:w`. This function is documented on page 49.)

```

\!tl_log:n Logging is much easier, simply line-wrap. The >~ and trailing period is there to match
the output of \!tl_show:n.

```

```

5068 \cs_new_protected:Npn \!tl_log:n #1
5069 { \!ow_wrap:nnnN { > ~ \!tl_to_str:n {#1} . } { } { } \!ow_log:n }

```

(End definition for `\!tl_log:n`. This function is documented on page 49.)

6.14 Scratch token lists

\g_tmpa_tl **\g_tmpb_tl** Global temporary token list variables. They are supposed to be set and used immediately, with no delay between the definition and the use because you can't count on other macros not to redefine them from under you.

```
5070 \tl_new:N \g_tmpa_tl
5071 \tl_new:N \g_tmpb_tl
```

(End definition for \g_tmpa_tl and \g_tmpb_tl. These variables are documented on page 50.)

\l_tmpa_tl **\l_tmpb_tl** These are local temporary token list variables. Be sure not to assume that the value you put into them will survive for long—see discussion above.

```
5072 \tl_new:N \l_tmpa_tl
5073 \tl_new:N \l_tmpb_tl
```

(End definition for \l_tmpa_tl and \l_tmpb_tl. These variables are documented on page 50.)

```
5074 </initex | package>
```

7 l3str implementation

```
5075 <*initex | package>
```

```
5076 <@@=str>
```

7.1 Creating and setting string variables

\str_new:N **\str_new:c** A string is simply a token list. The full mapping system isn't set up yet so do things by hand.

```
\str_use:N 5077 \group_begin:
\str_use:c 5078 \cs_set_protected:Npn \__str_tmp:n #1
\str_clear:N 5079 {
\str_clear:c 5080 \tl_if_blank:nF {#1}
\str_gclear:N 5081 {
\str_gclear:c 5082 \cs_new_eq:cc { str_ #1 :N } { tl_ #1 :N }
\str_clear_new:N 5083 \exp_args:Nc \cs_generate_variant:Nn { str_ #1 :N } { c }
\str_gclear_new:c 5084 \__str_tmp:n
\str_gclear_new:N 5085 }
\str_gclear_new:c 5086 }
\str_set_eq:NN 5087 \__str_tmp:n
\str_set_eq:cN 5088 { new }
\str_set_eq:Nc 5089 { use }
\str_set_eq:cc 5090 { clear }
\str_gset_eq:cc 5091 { gclear }
\str_gset_eq:NN 5092 { clear_new }
\str_gset_eq:cN 5093 { gclear_new }
\str_gset_eq:Nc 5094 { }
\str_gset_eq:cc 5095 \group_end:
\str_concat:NNN 5096 \cs_new_eq:NN \str_set_eq:NN \tl_set_eq:NN
\str_concat:ccc 5097 \cs_new_eq:NN \str_gset_eq:NN \tl_gset_eq:NN
\str_gconcat:NNN 5098 \cs_generate_variant:Nn \str_set_eq:NN { c , Nc , cc }
\str_gconcat:ccc 5099 \cs_generate_variant:Nn \str_gset_eq:NN { c , Nc , cc }
5100 \cs_new_eq:NN \str_concat:NNN \tl_concat:NNN
5101 \cs_new_eq:NN \str_gconcat:NNN \tl_gconcat:NNN
5102 \cs_generate_variant:Nn \str_concat:NNN { ccc }
5103 \cs_generate_variant:Nn \str_gconcat:NNN { ccc }
```

(End definition for `\str_new:N` and others. These functions are documented on page 51.)

```

\str_set:Nn Simply convert the token list inputs to  $\langle strings \rangle$ .
\str_set:NV
\str_set:Nx 5104 \group_begin:
\str_set:cn 5105 \cs_set_protected:Npn \__str_tmp:n #1
\str_set:cV 5106 {
\str_set:cx 5107 \tl_if_blank:nF {#1}
5108 {
\str_gset:Nn 5109 \cs_new_protected:cpx { str_ #1 :Nn } ##1##2
\str_gset:NV 5110 {
\str_gset:Nx 5111 \exp_not:c { tl_ #1 :Nx } ##1
\str_gset:cn 5112 { \exp_not:N \tl_to_str:n {##2} }
\str_gset:cV 5113 }
\str_gset:cx 5114 \cs_generate_variant:cn { str_ #1 :Nn } { NV , Nx , cn , cV , cx }
\str_const:Nn 5115 \__str_tmp:n
\str_const:NV 5116 }
\str_const:Nx 5117 \__str_tmp:n
\str_const:cn 5118 { set }
\str_const:cV 5119 { gset }
\str_const:cx 5120 { const }
\str_put_left:Nn 5121 { put_left }
\str_put_left:NV 5122 { gput_left }
\str_put_left:Nx 5123 { put_right }
\str_put_left:cn 5124 { gput_right }
\str_put_left:cV 5125 { }
\str_put_left:cx 5126 }
\str_gput_left:Nn 5127 \group_end:

```

(End definition for `\str_set:Nn` and others. These functions are documented on page 52.)

7.2 Modifying string variables

Start by applying `\tl_to_str:n` to convert the old and new token lists to strings, and also apply `\tl_to_str:N` to avoid any issues if we are fed a token list variable. Then the code is a much simplified version of the token list code because neither the delimiter nor the replacement can contain macro parameters or braces. The delimiter `\q_mark` cannot appear in the string to edit so it is used in all cases. Some x-expansion is unnecessary. There is no need to avoid losing braces nor to protect against expansion. The ending code is much simplified and does not need to hide in braces.

```

\str_replace_all:Nnn 5128 \cs_new_protected:Npn \str_replace_once:Nnn
\str_gput_left:cn 5129 { \__str_replace:NNNnn \prg_do_nothing: \tl_set:Nx }
\str_gput_left:cV 5130 \cs_new_protected:Npn \str_greplace_once:Nnn
\str_gput_left:cx 5131 { \__str_replace:NNNnn \prg_do_nothing: \tl_gset:Nx }
\str_greplace_all:Nnn 5132 \cs_new_protected:Npn \str_replace_all:Nnn
\str_gput_right:Nn 5133 { \__str_replace:NNNnn \__str_replace_next:w \tl_set:Nx }
\str_gput_right:Nx 5134 \cs_new_protected:Npn \str_greplace_all:Nnn
\str_gput_right:cn 5135 { \__str_replace:NNNnn \__str_replace_next:w \tl_gset:Nx }
\str_gput_right:cV 5136 \cs_generate_variant:Nn \str_replace_once:Nnn { c }
\str_gput_right:cx 5137 \cs_generate_variant:Nn \str_greplace_once:Nnn { c }
\__str_replace_aux:NNNnn 5138 \cs_generate_variant:Nn \str_replace_all:Nnn { c }
\__str_replace_next:w 5139 \cs_generate_variant:Nn \str_greplace_all:Nnn { c }
\str_gput_right:Nx 5140 \cs_new_protected:Npn \__str_replace:NNNnn #1#2#3#4#5
\str_gput_right:cn 5141 {
\str_gput_right:cV
\str_gput_right:cx

```

```

5142 \tl_if_empty:nTF {#4}
5143 {
5144   \__kernel_msg_error:nxx { kernel } { empty-search-pattern } {#5}
5145 }
5146 {
5147   \use:x
5148   {
5149     \exp_not:n { \__str_replace_aux:NNNnnn #1 #2 #3 }
5150     { \tl_to_str:N #3 }
5151     { \tl_to_str:n {#4} } { \tl_to_str:n {#5} }
5152   }
5153 }
5154 }
5155 \cs_new_protected:Npn \__str_replace_aux:NNNnnn #1#2#3#4#5#6
5156 {
5157   \cs_set:Npn \__str_replace_next:w ##1 #5 { ##1 #6 #1 }
5158   #2 #3
5159   {
5160     \__str_replace_next:w
5161     #4
5162     \use_none_delimit_by_q_stop:w
5163     #5
5164     \q_stop
5165   }
5166 }
5167 \cs_new_eq:NN \__str_replace_next:w ?

```

(End definition for `\str_replace_all:Nnn` and others. These functions are documented on page 53.)

```

\str_remove_once:Nn Removal is just a special case of replacement.
\str_remove_once:cn 5168 \cs_new_protected:Npn \str_remove_once:Nn #1#2
\str_gremove_once:Nn 5169 { \str_replace_once:Nnn #1 {#2} { } }
\str_gremove_once:cn 5170 \cs_new_protected:Npn \str_gremove_once:Nn #1#2
5171 { \str_greplace_once:Nnn #1 {#2} { } }
5172 \cs_generate_variant:Nn \str_remove_once:Nn { c }
5173 \cs_generate_variant:Nn \str_gremove_once:Nn { c }

```

(End definition for `\str_remove_once:Nn` and `\str_gremove_once:Nn`. These functions are documented on page 53.)

```

\str_remove_all:Nn Removal is just a special case of replacement.
\str_remove_all:cn 5174 \cs_new_protected:Npn \str_remove_all:Nn #1#2
\str_gremove_all:Nn 5175 { \str_replace_all:Nnn #1 {#2} { } }
\str_gremove_all:cn 5176 \cs_new_protected:Npn \str_gremove_all:Nn #1#2
5177 { \str_greplace_all:Nnn #1 {#2} { } }
5178 \cs_generate_variant:Nn \str_remove_all:Nn { c }
5179 \cs_generate_variant:Nn \str_gremove_all:Nn { c }

```

(End definition for `\str_remove_all:Nn` and `\str_gremove_all:Nn`. These functions are documented on page 53.)

7.3 String comparisons

```

\str_if_empty_p:N More copy-paste!
\str_if_empty_p:c 5180 \prg_new_eq_conditional:NNn \str_if_exist:N \tl_if_exist:N
\str_if_empty:N $\overline{TF}$  5181 { p , T , F , TF }
\str_if_empty:c $\overline{TF}$  5182 \prg_new_eq_conditional:NNn \str_if_exist:c \tl_if_exist:c
\str_if_exist_p:N 5183 { p , T , F , TF }
\str_if_exist_p:c 5184 \prg_new_eq_conditional:NNn \str_if_empty:N \tl_if_empty:N
\str_if_exist:N $\overline{TF}$  5185 { p , T , F , TF }
\str_if_exist:c $\overline{TF}$  5186 \prg_new_eq_conditional:NNn \str_if_empty:c \tl_if_empty:c
5187 { p , T , F , TF }

```

(End definition for `\str_if_empty:N \overline{TF}` and `\str_if_exist:N \overline{TF}` . These functions are documented on page 54.)

`__str_if_eq:nn` String comparisons rely on the primitive `\(pdf)strcmp` if available: LuaTeX does not have it, so emulation is required. As the net result is that we do not *always* use the primitive, the correct approach is to wrap up in a function with defined behaviour. That's done by providing a wrapper and then redefining in the LuaTeX case. Note that the necessary Lua code is loaded in `l3bootstrap`. The need to detokenize and force expansion of input arises from the case where a `#` token is used in the input, e.g. `__str_if_eq:nn {#} { \tl_to_str:n {#} }`, which otherwise would fail as `\tex_luaescapestring:D` does not double such tokens.

```

5188 \cs_new:Npn __str_if_eq:nn #1#2 { \tex_strcmp:D {#1} {#2} }
5189 \cs_if_exist:NT \tex luatexversion:D
5190 {
5191     \cs_set_eq:NN \lua_escape:e \tex_luaescapestring:D
5192     \cs_set_eq:NN \lua_now:e \tex_directlua:D
5193     \cs_set:Npn __str_if_eq:nn #1#2
5194     {
5195         \lua_now:e
5196         {
5197             l3kernel_strcmp
5198             (
5199                 " __str_escape:n {#1} " ,
5200                 " __str_escape:n {#2} "
5201             )
5202         }
5203     }
5204     \cs_new:Npn __str_escape:n #1
5205     {
5206         \lua_escape:e
5207         { \__kernel_tl_to_str:w \use:e { {#1} } }
5208     }
5209 }

```

(End definition for `__str_if_eq:nn` and `__str_escape:n`.)

`\str_if_eq:p:nn` Modern engines provide a direct way of comparing two token lists, but returning a number. This set of conditionals therefore make life a bit clearer. The `nn` and `xx` versions are created directly as this is most efficient.

```

\str_if_eq_p:Vn 5210 \prg_new_conditional:Npnn \str_if_eq:nn #1#2 { p , T , F , TF }
\str_if_eq_p:on 5211 {
\str_if_eq_p:nV 5212     \if_int_compare:w
\str_if_eq_p:no
\str_if_eq_p:VV
\str_if_eq:nn $\overline{TF}$ 
\str_if_eq:Vn $\overline{TF}$ 
\str_if_eq:on $\overline{TF}$ 
\str_if_eq:nV $\overline{TF}$ 
\str_if_eq:no $\overline{TF}$ 
\str_if_eq:VV $\overline{TF}$ 
\str_if_eq_p:ee
\str_if_eq:ee $\overline{TF}$ 

```

```

5213     \_str_if_eq:nn { \exp_not:n {#1} } { \exp_not:n {#2} }
5214     = 0 \exp_stop_f:
5215     \prg_return_true: \else: \prg_return_false: \fi:
5216   }
5217 \prg_generate_conditional_variant:Nnn \str_if_eq:nn
5218 { V , v , o , nV , no , VV , nv } { p , T , F , TF }
5219 \prg_new_conditional:Npnn \str_if_eq:ee #1#2 { p , T , F , TF }
5220 {
5221   \if_int_compare:w \_str_if_eq:nn {#1} {#2} = 0 \exp_stop_f:
5222   \prg_return_true: \else: \prg_return_false: \fi:
5223 }

```

(End definition for \str_if_eq:nnTF and \str_if_eq:eeTF. These functions are documented on page 54.)

\str_if_eq:p:NN Note that \str_if_eq:NN is different from \tl_if_eq:NN because it needs to ignore category codes.

```

\str_if_eq:p:Nc
\str_if_eq:p:cN
\str_if_eq:p:cc
\str_if_eq:NNTF
\str_if_eq:NcTF
\str_if_eq:cNTF
\str_if_eq:ccTF
5224 \prg_new_conditional:Npnn \str_if_eq:NN #1#2 { p , TF , T , F }
5225 {
5226   \if_int_compare:w
5227     \_str_if_eq:nn { \tl_to_str:N #1 } { \tl_to_str:N #2 }
5228     = 0 \exp_stop_f: \prg_return_true: \else: \prg_return_false: \fi:
5229 }
5230 \prg_generate_conditional_variant:Nnn \str_if_eq:NN
5231 { c , Nc , cc } { T , F , TF , p }

```

(End definition for \str_if_eq:NNTF. This function is documented on page 54.)

\str_if_in:NnTF Everything here needs to be detokenized but beyond that it is a simple token list test.
\str_if_in:cnTF It would be faster to fine-tune the T, F, TF variants by calling the appropriate variant of
\str_if_in:nnTF \tl_if_in:nnTF directly but that takes more code.

```

5232 \prg_new_protected_conditional:Npnn \str_if_in:Nn #1#2 { T , F , TF }
5233 {
5234   \use:x
5235   { \tl_if_in:nnTF { \tl_to_str:N #1 } { \tl_to_str:n {#2} } }
5236   { \prg_return_true: } { \prg_return_false: }
5237 }
5238 \prg_generate_conditional_variant:Nnn \str_if_in:Nn
5239 { c } { T , F , TF }
5240 \prg_new_protected_conditional:Npnn \str_if_in:nn #1#2 { T , F , TF }
5241 {
5242   \use:x
5243   { \tl_if_in:nnTF { \tl_to_str:n {#1} } { \tl_to_str:n {#2} } }
5244   { \prg_return_true: } { \prg_return_false: }
5245 }

```

(End definition for \str_if_in:NnTF and \str_if_in:nnTF. These functions are documented on page 54.)

\str_case:nn Much the same as \tl_case:nn(TF) here: just a change in the internal comparison.

```

\str_case:on
\str_case:nV
\str_case:nv
\str_case:nnTF
\str_case:onTF
\str_case:nVTF
\str_case:nvTF
5246 \cs_new:Npn \str_case:nn #1#2
5247 {
5248   \exp:w
5249   \_str_case:nnTF {#1} {#2} { } { }
5250 }

```

```

\str_case_e:nn
\str_case_e:nnTF
\_str_case:nnTF
\_str_case_e:nnTF
\_str_case:nw
\_str_case_e:nw
\_str_case_end:nw

```



```

5251 \cs_new:Npn \str_case:nnT #1#2#3
5252 {
5253   \exp:w
5254   \__str_case:nnTF {#1} {#2} {#3} { }
5255 }
5256 \cs_new:Npn \str_case:nnF #1#2
5257 {
5258   \exp:w
5259   \__str_case:nnTF {#1} {#2} { }
5260 }
5261 \cs_new:Npn \str_case:nnTF #1#2
5262 {
5263   \exp:w
5264   \__str_case:nnTF {#1} {#2}
5265 }
5266 \cs_new:Npn \__str_case:nnTF #1#2#3#4
5267 { \__str_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
5268 \cs_generate_variant:Nn \str_case:nn { o , nV , nv }
5269 \prg_generate_conditional_variant:Nnn \str_case:nn
5270 { o , nV , nv } { T , F , TF }
5271 \cs_new:Npn \__str_case:nw #1#2#3
5272 {
5273   \str_if_eq:nnTF {#1} {#2}
5274   { \__str_case_end:nw {#3} }
5275   { \__str_case:nw {#1} }
5276 }
5277 \cs_new:Npn \str_case_e:nn #1#2
5278 {
5279   \exp:w
5280   \__str_case_e:nnTF {#1} {#2} { } { }
5281 }
5282 \cs_new:Npn \str_case_e:nnT #1#2#3
5283 {
5284   \exp:w
5285   \__str_case_e:nnTF {#1} {#2} {#3} { }
5286 }
5287 \cs_new:Npn \str_case_e:nnF #1#2
5288 {
5289   \exp:w
5290   \__str_case_e:nnTF {#1} {#2} { }
5291 }
5292 \cs_new:Npn \str_case_e:nnTF #1#2
5293 {
5294   \exp:w
5295   \__str_case_e:nnTF {#1} {#2}
5296 }
5297 \cs_new:Npn \__str_case_e:nnTF #1#2#3#4
5298 { \__str_case_e:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
5299 \cs_new:Npn \__str_case_e:nw #1#2#3
5300 {
5301   \str_if_eq:eeTF {#1} {#2}
5302   { \__str_case_end:nw {#3} }
5303   { \__str_case_e:nw {#1} }
5304 }

```

```

5305 \cs_new:Npn \__str_case_end:nw #1#2#3 \q_mark #4#5 \q_stop
5306 { \exp_end: #1 #4 }

```

(End definition for `\str_case:nnTF` and others. These functions are documented on page 55.)

7.4 Mapping to strings

```

\str_map_function:NN The inline and variable mappings are similar to the usual token list mappings but start
\str_map_function:cN out by turning the argument to an “other string”. Doing the same for the expandable
\str_map_function:nN function mapping would require \__kernel_str_to_other:n, quadratic in the string
\str_map_inline:NN length. To deal with spaces in that case, \__str_map_function:w replaces the following
\str_map_inline:cN space by a braced space and a further call to itself. These are received by \__str_
\str_map_inline:nn map_function:Nn, which passes the space to #1 and calls \__str_map_function:w to
\str_map_variable:NNn deal with the next space. The space before the braced space allows to optimize the \q_
\str_map_variable:cN recursion_tail test. Of course we need to include a trailing space (the question mark
\str_map_variable:nn is needed to avoid losing the space when TEX tokenizes the line). At the cost of about
\str_map_break: three more auxiliaries this code could get a 9 times speed up by testing only every 9-th
\str_map_break:n character for whether it is \q_recursion_tail (also by converting 9 spaces at a time in
\__str_map_function:w the \str_map_function:nN case).
\__str_map_function:Nn
\__str_map_inline:NN
\__str_map_variable:NnN

```

```

5307 \cs_new:Npn \str_map_function:nN #1#2
5308 {
5309   \exp_after:wN \__str_map_function:w
5310   \exp_after:wN \__str_map_function:Nn \exp_after:wN #2
5311   \__kernel_tl_to_str:w {#1}
5312   \q_recursion_tail ? ~
5313   \prg_break_point:Nn \str_map_break: { }
5314 }
5315 \cs_new:Npn \str_map_function:NN
5316 { \exp_args:No \str_map_function:nN }
5317 \cs_new:Npn \__str_map_function:w #1 ~
5318 { #1 { ~ { ~ } \__str_map_function:w } }
5319 \cs_new:Npn \__str_map_function:Nn #1#2
5320 {
5321   \if_meaning:w \q_recursion_tail #2
5322   \exp_after:wN \str_map_break:
5323   \fi:
5324   #1 #2 \__str_map_function:Nn #1
5325 }
5326 \cs_generate_variant:Nn \str_map_function:NN { c }
5327 \cs_new_protected:Npn \str_map_inline:nn #1#2
5328 {
5329   \int_gincr:N \g__kernel_prg_map_int
5330   \cs_gset_protected:cpn
5331   { __str_map_ \int_use:N \g__kernel_prg_map_int :w } ##1 {#2}
5332   \use:x
5333   {
5334     \exp_not:N \__str_map_inline:NN
5335     \exp_not:c { __str_map_ \int_use:N \g__kernel_prg_map_int :w }
5336     \__kernel_str_to_other_fast:n {#1}
5337   }
5338   \q_recursion_tail
5339   \prg_break_point:Nn \str_map_break:
5340   { \int_gdecr:N \g__kernel_prg_map_int }

```

```

5341 }
5342 \cs_new_protected:Npn \str_map_inline:Nn
5343 { \exp_args:No \str_map_inline:nn }
5344 \cs_generate_variant:Nn \str_map_inline:Nn { c }
5345 \cs_new:Npn \__str_map_inline:NN #1#2
5346 {
5347   \quark_if_recursion_tail_break:NN #2 \str_map_break:
5348   \exp_args:No #1 { \token_to_str:N #2 }
5349   \__str_map_inline:NN #1
5350 }
5351 \cs_new_protected:Npn \str_map_variable:nNn #1#2#3
5352 {
5353   \use:x
5354   {
5355     \exp_not:n { \__str_map_variable:NnN #2 {#3} }
5356     \__kernel_str_to_other_fast:n {#1}
5357   }
5358   \q_recursion_tail
5359   \prg_break_point:Nn \str_map_break: { }
5360 }
5361 \cs_new_protected:Npn \str_map_variable:NNn
5362 { \exp_args:No \str_map_variable:nNn }
5363 \cs_new_protected:Npn \__str_map_variable:NnN #1#2#3
5364 {
5365   \quark_if_recursion_tail_break:NN #3 \str_map_break:
5366   \str_set:Nn #1 {#3}
5367   \use:n {#2}
5368   \__str_map_variable:NnN #1 {#2}
5369 }
5370 \cs_generate_variant:Nn \str_map_variable:NNn { c }
5371 \cs_new:Npn \str_map_break:
5372 { \prg_map_break:Nn \str_map_break: { } }
5373 \cs_new:Npn \str_map_break:n
5374 { \prg_map_break:Nn \str_map_break: }

```

(End definition for `\str_map_function:NN` and others. These functions are documented on page 55.)

7.5 Accessing specific characters in a string

`__kernel_str_to_other:n` First apply `\tl_to_str:n`, then replace all spaces by “other” spaces, 8 at a time, storing the converted part of the string between the `\q_mark` and `\q_stop` markers. The end is detected when `__str_to_other_loop:w` finds one of the trailing A, distinguished from any contents of the initial token list by their category. Then `__str_to_other_end:w` is called, and finds the result between `\q_mark` and the first A (well, there is also the need to remove a space).

```

5375 \cs_new:Npn \__kernel_str_to_other:n #1
5376 {
5377   \exp_after:wN \__str_to_other_loop:w
5378   \tl_to_str:n {#1} ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_mark \q_stop
5379 }
5380 \group_begin:
5381 \tex_lccode:D ‘\* = ‘\ %
5382 \tex_lccode:D ‘\A = ‘\A %
5383 \tex_lowercase:D

```

```

5384 {
5385   \group_end:
5386   \cs_new:Npn \__str_to_other_loop:w
5387     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 \q_stop
5388   {
5389     \if_meaning:w A #8
5390     \__str_to_other_end:w
5391     \fi:
5392     \__str_to_other_loop:w
5393     #9 #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * \q_stop
5394   }
5395   \cs_new:Npn \__str_to_other_end:w \fi: #1 \q_mark #2 * A #3 \q_stop
5396   { \fi: #2 }
5397 }

```

(End definition for `__kernel_str_to_other:n`, `__str_to_other_loop:w`, and `__str_to_other_end:w`.)

```

\__kernel_str_to_other_fast:n
\__kernel_str_to_other_fast_loop:w
\__str_to_other_fast_end:w

```

The difference with `__kernel_str_to_other:n` is that the converted part is left in the input stream, making these commands only restricted-expandable.

```

5398 \cs_new:Npn \__kernel_str_to_other_fast:n #1
5399 {
5400   \exp_after:wN \__str_to_other_fast_loop:w \tl_to_str:n {#1} ~
5401   A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ A ~ \q_stop
5402 }
5403 \group_begin:
5404 \tex_lccode:D '\* = '\ %
5405 \tex_lccode:D '\A = '\A %
5406 \tex_lowercase:D
5407 {
5408   \group_end:
5409   \cs_new:Npn \__str_to_other_fast_loop:w
5410     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 ~ #7 ~ #8 ~ #9 ~
5411   {
5412     \if_meaning:w A #9
5413     \__str_to_other_fast_end:w
5414     \fi:
5415     #1 * #2 * #3 * #4 * #5 * #6 * #7 * #8 * #9
5416     \__str_to_other_fast_loop:w *
5417   }
5418   \cs_new:Npn \__str_to_other_fast_end:w #1 * A #2 \q_stop {#1}
5419 }

```

(End definition for `__kernel_str_to_other_fast:n`, `__kernel_str_to_other_fast_loop:w`, and `__str_to_other_fast_end:w`.)

`\str_item:Nn` The `\str_item:nn` hands its argument with spaces escaped to `__str_item:nn`, and **`\str_item:cn`** makes sure to turn the result back into a proper string (with category code 10 spaces) eventually. The **`\str_item_ignore_spaces:nn`** function does not escape spaces, which are thus ignored by `__str_item:nn` since everything else is done with undelimited arguments. Evaluate the $\langle index \rangle$ argument #2 and count characters in the string, passing those two numbers to `__str_item:w` for further analysis. If the $\langle index \rangle$ is negative, shift it by the $\langle count \rangle$ to know the how many character to discard, and if that is still negative give an empty result. If the $\langle index \rangle$ is larger than the $\langle count \rangle$, give an empty result, and

otherwise discard $\langle index \rangle - 1$ characters before returning the following one. The shift by -1 is obtained by inserting an empty brace group before the string in that case: that brace group also covers the case where the $\langle index \rangle$ is zero.

```

5420 \cs_new:Npn \str_item:Nn { \exp_args:No \str_item:nn }
5421 \cs_generate_variant:Nn \str_item:Nn { c }
5422 \cs_new:Npn \str_item:nn #1#2
5423 {
5424   \exp_args:Nf \tl_to_str:n
5425   {
5426     \exp_args:Nf \__str_item:nn
5427     { \__kernel_str_to_other:n {#1} } {#2}
5428   }
5429 }
5430 \cs_new:Npn \str_item_ignore_spaces:nn #1
5431 { \exp_args:No \__str_item:nn { \tl_to_str:n {#1} } }
5432 \cs_new:Npn \__str_item:nn #1#2
5433 {
5434   \exp_after:wN \__str_item:w
5435   \int_value:w \int_eval:n {#2} \exp_after:wN ;
5436   \int_value:w \__str_count:n {#1} ;
5437   #1 \q_stop
5438 }
5439 \cs_new:Npn \__str_item:w #1; #2;
5440 {
5441   \int_compare:nNnTF {#1} < 0
5442   {
5443     \int_compare:nNnTF {#1} < {-#2}
5444     { \use_none_delimit_by_q_stop:w }
5445     {
5446       \exp_after:wN \use_i_delimit_by_q_stop:nw
5447       \exp:w \exp_after:wN \__str_skip_exp_end:w
5448       \int_value:w \int_eval:n { #1 + #2 } ;
5449     }
5450   }
5451   {
5452     \int_compare:nNnTF {#1} > {#2}
5453     { \use_none_delimit_by_q_stop:w }
5454     {
5455       \exp_after:wN \use_i_delimit_by_q_stop:nw
5456       \exp:w \__str_skip_exp_end:w #1 ; { }
5457     }
5458   }
5459 }

```

(End definition for `\str_item:Nn` and others. These functions are documented on page 58.)

<pre> __str_skip_exp_end:w __str_skip_loop:wNNNNNNNN __str_skip_end:w __str_skip_end:NNNNNNNN </pre>	<p>Removes $\max(\#1, 0)$ characters from the input stream, and then leaves <code>\exp_end:</code>. This should be expanded using <code>\exp:w</code>. We remove characters 8 at a time until there are at most 8 to remove. Then we do a dirty trick: the <code>\if_case:w</code> construction leaves between 0 and 8 times the <code>\or:</code> control sequence, and those <code>\or:</code> become arguments of <code>__str_skip_end:NNNNNNNN</code>. If the number of characters to remove is 6, say, then there are two <code>\or:</code> left, and the 8 arguments of <code>__str_skip_end:NNNNNNNN</code> are the two <code>\or:</code>, and 6 characters from the input stream, exactly what we wanted to remove. Then close</p>
--	---

the `\if_case:w` conditional with `\fi:`, and stop the initial expansion with `\exp_end:` (see places where `__str_skip_exp_end:w` is called).

```

5460 \cs_new:Npn \__str_skip_exp_end:w #1;
5461 {
5462   \if_int_compare:w #1 > 8 \exp_stop_f:
5463     \exp_after:wN \__str_skip_loop:wNNNNNNNN
5464   \else:
5465     \exp_after:wN \__str_skip_end:w
5466     \int_value:w \int_eval:w
5467   \fi:
5468   #1 ;
5469 }
5470 \cs_new:Npn \__str_skip_loop:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
5471 {
5472   \exp_after:wN \__str_skip_exp_end:w
5473   \int_value:w \int_eval:n { #1 - 8 } ;
5474 }
5475 \cs_new:Npn \__str_skip_end:w #1 ;
5476 {
5477   \exp_after:wN \__str_skip_end:NNNNNNNN
5478   \if_case:w #1 \exp_stop_f: \or: \or: \or: \or: \or: \or: \or: \or:
5479 }
5480 \cs_new:Npn \__str_skip_end:NNNNNNNN #1#2#3#4#5#6#7#8 { \fi: \exp_end: }

```

(End definition for `__str_skip_exp_end:w` and others.)

`\str_range:Nnn`
`\str_range:nnn`
`\str_range_ignore_spaces:nnn`
`__str_range:nnn`
`__str_range:w`
`__str_range:nnw`

Sanitize the string. Then evaluate the arguments. At this stage we also decrement the `<start index>`, since our goal is to know how many characters should be removed. Then limit the range to be non-negative and at most the length of the string (this avoids needing to check for the end of the string when grabbing characters), shifting negative numbers by the appropriate amount. Afterwards, skip characters, then keep some more, and finally drop the end of the string.

```

5481 \cs_new:Npn \str_range:Nnn { \exp_args:No \str_range:nnn }
5482 \cs_generate_variant:Nn \str_range:Nnn { c }
5483 \cs_new:Npn \str_range:nnn #1#2#3
5484 {
5485   \exp_args:Nf \tl_to_str:n
5486   {
5487     \exp_args:Nf \__str_range:nnn
5488     { \__kernel_str_to_other:n {#1} } {#2} {#3}
5489   }
5490 }
5491 \cs_new:Npn \str_range_ignore_spaces:nnn #1
5492 { \exp_args:No \__str_range:nnn { \tl_to_str:n {#1} } }
5493 \cs_new:Npn \__str_range:nnn #1#2#3
5494 {
5495   \exp_after:wN \__str_range:w
5496   \int_value:w \__str_count:n {#1} \exp_after:wN ;
5497   \int_value:w \int_eval:n { (#2) - 1 } \exp_after:wN ;
5498   \int_value:w \int_eval:n {#3} ;
5499   #1 \q_stop
5500 }
5501 \cs_new:Npn \__str_range:w #1; #2; #3;
5502 {

```

```

5503     \exp_args:Nf \__str_range:nnw
5504     { \__str_range_normalize:nn {#2} {#1} }
5505     { \__str_range_normalize:nn {#3} {#1} }
5506   }
5507 \cs_new:Npn \__str_range:nnw #1#2
5508 {
5509     \exp_after:wN \__str_collect_delimit_by_q_stop:w
5510     \int_value:w \int_eval:n { #2 - #1 } \exp_after:wN ;
5511     \exp:w \__str_skip_exp_end:w #1 ;
5512 }

```

(End definition for `\str_range:Nnn` and others. These functions are documented on page 59.)

`__str_range_normalize:nn` This function converts an *<index>* argument into an explicit position in the string (a result of 0 denoting “out of bounds”). Expects two explicit integer arguments: the *<index>* #1 and the string count #2. If #1 is negative, replace it by #1 + #2 + 1, then limit to the range [0, #2].

```

5513 \cs_new:Npn \__str_range_normalize:nn #1#2
5514 {
5515     \int_eval:n
5516     {
5517         \if_int_compare:w #1 < 0 \exp_stop_f:
5518         \if_int_compare:w #1 < -#2 \exp_stop_f:
5519             0
5520         \else:
5521             #1 + #2 + 1
5522         \fi:
5523     \else:
5524         \if_int_compare:w #1 < #2 \exp_stop_f:
5525             #1
5526         \else:
5527             #2
5528         \fi:
5529     \fi:
5530 }
5531 }

```

(End definition for `__str_range_normalize:nn`.)

`_str_collect_delimit_by_q_stop:w` Collects `max(#1,0)` characters, and removes everything else until `\q_stop`. This is somewhat similar to `__str_skip_exp_end:w`, but accepts integer expression arguments. This time we can only grab 7 characters at a time. At the end, we use an `\if_case:w` trick again, so that the 8 first arguments of `__str_collect_end:nnnnnnnnw` are some `\or:`, followed by an `\fi:`, followed by #1 characters from the input stream. Simply leaving this in the input stream closes the conditional properly and the `\or:` disappear.

```

5532 \cs_new:Npn \__str_collect_delimit_by_q_stop:w #1;
5533 { \__str_collect_loop:wn #1 ; { } }
5534 \cs_new:Npn \__str_collect_loop:wn #1 ;
5535 {
5536     \if_int_compare:w #1 > 7 \exp_stop_f:
5537     \exp_after:wN \__str_collect_loop:wnNNNNNNN
5538 \else:
5539     \exp_after:wN \__str_collect_end:wn
5540 \fi:

```

```

5541     #1 ;
5542   }
5543 \cs_new:Npn \__str_collect_loop:wnNNNNNNN #1; #2 #3#4#5#6#7#8#9
5544   {
5545     \exp_after:wN \__str_collect_loop:wn
5546     \int_value:w \int_eval:n { #1 - 7 } ;
5547     { #2 #3#4#5#6#7#8#9 }
5548   }
5549 \cs_new:Npn \__str_collect_end:wn #1 ;
5550   {
5551     \exp_after:wN \__str_collect_end:nnnnnnnnw
5552     \if_case:w \if_int_compare:w #1 > 0 \exp_stop_f:
5553       #1 \else: 0 \fi: \exp_stop_f:
5554     \or: \or: \or: \or: \or: \or: \or: \fi:
5555   }
5556 \cs_new:Npn \__str_collect_end:nnnnnnnnw #1#2#3#4#5#6#7#8 #9 \q_stop
5557   { #1#2#3#4#5#6#7#8 }

```

(End definition for `__str_collect_delimit_by_q_stop:w` and others.)

7.6 Counting characters

`\str_count_spaces:N` To speed up this function, we grab and discard 9 space-delimited arguments in each iteration of the loop. The loop stops when the last argument is one of the trailing $X\langle number \rangle$, and that $\langle number \rangle$ is added to the sum of 9 that precedes, to adjust the result.

```

5558 \cs_new:Npn \str_count_spaces:N
5559   { \exp_args:No \str_count_spaces:n }
5560 \cs_generate_variant:Nn \str_count_spaces:N { c }
5561 \cs_new:Npn \str_count_spaces:n #1
5562   {
5563     \int_eval:n
5564     {
5565       \exp_after:wN \__str_count_spaces_loop:w
5566       \tl_to_str:n {#1} ~
5567       X 7 ~ X 6 ~ X 5 ~ X 4 ~ X 3 ~ X 2 ~ X 1 ~ X 0 ~ X -1 ~
5568       \q_stop
5569     }
5570   }
5571 \cs_new:Npn \__str_count_spaces_loop:w #1~#2~#3~#4~#5~#6~#7~#8~#9~
5572   {
5573     \if_meaning:w X #9
5574       \use_i_delimit_by_q_stop:nw
5575     \fi:
5576     9 + \__str_count_spaces_loop:w
5577   }

```

(End definition for `\str_count_spaces:N`, `\str_count_spaces:n`, and `__str_count_spaces_loop:w`. These functions are documented on page 57.)

`\str_count:N` To count characters in a string we could first escape all spaces using `__kernel_str_to_other:n`, then pass the result to `\tl_count:n`. However, the escaping step would be quadratic in the number of characters in the string, and we can do better. Namely, sum

```

\str_count:N
\str_count:c
\str_count:n
\str_count_ignore_spaces:n
  \__str_count:n
  \__str_count_aux:n
\__str_count_loop:NNNNNNNNN

```


the number of spaces (`\str_count_spaces:n`) and the result of `\tl_count:n`, which ignores spaces. Since strings tend to be longer than token lists, we use specialized functions to count characters ignoring spaces. Namely, `loop`, grabbing 9 non-space characters at each step, and end as soon as we reach one of the 9 trailing items. The internal function `__str_count:n`, used in `\str_item:nn` and `\str_range:nnn`, is similar to `\str_count_ignore_spaces:n` but expects its argument to already be a string or a string with spaces escaped.

```

5578 \cs_new:Npn \str_count:N { \exp_args:No \str_count:n }
5579 \cs_generate_variant:Nn \str_count:N { c }
5580 \cs_new:Npn \str_count:n #1
5581 {
5582   \__str_count_aux:n
5583   {
5584     \str_count_spaces:n {#1}
5585     + \exp_after:wN \__str_count_loop:NNNNNNNNN \tl_to_str:n {#1}
5586   }
5587 }
5588 \cs_new:Npn \__str_count:n #1
5589 {
5590   \__str_count_aux:n
5591   { \__str_count_loop:NNNNNNNNN #1 }
5592 }
5593 \cs_new:Npn \str_count_ignore_spaces:n #1
5594 {
5595   \__str_count_aux:n
5596   { \exp_after:wN \__str_count_loop:NNNNNNNNN \tl_to_str:n {#1} }
5597 }
5598 \cs_new:Npn \__str_count_aux:n #1
5599 {
5600   \int_eval:n
5601   {
5602     #1
5603     { X 8 } { X 7 } { X 6 }
5604     { X 5 } { X 4 } { X 3 }
5605     { X 2 } { X 1 } { X 0 }
5606     \q_stop
5607   }
5608 }
5609 \cs_new:Npn \__str_count_loop:NNNNNNNNN #1#2#3#4#5#6#7#8#9
5610 {
5611   \if_meaning:w X #9
5612   \exp_after:wN \use_none_delimit_by_q_stop:w
5613   \fi:
5614   9 + \__str_count_loop:NNNNNNNNN
5615 }

```

(End definition for `\str_count:N` and others. These functions are documented on page 57.)

7.7 The first character in a string

`\str_head:N` The `_ignore_spaces` variant applies `\tl_to_str:n` then grabs the first item, thus skipping spaces. As usual, `\str_head:N` expands its argument and hands it to `\str_head:n`.

`\str_head:n`

`\str_head_ignore_spaces:n`

`__str_head:w`

To circumvent the fact that \TeX skips spaces when grabbing undelimited macro parameters, `__str_head:w` takes an argument delimited by a space. If `#1` starts with a non-space character, `\use_i_delimit_by_q_stop:nw` leaves that in the input stream. On the other hand, if `#1` starts with a space, the `__str_head:w` takes an empty argument, and the single (initially braced) space in the definition of `__str_head:w` makes its way to the output. Finally, for an empty argument, the (braced) empty brace group in the definition of `\str_head:n` gives an empty result after passing through `\use_i_delimit_by_q_stop:nw`.

```

5616 \cs_new:Npn \str_head:N { \exp_args:No \str_head:n }
5617 \cs_generate_variant:Nn \str_head:N { c }
5618 \cs_new:Npn \str_head:n #1
5619 {
5620   \exp_after:wN \__str_head:w
5621   \tl_to_str:n {#1}
5622   { { } } ~ \q_stop
5623 }
5624 \cs_new:Npn \__str_head:w #1 ~ %
5625 { \use_i_delimit_by_q_stop:nw #1 { ~ } }
5626 \cs_new:Npn \str_head_ignore_spaces:n #1
5627 {
5628   \exp_after:wN \use_i_delimit_by_q_stop:nw
5629   \tl_to_str:n {#1} { } \q_stop
5630 }

```

(End definition for `\str_head:N` and others. These functions are documented on page 58.)

`\str_tail:N` Getting the tail is a little bit more convoluted than the head of a string. We hit the front of the string with `\reverse_if:N` `\if_charcode:w` `\scan_stop:.` This removes the first character, and necessarily makes the test true, since the character cannot match `\scan_stop:.` The auxiliary function then inserts the required `\fi:` to close the conditional, and leaves the tail of the string in the input stream. The details are such that an empty string has an empty tail (this requires in particular that the end-marker `X` be unexpandable and not a control sequence). The `_ignore_spaces` is rather simpler: after converting the input to a string, `__str_tail_auxii:w` removes one undelimited argument and leaves everything else until an end-marker `\q_mark`. One can check that an empty (or blank) string yields an empty tail.

```

5631 \cs_new:Npn \str_tail:N { \exp_args:No \str_tail:n }
5632 \cs_generate_variant:Nn \str_tail:N { c }
5633 \cs_new:Npn \str_tail:n #1
5634 {
5635   \exp_after:wN \__str_tail_auxi:w
5636   \reverse_if:N \if_charcode:w
5637   \scan_stop: \tl_to_str:n {#1} X X \q_stop
5638 }
5639 \cs_new:Npn \__str_tail_auxi:w #1 X #2 \q_stop { \fi: #1 }
5640 \cs_new:Npn \str_tail_ignore_spaces:n #1
5641 {
5642   \exp_after:wN \__str_tail_auxii:w
5643   \tl_to_str:n {#1} \q_mark \q_mark \q_stop
5644 }
5645 \cs_new:Npn \__str_tail_auxii:w #1 #2 \q_mark #3 \q_stop { #2 }

```

(End definition for `\str_tail:N` and others. These functions are documented on page 58.)

7.8 String manipulation

Case changing for programmatic reasons is done by first detokenizing input then doing a simple loop that only has to worry about spaces and everything else. The output is detokenized to allow data sharing with text-based case changing.

```

\str_fold_case:n
\str_fold_case:V
\str_lower_case:n
\str_lower_case:f
\str_upper_case:n
\str_upper_case:f
__str_change_case:nn
__str_change_case_aux:nn
__str_change_case_result:n
__str_change_case_output:nw
__str_change_case_output:fw
__str_change_case_end:nw
__str_change_case_loop:nw
__str_change_case_space:n
__str_change_case_char:nN
5646 \cs_new:Npn \str_fold_case:n #1 { __str_change_case:nn {#1} { fold } }
5647 \cs_new:Npn \str_lower_case:n #1 { __str_change_case:nn {#1} { lower } }
5648 \cs_new:Npn \str_upper_case:n #1 { __str_change_case:nn {#1} { upper } }
5649 \cs_generate_variant:Nn \str_fold_case:n { V }
5650 \cs_generate_variant:Nn \str_lower_case:n { f }
5651 \cs_generate_variant:Nn \str_upper_case:n { f }
5652 \cs_new:Npn __str_change_case:nn #1
5653 {
5654   \exp_after:wN __str_change_case_aux:nn \exp_after:wN
5655   { \tl_to_str:n {#1} }
5656 }
5657 \cs_new:Npn __str_change_case_aux:nn #1#2
5658 {
5659   __str_change_case_loop:nw {#2} #1 \q_recursion_tail \q_recursion_stop
5660   __str_change_case_result:n { }
5661 }
5662 \cs_new:Npn __str_change_case_output:nw #1#2 __str_change_case_result:n #3
5663 { #2 __str_change_case_result:n { #3 #1 } }
5664 \cs_generate_variant:Nn __str_change_case_output:nw { f }
5665 \cs_new:Npn __str_change_case_end:wn #1 __str_change_case_result:n #2
5666 { \tl_to_str:n {#2} }
5667 \cs_new:Npn __str_change_case_loop:nw #1#2 \q_recursion_stop
5668 {
5669   \tl_if_head_is_space:nTF {#2}
5670   { __str_change_case_space:n }
5671   { __str_change_case_char:nN }
5672   {#1} #2 \q_recursion_stop
5673 }
5674 \exp_last_unbraced:NNNNo
5675 \cs_new:Npn __str_change_case_space:n #1 \c_space_tl
5676 {
5677   __str_change_case_output:nw { ~ }
5678   __str_change_case_loop:nw {#1}
5679 }
5680 \cs_new:Npn __str_change_case_char:nN #1#2
5681 {
5682   \quark_if_recursion_tail_stop_do:Nn #2
5683   { __str_change_case_end:wn }
5684   __str_change_case_output:fw
5685   { \use:c { char_ #1 _case:N } #2 }
5686   __str_change_case_loop:nw {#1}
5687 }

```

(End definition for `\str_fold_case:n` and others. These functions are documented on page 61.)

For all of those strings, use `\cs_to_str:N` to get characters with the correct category code without worries

```

5688 \str_const:Nx \c_ampsand_str { \cs_to_str:N & }
5689 \str_const:Nx \c_atsign_str { \cs_to_str:N @ }

```

`\c_ampsand_str`
`\c_atsign_str`
`\c_backslash_str`
`\c_left_brace_str`
`\c_right_brace_str`
`\c_circumflex_str`
`\c_colon_str`
`\c_dollar_str`
`\c_hash_str`
`\c_percent_str`
`\c_tilde_str`
`\c_underscore_str`

```

5690 \str_const:Nx \c_backslash_str { \cs_to_str:N \ }
5691 \str_const:Nx \c_left_brace_str { \cs_to_str:N \{ }
5692 \str_const:Nx \c_right_brace_str { \cs_to_str:N \} }
5693 \str_const:Nx \c_circumflex_str { \cs_to_str:N ^ }
5694 \str_const:Nx \c_colon_str { \cs_to_str:N \: }
5695 \str_const:Nx \c_dollar_str { \cs_to_str:N \$ }
5696 \str_const:Nx \c_hash_str { \cs_to_str:N \# }
5697 \str_const:Nx \c_percent_str { \cs_to_str:N \% }
5698 \str_const:Nx \c_tilde_str { \cs_to_str:N ~ }
5699 \str_const:Nx \c_underscore_str { \cs_to_str:N _ }

```

(End definition for `\c_ampersand_str` and others. These variables are documented on page 62.)

`\l_tmpa_str` Scratch strings.

```

\l_tmpb_str 5700 \str_new:N \l_tmpa_str
\g_tmpa_str 5701 \str_new:N \l_tmpb_str
\g_tmpb_str 5702 \str_new:N \g_tmpa_str
5703 \str_new:N \g_tmpb_str

```

(End definition for `\l_tmpa_str` and others. These variables are documented on page 62.)

7.9 Viewing strings

`\str_show:n` Displays a string on the terminal.

```

\str_show:N 5704 \cs_new_eq:NN \str_show:n \tl_show:n
\str_show:c 5705 \cs_new_eq:NN \str_show:N \tl_show:N
5706 \cs_generate_variant:Nn \str_show:N { c }

```

(End definition for `\str_show:n` and `\str_show:N`. These functions are documented on page 61.)

7.10 Deprecated functions

`\str_case_x:nn` For removal after 2019-12-31.

```

\str_case_x:nnTF 5707 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_case_e:nn }
\str_if_eq_x_p:nn 5708 \cs_new:Npn \str_case_x:nn { \str_case_e:nn }
\str_if_eq_x:nnTF 5709 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_case_e:nnT }
5710 \cs_new:Npn \str_case_x:nnT { \str_case_e:nnT }
5711 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_case_e:nnF }
5712 \cs_new:Npn \str_case_x:nnF { \str_case_e:nnF }
5713 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_case_e:nnTF }
5714 \cs_new:Npn \str_case_x:nnTF { \str_case_e:nnTF }
5715 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_if_eq_p:ee }
5716 \cs_new:Npn \str_if_eq_x_p:nn { \str_if_eq_p:ee }
5717 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_if_eq:eeT }
5718 \cs_new:Npn \str_if_eq_x:nnT { \str_if_eq:eeT }
5719 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_if_eq:eeF }
5720 \cs_new:Npn \str_if_eq_x:nnF { \str_if_eq:eeF }
5721 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \str_if_eq:eeTF }
5722 \cs_new:Npn \str_if_eq_x:nnTF { \str_if_eq:eeTF }

```

(End definition for `\str_case_x:nnTF` and `\str_if_eq_x:nnTF`.)

5723 `\</initex | package>`

8 l3quark implementation

The following test files are used for this code: *m3quark001.lvt*.

```
5724 \*initex | package)
```

8.1 Quarks

```
5725 \@@=quark)
```

\quark_new:N Allocate a new quark.

```
5726 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN q #1 } { }
5727 \cs_new_protected:Npn \quark_new:N #1
5728 {
5729   \__kernel_chk_if_free_cs:N #1
5730   \cs_gset_nopar:Npn #1 {#1}
5731 }
```

(End definition for `\quark_new:N`. This function is documented on page 63.)

\q_nil Some “public” quarks. `\q_stop` is an “end of argument” marker, `\q_nil` is a empty value
\q_mark and `\q_no_value` marks an empty argument.
\q_no_value `\quark_new:N \q_nil`
\q_stop `\quark_new:N \q_mark`
`\quark_new:N \q_no_value`
`\quark_new:N \q_stop`

(End definition for `\q_nil` and others. These variables are documented on page 64.)

\q_recursion_tail Quarks for ending recursions. Only ever used there! `\q_recursion_tail` is appended to
\q_recursion_stop whatever list structure we are doing recursion on, meaning it is added as a proper list
item with whatever list separator is in use. `\q_recursion_stop` is placed directly after
the list.

```
5736 \quark_new:N \q_recursion_tail
5737 \quark_new:N \q_recursion_stop
```

(End definition for `\q_recursion_tail` and `\q_recursion_stop`. These variables are documented on page 64.)

\quark_if_recursion_tail_stop:N When doing recursions, it is easy to spend a lot of time testing if the end marker has
\quark_if_recursion_tail_stop_do:Nn been found. To avoid this, a dedicated end marker is used each time a recursion is set up.
Thus if the marker is found everything can be wrapper up and finished off. The simple
case is when the test can guarantee that only a single token is being tested. In this case,
there is just a dedicated copy of the standard quark test. Both a gobbling version and
one inserting end code are provided.

```
5738 \cs_new:Npn \quark_if_recursion_tail_stop:N #1
5739 {
5740   \if_meaning:w \q_recursion_tail #1
5741   \exp_after:wN \use_none_delimit_by_q_recursion_stop:w
5742   \fi:
5743 }
5744 \cs_new:Npn \quark_if_recursion_tail_stop_do:Nn #1
5745 {
5746   \if_meaning:w \q_recursion_tail #1
5747   \exp_after:wN \use_i_delimit_by_q_recursion_stop:nw
```

(End definition for \quark_if_recursion_tail_stop:N and \quark_if_recursion_tail_stop_do:N.
These functions are documented on page 65.)

```
\quark_if_recursion_tail_stop_do: on
quark if recursion tail: w
```

(End definition for \quark_if_recursion_tail_stop:n, \quark_if_recursion_tail_stop_do:nn, and __quark_if_recursion_tail:w. These functions are documented on page 65.)

(End definition for `\quark_if_recursion_tail_break:NN` and `\quark_if_recursion_tail_break:nN`.
These functions are documented on page 65.)

```
\quark_if_no_value_p:c
\quark_if_no_value:N $\underline{TF}$ 
\quark_if_no_value:c $TF$ 
```

⁷It may still loop in special circumstances however!

```

5782 \prg_new_conditional:Npnn \quark_if_nil:N #1 { p, T , F , TF }
5783 {
5784   \if_meaning:w \q_nil #1
5785   \prg_return_true:
5786   \else:
5787   \prg_return_false:
5788   \fi:
5789 }
5790 \prg_new_conditional:Npnn \quark_if_no_value:N #1 { p, T , F , TF }
5791 {
5792   \if_meaning:w \q_no_value #1
5793   \prg_return_true:
5794   \else:
5795   \prg_return_false:
5796   \fi:
5797 }
5798 \prg_generate_conditional_variant:Nnn \quark_if_no_value:N
5799 { c } { p , T , F , TF }

```

(End definition for \quark_if_nil:N_{TF} and \quark_if_no_value:N_{TF}. These functions are documented on page 64.)

\quark_if_nil_p:n Let us explain \quark_if_nil:n(TF). Expanding __quark_if_nil:w once is safe thanks to the trailing \q_nil ??!. The result of expanding once is empty if and only if both delimited arguments #1 and #2 are empty and #3 is delimited by the last tokens ?!. Thanks to the leading {}, the argument #1 is empty if and only if the argument of \quark_if_nil:n starts with \q_nil. The argument #2 is empty if and only if this \q_nil is followed immediately by ? or by {}, coming either from the trailing tokens in the definition of \quark_if_nil:n, or from its argument. In the first case, __quark_if_nil:w is followed by {} \q_nil {} ? ! \q_nil ? !, hence #3 is delimited by the final ?!, and the test returns true as wanted. In the second case, the result is not empty since the first ?! in the definition of \quark_if_nil:n stop #3. The auxiliary here is the same as __tl_if_empty_if:o, with the same comments applying.

```

5800 \prg_new_conditional:Npnn \quark_if_nil:n #1 { p, T , F , TF }
5801 {
5802   \__quark_if_empty_if:o
5803   { \__quark_if_nil:w {} #1 {} ? ! \q_nil ? ! }
5804   \prg_return_true:
5805   \else:
5806   \prg_return_false:
5807   \fi:
5808 }
5809 \cs_new:Npn \__quark_if_nil:w #1 \q_nil #2 ? #3 ? ! { #1 #2 }
5810 \prg_new_conditional:Npnn \quark_if_no_value:n #1 { p, T , F , TF }
5811 {
5812   \__quark_if_empty_if:o
5813   { \__quark_if_no_value:w {} #1 {} ? ! \q_no_value ? ? ! }
5814   \prg_return_true:
5815   \else:
5816   \prg_return_false:
5817   \fi:
5818 }
5819 \cs_new:Npn \__quark_if_no_value:w #1 \q_no_value #2 ? #3 ? ! { #1 #2 }
5820 \prg_generate_conditional_variant:Nnn \quark_if_nil:n

```

```

5821 { V , o } { p , TF , T , F }
5822 \cs_new:Npn \__quark_if_empty_if:o #1
5823 {
5824   \exp_after:wN \if_meaning:w \exp_after:wN \q_nil
5825   \__kernel_tl_to_str:w \exp_after:wN {#1} \q_nil
5826 }

```

(End definition for `\quark_if_nil:nTF` and others. These functions are documented on page 64.)

8.2 Scan marks

```

5827 <@@=scan>

```

`\g__scan_marks_tl` The list of all scan marks currently declared.

```

5828 \tl_new:N \g__scan_marks_tl

```

(End definition for `\g__scan_marks_tl`.)

`\scan_new:N` Check whether the variable is already a scan mark, then declare it to be equal to `\scan_stop:` globally.

```

5829 \__kernel_patch:nnNpn { \__kernel_chk_var_scope:NN s #1 } { }
5830 \cs_new_protected:Npn \scan_new:N #1
5831 {
5832   \tl_if_in:NnTF \g__scan_marks_tl { #1 }
5833   {
5834     \__kernel_msg_error:nxx { kernel } { scanmark-already-defined }
5835     { \token_to_str:N #1 }
5836   }
5837   {
5838     \tl_gput_right:Nn \g__scan_marks_tl {#1}
5839     \cs_new_eq:NN #1 \scan_stop:
5840   }
5841 }

```

(End definition for `\scan_new:N`. This function is documented on page 66.)

`\s_stop` We only declare one scan mark here, more can be defined by specific modules.

```

5842 \scan_new:N \s_stop

```

(End definition for `\s_stop`. This variable is documented on page 66.)

`\use_none_delimit_by_s_stop:w` Similar to `\use_none_delimit_by_q_stop:w`.

```

5843 \cs_new:Npn \use_none_delimit_by_s_stop:w #1 \s_stop { }

```

(End definition for `\use_none_delimit_by_s_stop:w`. This function is documented on page 67.)

```

5844 </initex | package>

```


9 l3seq implementation

The following test files are used for this code: *m3seq002,m3seq003*.

```
5845 (*initex | package)
```

```
5846 <@@=seq>
```

A sequence is a control sequence whose top-level expansion is of the form “\s__seq __seq_item:n {<item₁>} ... __seq_item:n {<item_n>}”, with a leading scan mark followed by *n* items of the same form. An earlier implementation used the structure “\seq_elt:w <item₁> \seq_elt_end: ... \seq_elt:w <item_n> \seq_elt_end:”. This allowed rapid searching using a delimited function, but was not suitable for items containing {, } and # tokens, and also lead to the loss of surrounding braces around items

```
\__seq_item:n ★ \__seq_item:n {<item>}
```

The internal token used to begin each sequence entry. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

```
\__seq_push_item_def:n \__seq_push_item_def:n {<code>}
\__seq_push_item_def:x
```

Saves the definition of __seq_item:n and redefines it to accept one parameter and expand to <code>. This function should always be balanced by use of __seq_pop_item_def:.

```
\__seq_pop_item_def: \__seq_pop_item_def:
```

Restores the definition of __seq_item:n most recently saved by __seq_push_item_def:n. This function should always be used in a balanced pair with __seq_push_item_def:n.

```
\s__seq This private scan mark.
5847 \scan_new:N \s__seq
```

(End definition for \s__seq.)

```
\__seq_item:n The delimiter is always defined, but when used incorrectly simply removes its argument
and hits an undefined control sequence to raise an error.
```

```
5848 \cs_new:Npn \__seq_item:n
5849 {
5850   \__kernel_msg_expandable_error:nn { kernel } { misused-sequence }
5851   \use_none:n
5852 }
```

(End definition for __seq_item:n.)

```
\l__seq_internal_a_tl Scratch space for various internal uses.
```

```
\l__seq_internal_b_tl
5853 \tl_new:N \l__seq_internal_a_tl
5854 \tl_new:N \l__seq_internal_b_tl
```

(End definition for \l__seq_internal_a_tl and \l__seq_internal_b_tl.)

```
\__seq_tmp:w Scratch function for internal use.
```

```
5855 \cs_new_eq:NN \__seq_tmp:w ?
```

(End definition for `_seq_tmp:w.`)

`\c_empty_seq` A sequence with no item, following the structure mentioned above.

```
5856 \tl_const:Nn \c_empty_seq { \s_seq }
```

(End definition for `\c_empty_seq`. This variable is documented on page 77.)

9.1 Allocation and initialisation

`\seq_new:N` Sequences are initialized to `\c_empty_seq`.

```
\seq_new:c      5857 \cs_new_protected:Npn \seq_new:N #1
                  5858 {
                  5859   \__kernel_chk_if_free_cs:N #1
                  5860   \cs_gset_eq:NN #1 \c_empty_seq
                  5861 }
                  5862 \cs_generate_variant:Nn \seq_new:N { c }
```

(End definition for `\seq_new:N`. This function is documented on page 68.)

`\seq_clear:N` Clearing a sequence is similar to setting it equal to the empty one.

```
\seq_clear:c    5863 \cs_new_protected:Npn \seq_clear:N #1
\seq_gclear:N   5864 { \seq_set_eq:NN #1 \c_empty_seq }
\seq_gclear:c   5865 \cs_generate_variant:Nn \seq_clear:N { c }
                  5866 \cs_new_protected:Npn \seq_gclear:N #1
                  5867 { \seq_gset_eq:NN #1 \c_empty_seq }
                  5868 \cs_generate_variant:Nn \seq_gclear:N { c }
```

(End definition for `\seq_clear:N` and `\seq_gclear:N`. These functions are documented on page 68.)

`\seq_clear_new:N` Once again we copy code from the token list functions.

```
\seq_clear_new:c 5869 \cs_new_protected:Npn \seq_clear_new:N #1
\seq_gclear_new:N 5870 { \seq_if_exist:NTF #1 { \seq_clear:N #1 } { \seq_new:N #1 } }
\seq_gclear_new:c 5871 \cs_generate_variant:Nn \seq_clear_new:N { c }
                  5872 \cs_new_protected:Npn \seq_gclear_new:N #1
                  5873 { \seq_if_exist:NTF #1 { \seq_gclear:N #1 } { \seq_new:N #1 } }
                  5874 \cs_generate_variant:Nn \seq_gclear_new:N { c }
```

(End definition for `\seq_clear_new:N` and `\seq_gclear_new:N`. These functions are documented on page 68.)

`\seq_set_eq:NN` Copying a sequence is the same as copying the underlying token list.

```
\seq_set_eq:cN   5875 \cs_new_eq:NN \seq_set_eq:NN \tl_set_eq:NN
\seq_set_eq:Nc   5876 \cs_new_eq:NN \seq_set_eq:Nc \tl_set_eq:Nc
\seq_set_eq:cc   5877 \cs_new_eq:NN \seq_set_eq:cN \tl_set_eq:cN
\seq_gset_eq:NN  5878 \cs_new_eq:NN \seq_set_eq:cc \tl_set_eq:cc
\seq_gset_eq:cN  5879 \cs_new_eq:NN \seq_gset_eq:NN \tl_gset_eq:NN
\seq_gset_eq:Nc  5880 \cs_new_eq:NN \seq_gset_eq:Nc \tl_gset_eq:Nc
\seq_gset_eq:cN  5881 \cs_new_eq:NN \seq_gset_eq:cN \tl_gset_eq:cN
\seq_gset_eq:cc  5882 \cs_new_eq:NN \seq_gset_eq:cc \tl_gset_eq:cc
```

(End definition for `\seq_set_eq:NN` and `\seq_gset_eq:NN`. These functions are documented on page 68.)

`\seq_set_from_clist:NN` Setting a sequence from a comma-separated list is done using a simple mapping.

```

\seq_set_from_clist:cN 5883 \cs_new_protected:Npn \seq_set_from_clist:NN #1#2
\seq_set_from_clist:Nc 5884 {
\seq_set_from_clist:cc 5885   \tl_set:Nx #1
\seq_set_from_clist:Nn 5886   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
\seq_set_from_clist:cn 5887 }
\seq_gset_from_clist:NN 5888 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
\seq_gset_from_clist:cN 5889 {
\seq_gset_from_clist:Nc 5890   \tl_set:Nx #1
\seq_gset_from_clist:cc 5891   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
\seq_gset_from_clist:Nn 5892 }
\seq_gset_from_clist:NN 5893 \cs_new_protected:Npn \seq_gset_from_clist:NN #1#2
\seq_gset_from_clist:cn 5894 {
5895   \tl_gset:Nx #1
5896   { \s__seq \clist_map_function:NN #2 \__seq_wrap_item:n }
5897 }
5898 \cs_new_protected:Npn \seq_gset_from_clist:Nn #1#2
5899 {
5900   \tl_gset:Nx #1
5901   { \s__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
5902 }
5903 \cs_generate_variant:Nn \seq_set_from_clist:NN { Nc }
5904 \cs_generate_variant:Nn \seq_set_from_clist:NN { c , cc }
5905 \cs_generate_variant:Nn \seq_set_from_clist:Nn { c }
5906 \cs_generate_variant:Nn \seq_gset_from_clist:NN { Nc }
5907 \cs_generate_variant:Nn \seq_gset_from_clist:NN { c , cc }
5908 \cs_generate_variant:Nn \seq_gset_from_clist:Nn { c }

```

(End definition for `\seq_set_from_clist:NN` and others. These functions are documented on page 68.)

`\seq_set_split:Nnn` When the separator is empty, everything is very simple, just map `__seq_wrap_item:n` through the items of the last argument. For non-trivial separators, the goal is to split a given token list at the marker, strip spaces from each item, and remove one set of outer braces if after removing leading and trailing spaces the item is enclosed within braces. After `\tl_replace_all:Nnn`, the token list `\l__seq_internal_a_tl` is a repetition of the pattern `__seq_set_split_auxi:w \prg_do_nothing: <item with spaces>`. Then, x-expansion causes `__seq_set_split_auxi:w` to trim spaces, and leaves its result as `__seq_set_split_auxii:w <trimmed item>`. This is then converted to the l3seq internal structure by another x-expansion. In the first step, we insert `\prg_do_nothing:` to avoid losing braces too early; that would cause space trimming to act within those lost braces. The second step is solely there to strip braces which are outermost after space trimming.

```

5909 \cs_new_protected:Npn \seq_set_split:Nnn
5910 { \__seq_set_split:Nnnn \tl_set:Nx }
5911 \cs_new_protected:Npn \seq_gset_split:Nnn
5912 { \__seq_set_split:Nnnn \tl_gset:Nx }
5913 \cs_new_protected:Npn \__seq_set_split:Nnnn #1#2#3#4
5914 {
5915   \tl_if_empty:nTF {#3}
5916   {
5917     \tl_set:Nn \l__seq_internal_a_tl
5918     { \tl_map_function:nN {#4} \__seq_wrap_item:n }
5919   }

```

```

5920     {
5921         \tl_set:Nn \l__seq_internal_a_tl
5922         {
5923             \__seq_set_split_auxi:w \prg_do_nothing:
5924             #4
5925             \__seq_set_split_end:
5926         }
5927         \tl_replace_all:Nnn \l__seq_internal_a_tl { #3 }
5928         {
5929             \__seq_set_split_end:
5930             \__seq_set_split_auxi:w \prg_do_nothing:
5931         }
5932         \tl_set:Nx \l__seq_internal_a_tl { \l__seq_internal_a_tl }
5933     }
5934     #1 #2 { \s__seq \l__seq_internal_a_tl }
5935 }
5936 \cs_new:Npn \__seq_set_split_auxi:w #1 \__seq_set_split_end:
5937 {
5938     \exp_not:N \__seq_set_split_auxii:w
5939     \exp_args:No \tl_trim_spaces:n {#1}
5940     \exp_not:N \__seq_set_split_end:
5941 }
5942 \cs_new:Npn \__seq_set_split_auxii:w #1 \__seq_set_split_end:
5943 { \__seq_wrap_item:n {#1} }
5944 \cs_generate_variant:Nn \seq_set_split:Nnn { NnV }
5945 \cs_generate_variant:Nn \seq_gset_split:Nnn { NnV }

```

(End definition for `\seq_set_split:Nnn` and others. These functions are documented on page 69.)

`\seq_concat:NNN` When concatenating sequences, one must remove the leading `\s__seq` of the second sequence. The result starts with `\s__seq` (of the first sequence), which stops f-expansion.

`\seq_concat:ccc`

`\seq_gconcat:NNN`

```

5946 \cs_new_protected:Npn \seq_concat:NNN #1#2#3
5947 { \tl_set:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
5948 \cs_new_protected:Npn \seq_gconcat:NNN #1#2#3
5949 { \tl_gset:Nf #1 { \exp_after:wN \use_i:nn \exp_after:wN #2 #3 } }
5950 \cs_generate_variant:Nn \seq_concat:NNN { ccc }
5951 \cs_generate_variant:Nn \seq_gconcat:NNN { ccc }

```

(End definition for `\seq_concat:NNN` and `\seq_gconcat:NNN`. These functions are documented on page 69.)

`\seq_if_exist_p:N` Copies of the cs functions defined in l3basics.

`\seq_if_exist_p:c`

```

5952 \prg_new_eq_conditional:NNn \seq_if_exist:N \cs_if_exist:N
5953 { TF , T , F , p }
5954 \prg_new_eq_conditional:NNn \seq_if_exist:c \cs_if_exist:c
5955 { TF , T , F , p }

```

(End definition for `\seq_if_exist:NTF`. This function is documented on page 69.)

9.2 Appending data to either end

`\seq_put_left:Nn` When adding to the left of a sequence, remove `\s__seq`. This is done by `__seq_put_left_aux:w`, which also stops f-expansion.

`\seq_put_left:NV`

`\seq_put_left:Nv`

```

5956 \cs_new_protected:Npn \seq_put_left:Nn #1#2

```

`\seq_put_left:No`

`\seq_put_left:Nx`

`\seq_put_left:cn`

`\seq_put_left:cV`

`\seq_put_left:cv`

`\seq_put_left:co`

`\seq_put_left:cx`

`\seq_gput_left:Nn`

`\seq_gput_left:NV`

`\seq_gput_left:Nv`

`\seq_gput_left:No`

```

5957 {
5958   \tl_set:Nx #1
5959   {
5960     \exp_not:n { \s__seq \__seq_item:n {#2} }
5961     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
5962   }
5963 }
5964 \cs_new_protected:Npn \seq_gput_left:Nn #1#2
5965 {
5966   \tl_gset:Nx #1
5967   {
5968     \exp_not:n { \s__seq \__seq_item:n {#2} }
5969     \exp_not:f { \exp_after:wN \__seq_put_left_aux:w #1 }
5970   }
5971 }
5972 \cs_new:Npn \__seq_put_left_aux:w \s__seq { \exp_stop_f: }
5973 \cs_generate_variant:Nn \seq_put_left:Nn { NV , Nv , No , Nx }
5974 \cs_generate_variant:Nn \seq_put_left:Nn { c , cV , cv , co , cx }
5975 \cs_generate_variant:Nn \seq_gput_left:Nn { NV , Nv , No , Nx }
5976 \cs_generate_variant:Nn \seq_gput_left:Nn { c , cV , cv , co , cx }

```

(End definition for `\seq_put_left:Nn`, `\seq_gput_left:Nn`, and `__seq_put_left_aux:w`. These functions are documented on page 69.)

`\seq_put_right:Nn` Since there is no trailing marker, adding an item to the right of a sequence simply means wrapping it in `__seq_item:n`.

```

\seq_put_right:NV
\seq_put_right:Nv
\seq_put_right:No
\seq_put_right:Nx
\seq_put_right:cn
\seq_put_right:cV
\seq_put_right:cv
\seq_put_right:co
\seq_put_right:cx
5977 \cs_new_protected:Npn \seq_put_right:Nn #1#2
5978 { \tl_put_right:Nn #1 { \__seq_item:n {#2} } }
5979 \cs_new_protected:Npn \seq_gput_right:Nn #1#2
5980 { \tl_gput_right:Nn #1 { \__seq_item:n {#2} } }
5981 \cs_generate_variant:Nn \seq_gput_right:Nn { NV , Nv , No , Nx }
5982 \cs_generate_variant:Nn \seq_gput_right:Nn { c , cV , cv , co , cx }
5983 \cs_generate_variant:Nn \seq_put_right:Nn { NV , Nv , No , Nx }
5984 \cs_generate_variant:Nn \seq_put_right:Nn { c , cV , cv , co , cx }

```

`\seq_gput_right:Nn` (End definition for `\seq_put_right:Nn` and `\seq_gput_right:Nn`. These functions are documented on page 69.)

```

\seq_gput_right:Nv
\seq_gput_right:No
\seq_gput_right:Nx
\seq_gput_right:cn
\seq_gput_right:cV
\seq_gput_right:cv
\seq_gput_right:co
\seq_gput_right:cx
\__seq_remove_seq

```

9.3 Modifying sequences

This function converts its argument to a proper sequence item in an x-expansion context.

```

5985 \cs_new:Npn \__seq_wrap_item:n #1 { \exp_not:n { \__seq_item:n {#1} } }

```

(End definition for `__seq_wrap_item:n`.)

An internal sequence for the removal routines.

```

5986 \seq_new:N \l__seq_remove_seq

```

(End definition for `\l__seq_remove_seq`.)

`\seq_remove_duplicates:N` Removing duplicates means making a new list then copying it.

```

\seq_remove_duplicates:c
\seq_gremove_duplicates:N
\seq_gremove_duplicates:c
\__seq_remove_duplicates:NN
5987 \cs_new_protected:Npn \seq_remove_duplicates:N
5988 { \__seq_remove_duplicates:NN \seq_set_eq:NN }
5989 \cs_new_protected:Npn \seq_gremove_duplicates:N
5990 { \__seq_remove_duplicates:NN \seq_gset_eq:NN }

```

```

5991 \cs_new_protected:Npn \__seq_remove_duplicates:NN #1#2
5992 {
5993   \seq_clear:N \l__seq_remove_seq
5994   \seq_map_inline:Nn #2
5995   {
5996     \seq_if_in:NnF \l__seq_remove_seq {##1}
5997     { \seq_put_right:Nn \l__seq_remove_seq {##1} }
5998   }
5999   #1 #2 \l__seq_remove_seq
6000 }
6001 \cs_generate_variant:Nn \seq_remove_duplicates:N { c }
6002 \cs_generate_variant:Nn \seq_gremove_duplicates:N { c }

```

(End definition for `\seq_remove_duplicates:N`, `\seq_gremove_duplicates:N`, and `__seq_remove_duplicates:NN`. These functions are documented on page 72.)

`\seq_remove_all:Nn` The idea of the code here is to avoid a relatively expensive addition of items one at a time
`\seq_remove_all:cn` to an intermediate sequence. The approach taken is therefore similar to that in `__seq_`
`\seq_gremove_all:Nn` `pop_right:NNN`, using a “flexible” x-type expansion to do most of the work. As `\tl_`
`\seq_gremove_all:cn` `if_eq:nnT` is not expandable, a two-part strategy is needed. First, the x-type expansion
`__seq_remove_all_aux:NNn` uses `\str_if_eq:nnT` to find potential matches. If one is found, the expansion is halted
and the necessary set up takes place to use the `\tl_if_eq:NNT` test. The x-type is started
again, including all of the items copied already. This happens repeatedly until the entire
sequence has been scanned. The code is set up to avoid needing an intermediate scratch
list: the lead-off x-type expansion (`#1 #2 {#2}`) ensures that nothing is lost.

```

6003 \cs_new_protected:Npn \seq_remove_all:Nn
6004 { \__seq_remove_all_aux:NNn \tl_set:Nx }
6005 \cs_new_protected:Npn \seq_gremove_all:Nn
6006 { \__seq_remove_all_aux:NNn \tl_gset:Nx }
6007 \cs_new_protected:Npn \__seq_remove_all_aux:NNn #1#2#3
6008 {
6009   \__seq_push_item_def:n
6010   {
6011     \str_if_eq:nnT {##1} {#3}
6012     {
6013       \if_false: { \fi: }
6014       \tl_set:Nn \l__seq_internal_b_tl {##1}
6015       #1 #2
6016       { \if_false: } \fi:
6017       \exp_not:o {#2}
6018       \tl_if_eq:NNT \l__seq_internal_a_tl \l__seq_internal_b_tl
6019       { \use_none:nn }
6020     }
6021     \__seq_wrap_item:n {##1}
6022   }
6023   \tl_set:Nn \l__seq_internal_a_tl {#3}
6024   #1 #2 {#2}
6025   \__seq_pop_item_def:
6026 }
6027 \cs_generate_variant:Nn \seq_remove_all:Nn { c }
6028 \cs_generate_variant:Nn \seq_gremove_all:Nn { c }

```

(End definition for `\seq_remove_all:Nn`, `\seq_gremove_all:Nn`, and `__seq_remove_all_aux:NNn`. These functions are documented on page 72.)

```

\seq_reverse:N Previously, \seq_reverse:N was coded by collecting the items in reverse order after an
\seq_reverse:c \exp_stop_f: marker.
\seq_greverse:N
\seq_greverse:c
\__seq_reverse:NN
\__seq_reverse_item:nwn
\cs_new_protected:Npn \seq_reverse:N #1
{
  \cs_set_eq:NN \@@_item:n \@@_reverse_item:nw
  \tl_set:Nf #2 { #2 \exp_stop_f: }
}
\cs_new:Npn \@@_reverse_item:nw #1 #2 \exp_stop_f:
{
  #2 \exp_stop_f:
  \@@_item:n {#1}
}

```

At first, this seems optimal, since we can forget about each item as soon as it is placed after `\exp_stop_f:`. Unfortunately, \TeX 's usual tail recursion does not take place in this case: since the following `__seq_reverse_item:nw` only reads tokens until `\exp_stop_f:`, and never reads the `\@@_item:n {#1}` left by the previous call, \TeX cannot remove that previous call from the stack, and in particular must retain the various macro parameters in memory, until the end of the replacement text is reached. The stack is thus only flushed after all the `__seq_reverse_item:nw` are expanded. Keeping track of the arguments of all those calls uses up a memory quadratic in the length of the sequence. \TeX can then not cope with more than a few thousand items.

Instead, we collect the items in the argument of `\exp_not:n`. The previous calls are cleanly removed from the stack, and the memory consumption becomes linear.

```

6029 \cs_new_protected:Npn \seq_reverse:N
6030 { \__seq_reverse:NN \tl_set:Nx }
6031 \cs_new_protected:Npn \seq_greverse:N
6032 { \__seq_reverse:NN \tl_gset:Nx }
6033 \cs_new_protected:Npn \__seq_reverse:NN #1 #2
6034 {
6035   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
6036   \cs_set_eq:NN \__seq_item:n \__seq_reverse_item:nwn
6037   #1 #2 { #2 \exp_not:n { } }
6038   \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
6039 }
6040 \cs_new:Npn \__seq_reverse_item:nwn #1 #2 \exp_not:n #3
6041 {
6042   #2
6043   \exp_not:n { \__seq_item:n {#1} #3 }
6044 }
6045 \cs_generate_variant:Nn \seq_reverse:N { c }
6046 \cs_generate_variant:Nn \seq_greverse:N { c }

```

(End definition for `\seq_reverse:N` and others. These functions are documented on page 72.)

```

\seq_sort:Nn Implemented in l3sort.
\seq_sort:cn
\seq_gsort:Nn (End definition for \seq_sort:Nn and \seq_gsort:Nn. These functions are documented on page 72.)
\seq_gsort:cn

```

9.4 Sequence conditionals

`\seq_if_empty_p:N` Similar to token lists, we compare with the empty sequence.
`\seq_if_empty_p:c`
`\seq_if_empty:N \overline{TF}`
`\seq_if_empty:c \overline{TF}`

```

6047 \prg_new_conditional:Npnn \seq_if_empty:N #1 { p , T , F , TF }
6048 {
6049   \if_meaning:w #1 \c_empty_seq
6050   \prg_return_true:
6051   \else:
6052     \prg_return_false:
6053   \fi:
6054 }
6055 \prg_generate_conditional_variant:Nnn \seq_if_empty:N
6056 { c } { p , T , F , TF }

```

(End definition for `\seq_if_empty:N \overline{TF}` . This function is documented on page 72.)

`\seq_if_in:Nn \overline{TF}` The approach here is to define `__seq_item:n` to compare its argument with the test
`\seq_if_in:N \overline{VTF}` sequence. If the two items are equal, the mapping is terminated and `\group_end: \prg_`
`\seq_if_in:N \overline{vTF}` `return_true:` is inserted after skipping over the rest of the recursion. On the other hand,
`\seq_if_in:No \overline{TF}` if there is no match then the loop breaks, returning `\prg_return_false:`. Everything
`\seq_if_in:Nx \overline{TF}` is inside a group so that `__seq_item:n` is preserved in nested situations.
`\seq_if_in:cn \overline{TF}`
`\seq_if_in:c \overline{VTF}`
`\seq_if_in:cv \overline{TF}`
`\seq_if_in:co \overline{TF}`
`\seq_if_in:cx \overline{TF}`
`__seq_if_in:`

```

6057 \prg_new_protected_conditional:Npnn \seq_if_in:Nn #1#2
6058 { T , F , TF }
6059 {
6060   \group_begin:
6061   \tl_set:Nn \l__seq_internal_a_tl {#2}
6062   \cs_set_protected:Npn \__seq_item:n ##1
6063   {
6064     \tl_set:Nn \l__seq_internal_b_tl {##1}
6065     \if_meaning:w \l__seq_internal_a_tl \l__seq_internal_b_tl
6066     \exp_after:wN \__seq_if_in:
6067   \fi:
6068   }
6069   #1
6070   \group_end:
6071   \prg_return_false:
6072   \prg_break_point:
6073 }
6074 \cs_new:Npn \__seq_if_in:
6075 { \prg_break:n { \group_end: \prg_return_true: } }
6076 \prg_generate_conditional_variant:Nnn \seq_if_in:Nn
6077 { NV , Nv , No , Nx , c , cV , cv , co , cx } { T , F , TF }

```

(End definition for `\seq_if_in:Nn \overline{TF}` and `__seq_if_in:`. This function is documented on page 73.)

9.5 Recovering data from sequences

`__seq_pop:NNNN` The two `pop` functions share their emptiness tests. We also use a common emptiness test
`__seq_pop_TF:NNNN` for all branching `get` and `pop` functions.

```

6078 \cs_new_protected:Npn \__seq_pop:NNNN #1#2#3#4
6079 {
6080   \if_meaning:w #3 \c_empty_seq
6081   \tl_set:Nn #4 { \q_no_value }
6082   \else:

```



```

6083         #1#2#3#4
6084     \fi:
6085 }
6086 \cs_new_protected:Npn \__seq_pop_TF:NNNN #1#2#3#4
6087 {
6088     \if_meaning:w #3 \c_empty_seq
6089     % \tl_set:Nn #4 { \q_no_value }
6090     \prg_return_false:
6091 \else:
6092     #1#2#3#4
6093     \prg_return_true:
6094 \fi:
6095 }

```

(End definition for __seq_pop:NNNN and __seq_pop_TF:NNNN.)

\seq_get_left:NN Getting an item from the left of a sequence is pretty easy: just trim off the first item
\seq_get_left:cN after __seq_item:n at the start. We append a \q_no_value item to cover the case of
__seq_get_left:wnw an empty sequence

```

6096 \cs_new_protected:Npn \seq_get_left:NN #1#2
6097 {
6098     \tl_set:Nx #2
6099     {
6100         \exp_after:wN \__seq_get_left:wnw
6101         #1 \__seq_item:n { \q_no_value } \q_stop
6102     }
6103 }
6104 \cs_new:Npn \__seq_get_left:wnw #1 \__seq_item:n #2#3 \q_stop
6105 { \exp_not:n {#2} }
6106 \cs_generate_variant:Nn \seq_get_left:NN { c }

```

(End definition for \seq_get_left:NN and __seq_get_left:wnw. This function is documented on page 69.)

\seq_pop_left:NN The approach to popping an item is pretty similar to that to get an item, with the only
\seq_pop_left:cN difference being that the sequence itself has to be redefined. This makes it more sensible
\seq_gpop_left:NN to use an auxiliary function for the local and global cases.
\seq_gpop_left:cN
__seq_pop_left:NNN
__seq_pop_left:wnwNNN

```

6107 \cs_new_protected:Npn \seq_pop_left:NN
6108 { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_set:Nn }
6109 \cs_new_protected:Npn \seq_gpop_left:NN
6110 { \__seq_pop:NNNN \__seq_pop_left:NNN \tl_gset:Nn }
6111 \cs_new_protected:Npn \__seq_pop_left:NNN #1#2#3
6112 { \exp_after:wN \__seq_pop_left:wnwNNN #2 \q_stop #1#2#3 }
6113 \cs_new_protected:Npn \__seq_pop_left:wnwNNN
6114 #1 \__seq_item:n #2#3 \q_stop #4#5#6
6115 {
6116     #4 #5 { #1 #3 }
6117     \tl_set:Nn #6 {#2}
6118 }
6119 \cs_generate_variant:Nn \seq_pop_left:NN { c }
6120 \cs_generate_variant:Nn \seq_gpop_left:NN { c }

```

(End definition for \seq_pop_left:NN and others. These functions are documented on page 70.)

`\seq_get_right:NN` First remove `\s__seq` and prepend `\q_no_value`. The first argument of `__seq_get_right_loop:nw` is the last item found, and the second argument is empty until the end of the loop, where it is code that applies `\exp_not:n` to the last item and ends the loop.

`\seq_get_right:cN`

`__seq_get_right_loop:nw`

`__seq_get_right_end:NnN`

```

6121 \cs_new_protected:Npn \seq_get_right:NN #1#2
6122 {
6123   \tl_set:Nx #2
6124   {
6125     \exp_after:wN \use_i_ii:nnn
6126     \exp_after:wN \__seq_get_right_loop:nw
6127     \exp_after:wN \q_no_value
6128     #1
6129     \__seq_get_right_end:NnN \__seq_item:n
6130   }
6131 }
6132 \cs_new:Npn \__seq_get_right_loop:nw #1#2 \__seq_item:n
6133 {
6134   #2 \use_none:n {#1}
6135   \__seq_get_right_loop:nw
6136 }
6137 \cs_new:Npn \__seq_get_right_end:NnN #1#2#3 { \exp_not:n {#2} }
6138 \cs_generate_variant:Nn \seq_get_right:NN { c }

```

(End definition for `\seq_get_right:NN`, `__seq_get_right_loop:nw`, and `__seq_get_right_end:NnN`. This function is documented on page 70.)

`\seq_pop_right:NN` The approach to popping from the right is a bit more involved, but does use some of the same ideas as getting from the right. What is needed is a “flexible length” way to set a token list variable. This is supplied by the `{\if_false:} \fi:` construct. Using an x-type expansion and a “non-expanding” definition for `__seq_item:n`, the left-most $n - 1$ entries in a sequence of n items are stored back in the sequence. That needs a loop of unknown length, hence using the strange `\if_false:` way of including braces. When the last item of the sequence is reached, the closing brace for the assignment is inserted, and `\tl_set:Nn #3` is inserted in front of the final entry. This therefore does the pop assignment. One more iteration is performed, with an empty argument and `\use_none:nn`, which finally stops the loop.

`\seq_pop_right:cN`

`\seq_gpop_right:NN`

`\seq_gpop_right:cN`

`__seq_pop_right:NNN`

`__seq_pop_right_loop:nn`

```

6139 \cs_new_protected:Npn \seq_pop_right:NN
6140 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_set:Nx }
6141 \cs_new_protected:Npn \seq_gpop_right:NN
6142 { \__seq_pop:NNNN \__seq_pop_right:NNN \tl_gset:Nx }
6143 \cs_new_protected:Npn \__seq_pop_right:NNN #1#2#3
6144 {
6145   \cs_set_eq:NN \__seq_tmp:w \__seq_item:n
6146   \cs_set_eq:NN \__seq_item:n \scan_stop:
6147   #1 #2
6148   { \if_false: } \fi: \s__seq
6149   \exp_after:wN \use_i:nnn
6150   \exp_after:wN \__seq_pop_right_loop:nn
6151   #2
6152   {
6153     \if_false: { \fi: }
6154     \tl_set:Nx #3
6155   }
6156   { } \use_none:nn

```

```

6157     \cs_set_eq:NN \__seq_item:n \__seq_tmp:w
6158   }
6159   \cs_new:Npn \__seq_pop_right_loop:nn #1#2
6160   {
6161     #2 { \exp_not:n {#1} }
6162     \__seq_pop_right_loop:nn
6163   }
6164   \cs_generate_variant:Nn \seq_pop_right:NN { c }
6165   \cs_generate_variant:Nn \seq_gpop_right:NN { c }

```

(End definition for \seq_pop_right:NN and others. These functions are documented on page 70.)

\seq_get_left:NNTF Getting from the left or right with a check on the results. The first argument to __seq_pop_TF:NNNN is left unused.

```

\seq_get_left:cNTF
\seq_get_right:NNTF
\seq_get_right:cNTF
6166 \prg_new_protected_conditional:Npnn \seq_get_left:NN #1#2 { T , F , TF }
6167   { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_left:NN #1#2 }
6168 \prg_new_protected_conditional:Npnn \seq_get_right:NN #1#2 { T , F , TF }
6169   { \__seq_pop_TF:NNNN \prg_do_nothing: \seq_get_right:NN #1#2 }
6170 \prg_generate_conditional_variant:Nnn \seq_get_left:NN
6171   { c } { T , F , TF }
6172 \prg_generate_conditional_variant:Nnn \seq_get_right:NN
6173   { c } { T , F , TF }

```

(End definition for \seq_get_left:NNTF and \seq_get_right:NNTF. These functions are documented on page 71.)

\seq_pop_left:NNTF More or less the same for popping.

```

\seq_pop_left:cNTF
\seq_gpop_left:NNTF
\seq_gpop_left:cNTF
\seq_pop_right:NNTF
\seq_pop_right:cNTF
\seq_gpop_right:NNTF
\seq_gpop_right:cNTF
6174 \prg_new_protected_conditional:Npnn \seq_pop_left:NN #1#2
6175   { T , F , TF }
6176 \prg_new_protected_conditional:Npnn \seq_gpop_left:NN #1#2
6177   { T , F , TF }
6178 \prg_new_protected_conditional:Npnn \seq_pop_right:NN #1#2
6179   { T , F , TF }
6180 \prg_new_protected_conditional:Npnn \seq_gpop_right:NN #1#2
6181   { T , F , TF }
6182 \prg_new_protected_conditional:Npnn \seq_gpop_right:NN #1#2
6183   { T , F , TF }
6184 \prg_generate_conditional_variant:Nnn \seq_pop_left:NN { c }
6185   { T , F , TF }
6186 \prg_generate_conditional_variant:Nnn \seq_gpop_left:NN { c }
6187   { T , F , TF }
6188 \prg_generate_conditional_variant:Nnn \seq_pop_right:NN { c }
6189   { T , F , TF }
6190 \prg_generate_conditional_variant:Nnn \seq_gpop_right:NN { c }
6191   { T , F , TF }
6192 \prg_generate_conditional_variant:Nnn \seq_gpop_right:NN { c }
6193   { T , F , TF }

```

(End definition for \seq_pop_left:NNTF and others. These functions are documented on page 71.)

\seq_item:Nn The idea here is to find the offset of the item from the left, then use a loop to grab the correct item. If the resulting offset is too large, then the argument delimited by __seq_item:n is \prg_break: instead of being empty, terminating the loop and returning nothing at all.

```

\seq_item:cn
\__seq_item:wNn
\__seq_item:nN
\__seq_item:nwn

```

```

6194 \cs_new:Npn \seq_item:Nn #1
6195   { \exp_after:wN \__seq_item:wNn #1 \q_stop #1 }
6196 \cs_new:Npn \__seq_item:wNn \s__seq #1 \q_stop #2#3
6197   {
6198     \exp_args:Nf \__seq_item:nwn
6199     { \exp_args:Nf \__seq_item:nN { \int_eval:n {#3} } #2 }
6200     #1
6201     \prg_break: \__seq_item:n { }
6202     \prg_break_point:
6203   }
6204 \cs_new:Npn \__seq_item:nN #1#2
6205   {
6206     \int_compare:nNnTF {#1} < 0
6207     { \int_eval:n { \seq_count:N #2 + 1 + #1 } }
6208     {#1}
6209   }
6210 \cs_new:Npn \__seq_item:nwn #1#2 \__seq_item:n #3
6211   {
6212     #2
6213     \int_compare:nNnTF {#1} = 1
6214     { \prg_break:n { \exp_not:n {#3} } }
6215     { \exp_args:Nf \__seq_item:nwn { \int_eval:n { #1 - 1 } } }
6216   }
6217 \cs_generate_variant:Nn \seq_item:Nn { c }

```

(End definition for `\seq_item:Nn` and others. This function is documented on page 70.)

`\seq_rand_item:N` Importantly, `\seq_item:Nn` only evaluates its argument once.

```

\seq_rand_item:c
6218 \cs_new:Npn \seq_rand_item:N #1
6219   {
6220     \seq_if_empty:NF #1
6221     { \seq_item:Nn #1 { \int_rand:nn { 1 } } { \seq_count:N #1 } } }
6222   }
6223 \cs_generate_variant:Nn \seq_rand_item:N { c }

```

(End definition for `\seq_rand_item:N`. This function is documented on page 70.)

9.6 Mapping to sequences

`\seq_map_break:` To break a function, the special token `\prg_break_point:Nn` is used to find the end of the code. Any ending code is then inserted before the return value of `\seq_map_break:n` is inserted.

```

6224 \cs_new:Npn \seq_map_break:
6225   { \prg_map_break:Nn \seq_map_break: { } }
6226 \cs_new:Npn \seq_map_break:n
6227   { \prg_map_break:Nn \seq_map_break: }

```

(End definition for `\seq_map_break:` and `\seq_map_break:n`. These functions are documented on page 73.)

`\seq_map_function:NN` The idea here is to apply the code of #2 to each item in the sequence without altering the definition of `__seq_item:n`. The argument delimited by `__seq_item:n` is almost always empty, except at the end of the loop where it is `\prg_break:`. This allows to break the loop without needing to do a (relatively-expensive) quark test.

```

6228 \cs_new:Npn \seq_map_function:NN #1#2
6229 {
6230   \exp_after:wN \use_i_ii:nnn
6231   \exp_after:wN \__seq_map_function:Nw
6232   \exp_after:wN #2
6233   #1
6234   \prg_break: \__seq_item:n { } \prg_break_point:
6235   \prg_break_point:Nn \seq_map_break: { }
6236 }
6237 \cs_new:Npn \__seq_map_function:Nw #1#2 \__seq_item:n #3
6238 {
6239   #2
6240   #1 {#3}
6241   \__seq_map_function:Nw #1
6242 }
6243 \cs_generate_variant:Nn \seq_map_function:NN { c }

```

(End definition for `\seq_map_function:NN` and `__seq_map_function:NNn`. This function is documented on page 73.)

`__seq_push_item_def:n` The definition of `__seq_item:n` needs to be saved and restored at various points within the mapping and manipulation code. That is handled here: as always, this approach uses global assignments.

```

\__seq_push_item_def:x
\__seq_push_item_def:
\__seq_pop_item_def:
6244 \cs_new_protected:Npn \__seq_push_item_def:n
6245 {
6246   \__seq_push_item_def:
6247   \cs_gset:Npn \__seq_item:n ##1
6248 }
6249 \cs_new_protected:Npn \__seq_push_item_def:x
6250 {
6251   \__seq_push_item_def:
6252   \cs_gset:Npx \__seq_item:n ##1
6253 }
6254 \cs_new_protected:Npn \__seq_push_item_def:
6255 {
6256   \int_gincr:N \g__kernel_prg_map_int
6257   \cs_gset_eq:cN { \__seq_map_ \int_use:N \g__kernel_prg_map_int :w }
6258   \__seq_item:n
6259 }
6260 \cs_new_protected:Npn \__seq_pop_item_def:
6261 {
6262   \cs_gset_eq:Nc \__seq_item:n
6263   { \__seq_map_ \int_use:N \g__kernel_prg_map_int :w }
6264   \int_gdecr:N \g__kernel_prg_map_int
6265 }

```

(End definition for `__seq_push_item_def:n`, `__seq_push_item_def:`, and `__seq_pop_item_def:`.)

`\seq_map_inline:Nn` The idea here is that `__seq_item:n` is already “applied” to each item in a sequence, and so an in-line mapping is just a case of redefining `__seq_item:n`.

```

\seq_map_inline:cn
6266 \cs_new_protected:Npn \seq_map_inline:Nn #1#2
6267 {
6268   \__seq_push_item_def:n {#2}
6269   #1

```

```

6270     \prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
6271   }
6272 \cs_generate_variant:Nn \seq_map_inline:Nn { c }

```

(End definition for \seq_map_inline:Nn. This function is documented on page 73.)

\seq_map_variable:NNn This is just a specialised version of the in-line mapping function, using an x-type expansion for the code set up so that the number of # tokens required is as expected.

```

\seq_map_variable:Ncn
\seq_map_variable:cNn
\seq_map_variable:ccn
6273 \cs_new_protected:Npn \seq_map_variable:NNn #1#2#3
6274 {
6275   \__seq_push_item_def:x
6276   {
6277     \tl_set:Nn \exp_not:N #2 {##1}
6278     \exp_not:n {#3}
6279   }
6280   #1
6281   \prg_break_point:Nn \seq_map_break: { \__seq_pop_item_def: }
6282 }
6283 \cs_generate_variant:Nn \seq_map_variable:NNn { Nc }
6284 \cs_generate_variant:Nn \seq_map_variable:NNn { c , cc }

```

(End definition for \seq_map_variable:NNn. This function is documented on page 73.)

\seq_count:N Since counting the items in a sequence is quite common, we optimize it by grabbing 8 items at a time and correspondingly adding 8 to an integer expression. At the end of the loop, #9 is __seq_count_end:w instead of being empty. It removes 8+ and instead places the number of __seq_item:n that __seq_count:w grabbed before reaching the end of the sequence.

```

\seq_count:c
\__seq_count:w
\__seq_count_end:w
6285 \cs_new:Npn \seq_count:N #1
6286 {
6287   \int_eval:n
6288   {
6289     \exp_after:wN \use_i:nn
6290     \exp_after:wN \__seq_count:w
6291     #1
6292     \__seq_count_end:w \__seq_item:n 7
6293     \__seq_count_end:w \__seq_item:n 6
6294     \__seq_count_end:w \__seq_item:n 5
6295     \__seq_count_end:w \__seq_item:n 4
6296     \__seq_count_end:w \__seq_item:n 3
6297     \__seq_count_end:w \__seq_item:n 2
6298     \__seq_count_end:w \__seq_item:n 1
6299     \__seq_count_end:w \__seq_item:n 0
6300     \prg_break_point:
6301   }
6302 }
6303 \cs_new:Npn \__seq_count:w
6304   #1 \__seq_item:n #2 \__seq_item:n #3 \__seq_item:n #4 \__seq_item:n
6305   #5 \__seq_item:n #6 \__seq_item:n #7 \__seq_item:n #8 #9 \__seq_item:n
6306   { #9 8 + \__seq_count:w }
6307 \cs_new:Npn \__seq_count_end:w 8 + \__seq_count:w #1#2 \prg_break_point: {#1}
6308 \cs_generate_variant:Nn \seq_count:N { c }

```

(End definition for \seq_count:N, __seq_count:w, and __seq_count_end:w. This function is documented on page 74.)

9.7 Using sequences

`\seq_use:Nnnn` See `\clist_use:Nnnn` for a general explanation. The main difference is that we use `__seq_item:n` as a delimiter rather than commas. We also need to add `__seq_item:n` at various places, and `\s__seq`.

```

\seq_use:cn
\__seq_use:NNnNnn
\__seq_use_setup:w
\__seq_use:nwwwnwn
\__seq_use:nwwn
\seq_use:Nn
\seq_use:cn
6309 \cs_new:Npn \seq_use:Nnnn #1#2#3#4
6310 {
6311   \seq_if_exist:NTF #1
6312   {
6313     \int_case:nnF { \seq_count:N #1 }
6314     {
6315       { 0 } { }
6316       { 1 } { \exp_after:wN \__seq_use:NNnNnn #1 ? { } { } }
6317       { 2 } { \exp_after:wN \__seq_use:NNnNnn #1 {#2} }
6318     }
6319     {
6320       \exp_after:wN \__seq_use_setup:w #1 \__seq_item:n
6321       \q_mark { \__seq_use:nwwwnwn {#3} }
6322       \q_mark { \__seq_use:nwwn {#4} }
6323       \q_stop { }
6324     }
6325   }
6326   {
6327     \__kernel_msg_expandable_error:nnn
6328     { kernel } { bad-variable } {#1}
6329   }
6330 }
6331 \cs_generate_variant:Nn \seq_use:Nnnn { c }
6332 \cs_new:Npn \__seq_use:NNnNnn #1#2#3#4#5#6 { \exp_not:n { #3 #6 #5 } }
6333 \cs_new:Npn \__seq_use_setup:w \s__seq { \__seq_use:nwwwnwn { } }
6334 \cs_new:Npn \__seq_use:nwwwnwn
6335   #1 \__seq_item:n #2 \__seq_item:n #3 \__seq_item:n #4#5
6336   \q_mark #6#7 \q_stop #8
6337   {
6338     #6 \__seq_item:n {#3} \__seq_item:n {#4} #5
6339     \q_mark {#6} #7 \q_stop { #8 #1 #2 }
6340   }
6341 \cs_new:Npn \__seq_use:nwwn #1 \__seq_item:n #2 #3 \q_stop #4
6342   { \exp_not:n { #4 #1 #2 } }
6343 \cs_new:Npn \seq_use:Nn #1#2
6344   { \seq_use:Nnnn #1 {#2} {#2} {#2} }
6345 \cs_generate_variant:Nn \seq_use:Nn { c }

```

(End definition for `\seq_use:Nnnn` and others. These functions are documented on page 74.)

9.8 Sequence stacks

The same functions as for sequences, but with the correct naming.

`\seq_push:Nn` Pushing to a sequence is the same as adding on the left.

```

\seq_push:NV
\seq_push:Nv
\seq_push:No
\seq_push:Nx
\seq_push:cn
\seq_push:cV
\seq_push:cV
\seq_push:co
\seq_push:cx
\seq_gpush:Nn
\seq_gpush:NV
\seq_gpush:Nv
\seq_gpush:No
\seq_gpush:Nx

```

```

6350 \cs_new_eq:NN \seq_push:Nx \seq_put_left:Nx
6351 \cs_new_eq:NN \seq_push:cn \seq_put_left:cn
6352 \cs_new_eq:NN \seq_push:cV \seq_put_left:cV
6353 \cs_new_eq:NN \seq_push:cv \seq_put_left:cv
6354 \cs_new_eq:NN \seq_push:co \seq_put_left:co
6355 \cs_new_eq:NN \seq_push:cx \seq_put_left:cx
6356 \cs_new_eq:NN \seq_gpush:Nn \seq_gput_left:Nn
6357 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
6358 \cs_new_eq:NN \seq_gpush:Nv \seq_gput_left:Nv
6359 \cs_new_eq:NN \seq_gpush:No \seq_gput_left:No
6360 \cs_new_eq:NN \seq_gpush:Nx \seq_gput_left:Nx
6361 \cs_new_eq:NN \seq_gpush:cn \seq_gput_left:cn
6362 \cs_new_eq:NN \seq_gpush:cV \seq_gput_left:cV
6363 \cs_new_eq:NN \seq_gpush:cv \seq_gput_left:cv
6364 \cs_new_eq:NN \seq_gpush:co \seq_gput_left:co
6365 \cs_new_eq:NN \seq_gpush:cx \seq_gput_left:cx

```

(End definition for `\seq_push:Nn` and `\seq_gpush:Nn`. These functions are documented on page 76.)

`\seq_get:NN` In most cases, getting items from the stack does not need to specify that this is from the left. So alias are provided.

```

\seq_get:cn
\seq_pop:NN
\seq_pop:cn
\seq_gpop:NN
\seq_gpop:cn
6366 \cs_new_eq:NN \seq_get:NN \seq_get_left:NN
6367 \cs_new_eq:NN \seq_get:cn \seq_get_left:cn
6368 \cs_new_eq:NN \seq_pop:NN \seq_pop_left:NN
6369 \cs_new_eq:NN \seq_pop:cn \seq_pop_left:cn
6370 \cs_new_eq:NN \seq_gpop:NN \seq_gpop_left:NN
6371 \cs_new_eq:NN \seq_gpop:cn \seq_gpop_left:cn

```

(End definition for `\seq_get:NN`, `\seq_pop:NN`, and `\seq_gpop:NN`. These functions are documented on page 75.)

```

\seq_get:NNTF More copies.
\seq_get:cnTF
\seq_pop:NNTF
\seq_pop:cnTF
\seq_gpop:NNTF
\seq_gpop:cnTF
6372 \prg_new_eq_conditional:NNn \seq_get:NN \seq_get_left:NN { T , F , TF }
6373 \prg_new_eq_conditional:NNn \seq_get:cn \seq_get_left:cn { T , F , TF }
6374 \prg_new_eq_conditional:NNn \seq_pop:NN \seq_pop_left:NN { T , F , TF }
6375 \prg_new_eq_conditional:NNn \seq_pop:cn \seq_pop_left:cn { T , F , TF }
6376 \prg_new_eq_conditional:NNn \seq_gpop:NN \seq_gpop_left:NN { T , F , TF }
6377 \prg_new_eq_conditional:NNn \seq_gpop:cn \seq_gpop_left:cn { T , F , TF }

```

(End definition for `\seq_get:NNTF`, `\seq_pop:NNTF`, and `\seq_gpop:NNTF`. These functions are documented on page 75.)

9.9 Viewing sequences

```

\seq_show:N Apply the general \msg_show:nnnnnn.
\seq_show:c
\seq_log:N
\seq_log:c
\__seq_show:NN
6378 \cs_new_protected:Npn \seq_show:N { \__seq_show:NN \msg_show:nnxxxx }
6379 \cs_generate_variant:Nn \seq_show:N { c }
6380 \cs_new_protected:Npn \seq_log:N { \__seq_show:NN \msg_log:nnxxxx }
6381 \cs_generate_variant:Nn \seq_log:N { c }
6382 \cs_new_protected:Npn \__seq_show:NN #1#2
6383 {
6384   \__kernel_chk_defined:NT #2
6385   {
6386     #1 { LaTeX/kernel } { show-seq }
6387     { \token_to_str:N #2 }

```



```

6388         { \seq_map_function:NN #2 \msg_show_item:n }
6389         { } { }
6390     }
6391 }

```

(End definition for `\seq_show:N`, `\seq_log:N`, and `__seq_show:NN`. These functions are documented on page 78.)

9.10 Scratch sequences

`\l_tmpa_seq` Temporary comma list variables.

```

\l_tmpb_seq 6392 \seq_new:N \l_tmpa_seq
\g_tmpa_seq 6393 \seq_new:N \l_tmpb_seq
\g_tmpb_seq 6394 \seq_new:N \g_tmpa_seq
6395 \seq_new:N \g_tmpb_seq

```

(End definition for `\l_tmpa_seq` and others. These variables are documented on page 78.)

```
6396 </initex | package>
```

10 l3int implementation

```
6397 <*initex | package>
```

```
6398 <@@=int>
```

The following test files are used for this code: `m3int001`, `m3int002`, `m3int03`.

`\c_max_register_int` Done in l3basics.

(End definition for `\c_max_register_int`. This variable is documented on page 90.)

`__int_to_roman:w` Done in l3basics.

`\if_int_compare:w` (End definition for `__int_to_roman:w` and `\if_int_compare:w`. This function is documented on page 91.)

`\or:` Done in l3basics.

(End definition for `\or:`. This function is documented on page 91.)

`\int_value:w` Here are the remaining primitives for number comparisons and expressions.

```

\__int_eval:w 6399 \cs_new_eq:NN \int_value:w \tex_number:D
\__int_eval_end: 6400 \cs_new_eq:NN \__int_eval:w \tex_numexpr:D
\if_int_odd:w 6401 \cs_new_eq:NN \__int_eval_end: \tex_relax:D
\if_case:w 6402 \cs_new_eq:NN \if_int_odd:w \tex_ifodd:D
6403 \cs_new_eq:NN \if_case:w \tex_ifcase:D

```

(End definition for `\int_value:w` and others. These functions are documented on page 91.)

10.1 Integer expressions

`\int_eval:n` Wrapper for `__int_eval:w`: can be used in an integer expression or directly in the input stream. When debugging, use parentheses to catch early termination.

```
6404 \__kernel_patch_args:nNNpn
6405   { { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_eval:n } }
6406 \cs_new:Npn \int_eval:n #1
6407   { \int_value:w \__int_eval:w #1 \__int_eval_end: }
6408 \cs_new:Npn \int_eval:w { \int_value:w \__int_eval:w }
```

(End definition for `\int_eval:n` and `\int_eval:w`. These functions are documented on page 79.)

`\int_abs:n` Functions for min, max, and absolute value with only one evaluation. The absolute value is obtained by removing a leading sign if any. All three functions expand in two steps.

```
\__int_abs:N
\int_max:nn
\int_min:nn
\__int_maxmin:wwN
6409 \__kernel_patch_args:nNNpn
6410   { { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_abs:n } }
6411 \cs_new:Npn \int_abs:n #1
6412   {
6413     \int_value:w \exp_after:wN \__int_abs:N
6414     \int_value:w \__int_eval:w #1 \__int_eval_end:
6415     \exp_stop_f:
6416   }
6417 \cs_new:Npn \__int_abs:N #1
6418   { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
6419 \__kernel_patch_args:nNNpn
6420   {
6421     { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_max:nn }
6422     { \__kernel_chk_expr:nNnN {#2} \__int_eval:w { } \int_max:nn }
6423   }
6424 \cs_set:Npn \int_max:nn #1#2
6425   {
6426     \int_value:w \exp_after:wN \__int_maxmin:wwN
6427     \int_value:w \__int_eval:w #1 \exp_after:wN ;
6428     \int_value:w \__int_eval:w #2 ;
6429     >
6430     \exp_stop_f:
6431   }
6432 \__kernel_patch_args:nNNpn
6433   {
6434     { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_min:nn }
6435     { \__kernel_chk_expr:nNnN {#2} \__int_eval:w { } \int_min:nn }
6436   }
6437 \cs_set:Npn \int_min:nn #1#2
6438   {
6439     \int_value:w \exp_after:wN \__int_maxmin:wwN
6440     \int_value:w \__int_eval:w #1 \exp_after:wN ;
6441     \int_value:w \__int_eval:w #2 ;
6442     <
6443     \exp_stop_f:
6444   }
6445 \cs_new:Npn \__int_maxmin:wwN #1 ; #2 ; #3
6446   {
6447     \if_int_compare:w #1 #3 #2 ~
6448       #1
```

```

6449     \else:
6450         #2
6451     \fi:
6452 }

```

(End definition for `\int_abs:n` and others. These functions are documented on page 79.)

`\int_div_truncate:nn` As `__int_eval:w` rounds the result of a division we also provide a version that truncates the result. We use an auxiliary to make sure numerator and denominator are only evaluated once: this comes in handy when those are more expressions are expensive to evaluate (e.g., `\tl_count:n`). If the numerator `#1#2` is 0, then we divide 0 by the denominator (this ensures that 0/0 is correctly reported as an error). Otherwise, shift the numerator `#1#2` towards 0 by $(| \#3\#4 | - 1)/2$, which we round away from zero. It turns out that this quantity exactly compensates the difference between ε -TeX's rounding and the truncating behaviour that we want. The details are thanks to Heiko Oberdiek: getting things right in all cases is not so easy.

```

6453 \__kernel_patch_args:nNnNpn
6454 {
6455     { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_div_truncate:nn }
6456     { \__kernel_chk_expr:nNnN {#2} \__int_eval:w { } \int_div_truncate:nn }
6457 }
6458 \cs_new:Npn \int_div_truncate:nn #1#2
6459 {
6460     \int_value:w \__int_eval:w
6461     \exp_after:wN \__int_div_truncate:NwNw
6462     \int_value:w \__int_eval:w #1 \exp_after:wN ;
6463     \int_value:w \__int_eval:w #2 ;
6464     \__int_eval_end:
6465 }
6466 \cs_new:Npn \__int_div_truncate:NwNw #1#2; #3#4;
6467 {
6468     \if_meaning:w 0 #1
6469     0
6470     \else:
6471     (
6472         #1#2
6473         \if_meaning:w - #1 + \else: - \fi:
6474         ( \if_meaning:w - #3 - \fi: #3#4 - 1 ) / 2
6475     )
6476     \fi:
6477     / #3#4
6478 }

```

For the sake of completeness:

```

6479 \cs_new:Npn \int_div_round:nn #1#2
6480 { \int_value:w \__int_eval:w ( #1 ) / ( #2 ) \__int_eval_end: }

```

Finally there's the modulus operation.

```

6481 \__kernel_patch_args:nNnNpn
6482 {
6483     { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_mod:nn }
6484     { \__kernel_chk_expr:nNnN {#2} \__int_eval:w { } \int_mod:nn }
6485 }
6486 \cs_new:Npn \int_mod:nn #1#2

```

```

6487 {
6488   \int_value:w \__int_eval:w \exp_after:wN \__int_mod:ww
6489   \int_value:w \__int_eval:w #1 \exp_after:wN ;
6490   \int_value:w \__int_eval:w #2 ;
6491   \__int_eval_end:
6492 }
6493 \cs_new:Npn \__int_mod:ww #1; #2;
6494 { #1 - ( \__int_div_truncate:NwNw #1 ; #2 ; ) * #2 }

```

(End definition for `\int_div_truncate:nn` and others. These functions are documented on page 80.)

`__kernel_int_add:nnn` Equivalent to `\int_eval:n {#1+#2+#3}` except that overflow only occurs if the final result overflows $[-2^{31} + 1, 2^{31} - 1]$. The idea is to choose the order in which the three numbers are added together. If #1 and #2 have opposite signs (one is in $[-2^{31} + 1, -1]$ and the other in $[0, 2^{31} - 1]$) then #1+#2 cannot overflow so we compute the result as #1+#2+#3. If they have the same sign, then either #3 has the same sign and the order does not matter, or #3 has the opposite sign and any order in which #3 is not last will work. We use #1+#3+#2.

```

6495 \cs_new:Npn \__kernel_int_add:nnn #1#2#3
6496 {
6497   \int_value:w \__int_eval:w #1
6498   \if_int_compare:w #2 < \c_zero_int \exp_after:wN \reverse_if:N \fi:
6499   \if_int_compare:w #1 < \c_zero_int + #2 + #3 \else: + #3 + #2 \fi:
6500   \__int_eval_end:
6501 }

```

(End definition for `__kernel_int_add:nnn`.)

10.2 Creating and initialising integers

`\int_new:N` Two ways to do this: one for the format and one for the L^AT_EX 2_ε package. In plain T_EX, `\int_new:c` `\newcount` (and other allocators) are `\outer:` to allow the code here to work in “generic” mode this is therefore accessed by name. (The same applies to `\newbox`, `\newdimen` and so on.)

```

6502 \*package>
6503 \cs_new_protected:Npn \int_new:N #1
6504 {
6505   \__kernel_chk_if_free_cs:N #1
6506   \cs:w newcount \cs_end: #1
6507 }
6508 \</package>
6509 \cs_generate_variant:Nn \int_new:N { c }

```

(End definition for `\int_new:N`. This function is documented on page 80.)

`\int_const:Nn` As stated, most constants can be defined as `\chardef` or `\mathchardef` but that’s engine dependent. As a result, there is some set up code to determine what can be done. No full engine testing just yet so everything is a little awkward. We cannot use `\int_gset:Nn` because (when `check-declarations` is enabled) this runs some checks that constants would fail.

```

\int_const:cn
\__int_constdef:Nw
\c__int_max_constdef_int
6510 \__kernel_patch_args:nnnnNpn
6511 { \__kernel_chk_var_scope:NN c #1 }
6512 { }

```

```

6513 { {#1} { \_kernel_chk_expr:nNnN {#2} \_int_eval:w { } \int_const:Nn } }
6514 \cs_new_protected:Npn \int_const:Nn #1#2
6515 {
6516   \int_compare:nNnTF {#2} < \c_zero_int
6517   {
6518     \int_new:N #1
6519     \tex_global:D
6520   }
6521   {
6522     \int_compare:nNnTF {#2} > \c__int_max_constdef_int
6523     {
6524       \int_new:N #1
6525       \tex_global:D
6526     }
6527     {
6528       \_kernel_chk_if_free_cs:N #1
6529       \tex_global:D \_int_constdef:Nw
6530     }
6531   }
6532   #1 = \_int_eval:w #2 \_int_eval_end:
6533 }
6534 \cs_generate_variant:Nn \int_const:Nn { c }
6535 \if_int_odd:w 0
6536   \cs_if_exist:NT \tex_luatexversion:D { 1 }
6537   \cs_if_exist:NT \tex_disablecjktoken:D
6538   { \if_int_compare:w \tex_jis:D "2121 = "3000 ~ 1 \fi: }
6539   \cs_if_exist:NT \tex_XeTeXversion:D { 1 } ~
6540   \cs_if_exist:NTF \tex_disablecjktoken:D
6541   { \cs_new_eq:NN \_int_constdef:Nw \tex_kchardef:D }
6542   { \cs_new_eq:NN \_int_constdef:Nw \tex_chardef:D }
6543   \_int_constdef:Nw \c__int_max_constdef_int 1114111 ~
6544 \else:
6545   \cs_new_eq:NN \_int_constdef:Nw \tex_mathchardef:D
6546   \tex_mathchardef:D \c__int_max_constdef_int 32767 ~
6547 \fi:

```

(End definition for `\int_const:Nn`, `_int_constdef:Nw`, and `\c__int_max_constdef_int`. This function is documented on page 80.)

`\int_zero:N` Functions that reset an *integer* register to zero.

```

\int_zero:c 6548 \_kernel_patch:nnNNpn { \_kernel_chk_var_local:N #1 } { }
\int_gzero:N 6549 \cs_new_protected:Npn \int_zero:N #1 { #1 = \c_zero_int }
\int_gzero:c 6550 \_kernel_patch:nnNNpn { \_kernel_chk_var_global:N #1 } { }
6551 \cs_new_protected:Npn \int_gzero:N #1 { \tex_global:D #1 = \c_zero_int }
6552 \cs_generate_variant:Nn \int_zero:N { c }
6553 \cs_generate_variant:Nn \int_gzero:N { c }

```

(End definition for `\int_zero:N` and `\int_gzero:N`. These functions are documented on page 80.)

`\int_zero_new:N` Create a register if needed, otherwise clear it.

```

\int_zero_new:c 6554 \cs_new_protected:Npn \int_zero_new:N #1
\int_gzero_new:N 6555 { \int_if_exist:NTF #1 { \int_zero:N #1 } { \int_new:N #1 } }
\int_gzero_new:c 6556 \cs_new_protected:Npn \int_gzero_new:N #1
6557 { \int_if_exist:NTF #1 { \int_gzero:N #1 } { \int_new:N #1 } }
6558 \cs_generate_variant:Nn \int_zero_new:N { c }

```

```
6559 \cs_generate_variant:Nn \int_gzero_new:N { c }
```

(End definition for `\int_zero_new:N` and `\int_gzero_new:N`. These functions are documented on page 80.)

`\int_set_eq:NN` Setting equal means using one integer inside the set function of another. Check that assigned integer is local/global. No need to check that the other one is defined as `\TeX` does it for us.

```
\int_set_eq:cn
\int_set_eq:Nc
\int_set_eq:cc
6560 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\int_gset_eq:NN 6561 \cs_new_protected:Npn \int_set_eq:NN #1#2 { #1 = #2 }
\int_gset_eq:cn 6562 \cs_generate_variant:Nn \int_set_eq:NN { c , Nc , cc }
\int_gset_eq:Nc 6563 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
\int_gset_eq:cc 6564 \cs_new_protected:Npn \int_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
6565 \cs_generate_variant:Nn \int_gset_eq:NN { c , Nc , cc }
```

(End definition for `\int_set_eq:NN` and `\int_gset_eq:NN`. These functions are documented on page 81.)

`\int_if_exist_p:N` Copies of the `\cs` functions defined in `l3basics`.

```
\int_if_exist_p:c 6566 \prg_new_eq_conditional:NNn \int_if_exist:N \cs_if_exist:N
\int_if_exist:NTF 6567 { TF , T , F , p }
\int_if_exist:cTF 6568 \prg_new_eq_conditional:NNn \int_if_exist:c \cs_if_exist:c
6569 { TF , T , F , p }
```

(End definition for `\int_if_exist:NTF`. This function is documented on page 81.)

10.3 Setting and incrementing integers

Several functions here have a signature `:Nn` and are such that when debugging, the first argument should be checked to be a local/global variable and the second should be wrapped in code for an expression. The temporary function `__int_tmp:w` finds the name `#3` of the function being redefined and writes the appropriate patch.

```
6570 \cs_set_protected:Npn \__int_tmp:w #1#2#3
6571 {
6572   \__kernel_patch_args:nnnNNpn
6573     { #1 ##1 }
6574     { }
6575     { {##1} { \__kernel_chk_expr:nNnN {##2} \__int_eval:w { } #3 } }
6576     #2 #3
6577 }
```

`\int_add:Nn` Adding and subtracting to and from a counter. For each function, the debugging code produced by `__int_tmp:w` checks that the assigned variable is correctly local/global and wraps the expression in some checking code.

```
\int_add:cn
\int_gadd:Nn 6578 \__int_tmp:w \__kernel_chk_var_local:N
\int_gadd:cn 6579 \cs_new_protected:Npn \int_add:Nn #1#2
\int_sub:Nn 6580 { \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
\int_sub:cn 6581 \__int_tmp:w \__kernel_chk_var_local:N
\int_gsub:Nn 6582 \cs_new_protected:Npn \int_sub:Nn #1#2
\int_gsub:cn 6583 { \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
6584 \__int_tmp:w \__kernel_chk_var_global:N
6585 \cs_new_protected:Npn \int_gadd:Nn #1#2
6586 { \tex_global:D \tex_advance:D #1 by \__int_eval:w #2 \__int_eval_end: }
6587 \__int_tmp:w \__kernel_chk_var_global:N
```

```

6588 \cs_new_protected:Npn \int_gsub:Nn #1#2
6589 { \tex_global:D \tex_advance:D #1 by - \__int_eval:w #2 \__int_eval_end: }
6590 \cs_generate_variant:Nn \int_add:Nn { c }
6591 \cs_generate_variant:Nn \int_gadd:Nn { c }
6592 \cs_generate_variant:Nn \int_sub:Nn { c }
6593 \cs_generate_variant:Nn \int_gsub:Nn { c }

```

(End definition for `\int_add:Nn` and others. These functions are documented on page 81.)

`\int_incr:N` Incrementing and decrementing of integer registers is done with the following functions.

```

\int_incr:c 6594 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\int_gincr:N 6595 \cs_new_protected:Npn \int_incr:N #1
\int_gincr:c 6596 { \tex_advance:D #1 \c_one_int }
\int_decr:N 6597 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\int_decr:c 6598 \cs_new_protected:Npn \int_decr:N #1
\int_gdecr:N 6599 { \tex_advance:D #1 - \c_one_int }
\int_gdecr:c 6600 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
6601 \cs_new_protected:Npn \int_gincr:N #1
6602 { \tex_global:D \tex_advance:D #1 \c_one_int }
6603 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
6604 \cs_new_protected:Npn \int_gdecr:N #1
6605 { \tex_global:D \tex_advance:D #1 - \c_one_int }
6606 \cs_generate_variant:Nn \int_incr:N { c }
6607 \cs_generate_variant:Nn \int_decr:N { c }
6608 \cs_generate_variant:Nn \int_gincr:N { c }
6609 \cs_generate_variant:Nn \int_gdecr:N { c }

```

(End definition for `\int_incr:N` and others. These functions are documented on page 81.)

`\int_set:Nn` As integers are register-based TeX issues an error if they are not defined. Thus there is no need to check their existence as for token list variables. However, the code that checks whether the assignment is local or global is still needed.

```

\int_set:cn 6610 \__int_tmp:w \__kernel_chk_var_local:N
\int_gset:Nn 6611 \cs_new_protected:Npn \int_set:Nn #1#2
\int_gset:cn 6612 { #1 ~ \__int_eval:w #2 \__int_eval_end: }
6613 \__int_tmp:w \__kernel_chk_var_global:N
6614 \cs_new_protected:Npn \int_gset:Nn #1#2
6615 { \tex_global:D #1 ~ \__int_eval:w #2 \__int_eval_end: }
6616 \cs_generate_variant:Nn \int_set:Nn { c }
6617 \cs_generate_variant:Nn \int_gset:Nn { c }

```

(End definition for `\int_set:Nn` and `\int_gset:Nn`. These functions are documented on page 81.)

10.4 Using integers

`\int_use:N` Here is how counters are accessed:

```

\int_use:c 6618 \cs_new_eq:NN \int_use:N \tex_the:D
We hand-code this for some speed gain:
6619 %\cs_generate_variant:Nn \int_use:N { c }
6620 \cs_new:Npn \int_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\int_use:N`. This function is documented on page 82.)

10.5 Integer expression conditionals

`__int_compare_error:`
`__int_compare_error:Nw`

Those functions are used for comparison tests which use a simple syntax where only one set of braces is required and additional operators such as `!=` and `>=` are supported. The tests first evaluate their left-hand side, with a trailing `__int_compare_error:`. This marker is normally not expanded, but if the relation symbol is missing from the test's argument, then the marker inserts `=` (and itself) after triggering the relevant `TEX` error. If the first token which appears after evaluating and removing the left-hand side is not a known relation symbol, then a judiciously placed `__int_compare_error:Nw` gets expanded, cleaning up the end of the test and telling the user what the problem was.

```

6621 \cs_new_protected:Npn \__int_compare_error:
6622 {
6623   \if_int_compare:w \c_zero_int \c_zero_int \fi:
6624   =
6625   \__int_compare_error:
6626 }
6627 \cs_new:Npn \__int_compare_error:Nw
6628 #1#2 \q_stop
6629 {
6630   { }
6631   \c_zero_int \fi:
6632   \__kernel_msg_expandable_error:nnn
6633   { kernel } { unknown-comparison } {#1}
6634   \prg_return_false:
6635 }
```

(End definition for `__int_compare_error:` and `__int_compare_error:Nw`.)

`\int_compare_p:n`
`\int_compare:nTF`
`__int_compare:w`
`__int_compare:Nw`
`__int_compare:NNw`
`__int_compare:nnN`
`__int_compare_end=:NNw`
`__int_compare=:NNw`
`__int_compare<:NNw`
`__int_compare>:NNw`
`__int_compare=:NNw`
`__int_compare!=:NNw`
`__int_compare<=:NNw`
`__int_compare>=:NNw`

Comparison tests using a simple syntax where only one set of braces is required, additional operators such as `!=` and `>=` are supported, and multiple comparisons can be performed at once, for instance `0 < 5 <= 1`. The idea is to loop through the argument, finding one operand at a time, and comparing it to the previous one. The looping auxiliary `__int_compare:Nw` reads one *operand* and one *comparison* symbol, and leaves roughly

```

<operand> \prg_return_false: \fi:
\reverse_if:N \if_int_compare:w <operand> <comparison>
\__int_compare:Nw
```

in the input stream. Each call to this auxiliary provides the second operand of the last call's `\if_int_compare:w`. If one of the *comparisons* is `false`, the `true` branch of the `TEX` conditional is taken (because of `\reverse_if:N`), immediately returning `false` as the result of the test. There is no `TEX` conditional waiting the first operand, so we add an `\if_false:` and expand by hand with `\int_value:w`, thus skipping `\prg_return_false:` on the first iteration.

Before starting the loop, the first step is to make sure that there is at least one relation symbol. We first let `TEX` evaluate this left hand side of the (in)equality using `__int_eval:w`. Since the relation symbols `<`, `>`, `=` and `!` are not allowed in integer expressions, they would terminate the expression. If the argument contains no relation symbol, `__int_compare_error:` is expanded, inserting `=` and itself after an error. In all cases, `__int_compare:w` receives as its argument an integer, a relation symbol, and some more tokens. We then setup the loop, which is ended by the two odd-looking items `e` and `{=nd_}`, with a trailing `\q_stop` used to grab the entire argument when necessary.


```

6636 \prg_new_conditional:Npnn \int_compare:n #1 { p , T , F , TF }
6637 {
6638   \exp_after:wN \__int_compare:w
6639   \int_value:w \__int_eval:w #1 \__int_compare_error:
6640 }
6641 \cs_new:Npn \__int_compare:w #1 \__int_compare_error:
6642 {
6643   \exp_after:wN \if_false: \int_value:w
6644   \__int_compare:Nw #1 e { = nd_ } \q_stop
6645 }

```

The goal here is to find an *operand* and a *comparison*. The *operand* is already evaluated, but we cannot yet grab it as an argument. To access the following relation symbol, we remove the number by applying `__int_to_roman:w`, after making sure that the argument becomes non-positive: its roman numeral representation is then empty. Then probe the first two tokens with `__int_compare:NNw` to determine the relation symbol, building a control sequence from it (`\token_to_str:N` gives better errors if #1 is not a character). All the extended forms have an extra = hence the test for that as a second token. If the relation symbol is unknown, then the control sequence is turned by `\TeX` into `\scan_stop:`, ignored thanks to `\unexpanded`, and `__int_compare_error:Nw` raises an error.

```

6646 \cs_new:Npn \__int_compare:Nw #1#2 \q_stop
6647 {
6648   \exp_after:wN \__int_compare:NNw
6649   \__int_to_roman:w - 0 #2 \q_mark
6650   #1#2 \q_stop
6651 }
6652 \cs_new:Npn \__int_compare:NNw #1#2#3 \q_mark
6653 {
6654   \__kernel_exp_not:w
6655   \use:c
6656   {
6657     \__int_compare_ \token_to_str:N #1
6658     \if_meaning:w = #2 = \fi:
6659     :NNw
6660   }
6661   \__int_compare_error:Nw #1
6662 }

```

When the last *operand* is seen, `__int_compare:NNw` receives `e` and `=nd_` as arguments, hence calling `__int_compare_end=:NNw` to end the loop: return the result of the last comparison (involving the operand that we just found). When a normal relation is found, the appropriate auxiliary calls `__int_compare:nnN` where #1 is `\if_int_compare:w` or `\reverse_if:N \if_int_compare:w`, #2 is the *operand*, and #3 is one of `<`, `=`, or `>`. As announced earlier, we leave the *operand* for the previous conditional. If this conditional is true the result of the test is known, so we remove all tokens and return `false`. Otherwise, we apply the conditional #1 to the *operand* #2 and the comparison #3, and call `__int_compare:Nw` to look for additional operands, after evaluating the following expression.

```

6663 \cs_new:cpn { \__int_compare_end=:NNw } #1#2#3 e #4 \q_stop
6664 {
6665   {#3} \exp_stop_f:
6666   \prg_return_false: \else: \prg_return_true: \fi:

```

```

6667 }
6668 \cs_new:Npn \__int_compare:nnN #1#2#3
6669 {
6670     {#2} \exp_stop_f:
6671     \prg_return_false: \exp_after:wN \use_none_delimit_by_q_stop:w
6672     \fi:
6673     #1 #2 #3 \exp_after:wN \__int_compare:Nw \int_value:w \__int_eval:w
6674 }

```

The actual comparisons are then simple function calls, using the relation as delimiter for a delimited argument and discarding `__int_compare_error:Nw` *(token)* responsible for error detection.

```

6675 \cs_new:cpn { \__int_compare_=:NNw } #1#2#3 =
6676 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
6677 \cs_new:cpn { \__int_compare:<:NNw } #1#2#3 <
6678 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} < }
6679 \cs_new:cpn { \__int_compare:>:NNw } #1#2#3 >
6680 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} > }
6681 \cs_new:cpn { \__int_compare_=:NNw } #1#2#3 ==
6682 { \__int_compare:nnN { \reverse_if:N \if_int_compare:w } {#3} = }
6683 \cs_new:cpn { \__int_compare_!=:NNw } #1#2#3 !=
6684 { \__int_compare:nnN { \if_int_compare:w } {#3} = }
6685 \cs_new:cpn { \__int_compare_<=:NNw } #1#2#3 <=
6686 { \__int_compare:nnN { \if_int_compare:w } {#3} > }
6687 \cs_new:cpn { \__int_compare_>=:NNw } #1#2#3 >=
6688 { \__int_compare:nnN { \if_int_compare:w } {#3} < }

```

(End definition for `\int_compare:nTF` and others. This function is documented on page 83.)

`\int_compare_p:nNn` More efficient but less natural in typing.

```

\int_compare:nNnTF
6689 \__kernel_patch_conditional_args:nNnpnn
6690 {
6691     { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_compare:nNn }
6692     { \__int_eval_end: #2 }
6693     { \__kernel_chk_expr:nNnN {#3} \__int_eval:w { } \int_compare:nNn }
6694 }
6695 \prg_new_conditional:Npnn \int_compare:nNn #1#2#3 { p , T , F , TF }
6696 {
6697     \if_int_compare:w \__int_eval:w #1 #2 \__int_eval:w #3 \__int_eval_end:
6698     \prg_return_true:
6699     \else:
6700     \prg_return_false:
6701     \fi:
6702 }

```

(End definition for `\int_compare:nNnTF`. This function is documented on page 82.)

`\int_case:nn` For integer cases, the first task to fully expand the check condition. The over all idea is then much the same as for `\tl_case:nn(TF)` as described in l3tl.

```

\__int_case:nnTF
\__int_case:nw
\__int_case_end:nw
6703 \cs_new:Npn \int_case:nnTF #1
6704 {
6705     \exp:w
6706     \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} }
6707 }
6708 \cs_new:Npn \int_case:nnT #1#2#3

```

```

6709 {
6710   \exp:w
6711   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} {#3} { }
6712 }
6713 \cs_new:Npn \int_case:nnF #1#2
6714 {
6715   \exp:w
6716   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { }
6717 }
6718 \cs_new:Npn \int_case:nn #1#2
6719 {
6720   \exp:w
6721   \exp_args:Nf \__int_case:nnTF { \int_eval:n {#1} } {#2} { } { }
6722 }
6723 \cs_new:Npn \__int_case:nnTF #1#2#3#4
6724 { \__int_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
6725 \cs_new:Npn \__int_case:nw #1#2#3
6726 {
6727   \int_compare:nNnTF {#1} = {#2}
6728   { \__int_case_end:nw {#3} }
6729   { \__int_case:nw {#1} }
6730 }
6731 \cs_new:Npn \__int_case_end:nw #1#2#3 \q_mark #4#5 \q_stop
6732 { \exp_end: #1 #4 }

```

(End definition for `\int_case:nnTF` and others. This function is documented on page 84.)

```

\int_if_odd_p:n A predicate function.
\int_if_odd:nTF
\int_if_even_p:n
\int_if_even:nTF
6733 \__kernel_patch_conditional_args:nNnpnn
6734 { { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_if_odd:n } }
6735 \prg_new_conditional:Npnn \int_if_odd:n #1 { p , T , F , TF }
6736 {
6737   \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
6738   \prg_return_true:
6739   \else:
6740     \prg_return_false:
6741   \fi:
6742 }
6743 \__kernel_patch_conditional_args:nNnpnn
6744 { { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_if_even:n } }
6745 \prg_new_conditional:Npnn \int_if_even:n #1 { p , T , F , TF }
6746 {
6747   \reverse_if:N \if_int_odd:w \__int_eval:w #1 \__int_eval_end:
6748   \prg_return_true:
6749   \else:
6750     \prg_return_false:
6751   \fi:
6752 }

```

(End definition for `\int_if_odd:nTF` and `\int_if_even:nTF`. These functions are documented on page 84.)

10.6 Integer expression loops

`\int_while_do:nn` These are quite easy given the above functions. The `while` versions test first and then execute the body. The `do_while` does it the other way round.

```
\int_until_do:nn
\int_do_while:nn
\int_do_until:nn
6753 \cs_new:Npn \int_while_do:nn #1#2
6754 {
6755   \int_compare:nT {#1}
6756   {
6757     #2
6758     \int_while_do:nn {#1} {#2}
6759   }
6760 }
6761 \cs_new:Npn \int_until_do:nn #1#2
6762 {
6763   \int_compare:nF {#1}
6764   {
6765     #2
6766     \int_until_do:nn {#1} {#2}
6767   }
6768 }
6769 \cs_new:Npn \int_do_while:nn #1#2
6770 {
6771   #2
6772   \int_compare:nT {#1}
6773   { \int_do_while:nn {#1} {#2} }
6774 }
6775 \cs_new:Npn \int_do_until:nn #1#2
6776 {
6777   #2
6778   \int_compare:nF {#1}
6779   { \int_do_until:nn {#1} {#2} }
6780 }
```

(End definition for `\int_while_do:nn` and others. These functions are documented on page 85.)

`\int_while_do:nNnn` As above but not using the more natural syntax.

```
\int_until_do:nNnn
\int_do_while:nNnn
\int_do_until:nNnn
6781 \cs_new:Npn \int_while_do:nNnn #1#2#3#4
6782 {
6783   \int_compare:nNnT {#1} #2 {#3}
6784   {
6785     #4
6786     \int_while_do:nNnn {#1} #2 {#3} {#4}
6787   }
6788 }
6789 \cs_new:Npn \int_until_do:nNnn #1#2#3#4
6790 {
6791   \int_compare:nNnF {#1} #2 {#3}
6792   {
6793     #4
6794     \int_until_do:nNnn {#1} #2 {#3} {#4}
6795   }
6796 }
6797 \cs_new:Npn \int_do_while:nNnn #1#2#3#4
6798 {
```

```

6799     #4
6800     \int_compare:nNnT {#1} #2 {#3}
6801     { \int_do_while:nNnn {#1} #2 {#3} {#4} }
6802   }
6803 \cs_new:Npn \int_do_until:nNnn #1#2#3#4
6804 {
6805     #4
6806     \int_compare:nNnF {#1} #2 {#3}
6807     { \int_do_until:nNnn {#1} #2 {#3} {#4} }
6808 }

```

(End definition for `\int_while_do:nNnn` and others. These functions are documented on page 85.)

10.7 Integer step functions

`\int_step_function:nnnN` Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

6809 \__kernel_patch_args:nNnNpn
6810 {
6811   {
6812     \__kernel_chk_expr:nNnN {#1} \__int_eval:w { }
6813     \int_step_function:nnnN
6814   }
6815   {
6816     \__kernel_chk_expr:nNnN {#2} \__int_eval:w { }
6817     \int_step_function:nnnN
6818   }
6819   {
6820     \__kernel_chk_expr:nNnN {#3} \__int_eval:w { }
6821     \int_step_function:nnnN
6822   }
6823 }
6824 \cs_new:Npn \int_step_function:nnnN #1#2#3
6825 {
6826   \exp_after:wN \__int_step:wwwN
6827   \int_value:w \__int_eval:w #1 \exp_after:wN ;
6828   \int_value:w \__int_eval:w #2 \exp_after:wN ;
6829   \int_value:w \__int_eval:w #3 ;
6830 }
6831 \cs_new:Npn \__int_step:wwwN #1; #2; #3; #4
6832 {
6833   \int_compare:nNnTF {#2} > \c_zero_int
6834   { \__int_step:NwnnnN > }
6835   {
6836     \int_compare:nNnTF {#2} = \c_zero_int
6837     {
6838       \__kernel_msg_expandable_error:nnn
6839       { kernel } { zero-step } {#4}
6840       \prg_break:
6841     }
6842     { \__int_step:NwnnnN < }

```

```

6843     }
6844     #1 ; {#2} {#3} #4
6845     \prg_break_point:
6846   }
6847   \cs_new:Npn \__int_step:NwnnN #1#2 ; #3#4#5
6848   {
6849     \if_int_compare:w #2 #1 #4 \exp_stop_f:
6850       \prg_break:n
6851     \fi:
6852     #5 {#2}
6853     \exp_after:wN \__int_step:NwnnN
6854     \exp_after:wN #1
6855     \int_value:w \__int_eval:w #2 + #3 ; {#3} {#4} #5
6856   }
6857   \cs_new:Npn \int_step_function:nN
6858   { \int_step_function:nnnN { 1 } { 1 } }
6859   \cs_new:Npn \int_step_function:nnN #1
6860   { \int_step_function:nnnN {#1} { 1 } }

```

(End definition for \int_step_function:nnnN and others. These functions are documented on page 86.)

`\int_step_inline:nn` The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\int_step_function:nnnN`. We put a `\prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__kernel_prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so that no breaking function recognizes this break point as its own.

```

\int_step_inline:nnnN
\int_step_inline:nnnn
\int_step_variable:nNn
\int_step_variable:nnNn
\int_step_variable:nnnNn
\__int_step:NNnnnn
6861 \cs_new_protected:Npn \int_step_inline:nn
6862 { \int_step_inline:nnnn { 1 } { 1 } }
6863 \cs_new_protected:Npn \int_step_inline:nnn #1
6864 { \int_step_inline:nnnn {#1} { 1 } }
6865 \cs_new_protected:Npn \int_step_inline:nnnn
6866 {
6867   \int_gincr:N \g__kernel_prg_map_int
6868   \exp_args:NNc \__int_step:NNnnnn
6869   \cs_gset_protected:Npn
6870   { __int_map_ \int_use:N \g__kernel_prg_map_int :w }
6871 }
6872 \cs_new_protected:Npn \int_step_variable:nNn
6873 { \int_step_variable:nnnNn { 1 } { 1 } }
6874 \cs_new_protected:Npn \int_step_variable:nnNn #1
6875 { \int_step_variable:nnnNn {#1} { 1 } }
6876 \cs_new_protected:Npn \int_step_variable:nnnNn #1#2#3#4#5
6877 {
6878   \int_gincr:N \g__kernel_prg_map_int
6879   \exp_args:NNc \__int_step:NNnnnn
6880   \cs_gset_protected:Npx
6881   { __int_map_ \int_use:N \g__kernel_prg_map_int :w }
6882   {#1}{#2}{#3}
6883   {
6884     \tl_set:Nn \exp_not:N #4 {##1}
6885     \exp_not:n {#5}
6886   }
6887 }

```

```

6888 \cs_new_protected:Npn \__int_step:NNnnnn #1#2#3#4#5#6
6889 {
6890   #1 #2 ##1 {#6}
6891   \int_step_function:nnnN {#3} {#4} {#5} #2
6892   \prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__kernel_prg_map_int }
6893 }

```

(End definition for `\int_step_inline:nn` and others. These functions are documented on page 86.)

10.8 Formatting integers

`\int_to_arabic:n` Nothing exciting here.

```

6894 \cs_new_eq:NN \int_to_arabic:n \int_eval:n

```

(End definition for `\int_to_arabic:n`. This function is documented on page 87.)

`\int_to_symbols:nnn` For conversion of integers to arbitrary symbols the method is in general as follows. The input number (#1) is compared to the total number of symbols available at each place (#2). If the input is larger than the total number of symbols available then the modulus is needed, with one added so that the positions don't have to number from zero. Using an f-type expansion, this is done so that the system is recursive. The actual conversion function therefore gets a 'nice' number at each stage. Of course, if the initial input was small enough then there is no problem and everything is easy.

`__int_to_symbols:nnnn`

```

6895 \cs_new:Npn \int_to_symbols:nnn #1#2#3
6896 {
6897   \int_compare:nNnTF {#1} > {#2}
6898   {
6899     \exp_args:NNo \exp_args:No \__int_to_symbols:nnnn
6900     {
6901       \int_case:nn
6902       { 1 + \int_mod:nn { #1 - 1 } {#2} }
6903       {#3}
6904     }
6905     {#1} {#2} {#3}
6906   }
6907   { \int_case:nn {#1} {#3} }
6908 }
6909 \cs_new:Npn \__int_to_symbols:nnnn #1#2#3#4
6910 {
6911   \exp_args:Nf \int_to_symbols:nnn
6912   { \int_div_truncate:nn { #2 - 1 } {#3} } {#3} {#4}
6913   #1
6914 }

```

(End definition for `\int_to_symbols:nnn` and `__int_to_symbols:nnnn`. This function is documented on page 87.)

`\int_to_alph:n` These both use the above function with input functions that make sense for the alphabet in English.

`\int_to_Alph:n`

```

6915 \cs_new:Npn \int_to_alph:n #1
6916 {
6917   \int_to_symbols:nnn {#1} { 26 }
6918   {
6919     { 1 } { a }

```

```

6920         { 2 } { b }
6921         { 3 } { c }
6922         { 4 } { d }
6923         { 5 } { e }
6924         { 6 } { f }
6925         { 7 } { g }
6926         { 8 } { h }
6927         { 9 } { i }
6928         { 10 } { j }
6929         { 11 } { k }
6930         { 12 } { l }
6931         { 13 } { m }
6932         { 14 } { n }
6933         { 15 } { o }
6934         { 16 } { p }
6935         { 17 } { q }
6936         { 18 } { r }
6937         { 19 } { s }
6938         { 20 } { t }
6939         { 21 } { u }
6940         { 22 } { v }
6941         { 23 } { w }
6942         { 24 } { x }
6943         { 25 } { y }
6944         { 26 } { z }
6945     }
6946 }
6947 \cs_new:Npn \int_to_Alph:n #1
6948 {
6949     \int_to_symbols:nnn {#1} { 26 }
6950     {
6951         { 1 } { A }
6952         { 2 } { B }
6953         { 3 } { C }
6954         { 4 } { D }
6955         { 5 } { E }
6956         { 6 } { F }
6957         { 7 } { G }
6958         { 8 } { H }
6959         { 9 } { I }
6960         { 10 } { J }
6961         { 11 } { K }
6962         { 12 } { L }
6963         { 13 } { M }
6964         { 14 } { N }
6965         { 15 } { O }
6966         { 16 } { P }
6967         { 17 } { Q }
6968         { 18 } { R }
6969         { 19 } { S }
6970         { 20 } { T }
6971         { 21 } { U }
6972         { 22 } { V }
6973         { 23 } { W }

```



```

6974         { 24 } { X }
6975         { 25 } { Y }
6976         { 26 } { Z }
6977     }
6978 }

```

(End definition for `\int_to_alph:n` and `\int_to_Alph:n`. These functions are documented on page 87.)

```

\int_to_base:nn Converting from base ten (#1) to a second base (#2) starts with computing #1: if it is
\int_to_Base:nn a complicated calculation, we shouldn't perform it twice. Then check the sign, store it,
                  either - or \c_empty_tl, and feed the absolute value to the next auxiliary function.
\__int_to_base:nn
\__int_to_Base:nn
\__int_to_base:nnN
\__int_to_Base:nnN
\__int_to_base:nnnN
\__int_to_Base:nnnN
\__int_to_letter:n
\__int_to_Letter:n
6979 \cs_new:Npn \int_to_base:nn #1
6980 { \exp_args:Nf \__int_to_base:nn { \int_eval:n {#1} } }
6981 \cs_new:Npn \int_to_Base:nn #1
6982 { \exp_args:Nf \__int_to_Base:nn { \int_eval:n {#1} } }
6983 \cs_new:Npn \__int_to_base:nn #1#2
6984 {
6985     \int_compare:nNnTF {#1} < 0
6986     { \exp_args:No \__int_to_base:nnN { \use_none:n #1 } {#2} - }
6987     { \__int_to_base:nnN {#1} {#2} \c_empty_tl }
6988 }
6989 \cs_new:Npn \__int_to_Base:nn #1#2
6990 {
6991     \int_compare:nNnTF {#1} < 0
6992     { \exp_args:No \__int_to_Base:nnN { \use_none:n #1 } {#2} - }
6993     { \__int_to_Base:nnN {#1} {#2} \c_empty_tl }
6994 }

```

Here, the idea is to provide a recursive system to deal with the input. The output is built up after the end of the function. At each pass, the value in `#1` is checked to see if it is less than the new base (`#2`). If it is, then it is converted directly, putting the sign back in front. On the other hand, if the value to convert is greater than or equal to the new base then the modulus and remainder values are found. The modulus is converted to a symbol and put on the right, and the remainder is carried forward to the next round.

```

6995 \cs_new:Npn \__int_to_base:nnN #1#2#3
6996 {
6997     \int_compare:nNnTF {#1} < {#2}
6998     { \exp_last_unbraced:Nf #3 { \__int_to_letter:n {#1} } }
6999     {
7000         \exp_args:Nf \__int_to_base:nnnN
7001         { \__int_to_letter:n { \int_mod:nn {#1} {#2} } }
7002         {#1}
7003         {#2}
7004         #3
7005     }
7006 }
7007 \cs_new:Npn \__int_to_base:nnnN #1#2#3#4
7008 {
7009     \exp_args:Nf \__int_to_base:nnN
7010     { \int_div_truncate:nn {#2} {#3} }
7011     {#3}
7012     #4
7013     #1
7014 }

```

```

7015 \cs_new:Npn \__int_to_Base:nnN #1#2#3
7016 {
7017   \int_compare:nNnTF {#1} < {#2}
7018   { \exp_last_unbraced:Nf #3 { \__int_to_Letter:n {#1} } }
7019   {
7020     \exp_args:Nf \__int_to_Base:nnnN
7021     { \__int_to_Letter:n { \int_mod:nn {#1} {#2} } }
7022     {#1}
7023     {#2}
7024     #3
7025   }
7026 }
7027 \cs_new:Npn \__int_to_Base:nnnN #1#2#3#4
7028 {
7029   \exp_args:Nf \__int_to_Base:nnN
7030   { \int_div_truncate:nn {#2} {#3} }
7031   {#3}
7032   #4
7033   #1
7034 }

```

Convert to a letter only if necessary, otherwise simply return the value unchanged. It would be cleaner to use `\int_case:nn`, but in our case, the cases are contiguous, so it is forty times faster to use the `\if_case:w` primitive. The first `\exp_after:wN` expands the conditional, jumping to the correct case, the second one expands after the resulting character to close the conditional. Since `#1` might be an expression, and not directly a single digit, we need to evaluate it properly, and expand the trailing `\fi:`.

```

7035 \cs_new:Npn \__int_to_letter:n #1
7036 {
7037   \exp_after:wN \exp_after:wN
7038   \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
7039   a
7040   \or: b
7041   \or: c
7042   \or: d
7043   \or: e
7044   \or: f
7045   \or: g
7046   \or: h
7047   \or: i
7048   \or: j
7049   \or: k
7050   \or: l
7051   \or: m
7052   \or: n
7053   \or: o
7054   \or: p
7055   \or: q
7056   \or: r
7057   \or: s
7058   \or: t
7059   \or: u
7060   \or: v
7061   \or: w

```

```

7062     \or: x
7063     \or: y
7064     \or: z
7065     \else: \int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
7066     \fi:
7067 }
7068 \cs_new:Npn \__int_to_Letter:n #1
7069 {
7070     \exp_after:wN \exp_after:wN
7071     \if_case:w \__int_eval:w #1 - 10 \__int_eval_end:
7072         A
7073     \or: B
7074     \or: C
7075     \or: D
7076     \or: E
7077     \or: F
7078     \or: G
7079     \or: H
7080     \or: I
7081     \or: J
7082     \or: K
7083     \or: L
7084     \or: M
7085     \or: N
7086     \or: O
7087     \or: P
7088     \or: Q
7089     \or: R
7090     \or: S
7091     \or: T
7092     \or: U
7093     \or: V
7094     \or: W
7095     \or: X
7096     \or: Y
7097     \or: Z
7098     \else: \int_value:w \__int_eval:w #1 \exp_after:wN \__int_eval_end:
7099     \fi:
7100 }

```

(End definition for \int_to_base:nn and others. These functions are documented on page 88.)

```

\int_to_bin:n Wrappers around the generic function.
\int_to_hex:n 7101 \cs_new:Npn \int_to_bin:n #1
\int_to_hex:n { \int_to_base:nn {#1} { 2 } }
\int_to_hex:n 7102
\int_to_hex:n 7103 \cs_new:Npn \int_to_hex:n #1
\int_to_hex:n { \int_to_base:nn {#1} { 16 } }
\int_to_hex:n 7104
\int_to_hex:n 7105 \cs_new:Npn \int_to_hex:n #1
\int_to_hex:n { \int_to_base:nn {#1} { 16 } }
\int_to_hex:n 7106
\int_to_hex:n 7107 \cs_new:Npn \int_to_hex:n #1
\int_to_hex:n { \int_to_base:nn {#1} { 8 } }
\int_to_hex:n 7108

```

(End definition for \int_to_bin:n and others. These functions are documented on page 88.)

```

\int_to_roman:n The \__int_to_roman:w primitive creates tokens of category code 12 (other). Usually,
\int_to_Roman:n what is actually wanted is letters. The approach here is to convert the output of the
\__int_to_roman:N primitive into letters using appropriate control sequence names. That keeps everything
\__int_to_roman:N expandable. The loop is terminated by the conversion of the Q.
\__int_to_roman_i:w 7109 \cs_new:Npn \int_to_roman:n #1
\__int_to_roman_v:w 7110 {
\__int_to_roman_x:w 7111 \exp_after:wN \__int_to_roman:N
\__int_to_roman_l:w 7112 \__int_to_roman:w \int_eval:n {#1} Q
\__int_to_roman_c:w 7113 }
\__int_to_roman_d:w 7114 \cs_new:Npn \__int_to_roman:N #1
\__int_to_roman_m:w 7115 {
\__int_to_roman_Q:w 7116 \use:c { __int_to_roman_ #1 :w }
\__int_to_Roman_i:w 7117 \__int_to_roman:N
\__int_to_Roman_v:w 7118 }
\__int_to_Roman_x:w 7119 \cs_new:Npn \int_to_Roman:n #1
\__int_to_Roman_l:w 7120 {
\__int_to_Roman_c:w 7121 \exp_after:wN \__int_to_Roman_aux:N
\__int_to_Roman_d:w 7122 \__int_to_roman:w \int_eval:n {#1} Q
\__int_to_Roman_m:w 7123 }
\__int_to_Roman_Q:w 7124 \cs_new:Npn \__int_to_Roman_aux:N #1
7125 {
7126 \use:c { __int_to_Roman_ #1 :w }
7127 \__int_to_Roman_aux:N
7128 }
7129 \cs_new:Npn \__int_to_roman_i:w { i }
7130 \cs_new:Npn \__int_to_roman_v:w { v }
7131 \cs_new:Npn \__int_to_roman_x:w { x }
7132 \cs_new:Npn \__int_to_roman_l:w { l }
7133 \cs_new:Npn \__int_to_roman_c:w { c }
7134 \cs_new:Npn \__int_to_roman_d:w { d }
7135 \cs_new:Npn \__int_to_roman_m:w { m }
7136 \cs_new:Npn \__int_to_roman_Q:w #1 { }
7137 \cs_new:Npn \__int_to_Roman_i:w { I }
7138 \cs_new:Npn \__int_to_Roman_v:w { V }
7139 \cs_new:Npn \__int_to_Roman_x:w { X }
7140 \cs_new:Npn \__int_to_Roman_l:w { L }
7141 \cs_new:Npn \__int_to_Roman_c:w { C }
7142 \cs_new:Npn \__int_to_Roman_d:w { D }
7143 \cs_new:Npn \__int_to_Roman_m:w { M }
7144 \cs_new:Npn \__int_to_Roman_Q:w #1 { }

```

(End definition for \int_to_roman:n and others. These functions are documented on page 88.)

10.9 Converting from other formats to integers

__int_pass_signs:wn Called as __int_pass_signs:wn <signs and digits> \q_stop {<code>}, this function leaves in the input stream any sign it finds, then inserts the <code> before the first non-sign token (and removes \q_stop). More precisely, it deletes any + and passes any - to the input stream, hence should be called in an integer expression.

```

7145 \cs_new:Npn \__int_pass_signs:wn #1
7146 {
7147 \if:w + \if:w - \exp_not:N #1 + \fi: \exp_not:N #1
7148 \exp_after:wN \__int_pass_signs:wn

```

```

7149     \else:
7150         \exp_after:wN \__int_pass_signs_end:wn
7151         \exp_after:wN #1
7152     \fi:
7153 }
7154 \cs_new:Npn \__int_pass_signs_end:wn #1 \q_stop #2 { #2 #1 }

```

(End definition for __int_pass_signs:wn and __int_pass_signs_end:wn.)

\int_from_alph:n First take care of signs then loop through the input using the recursion quarks. The **__int_from_alph:nN** auxiliary collects in its first argument the value obtained so far, and the auxiliary **__int_from_alph:N** converts one letter to an expression which evaluates to the correct number.

```

7155 \cs_new:Npn \int_from_alph:n #1
7156 {
7157     \int_eval:n
7158     {
7159         \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
7160         \q_stop { \__int_from_alph:nN { 0 } }
7161         \q_recursion_tail \q_recursion_stop
7162     }
7163 }
7164 \cs_new:Npn \__int_from_alph:nN #1#2
7165 {
7166     \quark_if_recursion_tail_stop_do:Nn #2 {#1}
7167     \exp_args:Nf \__int_from_alph:nN
7168     { \int_eval:n { #1 * 26 + \__int_from_alph:N #2 } }
7169 }
7170 \cs_new:Npn \__int_from_alph:N #1
7171 { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 64 } { 96 } }

```

(End definition for \int_from_alph:n, __int_from_alph:nN, and __int_from_alph:N. This function is documented on page 88.)

\int_from_base:nn Leave the signs into the integer expression, then loop through characters, collecting the value found so far in the first argument of **__int_from_base:nnN**. To convert a single character, **__int_from_base:N** checks first for digits, then distinguishes lower from upper case letters, turning them into the appropriate number. Note that this auxiliary does not use **\int_eval:n**, hence is not safe for general use.

```

7172 \cs_new:Npn \int_from_base:nn #1#2
7173 {
7174     \int_eval:n
7175     {
7176         \exp_after:wN \__int_pass_signs:wn \tl_to_str:n {#1}
7177         \q_stop { \__int_from_base:nnN { 0 } {#2} }
7178         \q_recursion_tail \q_recursion_stop
7179     }
7180 }
7181 \cs_new:Npn \__int_from_base:nnN #1#2#3
7182 {
7183     \quark_if_recursion_tail_stop_do:Nn #3 {#1}
7184     \exp_args:Nf \__int_from_base:nnN
7185     { \int_eval:n { #1 * #2 + \__int_from_base:N #3 } }
7186     {#2}

```

```

7187 }
7188 \cs_new:Npn \__int_from_base:N #1
7189 {
7190   \int_compare:nNnTF { '#1 } < { 58 }
7191     {#1}
7192     { '#1 - \int_compare:nNnTF { '#1 } < { 91 } { 55 } { 87 } }
7193 }

```

(End definition for `\int_from_base:nn`, `__int_from_base:nnN`, and `__int_from_base:N`. This function is documented on page 89.)

`\int_from_bin:n` Wrappers around the generic function.

```

\int_from_hex:n
\int_from_oct:n
7194 \cs_new:Npn \int_from_bin:n #1
7195   { \int_from_base:nn {#1} { 2 } }
7196 \cs_new:Npn \int_from_hex:n #1
7197   { \int_from_base:nn {#1} { 16 } }
7198 \cs_new:Npn \int_from_oct:n #1
7199   { \int_from_base:nn {#1} { 8 } }

```

(End definition for `\int_from_bin:n`, `\int_from_hex:n`, and `\int_from_oct:n`. These functions are documented on page 88.)

`\c_int_from_roman_i_int` Constants used to convert from Roman numerals to integers.

```

\c_int_from_roman_v_int
\c_int_from_roman_x_int
\c_int_from_roman_l_int
\c_int_from_roman_c_int
\c_int_from_roman_d_int
\c_int_from_roman_m_int
\c_int_from_roman_I_int
\c_int_from_roman_V_int
\c_int_from_roman_X_int
\c_int_from_roman_L_int
\c_int_from_roman_C_int
\c_int_from_roman_D_int
\c_int_from_roman_M_int
7200 \int_const:cn { \c_int_from_roman_i_int } { 1 }
7201 \int_const:cn { \c_int_from_roman_v_int } { 5 }
7202 \int_const:cn { \c_int_from_roman_x_int } { 10 }
7203 \int_const:cn { \c_int_from_roman_l_int } { 50 }
7204 \int_const:cn { \c_int_from_roman_c_int } { 100 }
7205 \int_const:cn { \c_int_from_roman_d_int } { 500 }
7206 \int_const:cn { \c_int_from_roman_m_int } { 1000 }
7207 \int_const:cn { \c_int_from_roman_I_int } { 1 }
7208 \int_const:cn { \c_int_from_roman_V_int } { 5 }
7209 \int_const:cn { \c_int_from_roman_X_int } { 10 }
7210 \int_const:cn { \c_int_from_roman_L_int } { 50 }
7211 \int_const:cn { \c_int_from_roman_C_int } { 100 }
7212 \int_const:cn { \c_int_from_roman_D_int } { 500 }
7213 \int_const:cn { \c_int_from_roman_M_int } { 1000 }

```

(End definition for `\c_int_from_roman_i_int` and others.)

`\int_from_roman:n` The method here is to iterate through the input, finding the appropriate value for each letter and building up a sum. This is then evaluated by \TeX . If any unknown letter is found, skip to the closing parenthesis and insert `*0-1` afterwards, to replace the value by `-1`.

```

\__int_from_roman:NN
\__int_from_roman_error:w
7214 \cs_new:Npn \int_from_roman:n #1
7215   {
7216     \int_eval:n
7217     {
7218       (
7219         0
7220         \exp_after:wN \__int_from_roman:NN \tl_to_str:n {#1}
7221         \q_recursion_tail \q_recursion_tail \q_recursion_stop
7222       )
7223     }
7224   }

```

```

7225 \cs_new:Npn \__int_from_roman:NN #1#2
7226 {
7227   \quark_if_recursion_tail_stop:N #1
7228   \int_if_exist:cF { c__int_from_roman_ #1 _int }
7229   { \__int_from_roman_error:w }
7230   \quark_if_recursion_tail_stop_do:Nn #2
7231   { + \use:c { c__int_from_roman_ #1 _int } }
7232   \int_if_exist:cF { c__int_from_roman_ #2 _int }
7233   { \__int_from_roman_error:w }
7234   \int_compare:nNnTF
7235   { \use:c { c__int_from_roman_ #1 _int } }
7236   <
7237   { \use:c { c__int_from_roman_ #2 _int } }
7238   {
7239     + \use:c { c__int_from_roman_ #2 _int }
7240     - \use:c { c__int_from_roman_ #1 _int }
7241     \__int_from_roman:NN
7242   }
7243   {
7244     + \use:c { c__int_from_roman_ #1 _int }
7245     \__int_from_roman:NN #2
7246   }
7247 }
7248 \cs_new:Npn \__int_from_roman_error:w #1 \q_recursion_stop #2
7249 { #2 * 0 - 1 }

```

(End definition for `\int_from_roman:n`, `__int_from_roman:NN`, and `__int_from_roman_error:w`. This function is documented on page 89.)

10.10 Viewing integer

`\int_show:N` Diagnostics.

```

\int_show:c      7250 \cs_new_eq:NN \int_show:N \__kernel_register_show:N
\__int_show:nN   7251 \cs_generate_variant:Nn \int_show:N { c }

```

(End definition for `\int_show:N` and `__int_show:nN`. This function is documented on page 89.)

`\int_show:n` We don't use the \TeX primitive `\showthe` to show integer expressions: this gives a more unified output.

```

7252 \cs_new_protected:Npn \int_show:n
7253 { \msg_show_eval:Nn \int_eval:n }

```

(End definition for `\int_show:n`. This function is documented on page 90.)

`\int_log:N` Diagnostics.

```

\int_log:c      7254 \cs_new_eq:NN \int_log:N \__kernel_register_log:N
                7255 \cs_generate_variant:Nn \int_log:N { c }

```

(End definition for `\int_log:N`. This function is documented on page 90.)

`\int_log:n` Similar to `\int_show:n`.

```

7256 \cs_new_protected:Npn \int_log:n
7257 { \msg_log_eval:Nn \int_eval:n }

```

(End definition for `\int_log:n`. This function is documented on page 90.)

10.11 Random integers

`\int_rand:nn` Defined in `l3fp-random`.

(End definition for `\int_rand:nn`. This function is documented on page 89.)

10.12 Constant integers

`\c_zero_int` The zero is defined in `l3basics`.

`\c_one_int` 7258 `\int_const:Nn \c_one_int { 1 }`

(End definition for `\c_zero_int` and `\c_one_int`. These variables are documented on page 90.)

`\c_max_int` The largest number allowed is $2^{31} - 1$

7259 `\int_const:Nn \c_max_int { 2 147 483 647 }`

(End definition for `\c_max_int`. This variable is documented on page 90.)

`\c_max_char_int` The largest character code is 1114111 (hexadecimal 10FFFF) in X_ƎT_ƎX and LuaT_ƎX and 255 in other engines. In many places pT_ƎX and upT_ƎX support larger character codes but for instance the values of `\lccode` are restricted to $[0, 255]$.

```
7260 \int_const:Nn \c_max_char_int
7261 {
7262   \if_int_odd:w 0
7263     \cs_if_exist:NT \tex luatexversion:D { 1 }
7264     \cs_if_exist:NT \tex XeTeXversion:D { 1 } ~
7265     "10FFFF
7266   \else:
7267     "FF
7268   \fi:
7269 }
```

(End definition for `\c_max_char_int`. This variable is documented on page 90.)

10.13 Scratch integers

`\l_tmpa_int` We provide two local and two global scratch counters, maybe we need more or less.

`\l_tmpb_int` 7270 `\int_new:N \l_tmpa_int`

`\g_tmpa_int` 7271 `\int_new:N \l_tmpb_int`

`\g_tmpb_int` 7272 `\int_new:N \g_tmpa_int`

7273 `\int_new:N \g_tmpb_int`

(End definition for `\l_tmpa_int` and others. These variables are documented on page 90.)

10.14 Deprecated

`\c_zero` Constants that are now deprecated. By default define them with `\int_const:Nn`.
`\c_one` To deprecate them call for instance `_kernel_deprecation_error:Nnn \c_zero {0}`
`\c_two` `{2019-12-31}`. To redefine them (locally), use `_int_constdef:Nw`, with an `\exp_`
`\c_three` `not:N` construction because the constants themselves are outer at that point.

```

7274 \cs_new_protected:Npn \_int_deprecated_constants:nn #1#2
7275 {
7276   #1 \c_zero { 0 } #2
7277   #1 \c_one { 1 } #2
7278   #1 \c_two { 2 } #2
7279   #1 \c_three { 3 } #2
7280   #1 \c_four { 4 } #2
7281   #1 \c_five { 5 } #2
7282   #1 \c_six { 6 } #2
7283   #1 \c_seven { 7 } #2
7284   #1 \c_eight { 8 } #2
7285   #1 \c_nine { 9 } #2
7286   #1 \c_ten { 10 } #2
7287   #1 \c_eleven { 11 } #2
7288   #1 \c_twelve { 12 } #2
7289   #1 \c_thirteen { 13 } #2
7290   #1 \c_fourteen { 14 } #2
7291   #1 \c_fifteen { 15 } #2
7292   #1 \c_sixteen { 16 } #2
7293   #1 \c_thirty_two { 32 } #2
7294   #1 \c_one_hundred { 100 } #2
7295   #1 \c_two_hundred_fifty_five { 255 } #2
7296   #1 \c_two_hundred_fifty_six { 256 } #2
7297   #1 \c_one_thousand { 1000 } #2
7298   #1 \c_ten_thousand { 10000 } #2
7299 }
7300 \_int_deprecated_constants:nn { \int_const:Nn } { }
7301 \_kernel_deprecation_code:nn
7302 {
7303   \_int_deprecated_constants:nn
7304   { \_kernel_deprecation_error:Nnn } { { 2019-12-31 } }
7305 }
7306 {
7307   \_int_deprecated_constants:nn
7308   {
7309     \exp_after:wN \use:nnn
7310     \exp_after:wN \_int_constdef:Nw \exp_not:N
7311   }
7312   { \exp_stop_f: }
7313 }
```

(End definition for `\c_zero` and others.)

`_int_value:w` Made public.

```
7314 \cs_new_eq:NN \_int_value:w \int_value:w
```

(End definition for `_int_value:w`.)

```
7315 </initex | package>
```

11 l3flag implementation

7316 `*initex | package)`

7317 `\@@=flag)`

The following test files are used for this code: m3flag001.

11.1 Non-expandable flag commands

The height h of a flag (initially zero) is stored by setting control sequences of the form `\flag <name> <integer>` to `\relax` for $0 \leq \langle integer \rangle < h$. When a flag is raised, a “trap” function `\flag <name>` is called. The existence of this function is also used to test for the existence of a flag.

`\flag_new:n` For each flag, we define a “trap” function, which by default simply increases the flag by 1 by letting the appropriate control sequence to `\relax`. This can be done expandably!

```
7318 \cs_new_protected:Npn \flag_new:n #1
7319 {
7320   \cs_new:cpn { flag~#1 } ##1 ;
7321   { \exp_after:wN \use_none:n \cs:w flag~#1~##1 \cs_end: }
7322 }
```

(End definition for \flag_new:n. This function is documented on page 93.)

`\flag_clear:n` `__flag_clear:wn` Undefine control sequences, starting from the 0 flag, upwards, until reaching an undefined control sequence. We don’t use `\cs_undefine:c` because that would act globally. When the option `check-declarations` is used, check for the function defined by `\flag_new:n`.

```
7323 \__kernel_patch:nnNNpn
7324 { \exp_args:Nc \__kernel_chk_var_exist:N { flag~#1 } } { }
7325 \cs_new_protected:Npn \flag_clear:n #1 { \__flag_clear:wn 0 ; {#1} }
7326 \cs_new_protected:Npn \__flag_clear:wn #1 ; #2
7327 {
7328   \if_cs_exist:w flag~#2~#1 \cs_end:
7329   \cs_set_eq:cN { flag~#2~#1 } \tex_undefined:D
7330   \exp_after:wN \__flag_clear:wn
7331   \int_value:w \int_eval:w 1 + #1
7332   \else:
7333     \use_i:nnn
7334   \fi:
7335   ; {#2}
7336 }
```

(End definition for \flag_clear:n and __flag_clear:wn. This function is documented on page 93.)

`\flag_clear_new:n` As for other datatypes, clear the `<flag>` or create a new one, as appropriate.

```
7337 \cs_new_protected:Npn \flag_clear_new:n #1
7338 { \flag_if_exist:nTF {#1} { \flag_clear:n } { \flag_new:n } {#1} }
```

(End definition for \flag_clear_new:n. This function is documented on page 93.)

`\flag_show:n` `\flag_log:n` `__flag_show:Nn` Show the height (terminal or log file) using appropriate `l3msg` auxiliaries.

```
7339 \cs_new_protected:Npn \flag_show:n { \__flag_show:Nn \tl_show:n }
7340 \cs_new_protected:Npn \flag_log:n { \__flag_show:Nn \tl_log:n }
7341 \cs_new_protected:Npn \__flag_show:Nn #1#2
7342 {
```

```

7343 \exp_args:Nc \__kernel_chk_defined:NT { flag~#2 }
7344 {
7345   \exp_args:Nx #1
7346   { \tl_to_str:n { flag~#2~height } = \flag_height:n {#2} }
7347 }
7348 }

```

(End definition for `\flag_show:n`, `\flag_log:n`, and `__flag_show:Nn`. These functions are documented on page 93.)

11.2 Expandable flag commands

`__flag_chk_exist:n` Analogue of `__kernel_chk_var_exist:N` for flags, and with an expandable error. We need to add checks by hand because flags are not implemented in terms of other variables. Not all functions need to be patched since some are defined in terms of others.

```

7349 \*package
7350 \__kernel_if_debug:TF
7351 {
7352   \cs_new:Npn \__flag_chk_exist:n #1
7353   {
7354     \flag_if_exist:nF {#1}
7355     {
7356       \__kernel_msg_expandable_error:nnn
7357       { kernel } { bad-variable } { flag~#1~ }
7358     }
7359   }
7360 }
7361 { }
7362 \*package

```

(End definition for `__flag_chk_exist:n`.)

`\flag_if_exist_p:n` A flag exist if the corresponding trap `\flag <flag name>:n` is defined.

```

\flag_if_exist:nTF
7363 \prg_new_conditional:Npnn \flag_if_exist:n #1 { p , T , F , TF }
7364 {
7365   \cs_if_exist:cTF { flag~#1 }
7366   { \prg_return_true: } { \prg_return_false: }
7367 }

```

(End definition for `\flag_if_exist:nTF`. This function is documented on page 94.)

`\flag_if_raised_p:n` Test if the flag has a non-zero height, by checking the 0 control sequence.

```

\flag_if_raised:nTF
7368 \__kernel_patch_conditional:nNNpnn { \__flag_chk_exist:n {#1} }
7369 \prg_new_conditional:Npnn \flag_if_raised:n #1 { p , T , F , TF }
7370 {
7371   \if_cs_exist:w flag~#1~0 \cs_end:
7372   \prg_return_true:
7373   \else:
7374   \prg_return_false:
7375   \fi:
7376 }

```

(End definition for `\flag_if_raised:nTF`. This function is documented on page 94.)

\flag_height:n Extract the value of the flag by going through all of the control sequences starting from 0.

```

7377 \__kernel_patch:nnNNpn { \__flag_chk_exist:n {#1} } { }
7378 \cs_new:Npn \flag_height:n #1 { \__flag_height_loop:wn 0; {#1} }
7379 \cs_new:Npn \__flag_height_loop:wn #1 ; #2
7380 {
7381   \if_cs_exist:w flag~#2~#1 \cs_end:
7382   \exp_after:wN \__flag_height_loop:wn \int_value:w \int_eval:w 1 +
7383   \else:
7384   \exp_after:wN \__flag_height_end:wn
7385   \fi:
7386   #1 ; {#2}
7387 }
7388 \cs_new:Npn \__flag_height_end:wn #1 ; #2 {#1}

```

(End definition for \flag_height:n, __flag_height_loop:wn, and __flag_height_end:wn. This function is documented on page 94.)

\flag_raise:n Simply apply the trap to the height, after expanding the latter.

```

7389 \cs_new:Npn \flag_raise:n #1
7390 {
7391   \cs:w flag~#1 \exp_after:wN \cs_end:
7392   \int_value:w \flag_height:n {#1} ;
7393 }

```

(End definition for \flag_raise:n. This function is documented on page 94.)

```
7394 </initex | package>
```

12 l3prg implementation

The following test files are used for this code: m3prg001.lvt,m3prg002.lvt,m3prg003.lvt.

```
7395 <*initex | package>
```

12.1 Primitive conditionals

\if_bool:N Those two primitive T_EX conditionals are synonyms.
\if_predicate:w

```

7396 \cs_new_eq:NN \if_bool:N \tex_ifodd:D
7397 \cs_new_eq:NN \if_predicate:w \tex_ifodd:D

```

(End definition for \if_bool:N and \if_predicate:w. These functions are documented on page 102.)

12.2 Defining a set of conditional functions

\prg_set_conditional:Npnn These are all defined in l3basics, as they are needed “early”. This is just a reminder!

\prg_new_conditional:Npnn (End definition for \prg_set_conditional:Npnn and others. These functions are documented on page 95.)
\prg_set_protected_conditional:Npnn
\prg_new_protected_conditional:Npnn

\prg_set_conditional:Nnn

\prg_new_conditional:Nnn

\prg_set_protected_conditional:Nnn

\prg_new_protected_conditional:Nnn

\prg_set_eq_conditional:NNN

\prg_new_eq_conditional:NNN

\prg_return_true:

\prg_return_false:

12.3 The boolean data type

7398 <@@=bool>

\bool_new:N Boolean variables have to be initiated when they are created. Other than that there is not much to say here.

\bool_new:c

7399 \cs_new_protected:Npn \bool_new:N #1 { \cs_new_eq:NN #1 \c_false_bool }
7400 \cs_generate_variant:Nn \bool_new:N { c }

(End definition for \bool_new:N. This function is documented on page 97.)

\bool_set_true:N Setting is already pretty easy. When `check-declarations` is active, the definitions are patched to make sure the boolean exists. This is needed because booleans are not based on token lists nor on T_EX registers.

\bool_set_true:c

\bool_gset_true:N

\bool_gset_true:c

\bool_set_false:N

\bool_set_false:c

\bool_gset_false:N

\bool_gset_false:c

7401 __kernel_patch:nnNpn { __kernel_chk_var_local:N #1 } { }
7402 \cs_new_protected:Npn \bool_set_true:N #1
7403 { \cs_set_eq:NN #1 \c_true_bool }
7404 __kernel_patch:nnNpn { __kernel_chk_var_local:N #1 } { }
7405 \cs_new_protected:Npn \bool_set_false:N #1
7406 { \cs_set_eq:NN #1 \c_false_bool }
7407 __kernel_patch:nnNpn { __kernel_chk_var_global:N #1 } { }
7408 \cs_new_protected:Npn \bool_gset_true:N #1
7409 { \cs_gset_eq:NN #1 \c_true_bool }
7410 __kernel_patch:nnNpn { __kernel_chk_var_global:N #1 } { }
7411 \cs_new_protected:Npn \bool_gset_false:N #1
7412 { \cs_gset_eq:NN #1 \c_false_bool }
7413 \cs_generate_variant:Nn \bool_set_true:N { c }
7414 \cs_generate_variant:Nn \bool_set_false:N { c }
7415 \cs_generate_variant:Nn \bool_gset_true:N { c }
7416 \cs_generate_variant:Nn \bool_gset_false:N { c }

(End definition for \bool_set_true:N and others. These functions are documented on page 97.)

\bool_set_eq:NN The usual copy code. While it would be cleaner semantically to copy the `\cs_set_eq:NN` family of functions, we copy `\tl_set_eq:NN` because that has the correct checking code.

\bool_set_eq:cN

\bool_set_eq:Nc

\bool_set_eq:cc

\bool_gset_eq:NN

\bool_gset_eq:cN

\bool_gset_eq:Nc

\bool_gset_eq:cc

7417 \cs_new_eq:NN \bool_set_eq:NN \tl_set_eq:NN
7418 \cs_new_eq:NN \bool_gset_eq:NN \tl_gset_eq:NN
7419 \cs_generate_variant:Nn \bool_set_eq:NN { Nc, cN, cc }
7420 \cs_generate_variant:Nn \bool_gset_eq:NN { Nc, cN, cc }

(End definition for \bool_set_eq:NN and \bool_gset_eq:NN. These functions are documented on page 98.)

\bool_set:Nn This function evaluates a boolean expression and assigns the first argument the meaning `\c_true_bool` or `\c_false_bool`. Again, we include some checking code. It is important to evaluate the expression before applying the `\chardef` primitive, because that primitive sets the left-hand side to `\scan_stop:` before looking for the right-hand side.

\bool_set:cn

\bool_gset:Nn

\bool_gset:cn

7421 __kernel_patch:nnNpn { __kernel_chk_var_local:N #1 } { }
7422 \cs_new_protected:Npn \bool_set:Nn #1#2
7423 {
7424 \exp_last_unbraced:NNNf
7425 \tex_chardef:D #1 = { \bool_if_p:n {#2} }
7426 }
7427 __kernel_patch:nnNpn { __kernel_chk_var_global:N #1 } { }
7428 \cs_new_protected:Npn \bool_gset:Nn #1#2

```

7429 {
7430   \exp_last_unbraced:NNNNf
7431   \tex_global:D \tex_chardef:D #1 = { \bool_if_p:n {#2} }
7432 }
7433 \cs_generate_variant:Nn \bool_set:Nn { c }
7434 \cs_generate_variant:Nn \bool_gset:Nn { c }

```

(End definition for `\bool_set:Nn` and `\bool_gset:Nn`. These functions are documented on page 98.)

`\bool_if_p:N` Straight forward here. We could optimize here if we wanted to as the boolean can just be input directly.

```

\bool_if_p:c
\bool_if:N $\text{TF}$ 
\bool_if:c $\text{TF}$ 
7435 \prg_new_conditional:Npnn \bool_if:N #1 { p , T , F , TF }
7436 {
7437   \if_bool:N #1
7438     \prg_return_true:
7439   \else:
7440     \prg_return_false:
7441   \fi:
7442 }
7443 \prg_generate_conditional_variant:Nnn \bool_if:N { c } { p , T , F , TF }

```

(End definition for `\bool_if:N TF` . This function is documented on page 98.)

`\bool_show:n` Show the truth value of the boolean, as true or false.

```

\bool_log:n
\__bool_to_str:n
7444 \cs_new_protected:Npn \bool_show:n
7445 { \msg_show_eval:Nn \__bool_to_str:n }
7446 \cs_new_protected:Npn \bool_log:n
7447 { \msg_log_eval:Nn \__bool_to_str:n }
7448 \cs_new:Npn \__bool_to_str:n #1
7449 { \bool_if:nTF {#1} { true } { false } }

```

(End definition for `\bool_show:n`, `\bool_log:n`, and `__bool_to_str:n`. These functions are documented on page 98.)

`\bool_show:N` Show the truth value of the boolean, as true or false.

```

\bool_show:c
\bool_log:N
\bool_log:c
\__bool_show:NN
7450 \cs_new_protected:Npn \bool_show:N { \__bool_show:NN \tl_show:n }
7451 \cs_generate_variant:Nn \bool_show:N { c }
7452 \cs_new_protected:Npn \bool_log:N { \__bool_show:NN \tl_log:n }
7453 \cs_generate_variant:Nn \bool_log:N { c }
7454 \cs_new_protected:Npn \__bool_show:NN #1#2
7455 {
7456   \__kernel_chk_defined:NT #2
7457   { \exp_args:Nx #1 { \token_to_str:N #2 = \__bool_to_str:n {#2} } }
7458 }

```

(End definition for `\bool_show:N`, `\bool_log:N`, and `__bool_show:NN`. These functions are documented on page 98.)

`\l_tmpa_bool` A few booleans just if you need them.

```

\l_tmpb_bool
\g_tmpa_bool
\g_tmpb_bool
7459 \bool_new:N \l_tmpa_bool
7460 \bool_new:N \l_tmpb_bool
7461 \bool_new:N \g_tmpa_bool
7462 \bool_new:N \g_tmpb_bool

```

(End definition for `\l_tmpa_bool` and others. These variables are documented on page 98.)

```

\bool_if_exist_p:N Copies of the cs functions defined in l3basics.
\bool_if_exist_p:c 7463 \prg_new_eq_conditional:NNn \bool_if_exist:N \cs_if_exist:N
\bool_if_exist:NTF 7464 { TF , T , F , p }
\bool_if_exist:cTF 7465 \prg_new_eq_conditional:NNn \bool_if_exist:c \cs_if_exist:c
7466 { TF , T , F , p }

```

(End definition for \bool_if_exist:N~~TF~~. This function is documented on page 98.)

12.4 Boolean expressions

\bool_if_p:n Evaluating the truth value of a list of predicates is done using an input syntax somewhat similar to the one found in other programming languages with (and) for grouping, ! for logical “Not”, && for logical “And” and || for logical “Or”. However, they perform eager evaluation. We shall use the terms Not, And, Or, Open and Close for these operations.

Any expression is terminated by a Close operation. Evaluation happens from left to right in the following manner using a GetNext function:

- If an Open is seen, start evaluating a new expression using the Eval function and call GetNext again.
- If a Not is seen, remove the ! and call a GetNext function with the logic reversed.
- If none of the above, reinsert the token found (this is supposed to be a predicate function) in front of an Eval function, which evaluates it to the boolean value *<true>* or *<false>*.

The Eval function then contains a post-processing operation which grabs the instruction following the predicate. This is either And, Or or Close. In each case the truth value is used to determine where to go next. The following situations can arise:

*<true>***And** Current truth value is true, logical And seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

*<false>***And** Current truth value is false, logical And seen, stop using the values of predicates within this sub-expression until the next Close. Then return *<false>*.

*<true>***Or** Current truth value is true, logical Or seen, stop using the values of predicates within this sub-expression until the nearest Close. Then return *<true>*.

*<false>***Or** Current truth value is false, logical Or seen, continue with GetNext to examine truth value of next boolean (sub-)expression.

*<true>***Close** Current truth value is true, Close seen, return *<true>*.

*<false>***Close** Current truth value is false, Close seen, return *<false>*.

```

7467 \prg_new_conditional:Npnn \bool_if:n #1 { T , F , TF }
7468 {
7469   \if_predicate:w \bool_if_p:n {#1}
7470   \prg_return_true:
7471   \else:
7472     \prg_return_false:
7473   \fi:
7474 }

```

(End definition for \bool_if:n~~TF~~. This function is documented on page 100.)

`\bool_if_p:n` To speed up the case of a single predicate, `f-expand` and check whether the result is one token (possibly surrounded by spaces), which must be `\c_true_bool` or `\c_false_bool`. We use a version of `\tl_if_single:nTF` optimized for speed since we know that an empty `#1` is an error. The auxiliary `__bool_if_p_aux:w` removes the trailing parenthesis and gets rid of any space. For the general case, first issue a `\group_align_safe_begin:` as we are using `&&` as syntax shorthand for the And operation and we need to hide it for `TeX`. This group is closed after `__bool_get_next:NN` returns `\c_true_bool` or `\c_false_bool`. That function requires the trailing parenthesis to know where the expression ends.

```

7475 \cs_new:Npn \bool_if_p:n { \exp_args:Nf \__bool_if_p:n }
7476 \cs_new:Npn \__bool_if_p:n #1
7477 {
7478   \tl_if_empty:oT { \use_none:nn #1 . } { \__bool_if_p_aux:w }
7479   \group_align_safe_begin:
7480   \exp_after:wN
7481   \group_align_safe_end:
7482   \exp:w \exp_end_continue_f:w % (
7483   \__bool_get_next:NN \use_i:nnnn #1 )
7484 }
7485 \cs_new:Npn \__bool_if_p_aux:w #1 \use_i:nnnn #2#3 {#2}

```

(End definition for `\bool_if_p:n`, `__bool_if_p:n`, and `__bool_if_p_aux:w`. This function is documented on page 100.)

`__bool_get_next:NN` The GetNext operation. Its first argument is `\use_i:nnnn`, `\use_ii:nnnn`, `\use_iii:nnnn`, or `\use_iv:nnnn` (we call these “states”). In the first state, this function eventually expand to the truth value `\c_true_bool` or `\c_false_bool` of the expression which follows until the next unmatched closing parenthesis. For instance “`__bool_get_next:NN \use_i:nnnn \c_true_bool && \c_true_bool)`” (including the closing parenthesis) expands to `\c_true_bool`. In the second state (after a `!`) the logic is reversed. We call these two states “normal” and the next two “skipping”. In the third state (after `\c_true_bool||`) it always returns `\c_true_bool`. In the fourth state (after `\c_false_bool&&`) it always returns `\c_false_bool` and also stops when encountering `||`, not only parentheses. This code itself is a switch: if what follows is neither `!` nor `(`, we assume it is a predicate.

```

7486 \cs_new:Npn \__bool_get_next:NN #1#2
7487 {
7488   \use:c
7489   {
7490     __bool_
7491     \if_meaning:w !#2 ! \else: \if_meaning:w (#2 ( \else: p \fi: \fi:
7492     :Nw
7493   }
7494   #1 #2
7495 }

```

(End definition for `__bool_get_next:NN`.)

`__bool_!:Nw` The Not operation reverses the logic: it discards the `!` token and calls the GetNext operation with the appropriate first argument. Namely the first and second states are interchanged, but after `\c_true_bool||` or `\c_false_bool&&` the `!` is ignored.

```

7496 \cs_new:cpn { __bool_!:Nw } #1#2
7497 {

```



```

7498     \exp_after:wN \_bool_get_next:NN
7499     #1 \use_ii:nnnn \use_i:nnnn \use_iii:nnnn \use_iv:nnnn
7500 }

```

(End definition for _bool_!:Nw.)

bool(:Nw The Open operation starts a sub-expression after discarding the open parenthesis. This is done by calling GetNext (which eventually discards the corresponding closing parenthesis), with a post-processing step which looks for And, Or or Close after the group.

```

7501 \cs_new:cpn { \_bool_(:Nw } #1#2
7502 {
7503     \exp_after:wN \_bool_choose:NNN \exp_after:wN #1
7504     \int_value:w \_bool_get_next:NN \use_i:nnnn
7505 }

```

(End definition for _bool_(:Nw.)

_bool_p:Nw If what follows GetNext is neither ! nor (, evaluate the predicate using the primitive \int_value:w. The canonical true and false values have numerical values 1 and 0 respectively. Look for And, Or or Close afterwards.

```

7506 \cs_new:cpn { \_bool_p:Nw } #1
7507 { \exp_after:wN \_bool_choose:NNN \exp_after:wN #1 \int_value:w }

```

(End definition for _bool_p:Nw.)

_bool_choose:NNN The arguments are #1: a function such as \use_i:nnnn, #2: 0 or 1 encoding the current truth value, #3: the next operation, And, Or or Close. We distinguish three cases according to a combination of #1 and #2. Case 2 is when #1 is \use_iii:nnnn (state 3), namely after \c_true_bool ||. Case 1 is when #1 is \use_i:nnnn and #2 is true or when #1 is \use_ii:nnnn and #2 is false, for instance for !\c_false_bool. Case 0 includes the same with true/false interchanged and the case where #1 is \use_iv:nnnn namely after \c_false_bool &&.

bool|_0: When seeing) the current subexpression is done, leave the appropriate boolean.
bool|_1: When seeing & in case 0 go into state 4, equivalent to having seen \c_false_bool &&.
bool|_2: In case 1, namely when the argument is true and we are in a normal state continue in the normal state 1. In case 2, namely when skipping alternatives in an Or, continue in the same state. When seeing | in case 0, continue in a normal state; in particular stop skipping for \c_false_bool && because that binds more tightly than ||. In the other two cases start skipping for \c_true_bool ||.

```

7508 \cs_new:Npn \_bool_choose:NNN #1#2#3
7509 {
7510     \use:c
7511     {
7512         \_bool_ \token_to_str:N #3 _
7513         #1 #2 { \if_meaning:w 0 #2 1 \else: 0 \fi: } 2 0 :
7514     }
7515 }
7516 \cs_new:cpn { \_bool_)_0: } { \c_false_bool }
7517 \cs_new:cpn { \_bool_)_1: } { \c_true_bool }
7518 \cs_new:cpn { \_bool_)_2: } { \c_true_bool }
7519 \cs_new:cpn { \_bool_&_0: } & { \_bool_get_next:NN \use_iv:nnnn }
7520 \cs_new:cpn { \_bool_&_1: } & { \_bool_get_next:NN \use_i:nnnn }
7521 \cs_new:cpn { \_bool_&_2: } & { \_bool_get_next:NN \use_iii:nnnn }

```

```

7522 \cs_new:cpn { __bool_|_0: } | { \__bool_get_next:NN \use_i:nnnn }
7523 \cs_new:cpn { __bool_|_1: } | { \__bool_get_next:NN \use_iii:nnnn }
7524 \cs_new:cpn { __bool_|_2: } | { \__bool_get_next:NN \use_iii:nnnn }

```

(End definition for __bool_choose:NNN and others.)

\bool_lazy_all_p:n Go through the list of expressions, stopping whenever an expression is **false**. If the end
\bool_lazy_all:nTF is reached without finding any false expression, then the result is **true**.

```

\__bool_lazy_all:n
7525 \cs_new:Npn \bool_lazy_all_p:n #1
7526 { \__bool_lazy_all:n #1 \q_recursion_tail \q_recursion_stop }
7527 \prg_new_conditional:Npnn \bool_lazy_all:n #1 { T , F , TF }
7528 {
7529   \if_predicate:w \bool_lazy_all_p:n {#1}
7530   \prg_return_true:
7531   \else:
7532     \prg_return_false:
7533   \fi:
7534 }
7535 \cs_new:Npn \__bool_lazy_all:n #1
7536 {
7537   \quark_if_recursion_tail_stop_do:nn {#1} { \c_true_bool }
7538   \bool_if:nF {#1}
7539   { \use_i_delimit_by_q_recursion_stop:nw { \c_false_bool } }
7540   \__bool_lazy_all:n
7541 }

```

(End definition for \bool_lazy_all:nTF and __bool_lazy_all:n. This function is documented on page 100.)

\bool_lazy_and_p:nn Only evaluate the second expression if the first is **true**. Note that #2 must be removed
\bool_lazy_and:nnTF as an argument, not just by skipping to the **\else:** branch of the conditional since #2 may contain unbalanced **TeX** conditionals.

```

7542 \prg_new_conditional:Npnn \bool_lazy_and:nn #1#2 { p , T , F , TF }
7543 {
7544   \if_predicate:w
7545     \bool_if:nTF {#1} { \bool_if_p:n {#2} } { \c_false_bool }
7546     \prg_return_true:
7547   \else:
7548     \prg_return_false:
7549   \fi:
7550 }

```

(End definition for \bool_lazy_and:nnTF. This function is documented on page 100.)

\bool_lazy_any_p:n Go through the list of expressions, stopping whenever an expression is **true**. If the end
\bool_lazy_any:nTF is reached without finding any true expression, then the result is **false**.

```

\__bool_lazy_any:n
7551 \cs_new:Npn \bool_lazy_any_p:n #1
7552 { \__bool_lazy_any:n #1 \q_recursion_tail \q_recursion_stop }
7553 \prg_new_conditional:Npnn \bool_lazy_any:n #1 { T , F , TF }
7554 {
7555   \if_predicate:w \bool_lazy_any_p:n {#1}
7556   \prg_return_true:
7557   \else:
7558     \prg_return_false:

```

```

7559     \fi:
7560   }
7561 \cs_new:Npn \__bool_lazy_any:n #1
7562 {
7563   \quark_if_recursion_tail_stop_do:nn {#1} { \c_false_bool }
7564   \bool_if:nT {#1}
7565     { \use_i_delimit_by_q_recursion_stop:nw { \c_true_bool } }
7566   \__bool_lazy_any:n
7567 }

```

(End definition for `\bool_lazy_any:nTF` and `__bool_lazy_any:n`. This function is documented on page 100.)

`\bool_lazy_or_p:nn` Only evaluate the second expression if the first is false.

```

\bool_lazy_or:nnTF
7568 \prg_new_conditional:Npnn \bool_lazy_or:nn #1#2 { p , T , F , TF }
7569 {
7570   \if_predicate:w
7571     \bool_if:nTF {#1} { \c_true_bool } { \bool_if_p:n {#2} }
7572   \prg_return_true:
7573   \else:
7574     \prg_return_false:
7575   \fi:
7576 }

```

(End definition for `\bool_lazy_or:nnTF`. This function is documented on page 100.)

`\bool_not_p:n` The Not variant just reverses the outcome of `\bool_if_p:n`. Can be optimized but this is nice and simple and according to the implementation plan. Not even particularly useful to have it when the infix notation is easier to use.

```

7577 \cs_new:Npn \bool_not_p:n #1 { \bool_if_p:n { ! ( #1 ) } }

```

(End definition for `\bool_not_p:n`. This function is documented on page 100.)

`\bool_xor_p:nn` Exclusive or. If the boolean expressions have same truth value, return `false`, otherwise
`\bool_xor:nnTF` return `true`.

```

7578 \prg_new_conditional:Npnn \bool_xor:nn #1#2 { p , T , F , TF }
7579 {
7580   \bool_if:nT {#1} \reverse_if:N
7581   \if_predicate:w \bool_if_p:n {#2}
7582     \prg_return_true:
7583   \else:
7584     \prg_return_false:
7585   \fi:
7586 }

```

(End definition for `\bool_xor:nnTF`. This function is documented on page 101.)

12.5 Logical loops

`\bool_while_do:Nn` A while loop where the boolean is tested before executing the statement. The “while”
`\bool_while_do:cn` version executes the code as long as the boolean is true; the “until” version executes the
`\bool_until_do:Nn` code as long as the boolean is false.

```

\bool_until_do:cn
7587 \cs_new:Npn \bool_while_do:Nn #1#2
7588 { \bool_if:NT #1 { #2 \bool_while_do:Nn #1 {#2} } }

```

```

7589 \cs_new:Npn \bool_until_do:Nn #1#2
7590 { \bool_if:NF #1 { #2 \bool_until_do:Nn #1 {#2} } }
7591 \cs_generate_variant:Nn \bool_while_do:Nn { c }
7592 \cs_generate_variant:Nn \bool_until_do:Nn { c }

```

(End definition for `\bool_while_do:Nn` and `\bool_until_do:Nn`. These functions are documented on page 101.)

`\bool_do_while:Nn` A do-while loop where the body is performed at least once and the boolean is tested after executing the body. Otherwise identical to the above functions.

```

\bool_do_while:cn
\bool_do_until:Nn
\bool_do_until:cn
7593 \cs_new:Npn \bool_do_while:Nn #1#2
7594 { #2 \bool_if:NT #1 { \bool_do_while:Nn #1 {#2} } }
7595 \cs_new:Npn \bool_do_until:Nn #1#2
7596 { #2 \bool_if:NF #1 { \bool_do_until:Nn #1 {#2} } }
7597 \cs_generate_variant:Nn \bool_do_while:Nn { c }
7598 \cs_generate_variant:Nn \bool_do_until:Nn { c }

```

(End definition for `\bool_do_while:Nn` and `\bool_do_until:Nn`. These functions are documented on page 101.)

`\bool_while_do:nn` Loop functions with the test either before or after the first body expansion.

```

\bool_while_do:nn
\bool_do_while:nn
\bool_until_do:nn
\bool_do_until:nn
7599 \cs_new:Npn \bool_while_do:nn #1#2
7600 {
7601   \bool_if:nT {#1}
7602   {
7603     #2
7604     \bool_while_do:nn {#1} {#2}
7605   }
7606 }
7607 \cs_new:Npn \bool_do_while:nn #1#2
7608 {
7609   #2
7610   \bool_if:nT {#1} { \bool_do_while:nn {#1} {#2} }
7611 }
7612 \cs_new:Npn \bool_until_do:nn #1#2
7613 {
7614   \bool_if:nF {#1}
7615   {
7616     #2
7617     \bool_until_do:nn {#1} {#2}
7618   }
7619 }
7620 \cs_new:Npn \bool_do_until:nn #1#2
7621 {
7622   #2
7623   \bool_if:nF {#1} { \bool_do_until:nn {#1} {#2} }
7624 }

```

(End definition for `\bool_while_do:nn` and others. These functions are documented on page 102.)

12.6 Producing multiple copies

```

7625 <@@=prg>

```

`\prg_replicate:nn` This function uses a cascading csname technique by David Kastrup (who else :-)

```

\__prg_replicate:N
\__prg_replicate_first:N
\__prg_replicate_
\__prg_replicate_0:n
\__prg_replicate_1:n
\__prg_replicate_2:n
\__prg_replicate_3:n
\__prg_replicate_4:n
\__prg_replicate_5:n
\__prg_replicate_6:n

```

The idea is to make the input 25 result in first adding five, and then 20 copies of the code to be replicated. The technique uses cascading csnames which means that we start building several csnames so we end up with a list of functions to be called in reverse order. This is important here (and other places) because it means that we can for instance make the function that inserts five copies of something to also hand down ten to the next function in line. This is exactly what happens here: in the example with 25 then the next function is the one that inserts two copies but it sees the ten copies handed down by the previous function. In order to avoid the last function to insert say, 100 copies of the original argument just to gobble them again we define separate functions to be inserted first. These functions also close the expansion of `\exp:w`, which ensures that `\prg_replicate:nn` only requires two steps of expansion.

This function has one flaw though: Since it constantly passes down ten copies of its previous argument it severely affects the main memory once you start demanding hundreds of thousands of copies. Now I don't think this is a real limitation for any ordinary use, and if necessary, it is possible to write `\prg_replicate:nn {1000} { \prg_replicate:nn {1000} {<code>} }`. An alternative approach is to create a string of m's with `\exp:w` which can be done with just four macros but that method has its own problems since it can exhaust the string pool. Also, it is considerably slower than what we use here so the few extra csnames are well spent I would say.

```

7626 \cs_new:Npn \prg_replicate:nn #1
7627 {
7628   \exp:w
7629   \exp_after:wN \__prg_replicate_first:N
7630   \int_value:w \int_eval:n {#1}
7631   \cs_end:
7632 }
7633 \cs_new:Npn \__prg_replicate:N #1
7634 { \cs:w \__prg_replicate_#1 :n \__prg_replicate:N }
7635 \cs_new:Npn \__prg_replicate_first:N #1
7636 { \cs:w \__prg_replicate_first_#1 :n \__prg_replicate:N }

```

Then comes all the functions that do the hard work of inserting all the copies. The first function takes `:n` as a parameter.

```

7637 \cs_new:Npn \__prg_replicate_ :n #1 { \cs_end: }
7638 \cs_new:cpn { \__prg_replicate_0:n } #1
7639 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} }
7640 \cs_new:cpn { \__prg_replicate_1:n } #1
7641 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1 }
7642 \cs_new:cpn { \__prg_replicate_2:n } #1
7643 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1 }
7644 \cs_new:cpn { \__prg_replicate_3:n } #1
7645 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1 }
7646 \cs_new:cpn { \__prg_replicate_4:n } #1
7647 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1 }
7648 \cs_new:cpn { \__prg_replicate_5:n } #1
7649 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1 }
7650 \cs_new:cpn { \__prg_replicate_6:n } #1
7651 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1 }
7652 \cs_new:cpn { \__prg_replicate_7:n } #1
7653 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1 }
7654 \cs_new:cpn { \__prg_replicate_8:n } #1
7655 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1 }

```

```

7656 \cs_new:cpn { __prg_replicate_9:n } #1
7657 { \cs_end: {#1#1#1#1#1#1#1#1#1#1} #1#1#1#1#1#1#1#1#1#1 }

```

Users shouldn't ask for something to be replicated once or even not at all but...

```

7658 \cs_new:cpn { __prg_replicate_first_-:n } #1
7659 {
7660   \exp_end:
7661   \__kernel_msg_expandable_error:nn { kernel } { negative-replication }
7662 }
7663 \cs_new:cpn { __prg_replicate_first_0:n } #1 { \exp_end: }
7664 \cs_new:cpn { __prg_replicate_first_1:n } #1 { \exp_end: #1 }
7665 \cs_new:cpn { __prg_replicate_first_2:n } #1 { \exp_end: #1#1 }
7666 \cs_new:cpn { __prg_replicate_first_3:n } #1 { \exp_end: #1#1#1 }
7667 \cs_new:cpn { __prg_replicate_first_4:n } #1 { \exp_end: #1#1#1#1 }
7668 \cs_new:cpn { __prg_replicate_first_5:n } #1 { \exp_end: #1#1#1#1#1 }
7669 \cs_new:cpn { __prg_replicate_first_6:n } #1 { \exp_end: #1#1#1#1#1#1 }
7670 \cs_new:cpn { __prg_replicate_first_7:n } #1 { \exp_end: #1#1#1#1#1#1#1 }
7671 \cs_new:cpn { __prg_replicate_first_8:n } #1 { \exp_end: #1#1#1#1#1#1#1#1 }
7672 \cs_new:cpn { __prg_replicate_first_9:n } #1
7673 { \exp_end: #1#1#1#1#1#1#1#1#1#1 }

```

(End definition for \prg_replicate:nn and others. This function is documented on page 102.)

12.7 Detecting TeX's mode

\mode_if_vertical_p: For testing vertical mode. Strikes me here on the bus with David, that as long as we are just talking about returning true and false states, we can just use the primitive conditionals for this and gobbling the \exp_end: in the input stream. However this requires knowledge of the implementation so we keep things nice and clean and use the return statements.

```

7674 \prg_new_conditional:Npnn \mode_if_vertical: { p , T , F , TF }
7675 { \if_mode_vertical: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for \mode_if_vertical:TF. This function is documented on page 102.)

\mode_if_horizontal_p: For testing horizontal mode.

\mode_if_horizontal:TF

```

7676 \prg_new_conditional:Npnn \mode_if_horizontal: { p , T , F , TF }
7677 { \if_mode_horizontal: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for \mode_if_horizontal:TF. This function is documented on page 102.)

\mode_if_inner_p: For testing inner mode.

\mode_if_inner:TF

```

7678 \prg_new_conditional:Npnn \mode_if_inner: { p , T , F , TF }
7679 { \if_mode_inner: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for \mode_if_inner:TF. This function is documented on page 102.)

\mode_if_math_p: For testing math mode. At the beginning of an alignment cell, this should be used only inside a non-expandable function.

\mode_if_math:TF

```

7680 \prg_new_conditional:Npnn \mode_if_math: { p , T , F , TF }
7681 { \if_mode_math: \prg_return_true: \else: \prg_return_false: \fi: }

```

(End definition for \mode_if_math:TF. This function is documented on page 102.)

12.8 Internal programming functions

`\group_align_safe_begin:` `\group_align_safe_end:` T_EX’s alignment structures present many problems. As Knuth says himself in *T_EX: The Program*: “It’s sort of a miracle whenever `\halign` or `\valign` work, [...]” One problem relates to commands that internally issues a `\cr` but also peek ahead for the next character for use in, say, an optional argument. If the next token happens to be a `&` with category code 4 we get some sort of weird error message because the underlying `\futurelet` stores the token at the end of the alignment template. This could be a `&_4` giving a message like `! Misplaced \cr.` or even worse: it could be the `\endtemplate` token causing even more trouble! To solve this we have to open a special group so that T_EX still thinks it’s on safe ground but at the same time we don’t want to introduce any brace group that may find its way to the output. The following functions help with this by using code documented only in Appendix D of *The T_EXbook*... We place the `\if_false: { \fi:` part at that place so that the successive expansions of `\group_align_safe_begin/end:` are always brace balanced.

```
7682 \cs_new:Npn \group_align_safe_begin:
7683   { \if_int_compare:w \if_false: { \fi: ‘} = \c_zero_int \fi: }
7684 \cs_new:Npn \group_align_safe_end:
7685   { \if_int_compare:w ‘{ = \c_zero_int } \fi: }
```

(End definition for `\group_align_safe_begin:` and `\group_align_safe_end:`. These functions are documented on page 104.)

```
7686 <@@=prg>
```

`\g__kernel_prg_map_int` A nesting counter for mapping.

```
7687 \int_new:N \g__kernel_prg_map_int
```

(End definition for `\g__kernel_prg_map_int:`.)

`\prg_break_point:Nn` `\prg_map_break:Nn` These are defined in `l3basics`, as they are needed “early”. This is just a reminder that is the case!

(End definition for `\prg_break_point:Nn` and `\prg_map_break:Nn`. These functions are documented on page 103.)

`\prg_break_point:` Also done in `l3basics` as in format mode these are needed within `l3alloc`.

`\prg_break:` `\prg_break:n` (End definition for `\prg_break_point:`, `\prg_break:`, and `\prg_break:n`. These functions are documented on page 103.)

12.9 Deprecated functions

`__prg_break_point:Nn` `__prg_break_point:` `__prg_map_break:Nn` `__prg_break:` `__prg_break:n` Made public, but used by a few third-parties. It’s not possible to perfectly support a mixture of `__prg_map_break:Nn` and `\prg_map_break:Nn` because they use different delimiters. The following code only breaks if someone tries to break from two “old-style” mappings in one go. Basically, the `__prg_map_break:Nn` converts a single `__prg_break_point:Nn` to `\prg_break_point:Nn`, and that delimiter had better be the right one. Then we call `\prg_map_break:Nn` which may end up breaking intermediate looks in the (unbraced) argument #1. It is essential to define the `break_point` functions before the corresponding `break` functions: otherwise `\debug_on:n {deprecation} \debug_off:n {deprecation}` would break when trying to restore the definitions because they would involve deprecated commands whose definition has not yet been restored.

```

7688 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \prg_break_point:Nn }
7689 \cs_new:Npn \__prg_break_point:Nn { \prg_break_point:Nn }
7690 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \prg_break_point: }
7691 \cs_new:Npn \__prg_break_point: { \prg_break_point: }
7692 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \prg_map_break:Nn }
7693 \cs_new:Npn \__prg_map_break:Nn #1 \__prg_break_point:Nn
7694 { \prg_map_break:Nn #1 \prg_break_point:Nn }
7695 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \prg_break: }
7696 \cs_new:Npn \__prg_break: #1 \__prg_break_point: { }
7697 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \prg_break:n }
7698 \cs_new:Npn \__prg_break:n #1#2 \__prg_break_point: {#1}

(End definition for \__prg_break_point:Nn and others.)

7699 </initex | package>

```

13 l3sys implementation

```

7700 <*initex | package>
7701 <@@=sys>

```

13.1 The name of the job

\c_sys_jobname_str Inherited from the L^AT_EX3 name for the primitive: this needs to actually contain the text of the job name rather than the name of the primitive, of course.

```

7702 <*initex>
7703 \tex_everyjob:D \exp_after:wN
7704 {
7705   \tex_the:D \tex_everyjob:D
7706   \str_const:Nx \c_sys_jobname_str { \tex_jobname:D }
7707 }
7708 </initex>
7709 <*package>
7710 \str_const:Nx \c_sys_jobname_str { \tex_jobname:D }
7711 </package>

```

(End definition for \c_sys_jobname_str. This variable is documented on page 105.)

13.2 Time and date

\c_sys_minute_int Copies of the information provided by T_EX
\c_sys_hour_int
\c_sys_day_int
\c_sys_month_int
\c_sys_year_int

```

7712 \int_const:Nn \c_sys_minute_int
7713 { \int_mod:nn { \tex_time:D } { 60 } }
7714 \int_const:Nn \c_sys_hour_int
7715 { \int_div_truncate:nn { \tex_time:D } { 60 } }
7716 \int_const:Nn \c_sys_day_int { \tex_day:D }
7717 \int_const:Nn \c_sys_month_int { \tex_month:D }
7718 \int_const:Nn \c_sys_year_int { \tex_year:D }

```

(End definition for \c_sys_minute_int and others. These variables are documented on page 105.)

13.3 Detecting the engine

`__sys_const:nn` Set the T, F, TF, p forms of #1 to be constants equal to the result of evaluating the boolean expression #2.

```

7719 \cs_new_protected:Npn \__sys_const:nn #1#2
7720 {
7721   \bool_if:nTF {#2}
7722   {
7723     \cs_new_eq:cN { #1 :T } \use:n
7724     \cs_new_eq:cN { #1 :F } \use_none:n
7725     \cs_new_eq:cN { #1 :TF } \use_i:nn
7726     \cs_new_eq:cN { #1 _p: } \c_true_bool
7727   }
7728   {
7729     \cs_new_eq:cN { #1 :T } \use_none:n
7730     \cs_new_eq:cN { #1 :F } \use:n
7731     \cs_new_eq:cN { #1 :TF } \use_ii:nn
7732     \cs_new_eq:cN { #1 _p: } \c_false_bool
7733   }
7734 }

```

(End definition for `__sys_const:nn`.)

`\sys_if_engine luatex_p:` Set up the engine tests on the basis exactly one test should be true. Mainly a case of looking for the appropriate marker primitive. For `upTeX`, there is a complexity in that setting `-kanji-internal=sjis` or `-kanji-internal=euc` effective makes it more like `pTeX`. In those cases we therefore report `pTeX` rather than `upTeX`.

```

\sys_if_engine luatex:TF
\sys_if_engine pdftex_p:
\sys_if_engine pdftex:TF
  \sys_if_engine ptex_p:
  \sys_if_engine ptex:TF
\sys_if_engine uptex_p:
\sys_if_engine uptex:TF
\sys_if_engine xetex_p:
\sys_if_engine xetex:TF
  \c_sys_engine_str
7735 \str_const:Nx \c_sys_engine_str
7736 {
7737   \cs_if_exist:NT \tex luatexversion:D { luatex }
7738   \cs_if_exist:NT \tex pdftexversion:D { pdftex }
7739   \cs_if_exist:NT \tex kanjiskip:D
7740   {
7741     \bool_lazy_and:nnTF
7742     { \cs_if_exist_p:N \tex disablecjktoken:D }
7743     { \int_compare_p:nNn { \tex jis:D "2121 } = { "3000 } }
7744     { uptex }
7745     { ptex }
7746   }
7747   \cs_if_exist:NT \tex XeTeXversion:D { xetex }
7748 }
7749 \tl_map_inline:nn { { luatex } { pdftex } { ptex } { uptex } { xetex } }
7750 {
7751   \__sys_const:nn { sys_if_engine_ #1 }
7752   { \str_if_eq_p:Vn \c_sys_engine_str {#1} }
7753 }

```

(End definition for `\sys_if_engine luatex:TF` and others. These functions are documented on page 105.)

13.4 Detecting the output

`\sys_if_output dvi_p:` This is a simple enough concept: the two views here are complementary.

```

\sys_if_output dvi:TF
\sys_if_output pdf_p:
\sys_if_output pdf:TF
  \c_sys_output_str
7754 \str_const:Nx \c_sys_output_str

```

```

7755 {
7756   \int_compare:nNnTF
7757     { \cs_if_exist_use:NF \tex_pdfoutput:D { 0 } } > { 0 }
7758     { pdf }
7759     { dvi }
7760 }
7761 \__sys_const:nn { sys_if_output_dvi }
7762 { \str_if_eq_p:Vn \c_sys_output_str { dvi } }
7763 \__sys_const:nn { sys_if_output_pdf }
7764 { \str_if_eq_p:Vn \c_sys_output_str { pdf } }

```

(End definition for `\sys_if_output_dvi:TF`, `\sys_if_output_pdf:TF`, and `\c_sys_output_str`. These functions are documented on page 106.)

13.5 Randomness

This candidate function is placed there because `\sys_if_rand_exist:TF` is used in `l3fp-rand`.

`\sys_if_rand_exist_p:` Currently, randomness exists under pdfTeX, LuaTeX, pTeX and upTeX.

`\sys_if_rand_exist:TF`

```

7765 \__sys_const:nn { sys_if_rand_exist }
7766 { \cs_if_exist_p:N \tex_uniformdeviate:D }

```

(End definition for `\sys_if_rand_exist:TF`. This function is documented on page 250.)

```

7767 </initex | package>

```

14 l3clist implementation

The following test files are used for this code: `m3clist002`.

```

7768 <*initex | package>
7769 <@@=clist>

```

`\c_empty_clist` An empty comma list is simply an empty token list.

```

7770 \cs_new_eq:NN \c_empty_clist \c_empty_tl

```

(End definition for `\c_empty_clist`. This variable is documented on page 116.)

`\l__clist_internal_clist` Scratch space for various internal uses. This comma list variable cannot be declared as such because it comes before `\clist_new:N`

```

7771 \tl_new:N \l__clist_internal_clist

```

(End definition for `\l__clist_internal_clist`.)

`__clist_tmp:w` A temporary function for various purposes.

```

7772 \cs_new_protected:Npn \__clist_tmp:w { }

```

(End definition for `__clist_tmp:w`.)

14.1 Removing spaces around items

`__clist_trim_next:w` Called as `\exp:w __clist_trim_next:w \prg_do_nothing: <comma list> ...` it expands to `{<trimmed item>}` where the `<trimmed item>` is the first non-empty result from removing spaces from both ends of comma-delimited items in the `<comma list>`. The `\prg_do_nothing:` marker avoids losing braces. The test for blank items is a somewhat optimized `\tl_if_empty:oTF` construction; if blank, another item is sought, otherwise trim spaces.

```

7773 \cs_new:Npn \__clist_trim_next:w #1 ,
7774 {
7775     \tl_if_empty:oTF { \use_none:nn #1 ? }
7776     { \__clist_trim_next:w \prg_do_nothing: }
7777     { \tl_trim_spaces_apply:oN {#1} \exp_end: }
7778 }
```

(End definition for `__clist_trim_next:w`.)

`__clist_sanitize:n` The auxiliary `__clist_sanitize:Nn` receives a delimiter (`\c_empty_tl` the first time, afterwards a comma) and that item as arguments. Unless we are done with the loop it calls `__clist_wrap_item:w` to unbrace the item (using a comma delimiter is safe since `#2` came from removing spaces from an argument delimited by a comma) and possibly re-brace it if needed.

```

7779 \cs_new:Npn \__clist_sanitize:n #1
7780 {
7781     \exp_after:wN \__clist_sanitize:Nn \exp_after:wN \c_empty_tl
7782     \exp:w \__clist_trim_next:w \prg_do_nothing:
7783     #1 , \q_recursion_tail , \q_recursion_stop
7784 }
7785 \cs_new:Npn \__clist_sanitize:Nn #1#2
7786 {
7787     \quark_if_recursion_tail_stop:n {#2}
7788     #1 \__clist_wrap_item:w #2 ,
7789     \exp_after:wN \__clist_sanitize:Nn \exp_after:wN ,
7790     \exp:w \__clist_trim_next:w \prg_do_nothing:
7791 }
```

(End definition for `__clist_sanitize:n` and `__clist_sanitize:Nn`.)

`__clist_if_wrap:nTF` True if the argument must be wrapped to avoid getting altered by some clist operations.
`__clist_if_wrap:w` That is the case whenever the argument

- starts or end with a space or contains a comma,
- is empty, or
- consists of a single braced group.

All `l3clist` functions go through the same test when they need to determine whether to brace an item, so it is not a problem that this test has false positives such as “`\q_mark ?`”. If the argument starts or end with a space or contains a comma then one of the three arguments of `__clist_if_wrap:w` will have its end delimiter (partly) in one of the three copies of `#1` in `__clist_if_wrap:nTF`; this has a knock-on effect meaning that the result of the expansion is not empty; in that case, wrap. Otherwise, the argument

is safe unless it starts with a brace group (or is empty) and it is empty or consists of a single n-type argument.

```

7792 \prg_new_conditional:Npnn \__clist_if_wrap:n #1 { TF }
7793 {
7794   \tl_if_empty:oTF
7795   {
7796     \__clist_if_wrap:w
7797     \q_mark ? #1 ~ \q_mark ? ~ #1 \q_mark , ~ \q_mark #1 ,
7798   }
7799   {
7800     \tl_if_head_is_group:nTF { #1 { } }
7801     {
7802       \tl_if_empty:nTF {#1}
7803       { \prg_return_true: }
7804       {
7805         \tl_if_empty:oTF { \use_none:n #1}
7806         { \prg_return_true: }
7807         { \prg_return_false: }
7808       }
7809     }
7810     { \prg_return_false: }
7811   }
7812   { \prg_return_true: }
7813 }
7814 \cs_new:Npn \__clist_if_wrap:w #1 \q_mark ? ~ #2 ~ \q_mark #3 , { }

```

(End definition for __clist_if_wrap:nTF and __clist_if_wrap:w.)

__clist_wrap_item:w Safe items are put in \exp_not:n, otherwise we put an extra set of braces.

```

7815 \cs_new:Npn \__clist_wrap_item:w #1 ,
7816 { \__clist_if_wrap:nTF {#1} { \exp_not:n { {#1} } } { \exp_not:n {#1} } }

```

(End definition for __clist_wrap_item:w.)

14.2 Allocation and initialisation

\clist_new:N Internally, comma lists are just token lists.

```

\clist_new:c 7817 \cs_new_eq:NN \clist_new:N \tl_new:N
7818 \cs_new_eq:NN \clist_new:c \tl_new:c

```

(End definition for \clist_new:N. This function is documented on page 107.)

\clist_const:Nn Creating and initializing a constant comma list is done by sanitizing all items (stripping spaces and braces).

```

\clist_const:cn 7819 \cs_new_protected:Npn \clist_const:Nn #1#2
\clist_const:Nx 7820 { \tl_const:Nx #1 { \__clist_sanitize:n {#2} } }
\clist_const:cx 7821 \cs_generate_variant:Nn \clist_const:Nn { c , Nx , cx }

```

(End definition for \clist_const:Nn. This function is documented on page 108.)

\clist_clear:N Clearing comma lists is just the same as clearing token lists.

```

\clist_clear:c 7822 \cs_new_eq:NN \clist_clear:N \tl_clear:N
\clist_gclear:N 7823 \cs_new_eq:NN \clist_clear:c \tl_clear:c
\clist_gclear:c 7824 \cs_new_eq:NN \clist_gclear:N \tl_gclear:N
7825 \cs_new_eq:NN \clist_gclear:c \tl_gclear:c

```

(End definition for `\clist_clear:N` and `\clist_gclear:N`. These functions are documented on page 108.)

```

\clist_clear_new:N Once again a copy from the token list functions.
\clist_clear_new:c 7826 \cs_new_eq:NN \clist_clear_new:N \tl_clear_new:N
\clist_gclear_new:N 7827 \cs_new_eq:NN \clist_clear_new:c \tl_clear_new:c
\clist_gclear_new:c 7828 \cs_new_eq:NN \clist_gclear_new:N \tl_gclear_new:N
7829 \cs_new_eq:NN \clist_gclear_new:c \tl_gclear_new:c

```

(End definition for `\clist_clear_new:N` and `\clist_gclear_new:N`. These functions are documented on page 108.)

```

\clist_set_eq:NN Once again, these are simple copies from the token list functions.
\clist_set_eq:cN 7830 \cs_new_eq:NN \clist_set_eq:NN \tl_set_eq:NN
\clist_set_eq:Nc 7831 \cs_new_eq:NN \clist_set_eq:Nc \tl_set_eq:Nc
\clist_set_eq:cc 7832 \cs_new_eq:NN \clist_set_eq:cN \tl_set_eq:cN
\clist_gset_eq:NN 7833 \cs_new_eq:NN \clist_set_eq:cc \tl_set_eq:cc
\clist_gset_eq:cN 7834 \cs_new_eq:NN \clist_gset_eq:NN \tl_gset_eq:NN
\clist_gset_eq:Nc 7835 \cs_new_eq:NN \clist_gset_eq:Nc \tl_gset_eq:Nc
\clist_gset_eq:cN 7836 \cs_new_eq:NN \clist_gset_eq:cN \tl_gset_eq:cN
\clist_gset_eq:cc 7837 \cs_new_eq:NN \clist_gset_eq:cc \tl_gset_eq:cc

```

(End definition for `\clist_set_eq:NN` and `\clist_gset_eq:NN`. These functions are documented on page 108.)

```

\clist_set_from_seq:NN Setting a comma list from a comma-separated list is done using a simple mapping. Safe
\clist_set_from_seq:cN items are put in \exp_not:n, otherwise we put an extra set of braces. The first comma
\clist_set_from_seq:Nc must be removed, except in the case of an empty comma-list.
\clist_set_from_seq:cc 7838 \cs_new_protected:Npn \clist_set_from_seq:NN
\clist_gset_from_seq:NN 7839 { \__clist_set_from_seq:NNNN \clist_clear:N \tl_set:Nx }
\clist_gset_from_seq:cN 7840 \cs_new_protected:Npn \clist_gset_from_seq:NN
\clist_gset_from_seq:Nc 7841 { \__clist_set_from_seq:NNNN \clist_gclear:N \tl_gset:Nx }
\clist_gset_from_seq:cc 7842 \cs_new_protected:Npn \__clist_set_from_seq:NNNN #1#2#3#4
\__clist_set_from_seq:NNNN 7843 {
\__clist_set_from_seq:n 7844   \seq_if_empty:NTF #4
7845     { #1 #3 }
7846     {
7847       #2 #3
7848       {
7849         \exp_after:wN \use_none:n \exp:w \exp_end_continue_f:w
7850         \seq_map_function:NN #4 \__clist_set_from_seq:n
7851       }
7852     }
7853   }
7854 \cs_new:Npn \__clist_set_from_seq:n #1
7855 {
7856   ,
7857   \__clist_if_wrap:NTF {#1}
7858     { \exp_not:n { {#1} } }
7859     { \exp_not:n {#1} }
7860 }
7861 \cs_generate_variant:Nn \clist_set_from_seq:NN { Nc }
7862 \cs_generate_variant:Nn \clist_set_from_seq:NN { c , cc }
7863 \cs_generate_variant:Nn \clist_gset_from_seq:NN { Nc }
7864 \cs_generate_variant:Nn \clist_gset_from_seq:NN { c , cc }

```

(End definition for `\clist_set_from_seq:NN` and others. These functions are documented on page 108.)

```

\clist_concat:NNN Concatenating comma lists is not quite as easy as it seems, as there needs to be the
\clist_concat:ccc correct addition of a comma to the output. So a little work to do.
\clist_gconcat:NNN
\clist_gconcat:ccc
\__clist_concat:NNNN
7865 \cs_new_protected:Npn \clist_concat:NNN
7866 { \__clist_concat:NNNN \tl_set:Nx }
7867 \cs_new_protected:Npn \clist_gconcat:NNN
7868 { \__clist_concat:NNNN \tl_gset:Nx }
7869 \cs_new_protected:Npn \__clist_concat:NNNN #1#2#3#4
7870 {
7871   #1 #2
7872   {
7873     \exp_not:o #3
7874     \clist_if_empty:NF #3 { \clist_if_empty:NF #4 { , } }
7875     \exp_not:o #4
7876   }
7877 }
7878 \cs_generate_variant:Nn \clist_concat:NNN { ccc }
7879 \cs_generate_variant:Nn \clist_gconcat:NNN { ccc }

```

(End definition for `\clist_concat:NNN`, `\clist_gconcat:NNN`, and `__clist_concat:NNNN`. These functions are documented on page 108.)

```

\clist_if_exist_p:N Copies of the cs functions defined in l3basics.
\clist_if_exist_p:c
\clist_if_exist:NTF
\clist_if_exist:cTF
7880 \prg_new_eq_conditional:NNn \clist_if_exist:N \cs_if_exist:N
7881 { TF , T , F , p }
7882 \prg_new_eq_conditional:NNn \clist_if_exist:c \cs_if_exist:c
7883 { TF , T , F , p }

```

(End definition for `\clist_if_exist:NTF`. This function is documented on page 108.)

14.3 Adding data to comma lists

```

\clist_set:Nn
\clist_set:NV
\clist_set:No
\clist_set:Nx
\clist_set:cn
\clist_set:cV
\clist_set:co
\clist_set:cx
\clist_gset:Nn
7884 \cs_new_protected:Npn \clist_set:Nn #1#2
7885 { \tl_set:Nx #1 { \__clist_sanitiz:n {#2} } }
\clist_set:Nx
7886 \cs_new_protected:Npn \clist_gset:Nn #1#2
7887 { \tl_gset:Nx #1 { \__clist_sanitiz:n {#2} } }
\clist_set:cn
7888 \cs_generate_variant:Nn \clist_set:Nn { NV , No , Nx , c , cV , co , cx }
\clist_set:cV
7889 \cs_generate_variant:Nn \clist_gset:Nn { NV , No , Nx , c , cV , co , cx }
\clist_set:co
\clist_set:cx

```

(End definition for `\clist_set:Nn` and `\clist_gset:Nn`. These functions are documented on page 109.)

```

\clist_gset:Nn Everything is based on concatenation after storing in \l__clist_internal_clist. This
\clist_put_left:NV avoids having to worry here about space-trimming and so on.
\clist_put_left:Nx
\clist_put_left:Nn
\clist_put_left:cn
\clist_put_left:cV
\clist_put_left:co
\clist_put_left:cx
\clist_gput_left:Nn
\clist_gput_left:NV
\clist_gput_left:No
\clist_gput_left:Nx
\clist_gput_left:cn
\clist_gput_left:cV
\clist_gput_left:co
\clist_gput_left:cx
\__clist_put_left:NNNn
7890 \cs_new_protected:Npn \clist_put_left:Nn
7891 { \__clist_put_left:NNNn \clist_concat:NNN \clist_set:Nn }
7892 \cs_new_protected:Npn \clist_gput_left:Nn
7893 { \__clist_put_left:NNNn \clist_gconcat:NNN \clist_set:Nn }
7894 \cs_new_protected:Npn \__clist_put_left:NNNn #1#2#3#4
7895 {
7896   #2 \l__clist_internal_clist {#4}
7897   #1 #3 \l__clist_internal_clist #3
7898 }

```

```

7899 \cs_generate_variant:Nn \clist_put_left:Nn { NV , No , Nx }
7900 \cs_generate_variant:Nn \clist_put_left:Nn { c , cV , co , cx }
7901 \cs_generate_variant:Nn \clist_gput_left:Nn { NV , No , Nx }
7902 \cs_generate_variant:Nn \clist_gput_left:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_left:Nn`, `\clist_gput_left:Nn`, and `__clist_put_left:NNNn`. These functions are documented on page 109.)

```

\clist_put_right:Nn
\clist_put_right:NV
\clist_put_right:No
\clist_put_right:Nx
\clist_put_right:cn
\clist_put_right:cV
\clist_put_right:co
\clist_put_right:cx
\clist_gput_right:Nn
\clist_gput_right:NV
\clist_gput_right:No
\clist_gput_right:Nx
\clist_gput_right:cn
\clist_gput_right:cV
\clist_gput_right:co
\clist_gput_right:cx
\__clist_put_right:NNNn

```

```

7903 \cs_new_protected:Npn \clist_put_right:Nn
7904 { \__clist_put_right:NNNn \clist_concat:NNN \clist_set:Nn }
7905 \cs_new_protected:Npn \clist_gput_right:Nn
7906 { \__clist_put_right:NNNn \clist_gconcat:NNN \clist_set:Nn }
7907 \cs_new_protected:Npn \__clist_put_right:NNNn #1#2#3#4
7908 {
7909   #2 \l__clist_internal_clist {#4}
7910   #1 #3 #3 \l__clist_internal_clist
7911 }
7912 \cs_generate_variant:Nn \clist_put_right:Nn { NV , No , Nx }
7913 \cs_generate_variant:Nn \clist_put_right:Nn { c , cV , co , cx }
7914 \cs_generate_variant:Nn \clist_gput_right:Nn { NV , No , Nx }
7915 \cs_generate_variant:Nn \clist_gput_right:Nn { c , cV , co , cx }

```

(End definition for `\clist_put_right:Nn`, `\clist_gput_right:Nn`, and `__clist_put_right:NNNn`. These functions are documented on page 109.)

14.4 Comma lists as stacks

`\clist_get:NN` Getting an item from the left of a comma list is pretty easy: just trim off the first item using the comma. No need to trim spaces as comma-list *variables* are assumed to have “cleaned-up” items. (Note that grabbing a comma-delimited item removes an outer pair of braces if present, exactly as needed to uncover the underlying item.)

```

7916 \cs_new_protected:Npn \clist_get:NN #1#2
7917 {
7918   \if_meaning:w #1 \c_empty_clist
7919     \tl_set:Nn #2 { \q_no_value }
7920   \else:
7921     \exp_after:wN \__clist_get:wN #1 , \q_stop #2
7922   \fi:
7923 }
7924 \cs_new_protected:Npn \__clist_get:wN #1 , #2 \q_stop #3
7925 { \tl_set:Nn #3 {#1} }
7926 \cs_generate_variant:Nn \clist_get:NN { c }

```

(End definition for `\clist_get:NN` and `__clist_get:wN`. This function is documented on page 114.)

`\clist_pop:NN` An empty clist leads to `\q_no_value`, otherwise grab until the first comma and assign to the variable. The second argument of `__clist_pop:wwNNN` is a comma list ending in a comma and `\q_mark`, unless the original clist contained exactly one item: then the argument is just `\q_mark`. The next auxiliary picks either `\exp_not:n` or `\use_none:n` as #2, ensuring that the result can safely be an empty comma list.

```

\clist_pop:cn
\clist_gpop:NN
\__clist_pop:NNN
\__clist_pop:wwNNN
\__clist_pop:wN

```

```

7927 \cs_new_protected:Npn \clist_pop:NN
7928 { \__clist_pop:NNN \tl_set:Nx }
7929 \cs_new_protected:Npn \clist_gpop:NN

```

```

7930 { \_clst_pop:NNN \tl_gset:Nx }
7931 \cs_new_protected:Npn \_clst_pop:NNN #1#2#3
7932 {
7933   \if_meaning:w #2 \c_empty_clst
7934     \tl_set:Nn #3 { \q_no_value }
7935   \else:
7936     \exp_after:wN \_clst_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
7937   \fi:
7938 }
7939 \cs_new_protected:Npn \_clst_pop:wwNNN #1 , #2 \q_stop #3#4#5
7940 {
7941   \tl_set:Nn #5 {#1}
7942   #3 #4
7943   {
7944     \_clst_pop:wN \prg_do_nothing:
7945     #2 \exp_not:o
7946     , \q_mark \use_none:n
7947     \q_stop
7948   }
7949 }
7950 \cs_new:Npn \_clst_pop:wN #1 , \q_mark #2 #3 \q_stop { #2 {#1} }
7951 \cs_generate_variant:Nn \clst_pop:NN { c }
7952 \cs_generate_variant:Nn \clst_gpop:NN { c }

```

(End definition for \clst_pop:NN and others. These functions are documented on page 114.)

```

\clst_get:NNTF The same, as branching code: very similar to the above.
\clst_get:cNTF 7953 \prg_new_protected_conditional:Npnn \clst_get:NN #1#2 { T , F , TF }
\clst_pop:NNTF 7954 {
\clst_pop:cNTF 7955   \if_meaning:w #1 \c_empty_clst
\clst_gpop:NNTF 7956   \prg_return_false:
\clst_gpop:cNTF 7957   \else:
\clst_gpop:cNTF 7958   \exp_after:wN \_clst_get:wN #1 , \q_stop #2
\clst_gpop:cNTF 7959   \prg_return_true:
\clst_gpop:cNTF 7960   \fi:
\clst_gpop:cNTF 7961 }
\clst_gpop:cNTF 7962 \prg_generate_conditional_variant:Nnn \clst_get:NN { c } { T , F , TF }
\clst_gpop:cNTF 7963 \prg_new_protected_conditional:Npnn \clst_pop:NN #1#2 { T , F , TF }
\clst_gpop:cNTF 7964 { \_clst_pop_TF:NNN \tl_set:Nx #1 #2 }
\clst_gpop:cNTF 7965 \prg_new_protected_conditional:Npnn \clst_gpop:NN #1#2 { T , F , TF }
\clst_gpop:cNTF 7966 { \_clst_pop_TF:NNN \tl_gset:Nx #1 #2 }
\clst_gpop:cNTF 7967 \cs_new_protected:Npn \_clst_pop_TF:NNN #1#2#3
\clst_gpop:cNTF 7968 {
\clst_gpop:cNTF 7969   \if_meaning:w #2 \c_empty_clst
\clst_gpop:cNTF 7970   \prg_return_false:
\clst_gpop:cNTF 7971   \else:
\clst_gpop:cNTF 7972     \exp_after:wN \_clst_pop:wwNNN #2 , \q_mark \q_stop #1#2#3
\clst_gpop:cNTF 7973     \prg_return_true:
\clst_gpop:cNTF 7974   \fi:
\clst_gpop:cNTF 7975 }
\clst_gpop:cNTF 7976 \prg_generate_conditional_variant:Nnn \clst_pop:NN { c } { T , F , TF }
\clst_gpop:cNTF 7977 \prg_generate_conditional_variant:Nnn \clst_gpop:NN { c } { T , F , TF }

```

(End definition for \clst_get:NNTF and others. These functions are documented on page 114.)

\clist_push:Nn	Pushing to a comma list is the same as adding on the left.
\clist_push:NV	7978 \cs_new_eq:NN \clist_push:Nn \clist_put_left:Nn
\clist_push:No	7979 \cs_new_eq:NN \clist_push:NV \clist_put_left:NV
\clist_push:Nx	7980 \cs_new_eq:NN \clist_push:No \clist_put_left:No
\clist_push:cn	7981 \cs_new_eq:NN \clist_push:Nx \clist_put_left:Nx
\clist_push:cV	7982 \cs_new_eq:NN \clist_push:cn \clist_put_left:cn
\clist_push:co	7983 \cs_new_eq:NN \clist_push:cV \clist_put_left:cV
\clist_push:cx	7984 \cs_new_eq:NN \clist_push:co \clist_put_left:co
\clist_gpush:Nn	7985 \cs_new_eq:NN \clist_gpush:cx \clist_put_left:cx
\clist_gpush:NV	7986 \cs_new_eq:NN \clist_gpush:Nn \clist_gput_left:Nn
\clist_gpush:No	7987 \cs_new_eq:NN \clist_gpush:NV \clist_gput_left:NV
\clist_gpush:Nx	7988 \cs_new_eq:NN \clist_gpush:No \clist_gput_left:No
\clist_gpush:cn	7989 \cs_new_eq:NN \clist_gpush:Nx \clist_gput_left:Nx
\clist_gpush:cV	7990 \cs_new_eq:NN \clist_gpush:cn \clist_gput_left:cn
\clist_gpush:co	7991 \cs_new_eq:NN \clist_gpush:cV \clist_gput_left:cV
\clist_gpush:cx	7992 \cs_new_eq:NN \clist_gpush:co \clist_gput_left:co
	7993 \cs_new_eq:NN \clist_gpush:cx \clist_gput_left:cx

(End definition for \clist_push:Nn and \clist_gpush:Nn. These functions are documented on page 114.)

14.5 Modifying comma lists

\l__clist_internal_remove_clist	An internal comma list and a sequence for the removal routines.
\l__clist_internal_remove_seq	7994 \clist_new:N \l__clist_internal_remove_clist
	7995 \seq_new:N \l__clist_internal_remove_seq

(End definition for \l__clist_internal_remove_clist and \l__clist_internal_remove_seq.)

\clist_remove_duplicates:N	Removing duplicates means making a new list then copying it.
\clist_remove_duplicates:c	7996 \cs_new_protected:Npn \clist_remove_duplicates:N
\clist_gremove_duplicates:N	7997 { __clist_remove_duplicates:NN \clist_set_eq:NN }
\clist_gremove_duplicates:c	7998 \cs_new_protected:Npn \clist_gremove_duplicates:N
__clist_remove_duplicates:NN	7999 { __clist_remove_duplicates:NN \clist_gset_eq:NN }
	8000 \cs_new_protected:Npn __clist_remove_duplicates:NN #1#2
	8001 {
	8002 \clist_clear:N \l__clist_internal_remove_clist
	8003 \clist_map_inline:Nn #2
	8004 {
	8005 \clist_if_in:NnF \l__clist_internal_remove_clist {##1}
	8006 { \clist_put_right:Nn \l__clist_internal_remove_clist {##1} }
	8007 }
	8008 #1 #2 \l__clist_internal_remove_clist
	8009 }
	8010 \cs_generate_variant:Nn \clist_remove_duplicates:N { c }
	8011 \cs_generate_variant:Nn \clist_gremove_duplicates:N { c }

(End definition for \clist_remove_duplicates:N, \clist_gremove_duplicates:N, and __clist_remove_duplicates:NN. These functions are documented on page 110.)

\clist_remove_all:Nn	The method used here for safe items is very similar to \tl_replace_all:Nnn. However,
\clist_remove_all:cn	if the item contains commas or leading/trailing spaces, or is empty, or consists of a
\clist_gremove_all:Nn	single brace group, we know that it can only appear within braces so the code would
\clist_gremove_all:cn	fail; instead just convert to a sequence and do the removal with l3seq code (it involves
__clist_remove_all:NNNn	
__clist_remove_all:w	
__clist_remove_all:	

somewhat elaborate code to do most of the work expandably but the final token list comparisons non-expandably).

For “safe” items, build a function delimited by the $\langle item \rangle$ that should be removed, surrounded with commas, and call that function followed by the expanded comma list, and another copy of the $\langle item \rangle$. The loop is controlled by the argument grabbed by `__clist_remove_all:w`: when the item was found, the `\q_mark` delimiter used is the one inserted by `__clist_tmp:w`, and `\use_none_delimit_by_q_stop:w` is deleted. At the end, the final $\langle item \rangle$ is grabbed, and the argument of `__clist_tmp:w` contains `\q_mark`: in that case, `__clist_remove_all:w` removes the second `\q_mark` (inserted by `__clist_tmp:w`), and lets `\use_none_delimit_by_q_stop:w` act.

No brace is lost because items are always grabbed with a leading comma. The result of the first assignment has an extra leading comma, which we remove in a second assignment. Two exceptions: if the clist lost all of its elements, the result is empty, and we shouldn’t remove anything; if the clist started up empty, the first step happens to turn it into a single comma, and the second step removes it.

```

8012 \cs_new_protected:Npn \clist_remove_all:Nn
8013 { \__clist_remove_all:NNNn \clist_set_from_seq:NN \tl_set:Nx }
8014 \cs_new_protected:Npn \clist_gremove_all:Nn
8015 { \__clist_remove_all:NNNn \clist_gset_from_seq:NN \tl_gset:Nx }
8016 \cs_new_protected:Npn \__clist_remove_all:NNNn #1#2#3#4
8017 {
8018   \__clist_if_wrap:nTF {#4}
8019   {
8020     \seq_set_from_clist:NN \l__clist_internal_remove_seq #3
8021     \seq_remove_all:Nn \l__clist_internal_remove_seq {#4}
8022     #1 #3 \l__clist_internal_remove_seq
8023   }
8024   {
8025     \cs_set:Npn \__clist_tmp:w ##1 , #4 ,
8026     {
8027       ##1
8028       , \q_mark , \use_none_delimit_by_q_stop:w ,
8029       \__clist_remove_all:
8030     }
8031     #2 #3
8032     {
8033       \exp_after:wN \__clist_remove_all:
8034       #3 , \q_mark , #4 , \q_stop
8035     }
8036     \clist_if_empty:NF #3
8037     {
8038       #2 #3
8039       {
8040         \exp_args:No \exp_not:o
8041         { \exp_after:wN \use_none:n #3 }
8042       }
8043     }
8044   }
8045 }
8046 \cs_new:Npn \__clist_remove_all:
8047 { \exp_after:wN \__clist_remove_all:w \__clist_tmp:w , }
8048 \cs_new:Npn \__clist_remove_all:w #1 , \q_mark , #2 , { \exp_not:n {#1} }

```

```

8049 \cs_generate_variant:Nn \clist_remove_all:Nn { c }
8050 \cs_generate_variant:Nn \clist_gremove_all:Nn { c }

```

(End definition for `\clist_remove_all:Nn` and others. These functions are documented on page 110.)

`\clist_reverse:N` Use `\clist_reverse:n` in an x-expanding assignment. The extra work that `\clist_reverse:n` does to preserve braces and spaces would not be needed for the well-controlled case of N-type comma lists, but the slow-down is not too bad.

```

\clist_reverse:c
\clist_greverse:N
\clist_greverse:c
8051 \cs_new_protected:Npn \clist_reverse:N #1
8052 { \tl_set:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
8053 \cs_new_protected:Npn \clist_greverse:N #1
8054 { \tl_gset:Nx #1 { \exp_args:No \clist_reverse:n {#1} } }
8055 \cs_generate_variant:Nn \clist_reverse:N { c }
8056 \cs_generate_variant:Nn \clist_greverse:N { c }

```

(End definition for `\clist_reverse:N` and `\clist_greverse:N`. These functions are documented on page 110.)

`\clist_reverse:n` The reversed token list is built one item at a time, and stored between `\q_stop` and `\q_mark`, in the form of ? followed by zero or more instances of “ $\langle item \rangle$,”. We start from a comma list “ $\langle item_1 \rangle, \dots, \langle item_n \rangle$ ”. During the loop, the auxiliary `__clist_reverse:wwNww` receives “ $\langle item_i \rangle$ ” as #1, “ $\langle item_{i+1} \rangle, \dots, \langle item_n \rangle$ ” as #2, `__clist_reverse:wwNww` as #3, what remains until `\q_stop` as #4, and “ $\langle item_{i-1} \rangle, \dots, \langle item_1 \rangle$,” as #5. The auxiliary moves #1 just before #5, with a comma, and calls itself (#3). After the last item is moved, `__clist_reverse:wwNww` receives “`\q_mark __clist_reverse:wwNww !`” as its argument #1, thus `__clist_reverse_end:ww` as its argument #3. This second auxiliary cleans up until the marker !, removes the trailing comma (introduced when the first item was moved after `\q_stop`), and leaves its argument #1 within `\exp_not:n`. There is also a need to remove a leading comma, hence `\exp_not:o` and `\use_none:n`.

```

8057 \cs_new:Npn \clist_reverse:n #1
8058 {
8059   \__clist_reverse:wwNww ? #1 ,
8060   \q_mark \__clist_reverse:wwNww ! ,
8061   \q_mark \__clist_reverse_end:ww
8062   \q_stop ? \q_mark
8063 }
8064 \cs_new:Npn \__clist_reverse:wwNww
8065   #1 , #2 \q_mark #3 #4 \q_stop ? #5 \q_mark
8066   { #3 ? #2 \q_mark #3 #4 \q_stop #1 , #5 \q_mark }
8067 \cs_new:Npn \__clist_reverse_end:ww #1 ! #2 , \q_mark
8068   { \exp_not:o { \use_none:n #2 } }

```

(End definition for `\clist_reverse:n`, `__clist_reverse:wwNww`, and `__clist_reverse_end:ww`. This function is documented on page 110.)

`\clist_sort:Nn` Implemented in `l3sort`.

`\clist_sort:cn`

`\clist_gsort:Nn` (End definition for `\clist_sort:Nn` and `\clist_gsort:Nn`. These functions are documented on page 110.)

`\clist_gsort:cn`

14.6 Comma list conditionals

```

\clist_if_empty_p:N Simple copies from the token list variable material.
\clist_if_empty_p:c 8069 \prg_new_eq_conditional:NNn \clist_if_empty:N \tl_if_empty:N
\clist_if_empty:NTF 8070 { p , T , F , TF }
\clist_if_empty:cTF 8071 \prg_new_eq_conditional:NNn \clist_if_empty:c \tl_if_empty:c
8072 { p , T , F , TF }

```

(End definition for `\clist_if_empty:N`. This function is documented on page 110.)

```

\clist_if_empty_p:n As usual, we insert a token (here ?) before grabbing any argument: this avoids losing
\clist_if_empty:nTF braces. The argument of \tl_if_empty:oTF is empty if #1 is ? followed by blank spaces
  \__clist_if_empty_n:w (besides, this particular variant of the emptiness test is optimized). If the item of the
  \__clist_if_empty_n:wNw comma list is blank, grab the next one. As soon as one item is non-blank, exit: the second
                        auxiliary grabs \prg_return_false: as #2, unless every item in the comma list was blank
                        and the loop actually got broken by the trailing \q_mark \prg_return_false: item.

```

```

8073 \prg_new_conditional:Npnn \clist_if_empty:n #1 { p , T , F , TF }
8074 {
8075   \__clist_if_empty_n:w ? #1
8076   , \q_mark \prg_return_false:
8077   , \q_mark \prg_return_true:
8078   \q_stop
8079 }
8080 \cs_new:Npn \__clist_if_empty_n:w #1 ,
8081 {
8082   \tl_if_empty:oTF { \use_none:nn #1 ? }
8083   { \__clist_if_empty_n:w ? }
8084   { \__clist_if_empty_n:wNw }
8085 }
8086 \cs_new:Npn \__clist_if_empty_n:wNw #1 \q_mark #2#3 \q_stop {#2}

```

(End definition for `\clist_if_empty:nTF`, `__clist_if_empty_n:w`, and `__clist_if_empty_n:wNw`. This function is documented on page 111.)

```

\clist_if_in:NnTF For “safe” items, we simply surround the comma list, and the item, with commas, then
\clist_if_in:NVT use the same code as for \tl_if_in:Nn. For “unsafe” items we follow the same route as
\clist_if_in:NoTF \seq_if_in:Nn, mapping through the list a comparison function. If found, return true
\clist_if_in:cnTF and remove \prg_return_false:.
\clist_if_in:cVTF 8087 \prg_new_protected_conditional:Npnn \clist_if_in:Nn #1#2 { T , F , TF }
\clist_if_in:coTF 8088 {
\clist_if_in:nnTF 8089   \exp_args:No \__clist_if_in_return:nnN #1 {#2} #1
\clist_if_in:nVTF 8090 }
\clist_if_in:noTF 8091 \prg_new_protected_conditional:Npnn \clist_if_in:nn #1#2 { T , F , TF }
  \__clist_if_in_return:nnN 8092 {
                        8093   \clist_set:Nn \l__clist_internal_clist {#1}
                        8094   \exp_args:No \__clist_if_in_return:nnN \l__clist_internal_clist {#2}
                        8095   \l__clist_internal_clist
                        8096 }
8097 \cs_new_protected:Npn \__clist_if_in_return:nnN #1#2#3
8098 {
8099   \__clist_if_wrap:nTF {#2}
8100   {
8101     \cs_set:Npx \__clist_tmp:w ##1
8102     {

```

```

8103         \exp_not:N \tl_if_eq:nnT {##1}
8104         \exp_not:n
8105         {
8106             {#2}
8107             { \clist_map_break:n { \prg_return_true: \use_none:n } }
8108         }
8109     }
8110     \clist_map_function:NN #3 \__clist_tmp:w
8111     \prg_return_false:
8112 }
8113 {
8114     \cs_set:Npn \__clist_tmp:w ##1 ,#2, { }
8115     \tl_if_empty:oTF
8116     { \__clist_tmp:w ,#1, {} {} ,#2, }
8117     { \prg_return_false: } { \prg_return_true: }
8118 }
8119 }
8120 \prg_generate_conditional_variant:Nnn \clist_if_in:Nn
8121 { NV , No , c , cV , co } { T , F , TF }
8122 \prg_generate_conditional_variant:Nnn \clist_if_in:nn
8123 { nV , no } { T , F , TF }

```

(End definition for `\clist_if_in:NnTF`, `\clist_if_in:nnTF`, and `__clist_if_in_return:nnN`. These functions are documented on page 111.)

14.7 Mapping to comma lists

`\clist_map_function:NN` If the variable is empty, the mapping is skipped (otherwise, that comma-list would be seen as consisting of one empty item). Then loop over the comma-list, grabbing one comma-delimited item at a time. The end is marked by `\q_recursion_tail`. The auxiliary function `__clist_map_function:Nw` is also used in `\clist_map_inline:Nn`.

```

8124 \cs_new:Npn \clist_map_function:NN #1#2
8125 {
8126     \clist_if_empty:NF #1
8127     {
8128         \exp_last_unbraced:NNo \__clist_map_function:Nw #2 #1
8129         , \q_recursion_tail ,
8130         \prg_break_point:Nn \clist_map_break: { }
8131     }
8132 }
8133 \cs_new:Npn \__clist_map_function:Nw #1#2 ,
8134 {
8135     \quark_if_recursion_tail_break:nN {#2} \clist_map_break:
8136     #1 {#2}
8137     \__clist_map_function:Nw #1
8138 }
8139 \cs_generate_variant:Nn \clist_map_function:NN { c }

```

(End definition for `\clist_map_function:NN` and `__clist_map_function:Nw`. This function is documented on page 111.)

`\clist_map_function:nN` The n-type mapping function is a bit more awkward, since spaces must be trimmed from each item. Space trimming is again based on `__clist_trim_next:w`. The auxiliary `__clist_map_unbrace:Nw`

`__clist_map_function_n:Nn` receives as arguments the function, and the next non-empty item (after space trimming but before brace removal). One level of braces is removed by `__clist_map_unbrace:Nw`.

```

8140 \cs_new:Npn \clist_map_function:nN #1#2
8141 {
8142   \exp_after:wN \__clist_map_function_n:Nn \exp_after:wN #2
8143   \exp:w \__clist_trim_next:w \prg_do_nothing: #1 , \q_recursion_tail ,
8144   \prg_break_point:Nn \clist_map_break: { }
8145 }
8146 \cs_new:Npn \__clist_map_function_n:Nn #1 #2
8147 {
8148   \quark_if_recursion_tail_break:nN {#2} \clist_map_break:
8149   \__clist_map_unbrace:Nw #1 #2,
8150   \exp_after:wN \__clist_map_function_n:Nn \exp_after:wN #1
8151   \exp:w \__clist_trim_next:w \prg_do_nothing:
8152 }
8153 \cs_new:Npn \__clist_map_unbrace:Nw #1 #2, { #1 {#2} }

```

(End definition for `\clist_map_function:nN`, `__clist_map_function_n:Nn`, and `__clist_map_unbrace:Nw`. This function is documented on page 111.)

`\clist_map_inline:Nn`
`\clist_map_inline:cn`
`\clist_map_inline:nn`

Inline mapping is done by creating a suitable function “on the fly”: this is done globally to avoid any issues with \TeX ’s groups. We use a different function for each level of nesting.

Since the mapping is non-expandable, we can perform the space-trimming needed by the `n` version simply by storing the comma-list in a variable. We don’t need a different comma-list for each nesting level: the comma-list is expanded before the mapping starts.

```

8154 \cs_new_protected:Npn \clist_map_inline:Nn #1#2
8155 {
8156   \clist_if_empty:NF #1
8157   {
8158     \int_gincr:N \g__kernel_prg_map_int
8159     \cs_gset_protected:cpn
8160     { \__clist_map_ \int_use:N \g__kernel_prg_map_int :w } ##1 {#2}
8161     \exp_last_unbraced:Nco \__clist_map_function:Nw
8162     { \__clist_map_ \int_use:N \g__kernel_prg_map_int :w }
8163     #1 , \q_recursion_tail ,
8164     \prg_break_point:Nn \clist_map_break:
8165     { \int_gdecr:N \g__kernel_prg_map_int }
8166   }
8167 }
8168 \cs_new_protected:Npn \clist_map_inline:nn #1
8169 {
8170   \clist_set:Nn \l__clist_internal_clist {#1}
8171   \clist_map_inline:Nn \l__clist_internal_clist
8172 }
8173 \cs_generate_variant:Nn \clist_map_inline:Nn { c }

```

(End definition for `\clist_map_inline:Nn` and `\clist_map_inline:nn`. These functions are documented on page 111.)

`\clist_map_variable:NNn`
`\clist_map_variable:cNn`
`\clist_map_variable:nNn`
`__clist_map_variable:Nnw`

As for other comma-list mappings, filter out the case of an empty list. Same approach as `\clist_map_function:Nn`, additionally we store each item in the given variable. As for inline mappings, space trimming for the `n` variant is done by storing the comma

list in a variable. The strange `\use:n` avoids unlikely problems when #2 would contain `\q_recursion_stop`.

```

8174 \cs_new_protected:Npn \clist_map_variable:NNn #1#2#3
8175 {
8176   \clist_if_empty:NF #1
8177   {
8178     \exp_args:Nno \use:nn
8179     { \__clist_map_variable:Nnw #2 {#3} }
8180     #1
8181     , \q_recursion_tail , \q_recursion_stop
8182     \prg_break_point:Nn \clist_map_break: { }
8183   }
8184 }
8185 \cs_new_protected:Npn \clist_map_variable:nNn #1
8186 {
8187   \clist_set:Nn \l__clist_internal_clist {#1}
8188   \clist_map_variable:NNn \l__clist_internal_clist
8189 }
8190 \cs_new_protected:Npn \__clist_map_variable:Nnw #1#2#3,
8191 {
8192   \tl_set:Nn #1 {#3}
8193   \quark_if_recursion_tail_stop:N #1
8194   \use:n {#2}
8195   \__clist_map_variable:Nnw #1 {#2}
8196 }
8197 \cs_generate_variant:Nn \clist_map_variable:NNn { c }

```

(End definition for `\clist_map_variable:NNn`, `\clist_map_variable:nNn`, and `__clist_map_variable:Nnw`. These functions are documented on page 112.)

`\clist_map_break:` The break statements use the general `\prg_map_break:Nn` mechanism.
`\clist_map_break:n`

```

8198 \cs_new:Npn \clist_map_break:
8199 { \prg_map_break:Nn \clist_map_break: { } }
8200 \cs_new:Npn \clist_map_break:n
8201 { \prg_map_break:Nn \clist_map_break: }

```

(End definition for `\clist_map_break:` and `\clist_map_break:n`. These functions are documented on page 112.)

`\clist_count:N` Counting the items in a comma list is done using the same approach as for other token
`\clist_count:c` count functions: turn each entry into a +1 then use integer evaluation to actually do the
`\clist_count:n` mathematics. In the case of an n-type comma-list, we could of course use `\clist_map_-`
`__clist_count:n` **function:nN**, but that is very slow, because it carefully removes spaces. Instead, we loop
`__clist_count:w` manually, and skip blank items (but not {}, hence the extra spaces).

```

8202 \cs_new:Npn \clist_count:N #1
8203 {
8204   \int_eval:n
8205   {
8206     0
8207     \clist_map_function:NN #1 \__clist_count:n
8208   }
8209 }
8210 \cs_generate_variant:Nn \clist_count:N { c }
8211 \cs_new:Npx \clist_count:n #1

```

```

8212 {
8213   \exp_not:N \int_eval:n
8214   {
8215     0
8216     \exp_not:N \__clist_count:w \c_space_tl
8217     #1 \exp_not:n { , \q_recursion_tail , \q_recursion_stop }
8218   }
8219 }
8220 \cs_new:Npn \__clist_count:n #1 { + 1 }
8221 \cs_new:Npx \__clist_count:w #1 ,
8222 {
8223   \exp_not:n { \exp_args:Nf \quark_if_recursion_tail_stop:n } {#1}
8224   \exp_not:N \tl_if_blank:nF {#1} { + 1 }
8225   \exp_not:N \__clist_count:w \c_space_tl
8226 }

```

(End definition for `\clist_count:N` and others. These functions are documented on page 112.)

14.8 Using comma lists

`\clist_use:Nnnn` First check that the variable exists. Then count the items in the comma list. If it has none, output nothing. If it has one item, output that item, brace stripped (note that space-trimming has already been done when the comma list was assigned). If it has two, place the *<separator between two>* in the middle.

Otherwise, `__clist_use:nwwwnwn` takes the following arguments; 1: a *<separator>*, 2, 3, 4: three items from the comma list (or quarks), 5: the rest of the comma list, 6: a *<continuation>* function (`use_ii` or `use_iii` with its *<separator>* argument), 7: junk, and 8: the temporary result, which is built in a brace group following `\q_stop`. The *<separator>* and the first of the three items are placed in the result, then we use the *<continuation>*, placing the remaining two items after it. When we begin this loop, the three items really belong to the comma list, the first `\q_mark` is taken as a delimiter to the `use_ii` function, and the continuation is `use_ii` itself. When we reach the last two items of the original token list, `\q_mark` is taken as a third item, and now the second `\q_mark` serves as a delimiter to `use_ii`, switching to the other *<continuation>*, `use_iii`, which uses the *<separator between final two>*.

```

8227 \cs_new:Npn \clist_use:Nnnn #1#2#3#4
8228 {
8229   \clist_if_exist:NTF #1
8230   {
8231     \int_case:nnF { \clist_count:N #1 }
8232     {
8233       { 0 } { }
8234       { 1 } { \exp_after:wN \__clist_use:wnn #1 , , { } }
8235       { 2 } { \exp_after:wN \__clist_use:wnn #1 , {#2} }
8236     }
8237     {
8238       \exp_after:wN \__clist_use:nwwwnwn
8239       \exp_after:wN { \exp_after:wN } #1 ,
8240       \q_mark , { \__clist_use:nwwwnwn {#3} }
8241       \q_mark , { \__clist_use:nwnn {#4} }
8242       \q_stop { }
8243     }
8244   }

```



```

8245     {
8246         \_kernel_msg_expandable_error:nnn
8247         { kernel } { bad-variable } {#1}
8248     }
8249 }
8250 \cs_generate_variant:Nn \clist_use:Nnnn { c }
8251 \cs_new:Npn \__clist_use:wnn #1 , #2 , #3 { \exp_not:n { #1 #3 #2 } }
8252 \cs_new:Npn \__clist_use:nwwwnnw
8253     #1#2 , #3 , #4 , #5 \q_mark , #6#7 \q_stop #8
8254     { #6 {#3} , {#4} , #5 \q_mark , {#6} #7 \q_stop { #8 #1 #2 } }
8255 \cs_new:Npn \__clist_use:nwnn #1#2 , #3 \q_stop #4
8256     { \exp_not:n { #4 #1 #2 } }
8257 \cs_new:Npn \clist_use:Nn #1#2
8258     { \clist_use:Nnnn #1 {#2} {#2} {#2} }
8259 \cs_generate_variant:Nn \clist_use:Nn { c }

```

(End definition for `\clist_use:Nnnn` and others. These functions are documented on page [113](#).)

14.9 Using a single item

<pre> \clist_item:Nn \clist_item:cn __clist_item:nnnN __clist_item:ffoN __clist_item:ffnN __clist_item_N_loop:nw </pre>	<p>To avoid needing to test the end of the list at each step, we first compute the $\langle length \rangle$ of the list. If the item number is 0, less than $-\langle length \rangle$, or more than $\langle length \rangle$, the result is empty. If it is negative, but not less than $-\langle length \rangle$, add $\langle length \rangle + 1$ to the item number before performing the loop. The loop itself is very simple, return the item if the counter reached 1, otherwise, decrease the counter and repeat.</p> <pre> 8260 \cs_new:Npn \clist_item:Nn #1#2 8261 { 8262 __clist_item:ffoN 8263 { \clist_count:N #1 } 8264 { \int_eval:n {#2} } 8265 #1 8266 __clist_item_N_loop:nw 8267 } 8268 \cs_new:Npn __clist_item:nnnN #1#2#3#4 8269 { 8270 \int_compare:nNnTF {#2} < 0 8271 { 8272 \int_compare:nNnTF {#2} < { - #1 } 8273 { \use_none_delimit_by_q_stop:w } 8274 { \exp_args:Nf #4 { \int_eval:n { #2 + 1 + #1 } } } 8275 } 8276 { 8277 \int_compare:nNnTF {#2} > {#1} 8278 { \use_none_delimit_by_q_stop:w } 8279 { #4 {#2} } 8280 } 8281 { } , #3 , \q_stop 8282 } 8283 \cs_generate_variant:Nn __clist_item:nnnN { ffo, ff } 8284 \cs_new:Npn __clist_item_N_loop:nw #1 #2, 8285 { 8286 \int_compare:nNnTF {#1} = 0 8287 { \use_i_delimit_by_q_stop:nw { \exp_not:n {#2} } } 8288 { \exp_args:Nf __clist_item_N_loop:nw { \int_eval:n { #1 - 1 } } } </pre>
---	--

```

8289 }
8290 \cs_generate_variant:Nn \clist_item:Nn { c }

```

(End definition for `\clist_item:Nn`, `__clist_item:nnnN`, and `__clist_item_N_loop:nw`. This function is documented on page 115.)

```

\clist_item:nn This starts in the same way as \clist_item:Nn by counting the items of the comma list.
\__clist_item_n:nw The final item should be space-trimmed before being brace-stripped, hence we insert a
\__clist_item_n_loop:nw couple of odd-looking \prg_do_nothing: to avoid losing braces. Blank items are ignored.
\__clist_item_n_end:n
\__clist_item_n_strip:n
\__clist_item_n_strip:w
8291 \cs_new:Npn \clist_item:nn #1#2
8292 {
8293   \__clist_item:ffnN
8294   { \clist_count:n {#1} }
8295   { \int_eval:n {#2} }
8296   {#1}
8297   \__clist_item_n:nw
8298 }
8299 \cs_new:Npn \__clist_item_n:nw #1
8300 { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
8301 \cs_new:Npn \__clist_item_n_loop:nw #1 #2,
8302 {
8303   \exp_args:No \tl_if_blank:nTF {#2}
8304   { \__clist_item_n_loop:nw {#1} \prg_do_nothing: }
8305   {
8306     \int_compare:nNnTF {#1} = 0
8307     { \exp_args:No \__clist_item_n_end:n {#2} }
8308     {
8309       \exp_args:Nf \__clist_item_n_loop:nw
8310       { \int_eval:n { #1 - 1 } }
8311       \prg_do_nothing:
8312     }
8313   }
8314 }
8315 \cs_new:Npn \__clist_item_n_end:n #1 #2 \q_stop
8316 { \tl_trim_spaces_apply:nN {#1} \__clist_item_n_strip:n }
8317 \cs_new:Npn \__clist_item_n_strip:n #1 { \__clist_item_n_strip:w #1 , }
8318 \cs_new:Npn \__clist_item_n_strip:w #1 , { \exp_not:n {#1} }

```

(End definition for `\clist_item:nn` and others. This function is documented on page 115.)

```

\clist_rand_item:n The N-type function is not implemented through the n-type function for efficiency: for
\clist_rand_item:N instance comma-list variables do not require space-trimming of their items. Even testing
\clist_rand_item:c for emptiness of an n-type comma-list is slow, so we count items first and use that both
\__clist_rand_item:nn for the emptiness test and the pseudo-random integer. Importantly, \clist_item:Nn
and \clist_item:nn only evaluate their argument once.

```

```

8319 \cs_new:Npn \clist_rand_item:n #1
8320 { \exp_args:Nf \__clist_rand_item:nn { \clist_count:n {#1} } {#1} }
8321 \cs_new:Npn \__clist_rand_item:nn #1#2
8322 {
8323   \int_compare:nNnF {#1} = 0
8324   { \clist_item:nn {#2} { \int_rand:nn { 1 } {#1} } }
8325 }
8326 \cs_new:Npn \clist_rand_item:N #1
8327 {

```

```

8328 \clist_if_empty:NF #1
8329 { \clist_item:Nn #1 { \int_rand:nn { 1 } { \clist_count:N #1 } } }
8330 }
8331 \cs_generate_variant:Nn \clist_rand_item:N { c }

```

(End definition for `\clist_rand_item:n`, `\clist_rand_item:N`, and `__clist_rand_item:nn`. These functions are documented on page 115.)

14.10 Viewing comma lists

```

\clist_show:N Apply the general \__kernel_chk_defined:NT and \msg_show:nnnnnn.
\clist_show:c 8332 \cs_new_protected:Npn \clist_show:N { \__clist_show:NN \msg_show:nnxxxx }
\clist_log:N   8333 \cs_generate_variant:Nn \clist_show:N { c }
\clist_log:c   8334 \cs_new_protected:Npn \clist_log:N { \__clist_show:NN \msg_log:nnxxxx }
\__clist_show:NN 8335 \cs_generate_variant:Nn \clist_log:N { c }
                8336 \cs_new_protected:Npn \__clist_show:NN #1#2
                8337 {
                8338   \__kernel_chk_defined:NT #2
                8339   {
                8340     #1 { LaTeX/kernel } { show-clist }
                8341     { \token_to_str:N #2 }
                8342     { \clist_map_function:NN #2 \msg_show_item:n }
                8343     { } { }
                8344   }
                8345 }

```

(End definition for `\clist_show:N`, `\clist_log:N`, and `__clist_show:NN`. These functions are documented on page 115.)

```

\clist_show:n A variant of the above: no existence check, empty first argument for the message.
\clist_log:n   8346 \cs_new_protected:Npn \clist_show:n { \__clist_show:NN \msg_show:nnxxxx }
\__clist_show:NN 8347 \cs_new_protected:Npn \clist_log:n { \__clist_show:NN \msg_log:nnxxxx }
                8348 \cs_new_protected:Npn \__clist_show:NN #1#2
                8349 {
                8350   #1 { LaTeX/kernel } { show-clist }
                8351   { } { \clist_map_function:nN {#2} \msg_show_item:n } { } { }
                8352 }

```

(End definition for `\clist_show:n`, `\clist_log:n`, and `__clist_show:NN`. These functions are documented on page 115.)

14.11 Scratch comma lists

```

\l_tmpa_clist Temporary comma list variables.
\l_tmpb_clist
\g_tmpa_clist
\g_tmpb_clist
8353 \clist_new:N \l_tmpa_clist
8354 \clist_new:N \l_tmpb_clist
8355 \clist_new:N \g_tmpa_clist
8356 \clist_new:N \g_tmpb_clist

```

(End definition for `\l_tmpa_clist` and others. These variables are documented on page 116.)

```

8357 </initex | package>

```

15 l3token implementation

```
8358 \*initex | package)
```

```
8359 \@@=char)
```

15.1 Manipulating and interrogating character tokens

Simple wrappers around the primitives.

```
\char_set_catcode:nn
\char_value_catcode:n
\char_show_value_catcode:n

8360 \cs_new_protected:Npn \char_set_catcode:nn #1#2
8361 { \tex_catcode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
8362 \cs_new:Npn \char_value_catcode:n #1
8363 { \tex_the:D \tex_catcode:D \int_eval:n {#1} \exp_stop_f: }
8364 \cs_new_protected:Npn \char_show_value_catcode:n #1
8365 { \exp_args:Nf \tl_show:n { \char_value_catcode:n {#1} } }
```

(End definition for `\char_set_catcode:nn`, `\char_value_catcode:n`, and `\char_show_value_catcode:n`. These functions are documented on page 120.)

```
\char_set_catcode_escape:N
\char_set_catcode_group_begin:N
\char_set_catcode_group_end:N
\char_set_catcode_math_toggle:N
\char_set_catcode_alignment:N
\char_set_catcode_end_line:N
\char_set_catcode_parameter:N
\char_set_catcode_math_superscript:N
\char_set_catcode_math_subscript:N
\char_set_catcode_ignore:N
\char_set_catcode_space:N
\char_set_catcode_letter:N
\char_set_catcode_other:N
\char_set_catcode_active:N
\char_set_catcode_comment:N
\char_set_catcode_invalid:N

8366 \cs_new_protected:Npn \char_set_catcode_escape:N #1
8367 { \char_set_catcode:nn { '#1 } { 0 } }
8368 \cs_new_protected:Npn \char_set_catcode_group_begin:N #1
8369 { \char_set_catcode:nn { '#1 } { 1 } }
8370 \cs_new_protected:Npn \char_set_catcode_group_end:N #1
8371 { \char_set_catcode:nn { '#1 } { 2 } }
8372 \cs_new_protected:Npn \char_set_catcode_math_toggle:N #1
8373 { \char_set_catcode:nn { '#1 } { 3 } }
8374 \cs_new_protected:Npn \char_set_catcode_alignment:N #1
8375 { \char_set_catcode:nn { '#1 } { 4 } }
8376 \cs_new_protected:Npn \char_set_catcode_end_line:N #1
8377 { \char_set_catcode:nn { '#1 } { 5 } }
8378 \cs_new_protected:Npn \char_set_catcode_parameter:N #1
8379 { \char_set_catcode:nn { '#1 } { 6 } }
8380 \cs_new_protected:Npn \char_set_catcode_math_superscript:N #1
8381 { \char_set_catcode:nn { '#1 } { 7 } }
8382 \cs_new_protected:Npn \char_set_catcode_math_subscript:N #1
8383 { \char_set_catcode:nn { '#1 } { 8 } }
8384 \cs_new_protected:Npn \char_set_catcode_ignore:N #1
8385 { \char_set_catcode:nn { '#1 } { 9 } }
8386 \cs_new_protected:Npn \char_set_catcode_space:N #1
8387 { \char_set_catcode:nn { '#1 } { 10 } }
8388 \cs_new_protected:Npn \char_set_catcode_letter:N #1
8389 { \char_set_catcode:nn { '#1 } { 11 } }
8390 \cs_new_protected:Npn \char_set_catcode_other:N #1
8391 { \char_set_catcode:nn { '#1 } { 12 } }
8392 \cs_new_protected:Npn \char_set_catcode_active:N #1
8393 { \char_set_catcode:nn { '#1 } { 13 } }
8394 \cs_new_protected:Npn \char_set_catcode_comment:N #1
8395 { \char_set_catcode:nn { '#1 } { 14 } }
8396 \cs_new_protected:Npn \char_set_catcode_invalid:N #1
8397 { \char_set_catcode:nn { '#1 } { 15 } }
```

(End definition for `\char_set_catcode_escape:N` and others. These functions are documented on page 119.)

```

\char_set_catcode_escape:n
\char_set_catcode_group_begin:n
\char_set_catcode_group_end:n
\char_set_catcode_math_toggle:n
\char_set_catcode_alignment:n
\char_set_catcode_end_line:n
\char_set_catcode_parameter:n
\char_set_catcode_math_superscript:n
\char_set_catcode_math_subscript:n
\char_set_catcode_ignore:n
\char_set_catcode_space:n
\char_set_catcode_letter:n
\char_set_catcode_other:n
\char_set_catcode_active:n
\char_set_catcode_comment:n
\char_set_catcode_invalid:n

8398 \cs_new_protected:Npn \char_set_catcode_escape:n #1
8399   { \char_set_catcode:nn {#1} { 0 } }
8400 \cs_new_protected:Npn \char_set_catcode_group_begin:n #1
8401   { \char_set_catcode:nn {#1} { 1 } }
8402 \cs_new_protected:Npn \char_set_catcode_group_end:n #1
8403   { \char_set_catcode:nn {#1} { 2 } }
8404 \cs_new_protected:Npn \char_set_catcode_math_toggle:n #1
8405   { \char_set_catcode:nn {#1} { 3 } }
8406 \cs_new_protected:Npn \char_set_catcode_alignment:n #1
8407   { \char_set_catcode:nn {#1} { 4 } }
8408 \cs_new_protected:Npn \char_set_catcode_end_line:n #1
8409   { \char_set_catcode:nn {#1} { 5 } }
8410 \cs_new_protected:Npn \char_set_catcode_parameter:n #1
8411   { \char_set_catcode:nn {#1} { 6 } }
8412 \cs_new_protected:Npn \char_set_catcode_math_superscript:n #1
8413   { \char_set_catcode:nn {#1} { 7 } }
8414 \cs_new_protected:Npn \char_set_catcode_math_subscript:n #1
8415   { \char_set_catcode:nn {#1} { 8 } }
8416 \cs_new_protected:Npn \char_set_catcode_ignore:n #1
8417   { \char_set_catcode:nn {#1} { 9 } }
8418 \cs_new_protected:Npn \char_set_catcode_space:n #1
8419   { \char_set_catcode:nn {#1} { 10 } }
8420 \cs_new_protected:Npn \char_set_catcode_letter:n #1
8421   { \char_set_catcode:nn {#1} { 11 } }
8422 \cs_new_protected:Npn \char_set_catcode_other:n #1
8423   { \char_set_catcode:nn {#1} { 12 } }
8424 \cs_new_protected:Npn \char_set_catcode_active:n #1
8425   { \char_set_catcode:nn {#1} { 13 } }
8426 \cs_new_protected:Npn \char_set_catcode_comment:n #1
8427   { \char_set_catcode:nn {#1} { 14 } }
8428 \cs_new_protected:Npn \char_set_catcode_invalid:n #1
8429   { \char_set_catcode:nn {#1} { 15 } }

```

(End definition for `\char_set_catcode_escape:n` and others. These functions are documented on page 119.)

```

\char_set_mathcode:nn
\char_value_mathcode:n
\char_show_value_mathcode:n
\char_set_lccode:nn
\char_value_lccode:n
\char_show_value_lccode:n
\char_set_uccode:nn
\char_value_uccode:n
\char_show_value_uccode:n
\char_set_sfcode:nn
\char_value_sfcode:n
\char_show_value_sfcode:n

Pretty repetitive, but necessary!

8430 \cs_new_protected:Npn \char_set_mathcode:nn #1#2
8431   { \tex_mathcode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
8432 \cs_new:Npn \char_value_mathcode:n #1
8433   { \tex_the:D \tex_mathcode:D \int_eval:n {#1} \exp_stop_f: }
8434 \cs_new_protected:Npn \char_show_value_mathcode:n #1
8435   { \exp_args:Nf \tl_show:n { \char_value_mathcode:n {#1} } }
8436 \cs_new_protected:Npn \char_set_lccode:nn #1#2
8437   { \tex_lccode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
8438 \cs_new:Npn \char_value_lccode:n #1
8439   { \tex_the:D \tex_lccode:D \int_eval:n {#1} \exp_stop_f: }
8440 \cs_new_protected:Npn \char_show_value_lccode:n #1
8441   { \exp_args:Nf \tl_show:n { \char_value_lccode:n {#1} } }
8442 \cs_new_protected:Npn \char_set_uccode:nn #1#2
8443   { \tex_uccode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
8444 \cs_new:Npn \char_value_uccode:n #1
8445   { \tex_the:D \tex_uccode:D \int_eval:n {#1} \exp_stop_f: }

```

```

8446 \cs_new_protected:Npn \char_show_value_uccode:n #1
8447 { \exp_args:Nf \tl_show:n { \char_value_uccode:n {#1} } }
8448 \cs_new_protected:Npn \char_set_sfcode:nn #1#2
8449 { \tex_sfcode:D \int_eval:n {#1} = \int_eval:n {#2} \exp_stop_f: }
8450 \cs_new:Npn \char_value_sfcode:n #1
8451 { \tex_the:D \tex_sfcode:D \int_eval:n {#1} \exp_stop_f: }
8452 \cs_new_protected:Npn \char_show_value_sfcode:n #1
8453 { \exp_args:Nf \tl_show:n { \char_value_sfcode:n {#1} } }

```

(End definition for `\char_set_mathcode:nn` and others. These functions are documented on page 121.)

`\l_char_active_seq`
`\l_char_special_seq`

Two sequences for dealing with special characters. The first is characters which may be active, the second longer list is for “special” characters more generally. Both lists are escaped so that for example bulk code assignments can be carried out. In both cases, the order is by ASCII character code (as is done in for example `\ExplSyntaxOn`).

```

8454 \seq_new:N \l_char_special_seq
8455 \seq_set_split:Nnn \l_char_special_seq { }
8456 { \ \ " \# \$ \% \& \ \ ^ \_ \{ \} \~ }
8457 \seq_new:N \l_char_active_seq
8458 \seq_set_split:Nnn \l_char_active_seq { }
8459 { \ " \$ \& \^ \_ \~ }

```

(End definition for `\l_char_active_seq` and `\l_char_special_seq`. These variables are documented on page 121.)

15.2 Creating character tokens

`\char_set_active_eq:NN`
`\char_set_active_eq:Nc`
`\char_gset_active_eq:NN`
`\char_gset_active_eq:Nc`
`\char_set_active_eq:nN`
`\char_set_active_eq:nc`
`\char_gset_active_eq:nN`
`\char_gset_active_eq:nc`

Four simple functions with very similar definitions, so set up using an auxiliary. These are similar to LuaTeX’s `\lcharcode` primitive.

```

8460 \group_begin:
8461 \char_set_catcode_active:N \^^@
8462 \cs_set_protected:Npn \__char_tmp:nN #1#2
8463 {
8464   \cs_new_protected:cpn { #1 :nN } ##1
8465   {
8466     \group_begin:
8467     \char_set_lccode:nn { \^^@ } { ##1 }
8468     \tex_lowercase:D { \group_end: #2 ^^@ }
8469   }
8470   \cs_new_protected:cpx { #1 :NN } ##1
8471   { \exp_not:c { #1 : nN } { '##1' } }
8472 }
8473 \__char_tmp:nN { char_set_active_eq } \cs_set_eq:NN
8474 \__char_tmp:nN { char_gset_active_eq } \cs_gset_eq:NN
8475 \group_end:
8476 \cs_generate_variant:Nn \char_set_active_eq:NN { Nc }
8477 \cs_generate_variant:Nn \char_gset_active_eq:NN { Nc }
8478 \cs_generate_variant:Nn \char_set_active_eq:nN { nc }
8479 \cs_generate_variant:Nn \char_gset_active_eq:nN { nc }

```

(End definition for `\char_set_active_eq:NN` and others. These functions are documented on page 117.)

`__char_int_to_roman:w`

For efficiency in 8-bit engines, we use the faster primitive approach to making roman numerals.

```

8480 \cs_new_eq:NN \__char_int_to_roman:w \tex_romannumeral:D

```

(End definition for `_char_int_to_roman:w`.)

`\char_generate:nn` The aim here is to generate characters of (broadly) arbitrary category code. Where possible, that is done using engine support (XeTeX, LuaTeX). There are though various issues which are covered below. At the interface layer, turn the two arguments into integers up-front so this is only done once.

```

\__char_generate_aux:nn
\__char_generate_aux:nnw
\__char_generate_auxii:nnw
  \l__char_tmp_tl
\__char_generate_invalid_catcode:
8481 \cs_new:Npn \char_generate:nn #1#2
8482 {
8483   \exp:w \exp_after:wN \__char_generate_aux:w
8484     \int_value:w \int_eval:n {#1} \exp_after:wN ;
8485     \int_value:w \int_eval:n {#2} ;
8486 }
```

Before doing any actual conversion, first some special case filtering. Spaces are out here as LuaTeX emulation only makes normal (charcode 32 spaces). However, `^^@` is filtered out separately as that can't be done with macro emulation either, so is flagged up separately. That done, hand off to the engine-dependent part.

```

8487 \cs_new:Npn \__char_generate_aux:w #1 ; #2 ;
8488 {
8489   \if_int_compare:w #2 = 10 \exp_stop_f:
8490     \if_int_compare:w #1 = 0 \exp_stop_f:
8491       \__kernel_msg_expandable_error:nn { kernel } { char-null-space }
8492     \else:
8493       \__kernel_msg_expandable_error:nn { kernel } { char-space }
8494     \fi:
8495   \else:
8496     \if_int_odd:w 0
8497       \if_int_compare:w #2 < 1 \exp_stop_f: 1 \fi:
8498       \if_int_compare:w #2 = 5 \exp_stop_f: 1 \fi:
8499       \if_int_compare:w #2 = 9 \exp_stop_f: 1 \fi:
8500       \if_int_compare:w #2 > 13 \exp_stop_f: 1 \fi: \exp_stop_f:
8501       \__kernel_msg_expandable_error:nn { kernel }
8502         { char-invalid-catcode }
8503     \else:
8504       \if_int_odd:w 0
8505         \if_int_compare:w #1 < 0 \exp_stop_f: 1 \fi:
8506         \if_int_compare:w #1 > \c_max_char_int 1 \fi: \exp_stop_f:
8507         \__kernel_msg_expandable_error:nn { kernel }
8508           { char-out-of-range }
8509       \else:
8510         \__char_generate_aux:nnw {#1} {#2}
8511       \fi:
8512     \fi:
8513   \fi:
8514   \exp_end:
8515 }
8516 \tl_new:N \l__char_tmp_tl
```

Engine-dependent definitions are now needed for the implementation. For LuaTeX and XeTeX there is engine-level support. They can do cases that macro emulation can't. All of those are filtered out here using a primitive-based boolean expression for speed. The final level is the basic definition at the engine level: the arguments here are integers so there is no need to worry about them too much. Older versions of XeTeX cannot generate

active characters so we filter that: at some future stage that may change: the slightly odd ordering of auxiliaries reflects that.

```

8517 \group_begin:
8518 \package
8519 \char_set_catcode_active:N \^^L
8520 \cs_set:Npn \^^L { }
8521 \package
8522 \char_set_catcode_other:n { 0 }
8523 \if_int_odd:w 0
8524 \sys_if_engine luatex:T { 1 }
8525 \sys_if_engine xetex:T { 1 } \exp_stop_f:
8526 \sys_if_engine luatex:TF
8527 {
8528 \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
8529 {
8530 #3
8531 \exp_after:wN \exp_after:wN \exp_after:wN \exp_end:
8532 \lua_now:e { 13kernel.charcat(#1, #2) }
8533 }
8534 }
8535 {
8536 \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
8537 {
8538 #3
8539 \exp_after:wN \exp_end:
8540 \tex_Ucharcat:D #1 \exp_stop_f: #2 \exp_stop_f:
8541 }
8542 \cs_if_exist:NF \tex_expanded:D
8543 {
8544 \cs_new_eq:NN \__char_generate_auxii:nnw \__char_generate_aux:nnw
8545 \cs_gset:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
8546 {
8547 #3
8548 \if_int_compare:w #2 = 13 \exp_stop_f:
8549 \__kernel_msg_expandable_error:nn { kernel } { char-active }
8550 \else:
8551 \__char_generate_auxii:nnw {#1} {#2}
8552 \fi:
8553 \exp_end:
8554 }
8555 }
8556 }
8557 \else:

```

For engines where `\Ucharcat` isn't available (or emulated) then we have to work in macros, and cover only the 8-bit range. The first stage is to build up a `tl` containing `^^@` with each category code that can be accessed in this way, with an error set up for the other cases. This is all done such that it can be quickly accessed using a `\if_case:w` low-level conditional. There are a few things to notice here. As `^^L` is `\outer` we need to locally set it to avoid a problem. To get open/close braces into the list, they are set up using `\if_false:` pairing and are then x-type expanded together into the desired form.

```

8558 \tl_set:Nn \l__char_tmp_tl { \exp_not:N \or: }
8559 \char_set_catcode_group_begin:n { 0 } % {
8560 \tl_put_right:Nn \l__char_tmp_tl { ^^@ \if_false: } }

```



```

8561 \char_set_catcode_group_end:n { 0 }
8562 \tl_put_right:Nn \l__char_tmp_tl { { \fi: \exp_not:N \or: ^^@ } % }
8563 \tl_set:Nx \l__char_tmp_tl { \l__char_tmp_tl }
8564 \char_set_catcode_math_toggle:n { 0 }
8565 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

As T_EX is very unhappy if it finds an alignment character inside a primitive `\halign` even when skipping false branches, some precautions are required. T_EX is happy if the token is hidden inside `\unexpanded` (which needs to be the primitive). The expansion chain here is required so that the conditional gets cleaned up correctly (other code assumes there is exactly one token to skip during the clean-up).

```

8566 \char_set_catcode_alignment:n { 0 }
8567 \tl_put_right:Nn \l__char_tmp_tl
8568 {
8569   \or:
8570   \__kernel_exp_not:w \exp_after:wN
8571   { \exp_after:wN ^^@ \exp_after:wN }
8572 }
8573 \tl_put_right:Nn \l__char_tmp_tl { \or: }
8574 \char_set_catcode_parameter:n { 0 }
8575 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
8576 \char_set_catcode_math_superscript:n { 0 }
8577 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
8578 \char_set_catcode_math_subscript:n { 0 }
8579 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
8580 \tl_put_right:Nn \l__char_tmp_tl { \or: }

```

For making spaces, there needs to be an o-type expansion of a `\use:n` (or some other tokenization) to avoid dropping the space. We also set up active tokens although they are (currently) filtered out by the interface layer (`\Ucharcat` cannot make active tokens).

```

8581 \char_set_catcode_space:n { 0 }
8582 \tl_put_right:No \l__char_tmp_tl { \use:n { \or: } ^^@ }
8583 \char_set_catcode_letter:n { 0 }
8584 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
8585 \char_set_catcode_other:n { 0 }
8586 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }
8587 \char_set_catcode_active:n { 0 }
8588 \tl_put_right:Nn \l__char_tmp_tl { \or: ^^@ }

```

Convert the above temporary list into a series of constant token lists, one for each character code, using `\tex_lowercase:D` to convert `^^@` in each case. The x-type expansion ensures that `\tex_lowercase:D` receives the contents of the token list. In package mode, `^^L` is awkward hence this is done in three parts. Notice that at this stage `^^@` is active.

```

8589 \cs_set_protected:Npn \__char_tmp:n #1
8590 {
8591   \char_set_lccode:nn { 0 } {#1}
8592   \char_set_lccode:nn { 32 } {#1}
8593   \exp_args:Nx \tex_lowercase:D
8594   {
8595     \tl_const:Nn
8596     \exp_not:c { c__char_ \__char_int_to_roman:w #1 _tl }
8597     { \exp_not:o \l__char_tmp_tl }
8598   }
8599 }

```

```

8600 <*package>
8601     \int_step_function:nnN { 0 } { 11 } \__char_tmp:n
8602     \group_begin:
8603         \tl_replace_once:Nnn \l__char_tmp_tl { ^~@ } { \ERROR }
8604         \__char_tmp:n { 12 }
8605     \group_end:
8606     \int_step_function:nnN { 13 } { 255 } \__char_tmp:n
8607 </package>
8608 <*initex>
8609     \int_step_function:nnN { 0 } { 255 } \__char_tmp:n
8610 </initex>
8611     \cs_new:Npn \__char_generate_aux:nnw #1#2#3 \exp_end:
8612     {
8613         #3
8614         \exp_after:wN \exp_after:wN
8615         \exp_after:wN \exp_end:
8616         \exp_after:wN \exp_after:wN
8617         \if_case:w #2
8618             \exp_last_unbraced:Nv \exp_stop_f:
8619             { c__char_ \__char_int_to_roman:w #1 _tl }
8620         \fi:
8621     }
8622     \fi:
8623 \group_end:

```

(End definition for `\char_generate:nn` and others. This function is documented on page 118.)

`\c_catcode_other_space_tl` Create a space with category code 12: an “other” space.

```

8624 \tl_const:Nx \c_catcode_other_space_tl { \char_generate:nn { '\ } { 12 } }

```

(End definition for `\c_catcode_other_space_tl`. This function is documented on page 118.)

15.3 Generic tokens

```

8625 <@@=token>

```

`\token_to_meaning:N` These are all defined in `l3basics`, as they are needed “early”. This is just a reminder!

`\token_to_meaning:c`

`\token_to_str:N`

`\token_to_str:c`

(End definition for `\token_to_meaning:N` and `\token_to_str:N`. These functions are documented on page 122.)

`\c_group_begin_token`

`\c_group_end_token`

`\c_math_toggle_token`

`\c_alignment_token`

`\c_parameter_token`

We define these useful tokens. For the brace and space tokens things have to be done by hand: the formal argument spec. for `\cs_new_eq:NN` does not cover them so we do things by hand. (As currently coded it would *work* with `\cs_new_eq:NN` but that’s not really a great idea to show off: we want people to stick to the defined interfaces and that includes us.) So that these few odd names go into the log when appropriate there is a need to hand-apply the `__kernel_chk_if_free_cs:N` check.

`\c_math_superscript_token`

`\c_math_subscript_token`

`\c_space_token`

`\c_catcode_letter_token`

`\c_catcode_other_token`

```

8626 \group_begin:
8627     \__kernel_chk_if_free_cs:N \c_group_begin_token
8628     \tex_global:D \tex_let:D \c_group_begin_token {
8629     \__kernel_chk_if_free_cs:N \c_group_end_token
8630     \tex_global:D \tex_let:D \c_group_end_token }
8631     \char_set_catcode_math_toggle:N \*
8632     \cs_new_eq:NN \c_math_toggle_token *
8633     \char_set_catcode_alignment:N \*

```

```

8634 \cs_new_eq:NN \c_alignment_token *
8635 \cs_new_eq:NN \c_parameter_token #
8636 \cs_new_eq:NN \c_math_superscript_token ^
8637 \char_set_catcode_math_subscript:N \*
8638 \cs_new_eq:NN \c_math_subscript_token *
8639 \__kernel_chk_if_free_cs:N \c_space_token
8640 \use:n { \tex_global:D \tex_let:D \c_space_token = ~ } ~
8641 \cs_new_eq:NN \c_catcode_letter_token a
8642 \cs_new_eq:NN \c_catcode_other_token 1
8643 \group_end:

```

(End definition for `\c_group_begin_token` and others. These functions are documented on page 122.)

`\c_catcode_active_tl` Not an implicit token!

```

8644 \group_begin:
8645   \char_set_catcode_active:N \*
8646   \tl_const:Nn \c_catcode_active_tl { \exp_not:N * }
8647 \group_end:

```

(End definition for `\c_catcode_active_tl`. This variable is documented on page 122.)

15.4 Token conditionals

`\token_if_group_begin_p:N` Check if token is a begin group token. We use the constant `\c_group_begin_token` for this.
`\token_if_group_begin:N TF`

```

8648 \prg_new_conditional:Npnn \token_if_group_begin:N #1 { p , T , F , TF }
8649 {
8650   \if_catcode:w \exp_not:N #1 \c_group_begin_token
8651   \prg_return_true: \else: \prg_return_false: \fi:
8652 }

```

(End definition for `\token_if_group_begin:N TF` . This function is documented on page 123.)

`\token_if_group_end_p:N` Check if token is a end group token. We use the constant `\c_group_end_token` for this.

`\token_if_group_end:N TF`

```

8653 \prg_new_conditional:Npnn \token_if_group_end:N #1 { p , T , F , TF }
8654 {
8655   \if_catcode:w \exp_not:N #1 \c_group_end_token
8656   \prg_return_true: \else: \prg_return_false: \fi:
8657 }

```

(End definition for `\token_if_group_end:N TF` . This function is documented on page 123.)

`\token_if_math_toggle_p:N` Check if token is a math shift token. We use the constant `\c_math_toggle_token` for this.
`\token_if_math_toggle:N TF`

```

8658 \prg_new_conditional:Npnn \token_if_math_toggle:N #1 { p , T , F , TF }
8659 {
8660   \if_catcode:w \exp_not:N #1 \c_math_toggle_token
8661   \prg_return_true: \else: \prg_return_false: \fi:
8662 }

```

(End definition for `\token_if_math_toggle:N TF` . This function is documented on page 123.)

`\token_if_alignment_p:N` Check if token is an alignment tab token. We use the constant `\c_alignment_token` for this.
`\token_if_alignment:N \mathbf{TF}`

```

8663 \prg_new_conditional:Npnn \token_if_alignment:N #1 { p , T , F , TF }
8664 {
8665     \if_catcode:w \exp_not:N #1 \c_alignment_token
8666     \prg_return_true: \else: \prg_return_false: \fi:
8667 }

```

(End definition for `\token_if_alignment:N \mathbf{TF}` . This function is documented on page 123.)

`\token_if_parameter_p:N` Check if token is a parameter token. We use the constant `\c_parameter_token` for this.
`\token_if_parameter:N \mathbf{TF}` We have to trick T_EX a bit to avoid an error message: within a group we prevent `\c_parameter_token` from behaving like a macro parameter character. The definitions of `\prg_new_conditional:Npnn` are global, so they remain after the group.

```

8668 \group_begin:
8669 \cs_set_eq:NN \c_parameter_token \scan_stop:
8670 \prg_new_conditional:Npnn \token_if_parameter:N #1 { p , T , F , TF }
8671 {
8672     \if_catcode:w \exp_not:N #1 \c_parameter_token
8673     \prg_return_true: \else: \prg_return_false: \fi:
8674 }
8675 \group_end:

```

(End definition for `\token_if_parameter:N \mathbf{TF}` . This function is documented on page 123.)

`\token_if_math_superscript_p:N` Check if token is a math superscript token. We use the constant `\c_math_superscript_token` for this.
`\token_if_math_superscript:N \mathbf{TF}`

```

8676 \prg_new_conditional:Npnn \token_if_math_superscript:N #1
8677 { p , T , F , TF }
8678 {
8679     \if_catcode:w \exp_not:N #1 \c_math_superscript_token
8680     \prg_return_true: \else: \prg_return_false: \fi:
8681 }

```

(End definition for `\token_if_math_superscript:N \mathbf{TF}` . This function is documented on page 123.)

`\token_if_math_subscript_p:N` Check if token is a math subscript token. We use the constant `\c_math_subscript_token` for this.
`\token_if_math_subscript:N \mathbf{TF}`

```

8682 \prg_new_conditional:Npnn \token_if_math_subscript:N #1 { p , T , F , TF }
8683 {
8684     \if_catcode:w \exp_not:N #1 \c_math_subscript_token
8685     \prg_return_true: \else: \prg_return_false: \fi:
8686 }

```

(End definition for `\token_if_math_subscript:N \mathbf{TF}` . This function is documented on page 123.)

`\token_if_space_p:N` Check if token is a space token. We use the constant `\c_space_token` for this.
`\token_if_space:N \mathbf{TF}`

```

8687 \prg_new_conditional:Npnn \token_if_space:N #1 { p , T , F , TF }
8688 {
8689     \if_catcode:w \exp_not:N #1 \c_space_token
8690     \prg_return_true: \else: \prg_return_false: \fi:
8691 }

```

(End definition for `\token_if_space:N \mathbf{TF}` . This function is documented on page 123.)

`\token_if_letter_p:N` Check if token is a letter token. We use the constant `\c_catcode_letter_token` for this.

`\token_if_letter:N \underline{TF}`

```
8692 \prg_new_conditional:Npnn \token_if_letter:N #1 { p , T , F , TF }
8693 {
8694     \if_catcode:w \exp_not:N #1 \c_catcode_letter_token
8695     \prg_return_true: \else: \prg_return_false: \fi:
8696 }
```

(End definition for `\token_if_letter:N \underline{TF}` . This function is documented on page 124.)

`\token_if_other_p:N` Check if token is an other char token. We use the constant `\c_catcode_other_token`
`\token_if_other:N \underline{TF}` for this.

```
8697 \prg_new_conditional:Npnn \token_if_other:N #1 { p , T , F , TF }
8698 {
8699     \if_catcode:w \exp_not:N #1 \c_catcode_other_token
8700     \prg_return_true: \else: \prg_return_false: \fi:
8701 }
```

(End definition for `\token_if_other:N \underline{TF}` . This function is documented on page 124.)

`\token_if_active_p:N` Check if token is an active char token. We use the constant `\c_catcode_active_tl` for
`\token_if_active:N \underline{TF}` this. A technical point is that `\c_catcode_active_tl` is in fact a macro expanding to
`\exp_not:N *`, where `*` is active.

```
8702 \prg_new_conditional:Npnn \token_if_active:N #1 { p , T , F , TF }
8703 {
8704     \if_catcode:w \exp_not:N #1 \c_catcode_active_tl
8705     \prg_return_true: \else: \prg_return_false: \fi:
8706 }
```

(End definition for `\token_if_active:N \underline{TF}` . This function is documented on page 124.)

`\token_if_eq_meaning_p:NN` Check if the tokens #1 and #2 have same meaning.

`\token_if_eq_meaning:NN \underline{TF}`

```
8707 \prg_new_conditional:Npnn \token_if_eq_meaning:NN #1#2 { p , T , F , TF }
8708 {
8709     \if_meaning:w #1 #2
8710     \prg_return_true: \else: \prg_return_false: \fi:
8711 }
```

(End definition for `\token_if_eq_meaning:NN \underline{TF}` . This function is documented on page 124.)

`\token_if_eq_catcode_p:NN` Check if the tokens #1 and #2 have same category code.

`\token_if_eq_catcode:NN \underline{TF}`

```
8712 \prg_new_conditional:Npnn \token_if_eq_catcode:NN #1#2 { p , T , F , TF }
8713 {
8714     \if_catcode:w \exp_not:N #1 \exp_not:N #2
8715     \prg_return_true: \else: \prg_return_false: \fi:
8716 }
```

(End definition for `\token_if_eq_catcode:NN \underline{TF}` . This function is documented on page 124.)

`\token_if_eq_charcode_p:NN` Check if the tokens #1 and #2 have same character code.

`\token_if_eq_charcode:NN \underline{TF}`

```
8717 \prg_new_conditional:Npnn \token_if_eq_charcode:NN #1#2 { p , T , F , TF }
8718 {
8719     \if_charcode:w \exp_not:N #1 \exp_not:N #2
8720     \prg_return_true: \else: \prg_return_false: \fi:
8721 }
```

(End definition for `\token_if_eq_charcode:NNTF`. This function is documented on page 124.)

`\token_if_macro_p:N` When a token is a macro, `\token_to_meaning:N` always outputs something like
`\token_if_macro:NTF` `\long macro:#1->#1` so we could naively check to see if the meaning contains `->`.
`__token_if_macro_p:w` However, this can fail the five `\...mark` primitives, whose meaning has the form
`\...mark:<user material>`. The problem is that the `<user material>` can contain `->`.

However, only characters, macros, and marks can contain the colon character. The idea is thus to grab until the first `:`, and analyse what is left. However, macros can have any combination of `\long`, `\protected` or `\outer` (not used in L^AT_EX3) before the string `macro:`. We thus only select the part of the meaning between the first `ma` and the first following `:`. If this string is `cro`, then we have a macro. If the string is `rk`, then we have a mark. The string can also be `cro parameter character` for a colon with a weird category code (namely the usual category code of `#`). Otherwise, it is empty.

This relies on the fact that `\long`, `\protected`, `\outer` cannot contain `ma`, regardless of the escape character, even if the escape character is `m...`

Both `ma` and `:` must be of category code 12 (other), so are detokenized.

```

8722 \use:x
8723 {
8724   \prg_new_conditional:Npnn \exp_not:N \token_if_macro:N ##1
8725   { p , T , F , TF }
8726   {
8727     \exp_not:N \exp_after:wN \exp_not:N \__token_if_macro_p:w
8728     \exp_not:N \token_to_meaning:N ##1 \tl_to_str:n { ma : }
8729     \exp_not:N \q_stop
8730   }
8731   \cs_new:Npn \exp_not:N \__token_if_macro_p:w
8732   ##1 \tl_to_str:n { ma } ##2 \c_colon_str ##3 \exp_not:N \q_stop
8733 }
8734 {
8735   \str_if_eq:nnTF { #2 } { cro }
8736   { \prg_return_true: }
8737   { \prg_return_false: }
8738 }

```

(End definition for `\token_if_macro:NNTF` and `__token_if_macro_p:w`. This function is documented on page 124.)

`\token_if_cs_p:N` Check if token has same catcode as a control sequence. This follows the same pattern as
`\token_if_cs:NNTF` for `\token_if_letter:N` etc. We use `\scan_stop:` for this.

```

8739 \prg_new_conditional:Npnn \token_if_cs:N #1 { p , T , F , TF }
8740 {
8741   \if_catcode:w \exp_not:N #1 \scan_stop:
8742   \prg_return_true: \else: \prg_return_false: \fi:
8743 }

```

(End definition for `\token_if_cs:NNTF`. This function is documented on page 124.)

`\token_if_expandable_p:N` Check if token is expandable. We use the fact that T_EX temporarily converts `\exp_`
`\token_if_expandable:NNTF` `not:N <token>` into `\scan_stop:` if `<token>` is expandable. An undefined token is not considered as expandable. No problem nesting the conditionals, since the third `#1` is only skipped if it is non-expandable (hence not part of T_EX's conditional apparatus).

```

8744 \prg_new_conditional:Npnn \token_if_expandable:N #1 { p , T , F , TF }
8745 {

```

```

8746 \exp_after:wN \if_meaning:w \exp_not:N #1 #1
8747 \prg_return_false:
8748 \else:
8749 \if_cs_exist:N #1
8750 \prg_return_true:
8751 \else:
8752 \prg_return_false:
8753 \fi:
8754 \fi:
8755 }

```

(End definition for `\token_if_expandable:N`. This function is documented on page 124.)

These auxiliary functions are used below to define some conditionals which detect whether the `\meaning` of their argument begins with a particular string. Each auxiliary takes an argument delimited by a string, a second one delimited by `\q_stop`, and returns the first one and its delimiter. This result is eventually compared to another string.

```

\__token_delimit_by_char:w
\__token_delimit_by_count:w
\__token_delimit_by_dimen:w
\__token_delimit_by_macro:w
\__token_delimit_by_muskip:w
\__token_delimit_by_skip:w
\__token_delimit_by_toks:w

8756 \group_begin:
8757 \cs_set_protected:Npn \__token_tmp:w #1
8758 {
8759 \use:x
8760 {
8761 \cs_new:Npn \exp_not:c { __token_delimit_by_ #1 :w }
8762 ####1 \tl_to_str:n {#1} ####2 \exp_not:N \q_stop
8763 { ####1 \tl_to_str:n {#1} }
8764 }
8765 }
8766 \__token_tmp:w { char" }
8767 \__token_tmp:w { count }
8768 \__token_tmp:w { dimen }
8769 \__token_tmp:w { macro }
8770 \__token_tmp:w { muskip }
8771 \__token_tmp:w { skip }
8772 \__token_tmp:w { toks }
8773 \group_end:

```

(End definition for `__token_delimit_by_char:w` and others.)

Each of these conditionals tests whether its argument's `\meaning` starts with a given string. This is essentially done by having an auxiliary grab an argument delimited by the string and testing whether the argument was empty. Of course, a copy of this string must first be added to the end of the `\meaning` to avoid a runaway argument in case it does not contain the string. Two complications arise. First, the escape character is not fixed, and cannot be included in the delimiter of the auxiliary function (this function cannot be defined on the fly because tests must remain expandable): instead the first argument of the auxiliary (plus the delimiter to avoid complications with trailing spaces) is compared using `\str_if_eq:eeTF` to the result of applying `\token_to_str:N` to a control sequence. Second, the `\meaning` of primitives such as `\dimen` or `\dimendef` starts in the same way as registers such as `\dimen123`, so they must be tested for.

Characters used as delimiters must have catcode 12 and are obtained through `\tl_to_str:n`. This requires doing all definitions within x-expansion. The temporary function `__token_tmp:w` used to define each conditional receives three arguments: the name of the conditional, the auxiliary's delimiter (also used to name the auxiliary), and the string

```

\token_if_chardef_p:N
\token_if_chardef:NTF
\token_if_mathchardef_p:N
\token_if_mathchardef:NTF
\token_if_long_macro_p:N
\token_if_long_macro:NTF
\token_if_protected_macro_p:N
\token_if_protected_macro:NTF
\token_if_protected_long_macro_p:N
\token_if_protected_long_macro:NTF
\token_if_dim_register_p:N
\token_if_dim_register:NTF
\token_if_int_register_p:N
\token_if_int_register:NTF
\token_if_muskip_register_p:N
\token_if_muskip_register:NTF
\token_if_skip_register_p:N
\token_if_skip_register:NTF
\token_if_toks_register_p:N
\token_if_toks_register:NTF

```

to which one compares the auxiliary's result. Note that the `\meaning` of a protected long macro starts with `\protected\long macro`, with no space after `\protected` but a space after `\long`, hence the mixture of `\token_to_str:N` and `\tl_to_str:n`.

For the first five conditionals, `\cs_if_exist:cT` turns out to be `false`, and the code boils down to a string comparison between the result of the auxiliary on the `\meaning` of the conditional's argument `####1`, and `#3`. Both are evaluated at run-time, as this is important to get the correct escape character.

The other five conditionals have additional code that compares the argument `####1` to two `TeX` primitives which would wrongly be recognized as registers otherwise. Despite using `TeX`'s primitive conditional construction, this does not break when `####1` is itself a conditional, because branches of the conditionals are only skipped if `####1` is one of the two primitives that are tested for (which are not `TeX` conditionals).

```

8774 \group_begin:
8775 \cs_set_protected:Npn \__token_tmp:w #1#2#3
8776 {
8777   \use:x
8778   {
8779     \prg_new_conditional:Npnn \exp_not:c { token_if_ #1 :N } ####1
8780     { p , T , F , TF }
8781     {
8782       \cs_if_exist:cT { tex_ #2 :D }
8783       {
8784         \exp_not:N \if_meaning:w ####1 \exp_not:c { tex_ #2 :D }
8785         \exp_not:N \prg_return_false:
8786         \exp_not:N \else:
8787         \exp_not:N \if_meaning:w ####1 \exp_not:c { tex_ #2 def:D }
8788         \exp_not:N \prg_return_false:
8789         \exp_not:N \else:
8790         }
8791         \exp_not:N \str_if_eq:eeTF
8792         {
8793           \exp_not:N \exp_after:wN
8794           \exp_not:c { __token_delimit_by_ #2 :w }
8795           \exp_not:N \token_to_meaning:N ####1
8796           ? \tl_to_str:n {#2} \exp_not:N \q_stop
8797         }
8798         { \exp_not:n {#3} }
8799         { \exp_not:N \prg_return_true: }
8800         { \exp_not:N \prg_return_false: }
8801         \cs_if_exist:cT { tex_ #2 :D }
8802         {
8803           \exp_not:N \fi:
8804           \exp_not:N \fi:
8805         }
8806       }
8807     }
8808   }
8809   \__token_tmp:w { chardef } { char" } { \token_to_str:N \char" }
8810   \__token_tmp:w { mathchardef } { char" } { \token_to_str:N \mathchar" }
8811   \__token_tmp:w { long_macro } { macro } { \tl_to_str:n { \long } macro }
8812   \__token_tmp:w { protected_macro } { macro }
8813   { \tl_to_str:n { \protected } macro }
8814   \__token_tmp:w { protected_long_macro } { macro }

```



```

8815 { \token_to_str:N \protected \tl_to_str:n { \long } macro }
8816 \__token_tmp:w { dim_register } { dimen } { \token_to_str:N \dimen }
8817 \__token_tmp:w { int_register } { count } { \token_to_str:N \count }
8818 \__token_tmp:w { muskip_register } { muskip } { \token_to_str:N \muskip }
8819 \__token_tmp:w { skip_register } { skip } { \token_to_str:N \skip }
8820 \__token_tmp:w { toks_register } { toks } { \token_to_str:N \toks }
8821 \group_end:

```

(End definition for `\token_if_chardef:NTF` and others. These functions are documented on page 125.)

`\token_if_primitive_p:N`

`\token_if_primitive:NTF`

We filter out macros first, because they cause endless trouble later otherwise.

Primitives are almost distinguished by the fact that the result of `\token_to_meaning:N` is formed from letters only. Every other token has either a space (e.g., the letter A), a digit (e.g., `\count123`) or a double quote (e.g., `\char"A`).

Ten exceptions: on the one hand, `\tex_undefined:D` is not a primitive, but its meaning is undefined, only letters; on the other hand, `\space`, `\italiccorr`, `\hyphen`, `\firstmark`, `\topmark`, `\botmark`, `\splitfirstmark`, `\splitbotmark`, and `\nullfont` are primitives, but have non-letters in their meaning.

We start by removing the two first (non-space) characters from the meaning. This removes the escape character (which may be nonexistent depending on `\endlinechar`), and takes care of three of the exceptions: `\space`, `\italiccorr` and `\hyphen`, whose meaning is at most two characters. This leaves a string terminated by some `:`, and `\q_stop`.

The meaning of each one of the five `\...mark` primitives has the form $\langle letters \rangle : \langle user material \rangle$. In other words, the first non-letter is a colon. We remove everything after the first colon.

We are now left with a string, which we must analyze. For primitives, it contains only letters. For non-primitives, it contains either `"`, or a space, or a digit. Two exceptions remain: `\tex_undefined:D`, which is not a primitive, and `\nullfont`, which is a primitive.

Spaces cannot be grabbed in an undelimited way, so we check them separately. If there is a space, we test for `\nullfont`. Otherwise, we go through characters one by one, and stop at the first character less than ‘A’ (this is not quite a test for “only letters”, but is close enough to work in this context). If this first character is `:` then we have a primitive, or `\tex_undefined:D`, and if it is `"` or a digit, then the token is not a primitive.

```

8822 \tex_chardef:D \c__token_A_int = 'A ~ %
8823 \use:x
8824 {
8825   \prg_new_conditional:Npnn \exp_not:N \token_if_primitive:N ##1
8826   { p , T , F , TF }
8827   {
8828     \exp_not:N \token_if_macro:NTF ##1
8829     \exp_not:N \prg_return_false:
8830     {
8831       \exp_not:N \exp_after:wN \exp_not:N \__token_if_primitive:NNw
8832       \exp_not:N \token_to_meaning:N ##1
8833       \tl_to_str:n { : : : } \exp_not:N \q_stop ##1
8834     }
8835   }
8836   \cs_new:Npn \exp_not:N \__token_if_primitive:NNw
8837   ##1##2 ##3 \c_colon_str ##4 \exp_not:N \q_stop
8838   {

```

```

8839     \exp_not:N \tl_if_empty:oTF
8840     { \exp_not:N \__token_if_primitive_space:w ##3 ~ }
8841     {
8842         \exp_not:N \__token_if_primitive_loop:N ##3
8843         \c_colon_str \exp_not:N \q_stop
8844     }
8845     { \exp_not:N \__token_if_primitive_nullfont:N }
8846 }
8847 }
8848 \cs_new:Npn \__token_if_primitive_space:w #1 ~ { }
8849 \cs_new:Npn \__token_if_primitive_nullfont:N #1
8850 {
8851     \if_meaning:w \tex_nullfont:D #1
8852     \prg_return_true:
8853 \else:
8854     \prg_return_false:
8855 \fi:
8856 }
8857 \cs_new:Npn \__token_if_primitive_loop:N #1
8858 {
8859     \if_int_compare:w '#1 < \c__token_A_int %
8860     \exp_after:wN \__token_if_primitive:Nw
8861     \exp_after:wN #1
8862 \else:
8863     \exp_after:wN \__token_if_primitive_loop:N
8864 \fi:
8865 }
8866 \cs_new:Npn \__token_if_primitive:Nw #1 #2 \q_stop
8867 {
8868     \if:w : #1
8869     \exp_after:wN \__token_if_primitive_undefined:N
8870 \else:
8871     \prg_return_false:
8872     \exp_after:wN \use_none:n
8873 \fi:
8874 }
8875 \cs_new:Npn \__token_if_primitive_undefined:N #1
8876 {
8877     \if_cs_exist:N #1
8878     \prg_return_true:
8879 \else:
8880     \prg_return_false:
8881 \fi:
8882 }

```

(End definition for `\token_if_primitive:NTF` and others. This function is documented on page 126.)

15.5 Peeking ahead at the next token

8883 `<@@=peek>`

Peeking ahead is implemented using a two part mechanism. The outer level provides a defined interface to the lower level material. This allows a large amount of code to be shared. There are four cases:

1. peek at the next token;

2. peek at the next non-space token;
3. peek at the next token and remove it;
4. peek at the next non-space token and remove it.

\l_peek_token Storage tokens which are publicly documented: the token peeked.

\g_peek_token 8884 \cs_new_eq:NN \l_peek_token ?
8885 \cs_new_eq:NN \g_peek_token ?

(End definition for \l_peek_token and \g_peek_token. These variables are documented on page 126.)

\l__peek_search_token The token to search for as an implicit token: cf. \l__peek_search_tl.

8886 \cs_new_eq:NN \l__peek_search_token ?

(End definition for \l__peek_search_token.)

\l__peek_search_tl The token to search for as an explicit token: cf. \l__peek_search_token.

8887 \tl_new:N \l__peek_search_tl

(End definition for \l__peek_search_tl.)

__peek_true:w Functions used by the branching and space-stripping code.

__peek_true_aux:w 8888 \cs_new:Npn __peek_true:w { }
__peek_false:w 8889 \cs_new:Npn __peek_true_aux:w { }
__peek_tmp:w 8890 \cs_new:Npn __peek_false:w { }
8891 \cs_new:Npn __peek_tmp:w { }

(End definition for __peek_true:w and others.)

\peek_after:Nw Simple wrappers for \futurelet: no arguments absorbed here.

\peek_gafter:Nw 8892 \cs_new_protected:Npn \peek_after:Nw
8893 { \tex_futurelet:D \l_peek_token }
8894 \cs_new_protected:Npn \peek_gafter:Nw
8895 { \tex_global:D \tex_futurelet:D \g_peek_token }

(End definition for \peek_after:Nw and \peek_gafter:Nw. These functions are documented on page 126.)

__peek_true_remove:w A function to remove the next token and then regain control.

8896 \cs_new_protected:Npn __peek_true_remove:w
8897 {
8898 \tex_afterassignment:D __peek_true_aux:w
8899 \cs_set_eq:NN __peek_tmp:w
8900 }

(End definition for __peek_true_remove:w.)

`\peek_remove_spaces:n` Repeatedly use `__peek_true_remove:w` to remove a space and call `__peek_true_remove_spaces:w`.

```

8901 \cs_new_protected:Npn \peek_remove_spaces:n #1
8902 {
8903   \cs_set:Npx \__peek_false:w { \exp_not:n {#1} }
8904   \group_align_safe_begin:
8905   \cs_set:Npn \__peek_true_aux:w { \peek_after:Nw \__peek_remove_spaces: }
8906   \__peek_true_aux:w
8907 }
8908 \cs_new_protected:Npn \__peek_remove_spaces:
8909 {
8910   \if_meaning:w \l_peek_token \c_space_token
8911     \exp_after:wN \__peek_true_remove:w
8912   \else:
8913     \group_align_safe_end:
8914     \exp_after:wN \__peek_false:w
8915   \fi:
8916 }

```

(End definition for `\peek_remove_spaces:n` and `__peek_remove_spaces:..` This function is documented on page 258.)

`__peek_token_generic_aux:NNTF` The generic functions store the test token in both implicit and explicit modes, and the `true` and `false` code as token lists, more or less. The two branches have to be absorbed here as the input stream needs to be cleared for the peek function itself. Here, `#1` is `__peek_true_remove:w` when removing the token and `__peek_true_aux:w` otherwise.

```

8917 \cs_new_protected:Npn \__peek_token_generic_aux:NNTF #1#2#3#4#5
8918 {
8919   \group_align_safe_begin:
8920   \cs_set_eq:NN \l__peek_search_token #3
8921   \tl_set:Nn \l__peek_search_tl {#3}
8922   \cs_set:Npx \__peek_true_aux:w
8923   {
8924     \exp_not:N \group_align_safe_end:
8925     \exp_not:n {#4}
8926   }
8927   \cs_set_eq:NN \__peek_true:w #1
8928   \cs_set:Npx \__peek_false:w
8929   {
8930     \exp_not:N \group_align_safe_end:
8931     \exp_not:n {#5}
8932   }
8933   \peek_after:Nw #2
8934 }

```

(End definition for `__peek_token_generic_aux:NNTF`.)

`__peek_token_generic:NNTF` For token removal there needs to be a call to the auxiliary function which does the work.

```

\__peek_token_remove_generic:NNTF
8935 \cs_new_protected:Npn \__peek_token_generic:NNTF
8936 { \__peek_token_generic_aux:NNTF \__peek_true_aux:w }
8937 \cs_new_protected:Npn \__peek_token_generic:NNT #1#2#3
8938 { \__peek_token_generic:NNTF #1 #2 {#3} { } }
8939 \cs_new_protected:Npn \__peek_token_generic:NNF #1#2#3
8940 { \__peek_token_generic:NNTF #1 #2 { } {#3} }

```

```

8941 \cs_new_protected:Npn \__peek_token_remove_generic:NNTF
8942 { \__peek_token_generic_aux:NNNTF \__peek_true_remove:w }
8943 \cs_new_protected:Npn \__peek_token_remove_generic:NNT #1#2#3
8944 { \__peek_token_remove_generic:NNTF #1 #2 {#3} { } }
8945 \cs_new_protected:Npn \__peek_token_remove_generic:NNF #1#2#3
8946 { \__peek_token_remove_generic:NNTF #1 #2 { } {#3} }

```

(End definition for __peek_token_generic:NNTF and __peek_token_remove_generic:NNTF.)

__peek_execute_branches_meaning: The meaning test is straight forward.

```

8947 \cs_new:Npn \__peek_execute_branches_meaning:
8948 {
8949   \if_meaning:w \l_peek_token \l__peek_search_token
8950   \exp_after:wN \__peek_true:w
8951   \else:
8952   \exp_after:wN \__peek_false:w
8953   \fi:
8954 }

```

(End definition for __peek_execute_branches_meaning:.)

__peek_execute_branches_catcode: The catcode and charcode tests are very similar, and in order to use the same auxiliaries we do something a little bit odd, firing \if_catcode:w and \if_charcode:w before finding the operands for those tests, which are only given in the auxii:N and auxiii: auxiliaries. For our purposes, three kinds of tokens may follow the peeking function:

- control sequences which are not equal to a non-active character token (*e.g.*, macro, primitive);
- active characters which are not equal to a non-active character token (*e.g.*, macro, primitive);
- explicit non-active character tokens, or control sequences or active characters set equal to a non-active character token.

The first two cases are not distinguishable simply using TeX's \futurelet, because we can only access the \meaning of tokens in that way. In those cases, detected thanks to a comparison with \scan_stop:, we grab the following token, and compare it explicitly with the explicit search token stored in \l__peek_search_tl. The \exp_not:N prevents outer macros (coming from non- \LaTeX 3 code) from blowing up. In the third case, \l_peek_token is good enough for the test, and we compare it again with the explicit search token. Just like the peek token, the search token may be of any of the three types above, hence the need to use the explicit token that was given to the peek function.

```

8955 \cs_new:Npn \__peek_execute_branches_catcode:
8956 { \if_catcode:w \__peek_execute_branches_catcode_aux: }
8957 \cs_new:Npn \__peek_execute_branches_charcode:
8958 { \if_charcode:w \__peek_execute_branches_catcode_aux: }
8959 \cs_new:Npn \__peek_execute_branches_catcode_aux:
8960 {
8961   \if_catcode:w \exp_not:N \l_peek_token \scan_stop:
8962   \exp_after:wN \exp_after:wN
8963   \exp_after:wN \__peek_execute_branches_catcode_auxii:N
8964   \exp_after:wN \exp_not:N
8965   \else:

```

```

8966         \exp_after:wN \__peek_execute_branches_catcode_auxiii:
8967         \fi:
8968     }
8969 \cs_new:Npn \__peek_execute_branches_catcode_auxii:N #1
8970 {
8971     \exp_not:N #1
8972     \exp_after:wN \exp_not:N \l__peek_search_tl
8973     \exp_after:wN \__peek_true:w
8974     \else:
8975     \exp_after:wN \__peek_false:w
8976     \fi:
8977     #1
8978 }
8979 \cs_new:Npn \__peek_execute_branches_catcode_auxiii:
8980 {
8981     \exp_not:N \l_peek_token
8982     \exp_after:wN \exp_not:N \l__peek_search_tl
8983     \exp_after:wN \__peek_true:w
8984     \else:
8985     \exp_after:wN \__peek_false:w
8986     \fi:
8987 }

```

(End definition for __peek_execute_branches_catcode: and others.)

\peek_catcode:NTF The public functions themselves cannot be defined using \prg_new_conditional:Npnn. Instead, the TF, T, F variants are defined in terms of corresponding variants of __peek_token_generic:NNTF or __peek_token_remove_generic:NNTF, with first argument one of __peek_execute_branches_catcode:, __peek_execute_branches_charcode:, or __peek_execute_branches_meaning:.

\peek_catcode_remove:NTF

\peek_charcode:NTF

\peek_charcode_remove:NTF

\peek_meaning:NTF

\peek_meaning_remove:NTF

```

8988 \tl_map_inline:nn { { catcode } { charcode } { meaning } }
8989 {
8990     \tl_map_inline:nn { { } { _remove } }
8991     {
8992         \tl_map_inline:nn { { TF } { T } { F } }
8993         {
8994             \cs_new_protected:cpx { peek_ #1 ##1 :N ####1 }
8995             {
8996                 \exp_not:c { __peek_token ##1 _generic:NN ####1 }
8997                 \exp_not:c { __peek_execute_branches_ #1 : }
8998             }
8999         }
9000     }
9001 }

```

(End definition for \peek_catcode:NTF and others. These functions are documented on page 126.)

\peek_catcode_ignore_spaces:NTF To ignore spaces, remove them using \peek_remove_spaces:n before running the tests.

\peek_catcode_remove_ignore_spaces:NTF

\peek_charcode_ignore_spaces:NTF

\peek_charcode_remove_ignore_spaces:NTF

\peek_meaning_ignore_spaces:NTF

\peek_meaning_remove_ignore_spaces:NTF

```

9002 \tl_map_inline:nn
9003 {
9004     { catcode } { catcode_remove }
9005     { charcode } { charcode_remove }
9006     { meaning } { meaning_remove }
9007 }

```

```

9008 {
9009   \cs_new_protected:cpx { peek_#1_ignore_spaces:NTF } ##1##2##3
9010   {
9011     \peek_remove_spaces:n
9012     { \exp_not:c { peek_#1:NTF } ##1 {##2} {##3} }
9013   }
9014   \cs_new_protected:cpx { peek_#1_ignore_spaces:NT } ##1##2
9015   {
9016     \peek_remove_spaces:n
9017     { \exp_not:c { peek_#1:NT } ##1 {##2} }
9018   }
9019   \cs_new_protected:cpx { peek_#1_ignore_spaces:NF } ##1##2
9020   {
9021     \peek_remove_spaces:n
9022     { \exp_not:c { peek_#1:NF } ##1 {##2} }
9023   }
9024 }

```

(End definition for `\peek_catcode_ignore_spaces:NTF` and others. These functions are documented on page 127.)

15.6 Decomposing a macro definition

We sometimes want to test if a control sequence can be expanded to reveal a hidden value. However, we cannot just expand the macro blindly as it may have arguments and none might be present. Therefore we define these functions to pick either the prefix(es), the argument specification, or the replacement text from a macro. All of this information is returned as characters with catcode 12. If the token in question isn't a macro, the token `\scan_stop:` is returned instead.

```

9025 \exp_args:Nno \use:nn
9026 { \cs_new:Npn \__peek_get_prefix_arg_replacement:wN #1 }
9027 { \tl_to_str:n { macro : } #2 -> #3 \q_stop #4 }
9028 { #4 {#1} {#2} {#3} }
9029 \cs_new:Npn \token_get_prefix_spec:N #1
9030 {
9031   \token_if_macro:NTF #1
9032   {
9033     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
9034     \token_to_meaning:N #1 \q_stop \use_i:nnn
9035   }
9036   { \scan_stop: }
9037 }
9038 \cs_new:Npn \token_get_arg_spec:N #1
9039 {
9040   \token_if_macro:NTF #1
9041   {
9042     \exp_after:wN \__peek_get_prefix_arg_replacement:wN
9043     \token_to_meaning:N #1 \q_stop \use_ii:nnn
9044   }
9045   { \scan_stop: }
9046 }
9047 \cs_new:Npn \token_get_replacement_spec:N #1
9048 {
9049   \token_if_macro:NTF #1

```

```

9050     {
9051         \exp_after:wN \__peek_get_prefix_arg_replacement:wN
9052         \token_to_meaning:N #1 \q_stop \use_iii:nnn
9053     }
9054     { \scan_stop: }
9055 }

```

(End definition for `\token_get_prefix_spec:N` and others. These functions are documented on page 129.)

```

9056 </initex | package>

```

16 l3prop implementation

The following test files are used for this code: `m3prop001`, `m3prop002`, `m3prop003`, `m3prop004`, `m3show001`.

```

9057 <*initex | package>

```

```

9058 <@@=prop>

```

A property list is a macro whose top-level expansion is of the form

```

\__prop \__prop_pair:wn <key1> \s__prop {<value1>}
...
\__prop_pair:wn <keyn> \s__prop {<valuen>}

```

where `\s__prop` is a scan mark (equal to `\scan_stop:`), and `__prop_pair:wn` can be used to map through the property list.

`\s__prop` The internal token used at the beginning of property lists. This is also used after each `<key>` (see `__prop_pair:wn`).

(End definition for `\s__prop`.)

```

\__prop_pair:wn \__prop_pair:wn <key> \s__prop {<item>}

```

The internal token used to begin each key–value pair in the property list. If expanded outside of a mapping or manipulation function, an error is raised. The definition should always be set globally.

(End definition for `__prop_pair:wn`.)

`\l__prop_internal_tl` Token list used to store new key–value pairs to be inserted by functions of the `\prop_put:Nnn` family.

(End definition for `\l__prop_internal_tl`.)

`__prop_split:NnTF`

Updated: 2013-01-08

`__prop_split:NnTF` $\langle\textit{property list}\rangle$ $\langle\textit{key}\rangle$ $\langle\textit{true code}\rangle$ $\langle\textit{false code}\rangle$

Splits the $\langle\textit{property list}\rangle$ at the $\langle\textit{key}\rangle$, giving three token lists: the $\langle\textit{extract}\rangle$ of $\langle\textit{property list}\rangle$ before the $\langle\textit{key}\rangle$, the $\langle\textit{value}\rangle$ associated with the $\langle\textit{key}\rangle$ and the $\langle\textit{extract}\rangle$ of the $\langle\textit{property list}\rangle$ after the $\langle\textit{value}\rangle$. Both $\langle\textit{extracts}\rangle$ retain the internal structure of a property list, and the concatenation of the two $\langle\textit{extracts}\rangle$ is a property list. If the $\langle\textit{key}\rangle$ is present in the $\langle\textit{property list}\rangle$ then the $\langle\textit{true code}\rangle$ is left in the input stream, with #1, #2, and #3 replaced by the first $\langle\textit{extract}\rangle$, the $\langle\textit{value}\rangle$, and the second $\langle\textit{extract}\rangle$. If the $\langle\textit{key}\rangle$ is not present in the $\langle\textit{property list}\rangle$ then the $\langle\textit{false code}\rangle$ is left in the input stream, with no trailing material. Both $\langle\textit{true code}\rangle$ and $\langle\textit{false code}\rangle$ are used in the replacement text of a macro defined internally, hence macro parameter characters should be doubled, except #1, #2, and #3 which stand in the $\langle\textit{true code}\rangle$ for the three extracts from the property list. The $\langle\textit{key}\rangle$ comparison takes place as described for `\str_if_eq:nn`.

`\s__prop` A private scan mark is used as a marker after each key, and at the very beginning of the property list.

9059 `\scan_new:N \s__prop`

(End definition for `\s__prop`.)

`__prop_pair:wn` The delimiter is always defined, but when misused simply triggers an error and removes its argument.

9060 `\cs_new:Npn __prop_pair:wn #1 \s__prop #2`

9061 `{ __kernel_msg_expandable_error:nn { kernel } { misused-prop } }`

(End definition for `__prop_pair:wn`.)

`\l__prop_internal_tl` Token list used to store the new key–value pair inserted by `\prop_put:Nnn` and friends.

9062 `\tl_new:N \l__prop_internal_tl`

(End definition for `\l__prop_internal_tl`.)

`\c_empty_prop` An empty prop.

9063 `\tl_const:Nn \c_empty_prop { \s__prop }`

(End definition for `\c_empty_prop`. This variable is documented on page 137.)

16.1 Allocation and initialisation

`\prop_new:N` Property lists are initialized with the value `\c_empty_prop`.

`\prop_new:c`

9064 `\cs_new_protected:Npn \prop_new:N #1`

9065 `{`

9066 `__kernel_chk_if_free_cs:N #1`

9067 `\cs_gset_eq:NN #1 \c_empty_prop`

9068 `}`

9069 `\cs_generate_variant:Nn \prop_new:N { c }`

(End definition for `\prop_new:N`. This function is documented on page 132.)

`\prop_clear:N` The same idea for clearing.

`\prop_clear:c`

9070 `\cs_new_protected:Npn \prop_clear:N #1`

9071 `{ \prop_set_eq:NN #1 \c_empty_prop }`

`\prop_gclear:N`

9072 `\cs_generate_variant:Nn \prop_clear:N { c }`

`\prop_gclear:c`

9073 `\cs_new_protected:Npn \prop_gclear:N #1`

9074 `{ \prop_gset_eq:NN #1 \c_empty_prop }`

9075 `\cs_generate_variant:Nn \prop_gclear:N { c }`

(End definition for `\prop_clear:N` and `\prop_gclear:N`. These functions are documented on page 132.)

`\prop_clear_new:N` Once again a simple variation of the token list functions.
`\prop_clear_new:c` 9076 `\cs_new_protected:Npn \prop_clear_new:N #1`
`\prop_gclear_new:N` 9077 `{ \prop_if_exist:NTF #1 { \prop_clear:N #1 } { \prop_new:N #1 } }`
`\prop_gclear_new:c` 9078 `\cs_generate_variant:Nn \prop_clear_new:N { c }`
9079 `\cs_new_protected:Npn \prop_gclear_new:N #1`
9080 `{ \prop_if_exist:NTF #1 { \prop_gclear:N #1 } { \prop_new:N #1 } }`
9081 `\cs_generate_variant:Nn \prop_gclear_new:N { c }`

(End definition for `\prop_clear_new:N` and `\prop_gclear_new:N`. These functions are documented on page 132.)

`\prop_set_eq:NN` These are simply copies from the token list functions.
`\prop_set_eq:cN` 9082 `\cs_new_eq:NN \prop_set_eq:NN \tl_set_eq:NN`
`\prop_set_eq:Nc` 9083 `\cs_new_eq:NN \prop_set_eq:Nc \tl_set_eq:Nc`
`\prop_set_eq:cc` 9084 `\cs_new_eq:NN \prop_set_eq:cN \tl_set_eq:cN`
`\prop_gset_eq:NN` 9085 `\cs_new_eq:NN \prop_set_eq:cc \tl_set_eq:cc`
`\prop_gset_eq:cN` 9086 `\cs_new_eq:NN \prop_gset_eq:NN \tl_gset_eq:NN`
`\prop_gset_eq:Nc` 9087 `\cs_new_eq:NN \prop_gset_eq:Nc \tl_gset_eq:Nc`
`\prop_gset_eq:cN` 9088 `\cs_new_eq:NN \prop_gset_eq:cN \tl_gset_eq:cN`
`\prop_gset_eq:cc` 9089 `\cs_new_eq:NN \prop_gset_eq:cc \tl_gset_eq:cc`

(End definition for `\prop_set_eq:NN` and `\prop_gset_eq:NN`. These functions are documented on page 132.)

`\l_tmpa_prop` We can now initialize the scratch variables.
`\l_tmpb_prop` 9090 `\prop_new:N \l_tmpa_prop`
`\g_tmpa_prop` 9091 `\prop_new:N \l_tmpb_prop`
`\g_tmpb_prop` 9092 `\prop_new:N \g_tmpa_prop`
9093 `\prop_new:N \g_tmpb_prop`

(End definition for `\l_tmpa_prop` and others. These variables are documented on page 137.)

`\prop_set_from_keyval:Nn` Loop through items separated by commas, with `\q_mark` to avoid losing braces. After
`\prop_set_from_keyval:cN` checking for termination, split the item at the first then at the second = (which ought
`\prop_gset_from_keyval:Nn` to be the first of the trailing =). At both splits, trim spaces and call `__prop_from_`
`\prop_gset_from_keyval:cN` `keyval_key:w`, then `__prop_from_keyval_value:w`, followed by the trimmed material,
`\prop_const_from_keyval:Nn` `\q_nil`, the subsequent part of the item, and the trailing =’s and `\q_stop`. After finding
`\prop_const_from_keyval:cN` the `<key>` just store it after `\q_stop`. After finding the `<value>` ignore completely empty
`__prop_from_keyval:n` items (both trailing = were used as delimiters and all parts are empty); if the remaining
`__prop_from_keyval_loop:w` part #2 consists exactly of the second trailing = (namely there was exactly one = in the
`__prop_from_keyval_split:Nw` item) then output one key–value pair for the property list; otherwise complain about a
`__prop_from_keyval_key:n` missing or extra =.
`__prop_from_keyval_key:w` 9094 `\cs_new_protected:Npn \prop_set_from_keyval:Nn #1#2`
`__prop_from_keyval_value:n` 9095 `{ \tl_set:Nx #1 { __prop_from_keyval:n {#2} } }`
`__prop_from_keyval_value:w` 9096 `\cs_generate_variant:Nn \prop_set_from_keyval:Nn { c }`
9097 `\cs_new_protected:Npn \prop_gset_from_keyval:Nn #1#2`
9098 `{ \tl_gset:Nx #1 { __prop_from_keyval:n {#2} } }`
9099 `\cs_generate_variant:Nn \prop_gset_from_keyval:Nn { c }`
9100 `\cs_new_protected:Npn \prop_const_from_keyval:Nn #1#2`
9101 `{ \tl_const:Nx #1 { __prop_from_keyval:n {#2} } }`
9102 `\cs_generate_variant:Nn \prop_const_from_keyval:Nn { c }`
9103 `\cs_new:Npn __prop_from_keyval:n #1`

```

9104 {
9105   \s__prop
9106   \__prop_from_keyval_loop:w \q_mark #1 ,
9107   \q_recursion_tail , \q_recursion_stop
9108 }
9109 \cs_new:Npn \__prop_from_keyval_loop:w #1 ,
9110 {
9111   \quark_if_recursion_tail_stop:o { \use_none:n #1 }
9112   \__prop_from_keyval_split:Nw \__prop_from_keyval_key:n
9113   #1 = = \q_stop { \use_none:n #1 }
9114   \__prop_from_keyval_loop:w \q_mark
9115 }
9116 \cs_new:Npn \__prop_from_keyval_split:Nw #1#2 =
9117 {
9118   \tl_trim_spaces_apply:oN { \use_none:n #2 } #1
9119   \q_nil
9120 }
9121 \cs_new:Npn \__prop_from_keyval_key:n #1
9122 { \__prop_from_keyval_key:w #1 }
9123 \cs_new:Npn \__prop_from_keyval_key:w #1 \q_nil #2 \q_stop
9124 {
9125   \__prop_from_keyval_split:Nw \__prop_from_keyval_value:n
9126   \q_mark #2 \q_stop {#1}
9127 }
9128 \cs_new:Npn \__prop_from_keyval_value:n #1
9129 { \__prop_from_keyval_value:w #1 }
9130 \cs_new:Npn \__prop_from_keyval_value:w #1 \q_nil #2 \q_stop #3#4
9131 {
9132   \tl_if_empty:nF { #3 #1 #2 }
9133   {
9134     \str_if_eq:nnTF {#2} { = }
9135     {
9136       \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
9137       \s__prop { \exp_not:n {#1} }
9138     }
9139     {
9140       \__kernel_msg_expandable_error:nnf
9141       { kernel } { prop-keyval }
9142       { \exp_after:wN \exp_stop_f: #4 }
9143     }
9144   }
9145 }

```

(End definition for `\prop_set_from_keyval:Nn` and others. These functions are documented on page 247.)

16.2 Accessing data in property lists

```

\__prop_split:NnTF
\__prop_split_aux:NnTF
\__prop_split_aux:w

```

This function is used by most of the module, and hence must be fast. It receives a *property list*, a *key*, a *true code* and a *false code*. The aim is to split the *property list* at the given *key* into the *extract₁* before the key–value pair, the *value* associated with the *key* and the *extract₂* after the key–value pair. This is done using a delimited function, whose definition is as follows, where the *key* is turned into a string.

```

\cs_set:Npn \__prop_split_aux:w #1
\__prop_pair:wn <key> \s__prop #2
#3 \q_mark #4 #5 \q_stop
{ #4 {<true code>} {<false code>}}

```

If the *<key>* is present in the property list, *__prop_split_aux:w*'s #1 is the part before the *<key>*, #2 is the *<value>*, #3 is the part after the *<key>*, #4 is *\use_i:nn*, and #5 is additional tokens that we do not care about. The *<true code>* is left in the input stream, and can use the parameters #1, #2, #3 for the three parts of the property list as desired. Namely, the original property list is in this case #1 *__prop_pair:wn <key> \s__prop {#2} #3*.

If the *<key>* is not there, then the *<function>* is *\use_ii:nn*, which keeps the *<false code>*.

```

9146 \cs_new_protected:Npn \__prop_split:NnTF #1#2
9147 { \exp_args:NNo \__prop_split_aux:NnTF #1 { \tl_to_str:n {#2} } }
9148 \cs_new_protected:Npn \__prop_split_aux:NnTF #1#2#3#4
9149 {
9150   \cs_set:Npn \__prop_split_aux:w ##1
9151     \__prop_pair:wn #2 \s__prop ##2 ##3 \q_mark ##4 ##5 \q_stop
9152     { ##4 {#3} {#4} }
9153   \exp_after:wN \__prop_split_aux:w #1 \q_mark \use_i:nn
9154   \__prop_pair:wn #2 \s__prop { } \q_mark \use_ii:nn \q_stop
9155 }
9156 \cs_new:Npn \__prop_split_aux:w { }

```

(End definition for *__prop_split:NnTF*, *__prop_split_aux:NnTF*, and *__prop_split_aux:w*.)

\prop_remove:Nn Deleting from a property starts by splitting the list. If the key is present in the property list, the returned value is ignored. If the key is missing, nothing happens.

```

\prop_remove:NV
\prop_remove:cn
\prop_remove:cV
\prop_gremove:Nn
\prop_gremove:NV
\prop_gremove:cn
\prop_gremove:cV
9157 \cs_new_protected:Npn \prop_remove:Nn #1#2
9158 {
9159   \__prop_split:NnTF #1 {#2}
9160   { \tl_set:Nn #1 { ##1 ##3 } }
9161   { }
9162 }
9163 \cs_new_protected:Npn \prop_gremove:Nn #1#2
9164 {
9165   \__prop_split:NnTF #1 {#2}
9166   { \tl_gset:Nn #1 { ##1 ##3 } }
9167   { }
9168 }
9169 \cs_generate_variant:Nn \prop_remove:Nn { NV }
9170 \cs_generate_variant:Nn \prop_remove:Nn { c , cV }
9171 \cs_generate_variant:Nn \prop_gremove:Nn { NV }
9172 \cs_generate_variant:Nn \prop_gremove:Nn { c , cV }

```

(End definition for *\prop_remove:Nn* and *\prop_gremove:Nn*. These functions are documented on page 134.)

\prop_get:NnN Getting an item from a list is very easy: after splitting, if the key is in the property list, just set the token list variable to the return value, otherwise to *\q_no_value*.

```

\prop_get:NVN
\prop_get:NoN
\prop_get:cnN
\prop_get:cVN
\prop_get:coN
9173 \cs_new_protected:Npn \prop_get:NnN #1#2#3
9174 {

```

```

9175     \__prop_split:NnTF #1 {#2}
9176     { \tl_set:Nn #3 {##2} }
9177     { \tl_set:Nn #3 { \q_no_value } }
9178   }
9179 \cs_generate_variant:Nn \prop_get:NnN { NV , No }
9180 \cs_generate_variant:Nn \prop_get:NnN { c , cV , co }

```

(End definition for `\prop_get:NnN`. This function is documented on page 133.)

`\prop_pop:NnN` Popping a value also starts by doing the split. If the key is present, save the value in the token list and update the property list as when deleting. If the key is missing, save `\q_no_value` in the token list.

`\prop_pop:NoN`

`\prop_pop:cnN`

`\prop_pop:coN`

```

9181 \cs_new_protected:Npn \prop_pop:NnN #1#2#3
9182 {
9183   \__prop_split:NnTF #1 {#2}
9184   {
9185     \tl_set:Nn #3 {##2}
9186     \tl_set:Nn #1 { ##1 ##3 }
9187   }
9188   { \tl_set:Nn #3 { \q_no_value } }
9189 }
9190 \cs_new_protected:Npn \prop_gpop:NnN #1#2#3
9191 {
9192   \__prop_split:NnTF #1 {#2}
9193   {
9194     \tl_set:Nn #3 {##2}
9195     \tl_gset:Nn #1 { ##1 ##3 }
9196   }
9197   { \tl_set:Nn #3 { \q_no_value } }
9198 }
9199 \cs_generate_variant:Nn \prop_pop:NnN { No }
9200 \cs_generate_variant:Nn \prop_pop:NnN { c , co }
9201 \cs_generate_variant:Nn \prop_gpop:NnN { No }
9202 \cs_generate_variant:Nn \prop_gpop:NnN { c , co }

```

(End definition for `\prop_pop:NnN` and `\prop_gpop:NnN`. These functions are documented on page 133.)

`\prop_item:Nn` Getting the value corresponding to a key in a property list in an expandable fashion is similar to mapping some tokens. Go through the property list one $\langle key \rangle$ – $\langle value \rangle$ pair at a time: the arguments of `__prop_item_Nn:nwn` are the $\langle key \rangle$ we are looking for, a $\langle key \rangle$ of the property list, and its associated value. The $\langle keys \rangle$ are compared (as strings). If they match, the $\langle value \rangle$ is returned, within `\exp_not:n`. The loop terminates even if the $\langle key \rangle$ is missing, and yields an empty value, because we have appended the appropriate $\langle key \rangle$ – $\langle empty\ value \rangle$ pair to the property list.

```

9203 \cs_new:Npn \prop_item:Nn #1#2
9204 {
9205   \exp_last_unbraced:Noo \__prop_item_Nn:nwn { \tl_to_str:n {#2} } #1
9206   \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
9207   \prg_break_point:
9208 }
9209 \cs_new:Npn \__prop_item_Nn:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
9210 {
9211   \str_if_eq:eeTF {#1} {#3}
9212   { \prg_break:n { \exp_not:n {#4} } }

```

```

9213     { \_prop_item:Nn:nwn {#1} }
9214   }
9215 \cs_generate_variant:Nn \prop_item:Nn { c }

```

(End definition for `\prop_item:Nn` and `_prop_item:Nn:nwn`. This function is documented on page 134.)

`\prop_pop:NnTF` Popping an item from a property list, keeping track of whether the key was present or not, is implemented as a conditional. If the key was missing, neither the property list, nor the token list are altered. Otherwise, `\prg_return_true:` is used after the assignments.
`\prop_gpop:NnTF`
`\prop_gpop:cnTF`

```

9216 \prg_new_protected_conditional:Npnn \prop_pop:NnN #1#2#3 { T , F , TF }
9217 {
9218   \__prop_split:NnTF #1 {#2}
9219   {
9220     \tl_set:Nn #3 {##2}
9221     \tl_set:Nn #1 { ##1 ##3 }
9222     \prg_return_true:
9223   }
9224   { \prg_return_false: }
9225 }
9226 \prg_new_protected_conditional:Npnn \prop_gpop:NnN #1#2#3 { T , F , TF }
9227 {
9228   \__prop_split:NnTF #1 {#2}
9229   {
9230     \tl_set:Nn #3 {##2}
9231     \tl_gset:Nn #1 { ##1 ##3 }
9232     \prg_return_true:
9233   }
9234   { \prg_return_false: }
9235 }
9236 \prg_generate_conditional_variant:Nnn \prop_pop:NnN { c } { T , F , TF }
9237 \prg_generate_conditional_variant:Nnn \prop_gpop:NnN { c } { T , F , TF }

```

(End definition for `\prop_pop:NnTF` and `\prop_gpop:NnTF`. These functions are documented on page 135.)

`\prop_put:Nnn` Since the branches of `__prop_split:NnTF` are used as the replacement text of an internal macro, and since the `<key>` and new `<value>` may contain arbitrary tokens, it is not safe to include them in the argument of `__prop_split:NnTF`. We thus start by storing in `\l__prop_internal_tl` tokens which (after x-expansion) encode the key–value pair. This variable can safely be used in `__prop_split:NnTF`. If the `<key>` was absent, append the new key–value to the list. Otherwise concatenate the extracts `##1` and `##3` with the new key–value pair `\l__prop_internal_tl`. The updated entry is placed at the same spot as the original `<key>` in the property list, preserving the order of entries.

```

9238 \cs_new_protected:Npn \prop_put:Nnn { \__prop_put:Nnnn \tl_set:Nx }
9239 \cs_new_protected:Npn \prop_gput:Nnn { \__prop_put:Nnnn \tl_gset:Nx }
9240 \cs_new_protected:Npn \__prop_put:Nnnn #1#2#3#4
9241 {
9242   \tl_set:Nn \l__prop_internal_tl
9243   {
9244     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
9245     \s__prop { \exp_not:n {#4} }
9246   }
9247   \__prop_split:NnTF #2 {#3}

```

`\prop_gput:Nnn`
`\prop_gput:NnV`
`\prop_gput:Nno`
`\prop_gput:Nnx`
`\prop_gput:Nvn`
`\prop_gput:Nvv`
`\prop_gput:Nnon`
`\prop_gput:Noo`
`\prop_gput:cnn`
`\prop_gput:cnV`
`\prop_gput:cno`

```

9248     { #1 #2 { \exp_not:n {##1} \l__prop_internal_tl \exp_not:n {##3} } }
9249     { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
9250   }
9251   \cs_generate_variant:Nn \prop_put:Nnn
9252   { NnV , Nno , Nnx , NV , NVV , No , Noo }
9253   \cs_generate_variant:Nn \prop_put:Nnn
9254   { c , cnV , cno , cnx , cV , cVV , co , coo }
9255   \cs_generate_variant:Nn \prop_gput:Nnn
9256   { NnV , Nno , Nnx , NV , NVV , No , Noo }
9257   \cs_generate_variant:Nn \prop_gput:Nnn
9258   { c , cnV , cno , cnx , cV , cVV , co , coo }

```

(End definition for `\prop_put:Nnn`, `\prop_gput:Nnn`, and `__prop_put:NNnn`. These functions are documented on page 133.)

```

\prop_put_if_new:Nnn Adding conditionally also splits. If the key is already present, the three brace groups
\prop_put_if_new:cnn given by \__prop_split:NnTF are removed. If the key is new, then the value is added,
\prop_gput_if_new:Nnn being careful to convert the key to a string using \tl_to_str:n.
\prop_gput_if_new:cnn
\__prop_put_if_new:NNnn
9259 \cs_new_protected:Npn \prop_put_if_new:Nnn
9260 { \__prop_put_if_new:NNnn \tl_set:Nx }
9261 \cs_new_protected:Npn \prop_gput_if_new:Nnn
9262 { \__prop_put_if_new:NNnn \tl_gset:Nx }
9263 \cs_new_protected:Npn \__prop_put_if_new:NNnn #1#2#3#4
9264 {
9265   \tl_set:Nn \l__prop_internal_tl
9266   {
9267     \exp_not:N \__prop_pair:wn \tl_to_str:n {#3}
9268     \s__prop \exp_not:n { {#4} }
9269   }
9270   \__prop_split:NnTF #2 {#3}
9271   { }
9272   { #1 #2 { \exp_not:o {#2} \l__prop_internal_tl } }
9273 }
9274 \cs_generate_variant:Nn \prop_put_if_new:Nnn { c }
9275 \cs_generate_variant:Nn \prop_gput_if_new:Nnn { c }

```

(End definition for `\prop_put_if_new:Nnn`, `\prop_gput_if_new:Nnn`, and `__prop_put_if_new:NNnn`. These functions are documented on page 133.)

16.3 Property list conditionals

```

\prop_if_exist_p:N Copies of the cs functions defined in l3basics.
\prop_if_exist_p:c
\prop_if_exist:NTF
9276 \prg_new_eq_conditional:NNn \prop_if_exist:N \cs_if_exist:N
9277 { TF , T , F , p }
\prop_if_exist:cTF
9278 \prg_new_eq_conditional:NNn \prop_if_exist:c \cs_if_exist:c
9279 { TF , T , F , p }

```

(End definition for `\prop_if_exist:NTF`. This function is documented on page 134.)

```

\prop_if_empty_p:N Same test as for token lists.
\prop_if_empty_p:c
\prop_if_empty:NTF
9280 \prg_new_conditional:Npnn \prop_if_empty:N #1 { p , T , F , TF }
9281 {
9282   \tl_if_eq:NNTF #1 \c_empty_prop
9283   \prg_return_true: \prg_return_false:

```

```

9284 }
9285 \prg_generate_conditional_variant:Nnn \prop_if_empty:N
9286 { c } { p , T , F , TF }

```

(End definition for `\prop_if_empty:N`. This function is documented on page 134.)

```

\prop_if_in_p:Nn Testing expandably if a key is in a property list requires to go through the key–value
\prop_if_in_p:NV pairs one by one. This is rather slow, and a faster test would be
\prop_if_in_p:No
\prop_if_in_p:cn \prg_new_protected_conditional:Npnn \prop_if_in:Nn #1 #2
\prop_if_in_p:cV {
\prop_if_in_p:co @@_split:NnTF #1 {#2}
\prop_if_in:NnTF { \prg_return_true: }
\prop_if_in:NVTF { \prg_return_false: }
\prop_if_in:NoTF }
\prop_if_in:cnTF
\prop_if_in:cVTF
\prop_if_in:coTF
\__prop_if_in:nwwn
\__prop_if_in:N

```

but `__prop_split:NnTF` is non-expandable.

Instead, the key is compared to each key in turn using `\str_if_eq:ee`, which is expandable. To terminate the mapping, we append to the property list the key that is searched for. This second `\tl_to_str:n` is not expanded at the start, but only when included in the `\str_if_eq:ee`. It cannot make the breaking mechanism choke, because the arbitrary token list material is enclosed in braces. The second argument of `__prop_if_in:nwwn` is most often empty. When the *key* is found in the list, `__prop_if_in:N` receives `__prop_pair:wn`, and if it is found as the extra item, the function receives `\q_recursion_tail`, easily recognizable.

Here, `\prop_map_function:NN` is not sufficient for the mapping, since it can only map a single token, and cannot carry the key that is searched for.

```

9287 \prg_new_conditional:Npnn \prop_if_in:Nn #1#2 { p , T , F , TF }
9288 {
9289   \exp_last_unbraced:Noo \__prop_if_in:nwwn { \tl_to_str:n {#2} } #1
9290   \__prop_pair:wn \tl_to_str:n {#2} \s__prop { }
9291   \q_recursion_tail
9292   \prg_break_point:
9293 }
9294 \cs_new:Npn \__prop_if_in:nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
9295 {
9296   \str_if_eq:eeTF {#1} {#3}
9297   { \__prop_if_in:N }
9298   { \__prop_if_in:nwwn {#1} }
9299 }
9300 \cs_new:Npn \__prop_if_in:N #1
9301 {
9302   \if_meaning:w \q_recursion_tail #1
9303   \prg_return_false:
9304   \else:
9305     \prg_return_true:
9306   \fi:
9307   \prg_break:
9308 }
9309 \prg_generate_conditional_variant:Nnn \prop_if_in:Nn
9310 { NV , No , c , cV , co } { p , T , F , TF }

```

(End definition for `\prop_if_in:NnTF`, `__prop_if_in:nwwn`, and `__prop_if_in:N`. This function is documented on page 134.)

16.4 Recovering values from property lists with branching

`\prop_get:NnTF` Getting the value corresponding to a key, keeping track of whether the key was present or not, is implemented as a conditional (with side effects). If the key was absent, the token list is not altered.

```

\prop_get:NnTF
\prop_get:NVNTF
\prop_get:NoNTF
\prop_get:cnNTF
\prop_get:cVNTF
\prop_get:coNTF
9311 \prg_new_protected_conditional:Npnn \prop_get:NnN #1#2#3 { T , F , TF }
9312 {
9313   \__prop_split:NnTF #1 {#2}
9314   {
9315     \tl_set:Nn #3 {##2}
9316     \prg_return_true:
9317   }
9318   { \prg_return_false: }
9319 }
9320 \prg_generate_conditional_variant:Nnn \prop_get:NnN
9321 { NV , No , c , cV , co } { T , F , TF }

```

(End definition for `\prop_get:NnTF`. This function is documented on page 135.)

16.5 Mapping to property lists

The argument delimited by `__prop_pair:wn` is empty except at the end of the loop where it is `\prg_break:.` No need for any quark test.

```

\prop_map_function:NN
\prop_map_function:Nc
\prop_map_function:cN
\prop_map_function:cc
\__prop_map_function:Nwwn
9322 \cs_new:Npn \prop_map_function:NN #1#2
9323 {
9324   \exp_after:wN \use_i_ii:nnn
9325   \exp_after:wN \__prop_map_function:Nwwn
9326   \exp_after:wN #2
9327   #1
9328   \prg_break: \__prop_pair:wn \s__prop { } \prg_break_point:
9329   \prg_break_point:Nn \prop_map_break: { }
9330 }
9331 \cs_new:Npn \__prop_map_function:Nwwn #1#2 \__prop_pair:wn #3 \s__prop #4
9332 {
9333   #2
9334   #1 {#3} {#4}
9335   \__prop_map_function:Nwwn #1
9336 }
9337 \cs_generate_variant:Nn \prop_map_function:NN { Nc , c , cc }

```

(End definition for `\prop_map_function:NN` and `__prop_map_function:Nwwn`. This function is documented on page 135.)

`\prop_map_inline:Nn` Mapping in line requires a nesting level counter. Store the current definition of `__prop_pair:wn`, and define it anew. At the end of the loop, revert to the earlier definition. Note that besides pairs of the form `__prop_pair:wn <key> \s__prop {<value>}`, there are a leading and a trailing tokens, but both are equal to `\scan_stop:`, hence have no effect in such inline mapping. Such `\scan_stop:` could have affected ligatures if they appeared during the mapping.

```

9338 \cs_new_protected:Npn \prop_map_inline:Nn #1#2
9339 {
9340   \cs_gset_eq:cN
9341   { \__prop_map_ \int_use:N \g__kernel_prg_map_int :wn } \__prop_pair:wn
9342   \int_gincr:N \g__kernel_prg_map_int

```

```

9343 \cs_gset_protected:Npn \__prop_pair:wn ##1 \s__prop ##2 {#2}
9344 #1
9345 \prg_break_point:Nn \prop_map_break:
9346 {
9347   \int_gdecr:N \g__kernel_prg_map_int
9348   \cs_gset_eq:Nc \__prop_pair:wn
9349     { __prop_map_ \int_use:N \g__kernel_prg_map_int :wn }
9350 }
9351 }
9352 \cs_generate_variant:Nn \prop_map_inline:Nn { c }

```

(End definition for `\prop_map_inline:Nn`. This function is documented on page 135.)

`\prop_map_break:` The break statements are based on the general `\prg_map_break:Nn`.
`\prop_map_break:n`

```

9353 \cs_new:Npn \prop_map_break:
9354   { \prg_map_break:Nn \prop_map_break: { } }
9355 \cs_new:Npn \prop_map_break:n
9356   { \prg_map_break:Nn \prop_map_break: }

```

(End definition for `\prop_map_break:` and `\prop_map_break:n`. These functions are documented on page 136.)

16.6 Viewing property lists

`\prop_show:N` Apply the general `__kernel_chk_defined:NT` and `\msg_show:nnnnnn`. Contrarily to sequences and comma lists, we use `\msg_show_item:nn` to format both the key and the value for each pair.

```

\prop_log:N
\prop_log:c
9357 \cs_new_protected:Npn \prop_show:N { \__prop_show:NN \msg_show:nnxxxx }
9358 \cs_generate_variant:Nn \prop_show:N { c }
9359 \cs_new_protected:Npn \prop_log:N { \__prop_show:NN \msg_log:nnxxxx }
9360 \cs_generate_variant:Nn \prop_log:N { c }
9361 \cs_new_protected:Npn \__prop_show:NN #1#2
9362 {
9363   \__kernel_chk_defined:NT #2
9364   {
9365     #1 { LaTeX/kernel } { show-prop }
9366     { \token_to_str:N #2 }
9367     { \prop_map_function:NN #2 \msg_show_item:nn }
9368     { } { }
9369   }
9370 }

```

(End definition for `\prop_show:N` and `\prop_log:N`. These functions are documented on page 136.)

```

9371 </initex | package>

```

17 l3msg implementation

```

9372 <*initex | package>
9373 <@@=msg>

```

`\l__msg_tmp_tl` A general scratch for the module.

```

9374 \tl_new:N \l__msg_tmp_tl

```

(End definition for \l__msg_tmp_tl.)

\l__msg_name_str Used to save module info when creating messages.

```
\l__msg_text_str 9375 \str_new:N \l__msg_name_str
9376 \str_new:N \l__msg_text_str
```

(End definition for \l__msg_name_str and \l__msg_text_str.)

17.1 Creating messages

Messages are created and used separately, so there two parts to the code here. First, a mechanism for creating message text. This is pretty simple, as there is not actually a lot to do.

\c__msg_text_prefix_tl Locations for the text of messages.

```
\c__msg_more_text_prefix_tl 9377 \tl_const:Nn \c__msg_text_prefix_tl { msg~text~>~ }
9378 \tl_const:Nn \c__msg_more_text_prefix_tl { msg~extra~text~>~ }
```

(End definition for \c__msg_text_prefix_tl and \c__msg_more_text_prefix_tl.)

\msg_if_exist_p:nn Test whether the control sequence containing the message text exists or not.

```
\msg_if_exist:nnTF 9379 \prg_new_conditional:Npnn \msg_if_exist:nn #1#2 { p , T , F , TF }
9380 {
9381   \cs_if_exist:cTF { \c__msg_text_prefix_tl #1 / #2 }
9382   { \prg_return_true: } { \prg_return_false: }
9383 }
```

(End definition for \msg_if_exist:nnTF. This function is documented on page 139.)

__msg_chk_if_free:nn This auxiliary is similar to __kernel_chk_if_free_cs:N, and is used when defining messages with \msg_new:nnnn.

```
9384 \__kernel_patch:nnNNpn { }
9385 {
9386   \__kernel_debug_log:x
9387   { Defining~message~ #1 / #2 ~\msg_line_context: }
9388 }
9389 \cs_new_protected:Npn \__msg_chk_free:nn #1#2
9390 {
9391   \msg_if_exist:nnT {#1} {#2}
9392   {
9393     \__kernel_msg_error:nxxx { kernel } { message-already-defined }
9394     {#1} {#2}
9395   }
9396 }
```

(End definition for __msg_chk_if_free:nn.)

\msg_new:nnnn Setting a message simply means saving the appropriate text into two functions. A sanity check first.

```
\msg_new:nnn 9397 \cs_new_protected:Npn \msg_new:nnnn #1#2
\msg_gset:nnnn 9398 {
\msg_set:nnnn 9399   \__msg_chk_free:nn {#1} {#2}
\msg_set:nnnn 9400   \msg_gset:nnnn {#1} {#2}
\msg_set:nnn 9401 }
```

```

9402 \cs_new_protected:Npn \msg_new:nnn #1#2#3
9403 { \msg_new:nnnn {#1} {#2} {#3} { } }
9404 \cs_new_protected:Npn \msg_set:nnnn #1#2#3#4
9405 {
9406   \cs_set:cpn { \c__msg_text_prefix_tl #1 / #2 }
9407     ##1##2##3##4 {#3}
9408   \cs_set:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
9409     ##1##2##3##4 {#4}
9410 }
9411 \cs_new_protected:Npn \msg_set:nnn #1#2#3
9412 { \msg_set:nnnn {#1} {#2} {#3} { } }
9413 \cs_new_protected:Npn \msg_gset:nnnn #1#2#3#4
9414 {
9415   \cs_gset:cpn { \c__msg_text_prefix_tl #1 / #2 }
9416     ##1##2##3##4 {#3}
9417   \cs_gset:cpn { \c__msg_more_text_prefix_tl #1 / #2 }
9418     ##1##2##3##4 {#4}
9419 }
9420 \cs_new_protected:Npn \msg_gset:nnn #1#2#3
9421 { \msg_gset:nnnn {#1} {#2} {#3} { } }

```

(End definition for `\msg_new:nnnn` and others. These functions are documented on page [138](#).)

17.2 Messages: support functions and text

```

\c__msg_coding_error_text_tl Simple pieces of text for messages.
\c__msg_continue_text_tl
\c__msg_critical_text_tl
\c__msg_fatal_text_tl
\c__msg_help_text_tl
\c__msg_no_info_text_tl
\c__msg_on_line_text_tl
\c__msg_return_text_tl
\c__msg_trouble_text_tl
9422 \tl_const:Nn \c__msg_coding_error_text_tl
9423 {
9424   This~is~a~coding~error.
9425   \\ \\
9426 }
9427 \tl_const:Nn \c__msg_continue_text_tl
9428 { Type~<return>~to~continue }
9429 \tl_const:Nn \c__msg_critical_text_tl
9430 { Reading~the~current~file~'\g_file_curr_name_str'~will~stop. }
9431 \tl_const:Nn \c__msg_fatal_text_tl
9432 { This~is~a~fatal~error:~LaTeX~will~abort. }
9433 \tl_const:Nn \c__msg_help_text_tl
9434 { For~immediate~help~type~H~<return> }
9435 \tl_const:Nn \c__msg_no_info_text_tl
9436 {
9437   LaTeX~does~not~know~anything~more~about~this~error,~sorry.
9438   \c__msg_return_text_tl
9439 }
9440 \tl_const:Nn \c__msg_on_line_text_tl { on~line }
9441 \tl_const:Nn \c__msg_return_text_tl
9442 {
9443   \\ \\
9444   Try~typing~<return>~to~proceed.
9445   \\
9446   If~that~doesn't~work,~type~X~<return>~to~quit.
9447 }
9448 \tl_const:Nn \c__msg_trouble_text_tl
9449 {

```

```

9450    \\\ \\\
9451    More~errors~will~almost~certainly~follow: \\\
9452    the~LaTeX~run~should~be~aborted.
9453  }

```

(End definition for `\c_msg_coding_error_text_tl` and others.)

`\msg_line_number:` For writing the line number nicely. `\msg_line_context:` was set up earlier, so this is not new.

```

9454 \cs_new:Npn \msg_line_number: { \int_use:N \tex_inputlineno:D }
9455 \cs_gset:Npn \msg_line_context:
9456 {
9457   \c_msg_on_line_text_tl
9458   \c_space_tl
9459   \msg_line_number:
9460 }

```

(End definition for `\msg_line_number:` and `\msg_line_context:`. These functions are documented on page 139.)

17.3 Showing messages: low level mechanism

`_msg_interrupt:Nnnn` The low-level interruption macro is rather opaque, unfortunately. Depending on the availability of more information there is a choice of how to set up the further help. We feed the extra help text and the message itself to a wrapping auxiliary, in this order because we must first setup TeX's `\errhelp` register before issuing an `\errmessage`.

```

9461 \cs_new_protected:Npn \_msg_interrupt:Nnnn #1#2#3#4
9462 {
9463   \str_set:Nx \l__msg_text_str { #1 {#2} }
9464   \str_set:Nx \l__msg_name_str { \msg_module_name:n {#2} }
9465   \tl_if_empty:nTF {#4}
9466   {
9467     \_msg_interrupt_wrap:nnn {#3}
9468     { \c_msg_continue_text_tl }
9469     { \c_msg_no_info_text_tl }
9470   }
9471   {
9472     \_msg_interrupt_wrap:nnn {#3}
9473     { \c_msg_help_text_tl }
9474     {#4}
9475   }
9476 }

```

(End definition for `_msg_interrupt:Nnnn`.)

`_msg_interrupt_wrap:nnn` First setup TeX's `\errhelp` register with the extra help #1, then build a nice-looking error message with #2. Everything is done using x-type expansion as the new line markers are different for the two type of text and need to be correctly set up. The auxiliary `_msg_interrupt_more_text:n` receives its argument as a line-wrapped string, which is thus unaffected by expansion. We have to split the main text into two parts as only the “message” itself is wrapped with a leader: the generic help is wrapped at full width. We also have to allow for the two characters used by `\errmessage` itself.

```

9477 \cs_new_protected:Npn \_msg_interrupt_wrap:nnn #1#2#3
9478 {

```

```

9479 \iow_wrap:nnnN { \ \ #3 } { } { } \_msg_interrupt_more_text:n
9480 \group_begin:
9481 \int_sub:Nn \l_iow_line_count_int { 2 }
9482 \iow_wrap:nxnN { \l__msg_text_str : ~ #1 }
9483 {
9484   ( \l__msg_name_str )
9485   \prg_replicate:nn
9486   {
9487     \str_count:N \l__msg_text_str
9488     - \str_count:N \l__msg_name_str
9489     + 2
9490   }
9491   { ~ }
9492 }
9493 { } \_msg_interrupt_text:n
9494 \iow_wrap:nnnN { \l__msg_tmp_tl \ \ \ #2 } { } { }
9495 \_msg_interrupt:n
9496 }
9497 \cs_new_protected:Npn \_msg_interrupt_text:n #1
9498 {
9499   \group_end:
9500   \tl_set:Nn \l__msg_tmp_tl {#1}
9501 }
9502 \cs_new_protected:Npn \_msg_interrupt_more_text:n #1
9503 { \exp_args:Nx \tex_errhelp:D { #1 \iow_newline: } }

```

(End definition for `_msg_interrupt_wrap:nnn`, `_msg_interrupt_text:n`, and `_msg_interrupt_more_text:n`.)

`_msg_interrupt:n` The business end of the process starts by producing some visual separation of the message from the main part of the log. The error message needs to be printed with everything made “invisible”: T_EX’s own information involves the macro in which `\errmessage` is called, and the end of the argument of the `\errmessage`, including the closing brace. We use an active `!` to call the `\errmessage` primitive, and end its argument with `\use_none:n {<spaces>}` which fills the output with spaces. Two trailing closing braces are turned into spaces to hide them as well. The group in which we alter the definition of the active `!` is closed before producing the message: this ensures that tokens inserted by typing `I` in the command-line are inserted after the message is entirely cleaned up.

The `__kernel_iow_with:Nnn` auxiliary, defined in `l3file`, expects an *<integer variable>*, an integer *<value>*, and some *<code>*. It runs the *<code>* after ensuring that the *<integer variable>* takes the given *<value>*, then restores the former value of the *<integer variable>* if needed. We use it to ensure that the `\newlinechar` is 10, as needed for `\iow_newline:` to work, and that `\errorcontextlines` is `-1`, to avoid showing irrelevant context. Note that restoring the former value of these integers requires inserting tokens after the `\errmessage`, which goes in the way of tokens which could be inserted by the user. This is unavoidable.

```

9504 \group_begin:
9505   \char_set_lccode:nn { 38 } { 32 } % &
9506   \char_set_lccode:nn { 46 } { 32 } % .
9507   \char_set_lccode:nn { 123 } { 32 } % {
9508   \char_set_lccode:nn { 125 } { 32 } % }
9509   \char_set_catcode_active:N \&
9510 \tex_lowercase:D

```

```

9511 {
9512   \group_end:
9513   \cs_new_protected:Npn \__msg_interrupt:n #1
9514   {
9515     \iow_term:n { }
9516     \__kernel_iow_with:Nnn \tex_newlinechar:D { ‘^^J }
9517     {
9518       \__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }
9519       {
9520         \group_begin:
9521         \cs_set_protected:Npn &
9522         {
9523           \tex_errmessage:D
9524           {
9525             #1
9526             \use_none:n
9527             { ..... }
9528           }
9529         }
9530         \exp_after:wN
9531         \group_end:
9532         &
9533       }
9534     }
9535   }
9536 }

```

(End definition for __msg_interrupt:n.)

17.4 Displaying messages

L^AT_EX is handling error messages and so the T_EX ones are disabled. This is already done by the L^AT_EX 2_ε kernel, so to avoid messing up any deliberate change by a user this is only set in format mode.

```

9537 \*initex
9538 \int_gset:Nn \tex_errorcontextlines:D { -1 }
9539 \</initex

```

\msg_fatal_text:n A function for issuing messages: both the text and order could in principle vary. The module name may be empty for kernel messages, hence the slightly contorted code path for a space.

```

\msg_critical_text:n
\msg_error_text:n
\msg_warning_text:n
\msg_info_text:n
\__msg_text:nn
\__msg_text:n
9540 \cs_new:Npn \msg_fatal_text:n #1
9541 {
9542   Fatal ~
9543   \msg_error_text:n {#1}
9544 }
9545 \cs_new:Npn \msg_critical_text:n #1
9546 {
9547   Critical ~
9548   \msg_error_text:n {#1}
9549 }
9550 \cs_new:Npn \msg_error_text:n #1
9551 { \__msg_text:nn {#1} { Error } }

```

```

9552 \cs_new:Npn \msg_warning_text:n #1
9553 { \__msg_text:nn {#1} { Warning } }
9554 \cs_new:Npn \msg_info_text:n #1
9555 { \__msg_text:nn {#1} { Info } }
9556 \cs_new:Npn \__msg_text:nn #1#2
9557 {
9558   \exp_args:Nf \__msg_text:n { \msg_module_type:n {#1} }
9559   \msg_module_name:n {#1} ~
9560   #2
9561 }
9562 \cs_new:Npn \__msg_text:n #1
9563 {
9564   \tl_if_blank:nF {#1}
9565     { #1 ~ }
9566 }

```

(End definition for `\msg_fatal_text:n` and others. These functions are documented on page 139.)

`\g_msg_module_name_prop` For storing public module information: the kernel data is set up in advance.
`\g_msg_module_type_prop`

```

9567 \prop_new:N \g_msg_module_name_prop
9568 \prop_gput:Nnn \g_msg_module_name_prop { LaTeX } { LaTeX3 }
9569 \prop_new:N \g_msg_module_type_prop
9570 \prop_gput:Nnn \g_msg_module_type_prop { LaTeX } { }

```

(End definition for `\g_msg_module_name_prop` and `\g_msg_module_type_prop`. These variables are documented on page 140.)

`\msg_module_type:n` Contextual footer information, with the potential to give modules an alternative name.

```

9571 \cs_new:Npn \msg_module_type:n #1
9572 {
9573   \prop_if_in:NnTF \g_msg_module_type_prop {#1}
9574     { \prop_item:Nn \g_msg_module_type_prop {#1} }
9575   \*initex
9576     { Module }
9577   \*initex
9578   \*package
9579     { Package }
9580   \*package
9581 }

```

(End definition for `\msg_module_type:n`. This function is documented on page 140.)

`\msg_module_name:n` Contextual footer information, with the potential to give modules an alternative name.
`\msg_see_documentation_text:n`

```

9582 \cs_new:Npn \msg_module_name:n #1
9583 {
9584   \prop_if_in:NnTF \g_msg_module_name_prop {#1}
9585     { \prop_item:Nn \g_msg_module_name_prop {#1} }
9586     {#1}
9587 }
9588 \cs_new:Npn \msg_see_documentation_text:n #1
9589 {
9590   See~the~ \msg_module_name:n {#1} ~
9591   documentation~for~further~information.
9592 }

```


(End definition for `\msg_module_name:n` and `\msg_see_documentation_text:n`. These functions are documented on page 140.)

`__msg_class_new:nn`

```

9593 \group_begin:
9594   \cs_set_protected:Npn \__msg_class_new:nn #1#2
9595   {
9596     \prop_new:c { l__msg_redirect_ #1 _prop }
9597     \cs_new_protected:cpn { __msg_ #1 _code:nnnnnn }
9598       ##1##2##3##4##5##6 {#2}
9599     \cs_new_protected:cpn { msg_ #1 :nnnnnn } ##1##2##3##4##5##6
9600     {
9601       \use:x
9602       {
9603         \exp_not:n { \__msg_use:nnnnnn {#1} {##1} {##2} }
9604         { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
9605         { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
9606       }
9607     }
9608     \cs_new_protected:cpx { msg_ #1 :nnnnn } ##1##2##3##4##5
9609     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
9610     \cs_new_protected:cpx { msg_ #1 :nnnn } ##1##2##3##4
9611     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
9612     \cs_new_protected:cpx { msg_ #1 :nnn } ##1##2##3
9613     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
9614     \cs_new_protected:cpx { msg_ #1 :nn } ##1##2
9615     { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} { } { } { } { } }
9616     \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5##6
9617     {
9618       \use:x
9619       {
9620         \exp_not:N \exp_not:n
9621         { \exp_not:c { msg_ #1 :nnnnnn } {##1} {##2} }
9622         {##3} {##4} {##5} {##6}
9623       }
9624     }
9625     \cs_new_protected:cpx { msg_ #1 :nnxxx } ##1##2##3##4##5
9626     { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
9627     \cs_new_protected:cpx { msg_ #1 :nnxx } ##1##2##3##4
9628     { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
9629     \cs_new_protected:cpx { msg_ #1 :nnx } ##1##2##3
9630     { \exp_not:c { msg_ #1 :nnxxxx } {##1} {##2} {##3} { } { } { } }
9631   }

```

(End definition for `__msg_class_new:nn`.)

`\msg_fatal:nnnnnn` For fatal errors, after the error message T_EX bails out.

```

\msg_fatal:nnxxxx 9632 \__msg_class_new:nn { fatal }
\msg_fatal:nnnnn 9633 {
\msg_fatal:nnxxx 9634   \__msg_interrupt:Nnnn
\msg_fatal:nnnn 9635   \msg_fatal_text:n
\msg_fatal:nnxx 9636   {#1}
\msg_fatal:nnn 9637   { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_fatal:nnx 9638   { \c__msg_fatal_text_tl }
\msg_fatal:nn

```

```

9639     \tex_end:D
9640 }

```

(End definition for `\msg_fatal:nnnnnn` and others. These functions are documented on page 141.)

`\msg_critical:nnnnnn` Not quite so bad: just end the current file.

```

\msg_critical:nnxxxx 9641 \__msg_class_new:nn { critical }
\msg_critical:nnnnn 9642 {
\msg_critical:nnxxx 9643   \__msg_interrupt:Nnnn
\msg_critical:nnnn 9644   \msg_critical_text:n
\msg_critical:nnxx 9645   {#1}
\msg_critical:nnn 9646   { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_critical:nnx 9647   { \c__msg_critical_text_tl }
\msg_critical:nn 9648   \tex_endinput:D
9649 }

```

(End definition for `\msg_critical:nnnnnn` and others. These functions are documented on page 141.)

`\msg_error:nnnnnn` For an error, the interrupt routine is called. We check if there is a “more text” by comparing that control sequence with a permanently empty text.

```

\msg_error:nnxxxx 9650 \__msg_class_new:nn { error }
\msg_error:nnxxx 9651 {
\msg_error:nnnnn 9652   \__msg_error:cnnnnn
\msg_error:nnxx 9653   { \c__msg_more_text_prefix_tl #1 / #2 }
\msg_error:nnn 9654   {#3} {#4} {#5} {#6}
\msg_error:nnx 9655   {
\msg_error:nn 9656     \__msg_interrupt:Nnnn
\__msg_error:cnnnnn 9657     \msg_error_text:n
9658     {#1}
9659     { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
9660   }
9661 }
9662 \cs_new_protected:Npn \__msg_error:cnnnnn #1#2#3#4#5#6
9663 {
9664   \cs_if_eq:cNTF {#1} \__msg_no_more_text:nnnn
9665   { #6 { } }
9666   { #6 { \use:c {#1} {#2} {#3} {#4} {#5} } }
9667 }
9668 \cs_new:Npn \__msg_no_more_text:nnnn #1#2#3#4 { }

```

(End definition for `\msg_error:nnnnnn` and others. These functions are documented on page 141.)

`\msg_warning:nnnnnn` Warnings are printed to the terminal.

```

\msg_warning:nnxxxx 9669 \__msg_class_new:nn { warning }
\msg_warning:nnnnn 9670 {
\msg_warning:nnxxx 9671   \str_set:Nx \l__msg_text_str { \msg_warning_text:n {#1} }
\msg_warning:nnnn 9672   \str_set:Nx \l__msg_name_str { \msg_module_name:n {#1} }
\msg_warning:nnxx 9673   \iow_term:n { }
\msg_warning:nnn 9674   \iow_wrap:nxnN
\msg_warning:nnx 9675   {
\msg_warning:nn 9676     \l__msg_text_str : ~
9677     \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
9678   }
9679   {
9680     ( \l__msg_name_str )

```

```

9681         \prg_replicate:nn
9682         {
9683             \str_count:N \l__msg_text_str
9684             - \str_count:N \l__msg_name_str
9685         }
9686         { ~ }
9687     }
9688     { } \iow_term:n
9689     \iow_term:n { }
9690 }

```

(End definition for `\msg_warning:nnnnnn` and others. These functions are documented on page 141.)

```

\msg_info:nnnnnn Information only goes into the log.
\msg_info:nnxxxx 9691  \__msg_class_new:nn { info }
\msg_info:nnnnn 9692  {
\msg_info:nnxxx 9693      \str_set:Nx \l__msg_text_str { \msg_info_text:n {#1} }
\msg_info:nnnn 9694      \str_set:Nx \l__msg_name_str { \msg_module_name:n {#1} }
\msg_info:nnxx 9695      \iow_log:n { }
\msg_info:nnn 9696      \iow_wrap:nxnN
\msg_info:nnx 9697      {
\msg_info:nn 9698          \l__msg_text_str : ~
9699          \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6}
9700      }
9701      {
9702          ( \l__msg_name_str )
9703          \prg_replicate:nn
9704          {
9705              \str_count:N \l__msg_text_str
9706              - \str_count:N \l__msg_name_str
9707          }
9708          { ~ }
9709      }
9710      { } \iow_log:n
9711      \iow_log:n { }
9712  }

```

(End definition for `\msg_info:nnnnnn` and others. These functions are documented on page 142.)

```

\msg_log:nnnnnn “Log” data is very similar to information, but with no extras added.
\msg_log:nnxxxx 9713  \__msg_class_new:nn { log }
\msg_log:nnnnn 9714  {
\msg_log:nnxxx 9715      \iow_wrap:nnnN
\msg_log:nnnn 9716      { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
\msg_log:nnxx 9717      { } { } \iow_log:n
\msg_log:nnn 9718  }

```

(End definition for `\msg_log:nnnnnn` and others. These functions are documented on page 142.)

`\msg_none:nnnnnn` The none message type is needed so that input can be gobbled.

```

\msg_none:nnxxxx 9719  \__msg_class_new:nn { none } { }

```

(End definition for `\msg_none:nnnnnn` and others. These functions are documented on page 142.)

```

\msg_none:nnnnn
\msg_none:nnxx
\msg_none:nnn
\msg_none:nnx
\msg_none:nn

```

`\msg_show:nnnnnn` The `show` message type is used for `\seq_show:N` and similar complicated data structures.
`\msg_show:nnxxxx` Wrap the given text with a trailing dot (important later) then pass it to `__msg_show:n`.
`\msg_show:nnnnn` If there is `\\>~` (or if the whole thing starts with `>~`) we split there, print the first part
`\msg_show:nnxxx` and show the second part using `\showtokens` (the `\exp_after:wN` ensure a nice display).
`\msg_show:nnnn` Note that that primitive adds a leading `>~` and trailing dot. That is why we included a
`\msg_show:nnxx` trailing dot before wrapping and removed it afterwards. If there is no `\\>~` do the same
`\msg_show:nnn` but with an empty second part which adds a spurious but inevitable `>~`.
`\msg_show:nnx`
`\msg_show:nn`
`__msg_show:n`
`__msg_show:w`
`__msg_show_dot:w`
`__msg_show:nn`

```

9720 \__msg_class_new:nn { show }
9721 {
9722   \iow_wrap:nnnN
9723   { \use:c { \c__msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
9724   { } { } \__msg_show:n
9725 }
9726 \cs_new_protected:Npn \__msg_show:n #1
9727 {
9728   \tl_if_in:nnTF { ^^J #1 } { ^^J > ~ }
9729   {
9730     \tl_if_in:nnTF { #1 \q_mark } { . \q_mark }
9731     { \__msg_show_dot:w } { \__msg_show:w }
9732     ^^J #1 \q_stop
9733   }
9734   { \__msg_show:nn { ? #1 } { } }
9735 }
9736 \cs_new:Npn \__msg_show_dot:w #1 ^^J > ~ #2 . \q_stop
9737 { \__msg_show:nn {#1} {#2} }
9738 \cs_new:Npn \__msg_show:w #1 ^^J > ~ #2 \q_stop
9739 { \__msg_show:nn {#1} {#2} }
9740 \cs_new_protected:Npn \__msg_show:nn #1#2
9741 {
9742   \tl_if_empty:nF {#1}
9743   { \exp_args:No \iow_term:n { \use_none:n #1 } }
9744   \tl_set:Nn \l__msg_tmp_tl {#2}
9745   \__kernel_iow_with:Nnn \tex_newlinechar:D { 10 }
9746   {
9747     \__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }
9748     {
9749       \tex_showtokens:D \exp_after:wN \exp_after:wN \exp_after:wN
9750       { \exp_after:wN \l__msg_tmp_tl }
9751     }
9752   }
9753 }

```

(End definition for `\msg_show:nnnnnn` and others. These functions are documented on page 246.)

End the group to eliminate `__msg_class_new:nn`.

```
9754 \group_end:
```

`__msg_class_chk_exist:nT` Checking that a message class exists. We build this from `\cs_if_free:cTF` rather than `\cs_if_exist:cTF` because that avoids reading the second argument earlier than necessary.

```

9755 \cs_new:Npn \__msg_class_chk_exist:nT #1
9756 {
9757   \cs_if_free:cTF { __msg_ #1 _code:nnnnnn }
9758   { \__kernel_msg_error:nnx { kernel } { message-class-unknown } {#1} }

```

```
9759 }
```

(End definition for _msg_class_chk_exist:nT.)

\l__msg_class_tl Support variables needed for the redirection system.

```
\l__msg_current_class_tl 9760 \tl_new:N \l__msg_class_tl
```

```
9761 \tl_new:N \l__msg_current_class_tl
```

(End definition for \l__msg_class_tl and \l__msg_current_class_tl.)

\l__msg_redirect_prop For redirection of individually-named messages

```
9762 \prop_new:N \l__msg_redirect_prop
```

(End definition for \l__msg_redirect_prop.)

\l__msg_hierarchy_seq During redirection, split the message name into a sequence: {/module/submodule}, {/module}, and {}.

```
9763 \seq_new:N \l__msg_hierarchy_seq
```

(End definition for \l__msg_hierarchy_seq.)

\l__msg_class_loop_seq Classes encountered when following redirections to check for loops.

```
9764 \seq_new:N \l__msg_class_loop_seq
```

(End definition for \l__msg_class_loop_seq.)

__msg_use:nnnnnnn

__msg_use_redirect_name:n

__msg_use_hierarchy:nwN

__msg_use_redirect_module:n

__msg_use_code:

Actually using a message is a multi-step process. First, some safety checks on the message and class requested. The code and arguments are then stored to avoid passing them around. The assignment to __msg_use_code: is similar to \tl_set:Nn. The message is eventually produced with whatever \l__msg_class_tl is when __msg_use_code: is called. Here is also a good place to suppress tracing output if the trace package is loaded since all (non-expandable) messages go through this auxiliary.

```
9765 \cs_new_protected:Npn \__msg_use:nnnnnnn #1#2#3#4#5#6#7
```

```
9766 {
```

```
9767 {package} \use:c { conditionally@traceoff }
```

```
9768 \msg_if_exist:nnTF {#2} {#3}
```

```
9769 {
```

```
9770 \__msg_class_chk_exist:nT {#1}
```

```
9771 {
```

```
9772 \tl_set:Nn \l__msg_current_class_tl {#1}
```

```
9773 \cs_set_protected:Npx \__msg_use_code:
```

```
9774 {
```

```
9775 \exp_not:n
```

```
9776 {
```

```
9777 \use:c { __msg_ \l__msg_class_tl _code:nnnnnnn }
```

```
9778 {#2} {#3} {#4} {#5} {#6} {#7}
```

```
9779 }
```

```
9780 }
```

```
9781 \__msg_use_redirect_name:n { #2 / #3 }
```

```
9782 }
```

```
9783 }
```

```
9784 { \__kernel_msg_error:nxxx { kernel } { message-unknown } {#2} {#3} }
```

```
9785 {package} \use:c { conditionally@traceon }
```

```
9786 }
```

```
9787 \cs_new_protected:Npn \__msg_use_code: { }
```

The first check is for a individual message redirection. If this applies then no further redirection is attempted. Otherwise, split the message name into $\langle module \rangle$, $\langle submodule \rangle$ and $\langle message \rangle$ (with an arbitrary number of slashes), and store $\{/module/submodule\}$, $\{/module\}$ and $\{\}$ into $\backslash l_msg_hierarchy_seq$. We then map through this sequence, applying the most specific redirection.

```

9788 \cs_new_protected:Npn \__msg_use_redirect_name:n #1
9789 {
9790   \prop_get:NnNTF \l__msg_redirect_prop { / #1 } \l__msg_class_tl
9791   { \__msg_use_code: }
9792   {
9793     \seq_clear:N \l__msg_hierarchy_seq
9794     \__msg_use_hierarchy:nwwN { }
9795     #1 \q_mark \__msg_use_hierarchy:nwwN
9796     / \q_mark \use_none_delimit_by_q_stop:w
9797     \q_stop
9798     \__msg_use_redirect_module:n { }
9799   }
9800 }
9801 \cs_new_protected:Npn \__msg_use_hierarchy:nwwN #1#2 / #3 \q_mark #4
9802 {
9803   \seq_put_left:Nn \l__msg_hierarchy_seq {#1}
9804   #4 { #1 / #2 } #3 \q_mark #4
9805 }

```

At this point, the items of $\backslash l_msg_hierarchy_seq$ are the various levels at which we should look for a redirection. Redirections which are less specific than the argument of $\backslash _msg_use_redirect_module:n$ are not attempted. This argument is empty for a class redirection, $/module$ for a module redirection, *etc.* Loop through the sequence to find the most specific redirection, with module **##1**. The loop is interrupted after testing for a redirection for **##1** equal to the argument **#1** (least specific redirection allowed). When a redirection is found, break the mapping, then if the redirection targets the same class, output the code with that class, and otherwise set the target as the new current class, and search for further redirections. Those redirections should be at least as specific as **##1**.

```

9806 \cs_new_protected:Npn \__msg_use_redirect_module:n #1
9807 {
9808   \seq_map_inline:Nn \l__msg_hierarchy_seq
9809   {
9810     \prop_get:cnNTF { l__msg_redirect_ \l__msg_current_class_tl _prop }
9811     {##1} \l__msg_class_tl
9812     {
9813       \seq_map_break:n
9814       {
9815         \tl_if_eq:NNTF \l__msg_current_class_tl \l__msg_class_tl
9816         { \__msg_use_code: }
9817         {
9818           \tl_set_eq:NN \l__msg_current_class_tl \l__msg_class_tl
9819           \__msg_use_redirect_module:n {##1}
9820         }
9821       }
9822     }
9823     {
9824       \str_if_eq:nnT {##1} {#1}

```

```

9825         {
9826         \tl_set_eq:Nn \l__msg_class_tl \l__msg_current_class_tl
9827         \seq_map_break:n { \__msg_use_code: }
9828         }
9829     }
9830 }
9831 }

```

(End definition for `__msg_use:nnnnnn` and others.)

`\msg_redirect_name:nnn` Named message always use the given class even if that class is redirected further. An empty target class cancels any existing redirection for that message.

```

9832 \cs_new_protected:Npn \msg_redirect_name:nnn #1#2#3
9833 {
9834     \tl_if_empty:nTF {#3}
9835     { \prop_remove:Nn \l__msg_redirect_prop { / #1 / #2 } }
9836     {
9837         \__msg_class_chk_exist:nT {#3}
9838         { \prop_put:Nnn \l__msg_redirect_prop { / #1 / #2 } {#3} }
9839     }
9840 }

```

(End definition for `\msg_redirect_name:nnn`. This function is documented on page 143.)

`\msg_redirect_class:nn` If the target class is empty, eliminate the corresponding redirection. Otherwise, add the redirection. We must then check for a loop: as an initialization, we start by storing the initial class in `\l__msg_current_class_tl`.

`\msg_redirect_module:nnn`
`__msg_redirect:nnn`
`__msg_redirect_loop_chk:nnn`
`__msg_redirect_loop_list:n`

```

9841 \cs_new_protected:Npn \msg_redirect_class:nn
9842 { \__msg_redirect:nnn { } }
9843 \cs_new_protected:Npn \msg_redirect_module:nnn #1
9844 { \__msg_redirect:nnn { / #1 } }
9845 \cs_new_protected:Npn \__msg_redirect:nnn #1#2#3
9846 {
9847     \__msg_class_chk_exist:nT {#2}
9848     {
9849         \tl_if_empty:nTF {#3}
9850         { \prop_remove:cn { l__msg_redirect_ #2 _prop } {#1} }
9851         {
9852             \__msg_class_chk_exist:nT {#3}
9853             {
9854                 \prop_put:cnn { l__msg_redirect_ #2 _prop } {#1} {#3}
9855                 \tl_set:Nn \l__msg_current_class_tl {#2}
9856                 \seq_clear:N \l__msg_class_loop_seq
9857                 \__msg_redirect_loop_chk:nnn {#2} {#3} {#1}
9858             }
9859         }
9860     }
9861 }

```

Since multiple redirections can only happen with increasing specificity, a loop requires that all steps are of the same specificity. The new redirection can thus only create a loop with other redirections for the exact same module, #1, and not submodules. After some initialization above, follow redirections with `\l__msg_class_tl`, and keep track in `\l__msg_class_loop_seq` of the various classes encountered. A redirection from a class to

itself, or the absence of redirection both mean that there is no loop. A redirection to the initial class marks a loop. To break it, we must decide which redirection to cancel. The user most likely wants the newly added redirection to hold with no further redirection. We thus remove the redirection starting from #2, target of the new redirection. Note that no message is emitted by any of the underlying functions: otherwise we may get an infinite loop because of a message from the message system itself.

```

9862 \cs_new_protected:Npn \__msg_redirect_loop_chk:nnn #1#2#3
9863 {
9864   \seq_put_right:Nn \l__msg_class_loop_seq {#1}
9865   \prop_get:cnNT { l__msg_redirect_ #1 _prop } {#3} \l__msg_class_tl
9866   {
9867     \str_if_eq:VnF \l__msg_class_tl {#1}
9868     {
9869       \tl_if_eq:NNTF \l__msg_class_tl \l__msg_current_class_tl
9870       {
9871         \prop_put:cnn { l__msg_redirect_ #2 _prop } {#3} {#2}
9872         \__kernel_msg_warning:nxxxx
9873         { kernel } { message-redirect-loop }
9874         { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
9875         { \seq_item:Nn \l__msg_class_loop_seq { 2 } }
9876         {#3}
9877         {
9878           \seq_map_function:NN \l__msg_class_loop_seq
9879           \__msg_redirect_loop_list:n
9880           { \seq_item:Nn \l__msg_class_loop_seq { 1 } }
9881         }
9882       }
9883       { \__msg_redirect_loop_chk:onn \l__msg_class_tl {#2} {#3} }
9884     }
9885   }
9886 }
9887 \cs_generate_variant:Nn \__msg_redirect_loop_chk:nnn { o }
9888 \cs_new:Npn \__msg_redirect_loop_list:n #1 { {#1} ~ => ~ }

```

(End definition for `\msg_redirect_class:nn` and others. These functions are documented on page 143.)

17.5 Kernel-specific functions

`__kernel_msg_new:nnnn` The kernel needs some messages of its own. These are created using pre-built functions. Two functions are provided: one more general and one which only has the short text part.

```

\__kernel_msg_new:nnn
\__kernel_msg_set:nnnn
\__kernel_msg_set:nnn
9889 \cs_new_protected:Npn \__kernel_msg_new:nnnn #1#2
9890 { \msg_new:nnnn { LaTeX } { #1 / #2 } }
9891 \cs_new_protected:Npn \__kernel_msg_new:nnn #1#2
9892 { \msg_new:nnn { LaTeX } { #1 / #2 } }
9893 \cs_new_protected:Npn \__kernel_msg_set:nnnn #1#2
9894 { \msg_set:nnnn { LaTeX } { #1 / #2 } }
9895 \cs_new_protected:Npn \__kernel_msg_set:nnn #1#2
9896 { \msg_set:nnn { LaTeX } { #1 / #2 } }

```

(End definition for `__kernel_msg_new:nnnn` and others.)

`__msg_kernel_class_new:nN` All the functions for kernel messages come in variants ranging from 0 to 4 arguments. Those with less than 4 arguments are defined in terms of the 4-argument variant, in a

way very similar to `_msg_class_new:nN`. This auxiliary is destroyed at the end of the group.

```

9897 \group_begin:
9898   \cs_set_protected:Npn \_msg\_kernel\_class\_new:nN #1
9899     { \_msg\_kernel\_class\_new\_aux:nN { \_kernel\_msg\_ #1 } }
9900   \cs_set_protected:Npn \_msg\_kernel\_class\_new\_aux:nN #1#2
9901     {
9902       \cs_new_protected:cpn { #1 :nnnnnn } ##1##2##3##4##5##6
9903       {
9904         \use:x
9905         {
9906           \exp_not:n { #2 { LaTeX } { ##1 / ##2 } }
9907           { \tl_to_str:n {##3} } { \tl_to_str:n {##4} }
9908           { \tl_to_str:n {##5} } { \tl_to_str:n {##6} }
9909         }
9910       }
9911       \cs_new_protected:cpx { #1 :nnnnn } ##1##2##3##4##5
9912       { \exp_not:c { #1 :nnnnnn } {##1} {##2} {##3} {##4} {##5} { } }
9913       \cs_new_protected:cpx { #1 :nnnn } ##1##2##3##4
9914       { \exp_not:c { #1 :nnnnnn } {##1} {##2} {##3} {##4} { } { } }
9915       \cs_new_protected:cpx { #1 :nnn } ##1##2##3
9916       { \exp_not:c { #1 :nnnnnn } {##1} {##2} {##3} { } { } { } }
9917       \cs_new_protected:cpx { #1 :nn } ##1##2
9918       { \exp_not:c { #1 :nnnnnn } {##1} {##2} { } { } { } { } }
9919       \cs_new_protected:cpx { #1 :nnxxxx } ##1##2##3##4##5##6
9920       {
9921         \use:x
9922         {
9923           \exp_not:N \exp_not:n
9924           { \exp_not:c { #1 :nnnnnn } {##1} {##2} }
9925           {##3} {##4} {##5} {##6}
9926         }
9927       }
9928       \cs_new_protected:cpx { #1 :nnxxx } ##1##2##3##4##5
9929       { \exp_not:c { #1 :nnxxxx } {##1} {##2} {##3} {##4} {##5} { } }
9930       \cs_new_protected:cpx { #1 :nnxx } ##1##2##3##4
9931       { \exp_not:c { #1 :nnxxxx } {##1} {##2} {##3} {##4} { } { } }
9932       \cs_new_protected:cpx { #1 :nnx } ##1##2##3
9933       { \exp_not:c { #1 :nnxxxx } {##1} {##2} {##3} { } { } { } }
9934     }

```

(End definition for `_msg_kernel_class_new:nN` and `_msg_kernel_class_new_aux:nN`.)

`_kernel_msg_fatal:nnnnnn` Neither fatal kernel errors nor kernel errors can be redirected. We directly use the code for (non-kernel) fatal errors and errors, adding the “`LaTeX`” module name. Three functions are already defined by `l3basics`; we need to undefine them to avoid errors.

```

9935 \_kernel\_msg\_fatal:nnnnnn \_msg\_kernel\_class\_new:nN { fatal } \_msg\_fatal\_code:nnnnnn
9936 \_kernel\_msg\_fatal:nnxxxx \_cs\_undefine:N \_kernel\_msg\_error:nnxx
9937 \_kernel\_msg\_fatal:nnnnn \_cs\_undefine:N \_kernel\_msg\_error:nnx
9938 \_kernel\_msg\_fatal:nnxxx \_cs\_undefine:N \_kernel\_msg\_error:nn
9939 \_kernel\_msg\_fatal:nnnn \_msg\_kernel\_class\_new:nN { error } \_msg\_error\_code:nnnnnn
\_kernel\_msg\_fatal:nnx
\_kernel\_msg\_fatal:nn
\_kernel\_msg\_fatal:nnnnnn
\_kernel\_msg\_error:nnnnnn
\_kernel\_msg\_error:nnxxxx
\_kernel\_msg\_error:nnnnn
\_kernel\_msg\_error:nnxxx
\_kernel\_msg\_error:nnnn
\_kernel\_msg\_error:nnxx
\_kernel\_msg\_error:nnn
\_kernel\_msg\_error:nnx
\_kernel\_msg\_error:nn

```

(End definition for `_kernel_msg_fatal:nnnnnn` and others.)

Kernel messages which can be redirected simply use the machinery for normal messages, with the module name “`LATEX`”.

```

\__kernel_msg_warning:nnnnnn 9940 \__msg_kernel_class_new:nN { warning } \msg_warning:nnxxxx
\__kernel_msg_warning:nnxxxx 9941 \__msg_kernel_class_new:nN { info } \msg_info:nnxxxx
\__kernel_msg_warning:nnnnn
\__kernel_msg_warning:nnxxx
\__kernel_msg_warning:nnnn
\__kernel_msg_warning:nnxx
\__kernel_msg_warning:nnn
\__kernel_msg_warning:nnx
\__kernel_msg_warning:nn
\__kernel_msg_info:nnnnnn
\__kernel_msg_info:nnxxxx
\__kernel_msg_info:nnnnn
\__kernel_msg_info:nnxxx
\__kernel_msg_info:nnnn
\__kernel_msg_info:nnxx
\__kernel_msg_info:nnn
\__kernel_msg_info:nnx
\__kernel_msg_info:nn

```

(End definition for `__kernel_msg_warning:nnnnnn` and others.)

End the group to eliminate `__msg_kernel_class_new:nN`.

```
9942 \group_end:
```

Error messages needed to actually implement the message system itself.

```

9943 \__kernel_msg_new:nnnn { kernel } { message-already-defined }
9944 { Message~'#2'~for~module~'#1'~already-defined. }
9945 {
9946   \c__msg_coding_error_text_tl
9947   LaTeX~was~asked~to~define~a~new~message~called~'#2'\
9948   by~the~module~'#1':~this~message~already~exists.
9949   \c__msg_return_text_tl
9950 }
9951 \__kernel_msg_new:nnnn { kernel } { message-unknown }
9952 { Unknown~message~'#2'~for~module~'#1'. }
9953 {
9954   \c__msg_coding_error_text_tl
9955   LaTeX~was~asked~to~display~a~message~called~'#2'\
9956   by~the~module~'#1':~this~message~does~not~exist.
9957   \c__msg_return_text_tl
9958 }
9959 \__kernel_msg_new:nnnn { kernel } { message-class-unknown }
9960 { Unknown~message~class~'#1'. }
9961 {
9962   LaTeX~has~been~asked~to~redirect~messages~to~a~class~'#1':\
9963   this~was~never~defined.
9964   \c__msg_return_text_tl
9965 }
9966 \__kernel_msg_new:nnnn { kernel } { message-redirect-loop }
9967 {
9968   Message~redirection~loop~caused~by~ {#1} ~=>~ {#2}
9969   \tl_if_empty:nF {#3} { ~for~module~' \use_none:n #3 ' } .
9970 }
9971 {
9972   Adding~the~message~redirection~ {#1} ~=>~ {#2}
9973   \tl_if_empty:nF {#3} { ~for~the~module~' \use_none:n #3 ' } ~
9974   created~an~infinite~loop\\\
9975   \iow_indent:n { #4 \\\ }
9976 }

```

Messages for earlier kernel modules plus a few for `l3keys` which cover coding errors.

```

9977 \__kernel_msg_new:nnnn { kernel } { bad-number-of-arguments }
9978 { Function~'#1'~cannot~be~defined~with~#2~arguments. }
9979 {
9980   \c__msg_coding_error_text_tl
9981   LaTeX~has~been~asked~to~define~a~function~'#1'~with~
9982   #2~arguments.~
9983   TeX~allows~between~0~and~9~arguments~for~a~single~function.
9984 }

```

```

9985 \_kernel_msg_new:nnn { kernel } { char-active }
9986 { Cannot~generate~active~chars. }
9987 \_kernel_msg_new:nnn { kernel } { char-invalid-catcode }
9988 { Invalid~catcode~for~char~generation. }
9989 \_kernel_msg_new:nnn { kernel } { char-null-space }
9990 { Cannot~generate~null~char~as~a~space. }
9991 \_kernel_msg_new:nnn { kernel } { char-out-of-range }
9992 { Charcode~requested~out~of~engine~range. }
9993 \_kernel_msg_new:nnn { kernel } { char-space }
9994 { Cannot~generate~space~chars. }
9995 \_kernel_msg_new:nnnn { kernel } { command-already-defined }
9996 { Control~sequence~#1~already~defined. }
9997 {
9998   \c_msg_coding_error_text_tl
9999   LaTeX~has~been~asked~to~create~a~new~control~sequence~'~#1'~
10000   but~this~name~has~already~been~used~elsewhere. \\ \\
10001   The~current~meaning~is:\\
10002   \\ #2
10003 }
10004 \_kernel_msg_new:nnnn { kernel } { command-not-defined }
10005 { Control~sequence~#1~undefined. }
10006 {
10007   \c_msg_coding_error_text_tl
10008   LaTeX~has~been~asked~to~use~a~control~sequence~'~#1':\\
10009   this~has~not~been~defined~yet.
10010 }
10011 \_kernel_msg_new:nnn { kernel } { deprecated-command }
10012 {
10013   The~deprecated~command~'~#2'~has~been~or~will~be~removed~on~#1.
10014   \tl_if_empty:nF {#3} { ~Use~instead~'~#3'. }
10015 }
10016 \_kernel_msg_new:nnnn { kernel } { empty-search-pattern }
10017 { Empty~search~pattern. }
10018 {
10019   \c_msg_coding_error_text_tl
10020   LaTeX~has~been~asked~to~replace~an~empty~pattern~by~'~#1':~that~
10021   would~lead~to~an~infinite~loop!
10022 }
10023 \_kernel_msg_new:nnnn { kernel } { out-of-registers }
10024 { No~room~for~a~new~#1. }
10025 {
10026   TeX~only~supports~\int_use:N \c_max_register_int \ %
10027   of~each~type.~All~the~#1~registers~have~been~used.~
10028   This~run~will~be~aborted~now.
10029 }
10030 \_kernel_msg_new:nnnn { kernel } { non-base-function }
10031 { Function~'~#1'~is~not~a~base~function }
10032 {
10033   \c_msg_coding_error_text_tl
10034   Functions~defined~through~\iow_char:N\\cs_new:Nn~must~have~
10035   a~signature~consisting~of~only~normal~arguments~'~N'~and~'~n'.~
10036   To~define~variants~use~\iow_char:N\\cs_generate_variant:Nn~
10037   and~to~define~other~functions~use~\iow_char:N\\cs_new:Npn.
10038 }

```

```

10039 \__kernel_msg_new:nnnn { kernel } { missing-colon }
10040 { Function~'#1'~contains~no~':'~. }
10041 {
10042   \c__msg_coding_error_text_tl
10043   Code-level-functions-must-contain~':'~to-separate-the~
10044   argument-specification-from-the-function-name.~This-is~
10045   needed-when-defining-conditionals-or-variants,~or-when-building-a~
10046   parameter-text-from-the-number-of-arguments-of-the-function.
10047 }
10048 \__kernel_msg_new:nnnn { kernel } { overflow }
10049 { Integers-larger-than-2^{30}-1~cannot-be-stored-in-arrays. }
10050 {
10051   An-attempt-was-made-to-store~#3~
10052   \tl_if_empty:nF {#2} { at-position~#2~ } in-the-array~'#1'~.~
10053   The-largest-allowed-value~#4~will-be-used-instead.
10054 }
10055 \__kernel_msg_new:nnnn { kernel } { out-of-bounds }
10056 { Access-to-an-entry-beyond-an-array's-bounds. }
10057 {
10058   An-attempt-was-made-to-access-or-store-data-at-position~#2~of-the~
10059   array~'#1',~but-this-array-has-entries-at-positions-from-1-to~#3.
10060 }
10061 \__kernel_msg_new:nnnn { kernel } { protected-predicate }
10062 { Predicate~'#1'~must-be-expandable. }
10063 {
10064   \c__msg_coding_error_text_tl
10065   LaTeX-has-been-asked-to-define~'#1'~as-a-protected-predicate.~
10066   Only-expandable-tests-can-have-a-predicate-version.
10067 }
10068 \__kernel_msg_new:nnn { kernel } { randint-backward-range }
10069 { Bounds-ordered-backwards-in-\int_rand:nn {#1}~{#2}. }
10070 \__kernel_msg_new:nnnn { kernel } { conditional-form-unknown }
10071 { Conditional-form~'#1'~for-function~'#2'~unknown. }
10072 {
10073   \c__msg_coding_error_text_tl
10074   LaTeX-has-been-asked-to-define-the-conditional-form~'#1'~of~
10075   the-function~'#2',~but-only~'TF',~'T',~'F',~and~'p'~forms-exist.
10076 }
10077 \__kernel_msg_new:nnnn { kernel } { key-no-property }
10078 { No-property-given-in-definition-of-key~'#1'. }
10079 {
10080   \c__msg_coding_error_text_tl
10081   Inside~\keys_define:nn each-key-name~
10082   needs-a-property: \ \ \
10083   \iow_indent:n { #1 .<property> } \ \ \
10084   LaTeX-did-not-find-a~'. '~-to-indicate-the-start-of-a-property.
10085 }
10086 \__kernel_msg_new:nnnn { kernel } { key-property-boolean-values-only }
10087 { The-property~'#1'~accepts-boolean-values-only. }
10088 {
10089   \c__msg_coding_error_text_tl
10090   The-property~'#1'~only-accepts-the-values~'true'~and~'false'.
10091 }
10092 \__kernel_msg_new:nnnn { kernel } { key-property-requires-value }

```

```

10093 { The~property~'~#1'~requires~a~value. }
10094 {
10095   \c__msg_coding_error_text_tl
10096   LaTeX~was~asked~to~set~property~'~#1'~for~key~'~#2'~.\\
10097   No~value~was~given~for~the~property,~and~one~is~required.
10098 }
10099 \__kernel_msg_new:nnnn { kernel } { key-property-unknown }
10100 { The~key~property~'~#1'~is~unknown. }
10101 {
10102   \c__msg_coding_error_text_tl
10103   LaTeX~has~been~asked~to~set~the~property~'~#1'~for~key~'~#2'~:~
10104   this~property~is~not~defined.
10105 }
10106 \__kernel_msg_new:nnnn { kernel } { scanmark-already-defined }
10107 { Scan~mark~#1~already~defined. }
10108 {
10109   \c__msg_coding_error_text_tl
10110   LaTeX~has~been~asked~to~create~a~new~scan~mark~'~#1'~
10111   but~this~name~has~already~been~used~for~a~scan~mark.
10112 }
10113 \__kernel_msg_new:nnnn { kernel } { variable-not-defined }
10114 { Variable~#1~undefined. }
10115 {
10116   \c__msg_coding_error_text_tl
10117   LaTeX~has~been~asked~to~show~a~variable~#1,~but~this~has~not~
10118   been~defined~yet.
10119 }
10120 \__kernel_msg_new:nnnn { kernel } { variant-too-long }
10121 { Variant~form~'~#1'~longer~than~base~signature~of~'~#2'~. }
10122 {
10123   \c__msg_coding_error_text_tl
10124   LaTeX~has~been~asked~to~create~a~variant~of~the~function~'~#2'~
10125   with~a~signature~starting~with~'~#1',~but~that~is~longer~than~
10126   the~signature~(part~after~the~colon)~of~'~#2'~.
10127 }
10128 \__kernel_msg_new:nnnn { kernel } { invalid-variant }
10129 { Variant~form~'~#1'~invalid~for~base~form~'~#2'~. }
10130 {
10131   \c__msg_coding_error_text_tl
10132   LaTeX~has~been~asked~to~create~a~variant~of~the~function~'~#2'~
10133   with~a~signature~starting~with~'~#1',~but~cannot~change~an~argument~
10134   from~type~'~#3'~to~type~'~#4'~.
10135 }
10136 \__kernel_msg_new:nnnn { kernel } { invalid-exp-args }
10137 { Invalid~variant~specifier~'~#1'~in~'~#2'~. }
10138 {
10139   \c__msg_coding_error_text_tl
10140   LaTeX~has~been~asked~to~create~an~\iow_char:N\\exp_args:N...~
10141   function~with~signature~'~N#2'~but~'~#1'~is~not~a~valid~argument~
10142   specifier.
10143 }
10144 \__kernel_msg_new:nnn { kernel } { deprecated-variant }
10145 {
10146   Variant~form~'~#1'~deprecated~for~base~form~'~#2'~.~

```

```

10147 One~should~not~change~an~argument~from~type~'#3'~to~type~'#4'
10148 \str_case:nnF {#3}
10149 {
10150   { n } { :~use~a~'\token_if_eq_charcode:NNTF #4 c v V'~variant? }
10151   { N } { :~base~form~only~accepts~a~single~token~argument. }
10152   {#4} { :~base~form~is~already~a~variant. }
10153 } { . }
10154 }

```

Some errors are only needed in package mode if debugging is enabled by one of the options `enable-debug`, `check-declarations`, `log-functions`, or on the contrary if debugging is turned off. In format mode the error is somewhat different.

```

10155 (*package)
10156 \__kernel_if_debug:TF
10157 {
10158   \__kernel_msg_new:nnnn { kernel } { debug }
10159   { The~debugging~option~'#1'~does~not~exist~\msg_line_context:. }
10160   {
10161     The~functions~'\iow_char:N\debug_on:n'~and~
10162     '\iow_char:N\debug_off:n'~only~accept~the~arguments~
10163     'check-declarations',~'deprecation',~'log-functions',~not~'#1'.
10164   }
10165   \__kernel_msg_new:nnn { kernel } { expr } { '#2'~in~#1 }
10166   \__kernel_msg_new:nnnn { kernel } { local-global }
10167   { Inconsistent~local/global~assignment }
10168   {
10169     \c__msg_coding_error_text_tl
10170     \if:w l #2 Local \else: Global \fi: \ %
10171     assignment~to~a~
10172     \if:w l #1 local
10173     \else:
10174       \if:w g #1 global \else: constant \fi:
10175       \fi:
10176       \ %
10177       variable~'#3'.
10178   }
10179   \__kernel_msg_new:nnnn { kernel } { non-declared-variable }
10180   { The~variable~#1~has~not~been~declared~\msg_line_context:. }
10181   {
10182     \c__msg_coding_error_text_tl
10183     Checking~is~active,~and~you~have~tried~do~so~something~like: \\
10184     \\ \tl_set:Nn ~ #1 ~ \{ ~ ... ~ \} \\
10185     without~first~having: \\
10186     \\ \tl_new:N ~ #1 \\
10187     \\
10188     LaTeX~will~create~the~variable~and~continue.
10189   }
10190 }
10191 {
10192   \__kernel_msg_new:nnnn { kernel } { enable-debug }
10193   { To~use~'#1'~load~expl3~with~the~'enable-debug'~option. }
10194   {
10195     The~function~'#1'~will~be~ignored~because~it~can~only~work~if~
10196     some~internal~functions~in~expl3~have~been~appropriately~

```

```

10197         defined.~This-only-happens-if-one-of-the-options~
10198         'enable-debug',~'check-declarations'~or~'log-functions'~was~
10199         given-when-loading-expl3.
10200     }
10201 }
10202 </package>
10203 <*initex>
10204 \__kernel_msg_new:nnnn { kernel } { enable-debug }
10205 { '#1'~cannot-be-used-in-format-mode. }
10206 {
10207     The-function~'#1'~will-be-ignored-because-it-can-only-work-if~
10208     some-internal-functions-in-expl3-have-been-appropriately~
10209     defined.~This-only-happens-in-package-mode~(and-only-if-one-of~
10210     the-options~'enable-debug',~'check-declarations'~or~'log-functions'~
10211     was-given-when-loading-expl3.
10212 }
10213 </initex>

```

Some errors only appear in expandable settings, hence don't need a "more-text" argument.

```

10214 \__kernel_msg_new:nnn { kernel } { bad-exp-end-f }
10215 { Misused~\exp_end_continue_f:w or~:nw }
10216 \__kernel_msg_new:nnn { kernel } { bad-variable }
10217 { Erroneous~variable~#1 used! }
10218 \__kernel_msg_new:nnn { kernel } { misused-sequence }
10219 { A~sequence~was~misused. }
10220 \__kernel_msg_new:nnn { kernel } { misused-prop }
10221 { A~property~list~was~misused. }
10222 \__kernel_msg_new:nnn { kernel } { negative-replication }
10223 { Negative~argument~for~\prg_replicate:nn. }
10224 \__kernel_msg_new:nnn { kernel } { prop-keyval }
10225 { Missing/extra~'=~in~'#1'~(in~'...keyval:Nn') }
10226 \__kernel_msg_new:nnn { kernel } { unknown-comparison }
10227 { Relation~'#1'~unknown:~use~<,>,<=,>=,~<,>=,~<=>. }
10228 \__kernel_msg_new:nnn { kernel } { zero-step }
10229 { Zero~step~size~for~step~function~#1. }
10230 \cs_if_exist:NF \tex_expanded:D
10231 {
10232     \__kernel_msg_new:nnn { kernel } { e-type }
10233     { #1 ~ in~e-type~argument }
10234 }

```

Messages used by the "show" functions.

```

10235 \__kernel_msg_new:nnn { kernel } { show-clist }
10236 {
10237     The-comma-list~ \tl_if_empty:nF {#1} { #1 ~ }
10238     \tl_if_empty:nTF {#2}
10239     { is-empty \>~ . }
10240     { contains-the-items~(without-outer-braces): #2 . }
10241 }
10242 \__kernel_msg_new:nnn { kernel } { show-intarray }
10243 { The-integer-array~#1~contains~#2~items: \ \ #3 . }
10244 \__kernel_msg_new:nnn { kernel } { show-prop }
10245 {
10246     The-property-list~#1~

```

```

10247 \tl_if_empty:nTF {#2}
10248 { is~empty \>~ . }
10249 { contains~the~pairs~(without~outer~braces): #2 . }
10250 }
10251 \__kernel_msg_new:nnn { kernel } { show-seq }
10252 {
10253   The~sequence~#1~
10254   \tl_if_empty:nTF {#2}
10255   { is~empty \>~ . }
10256   { contains~the~items~(without~outer~braces): #2 . }
10257 }
10258 \__kernel_msg_new:nnn { kernel } { show-streams }
10259 {
10260   \tl_if_empty:nTF {#2} { No~ } { The~following~ }
10261   \str_case:nn {#1}
10262   {
10263     { ior } { input ~ }
10264     { iow } { output ~ }
10265   }
10266   streams~are~
10267   \tl_if_empty:nTF {#2} { open } { in~use: #2 . }
10268 }

```

17.6 Expandable errors

`__msg_expandable_error:n` In expansion only context, we cannot use the normal means of reporting errors. Instead, we feed \TeX an undefined control sequence, `\LaTeX3 error:.` It is thus interrupted, and shows the context, which thanks to the odd-looking `\use:n` is

```

<argument> \LaTeX3 error:
                The error message.

```

In other words, \TeX is processing the argument of `\use:n`, which is `\LaTeX3 error: (error message)`. Then `__msg_expandable_error:w` cleans up. In fact, there is an extra subtlety: if the user inserts tokens for error recovery, they should be kept. Thus we also use an odd space character (with category code 7) and keep tokens until that space character, dropping everything else until `\q_stop`. The `\exp_end:` prevents losing braces around the user-inserted text if any, and stops the expansion of `\exp:w`. The group is used to prevent `\LaTeX3~error:` from being globally equal to `\scan_stop:.`

```

10269 \group_begin:
10270 \cs_set_protected:Npn \__msg_tmp:w #1#2
10271 {
10272   \cs_new:Npn \__msg_expandable_error:n ##1
10273   {
10274     \exp:w
10275     \exp_after:wN \exp_after:wN
10276     \exp_after:wN \__msg_expandable_error:w
10277     \exp_after:wN \exp_after:wN
10278     \exp_after:wN \exp_end:
10279     \use:n { #1 #2 ##1 } #2
10280   }
10281   \cs_new:Npn \__msg_expandable_error:w ##1 #2 ##2 #2 {##1}
10282 }

```



```

10283 \exp_args:Ncx \_msg_tmp:w { LaTeX3-error: }
10284 { \char_generate:nn { '\ } { 7 } }
10285 \group_end:

```

(End definition for _msg_expandable_error:n and _msg_expandable_error:w.)

```

\_kernel_msg_expandable_error:nnnnnn
\_kernel_msg_expandable_error:nnffff
\_kernel_msg_expandable_error:nnnnn
\_kernel_msg_expandable_error:nnfff
\_kernel_msg_expandable_error:nnnn
\_kernel_msg_expandable_error:nnff
\_kernel_msg_expandable_error:nnn
\_kernel_msg_expandable_error:nff
\_kernel_msg_expandable_error:nn

```

The command built from the csname \c_msg_text_prefix_tl LaTeX / #1 / #2 takes four arguments and builds the error text, which is fed to _msg_expandable_error:n.

```

10286 \cs_new:Npn \_kernel_msg_expandable_error:nnnnnn #1#2#3#4#5#6
10287 {
10288   \exp_args:Nf \_msg_expandable_error:n
10289   {
10290     \exp_args:NNc \exp_after:wN \exp_stop_f:
10291     { \c\_msg_text_prefix_tl LaTeX / #1 / #2 }
10292     {#3} {#4} {#5} {#6}
10293   }
10294 }
10295 \cs_new:Npn \_kernel_msg_expandable_error:nnnnn #1#2#3#4#5
10296 {
10297   \_kernel_msg_expandable_error:nnnnnn
10298   {#1} {#2} {#3} {#4} {#5} { }
10299 }
10300 \cs_new:Npn \_kernel_msg_expandable_error:nnnn #1#2#3#4
10301 {
10302   \_kernel_msg_expandable_error:nnnnnn
10303   {#1} {#2} {#3} {#4} { } { }
10304 }
10305 \cs_new:Npn \_kernel_msg_expandable_error:nnn #1#2#3
10306 {
10307   \_kernel_msg_expandable_error:nnnnnn
10308   {#1} {#2} {#3} { } { } { }
10309 }
10310 \cs_new:Npn \_kernel_msg_expandable_error:nn #1#2
10311 {
10312   \_kernel_msg_expandable_error:nnnnnn
10313   {#1} {#2} { } { } { } { }
10314 }
10315 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnnnnn { nnffff }
10316 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnnnnn { nnfff }
10317 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnnn { nnff }
10318 \cs_generate_variant:Nn \_kernel_msg_expandable_error:nnn { nnf }

```

(End definition for _kernel_msg_expandable_error:nnnnnn and others.)

```

\_msg_log:n
\_msg_term:n

```

```

10319 \_kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \iow_log:n }
10320 \cs_new_protected:Npn \msg_log:n #1
10321 {
10322   \iow_log:n { ..... }
10323   \iow_wrap:nnn { . ~ #1 } { . ~ } { } \iow_log:n
10324   \iow_log:n { ..... }
10325 }
10326 \_kernel_patch_deprecation:nnNNpn { 2019-12-31 } { \iow_term:n }
10327 \cs_new_protected:Npn \msg_term:n #1

```

```

10328 {
10329   \iow_term:n { ***** }
10330   \iow_wrap:nnnN { * ~ #1 } { * ~ } { } \iow_term:n
10331   \iow_term:n { ***** }
10332 }

```

(End definition for \msg_log:n and \msg_term:n.)

\msg_interrupt:nnn

```

10333 \__kernel_patch_deprecation:nnNn { 2019-12-31 } { [Defined-error-message] }
10334 \cs_new_protected:Npn \msg_interrupt:nnn #1#2#3
10335 {
10336   \tl_if_empty:nTF {#3}
10337   {
10338     \__msg_old_interrupt_wrap:nn { \ \ \c__msg_no_info_text_tl }
10339     {#1 \ \ \ \ #2 \ \ \ \ \c__msg_continue_text_tl }
10340   }
10341   {
10342     \__msg_old_interrupt_wrap:nn { \ \ #3 }
10343     {#1 \ \ \ \ #2 \ \ \ \ \c__msg_help_text_tl }
10344   }
10345 }
10346 \cs_new_protected:Npn \__msg_old_interrupt_wrap:nn #1#2
10347 {
10348   \iow_wrap:nnnN {#1} { | ~ } { } \__msg_old_interrupt_more_text:n
10349   \iow_wrap:nnnN {#2} { ! ~ } { } \__msg_old_interrupt_text:n
10350 }
10351 \cs_new_protected:Npn \__msg_old_interrupt_more_text:n #1
10352 {
10353   \exp_args:Nx \tex_errhelp:D
10354   {
10355     |,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
10356     #1 \iow_newline:
10357     |.....
10358   }
10359 }
10360 \group_begin:
10361   \char_set_lccode:nn {'\} {'\ }
10362   \char_set_lccode:nn {'\} {'\ }
10363   \char_set_lccode:nn {'\&} {'\!}
10364   \char_set_catcode_active:N \&
10365   \tex_lowercase:D
10366   {
10367     \group_end:
10368     \cs_new_protected:Npn \__msg_old_interrupt_text:n #1
10369     {
10370       \iow_term:x
10371       {
10372         \iow_newline:
10373         !!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!!
10374         \iow_newline:
10375         !
10376       }
10377       \__kernel_iow_with:Nnn \tex_newlinechar:D { '^J }

```

```

10378 {
10379   \__kernel_iow_with:Nnn \tex_errorcontextlines:D { -1 }
10380   {
10381     \group_begin:
10382     \cs_set_protected:Npn &
10383     {
10384       \tex_errmessage:D
10385       {
10386         #1
10387         \use_none:n
10388         { ..... }
10389       }
10390     }
10391     \exp_after:wN
10392     \group_end:
10393     &
10394   }
10395 }
10396 }
10397 }

```

(End definition for `\msg_interrupt:nnn`.)

```
10398 </initex | package>
```

18 l3file implementation

The following test files are used for this code: `m3file001`.

```
10399 <*initex | package>
```

18.1 Input operations

```
10400 <@@=ior>
```

18.1.1 Variables and constants

`\l__ior_internal_tl` Used as a short-term scratch variable.

```
10401 \tl_new:N \l__ior_internal_tl
```

(End definition for `\l__ior_internal_tl`.)

`\c_term_ior` Reading from the terminal (with a prompt) is done using a positive but non-existent stream number. Unlike writing, there is no concept of reading from the log.

```
10402 \int_const:Nn \c_term_ior { 16 }
```

(End definition for `\c_term_ior`. This variable is documented on page 151.)

`\g__ior_streams_seq` A list of the currently-available input streams to be used as a stack. In format mode, all streams (from 0 to 15) are available, while the package requests streams to L^AT_EX 2_ε as they are needed (initially none are needed), so the starting point varies!

```
10403 \seq_new:N \g__ior_streams_seq
```

```
10404 <*initex>
```

```
10405 \seq_gset_split:Nnn \g__ior_streams_seq { , }
```

```
10406 { 0 , 1 , 2 , 3 , 4 , 5 , 6 , 7 , 8 , 9 , 10 , 11 , 12 , 13 , 14 , 15 }
```

```
10407 </initex>
```

(End definition for `\g__ior_streams_seq`.)

`\l__ior_stream_tl` Used to recover the raw stream number from the stack.

```
10408 \tl_new:N \l__ior_stream_tl
```

(End definition for `\l__ior_stream_tl`.)

`\g__ior_streams_prop` The name of the file attached to each stream is tracked in a property list. To get the correct number of reserved streams in package mode the underlying mechanism needs to be queried. For $\text{\LaTeX} 2_{\epsilon}$ and plain \TeX this data is stored in `\count16`: with the `etex` package loaded we need to subtract 1 as the register holds the number of the next stream to use. In `ConTeXt`, we need to look at `\count38` but there is no subtraction: like the original plain \TeX / $\text{\LaTeX} 2_{\epsilon}$ mechanism it holds the value of the *last* stream allocated.

```
10409 \prop_new:N \g__ior_streams_prop
10410 \langle *package \rangle
10411 \int_step_inline:nnn
10412   { 0 }
10413   {
10414     \cs_if_exist:NTF \normalend
10415     { \tex_count:D 38 ~ }
10416     {
10417       \tex_count:D 16 ~ %
10418       \cs_if_exist:NT \loccount { - 1 }
10419     }
10420   }
10421   {
10422     \prop_gput:Nnn \g__ior_streams_prop {#1} { Reserved-by~format }
10423   }
10424 \langle /package \rangle
```

(End definition for `\g__ior_streams_prop`.)

18.1.2 Stream management

`\ior_new:N` Reserving a new stream is done by defining the name as equal to using the terminal.

```
\ior_new:cn 10425 \cs_new_protected:Npn \ior_new:N #1 { \cs_new_eq:NN #1 \c_term_ior }
10426 \cs_generate_variant:Nn \ior_new:N { c }
```

(End definition for `\ior_new:N`. This function is documented on page 144.)

`\g_tmpa_ior` The usual scratch space.

```
\g_tmpb_ior 10427 \ior_new:N \g_tmpa_ior
10428 \ior_new:N \g_tmpb_ior
```

(End definition for `\g_tmpa_ior` and `\g_tmpb_ior`. These variables are documented on page 151.)

`\ior_open:Nn` Use the conditional version, with an error if the file is not found.

```
\ior_open:cn 10429 \cs_new_protected:Npn \ior_open:Nn #1#2
10430   { \ior_open:NnF #1 {#2} { __kernel_file_missing:n {#2} } }
10431 \cs_generate_variant:Nn \ior_open:Nn { c }
```

(End definition for `\ior_open:Nn`. This function is documented on page 144.)

`\l__ior_file_name_str` Data storage.

```
10432 \str_new:N \l__ior_file_name_str
```

(End definition for \l__ior_file_name_str.)

\ior_open:NnTF An auxiliary searches for the file in the T_EX, L^AT_EX 2_ε and L^AT_EX 3 paths. Then pass the file found to the lower-level function which deals with streams. The full_name is empty when the file is not found.

```

10433 \prg_new_protected_conditional:Npnn \ior_open:Nn #1#2 { T , F , TF }
10434 {
10435   \file_get_full_name:nN {#2} \l__ior_file_name_str
10436   \str_if_empty:NTF \l__ior_file_name_str
10437   { \prg_return_false: }
10438   {
10439     \__kernel_ior_open:No #1 \l__ior_file_name_str
10440     \prg_return_true:
10441   }
10442 }
10443 \prg_generate_conditional_variant:Nnn \ior_open:Nn { c } { T , F , TF }

```

(End definition for \ior_open:NnTF. This function is documented on page 145.)

__ior_new:N In package mode, streams are reserved using \newread before they can be managed by ior. To prevent ior from being affected by redefinitions of \newread (such as done by the third-party package morewrites), this macro is saved here under a private name. The complicated code ensures that __ior_new:N is not \outer despite plain T_EX's \newread being \outer. For ConT_EXt, we have to deal with the fact that \newread works like our own: it actually checks before altering definition.

```

10444 \*package
10445 \exp_args:NNf \cs_new_protected:Npn \__ior_new:N
10446 { \exp_args:NNc \exp_after:wN \exp_stop_f: { newread } }
10447 \cs_if_exist:NT \normalend
10448 {
10449   \cs_new_eq:NN \__ior_new_aux:N \__ior_new:N
10450   \cs_set_protected:Npn \__ior_new:N #1
10451   {
10452     \cs_undefine:N #1
10453     \__ior_new_aux:N #1
10454   }
10455 }
10456 \*package

```

(End definition for __ior_new:N.)

__kernel_ior_open:Nn The stream allocation itself uses the fact that there is a list of all of those available, so allocation is simply a question of using the number at the top of the list. In package mode, life gets more complex as it's important to keep things in sync. That is done using a two-part approach: any streams that have already been taken up by ior but are now free are tracked, so we first try those. If that fails, ask plain T_EX or L^AT_EX 2_ε for a new stream and use that number (after a bit of conversion).

__kernel_ior_open:No
__ior_open_stream:Nn

```

10457 \cs_new_protected:Npn \__kernel_ior_open:Nn #1#2
10458 {
10459   \ior_close:N #1
10460   \seq_gpop:NNTF \g__ior_streams_seq \l__ior_stream_tl
10461   { \__ior_open_stream:Nn #1 {#2} }
10462 \*initex

```

```

10463      { \_kernel_msg_fatal:nn { kernel } { input-streams-exhausted } }
10464 \end{initex}
10465 \begin{package}
10466 {
10467   \_ior_new:N #1
10468   \tl_set:Nx \l__ior_stream_tl { \int_eval:n {#1} }
10469   \_ior_open_stream:Nn #1 {#2}
10470 }
10471 \end{package}
10472 }
10473 \cs_generate_variant:Nn \_kernel_ior_open:Nn { No }
10474 \cs_new_protected:Npn \_ior_open_stream:Nn #1#2
10475 {
10476   \tex_global:D \tex_chardef:D #1 = \l__ior_stream_tl \scan_stop:
10477   \prop_gput:NVn \g__ior_streams_prop #1 {#2}
10478   \tex_openin:D #1 #2 \scan_stop:
10479 }

```

(End definition for `_kernel_ior_open:Nn` and `_ior_open_stream:Nn`.)

`\ior_close:N` Closing a stream means getting rid of it at the \TeX level and removing from the various data structures. Unless the name passed is an invalid stream number (outside the range $[0, 15]$), it can be closed. On the other hand, it only gets added to the stack if it was not already there, to avoid duplicates building up.

`\ior_close:c`

```

10480 \cs_new_protected:Npn \ior_close:N #1
10481 {
10482   \int_compare:nT { -1 < #1 < \c_term_ior }
10483   {
10484     \tex_closein:D #1
10485     \prop_gremove:NV \g__ior_streams_prop #1
10486     \seq_if_in:NVF \g__ior_streams_seq #1
10487     { \seq_gpush:NV \g__ior_streams_seq #1 }
10488     \cs_gset_eq:NN #1 \c_term_ior
10489   }
10490 }
10491 \cs_generate_variant:Nn \ior_close:N { c }

```

(End definition for `\ior_close:N`. This function is documented on page 145.)

`\ior_show_list:` Show the property lists, but with some “pretty printing”. See the `l3msg` module. The first argument of the message is `ior` (as opposed to `iow`) and the second is empty if no read stream is open and non-empty (the list of streams formatted using `\msg_show_item_unbraced:nn`) otherwise. The code of the message `show-streams` takes care of translating `ior/iow` to English.

`\ior_log_list:`

`__ior_list:N`

```

10492 \cs_new_protected:Npn \ior_show_list: { \__ior_list:N \msg_show:nnxxxx }
10493 \cs_new_protected:Npn \ior_log_list: { \__ior_list:N \msg_log:nnxxxx }
10494 \cs_new_protected:Npn \__ior_list:N #1
10495 {
10496   #1 { LaTeX / kernel } { show-streams }
10497   { ior }
10498   {
10499     \prop_map_function:NN \g__ior_streams_prop
10500     \msg_show_item_unbraced:nn
10501   }

```

```

10502     { } { }
10503 }

```

(End definition for `\ior_show_list:`, `\ior_log_list:`, and `_ior_list:N`. These functions are documented on page 145.)

18.1.3 Reading input

`\if_eof:w` The primitive conditional

```

10504 \cs_new_eq:NN \if_eof:w \tex_ifeof:D

```

(End definition for `\if_eof:w`. This function is documented on page 151.)

`\ior_if_eof_p:N` To test if some particular input stream is exhausted the following conditional is provided.
`\ior_if_eof:NTF` The primitive test can only deal with numbers in the range $[0, 15]$ so we catch outliers (they are exhausted).

```

10505 \prg_new_conditional:Npnn \ior_if_eof:N #1 { p , T , F , TF }
10506 {
10507     \cs_if_exist:NTF #1
10508     {
10509         \int_compare:nTF { -1 < #1 < \c_term_ior }
10510         {
10511             \if_eof:w #1
10512             \prg_return_true:
10513             \else:
10514             \prg_return_false:
10515             \fi:
10516         }
10517         { \prg_return_true: }
10518     }
10519     { \prg_return_true: }
10520 }

```

(End definition for `\ior_if_eof:NTF`. This function is documented on page 148.)

`\ior_get:NN` And here we read from files.

```

10521 \cs_new_protected:Npn \ior_get:NN #1#2
10522 { \tex_read:D #1 to #2 }

```

(End definition for `\ior_get:NN`. This function is documented on page 146.)

`\ior_str_get:NN` Reading as strings is a more complicated wrapper, as we wish to remove the newline character and restore it afterwards.

```

10523 \cs_new_protected:Npn \ior_str_get:NN #1#2
10524 {
10525     \exp_args:Nno \use:n
10526     {
10527         \int_set:Nn \tex_endlinechar:D { -1 }
10528         \tex_readline:D #1 to #2
10529         \int_set:Nn \tex_endlinechar:D
10530     } { \int_use:N \tex_endlinechar:D }
10531 }

```

(End definition for `\ior_str_get:NN`. This function is documented on page 146.)

`\ior_map_break:` Usual map breaking functions.

```
\ior_map_break:n 10532 \cs_new:Npn \ior_map_break:
10533 { \prg_map_break:Nn \ior_map_break: { } }
10534 \cs_new:Npn \ior_map_break:n
10535 { \prg_map_break:Nn \ior_map_break: }
```

(End definition for `\ior_map_break:` and `\ior_map_break:n`. These functions are documented on page 147.)

`\ior_map_inline:Nn` Mapping to an input stream can be done on either a token or a string basis, hence the set up. Within that, there is a check to avoid reading past the end of a file, hence the two applications of `\ior_if_eof:N` and its lower-level analogue `\if_eof:w`. This mapping cannot be nested with twice the same stream, as the stream has only one “current line”.

```
\ior_str_map_inline:Nn
\__ior_map_inline:NNn
\__ior_map_inline:NNNn
\__ior_map_inline_loop:NNN 10536 \cs_new_protected:Npn \ior_map_inline:Nn
10537 { \__ior_map_inline:NNn \ior_get:NN }
10538 \cs_new_protected:Npn \ior_str_map_inline:Nn
10539 { \__ior_map_inline:NNn \ior_str_get:NN }
10540 \cs_new_protected:Npn \__ior_map_inline:NNn
10541 {
10542   \int_gincr:N \g__kernel_prg_map_int
10543   \exp_args:Nc \__ior_map_inline:NNNn
10544     { \__ior_map_ \int_use:N \g__kernel_prg_map_int :n }
10545 }
10546 \cs_new_protected:Npn \__ior_map_inline:NNNn #1#2#3#4
10547 {
10548   \cs_gset_protected:Npn #1 ##1 {#4}
10549   \ior_if_eof:NF #3 { \__ior_map_inline_loop:NNN #1#2#3 }
10550   \prg_break_point:Nn \ior_map_break:
10551     { \int_gdecr:N \g__kernel_prg_map_int }
10552 }
10553 \cs_new_protected:Npn \__ior_map_inline_loop:NNN #1#2#3
10554 {
10555   #2 #3 \l__ior_internal_tl
10556   \if_eof:w #3
10557     \exp_after:wN \ior_map_break:
10558   \fi:
10559   \exp_args:No #1 \l__ior_internal_tl
10560   \__ior_map_inline_loop:NNN #1#2#3
10561 }
```

(End definition for `\ior_map_inline:Nn` and others. These functions are documented on page 147.)

`\ior_map_variable:NNn` Since the $\text{T}_{\text{E}}\text{X}$ primitive (`\read` or `\readline`) assigns the tokens read in the same way as a token list assignment, we simply call the appropriate primitive. The end-of-loop is checked using the primitive conditional for speed.

```
\ior_str_map_variable:NNn
\__ior_map_variable:NNNn
\__ior_map_variable_loop:NNNn 10562 \cs_new_protected:Npn \ior_map_variable:NNn
10563 { \__ior_map_variable:NNNn \ior_get:NN }
10564 \cs_new_protected:Npn \ior_str_map_variable:NNn
10565 { \__ior_map_variable:NNNn \ior_str_get:NN }
10566 \cs_new_protected:Npn \__ior_map_variable:NNNn #1#2#3#4
10567 {
10568   \ior_if_eof:NF #2 { \__ior_map_variable_loop:NNNn #1#2#3 {#4} }
10569   \prg_break_point:Nn \ior_map_break: { }
10570 }
```



```

10571 \cs_new_protected:Npn \__ior_map_variable_loop:NNNn #1#2#3#4
10572 {
10573   #1 #2 #3
10574   \if_eof:w #2
10575     \exp_after:wN \ior_map_break:
10576   \fi:
10577   #4
10578   \__ior_map_variable_loop:NNNn #1#2#3 {#4}
10579 }

```

(End definition for `\ior_map_variable:NNn` and others. These functions are documented on page 244.)

18.2 Output operations

```

10580 <@@=iow>

```

There is a lot of similarity here to the input operations, at least for many of the basics. Thus quite a bit is copied from the earlier material with minor alterations.

18.2.1 Variables and constants

`\c_log_iow` Here we allocate two output streams for writing to the transcript file only (`\c_log_iow`) and to both the terminal and transcript file (`\c_term_iow`). Recent LuaTeX provide 128 write streams; we also use `\c_term_iow` as the first non-allowed write stream so its value depends on the engine.

```

10581 \int_const:Nn \c_log_iow { -1 }
10582 \int_const:Nn \c_term_iow
10583 {
10584   \bool_lazy_and:nnTF
10585     { \sys_if_engine luatex_p: }
10586     { \int_compare_p:nNn \tex_luatexversion:D > { 80 } }
10587     { 128 }
10588     { 16 }
10589 }

```

(End definition for `\c_log_iow` and `\c_term_iow`. These variables are documented on page 151.)

`\g__iow_streams_seq` A list of the currently-available output streams to be used as a stack. The stream 18 is special, as `\write18` is used to denote commands to be sent to the OS.

```

10590 \seq_new:N \g__iow_streams_seq
10591 <*/initex>
10592 \exp_args:Nnx \use:n
10593 { \seq_gset_split:Nnn \g__iow_streams_seq { } }
10594 {
10595   \int_step_function:nnN { 0 } { \c_term_iow }
10596   \prg_do_nothing:
10597 }
10598 \int_compare:nNnF \c_term_iow < { 18 }
10599 { \seq_gremove_all:Nn \g__iow_streams_seq { 18 } }
10600 </initex>

```

(End definition for `\g__iow_streams_seq`.)

`\l__iow_stream_tl` Used to recover the raw stream number from the stack.

```

10601 \tl_new:N \l__iow_stream_tl

```

(End definition for \l__iow_stream_tl.)

\g__iow_streams_prop As for reads with the appropriate adjustment of the register numbers to check on.

```

10602 \prop_new:N \g__iow_streams_prop
10603 \<{*package}
10604 \int_step_inline:nnn
10605   { 0 }
10606   {
10607     \cs_if_exist:NTF \normalend
10608     { \tex_count:D 39 ~ }
10609     {
10610       \tex_count:D 17 ~
10611       \cs_if_exist:NT \loccount { - 1 }
10612     }
10613   }
10614   {
10615     \prop_gput:Nnn \g__iow_streams_prop {#1} { Reserved-by~format }
10616   }
10617 \</package>

```

(End definition for \g__iow_streams_prop.)

18.3 Stream management

\iow_new:N Reserving a new stream is done by defining the name as equal to writing to the terminal:
\iow_new:c odd but at least consistent.

```

10618 \cs_new_protected:Npn \iow_new:N #1 { \cs_new_eq:NN #1 \c_term_iow }
10619 \cs_generate_variant:Nn \iow_new:N { c }

```

(End definition for \iow_new:N. This function is documented on page 144.)

\g_tmpa_iow The usual scratch space.

\g_tmpb_iow

```

10620 \iow_new:N \g_tmpa_iow
10621 \iow_new:N \g_tmpb_iow

```

(End definition for \g_tmpa_iow and \g_tmpb_iow. These variables are documented on page 151.)

__iow_new:N As for read streams, copy \newwrite in package mode, making sure that it is not \outer.

```

10622 \<{*package}
10623 \exp_args:NNf \cs_new_protected:Npn \__iow_new:N
10624   { \exp_args:NNc \exp_after:wN \exp_stop_f: { newwrite } }
10625 \</package>

```

(End definition for __iow_new:N.)

\l__iow_file_name_str Data storage.

```

10626 \str_new:N \l__iow_file_name_str

```

(End definition for \l__iow_file_name_str.)

\iow_open:Nn The same idea as for reading, but without the path and without the need to allow for a conditional version.

\iow_open:cn

__iow_open_stream:Nn

__iow_open_stream:NV

```

10627 \cs_new_protected:Npn \iow_open:Nn #1#2
10628 {
10629   \__kernel_file_name_sanitiz:n {#2} \l__iow_file_name_str
10630   \iow_close:N #1
10631   \seq_gpop:NNTF \g__iow_streams_seq \l__iow_stream_tl
10632   { \__iow_open_stream:NV #1 \l__iow_file_name_str }
10633   (*initex)
10634   { \__kernel_msg_fatal:nn { kernel } { output-streams-exhausted } }
10635   (/initex)
10636   (*package)
10637   {
10638     \__iow_new:N #1
10639     \tl_set:Nx \l__iow_stream_tl { \int_eval:n {#1} }
10640     \__iow_open_stream:NV #1 \l__iow_file_name_str
10641   }
10642   (/package)
10643 }
10644 \cs_generate_variant:Nn \iow_open:Nn { c }
10645 \cs_new_protected:Npn \__iow_open_stream:Nn #1#2
10646 {
10647   \tex_global:D \tex_chardef:D #1 = \l__iow_stream_tl \scan_stop:
10648   \prop_gput:Nvn \g__iow_streams_prop #1 {#2}
10649   \tex_immediate:D \tex_openout:D #1 #2 \scan_stop:
10650 }
10651 \cs_generate_variant:Nn \__iow_open_stream:Nn { NV }

```

(End definition for \iow_open:Nn and __iow_open_stream:Nn. This function is documented on page 145.)

\iow_close:N Closing a stream is not quite the reverse of opening one. First, the close operation is easier than the open one, and second as the stream is actually a number we can use it directly to show that the slot has been freed up.

\iow_close:c

```

10652 \cs_new_protected:Npn \iow_close:N #1
10653 {
10654   \int_compare:nT { - \c_log_iow < #1 < \c_term_iow }
10655   {
10656     \tex_immediate:D \tex_closeout:D #1
10657     \prop_gremove:Nv \g__iow_streams_prop #1
10658     \seq_if_in:NVF \g__iow_streams_seq #1
10659     { \seq_gpush:Nv \g__iow_streams_seq #1 }
10660     \cs_gset_eq:NN #1 \c_term_iow
10661   }
10662 }
10663 \cs_generate_variant:Nn \iow_close:N { c }

```

(End definition for \iow_close:N. This function is documented on page 145.)

\iow_show_list: Done as for input, but with a copy of the auxiliary so the name is correct.

\iow_log_list:

__iow_list:N

```

10664 \cs_new_protected:Npn \iow_show_list: { \__iow_list:N \msg_show:nnxxxx }
10665 \cs_new_protected:Npn \iow_log_list: { \__iow_list:N \msg_log:nnxxxx }
10666 \cs_new_protected:Npn \__iow_list:N #1
10667 {

```

```

10668     #1 { LaTeX / kernel } { show-streams }
10669     { iow }
10670     {
10671         \prop_map_function:NN \g__iow_streams_prop
10672         \msg_show_item_unbraced:nn
10673     }
10674     { } { }
10675 }

```

(End definition for `\iow_show_list:`, `\iow_log_list:`, and `__iow_list:N`. These functions are documented on page 145.)

18.3.1 Deferred writing

`\iow_shipout_x:Nn` First the easy part, this is the primitive, which expects its argument to be braced.

```

\iow_shipout_x:Nx 10676 \cs_new_protected:Npn \iow_shipout_x:Nn #1#2
\iow_shipout_x:cn 10677 { \tex_write:D #1 {#2} }
\iow_shipout_x:cx 10678 \cs_generate_variant:Nn \iow_shipout_x:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout_x:Nn`. This function is documented on page 149.)

`\iow_shipout:Nn` With ε -TeX available deferred writing without expansion is easy.

```

\iow_shipout:Nx 10679 \cs_new_protected:Npn \iow_shipout:Nn #1#2
\iow_shipout:cn 10680 { \tex_write:D #1 { \exp_not:n {#2} } }
\iow_shipout:cx 10681 \cs_generate_variant:Nn \iow_shipout:Nn { c, Nx, cx }

```

(End definition for `\iow_shipout:Nn`. This function is documented on page 149.)

18.3.2 Immediate writing

`__kernel_iow_with:Nnn` If the integer #1 is equal to #2, just leave #3 in the input stream. Otherwise, pass the old value to an auxiliary, which sets the integer to the new value, runs the code, and restores the integer.

```

10682 \cs_new_protected:Npn \__kernel_iow_with:Nnn #1#2
10683 {
10684     \int_compare:nNnTF {#1} = {#2}
10685     { \use:n }
10686     { \exp_args:No \__iow_with:nNnn { \int_use:N #1 } #1 {#2} }
10687 }
10688 \cs_new_protected:Npn \__iow_with:nNnn #1#2#3#4
10689 {
10690     \int_set:Nn #2 {#3}
10691     #4
10692     \int_set:Nn #2 {#1}
10693 }

```

(End definition for `__kernel_iow_with:Nnn` and `__iow_with:nNnn`.)

`\iow_now:Nn` This routine writes the second argument onto the output stream without expansion. If this stream isn't open, the output goes to the terminal instead. If the first argument is no output stream at all, we get an internal error. We don't use the expansion done by `\write` to get the Nx variant, because it differs in subtle ways from x-expansion, namely, macro parameter characters would not need to be doubled. We set the `\newlinechar` to 10 using `__kernel_iow_with:Nnn` to support formats such as plain TeX: otherwise,

`\iow_newline:` would not work. We do not do this for `\iow_shipout:Nn` or `\iow_shipout_x:Nn`, as \TeX looks at the value of the `\newlinechar` at shipout time in those cases.

```

10694 \cs_new_protected:Npn \iow_now:Nn #1#2
10695 {
10696   \__kernel_iow_with:Nnn \tex_newlinechar:D { '\^^J }
10697   { \tex_immediate:D \tex_write:D #1 { \exp_not:n {#2} } }
10698 }
10699 \cs_generate_variant:Nn \iow_now:Nn { c, Nx, cx }

```

(End definition for `\iow_now:Nn`. This function is documented on page 148.)

```

\iow_log:n Writing to the log and the terminal directly are relatively easy.
\iow_log:x 10700 \cs_set_protected:Npn \iow_log:x { \iow_now:Nx \c_log_iow }
\iow_term:n 10701 \cs_new_protected:Npn \iow_log:n { \iow_now:Nn \c_log_iow }
\iow_term:x 10702 \cs_set_protected:Npn \iow_term:x { \iow_now:Nx \c_term_iow }
10703 \cs_new_protected:Npn \iow_term:n { \iow_now:Nn \c_term_iow }

```

(End definition for `\iow_log:n` and `\iow_term:n`. These functions are documented on page 148.)

18.3.3 Special characters for writing

`\iow_newline:` Global variable holding the character that forces a new line when something is written to an output stream.

```

10704 \cs_new:Npn \iow_newline: { ^^J }

```

(End definition for `\iow_newline:.` This function is documented on page 149.)

`\iow_char:N` Function to write any escaped char to an output stream.

```

10705 \cs_new_eq:NN \iow_char:N \cs_to_str:N

```

(End definition for `\iow_char:N`. This function is documented on page 149.)

18.3.4 Hard-wrapping lines to a character count

The code here implements a generic hard-wrapping function. This is used by the messaging system, but is designed such that it is available for other uses.

`\l_iow_line_count_int` This is the “raw” number of characters in a line which can be written to the terminal. The standard value is the line length typically used by \TeX Live and $\text{MiK}\TeX$.

```

10706 \int_new:N \l_iow_line_count_int
10707 \int_set:Nn \l_iow_line_count_int { 78 }

```

(End definition for `\l_iow_line_count_int`. This variable is documented on page 150.)

`\l__iow_newline_tl` The token list inserted to produce a new line, with the *⟨run-on text⟩*.

```

10708 \tl_new:N \l__iow_newline_tl

```

(End definition for `\l__iow_newline_tl`.)

`\l_iow_line_target_int` This stores the target line count: the full number of characters in a line, minus any part for a leader at the start of each line.

```

10709 \int_new:N \l_iow_line_target_int

```

(End definition for `\l_iow_line_target_int`.)

`__iow_set_indent:n` The `one_indent` variables hold one indentation marker and its length. The `__iow_unindent:w` auxiliary removes one indentation. The function `__iow_set_indent:n` (that could possibly be public) sets the indentation in a consistent way. We set it to four spaces by default.

```

10710 \tl_new:N \l__iow_one_indent_tl
10711 \int_new:N \l__iow_one_indent_int
10712 \cs_new:Npn \__iow_unindent:w { }
10713 \cs_new_protected:Npn \__iow_set_indent:n #1
10714 {
10715   \tl_set:Nx \l__iow_one_indent_tl
10716     { \exp_args:No \__kernel_str_to_other_fast:n { \tl_to_str:n {#1} } }
10717   \int_set:Nn \l__iow_one_indent_int
10718     { \str_count:N \l__iow_one_indent_tl }
10719   \exp_last_unbraced:NNo
10720     \cs_set:Npn \__iow_unindent:w \l__iow_one_indent_tl { }
10721 }
10722 \exp_args:Nx \__iow_set_indent:n { \prg_replicate:nn { 4 } { ~ } }

```

(End definition for `__iow_set_indent:n` and others.)

`\l__iow_indent_tl` The current indentation (some copies of `\l__iow_one_indent_tl`) and its number of
`\l__iow_indent_int` characters.

```

10723 \tl_new:N \l__iow_indent_tl
10724 \int_new:N \l__iow_indent_int

```

(End definition for `\l__iow_indent_tl` and `\l__iow_indent_int`.)

`\l__iow_line_tl` These hold the current line of text and a partial line to be added to it, respectively.
`\l__iow_line_part_tl`

```

10725 \tl_new:N \l__iow_line_tl
10726 \tl_new:N \l__iow_line_part_tl

```

(End definition for `\l__iow_line_tl` and `\l__iow_line_part_tl`.)

`\l__iow_line_break_bool` Indicates whether the line was broken precisely at a chunk boundary.

```

10727 \bool_new:N \l__iow_line_break_bool

```

(End definition for `\l__iow_line_break_bool`.)

`\l__iow_wrap_tl` Used for the expansion step before detokenizing, and for the output from wrapping text: fully expanded and with lines which are not overly long.

```

10728 \tl_new:N \l__iow_wrap_tl

```

(End definition for `\l__iow_wrap_tl`.)

`\c__iow_wrap_marker_tl` Every special action of the wrapping code is starts with the same recognizable string,
`\c__iow_wrap_end_marker_tl` `\c__iow_wrap_marker_tl`. Upon seeing that “word”, the wrapping code reads one space-
`\c__iow_wrap_newline_marker_tl` delimited argument to know what operation to perform. The setting of `\escapechar` here
`\c__iow_wrap_allow_break_marker_tl` is not very important, but makes `\c__iow_wrap_marker_tl` look marginally nicer.

```

10729 \group_begin:
10730   \int_set:Nn \tex_escapechar:D { -1 }
10731   \tl_const:Nx \c__iow_wrap_marker_tl
10732     { \tl_to_str:n { \^^I \^^O \^^W \^^_ \^^W \^^R \^^A \^^P } }
10733 \group_end:
10734 \tl_map_inline:nn

```

```

10735 { { end } { newline } { allow_break } { indent } { unindent } }
10736 {
10737     \tl_const:cx { c__iow_wrap_ #1 _marker_tl }
10738     {
10739         \c__iow_wrap_marker_tl
10740         #1
10741         \c_catcode_other_space_tl
10742     }
10743 }

```

(End definition for `\c__iow_wrap_marker_tl` and others.)

`\iow_allow_break:` We set `\iow_allow_break:n` to produce an error when outside messages. Within wrapped message, it is set to `__iow_allow_break:` when valid and otherwise to `__iow_allow_break_error:`. The second produces an error expandably.

```

10744 \cs_new_protected:Npn \iow_allow_break:
10745 {
10746     \__kernel_msg_error:nnnn { kernel } { iow-indent }
10747     { \iow_wrap:nnnN } { \iow_allow_break: }
10748 }
10749 \cs_new:Npx \__iow_allow_break: { \c__iow_wrap_allow_break_marker_tl }
10750 \cs_new:Npn \__iow_allow_break_error:
10751 {
10752     \__kernel_msg_expandable_error:nnnn { kernel } { iow-indent }
10753     { \iow_wrap:nnnN } { \iow_allow_break: }
10754 }

```

(End definition for `\iow_allow_break:`, `__iow_allow_break:`, and `__iow_allow_break_error:`. This function is documented on page 244.)

`\iow_indent:n` We set `\iow_indent:n` to produce an error when outside messages. Within wrapped message, it is set to `__iow_indent:n` when valid and otherwise to `__iow_indent_error:n`. The first places the instruction for increasing the indentation before its argument, and the instruction for unindenting afterwards. The second produces an error expandably. Note that there are no forced line-break, so the indentation only changes when the next line is started.

```

10755 \cs_new_protected:Npn \iow_indent:n #1
10756 {
10757     \__kernel_msg_error:nnnnn { kernel } { iow-indent }
10758     { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
10759     #1
10760 }
10761 \cs_new:Npx \__iow_indent:n #1
10762 {
10763     \c__iow_wrap_indent_marker_tl
10764     #1
10765     \c__iow_wrap_unindent_marker_tl
10766 }
10767 \cs_new:Npn \__iow_indent_error:n #1
10768 {
10769     \__kernel_msg_expandable_error:nnnnn { kernel } { iow-indent }
10770     { \iow_wrap:nnnN } { \iow_indent:n } { #1 }
10771     #1
10772 }

```

(End definition for `\iow_indent:n`, `__iow_indent:n`, and `__iow_indent_error:n`. This function is documented on page 150.)

`\iow_wrap:nnnN` The main wrapping function works as follows. First give `\`, `_` and other formatting commands the correct definition for messages and perform the given setup #3. `\iow_wrap:nxnN` The definition of `_` uses an “other” space rather than a normal space, because the latter might be absorbed by \TeX to end a number or other f-type expansions. Use `\conditionally@traceoff` if defined; it is introduced by the `trace` package and suppresses uninteresting tracing of the wrapping code.

```

10773 \cs_new_protected:Npn \iow_wrap:nnnN #1#2#3#4
10774 {
10775   \group_begin:
10776   <package> \use:c { conditionally@traceoff }
10777   \int_set:Nn \tex_escapechar:D { -1 }
10778   \cs_set:Npx \{ { \token_to_str:N \{ }
10779   \cs_set:Npx \# { \token_to_str:N \# }
10780   \cs_set:Npx \} { \token_to_str:N \} }
10781   \cs_set:Npx \% { \token_to_str:N \% }
10782   \cs_set:Npx \~ { \token_to_str:N \~ }
10783   \int_set:Nn \tex_escapechar:D { 92 }
10784   \cs_set_eq:NN \_ \iow_newline:
10785   \cs_set_eq:NN \_c_catcode_other_space_tl
10786   \cs_set_eq:NN \iow_allow_break: \__iow_allow_break:
10787   \cs_set_eq:NN \iow_indent:n \__iow_indent:n
10788   #3

```

Then fully-expand the input: in package mode, the expansion uses \LaTeX 2 ϵ ’s `\protect` mechanism in the same way as `\typeout`. In generic mode this setting is useless but harmless. As soon as the expansion is done, reset `\iow_indent:n` to its error definition: it only works in the first argument of `\iow_wrap:nnnN`.

```

10789 <package> \cs_set_eq:NN \protect \token_to_str:N
10790 \tl_set:Nx \l__iow_wrap_tl {#1}
10791 \cs_set_eq:NN \iow_allow_break: \__iow_allow_break_error:
10792 \cs_set_eq:NN \iow_indent:n \__iow_indent_error:n

```

Afterwards, set the newline marker (two assignments to fully expand, then convert to a string) and initialize the target count for lines (the first line has target count `\l_iow_line_count_int` instead).

```

10793 \tl_set:Nx \l__iow_newline_tl { \iow_newline: #2 }
10794 \tl_set:Nx \l__iow_newline_tl { \tl_to_str:N \l__iow_newline_tl }
10795 \int_set:Nn \l__iow_line_target_int
10796 { \l_iow_line_count_int - \str_count:N \l__iow_newline_tl + 1 }

```

Sanity check.

```

10797 \int_compare:nNnT { \l__iow_line_target_int } < 0
10798 {
10799   \tl_set:Nn \l__iow_newline_tl { \iow_newline: }
10800   \int_set:Nn \l__iow_line_target_int
10801   { \l_iow_line_count_int + 1 }
10802 }

```

There is then a loop over the input, which stores the wrapped result in `\l__iow_wrap_tl`. After the loop, the resulting text is passed on to the function which has been given as a post-processor. The `\tl_to_str:N` step converts the “other” spaces back to normal spaces. The f-expansion removes a leading space from `\l__iow_wrap_tl`.


```

10803     \__iow_wrap_do:
10804     \exp_args:NNf \group_end:
10805     #4 { \tl_to_str:N \l__iow_wrap_tl }
10806   }
10807 \cs_generate_variant:Nn \iow_wrap:nnnN { nx }

```

(End definition for \iow_wrap:nnnN. This function is documented on page ??.)

__iow_wrap_do: Escape spaces and change newlines to \c__iow_wrap_newline_marker_tl. Set up a few variables, in particular the initial value of \l__iow_wrap_tl: the space stops the f-expansion of the main wrapping function and \use_none:n removes a newline marker inserted by later code. The main loop consists of repeatedly calling the chunk auxiliary to wrap chunks delimited by (newline or indentation) markers.

```

10808 \cs_new_protected:Npn \__iow_wrap_do:
10809 {
10810   \tl_set:Nx \l__iow_wrap_tl
10811   {
10812     \exp_args:No \__kernel_str_to_other_fast:n \l__iow_wrap_tl
10813     \c__iow_wrap_end_marker_tl
10814   }
10815   \tl_set:Nx \l__iow_wrap_tl
10816   {
10817     \exp_after:wN \__iow_wrap_fix_newline:w \l__iow_wrap_tl
10818     ^^J \q_nil ^^J \q_stop
10819   }
10820   \exp_after:wN \__iow_wrap_start:w \l__iow_wrap_tl
10821 }
10822 \cs_new:Npn \__iow_wrap_fix_newline:w #1 ^^J #2 ^^J
10823 {
10824   #1
10825   \if_meaning:w \q_nil #2
10826     \use_i_delimit_by_q_stop:nw
10827   \fi:
10828   \c__iow_wrap_newline_marker_tl
10829   \__iow_wrap_fix_newline:w #2 ^^J
10830 }
10831 \cs_new_protected:Npn \__iow_wrap_start:w
10832 {
10833   \bool_set_false:N \l__iow_line_break_bool
10834   \tl_clear:N \l__iow_line_tl
10835   \tl_clear:N \l__iow_line_part_tl
10836   \tl_set:Nn \l__iow_wrap_tl { ~ \use_none:n }
10837   \int_zero:N \l__iow_indent_int
10838   \tl_clear:N \l__iow_indent_tl
10839   \__iow_wrap_chunk:nw { \l__iow_line_count_int }
10840 }

```

(End definition for __iow_wrap_do:, __iow_wrap_fix_newline:w, and __iow_wrap_start:w.)

__iow_wrap_chunk:nw The chunk and next auxiliaries are defined indirectly to obtain the expansions of \c_catcode_other_space_tl and \c__iow_wrap_marker_tl in their definition. The next auxiliary calls a function corresponding to the type of marker (its ##2), which can be newline or indent or unindent or end. The first argument of the chunk auxiliary is a target number of characters and the second is some string to wrap. If the chunk is

empty simply call `next`. Otherwise, set up a call to `__iow_wrap_line:nw`, including the indentation if the current line is empty, and including a trailing space (`#1`) before the `__iow_wrap_end_chunk:w` auxiliary.

```

10841 \cs_set_protected:Npn \__iow_tmp:w #1#2
10842 {
10843   \cs_new_protected:Npn \__iow_wrap_chunk:nw ##1##2 #2
10844   {
10845     \tl_if_empty:NTF {##2}
10846     {
10847       \tl_clear:N \l__iow_line_part_tl
10848       \__iow_wrap_next:nw {##1}
10849     }
10850     {
10851       \tl_if_empty:NTF \l__iow_line_tl
10852       {
10853         \__iow_wrap_line:nw
10854         { \l__iow_indent_tl }
10855         ##1 - \l__iow_indent_int ;
10856       }
10857       { \__iow_wrap_line:nw { } ##1 ; }
10858       ##2 #1
10859       \__iow_wrap_end_chunk:w 7 6 5 4 3 2 1 0 \q_stop
10860     }
10861   }
10862   \cs_new_protected:Npn \__iow_wrap_next:nw ##1##2 #1
10863   { \use:c { __iow_wrap_##2:n } {##1} }
10864 }
10865 \exp_args:NVV \__iow_tmp:w \c_catcode_other_space_tl \c__iow_wrap_marker_tl

```

(End definition for `__iow_wrap_chunk:nw` and `__iow_wrap_next:nw`.)

`__iow_wrap_line:nw` This is followed by `{\langle string \rangle \langle intexpr \rangle ;}`. It stores the `\langle string \rangle` and up to `\langle intexpr \rangle` characters from the current chunk into `\l__iow_line_part_tl`. Characters are grabbed 8 at a time and left in `\l__iow_line_part_tl` by the `line_loop` auxiliary. When $k < 8$ remain to be found, the `line_aux` auxiliary calls the `line_end` auxiliary followed by (the single digit) k , then $7 - k$ empty brace groups, then the chunk's remaining characters. The `line_end` auxiliary leaves k characters from the chunk in the line part, then ends the assignment. Ignore the `\use_none:nnnnn` line for now. If the next character is a space the line can be broken there: store what we found into the result and get the next line. Otherwise some work is needed to find a break-point. So far we have ignored what happens if the chunk is shorter than the requested number of characters: this is dealt with by the `end_chunk` auxiliary, which gets treated like a character by the rest of the code. It ends up being called either as one of the arguments `#2-#9` of the `line_loop` auxiliary or as one of the arguments `#2-#8` of the `line_end` auxiliary. In both cases stop the assignment and work out how many characters are still needed. Notice that when we have exactly seven arguments to clean up, a `\exp_stop_f:` has to be inserted to stop the `\exp:w`. The weird `\use_none:nnnnn` ensures that the required data is in the right place.

```

10866 \cs_new_protected:Npn \__iow_wrap_line:nw #1
10867 {
10868   \tex_edef:D \l__iow_line_part_tl { \if_false: } \fi:
10869   #1

```

```

10870     \exp_after:wN \__iow_wrap_line_loop:w
10871     \int_value:w \int_eval:w
10872   }
10873   \cs_new:Npn \__iow_wrap_line_loop:w #1 ; #2#3#4#5#6#7#8#9
10874   {
10875     \if_int_compare:w #1 < 8 \exp_stop_f:
10876     \__iow_wrap_line_aux:Nw #1
10877     \fi:
10878     #2 #3 #4 #5 #6 #7 #8 #9
10879     \exp_after:wN \__iow_wrap_line_loop:w
10880     \int_value:w \int_eval:w #1 - 8 ;
10881   }
10882   \cs_new:Npn \__iow_wrap_line_aux:Nw #1#2#3 \exp_after:wN #4 ;
10883   {
10884     #2
10885     \exp_after:wN \__iow_wrap_line_end:NnnnnnnnN
10886     \exp_after:wN #1
10887     \exp:w \exp_end_continue_f:w
10888     \exp_after:wN \exp_after:wN
10889     \if_case:w #1 \exp_stop_f:
10890       \prg_do_nothing:
10891     \or: \use_none:n
10892     \or: \use_none:nn
10893     \or: \use_none:nnn
10894     \or: \use_none:nnnn
10895     \or: \use_none:nnnnn
10896     \or: \use_none:nnnnnn
10897     \or: \__iow_wrap_line_seven:nnnnnnn
10898     \fi:
10899     { } { } { } { } { } { } { } { } { } #3
10900   }
10901   \cs_new:Npn \__iow_wrap_line_seven:nnnnnnn #1#2#3#4#5#6#7 { \exp_stop_f: }
10902   \cs_new:Npn \__iow_wrap_line_end:NnnnnnnnN #1#2#3#4#5#6#7#8#9
10903   {
10904     #2 #3 #4 #5 #6 #7 #8
10905     \use_none:nnnnn \int_eval:w 8 - ; #9
10906     \token_if_eq_charcode:NNTF \c_space_token #9
10907     { \__iow_wrap_line_end:nw { } }
10908     { \if_false: { \fi: } \__iow_wrap_break:w #9 }
10909   }
10910   \cs_new:Npn \__iow_wrap_line_end:nw #1
10911   {
10912     \if_false: { \fi: }
10913     \__iow_wrap_store_do:n {#1}
10914     \__iow_wrap_next_line:w
10915   }
10916   \cs_new:Npn \__iow_wrap_end_chunk:w
10917   #1 \int_eval:w #2 - #3 ; #4#5 \q_stop
10918   {
10919     \if_false: { \fi: }
10920     \exp_args:Nf \__iow_wrap_next:nw { \int_eval:n { #2 - #4 } }
10921   }

```

(End definition for __iow_wrap_line:nw and others.)

`__iow_wrap_break:w`
`__iow_wrap_break_first:w`
`__iow_wrap_break_none:w`
`__iow_wrap_break_loop:w`
`__iow_wrap_break_end:w`

Functions here are defined indirectly: `__iow_tmp:w` is eventually called with an “other” space as its argument. The goal is to remove from `\l__iow_line_part_tl` the part after the last space. In most cases this is done by repeatedly calling the `break_loop` auxiliary, which leaves “words” (delimited by spaces) until it hits the trailing space: then its argument `##3` is `__iow_wrap_break_end:w` instead of a single token, and that `break_end` auxiliary leaves in the assignment the line until the last space, then calls `__iow_wrap_line_end:nw` to finish up the line and move on to the next. If there is no space in `\l__iow_line_part_tl` then the `break_first` auxiliary calls the `break_none` auxiliary. In that case, if the current line is empty, the complete word (including `##4`, characters beyond what we had grabbed) is added to the line, making it over-long. Otherwise, the word is used for the following line (and the last space of the line so far is removed because it was inserted due to the presence of a marker).

```

10922 \cs_set_protected:Npn \__iow_tmp:w #1
10923 {
10924   \cs_new:Npn \__iow_wrap_break:w
10925   {
10926     \tex_edef:D \l__iow_line_part_tl
10927     { \if_false: } \fi:
10928     \exp_after:wN \__iow_wrap_break_first:w
10929     \l__iow_line_part_tl
10930     #1
10931     { ? \__iow_wrap_break_end:w }
10932     \q_mark
10933   }
10934   \cs_new:Npn \__iow_wrap_break_first:w ##1 #1 ##2
10935   {
10936     \use_none:nn ##2 \__iow_wrap_break_none:w
10937     \__iow_wrap_break_loop:w ##1 #1 ##2
10938   }
10939   \cs_new:Npn \__iow_wrap_break_none:w ##1##2 #1 ##3 \q_mark ##4 #1
10940   {
10941     \tl_if_empty:NTF \l__iow_line_tl
10942     { ##2 ##4 \__iow_wrap_line_end:nw { } }
10943     { \__iow_wrap_line_end:nw { \__iow_wrap_trim:N } ##2 ##4 #1 }
10944   }
10945   \cs_new:Npn \__iow_wrap_break_loop:w ##1 #1 ##2 #1 ##3
10946   {
10947     \use_none:n ##3
10948     ##1 #1
10949     \__iow_wrap_break_loop:w ##2 #1 ##3
10950   }
10951   \cs_new:Npn \__iow_wrap_break_end:w ##1 #1 ##2 ##3 #1 ##4 \q_mark
10952   { ##1 \__iow_wrap_line_end:nw { } ##3 }
10953 }
10954 \exp_args:NV \__iow_tmp:w \c_catcode_other_space_tl

```

(End definition for `__iow_wrap_break:w` and others.)

`__iow_wrap_next_line:w`

The special case where the end of a line coincides with the end of a chunk is detected here, to avoid a spurious empty line. Otherwise, call `__iow_wrap_line:nw` to find characters for the next line (remembering to account for the indentation).

```

10955 \cs_new_protected:Npn \__iow_wrap_next_line:w #1#2 \q_stop
10956 {

```

```

10957 \tl_clear:N \l__iow_line_tl
10958 \token_if_eq_meaning:NNTF #1 \__iow_wrap_end_chunk:w
10959 {
10960   \tl_clear:N \l__iow_line_part_tl
10961   \bool_set_true:N \l__iow_line_break_bool
10962   \__iow_wrap_next:nw { \l__iow_line_target_int }
10963 }
10964 {
10965   \__iow_wrap_line:nw
10966   { \l__iow_indent_tl }
10967   \l__iow_line_target_int - \l__iow_indent_int ;
10968   #1 #2 \q_stop
10969 }
10970 }

```

(End definition for __iow_wrap_next_line:w.)

__iow_wrap_allow_break:n This is called after a chunk has been wrapped. The \l__iow_line_part_tl typically ends with a space (except at the beginning of a line?), which we remove since the **allow_break** marker should not insert a space. Then move on with the next chunk, making sure to adjust the target number of characters for the line in case we did remove a space.

```

10971 \cs_new_protected:Npn \__iow_wrap_allow_break:n #1
10972 {
10973   \tl_set:Nx \l__iow_line_tl
10974   { \l__iow_line_tl \__iow_wrap_trim:N \l__iow_line_part_tl }
10975   \bool_set_false:N \l__iow_line_break_bool
10976   \tl_if_empty:NNTF \l__iow_line_part_tl
10977   { \__iow_wrap_chunk:nw {#1} }
10978   { \exp_args:Nf \__iow_wrap_chunk:nw { \int_eval:n { #1 + 1 } } }
10979 }

```

(End definition for __iow_wrap_allow_break:n.)

__iow_wrap_indent:n These functions are called after a chunk has been wrapped, when encountering **indent/unindent** markers. Add the line part (last line part of the previous chunk) to the line so far and reset a boolean denoting the presence of a line-break. Most importantly, add or remove one indent from the current indent (both the integer and the token list). Finally, continue wrapping.

__iow_wrap_unindent:n

```

10980 \cs_new_protected:Npn \__iow_wrap_indent:n #1
10981 {
10982   \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
10983   \bool_set_false:N \l__iow_line_break_bool
10984   \int_add:Nn \l__iow_indent_int { \l__iow_one_indent_int }
10985   \tl_put_right:No \l__iow_indent_tl { \l__iow_one_indent_tl }
10986   \__iow_wrap_chunk:nw {#1}
10987 }
10988 \cs_new_protected:Npn \__iow_wrap_unindent:n #1
10989 {
10990   \tl_put_right:Nx \l__iow_line_tl { \l__iow_line_part_tl }
10991   \bool_set_false:N \l__iow_line_break_bool
10992   \int_sub:Nn \l__iow_indent_int { \l__iow_one_indent_int }
10993   \tl_set:Nx \l__iow_indent_tl
10994   { \exp_after:wN \__iow_unindent:w \l__iow_indent_tl }
10995   \__iow_wrap_chunk:nw {#1}
10996 }

```

(End definition for _iow_wrap_indent:n and _iow_wrap_unindent:n.)

_iow_wrap_newline:n These functions are called after a chunk has been line-wrapped, when encountering a
 _iow_wrap_end:n newline/end marker. Unless we just took a line-break, store the line part and the line
 so far into the whole \l__iow_wrap_tl, trimming a trailing space. In the newline case
 look for a new line (of length \l__iow_line_target_int) in a new chunk.

```

10997 \cs_new_protected:Npn \_iow_wrap_newline:n #1
10998 {
10999   \bool_if:NF \l__iow_line_break_bool
11000     { \_iow_wrap_store_do:n { \_iow_wrap_trim:N } }
11001   \bool_set_false:N \l__iow_line_break_bool
11002   \_iow_wrap_chunk:nw { \l__iow_line_target_int }
11003 }
11004 \cs_new_protected:Npn \_iow_wrap_end:n #1
11005 {
11006   \bool_if:NF \l__iow_line_break_bool
11007     { \_iow_wrap_store_do:n { \_iow_wrap_trim:N } }
11008   \bool_set_false:N \l__iow_line_break_bool
11009 }

```

(End definition for _iow_wrap_newline:n and _iow_wrap_end:n.)

_iow_wrap_store_do:n First add the last line part to the line, then append it to \l__iow_wrap_tl with the
 appropriate new line (with “run-on” text), possibly with its last space removed (#1 is
 empty or _iow_wrap_trim:N).

```

11010 \cs_new_protected:Npn \_iow_wrap_store_do:n #1
11011 {
11012   \tl_set:Nx \l__iow_line_tl
11013     { \l__iow_line_tl \l__iow_line_part_tl }
11014   \tl_set:Nx \l__iow_wrap_tl
11015     {
11016       \l__iow_wrap_tl
11017       \l__iow_newline_tl
11018       #1 \l__iow_line_tl
11019     }
11020   \tl_clear:N \l__iow_line_tl
11021 }

```

(End definition for _iow_wrap_store_do:n.)

_iow_wrap_trim:N Remove one trailing “other” space from the argument if present.

```

\_iow_wrap_trim:w
\_iow_wrap_trim_aux:w
11022 \cs_set_protected:Npn \_iow_tmp:w #1
11023 {
11024   \cs_new:Npn \_iow_wrap_trim:N ##1
11025     { \exp_after:wN \_iow_wrap_trim:w ##1 \q_mark #1 \q_mark \q_stop }
11026   \cs_new:Npn \_iow_wrap_trim:w ##1 #1 \q_mark
11027     { \_iow_wrap_trim_aux:w ##1 \q_mark }
11028   \cs_new:Npn \_iow_wrap_trim_aux:w ##1 \q_mark ##2 \q_stop {##1}
11029 }
11030 \exp_args:NV \_iow_tmp:w \c_catcode_other_space_tl

```

(End definition for _iow_wrap_trim:N, _iow_wrap_trim:w, and _iow_wrap_trim_aux:w.)

```

11031 <@@=file>

```

18.4 File operations

`\l__file_internal_tl` Used as a short-term scratch variable.

```
11032 \tl_new:N \l__file_internal_tl
```

(End definition for `\l__file_internal_tl`.)

`\g__file_internal_ior` A reserved stream to test for file existence.

```
11033 \ior_new:N \g__file_internal_ior
```

(End definition for `\g__file_internal_ior`.)

`\g_file_curr_dir_str` The name of the current file should be available at all times. For the format the file name
`\g_file_curr_ext_str` needs to be picked up at the start of the run. In L^AT_EX 2_ε package mode the current file
`\g_file_curr_name_str` name is collected from `\@currname`.

```
11034 \str_new:N \g_file_curr_dir_str
11035 \str_new:N \g_file_curr_ext_str
11036 \str_new:N \g_file_curr_name_str
11037 \<initex>
11038 \tex_everyjob:D \exp_after:wN
11039 {
11040   \tex_the:D \tex_everyjob:D
11041   \str_gset:Nx \g_file_curr_name_str { \tex_jobname:D }
11042 }
11043 \</initex>
11044 \<*package>
11045 \cs_if_exist:NT \@currname
11046 { \str_gset_eq:NN \g_file_curr_name_str \@currname }
11047 \</package>
```

(End definition for `\g_file_curr_dir_str`, `\g_file_curr_ext_str`, and `\g_file_curr_name_str`. These variables are documented on page 151.)

`\g__file_stack_seq` The input list of files is stored as a sequence stack. In package mode we can recover the information from the details held by L^AT_EX 2_ε (we must be in the preamble and loaded using `\usepackage` or `\RequirePackage`). As L^AT_EX 2_ε doesn't store directory and name separately, we stick to the same convention here.

```
11048 \seq_new:N \g__file_stack_seq
11049 \<*package>
11050 \group_begin:
11051   \cs_set_protected:Npn \__file_tmp:w #1#2#3
11052   {
11053     \tl_if_blank:nTF {#1}
11054     {
11055       \cs_set:Npn \__file_tmp:w ##1 " ##2 " ##3 \q_stop
11056       { { } {##2} { } }
11057       \seq_gput_right:Nx \g__file_stack_seq
11058       {
11059         \exp_after:wN \__file_tmp:w \tex_jobname:D
11060         " \tex_jobname:D " \q_stop
11061       }
11062     }
11063   }
11064   \seq_gput_right:Nn \g__file_stack_seq { { } {#1} {#2} }
```

```

11065         \__file_tmp:w
11066     }
11067 }
11068 \cs_if_exist:NT \@currnamestack
11069 { \exp_after:wN \__file_tmp:w \@currnamestack }
11070 \group_end:
11071 \</package>

```

(End definition for \g__file_stack_seq.)

\g__file_record_seq The total list of files used is recorded separately from the current file stack, as nothing is ever popped from this list. The current file name should be included in the file list! In format mode, this is done at the very start of the T_EX run. In package mode we will eventually copy the contents of \@filelist.

```

11072 \seq_new:N \g__file_record_seq
11073 \<{*initex>
11074 \tex_everyjob:D \exp_after:wN
11075 {
11076     \tex_the:D \tex_everyjob:D
11077     \seq_gput_right:NV \g__file_record_seq \g_file_curr_name_str
11078 }
11079 \</initex>

```

(End definition for \g__file_record_seq.)

\l__file_base_name_str For storing the basename and full path whilst passing data internally.

```

\l__file_full_name_str
11080 \str_new:N \l__file_base_name_str
11081 \str_new:N \l__file_full_name_str

```

(End definition for \l__file_base_name_str and \l__file_full_name_str.)

\l__file_dir_str Used in parsing a path into parts: in contrast to the above, these are never used outside of the current module.

```

\l__file_ext_str
\l__file_name_str
11082 \str_new:N \l__file_dir_str
11083 \str_new:N \l__file_ext_str
11084 \str_new:N \l__file_name_str

```

(End definition for \l__file_dir_str, \l__file_ext_str, and \l__file_name_str.)

\l_file_search_path_seq The current search path.

```

11085 \seq_new:N \l_file_search_path_seq

```

(End definition for \l_file_search_path_seq. This variable is documented on page 152.)

\l__file_tmp_seq Scratch space for comma list conversion in package mode.

```

11086 \<{*package>
11087 \seq_new:N \l__file_tmp_seq
11088 \</package>

```

(End definition for \l__file_tmp_seq.)

`_kernel_file_name_sanitiz:nN` For converting a token list to a string where active characters are treated as strings
`_file_name_quote:nN` from the start. The logic to the quoting normalisation is the same as used by
`_file_name_sanitiz_aux:n` `lualatexquotejobname`: check for balanced `"`, and assuming they balance strip all of
them out before quoting the entire name if it contains spaces.

```

11089 \cs_new_protected:Npn \_kernel_file_name_sanitiz:nN #1#2
11090 {
11091   \group_begin:
11092     \seq_map_inline:Nn \l_char_active_seq
11093     {
11094       \tl_set:Nx \l__file_internal_tl { \iow_char:N ##1 }
11095       \char_set_active_eq:NN ##1 \l__file_internal_tl
11096     }
11097     \tl_set:Nx \l__file_internal_tl {#1}
11098     \tl_set:Nx \l__file_internal_tl
11099     { \tl_to_str:N \l__file_internal_tl }
11100     \exp_args:NNNV \group_end:
11101     \str_set:Nn #2 \l__file_internal_tl
11102   }
11103 \cs_new_protected:Npn \_file_name_quote:nN #1#2
11104 {
11105   \str_set:Nx #2 {#1}
11106   \int_if_even:nF
11107   { 0 \tl_map_function:NN #2 \_file_name_quote_aux:n }
11108   {
11109     \_kernel_msg_error:nnx
11110     { kernel } { unbalanced-quote-in-filename } {#2}
11111   }
11112   \tl_remove_all:Nn #2 { " }
11113   \tl_if_in:NnT #2 { ~ }
11114   { \str_set:Nx #2 { " \exp_not:V #2 " } }
11115 }
11116 \cs_new:Npn \_file_name_quote_aux:n #1
11117 { \token_if_eq_charcode:NNT #1 " { + 1 } }

```

(End definition for `_kernel_file_name_sanitiz:nN`, `_file_name_quote:nN`, and `_file_name_sanitiz_aux:n`.)

`\file_get_full_name:nN` The way to test if a file exists is to try to open it: if it does not exist then T_EX reports
`\file_get_full_name:VN` end-of-file. A search is made looking at each potential path in turn (starting from the
`_file_get_full_name_search:nN` current directory). The first location is of course treated as the correct one: this is
done by jumping to `\prg_break_point:.` If nothing is found, #2 is returned empty. A
special case when there is no extension is that once the first location is found we test the
existence of the file with `.tex` extension in that directory, and if it exists we include the
`.tex` extension in the result.

```

11118 \cs_new_protected:Npn \file_get_full_name:nN #1#2
11119 {
11120   \_kernel_file_name_sanitiz:nN {#1} \l__file_base_name_str
11121   \_file_get_full_name_search:nN { } \use:n
11122   \seq_map_inline:Nn \l_file_search_path_seq
11123   { \_file_get_full_name_search:nN { ##1 / } \seq_map_break:n }
11124   (*package)
11125   \cs_if_exist:NT \input@path
11126   {

```

```

11127         \tl_map_inline:Nn \input@path
11128         { \__file_get_full_name_search:nN { ##1 } \tl_map_break:n }
11129     }
11130 </package>
11131 \str_clear:N \l__file_full_name_str
11132 \prg_break_point:
11133 \str_if_empty:NF \l__file_full_name_str
11134 {
11135     \exp_args:NV \file_parse_full_name:nNNN \l__file_full_name_str
11136     \l__file_dir_str \l__file_name_str \l__file_ext_str
11137     \str_if_empty:NT \l__file_ext_str
11138     {
11139         \__kernel_ior_open:No \g__file_internal_ior
11140         { \l__file_full_name_str .tex }
11141         \ior_if_eof:NF \g__file_internal_ior
11142         { \str_put_right:Nn \l__file_full_name_str { .tex } }
11143     }
11144 }
11145 \str_set_eq:NN #2 \l__file_full_name_str
11146 \ior_close:N \g__file_internal_ior
11147 }
11148 \cs_generate_variant:Nn \file_get_full_name:nN { V }
11149 \cs_new_protected:Npn \__file_get_full_name_search:nN #1#2
11150 {
11151     \__file_name_quote:nN
11152     { \tl_to_str:n {#1} \l__file_base_name_str }
11153     \l__file_full_name_str
11154     \__kernel_ior_open:No \g__file_internal_ior \l__file_full_name_str
11155     \ior_if_eof:NF \g__file_internal_ior { #2 { \prg_break: } }
11156 }

```

(End definition for `\file_get_full_name:nN` and `__file_get_full_name_search:nN`. This function is documented on page 152.)

`\file_if_exist:nTF` The test for the existence of a file is a wrapper around the function to add a path to a file. If the file was found, the path contains something, whereas if the file was not located then the return value is empty.

```

11157 \prg_new_protected_conditional:Npnn \file_if_exist:n #1 { T , F , TF }
11158 {
11159     \file_get_full_name:nN {#1} \l__file_full_name_str
11160     \str_if_empty:NTF \l__file_full_name_str
11161     { \prg_return_false: }
11162     { \prg_return_true: }
11163 }

```

(End definition for `\file_if_exist:nTF`. This function is documented on page 152.)

`__kernel_file_missing:n` An error message for a missing file, also used in `\ior_open:Nn`.

```

11164 \cs_new_protected:Npn \__kernel_file_missing:n #1
11165 {
11166     \__kernel_file_name_sanitize:nN {#1} \l__file_base_name_str
11167     \__kernel_msg_error:nxx { kernel } { file-not-found }
11168     { \l__file_base_name_str }
11169 }

```

(End definition for _kernel_file_missing:n.)

\file_input:n Loading a file is done in a safe way, checking first that the file exists and loading only if it does. Push the file name on the \g_file_stack_seq, and add it to the file list, either \g_file_record_seq, or \@filelist in package mode.

```

\__file\_input:n
\__file\_input:V
\__file\_input\_push:n
\_kernel\_file\_input\_push:n
\__file\_input\_pop:
\_kernel\_file\_input\_pop:
\__file\_input\_pop:nnn
11170 \cs\_new\_protected:Npn \file\_input:n #1
11171 {
11172   \file\_get\_full\_name:nN {#1} \l\_file\_full\_name\_str
11173   \str\_if\_empty:NTF \l\_file\_full\_name\_str
11174     { \_kernel\_file\_missing:n {#1} }
11175     { \__file\_input:V \l\_file\_full\_name\_str }
11176 }
11177 \cs\_new\_protected:Npn \__file\_input:n #1
11178 {
11179   <*\initex>
11180   \seq\_gput\_right:Nn \g\_file\_record\_seq {#1}
11181   </\initex>
11182   <*\package>
11183   \clist\_if\_exist:NTF \@filelist
11184     { \@addtofilelist {#1} }
11185     { \seq\_gput\_right:Nn \g\_file\_record\_seq {#1} }
11186   </\package>
11187   \__file\_input\_push:n {#1}
11188   \tex\_input:D #1 \c\_space\_tl
11189   \__file\_input\_pop:
11190 }
11191 \cs\_generate\_variant:Nn \__file\_input:n { V }

```

Keeping a track of the file data is easy enough: we store the separated parts so we do not need to parse them twice.

```

11192 \cs\_new\_protected:Npn \__file\_input\_push:n #1
11193 {
11194   \seq\_gpush:Nx \g\_file\_stack\_seq
11195   {
11196     { \g\_file\_curr\_dir\_str }
11197     { \g\_file\_curr\_name\_str }
11198     { \g\_file\_curr\_ext\_str }
11199   }
11200   \file\_parse\_full\_name:nNNN {#1}
11201   \l\_file\_dir\_str \l\_file\_name\_str \l\_file\_ext\_str
11202   \str\_gset\_eq:NN \g\_file\_curr\_dir\_str \l\_file\_dir\_str
11203   \str\_gset\_eq:NN \g\_file\_curr\_name\_str \l\_file\_name\_str
11204   \str\_gset\_eq:NN \g\_file\_curr\_ext\_str \l\_file\_ext\_str
11205 }
11206 <*\package>
11207 \cs\_new\_eq:NN \_kernel\_file\_input\_push:n \__file\_input\_push:n
11208 </\package>
11209 \cs\_new\_protected:Npn \__file\_input\_pop:
11210 {
11211   \seq\_gpop:NN \g\_file\_stack\_seq \l\_file\_internal\_tl
11212   \exp\_after:wN \__file\_input\_pop:nnn \l\_file\_internal\_tl
11213 }
11214 <*\package>
11215 \cs\_new\_eq:NN \_kernel\_file\_input\_pop: \__file\_input\_pop:

```

```

11216 \package
11217 \cs_new_protected:Npn \__file_input_pop:nnn #1#2#3
11218 {
11219   \str_gset:Nn \g_file_curr_dir_str {#1}
11220   \str_gset:Nn \g_file_curr_name_str {#2}
11221   \str_gset:Nn \g_file_curr_ext_str {#3}
11222 }

```

(End definition for \file_input:n and others. This function is documented on page 152.)

```

\file_parse_full_name:nNNN
  \__file_parse_full_name_auxi:w
  \__file_parse_full_name_split:nNNNTF

```

Parsing starts by stripping off any surrounding quotes. Then find the directory #4 by splitting at the last /. (The auxiliary returns true/false depending on whether it found the delimiter.) We correct for the case of a file in the root /, as in that case we wish to keep the trailing (and only) slash. Then split the base name #5 at the last dot. If there was indeed a dot, #5 contains the name and #6 the extension without the dot, which we add back for convenience. In the special case of no extension given, the auxiliary stored the name into #6, we just have to move it to #5.

```

11223 \cs_new_protected:Npn \file_parse_full_name:nNNN #1#2#3#4
11224 {
11225   \exp_after:wN \__file_parse_full_name_auxi:w
11226   \tl_to_str:n { #1 " #1 " } \q_stop #2#3#4
11227 }
11228 \cs_new_protected:Npn \__file_parse_full_name_auxi:w
11229 #1 " #2 " #3 \q_stop #4#5#6
11230 {
11231   \__file_parse_full_name_split:nNNNTF {#2} / #4 #5
11232   { \str_if_empty:NT #4 { \str_set:Nn #4 { / } } }
11233   { }
11234   \exp_args:No \__file_parse_full_name_split:nNNNTF {#5} . #5 #6
11235   { \str_put_left:Nn #6 { . } }
11236   {
11237     \str_set_eq:NN #5 #6
11238     \str_clear:N #6
11239   }
11240 }
11241 \cs_new_protected:Npn \__file_parse_full_name_split:nNNNTF #1#2#3#4
11242 {
11243   \cs_set_protected:Npn \__file_tmp:w ##1 ##2 #2 ##3 \q_stop
11244   {
11245     \tl_if_empty:nTF {##3}
11246     {
11247       \str_set:Nn #4 {##2}
11248       \tl_if_empty:nTF {##1}
11249       {
11250         \str_clear:N #3
11251         \use_ii:nn
11252       }
11253       {
11254         \str_set:Nx #3 { \str_tail:n {##1} }
11255         \use_i:nn
11256       }
11257     }
11258     { \__file_tmp:w { ##1 #2 ##2 } ##3 \q_stop }
11259   }

```

```

11260   \_file_tmp:w { } #1 #2 \q_stop
11261 }

```

(End definition for `\file_parse_full_name:nNNN`, `_file_parse_full_name_auxi:w`, and `_file_parse_full_name_split:nNNNTF`. This function is documented on page 152.)

`\file_show_list:` A function to list all files used to the log, without duplicates. In package mode, if `\file_log_list:` `\@filelist` is still defined, we need to take this list of file names into account (we capture it `\AtBeginDocument` into `\g__file_record_seq`), turning it to a string (this does not affect the commas of this comma list).

```

11262 \cs_new_protected:Npn \file_show_list: { \_file_list:N \msg_show:nnxxxx }
11263 \cs_new_protected:Npn \file_log_list: { \_file_list:N \msg_log:nnxxxx }
11264 \cs_new_protected:Npn \_file_list:N #1
11265 {
11266   \seq_clear:N \l__file_tmp_seq
11267   (*package)
11268   \clist_if_exist:NT \@filelist
11269   {
11270     \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
11271     { \tl_to_str:N \@filelist }
11272   }
11273   </package>
11274   \seq_concat:NNN \l__file_tmp_seq \l__file_tmp_seq \g__file_record_seq
11275   \seq_remove_duplicates:N \l__file_tmp_seq
11276   #1 { LaTeX/kernel } { file-list }
11277   { \seq_map_function:NN \l__file_tmp_seq \_file_list_aux:n }
11278   { } { } { }
11279 }
11280 \cs_new:Npn \_file_list_aux:n #1 { \iow_newline: #1 }

```

(End definition for `\file_show_list:` and others. These functions are documented on page 152.)

When used as a package, there is a need to hold onto the standard file list as well as the new one here. File names recorded in `\@filelist` must be turned to strings before being added to `\g__file_record_seq`.

```

11281 (*package)
11282 \AtBeginDocument
11283 {
11284   \exp_args:NNx \seq_set_from_clist:Nn \l__file_tmp_seq
11285   { \tl_to_str:N \@filelist }
11286   \seq_gconcat:NNN
11287   \g__file_record_seq
11288   \g__file_record_seq
11289   \l__file_tmp_seq
11290 }
11291 </package>

```

18.5 Messages

```

11292 \_kernel_msg_new:nnnn { kernel } { file-not-found }
11293 { File~'#1'~not~found. }
11294 {
11295   The~requested~file~could~not~be~found~in~the~current~directory,~
11296   in~the~TeX~search~path~or~in~the~LaTeX~search~path.
11297 }

```

```

11298 \__kernel_msg_new:nnn { kernel } { file-list }
11299 {
11300   >~File~List~<
11301   #1 \\\
11302   .....
11303 }
11304 \__kernel_msg_new:nnnn { kernel } { input-streams-exhausted }
11305 { Input~streams-exhausted }
11306 {
11307   TeX-can-only-open-up-to-16-input-streams-at-one-time.\\
11308   All-16-are-currently-in-use,~and-something-wanted-to-open-
11309   another-one.
11310 }
11311 \__kernel_msg_new:nnnn { kernel } { output-streams-exhausted }
11312 { Output~streams-exhausted }
11313 {
11314   TeX-can-only-open-up-to-16-output-streams-at-one-time.\\
11315   All-16-are-currently-in-use,~and-something-wanted-to-open-
11316   another-one.
11317 }
11318 \__kernel_msg_new:nnnn { kernel } { unbalanced-quote-in-filename }
11319 { Unbalanced~quotes-in-file-name~'~#1'. }
11320 {
11321   File-names-must-contain-balanced-numbers-of-quotes~(").
11322 }
11323 \__kernel_msg_new:nnnn { kernel } { iow-indent }
11324 { Only~#1 (arg-1)~allows~#2 }
11325 {
11326   The-command~#2 can-only-be-used-in-messages~
11327   which-will-be-wrapped-using~#1.
11328   \tl_if_empty:nF {#3} { ~ It-was-called-with-argument~'~#3'. }
11329 }
11330 </initex | package>

```

19 l3skip implementation

```

11331 <(*initex | package>
11332 <@@=dim>

```

19.1 Length primitives renamed

```

\if_dim:w Primitives renamed.
\__dim_eval:w 11333 \cs_new_eq:NN \if_dim:w \tex_ifdim:D
\__dim_eval_end: 11334 \cs_new_eq:NN \__dim_eval:w \tex_dimexpr:D
11335 \cs_new_eq:NN \__dim_eval_end: \tex_relax:D

```

(End definition for `\if_dim:w`, `__dim_eval:w`, and `__dim_eval_end:`. This function is documented on page 167.)

19.2 Creating and initialising dim variables

```

\dim_new:N Allocating <dim> registers ...
\dim_new:c 11336 <*package>
11337 \cs_new_protected:Npn \dim_new:N #1

```

```

11338 {
11339   \__kernel_chk_if_free_cs:N #1
11340   \cs:w newdimen \cs_end: #1
11341 }
11342 \</package>
11343 \cs_generate_variant:Nn \dim_new:N { c }

```

(End definition for `\dim_new:N`. This function is documented on page 153.)

`\dim_const:Nn` Contrarily to integer constants, we cannot avoid using a register, even for constants. We cannot use `\dim_gset:Nn` because debugging code would complain that the constant is not a global variable. Since `\dim_const:Nn` does not need to be fast, use `\dim_eval:n` to avoid needing a debugging patch that wraps the expression in checking code.

`\dim_const:cn`

```

11344 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN c #1 } { }
11345 \cs_new_protected:Npn \dim_const:Nn #1#2
11346 {
11347   \dim_new:N #1
11348   \tex_global:D #1 ~ \dim_eval:n {#2} \scan_stop:
11349 }
11350 \cs_generate_variant:Nn \dim_const:Nn { c }

```

(End definition for `\dim_const:Nn`. This function is documented on page 153.)

`\dim_zero:N` Reset the register to zero. Using `\c_zero_skip` deals with the case where the variable passed is incorrectly a skip (for example a L^AT_EX 2_ε length).

`\dim_zero:c`

`\dim_gzero:N`

`\dim_gzero:c`

```

11351 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
11352 \cs_new_protected:Npn \dim_zero:N #1 { #1 \c_zero_skip }
11353 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
11354 \cs_new_protected:Npn \dim_gzero:N #1
11355 { \tex_global:D #1 \c_zero_skip }
11356 \cs_generate_variant:Nn \dim_zero:N { c }
11357 \cs_generate_variant:Nn \dim_gzero:N { c }

```

(End definition for `\dim_zero:N` and `\dim_gzero:N`. These functions are documented on page 153.)

`\dim_zero_new:N` Create a register if needed, otherwise clear it.

`\dim_zero_new:c`

`\dim_gzero_new:N`

`\dim_gzero_new:c`

```

11358 \cs_new_protected:Npn \dim_zero_new:N #1
11359 { \dim_if_exist:NTF #1 { \dim_zero:N #1 } { \dim_new:N #1 } }
11360 \cs_new_protected:Npn \dim_gzero_new:N #1
11361 { \dim_if_exist:NTF #1 { \dim_gzero:N #1 } { \dim_new:N #1 } }
11362 \cs_generate_variant:Nn \dim_zero_new:N { c }
11363 \cs_generate_variant:Nn \dim_gzero_new:N { c }

```

(End definition for `\dim_zero_new:N` and `\dim_gzero_new:N`. These functions are documented on page 153.)

`\dim_if_exist_p:N` Copies of the `cs` functions defined in `l3basics`.

`\dim_if_exist_p:c`

`\dim_if_exist:NTF`

`\dim_if_exist:cTF`

```

11364 \prg_new_eq_conditional:NNn \dim_if_exist:N \cs_if_exist:N
11365 { TF , T , F , p }
11366 \prg_new_eq_conditional:NNn \dim_if_exist:c \cs_if_exist:c
11367 { TF , T , F , p }

```

(End definition for `\dim_if_exist:NTF`. This function is documented on page 153.)

19.3 Setting dim variables

Several functions here have a signature `:Nn` and are such that when debugging, the first argument should be checked to be a local/global variable and the second should be wrapped in code for an expression. The temporary function `__dim_tmp:w` finds the name `#3` of the function being redefined and writes the appropriate patch.

```

11368 \cs_set_protected:Npn \__dim_tmp:w #1#2#3
11369 {
11370   \__kernel_patch_args:nnnNnNpn
11371   { #1 ##1 }
11372   { }
11373   { {##1} { \__kernel_chk_expr:nNnN {##2} \__dim_eval:w { } #3 } }
11374   #2 #3
11375 }
```

\dim_set:Nn Setting dimensions is easy enough but when debugging we want both to check that the variable is correctly local/global and to wrap the expression in some code. The `\scan_stop:` deals with the case where the variable passed is a skip (for example a $\text{\LaTeX} 2_{\epsilon}$ length).

```

11376 \__dim_tmp:w \__kernel_chk_var_local:N
11377 \cs_new_protected:Npn \dim_set:Nn #1#2
11378 { #1 ~ \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
11379 \__dim_tmp:w \__kernel_chk_var_global:N
11380 \cs_new_protected:Npn \dim_gset:Nn #1#2
11381 { \tex_global:D #1 ~ \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
11382 \cs_generate_variant:Nn \dim_set:Nn { c }
11383 \cs_generate_variant:Nn \dim_gset:Nn { c }
```

(End definition for `\dim_set:Nn` and `\dim_gset:Nn`. These functions are documented on page 154.)

\dim_set_eq:NN All straightforward, with a `\scan_stop:` to deal with the case where `#1` is (incorrectly) a skip.

```

11384 \__kernel_patch:nnNnNpn { \__kernel_chk_var_local:N #1 } { }
11385 \cs_new_protected:Npn \dim_set_eq:NN #1#2
11386 { #1 = #2 \scan_stop: }
11387 \cs_generate_variant:Nn \dim_set_eq:NN { c , Nc , cc }
11388 \__kernel_patch:nnNnNpn { \__kernel_chk_var_global:N #1 } { }
11389 \cs_new_protected:Npn \dim_gset_eq:NN #1#2
11390 { \tex_global:D #1 = #2 \scan_stop: }
11391 \cs_generate_variant:Nn \dim_gset_eq:NN { c , Nc , cc }
```

(End definition for `\dim_set_eq:NN` and `\dim_gset_eq:NN`. These functions are documented on page 154.)

\dim_add:Nn Using `by` here deals with the (incorrect) case `\dimen123`. Using `\scan_stop:` deals with skip variables. Since debugging checks that the variable is correctly local/global, the global versions cannot be defined as `\tex_global:D` followed by the local versions. The debugging code is inserted by `__dim_tmp:w`.

```

11392 \__dim_tmp:w \__kernel_chk_var_local:N
11393 \cs_new_protected:Npn \dim_add:Nn #1#2
11394 { \tex_advance:D #1 by \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
11395 \__dim_tmp:w \__kernel_chk_var_global:N
11396 \cs_new_protected:Npn \dim_gadd:Nn #1#2
11397 {
```



```

11398 \tex_global:D \tex_advance:D #1 by
11399 \__dim_eval:w #2 \__dim_eval_end: \scan_stop:
11400 }
11401 \cs_generate_variant:Nn \dim_add:Nn { c }
11402 \cs_generate_variant:Nn \dim_gadd:Nn { c }
11403 \__dim_tmp:w \__kernel_chk_var_local:N
11404 \cs_new_protected:Npn \dim_sub:Nn #1#2
11405 { \tex_advance:D #1 by - \__dim_eval:w #2 \__dim_eval_end: \scan_stop: }
11406 \__dim_tmp:w \__kernel_chk_var_global:N
11407 \cs_new_protected:Npn \dim_gsub:Nn #1#2
11408 {
11409 \tex_global:D \tex_advance:D #1 by
11410 -\__dim_eval:w #2 \__dim_eval_end: \scan_stop:
11411 }
11412 \cs_generate_variant:Nn \dim_sub:Nn { c }
11413 \cs_generate_variant:Nn \dim_gsub:Nn { c }

```

(End definition for `\dim_add:Nn` and others. These functions are documented on page 154.)

19.4 Utilities for dimension calculations

`\dim_abs:n` Functions for min, max, and absolute value with only one evaluation. The absolute value is evaluated by removing a leading `-` if present.

`__dim_abs:N`

`\dim_max:nn`

`\dim_min:nn`

`__dim_maxmin:wwN`

```

11414 \__kernel_patch_args:nNNpn
11415 { { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_abs:n } }
11416 \cs_new:Npn \dim_abs:n #1
11417 {
11418 \exp_after:wN \__dim_abs:N
11419 \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
11420 }
11421 \cs_new:Npn \__dim_abs:N #1
11422 { \if_meaning:w - #1 \else: \exp_after:wN #1 \fi: }
11423 \__kernel_patch_args:nNNpn
11424 {
11425 { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_max:nn }
11426 { \__kernel_chk_expr:nNnN {#2} \__dim_eval:w { } \dim_max:nn }
11427 }
11428 \cs_new:Npn \dim_max:nn #1#2
11429 {
11430 \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
11431 \dim_use:N \__dim_eval:w #1 \exp_after:wN ;
11432 \dim_use:N \__dim_eval:w #2 ;
11433 >
11434 \__dim_eval_end:
11435 }
11436 \__kernel_patch_args:nNNpn
11437 {
11438 { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_min:nn }
11439 { \__kernel_chk_expr:nNnN {#2} \__dim_eval:w { } \dim_min:nn }
11440 }
11441 \cs_new:Npn \dim_min:nn #1#2
11442 {
11443 \dim_use:N \__dim_eval:w \exp_after:wN \__dim_maxmin:wwN
11444 \dim_use:N \__dim_eval:w #1 \exp_after:wN ;

```

```

11445     \dim_use:N \__dim_eval:w #2 ;
11446     <
11447     \__dim_eval_end:
11448   }
11449 \cs_new:Npn \__dim_maxmin:wwN #1 ; #2 ; #3
11450 {
11451   \if_dim:w #1 #3 #2 ~
11452     #1
11453   \else:
11454     #2
11455   \fi:
11456 }

```

(End definition for `\dim_abs:n` and others. These functions are documented on page 154.)

`\dim_ratio:nn` With dimension expressions, something like `10 pt * (5 pt / 10 pt)` does not work. Instead, the ratio part needs to be converted to an integer expression. Using `\int_value:w` forces everything into `sp`, avoiding any decimal parts.

```

11457 \cs_new:Npn \dim_ratio:nn #1#2
11458 { \__dim_ratio:n {#1} / \__dim_ratio:n {#2} }
11459 \cs_new:Npn \__dim_ratio:n #1
11460 { \int_value:w \__dim_eval:w (#1) \__dim_eval_end: }

```

(End definition for `\dim_ratio:nn` and `__dim_ratio:n`. This function is documented on page 155.)

19.5 Dimension expression conditionals

`\dim_compare_p:nNn` Simple comparison.

```

\dim_compare:nNnTF
11461 \__kernel_patch_conditional_args:nNnpnn
11462 {
11463   { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_compare:nNn }
11464   { \__dim_eval_end: #2 }
11465   { \__kernel_chk_expr:nNnN {#3} \__dim_eval:w { } \dim_compare:nNn }
11466 }
11467 \prg_new_conditional:Npnn \dim_compare:nNn #1#2#3 { p , T , F , TF }
11468 {
11469   \if_dim:w \__dim_eval:w #1 #2 \__dim_eval:w #3 \__dim_eval_end:
11470   \prg_return_true: \else: \prg_return_false: \fi:
11471 }

```

(End definition for `\dim_compare:nNnTF`. This function is documented on page 155.)

`\dim_compare_p:n` This code is adapted from the `\int_compare:nTF` function. First make sure that there is at least one relation operator, by evaluating a dimension expression with a trailing `__dim_compare_error:.` Just like for integers, the looping auxiliary `__dim_compare:wNN` closes a primitive conditional and opens a new one. It is actually easier to grab a dimension operand than an integer one, because once evaluated, dimensions all end with `pt` (with category other). Thus we do not need specific auxiliaries for the three “simple” relations `<`, `=`, and `>`.

```

\dim_compare:nTF
\__dim_compare:w
\__dim_compare:wNN
\__dim_compare_=:w
\__dim_compare_!=:w
\__dim_compare_<:w
\__dim_compare_>:w
\__dim_compare_error:
11472 \prg_new_conditional:Npnn \dim_compare:n #1 { p , T , F , TF }
11473 {
11474   \exp_after:wN \__dim_compare:w
11475   \dim_use:N \__dim_eval:w #1 \__dim_compare_error:
11476 }

```

```

11477 \cs_new:Npn \__dim_compare:w #1 \__dim_compare_error:
11478 {
11479   \exp_after:wN \if_false: \exp:w \exp_end_continue_f:w
11480   \__dim_compare:wNN #1 ? { = \__dim_compare_end:w \else: } \q_stop
11481 }
11482 \exp_args:Nno \use:nn
11483 { \cs_new:Npn \__dim_compare:wNN #1 } { \tl_to_str:n {pt} #2#3 }
11484 {
11485   \if_meaning:w = #3
11486   \use:c { __dim_compare_#2:w }
11487   \fi:
11488   #1 pt \exp_stop_f:
11489   \prg_return_false:
11490   \exp_after:wN \use_none_delimit_by_q_stop:w
11491   \fi:
11492   \reverse_if:N \if_dim:w #1 pt #2
11493   \exp_after:wN \__dim_compare:wNN
11494   \dim_use:N \__dim_eval:w #3
11495 }
11496 \cs_new:cpn { __dim_compare_ ! :w }
11497 #1 \reverse_if:N #2 ! #3 = { #1 #2 = #3 }
11498 \cs_new:cpn { __dim_compare_ = :w }
11499 #1 \__dim_eval:w = { #1 \__dim_eval:w }
11500 \cs_new:cpn { __dim_compare_ < :w }
11501 #1 \reverse_if:N #2 < #3 = { #1 #2 > #3 }
11502 \cs_new:cpn { __dim_compare_ > :w }
11503 #1 \reverse_if:N #2 > #3 = { #1 #2 < #3 }
11504 \cs_new:Npn \__dim_compare_end:w #1 \prg_return_false: #2 \q_stop
11505 { #1 \prg_return_false: \else: \prg_return_true: \fi: }
11506 \cs_new_protected:Npn \__dim_compare_error:
11507 {
11508   \if_int_compare:w \c_zero_int \c_zero_int \fi:
11509   =
11510   \__dim_compare_error:
11511 }

```

(End definition for \dim_compare:nTF and others. This function is documented on page 156.)

\dim_case:nn For dimension cases, the first task to fully expand the check condition. The over all idea is then much the same as for \str_case:nn(TF) as described in l3basics.

\dim_case:nnTF

```

\__dim_case:nnTF 11512 \cs_new:Npn \dim_case:nnTF #1
\__dim_case:nw 11513 {
\__dim_case_end:nw 11514   \exp:w
11515   \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} }
11516 }
11517 \cs_new:Npn \dim_case:nnT #1#2#3
11518 {
11519   \exp:w
11520   \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} {#3} { }
11521 }
11522 \cs_new:Npn \dim_case:nnF #1#2
11523 {
11524   \exp:w
11525   \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} { }

```

```

11526     }
11527 \cs_new:Npn \dim_case:nn #1#2
11528 {
11529     \exp:w
11530     \exp_args:Nf \__dim_case:nnTF { \dim_eval:n {#1} } {#2} { } { }
11531 }
11532 \cs_new:Npn \__dim_case:nnTF #1#2#3#4
11533 { \__dim_case:nw {#1} #2 {#1} { } \q_mark {#3} \q_mark {#4} \q_stop }
11534 \cs_new:Npn \__dim_case:nw #1#2#3
11535 {
11536     \dim_compare:nNnTF {#1} = {#2}
11537     { \__dim_case_end:nw {#3} }
11538     { \__dim_case:nw {#1} }
11539 }
11540 \cs_new:Npn \__dim_case_end:nw #1#2#3 \q_mark #4#5 \q_stop
11541 { \exp_end: #1 #4 }

```

(End definition for `\dim_case:nnTF` and others. This function is documented on page 157.)

19.6 Dimension expression loops

`\dim_while_do:nn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nn
\dim_do_while:nn
\dim_do_until:nn
11542 \cs_new:Npn \dim_while_do:nn #1#2
11543 {
11544     \dim_compare:nT {#1}
11545     {
11546         #2
11547         \dim_while_do:nn {#1} {#2}
11548     }
11549 }
11550 \cs_new:Npn \dim_until_do:nn #1#2
11551 {
11552     \dim_compare:nF {#1}
11553     {
11554         #2
11555         \dim_until_do:nn {#1} {#2}
11556     }
11557 }
11558 \cs_new:Npn \dim_do_while:nn #1#2
11559 {
11560     #2
11561     \dim_compare:nT {#1}
11562     { \dim_do_while:nn {#1} {#2} }
11563 }
11564 \cs_new:Npn \dim_do_until:nn #1#2
11565 {
11566     #2
11567     \dim_compare:nF {#1}
11568     { \dim_do_until:nn {#1} {#2} }
11569 }

```

(End definition for `\dim_while_do:nn` and others. These functions are documented on page 158.)

`\dim_while_do:nNnn` `while_do` and `do_while` functions for dimensions. Same as for the `int` type only the names have changed.

```

\dim_until_do:nNnn
\dim_do_while:nNnn
\dim_do_until:nNnn
11570 \cs_new:Npn \dim_while_do:nNnn #1#2#3#4
11571 {
11572     \dim_compare:nNnT {#1} #2 {#3}
11573     {
11574         #4
11575         \dim_while_do:nNnn {#1} #2 {#3} {#4}
11576     }
11577 }
11578 \cs_new:Npn \dim_until_do:nNnn #1#2#3#4
11579 {
11580     \dim_compare:nNnF {#1} #2 {#3}
11581     {
11582         #4
11583         \dim_until_do:nNnn {#1} #2 {#3} {#4}
11584     }
11585 }
11586 \cs_new:Npn \dim_do_while:nNnn #1#2#3#4
11587 {
11588     #4
11589     \dim_compare:nNnT {#1} #2 {#3}
11590     { \dim_do_while:nNnn {#1} #2 {#3} {#4} }
11591 }
11592 \cs_new:Npn \dim_do_until:nNnn #1#2#3#4
11593 {
11594     #4
11595     \dim_compare:nNnF {#1} #2 {#3}
11596     { \dim_do_until:nNnn {#1} #2 {#3} {#4} }
11597 }

```

(End definition for `\dim_while_do:nNnn` and others. These functions are documented on page 158.)

19.7 Dimension step functions

`\dim_step_function:nnnN` Before all else, evaluate the initial value, step, and final value. Repeating a function by steps first needs a check on the direction of the steps. After that, do the function for the start value then step and loop around. It would be more symmetrical to test for a step size of zero before checking the sign, but we optimize for the most frequent case (positive step).

```

\__dim_step:wwwN
\__dim_step:NnnnN
11598 \__kernel_patch_args:nNNpn
11599 {
11600     {
11601         \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { }
11602         \dim_step_function:nnnN
11603     }
11604     {
11605         \__kernel_chk_expr:nNnN {#2} \__dim_eval:w { }
11606         \dim_step_function:nnnN
11607     }
11608     {
11609         \__kernel_chk_expr:nNnN {#3} \__dim_eval:w { }
11610         \dim_step_function:nnnN

```

```

11611     }
11612   }
11613   \cs_new:Npn \dim_step_function:nnnN #1#2#3
11614   {
11615     \exp_after:wN \__dim_step:wwwN
11616     \tex_the:D \__dim_eval:w #1 \exp_after:wN ;
11617     \tex_the:D \__dim_eval:w #2 \exp_after:wN ;
11618     \tex_the:D \__dim_eval:w #3 ;
11619   }
11620   \cs_new:Npn \__dim_step:wwwN #1; #2; #3; #4
11621   {
11622     \dim_compare:nNnTF {#2} > \c_zero_dim
11623     { \__dim_step:NnnnN > }
11624     {
11625       \dim_compare:nNnTF {#2} = \c_zero_dim
11626       {
11627         \__kernel_msg_expandable_error:nnn { kernel } { zero-step } {#4}
11628         \use_none:nnnn
11629       }
11630       { \__dim_step:NnnnN < }
11631     }
11632     {#1} {#2} {#3} #4
11633   }
11634   \cs_new:Npn \__dim_step:NnnnN #1#2#3#4#5
11635   {
11636     \dim_compare:nNnF {#2} #1 {#4}
11637     {
11638       #5 {#2}
11639       \exp_args:NNf \__dim_step:NnnnN
11640       #1 { \dim_eval:n { #2 + #3 } } {#3} {#4} #5
11641     }
11642   }

```

(End definition for `\dim_step_function:nnnN`, `__dim_step:wwwN`, and `__dim_step:NnnnN`. This function is documented on page 158.)

`\dim_step_inline:nnnn`
`\dim_step_variable:nnnNn`
`__dim_step:NNnnnn`

The approach here is to build a function, with a global integer required to make the nesting safe (as seen in other in line functions), and map that function using `\dim_step_function:nnnN`. We put a `\prg_break_point:Nn` so that `map_break` functions from other modules correctly decrement `\g__kernel_prg_map_int` before looking for their own break point. The first argument is `\scan_stop:`, so that no breaking function recognizes this break point as its own.

```

11643   \cs_new_protected:Npn \dim_step_inline:nnnn
11644   {
11645     \int_gincr:N \g__kernel_prg_map_int
11646     \exp_args:NNc \__dim_step:NNnnnn
11647     \cs_gset_protected:Npn
11648     { \__dim_map_ \int_use:N \g__kernel_prg_map_int :w }
11649   }
11650   \cs_new_protected:Npn \dim_step_variable:nnnNn #1#2#3#4#5
11651   {
11652     \int_gincr:N \g__kernel_prg_map_int
11653     \exp_args:NNc \__dim_step:NNnnnn
11654     \cs_gset_protected:Npx

```

```

11655     { __dim_map_ \int_use:N \g__kernel_prg_map_int :w }
11656     {#1}{#2}{#3}
11657     {
11658       \tl_set:Nn \exp_not:N #4 {##1}
11659       \exp_not:n {#5}
11660     }
11661   }
11662 \cs_new_protected:Npn \__dim_step:NNnnnn #1#2#3#4#5#6
11663 {
11664   #1 #2 ##1 {#6}
11665   \dim_step_function:nnnN {#3} {#4} {#5} #2
11666   \prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__kernel_prg_map_int }
11667 }

```

(End definition for `\dim_step_inline:nnnn`, `\dim_step_variable:nnnN`, and `__dim_step:NNnnnn`. These functions are documented on page 158.)

19.8 Using dim expressions and variables

`\dim_eval:n` Evaluating a dimension expression expandably.

```

11668 \__kernel_patch_args:nNNpn
11669 { { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_eval:n } }
11670 \cs_new:Npn \dim_eval:n #1
11671 { \dim_use:N \__dim_eval:w #1 \__dim_eval_end: }

```

(End definition for `\dim_eval:n`. This function is documented on page 159.)

`\dim_use:N` Accessing a $\langle dim \rangle$.

`\dim_use:c` 11672 \cs_new_eq:NN \dim_use:N \tex_the:D

We hand-code this for some speed gain:

```

11673 %\cs_generate_variant:Nn \dim_use:N { c }
11674 \cs_new:Npn \dim_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\dim_use:N`. This function is documented on page 159.)

`\dim_to_decimal:n` A function which comes up often enough to deserve a place in the kernel. Evaluate the dimension expression `#1` then remove the trailing `pt`. When debugging is enabled, the argument is put in parentheses as this prevents the dimension expression from terminating early and leaving extra tokens lying around. This is used a lot by low-level manipulations.

```

11675 \__kernel_patch_args:nNNpn
11676 { { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_to_decimal:n } }
11677 \cs_new:Npn \dim_to_decimal:n #1
11678 {
11679   \exp_after:wN
11680   \__dim_to_decimal:w \dim_use:N \__dim_eval:w #1 \__dim_eval_end:
11681 }
11682 \use:x
11683 {
11684   \cs_new:Npn \exp_not:N \__dim_to_decimal:w
11685     ##1 . ##2 \tl_to_str:n { pt }
11686 }
11687 {
11688   \int_compare:nNnTF {#2} > { 0 }
11689   { #1 . #2 }

```

```

11690         { #1 }
11691     }

```

(End definition for `\dim_to_decimal:n` and `_dim_to_decimal:w`. This function is documented on page 159.)

`\dim_to_decimal_in_bp:n` Conversion to big points is done using a scaling inside `_dim_eval:w` as ϵ -TeX does that using 64-bit precision. Here, 800/803 is the integer fraction for 72/72.27. This is a common case so is hand-coded for accuracy (and speed).

```

11692 \cs_new:Npn \dim_to_decimal_in_bp:n #1
11693 { \dim_to_decimal:n { ( #1 ) * 800 / 803 } }

```

(End definition for `\dim_to_decimal_in_bp:n`. This function is documented on page 160.)

`\dim_to_decimal_in_sp:n` Another hard-coded conversion: this one is necessary to avoid things going off-scale.

```

11694 \__kernel_patch_args:nNnNpn
11695 {
11696     {
11697         \__kernel_chk_expr:nNnN {#1} \_dim_eval:w { }
11698         \dim_to_decimal_in_sp:n
11699     }
11700 }
11701 \cs_new:Npn \dim_to_decimal_in_sp:n #1
11702 { \int_value:w \_dim_eval:w #1 \_dim_eval_end: }

```

(End definition for `\dim_to_decimal_in_sp:n`. This function is documented on page 160.)

`\dim_to_decimal_in_unit:nn` An analogue of `\dim_ratio:nn` that produces a decimal number as its result, rather than a rational fraction for use within dimension expressions.

```

11703 \cs_new:Npn \dim_to_decimal_in_unit:nn #1#2
11704 {
11705     \dim_to_decimal:n
11706     {
11707         1pt *
11708         \dim_ratio:nn {#1} {#2}
11709     }
11710 }

```

(End definition for `\dim_to_decimal_in_unit:nn`. This function is documented on page 160.)

`\dim_to_fp:n` Defined in `l3fp-convert`, documented here.

(End definition for `\dim_to_fp:n`. This function is documented on page 160.)

19.9 Viewing dim variables

`\dim_show:N` Diagnostics.

```

\dim_show:c 11711 \cs_new_eq:NN \dim_show:N \__kernel_register_show:N
11712 \cs_generate_variant:Nn \dim_show:N { c }

```

(End definition for `\dim_show:N`. This function is documented on page 160.)

`\dim_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show dimension expressions: this gives a more unified output.

```

11713 \cs_new_protected:Npn \dim_show:n
11714 { \msg_show_eval:Nn \dim_eval:n }

```


(End definition for `\dim_show:n`. This function is documented on page 161.)

```
\dim_log:N Diagnostics. Redirect output of \dim_show:n to the log.
\dim_log:c 11715 \cs_new_eq:NN \dim_log:N \__kernel_register_log:N
\dim_log:n 11716 \cs_new_eq:NN \dim_log:c \__kernel_register_log:c
11717 \cs_new_protected:Npn \dim_log:n
11718 { \msg_log_eval:Nn \dim_eval:n }
```

(End definition for `\dim_log:N` and `\dim_log:n`. These functions are documented on page 161.)

19.10 Constant dimensions

```
\c_zero_dim Constant dimensions.
\c_max_dim 11719 \dim_const:Nn \c_zero_dim { 0 pt }
11720 \dim_const:Nn \c_max_dim { 16383.99999 pt }
```

(End definition for `\c_zero_dim` and `\c_max_dim`. These variables are documented on page 161.)

19.11 Scratch dimensions

```
\l_tmpa_dim We provide two local and two global scratch registers, maybe we need more or less.
\l_tmpb_dim 11721 \dim_new:N \l_tmpa_dim
\g_tmpa_dim 11722 \dim_new:N \l_tmpb_dim
\g_tmpb_dim 11723 \dim_new:N \g_tmpa_dim
11724 \dim_new:N \g_tmpb_dim
```

(End definition for `\l_tmpa_dim` and others. These variables are documented on page 161.)

19.12 Creating and initialising skip variables

```
11725 <@@=skip>
\skip_new:N Allocation of a new internal registers.
\skip_new:c 11726 <*package>
11727 \cs_new_protected:Npn \skip_new:N #1
11728 {
11729 \__kernel_chk_if_free_cs:N #1
11730 \cs:w newskip \cs_end: #1
11731 }
11732 </package>
11733 \cs_generate_variant:Nn \skip_new:N { c }
```

(End definition for `\skip_new:N`. This function is documented on page 161.)

```
\skip_const:Nn Contrarily to integer constants, we cannot avoid using a register, even for constants. See
\skip_const:cn \dim_const:Nn for why we cannot use \skip_gset:Nn.
11734 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN c #1 } { }
11735 \cs_new_protected:Npn \skip_const:Nn #1#2
11736 {
11737 \skip_new:N #1
11738 \tex_global:D #1 ~ \skip_eval:n {#2} \scan_stop:
11739 }
11740 \cs_generate_variant:Nn \skip_const:Nn { c }
```

(End definition for `\skip_const:Nn`. This function is documented on page 161.)

```

\skip_zero:N Reset the register to zero.
\skip_zero:c 11741 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\skip_gzero:N 11742 \cs_new_protected:Npn \skip_zero:N #1 { #1 \c_zero_skip }
\skip_gzero:c 11743 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
11744 \cs_new_protected:Npn \skip_gzero:N #1 { \tex_global:D #1 \c_zero_skip }
11745 \cs_generate_variant:Nn \skip_zero:N { c }
11746 \cs_generate_variant:Nn \skip_gzero:N { c }

```

(End definition for `\skip_zero:N` and `\skip_gzero:N`. These functions are documented on page 162.)

```

\skip_zero_new:N Create a register if needed, otherwise clear it.
\skip_zero_new:c 11747 \cs_new_protected:Npn \skip_zero_new:N #1
\skip_gzero_new:N 11748 { \skip_if_exist:NTF #1 { \skip_zero:N #1 } { \skip_new:N #1 } }
\skip_gzero_new:c 11749 \cs_new_protected:Npn \skip_gzero_new:N #1
11750 { \skip_if_exist:NTF #1 { \skip_gzero:N #1 } { \skip_new:N #1 } }
11751 \cs_generate_variant:Nn \skip_zero_new:N { c }
11752 \cs_generate_variant:Nn \skip_gzero_new:N { c }

```

(End definition for `\skip_zero_new:N` and `\skip_gzero_new:N`. These functions are documented on page 162.)

```

\skip_if_exist_p:N Copies of the cs functions defined in l3basics.
\skip_if_exist_p:c 11753 \prg_new_eq_conditional:NNn \skip_if_exist:N \cs_if_exist:N
\skip_if_exist:N $\underline{TF}$  11754 { TF , T , F , p }
\skip_if_exist:c $\underline{TF}$  11755 \prg_new_eq_conditional:NNn \skip_if_exist:c \cs_if_exist:c
11756 { TF , T , F , p }

```

(End definition for `\skip_if_exist:N \underline{TF}` . This function is documented on page 162.)

19.13 Setting skip variables

Much as for dim variables, `__skip_tmp:w` prepares a patch for `:Nn` function definitions in which the first argument should be checked to be a local/global variable and the second should be wrapped in code for an expression.

```

11757 \cs_set_protected:Npn \__skip_tmp:w #1#2#3
11758 {
11759   \__kernel_patch_args:nnnNNpn
11760     { #1 ##1 }
11761     { }
11762     { {##1} { \__kernel_chk_expr:nNnN {##2} \tex_glueexpr:D { } #3 } }
11763   #2 #3
11764 }

```

```

\skip_set:Nn Much the same as for dimensions.
\skip_set:cn 11765 \__skip_tmp:w \__kernel_chk_var_local:N
\skip_gset:Nn 11766 \cs_new_protected:Npn \skip_set:Nn #1#2
\skip_gset:cn 11767 { #1 ~ \tex_glueexpr:D #2 \scan_stop: }
11768 \__skip_tmp:w \__kernel_chk_var_global:N
11769 \cs_new_protected:Npn \skip_gset:Nn #1#2
11770 { \tex_global:D #1 ~ \tex_glueexpr:D #2 \scan_stop: }
11771 \cs_generate_variant:Nn \skip_set:Nn { c }
11772 \cs_generate_variant:Nn \skip_gset:Nn { c }

```

(End definition for `\skip_set:Nn` and `\skip_gset:Nn`. These functions are documented on page 162.)

`\skip_set_eq:NN` All straightforward.

```

\skip_set_eq:cN 11773 \cs_new_protected:Npn \skip_set_eq:NN #1#2 { #1 = #2 }
\skip_set_eq:Nc 11774 \cs_generate_variant:Nn \skip_set_eq:NN { c , Nc , cc }
\skip_set_eq:cc 11775 \cs_new_protected:Npn \skip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\skip_gset_eq:NN 11776 \cs_generate_variant:Nn \skip_gset_eq:NN { c , Nc , cc }
\skip_gset_eq:cN
\skip_gset_eq:Nc
\skip_gset_eq:cc

```

(End definition for `\skip_set_eq:NN` and `\skip_gset_eq:NN`. These functions are documented on page 162.)

Using `by` here deals with the (incorrect) case `\skip123`.

```

\skip_add:Nn 11777 \__skip_tmp:w \__kernel_chk_var_local:N
\skip_add:cn 11778 \cs_new_protected:Npn \skip_add:Nn #1#2
\skip_gadd:Nn 11779 { \tex_advance:D #1 by \tex_glueexpr:D #2 \scan_stop: }
\skip_gadd:cn 11780 \__skip_tmp:w \__kernel_chk_var_global:N
\skip_sub:Nn 11781 \cs_new_protected:Npn \skip_gadd:Nn #1#2
\skip_sub:cn 11782 { \tex_global:D \tex_advance:D #1 by \tex_glueexpr:D #2 \scan_stop: }
\skip_gsub:Nn 11783 \cs_generate_variant:Nn \skip_add:Nn { c }
\skip_gsub:cn 11784 \cs_generate_variant:Nn \skip_gadd:Nn { c }
11785 \__skip_tmp:w \__kernel_chk_var_local:N
11786 \cs_new_protected:Npn \skip_sub:Nn #1#2
11787 { \tex_advance:D #1 by - \tex_glueexpr:D #2 \scan_stop: }
11788 \__skip_tmp:w \__kernel_chk_var_global:N
11789 \cs_new_protected:Npn \skip_gsub:Nn #1#2
11790 { \tex_global:D \tex_advance:D #1 by - \tex_glueexpr:D #2 \scan_stop: }
11791 \cs_generate_variant:Nn \skip_sub:Nn { c }
11792 \cs_generate_variant:Nn \skip_gsub:Nn { c }

```

(End definition for `\skip_add:Nn` and others. These functions are documented on page 162.)

19.14 Skip expression conditionals

`\skip_if_eq_p:nn` Comparing skips means doing two expansions to make strings, and then testing them.
`\skip_if_eq:nnTF` As a result, only equality is tested.

```

11793 \prg_new_conditional:Npnn \skip_if_eq:nn #1#2 { p , T , F , TF }
11794 {
11795   \str_if_eq:eeTF { \skip_eval:n { #1 } } { \skip_eval:n { #2 } }
11796   { \prg_return_true: }
11797   { \prg_return_false: }
11798 }

```

(End definition for `\skip_if_eq:nnTF`. This function is documented on page 163.)

`\skip_if_finite_p:n` With ε -TeX, we have an easy access to the order of infinities of the stretch and shrink components of a skip. However, to access both, we either need to evaluate the expression twice, or evaluate it, then call an auxiliary to extract both pieces of information from the result. Since we are going to need an auxiliary anyways, it is quicker to make it search for the string `fil` which characterizes infinite glue.

```

11799 \cs_set_protected:Npn \__skip_tmp:w #1
11800 {
11801   \__kernel_patch_conditional_args:nNNpnn
11802   {
11803     {
11804       \__kernel_chk_expr:nNnN
11805       {##1} \tex_glueexpr:D { } \skip_if_finite:n

```

```

11806     }
11807   }
11808   \prg_new_conditional:Npnn \skip_if_finite:n ##1 { p , T , F , TF }
11809   {
11810     \exp_after:wN \__skip_if_finite:wwNw
11811     \skip_use:N \tex_glueexpr:D ##1 ; \prg_return_false:
11812     #1 ; \prg_return_true: \q_stop
11813   }
11814   \cs_new:Npn \__skip_if_finite:wwNw ##1 #1 ##2 ; ##3 ##4 \q_stop {##3}
11815 }
11816 \exp_args:No \__skip_tmp:w { \tl_to_str:n { fil } }

```

(End definition for `\skip_if_finite:nTF` and `__skip_if_finite:wwNw`. This function is documented on page 163.)

19.15 Using skip expressions and variables

`\skip_eval:n` Evaluating a skip expression expandably.

```

11817 \__kernel_patch_args:nNnNpn
11818 { { \__kernel_chk_expr:nNnN {#1} \tex_glueexpr:D { } \skip_eval:n } }
11819 \cs_new:Npn \skip_eval:n #1
11820 { \skip_use:N \tex_glueexpr:D #1 \scan_stop: }

```

(End definition for `\skip_eval:n`. This function is documented on page 163.)

`\skip_use:N` Accessing a `\skip`.

```

\skip_use:c 11821 \cs_new_eq:NN \skip_use:N \tex_the:D
11822 %\cs_generate_variant:Nn \skip_use:N { c }
11823 \cs_new:Npn \skip_use:c #1 { \tex_the:D \cs:w #1 \cs_end: }

```

(End definition for `\skip_use:N`. This function is documented on page 163.)

19.16 Inserting skips into the output

`\skip_horizontal:N` Inserting skips.

```

\skip_horizontal:c 11824 \cs_new_eq:NN \skip_horizontal:N \tex_hskip:D
\skip_horizontal:n 11825 \__kernel_patch_args:nNnNpn
\skip_vertical:N 11826 {
\skip_vertical:c 11827 {
\skip_vertical:n 11828 \__kernel_chk_expr:nNnN {#1} \tex_glueexpr:D { }
11829 \skip_horizontal:n
11830 }
11831 }
11832 \cs_new:Npn \skip_horizontal:n #1
11833 { \skip_horizontal:N \tex_glueexpr:D #1 \scan_stop: }
11834 \cs_new_eq:NN \skip_vertical:N \tex_vskip:D
11835 \__kernel_patch_args:nNnNpn
11836 {
11837 {
11838 \__kernel_chk_expr:nNnN {#1} \tex_glueexpr:D { }
11839 \skip_vertical:n
11840 }
11841 }
11842 \cs_new:Npn \skip_vertical:n #1

```

```

11843 { \skip_vertical:N \tex_glueexpr:D #1 \scan_stop: }
11844 \cs_generate_variant:Nn \skip_horizontal:N { c }
11845 \cs_generate_variant:Nn \skip_vertical:N { c }

```

(End definition for `\skip_horizontal:N` and others. These functions are documented on page 164.)

19.17 Viewing skip variables

`\skip_show:N` Diagnostics.

```

\skip_show:c 11846 \cs_new_eq:NN \skip_show:N \__kernel_register_show:N
11847 \cs_generate_variant:Nn \skip_show:N { c }

```

(End definition for `\skip_show:N`. This function is documented on page 163.)

`\skip_show:n` Diagnostics. We don't use the TeX primitive `\showthe` to show skip expressions: this gives a more unified output.

```

11848 \cs_new_protected:Npn \skip_show:n
11849 { \msg_show_eval:Nn \skip_eval:n }

```

(End definition for `\skip_show:n`. This function is documented on page 163.)

`\skip_log:N` Diagnostics. Redirect output of `\skip_show:n` to the log.

```

\skip_log:c 11850 \cs_new_eq:NN \skip_log:N \__kernel_register_log:N
\skip_log:n 11851 \cs_new_eq:NN \skip_log:c \__kernel_register_log:c
11852 \cs_new_protected:Npn \skip_log:n
11853 { \msg_log_eval:Nn \skip_eval:n }

```

(End definition for `\skip_log:N` and `\skip_log:n`. These functions are documented on page 164.)

19.18 Constant skips

`\c_zero_skip` Skips with no rubber component are just dimensions but need to terminate correctly.

```

\c_max_skip 11854 \skip_const:Nn \c_zero_skip { \c_zero_dim }
11855 \skip_const:Nn \c_max_skip { \c_max_dim }

```

(End definition for `\c_zero_skip` and `\c_max_skip`. These functions are documented on page 164.)

19.19 Scratch skips

`\l_tmpa_skip` We provide two local and two global scratch registers, maybe we need more or less.

```

\l_tmpb_skip 11856 \skip_new:N \l_tmpa_skip
\g_tmpa_skip 11857 \skip_new:N \l_tmpb_skip
\g_tmpb_skip 11858 \skip_new:N \g_tmpa_skip
11859 \skip_new:N \g_tmpb_skip

```

(End definition for `\l_tmpa_skip` and others. These variables are documented on page 164.)

19.20 Creating and initialising muskip variables

\muskip_new:N And then we add muskips.

```
\muskip_new:c 11860 (*package)
11861 \cs_new_protected:Npn \muskip_new:N #1
11862 {
11863     \__kernel_chk_if_free_cs:N #1
11864     \cs:w newmuskip \cs_end: #1
11865 }
11866 \end{package}
11867 \cs_generate_variant:Nn \muskip_new:N { c }
```

(End definition for \muskip_new:N. This function is documented on page 165.)

\muskip_const:Nn See \skip_const:Nn.

```
\muskip_const:cn 11868 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN c #1 } { }
11869 \cs_new_protected:Npn \muskip_const:Nn #1#2
11870 {
11871     \muskip_new:N #1
11872     \tex_global:D #1 ~ \muskip_eval:n {#2} \scan_stop:
11873 }
11874 \cs_generate_variant:Nn \muskip_const:Nn { c }
```

(End definition for \muskip_const:Nn. This function is documented on page 165.)

\muskip_zero:N Reset the register to zero.

```
\muskip_zero:c 11875 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\muskip_gzero:N 11876 \cs_new_protected:Npn \muskip_zero:N #1
\muskip_gzero:c 11877 { #1 \c_zero_muskip }
11878 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
11879 \cs_new_protected:Npn \muskip_gzero:N #1
11880 { \tex_global:D #1 \c_zero_muskip }
11881 \cs_generate_variant:Nn \muskip_zero:N { c }
11882 \cs_generate_variant:Nn \muskip_gzero:N { c }
```

(End definition for \muskip_zero:N and \muskip_gzero:N. These functions are documented on page 165.)

\muskip_zero_new:N Create a register if needed, otherwise clear it.

```
\muskip_zero_new:c 11883 \cs_new_protected:Npn \muskip_zero_new:N #1
\muskip_gzero_new:N 11884 { \muskip_if_exist:NTF #1 { \muskip_zero:N #1 } { \muskip_new:N #1 } }
\muskip_gzero_new:c 11885 \cs_new_protected:Npn \muskip_gzero_new:N #1
11886 { \muskip_if_exist:NTF #1 { \muskip_gzero:N #1 } { \muskip_new:N #1 } }
11887 \cs_generate_variant:Nn \muskip_zero_new:N { c }
11888 \cs_generate_variant:Nn \muskip_gzero_new:N { c }
```

(End definition for \muskip_zero_new:N and \muskip_gzero_new:N. These functions are documented on page 165.)

\muskip_if_exist_p:N Copies of the cs functions defined in l3basics.

```
\muskip_if_exist_p:c 11889 \prg_new_eq_conditional:NNn \muskip_if_exist:N \cs_if_exist:N
\muskip_if_exist:NTF 11890 { TF , T , F , p }
\muskip_if_exist:cTF 11891 \prg_new_eq_conditional:NNn \muskip_if_exist:c \cs_if_exist:c
11892 { TF , T , F , p }
```

(End definition for \muskip_if_exist:NTF. This function is documented on page 165.)

19.21 Setting muskip variables

See skip case.

```

11893 \cs_set_protected:Npn \__skip_tmp:w #1#2#3
11894 {
11895   \__kernel_patch_args:nnnNNpn
11896   { #1 ##1 }
11897   { }
11898   {
11899     {##1}
11900     {
11901       \__kernel_chk_expr:nNnN {##2}
11902       \tex_muexpr:D { \tex_mutoglue:D } #3
11903     }
11904   }
11905   #2 #3
11906 }

```

\muskip_set:Nn This should be pretty familiar.

```

\muskip_set:cn 11907 \__skip_tmp:w \__kernel_chk_var_local:N
\muskip_gset:Nn 11908 \cs_new_protected:Npn \muskip_set:Nn #1#2
\muskip_gset:cn 11909 { #1 ~ \tex_muexpr:D #2 \scan_stop: }
11910 \__skip_tmp:w \__kernel_chk_var_global:N
11911 \cs_new_protected:Npn \muskip_gset:Nn #1#2
11912 { \tex_global:D #1 ~ \tex_muexpr:D #2 \scan_stop: }
11913 \cs_generate_variant:Nn \muskip_set:Nn { c }
11914 \cs_generate_variant:Nn \muskip_gset:Nn { c }

```

(End definition for \muskip_set:Nn and \muskip_gset:Nn. These functions are documented on page 165.)

\muskip_set_eq:NN All straightforward.

```

\muskip_set_eq:cn 11915 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\muskip_set_eq:Nc 11916 \cs_new_protected:Npn \muskip_set_eq:NN #1#2 { #1 = #2 }
\muskip_set_eq:cc 11917 \cs_generate_variant:Nn \muskip_set_eq:NN { c , Nc , cc }
\muskip_gset_eq:Nn 11918 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
\muskip_gset_eq:cn 11919 \cs_new_protected:Npn \muskip_gset_eq:NN #1#2 { \tex_global:D #1 = #2 }
\muskip_gset_eq:Nc 11920 \cs_generate_variant:Nn \muskip_gset_eq:NN { c , Nc , cc }
\muskip_gset_eq:cc

```

(End definition for \muskip_set_eq:NN and \muskip_gset_eq:NN. These functions are documented on page 165.)

\muskip_add:Nn Using by here deals with the (incorrect) case \muskip123.

```

\muskip_add:cn 11921 \__skip_tmp:w \__kernel_chk_var_local:N
\muskip_gadd:Nn 11922 \cs_new_protected:Npn \muskip_add:Nn #1#2
\muskip_gadd:cn 11923 { \tex_advance:D #1 by \tex_muexpr:D #2 \scan_stop: }
\muskip_sub:Nn 11924 \__skip_tmp:w \__kernel_chk_var_global:N
\muskip_sub:cn 11925 \cs_new_protected:Npn \muskip_gadd:Nn #1#2
\muskip_gsub:Nn 11926 { \tex_global:D \tex_advance:D #1 by \tex_muexpr:D #2 \scan_stop: }
\muskip_gsub:cn 11927 \cs_generate_variant:Nn \muskip_add:Nn { c }
11928 \cs_generate_variant:Nn \muskip_gadd:Nn { c }
11929 \__skip_tmp:w \__kernel_chk_var_local:N
11930 \cs_new_protected:Npn \muskip_sub:Nn #1#2
11931 { \tex_advance:D #1 by - \tex_muexpr:D #2 \scan_stop: }
11932 \__skip_tmp:w \__kernel_chk_var_global:N

```

```

11933 \cs_new_protected:Npn \muskip_gsub:Nn #1#2
11934 { \tex_global:D \tex_advance:D #1 by - \tex_muexpr:D #2 \scan_stop: }
11935 \cs_generate_variant:Nn \muskip_sub:Nn { c }
11936 \cs_generate_variant:Nn \muskip_gsub:Nn { c }

```

(End definition for `\muskip_add:Nn` and others. These functions are documented on page 165.)

19.22 Using muskip expressions and variables

`\muskip_eval:n` Evaluating a muskip expression expandably.

```

11937 \__kernel_patch_args:nNnNpn
11938 {
11939   {
11940     \__kernel_chk_expr:nNnN {#1} \tex_muexpr:D
11941     { \tex_mutogluue:D } \muskip_eval:n
11942   }
11943 }
11944 \cs_new:Npn \muskip_eval:n #1
11945 { \muskip_use:N \tex_muexpr:D #1 \scan_stop: }

```

(End definition for `\muskip_eval:n`. This function is documented on page 166.)

`\muskip_use:N` Accessing a $\langle muskip \rangle$.

`\muskip_use:c`

```

11946 \cs_new_eq:NN \muskip_use:N \tex_the:D
11947 \cs_generate_variant:Nn \muskip_use:N { c }

```

(End definition for `\muskip_use:N`. This function is documented on page 166.)

19.23 Viewing muskip variables

`\muskip_show:N` Diagnostics.

`\muskip_show:c`

```

11948 \cs_new_eq:NN \muskip_show:N \__kernel_register_show:N
11949 \cs_generate_variant:Nn \muskip_show:N { c }

```

(End definition for `\muskip_show:N`. This function is documented on page 166.)

`\muskip_show:n` Diagnostics. We don't use the $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ primitive `\showthe` to show muskip expressions: this gives a more unified output.

```

11950 \cs_new_protected:Npn \muskip_show:n
11951 { \msg_show_eval:Nn \muskip_eval:n }

```

(End definition for `\muskip_show:n`. This function is documented on page 166.)

`\muskip_log:N` Diagnostics. Redirect output of `\muskip_show:n` to the log.

`\muskip_log:c`

`\muskip_log:n`

```

11952 \cs_new_eq:NN \muskip_log:N \__kernel_register_log:N
11953 \cs_new_eq:NN \muskip_log:c \__kernel_register_log:c
11954 \cs_new_protected:Npn \muskip_log:n
11955 { \msg_log_eval:Nn \muskip_eval:n }

```

(End definition for `\muskip_log:N` and `\muskip_log:n`. These functions are documented on page 166.)

19.24 Constant muskips

`\c_zero_muskip` Constant muskips given by their value.

```
\c_max_muskip 11956 \muskip_const:Nn \c_zero_muskip { 0 mu }
11957 \muskip_const:Nn \c_max_muskip { 16383.99999 mu }
```

(End definition for `\c_zero_muskip` and `\c_max_muskip`. These functions are documented on page 167.)

19.25 Scratch muskips

`\l_tmpa_muskip` We provide two local and two global scratch registers, maybe we need more or less.

```
\l_tmpb_muskip 11958 \muskip_new:N \l_tmpa_muskip
\g_tmpa_muskip 11959 \muskip_new:N \l_tmpb_muskip
\g_tmpb_muskip 11960 \muskip_new:N \g_tmpa_muskip
11961 \muskip_new:N \g_tmpb_muskip
```

(End definition for `\l_tmpa_muskip` and others. These variables are documented on page 167.)

```
11962 </initex | package>
```

20 l3keys Implementation

```
11963 <*initex | package>
```

20.1 Low-level interface

The low-level key parser is based heavily on `keyval`, but with a number of additional “safety” requirements and with the idea that the parsed list of key–value pairs can be processed in a variety of ways. The net result is that this code needs around twice the amount of time as `keyval` to parse the same list of keys. To optimise speed as far as reasonably practical, a number of lower-level approaches are taken rather than using the higher-level `expl3` interfaces.

```
11964 <@@=keyval>
```

`\l_keyval_key_tl` The current key name and value.

```
\l_keyval_value_tl 11965 \tl_new:N \l_keyval_key_tl
11966 \tl_new:N \l_keyval_value_tl
```

(End definition for `\l_keyval_key_tl` and `\l_keyval_value_tl`.)

`\l_keyval_sanitise_tl` A token list variable for dealing with awkward category codes in the input.

```
11967 \tl_new:N \l_keyval_sanitise_tl
```

(End definition for `\l_keyval_sanitise_tl`.)

`\keyval_parse:NNn` The main function starts off by normalising category codes in package mode. That’s relatively “expensive” so is skipped (hopefully) in format mode. We then hand off to the parser. The use of `\q_mark` here prevents loss of braces from the key argument. Notice that by passing the two processor commands along the input stack we avoid the need to track these at all.

```
11968 \cs_new_protected:Npn \keyval_parse:NNn #1#2#3
11969 {
11970 <*initex>
11971 \__keyval_loop:NNw #1#2 \q_mark #3 , \q_recursion_tail ,
```

```

11972 \end{initex}
11973 \begin{package}
11974   \tl_set:Nn \l__keyval_sanitise_tl {#3}
11975   \__keyval_sanitise_equals:
11976   \__keyval_sanitise_comma:
11977   \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
11978   \exp_after:wN \q_mark \l__keyval_sanitise_tl , \q_recursion_tail ,
11979 \end{package}
11980 }

```

(End definition for `\keyval_parse:NNn`. This function is documented on page 180.)

`__keyval_sanitise_equals:` A reasonably fast search and replace set up specifically for the active tokens. The nature of the input is known so everything is hard-coded. With only two tokens to cover, the speed gain from using dedicated functions is worth it.

```

11981 \begin{package}
11982 \group_begin:
11983   \char_set_catcode_active:n { '=' }
11984   \char_set_catcode_active:n { '\,' }
11985   \cs_new_protected:Npn \__keyval_sanitise_equals:
11986   {
11987     \exp_after:wN \__keyval_sanitise_equals_auxi:w \l__keyval_sanitise_tl
11988     \q_mark = \q_nil =
11989     \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
11990   }
11991   \cs_new_protected:Npn \__keyval_sanitise_equals_auxi:w #1 =
11992   {
11993     \tl_set:Nn \l__keyval_sanitise_tl {#1}
11994     \__keyval_sanitise_equals_auxii:w
11995   }
11996   \cs_new_protected:Npn \__keyval_sanitise_equals_auxii:w #1 =
11997   {
11998     \if_meaning:w \q_nil #1 \scan_stop:
11999     \else:
12000       \tl_set:Nx \l__keyval_sanitise_tl
12001       {
12002         \exp_not:o \l__keyval_sanitise_tl
12003         \token_to_str:N =
12004         \exp_not:n {#1}
12005       }
12006       \exp_after:wN \__keyval_sanitise_equals_auxii:w
12007     \fi:
12008   }
12009   \cs_new_protected:Npn \__keyval_sanitise_comma:
12010   {
12011     \exp_after:wN \__keyval_sanitise_comma_auxi:w \l__keyval_sanitise_tl
12012     \q_mark , \q_nil ,
12013     \exp_after:wN \__keyval_sanitise_aux:w \l__keyval_sanitise_tl
12014   }
12015   \cs_new_protected:Npn \__keyval_sanitise_comma_auxi:w #1 ,
12016   {
12017     \tl_set:Nn \l__keyval_sanitise_tl {#1}
12018     \__keyval_sanitise_comma_auxii:w
12019   }

```

```

12020 \cs_new_protected:Npn \__keyval_sanitise_comma_auxii:w #1 ,
12021 {
12022   \if_meaning:w \q_nil #1 \scan_stop:
12023   \else:
12024     \tl_set:Nx \l__keyval_sanitise_tl
12025     {
12026       \exp_not:o \l__keyval_sanitise_tl
12027       \token_to_str:N ,
12028       \exp_not:n {#1}
12029     }
12030     \exp_after:wN \__keyval_sanitise_comma_auxii:w
12031     \fi:
12032   }
12033 \group_end:
12034 \cs_new_protected:Npn \__keyval_sanitise_aux:w #1 \q_mark
12035 { \tl_set:Nn \l__keyval_sanitise_tl {#1} }
12036 \</package>

```

(End definition for __keyval_sanitise_equals: and others.)

__keyval_loop:NNw A fast test for the end of the loop, remembering to remove the leading quark first. Assuming that is not the case, look for a key and value then loop around, re-inserting a leading quark in front of the next position.

```

12037 \cs_new_protected:Npn \__keyval_loop:NNw #1#2#3 ,
12038 {
12039   \exp_after:wN \if_meaning:w \exp_after:wN \q_recursion_tail
12040   \use_none:n #3 \prg_do_nothing:
12041   \else:
12042     \__keyval_split:NNw #1#2#3 == \q_stop
12043     \exp_after:wN \__keyval_loop:NNw \exp_after:wN #1 \exp_after:wN #2
12044     \exp_after:wN \q_mark
12045   \fi:
12046 }

```

(End definition for __keyval_loop:NNw.)

__keyval_split:NNw The value is picked up separately from the key so there can be another quark inserted at the front, keeping braces and allowing both parts to share the same code paths. The
 __keyval_split_value:NNw at the front, keeping braces and allowing both parts to share the same code paths. The
 __keyval_split_tidy:w key is found first then there's a check that there is something there: this is biased to the
 __keyval_action: common case of there actually being a key. For the value, we first need to see if there is
 anything to do: if there is, extract it. The appropriate action is then inserted in front
 of the key and value. Doing this using an assignment is marginally faster than an an
 expansion chain.

```

12047 \cs_new_protected:Npn \__keyval_split:NNw #1#2#3 =
12048 {
12049   \__keyval_def:Nn \l__keyval_key_tl {#3}
12050   \if_meaning:w \l__keyval_key_tl \c_empty_tl
12051     \exp_after:wN \__keyval_split_tidy:w
12052   \else:
12053     \exp_after:wN \__keyval_split_value:NNw
12054     \exp_after:wN #1
12055     \exp_after:wN #2
12056     \exp_after:wN \q_mark
12057   \fi:

```

```

12058 }
12059 \cs_new_protected:Npn \__keyval_split_value:NNw #1#2#3 = #4 \q_stop
12060 {
12061   \if:w \scan_stop: \tl_to_str:n {#4} \scan_stop:
12062     \cs_set:Npx \__keyval_action:
12063       { \exp_not:N #1 { \exp_not:o \l__keyval_key_tl } }
12064   \else:
12065     \if:w
12066       \scan_stop:
12067       \__kernel_tl_to_str:w \exp_after:wN { \use_none:n #4 }
12068       \scan_stop:
12069       \__keyval_def:Nn \l__keyval_value_tl {#3}
12070       \cs_set:Npx \__keyval_action:
12071         {
12072           \exp_not:N #2
12073           { \exp_not:o \l__keyval_key_tl }
12074           { \exp_not:o \l__keyval_value_tl }
12075         }
12076     \else:
12077       \cs_set:Npn \__keyval_action:
12078       {
12079         \__kernel_msg_error:nn { kernel }
12080         { misplaced-equals-sign }
12081       }
12082     \fi:
12083   \fi:
12084   \__keyval_action:
12085 }
12086 \cs_new_protected:Npn \__keyval_split_tidy:w #1 \q_stop
12087 {
12088   \if:w
12089     \scan_stop:
12090     \__kernel_tl_to_str:w \exp_after:wN { \use_none:n #1 }
12091     \scan_stop:
12092   \else:
12093     \exp_after:wN \__keyval_empty_key:
12094   \fi:
12095 }
12096 \cs_new:Npn \__keyval_action: { }
12097 \cs_new_protected:Npn \__keyval_empty_key:
12098 { \__kernel_msg_error:nn { kernel } { misplaced-equals-sign } }

```

(End definition for __keyval_split:NNw and others.)

<pre> __keyval_def:Nn __keyval_def_aux:n __keyval_def_aux:w </pre>	<p>First remove the leading quark, then trim spaces off, and finally remove a set of braces.</p> <pre> 12099 \cs_new_protected:Npn __keyval_def:Nn #1#2 12100 { 12101 \tl_set:Nx #1 12102 { \tl_trim_spaces_apply:oN { \use_none:n #2 } __keyval_def_aux:n } 12103 } 12104 \cs_new:Npn __keyval_def_aux:n #1 12105 { __keyval_def_aux:w #1 \q_stop } 12106 \cs_new:Npn __keyval_def_aux:w #1 \q_stop { \exp_not:n {#1} } </pre>
---	--

(End definition for __keyval_def:Nn, __keyval_def_aux:n, and __keyval_def_aux:w.)

One message for the low level parsing system.

```

12107 \__kernel_msg_new:nnnn { kernel } { misplaced-equals-sign }
12108 { Misplaced-equals-sign-in-key-value-input~\msg_line_number: }
12109 {
12110     LaTeX-is-attempting-to-parse-some-key-value-input-but-found~
12111     two-equals-signs-not-separated-by-a-comma.
12112 }

```

20.2 Constants and variables

12113 `<@@=keys>`

Various storage areas for the different data which make up keys.

```

\c__keys_code_root_tl
\c__keys_default_root_tl
\c__keys_groups_root_tl
\c__keys_inherit_root_tl
\c__keys_type_root_tl
\c__keys_validate_root_tl
12114 \tl_const:Nn \c__keys_code_root_tl { key-code~>~ }
12115 \tl_const:Nn \c__keys_default_root_tl { key-default~>~ }
12116 \tl_const:Nn \c__keys_groups_root_tl { key-groups~>~ }
12117 \tl_const:Nn \c__keys_inherit_root_tl { key-inherit~>~ }
12118 \tl_const:Nn \c__keys_type_root_tl { key-type~>~ }
12119 \tl_const:Nn \c__keys_validate_root_tl { key-validate~>~ }

```

(End definition for \c__keys_code_root_tl and others.)

\c__keys_props_root_tl The prefix for storing properties.

```

12120 \tl_const:Nn \c__keys_props_root_tl { key-prop~>~ }

```

(End definition for \c__keys_props_root_tl.)

`\l_keys_choice_int` `\l_keys_choice_tl` Publicly accessible data on which choice is being used when several are generated as a set.

```

12121 \int_new:N \l_keys_choice_int
12122 \tl_new:N \l_keys_choice_tl

```

(End definition for \l_keys_choice_int and \l_keys_choice_tl. These variables are documented on page 174.)

\l__keys_groups_clist Used for storing and recovering the list of groups which apply to a key: set as a comma list but at one point we have to use this for a token list recovery.

```

12123 \clist_new:N \l__keys_groups_clist

```

(End definition for \l__keys_groups_clist.)

`\l_keys_key_tl` The name of a key itself: needed when setting keys.

```

12124 \tl_new:N \l_keys_key_tl

```

(End definition for \l_keys_key_tl. This variable is documented on page 176.)

\l__keys_module_tl The module for an entire set of keys.

```

12125 \tl_new:N \l__keys_module_tl

```

(End definition for \l__keys_module_tl.)

\l__keys_no_value_bool A marker is needed internally to show if only a key or a key plus a value was seen: this is recorded here.

```

12126 \bool_new:N \l__keys_no_value_bool

```

(End definition for \l__keys_no_value_bool.)

`\l__keys_only_known_bool` Used to track if only “known” keys are being set.

```
12127 \bool_new:N \l__keys_only_known_bool
```

(End definition for \l__keys_only_known_bool.)

`\l_keys_path_tl` The “path” of the current key is stored here: this is available to the programmer and so is public.

```
12128 \tl_new:N \l_keys_path_tl
```

(End definition for \l_keys_path_tl. This variable is documented on page 176.)

`\l__keys_inherit_tl`

```
12129 \tl_new:N \l__keys_inherit_tl
```

(End definition for \l__keys_inherit_tl.)

`\l__keys_property_tl` The “property” begin set for a key at definition time is stored here.

```
12130 \tl_new:N \l__keys_property_tl
```

(End definition for \l__keys_property_tl.)

`\l__keys_selective_bool` Two flags for using key groups: one to indicate that “selective” setting is active, a second to specify which type (“opt-in” or “opt-out”).

```
12131 \bool_new:N \l__keys_selective_bool
12132 \bool_new:N \l__keys_filtered_bool
```

(End definition for \l__keys_selective_bool and \l__keys_filtered_bool.)

`\l__keys_selective_seq` The list of key groups being filtered in or out during selective setting.

```
12133 \seq_new:N \l__keys_selective_seq
```

(End definition for \l__keys_selective_seq.)

`\l__keys_unused_clist` Used when setting only some keys to store those left over.

```
12134 \tl_new:N \l__keys_unused_clist
```

(End definition for \l__keys_unused_clist.)

`\l_keys_value_tl` The value given for a key: may be empty if no value was given.

```
12135 \tl_new:N \l_keys_value_tl
```

(End definition for \l_keys_value_tl. This variable is documented on page 176.)

`\l__keys_tmp_bool` Scratch space.

```
12136 \bool_new:N \l__keys_tmp_bool
```

(End definition for \l__keys_tmp_bool.)

20.3 The key defining mechanism

`\keys_define:nn` The public function for definitions is just a wrapper for the lower level mechanism, more or less. The outer function is designed to keep a track of the current module, to allow safe nesting. The module is set removing any leading / (which is not needed here).

```

12137 \cs_new_protected:Npn \keys_define:nn
12138 { \__keys_define:onn \l__keys_module_tl }
12139 \cs_new_protected:Npn \__keys_define:nnn #1#2#3
12140 {
12141   \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
12142   \keyval_parse:NNn \__keys_define:n \__keys_define:nn {#3}
12143   \tl_set:Nn \l__keys_module_tl {#1}
12144 }
12145 \cs_generate_variant:Nn \__keys_define:nnn { o }

```

(End definition for `\keys_define:nn` and `__keys_define:nnn`. This function is documented on page 169.)

`__keys_define:n` The outer functions here record whether a value was given and then converge on a common internal mechanism. There is first a search for a property in the current key name, then a check to make sure it is known before the code hands off to the next step.

```

12146 \cs_new_protected:Npn \__keys_define:n #1
12147 {
12148   \bool_set_true:N \l__keys_no_value_bool
12149   \__keys_define_aux:nn {#1} { }
12150 }
12151 \cs_new_protected:Npn \__keys_define:nn #1#2
12152 {
12153   \bool_set_false:N \l__keys_no_value_bool
12154   \__keys_define_aux:nn {#1} {#2}
12155 }
12156 \cs_new_protected:Npn \__keys_define_aux:nn #1#2
12157 {
12158   \__keys_property_find:n {#1}
12159   \cs_if_exist:cTF { \c__keys_props_root_tl \l__keys_property_tl }
12160   { \__keys_define_code:n {#2} }
12161   {
12162     \tl_if_empty:NF \l__keys_property_tl
12163     {
12164       \__kernel_msg_error:nxxx { kernel } { key-property-unknown }
12165       { \l__keys_property_tl } { \l_keys_path_tl }
12166     }
12167   }
12168 }

```

(End definition for `__keys_define:n`, `__keys_define:nn`, and `__keys_define_aux:nn`.)

`__keys_property_find:n` Searching for a property means finding the last . in the input, and storing the text before and after it. Everything is turned into strings, so there is no problem using an x-type expansion.

```

12169 \cs_new_protected:Npn \__keys_property_find:n #1
12170 {
12171   \tl_set:Nx \l__keys_property_tl { \__keys_remove_spaces:n {#1} }
12172   \exp_after:wN \__keys_property_find:w \l__keys_property_tl . .

```

```

12173     \q_stop {#1}
12174 }
12175 \cs_new_protected:Npn \__keys_property_find:w #1 . #2 . #3 \q_stop #4
12176 {
12177     \tl_if_blank:nTF {#3}
12178     {
12179         \tl_clear:N \l__keys_property_tl
12180         \__kernel_msg_error:nnn { kernel } { key-no-property } {#4}
12181     }
12182     {
12183         \str_if_eq:nnTF {#3} { . }
12184         {
12185             \tl_set:Nx \l_keys_path_tl
12186             {
12187                 \tl_if_empty:NF \l__keys_module_tl
12188                 { \l__keys_module_tl / }
12189                 #1
12190             }
12191             \tl_set:Nn \l__keys_property_tl { . #2 }
12192         }
12193         {
12194             \tl_set:Nx \l_keys_path_tl { \l__keys_module_tl / #1 . #2 }
12195             \__keys_property_search:w #3 \q_stop
12196         }
12197     }
12198 }
12199 \cs_new_protected:Npn \__keys_property_search:w #1 . #2 \q_stop
12200 {
12201     \str_if_eq:nnTF {#2} { . }
12202     {
12203         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl }
12204         \tl_set:Nn \l__keys_property_tl { . #1 }
12205     }
12206     {
12207         \tl_set:Nx \l_keys_path_tl { \l_keys_path_tl . #1 }
12208         \__keys_property_search:w #2 \q_stop
12209     }
12210 }

```

(End definition for __keys_property_find:n and __keys_property_find:w.)

__keys_define_code:n Two possible cases. If there is a value for the key, then just use the function. If not, then
 __keys_define_code:w a check to make sure there is no need for a value with the property. If there should be
 one then complain, otherwise execute it. There is no need to check for a : as if it was
 missing the earlier tests would have failed.

```

12211 \cs_new_protected:Npn \__keys_define_code:n #1
12212 {
12213     \bool_if:NTF \l__keys_no_value_bool
12214     {
12215         \exp_after:wN \__keys_define_code:w
12216         \l__keys_property_tl \q_stop
12217         { \use:c { \c__keys_props_root_tl \l__keys_property_tl } }
12218         {
12219             \__kernel_msg_error:nnxx { kernel }

```



```

12220             { key-property-requires-value } { \l__keys_property_tl }
12221             { \l_keys_path_tl }
12222         }
12223     }
12224     { \use:c { \c__keys_props_root_tl \l__keys_property_tl } {#1} }
12225 }
12226 \exp_last_unbraced:NNNN
12227 \cs_new:Npn \__keys_define_code:w #1 \c_colon_str #2 \q_stop
12228     { \tl_if_empty:nTF {#2} }

```

(End definition for __keys_define_code:n and __keys_define_code:w.)

20.4 Turning properties into actions

__keys_bool_set:Nn Boolean keys are really just choices, but all done by hand. The second argument here is the scope: either empty or `g` for global.

```

12229 \cs_new_protected:Npn \__keys_bool_set:Nn #1#2
12230 {
12231     \bool_if_exist:NF #1 { \bool_new:N #1 }
12232     \__keys_choice_make:
12233     \__keys_cmd_set:nx { \l_keys_path_tl / true }
12234     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
12235     \__keys_cmd_set:nx { \l_keys_path_tl / false }
12236     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
12237     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
12238     {
12239         \__kernel_msg_error:nnx { kernel } { boolean-values-only }
12240         { \l_keys_key_tl }
12241     }
12242     \__keys_default_set:n { true }
12243 }
12244 \cs_generate_variant:Nn \__keys_bool_set:Nn { c }

```

(End definition for __keys_bool_set:Nn.)

__keys_bool_set_inverse:Nn Inverse boolean setting is much the same.

```

12245 \cs_new_protected:Npn \__keys_bool_set_inverse:Nn #1#2
12246 {
12247     \bool_if_exist:NF #1 { \bool_new:N #1 }
12248     \__keys_choice_make:
12249     \__keys_cmd_set:nx { \l_keys_path_tl / true }
12250     { \exp_not:c { bool_ #2 set_false:N } \exp_not:N #1 }
12251     \__keys_cmd_set:nx { \l_keys_path_tl / false }
12252     { \exp_not:c { bool_ #2 set_true:N } \exp_not:N #1 }
12253     \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
12254     {
12255         \__kernel_msg_error:nnx { kernel } { boolean-values-only }
12256         { \l_keys_key_tl }
12257     }
12258     \__keys_default_set:n { true }
12259 }
12260 \cs_generate_variant:Nn \__keys_bool_set_inverse:Nn { c }

```

(End definition for __keys_bool_set_inverse:Nn.)

`__keys_choice_make:` To make a choice from a key, two steps: set the code, and set the unknown key. As
`__keys_multichoice_make:` multichoices and choices are essentially the same bar one function, the code is given
`__keys_choice_make:N` together.
`__keys_choice_make_aux:N`

```

12261 \cs_new_protected:Npn __keys_choice_make:
12262 { __keys_choice_make:N __keys_choice_find:n }
12263 \cs_new_protected:Npn __keys_multichoice_make:
12264 { __keys_choice_make:N __keys_multichoice_find:n }
12265 \cs_new_protected:Npn __keys_choice_make:N #1
12266 {
12267   \cs_if_exist:cTF
12268     { \c__keys_type_root_tl __keys_parent:o \l_keys_path_tl }
12269     {
12270       \str_if_eq:vnTF
12271         { \c__keys_type_root_tl __keys_parent:o \l_keys_path_tl }
12272         { choice }
12273         {
12274           \__kernel_msg_error:nxxx { kernel } { nested-choice-key }
12275           { \l_keys_path_tl } { __keys_parent:o \l_keys_path_tl }
12276         }
12277         { __keys_choice_make_aux:N #1 }
12278       }
12279     { __keys_choice_make_aux:N #1 }
12280   }
12281 \cs_new_protected:Npn __keys_choice_make_aux:N #1
12282 {
12283   \cs_set_nopar:cpn { \c__keys_type_root_tl \l_keys_path_tl }
12284   { choice }
12285   \__keys_cmd_set:nn { \l_keys_path_tl } { #1 {##1} }
12286   \__keys_cmd_set:nn { \l_keys_path_tl / unknown }
12287   {
12288     \__kernel_msg_error:nxxx { kernel } { key-choice-unknown }
12289     { \l_keys_path_tl } {##1}
12290   }
12291 }

```

(End definition for `__keys_choice_make:` and others.)

`__keys_choices_make:nn` Auto-generating choices means setting up the root key as a choice, then defining each
`__keys_multichoices_make:nn` choice in turn.
`__keys_choices_make:Nnn`

```

12292 \cs_new_protected:Npn __keys_choices_make:nn
12293 { __keys_choices_make:Nnn __keys_choice_make: }
12294 \cs_new_protected:Npn __keys_multichoices_make:nn
12295 { __keys_choices_make:Nnn __keys_multichoice_make: }
12296 \cs_new_protected:Npn __keys_choices_make:Nnn #1#2#3
12297 {
12298   #1
12299   \int_zero:N \l_keys_choice_int
12300   \clist_map_inline:nn {#2}
12301   {
12302     \int_incr:N \l_keys_choice_int
12303     \__keys_cmd_set:nx
12304     { \l_keys_path_tl / __keys_remove_spaces:n {##1} }
12305     {
12306       \tl_set:Nn \exp_not:N \l_keys_choice_tl {##1}

```

```

12307         \int_set:Nn \exp_not:N \l_keys_choice_int
12308         { \int_use:N \l_keys_choice_int }
12309         \exp_not:n {#3}
12310     }
12311 }
12312 }

```

(End definition for `__keys_choices_make:nn`, `__keys_multichoices_make:nn`, and `__keys_choices_make:Nnn`.)

`__keys_cmd_set:nn` Setting the code for a key first logs if appropriate that we are defining a new key, then saves the code.

```

12313 \__kernel_patch:nnNnpn
12314 {
12315     \cs_if_exist:cF { \c__keys_code_root_tl #1 }
12316     { \__kernel_debug_log:x { Defining-key~#1~\msg_line_context: } }
12317 }
12318 { }
12319 \cs_new_protected:Npn \__keys_cmd_set:nn #1#2
12320 { \cs_set_protected:cpn { \c__keys_code_root_tl #1 } ##1 {#2} }
12321 \cs_generate_variant:Nn \__keys_cmd_set:nn { nx , Vn , Vo }

```

(End definition for `__keys_cmd_set:nn`.)

`__keys_default_set:n` Setting a default value is easy. These are stored using `\cs_set:cpx` as this avoids any worries about whether a token list exists.

```

12322 \cs_new_protected:Npn \__keys_default_set:n #1
12323 {
12324     \tl_if_empty:nTF {#1}
12325     {
12326         \cs_set_eq:cN
12327         { \c__keys_default_root_tl \l_keys_path_tl }
12328         \tex_undefined:D
12329     }
12330     {
12331         \cs_set:cpx
12332         { \c__keys_default_root_tl \l_keys_path_tl }
12333         { \exp_not:n {#1} }
12334     }
12335 }

```

(End definition for `__keys_default_set:n`.)

`__keys_groups_set:n` Assigning a key to one or more groups uses comma lists. As the list of groups only exists if there is anything to do, the setting is done using a scratch list. For the usual grouping reasons we use the low-level approach to undefining a list. We also use the low-level approach for the other case to avoid tripping up the `check-declarations` code.

```

12336 \cs_new_protected:Npn \__keys_groups_set:n #1
12337 {
12338     \clist_set:Nn \l__keys_groups_clist {#1}
12339     \clist_if_empty:NTF \l__keys_groups_clist
12340     {
12341         \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
12342         \tex_undefined:D

```

```

12343     }
12344     {
12345         \cs_set_eq:cN { \c__keys_groups_root_tl \l_keys_path_tl }
12346         \l__keys_groups_clist
12347     }
12348 }

```

(End definition for __keys_groups_set:n.)

`__keys_inherit:n` Inheritance means ignoring anything already said about the key: zap the lot and set up.

```

12349 \cs_new_protected:Npn \__keys_inherit:n #1
12350 {
12351     \__keys_undefine:
12352     \cs_set_nopar:cpn { \c__keys_inherit_root_tl \l_keys_path_tl } {#1}
12353 }

```

(End definition for __keys_inherit:n.)

`__keys_initialise:n` A set up for initialisation: just run the code if it exists.

```

12354 \cs_new_protected:Npn \__keys_initialise:n #1
12355 {
12356     \cs_if_exist_use:cT { \c__keys_code_root_tl \l_keys_path_tl } { {#1} }
12357 }

```

(End definition for __keys_initialise:n.)

`__keys_meta_make:n` To create a meta-key, simply set up to pass data through.

```

\__keys_meta_make:nn
12358 \cs_new_protected:Npn \__keys_meta_make:n #1
12359 {
12360     \__keys_cmd_set:Vo \l_keys_path_tl
12361     {
12362         \exp_after:wN \keys_set:nn
12363         \exp_after:wN { \l__keys_module_tl } {#1}
12364     }
12365 }
12366 \cs_new_protected:Npn \__keys_meta_make:nn #1#2
12367 { \__keys_cmd_set:Vn \l_keys_path_tl { \keys_set:nn {#1} {#2} } }

```

(End definition for __keys_meta_make:n and __keys_meta_make:nn.)

`__keys_undefine:` Undefining a key has to be done without `\cs_undefine:c` as that function acts globally.

```

12368 \cs_new_protected:Npn \__keys_undefine:
12369 {
12370     \clist_map_inline:nn
12371     { code , default , groups , inherit , type , validate }
12372     {
12373         \cs_set_eq:cN
12374         { \tl_use:c { c__keys_ ##1 _root_tl } \l_keys_path_tl }
12375         \tex_undefined:D
12376     }
12377 }

```

(End definition for __keys_undefine:.)

`__keys_value_requirement:nn` Validating key input is done using a second function which runs before the main key code. Setting that up means setting it equal to a generic stub which does the check. This approach makes the lookup very fast at the cost of one additional csname per key that needs it. The cleanup here has to know the structure of the following code.

```

12378 \cs_new_protected:Npn \__keys_value_requirement:nn #1#2
12379 {
12380   \str_case:nnF {#2}
12381   {
12382     { true }
12383     {
12384       \cs_set_eq:cc
12385       { \c__keys_validate_root_tl \l_keys_path_tl }
12386       { __keys_validate_ #1 : }
12387     }
12388     { false }
12389     {
12390       \cs_if_eq:ccT
12391       { \c__keys_validate_root_tl \l_keys_path_tl }
12392       { __keys_validate_ #1 : }
12393       {
12394         \cs_set_eq:cN
12395         { \c__keys_validate_root_tl \l_keys_path_tl }
12396         \tex_undefined:D
12397       }
12398     }
12399   }
12400   {
12401     \__kernel_msg_error:nnx { kernel }
12402     { key-property-boolean-values-only }
12403     { .value_ #1 :n }
12404   }
12405 }
12406 \cs_new_protected:Npn \__keys_validate_forbidden:
12407 {
12408   \bool_if:NF \l__keys_no_value_bool
12409   {
12410     \__kernel_msg_error:nnxx { kernel } { value-forbidden }
12411     { \l_keys_path_tl } { \l_keys_value_tl }
12412     \__keys_validate_cleanup:w
12413   }
12414 }
12415 \cs_new_protected:Npn \__keys_validate_required:
12416 {
12417   \bool_if:NT \l__keys_no_value_bool
12418   {
12419     \__kernel_msg_error:nnx { kernel } { value-required }
12420     { \l_keys_path_tl }
12421     \__keys_validate_cleanup:w
12422   }
12423 }
12424 \cs_new_protected:Npn \__keys_validate_cleanup:w #1 \cs_end: #2#3 { }

```

(End definition for `__keys_value_requirement:nn` and others.)

```

\__keys_variable_set:NnnN
\__keys_variable_set:cnnN

```

Setting a variable takes the type and scope separately so that it is easy to make a new variable if needed.

```

12425 \cs_new_protected:Npn \__keys_variable_set:NnnN #1#2#3#4
12426 {
12427   \use:c { #2_if_exist:Nf } #1 { \use:c { #2_new:N } #1 }
12428   \__keys_cmd_set:nx { \l_keys_path_tl }
12429   {
12430     \exp_not:c { #2 _ #3 set:N #4 }
12431     \exp_not:N #1
12432     \exp_not:n { {#1} }
12433   }
12434 }
12435 \cs_generate_variant:Nn \__keys_variable_set:NnnN { c }

```

(End definition for __keys_variable_set:NnnN.)

20.5 Creating key properties

The key property functions are all wrappers for internal functions, meaning that things stay readable and can also be altered later on.

Importantly, while key properties have “normal” argument specs, the underlying code always supplies one braced argument to these. As such, argument expansion is handled by hand rather than using the standard tools. This shows up particularly for the two-argument properties, where things would otherwise go badly wrong.

```

.bool_set:N One function for this.
.bool_set:c 12436 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:N } #1
.bool_gset:N 12437 { \__keys_bool_set:Nn #1 { } }
.bool_gset:c 12438 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set:c } #1
12439 { \__keys_bool_set:cn {#1} { } }
12440 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:N } #1
12441 { \__keys_bool_set:Nn #1 { g } }
12442 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset:c } #1
12443 { \__keys_bool_set:cn {#1} { g } }

```

(End definition for .bool_set:N and .bool_gset:N. These functions are documented on page 170.)

```

.bool_set_inverse:N One function for this.
.bool_set_inverse:c 12444 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:N } #1
.bool_gset_inverse:N 12445 { \__keys_bool_set_inverse:Nn #1 { } }
.bool_gset_inverse:c 12446 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_set_inverse:c } #1
12447 { \__keys_bool_set_inverse:cn {#1} { } }
12448 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:N } #1
12449 { \__keys_bool_set_inverse:Nn #1 { g } }
12450 \cs_new_protected:cpn { \c__keys_props_root_tl .bool_gset_inverse:c } #1
12451 { \__keys_bool_set_inverse:cn {#1} { g } }

```

(End definition for .bool_set_inverse:N and .bool_gset_inverse:N. These functions are documented on page 170.)

.choice: Making a choice is handled internally, as it is also needed by .generate_choices:n.

```

12452 \cs_new_protected:cpn { \c__keys_props_root_tl .choice: }
12453 { \__keys_choice_make: }

```

(End definition for `.choice:`. This function is documented on page 170.)

.choices:nn For auto-generation of a series of mutually-exclusive choices. Here, #1 consists of two separate arguments, hence the slightly odd-looking implementation.

```
.choices:Vn
.choices:on
.choices:xn
12454 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:nn } #1
12455   { \__keys_choices_make:nn #1 }
12456 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:Vn } #1
12457   { \exp_args:NV \__keys_choices_make:nn #1 }
12458 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:on } #1
12459   { \exp_args:No \__keys_choices_make:nn #1 }
12460 \cs_new_protected:cpn { \c__keys_props_root_tl .choices:xn } #1
12461   { \exp_args:Nx \__keys_choices_make:nn #1 }
```

(End definition for `.choices:nn`. This function is documented on page 170.)

.code:n Creating code is simply a case of passing through to the underlying set function.

```
12462 \cs_new_protected:cpn { \c__keys_props_root_tl .code:n } #1
12463   { \__keys_cmd_set:nn { \l_keys_path_tl } {#1} }
```

(End definition for `.code:n`. This function is documented on page 170.)

.clist_set:N

```
.clist_set:c
.clist_gset:N
.clist_gset:c
12464 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:N } #1
12465   { \__keys_variable_set:NnnN #1 { clist } { } n }
12466 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_set:c } #1
12467   { \__keys_variable_set:cnnN {#1} { clist } { } n }
12468 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:N } #1
12469   { \__keys_variable_set:NnnN #1 { clist } { g } n }
12470 \cs_new_protected:cpn { \c__keys_props_root_tl .clist_gset:c } #1
12471   { \__keys_variable_set:cnnN {#1} { clist } { g } n }
```

(End definition for `.clist_set:N` and `.clist_gset:N`. These functions are documented on page 170.)

.default:n Expansion is left to the internal functions.

```
.default:V
.default:o
.default:x
12472 \cs_new_protected:cpn { \c__keys_props_root_tl .default:n } #1
12473   { \__keys_default_set:n {#1} }
12474 \cs_new_protected:cpn { \c__keys_props_root_tl .default:V } #1
12475   { \exp_args:NV \__keys_default_set:n #1 }
12476 \cs_new_protected:cpn { \c__keys_props_root_tl .default:o } #1
12477   { \exp_args:No \__keys_default_set:n {#1} }
12478 \cs_new_protected:cpn { \c__keys_props_root_tl .default:x } #1
12479   { \exp_args:Nx \__keys_default_set:n {#1} }
```

(End definition for `.default:n`. This function is documented on page 171.)

.dim_set:N Setting a variable is very easy: just pass the data along.

```
.dim_set:c
.dim_gset:N
.dim_gset:c
12480 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:N } #1
12481   { \__keys_variable_set:NnnN #1 { dim } { } n }
12482 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_set:c } #1
12483   { \__keys_variable_set:cnnN {#1} { dim } { } n }
12484 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:N } #1
12485   { \__keys_variable_set:NnnN #1 { dim } { g } n }
12486 \cs_new_protected:cpn { \c__keys_props_root_tl .dim_gset:c } #1
12487   { \__keys_variable_set:cnnN {#1} { dim } { g } n }
```

(End definition for `.dim_set:N` and `.dim_gset:N`. These functions are documented on page 171.)

.fp_set:N Setting a variable is very easy: just pass the data along.

```
.fp_set:c 12488 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:N } #1
          12489 { \__keys_variable_set:NnnN #1 { fp } { } n }
.fp_gset:N
          12490 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_set:c } #1
          12491 { \__keys_variable_set:cnnN {#1} { fp } { } n }
          12492 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:N } #1
          12493 { \__keys_variable_set:NnnN #1 { fp } { g } n }
          12494 \cs_new_protected:cpn { \c__keys_props_root_tl .fp_gset:c } #1
          12495 { \__keys_variable_set:cnnN {#1} { fp } { g } n }
```

(End definition for `.fp_set:N` and `.fp_gset:N`. These functions are documented on page 171.)

.groups:n A single property to create groups of keys.

```
12496 \cs_new_protected:cpn { \c__keys_props_root_tl .groups:n } #1
12497 { \__keys_groups_set:n {#1} }
```

(End definition for `.groups:n`. This function is documented on page 171.)

.inherit:n Nothing complex: only one variant at the moment!

```
12498 \cs_new_protected:cpn { \c__keys_props_root_tl .inherit:n } #1
12499 { \__keys_inherit:n {#1} }
```

(End definition for `.inherit:n`. This function is documented on page 171.)

.initial:n The standard hand-off approach.

```
.initial:V 12500 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:n } #1
.initial:o 12501 { \__keys_initialise:n {#1} }
.initial:x 12502 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:V } #1
          12503 { \exp_args:NV \__keys_initialise:n #1 }
          12504 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:o } #1
          12505 { \exp_args:No \__keys_initialise:n {#1} }
          12506 \cs_new_protected:cpn { \c__keys_props_root_tl .initial:x } #1
          12507 { \exp_args:Nx \__keys_initialise:n {#1} }
```

(End definition for `.initial:n`. This function is documented on page 172.)

.int_set:N Setting a variable is very easy: just pass the data along.

```
.int_set:c 12508 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:N } #1
          12509 { \__keys_variable_set:NnnN #1 { int } { } n }
.int_gset:N
          12510 \cs_new_protected:cpn { \c__keys_props_root_tl .int_set:c } #1
          12511 { \__keys_variable_set:cnnN {#1} { int } { } n }
          12512 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:N } #1
          12513 { \__keys_variable_set:NnnN #1 { int } { g } n }
          12514 \cs_new_protected:cpn { \c__keys_props_root_tl .int_gset:c } #1
          12515 { \__keys_variable_set:cnnN {#1} { int } { g } n }
```

(End definition for `.int_set:N` and `.int_gset:N`. These functions are documented on page 172.)

.meta:n Making a meta is handled internally.

```
12516 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:n } #1
12517 { \__keys_meta_make:n {#1} }
```

(End definition for `.meta:n`. This function is documented on page 172.)

.meta:nn Meta with path: potentially lots of variants, but for the moment no so many defined.

```
12518 \cs_new_protected:cpn { \c__keys_props_root_tl .meta:nn } #1
12519 { \__keys_meta_make:nn #1 }
```

(End definition for .meta:nn. This function is documented on page 172.)

.multichoice: The same idea as .choice: and .choices:nn, but where more than one choice is allowed.

```
.multichoices:nn 12520 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoice: }
.multichoices:Vn 12521 { \__keys_multichoice_make: }
.multichoices:on 12522 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:nn } #1
.multichoices:xn 12523 { \__keys_multichoices_make:nn #1 }
12524 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:Vn } #1
12525 { \exp_args:NV \__keys_multichoices_make:nn #1 }
12526 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:on } #1
12527 { \exp_args:No \__keys_multichoices_make:nn #1 }
12528 \cs_new_protected:cpn { \c__keys_props_root_tl .multichoices:xn } #1
12529 { \exp_args:Nx \__keys_multichoices_make:nn #1 }
```

(End definition for .multichoice: and .multichoices:nn. These functions are documented on page 172.)

.skip_set:N Setting a variable is very easy: just pass the data along.

```
.skip_set:c 12530 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:N } #1
.skip_gset:N 12531 { \__keys_variable_set:NnnN #1 { skip } { } n }
12532 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_set:c } #1
12533 { \__keys_variable_set:cnnN {#1} { skip } { } n }
12534 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:N } #1
12535 { \__keys_variable_set:NnnN #1 { skip } { g } n }
12536 \cs_new_protected:cpn { \c__keys_props_root_tl .skip_gset:c } #1
12537 { \__keys_variable_set:cnnN {#1} { skip } { g } n }
```

(End definition for .skip_set:N and .skip_gset:N. These functions are documented on page 172.)

.tl_set:N Setting a variable is very easy: just pass the data along.

```
.tl_set:c 12538 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:N } #1
.tl_gset:N 12539 { \__keys_variable_set:NnnN #1 { tl } { } n }
12540 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set:c } #1
12541 { \__keys_variable_set:cnnN {#1} { tl } { } n }
.tl_set_x:N 12542 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:N } #1
.tl_gset_x:N 12543 { \__keys_variable_set:NnnN #1 { tl } { } x }
12544 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_set_x:c } #1
12545 { \__keys_variable_set:cnnN {#1} { tl } { } x }
12546 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:N } #1
12547 { \__keys_variable_set:NnnN #1 { tl } { g } n }
12548 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset:c } #1
12549 { \__keys_variable_set:cnnN {#1} { tl } { g } n }
12550 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:N } #1
12551 { \__keys_variable_set:NnnN #1 { tl } { g } x }
12552 \cs_new_protected:cpn { \c__keys_props_root_tl .tl_gset_x:c } #1
12553 { \__keys_variable_set:cnnN {#1} { tl } { g } x }
```

(End definition for .tl_set:N and others. These functions are documented on page 172.)

.undefine: Another simple wrapper.

```
12554 \cs_new_protected:cpn { \c__keys_props_root_tl .undefine: }
12555 { \__keys_undefine: }
```

(End definition for `.undefine:.`. This function is documented on page 173.)

`.value_forbidden:n` These are very similar, so both call the same function.

```
.value_required:n 12556 \cs_new_protected:cpn { \c__keys_props_root_tl .value_forbidden:n } #1
                  12557 { \__keys_value_requirement:nn { forbidden } {#1} }
                  12558 \cs_new_protected:cpn { \c__keys_props_root_tl .value_required:n } #1
                  12559 { \__keys_value_requirement:nn { required } {#1} }
```

(End definition for `.value_forbidden:n` and `.value_required:n`. These functions are documented on page 173.)

20.6 Setting keys

`\keys_set:nn` A simple wrapper again.

```
\keys_set:nV 12560 \cs_new_protected:Npn \keys_set:nn
\keys_set:nv 12561 { \__keys_set:onnn { \l__keys_module_tl } }
\keys_set:no 12562 \cs_new_protected:Npn \keys_set:nnn #1#2#3
\__keys_set:nnn 12563 {
\__keys_set:onnn 12564 \tl_set:Nx \l__keys_module_tl { \__keys_remove_spaces:n {#2} }
                  12565 \keyval_parse:NNn \__keys_set:n \__keys_set:nn {#3}
                  12566 \tl_set:Nn \l__keys_module_tl {#1}
                  12567 }
                  12568 \cs_generate_variant:Nn \keys_set:nn { nV , nv , no }
                  12569 \cs_generate_variant:Nn \__keys_set:nnn { o }
```

(End definition for `\keys_set:nn` and `__keys_set:nnn`. This function is documented on page 176.)

`\keys_set_known:nnN` Setting known keys simply means setting the appropriate flag, then running the standard code. To allow for nested setting, any existing value of `\l__keys_unused_clist` is saved on the stack and reset afterwards. Note that for speed/simplicity reasons we use a `tl` operation to set the `clist` here!

```
\keys_set_known:nVN 12570 \cs_new_protected:Npn \keys_set_known:nnN
\keys_set_known:nvN 12571 { \__keys_set_known:onnnN \l__keys_unused_clist }
\keys_set_known:noN 12572 \cs_generate_variant:Nn \keys_set_known:nnN { nV , nv , no }
\__keys_set_known:nnnN 12573 \cs_new_protected:Npn \keys_set_known:nnnN #1#2#3#4
\__keys_set_known:onnnN 12574 {
\keys_set_known:nV 12575 \clist_clear:N \l__keys_unused_clist
\keys_set_known:nv 12576 \keys_set_known:nn {#2} {#3}
\keys_set_known:no 12577 \tl_set:Nx #4 { \exp_not:o { \l__keys_unused_clist } }
\__keys_keys_set_known:nn 12578 \tl_set:Nn \l__keys_unused_clist {#1}
                          12579 }
                          12580 \cs_generate_variant:Nn \__keys_set_known:nnnN { o }
                          12581 \cs_new_protected:Npn \keys_set_known:nn #1#2
                          12582 {
                          12583 \bool_if:NTF \l__keys_only_known_bool
                          12584 { \keys_set:nn }
                          12585 { \__keys_set_known:nn }
                          12586 {#1} {#2}
                          12587 }
                          12588 \cs_generate_variant:Nn \keys_set_known:nn { nV , nv , no }
                          12589 \cs_new_protected:Npn \__keys_set_known:nn #1#2
                          12590 {
                          12591 \bool_set_true:N \l__keys_only_known_bool
                          12592 \keys_set:nn {#1} {#2}
```

```

12593     \bool_set_false:N \l__keys_only_known_bool
12594 }

```

(End definition for \keys_set_known:nnN and others. These functions are documented on page 177.)

```

\keys_set_filter:nnnN The idea of setting keys in a selective manner again uses flags wrapped around the basic
\keys_set_filter:nnVN code. The comments on \keys_set_known:nnN also apply here. We have a bit more
\keys_set_filter:nnvN shuffling to do to keep everything nestable.
\keys_set_filter:nnoN
\__keys_set_filter:nnnnN
\__keys_set_filter:onnnN
\keys_set_filter:nnn 12595 \cs_new_protected:Npn \keys_set_filter:nnnN
\keys_set_filter:nnV { \__keys_set_filter:onnnN \l__keys_unused_clist }
\keys_set_filter:nnv 12596 { \__keys_set_filter:onnnN \l__keys_unused_clist }
\keys_set_filter:nno 12597 \cs_generate_variant:Nn \keys_set_filter:nnnN { nnV , nnv , nno }
\__keys_set_filter:nnn 12598 \cs_new_protected:Npn \__keys_set_filter:nnnnN #1#2#3#4#5
\keys_set_groups:nnn {
12599 {
12600 \clist_clear:N \l__keys_unused_clist
12601 \keys_set_filter:nnn {#2} {#3} {#4}
12602 \tl_set:Nx #5 { \exp_not:o { \l__keys_unused_clist } }
12603 \tl_set:Nn \l__keys_unused_clist {#1}
12604 }
12605 \cs_generate_variant:Nn \__keys_set_filter:nnnnN { o }
12606 \cs_new_protected:Npn \keys_set_filter:nnn #1#2#3
12607 {
12608 \bool_if:NTF \l__keys_filtered_bool
12609 { \__keys_set_selective:nnn }
12610 { \__keys_set_filter:nnn }
12611 {#1} {#2} {#3}
12612 }
12613 \cs_generate_variant:Nn \keys_set_filter:nnn { nnV , nnv , nno }
12614 \cs_new_protected:Npn \__keys_set_filter:nnn #1#2#3
12615 {
12616 \bool_set_true:N \l__keys_filtered_bool
12617 \__keys_set_selective:nnn {#1} {#2} {#3}
12618 \bool_set_false:N \l__keys_filtered_bool
12619 }
12620 \cs_new_protected:Npn \keys_set_groups:nnn #1#2#3
12621 {
12622 \bool_if:NTF \l__keys_filtered_bool
12623 { \__keys_set_groups:nnn }
12624 { \__keys_set_selective:nnn }
12625 {#1} {#2} {#3}
12626 }
12627 \cs_generate_variant:Nn \keys_set_groups:nnn { nnV , nnv , nno }
12628 \cs_new_protected:Npn \__keys_set_groups:nnn #1#2#3
12629 {
12630 \bool_set_false:N \l__keys_filtered_bool
12631 \__keys_set_selective:nnn {#1} {#2} {#3}
12632 \bool_set_true:N \l__keys_filtered_bool
12633 }
12634 \cs_new_protected:Npn \__keys_set_selective:nnn
12635 { \__keys_set_selective:onnn \l__keys_selective_seq }
12636 \cs_new_protected:Npn \__keys_set_selective:nnnn #1#2#3#4
12637 {
12638 \seq_set_from_clist:Nn \l__keys_selective_seq {#3}
12639 \bool_if:NTF \l__keys_selective_bool
12640 { \keys_set:nn }

```

```

12641     { \_keys_set_selective:nn }
12642     {#2} {#4}
12643     \tl_set:Nn \l__keys_selective_seq {#1}
12644   }
12645   \cs_generate_variant:Nn \_keys_set_selective:nnnn { o }
12646   \cs_new_protected:Npn \_keys_set_selective:nn #1#2
12647   {
12648     \bool_set_true:N \l__keys_selective_bool
12649     \keys_set:nn {#1} {#2}
12650     \bool_set_false:N \l__keys_selective_bool
12651   }

```

(End definition for `\keys_set_filter:nnnN` and others. These functions are documented on page 178.)

```

\_keys_set:n      A shared system once again. First, set the current path and add a default if needed.
\_keys_set:nn     There are then checks to see if the a value is required or forbidden. If everything passes,
\_keys_set_aux:nnn move on to execute the code.
\_keys_set_aux:onn
\_keys_find_key_module:w
  \_keys_set_aux:
\_keys_set_selective:
12652 \cs_new_protected:Npn \_keys_set:n #1
12653 {
12654   \bool_set_true:N \l__keys_no_value_bool
12655   \_keys_set_aux:onn \l__keys_module_tl {#1} { }
12656 }
12657 \cs_new_protected:Npn \_keys_set:nn #1#2
12658 {
12659   \bool_set_false:N \l__keys_no_value_bool
12660   \_keys_set_aux:onn \l__keys_module_tl {#1} {#2}
12661 }

```

The key path here can be fully defined, after which there is a search for the key and module names: the user may have passed them with part of what is actually the module (for our purposes) in the key name. As that happens on a per-key basis, we use the stack approach to restore the module name without a group.

```

12662 \cs_new_protected:Npn \_keys_set_aux:nnn #1#2#3
12663 {
12664   \tl_set:Nx \l_keys_path_tl
12665   {
12666     \tl_if_blank:nF {#1}
12667     { #1 / }
12668     \_keys_remove_spaces:n {#2}
12669   }
12670   \tl_clear:N \l__keys_module_tl
12671   \exp_after:wN \_keys_find_key_module:w \l_keys_path_tl / \q_stop
12672   \_keys_value_or_default:n {#3}
12673   \bool_if:NTF \l__keys_selective_bool
12674   { \_keys_set_selective: }
12675   { \_keys_execute: }
12676   \tl_set:Nn \l__keys_module_tl {#1}
12677 }
12678 \cs_generate_variant:Nn \_keys_set_aux:nnn { o }
12679 \cs_new_protected:Npn \_keys_find_key_module:w #1 / #2 \q_stop
12680 {
12681   \tl_if_blank:nTF {#2}
12682   { \tl_set:Nn \l_keys_key_tl {#1} }
12683   {

```

```

12684         \tl_put_right:Nx \l__keys_module_tl
12685         {
12686             \tl_if_empty:NF \l__keys_module_tl { / }
12687             #1
12688         }
12689         \__keys_find_key_module:w #2 \q_stop
12690     }
12691 }

```

If selective setting is active, there are a number of possible sub-cases to consider. The key name may not be known at all or if it is, it may not have any groups assigned. There is then the question of whether the selection is opt-in or opt-out.

```

12692 \cs_new_protected:Npn \__keys_set_selective:
12693 {
12694     \cs_if_exist:cTF { \c__keys_groups_root_tl \l_keys_path_tl }
12695     {
12696         \clist_set_eq:Nc \l__keys_groups_clist
12697         { \c__keys_groups_root_tl \l_keys_path_tl }
12698         \__keys_check_groups:
12699     }
12700     {
12701         \bool_if:NTF \l__keys_filtered_bool
12702         { \__keys_execute: }
12703         { \__keys_store_unused: }
12704     }
12705 }

```

In the case where selective setting requires a comparison of the list of groups which apply to a key with the list of those which have been set active. That requires two mappings, and again a different outcome depending on whether opt-in or opt-out is set.

```

12706 \cs_new_protected:Npn \__keys_check_groups:
12707 {
12708     \bool_set_false:N \l__keys_tmp_bool
12709     \seq_map_inline:Nn \l__keys_selective_seq
12710     {
12711         \clist_map_inline:Nn \l__keys_groups_clist
12712         {
12713             \str_if_eq:nnT {##1} {####1}
12714             {
12715                 \bool_set_true:N \l__keys_tmp_bool
12716                 \clist_map_break:n { \seq_map_break: }
12717             }
12718         }
12719     }
12720     \bool_if:NTF \l__keys_tmp_bool
12721     {
12722         \bool_if:NTF \l__keys_filtered_bool
12723         { \__keys_store_unused: }
12724         { \__keys_execute: }
12725     }
12726     {
12727         \bool_if:NTF \l__keys_filtered_bool
12728         { \__keys_execute: }
12729         { \__keys_store_unused: }
12730     }

```

```
12731 }
```

(End definition for `__keys_set:n` and others.)

`__keys_value_or_default:n` If a value is given, return it as #1, otherwise send a default if available.

```
12732 \cs_new_protected:Npn \__keys_value_or_default:n #1
12733 {
12734   \bool_if:NTF \l__keys_no_value_bool
12735   {
12736     \cs_if_exist:cTF { \c__keys_default_root_tl \l_keys_path_tl }
12737     {
12738       \tl_set_eq:Nc
12739         \l_keys_value_tl
12740         { \c__keys_default_root_tl \l_keys_path_tl }
12741     }
12742     { \tl_clear:N \l_keys_value_tl }
12743   }
12744   { \tl_set:Nn \l_keys_value_tl {#1} }
12745 }
```

(End definition for `__keys_value_or_default:n`.)

`__keys_execute:` Actually executing a key is done in two parts. First, look for the key itself, then look
`__keys_execute_inherit:` for the **unknown** key with the same path. If both of these fail, complain. What exactly
`__keys_execute_unknown:` happens if a key is unknown depends on whether unknown keys are being skipped or if
`__keys_execute:nn` an error should be raised.

```
\__keys_store_unused:
12746 \cs_new_protected:Npn \__keys_execute:
12747 {
12748   \cs_if_exist:cTF { \c__keys_code_root_tl \l_keys_path_tl }
12749   {
12750     \cs_if_exist_use:c { \c__keys_validate_root_tl \l_keys_path_tl }
12751     \cs:w \c__keys_code_root_tl \l_keys_path_tl \exp_after:wN \cs_end:
12752     \exp_after:wN { \l_keys_value_tl }
12753   }
12754   {
12755     \bool_if:NTF \l__keys_only_known_bool
12756     { \__keys_store_unused: }
12757     {
12758       \cs_if_exist:cTF
12759       { \c__keys_inherit_root_tl \__keys_parent:o \l_keys_path_tl }
12760       { \__keys_execute_inherit: }
12761       { \__keys_execute_unknown: }
12762     }
12763   }
12764 }
```

To deal with the case where there is no hit, we leave `__keys_execute_unknown:` in the input stream and clean it up using the break function: that avoids needing a boolean.

```
12765 \cs_new_protected:Npn \__keys_execute_inherit:
12766 {
12767   \clist_map_inline:cn
12768   { \c__keys_inherit_root_tl \__keys_parent:o \l_keys_path_tl }
12769   {
12770     \cs_if_exist:cT
```

```

12771         { \c__keys_code_root_tl ##1 / \l_keys_key_tl }
12772         {
12773             \tl_set:Nn \l__keys_inherit_tl {##1}
12774             \cs:w \c__keys_code_root_tl ##1 / \l_keys_key_tl
12775             \exp_after:wN \cs_end: \exp_after:wN
12776             { \l_keys_value_tl }
12777             \clist_map_break:n { \use_none:n }
12778         }
12779     }
12780     \__keys_execute_unknown:
12781 }
12782 \cs_new_protected:Npn \__keys_execute_unknown:
12783 {
12784     \cs_if_exist:cTF
12785     { \c__keys_code_root_tl \l__keys_module_tl / unknown }
12786     {
12787         \cs:w \c__keys_code_root_tl \l__keys_module_tl / unknown
12788         \exp_after:wN \cs_end: \exp_after:wN { \l_keys_value_tl }
12789     }
12790     {
12791         \__kernel_msg_error:nnxx { kernel } { key-unknown }
12792         { \l_keys_path_tl } { \l__keys_module_tl }
12793     }
12794 }
12795 \cs_new:Npn \__keys_execute:nn #1#2
12796 {
12797     \cs_if_exist:cTF { \c__keys_code_root_tl #1 }
12798     {
12799         \cs:w \c__keys_code_root_tl #1 \exp_after:wN \cs_end:
12800         \exp_after:wN { \l_keys_value_tl }
12801     }
12802     {#2}
12803 }
12804 \cs_new_protected:Npn \__keys_store_unused:
12805 {
12806     \clist_put_right:Nx \l__keys_unused_clist
12807     {
12808         \exp_not:o \l_keys_key_tl
12809         \bool_if:NF \l__keys_no_value_bool
12810         { = { \exp_not:o \l_keys_value_tl } }
12811     }
12812 }

```

(End definition for __keys_execute: and others.)

__keys_choice_find:n Executing a choice has two parts. First, try the choice given, then if that fails call the
 __keys_choice_find:nn unknown key. That always exists, as it is created when a choice is first made. So there
 __keys_multichoice_find:n is no need for any escape code. For multiple choices, the same code ends up used in a
 mapping.

```

12813 \cs_new:Npn \__keys_choice_find:n #1
12814 {
12815     \tl_if_empty:NTF \l__keys_inherit_tl
12816     { \__keys_choice_find:nn { \l_keys_path_tl } {#1} }
12817     {

```

```

12818         \__keys_choice_find:nn
12819         { \l__keys_inherit_tl / \l_keys_key_tl } {#1}
12820     }
12821 }
12822 \cs_new:Npn \__keys_choice_find:nn #1#2
12823 {
12824     \cs_if_exist:cTF { \c__keys_code_root_tl #1 / \__keys_remove_spaces:n {#2} }
12825     { \use:c { \c__keys_code_root_tl #1 / \__keys_remove_spaces:n {#2} } {#2} }
12826     { \use:c { \c__keys_code_root_tl #1 / unknown } {#2} }
12827 }
12828 \cs_new:Npn \__keys_multichoice_find:n #1
12829 { \clist_map_function:nN {#1} \__keys_choice_find:n }

```

(End definition for __keys_choice_find:n, __keys_choice_find:nn, and __keys_multichoice_find:n.)

20.7 Utilities

__keys_parent:n Used to strip off the ending part of the key path after the last /.
 __keys_parent:o
 __keys_parent:w

```

12830 \cs_new:Npn \__keys_parent:n #1
12831 { \__keys_parent:w #1 / / \q_stop { } }
12832 \cs_generate_variant:Nn \__keys_parent:n { o }
12833 \cs_new:Npn \__keys_parent:w #1 / #2 / #3 \q_stop #4
12834 {
12835     \tl_if_blank:nTF {#2}
12836     { \use_none:n #4 }
12837     {
12838         \__keys_parent:w #2 / #3 \q_stop { #4 / #1 }
12839     }
12840 }

```

(End definition for __keys_parent:n and __keys_parent:w.)

__keys_remove_spaces:n Used in a few places so worth handling as a dedicated function.

```

12841 \cs_new:Npn \__keys_remove_spaces:n #1
12842 { \tl_trim_spaces:o { \tl_to_str:n {#1} } }

```

(End definition for __keys_remove_spaces:n.)

\keys_if_exist_p:nn A utility for others to see if a key exists.
 \keys_if_exist:nnTF

```

12843 \prg_new_conditional:Npnn \keys_if_exist:nn #1#2 { p , T , F , TF }
12844 {
12845     \cs_if_exist:cTF
12846     { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 } }
12847     { \prg_return_true: }
12848     { \prg_return_false: }
12849 }

```

(End definition for \keys_if_exist:nnTF. This function is documented on page 178.)

\keys_if_choice_exist_p:nnn Just an alternative view on \keys_if_exist:nnTF.
 \keys_if_choice_exist:nnnTF

```

12850 \prg_new_conditional:Npnn \keys_if_choice_exist:nnn #1#2#3
12851 { p , T , F , TF }
12852 {
12853     \cs_if_exist:cTF

```



```

12854     { \c__keys_code_root_tl \__keys_remove_spaces:n { #1 / #2 / #3 } }
12855     { \prg_return_true: }
12856     { \prg_return_false: }
12857   }

```

(End definition for \keys_if_choice_exist:nnnTF. This function is documented on page 178.)

```

\keys_show:nn To show a key, show its code using a message.
\keys_log:nn
\__keys_show:Nnn
12858 \cs_new_protected:Npn \keys_show:nn
12859   { \__keys_show:Nnn \msg_show:nnxxxx }
12860 \cs_new_protected:Npn \keys_log:nn
12861   { \__keys_show:Nnn \msg_log:nnxxxx }
12862 \cs_new_protected:Npn \__keys_show:Nnn #1#2#3
12863   {
12864     #1 { LaTeX / kernel } { show-key }
12865     { \__keys_remove_spaces:n { #2 / #3 } }
12866     {
12867       \keys_if_exist:nnT {#2} {#3}
12868       {
12869         \exp_args:Nnf \msg_show_item_unbraced:nn { code }
12870         {
12871           \exp_args:Nc \token_get_replacement_spec:N
12872           {
12873             \c__keys_code_root_tl
12874             \__keys_remove_spaces:n { #2 / #3 }
12875           }
12876         }
12877       }
12878     }
12879     { } { }
12880   }

```

(End definition for \keys_show:nn, \keys_log:nn, and __keys_show:Nnn. These functions are documented on page 178.)

20.8 Messages

For when there is a need to complain.

```

12881 \__kernel_msg_new:nnnn { kernel } { boolean-values-only }
12882   { Key~'#1'~accepts~boolean~values~only. }
12883   { The~key~'#1'~only~accepts~the~values~'true'~and~'false'. }
12884 \__kernel_msg_new:nnnn { kernel } { key-choice-unknown }
12885   { Key~'#1'~accepts~only~a~fixed~set~of~choices. }
12886   {
12887     The~key~'#1'~only~accepts~predefined~values,~
12888     and~'#2'~is~not~one~of~these.
12889   }
12890 \__kernel_msg_new:nnnn { kernel } { key-unknown }
12891   { The~key~'#1'~is~unknown~and~is~being~ignored. }
12892   {
12893     The~module~'#2'~does~not~have~a~key~called~'#1'.\\
12894     Check~that~you~have~spelled~the~key~name~correctly.
12895   }
12896 \__kernel_msg_new:nnnn { kernel } { nested-choice-key }

```

```

12897 { Attempt-to-define-#1'-as-a-nested-choice-key. }
12898 {
12899   The-key-#1'-cannot-be-defined-as-a-choice-as-the-parent-key-#2'-is-
12900   itself-a-choice.
12901 }
12902 \__kernel_msg_new:nnnn { kernel } { value-forbidden }
12903 { The-key-#1'-does-not-take-a-value. }
12904 {
12905   The-key-#1'-should-be-given-without-a-value.\
12906   The-value-#2'-was-present:-the-key-will-be-ignored.
12907 }
12908 \__kernel_msg_new:nnnn { kernel } { value-required }
12909 { The-key-#1'-requires-a-value. }
12910 {
12911   The-key-#1'-must-have-a-value.\
12912   No-value-was-present:-the-key-will-be-ignored.
12913 }
12914 \__kernel_msg_new:nnn { kernel } { show-key }
12915 {
12916   The-key-#1~
12917   \tl_if_empty:nTF {#2}
12918   { is-undefined. }
12919   { has-the-properties: #2 . }
12920 }
12921 </initex | package>

```

21 l3intarray implementation

```

12922 <*initex | package>
12923 <@@=intarray>

```

21.1 Allocating arrays

`__intarray_entry:w` We use these primitives quite a lot in this module.
`__intarray_count:w`

```

12924 \cs_new_eq:NN \__intarray_entry:w \tex_fontdimen:D
12925 \cs_new_eq:NN \__intarray_count:w \tex_hyphenchar:D

```

(End definition for `__intarray_entry:w` and `__intarray_count:w`.)

`\l__intarray_loop_int` A loop index.

```

12926 \int_new:N \l__intarray_loop_int

```

(End definition for `\l__intarray_loop_int`.)

`\c__intarray_sp_dim` Used to convert integers to dimensions fast.

```

12927 \dim_const:Nn \c__intarray_sp_dim { 1 sp }

```

(End definition for `\c__intarray_sp_dim`.)

`\g__intarray_font_int` Used to assign one font per array.

```

12928 \int_new:N \g__intarray_font_int

```

(End definition for `\g__intarray_font_int`.)

```
12929 \__kernel_msg_new:nnn { kernel } { negative-array-size }
12930 { Size-of-array-may-not-be-negative:~#1 }
```

`\intarray_new:Nn` Declare `#1` to be a font (arbitrarily `cmr10` at a never-used size). Store the array's size as the `\hyphenchar` of that font and make sure enough `\fontdimen` are allocated, by setting the last one. Then clear any `\fontdimen` that `cmr10` starts with. It seems LuaTeX's `cmr10` has an extra `\fontdimen` parameter number 8 compared to other engines (for a math font we would replace 8 by 22 or some such). Every `intarray` must be global; it's enough to run this check in `\intarray_new:Nn`.

```
12931 \cs_new_protected:Npn \__intarray_new:N #1
12932 {
12933   \__kernel_chk_if_free_cs:N #1
12934   \int_gincr:N \g__intarray_font_int
12935   \tex_global:D \tex_font:D #1
12936   = cmr10~at~ \g__intarray_font_int \c__intarray_sp_dim \scan_stop:
12937   \int_step_inline:nn { 8 }
12938   { \__kernel_intarray_gset:Nnn #1 {##1} \c_zero_int }
12939 }
12940 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN g #1 } { }
12941 \cs_new_protected:Npn \intarray_new:Nn #1#2
12942 {
12943   \__intarray_new:N #1
12944   \__intarray_count:w #1 = \int_eval:n {#2} \scan_stop:
12945   \int_compare:nNnT { \intarray_count:N #1 } < 0
12946   {
12947     \__kernel_msg_error:nxx { kernel } { negative-array-size }
12948     { \intarray_count:N #1 }
12949   }
12950   \int_compare:nNnT { \intarray_count:N #1 } > 0
12951   { \__kernel_intarray_gset:Nnn #1 { \intarray_count:N #1 } { 0 } }
12952 }
```

(End definition for `\intarray_new:Nn` and `__intarray_new:N`. This function is documented on page 181.)

`\intarray_count:N` Size of an array.

```
12953 \cs_new:Npn \intarray_count:N #1 { \int_value:w \__intarray_count:w #1 }
```

(End definition for `\intarray_count:N`. This function is documented on page 181.)

21.2 Array items

`__intarray_signed_max_dim:n` Used when an item to be stored is larger than `\c_max_dim` in absolute value; it is replaced by $\pm\c_max_dim$.

```
12954 \cs_new:Npn \__intarray_signed_max_dim:n #1
12955 { \int_value:w \int_compare:nNnT {#1} < 0 { - } \c_max_dim }
```

(End definition for `__intarray_signed_max_dim:n`.)

`__intarray_bounds:NNnTF` The functions `\intarray_gset:Nnn` and `\intarray_item:Nn` share bounds checking.
`__intarray_bounds_error:NNn` The T branch is used if #3 is within bounds of the array #2.

```

12956 \cs_new:Npn \__intarray_bounds:NNnTF #1#2#3#4#5
12957 {
12958   \if_int_compare:w 1 > #3 \exp_stop_f:
12959     \__intarray_bounds_error:NNn #1 #2 {#3}
12960     #5
12961   \else:
12962     \if_int_compare:w #3 > \intarray_count:N #2 \exp_stop_f:
12963     \__intarray_bounds_error:NNn #1 #2 {#3}
12964     #5
12965   \else:
12966     #4
12967   \fi:
12968 \fi:
12969 }
12970 \cs_new:Npn \__intarray_bounds_error:NNn #1#2#3
12971 {
12972   #1 { kernel } { out-of-bounds }
12973   { \token_to_str:N #2 } {#3} { \intarray_count:N #2 }
12974 }

```

(End definition for `__intarray_bounds:NNnTF` and `__intarray_bounds_error:NNn`.)

`\intarray_gset:Nnn` Set the appropriate `\fontdimen`. The `__kernel_intarray_gset:Nnn` function does not
`__kernel_intarray_gset:Nnn` use `\int_eval:n`, namely its arguments must be suitable for `\int_value:w`. The user
`__intarray_gset:Nnn` version checks the position and value are within bounds.
`__intarray_gset_overflow:NNn`

```

12975 \cs_new_protected:Npn \__kernel_intarray_gset:Nnn #1#2#3
12976 { \__intarray_entry:w #2 #1 #3 \c__intarray_sp_dim }
12977 \cs_new_protected:Npn \intarray_gset:Nnn #1#2#3
12978 {
12979   \exp_after:wN \__intarray_gset:Nww
12980   \exp_after:wN #1
12981   \int_value:w \int_eval:n {#2} \exp_after:wN ;
12982   \int_value:w \int_eval:n {#3} ;
12983 }
12984 \cs_new_protected:Npn \__intarray_gset:Nww #1#2 ; #3 ;
12985 {
12986   \__intarray_bounds:NNnTF \__kernel_msg_error:nnxxx #1 {#2}
12987   {
12988     \__intarray_gset_overflow_test:nw {#3}
12989     \__kernel_intarray_gset:Nnn #1 {#2} {#3}
12990   }
12991   { }
12992 }
12993 \cs_if_exist:NTF \tex_ifabsnum:D
12994 {
12995   \cs_new_protected:Npn \__intarray_gset_overflow_test:nw #1
12996   {
12997     \tex_ifabsnum:D #1 > \c_max_dim
12998     \exp_after:wN \__intarray_gset_overflow:NNnn
12999   \fi:
13000 }
13001 }

```

```

13002 {
13003   \cs_new_protected:Npn \__intarray_gset_overflow_test:nw #1
13004   {
13005     \if_int_compare:w \int_abs:n {#1} > \c_max_dim
13006     \exp_after:wN \__intarray_gset_overflow:NNnn
13007     \fi:
13008   }
13009 }
13010 \cs_new_protected:Npn \__intarray_gset_overflow:NNnn #1#2#3#4
13011 {
13012   \__kernel_msg_error:nnxxxx { kernel } { overflow }
13013   { \token_to_str:N #2 } {#3} {#4} { \__intarray_signed_max_dim:n {#4} }
13014   #1 #2 {#3} { \__intarray_signed_max_dim:n {#4} }
13015 }

```

(End definition for `\intarray_gset:Nnn` and others. This function is documented on page 181.)

`\intarray_gzero:N` Set the appropriate `\fontdimen` to zero. No bound checking needed. The `\prg_replicate:nn` possibly uses quite a lot of memory, but this is somewhat comparable to the size of the array, and it is much faster than an `\int_step_inline:nn` loop.

```

13016 \cs_new_protected:Npn \intarray_gzero:N #1
13017 {
13018   \int_zero:N \l__intarray_loop_int
13019   \prg_replicate:nn { \intarray_count:N #1 }
13020   {
13021     \int_incr:N \l__intarray_loop_int
13022     \__intarray_entry:w \l__intarray_loop_int #1 \c_zero_dim
13023   }
13024 }

```

(End definition for `\intarray_gzero:N`. This function is documented on page 181.)

`\intarray_item:Nn` Get the appropriate `\fontdimen` and perform bound checks. The `__kernel_intarray_item:Nn` function omits bound checks and omits `\int_eval:n`, namely its argument must be a TeX integer suitable for `\int_value:w`.

```

13025 \cs_new:Npn \__kernel_intarray_item:Nn #1#2
13026 { \int_value:w \__intarray_entry:w #2 #1 }
13027 \cs_new:Npn \intarray_item:Nn #1#2
13028 {
13029   \exp_after:wN \__intarray_item:Nw
13030   \exp_after:wN #1
13031   \int_value:w \int_eval:n {#2} ;
13032 }
13033 \cs_new:Npn \__intarray_item:Nw #1#2 ;
13034 {
13035   \__intarray_bounds:NNnTF \__kernel_msg_expandable_error:nnfff #1 {#2}
13036   { \__kernel_intarray_item:Nn #1 {#2} }
13037   { 0 }
13038 }

```

(End definition for `\intarray_item:Nn`, `__kernel_intarray_item:Nn`, and `__intarray_item:Nn`. This function is documented on page 181.)

`\intarray_rand_item:N` Importantly, `\intarray_item:Nn` only evaluates its argument once.

```
13039 \cs_new:Npn \intarray_rand_item:N #1
13040 { \intarray_item:Nn #1 { \int_rand:n { \intarray_count:N #1 } } }
```

(End definition for `\intarray_rand_item:N`. This function is documented on page 181.)

21.3 Working with contents of integer arrays

At the time of writing these are candidates, but we need at least `\intarray_const_from_clist:Nn` in `l3fp` so before `l3candidates`.

`\intarray_const_from_clist:Nn` Similar to `\intarray_new:Nn` (which we don't use because when debugging is enabled that function checks the variable name starts with `g_`). We make use of the fact that `TEX` allows allocation of successive `\fontdimen` as long as no other font has been declared: no need to count the comma list items first. We need the code in `\intarray_gset:Nnn` that checks the item value is not too big, namely `__intarray_gset_overflow_test:nw`, but not the code that checks bounds. At the end, set the size of the intarray.

```
13041 \__kernel_patch:nnNNpn { \__kernel_chk_var_scope:NN c #1 } { }
13042 \cs_new_protected:Npn \intarray_const_from_clist:Nn #1#2
13043 {
13044   \__intarray_new:N #1
13045   \int_zero:N \l__intarray_loop_int
13046   \clist_map_inline:nn {#2}
13047     { \exp_args:Nf \__intarray_const_from_clist:nN { \int_eval:n {##1} } } #1 }
13048   \__intarray_count:w #1 \l__intarray_loop_int
13049 }
13050 \cs_new_protected:Npn \__intarray_const_from_clist:nN #1#2
13051 {
13052   \int_incr:N \l__intarray_loop_int
13053   \__intarray_gset_overflow_test:nw {#1}
13054   \__kernel_intarray_gset:Nnn #2 \l__intarray_loop_int {#1}
13055 }
```

(End definition for `\intarray_const_from_clist:Nn` and `__intarray_const_from_clist:nN`. This function is documented on page 245.)

`\intarray_to_clist:N` Loop through the array, putting a comma before each item. Remove the leading comma with `f`-expansion. We also use the auxiliary in `\intarray_show:N` with argument comma, `__intarray_to_clist:Nn` space.

```
13056 \cs_new:Npn \intarray_to_clist:N #1 { \__intarray_to_clist:Nn #1 { , } }
13057 \cs_new:Npn \__intarray_to_clist:Nn #1#2
13058 {
13059   \int_compare:nNnF { \intarray_count:N #1 } = \c_zero_int
13060   {
13061     \exp_last_unbraced:Nf \use_none:n
13062       { \__intarray_to_clist:w 1 ; #1 {#2} \prg_break_point: }
13063   }
13064 }
13065 \cs_new:Npn \__intarray_to_clist:w #1 ; #2#3
13066 {
13067   \if_int_compare:w #1 > \__intarray_count:w #2
13068     \prg_break:n
13069   \fi:
```

```

13070      #3 \__kernel_intarray_item:Nn #2 {#1}
13071      \exp_after:wN \__intarray_to_clist:w
13072      \int_value:w \int_eval:w #1 + \c_one_int ; #2 {#3}
13073    }

```

(End definition for `\intarray_to_clist:N`, `__intarray_to_clist:Nn`, and `__intarray_to_clist:w`. This function is documented on page 245.)

`\intarray_show:N` Convert the list to a comma list (with spaces after each comma)

```

\intarray_log:N
13074 \cs_new_protected:Npn \intarray_show:N { \__intarray_show:NN \msg_show:nnxxxx }
13075 \cs_generate_variant:Nn \intarray_show:N { c }
13076 \cs_new_protected:Npn \intarray_log:N { \__intarray_show:NN \msg_log:nnxxxx }
13077 \cs_generate_variant:Nn \intarray_log:N { c }
13078 \cs_new_protected:Npn \__intarray_show:NN #1#2
13079 {
13080   \__kernel_chk_defined:NT #2
13081   {
13082     #1 { LaTeX/kernel } { show-intarray }
13083     { \token_to_str:N #2 }
13084     { \intarray_count:N #2 }
13085     { >~ \__intarray_to_clist:Nn #2 { , ~ } }
13086     { }
13087   }
13088 }

```

(End definition for `\intarray_show:N` and `\intarray_log:N`. These functions are documented on page 245.)

21.4 Random arrays

`\intarray_gset_rand:Nn`
`\intarray_gset_rand:Nnn`

We only perform the bounds checks once. This is done by two `__intarray_gset_overflow_test:nw`, with an appropriate empty argument to avoid a spurious “at position #1” part in the error message. Then calculate the number of choices: this is at most $(2^{30} - 1) - (-(2^{30} - 1)) + 1 = 2^{31} - 1$, which just barely does not overflow. For small ranges use `__kernel_randint:n` (making sure to subtract 1 *before* adding the random number to the $\langle min \rangle$, to avoid overflow when $\langle min \rangle$ or $\langle max \rangle$ are $\pm \c_max_int$), otherwise `__kernel_randint:nn`. Finally, if there are no random numbers do not define any of the auxiliaries.

`__intarray_gset_rand:Nnn`
`__intarray_gset_rand:Nff`
`__intarray_gset_rand_auxi:Nnn`
`__intarray_gset_rand_auxii:Nnn`
`__intarray_gset_rand_auxiii:Nnn`
`__intarray_gset_all_same:Nn`

```

13089 \cs_new_protected:Npn \intarray_gset_rand:Nn #1
13090 { \intarray_gset_rand:Nnn #1 { 1 } }
13091 \sys_if_rand_exist:TF
13092 {
13093   \cs_new_protected:Npn \intarray_gset_rand:Nnn #1#2#3
13094   {
13095     \__intarray_gset_rand:Nff #1
13096     { \int_eval:n {#2} } { \int_eval:n {#3} }
13097   }
13098   \cs_new_protected:Npn \__intarray_gset_rand:Nnn #1#2#3
13099   {
13100     \int_compare:nNnTF {#2} > {#3}
13101     {
13102       \__kernel_msg_expandable_error:nnnn
13103       { kernel } { randint-backward-range } {#2} {#3}
13104       \__intarray_gset_rand:Nnn #1 {#3} {#2}

```

```

13105     }
13106     {
13107         \__intarray_gset_overflow_test:nw {#2}
13108         \__intarray_gset_rand_auxi:Nnnn #1 { } {#2} {#3}
13109     }
13110 }
13111 \cs_generate_variant:Nn \__intarray_gset_rand:Nnn { Nff }
13112 \cs_new_protected:Npn \__intarray_gset_rand_auxi:Nnnn #1#2#3#4
13113 {
13114     \__intarray_gset_overflow_test:nw {#4}
13115     \__intarray_gset_rand_auxii:Nnnn #1 { } {#4} {#3}
13116 }
13117 \cs_new_protected:Npn \__intarray_gset_rand_auxii:Nnnn #1#2#3#4
13118 {
13119     \exp_args:NNf \__intarray_gset_rand_auxiii:Nnnn #1
13120     { \int_eval:n { #3 - #4 + 1 } } {#4} {#3}
13121 }
13122 \cs_new_protected:Npn \__intarray_gset_rand_auxiii:Nnnn #1#2#3#4
13123 {
13124     \exp_args:NNf \__intarray_gset_all_same:Nn #1
13125     {
13126         \int_compare:nNnTF {#2} > \c__kernel_randint_max_int
13127         {
13128             \exp_stop_f:
13129             \int_eval:n { \__kernel_randint:nn {#3} {#4} }
13130         }
13131         {
13132             \exp_stop_f:
13133             \int_eval:n { \__kernel_randint:n {#2} - 1 + #3 }
13134         }
13135     }
13136 }
13137 \cs_new_protected:Npn \__intarray_gset_all_same:Nn #1#2
13138 {
13139     \int_zero:N \l__intarray_loop_int
13140     \prg_replicate:nn { \intarray_count:N #1 }
13141     {
13142         \int_incr:N \l__intarray_loop_int
13143         \__kernel_intarray_gset:Nnn #1 \l__intarray_loop_int {#2}
13144     }
13145 }
13146 }
13147 {
13148     \cs_new_protected:Npn \intarray_gset_rand:Nnn #1#2#3
13149     {
13150         \__kernel_msg_error:nnn { kernel } { fp-no-random }
13151         { \intarray_gset_rand:Nnn #1 {#2} {#3} }
13152     }
13153 }

```

(End definition for `\intarray_gset_rand:Nn` and others. These functions are documented on page 245.)

13154 `\</initex | package>`

22 l3fp implementation

Nothing to see here: everything is in the subfiles!

23 l3fp-aux implementation

```
13155 <*initex | package>
```

```
13156 <@@=fp>
```

23.1 Access to primitives

```
__fp_int_eval:w Largely for performance reasons, we need to directly access primitives rather than use  
__fp_int_eval_end: \int_eval:n. This happens a lot, so we use private names. The same is true for  
__fp_int_to_roman:w \romannumeral, although it is used much less widely.
```

```
13157 \cs_new_eq:NN __fp_int_eval:w \tex_numexpr:D
```

```
13158 \cs_new_eq:NN __fp_int_eval_end: \scan_stop:
```

```
13159 \cs_new_eq:NN __fp_int_to_roman:w \tex_romannumeral:D
```

(End definition for `__fp_int_eval:w`, `__fp_int_eval_end:`, and `__fp_int_to_roman:w`.)

23.2 Internal representation

Internally, a floating point number $\langle X \rangle$ is a token list containing

```
\s_fp __fp_chk:w <case> <sign> <body> ;
```

Let us explain each piece separately.

Internal floating point numbers are used in expressions, and in this context are subject to `f`-expansion. They must leave a recognizable mark after `f`-expansion, to prevent the floating point number from being re-parsed. Thus, `\s_fp` is simply another name for `\relax`.

When used directly without an accessor function, floating points should produce an error: this is the role of `__fp_chk:w`. We could make floating point variables be protected to prevent them from expanding under `x`-expansion, but it seems more convenient to treat them as a subcase of token list variables.

The (decimal part of the) IEEE-754-2008 standard requires the format to be able to represent special floating point numbers besides the usual positive and negative cases. We distinguish the various possibilities by their $\langle case \rangle$, which is a single digit:

0 zeros: `+0` and `-0`,

1 “normal” numbers (positive and negative),

2 infinities: `+inf` and `-inf`,

3 quiet and signalling `nan`.

The $\langle sign \rangle$ is 0 (positive) or 2 (negative), except in the case of `nan`, which have $\langle sign \rangle = 1$. This ensures that changing the $\langle sign \rangle$ digit to $2 - \langle sign \rangle$ is exactly equivalent to changing the sign of the number.

Special floating point numbers have the form

```
\s_fp __fp_chk:w <case> <sign> \s_fp... ;
```

Table 1: Internal representation of floating point numbers.

Representation	Meaning
0 0 \s__fp... ;	Positive zero.
0 2 \s__fp... ;	Negative zero.
1 0 {⟨exponent⟩} {⟨X ₁ ⟩} {⟨X ₂ ⟩} {⟨X ₃ ⟩} {⟨X ₄ ⟩} ;	Positive floating point.
1 2 {⟨exponent⟩} {⟨X ₁ ⟩} {⟨X ₂ ⟩} {⟨X ₃ ⟩} {⟨X ₄ ⟩} ;	Negative floating point.
2 0 \s__fp... ;	Positive infinity.
2 2 \s__fp... ;	Negative infinity.
3 1 \s__fp... ;	Quiet nan.
3 1 \s__fp... ;	Signalling nan.

where \s__fp... is a scan mark carrying information about how the number was formed (useful for debugging).

Normal floating point numbers ($\langle case \rangle = 1$) have the form

`\s__fp __fp_chk:w 1 ⟨sign⟩ {⟨exponent⟩} {⟨X1⟩} {⟨X2⟩} {⟨X3⟩} {⟨X4⟩} ;`

Here, the $\langle exponent \rangle$ is an integer, between -10000 and 10000 . The body consists in four blocks of exactly 4 digits, $0000 \leq \langle X_i \rangle \leq 9999$, and the floating point is

$$(-1)^{\langle sign \rangle / 2} \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle \cdot 10^{\langle exponent \rangle - 16}$$

where we have concatenated the 16 digits. Currently, floating point numbers are normalized such that the $\langle exponent \rangle$ is minimal, in other words, $1000 \leq \langle X_1 \rangle \leq 9999$.

Calculations are done in base 10000, *i.e.* one myriad.

23.3 Using arguments and semicolons

`__fp_use_none_stop_f:n` This function removes an argument (typically a digit) and replaces it by `\exp_stop_f:`, a marker which stops f-type expansion.

13160 `\cs_new:Npn __fp_use_none_stop_f:n #1 { \exp_stop_f: }`

(End definition for `__fp_use_none_stop_f:n`.)

`__fp_use_s:n` Those functions place a semicolon after one or two arguments (typically digits).

13161 `\cs_new:Npn __fp_use_s:n #1 { #1; }`

13162 `\cs_new:Npn __fp_use_s:nn #1#2 { #1#2; }`

(End definition for `__fp_use_s:n` and `__fp_use_s:nn`.)

`__fp_use_none_until_s:w` Those functions select specific arguments among a set of arguments delimited by a semicolon.

`__fp_use_i_until_s:nw`

`__fp_use_ii_until_s:nnw`

13163 `\cs_new:Npn __fp_use_none_until_s:w #1; { }`

13164 `\cs_new:Npn __fp_use_i_until_s:nw #1#2; { #1 }`

13165 `\cs_new:Npn __fp_use_ii_until_s:nnw #1#2#3; { #2 }`

(End definition for `__fp_use_none_until_s:w`, `__fp_use_i_until_s:nw`, and `__fp_use_ii_until_s:nnw`.)

`__fp_reverse_args:Nww` Many internal functions take arguments delimited by semicolons, and it is occasionally useful to swap two such arguments.

13166 `\cs_new:Npn __fp_reverse_args:Nww #1 #2; #3; { #1 #3; #2; }`

(End definition for `_fp_reverse_args:Nww`.)

`_fp_rrot:www` Rotate three arguments delimited by semicolons. This is the inverse (or the square) of the Forth primitive ROT, hence the name.

```
13167 \cs_new:Npn \_fp_rrot:www #1; #2; #3; { #2; #3; #1; }
```

(End definition for `_fp_rrot:www`.)

`_fp_use_i:ww` Many internal functions take arguments delimited by semicolons, and it is occasionally useful to remove one or two such arguments.

```
13168 \cs_new:Npn \_fp_use_i:ww #1; #2; { #1; }
```

```
13169 \cs_new:Npn \_fp_use_i:www #1; #2; #3; { #1; }
```

(End definition for `_fp_use_i:ww` and `_fp_use_i:www`.)

23.4 Constants, and structure of floating points

`_fp_misused:n` This receives a floating point object (floating point number or tuple) and generates an error stating that it was misused. This is called when for instance an `fp` variable is left in the input stream and its contents reach T_EX's stomach.

```
13170 \cs_new_protected:Npn \_fp_misused:n #1
```

```
13171 { \_kernel_msg_error:nnx { kernel } { misused-fp } { \fp_to_tl:n {#1} } }
```

(End definition for `_fp_misused:n`.)

`\s__fp` Floating points numbers all start with `\s__fp _fp_chk:w`, where `\s__fp` is equal to the T_EX primitive `\relax`, and `_fp_chk:w` is protected. The rest of the floating point number is made of characters (or `\relax`). This ensures that nothing expands under f-expansion, nor under x-expansion. However, when typeset, `\s__fp` does nothing, and `_fp_chk:w` is expanded. We define `_fp_chk:w` to produce an error.

```
13172 \scan_new:N \s__fp
```

```
13173 \cs_new_protected:Npn \_fp_chk:w #1 ;
```

```
13174 { \_fp_misused:n { \s__fp \_fp_chk:w #1 ; } }
```

(End definition for `\s__fp` and `_fp_chk:w`.)

`\s__fp_mark` Aliases of `\tex_relax:D`, used to terminate expressions.

```
13175 \scan_new:N \s__fp_mark
```

```
13176 \scan_new:N \s__fp_stop
```

(End definition for `\s__fp_mark` and `\s__fp_stop`.)

`\s__fp_invalid` A couple of scan marks used to indicate where special floating point numbers come from.

```
\s__fp_underflow 13177 \scan_new:N \s__fp_invalid
```

```
\s__fp_overflow 13178 \scan_new:N \s__fp_underflow
```

```
\s__fp_division 13179 \scan_new:N \s__fp_overflow
```

```
\s__fp_exact 13180 \scan_new:N \s__fp_division
```

```
13181 \scan_new:N \s__fp_exact
```

(End definition for `\s__fp_invalid` and others.)

`\c_zero_fp` The special floating points. We define the floating points here as “exact”.
`\c_minus_zero_fp` 13182 `\tl_const:Nn \c_zero_fp { \s__fp __fp_chk:w 0 0 \s__fp_exact ; }`
`\c_inf_fp` 13183 `\tl_const:Nn \c_minus_zero_fp { \s__fp __fp_chk:w 0 2 \s__fp_exact ; }`
`\c_minus_inf_fp` 13184 `\tl_const:Nn \c_inf_fp { \s__fp __fp_chk:w 2 0 \s__fp_exact ; }`
`\c_nan_fp` 13185 `\tl_const:Nn \c_minus_inf_fp { \s__fp __fp_chk:w 2 2 \s__fp_exact ; }`
13186 `\tl_const:Nn \c_nan_fp { \s__fp __fp_chk:w 3 1 \s__fp_exact ; }`

(End definition for `\c_zero_fp` and others. These variables are documented on page 190.)

`\c__fp_prec_int` The number of digits of floating points.
`\c__fp_half_prec_int` 13187 `\int_const:Nn \c__fp_prec_int { 16 }`
`\c__fp_block_int` 13188 `\int_const:Nn \c__fp_half_prec_int { 8 }`
13189 `\int_const:Nn \c__fp_block_int { 4 }`

(End definition for `\c__fp_prec_int`, `\c__fp_half_prec_int`, and `\c__fp_block_int`.)

`\c__fp_myriad_int` Blocks have 4 digits so this integer is useful.
13190 `\int_const:Nn \c__fp_myriad_int { 10000 }`

(End definition for `\c__fp_myriad_int`.)

`\c__fp_minus_min_exponent_int` Normal floating point numbers have an exponent between `–minus_min_exponent` and
`\c__fp_max_exponent_int` `max_exponent` inclusive. Larger numbers are rounded to $\pm\infty$. Smaller numbers are
rounded to ± 0 . It would be more natural to define a `min_exponent` with the opposite
sign but that would waste one T_EX count.

13191 `\int_const:Nn \c__fp_minus_min_exponent_int { 10000 }`
13192 `\int_const:Nn \c__fp_max_exponent_int { 10000 }`

(End definition for `\c__fp_minus_min_exponent_int` and `\c__fp_max_exponent_int`.)

`\c__fp_max_exp_exponent_int` If a number’s exponent is larger than that, its exponential overflows/underflows.
13193 `\int_const:Nn \c__fp_max_exp_exponent_int { 5 }`

(End definition for `\c__fp_max_exp_exponent_int`.)

`\c__fp_overflowing_fp` A floating point number that is bigger than all normal floating point numbers. This
replaces infinities when converting to formats that do not support infinities.

13194 `\tl_const:Nx \c__fp_overflowing_fp`
13195 `{`
13196 `\s__fp __fp_chk:w 1 0`
13197 `{ \int_eval:n { \c__fp_max_exponent_int + 1 } }`
13198 `{1000} {0000} {0000} {0000} ;`
13199 `}`

(End definition for `\c__fp_overflowing_fp`.)

`__fp_zero_fp:N` In case of overflow or underflow, we have to output a zero or infinity with a given sign.
`__fp_inf_fp:N`

13200 `\cs_new:Npn __fp_zero_fp:N #1`
13201 `{ \s__fp __fp_chk:w 0 #1 \s__fp_underflow ; }`
13202 `\cs_new:Npn __fp_inf_fp:N #1`
13203 `{ \s__fp __fp_chk:w 2 #1 \s__fp_overflow ; }`

(End definition for `__fp_zero_fp:N` and `__fp_inf_fp:N`.)

`__fp_exponent:w` For normal numbers, the function expands to the exponent, otherwise to 0. This is used in `l3str-format`.

```

13204 \cs_new:Npn \__fp_exponent:w \s__fp \__fp_chk:w #1
13205 {
13206   \if_meaning:w 1 #1
13207     \exp_after:wN \__fp_use_ii_until_s:nnw
13208   \else:
13209     \exp_after:wN \__fp_use_i_until_s:nw
13210     \exp_after:wN 0
13211   \fi:
13212 }
```

(End definition for `__fp_exponent:w`.)

`__fp_neg_sign:N` When appearing in an integer expression or after `\int_value:w`, this expands to the sign opposite to #1, namely 0 (positive) is turned to 2 (negative), 1 (nan) to 1, and 2 to 0.

```

13213 \cs_new:Npn \__fp_neg_sign:N #1
13214 { \__fp_int_eval:w 2 - #1 \__fp_int_eval_end: }
```

(End definition for `__fp_neg_sign:N`.)

23.5 Overflow, underflow, and exact zero

`__fp_sanitize:Nw` `__fp_sanitize:wN` `__fp_sanitize_zero:w` Expects the sign and the exponent in some order, then the significand (which we don't touch). Outputs the corresponding floating point number, possibly underflowed to ± 0 or overflowed to $\pm\infty$. The functions `__fp_underflow:w` and `__fp_overflow:w` are defined in `l3fp-traps`.

```

13215 \cs_new:Npn \__fp_sanitize:Nw #1 #2;
13216 {
13217   \if_case:w
13218     \if_int_compare:w #2 > \c__fp_max_exponent_int 1 ~ \else:
13219     \if_int_compare:w #2 < - \c__fp_minus_min_exponent_int 2 ~ \else:
13220     \if_meaning:w 1 #1 3 ~ \fi: \fi: \fi: 0 ~
13221   \or: \exp_after:wN \__fp_overflow:w
13222   \or: \exp_after:wN \__fp_underflow:w
13223   \or: \exp_after:wN \__fp_sanitize_zero:w
13224   \fi:
13225   \s__fp \__fp_chk:w 1 #1 {#2}
13226 }
13227 \cs_new:Npn \__fp_sanitize:wN #1; #2 { \__fp_sanitize:Nw #2 #1; }
13228 \cs_new:Npn \__fp_sanitize_zero:w \s__fp \__fp_chk:w #1 #2 #3;
13229 { \c_zero_fp }
```

(End definition for `__fp_sanitize:Nw`, `__fp_sanitize:wN`, and `__fp_sanitize_zero:w`.)

23.6 Expanding after a floating point number

`__fp_exp_after_o:w`
`__fp_exp_after_f:nw`

`__fp_exp_after_o:w` *<floating point>*
`__fp_exp_after_f:nw` *{<tokens>}* *<floating point>*

Places *<tokens>* (empty in the case of `__fp_exp_after_o:w`) between the *<floating point>* and the following tokens, then hits those tokens with `o` or `f`-expansion, and leaves the floating point number unchanged.

We first distinguish normal floating points, which have a significand, from the much simpler special floating points.

```

13230 \cs_new:Npn \__fp_exp_after_o:w \s__fp \__fp_chk:w #1
13231 {
13232   \if_meaning:w 1 #1
13233     \exp_after:wN \__fp_exp_after_normal:nNNw
13234   \else:
13235     \exp_after:wN \__fp_exp_after_special:nNNw
13236   \fi:
13237   { }
13238   #1
13239 }
13240 \cs_new:Npn \__fp_exp_after_f:nw #1 \s__fp \__fp_chk:w #2
13241 {
13242   \if_meaning:w 1 #2
13243     \exp_after:wN \__fp_exp_after_normal:nNNw
13244   \else:
13245     \exp_after:wN \__fp_exp_after_special:nNNw
13246   \fi:
13247   { \exp:w \exp_end_continue_f:w #1 }
13248   #2
13249 }

```

(End definition for __fp_exp_after_o:w and __fp_exp_after_f:nw.)

__fp_exp_after_special:nNNw

__fp_exp_after_special:nNNw {<after>} <case> <sign> <scan mark> ;
Special floating point numbers are easy to jump over since they contain few tokens.

```

13250 \cs_new:Npn \__fp_exp_after_special:nNNw #1#2#3#4;
13251 {
13252   \exp_after:wN \s__fp
13253   \exp_after:wN \__fp_chk:w
13254   \exp_after:wN #2
13255   \exp_after:wN #3
13256   \exp_after:wN #4
13257   \exp_after:wN ;
13258   #1
13259 }

```

(End definition for __fp_exp_after_special:nNNw.)

__fp_exp_after_normal:nNNw

For normal floating point numbers, life is slightly harder, since we have many tokens to jump over. Here it would be slightly better if the digits were not braced but instead were delimited arguments (for instance delimited by ,). That may be changed some day.

```

13260 \cs_new:Npn \__fp_exp_after_normal:nNNw #1 1 #2 #3 #4#5#6#7;
13261 {
13262   \exp_after:wN \__fp_exp_after_normal:Nwwwww
13263   \exp_after:wN #2
13264   \int_value:w #3 \exp_after:wN ;
13265   \int_value:w 1 #4 \exp_after:wN ;
13266   \int_value:w 1 #5 \exp_after:wN ;
13267   \int_value:w 1 #6 \exp_after:wN ;
13268   \int_value:w 1 #7 \exp_after:wN ; #1
13269 }
13270 \cs_new:Npn \__fp_exp_after_normal:Nwwwww

```

```

13271      #1 #2; 1 #3 ; 1 #4 ; 1 #5 ; 1 #6 ;
13272      { \s__fp \__fp_chk:w 1 #1 {#2} {#3} {#4} {#5} {#6} ; }

```

(End definition for __fp_exp_after_normal:nNNw.)

23.7 Other floating point types

\s__fp_tuple Floating point tuples take the form \s__fp_tuple __fp_tuple_chk:w { *<fp 1>* *<fp 2>* ... } ; where each *<fp>* is a floating point number or tuple, hence ends with ; itself. When a tuple is typeset, __fp_tuple_chk:w produces an error, just like usual floating point numbers. Tuples may have zero or one element.

```

13273 \scan_new:N \s__fp_tuple
13274 \cs_new_protected:Npn \__fp_tuple_chk:w #1 ;
13275   { \__fp_misused:n { \s__fp_tuple \__fp_tuple_chk:w #1 ; } }
13276 \tl_const:Nn \c__fp_empty_tuple_fp
13277   { \s__fp_tuple \__fp_tuple_chk:w { } ; }

```

(End definition for \s__fp_tuple, __fp_tuple_chk:w, and \c__fp_empty_tuple_fp.)

__fp_tuple_count:w Count the number of items in a tuple of floating points by counting semicolons. The technique is very similar to \tl_count:n, but with the loop built-in. Checking for the end of the loop is done with the \use_none:n #1 construction.

```

13278 \cs_new:Npn \__fp_array_count:n #1
13279   { \__fp_tuple_count:w \s__fp_tuple \__fp_tuple_chk:w {#1} ; }
13280 \cs_new:Npn \__fp_tuple_count:w \s__fp_tuple \__fp_tuple_chk:w #1 ;
13281   {
13282     \int_value:w \__fp_int_eval:w 0
13283     \__fp_tuple_count_loop:Nw #1 { ? \prg_break: } ;
13284     \prg_break_point:
13285     \__fp_int_eval_end:
13286   }
13287 \cs_new:Npn \__fp_tuple_count_loop:Nw #1#2;
13288   { \use_none:n #1 + 1 \__fp_tuple_count_loop:Nw }

```

(End definition for __fp_tuple_count:w, __fp_array_count:n, and __fp_tuple_count_loop:Nw.)

__fp_if_type_fp:NTwFw Used as __fp_if_type_fp:NTwFw *<marker>* {*<true code>*} \s__fp {*<false code>*} \q_stop, this test whether the *<marker>* is \s__fp or not and runs the appropriate *<code>*. The very unusual syntax is for optimization purposes as that function is used for all floating point operations.

```

13289 \cs_new:Npn \__fp_if_type_fp:NTwFw #1 \s__fp #2 #3 \q_stop {#2}

```

(End definition for __fp_if_type_fp:NTwFw.)

__fp_array_if_all_fp:nTF True if all items are floating point numbers. Used for min.

```

13290 \cs_new:Npn \__fp_array_if_all_fp:nTF #1
13291   {
13292     \__fp_array_if_all_fp_loop:w #1 { \s__fp \prg_break: } ;
13293     \prg_break_point: \use_i:nn
13294   }
13295 \cs_new:Npn \__fp_array_if_all_fp_loop:w #1#2 ;
13296   {
13297     \__fp_if_type_fp:NTwFw
13298     #1 \__fp_array_if_all_fp_loop:w

```

```

13299     \s__fp { \prg_break:n \use_iii:nnn }
13300     \q_stop
13301 }

```

(End definition for _fp_array_if_all_fp:nTF and _fp_array_if_all_fp_loop:w.)

_fp_type_from_scan:N Used as _fp_type_from_scan:N *<token>*. Grabs the pieces of the stringified *<token>* which lies after the first s__fp. If the *<token>* does not contain that string, the result is _?.

```

13302 \cs_new:Npn \_fp_type_from_scan:N #1
13303 {
13304     \_fp_if_type_fp:NTwFw
13305     #1 { }
13306     \s__fp { \_fp_type_from_scan_other:N #1 }
13307     \q_stop
13308 }
13309 \cs_new:Npx \_fp_type_from_scan_other:N #1
13310 {
13311     \exp_not:N \exp_after:wN \exp_not:N \_fp_type_from_scan:w
13312     \exp_not:N \token_to_str:N #1 \exp_not:N \q_mark
13313     \tl_to_str:n { s__fp _? } \exp_not:N \q_mark \exp_not:N \q_stop
13314 }
13315 \exp_last_unbraced:NNNNo
13316 \cs_new:Npn \_fp_type_from_scan:w #1
13317 { \tl_to_str:n { s__fp } } #2 \q_mark #3 \q_stop {#2}

```

(End definition for _fp_type_from_scan:N, _fp_type_from_scan_other:N, and _fp_type_from_scan:w.)

_fp_change_func_type:NNN Arguments are *<type marker>* *<function>* *<recovery>*. This gives the function obtained by placing the type after @@. If the function is not defined then *<recovery>* *<function>* is used instead; however that test is not run when the *<type marker>* is s__fp.

```

13318 \cs_new:Npn \_fp_change_func_type:NNN #1#2#3
13319 {
13320     \_fp_if_type_fp:NTwFw
13321     #1 #2
13322     \s__fp
13323     {
13324         \exp_after:wN \_fp_change_func_type_chk:NNN
13325         \cs:w
13326         __fp \_fp_type_from_scan_other:N #1
13327         \exp_after:wN \_fp_change_func_type_aux:w \token_to_str:N #2
13328         \cs_end:
13329         #2 #3
13330     }
13331     \q_stop
13332 }
13333 \exp_last_unbraced:NNNNo
13334 \cs_new:Npn \_fp_change_func_type_aux:w #1 { \tl_to_str:n { __fp } } { }
13335 \cs_new:Npn \_fp_change_func_type_chk:NNN #1#2#3
13336 {
13337     \if_meaning:w \scan_stop: #1
13338     \exp_after:wN #3 \exp_after:wN #2
13339     \else:

```



```

13340     \exp_after:wN #1
13341     \fi:
13342   }

```

(End definition for `__fp_change_func_type:NNN`, `__fp_change_func_type_aux:w`, and `__fp_change_func_type_chk:NNN`.)

```

\__fp_exp_after_any_f:Nnw
\__fp_exp_after_any_f:nw
\__fp_exp_after_stop_f:nw

```

The `Nnw` function simply dispatches to the appropriate `__fp_exp_after..._f:nw` with “...” (either empty or $\langle type \rangle$) extracted from `#1`, which should start with `\s__fp`. If it doesn’t start with `\s__fp` the function `__fp_exp_after_?_f:nw` defined in `l3fp-parse` gives an error; another special $\langle type \rangle$ is `stop`, useful for loops, see below. The `nw` function has an important optimization for floating points numbers; it also fetches its type marker `#2` from the floating point.

```

13343 \cs_new:Npn \__fp_exp_after_any_f:Nnw #1
13344   { \cs:w __fp_exp_after \__fp_type_from_scan_other:N #1 _f:nw \cs_end: }
13345 \cs_new:Npn \__fp_exp_after_any_f:nw #1#2
13346   {
13347     \__fp_if_type_fp:NTwFw
13348     #2 \__fp_exp_after_f:nw
13349     \s__fp { \__fp_exp_after_any_f:Nnw #2 }
13350     \q_stop
13351     {#1} #2
13352   }
13353 \cs_new_eq:NN \__fp_exp_after_stop_f:nw \use_none:nn

```

(End definition for `__fp_exp_after_any_f:Nnw`, `__fp_exp_after_any_f:nw`, and `__fp_exp_after_stop_f:nw`.)

```

\__fp_exp_after_tuple_o:w
\__fp_exp_after_tuple_f:nw
\__fp_exp_after_array_f:w

```

The loop works by using the `n` argument of `__fp_exp_after_any_f:nw` to place the loop macro after the next item in the tuple and expand it.

```

\__fp_exp_after_array_f:w
 $\langle fp_1 \rangle$  ;
...
 $\langle fp_n \rangle$  ;
\s__fp_stop

```

```

13354 \cs_new:Npn \__fp_exp_after_tuple_o:w
13355   { \__fp_exp_after_tuple_f:nw { \exp_after:wN \exp_stop_f: } }
13356 \cs_new:Npn \__fp_exp_after_tuple_f:nw
13357   #1 \s__fp_tuple \__fp_tuple_chk:w #2 ;
13358   {
13359     \exp_after:wN \s__fp_tuple
13360     \exp_after:wN \__fp_tuple_chk:w
13361     \exp_after:wN {
13362       \exp:w \exp_end_continue_f:w
13363       \__fp_exp_after_array_f:w #2 \s__fp_stop
13364       \exp_after:wN }
13365       \exp_after:wN ;
13366       \exp:w \exp_end_continue_f:w #1
13367     }
13368 \cs_new:Npn \__fp_exp_after_array_f:w
13369   { \__fp_exp_after_any_f:nw { \__fp_exp_after_array_f:w } }

```

(End definition for `__fp_exp_after_tuple_o:w`, `__fp_exp_after_tuple_f:nw`, and `__fp_exp_after_array_f:w`.)

23.8 Packing digits

When a positive integer `#1` is known to be less than 10^8 , the following trick splits it into two blocks of 4 digits, padding with zeros on the left.

```
\cs_new:Npn \pack:NNNNNw #1 #2#3#4#5 #6; { {#2#3#4#5} {#6} }
\exp_after:wN \pack:NNNNNw
  \__fp_int_value:w \__fp_int_eval:w 1 0000 0000 + #1 ;
```

The idea is that adding 10^8 to the number ensures that it has exactly 9 digits, and can then easily find which digits correspond to what position in the number. Of course, this can be modified for any number of digits less or equal to 9 (we are limited by `TeX`'s integers). This method is very heavily relied upon in `l3fp-basics`.

More specifically, the auxiliary inserts `+ #1#2#3#4#5 ; {#6}`, which allows us to compute several blocks of 4 digits in a nested manner, performing carries on the fly. Say we want to compute 12345×66778899 . With simplified names, we would do

```
\exp_after:wN \post_processing:w
\__fp_int_value:w \__fp_int_eval:w - 5 0000
  \exp_after:wN \pack:NNNNNw
  \__fp_int_value:w \__fp_int_eval:w 4 9995 0000
    + 12345 * 6677
  \exp_after:wN \pack:NNNNNw
  \__fp_int_value:w \__fp_int_eval:w 5 0000 0000
    + 12345 * 8899 ;
```

The `\exp_after:wN` triggers `\int_value:w __fp_int_eval:w`, which starts a first computation, whose initial value is $-5\,0000$ (the “leading shift”). In that computation appears an `\exp_after:wN`, which triggers the nested computation `\int_value:w __fp_int_eval:w` with starting value $4\,9995\,0000$ (the “middle shift”). That, in turn, expands `\exp_after:wN` which triggers the third computation. The third computation's value is $5\,0000\,0000 + 12345 \times 8899$, which has 9 digits. Adding $5 \cdot 10^8$ to the product allowed us to know how many digits to expect as long as the numbers to multiply are not too big; it also works to some extent with negative results. The `pack` function puts the last 4 of those 9 digits into a brace group, moves the semi-colon delimiter, and inserts a `+`, which combines the carry with the previous computation. The shifts nicely combine into $5\,0000\,0000/10^4 + 4\,9995\,0000 = 5\,0000\,0000$. As long as the operands are in some range, the result of this second computation has 9 digits. The corresponding `pack` function, expanded after the result is computed, braces the last 4 digits, and leaves `+ <5 digits>` for the initial computation. The “leading shift” cancels the combination of the other shifts, and the `\post_processing:w` takes care of packing the last few digits.

Admittedly, this is quite intricate. It is probably the key in making `l3fp` as fast as other pure `TeX` floating point units despite its increased precision. In fact, this is used so much that we provide different sets of packing functions and shifts, depending on ranges of input.

This set of shifts allows for computations involving results in the range $[-4 \cdot 10^8, 5 \cdot 10^8 - 1]$. Shifted values all have exactly 9 digits.

```
\__fp_pack:NNNNNw
\c__fp_trailing_shift_int
\c__fp_middle_shift_int
\c__fp_leading_shift_int
13370 \int_const:Nn \c__fp_leading_shift_int { - 5 0000 }
13371 \int_const:Nn \c__fp_middle_shift_int { 5 0000 * 9999 }
13372 \int_const:Nn \c__fp_trailing_shift_int { 5 0000 * 10000 }
13373 \cs_new:Npn \__fp_pack:NNNNNw #1 #2#3#4#5 #6; { + #1#2#3#4#5 ; {#6} }
```

(End definition for `_fp_pack:NNNNNw` and others.)

`_fp_pack_big:NNNNNw`
`\c_fp_big_trailing_shift_int`
`\c_fp_big_middle_shift_int`
`\c_fp_big_leading_shift_int`

This set of shifts allows for computations involving results in the range $[-5 \cdot 10^8, 6 \cdot 10^8 - 1]$ (actually a bit more). Shifted values all have exactly 10 digits. Note that the upper bound is due to $\text{T}_{\text{E}}\text{X}$'s limit of $2^{31} - 1$ on integers. The shifts are chosen to be roughly the mid-point of 10^9 and 2^{31} , the two bounds on 10-digit integers in $\text{T}_{\text{E}}\text{X}$.

```
13374 \int_const:Nn \c\_fp_big_leading_shift_int { - 15 2374 }
13375 \int_const:Nn \c\_fp_big_middle_shift_int { 15 2374 * 9999 }
13376 \int_const:Nn \c\_fp_big_trailing_shift_int { 15 2374 * 10000 }
13377 \cs_new:Npn \_fp_pack_big:NNNNNw #1#2 #3#4#5#6 #7;
13378 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `_fp_pack_big:NNNNNw` and others.)

`_fp_pack_Bigg:NNNNNw`
`\c_fp_Bigg_trailing_shift_int`
`\c_fp_Bigg_middle_shift_int`
`\c_fp_Bigg_leading_shift_int`

This set of shifts allows for computations with results in the range $[-1 \cdot 10^9, 147483647]$; the end-point is $2^{31} - 1 - 2 \cdot 10^9 \simeq 1.47 \cdot 10^8$. Shifted values all have exactly 10 digits.

```
13379 \int_const:Nn \c\_fp_Bigg_leading_shift_int { - 20 0000 }
13380 \int_const:Nn \c\_fp_Bigg_middle_shift_int { 20 0000 * 9999 }
13381 \int_const:Nn \c\_fp_Bigg_trailing_shift_int { 20 0000 * 10000 }
13382 \cs_new:Npn \_fp_pack_Bigg:NNNNNw #1#2 #3#4#5#6 #7;
13383 { + #1#2#3#4#5#6 ; {#7} }
```

(End definition for `_fp_pack_Bigg:NNNNNw` and others.)

`_fp_pack_twice_four:wNNNNNNNN`

`_fp_pack_twice_four:wNNNNNNNN` *(tokens)* ; $\langle \geq 8 \text{ digits} \rangle$

Grabs two sets of 4 digits and places them before the semi-colon delimiter. Putting several copies of this function before a semicolon packs more digits since each takes the digits packed by the others in its first argument.

```
13384 \cs_new:Npn \_fp_pack_twice_four:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
13385 { #1 {#2#3#4#5} {#6#7#8#9} ; }
```

(End definition for `_fp_pack_twice_four:wNNNNNNNN`.)

`_fp_pack_eight:wNNNNNNNN`

`_fp_pack_eight:wNNNNNNNN` *(tokens)* ; $\langle \geq 8 \text{ digits} \rangle$

Grabs one set of 8 digits and places them before the semi-colon delimiter as a single group. Putting several copies of this function before a semicolon packs more digits since each takes the digits packed by the others in its first argument.

```
13386 \cs_new:Npn \_fp_pack_eight:wNNNNNNNN #1; #2#3#4#5 #6#7#8#9
13387 { #1 {#2#3#4#5#6#7#8#9} ; }
```

(End definition for `_fp_pack_eight:wNNNNNNNN`.)

`_fp_basics_pack_low:NNNNNw`
`_fp_basics_pack_high:NNNNNw`
`_fp_basics_pack_high_carry:w`

Addition and multiplication of significands are done in two steps: first compute a (more or less) exact result, then round and pack digits in the final (braced) form. These functions take care of the packing, with special attention given to the case where rounding has caused a carry. Since rounding can only shift the final digit by 1, a carry always produces an exact power of 10. Thus, `_fp_basics_pack_high_carry:w` is always followed by four times `{0000}`.

This is used in `l3fp-basics` and `l3fp-extended`.

```
13388 \cs_new:Npn \_fp_basics_pack_low:NNNNNw #1 #2#3#4#5 #6;
13389 { + #1 - 1 ; {#2#3#4#5} {#6} ; }
13390 \cs_new:Npn \_fp_basics_pack_high:NNNNNw #1 #2#3#4#5 #6;
13391 {
```

```

13392     \if_meaning:w 2 #1
13393         \__fp_basics_pack_high_carry:w
13394     \fi:
13395     ; {#2#3#4#5} {#6}
13396 }
13397 \cs_new:Npn \__fp_basics_pack_high_carry:w \fi: ; #1
13398 { \fi: + 1 ; {1000} }

```

(End definition for `__fp_basics_pack_low:NNNNw`, `__fp_basics_pack_high:NNNNw`, and `__fp_basics_pack_high_carry:w`.)

`__fp_basics_pack_weird_low:NNNNw`
`__fp_basics_pack_weird_high:NNNNNNNw`

This is used in `l3fp-basics` for additions and divisions. Their syntax is confusing, hence the name.

```

13399 \cs_new:Npn \__fp_basics_pack_weird_low:NNNNw #1 #2#3#4 #5;
13400 {
13401     \if_meaning:w 2 #1
13402         + 1
13403     \fi:
13404     \__fp_int_eval_end:
13405     #2#3#4; {#5} ;
13406 }
13407 \cs_new:Npn \__fp_basics_pack_weird_high:NNNNNNNw
13408     1 #1#2#3#4 #5#6#7#8 #9; { ; {#1#2#3#4} {#5#6#7#8} {#9} }

```

(End definition for `__fp_basics_pack_weird_low:NNNNw` and `__fp_basics_pack_weird_high:NNNNNNNw`.)

23.9 Decimate (dividing by a power of 10)

`__fp_decimate:nNnnnn`

`__fp_decimate:nNnnnn {⟨shift⟩} {f1}`
`{⟨X1⟩} {⟨X2⟩} {⟨X3⟩} {⟨X4⟩}`

Each $\langle X_i \rangle$ consists in 4 digits exactly, and $1000 \leq \langle X_1 \rangle < 9999$. The first argument determines by how much we shift the digits. $\langle f_1 \rangle$ is called as follows:

$\langle f_1 \rangle \langle \text{rounding} \rangle \{ \langle X'_1 \rangle \} \{ \langle X'_2 \rangle \} \langle \text{extra-digits} \rangle ;$

where $0 \leq \langle X'_i \rangle < 10^8 - 1$ are 8 digit integers, forming the truncation of our number. In other words,

$$\left(\sum_{i=1}^4 \langle X_i \rangle \cdot 10^{-4i} \cdot 10^{-\langle \text{shift} \rangle} \right) - (\langle X'_1 \rangle \cdot 10^{-8} + \langle X'_2 \rangle \cdot 10^{-16}) = 0. \langle \text{extra-digits} \rangle \cdot 10^{-16} \in [0, 10^{-16}).$$

To round properly later, we need to remember some information about the difference. The $\langle \text{rounding} \rangle$ digit is 0 if and only if the difference is exactly 0, and 5 if and only if the difference is exactly $0.5 \cdot 10^{-16}$. Otherwise, it is the (non-0, non-5) digit closest to 10^{17} times the difference. In particular, if the shift is 17 or more, all the digits are dropped, $\langle \text{rounding} \rangle$ is 1 (not 0), and $\langle X'_1 \rangle$ and $\langle X'_2 \rangle$ are both zero.

If the shift is 1, the $\langle \text{rounding} \rangle$ digit is simply the only digit that was pushed out of the brace groups (this is important for subtraction). It would be more natural for the $\langle \text{rounding} \rangle$ digit to be placed after the $\langle X'_i \rangle$, but the choice we make involves less reshuffling.

Note that this function treats negative $\langle \text{shift} \rangle$ as 0.

```

13409 \cs_new:Npn \__fp_decimate:nNnnnn #1
13410 {

```

```

13411 \cs:w
13412   __fp_decimate_
13413   \if_int_compare:w \__fp_int_eval:w #1 > \c__fp_prec_int
13414     tiny
13415   \else:
13416     \__fp_int_to_roman:w \__fp_int_eval:w #1
13417   \fi:
13418   :Nnnnn
13419   \cs_end:
13420 }

```

Each of the auxiliaries see the function $\langle f_1 \rangle$, followed by 4 blocks of 4 digits.

(End definition for `__fp_decimate:nNnnnn`.)

```

\__fp_decimate_:Nnnnn
\__fp_decimate_tiny:Nnnnn
13421 \cs_new:Npn \__fp_decimate_:Nnnnn #1 #2#3#4#5
13422   { #1 0 {#2#3} {#4#5} ; }
13423 \cs_new:Npn \__fp_decimate_tiny:Nnnnn #1 #2#3#4#5
13424   { #1 1 { 0000 0000 } { 0000 0000 } 0 #2#3#4#5 ; }

```

(End definition for `__fp_decimate_:Nnnnn` and `__fp_decimate_tiny:Nnnnn`.)

```

\__fp_decimate_auxi:Nnnnn
\__fp_decimate_auxii:Nnnnn
\__fp_decimate_auxiii:Nnnnn
\__fp_decimate_auxiv:Nnnnn
\__fp_decimate_auxv:Nnnnn
\__fp_decimate_auxvi:Nnnnn
\__fp_decimate_auxvii:Nnnnn
\__fp_decimate_auxviii:Nnnnn
\__fp_decimate_auxix:Nnnnn
\__fp_decimate_auxx:Nnnnn
\__fp_decimate_auxxi:Nnnnn
\__fp_decimate_auxxii:Nnnnn
\__fp_decimate_auxxiii:Nnnnn
\__fp_decimate_auxxiv:Nnnnn
\__fp_decimate_auxxv:Nnnnn
\__fp_decimate_auxxvi:Nnnnn

```

```

\__fp_decimate_auxi:Nnnnn \langle f_1 \rangle \{ \langle X_1 \rangle \} \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \}

```

Shifting happens in two steps: compute the $\langle \text{rounding} \rangle$ digit, and repack digits into two blocks of 8. The sixteen functions are very similar, and defined through `__fp_tmp:w`. The arguments are as follows: #1 indicates which function is being defined; after one step of expansion, #2 yields the “extra digits” which are then converted by `__fp_round_digit:Nw` to the $\langle \text{rounding} \rangle$ digit (note the + separating blocks of digits to avoid overflowing TeX’s integers). This triggers the f-expansion of `__fp_decimate_pack:nnnnnnnnnw`,⁸ responsible for building two blocks of 8 digits, and removing the rest. For this to work, #3 alternates between braced and unbraced blocks of 4 digits, in such a way that the 5 first and 5 next token groups yield the correct blocks of 8 digits.

```

13425 \cs_new:Npn \__fp_tmp:w #1 #2 #3
13426   {
13427     \cs_new:cpn { __fp_decimate_ #1 :Nnnnn } ##1 ##2##3##4##5
13428     {
13429       \exp_after:wN ##1
13430       \int_value:w
13431       \exp_after:wN \__fp_round_digit:Nw #2 ;
13432       \__fp_decimate_pack:nnnnnnnnnw #3 ;
13433     }
13434   }
13435 \__fp_tmp:w {i}   {\use_none:nnn   #50}{ 0{#2}#3{#4}#5      }
13436 \__fp_tmp:w {ii}  {\use_none:nn    #5 }{ 00{#2}#3{#4}#5      }
13437 \__fp_tmp:w {iii} {\use_none:n     #5 }{ 000{#2}#3{#4}#5      }
13438 \__fp_tmp:w {iv}  {                 #5 }{ {0000}#2{#3}#4 #5    }
13439 \__fp_tmp:w {v}   {\use_none:nnn   #4#5 }{ 0{0000}#2{#3}#4 #5    }
13440 \__fp_tmp:w {vi}  {\use_none:nn    #4#5 }{ 00{0000}#2{#3}#4 #5    }
13441 \__fp_tmp:w {vii} {\use_none:n     #4#5 }{ 000{0000}#2{#3}#4 #5    }
13442 \__fp_tmp:w {viii}{                 #4#5 }{ {0000}0000{#2}#3 #4 #5 }
13443 \__fp_tmp:w {ix}  {\use_none:nnn   #3#4+#5}{ 0{0000}0000{#2}#3 #4 #5 }

```

⁸No, the argument spec is not a mistake: the function calls an auxiliary to do half of the job.

```

13444 \__fp_tmp:w {x}    {\use_none:nn #3#4+#5}{ 00{0000}0000{#2}#3 #4 #5    }
13445 \__fp_tmp:w {xi}   {\use_none:n  #3#4+#5}{ 000{0000}0000{#2}#3 #4 #5    }
13446 \__fp_tmp:w {xii}  { #3#4+#5}{ {0000}0000{0000}#2 #3 #4 #5    }
13447 \__fp_tmp:w {xiii}{\use_none:nnn#2#3+#4#5}{ 0{0000}0000{0000}#2 #3 #4 #5    }
13448 \__fp_tmp:w {xiv}  {\use_none:nn #2#3+#4#5}{ 00{0000}0000{0000}#2 #3 #4 #5    }
13449 \__fp_tmp:w {xv}   {\use_none:n  #2#3+#4#5}{ 000{0000}0000{0000}#2 #3 #4 #5    }
13450 \__fp_tmp:w {xvi}  { #2#3+#4#5}{ {0000}0000{0000}0000 #2 #3 #4 #5 }

```

(End definition for __fp_decimate_auxi:Nnnnn and others.)

__fp_decimate_pack:nnnnnnnnnw

The computation of the *<rounding>* digit leaves an unfinished \int_value:w, which expands the following functions. This allows us to repack nicely the digits we keep. Those digits come as an alternation of unbraced and braced blocks of 4 digits, such that the first 5 groups of token consist in 4 single digits, and one brace group (in some order), and the next 5 have the same structure. This is followed by some digits and a semicolon.

```

13451 \cs_new:Npn \__fp_decimate_pack:nnnnnnnnnw #1#2#3#4#5
13452   { \__fp_decimate_pack:nnnnnw { #1#2#3#4#5 } }
13453 \cs_new:Npn \__fp_decimate_pack:nnnnnw #1 #2#3#4#5#6
13454   { {#1} {#2#3#4#5#6} }

```

(End definition for __fp_decimate_pack:nnnnnnnnnw.)

23.10 Functions for use within primitive conditional branches

The functions described in this section are not pretty and can easily be misused. When correctly used, each of them removes one \fi: as part of its parameter text, and puts one back as part of its replacement text.

Many computation functions in l3fp must perform tests on the type of floating points that they receive. This is often done in an \if_case:w statement or another conditional statement, and only a few cases lead to actual computations: most of the special cases are treated using a few standard functions which we define now. A typical use context for those functions would be

```

\if_case:w <integer> \exp_stop_f:
  \__fp_case_return_o:Nw <fp var>
\or: \__fp_case_use:nw {<some computation>}
\or: \__fp_case_return_same_o:w
\or: \__fp_case_return:nw {<something>}
\fi:
<junk>
<floating point>

```

In this example, the case 0 returns the floating point *<fp var>*, expanding once after that floating point. Case 1 does *<some computation>* using the *<floating point>* (presumably compute the operation requested by the user in that non-trivial case). Case 2 returns the *<floating point>* without modifying it, removing the *<junk>* and expanding once after. Case 3 closes the conditional, removes the *<junk>* and the *<floating point>*, and expands *<something>* next. In other cases, the “*<junk>*” is expanded, performing some other operation on the *<floating point>*. We provide similar functions with two trailing *<floating points>*.

`__fp_case_use:nw` This function ends a \TeX conditional, removes junk until the next floating point, and places its first argument before that floating point, to perform some operation on the floating point.

```
13455 \cs_new:Npn \__fp_case_use:nw #1#2 \fi: #3 \s__fp { \fi: #1 \s__fp }
```

(End definition for `__fp_case_use:nw`.)

`__fp_case_return:nw` This function ends a \TeX conditional, removes junk and a floating point, and places its first argument in the input stream. A quirk is that we don't define this function requiring a floating point to follow, simply anything ending in a semicolon. This, in turn, means that the *junk* may not contain semicolons.

```
13456 \cs_new:Npn \__fp_case_return:nw #1#2 \fi: #3 ; { \fi: #1 }
```

(End definition for `__fp_case_return:nw`.)

`__fp_case_return_o:Nw` This function ends a \TeX conditional, removes junk and a floating point, and returns its first argument (an *fp var*) then expands once after it.

```
13457 \cs_new:Npn \__fp_case_return_o:Nw #1#2 \fi: #3 \s__fp #4 ;
13458 { \fi: \exp_after:wN #1 }
```

(End definition for `__fp_case_return_o:Nw`.)

`__fp_case_return_same_o:w` This function ends a \TeX conditional, removes junk, and returns the following floating point, expanding once after it.

```
13459 \cs_new:Npn \__fp_case_return_same_o:w #1 \fi: #2 \s__fp
13460 { \fi: \__fp_exp_after_o:w \s__fp }
```

(End definition for `__fp_case_return_same_o:w`.)

`__fp_case_return_o:Nww` Same as `__fp_case_return_o:Nw` but with two trailing floating points.

```
13461 \cs_new:Npn \__fp_case_return_o:Nww #1#2 \fi: #3 \s__fp #4 ; #5 ;
13462 { \fi: \exp_after:wN #1 }
```

(End definition for `__fp_case_return_o:Nww`.)

`__fp_case_return_i_o:ww` Similar to `__fp_case_return_same_o:w`, but this returns the first or second of two trailing floating point numbers, expanding once after the result.

```
13463 \cs_new:Npn \__fp_case_return_i_o:ww #1 \fi: #2 \s__fp #3 ; \s__fp #4 ;
13464 { \fi: \__fp_exp_after_o:w \s__fp #3 ; }
13465 \cs_new:Npn \__fp_case_return_ii_o:ww #1 \fi: #2 \s__fp #3 ;
13466 { \fi: \__fp_exp_after_o:w }
```

(End definition for `__fp_case_return_i_o:ww` and `__fp_case_return_ii_o:ww`.)

23.11 Integer floating points

`_fp_int_p:w` Tests if the floating point argument is an integer. For normal floating point numbers, this holds if the rounding digit resulting from `_fp_decimate:nNnnnn` is 0.

`_fp_int:wTF`

```

13467 \prg_new_conditional:Npnn \_fp_int:w \s_fp \_fp_chk:w #1 #2 #3 #4;
13468 { TF , T , F , p }
13469 {
13470   \if_case:w #1 \exp_stop_f:
13471     \prg_return_true:
13472   \or:
13473     \if_charcode:w 0
13474       \_fp_decimate:nNnnnn { \c_fp_prec_int - #3 }
13475       \_fp_use_i_until_s:nw #4
13476       \prg_return_true:
13477     \else:
13478       \prg_return_false:
13479     \fi:
13480   \else: \prg_return_false:
13481   \fi:
13482 }

```

(End definition for `_fp_int:wTF`.)

23.12 Small integer floating points

`_fp_small_int:wTF` Tests if the floating point argument is an integer or $\pm\infty$. If so, it is converted to an integer in the range $[-10^8, 10^8]$ and fed as a braced argument to the *⟨true code⟩*. Otherwise, the *⟨false code⟩* is performed.

`_fp_small_int_true:wTF`

`_fp_small_int_normal:NnwTF`

`_fp_small_int_test:NnnwNTF`

First filter special cases: zeros and infinities are integers, `nan` is not. For normal numbers, decimate. If the rounding digit is not 0 run the *⟨false code⟩*. If it is, then the integer is `#2 #3`; use `#3` if `#2` vanishes and otherwise 10^8 .

```

13483 \cs_new:Npn \_fp_small_int:wTF \s_fp \_fp_chk:w #1#2
13484 {
13485   \if_case:w #1 \exp_stop_f:
13486     \_fp_case_return:nw { \_fp_small_int_true:wTF 0 ; }
13487   \or: \exp_after:wN \_fp_small_int_normal:NnwTF
13488   \or:
13489     \_fp_case_return:nw
13490     {
13491       \exp_after:wN \_fp_small_int_true:wTF \int_value:w
13492       \if_meaning:w 2 #2 - \fi: 1 0000 0000 ;
13493     }
13494   \else: \_fp_case_return:nw \use_ii:nn
13495   \fi:
13496   #2
13497 }
13498 \cs_new:Npn \_fp_small_int_true:wTF #1; #2#3 { #2 {#1} }
13499 \cs_new:Npn \_fp_small_int_normal:NnwTF #1#2#3;
13500 {
13501   \_fp_decimate:nNnnnn { \c_fp_prec_int - #2 }
13502   \_fp_small_int_test:NnnwNw
13503   #3 #1
13504 }

```



```

13505 \cs_new:Npn \__fp_small_int_test:NnnwNw #1#2#3#4; #5
13506 {
13507   \if_meaning:w 0 #1
13508     \exp_after:wN \__fp_small_int_true:wTF
13509     \int_value:w \if_meaning:w 2 #5 - \fi:
13510     \if_int_compare:w #2 > 0 \exp_stop_f:
13511       1 0000 0000
13512     \else:
13513       #3
13514     \fi:
13515     \exp_after:wN ;
13516   \else:
13517     \exp_after:wN \use_ii:nn
13518   \fi:
13519 }

```

(End definition for `__fp_small_int:wTF` and others.)

23.13 x-like expansion expandably

`__fp_expand:n`
`__fp_expand_loop:nwnN`

This expandable function behaves in a way somewhat similar to `\use:x`, but much less robust. The argument is f-expanded, then the leading item (often a single character token) is moved to a storage area after `\s__fp_mark`, and f-expansion is applied again, repeating until the argument is empty. The result built one piece at a time is then inserted in the input stream. Note that spaces are ignored by this procedure, unless surrounded with braces. Multiple tokens which do not need expansion can be inserted within braces.

```

13520 \cs_new:Npn \__fp_expand:n #1
13521 {
13522   \__fp_expand_loop:nwnN { }
13523   #1 \prg_do_nothing:
13524   \s__fp_mark { } \__fp_expand_loop:nwnN
13525   \s__fp_mark { } \__fp_use_i_until_s:nw ;
13526 }
13527 \cs_new:Npn \__fp_expand_loop:nwnN #1#2 \s__fp_mark #3 #4
13528 {
13529   \exp_after:wN #4 \exp:w \exp_end_continue_f:w
13530   #2
13531   \s__fp_mark { #3 #1 } #4
13532 }

```

(End definition for `__fp_expand:n` and `__fp_expand_loop:nwnN`.)

23.14 Fast string comparison

`__fp_str_if_eq:nn`

A private version of the low-level string comparison function. As the nature of the arguments is restricted and as speed is of the essence, this version does not seek to deal with # tokens. No `l3sys` or `l3luatex` just yet so we have to define in terms of primitives.

```

13533 \cs_new:Npn \__fp_str_if_eq:nn #1#2 { \tex_strcmp:D {#1} {#2} }
13534 \sys_if_engine luatex:T
13535 {
13536   \cs_set:Npn \__fp_str_if_eq:nn #1#2
13537   {

```

```

13538     \tex_directlua:D
13539     {
13540         l3kernel.strptime
13541         (
13542             " \tex_luaescapestring:D {#1}",
13543             " \tex_luaescapestring:D {#2}"
13544         )
13545     }
13546 }
13547 }

```

(End definition for `__fp_str_if_eq:nn`.)

23.15 Name of a function from its l3fp-parse name

`__fp_func_to_name:N` The goal is to convert for instance `__fp_sin_o:w` to `sin`. This is used in error messages hence does not need to be fast.

```

13548 \cs_new:Npn \__fp_func_to_name:N #1
13549 {
13550     \exp_last_unbraced:Nf
13551     \__fp_func_to_name_aux:w { \cs_to_str:N #1 } X
13552 }
13553 \cs_set_protected:Npn \__fp_tmp:w #1 #2
13554 { \cs_new:Npn \__fp_func_to_name_aux:w ##1 #1 ##2 #2 ##3 X {##2} }
13555 \exp_args:Nff \__fp_tmp:w { \tl_to_str:n { __fp_ } }
13556 { \tl_to_str:n { _o: } }

```

(End definition for `__fp_func_to_name:N` and `__fp_func_to_name_aux:w`.)

23.16 Messages

Using a floating point directly is an error.

```

13557 \__kernel_msg_new:nnnn { kernel } { misused-fp }
13558 { A~floating~point~with~value~'#1'~was~misused. }
13559 {
13560     To~obtain~the~value~of~a~floating~point~variable,~use~
13561     '\token_to_str:N \fp_to_decimal:N',~
13562     '\token_to_str:N \fp_to_tl:N',~or~other~
13563     conversion~functions.
13564 }
13565 </initex | package>

```

24 l3fp-traps Implementation

```

13566 (*initex | package)
13567 <@@=fp>

```

Exceptions should be accessed by an `n`-type argument, among

- `invalid_operation`
- `division_by_zero`
- `overflow`

- underflow
- inexact (actually never used).

24.1 Flags

```

flag_fp_invalid_operation  Flags to denote exceptions.
flag_fp_division_by_zero   13568 \flag_new:n { fp_invalid_operation }
                             13569 \flag_new:n { fp_division_by_zero }
                             13570 \flag_new:n { fp_overflow }
                             13571 \flag_new:n { fp_underflow }
flag_fp_overflow
flag_fp_underflow

```

(End definition for flag fp_invalid_operation and others. These variables are documented on page 192.)

24.2 Traps

Exceptions can be trapped to obtain custom behaviour. When an invalid operation or a division by zero is trapped, the trap receives as arguments the result as an N-type floating point number, the function name (multiple letters for prefix operations, or a single symbol for infix operations), and the operand(s). When an overflow or underflow is trapped, the trap receives the resulting overly large or small floating point number if it is not too big, otherwise it receives $+\infty$. Currently, the inexact exception is entirely ignored.

The behaviour when an exception occurs is controlled by the definitions of the functions

- __fp_invalid_operation:nnw,
- __fp_invalid_operation_o:Nww,
- __fp_invalid_operation_tl_o:ff,
- __fp_division_by_zero_o:Nnw,
- __fp_division_by_zero_o:NNww,
- __fp_overflow:w,
- __fp_underflow:w.

Rather than changing them directly, we provide a user interface as \fp_trap:nn {*exception*} {*way of trapping*}, where the *way of trapping* is one of **error**, **flag**, or **none**.

We also provide __fp_invalid_operation_o:nw, defined in terms of __fp_invalid_operation:nnw.

```

\fp_trap:nn
13572 \cs_new_protected:Npn \fp_trap:nn #1#2
13573 {
13574   \cs_if_exist_use:cF { __fp_trap_#1_set_#2: }
13575   {
13576     \clist_if_in:nnTF
13577       { invalid_operation , division_by_zero , overflow , underflow }
13578       {#1}
13579       {

```

```

13580         \__kernel_msg_error:nxxx { kernel }
13581         { unknown-fpu-trap-type } {#1} {#2}
13582     }
13583     {
13584         \__kernel_msg_error:nxx
13585         { kernel } { unknown-fpu-exception } {#1}
13586     }
13587 }
13588 }

```

(End definition for \fp_trap:nn. This function is documented on page 192.)

_fp_trap_invalid_operation_set_error: We provide three types of trapping for invalid operations: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the flag. In most cases, the function produces as a result its first argument, possibly with post-expansion.

```

\_fp_trap_invalid_operation_set_flag:
\_fp_trap_invalid_operation_set_none:
\_fp_trap_invalid_operation_set:N
13589 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_error:
13590 { \__fp_trap_invalid_operation_set:N \prg_do_nothing: }
13591 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_flag:
13592 { \__fp_trap_invalid_operation_set:N \use_none:nnnnn }
13593 \cs_new_protected:Npn \__fp_trap_invalid_operation_set_none:
13594 { \__fp_trap_invalid_operation_set:N \use_none:nnnnnnn }
13595 \cs_new_protected:Npn \__fp_trap_invalid_operation_set:N #1
13596 {
13597     \exp_args:Nno \use:n
13598     { \cs_set:Npn \__fp_invalid_operation:nw ##1##2##3; }
13599     {
13600         #1
13601         \__fp_error:nfn { fp-invalid } {##2} { \fp_to_tl:n { ##3; } } { }
13602         \flag_raise_if_clear:n { fp_invalid_operation }
13603         ##1
13604     }
13605     \exp_args:Nno \use:n
13606     { \cs_set:Npn \__fp_invalid_operation_o:Nw ##1##2; ##3; }
13607     {
13608         #1
13609         \__fp_error:nfn { fp-invalid-ii }
13610         { \fp_to_tl:n { ##2; } } { \fp_to_tl:n { ##3; } } {##1}
13611         \flag_raise_if_clear:n { fp_invalid_operation }
13612         \exp_after:wN \c_nan_fp
13613     }
13614     \exp_args:Nno \use:n
13615     { \cs_set:Npn \__fp_invalid_operation_tl_o:ff ##1##2 }
13616     {
13617         #1
13618         \__fp_error:nfn { fp-invalid } {##1} {##2} { }
13619         \flag_raise_if_clear:n { fp_invalid_operation }
13620         \exp_after:wN \c_nan_fp
13621     }
13622 }

```

(End definition for __fp_trap_invalid_operation_set_error: and others.)

_fp_trap_division_by_zero_set_error: We provide three types of trapping for invalid operations and division by zero: either produce an error and raise the relevant flag; or only raise the flag; or don't even raise the

_fp_trap_division_by_zero_set_flag:

_fp_trap_division_by_zero_set_none:

_fp_trap_division_by_zero_set:N

flag. In all cases, the function must produce a result, namely its first argument, $\pm\infty$ or NaN.

```

13623 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_error:
13624 { \__fp_trap_division_by_zero_set:N \prg_do_nothing: }
13625 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_flag:
13626 { \__fp_trap_division_by_zero_set:N \use_none:nnnnn }
13627 \cs_new_protected:Npn \__fp_trap_division_by_zero_set_none:
13628 { \__fp_trap_division_by_zero_set:N \use_none:nnnnnnn }
13629 \cs_new_protected:Npn \__fp_trap_division_by_zero_set:N #1
13630 {
13631   \exp_args:Nno \use:n
13632   { \cs_set:Npn \__fp_division_by_zero_o:Nnw ##1##2##3; }
13633   {
13634     #1
13635     \__fp_error:nfn { fp-zero-div } {##2} { \fp_to_tl:n { ##3; } } { }
13636     \flag_raise_if_clear:n { fp_division_by_zero }
13637     \exp_after:wN ##1
13638   }
13639   \exp_args:Nno \use:n
13640   { \cs_set:Npn \__fp_division_by_zero_o:NNww ##1##2##3; ##4; }
13641   {
13642     #1
13643     \__fp_error:nfn { fp-zero-div-ii }
13644     { \fp_to_tl:n { ##3; } } { \fp_to_tl:n { ##4; } } {##2}
13645     \flag_raise_if_clear:n { fp_division_by_zero }
13646     \exp_after:wN ##1
13647   }
13648 }

```

(End definition for `__fp_trap_division_by_zero_set_error:` and others.)

<code>__fp_trap_overflow_set_error:</code> <code>__fp_trap_overflow_set_flag:</code> <code>__fp_trap_overflow_set_none:</code> <code>__fp_trap_overflow_set:N</code> <code>__fp_trap_underflow_set_error:</code> <code>__fp_trap_underflow_set_flag:</code> <code>__fp_trap_underflow_set_none:</code> <code>__fp_trap_underflow_set:N</code> <code>__fp_trap_overflow_set:NnNn</code>	<p>Just as for invalid operations and division by zero, the three different behaviours are obtained by feeding <code>\prg_do_nothing:</code>, <code>\use_none:nnnnn</code> or <code>\use_none:nnnnnnn</code> to an auxiliary, with a further auxiliary common to overflow and underflow functions. In most cases, the argument of the <code>__fp_overflow:w</code> and <code>__fp_underflow:w</code> functions will be an (almost) normal number (with an exponent outside the allowed range), and the error message thus displays that number together with the result to which it overflowed or underflowed. For extreme cases such as <code>10 ** 1e9999</code>, the exponent would be too large for T_EX, and <code>__fp_overflow:w</code> receives $\pm\infty$ (<code>__fp_underflow:w</code> would receive ± 0); then we cannot do better than simply say an overflow or underflow occurred.</p>
---	--

```

13649 \cs_new_protected:Npn \__fp_trap_overflow_set_error:
13650 { \__fp_trap_overflow_set:N \prg_do_nothing: }
13651 \cs_new_protected:Npn \__fp_trap_overflow_set_flag:
13652 { \__fp_trap_overflow_set:N \use_none:nnnnn }
13653 \cs_new_protected:Npn \__fp_trap_overflow_set_none:
13654 { \__fp_trap_overflow_set:N \use_none:nnnnnnn }
13655 \cs_new_protected:Npn \__fp_trap_overflow_set:N #1
13656 { \__fp_trap_overflow_set:NnNn #1 { overflow } \__fp_inf_fp:N { inf } }
13657 \cs_new_protected:Npn \__fp_trap_underflow_set_error:
13658 { \__fp_trap_underflow_set:N \prg_do_nothing: }
13659 \cs_new_protected:Npn \__fp_trap_underflow_set_flag:
13660 { \__fp_trap_underflow_set:N \use_none:nnnnn }
13661 \cs_new_protected:Npn \__fp_trap_underflow_set_none:

```

```

13662 { \__fp_trap_underflow_set:N \use_none:nnnnnnn }
13663 \cs_new_protected:Npn \__fp_trap_underflow_set:N #1
13664 { \__fp_trap_overflow_set:NnNn #1 { underflow } \__fp_zero_fp:N { 0 } }
13665 \cs_new_protected:Npn \__fp_trap_overflow_set:NnNn #1#2#3#4
13666 {
13667   \exp_args:Nno \use:n
13668   { \cs_set:cpn { \__fp_ #2 :w } \s__fp \__fp_chk:w ##1##2##3; }
13669   {
13670     #1
13671     \__fp_error:nffn
13672     { fp-flow \if_meaning:w 1 ##1 -to \fi: }
13673     { \fp_to_tl:n { \s__fp \__fp_chk:w ##1##2##3; } }
13674     { \token_if_eq_meaning:NNF 0 ##2 { - } #4 }
13675     {#2}
13676     \flag_raise_if_clear:n { fp_#2 }
13677     #3 ##2
13678   }
13679 }

```

(End definition for __fp_trap_overflow_set_error: and others.)

__fp_invalid_operation:nnw Initialize the control sequences (to log properly their existence). Then set invalid operations to trigger an error, and division by zero, overflow, and underflow to act silently on their flag.

```

\__fp_invalid_operation_o:Nnw
\__fp_invalid_operation_tl_o:ff
\__fp_division_by_zero_o:Nnw
\__fp_division_by_zero_o:NNww
\__fp_overflow:w
\__fp_underflow:w
13680 \cs_new:Npn \__fp_invalid_operation:nnw #1#2#3; { }
13681 \cs_new:Npn \__fp_invalid_operation_o:Nnw #1#2; #3; { }
13682 \cs_new:Npn \__fp_invalid_operation_tl_o:ff #1 #2 { }
13683 \cs_new:Npn \__fp_division_by_zero_o:Nnw #1#2#3; { }
13684 \cs_new:Npn \__fp_division_by_zero_o:NNww #1#2#3; #4; { }
13685 \cs_new:Npn \__fp_overflow:w { }
13686 \cs_new:Npn \__fp_underflow:w { }
13687 \fp_trap:nn { invalid_operation } { error }
13688 \fp_trap:nn { division_by_zero } { flag }
13689 \fp_trap:nn { overflow } { flag }
13690 \fp_trap:nn { underflow } { flag }

```

(End definition for __fp_invalid_operation:nnw and others.)

__fp_invalid_operation_o:nw Convenient short-hands for returning \c_nan_fp for a unary or binary operation, and expanding after.

```

13691 \cs_new:Npn \__fp_invalid_operation_o:nw
13692 { \__fp_invalid_operation:nnw { \exp_after:wN \c_nan_fp } }
13693 \cs_generate_variant:Nn \__fp_invalid_operation_o:nw { f }

```

(End definition for __fp_invalid_operation_o:nw.)

24.3 Errors

```

\__fp_error:nnnn
\__fp_error:nfnf 13694 \cs_new:Npn \__fp_error:nnnn
\__fp_error:nffn 13695 { \__kernel_msg_expandable_error:nnnnn { kernel } }
\__fp_error:nfff 13696 \cs_generate_variant:Nn \__fp_error:nnnn { nnf, nff , nfff }

```

(End definition for __fp_error:nnnn.)

24.4 Messages

Some messages.

```

13697 \__kernel_msg_new:nnnn { kernel } { unknown-fpu-exception }
13698 {
13699     The~FPU~exception~'#1'~is~not~known:~
13700     that~trap~will~never~be~triggered.
13701 }
13702 {
13703     The~only~exceptions~to~which~traps~can~be~attached~are \\
13704     \iow_indent:n
13705     {
13706         * ~ invalid_operation \\
13707         * ~ division_by_zero \\
13708         * ~ overflow \\
13709         * ~ underflow
13710     }
13711 }
13712 \__kernel_msg_new:nnnn { kernel } { unknown-fpu-trap-type }
13713 { The~FPU~trap~type~'#2'~is~not~known. }
13714 {
13715     The~trap~type~must~be~one~of \\
13716     \iow_indent:n
13717     {
13718         * ~ error \\
13719         * ~ flag \\
13720         * ~ none
13721     }
13722 }
13723 \__kernel_msg_new:nnn { kernel } { fp-flow }
13724 { An ~ #3 ~ occurred. }
13725 \__kernel_msg_new:nnn { kernel } { fp-flow-to }
13726 { #1 ~ #3 ed ~ to ~ #2 . }
13727 \__kernel_msg_new:nnn { kernel } { fp-zero-div }
13728 { Division~by~zero~in~ #1 (#2) }
13729 \__kernel_msg_new:nnn { kernel } { fp-zero-div-ii }
13730 { Division~by~zero~in~ (#1) #3 (#2) }
13731 \__kernel_msg_new:nnn { kernel } { fp-invalid }
13732 { Invalid~operation~ #1 (#2) }
13733 \__kernel_msg_new:nnn { kernel } { fp-invalid-ii }
13734 { Invalid~operation~ (#1) #3 (#2) }
13735 \__kernel_msg_new:nnn { kernel } { fp-unknown-type }
13736 { Unknown~type~for~'#1' }
13737 </initex | package>

```

25 I3fp-round implementation

```

13738 <*initex | package>
13739 <@@=fp>

\__fp_parse_word_trunc:N
\__fp_parse_word_floor:N
\__fp_parse_word_ceil:N
13740 \cs_new:Npn \__fp_parse_word_trunc:N
13741 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_zero:NNN }

```

```

13742 \cs_new:Npn \__fp_parse_word_floor:N
13743 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_ninf:NNN }
13744 \cs_new:Npn \__fp_parse_word_ceil:N
13745 { \__fp_parse_function:NNN \__fp_round_o:Nw \__fp_round_to_pinf:NNN }

(End definition for \__fp_parse_word_trunc:N, \__fp_parse_word_floor:N, and \__fp_parse_word_
ceil:N.)

```

```

\__fp_parse_word_round:N
  \__fp_parse_round:Nw
13746 \cs_new:Npn \__fp_parse_word_round:N #1#2
13747 {
13748   \__fp_parse_function:NNN
13749   \__fp_round_o:Nw \__fp_round_to_nearest:NNN #1
13750   #2
13751 }
13752 \cs_new:Npn \__fp_parse_round:Nw #1 #2 \__fp_round_to_nearest:NNN #3#4
13753 { #2 #1 #3 }
13754

```

(End definition for __fp_parse_word_round:N and __fp_parse_round:Nw.)

25.1 Rounding tools

\c__fp_five_int This is used as the half-point for which numbers are rounded up/down.

```

13755 \int_const:Nn \c__fp_five_int { 5 }

```

(End definition for \c__fp_five_int.)

Floating point operations often yield a result that cannot be exactly represented in a significand with 16 digits. In that case, we need to round the exact result to a representable number. The IEEE standard defines four rounding modes:

- Round to nearest: round to the representable floating point number whose absolute difference with the exact result is the smallest. If the exact result lies exactly at the mid-point between two consecutive representable floating point numbers, round to the floating point number whose last digit is even.
- Round towards negative infinity: round to the greatest floating point number not larger than the exact result.
- Round towards zero: round to a floating point number with the same sign as the exact result, with the largest absolute value not larger than the absolute value of the exact result.
- Round towards positive infinity: round to the least floating point number not smaller than the exact result.

This is not fully implemented in l3fp yet, and transcendental functions fall back on the “round to nearest” mode. All rounding for basic algebra is done through the functions defined in this module, which can be redefined to change their rounding behaviour (but there is not interface for that yet).

The rounding tools available in this module are many variations on a base function __fp_round:NNN, which expands to 0\exp_stop_f: or 1\exp_stop_f: depending on whether the final result should be rounded up or down.

- __fp_round:NNN $\langle sign \rangle \langle digit_1 \rangle \langle digit_2 \rangle$ can expand to 0\exp_stop_f: or 1\exp_stop_f:.

- `__fp_round_s:NNNw <sign> <digit1> <digit2> <more digits>;` can expand to `0\exp_stop_f::` or `1\exp_stop_f::`.
- `__fp_round_neg:NNN <sign> <digit1> <digit2>` can expand to `0\exp_stop_f:` or `1\exp_stop_f:`.

See implementation comments for details on the syntax.

```
\__fp_round:NNN
\__fp_round_to_nearest:NNN
  \_fp_round_to_nearest_ninf:NNN
  \_fp_round_to_nearest_zero:NNN
  \_fp_round_to_nearest_pinf:NNN
\__fp_round_to_ninf:NNN
\__fp_round_to_zero:NNN
\__fp_round_to_pinf:NNN
```

`__fp_round:NNN <final sign> <digit1> <digit2>`
 If rounding the number `<final sign><digit1>.<digit2>` to an integer rounds it towards zero (truncates it), this function expands to `0\exp_stop_f:`, and otherwise to `1\exp_stop_f:`. Typically used within the scope of an `__fp_int_eval:w`, to add 1 if needed, and thereby round correctly. The result depends on the rounding mode.

It is very important that `<final sign>` be the final sign of the result. Otherwise, the result would be incorrect in the case of rounding towards $-\infty$ or towards $+\infty$. Also recall that `<final sign>` is 0 for positive, and 2 for negative.

By default, the functions below return `0\exp_stop_f:`, but this is superseded by `__fp_round_return_one:`, which instead returns `1\exp_stop_f:`, expanding everything and removing `0\exp_stop_f:` in the process. In the case of rounding towards $\pm\infty$ or towards 0, this is not really useful, but it prepares us for the “round to nearest, ties to even” mode.

The “round to nearest” mode is the default. If the `<digit2>` is larger than 5, then round up. If it is less than 5, round down. If it is exactly 5, then round such that `<digit1>` plus the result is even. In other words, round up if `<digit1>` is odd.

The “round to nearest” mode has three variants, which differ in how ties are rounded: down towards $-\infty$, truncated towards 0, or up towards $+\infty$.

```
13756 \cs_new:Npn \__fp_round_return_one:
13757 { \exp_after:wN 1 \exp_after:wN \exp_stop_f: \exp:w }
13758 \cs_new:Npn \__fp_round_to_ninf:NNN #1 #2 #3
13759 {
13760   \if_meaning:w 2 #1
13761     \if_int_compare:w #3 > 0 \exp_stop_f:
13762       \__fp_round_return_one:
13763     \fi:
13764   \fi:
13765   0 \exp_stop_f:
13766 }
13767 \cs_new:Npn \__fp_round_to_zero:NNN #1 #2 #3 { 0 \exp_stop_f: }
13768 \cs_new:Npn \__fp_round_to_pinf:NNN #1 #2 #3
13769 {
13770   \if_meaning:w 0 #1
13771     \if_int_compare:w #3 > 0 \exp_stop_f:
13772       \__fp_round_return_one:
13773     \fi:
13774   \fi:
13775   0 \exp_stop_f:
13776 }
13777 \cs_new:Npn \__fp_round_to_nearest:NNN #1 #2 #3
13778 {
13779   \if_int_compare:w #3 > \c__fp_five_int
13780     \__fp_round_return_one:
13781   \else:
```

```

13782     \if_meaning:w 5 #3
13783     \if_int_odd:w #2 \exp_stop_f:
13784     \__fp_round_return_one:
13785     \fi:
13786     \fi:
13787     \fi:
13788     0 \exp_stop_f:
13789 }
13790 \cs_new:Npn \__fp_round_to_nearest_ninf:NNN #1 #2 #3
13791 {
13792     \if_int_compare:w #3 > \c__fp_five_int
13793     \__fp_round_return_one:
13794     \else:
13795     \if_meaning:w 5 #3
13796     \if_meaning:w 2 #1
13797     \__fp_round_return_one:
13798     \fi:
13799     \fi:
13800     \fi:
13801     0 \exp_stop_f:
13802 }
13803 \cs_new:Npn \__fp_round_to_nearest_zero:NNN #1 #2 #3
13804 {
13805     \if_int_compare:w #3 > \c__fp_five_int
13806     \__fp_round_return_one:
13807     \fi:
13808     0 \exp_stop_f:
13809 }
13810 \cs_new:Npn \__fp_round_to_nearest_pinf:NNN #1 #2 #3
13811 {
13812     \if_int_compare:w #3 > \c__fp_five_int
13813     \__fp_round_return_one:
13814     \else:
13815     \if_meaning:w 5 #3
13816     \if_meaning:w 0 #1
13817     \__fp_round_return_one:
13818     \fi:
13819     \fi:
13820     \fi:
13821     0 \exp_stop_f:
13822 }
13823 \cs_new_eq:NN \__fp_round:NNN \__fp_round_to_nearest:NNN

```

(End definition for __fp_round:NNN and others.)

__fp_round_s:NNNw

__fp_round_s:NNNw *<final sign>* *<digit>* *<more digits>* ;

Similar to __fp_round:NNN, but with an extra semicolon, this function expands to 0\exp_stop_f:; if rounding *<final sign>**<digit>*.*<more digits>* to an integer truncates, and to 1\exp_stop_f:; otherwise. The *<more digits>* part must be a digit, followed by something that does not overflow a \int_use:N __fp_int_eval:w construction. The only relevant information about this piece is whether it is zero or not.

```

13824 \cs_new:Npn \__fp_round_s:NNNw #1 #2 #3 #4;
13825 {
13826     \exp_after:wN \__fp_round:NNN

```

```

13827 \exp_after:wN #1
13828 \exp_after:wN #2
13829 \int_value:w \_fp_int_eval:w
13830 \if_int_odd:w 0 \if_meaning:w 0 #3 1 \fi:
13831 \if_meaning:w 5 #3 1 \fi:
13832 \exp_stop_f:
13833 \if_int_compare:w \_fp_int_eval:w #4 > 0 \exp_stop_f:
13834 1 +
13835 \fi:
13836 \fi:
13837 #3
13838 ;
13839 }

```

(End definition for `_fp_round_s:NNNw`.)

`_fp_round_digit:Nw` `\int_value:w _fp_round_digit:Nw <digit> <intexpr> ;`
This function should always be called within an `\int_value:w` or `_fp_int_eval:w` expansion; it may add an extra `_fp_int_eval:w`, which means that the integer or integer expression should not be ended with a synonym of `\relax`, but with a semi-colon for instance.

```

13840 \cs_new:Npn \_fp_round_digit:Nw #1 #2;
13841 {
13842 \if_int_odd:w \if_meaning:w 0 #1 1 \else:
13843 \if_meaning:w 5 #1 1 \else:
13844 0 \fi: \fi: \exp_stop_f:
13845 \if_int_compare:w \_fp_int_eval:w #2 > 0 \exp_stop_f:
13846 \_fp_int_eval:w 1 +
13847 \fi:
13848 \fi:
13849 #1
13850 }

```

(End definition for `_fp_round_digit:Nw`.)

`_fp_round_neg:NNN` `_fp_round_neg:NNN <final sign> <digit1> <digit2>`
`_fp_round_to_nearest_neg:NNN` This expands to `0\exp_stop_f:` or `1\exp_stop_f:` after doing the following test.
`_fp_round_to_nearest_ninf_neg:NNN` Starting from a number of the form `<final sign>0.<15 digits><digit1>` with exactly 15 (non-
`_fp_round_to_nearest_zero_neg:NNN` all-zero) digits before `<digit1>`, subtract from it `<final sign>0.0...0<digit2>`, where there
`_fp_round_to_nearest_pinf_neg:NNN` are 16 zeros. If in the current rounding mode the result should be rounded down, then
`_fp_round_to_ninf_neg:NNN` this function returns `1\exp_stop_f:`. Otherwise, *i.e.*, if the result is rounded back to
`_fp_round_to_zero_neg:NNN` the first operand, then this function returns `0\exp_stop_f:`.
`_fp_round_to_pinf_neg:NNN` It turns out that this negative “round to nearest” is identical to the positive one.
And this is the default mode.

```

13851 \cs_new_eq:NN \_fp_round_to_ninf_neg:NNN \_fp_round_to_pinf:NNN
13852 \cs_new:Npn \_fp_round_to_zero_neg:NNN #1 #2 #3
13853 {
13854 \if_int_compare:w #3 > 0 \exp_stop_f:
13855 \_fp_round_return_one:
13856 \fi:
13857 0 \exp_stop_f:
13858 }
13859 \cs_new_eq:NN \_fp_round_to_pinf_neg:NNN \_fp_round_to_ninf:NNN

```

```

13860 \cs_new_eq:NN \__fp_round_to_nearest_neg:NNN \__fp_round_to_nearest:NNN
13861 \cs_new_eq:NN \__fp_round_to_nearest_ninf_neg:NNN
13862   \__fp_round_to_nearest_pinf:NNN
13863 \cs_new:Npn \__fp_round_to_nearest_zero_neg:NNN #1 #2 #3
13864 {
13865   \if_int_compare:w #3 < \c__fp_five_int \else:
13866     \__fp_round_return_one:
13867   \fi:
13868   0 \exp_stop_f:
13869 }
13870 \cs_new_eq:NN \__fp_round_to_nearest_pinf_neg:NNN
13871   \__fp_round_to_nearest_ninf:NNN
13872 \cs_new_eq:NN \__fp_round_neg:NNN \__fp_round_to_nearest_neg:NNN

```

(End definition for __fp_round_neg:NNN and others.)

25.2 The round function

__fp_round_o:Nw First check that all arguments are floating point numbers. The `trunc`, `ceil` and `floor` functions expect one or two arguments (the second is 0 by default), and the `round` function also accepts a third argument (`nan` by default), which changes `#1` from `__fp_round_to_nearest:NNN` to one of its analogues.

```

13873 \cs_new:Npn \__fp_round_o:Nw #1
13874 {
13875   \__fp_parse_function_all_fp_o:fnw
13876   { \__fp_round_name_from_cs:N #1 }
13877   { \__fp_round_aux_o:Nw #1 }
13878 }
13879 \cs_new:Npn \__fp_round_aux_o:Nw #1#2 @
13880 {
13881   \if_case:w
13882     \__fp_int_eval:w \__fp_array_count:n {#2} \__fp_int_eval_end:
13883     \__fp_round_no_arg_o:Nw #1 \exp:w
13884   \or: \__fp_round:Nwn #1 #2 {0} \exp:w
13885   \or: \__fp_round:Nww #1 #2 \exp:w
13886   \else: \__fp_round:Nwww #1 #2 @ \exp:w
13887   \fi:
13888   \exp_after:wN \exp_end:
13889 }

```

(End definition for __fp_round_o:Nw and __fp_round_aux_o:Nw.)

__fp_round_no_arg_o:Nw

```

13890 \cs_new:Npn \__fp_round_no_arg_o:Nw #1
13891 {
13892   \cs_if_eq:NNTF #1 \__fp_round_to_nearest:NNN
13893   { \__fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 } }
13894   {
13895     \__fp_error:nffn { fp-num-args }
13896     { \__fp_round_name_from_cs:N #1 () } { 1 } { 2 }
13897   }
13898   \exp_after:wN \c_nan_fp
13899 }

```

(End definition for _fp_round_no_arg_o:Nw.)

_fp_round:Nwww Having three arguments is only allowed for round, not trunc, ceil, floor, so check for that case. If all is well, construct one of _fp_round_to_nearest:NNN, _fp_round_to_nearest_zero:NNN, _fp_round_to_nearest_ninf:NNN, _fp_round_to_nearest_pinf:NNN and act accordingly.

```

13900 \cs_new:Npn \_fp_round:Nwww #1#2 ; #3 ; \s_fp \_fp_chk:w #4#5#6 ; #7 @
13901 {
13902   \cs_if_eq:NNTF #1 \_fp_round_to_nearest:NNN
13903   {
13904     \tl_if_empty:nTF {#7}
13905     {
13906       \exp_args:Nc \_fp_round:Nww
13907       {
13908         \_fp_round_to_nearest
13909         \if_meaning:w 0 #4 _zero \else:
13910         \if_case:w #5 \exp_stop_f: _pinf \or: \else: _ninf \fi: \fi:
13911         :NNN
13912       }
13913       #2 ; #3 ;
13914     }
13915     {
13916       \_fp_error:nnnn { fp-num-args } { round () } { 1 } { 3 }
13917       \exp_after:wN \c_nan_fp
13918     }
13919   }
13920   {
13921     \_fp_error:nffn { fp-num-args }
13922     { \_fp_round_name_from_cs:N #1 () } { 1 } { 2 }
13923     \exp_after:wN \c_nan_fp
13924   }
13925 }

```

(End definition for _fp_round:Nwww.)

_fp_round_name_from_cs:N

```

13926 \cs_new:Npn \_fp_round_name_from_cs:N #1
13927 {
13928   \cs_if_eq:NNTF #1 \_fp_round_to_zero:NNN { trunc }
13929   {
13930     \cs_if_eq:NNTF #1 \_fp_round_to_ninf:NNN { floor }
13931     {
13932       \cs_if_eq:NNTF #1 \_fp_round_to_pinf:NNN { ceil }
13933       { round }
13934     }
13935   }
13936 }

```

(End definition for _fp_round_name_from_cs:N.)

_fp_round:Nww

_fp_round:Nwn

```

13937 \cs_new:Npn \_fp_round:Nww #1#2 ; #3 ;

```

```

13938 {
13939   \_fp_small_int:wTF #3; { \_fp_round:Nwn #1#2; }

```

_fp_round_normal:NwNNnw

_fp_round_normal:NnnwNNnn

_fp_round_pack:Nw

_fp_round_normal:NNwNnn

_fp_round_normal_end:wwNnn

_fp_round_special:NwwNnn

_fp_round_special_aux:Nw

```

13940     {
13941         \__fp_invalid_operation_tl_o:ff
13942         { \__fp_round_name_from_cs:N #1 }
13943         { \__fp_array_to_clist:n { #2; #3; } }
13944     }
13945 }
13946 \cs_new:Npn \__fp_round:Nwn #1 \s__fp \__fp_chk:w #2#3#4; #5
13947 {
13948     \if_meaning:w 1 #2
13949     \exp_after:wN \__fp_round_normal:NwNNnw
13950     \exp_after:wN #1
13951     \int_value:w #5
13952     \else:
13953     \exp_after:wN \__fp_exp_after_o:w
13954     \fi:
13955     \s__fp \__fp_chk:w #2#3#4;
13956 }
13957 \cs_new:Npn \__fp_round_normal:NwNNnw #1#2 \s__fp \__fp_chk:w 1#3#4#5;
13958 {
13959     \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 - #2 }
13960     \__fp_round_normal:NnnwNNnn #5 #1 #3 {#4} {#2}
13961 }
13962 \cs_new:Npn \__fp_round_normal:NnnwNNnn #1#2#3#4; #5#6
13963 {
13964     \exp_after:wN \__fp_round_normal:NNwNnn
13965     \int_value:w \__fp_int_eval:w
13966     \if_int_compare:w #2 > 0 \exp_stop_f:
13967     1 \int_value:w #2
13968     \exp_after:wN \__fp_round_pack:Nw
13969     \int_value:w \__fp_int_eval:w 1#3 +
13970     \else:
13971     \if_int_compare:w #3 > 0 \exp_stop_f:
13972     1 \int_value:w #3 +
13973     \fi:
13974     \fi:
13975     \exp_after:wN #5
13976     \exp_after:wN #6
13977     \use_none:nnnnnnn #3
13978     #1
13979     \__fp_int_eval_end:
13980     0000 0000 0000 0000 ; #6
13981 }
13982 \cs_new:Npn \__fp_round_pack:Nw #1
13983 { \if_meaning:w 2 #1 + 1 \fi: \__fp_int_eval_end: }
13984 \cs_new:Npn \__fp_round_normal:NNwNnn #1 #2
13985 {
13986     \if_meaning:w 0 #2
13987     \exp_after:wN \__fp_round_special:NwwNnn
13988     \exp_after:wN #1
13989     \fi:
13990     \__fp_pack_twice_four:wNNNNNNNN
13991     \__fp_pack_twice_four:wNNNNNNNN
13992     \__fp_round_normal_end:wwNnn
13993     ; #2

```

```

13994 }
13995 \cs_new:Npn \__fp_round_normal_end:wwNnn #1;#2;#3#4#5
13996 {
13997   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
13998   \__fp_sanitiz:Nw #3 #4 ; #1 ;
13999 }
14000 \cs_new:Npn \__fp_round_special:NwwNnn #1#2;#3;#4#5#6
14001 {
14002   \if_meaning:w 0 #1
14003     \__fp_case_return:nw
14004     { \exp_after:wN \__fp_zero_fp:N \exp_after:wN #4 }
14005   \else:
14006     \exp_after:wN \__fp_round_special_aux:Nw
14007     \exp_after:wN #4
14008     \int_value:w \__fp_int_eval:w 1
14009     \if_meaning:w 1 #1 -#6 \else: +#5 \fi:
14010   \fi:
14011 ;
14012 }
14013 \cs_new:Npn \__fp_round_special_aux:Nw #1#2;
14014 {
14015   \exp_after:wN \__fp_exp_after_o:w \exp:w \exp_end_continue_f:w
14016   \__fp_sanitiz:Nw #1#2; {1000}{0000}{0000}{0000};
14017 }

```

(End definition for __fp_round:Nww and others.)

```
14018 </initex | package>
```

26 l3fp-parse implementation

```
14019 <*initex | package>
```

```
14020 <@@=fp>
```

26.1 Work plan

The task at hand is non-trivial, and some previous failed attempts show that the code leads to unreadable logs, so we had better get it (almost) right the first time. Let us first describe our goal, then discuss the design precisely before writing any code.

In this file at least, a *floating point object* is a floating point number or tuple. This can be extended to anything that starts with `\s__fp` or `\s__fp_⟨type⟩` and ends with `;` with some internal structure that depends on the *⟨type⟩*.

```
\__fp_parse:n
```

```
\__fp_parse:n {⟨fpexpr⟩}
```

Evaluates the *floating point expression* and leaves the result in the input stream as a floating point object. This function forms the basis of almost all public `l3fp` functions. During evaluation, each token is fully `f`-expanded.

`__fp_parse_o:n` does the same but expands once after its result.

T_EXhackers note: Registers (integers, toks, etc.) are automatically unpacked, without requiring a function such as `\int_use:N`. Invalid tokens remaining after `f`-expansion lead to unrecoverable low-level T_EX errors.

(End definition for _fp_parse:n.)

\c__fp_prec_func_int Floating point expressions are composed of numbers, given in various forms, infix operators, such as +, **, or , (which joins two numbers into a list), and prefix operators, such as the unary -, functions, or opening parentheses. Here is a list of precedences which control the order of evaluation (some distinctions are irrelevant for the order of evaluation, but serve as signals), from the tightest binding to the loosest binding.

- \c__fp_prec_hatii_int 16 Function calls.
- \c__fp_prec_hat_int 13/14 Binary ** and ^ (right to left).
- \c__fp_prec_not_int 12 Unary +, -, ! (right to left).
- \c__fp_prec_times_int 10 Binary *, /, and juxtaposition (implicit *).
- \c__fp_prec_plus_int 9 Binary + and -.
- \c__fp_prec_comp_int 7 Comparisons.
- \c__fp_prec_and_int 6 Logical and, denoted by &&.
- \c__fp_prec_or_int 5 Logical or, denoted by ||.
- \c__fp_prec_quest_int 4 Ternary operator ?:, piece ?.
- \c__fp_prec_colon_int 3 Ternary operator ?:, piece :.
- \c__fp_prec_comma_int 2 Commas.
- \c__fp_prec_tuple_int 1 Place where a comma is allowed and generates a tuple.
- \c__fp_prec_end_int 0 Start and end of the expression.

```

14021 \int_const:Nn \c__fp_prec_func_int { 16 }
14022 \int_const:Nn \c__fp_prec_hatii_int { 14 }
14023 \int_const:Nn \c__fp_prec_hat_int { 13 }
14024 \int_const:Nn \c__fp_prec_not_int { 12 }
14025 \int_const:Nn \c__fp_prec_times_int { 10 }
14026 \int_const:Nn \c__fp_prec_plus_int { 9 }
14027 \int_const:Nn \c__fp_prec_comp_int { 7 }
14028 \int_const:Nn \c__fp_prec_and_int { 6 }
14029 \int_const:Nn \c__fp_prec_or_int { 5 }
14030 \int_const:Nn \c__fp_prec_quest_int { 4 }
14031 \int_const:Nn \c__fp_prec_colon_int { 3 }
14032 \int_const:Nn \c__fp_prec_comma_int { 2 }
14033 \int_const:Nn \c__fp_prec_tuple_int { 1 }
14034 \int_const:Nn \c__fp_prec_end_int { 0 }

```

(End definition for \c__fp_prec_func_int and others.)

26.1.1 Storing results

The main question in parsing expressions expandably is to decide where to put the intermediate results computed for various subexpressions.

One option is to store the values at the start of the expression, and carry them together as the first argument of each macro. However, we want to **f**-expand tokens one by one in the expression (as `\int_eval:n` does), and with this approach, expanding the next unread token forces us to jump with `\exp_after:wN` over every value computed earlier in the expression. With this approach, the run-time grows at least quadratically in the length of the expression, if not as its cube (inserting the `\exp_after:wN` is tricky and slow).

A second option is to place those values at the end of the expression. Then expanding the next unread token is straightforward, but this still hits a performance issue: for long expressions we would be reaching all the way to the end of the expression at every step of the calculation. The run-time is again quadratic.

A variation of the above attempts to place the intermediate results which appear when computing a parenthesized expression near the closing parenthesis. This still lets us expand tokens as we go, and avoids performance problems as long as there are enough parentheses. However, it would be better to avoid requiring the closing parenthesis to be present as soon as the corresponding opening parenthesis is read: the closing parenthesis may still be hidden in a macro yet to be expanded.

Hence, we need to go for some fine expansion control: the result is stored *before* the start!

Let us illustrate this idea in a simple model: adding positive integers which may be resulting from the expansion of macros, or may be values of registers. Assume that one number, say, 12345, has already been found, and that we want to parse the next number. The current status of the code may look as follows.

```
\exp_after:wN \add:ww \int_value:w 12345 \exp_after:wN ;  
\exp:w \operand:w {stuff}
```

One step of expansion expands `\exp_after:wN`, which triggers the primitive `\int_value:w`, which reads the five digits we have already found, 12345. This integer is unfinished, causing the second `\exp_after:wN` to expand, and to trigger the construction `\exp:w`, which expands `\operand:w`, defined to read what follows and make a number out of it, then leave `\exp_end:`, the number, and a semicolon in the input stream. Once `\operand:w` is done expanding, we obtain essentially

```
\exp_after:wN \add:ww \int_value:w 12345 ;  
\exp:w \exp_end: 333444 ;
```

where in fact `\exp_after:wN` has already been expanded, `\int_value:w` has already seen 12345, and `\exp:w` is still looking for a number. It finds `\exp_end:`, hence expands to nothing. Now, `\int_value:w` sees the `;`, which cannot be part of a number. The expansion stops, and we are left with

```
\add:ww 12345 ; 333444 ;
```

which can safely perform the addition by grabbing two arguments delimited by `;`.

If we were to continue parsing the expression, then the following number should also be cleaned up before the next use of a binary operation such as `\add:ww`. Just like `\int_value:w 12345 \exp_after:wN ;` expanded what follows once, we need `\add:ww` to

do the calculation, and in the process to expand the following once. This is also true in our real application: all the functions of the form `__fp..._o:ww` expand what follows once. This comes at the cost of leaving tokens in the input stack, and we need to be careful not to waste this memory. All of our discussion above is nice but simplistic, as operations should not simply be performed in the order they appear.

26.1.2 Precedence and infix operators

The various operators we will encounter have different precedences, which influence the order of calculations: $1 + 2 \times 3 = 1 + (2 \times 3)$ because \times has a higher precedence than $+$. The true analog of our macro `\operand:w` must thus take care of that. When looking for an operand, it needs to perform calculations until reaching an operator which has lower precedence than the one which called `\operand:w`. This means that `\operand:w` must know what the previous binary operator is, or rather, its precedence: we thus rename it `\operand:Nw`. Let us describe as an example how we plan to do the calculation $41 - 2^3 * 4 + 5$. More precisely we describe how to perform the first operation in this expression. Here, we abuse notations: the first argument of `\operand:Nw` should be an integer constant (`\c__fp_prec_plus_int, ...`) equal to the precedence of the given operator, not directly the operator itself.

- Clean up 41 and find $-$. We call `\operand:Nw -` to find the second operand.
- Clean up 2 and find \wedge .
- Compare the precedences of $-$ and \wedge . Since the latter is higher, we need to compute the exponentiation. For this, find the second operand with a nested call to `\operand:Nw \wedge`.
- Clean up 3 and find $*$.
- Compare the precedences of \wedge and $*$. Since the former is higher, `\operand:Nw \wedge` has found the second operand of the exponentiation, which is computed: $2^3 = 8$.
- We now have $41 - 8 * 4 + 5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 8?
- Compare the precedences of $-$ and $*$. Since the latter is higher, we are not done with 8. Call `\operand:Nw *` to find the second operand of the multiplication.
- Clean up 4, and find $+$.
- Compare the precedences of $*$ and $+$. Since the former is higher, `\operand:Nw *` has found the second operand of the multiplication, which is computed: $8 * 4 = 32$.
- We now have $41 - 32 + 5$, and `\operand:Nw -` is still looking for a second operand for the subtraction. Is it 32?
- Compare the precedences of $-$ and $+$. Since they are equal, `\operand:Nw -` has found the second operand for the subtraction, which is computed: $41 - 32 = 9$.
- We now have $9 + 5$.

The procedure above stops short of performing all computations, but adding a surrounding call to `\operand:Nw` with a very low precedence ensures that all computations are performed before `\operand:Nw` is done. Adding a trailing marker with the same very low precedence prevents the surrounding `\operand:Nw` from going beyond the marker.

The pattern above to find an operand for a given operator, is to find one number and the next operator, then compare precedences to know if the next computation should be done. If it should, then perform it after finding its second operand, and look at the next operator, then compare precedences to know if the next computation should be done. This continues until we find that the next computation should not be done. Then, we stop.

We are now ready to get a bit more technical and describe which of the `l3fp-parse` functions correspond to each step above.

First, `_fp_parse_operand:Nw` is the `\operand:Nw` function above, with small modifications due to expansion issues discussed later. We denote by $\langle precedence \rangle$ the argument of `_fp_parse_operand:Nw`, that is, the precedence of the binary operator whose operand we are trying to find. The basic action is to read numbers from the input stream. This is done by `_fp_parse_one:Nw`. A first approximation of this function is that it reads one $\langle number \rangle$, performing no computation, and finds the following binary $\langle operator \rangle$. Then it expands to

$$\langle number \rangle \\ _fp_parse_infix_ \langle operator \rangle : N \langle precedence \rangle$$

expanding the `infix` auxiliary before leaving the above in the input stream.

We now explain the `infix` auxiliaries. We need some flexibility in how we treat the case of equal precedences: most often, the first operation encountered should be performed, such as $1-2-3$ being computed as $(1-2)-3$, but 2^3^4 should be evaluated as $2^{(3^4)}$ instead. For this reason, and to support the equivalence between `**` and `^` more easily, each binary operator is converted to a control sequence `_fp_parse_infix_ \langle operator \rangle : N` when it is encountered for the first time. Instead of passing both precedences to a test function to do the comparison steps above, we pass the $\langle precedence \rangle$ (of the earlier operator) to the `infix` auxiliary for the following $\langle operator \rangle$, to know whether to perform the computation of the $\langle operator \rangle$. If it should not be performed, the `infix` auxiliary expands to

$$@ _use_none : n _fp_parse_infix_ \langle operator \rangle : N$$

and otherwise it calls `_fp_parse_operand:Nw` with the precedence of the $\langle operator \rangle$ to find its second operand $\langle number_2 \rangle$ and the next $\langle operator_2 \rangle$, and expands to

$$@ _fp_parse_apply_binary : NwNwN \\ \langle operator \rangle \langle number_2 \rangle \\ @ _fp_parse_infix_ \langle operator_2 \rangle : N$$

The `infix` function is responsible for comparing precedences, but cannot directly call the computation functions, because the first operand $\langle number \rangle$ is before the `infix` function in the input stream. This is why we stop the expansion here and give control to another function to close the loop.

A definition of `_fp_parse_operand:Nw \langle precedence \rangle` with some of the expansion control removed is

```

\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN <precedence>
\exp:w \exp_end_continue_f:w
\__fp_parse_one:Nw <precedence>

```

This expands `__fp_parse_one:Nw <precedence>` completely, which finds a number, wraps the next `<operator>` into an infix function, feeds this function the `<precedence>`, and expands it, yielding either

```

\__fp_parse_continue:NwN <precedence>
<number> @
\use_none:n \__fp_parse_infix_<operator>:N

```

or

```

\__fp_parse_continue:NwN <precedence>
<number> @
\__fp_parse_apply_binary:NwNwN
<operator> <number2>
@ \__fp_parse_infix_<operator2>:N

```

The definition of `__fp_parse_continue:NwN` is then very simple:

```

\cs_new:Npn \__fp_parse_continue:NwN #1#2@#3 { #3 #1 #2 @ }

```

In the first case, `#3` is `\use_none:n`, yielding

```

\use_none:n <precedence> <number> @
\__fp_parse_infix_<operator>:N

```

then `<number> @ __fp_parse_infix_<operator>:N`. In the second case, `#3` is `__fp_parse_apply_binary:NwNwN`, whose role is to compute `<number> <operator> <number2>` and to prepare for the next comparison of precedences: first we get

```

\__fp_parse_apply_binary:NwNwN
<precedence> <number> @
<operator> <number2>
@ \__fp_parse_infix_<operator2>:N

```

then

```

\exp_after:wN \__fp_parse_continue:NwN
\exp_after:wN <precedence>
\exp:w \exp_end_continue_f:w
\__fp_<operator>_o:ww <number> <number2>
\exp:w \exp_end_continue_f:w
\__fp_parse_infix_<operator2>:N <precedence>

```

where `__fp_<operator>_o:ww` computes `<number> <operator> <number2>` and expands after the result, thus triggers the comparison of the precedence of the `<operator2>` and the `<precedence>`, continuing the loop.

We have introduced the most important functions here, and the next few paragraphs we describe various subtleties.

26.1.3 Prefix operators, parentheses, and functions

Prefix operators (unary `-`, `+`, `!`) and parentheses are taken care of by the same mechanism, and functions (`sin`, `exp`, etc.) as well. Finding the argument of the unary `-`, for instance, is very similar to grabbing the second operand of a binary infix operator, with a subtle precedence explained below. Once that operand is found, the operator can be applied to it (for the unary `-`, this simply flips the sign). A left parenthesis is just a prefix operator with a very low precedence equal to that of the closing parenthesis (which is treated as an infix operator, since it normally appears just after numbers), so that all computations are performed until the closing parenthesis. The prefix operator associated to the left parenthesis does not alter its argument, but it removes the closing parenthesis (with some checks).

Prefix operators are the reason why we only summarily described the function `_fp_parse_one:Nw` earlier. This function is responsible for reading in the input stream the first possible *number* and the next infix *operator*. If what follows `_fp_parse_one:Nw` *precedence* is a prefix operator, then we must find the operand of this prefix operator through a nested call to `_fp_parse_operand:Nw` with the appropriate precedence, then apply the operator to the operand found to yield the result of `_fp_parse_one:Nw`. So far, all is simple.

The unary operators `+`, `-`, `!` complicate things a little bit: `-3**2` should be $-(3^2) = -9$, and not $(-3)^2 = 9$. This would easily be done by giving `-` a lower precedence, equal to that of the infix `+` and `-`. Unfortunately, this fails in cases such as `3**-2*4`, yielding $3^{-2 \times 4}$ instead of the correct $3^{-2} \times 4$. A second attempt would be to call `_fp_parse_operand:Nw` with the *precedence* of the previous operator, but `0>-2+3` is then parsed as `0>-(2+3)`: the addition is performed because it binds more tightly than the comparison which precedes `-`. The correct approach is for a unary `-` to perform operations whose precedence is greater than both that of the previous operation, and that of the unary `-` itself. The unary `-` is given a precedence higher than multiplication and division. This does not lead to any surprising result, since $-(x/y) = (-x)/y$ and similarly for multiplication, and it reduces the number of nested calls to `_fp_parse_operand:Nw`.

Functions are implemented as prefix operators with very high precedence, so that their argument is the first number that can possibly be built.

Note that contrarily to the *infix* functions discussed earlier, the *prefix* functions do perform tests on the previous *precedence* to decide whether to find an argument or not, since we know that we need a number, and must never stop there.

26.1.4 Numbers and reading tokens one by one

So far, we have glossed over one important point: what is a “number”? A number is typically given in the form *significand**e**exponent*, where the *significand* is any non-empty string composed of decimal digits and at most one decimal separator (a period), the exponent “*e**exponent*” is optional and is composed of an exponent mark *e* followed by a possibly empty string of signs `+` or `-` and a non-empty string of decimal digits. The *significand* can also be an integer, dimension, skip, or muskip variable, in which case dimensions are converted from points (or mu units) to floating points, and the *exponent* can also be an integer variable. Numbers can also be given as floating point variables, or as named constants such as `nan`, `inf` or `pi`. We may add more types in the future.

When `_fp_parse_one:Nw` is looking for a “number”, here is what happens.

- If the next token is a control sequence with the meaning of `\scan_stop:`, it can be: `\s__fp`, in which case our job is done, as what follows is an internal floating point number, or `\s__fp_mark`, in which case the expression has come to an early end, as we are still looking for a number here, or something else, in which case we consider the control sequence to be a bad variable resulting from c-expansion.
- If the next token is a control sequence with a different meaning, we assume that it is a register, unpack it with `\tex_the:D`, and use its value (in `pt` for dimensions and `mu` for muskips) as the *significand* of a number: we look for an exponent.
- If the next token is a digit, we remove any leading zeros, then read a significand larger than 1 if the next character is a digit, read a significand smaller than 1 if the next character is a period, or we have found a significand equal to 0 otherwise, and look for an exponent.
- If the next token is a letter, we collect more letters until the first non-letter: the resulting word may denote a function such as `asin`, a constant such as `pi` or be unknown. In the first case, we call `__fp_parse_operand:Nw` to find the argument of the function, then apply the function, before declaring that we are done. Otherwise, we are done, either with the value of the constant, or with the value `nan` for unknown words.
- If the next token is anything else, we check whether it is a known prefix operator, in which case `__fp_parse_operand:Nw` finds its operand. If it is not known, then either a number is missing (if the token is a known infix operator) or the token is simply invalid in floating point expressions.

Once a number is found, `__fp_parse_one:Nw` also finds an infix operator. This goes as follows.

- If the next token is a control sequence, it could be the special marker `\s__fp_mark`, and otherwise it is a case of juxtaposing numbers, such as `2\c_zero_int`, with an implied multiplication.
- If the next token is a letter, it is also a case of juxtaposition, as letters cannot be proper infix operators.
- Otherwise (including in the case of digits), if the token is a known infix operator, the appropriate `__fp_infix_<operator>:N` function is built, and if it does not exist, we complain. In particular, the juxtaposition `\c_zero_int 2` is disallowed.

In the above, we need to test whether a character token `#1` is a digit:

```
\if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
  is a digit
\else:
  not a digit
\fi:
```

To exclude 0, replace 9 by 10. The use of `\token_to_str:N` ensures that a digit with any catcode is detected. To test if a character token is a letter, we need to work with its character code, testing if ‘`#1`’ lies in [65, 90] (uppercase letters) or [97, 112] (lowercase letters)

```

\if_int_compare:w \__fp_int_eval:w
  ( '#1 \if_int_compare:w '#1 > 'Z - 32 \fi: ) / 26 = 3 \exp_stop_f:
  is a letter
\else:
  not a letter
\fi:

```

At all steps, we try to accept all category codes: when #1 is kept to be used later, it is almost always converted to category code other through `\token_to_str:N`. More precisely, catcodes {3, 6, 7, 8, 11, 12} should work without trouble, but not {1, 2, 4, 10, 13}, and of course {0, 5, 9} cannot become tokens.

Floating point expressions should behave as much as possible like ε -TeX-based integer expressions and dimension expressions. In particular, `f`-expansion should be performed as the expression is read, token by token, forcing the expansion of protected macros, and ignoring spaces. One advantage of expanding at every step is that restricted expandable functions can then be used in floating point expressions just as they can be in other kinds of expressions. Problematically, spaces stop `f`-expansion: for instance, the macro `\X` below would not be expanded if we simply performed `f`-expansion.

```

\DeclareDocumentCommand {\test} {m} { \fp_eval:n {#1} }
\ExplSyntaxOff
\test { 1 + \X }

```

Of course, spaces typically do not appear in a code setting, but may very easily come in document-level input, from which some expressions may come. To avoid this problem, at every step, we do essentially what `\use:f` would do: take an argument, put it back in the input stream, then `f`-expand it. This is not a complete solution, since a macro's expansion could contain leading spaces which would stop the `f`-expansion before further macro calls are performed. However, in practice it should be enough: in particular, floating point numbers are correctly expanded to the underlying `\s__fp ...` structure. The `f`-expansion is performed by `__fp_parse_expand:w`.

26.2 Main auxiliary functions

```

\__fp_parse_operand:Nw \exp:w \__fp_parse_operand:Nw <precedence> \__fp_parse_expand:w
Reads the "...", performing every computation with a precedence higher than
<precedence>, then expands to

```

```

<result> @ \__fp_parse_infix_<operation>:N ...

```

where the `<operation>` is the first operation with a lower precedence, possibly `end`, and the `"..."` start just after the `<operation>`.

(End definition for `__fp_parse_operand:Nw`.)

```

\__fp_parse_infix_+:N \__fp_parse_infix_+:N <precedence> ...
If + has a precedence higher than the <precedence>, cleans up a second <operand> and
finds the <operation_2> which follows, and expands to

```

```

@ \__fp_parse_apply_binary:NwNw + <operand> @ \__fp_parse_infix_<operation_2>:N
...

```

Otherwise expands to

```
@ \use_none:n \__fp_parse_infix_+:N ...
```

A similar function exists for each infix operator.

(End definition for __fp_parse_infix_+:N.)

```
\__fp_parse_one:Nw \__fp_parse_one:Nw <precedence> ...
```

Cleans up one or two operands depending on how the precedence of the next operation compares to the *<precedence>*. If the following *<operation>* has a precedence higher than *<precedence>*, expands to

```
<operand1> @ \__fp_parse_apply_binary:NwNwN <operation> <operand2> @  
\__fp_parse_infix_<operation2>:N ...
```

and otherwise expands to

```
<operand> @ \use_none:n \__fp_parse_infix_<operation>:N ...
```

(End definition for __fp_parse_one:Nw.)

26.3 Helpers

```
\__fp_parse_expand:w \exp:w \__fp_parse_expand:w <tokens>
```

This function must always come within a `\exp:w` expansion. The *<tokens>* should be the part of the expression that we have not yet read. This requires in particular closing all conditionals properly before expanding.

```
14035 \cs_new:Npn \__fp_parse_expand:w #1 { \exp_end_continue_f:w #1 }
```

(End definition for __fp_parse_expand:w.)

```
\_fp_parse_return_semicolon:w
```

This very odd function swaps its position with the following `\fi:` and removes `__fp_parse_expand:w` normally responsible for expansion. That turns out to be useful.

```
14036 \cs_new:Npn \_fp_parse_return_semicolon:w  
14037 #1 \fi: \__fp_parse_expand:w { \fi: ; #1 }
```

(End definition for _fp_parse_return_semicolon:w.)

```
\__fp_parse_digits_vii:N  
\__fp_parse_digits_vi:N  
\__fp_parse_digits_v:N  
\__fp_parse_digits_iv:N  
\__fp_parse_digits_iii:N  
\__fp_parse_digits_ii:N  
\__fp_parse_digits_i:N  
\__fp_parse_digits_:N
```

These functions must be called within an `\int_value:w` or `__fp_int_eval:w` construction. The first token which follows must be `f`-expanded prior to calling those functions. The functions read tokens one by one, and output digits into the input stream, until meeting a non-digit, or up to a number of digits equal to their index. The full expansion is

```
<digits> ; <filling 0> ; <length>
```

where *<filling 0>* is a string of zeros such that *<digits>* *<filling 0>* has the length given by the index of the function, and *<length>* is the number of zeros in the *<filling 0>* string. Each function puts a digit into the input stream and calls the next function, until we find a non-digit. We are careful to pass the tested tokens through `\token_to_str:N` to normalize their category code.

```
14038 \cs_set_protected:Npn \__fp_tmp:w #1 #2 #3  
14039 {  
14040 \cs_new:cpn { \__fp_parse_digits_ #1 :N } ##1  
14041 {
```



```

14042     \if_int_compare:w 9 < 1 \token_to_str:N ##1 \exp_stop_f:
14043     \token_to_str:N ##1 \exp_after:wN #2 \exp:w
14044     \else:
14045     \__fp_parse_return_semicolon:w #3 ##1
14046     \fi:
14047     \__fp_parse_expand:w
14048   }
14049 }
14050 \__fp_tmp:w {vii} \__fp_parse_digits_vi:N { 0000000 ; 7 }
14051 \__fp_tmp:w {vi} \__fp_parse_digits_v:N { 000000 ; 6 }
14052 \__fp_tmp:w {v} \__fp_parse_digits_iv:N { 00000 ; 5 }
14053 \__fp_tmp:w {iv} \__fp_parse_digits_iii:N { 0000 ; 4 }
14054 \__fp_tmp:w {iii} \__fp_parse_digits_ii:N { 000 ; 3 }
14055 \__fp_tmp:w {ii} \__fp_parse_digits_i:N { 00 ; 2 }
14056 \__fp_tmp:w {i} \__fp_parse_digits_:N { 0 ; 1 }
14057 \cs_new:Npn \__fp_parse_digits_:N { ; ; 0 }

```

(End definition for `__fp_parse_digits_vii:N` and others.)

26.4 Parsing one number

`__fp_parse_one:Nw` This function finds one number, and packs the symbol which follows in an `__fp_parse_infix_...` csname. #1 is the previous *<precedence>*, and #2 the first token of the operand. We distinguish four cases: #2 is equal to `\scan_stop:` in meaning, #2 is a different control sequence, #2 is a digit, and #2 is something else (this last case is split further later). Despite the earlier `f`-expansion, #2 may still be expandable if it was protected by `\exp_not:N`, as may happen with the L^AT_EX 2_ε command `\protect`. Using a well placed `\reverse_if:N`, this case is sent to `__fp_parse_one_fp:NN` which deals with it robustly.

```

14058 \cs_new:Npn \__fp_parse_one:Nw #1 #2
14059 {
14060   \if_catcode:w \scan_stop: \exp_not:N #2
14061   \exp_after:wN \if_meaning:w \exp_not:N #2 #2 \else:
14062   \exp_after:wN \reverse_if:N
14063   \fi:
14064   \if_meaning:w \scan_stop: #2
14065   \exp_after:wN \exp_after:wN
14066   \exp_after:wN \__fp_parse_one_fp:NN
14067   \else:
14068   \exp_after:wN \exp_after:wN
14069   \exp_after:wN \__fp_parse_one_register:NN
14070   \fi:
14071   \else:
14072   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
14073   \exp_after:wN \exp_after:wN
14074   \exp_after:wN \__fp_parse_one_digit:NN
14075   \else:
14076   \exp_after:wN \exp_after:wN
14077   \exp_after:wN \__fp_parse_one_other:NN
14078   \fi:
14079   \fi:
14080   #1 #2
14081 }

```

(End definition for _fp_parse_one:Nw.)

_fp_parse_one_fp:NN
_fp_exp_after_mark_f:nw
_fp_exp_after_?_f:nw

This function receives a $\langle precedence \rangle$ and a control sequence equal to \scan_stop: in meaning. There are three cases.

- \s_fp starts a floating point number, and we call _fp_exp_after_f:nw, which f-expands after the floating point.
- \s_fp_mark is a premature end, we call _fp_exp_after_mark_f:nw, which triggers an fp-early-end error.
- For a control sequence not containing \s_fp, we call _fp_exp_after_?_f:nw, causing a bad-variable error.

This scheme is extensible: additional types can be added by starting the variables with a scan mark of the form \s_fp_⟨type⟩ and defining _fp_exp_after_⟨type⟩_f:nw. In all cases, we make sure that the second argument of _fp_parse_infix:NN is correctly expanded. A special case only enabled in L^AT_EX 2_ε is that if \protect is encountered then the error message mentions the control sequence which follows it rather than \protect itself. The test for L^AT_EX 2_ε uses \@unexpandable@protect rather than \protect because \protect is often \scan_stop: hence “does not exist”.

```

14082 \cs_new:Npn \_fp_parse_one_fp:NN #1
14083 {
14084   \_fp_exp_after_any_f:nw
14085   {
14086     \exp_after:wN \_fp_parse_infix:NN
14087     \exp_after:wN #1 \exp:w \_fp_parse_expand:w
14088   }
14089 }
14090 \cs_new:Npn \_fp_exp_after_mark_f:nw #1
14091 {
14092   \int_case:nnF { \exp_after:wN \use_i:nnn \use_none:nnn #1 }
14093   {
14094     \c\_fp_prec_comma_int { }
14095     \c\_fp_prec_tuple_int { }
14096     \c\_fp_prec_end_int
14097     {
14098       \exp_after:wN \c\_fp_empty_tuple_fp
14099       \exp:w \exp_end_continue_f:w
14100     }
14101   }
14102   {
14103     \_kernel_msg_expandable_error:nn { kernel } { fp-early-end }
14104     \exp_after:wN \c\_nan_fp \exp:w \exp_end_continue_f:w
14105   }
14106   #1
14107 }
14108 \cs_new:cpn { \_fp_exp_after_?_f:nw } #1#2
14109 {
14110   \_kernel_msg_expandable_error:nnn { kernel } { bad-variable }
14111   {#2}
14112   \exp_after:wN \c\_nan_fp \exp:w \exp_end_continue_f:w #1
14113 }
14114 (*package)

```

```

14115 \cs_set_protected:Npn \__fp_tmp:w #1
14116 {
14117   \cs_if_exist:NT #1
14118   {
14119     \cs_gset:cpn { __fp_exp_after_?_f:nw } ##1##2
14120     {
14121       \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w ##1
14122       \str_if_eq:nnTF {##2} { \protect }
14123       {
14124         \cs_if_eq:NNTF ##2 #1 { \use_i:nn } { \use:n }
14125         {
14126           \__kernel_msg_expandable_error:nnn { kernel }
14127           { fp-robust-cmd }
14128         }
14129       }
14130       {
14131         \__kernel_msg_expandable_error:nnn { kernel }
14132         { bad-variable } {##2}
14133       }
14134     }
14135   }
14136 }
14137 \exp_args:Nc \__fp_tmp:w { @unexpandable@protect }
14138 </package>

```

(End definition for __fp_parse_one_fp:NN, __fp_exp_after_mark_f:nw, and __fp_exp_after_?_f:nw.)

```

\__fp_parse_one_register:NN
  \__fp_parse_one_register_aux:Nw
\__fp_parse_one_register_auxii:wwwNw
  \__fp_parse_one_register_int:www
  \__fp_parse_one_register_mu:www
  \__fp_parse_one_register_dim:ww

```

This is called whenever #2 is a control sequence other than `\scan_stop:` in meaning. We special-case `\wd`, `\ht`, `\dp` (see later) and otherwise assume that it is a register, but carefully unpack it with `\tex_the:D` within braces. First, we find the exponent following #2. Then we unpack #2 with `\tex_the:D`, and the `auxii` auxiliary distinguishes integer registers from dimensions/skips from muskips, according to the presence of a period and/or of `pt`. For integers, simply convert $\langle value \rangle e \langle exponent \rangle$ to a floating point number with `__fp_parse:n` (this is somewhat wasteful). For other registers, the decimal rounding provided by `TeX` does not accurately represent the binary value that it manipulates, so we extract this binary value as a number of scaled points with `\int_value:w \dim_to_decimal_in_sp:n { \langle decimal value \rangle pt }`, and use an auxiliary of `\dim_to_fp:n`, which performs the multiplication by 2^{-16} , correctly rounded.

```

14139 \cs_new:Npn \__fp_parse_one_register:NN #1#2
14140 {
14141   \exp_after:wN \__fp_parse_infix_after_operand:NwN
14142   \exp_after:wN #1
14143   \exp:w \exp_end_continue_f:w
14144   \__fp_parse_one_register_special:N #2
14145   \exp_after:wN \__fp_parse_one_register_aux:Nw
14146   \exp_after:wN #2
14147   \int_value:w
14148   \exp_after:wN \__fp_parse_exponent:N
14149   \exp:w \__fp_parse_expand:w
14150 }
14151 \cs_new:Npx \__fp_parse_one_register_aux:Nw #1
14152 {
14153   \exp_not:n

```

```

14154     {
14155       \exp_after:wN \use:nn
14156       \exp_after:wN \__fp_parse_one_register_auxii:wwwNw
14157     }
14158     \exp_not:N \exp_after:wN { \exp_not:N \tex_the:D #1 }
14159     ; \exp_not:N \__fp_parse_one_register_dim:ww
14160     \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_mu:www
14161     . \tl_to_str:n { pt } ; \exp_not:N \__fp_parse_one_register_int:www
14162     \exp_not:N \q_stop
14163   }
14164   \exp_args:Nno \use:nn
14165   { \cs_new:Npn \__fp_parse_one_register_auxii:wwwNw #1 . #2 }
14166   { \tl_to_str:n { pt } #3 ; #4#5 \q_stop }
14167   { #4 #1.#2; }
14168   \exp_args:Nno \use:nn
14169   { \cs_new:Npn \__fp_parse_one_register_mu:www #1 }
14170   { \tl_to_str:n { mu } ; #2 ; }
14171   { \__fp_parse_one_register_dim:ww #1 ; }
14172   \cs_new:Npn \__fp_parse_one_register_int:www #1; #2.; #3;
14173   { \__fp_parse:n { #1 e #3 } }
14174   \cs_new:Npn \__fp_parse_one_register_dim:ww #1; #2;
14175   {
14176     \exp_after:wN \__fp_from_dim_test:ww
14177     \int_value:w #2 \exp_after:wN ,
14178     \int_value:w \dim_to_decimal_in_sp:n { #1 pt } ;
14179   }

```

(End definition for `__fp_parse_one_register:NN` and others.)

`__fp_parse_one_register_special:N`
`__fp_parse_one_register_math:NNw`
`__fp_parse_one_register_wd:w`
`__fp_parse_one_register_wd:Nw`

The `\wd`, `\dp`, `\ht` primitives expect an integer argument. We abuse the exponent parser to find the integer argument: simply include the exponent marker `e`. Once that “exponent” is found, use `\tex_the:D` to find the box dimension and then copy what we did for dimensions.

```

14180 \cs_new:Npn \__fp_parse_one_register_special:N #1
14181 {
14182   \if_meaning:w \box_wd:N #1 \__fp_parse_one_register_wd:w \fi:
14183   \if_meaning:w \box_ht:N #1 \__fp_parse_one_register_wd:w \fi:
14184   \if_meaning:w \box_dp:N #1 \__fp_parse_one_register_wd:w \fi:
14185   \if_meaning:w \infty #1
14186     \__fp_parse_one_register_math:NNw \infty #1
14187   \fi:
14188   \if_meaning:w \pi #1
14189     \__fp_parse_one_register_math:NNw \pi #1
14190   \fi:
14191 }
14192 \cs_new:Npn \__fp_parse_one_register_math:NNw
14193 #1#2#3#4 \__fp_parse_expand:w
14194 {
14195   #3
14196   \str_if_eq:nnTF {#1} {#2}
14197   {
14198     \__kernel_msg_expandable_error:nnn
14199     { kernel } { fp-infty-pi } {#1}
14200     \c_nan_fp

```

```

14201     }
14202     { #4 \__fp_parse_expand:w }
14203   }
14204   \cs_new:Npn \__fp_parse_one_register_wd:w
14205     #1#2 \exp_after:wN #3#4 \__fp_parse_expand:w
14206   {
14207     #1
14208     \exp_after:wN \__fp_parse_one_register_wd:Nw
14209     #4 \__fp_parse_expand:w e
14210   }
14211   \cs_new:Npn \__fp_parse_one_register_wd:Nw #1#2 ;
14212   {
14213     \exp_after:wN \__fp_from_dim_test:ww
14214     \exp_after:wN 0 \exp_after:wN ,
14215     \int_value:w \dim_to_decimal_in_sp:n { #1 #2 } ;
14216   }

```

(End definition for __fp_parse_one_register_special:N and others.)

__fp_parse_one_digit:NN A digit marks the beginning of an explicit floating point number. Once the number is found, we catch the case of overflow and underflow with __fp_sanitize:wN, then __fp_parse_infix_after_operand:NwN expands __fp_parse_infix:NN after the number we find, to wrap the following infix operator as required. Finding the number itself begins by removing leading zeros: further steps are described later.

```

14217   \cs_new:Npn \__fp_parse_one_digit:NN #1
14218   {
14219     \exp_after:wN \__fp_parse_infix_after_operand:NwN
14220     \exp_after:wN #1
14221     \exp:w \exp_end_continue_f:w
14222     \exp_after:wN \__fp_sanitize:wN
14223     \int_value:w \__fp_int_eval:w 0 \__fp_parse_trim_zeros:N
14224   }

```

(End definition for __fp_parse_one_digit:NN.)

__fp_parse_one_other:NN For this function, #2 is a character token which is not a digit. If it is an ASCII letter, __fp_parse_letters:N beyond this one and give the result to __fp_parse_word:Nw. Otherwise, the character is assumed to be a prefix operator, and we build __fp_parse_prefix_{operator}:Nw.

```

14225   \cs_new:Npn \__fp_parse_one_other:NN #1 #2
14226   {
14227     \if_int_compare:w
14228       \__fp_int_eval:w
14229       ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
14230     = 3 \exp_stop_f:
14231     \exp_after:wN \__fp_parse_word:Nw
14232     \exp_after:wN #1
14233     \exp_after:wN #2
14234     \exp:w \exp_after:wN \__fp_parse_letters:N
14235     \exp:w
14236   \else:
14237     \exp_after:wN \__fp_parse_prefix:NNN
14238     \exp_after:wN #1
14239     \exp_after:wN #2

```

```

14240     \cs:w
14241     __fp_parse_prefix_ \token_to_str:N #2 :Nw
14242     \exp_after:wN
14243     \cs_end:
14244     \exp:w
14245     \fi:
14246     \__fp_parse_expand:w
14247 }

```

(End definition for __fp_parse_one_other:NN.)

__fp_parse_word:Nw
__fp_parse_letters:N

Finding letters is a simple recursion. Once __fp_parse_letters:N has done its job, we try to build a control sequence from the word #2. If it is a known word, then the corresponding action is taken, and otherwise, we complain about an unknown word, yield \c_nan_fp, and look for the following infix operator. Note that the unknown word could be a mistyped function as well as a mistyped constant, so there is no way to tell whether to look for arguments; we do not. The standard requires “inf” and “infinity” and “nan” to be recognized regardless of case, but we probably don’t want to allow every l3fp word to have an arbitrary mixture of lower and upper case, so we test and use a differently-named control sequence.

```

14248 \cs_new:Npn \__fp_parse_word:Nw #1#2;
14249 {
14250     \cs_if_exist_use:cF { __fp_parse_word_#2:N }
14251     {
14252         \cs_if_exist_use:cF
14253         { __fp_parse_caseless_ \str_fold_case:n {#2} :N }
14254         {
14255             \__kernel_msg_expandable_error:nnn
14256             { kernel } { unknown-fp-word } {#2}
14257             \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
14258             \__fp_parse_infix:NN
14259         }
14260     }
14261     #1
14262 }
14263 \cs_new:Npn \__fp_parse_letters:N #1
14264 {
14265     \exp_end_continue_f:w
14266     \if_int_compare:w
14267     \if_catcode:w \scan_stop: \exp_not:N #1
14268     0
14269     \else:
14270     \__fp_int_eval:w
14271     ( '#1 \if_int_compare:w '#1 > 'Z - 32 \fi: ) / 26
14272     \fi:
14273     = 3 \exp_stop_f:
14274     \exp_after:wN #1
14275     \exp:w \exp_after:wN \__fp_parse_letters:N
14276     \exp:w
14277     \else:
14278     \__fp_parse_return_semicolon:w #1
14279     \fi:
14280     \__fp_parse_expand:w
14281 }

```

(End definition for `_fp_parse_word:Nw` and `_fp_parse_letters:N`.)

`_fp_parse_prefix:NNN` For this function, #1 is the previous *<precedence>*, #2 is the operator just seen, and #3 is a control sequence which implements the operator if it is a known operator. If this control sequence is `\scan_stop:`, then the operator is in fact unknown. Either the expression is missing a number there (if the operator is valid as an infix operator), and we put `nan`, wrapping the infix operator in a `csname` as appropriate, or the character is simply invalid in floating point expressions, and we continue looking for a number, starting again from `_fp_parse_one:Nw`.

`_fp_parse_prefix_unknown:NNN`

```

14282 \cs_new:Npn \_fp_parse_prefix:NNN #1#2#3
14283 {
14284   \if_meaning:w \scan_stop: #3
14285     \exp_after:wN \_fp_parse_prefix_unknown:NNN
14286     \exp_after:wN #2
14287   \fi:
14288   #3 #1
14289 }
14290 \cs_new:Npn \_fp_parse_prefix_unknown:NNN #1#2#3
14291 {
14292   \cs_if_exist:cTF { \_fp_parse_infix_ \token_to_str:N #1 :N }
14293   {
14294     \_kernel_msg_expandable_error:nnn
14295     { kernel } { fp-missing-number } {#1}
14296     \exp_after:wN \c_nan_fp \exp:w \exp_end_continue_f:w
14297     \_fp_parse_infix:NN #3 #1
14298   }
14299   {
14300     \_kernel_msg_expandable_error:nnn
14301     { kernel } { fp-unknown-symbol } {#1}
14302     \_fp_parse_one:Nw #3
14303   }
14304 }
```

(End definition for `_fp_parse_prefix:NNN` and `_fp_parse_prefix_unknown:NNN`.)

26.4.1 Numbers: trimming leading zeros

Numbers are parsed as follows: first we trim leading zeros, then if the next character is a digit, start reading a significand ≥ 1 with the set of functions `_fp_parse_large...`; if it is a period, the significand is < 1 ; and otherwise it is zero. In the second case, trim additional zeros after the period, counting them for an exponent shift $\langle exp_1 \rangle < 0$, then read the significand with the set of functions `_fp_parse_small...`. Once the significand is read, read the exponent if `e` is present.

`_fp_parse_trim_zeros:N`
`_fp_parse_trim_end:w`

This function expects an already expanded token. It removes any leading zero, then distinguishes three cases: if the first non-zero token is a digit, then call `_fp_parse_large:N` (the significand is ≥ 1); if it is `.`, then continue trimming zeros with `_fp_parse_strim_zeros:N`; otherwise, our number is exactly zero, and we call `_fp_parse_zero:` to take care of that case.

```

14305 \cs_new:Npn \_fp_parse_trim_zeros:N #1
14306 {
14307   \if:w 0 \exp_not:N #1
14308     \exp_after:wN \_fp_parse_trim_zeros:N
```

```

14309     \exp:w
14310 \else:
14311     \if:w . \exp_not:N #1
14312         \exp_after:wN \__fp_parse_strim_zeros:N
14313         \exp:w
14314     \else:
14315         \__fp_parse_trim_end:w #1
14316     \fi:
14317 \fi:
14318 \__fp_parse_expand:w
14319 }
14320 \cs_new:Npn \__fp_parse_trim_end:w #1 \fi: \fi: \__fp_parse_expand:w
14321 {
14322     \fi:
14323     \fi:
14324     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
14325         \exp_after:wN \__fp_parse_large:N
14326     \else:
14327         \exp_after:wN \__fp_parse_zero:
14328     \fi:
14329     #1
14330 }

```

(End definition for __fp_parse_trim_zeros:N and __fp_parse_trim_end:w.)

__fp_parse_strim_zeros:N If we have removed all digits until a period (or if the body started with a period), then
 __fp_parse_strim_end:w enter the “small_trim” loop which outputs −1 for each removed 0. Those −1 are added to an integer expression waiting for the exponent. If the first non-zero token is a digit, call __fp_parse_small:N (our significand is smaller than 1), and otherwise, the number is an exact zero. The name `strim` stands for “small trim”.

```

14331 \cs_new:Npn \__fp_parse_strim_zeros:N #1
14332 {
14333     \if:w 0 \exp_not:N #1
14334         - 1
14335         \exp_after:wN \__fp_parse_strim_zeros:N \exp:w
14336     \else:
14337         \__fp_parse_strim_end:w #1
14338     \fi:
14339     \__fp_parse_expand:w
14340 }
14341 \cs_new:Npn \__fp_parse_strim_end:w #1 \fi: \__fp_parse_expand:w
14342 {
14343     \fi:
14344     \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
14345         \exp_after:wN \__fp_parse_small:N
14346     \else:
14347         \exp_after:wN \__fp_parse_zero:
14348     \fi:
14349     #1
14350 }

```

(End definition for __fp_parse_strim_zeros:N and __fp_parse_strim_end:w.)

__fp_parse_zero: After reading a significand of 0, find any exponent, then put a sign of 1 for __fp-sanitize:wN, which removes everything and leaves an exact zero.


```

14351 \cs_new:Npn \__fp_parse_zero:
14352 {
14353   \exp_after:wN ; \exp_after:wN 1
14354   \int_value:w \__fp_parse_exponent:N
14355 }

```

(End definition for __fp_parse_zero:.)

26.4.2 Number: small significand

`__fp_parse_small:N` This function is called after we have passed the decimal separator and removed all leading zeros from the significand. It is followed by a non-zero digit (with any catcode). The goal is to read up to 16 digits. But we can't do that all at once, because `\int_value:w` (which allows us to collect digits and continue expanding) can only go up to 9 digits. Hence we grab digits in two steps of 8 digits. Since `#1` is a digit, read seven more digits using `__fp_parse_digits_vii:N`. The `small_leading` auxiliary leaves those digits in the `\int_value:w`, and grabs some more, or stops if there are no more digits. Then the `pack_leading` auxiliary puts the various parts in the appropriate order for the processing further up.

```

14356 \cs_new:Npn \__fp_parse_small:N #1
14357 {
14358   \exp_after:wN \__fp_parse_pack_leading:NNNNNww
14359   \int_value:w \__fp_int_eval:w 1 \token_to_str:N #1
14360   \exp_after:wN \__fp_parse_small_leading:wwNN
14361   \int_value:w 1
14362   \exp_after:wN \__fp_parse_digits_vii:N
14363   \exp:w \__fp_parse_expand:w
14364 }

```

(End definition for __fp_parse_small:N.)

`__fp_parse_small_leading:wwNN` `__fp_parse_small_leading:wwNN 1 <digits> ; <zeros> ; <number of zeros>`

We leave `<digits>` `<zeros>` in the input stream: the functions used to grab digits are such that this constitutes digits 1 through 8 of the significand. Then prepare to pack 8 more digits, with an exponent shift of zero (this shift is used in the case of a large significand). If `#4` is a digit, leave it behind for the packing function, and read 6 more digits to reach a total of 15 digits: further digits are involved in the rounding. Otherwise put 8 zeros in to complete the significand, then look for an exponent.

```

14365 \cs_new:Npn \__fp_parse_small_leading:wwNN 1 #1 ; #2; #3 #4
14366 {
14367   #1 #2
14368   \exp_after:wN \__fp_parse_pack_trailing:NNNNNNww
14369   \exp_after:wN 0
14370   \int_value:w \__fp_int_eval:w 1
14371   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
14372     \token_to_str:N #4
14373     \exp_after:wN \__fp_parse_small_trailing:wwNN
14374     \int_value:w 1
14375     \exp_after:wN \__fp_parse_digits_vi:N
14376     \exp:w
14377   \else:
14378     0000 0000 \__fp_parse_exponent:Nw #4
14379   \fi:

```

```

14380     \__fp_parse_expand:w
14381 }

```

(End definition for __fp_parse_small_leading:wwNN.)

```

\__fp_parse_small_trailing:wwNN    \__fp_parse_small_trailing:wwNN 1 <digits> ; <zeros> ; <number of zeros>
                                   <next token>

```

Leave digits 10 to 15 (arguments #1 and #2) in the input stream. If the *<next token>* is a digit, it is the 16th digit, we keep it, then the `small_round` auxiliary considers this digit and all further digits to perform the rounding: the function expands to nothing, to +0 or to +1. Otherwise, there is no 16-th digit, so we put a 0, and look for an exponent.

```

14382 \cs_new:Npn \__fp_parse_small_trailing:wwNN 1 #1 ; #2; #3 #4
14383 {
14384     #1 #2
14385     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
14386         \token_to_str:N #4
14387         \exp_after:wN \__fp_parse_small_round:NN
14388         \exp_after:wN #4
14389         \exp:w
14390     \else:
14391         0 \__fp_parse_exponent:Nw #4
14392     \fi:
14393     \__fp_parse_expand:w
14394 }

```

(End definition for __fp_parse_small_trailing:wwNN.)

```

\__fp_parse_pack_trailing:NNNNNNww
\__fp_parse_pack_leading:NNNNNNww
\__fp_parse_pack_carry:w

```

Those functions are expanded after all the digits are found, we took care of the rounding, as well as the exponent. The last argument is the exponent. The previous five arguments are 8 digits which we pack in groups of 4, and the argument before that is 1, except in the rare case where rounding lead to a carry, in which case the argument is 2. The `trailing` function has an exponent shift as its first argument, which we add to the exponent found in the `e...` syntax. If the trailing digits cause a carry, the integer expression for the leading digits is incremented (+1 in the code below). If the leading digits propagate this carry all the way up, the function `__fp_parse_pack_carry:w` increments the exponent, and changes the significand from 0000... to 1000...: this is simple because such a carry can only occur to give rise to a power of 10.

```

14395 \cs_new:Npn \__fp_parse_pack_trailing:NNNNNNww #1 #2 #3#4#5#6 #7; #8 ;
14396 {
14397     \if_meaning:w 2 #2 + 1 \fi:
14398     ; #8 + #1 ; {#3#4#5#6} {#7};
14399 }
14400 \cs_new:Npn \__fp_parse_pack_leading:NNNNNNww #1 #2#3#4#5 #6; #7;
14401 {
14402     + #7
14403     \if_meaning:w 2 #1 \__fp_parse_pack_carry:w \fi:
14404     ; 0 {#2#3#4#5} {#6}
14405 }
14406 \cs_new:Npn \__fp_parse_pack_carry:w \fi: ; 0 #1
14407 { \fi: + 1 ; 0 {1000} }

```

(End definition for __fp_parse_pack_trailing:NNNNNNww, __fp_parse_pack_leading:NNNNNNww, and __fp_parse_pack_carry:w.)

26.4.3 Number: large significand

Parsing a significand larger than 1 is a little bit more difficult than parsing small significands. We need to count the number of digits before the decimal separator, and add that to the final exponent. We also need to test for the presence of a dot each time we run out of digits, and branch to the appropriate `parse_small` function in those cases.

`_fp_parse_large:N` This function is followed by the first non-zero digit of a “large” significand (≥ 1). It is called within an integer expression for the exponent. Grab up to 7 more digits, for a total of 8 digits.

```

14408 \cs_new:Npn \_fp_parse_large:N #1
14409 {
14410   \exp_after:wN \_fp_parse_large_leading:wwNN
14411   \int_value:w 1 \token_to_str:N #1
14412   \exp_after:wN \_fp_parse_digits_vii:N
14413   \exp:w \_fp_parse_expand:w
14414 }

```

(End definition for `_fp_parse_large:N`.)

`_fp_parse_large_leading:wwNN` `_fp_parse_large_leading:wwNN 1 <digits> ; <zeros> ; <number of zeros>`
`<next token>`

We shift the exponent by the number of digits in #1, namely the target number, 8, minus the *<number of zeros>* (number of digits missing). Then prepare to pack the 8 first digits. If the *<next token>* is a digit, read up to 6 more digits (digits 10 to 15). If it is a period, try to grab the end of our 8 first digits, branching to the `small` functions since the number of digit does not affect the exponent anymore. Finally, if this is the end of the significand, insert the *<zeros>* to complete the 8 first digits, insert 8 more, and look for an exponent.

```

14415 \cs_new:Npn \_fp_parse_large_leading:wwNN 1 #1 ; #2; #3 #4
14416 {
14417   + \c__fp_half_prec_int - #3
14418   \exp_after:wN \_fp_parse_pack_leading:NNNNNww
14419   \int_value:w \_fp_int_eval:w 1 #1
14420   \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
14421     \exp_after:wN \_fp_parse_large_trailing:wwNN
14422     \int_value:w 1 \token_to_str:N #4
14423     \exp_after:wN \_fp_parse_digits_vi:N
14424     \exp:w
14425   \else:
14426     \if:w . \exp_not:N #4
14427       \exp_after:wN \_fp_parse_small_leading:wwNN
14428       \int_value:w 1
14429       \cs:w
14430         \_fp_parse_digits_
14431         \_fp_int_to_roman:w #3
14432         :N \exp_after:wN
14433       \cs_end:
14434       \exp:w
14435     \else:
14436       #2
14437       \exp_after:wN \_fp_parse_pack_trailing:NNNNNNww
14438       \exp_after:wN 0

```

```

14439         \int_value:w 1 0000 0000
14440         \__fp_parse_exponent:Nw #4
14441         \fi:
14442     \fi:
14443     \__fp_parse_expand:w
14444 }

```

(End definition for __fp_parse_large_leading:wwNN.)

```

\__fp_parse_large_trailing:wwNN    \__fp_parse_large_trailing:wwNN 1 <digits> ; <zeros> ; <number of zeros>
                                   <next token>

```

We have just read 15 digits. If the *<next token>* is a digit, then the exponent shift caused by this block of 8 digits is 8, first argument to the `pack_trailing` function. We keep the *<digits>* and this 16-th digit, and find how this should be rounded using `__fp_parse_large_round:NN`. Otherwise, the exponent shift is the number of *<digits>*, 7 minus the *<number of zeros>*, and we test for a decimal point. This case happens in 123451234512345.67 with exactly 15 digits before the decimal separator. Then branch to the appropriate `small` auxiliary, grabbing a few more digits to complement the digits we already grabbed. Finally, if this is truly the end of the significand, look for an exponent after using the *<zeros>* and providing a 16-th digit of 0.

```

14445 \cs_new:Npn \__fp_parse_large_trailing:wwNN 1 #1 ; #2; #3 #4
14446 {
14447     \if_int_compare:w 9 < 1 \token_to_str:N #4 \exp_stop_f:
14448     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNnw
14449     \exp_after:wN \c__fp_half_prec_int
14450     \int_value:w \__fp_int_eval:w 1 #1 \token_to_str:N #4
14451     \exp_after:wN \__fp_parse_large_round:NN
14452     \exp_after:wN #4
14453     \exp:w
14454 \else:
14455     \exp_after:wN \__fp_parse_pack_trailing:NNNNNNnw
14456     \int_value:w \__fp_int_eval:w 7 - #3 \exp_stop_f:
14457     \int_value:w \__fp_int_eval:w 1 #1
14458     \if:w . \exp_not:N #4
14459     \exp_after:wN \__fp_parse_small_trailing:wwNN
14460     \int_value:w 1
14461     \cs:w
14462         __fp_parse_digits_
14463         \__fp_int_to_roman:w #3
14464         :N \exp_after:wN
14465     \cs_end:
14466     \exp:w
14467 \else:
14468     #2 0 \__fp_parse_exponent:Nw #4
14469 \fi:
14470 \fi:
14471 \__fp_parse_expand:w
14472 }

```

(End definition for __fp_parse_large_trailing:wwNN.)

26.4.4 Number: beyond 16 digits, rounding

`__fp_parse_round_loop:N` This loop is called when rounding a number (whether the mantissa is small or large). It should appear in an integer expression. This function reads digits one by one, until reaching a non-digit, and adds 1 to the integer expression for each digit. If all digits found are 0, the function ends the expression by ;0, otherwise by ;1. This is done by switching the loop to `round_up` at the first non-zero digit, thus we avoid to test whether digits are 0 or not once we see a first non-zero digit.

```

14473 \cs_new:Npn \__fp_parse_round_loop:N #1
14474 {
14475   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
14476     + 1
14477     \if:w 0 \token_to_str:N #1
14478       \exp_after:wN \__fp_parse_round_loop:N
14479       \exp:w
14480     \else:
14481       \exp_after:wN \__fp_parse_round_up:N
14482       \exp:w
14483     \fi:
14484   \else:
14485     \__fp_parse_return_semicolon:w 0 #1
14486   \fi:
14487   \__fp_parse_expand:w
14488 }
14489 \cs_new:Npn \__fp_parse_round_up:N #1
14490 {
14491   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
14492     + 1
14493     \exp_after:wN \__fp_parse_round_up:N
14494     \exp:w
14495   \else:
14496     \__fp_parse_return_semicolon:w 1 #1
14497   \fi:
14498   \__fp_parse_expand:w
14499 }
```

(End definition for `__fp_parse_round_loop:N` and `__fp_parse_round_up:N`.)

`__fp_parse_round_after:wN` After the loop `__fp_parse_round_loop:N`, this function fetches an exponent with `__fp_parse_exponent:N`, and combines it with the number of digits counted by `__fp_parse_round_loop:N`. At the same time, the result 0 or 1 is added to the surrounding integer expression.

```

14500 \cs_new:Npn \__fp_parse_round_after:wN #1; #2
14501 {
14502   + #2 \exp_after:wN ;
14503   \int_value:w \__fp_int_eval:w #1 + \__fp_parse_exponent:N
14504 }
```

(End definition for `__fp_parse_round_after:wN`.)

`__fp_parse_small_round:NN` Here, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If #2 is not a digit, then fetch an exponent and expand to ;*exponent* only. Otherwise, we expand to +0 or +1, then ;*exponent*. To decide which, call `__fp_round_s:NNNw` to know whether to round up, giving it as arguments a sign 0 (all explicit

numbers are positive), the digit #1 to round, the first following digit #2, and either +0 or +1 depending on whether the following digits are all zero or not. This last argument is obtained by `__fp_parse_round_loop:N`, whose number of digits we discard by multiplying it by 0. The exponent which follows the number is also fetched by `__fp_parse_round_after:wN`.

```

14505 \cs_new:Npn \__fp_parse_small_round:NN #1#2
14506 {
14507   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
14508   +
14509   \exp_after:wN \__fp_round_s:NNNw
14510   \exp_after:wN 0
14511   \exp_after:wN #1
14512   \exp_after:wN #2
14513   \int_value:w \__fp_int_eval:w
14514   \exp_after:wN \__fp_parse_round_after:wN
14515   \int_value:w \__fp_int_eval:w 0 * \__fp_int_eval:w 0
14516   \exp_after:wN \__fp_parse_round_loop:N
14517   \exp:w
14518   \else:
14519     \__fp_parse_exponent:Nw #2
14520   \fi:
14521   \__fp_parse_expand:w
14522 }

```

(End definition for `__fp_parse_small_round:NN` and `__fp_parse_round_after:wN`.)

```

\__fp_parse_large_round:NN
  \__fp_parse_large_round_test:NN
  \__fp_parse_large_round_aux:wNN

```

Large numbers are harder to round, as there may be a period in the way. Again, #1 is the digit that we are currently rounding (we only care whether it is even or odd). If there are no more digits (#2 is not a digit), then we must test for a period: if there is one, then switch to the rounding function for small significands, otherwise fetch an exponent. If there are more digits (#2 is a digit), then round, checking with `__fp_parse_round_loop:N` if all further digits vanish, or some are non-zero. This loop is not enough, as it is stopped by a period. After the loop, the `aux` function tests for a period: if it is present, then we must continue looking for digits, this time discarding the number of digits we find.

```

14523 \cs_new:Npn \__fp_parse_large_round:NN #1#2
14524 {
14525   \if_int_compare:w 9 < 1 \token_to_str:N #2 \exp_stop_f:
14526   +
14527   \exp_after:wN \__fp_round_s:NNNw
14528   \exp_after:wN 0
14529   \exp_after:wN #1
14530   \exp_after:wN #2
14531   \int_value:w \__fp_int_eval:w
14532   \exp_after:wN \__fp_parse_large_round_aux:wNN
14533   \int_value:w \__fp_int_eval:w 1
14534   \exp_after:wN \__fp_parse_round_loop:N
14535   \else: %^^A could be dot, or e, or other
14536     \exp_after:wN \__fp_parse_large_round_test:NN
14537     \exp_after:wN #1
14538     \exp_after:wN #2
14539   \fi:
14540 }

```

```

14541 \cs_new:Npn \__fp_parse_large_round_test:NN #1#2
14542 {
14543   \if:w . \exp_not:N #2
14544     \exp_after:wN \__fp_parse_small_round:NN
14545     \exp_after:wN #1
14546     \exp:w
14547   \else:
14548     \__fp_parse_exponent:Nw #2
14549   \fi:
14550   \__fp_parse_expand:w
14551 }
14552 \cs_new:Npn \__fp_parse_large_round_aux:wNN #1 ; #2 #3
14553 {
14554   + #2
14555   \exp_after:wN \__fp_parse_round_after:wN
14556   \int_value:w \__fp_int_eval:w #1
14557   \if:w . \exp_not:N #3
14558     + 0 * \__fp_int_eval:w 0
14559     \exp_after:wN \__fp_parse_round_loop:N
14560     \exp:w \exp_after:wN \__fp_parse_expand:w
14561   \else:
14562     \exp_after:wN ;
14563     \exp_after:wN 0
14564     \exp_after:wN #3
14565   \fi:
14566 }

```

(End definition for `__fp_parse_large_round:NN`, `__fp_parse_large_round_test:NN`, and `__fp_parse_large_round_aux:wNN`.)

26.4.5 Number: finding the exponent

Expansion is a little bit tricky here, in part because we accept input where multiplication is implicit.

```

\__fp_parse:n { 3.2 erf(0.1) }
\__fp_parse:n { 3.2 e1_my_int }
\__fp_parse:n { 3.2 \c_pi_fp }

```

The first case indicates that just looking one character ahead for an “e” is not enough, since we would mistake the function `erf` for an exponent of “`rf`”. An alternative would be to look two tokens ahead and check if what follows is a sign or a digit, considering in that case that we must be finding an exponent. But taking care of the second case requires that we unpack registers after `e`. However, blindly expanding the two tokens ahead completely would break the third example (unpacking is even worse). Indeed, in the course of reading `3.2`, `\c_pi_fp` is expanded to `\s__fp __fp_chk:w 1 0 {-1} {3141}` \cdots ; and `\s__fp` stops the expansion. Expanding two tokens ahead would then force the expansion of `__fp_chk:w` (despite it being protected), and that function tries to produce an error.

What can we do? Really, the reason why this last case breaks is that just as \TeX does, we should read ahead as little as possible. Here, the only case where there may be an exponent is if the first token ahead is `e`. Then we expand (and possibly unpack) the second token.

`__fp_parse_exponent:Nw` This auxiliary is convenient to smuggle some material through `\fi:` ending conditional processing. We place those `\fi:` (argument #2) at a very odd place because this allows us to insert `__fp_int_eval:w ...` there if needed.

```

14567 \cs_new:Npn \__fp_parse_exponent:Nw #1 #2 \__fp_parse_expand:w
14568 {
14569     \exp_after:wN ;
14570     \int_value:w #2 \__fp_parse_exponent:N #1
14571 }

```

(End definition for __fp_parse_exponent:Nw.)

`__fp_parse_exponent:N` This function should be called within an `\int_value:w` expansion (or within an integer expression). It leaves digits of the exponent behind it in the input stream, and terminates the expansion with a semicolon. If there is no `e`, leave an exponent of 0. If there is an `e`, expand the next token to run some tests on it. The first rough test is that if the character code of #1 is greater than that of 9 (largest code valid for an exponent, less than any code valid for an identifier), there was in fact no exponent; otherwise, we search for the sign of the exponent.

```

14572 \cs_new:Npn \__fp_parse_exponent:N #1
14573 {
14574     \if:w e \exp_not:N #1
14575         \exp_after:wN \__fp_parse_exponent_aux:N
14576         \exp:w
14577     \else:
14578         0 \__fp_parse_return_semicolon:w #1
14579     \fi:
14580     \__fp_parse_expand:w
14581 }
14582 \cs_new:Npn \__fp_parse_exponent_aux:N #1
14583 {
14584     \if_int_compare:w \if_catcode:w \scan_stop: \exp_not:N #1
14585         0 \else: '#1 \fi: > '9 \exp_stop_f:
14586     0 \exp_after:wN ; \exp_after:wN e
14587     \else:
14588         \exp_after:wN \__fp_parse_exponent_sign:N
14589     \fi:
14590     #1
14591 }

```

(End definition for __fp_parse_exponent:N and __fp_parse_exponent_aux:N.)

`__fp_parse_exponent_sign:N` Read signs one by one (if there is any).

```

14592 \cs_new:Npn \__fp_parse_exponent_sign:N #1
14593 {
14594     \if:w + \if:w - \exp_not:N #1 + \fi: \token_to_str:N #1
14595     \exp_after:wN \__fp_parse_exponent_sign:N
14596     \exp:w \exp_after:wN \__fp_parse_expand:w
14597     \else:
14598         \exp_after:wN \__fp_parse_exponent_body:N
14599         \exp_after:wN #1
14600     \fi:
14601 }

```

(End definition for __fp_parse_exponent_sign:N.)

`__fp_parse_exponent_body:N` An exponent can be an explicit integer (most common case), or various other things (most of which are invalid).

```

14602 \cs_new:Npn \__fp_parse_exponent_body:N #1
14603 {
14604   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
14605     \token_to_str:N #1
14606     \exp_after:wN \__fp_parse_exponent_digits:N
14607     \exp:w
14608   \else:
14609     \__fp_parse_exponent_keep:NTF #1
14610     { \__fp_parse_return_semicolon:w #1 }
14611     {
14612       \exp_after:wN ;
14613       \exp:w
14614     }
14615   \fi:
14616   \__fp_parse_expand:w
14617 }

```

(End definition for `__fp_parse_exponent_body:N`.)

`__fp_parse_exponent_digits:N` Read digits one by one, and leave them behind in the input stream. When finding a non-digit, stop, and insert a semicolon. Note that we do not check for overflow of the exponent, hence there can be a T_EX error. It is mostly harmless, except when parsing 0e9876543210, which should be a valid representation of 0, but is not.

```

14618 \cs_new:Npn \__fp_parse_exponent_digits:N #1
14619 {
14620   \if_int_compare:w 9 < 1 \token_to_str:N #1 \exp_stop_f:
14621     \token_to_str:N #1
14622     \exp_after:wN \__fp_parse_exponent_digits:N
14623     \exp:w
14624   \else:
14625     \__fp_parse_return_semicolon:w #1
14626   \fi:
14627   \__fp_parse_expand:w
14628 }

```

(End definition for `__fp_parse_exponent_digits:N`.)

`__fp_parse_exponent_keep:N` This is the last building block for parsing exponents. The argument #1 is already fully expanded, and neither + nor - nor a digit. It can be:

- `\s__fp`, marking the start of an internal floating point, invalid here;
- another control sequence equal to `\relax`, probably a bad variable;
- a register: in this case we make sure that it is an integer register, not a dimension;
- a character other than +, - or digits, again, an error.

```

14629 \prg_new_conditional:Npnn \__fp_parse_exponent_keep:N #1 { TF }
14630 {
14631   \if_catcode:w \scan_stop: \exp_not:N #1
14632     \if_meaning:w \scan_stop: #1
14633     \if_int_compare:w

```

```

14634         \_fp_str_if_eq:nn { \s_fp } { \exp_not:N #1 }
14635         = 0 \exp_stop_f:
14636     0
14637     \_kernel_msg_expandable_error:nnn
14638     { kernel } { fp-after-e } { floating-point~ }
14639     \prg_return_true:
14640 \else:
14641     0
14642     \_kernel_msg_expandable_error:nnn
14643     { kernel } { bad-variable } { #1 }
14644     \prg_return_false:
14645 \fi:
14646 \else:
14647     \if_int_compare:w
14648         \_fp_str_if_eq:nn { \int_value:w #1 } { \tex_the:D #1 }
14649         = 0 \exp_stop_f:
14650         \int_value:w #1
14651     \else:
14652         0
14653         \_kernel_msg_expandable_error:nnn
14654         { kernel } { fp-after-e } { dimension~#1 }
14655     \fi:
14656     \prg_return_false:
14657 \fi:
14658 \else:
14659     0
14660     \_kernel_msg_expandable_error:nnn
14661     { kernel } { fp-missing } { exponent }
14662     \prg_return_true:
14663 \fi:
14664 }

```

(End definition for _fp_parse_exponent_keep:NTF.)

26.5 Constants, functions and prefix operators

26.5.1 Prefix operators

_fp_parse_prefix+:Nw A unary + does nothing: we should continue looking for a number.

```

14665 \cs_new_eq:cN { \_fp_parse_prefix+:Nw } \_fp_parse_one:Nw

```

(End definition for _fp_parse_prefix+:Nw.)

_fp_parse_apply_function:NNwN Here, #1 is a precedence, #2 is some extra data used by some functions, #3 is *e.g.*, _fp_sin_o:w, and expands once after the calculation, #4 is the operand, and #5 is a _fp_parse_infix...:N function. We feed the data #2, and the argument #4, to the function #3, which expands \exp:w thus the infix function #5.

```

14666 \cs_new:Npn \_fp_parse_apply_function:NNwN #1#2#3#4#5
14667 {
14668     #3 #2 #4 @
14669     \exp:w \exp_end_continue_f:w #5 #1
14670 }

```

(End definition for _fp_parse_apply_function:NNwN.)

`_fp_parse_apply_unary:NNWwN`
`_fp_parse_apply_unary_chk:NwNw`
`_fp_parse_apply_unary_chk:nNNWw`
`_fp_parse_apply_unary_type:NNN`
`_fp_parse_apply_unary_error:NNw`

In contrast to `__fp_parse_apply_function:NNNwN`, this checks that the operand #4 is a single argument (namely there is a single `;`). We use the fact that any floating point starts with a “safe” token like `\s__fp`. If there is no argument produce the `fp-no-arg` error; if there are at least two produce `fp-multi-arg`. For the error message extract the mathematical function name (such as `sin`) from the `expl3` function that computes it, such as `__fp_sin_o:w`.

In addition, since there is a single argument we can dispatch on type and check that the resulting function exists. This catches things like `sin((1,2))` where it does not make sense to take the sine of a tuple.

```

14671 \cs_new:Npn \__fp_parse_apply_unary:NNNwN #1#2#3#4#5
14672 {
14673   \__fp_parse_apply_unary_chk:NwNw #4 @ ; . \q_stop
14674   \__fp_parse_apply_unary_type:NNN
14675   #3 #2 #4 @
14676   \exp:w \exp_end_continue_f:w #5 #1
14677 }
14678 \cs_new:Npn \__fp_parse_apply_unary_chk:NwNw #1#2 ; #3#4 \q_stop
14679 {
14680   \if_meaning:w @ #3 \else:
14681     \token_if_eq_meaning:NNTF . #3
14682     { \__fp_parse_apply_unary_chk:nNNNNw { no } }
14683     { \__fp_parse_apply_unary_chk:nNNNNw { multi } }
14684   \fi:
14685 }
14686 \cs_new:Npn \__fp_parse_apply_unary_chk:nNNNNw #1#2#3#4#5#6 @
14687 {
14688   #2
14689   \__fp_error:nffn { fp-#1-arg } { \__fp_func_to_name:N #4 } { } { }
14690   \exp_after:wN #4 \exp_after:wN #5 \c_nan_fp @
14691 }
14692 \cs_new:Npn \__fp_parse_apply_unary_type:NNN #1#2#3
14693 {
14694   \__fp_change_func_type:NNN #3 #1 \__fp_parse_apply_unary_error:NNw
14695   #2 #3
14696 }
14697 \cs_new:Npn \__fp_parse_apply_unary_error:NNw #1#2#3 @
14698 { \__fp_invalid_operation_o:fw { \__fp_func_to_name:N #1 } #3 }

```

(End definition for `_fp_parse_apply_unary:NNNwN` and others.)

`_fp_parse_prefix_-:Nw`
`_fp_parse_prefix_!:Nw`

The unary `-` and boolean not are harder: we parse the operand using a precedence equal to the maximum of the previous precedence ##1 and the precedence `\c__fp_prec_not_int` of the unary operator, then call the appropriate `__fp_⟨operation⟩_o:w` function, where the `⟨operation⟩` is `set_sign` or `not`.

```

14699 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
14700 {
14701   \cs_new:cpn { \__fp_parse_prefix_ #1 :Nw } ##1
14702   {
14703     \exp_after:wN \__fp_parse_apply_unary:NNNwN
14704     \exp_after:wN ##1
14705     \exp_after:wN #4
14706     \exp_after:wN #3
14707     \exp:w

```

```

14708     \if_int_compare:w #2 < ##1
14709     \__fp_parse_operand:Nw ##1
14710     \else:
14711     \__fp_parse_operand:Nw #2
14712     \fi:
14713     \__fp_parse_expand:w
14714 }
14715 }
14716 \__fp_tmp:w - \c__fp_prec_not_int \__fp_set_sign_o:w 2
14717 \__fp_tmp:w ! \c__fp_prec_not_int \__fp_not_o:w ?

```

(End definition for __fp_parse_prefix -:Nw and __fp_parse_prefix !:Nw.)

__fp_parse_prefix .:Nw Numbers which start with a decimal separator (a period) end up here. Of course, we do not look for an operand, but for the rest of the number. This function is very similar to __fp_parse_one_digit:NN but calls __fp_parse_strim_zeros:N to trim zeros after the decimal point, rather than the trim_zeros function for zeros before the decimal point.

```

14718 \cs_new:cpn { __fp_parse_prefix .:Nw } #1
14719 {
14720     \exp_after:wN \__fp_parse_infix_after_operand:NwN
14721     \exp_after:wN #1
14722     \exp:w \exp_end_continue_f:w
14723     \exp_after:wN \__fp_sanitizew
14724     \int_value:w \__fp_int_eval:w 0 \__fp_parse_strim_zeros:N
14725 }

```

(End definition for __fp_parse_prefix .:Nw.)

__fp_parse_prefix (:Nw __fp_parse_lparen_after:NwN The left parenthesis is treated as a unary prefix operator because it appears in exactly the same settings. If the previous precedence is \c__fp_prec_func_int we are parsing arguments of a function and commas should not build tuples; otherwise commas should build tuples. We distinguish these cases by precedence: \c__fp_prec_comma_int for the case of arguments, \c__fp_prec_tuple_int for the case of tuples. Once the operand is found, the lparen_after auxiliary makes sure that there was a closing parenthesis (otherwise it complains), and leaves in the input stream an operand, fetching the following infix operator.

```

14726 \cs_new:cpn { __fp_parse_prefix (:Nw } #1
14727 {
14728     \exp_after:wN \__fp_parse_lparen_after:NwN
14729     \exp_after:wN #1
14730     \exp:w
14731     \if_int_compare:w #1 = \c__fp_prec_func_int
14732     \__fp_parse_operand:Nw \c__fp_prec_comma_int
14733     \else:
14734     \__fp_parse_operand:Nw \c__fp_prec_tuple_int
14735     \fi:
14736     \__fp_parse_expand:w
14737 }
14738 \cs_new:Npx \__fp_parse_lparen_after:NwN #1#2 @ #3
14739 {
14740     \exp_not:N \token_if_eq_meaning:NNTF #3
14741     \exp_not:c { __fp_parse_infix_):N }
14742     {

```

```

14743         \exp_not:N \__fp_exp_after_array_f:w #2 \s__fp_stop
14744         \exp_not:N \exp_after:wN
14745         \exp_not:N \__fp_parse_infix:NN
14746         \exp_not:N \exp_after:wN #1
14747         \exp_not:N \exp:w
14748         \exp_not:N \__fp_parse_expand:w
14749     }
14750     {
14751         \exp_not:N \__kernel_msg_expandable_error:nnn
14752         { kernel } { fp-missing } { ) }
14753         \exp_not:N \tl_if_empty:nT {#2} \exp_not:N \c__fp_empty_tuple_fp
14754         #2 @
14755         \exp_not:N \use_none:n #3
14756     }
14757 }

```

(End definition for __fp_parse_prefix_(:Nw and __fp_parse_lparen_after:NwN.)

__fp_parse_prefix_):Nw

The right parenthesis can appear as a prefix in two similar cases: in an empty tuple or tuple ending with a comma, or in an empty argument list or argument list ending with a comma, such as in `max(1,2,)` or in `rand()`.

```

14758 \cs_new:cpn { __fp_parse_prefix_):Nw } #1
14759 {
14760     \if_int_compare:w #1 = \c__fp_prec_comma_int
14761     \else:
14762         \if_int_compare:w #1 = \c__fp_prec_tuple_int
14763         \exp_after:wN \c__fp_empty_tuple_fp \exp:w
14764     \else:
14765         \__kernel_msg_expandable_error:nnn
14766         { kernel } { fp-missing-number } { ) }
14767         \exp_after:wN \c_nan_fp \exp:w
14768     \fi:
14769     \exp_end_continue_f:w
14770 \fi:
14771 \__fp_parse_infix:NN #1 )
14772 }

```

(End definition for __fp_parse_prefix_):Nw.)

26.5.2 Constants

__fp_parse_word_inf:N
__fp_parse_word_nan:N
__fp_parse_word_pi:N
__fp_parse_word_deg:N
__fp_parse_word_true:N
__fp_parse_word_false:N

Some words correspond to constant floating points. The floating point constant is left as a result of __fp_parse_one:Nw after expanding __fp_parse_infix:NN.

```

14773 \cs_set_protected:Npn \__fp_tmp:w #1 #2
14774 {
14775     \cs_new:cpn { __fp_parse_word_#1:N }
14776     { \exp_after:wN #2 \exp:w \exp_end_continue_f:w \__fp_parse_infix:NN }
14777 }
14778 \__fp_tmp:w { inf } \c_inf_fp
14779 \__fp_tmp:w { nan } \c_nan_fp
14780 \__fp_tmp:w { pi } \c_pi_fp
14781 \__fp_tmp:w { deg } \c_one_degree_fp
14782 \__fp_tmp:w { true } \c_one_fp
14783 \__fp_tmp:w { false } \c_zero_fp

```

(End definition for `_fp_parse_word_inf:N` and others.)

`_fp_parse_caseless_inf:N` Copies of `_fp_parse_word_...:N` commands, to allow arbitrary case as mandated by the standard.

```

\fp_parse_caseless_infinity:N
\fp_parse_caseless_nan:N
14784 \cs_new_eq:NN \_fp_parse_caseless_inf:N \_fp_parse_word_inf:N
14785 \cs_new_eq:NN \_fp_parse_caseless_infinity:N \_fp_parse_word_inf:N
14786 \cs_new_eq:NN \_fp_parse_caseless_nan:N \_fp_parse_word_nan:N

```

(End definition for `_fp_parse_caseless_inf:N`, `_fp_parse_caseless_infinity:N`, and `_fp_parse_caseless_nan:N`.)

`_fp_parse_word_pt:N` Dimension units are also floating point constants but their value is not stored as a floating point constant. We give the values explicitly here.

```

\fp_parse_word_in:N
\fp_parse_word_pc:N
\fp_parse_word_cm:N
\fp_parse_word_mm:N
\fp_parse_word_dd:N
\fp_parse_word_cc:N
\fp_parse_word_nd:N
\fp_parse_word_nc:N
\fp_parse_word_bp:N
\fp_parse_word_sp:N
14787 \cs_set_protected:Npn \_fp_tmp:w #1 #2
14788 {
14789   \cs_new:cpn { \_fp_parse_word_#1:N }
14790   {
14791     \_fp_exp_after_f:nw { \_fp_parse_infix:NN }
14792     \s__fp \_fp_chk:w 10 #2 ;
14793   }
14794 }
14795 \_fp_tmp:w {pt} { {1} {1000} {0000} {0000} {0000} }
14796 \_fp_tmp:w {in} { {2} {7227} {0000} {0000} {0000} }
14797 \_fp_tmp:w {pc} { {2} {1200} {0000} {0000} {0000} }
14798 \_fp_tmp:w {cm} { {2} {2845} {2755} {9055} {1181} }
14799 \_fp_tmp:w {mm} { {1} {2845} {2755} {9055} {1181} }
14800 \_fp_tmp:w {dd} { {1} {1070} {0085} {6496} {0630} }
14801 \_fp_tmp:w {cc} { {2} {1284} {0102} {7795} {2756} }
14802 \_fp_tmp:w {nd} { {1} {1066} {9783} {4645} {6693} }
14803 \_fp_tmp:w {nc} { {2} {1280} {3740} {1574} {8031} }
14804 \_fp_tmp:w {bp} { {1} {1003} {7500} {0000} {0000} }
14805 \_fp_tmp:w {sp} { {-4} {1525} {8789} {0625} {0000} }

```

(End definition for `_fp_parse_word_pt:N` and others.)

`_fp_parse_word_em:N` The font-dependent units `em` and `ex` must be evaluated on the fly. We reuse an auxiliary of `\dim_to_fp:n`.

```

\fp_parse_word_ex:N
14806 \tl_map_inline:nn { {em} {ex} }
14807 {
14808   \cs_new:cpn { \_fp_parse_word_#1:N }
14809   {
14810     \exp_after:wN \_fp_from_dim_test:ww
14811     \exp_after:wN 0 \exp_after:wN ,
14812     \int_value:w \dim_to_decimal_in_sp:n { 1 #1 } \exp_after:wN ;
14813     \exp:w \exp_end_continue_f:w \_fp_parse_infix:NN
14814   }
14815 }

```

(End definition for `_fp_parse_word_em:N` and `_fp_parse_word_ex:N`.)

26.5.3 Functions

```

\__fp_parse_unary_function:NNN
\__fp_parse_function:NNN
14816 \cs_new:Npn \__fp_parse_unary_function:NNN #1#2#3
14817 {
14818   \exp_after:wN \__fp_parse_apply_unary:NNNwN
14819   \exp_after:wN #3
14820   \exp_after:wN #2
14821   \exp_after:wN #1
14822   \exp:w
14823   \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
14824 }
14825 \cs_new:Npn \__fp_parse_function:NNN #1#2#3
14826 {
14827   \exp_after:wN \__fp_parse_apply_function:NNNwN
14828   \exp_after:wN #3
14829   \exp_after:wN #2
14830   \exp_after:wN #1
14831   \exp:w
14832   \__fp_parse_operand:Nw \c__fp_prec_func_int \__fp_parse_expand:w
14833 }

```

(End definition for `__fp_parse_unary_function:NNN` and `__fp_parse_function:NNN`.)

26.6 Main functions

`__fp_parse:n` Start an `\exp:w` expansion so that `__fp_parse:n` expands in two steps. The `__fp_parse_operand:Nw` function performs computations until reaching an operation with precedence `\c__fp_prec_end_int` or less, namely, the end of the expression. The marker `\s__fp_mark` indicates that the next token is an already parsed version of an infix operator, and `__fp_parse_infix_end:N` has infinitely negative precedence. Finally, clean up a (well-defined) set of extra tokens and stop the initial expansion with `\exp_end:.`

```

14834 \cs_new:Npn \__fp_parse:n #1
14835 {
14836   \exp:w
14837   \exp_after:wN \__fp_parse_after:ww
14838   \exp:w
14839   \__fp_parse_operand:Nw \c__fp_prec_end_int
14840   \__fp_parse_expand:w #1
14841   \s__fp_mark \__fp_parse_infix_end:N
14842   \s__fp_stop
14843   \exp_end:
14844 }
14845 \cs_new:Npn \__fp_parse_after:ww
14846   #1@ \__fp_parse_infix_end:N \s__fp_stop #2 { #2 #1 }
14847 \cs_new:Npn \__fp_parse_o:n #1
14848 {
14849   \exp:w
14850   \exp_after:wN \__fp_parse_after:ww
14851   \exp:w
14852   \__fp_parse_operand:Nw \c__fp_prec_end_int
14853   \__fp_parse_expand:w #1
14854   \s__fp_mark \__fp_parse_infix_end:N
14855   \s__fp_stop

```

```

14856     {
14857         \exp_end_continue_f:w
14858         \__fp_exp_after_any_f:nw { \exp_after:wN \exp_stop_f: }
14859     }
14860 }

```

(End definition for __fp_parse:n, __fp_parse_o:n, and __fp_parse_after:ww.)

__fp_parse_operand:Nw This is just a shorthand which sets up both __fp_parse_continue:NwN and __fp_parse_one:Nw with the same precedence. Note the trailing \exp:w.

```

14861 \cs_new:Npn \__fp_parse_operand:Nw #1
14862 {
14863     \exp_end_continue_f:w
14864     \exp_after:wN \__fp_parse_continue:NwN
14865     \exp_after:wN #1
14866     \exp:w \exp_end_continue_f:w
14867     \exp_after:wN \__fp_parse_one:Nw
14868     \exp_after:wN #1
14869     \exp:w
14870 }
14871 \cs_new:Npn \__fp_parse_continue:NwN #1 #2 @ #3 { #3 #1 #2 @ }

```

(End definition for __fp_parse_operand:Nw and __fp_parse_continue:NwN.)

_fp_parse_apply_binary:NwNwN Receives $\langle precedence \rangle \langle operand_1 \rangle @ \langle operation \rangle \langle operand_2 \rangle @ \langle infix command \rangle$. Builds the appropriate call to the $\langle operation \rangle$ #3, dispatching on both types. If the resulting control sequence does not exist, the operation is not allowed.

This is redefined in l3fp-extras.

```

14872 \cs_new:Npn \__fp_parse_apply_binary:NwNwN #1 #2#3@ #4 #5#6@ #7
14873 {
14874     \exp_after:wN \__fp_parse_continue:NwN
14875     \exp_after:wN #1
14876     \exp:w \exp_end_continue_f:w
14877     \exp_after:wN \__fp_parse_apply_binary_chk:NN
14878     \cs:w
14879         \__fp
14880         \__fp_type_from_scan:N #2
14881         _#4
14882         \__fp_type_from_scan:N #5
14883         _o:ww
14884     \cs_end:
14885     #4
14886     #2#3 #5#6
14887     \exp:w \exp_end_continue_f:w #7 #1
14888 }
14889 \cs_new:Npn \__fp_parse_apply_binary_chk:NN #1#2
14890 {
14891     \if_meaning:w \scan_stop: #1
14892         \__fp_parse_apply_binary_error:NNN #2
14893     \fi:
14894     #1
14895 }
14896 \cs_new:Npn \__fp_parse_apply_binary_error:NNN #1#2#3
14897 {

```



```

14898     #2
14899     \__fp_invalid_operation_o:Nww #1
14900 }

```

(End definition for __fp_parse_apply_binary:NwNwN, __fp_parse_apply_binary_chk:NN, and __fp_parse_apply_binary_error:NNN.)

__fp_binary_type_o:Nww
__fp_binary_rev_type_o:Nww

Applies the operator #1 to its two arguments, dispatching according to their types, and expands once after the result. The rev version swaps its arguments before doing this.

```

14901 \cs_new:Npn \__fp_binary_type_o:Nww #1 #2#3 ; #4
14902 {
14903     \exp_after:wN \__fp_parse_apply_binary_chk:NN
14904     \cs:w
14905         __fp
14906         \__fp_type_from_scan:N #2
14907         _ #1
14908         \__fp_type_from_scan:N #4
14909         _o:ww
14910     \cs_end:
14911     #1
14912     #2 #3 ; #4
14913 }
14914 \cs_new:Npn \__fp_binary_rev_type_o:Nww #1 #2#3 ; #4#5 ;
14915 {
14916     \exp_after:wN \__fp_parse_apply_binary_chk:NN
14917     \cs:w
14918         __fp
14919         \__fp_type_from_scan:N #4
14920         _ #1
14921         \__fp_type_from_scan:N #2
14922         _o:ww
14923     \cs_end:
14924     #1
14925     #4 #5 ; #2 #3 ;
14926 }

```

(End definition for __fp_binary_type_o:Nww and __fp_binary_rev_type_o:Nww.)

26.7 Infix operators

__fp_parse_infix_after_operand:NwN

```

14927 \cs_new:Npn \__fp_parse_infix_after_operand:NwN #1 #2;
14928 {
14929     \__fp_exp_after_f:nw { \__fp_parse_infix:NN #1 }
14930     #2;
14931 }
14932 \cs_new:Npn \__fp_parse_infix:NN #1 #2
14933 {
14934     \if_catcode:w \scan_stop: \exp_not:N #2
14935     \if_int_compare:w
14936         \__fp_str_if_eq:nn { \s__fp_mark } { \exp_not:N #2 }
14937         = 0 \exp_stop_f:
14938     \exp_after:wN \exp_after:wN
14939     \exp_after:wN \__fp_parse_infix_mark:NNN

```

```

14940     \else:
14941         \exp_after:wN \exp_after:wN
14942         \exp_after:wN \_fp_parse_infix_mul:N
14943     \fi:
14944 \else:
14945     \if_int_compare:w
14946         \_fp_int_eval:w
14947         ( '#2 \if_int_compare:w '#2 > 'Z - 32 \fi: ) / 26
14948         = 3 \exp_stop_f:
14949         \exp_after:wN \exp_after:wN
14950         \exp_after:wN \_fp_parse_infix_mul:N
14951     \else:
14952         \exp_after:wN \_fp_parse_infix_check:NNN
14953         \cs:w
14954         \_fp_parse_infix_ \token_to_str:N #2 :N
14955         \exp_after:wN \exp_after:wN \exp_after:wN
14956         \cs_end:
14957     \fi:
14958 \fi:
14959 #1
14960 #2
14961 }
14962 \cs_new:Npx \_fp_parse_infix_check:NNN #1#2#3
14963 {
14964     \exp_not:N \if_meaning:w \scan_stop: #1
14965     \exp_not:N \_kernel_msg_expandable_error:nnn
14966     { kernel } { fp-missing } { * }
14967     \exp_not:N \exp_after:wN
14968     \exp_not:c { \_fp_parse_infix_*:N }
14969     \exp_not:N \exp_after:wN #2
14970     \exp_not:N \exp_after:wN #3
14971     \exp_not:N \else:
14972         \exp_not:N \exp_after:wN #1
14973         \exp_not:N \exp_after:wN #2
14974         \exp_not:N \exp:w
14975         \exp_not:N \exp_after:wN
14976         \exp_not:N \_fp_parse_expand:w
14977     \exp_not:N \fi:
14978 }

```

(End definition for _fp_parse_infix_after_operand:NwN.)

26.7.1 Closing parentheses and commas

_fp_parse_infix_mark:NNN As an infix operator, \s_fp_mark means that the next token (#3) has already gone through _fp_parse_infix:NN and should be provided the precedence #1. The scan mark #2 is discarded.

```

14979 \cs_new:Npn \_fp_parse_infix_mark:NNN #1#2#3 { #3 #1 }

```

(End definition for _fp_parse_infix_mark:NNN.)

_fp_parse_infix_end:N This one is a little bit odd: force every previous operator to end, regardless of the precedence.

```

14980 \cs_new:Npn \_fp_parse_infix_end:N #1
14981 { @ \use_none:n \_fp_parse_infix_end:N }

```

(End definition for _fp_parse_infix_end:N.)

_fp_parse_infix_):N This is very similar to _fp_parse_infix_end:N, complaining about an extra closing parenthesis if the previous operator was the beginning of the expression, with precedence \c__fp_prec_end_int.

```

14982 \cs_set_protected:Npn \_fp_tmp:w #1
14983 {
14984   \cs_new:Npn #1 ##1
14985   {
14986     \if_int_compare:w ##1 > \c__fp_prec_end_int
14987       \exp_after:wN @
14988       \exp_after:wN \use_none:n
14989       \exp_after:wN #1
14990     \else:
14991       \__kernel_msg_expandable_error:nnn { kernel } { fp-extra } { } }
14992       \exp_after:wN \_fp_parse_infix:NN
14993       \exp_after:wN ##1
14994       \exp:w \exp_after:wN \_fp_parse_expand:w
14995     \fi:
14996   }
14997 }
14998 \exp_args:Nc \_fp_tmp:w { \_fp_parse_infix_):N }

```

(End definition for _fp_parse_infix_):N.)

_fp_parse_infix_,:N As for other infix operations, if the previous operations has higher precedence the comma waits. Otherwise we call _fp_parse_operand:Nw to read more comma-delimited arguments that _fp_parse_infix_comma:w simply concatenates into a @-delimited array. The first comma in a tuple that is not a function argument is distinguished: in that case call _fp_parse_apply_comma:NwNwN whose job is to convert the first item of the tuple and an array of the remaining items into a tuple. In contrast to _fp_parse_apply_binary:NwNwN this function's operands are not single-object arrays.

```

14999 \cs_set_protected:Npn \_fp_tmp:w #1
15000 {
15001   \cs_new:Npn #1 ##1
15002   {
15003     \if_int_compare:w ##1 > \c__fp_prec_comma_int
15004       \exp_after:wN @
15005       \exp_after:wN \use_none:n
15006       \exp_after:wN #1
15007     \else:
15008       \if_int_compare:w ##1 < \c__fp_prec_comma_int
15009         \exp_after:wN @
15010         \exp_after:wN \_fp_parse_apply_comma:NwNwN
15011         \exp_after:wN ,
15012         \exp:w
15013       \else:
15014         \exp_after:wN \_fp_parse_infix_comma:w
15015         \exp:w
15016       \fi:
15017       \_fp_parse_operand:Nw \c__fp_prec_comma_int
15018       \exp_after:wN \_fp_parse_expand:w
15019     \fi:

```

```

15020     }
15021   }
15022   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_,:N }
15023   \cs_new:Npn \__fp_parse_infix_comma:w #1 @
15024     { #1 @ \use_none:n }
15025   \cs_new:Npn \__fp_parse_apply_comma:NwNwN #1 #2@ #3 #4@ #5
15026     {
15027       \exp_after:wN \__fp_parse_continue:NwN
15028       \exp_after:wN #1
15029       \exp:w \exp_end_continue_f:w
15030       \__fp_exp_after_tuple_f:nw { }
15031       \s__fp_tuple \__fp_tuple_chk:w { #2 #4 } ;
15032       #5 #1
15033     }

```

(End definition for __fp_parse_infix_,:N, __fp_parse_infix_comma:w, and __fp_parse_apply_comma:NwNwN.)

26.7.2 Usual infix operators

As described in the “work plan”, each infix operator has an associated \..._infix... function, a computing function, and precedence, given as arguments to __fp_tmp:w. Using the general mechanism for arithmetic operations. The power operation must be associative in the opposite order from all others. For this, we use two distinct precedences.

```

\__fp_parse_infix_+:N
\__fp_parse_infix_-:N
\__fp_parse_infix_/:N
\__fp_parse_infix_mul:N
\__fp_parse_infix_and:N
\__fp_parse_infix_or:N
\__fp_parse_infix^:N
15034 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
15035   {
15036     \cs_new:Npn #1 ##1
15037       {
15038         \if_int_compare:w ##1 < #3
15039           \exp_after:wN @
15040           \exp_after:wN \__fp_parse_apply_binary:NwNwN
15041           \exp_after:wN #2
15042           \exp:w
15043           \__fp_parse_operand:Nw #4
15044           \exp_after:wN \__fp_parse_expand:w
15045         \else:
15046           \exp_after:wN @
15047           \exp_after:wN \use_none:n
15048           \exp_after:wN #1
15049         \fi:
15050       }
15051   }
15052   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix^:N } ^
15053   \c__fp_prec_hatii_int \c__fp_prec_hat_int
15054   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_/:N } /
15055   \c__fp_prec_times_int \c__fp_prec_times_int
15056   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_mul:N } *
15057   \c__fp_prec_times_int \c__fp_prec_times_int
15058   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_-:N } -
15059   \c__fp_prec_plus_int \c__fp_prec_plus_int
15060   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_+:N } +
15061   \c__fp_prec_plus_int \c__fp_prec_plus_int
15062   \exp_args:Nc \__fp_tmp:w { \__fp_parse_infix_and:N } &
15063   \c__fp_prec_and_int \c__fp_prec_and_int

```

```

15064 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_or:N } |
15065 \c__fp_prec_or_int \c__fp_prec_or_int
(End definition for \__fp_parse_infix_+:N and others.)

```

26.7.3 Juxtaposition

`__fp_parse_infix_(:N` When an opening parenthesis appears where we expect an infix operator, we compute the product of the previous operand and the contents of the parentheses using `__fp_parse_infix_mul:N`.

```

15066 \cs_new:cpn { __fp_parse_infix_(:N } #1
15067 { \__fp_parse_infix_mul:N #1 ( }
(End definition for \__fp_parse_infix_(:N.)

```

26.7.4 Multi-character cases

`__fp_parse_infix_*:N`

```

15068 \cs_set_protected:Npn \__fp_tmp:w #1
15069 {
15070   \cs_new:cpn { __fp_parse_infix_*:N } ##1##2
15071   {
15072     \if:w * \exp_not:N ##2
15073       \exp_after:wN #1
15074       \exp_after:wN ##1
15075     \else:
15076       \exp_after:wN \__fp_parse_infix_mul:N
15077       \exp_after:wN ##1
15078       \exp_after:wN ##2
15079     \fi:
15080   }
15081 }
15082 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix^:N }
(End definition for \__fp_parse_infix_*:N.)

```

`__fp_parse_infix_|:Nw`

`__fp_parse_infix_&:Nw`

```

15083 \cs_set_protected:Npn \__fp_tmp:w #1#2#3
15084 {
15085   \cs_new:Npn #1 ##1##2
15086   {
15087     \if:w #2 \exp_not:N ##2
15088       \exp_after:wN #1
15089       \exp_after:wN ##1
15090       \exp:w \exp_after:wN \__fp_parse_expand:w
15091     \else:
15092       \exp_after:wN #3
15093       \exp_after:wN ##1
15094       \exp_after:wN ##2
15095     \fi:
15096   }
15097 }
15098 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_|:N } | \__fp_parse_infix_or:N
15099 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_&:N } & \__fp_parse_infix_and:N
(End definition for \__fp_parse_infix_|:Nw and \__fp_parse_infix_&:Nw.)

```

26.7.5 Ternary operator

```

__fp_parse_infix?:N
__fp_parse_infix_:N
15100 \cs_set_protected:Npn \__fp_tmp:w #1#2#3#4
15101 {
15102   \cs_new:Npn #1 ##1
15103   {
15104     \if_int_compare:w ##1 < \c__fp_prec_quest_int
15105     #4
15106     \exp_after:wN @
15107     \exp_after:wN #2
15108     \exp:w
15109     \__fp_parse_operand:Nw #3
15110     \exp_after:wN \__fp_parse_expand:w
15111   \else:
15112     \exp_after:wN @
15113     \exp_after:wN \use_none:n
15114     \exp_after:wN #1
15115   \fi:
15116 }
15117 }
15118 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix?:N }
15119 \__fp_ternary:NwwN \c__fp_prec_quest_int { }
15120 \exp_args:Nc \__fp_tmp:w { __fp_parse_infix_:N }
15121 \__fp_ternary_auxii:NwwN \c__fp_prec_colon_int
15122 {
15123   \__kernel_msg_expandable_error:nnnn
15124   { kernel } { fp-missing } { ? } { ~for~?: }
15125 }

```

(End definition for __fp_parse_infix?:N and __fp_parse_infix_:N.)

26.7.6 Comparisons

```

__fp_parse_infix<:N
__fp_parse_infix=:N
__fp_parse_infix>:N
__fp_parse_infix!:N
__fp_parse_excl_error:
__fp_parse_compare:NNNNNNN
  __fp_parse_compare_auxi:NNNNNNN
  __fp_parse_compare_auxii:NNNNN
  __fp_parse_compare_end:NNNNw
  __fp_compare:wNNNNw
15126 \cs_new:cpn { __fp_parse_infix<:N } #1
15127 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 < }
15128 \cs_new:cpn { __fp_parse_infix=:N } #1
15129 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 = }
15130 \cs_new:cpn { __fp_parse_infix>:N } #1
15131 { \__fp_parse_compare:NNNNNNN #1 1 0 0 0 0 > }
15132 \cs_new:cpn { __fp_parse_infix!:N } #1
15133 {
15134   \exp_after:wN \__fp_parse_compare:NNNNNNN
15135   \exp_after:wN #1
15136   \exp_after:wN 0
15137   \exp_after:wN 1
15138   \exp_after:wN 1
15139   \exp_after:wN 1
15140   \exp_after:wN 1
15141 }
15142 \cs_new:Npn \__fp_parse_excl_error:
15143 {
15144   \__kernel_msg_expandable_error:nnnn

```

```

15145         { kernel } { fp-missing } { = } { ~after~!. }
15146     }
15147 \cs_new:Npn \__fp_parse_compare:NNNNNNN #1
15148 {
15149     \if_int_compare:w #1 < \c__fp_prec_comp_int
15150         \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
15151         \exp_after:wN \__fp_parse_excl_error:
15152     \else:
15153         \exp_after:wN @
15154         \exp_after:wN \use_none:n
15155         \exp_after:wN \__fp_parse_compare:NNNNNNN
15156     \fi:
15157 }
15158 \cs_new:Npn \__fp_parse_compare_auxi:NNNNNNN #1#2#3#4#5#6#7
15159 {
15160     \if_case:w
15161         \__fp_int_eval:w \exp_after:wN ' \token_to_str:N #7 - '<
15162         \__fp_int_eval_end:
15163         \__fp_parse_compare_auxii:NNNNN #2#2#4#5#6
15164     \or: \__fp_parse_compare_auxii:NNNNN #2#3#2#5#6
15165     \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#2#6
15166     \or: \__fp_parse_compare_auxii:NNNNN #2#3#4#5#2
15167     \else: #1 \__fp_parse_compare_end:NNNNw #3#4#5#6#7
15168     \fi:
15169 }
15170 \cs_new:Npn \__fp_parse_compare_auxii:NNNNN #1#2#3#4#5
15171 {
15172     \exp_after:wN \__fp_parse_compare_auxi:NNNNNNN
15173     \exp_after:wN \prg_do_nothing:
15174     \exp_after:wN #1
15175     \exp_after:wN #2
15176     \exp_after:wN #3
15177     \exp_after:wN #4
15178     \exp_after:wN #5
15179     \exp:w \exp_after:wN \__fp_parse_expand:w
15180 }
15181 \cs_new:Npn \__fp_parse_compare_end:NNNNw #1#2#3#4#5 \fi:
15182 {
15183     \fi:
15184     \exp_after:wN @
15185     \exp_after:wN \__fp_parse_apply_compare:NwNNNNNNwN
15186     \exp_after:wN \c_one_fp
15187     \exp_after:wN #1
15188     \exp_after:wN #2
15189     \exp_after:wN #3
15190     \exp_after:wN #4
15191     \exp:w
15192     \__fp_parse_operand:Nw \c__fp_prec_comp_int \__fp_parse_expand:w #5
15193 }
15194 \cs_new:Npn \__fp_parse_apply_compare:NwNNNNNNwN
15195     #1 #2@ #3 #4#5#6#7 #8@ #9
15196 {
15197     \if_int_odd:w
15198         \if_meaning:w \c_zero_fp #3

```

```

15199         0
15200     \else:
15201         \if_case:w \_fp_compare_back_any:ww #8 #2 \exp_stop_f:
15202             #5 \or: #6 \or: #7 \else: #4
15203         \fi:
15204     \fi:
15205     \exp_stop_f:
15206     \exp_after:wN \_fp_parse_apply_compare_aux:NNwN
15207     \exp_after:wN \c_one_fp
15208 \else:
15209     \exp_after:wN \_fp_parse_apply_compare_aux:NNwN
15210     \exp_after:wN \c_zero_fp
15211 \fi:
15212 #1 #8 #9
15213 }
15214 \cs_new:Npn \_fp_parse_apply_compare_aux:NNwN #1 #2 #3; #4
15215 {
15216     \if_meaning:w \_fp_parse_compare:NNNNNNN #4
15217     \exp_after:wN \_fp_parse_continue_compare:NNwNN
15218     \exp_after:wN #1
15219     \exp_after:wN #2
15220     \exp:w \exp_end_continue_f:w
15221     \_fp_exp_after_o:w #3;
15222     \exp:w \exp_end_continue_f:w
15223 \else:
15224     \exp_after:wN \_fp_parse_continue:NwN
15225     \exp_after:wN #2
15226     \exp:w \exp_end_continue_f:w
15227     \exp_after:wN #1
15228     \exp:w \exp_end_continue_f:w
15229 \fi:
15230 #4 #2
15231 }
15232 \cs_new:Npn \_fp_parse_continue_compare:NNwNN #1#2 #3@ #4#5
15233 { #4 #2 #3@ #1 }

```

(End definition for _fp_parse_infix_<:N and others.)

26.8 Tools for functions

_fp_parse_function_all_fp_o:fnw Followed by {<function name>} {<code>} <float array> @ this checks all floats are floating point numbers (no tuples).

```

15234 \cs_new:Npn \_fp_parse_function_all_fp_o:fnw #1#2#3 @
15235 {
15236     \_fp_array_if_all_fp:nTF {#3}
15237     { #2 #3 @ }
15238     {
15239         \_fp_error:nffn { fp-bad-args }
15240         {#1}
15241         { \fp_to_tl:n { \s__fp_tuple \_fp_tuple_chk:w {#3} ; } }
15242         { }
15243     \exp_after:wN \c_nan_fp
15244     }
15245 }

```


(End definition for `_fp_parse_function_all_fp_o:fnw`.)

`_fp_parse_function_one_two:nnw`
`_fp_parse_function_one_two_error_o:w`
`_fp_parse_function_one_two_aux:nnw`
`_fp_parse_function_one_two_auxii:nnw`

This is followed by $\{(function\ name)\} \{(code)\} \langle float\ array \rangle @$. It checks that the $\langle float\ array \rangle$ consists of one or two floating point numbers (not tuples), then leaves the $\langle code \rangle$ (if there is one float) or its tail (if there are two floats) followed by the $\langle float\ array \rangle$. The $\langle code \rangle$ should start with a single token such as `_fp_atan_default:w` that deals with the single-float case.

The first `_fp_if_type_fp:NTwFw` test catches the case of no argument and the case of a tuple argument. The next one distinguishes the case of a single argument (no error, just add `\c_one_fp`) from a tuple second argument. Finally check there is no further argument.

```

15246 \cs_new:Npn \_fp_parse_function_one_two:nnw #1#2#3
15247 {
15248   \_fp_if_type_fp:NTwFw
15249   #3 { } \s__fp \_fp_parse_function_one_two_error_o:w \q_stop
15250   \_fp_parse_function_one_two_aux:nnw {#1} {#2} #3
15251 }
15252 \cs_new:Npn \_fp_parse_function_one_two_error_o:w #1#2#3#4 @
15253 {
15254   \_fp_error:nffn { fp-bad-args }
15255   {#2}
15256   { \fp_to_tl:n { \s__fp_tuple \_fp_tuple_chk:w {#4} ; } }
15257   { }
15258   \exp_after:wN \c_nan_fp
15259 }
15260 \cs_new:Npn \_fp_parse_function_one_two_aux:nnw #1#2 #3; #4
15261 {
15262   \_fp_if_type_fp:NTwFw
15263   #4 { }
15264   \s__fp
15265   {
15266     \if_meaning:w @ #4
15267     \exp_after:wN \use_iv:nnnn
15268     \fi:
15269     \_fp_parse_function_one_two_error_o:w
15270   }
15271   \q_stop
15272   \_fp_parse_function_one_two_auxii:nnw {#1} {#2} #3; #4
15273 }
15274 \cs_new:Npn \_fp_parse_function_one_two_auxii:nnw #1#2#3; #4; #5
15275 {
15276   \if_meaning:w @ #5 \else:
15277   \exp_after:wN \_fp_parse_function_one_two_error_o:w
15278   \fi:
15279   \use_ii:nn {#1} { \use_none:n #2 } #3; #4; #5
15280 }

```

(End definition for `_fp_parse_function_one_two:nnw` and others.)

`_fp_tuple_map_o:nw`
`_fp_tuple_map_loop_o:nw`

Apply #1 to all items in the following tuple and expand once afterwards. The code #1 should itself expand once after its result.

```

15281 \cs_new:Npn \_fp_tuple_map_o:nw #1 \s__fp_tuple \_fp_tuple_chk:w #2 ;
15282 {

```

```

15283 \exp_after:wN \s__fp_tuple
15284 \exp_after:wN \__fp_tuple_chk:w
15285 \exp_after:wN {
15286   \exp:w \exp_end_continue_f:w
15287   \__fp_tuple_map_loop_o:nw {#1} #2
15288   { \s__fp \prg_break: } ;
15289   \prg_break_point:
15290   \exp_after:wN } \exp_after:wN ;
15291 }
15292 \cs_new:Npn \__fp_tuple_map_loop_o:nw #1#2#3 ;
15293 {
15294   \use_none:n #2
15295   #1 #2 #3 ;
15296   \exp:w \exp_end_continue_f:w
15297   \__fp_tuple_map_loop_o:nw {#1}
15298 }

```

(End definition for __fp_tuple_map_o:nw and __fp_tuple_map_loop_o:nw.)

__fp_tuple_mapthread_o:nww Apply #1 to pairs of items in the two following tuples and expand once afterwards.

```

\__fp_tuple_mapthread_loop_o:nw
15299 \cs_new:Npn \__fp_tuple_mapthread_o:nww #1
15300   \s__fp_tuple \__fp_tuple_chk:w #2 ;
15301   \s__fp_tuple \__fp_tuple_chk:w #3 ;
15302   {
15303     \exp_after:wN \s__fp_tuple
15304     \exp_after:wN \__fp_tuple_chk:w
15305     \exp_after:wN {
15306       \exp:w \exp_end_continue_f:w
15307       \__fp_tuple_mapthread_loop_o:nw {#1}
15308       #2 { \s__fp \prg_break: } ; @
15309       #3 { \s__fp \prg_break: } ;
15310       \prg_break_point:
15311       \exp_after:wN } \exp_after:wN ;
15312     }
15313   \cs_new:Npn \__fp_tuple_mapthread_loop_o:nw #1#2#3 ; #4 @ #5#6 ;
15314   {
15315     \use_none:n #2
15316     \use_none:n #5
15317     #1 #2 #3 ; #5 #6 ;
15318     \exp:w \exp_end_continue_f:w
15319     \__fp_tuple_mapthread_loop_o:nw {#1} #4 @
15320   }

```

(End definition for __fp_tuple_mapthread_o:nww and __fp_tuple_mapthread_loop_o:nw.)

26.9 Messages

```

15321 \__kernel_msg_new:nnn { kernel } { fp-deprecated }
15322 { '#1'~deprecated;~use~'#2' }
15323 \__kernel_msg_new:nnn { kernel } { unknown-fp-word }
15324 { Unknown~fp~word~#1. }
15325 \__kernel_msg_new:nnn { kernel } { fp-missing }
15326 { Missing~#1~inserted #2. }
15327 \__kernel_msg_new:nnn { kernel } { fp-extra }
15328 { Extra~#1~ignored. }

```

```

15329 \__kernel_msg_new:nnn { kernel } { fp-early-end }
15330 { Premature~end~in~fp~expression. }
15331 \__kernel_msg_new:nnn { kernel } { fp-after-e }
15332 { Cannot~use~#1 after~'e'. }
15333 \__kernel_msg_new:nnn { kernel } { fp-missing-number }
15334 { Missing~number~before~'#1'. }
15335 \__kernel_msg_new:nnn { kernel } { fp-unknown-symbol }
15336 { Unknown~symbol~#1~ignored. }
15337 \__kernel_msg_new:nnn { kernel } { fp-extra-comma }
15338 { Unexpected~comma~turned~to~nan~result. }
15339 \__kernel_msg_new:nnn { kernel } { fp-no-arg }
15340 { #1~got~no~argument;~used~nan. }
15341 \__kernel_msg_new:nnn { kernel } { fp-multi-arg }
15342 { #1~got~more~than~one~argument;~used~nan. }
15343 \__kernel_msg_new:nnn { kernel } { fp-num-args }
15344 { #1~expects~between~#2~and~#3~arguments. }
15345 \__kernel_msg_new:nnn { kernel } { fp-bad-args }
15346 { Arguments~in~#1#2~are~invalid. }
15347 \__kernel_msg_new:nnn { kernel } { fp-infty-pi }
15348 { Math~command~#1 is~not~an~fp }
15349 (*package)
15350 \cs_if_exist:cT { @unexpandable@protect }
15351 {
15352   \__kernel_msg_new:nnn { kernel } { fp-robust-cmd }
15353   { Robust~command~#1 invalid~in~fp~expression! }
15354 }
15355 </package>
15356 </initex | package>

```

27 l3fp-assign implementation

```

15357 (*initex | package)
15358 <@@=fp>

```

27.1 Assigning values

\fp_new:N Floating point variables are initialized to be +0.

```

15359 \cs_new_protected:Npn \fp_new:N #1
15360 { \cs_new_eq:NN #1 \c_zero_fp }
15361 \cs_generate_variant:Nn \fp_new:N {c}

```

(End definition for \fp_new:N. This function is documented on page 184.)

\fp_set:Nn Simply use __fp_parse:n within various f-expanding assignments.

\fp_set:cn

\fp_gset:Nn

\fp_gset:cn

\fp_const:Nn

\fp_const:cn

```

15362 \cs_new_protected:Npn \fp_set:Nn #1#2
15363 { \tl_set:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
15364 \cs_new_protected:Npn \fp_gset:Nn #1#2
15365 { \tl_gset:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
15366 \cs_new_protected:Npn \fp_const:Nn #1#2
15367 { \tl_const:Nx #1 { \exp_not:f { \__fp_parse:n {#2} } } }
15368 \cs_generate_variant:Nn \fp_set:Nn {c}
15369 \cs_generate_variant:Nn \fp_gset:Nn {c}
15370 \cs_generate_variant:Nn \fp_const:Nn {c}

```

(End definition for `\fp_set:Nn`, `\fp_gset:Nn`, and `\fp_const:Nn`. These functions are documented on page 185.)

`\fp_set_eq:NN` Copying a floating point is the same as copying the underlying token list.
`\fp_set_eq:cN` 15371 `\cs_new_eq:NN \fp_set_eq:NN \tl_set_eq:NN`
`\fp_set_eq:Nc` 15372 `\cs_new_eq:NN \fp_gset_eq:NN \tl_gset_eq:NN`
`\fp_set_eq:cc` 15373 `\cs_generate_variant:Nn \fp_set_eq:NN { c , Nc , cc }`
`\fp_gset_eq:NN` 15374 `\cs_generate_variant:Nn \fp_gset_eq:NN { c , Nc , cc }`
`\fp_gset_eq:cN` (End definition for `\fp_set_eq:NN` and `\fp_gset_eq:NN`. These functions are documented on page 185.)
`\fp_gset_eq:Nc`
`\fp_gset_eq:cc`
`\fp_zero:N` Setting a floating point to zero: copy `\c_zero_fp`.
`\fp_zero:c` 15375 `\cs_new_protected:Npn \fp_zero:N #1 { \fp_set_eq:NN #1 \c_zero_fp }`
`\fp_gzero:N` 15376 `\cs_new_protected:Npn \fp_gzero:N #1 { \fp_gset_eq:NN #1 \c_zero_fp }`
`\fp_gzero:c` 15377 `\cs_generate_variant:Nn \fp_zero:N { c }`
15378 `\cs_generate_variant:Nn \fp_gzero:N { c }`
(End definition for `\fp_zero:N` and `\fp_gzero:N`. These functions are documented on page 184.)

`\fp_zero_new:N` Set the floating point to zero, or define it if needed.
`\fp_zero_new:c` 15379 `\cs_new_protected:Npn \fp_zero_new:N #1`
`\fp_gzero_new:N` 15380 `{ \fp_if_exist:NTF #1 { \fp_zero:N #1 } { \fp_new:N #1 } }`
`\fp_gzero_new:c` 15381 `\cs_new_protected:Npn \fp_gzero_new:N #1`
15382 `{ \fp_if_exist:NTF #1 { \fp_gzero:N #1 } { \fp_new:N #1 } }`
15383 `\cs_generate_variant:Nn \fp_zero_new:N { c }`
15384 `\cs_generate_variant:Nn \fp_gzero_new:N { c }`
(End definition for `\fp_zero_new:N` and `\fp_gzero_new:N`. These functions are documented on page 185.)

27.2 Updating values

These match the equivalent functions in `l3int` and `l3skip`.

`\fp_add:Nn` For the sake of error recovery we should not simply set `#1` to `#1 ± (#2)`: for instance, if `#2`
`\fp_add:cN` is 0)+2, the parsing error would be raised at the last closing parenthesis rather than at
`\fp_gadd:Nn` the closing parenthesis in the user argument. Thus we evaluate `#2` instead of just putting
`\fp_gadd:cN` parentheses. As an optimization we use `__fp_parse:n` rather than `\fp_eval:n`, which
`\fp_sub:Nn` would convert the result away from the internal representation and back.
`\fp_sub:cN` 15385 `\cs_new_protected:Npn \fp_add:Nn { __fp_add:NNNn \fp_set:Nn + }`
`\fp_gsub:Nn` 15386 `\cs_new_protected:Npn \fp_gadd:Nn { __fp_add:NNNn \fp_gset:Nn + }`
`\fp_gsub:cN` 15387 `\cs_new_protected:Npn \fp_sub:Nn { __fp_add:NNNn \fp_set:Nn - }`
`__fp_add:NNNn` 15388 `\cs_new_protected:Npn \fp_gsub:Nn { __fp_add:NNNn \fp_gset:Nn - }`
15389 `\cs_new_protected:Npn __fp_add:NNNn #1#2#3#4`
15390 `{ #1 #3 { #3 #2 __fp_parse:n {#4} } }`
15391 `\cs_generate_variant:Nn \fp_add:Nn { c }`
15392 `\cs_generate_variant:Nn \fp_gadd:Nn { c }`
15393 `\cs_generate_variant:Nn \fp_sub:Nn { c }`
15394 `\cs_generate_variant:Nn \fp_gsub:Nn { c }`
(End definition for `\fp_add:Nn` and others. These functions are documented on page 185.)

27.3 Showing values

`\fp_show:N` This shows the result of computing its argument by passing the right data to `\tl_show:n` or `\tl_log:n`.

`\fp_show:c`

`\fp_log:N` 15395 `\cs_new_protected:Npn \fp_show:N { __fp_show:NN \tl_show:n }`

`\fp_log:c` 15396 `\cs_generate_variant:Nn \fp_show:N { c }`

`__fp_show:NN` 15397 `\cs_new_protected:Npn \fp_log:N { __fp_show:NN \tl_log:n }`

15398 `\cs_generate_variant:Nn \fp_log:N { c }`

15399 `\cs_new_protected:Npn __fp_show:NN #1#2`

15400 `{`

15401 `__kernel_chk_defined:NT #2`

15402 `{ \exp_args:Nx #1 { \token_to_str:N #2 = \fp_to_tl:N #2 } }`

15403 `}`

(End definition for `\fp_show:N`, `\fp_log:N`, and `__fp_show:NN`. These functions are documented on page 192.)

`\fp_show:n` Use general tools.

`\fp_log:n` 15404 `\cs_new_protected:Npn \fp_show:n`

15405 `{ \msg_show_eval:Nn \fp_to_tl:n }`

15406 `\cs_new_protected:Npn \fp_log:n`

15407 `{ \msg_log_eval:Nn \fp_to_tl:n }`

(End definition for `\fp_show:n` and `\fp_log:n`. These functions are documented on page 192.)

27.4 Some useful constants and scratch variables

`\c_one_fp` Some constants.

`\c_e_fp` 15408 `\fp_const:Nn \c_e_fp { 2.718 2818 2845 9045 }`

15409 `\fp_const:Nn \c_one_fp { 1 }`

(End definition for `\c_one_fp` and `\c_e_fp`. These variables are documented on page 190.)

`\c_pi_fp` We simply round π to and $\pi/180$ to 16 significant digits.

`\c_one_degree_fp` 15410 `\fp_const:Nn \c_pi_fp { 3.141 5926 5358 9793 }`

15411 `\fp_const:Nn \c_one_degree_fp { 0.0 1745 3292 5199 4330 }`

(End definition for `\c_pi_fp` and `\c_one_degree_fp`. These variables are documented on page 191.)

`\l_tmpa_fp` Scratch variables are simply initialized there.

`\l_tmpb_fp` 15412 `\fp_new:N \l_tmpa_fp`

`\g_tmpa_fp` 15413 `\fp_new:N \l_tmpb_fp`

`\g_tmpb_fp` 15414 `\fp_new:N \g_tmpa_fp`

15415 `\fp_new:N \g_tmpb_fp`

(End definition for `\l_tmpa_fp` and others. These variables are documented on page 191.)

15416 `</initex | package>`

28 l3fp-logic Implementation

15417 $\langle *initex | package \rangle$

15418 $\langle @@=fp \rangle$

$\backslash_fp_parse_word_max:N$

$\backslash_fp_parse_word_min:N$

Those functions may receive a variable number of arguments.

15419 $\backslash cs_new:Npn \backslash_fp_parse_word_max:N$

15420 $\{ \backslash_fp_parse_function:NNN \backslash_fp_minmax_o:Nw 2 \}$

15421 $\backslash cs_new:Npn \backslash_fp_parse_word_min:N$

15422 $\{ \backslash_fp_parse_function:NNN \backslash_fp_minmax_o:Nw 0 \}$

(End definition for $\backslash_fp_parse_word_max:N$ and $\backslash_fp_parse_word_min:N$.)

28.1 Syntax of internal functions

- $\backslash_fp_compare_npos:nwnw \{ \langle expo_1 \rangle \} \langle body_1 \rangle ; \{ \langle expo_2 \rangle \} \langle body_2 \rangle ;$
- $\backslash_fp_minmax_o:Nw \langle sign \rangle \langle floating\ point\ array \rangle$
- $\backslash_fp_not_o:w ? \langle floating\ point\ array \rangle$ (with one floating point number only)
- $\backslash_fp_ \& _o:ww \langle floating\ point \rangle \langle floating\ point \rangle$
- $\backslash_fp_ | _o:ww \langle floating\ point \rangle \langle floating\ point \rangle$
- $\backslash_fp_ternary:NwwN, \backslash_fp_ternary_auxi:NwwN, \backslash_fp_ternary_auxii:NwwN$ have to be understood.

28.2 Existence test

$\backslash fp_if_exist_p:N$

$\backslash fp_if_exist_p:c$

$\backslash fp_if_exist:N\overline{TF}$

$\backslash fp_if_exist:c\overline{TF}$

Copies of the cs functions defined in l3basics.

15423 $\backslash prg_new_eq_conditional:NNn \backslash fp_if_exist:N \backslash cs_if_exist:N \{ TF , T , F , p \}$

15424 $\backslash prg_new_eq_conditional:NNn \backslash fp_if_exist:c \backslash cs_if_exist:c \{ TF , T , F , p \}$

(End definition for $\backslash fp_if_exist:N\overline{TF}$. This function is documented on page 187.)

28.3 Comparison

$\backslash fp_compare_p:n$

$\backslash fp_compare:n\overline{TF}$

$\backslash_fp_compare_return:w$

Within floating point expressions, comparison operators are treated as operations, so we evaluate #1, then compare with ± 0 . Tuples are true.

15425 $\backslash prg_new_conditional:Npnn \backslash fp_compare:n \#1 \{ p , T , F , TF \}$

15426 $\{$

15427 $\backslash exp_after:wN \backslash_fp_compare_return:w$

15428 $\backslash exp:w \backslash exp_end_continue_f:w \backslash_fp_parse:n \{ \#1 \}$

15429 $\}$

15430 $\backslash cs_new:Npn \backslash_fp_compare_return:w \#1\#2\#3;$

15431 $\{$

15432 $\backslash if_charcode:w 0$

15433 $\backslash_fp_if_type_fp:NTwFw$

15434 $\#1 \{ \backslash use_i_delimit_by_q_stop:nw \#3 \backslash q_stop \}$

15435 $\backslash s_fp 1 \backslash q_stop$

15436 $\backslash prg_return_false:$

15437 $\backslash else:$

15438 $\backslash prg_return_true:$

15439 $\backslash fi:$

15440 $\}$

(End definition for `\fp_compare:nTF` and `__fp_compare_return:w`. This function is documented on page 188.)

`\fp_compare_p:nNn` Evaluate #1 and #3, using an auxiliary to expand both, and feed the two floating point numbers swapped to `__fp_compare_back_any:ww`, defined below. Compare the result with '`#2-'`', which is -1 for $<$, 0 for $=$, 1 for $>$ and 2 for $?$.

```

15441 \prg_new_conditional:Npnn \fp_compare:nNn #1#2#3 { p , T , F , TF }
15442 {
15443   \if_int_compare:w
15444     \exp_after:wN \__fp_compare_aux:wn
15445     \exp:w \exp_end_continue_f:w \__fp_parse:n {#1} {#3}
15446     = \__fp_int_eval:w '#2 - ' = \__fp_int_eval_end:
15447     \prg_return_true:
15448   \else:
15449     \prg_return_false:
15450   \fi:
15451 }
15452 \cs_new:Npn \__fp_compare_aux:wn #1; #2
15453 {
15454   \exp_after:wN \__fp_compare_back_any:ww
15455   \exp:w \exp_end_continue_f:w \__fp_parse:n {#2} #1;
15456 }

```

(End definition for `\fp_compare:nNnTF` and `__fp_compare_aux:wn`. This function is documented on page 187.)

`__fp_compare_back_any:ww` `__fp_compare_back_any:ww` $\langle y \rangle$; $\langle x \rangle$;
`__fp_compare_back:ww` Expands (in the same way as `\int_eval:n`) to -1 if $x < y$, 0 if $x = y$, 1 if $x > y$,
`__fp_compare_nan:w` and 2 otherwise (denoted as $x?y$). If either operand is `nan`, stop the comparison with
`__fp_compare_nan:w` returning 2 . If x is negative, swap the outputs 1 and -1 (i.e., $>$
and $<$); we can henceforth assume that $x \geq 0$. If $y \geq 0$, and they have the same type,
either they are normal and we compare them with `__fp_compare_npos:wnnw`, or they
are equal. If $y \geq 0$, but of a different type, the highest type is a larger number. Finally,
if $y \leq 0$, then $x > y$, unless both are zero.

```

15457 \cs_new:Npn \__fp_compare_back_any:ww #1#2; #3
15458 {
15459   \__fp_if_type_fp:NTwFw
15460   #1 { \__fp_if_type_fp:NTwFw #3 \use_i:nn \s__fp \use_ii:nn \q_stop }
15461   \s__fp \use_ii:nn \q_stop
15462   \__fp_compare_back:ww
15463   {
15464     \cs:w
15465     __fp
15466     \__fp_type_from_scan:N #1
15467     _compare_back
15468     \__fp_type_from_scan:N #3
15469     :ww
15470   \cs_end:
15471   }
15472   #1#2 ; #3
15473 }
15474 \cs_new:Npn \__fp_compare_back:ww
15475   \s__fp \__fp_chk:w #1 #2 #3;
15476   \s__fp \__fp_chk:w #4 #5 #6;

```

```

15477 {
15478   \int_value:w
15479   \if_meaning:w 3 #1 \exp_after:wN \__fp_compare_nan:w \fi:
15480   \if_meaning:w 3 #4 \exp_after:wN \__fp_compare_nan:w \fi:
15481   \if_meaning:w 2 #5 - \fi:
15482   \if_meaning:w #2 #5
15483     \if_meaning:w #1 #4
15484       \if_meaning:w 1 #1
15485         \__fp_compare_npos:nwnw #6; #3;
15486       \else:
15487         0
15488       \fi:
15489     \else:
15490       \if_int_compare:w #4 < #1 - \fi: 1
15491     \fi:
15492   \else:
15493     \if_int_compare:w #1#4 = 0 \exp_stop_f:
15494     0
15495   \else:
15496     1
15497   \fi:
15498 \fi:
15499 \exp_stop_f:
15500 }
15501 \cs_new:Npn \__fp_compare_nan:w #1 \fi: \exp_stop_f: { 2 \exp_stop_f: }

```

(End definition for __fp_compare_back_any:ww, __fp_compare_back:ww, and __fp_compare_nan:w.)

__fp_compare_back_tuple:ww Tuple and floating point numbers are not comparable so return 2 in mixed cases or
 __fp_tuple_compare_back:ww when tuples have a different number of items. Otherwise compare pairs of items with
 __fp_tuple_compare_back_tuple:ww __fp_compare_back_any:ww and if any don't match return 2 (as \int_value:w 02
 __fp_tuple_compare_back_loop:w \exp_stop_f:).

```

15502 \cs_new:Npn \__fp_compare_back_tuple:ww #1; #2; { 2 }
15503 \cs_new:Npn \__fp_tuple_compare_back:ww #1; #2; { 2 }
15504 \cs_new:Npn \__fp_tuple_compare_back_tuple:ww
15505   \s__fp_tuple \__fp_tuple_chk:w #1;
15506   \s__fp_tuple \__fp_tuple_chk:w #2;
15507   {
15508     \int_compare:nNnTF { \__fp_array_count:n {#1} } =
15509     { \__fp_array_count:n {#2} }
15510     {
15511       \int_value:w 0
15512       \__fp_tuple_compare_back_loop:w
15513         #1 { \s__fp \prg_break: } ; @
15514         #2 { \s__fp \prg_break: } ;
15515       \prg_break_point:
15516       \exp_stop_f:
15517     }
15518     { 2 }
15519   }
15520 \cs_new:Npn \__fp_tuple_compare_back_loop:w #1#2 ; #3 @ #4#5 ;
15521 {
15522   \use_none:n #1
15523   \use_none:n #4

```



```

15524 \if_int_compare:w
15525 \__fp_compare_back_any:ww #1 #2 ; #4 #5 ; = 0 \exp_stop_f:
15526 \else:
15527 2 \exp_after:wN \prg_break:
15528 \fi:
15529 \__fp_tuple_compare_back_loop:w #3 @
15530 }

```

(End definition for __fp_compare_back_tuple:ww and others.)

```

\__fp_compare_npos:nwnw
\__fp_compare_significand:nnnnnnnn

```

__fp_compare_npos:nwnw { $\langle expo_1 \rangle$ } $\langle body_1 \rangle$; { $\langle expo_2 \rangle$ } $\langle body_2 \rangle$;
 Within an \int_value:w ... \exp_stop_f: construction, this expands to 0 if the two numbers are equal, -1 if the first is smaller, and 1 if the first is bigger. First compare the exponents: the larger one denotes the larger number. If they are equal, we must compare significands. If both the first 8 digits and the next 8 digits coincide, the numbers are equal. If only the first 8 digits coincide, the next 8 decide. Otherwise, the first 8 digits are compared.

```

15531 \cs_new:Npn \__fp_compare_npos:nwnw #1#2; #3#4;
15532 {
15533 \if_int_compare:w #1 = #3 \exp_stop_f:
15534 \__fp_compare_significand:nnnnnnnn #2 #4
15535 \else:
15536 \if_int_compare:w #1 < #3 - \fi: 1
15537 \fi:
15538 }
15539 \cs_new:Npn \__fp_compare_significand:nnnnnnnn #1#2#3#4#5#6#7#8
15540 {
15541 \if_int_compare:w #1#2 = #5#6 \exp_stop_f:
15542 \if_int_compare:w #3#4 = #7#8 \exp_stop_f:
15543 0
15544 \else:
15545 \if_int_compare:w #3#4 < #7#8 - \fi: 1
15546 \fi:
15547 \else:
15548 \if_int_compare:w #1#2 < #5#6 - \fi: 1
15549 \fi:
15550 }

```

(End definition for __fp_compare_npos:nwnw and __fp_compare_significand:nnnnnnnn.)

28.4 Floating point expression loops

\fp_do_until:nn These are quite easy given the above functions. The do_until and do_while versions execute the body, then test. The until_do and while_do do it the other way round.

```

\fp_do_while:nn
\fp_until_do:nn
\fp_while_do:nn
15551 \cs_new:Npn \fp_do_until:nn #1#2
15552 {
15553 #2
15554 \fp_compare:nF {#1}
15555 { \fp_do_until:nn {#1} {#2} }
15556 }
15557 \cs_new:Npn \fp_do_while:nn #1#2
15558 {
15559 #2
15560 \fp_compare:nT {#1}

```

```

15561     { \fp_do_while:nn {#1} {#2} }
15562   }
15563 \cs_new:Npn \fp_until_do:nn #1#2
15564 {
15565   \fp_compare:nF {#1}
15566   {
15567     #2
15568     \fp_until_do:nn {#1} {#2}
15569   }
15570 }
15571 \cs_new:Npn \fp_while_do:nn #1#2
15572 {
15573   \fp_compare:nT {#1}
15574   {
15575     #2
15576     \fp_while_do:nn {#1} {#2}
15577   }
15578 }

```

(End definition for `\fp_do_until:nn` and others. These functions are documented on page 189.)

`\fp_do_until:nNnn` As above but not using the `nNn` syntax.

```

\fp_do_while:nNnn
\fp_until_do:nNnn
\fp_while_do:nNnn
15579 \cs_new:Npn \fp_do_until:nNnn #1#2#3#4
15580 {
15581   #4
15582   \fp_compare:nNnF {#1} #2 {#3}
15583   { \fp_do_until:nNnn {#1} #2 {#3} {#4} }
15584 }
15585 \cs_new:Npn \fp_do_while:nNnn #1#2#3#4
15586 {
15587   #4
15588   \fp_compare:nNnT {#1} #2 {#3}
15589   { \fp_do_while:nNnn {#1} #2 {#3} {#4} }
15590 }
15591 \cs_new:Npn \fp_until_do:nNnn #1#2#3#4
15592 {
15593   \fp_compare:nNnF {#1} #2 {#3}
15594   {
15595     #4
15596     \fp_until_do:nNnn {#1} #2 {#3} {#4}
15597   }
15598 }
15599 \cs_new:Npn \fp_while_do:nNnn #1#2#3#4
15600 {
15601   \fp_compare:nNnT {#1} #2 {#3}
15602   {
15603     #4
15604     \fp_while_do:nNnn {#1} #2 {#3} {#4}
15605   }
15606 }

```

(End definition for `\fp_do_until:nNnn` and others. These functions are documented on page 188.)

`\fp_step_function:nnnN` The approach here is somewhat similar to `\int_step_function:nnnN`. There are two subtleties: we use the internal parser `__fp_parse:n` to avoid converting back and forth

```

\fp_step_function:nnnc
  \__fp_step:wwwN
\__fp_step:wwwN
  \__fp_step:NnnnnN
  \__fp_step:NfnnnN

```

from the internal representation; and (due to rounding) even a non-zero step does not guarantee that the loop counter increases.

```

15607 \cs_new:Npn \fp_step_function:nnnN #1#2#3
15608 {
15609     \exp_after:wN \__fp_step:wwwN
15610     \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#1}
15611     \exp:w \exp_end_continue_f:w \__fp_parse_o:n {#2}
15612     \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
15613 }
15614 \cs_generate_variant:Nn \fp_step_function:nnnN { nnnC }
15615 % \end{macrocode}
15616 % Only floating point numbers (not tuples) are allowed arguments.
15617 % Only \enquote{normal} floating points (not $\pm 0$,
15618 % $\pm\texttt{\textit{inf}}$, $\texttt{\textit{nan}}$) can be used as step; if positive,
15619 % call \cs{__fp_step:NnnnnN} with argument |>| otherwise~|<|. This
15620 % function has one more argument than its integer counterpart, namely
15621 % the previous value, to catch the case where the loop has made no
15622 % progress. Conversion to decimal is done just before calling the
15623 % user's function.
15624 % \begin{macrocode}
15625 \cs_new:Npn \__fp_step:wwwN #1#2; #3#4; #5#6; #7
15626 {
15627     \__fp_if_type_fp:NTwFw #1 { } \s__fp \prg_break: \q_stop
15628     \__fp_if_type_fp:NTwFw #3 { } \s__fp \prg_break: \q_stop
15629     \__fp_if_type_fp:NTwFw #5 { } \s__fp \prg_break: \q_stop
15630     \use_i:nnnn { \__fp_step_fp:wwwN #1#2; #3#4; #5#6; #7 }
15631     \prg_break_point:
15632     \use:n
15633     {
15634         \__fp_error:nfff { fp-step-tuple } { \fp_to_tl:n { #1#2 ; } }
15635         { \fp_to_tl:n { #3#4 ; } } { \fp_to_tl:n { #5#6 ; } }
15636     }
15637 }
15638 \cs_new:Npn \__fp_step_fp:wwwN #1 ; \s__fp \__fp_chk:w #2#3#4 ; #5; #6
15639 {
15640     \token_if_eq_meaning:NNTF #2 1
15641     {
15642         \token_if_eq_meaning:NNTF #3 0
15643         { \__fp_step:NnnnnN > }
15644         { \__fp_step:NnnnnN < }
15645     }
15646     {
15647         \token_if_eq_meaning:NNTF #2 0
15648         {
15649             \__kernel_msg_expandable_error:nnn { kernel }
15650             { zero-step } {#6}
15651         }
15652         {
15653             \__fp_error:nnfn { fp-bad-step } { }
15654             { \fp_to_tl:n { \s__fp \__fp_chk:w #2#3#4 ; } } {#6}
15655         }
15656         \use_none:nnnnn
15657     }
15658     { #1 ; } { \c_nan_fp } { \s__fp \__fp_chk:w #2#3#4 ; } { #5 ; } { #6

```

```

15659 }
15660 \cs_new:Npn \__fp_step:NnnnnN #1#2#3#4#5#6
15661 {
15662   \fp_compare:nNnTF {#2} = {#3}
15663   {
15664     \__fp_error:nffn { fp-tiny-step }
15665     { \fp_to_tl:n {#3} } { \fp_to_tl:n {#4} } {#6}
15666   }
15667   {
15668     \fp_compare:nNnF {#2} #1 {#5}
15669     {
15670       \exp_args:Nf #6 { \__fp_to_decimal_dispatch:w #2 }
15671       \__fp_step:NfnnnnN
15672       #1 { \__fp_parse:n { #2 + #4 } } {#2} {#4} {#5} #6
15673     }
15674   }
15675 }
15676 \cs_generate_variant:Nn \__fp_step:NnnnnN { Nf }

```

(End definition for `\fp_step_function:nnnN` and others. This function is documented on page 190.)

`\fp_step_inline:nnnn` As for `\int_step_inline:nnnn`, create a global function and apply it, following up with
`\fp_step_variable:nnnNn` a break point.

```

\__fp_step:NNnnnn
15677 \cs_new_protected:Npn \fp_step_inline:nnnn
15678 {
15679   \int_gincr:N \g__kernel_prg_map_int
15680   \exp_args:NNc \__fp_step:NNnnnn
15681   \cs_gset_protected:Npn
15682   { __fp_map_ \int_use:N \g__kernel_prg_map_int :w }
15683 }
15684 \cs_new_protected:Npn \fp_step_variable:nnnNn #1#2#3#4#5
15685 {
15686   \int_gincr:N \g__kernel_prg_map_int
15687   \exp_args:NNc \__fp_step:NNnnnn
15688   \cs_gset_protected:Npx
15689   { __fp_map_ \int_use:N \g__kernel_prg_map_int :w }
15690   {#1} {#2} {#3}
15691   {
15692     \tl_set:Nn \exp_not:N #4 {##1}
15693     \exp_not:n {#5}
15694   }
15695 }
15696 \cs_new_protected:Npn \__fp_step:NNnnnn #1#2#3#4#5#6
15697 {
15698   #1 #2 ##1 {#6}
15699   \fp_step_function:nnnN {#3} {#4} {#5} #2
15700   \prg_break_point:Nn \scan_stop: { \int_gdecr:N \g__kernel_prg_map_int }
15701 }

```

(End definition for `\fp_step_inline:nnnn`, `\fp_step_variable:nnnNn`, and `__fp_step:NNnnnn`. These functions are documented on page 190.)

```

15702 \__kernel_msg_new:nnn { kernel } { fp-step-tuple }
15703 { Tuple~argument~in~fp_step...~{#1}{#2}{#3}. }
15704 \__kernel_msg_new:nnn { kernel } { fp-bad-step }

```

```

15705 { Invalid~step~size~#2~in~step~function~#3. }
15706 \__kernel_msg_new:nnn { kernel } { fp~tiny~step }
15707 { Tiny~step~size~(#1+#2=#1)~in~step~function~#3. }

```

28.5 Extrema

__fp_minmax_o:Nw
__fp_minmax_aux_o:Nw

First check all operands are floating point numbers. The argument #1 is 2 to find the maximum of an array #2 of floating point numbers, and 0 to find the minimum. We read numbers sequentially, keeping track of the largest (smallest) number found so far. If numbers are equal (for instance ± 0), the first is kept. We append $-\infty$ (∞), for the case of an empty array. Since no number is smaller (larger) than that, this additional item only affects the maximum (minimum) in the case of `max()` and `min()` with no argument. The weird fp-like trailing marker breaks the loop correctly: see the precise definition of `__fp_minmax_loop:Nww`.

```

15708 \cs_new:Npn \__fp_minmax_o:Nw #1
15709 {
15710   \__fp_parse_function_all_fp_o:fnw
15711   { \token_if_eq_meaning:NNTF 0 #1 { min } { max } }
15712   { \__fp_minmax_aux_o:Nw #1 }
15713 }
15714 \cs_new:Npn \__fp_minmax_aux_o:Nw #1#2 @
15715 {
15716   \if_meaning:w 0 #1
15717   \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN +
15718   \else:
15719   \exp_after:wN \__fp_minmax_loop:Nww \exp_after:wN -
15720   \fi:
15721   #2
15722   \s__fp \__fp_chk:w 2 #1 \s__fp_exact ;
15723   \s__fp \__fp_chk:w { 3 \__fp_minmax_break_o:w } ;
15724 }

```

(End definition for `__fp_minmax_o:Nw` and `__fp_minmax_aux_o:Nw`.)

__fp_minmax_loop:Nww

The first argument is `-` or `+` to denote the case where the currently largest (smallest) number found (first floating point argument) should be replaced by the new number (second floating point argument). If the new number is `nan`, keep that as the extremum, unless that extremum is already a `nan`. Otherwise, compare the two numbers. If the new number is larger (in the case of `max`) or smaller (in the case of `min`), the test yields `true`, and we keep the second number as a new maximum; otherwise we keep the first number. Then loop.

```

15725 \cs_new:Npn \__fp_minmax_loop:Nww
15726   #1 \s__fp \__fp_chk:w #2#3; \s__fp \__fp_chk:w #4#5;
15727 {
15728   \if_meaning:w 3 #4
15729   \if_meaning:w 3 #2
15730   \__fp_minmax_auxi:ww
15731   \else:
15732   \__fp_minmax_auxii:ww
15733   \fi:
15734   \else:
15735   \if_int_compare:w
15736     \__fp_compare_back:ww

```

```

15737         \s__fp \__fp_chk:w #4#5;
15738         \s__fp \__fp_chk:w #2#3;
15739         = #1 1 \exp_stop_f:
15740         \__fp_minmax_auxii:ww
15741     \else:
15742         \__fp_minmax_auxi:ww
15743     \fi:
15744 \fi:
15745 \__fp_minmax_loop:Nww #1
15746     \s__fp \__fp_chk:w #2#3;
15747     \s__fp \__fp_chk:w #4#5;
15748 }

```

(End definition for __fp_minmax_loop:Nww.)

```

\__fp_minmax_auxi:ww Keep the first/second number, and remove the other.
\__fp_minmax_auxii:ww
15749 \cs_new:Npn \__fp_minmax_auxi:ww #1 \fi: \fi: #2 \s__fp #3 ; \s__fp #4;
15750 { \fi: \fi: #2 \s__fp #3 ; }
15751 \cs_new:Npn \__fp_minmax_auxii:ww #1 \fi: \fi: #2 \s__fp #3 ;
15752 { \fi: \fi: #2 }

```

(End definition for __fp_minmax_auxi:ww and __fp_minmax_auxii:ww.)

__fp_minmax_break_o:w This function is called from within an \if_meaning:w test. Skip to the end of the tests, close the current test with \fi:, clean up, and return the appropriate number with one post-expansion.

```

15753 \cs_new:Npn \__fp_minmax_break_o:w #1 \fi: \fi: #2 \s__fp #3; #4;
15754 { \fi: \__fp_exp_after_o:w \s__fp #3; }

```

(End definition for __fp_minmax_break_o:w.)

28.6 Boolean operations

__fp_not_o:w Return true or false, with two expansions, one to exit the conditional, and one to please l3fp-parse. The first argument is provided by l3fp-parse and is ignored.

```

15755 \cs_new:Npn \__fp_not_o:w #1 \s__fp \__fp_chk:w #2#3; @
15756 {
15757     \if_meaning:w 0 #2
15758     \exp_after:wN \exp_after:wN \exp_after:wN \c_one_fp
15759     \else:
15760     \exp_after:wN \exp_after:wN \exp_after:wN \c_zero_fp
15761     \fi:
15762 }
15763 \cs_new:Npn \__fp_tuple_not_o:w #1 @ { \exp_after:wN \c_zero_fp }

```

(End definition for __fp_not_o:w and __fp_tuple_not_o:w.)

__fp_&_o:w For and, if the first number is zero, return it (with the same sign). Otherwise, return the second one. For or, the logic is reversed: if the first number is non-zero, return it, otherwise return the second number: we achieve that by hi-jacking __fp_&_o:w, inserting an extra argument, \else:, before \s__fp. In all cases, expand after the floating point number.

```

\__fp_&_o:w
\__fp_tuple_&_o:w
\__fp_&_tuple_o:w
\__fp_tuple_&_tuple_o:w
\__fp_|_o:w
\__fp_tuple_|_o:w
\__fp_|_tuple_o:w
\__fp_tuple_|_tuple_o:w
\__fp_and_return:wNw
15764 \group_begin:
15765 \char_set_catcode_letter:N &

```

```

15766 \char_set_catcode_letter:N |
15767 \cs_new:Npn \__fp_&_o:ww #1 \s__fp \__fp_chk:w #2#3;
15768 {
15769     \if_meaning:w 0 #2 #1
15770     \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
15771     \fi:
15772     \__fp_exp_after_o:w
15773 }
15774 \cs_new:Npn \__fp_&_tuple_o:ww #1 \s__fp \__fp_chk:w #2#3;
15775 {
15776     \if_meaning:w 0 #2 #1
15777     \__fp_and_return:wNw \s__fp \__fp_chk:w #2#3;
15778     \fi:
15779     \__fp_exp_after_tuple_o:w
15780 }
15781 \cs_new:Npn \__fp_tuple_&_o:ww #1; { \__fp_exp_after_o:w }
15782 \cs_new:Npn \__fp_tuple_&_tuple_o:ww #1; { \__fp_exp_after_tuple_o:w }
15783 \cs_new:Npn \__fp_|_o:ww { \__fp_&_o:ww \else: }
15784 \cs_new:Npn \__fp_|_tuple_o:ww { \__fp_&_tuple_o:ww \else: }
15785 \cs_new:Npn \__fp_tuple_|_o:ww #1; #2; { \__fp_exp_after_tuple_o:w #1; }
15786 \cs_new:Npn \__fp_tuple_|_tuple_o:ww #1; #2;
15787 { \__fp_exp_after_tuple_o:w #1; }
15788 \group_end:
15789 \cs_new:Npn \__fp_and_return:wNw #1; \fi: #2;
15790 { \fi: \__fp_exp_after_o:w #1; }

```

(End definition for __fp_&_o:ww and others.)

28.7 Ternary operator

__fp_ternary:NwwN The first function receives the test and the true branch of the ?: ternary operator. __fp_ternary_auxi:NwwN It calls __fp_ternary_auxii:NwwN if the test branch is a floating point number ± 0 , and otherwise calls __fp_ternary_auxi:NwwN. These functions select one of their two arguments.

```

15791 \cs_new:Npn \__fp_ternary:NwwN #1 #2#3@ #4@ #5
15792 {
15793     \if_meaning:w \__fp_parse_infix_:N #5
15794     \if_charcode:w 0
15795         \__fp_if_type_fp:NTwFw
15796         #2 { \use_i:nn \use_i_delimit_by_q_stop:nw #3 \q_stop }
15797         \s__fp 1 \q_stop
15798         \exp_after:wN \exp_after:wN \exp_after:wN \__fp_ternary_auxii:NwwN
15799     \else:
15800         \exp_after:wN \exp_after:wN \exp_after:wN \__fp_ternary_auxi:NwwN
15801     \fi:
15802     \exp_after:wN #1
15803     \exp:w \exp_end_continue_f:w
15804     \__fp_exp_after_array_f:w #4 \s__fp_stop
15805     \exp_after:wN @
15806     \exp:w
15807     \__fp_parse_operand:Nw \c__fp_prec_colon_int
15808     \__fp_parse_expand:w
15809 \else:
15810     \__kernel_msg_expandable_error:nnnn

```

```

15811      { kernel } { fp-missing } { : } { ~for~?: }
15812      \exp_after:wN \__fp_parse_continue:NwN
15813      \exp_after:wN #1
15814      \exp:w \exp_end_continue_f:w
15815      \__fp_exp_after_array_f:w #4 \s__fp_stop
15816      \exp_after:wN #5
15817      \exp_after:wN #1
15818      \fi:
15819    }
15820    \cs_new:Npn \__fp_ternary_auxi:NwwN #1#2@#3@#4
15821    {
15822      \exp_after:wN \__fp_parse_continue:NwN
15823      \exp_after:wN #1
15824      \exp:w \exp_end_continue_f:w
15825      \__fp_exp_after_array_f:w #2 \s__fp_stop
15826      #4 #1
15827    }
15828    \cs_new:Npn \__fp_ternary_auxii:NwwN #1#2@#3@#4
15829    {
15830      \exp_after:wN \__fp_parse_continue:NwN
15831      \exp_after:wN #1
15832      \exp:w \exp_end_continue_f:w
15833      \__fp_exp_after_array_f:w #3 \s__fp_stop
15834      #4 #1
15835    }

```

(End definition for __fp_ternary:NwwN, __fp_ternary_auxi:NwwN, and __fp_ternary_auxii:NwwN.)

```
15836 </initex | package>
```

29 l3fp-basics Implementation

```
15837 (*initex | package)
```

```
15838 <@@=fp>
```

The l3fp-basics module implements addition, subtraction, multiplication, and division of two floating points, and the absolute value and sign-changing operations on one floating point. All operations implemented in this module yield the outcome of rounding the infinitely precise result of the operation to the nearest floating point.

Some algorithms used below end up being quite similar to some described in “What Every Computer Scientist Should Know About Floating Point Arithmetic”, by David Goldberg, which can be found at <http://cr.yp.to/2005-590/goldberg.pdf>.

Unary functions.

```

\__fp_parse_word_abs:N
\__fp_parse_word_logb:N
\__fp_parse_word_sign:N
\__fp_parse_word_sqrt:N
15839 \cs_new:Npn \__fp_parse_word_abs:N
15840 { \__fp_parse_unary_function:NNN \__fp_set_sign_o:w 0 }
15841 \cs_new:Npn \__fp_parse_word_logb:N
15842 { \__fp_parse_unary_function:NNN \__fp_logb_o:w ? }
15843 \cs_new:Npn \__fp_parse_word_sign:N
15844 { \__fp_parse_unary_function:NNN \__fp_sign_o:w ? }
15845 \cs_new:Npn \__fp_parse_word_sqrt:N
15846 { \__fp_parse_unary_function:NNN \__fp_sqrt_o:w ? }

```

(End definition for __fp_parse_word_abs:N and others.)

29.1 Addition and subtraction

We define here two functions, `__fp_-_o:ww` and `__fp+_o:ww`, which perform the subtraction and addition of their two floating point operands, and expand the tokens following the result once.

A more obscure function, `__fp_add_big_i_o:wNww`, is used in `l3fp-expo`.

The logic goes as follows:

- `__fp_-_o:ww` calls `__fp+_o:ww` to do the work, with the sign of the second operand flipped;
- `__fp+_o:ww` dispatches depending on the type of floating point, calling specialized auxiliaries;
- in all cases except summing two normal floating point numbers, we return one or the other operands depending on the signs, or detect an invalid operation in the case of $\infty - \infty$;
- for normal floating point numbers, compare the signs;
- to add two floating point numbers of the same sign or of opposite signs, shift the significand of the smaller one to match the bigger one, perform the addition or subtraction of significands, check for a carry, round, and pack using the `__fp-basics_pack_...` functions.

The trickiest part is to round correctly when adding or subtracting normal floating point numbers.

29.1.1 Sign, exponent, and special numbers

`__fp_-_o:ww` The `__fp+_o:ww` auxiliary has a hook: it takes one argument between the first `\s__fp` and `__fp_chk:w`, which is applied to the sign of the second operand. Positioning the hook there means that `__fp+_o:ww` can still perform the sanity check that it was followed by `\s__fp`.

```

15847 \cs_new:cpx { __fp_-_o:ww } \s__fp
15848 {
15849   \exp_not:c { __fp+_o:ww }
15850   \exp_not:n { \s__fp \__fp_neg_sign:N }
15851 }

```

(End definition for `__fp_-_o:ww`.)

`__fp+_o:ww` This function is either called directly with an empty `#1` to compute an addition, or it is called by `__fp_-_o:ww` with `__fp_neg_sign:N` as `#1` to compute a subtraction, in which case the second operand's sign should be changed. If the *<types>* `#2` and `#4` are the same, dispatch to case `#2` (0, 1, 2, or 3), where we call specialized functions: thanks to `\int_value:w`, those receive the tweaked *<sign_{2 (expansion of `#1#5`) as an argument. If the *<types>* are distinct, the result is simply the floating point number with the highest *<type>*. Since case 3 (used for two `nan`) also picks the first operand, we can also use it when *<type_{1 is greater than *<type_{2. Also note that we don't need to worry about *<sign_{2 in that case since the second operand is discarded.}*}*}*}*

```

15852 \cs_new:cpx { __fp+_o:ww }
15853   \s__fp #1 \__fp_chk:w #2 #3 ; \s__fp \__fp_chk:w #4 #5

```

```

15854 {
15855     \if_case:w
15856         \if_meaning:w #2 #4
15857             #2
15858     \else:
15859         \if_int_compare:w #2 > #4 \exp_stop_f:
15860             3
15861         \else:
15862             4
15863     \fi:
15864 \fi:
15865 \exp_stop_f:
15866     \exp_after:wN \__fp_add_zeros_o:Nww \int_value:w
15867 \or: \exp_after:wN \__fp_add_normal_o:Nww \int_value:w
15868 \or: \exp_after:wN \__fp_add_inf_o:Nww \int_value:w
15869 \or: \__fp_case_return_i_o:ww
15870 \else: \exp_after:wN \__fp_add_return_ii_o:Nww \int_value:w
15871 \fi:
15872 #1 #5
15873 \s__fp \__fp_chk:w #2 #3 ;
15874 \s__fp \__fp_chk:w #4 #5
15875 }

```

(End definition for __fp+_o:ww.)

__fp_add_return_ii_o:Nww Ignore the first operand, and return the second, but using the sign #1 rather than #4. As usual, expand after the floating point.

```

15876 \cs_new:Npn \__fp_add_return_ii_o:Nww #1 #2 ; \s__fp \__fp_chk:w #3 #4
15877 { \__fp_exp_after_o:w \s__fp \__fp_chk:w #3 #1 }

```

(End definition for __fp_add_return_ii_o:Nww.)

__fp_add_zeros_o:Nww Adding two zeros yields \c_zero_fp, except if both zeros were -0.

```

15878 \cs_new:Npn \__fp_add_zeros_o:Nww #1 \s__fp \__fp_chk:w 0 #2
15879 {
15880     \if_int_compare:w #2 #1 = 20 \exp_stop_f:
15881     \exp_after:wN \__fp_add_return_ii_o:Nww
15882 \else:
15883     \__fp_case_return_i_o:ww
15884 \fi:
15885 #1
15886 \s__fp \__fp_chk:w 0 #2
15887 }

```

(End definition for __fp_add_zeros_o:Nww.)

__fp_add_inf_o:Nww If both infinities have the same sign, just return that infinity, otherwise, it is an invalid operation. We find out if that invalid operation is an addition or a subtraction by testing whether the tweaked $\langle sign_2 \rangle$ (#1) and the $\langle sign_2 \rangle$ (#4) are identical.

```

15888 \cs_new:Npn \__fp_add_inf_o:Nww
15889 #1 \s__fp \__fp_chk:w 2 #2 #3; \s__fp \__fp_chk:w 2 #4
15890 {
15891     \if_meaning:w #1 #2
15892     \__fp_case_return_i_o:ww

```

```

15893     \else:
15894         \__fp_case_use:nw
15895         {
15896             \exp_last_unbraced:Nf \__fp_invalid_operation_o:Nww
15897             { \token_if_eq_meaning:NNTF #1 #4 + - }
15898         }
15899     \fi:
15900     \s__fp \__fp_chk:w 2 #2 #3;
15901     \s__fp \__fp_chk:w 2 #4
15902 }

```

(End definition for __fp_add_inf_o:Nww.)

```

\__fp_add_normal_o:Nww \__fp_add_normal_o:Nww <sign2> \s__fp \__fp_chk:w 1 <sign1> <exp1>
<body1> ; \s__fp \__fp_chk:w 1 <initial sign2> <exp2> <body2> ;

```

We now have two normal numbers to add, and we have to check signs and exponents more carefully before performing the addition.

```

15903 \cs_new:Npn \__fp_add_normal_o:Nww #1 \s__fp \__fp_chk:w 1 #2
15904 {
15905     \if_meaning:w #1#2
15906     \exp_after:wN \__fp_add_npos_o:NnwNnw
15907     \else:
15908     \exp_after:wN \__fp_sub_npos_o:NnwNnw
15909     \fi:
15910     #2
15911 }

```

(End definition for __fp_add_normal_o:Nww.)

29.1.2 Absolute addition

In this subsection, we perform the addition of two positive normal numbers.

```

\__fp_add_npos_o:NnwNnw \__fp_add_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp \__fp_chk:w 1
<initial sign2> <exp2> <body2> ;

```

Since we are doing an addition, the final sign is $\langle sign_1 \rangle$. Start an `__fp_int_eval:w`, responsible for computing the exponent: the result, and the $\langle final\ sign \rangle$ are then given to `__fp_sanitize:Nw` which checks for overflow. The exponent is computed as the largest exponent #2 or #5, incremented if there is a carry. To add the significands, we decimate the smaller number by the difference between the exponents. This is done by `__fp_add_big_i:wNnw` or `__fp_add_big_ii:wNnw`. We need to bring the final sign with us in the midst of the calculation to round properly at the end.

```

15912 \cs_new:Npn \__fp_add_npos_o:NnwNnw #1#2#3 ; \s__fp \__fp_chk:w 1 #4 #5
15913 {
15914     \exp_after:wN \__fp_sanitize:Nw
15915     \exp_after:wN #1
15916     \int_value:w \__fp_int_eval:w
15917     \if_int_compare:w #2 > #5 \exp_stop_f:
15918     #2
15919     \exp_after:wN \__fp_add_big_i_o:wNnw \int_value:w -
15920     \else:
15921     #5
15922     \exp_after:wN \__fp_add_big_ii_o:wNnw \int_value:w

```

```

15923     \fi:
15924     \__fp_int_eval:w #5 - #2 ; #1 #3;
15925 }

```

(End definition for __fp_add_npos_o:NnwNnw.)

```

\__fp_add_big_i_o:wNww     \__fp_add_big_i_o:wNww <shift> ; <final sign> <body1> ; <body2> ;
\__fp_add_big_ii_o:wNww    Used in l3fp-expo. Shift the significand of the small number, then add with \__fp-
add_significand_o:NnnwnnnnN.

```

```

15926 \cs_new:Npn \__fp_add_big_i_o:wNww #1; #2 #3; #4;
15927 {
15928     \__fp_decimate:nNnnnn {#1}
15929     \__fp_add_significand_o:NnnwnnnnN
15930     #4
15931     #3
15932     #2
15933 }
15934 \cs_new:Npn \__fp_add_big_ii_o:wNww #1; #2 #3; #4;
15935 {
15936     \__fp_decimate:nNnnnn {#1}
15937     \__fp_add_significand_o:NnnwnnnnN
15938     #3
15939     #4
15940     #2
15941 }

```

(End definition for __fp_add_big_i_o:wNww and __fp_add_big_ii_o:wNww.)

```

\__fp_add_significand_o:NnnwnnnnN     \__fp_add_significand_o:NnnwnnnnN <rounding digit> {\langle Y'_1 \rangle} {\langle Y'_2 \rangle}
\__fp_add_significand_pack:NNNNNNN    <extra-digits> ; {\langle X_1 \rangle} {\langle X_2 \rangle} {\langle X_3 \rangle} {\langle X_4 \rangle} <final sign>
\__fp_add_significand_test_o:N        To round properly, we must know at which digit the rounding should occur. This

```

requires to know whether the addition produces an overall carry or not. Thus, we do the computation now and check for a carry, then go back and do the rounding. The rounding may cause a carry in very rare cases such as $0.99 \dots 95 \rightarrow 1.00 \dots 0$, but this situation always give an exact power of 10, for which it is easy to correct the result at the end.

```

15942 \cs_new:Npn \__fp_add_significand_o:NnnwnnnnN #1 #2#3 #4; #5#6#7#8
15943 {
15944     \exp_after:wN \__fp_add_significand_test_o:N
15945     \int_value:w \__fp_int_eval:w 1#5#6 + #2
15946     \exp_after:wN \__fp_add_significand_pack:NNNNNNN
15947     \int_value:w \__fp_int_eval:w 1#7#8 + #3 ; #1
15948 }
15949 \cs_new:Npn \__fp_add_significand_pack:NNNNNNN #1 #2#3#4#5#6#7
15950 {
15951     \if_meaning:w 2 #1
15952     + 1
15953     \fi:
15954     ; #2 #3 #4 #5 #6 #7 ;
15955 }
15956 \cs_new:Npn \__fp_add_significand_test_o:N #1
15957 {
15958     \if_meaning:w 2 #1
15959     \exp_after:wN \__fp_add_significand_carry_o:wwwNN
15960     \else:

```

```

15961         \exp_after:wN \__fp_add_significand_no_carry_o:wwwNN
15962     \fi:
15963 }

```

(End definition for __fp_add_significand_o:NnnwnnnN, __fp_add_significand_pack:NNNNNN, and __fp_add_significand_test_o:N.)

```

\__fp_add_significand_no_carry_o:wwwNN    \__fp_add_significand_no_carry_o:wwwNN <8d> ; <6d> ; <2d> ; <rounding
digit> <sign>

```

If there's no carry, grab all the digits again and round. The packing function __fp_basics_pack_high:NNNNNw takes care of the case where rounding brings a carry.

```

15964 \cs_new:Npn \__fp_add_significand_no_carry_o:wwwNN
15965     #1; #2; #3#4 ; #5#6
15966 {
15967     \exp_after:wN \__fp_basics_pack_high:NNNNNw
15968     \int_value:w \__fp_int_eval:w 1 #1
15969     \exp_after:wN \__fp_basics_pack_low:NNNNNw
15970     \int_value:w \__fp_int_eval:w 1 #2 #3#4
15971     + \__fp_round:NNN #6 #4 #5
15972     \exp_after:wN ;
15973 }

```

(End definition for __fp_add_significand_no_carry_o:wwwNN.)

```

\__fp_add_significand_carry_o:wwwNN    \__fp_add_significand_carry_o:wwwNN <8d> ; <6d> ; <2d> ; <rounding
digit> <sign>

```

The case where there is a carry is very similar. Rounding can even raise the first digit from 1 to 2, but we don't care.

```

15974 \cs_new:Npn \__fp_add_significand_carry_o:wwwNN
15975     #1; #2; #3#4; #5#6
15976 {
15977     + 1
15978     \exp_after:wN \__fp_basics_pack_weird_high:NNNNNNNw
15979     \int_value:w \__fp_int_eval:w 1 1 #1
15980     \exp_after:wN \__fp_basics_pack_weird_low:NNNNw
15981     \int_value:w \__fp_int_eval:w 1 #2#3 +
15982     \exp_after:wN \__fp_round:NNN
15983     \exp_after:wN #6
15984     \exp_after:wN #3
15985     \int_value:w \__fp_round_digit:Nw #4 #5 ;
15986     \exp_after:wN ;
15987 }

```

(End definition for __fp_add_significand_carry_o:wwwNN.)

29.1.3 Absolute subtraction

```

\__fp_sub_npos_o:NnwNnw    \__fp_sub_npos_o:NnwNnw <sign1> <exp1> <body1> ; \s__fp \__fp_chk:w 1
\__fp_sub_eq_o:Nwnnw        <initial sign2> <exp2> <body2> ;
\__fp_sub_npos_ii_o:Nwnnw

```

Rounding properly in some modes requires to know what the sign of the result will be. Thus, we start by comparing the exponents and significands. If the numbers coincide, return zero. If the second number is larger, swap the numbers and call __fp_sub_npos_i_o:Nwnnw with the opposite of $\langle sign_1 \rangle$.

```

15988 \cs_new:Npn \__fp_sub_npos_o:NnwNnw #1#2#3; \s__fp \__fp_chk:w 1 #4#5#6;

```

```

15989 {
15990   \if_case:w \__fp_compare_npos:nwnw {#2} #3; {#5} #6; \exp_stop_f:
15991     \exp_after:wN \__fp_sub_eq_o:Nnwnw
15992   \or:
15993     \exp_after:wN \__fp_sub_npos_i_o:Nnwnw
15994   \else:
15995     \exp_after:wN \__fp_sub_npos_ii_o:Nnwnw
15996   \fi:
15997   #1 {#2} #3; {#5} #6;
15998 }
15999 \cs_new:Npn \__fp_sub_eq_o:Nnwnw #1#2; #3; { \exp_after:wN \c_zero_fp }
16000 \cs_new:Npn \__fp_sub_npos_ii_o:Nnwnw #1 #2; #3;
16001 {
16002   \exp_after:wN \__fp_sub_npos_i_o:Nnwnw
16003   \int_value:w \__fp_neg_sign:N #1
16004   #3; #2;
16005 }

```

(End definition for __fp_sub_npos_o:Nnwnw, __fp_sub_eq_o:Nnwnw, and __fp_sub_npos_ii_o:Nnwnw.)

__fp_sub_npos_i_o:Nnwnw

After the computation is done, __fp_sanitize:Nw checks for overflow/underflow. It expects the $\langle final\ sign \rangle$ and the $\langle exponent \rangle$ (delimited by ;). Start an integer expression for the exponent, which starts with the exponent of the largest number, and may be decreased if the two numbers are very close. If the two numbers have the same exponent, call the **near** auxiliary. Otherwise, decimate y , then call the **far** auxiliary to evaluate the difference between the two significands. Note that we decimate by 1 less than one could expect.

```

16006 \cs_new:Npn \__fp_sub_npos_i_o:Nnwnw #1 #2#3; #4#5;
16007 {
16008   \exp_after:wN \__fp_sanitize:Nw
16009   \exp_after:wN #1
16010   \int_value:w \__fp_int_eval:w
16011   #2
16012   \if_int_compare:w #2 = #4 \exp_stop_f:
16013     \exp_after:wN \__fp_sub_back_near_o:nnnnnnnnN
16014   \else:
16015     \exp_after:wN \__fp_decimate:nNnnnn \exp_after:wN
16016     { \int_value:w \__fp_int_eval:w #2 - #4 - 1 \exp_after:wN }
16017     \exp_after:wN \__fp_sub_back_far_o:NnnwnnnnnN
16018   \fi:
16019   #5
16020   #3
16021   #1
16022 }

```

(End definition for __fp_sub_npos_i_o:Nnwnw.)

__fp_sub_back_near_o:nnnnnnnnN
 __fp_sub_back_near_pack:NNNNNNw
 __fp_sub_back_near_after:wNNNNw

__fp_sub_back_near_o:nnnnnnnnN { $\langle Y_1 \rangle$ } { $\langle Y_2 \rangle$ } { $\langle Y_3 \rangle$ } { $\langle Y_4 \rangle$ } { $\langle X_1 \rangle$ }
 { $\langle X_2 \rangle$ } { $\langle X_3 \rangle$ } { $\langle X_4 \rangle$ } $\langle final\ sign \rangle$

In this case, the subtraction is exact, so we discard the $\langle final\ sign \rangle$ #9. The very large shifts of 10^9 and $1.1 \cdot 10^9$ are unnecessary here, but allow the auxiliaries to be reused later. Each integer expression produces a 10 digit result. If the resulting 16 digits start with a 0, then we need to shift the group, padding with trailing zeros.

```

16023 \cs_new:Npn \__fp_sub_back_near_o:nnnnnnnnN #1#2#3#4 #5#6#7#8 #9
16024 {
16025   \exp_after:wN \__fp_sub_back_near_after:wNNNNw
16026   \int_value:w \__fp_int_eval:w 10#5#6 - #1#2 - 11
16027   \exp_after:wN \__fp_sub_back_near_pack:NNNNNNw
16028   \int_value:w \__fp_int_eval:w 11#7#8 - #3#4 \exp_after:wN ;
16029 }
16030 \cs_new:Npn \__fp_sub_back_near_pack:NNNNNNw #1#2#3#4#5#6#7 ;
16031 { + #1#2 ; {#3#4#5#6} {#7} ; }
16032 \cs_new:Npn \__fp_sub_back_near_after:wNNNNw 10 #1#2#3#4 #5 ;
16033 {
16034   \if_meaning:w 0 #1
16035   \exp_after:wN \__fp_sub_back_shift:wnnnn
16036   \fi:
16037   ; {#1#2#3#4} {#5}
16038 }

```

(End definition for __fp_sub_back_near_o:nnnnnnnnN, __fp_sub_back_near_pack:NNNNNNw, and __fp_sub_back_near_after:wNNNNw.)

```

\__fp_sub_back_shift:wnnnn
\__fp_sub_back_shift_ii:ww
\__fp_sub_back_shift_iii:NNNNNNNNw
\__fp_sub_back_shift_iv:nnnnw

```

__fp_sub_back_shift:wnnnn ; { $\langle Z_1 \rangle$ } { $\langle Z_2 \rangle$ } { $\langle Z_3 \rangle$ } { $\langle Z_4 \rangle$ } ;

This function is called with $\langle Z_1 \rangle \leq 999$. Act with \number to trim leading zeros from $\langle Z_1 \rangle$ $\langle Z_2 \rangle$ (we don't do all four blocks at once, since non-zero blocks would then overflow \TeX 's integers). If the first two blocks are zero, the auxiliary receives an empty #1 and trims #2#30 from leading zeros, yielding a total shift between 7 and 16 to the exponent. Otherwise we get the shift from #1 alone, yielding a result between 1 and 6. Once the exponent is taken care of, trim leading zeros from #1#2#3 (when #1 is empty, the space before #2#3 is ignored), get four blocks of 4 digits and finally clean up. Trailing zeros are added so that digits can be grabbed safely.

```

16039 \cs_new:Npn \__fp_sub_back_shift:wnnnn ; #1#2
16040 {
16041   \exp_after:wN \__fp_sub_back_shift_ii:ww
16042   \int_value:w #1 #2 0 ;
16043 }
16044 \cs_new:Npn \__fp_sub_back_shift_ii:ww #1 0 ; #2#3 ;
16045 {
16046   \if_meaning:w @ #1 @
16047   - 7
16048   - \exp_after:wN \use_i:nnn
16049   \exp_after:wN \__fp_sub_back_shift_iii:NNNNNNNNw
16050   \int_value:w #2#3 0 ~ 123456789;
16051   \else:
16052   - \__fp_sub_back_shift_iii:NNNNNNNNw #1 123456789;
16053   \fi:
16054   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
16055   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
16056   \exp_after:wN \__fp_sub_back_shift_iv:nnnnw
16057   \exp_after:wN ;
16058   \int_value:w
16059   #1 ~ #2#3 0 ~ 0000 0000 0000 000 ;
16060 }
16061 \cs_new:Npn \__fp_sub_back_shift_iii:NNNNNNNNw #1#2#3#4#5#6#7#8#9; {#8}
16062 \cs_new:Npn \__fp_sub_back_shift_iv:nnnnw #1 ; #2 ; { ; #1 ; }

```

(End definition for _fp_sub_back_shift:wnnnn and others.)

_fp_sub_back_far_o:NnnwnnnN $\langle \text{rounding} \rangle \{ \langle Y'_1 \rangle \} \{ \langle Y'_2 \rangle \}$
 $\langle \text{extra-digits} \rangle ; \{ \langle X_1 \rangle \} \{ \langle X_2 \rangle \} \{ \langle X_3 \rangle \} \{ \langle X_4 \rangle \} \langle \text{final sign} \rangle$

If the difference is greater than $10^{\langle \text{expo}_x \rangle}$, call the **very_far** auxiliary. If the result is less than $10^{\langle \text{expo}_x \rangle}$, call the **not_far** auxiliary. If it is too close a call to know yet, namely if $1 \langle Y'_1 \rangle \langle Y'_2 \rangle = \langle X_1 \rangle \langle X_2 \rangle \langle X_3 \rangle \langle X_4 \rangle 0$, then call the **quite_far** auxiliary. We use the odd combination of space and semi-colon delimiters to allow the **not_far** auxiliary to grab each piece individually, the **very_far** auxiliary to use _fp_pack_eight:wNNNNNNNN, and the **quite_far** to ignore the significands easily (using the ; delimiter).

```

16063 \cs_new:Npn \_fp_sub_back_far_o:NnnwnnnN #1 #2#3 #4; #5#6#7#8
16064 {
16065   \if_case:w
16066     \if_int_compare:w 1 #2 = #5#6 \use_i:nnnn #7 \exp_stop_f:
16067     \if_int_compare:w #3 = \use_none:n #7#8 0 \exp_stop_f:
16068       0
16069     \else:
16070       \if_int_compare:w #3 > \use_none:n #7#8 0 - \fi: 1
16071     \fi:
16072   \else:
16073     \if_int_compare:w 1 #2 > #5#6 \use_i:nnnn #7 - \fi: 1
16074   \fi:
16075   \exp_stop_f:
16076     \exp_after:wN \_fp_sub_back_quite_far_o:wwNN
16077   \or:   \exp_after:wN \_fp_sub_back_very_far_o:wwwNN
16078   \else: \exp_after:wN \_fp_sub_back_not_far_o:wwwNN
16079   \fi:
16080   #2 ~ #3 ; #5 #6 ~ #7 #8 ; #1
16081 }

```

(End definition for _fp_sub_back_far_o:NnnwnnnN.)

_fp_sub_back_quite_far_o:wwNN
 _fp_sub_back_quite_far_ii:NN

The easiest case is when $x - y$ is extremely close to a power of 10, namely the first digit of x is 1, and all others vanish when subtracting y . Then the $\langle \text{rounding} \rangle$ #3 and the $\langle \text{final sign} \rangle$ #4 control whether we get 1 or 0.9999999999999999. In the usual round-to-nearest mode, we get 1 whenever the $\langle \text{rounding} \rangle$ digit is less than or equal to 5 (remember that the $\langle \text{rounding} \rangle$ digit is only equal to 5 if there was no further non-zero digit).

```

16082 \cs_new:Npn \_fp_sub_back_quite_far_o:wwNN #1; #2; #3#4
16083 {
16084   \exp_after:wN \_fp_sub_back_quite_far_ii:NN
16085   \exp_after:wN #3
16086   \exp_after:wN #4
16087 }
16088 \cs_new:Npn \_fp_sub_back_quite_far_ii:NN #1#2
16089 {
16090   \if_case:w \_fp_round_neg:NNN #2 0 #1
16091     \exp_after:wN \use_i:nn
16092   \else:
16093     \exp_after:wN \use_ii:nn
16094   \fi:
16095   { ; {1000} {0000} {0000} {0000} ; }
16096   { - 1 ; {9999} {9999} {9999} {9999} ; }
16097 }

```


(End definition for `_fp_sub_back_quite_far_o:wwwNN` and `_fp_sub_back_quite_far_ii:NN`.)

`_fp_sub_back_not_far_o:wwwNN` In the present case, x and y have different exponents, but y is large enough that $x - y$ has a smaller exponent than x . Decrement the exponent (with `-1`). Then proceed in a way similar to the `near` auxiliaries seen earlier, but multiplying x by 10 (`#30` and `#40` below), and with the added quirk that the *rounding* digit has to be taken into account. Namely, we may have to decrease the result by one unit if `_fp_round_neg:NNN` returns 1. This function expects the *final sign* `#6`, the last digit of `1100000000+#40-#2`, and the *rounding* digit. Instead of redoing the computation for the second argument, we note that `_fp_round_neg:NNN` only cares about its parity, which is identical to that of the last digit of `#2`.

```

16098 \cs_new:Npn \_fp_sub_back_not_far_o:wwwNN #1 ~ #2; #3 ~ #4; #5#6
16099 {
16100   - 1
16101   \exp_after:wN \_fp_sub_back_near_after:wNNNNw
16102   \int_value:w \_fp_int_eval:w 1#30 - #1 - 11
16103   \exp_after:wN \_fp_sub_back_near_pack:NNNNNNw
16104   \int_value:w \_fp_int_eval:w 11 0000 0000 + #40 - #2
16105   - \exp_after:wN \_fp_round_neg:NNN
16106   \exp_after:wN #6
16107   \use_none:nnnnnnn #2 #5
16108   \exp_after:wN ;
16109 }

```

(End definition for `_fp_sub_back_not_far_o:wwwNN`.)

`_fp_sub_back_very_far_o:wwwNN` The case where $x - y$ and x have the same exponent is a bit more tricky, mostly because
`_fp_sub_back_very_far_ii_o:nnNwwNN` it cannot reuse the same auxiliaries. Shift the y significand by adding a leading 0. Then the logic is similar to the `not_far` functions above. Rounding is a bit more complicated: we have two *rounding* digits `#3` and `#6` (from the decimation, and from the new shift) to take into account, and getting the parity of the main result requires a computation. The first `\int_value:w` triggers the second one because the number is unfinished; we can thus not use 0 in place of 2 there.

```

16110 \cs_new:Npn \_fp_sub_back_very_far_o:wwwNN #1#2#3#4#5#6#7
16111 {
16112   \_fp_pack_eight:wNNNNNNNN
16113   \_fp_sub_back_very_far_ii_o:nnNwwNN
16114   { 0 #1#2#3 #4#5#6#7 }
16115   ;
16116 }
16117 \cs_new:Npn \_fp_sub_back_very_far_ii_o:nnNwwNN #1#2 ; #3 ; #4 ~ #5; #6#7
16118 {
16119   \exp_after:wN \_fp_basics_pack_high:NNNNNw
16120   \int_value:w \_fp_int_eval:w 1#4 - #1 - 1
16121   \exp_after:wN \_fp_basics_pack_low:NNNNNw
16122   \int_value:w \_fp_int_eval:w 2#5 - #2
16123   - \exp_after:wN \_fp_round_neg:NNN
16124   \exp_after:wN #7
16125   \int_value:w
16126   \if_int_odd:w \_fp_int_eval:w #5 - #2 \_fp_int_eval_end:
16127     1 \else: 2 \fi:
16128   \int_value:w \_fp_round_digit:Nw #3 #6 ;
16129   \exp_after:wN ;

```

```
16130 }
```

(End definition for `__fp_sub_back_very_far_o:wwwNN` and `__fp_sub_back_very_far_ii_o:nnNwwNN`.)

29.2 Multiplication

29.2.1 Signs, and special numbers

`__fp*_o:ww` We go through an auxiliary, which is common with `__fp/_o:ww`. The first argument is the operation, used for the invalid operation exception. The second is inserted in a formula to dispatch cases slightly differently between multiplication and division. The third is the operation for normal floating points. The fourth is there for extra cases needed in `__fp/_o:ww`.

```
16131 \cs_new:cpn { __fp*_o:ww }
16132 {
16133   \__fp_mul_cases_o:NnNnw
16134   *
16135   { - 2 + }
16136   \__fp_mul_npos_o:Nww
16137   { }
16138 }
```

(End definition for `__fp*_o:ww`.)

`__fp_mul_cases_o:nNnw` Split into 10 cases (12 for division). If both numbers are normal, go to case 0 (same sign) or case 1 (opposite signs): in both cases, call `__fp_mul_npos_o:Nww` to do the work. If the first operand is `nan`, go to case 2, in which the second operand is discarded; if the second operand is `nan`, go to case 3, in which the first operand is discarded (note the weird interaction with the final test on signs). Then we separate the case where the first number is normal and the second is zero: this goes to cases 4 and 5 for multiplication, 10 and 11 for division. Otherwise, we do a computation which dispatches the products $0 \times 0 = 0 \times 1 = 1 \times 0 = 0$ to case 4 or 5 depending on the combined sign, the products $0 \times \infty$ and $\infty \times 0$ to case 6 or 7 (invalid operation), and the products $1 \times \infty = \infty \times 1 = \infty \times \infty = \infty$ to cases 8 and 9. Note that the code for these two cases (which return $\pm\infty$) is inserted as argument #4, because it differs in the case of divisions.

```
16139 \cs_new:Npn \__fp_mul_cases_o:NnNnw
16140   #1#2#3#4 \s__fp \__fp_chk:w #5#6#7; \s__fp \__fp_chk:w #8#9
16141   {
16142     \if_case:w \__fp_int_eval:w
16143       \if_int_compare:w #5 #8 = 11 ~
16144       1
16145     \else:
16146       \if_meaning:w 3 #8
16147       3
16148     \else:
16149       \if_meaning:w 3 #5
16150       2
16151     \else:
16152       \if_int_compare:w #5 #8 = 10 ~
16153       9 #2 - 2
16154     \else:
16155       (#5 #2 #8) / 2 * 2 + 7
16156   \fi:
```

```

16157         \fi:
16158     \fi:
16159     \fi:
16160     \if_meaning:w #6 #9 - 1 \fi:
16161     \__fp_int_eval_end:
16162     \__fp_case_use:nw { #3 0 }
16163     \or: \__fp_case_use:nw { #3 2 }
16164     \or: \__fp_case_return_i_o:ww
16165     \or: \__fp_case_return_ii_o:ww
16166     \or: \__fp_case_return_o:Nww \c_zero_fp
16167     \or: \__fp_case_return_o:Nww \c_minus_zero_fp
16168     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
16169     \or: \__fp_case_use:nw { \__fp_invalid_operation_o:Nww #1 }
16170     \or: \__fp_case_return_o:Nww \c_inf_fp
16171     \or: \__fp_case_return_o:Nww \c_minus_inf_fp
16172     #4
16173     \fi:
16174     \s__fp \__fp_chk:w #5 #6 #7;
16175     \s__fp \__fp_chk:w #8 #9
16176 }

```

(End definition for __fp_mul_cases_o:nNnnww.)

29.2.2 Absolute multiplication

In this subsection, we perform the multiplication of two positive normal numbers.

```

\__fp_mul_npos_o:Nww     \__fp_mul_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign1> {<exp1>}
                        <body1> ; \s__fp \__fp_chk:w 1 <sign2> {<exp2>} <body2> ;

```

After the computation, __fp_sanitize:Nw checks for overflow or underflow. As we did for addition, __fp_int_eval:w computes the exponent, catching any shift coming from the computation in the significand. The <final sign> is needed to do the rounding properly in the significand computation. We setup the post-expansion here, triggered by __fp_mul_significand_o:nnnnNnnnn.

This is also used in l3fp-convert.

```

16177 \cs_new:Npn \__fp_mul_npos_o:Nww
16178     #1 \s__fp \__fp_chk:w #2 #3 #4 #5 ; \s__fp \__fp_chk:w #6 #7 #8 #9 ;
16179 {
16180     \exp_after:wN \__fp_sanitize:Nw
16181     \exp_after:wN #1
16182     \int_value:w \__fp_int_eval:w
16183     #4 + #8
16184     \__fp_mul_significand_o:nnnnNnnnn #5 #1 #9
16185 }

```

(End definition for __fp_mul_npos_o:Nww.)

```

\__fp_mul_significand_o:nnnnNnnnn     \__fp_mul_significand_o:nnnnNnnnn {<X1>} {<X2>} {<X3>} {<X4>} <sign>
\__fp_mul_significand_drop:NNNNNw     {<Y1>} {<Y2>} {<Y3>} {<Y4>}
\__fp_mul_significand_keep:NNNNNw

```

Note the three semicolons at the end of the definition. One is for the last __fp_mul_significand_drop:NNNNNw; one is for __fp_round_digit:Nw later on; and one, preceded by \exp_after:wN, which is correctly expanded (within an __fp_int_eval:w), is used by __fp_basics_pack_low:NNNNNw.

The product of two 16 digit integers has 31 or 32 digits, but it is impossible to know which one before computing. The place where we round depends on that number of digits, and may depend on all digits until the last in some rare cases. The approach is thus to compute the 5 first blocks of 4 digits (the first one is between 100 and 9999 inclusive), and a compact version of the remaining 3 blocks. Afterwards, the number of digits is known, and we can do the rounding within yet another set of `__fp_int_eval:w`.

```

16186 \cs_new:Npn \__fp_mul_significand_o:nnnnNnnnn #1#2#3#4 #5 #6#7#8#9
16187 {
16188   \exp_after:wN \__fp_mul_significand_test_f:NNN
16189   \exp_after:wN #5
16190   \int_value:w \__fp_int_eval:w 99990000 + #1*#6 +
16191   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
16192   \int_value:w \__fp_int_eval:w 99990000 + #1*#7 + #2*#6 +
16193   \exp_after:wN \__fp_mul_significand_keep:NNNNNw
16194   \int_value:w \__fp_int_eval:w 99990000 + #1*#8 + #2*#7 + #3*#6 +
16195   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
16196   \int_value:w \__fp_int_eval:w 99990000 + #1*#9 + #2*#8 +
16197   #3*#7 + #4*#6 +
16198   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
16199   \int_value:w \__fp_int_eval:w 99990000 + #2*#9 + #3*#8 +
16200   #4*#7 +
16201   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
16202   \int_value:w \__fp_int_eval:w 99990000 + #3*#9 + #4*#8 +
16203   \exp_after:wN \__fp_mul_significand_drop:NNNNNw
16204   \int_value:w \__fp_int_eval:w 100000000 + #4*#9 ;
16205   ; \exp_after:wN ;
16206 }
16207 \cs_new:Npn \__fp_mul_significand_drop:NNNNNw #1#2#3#4#5 #6;
16208 { #1#2#3#4#5 ; + #6 }
16209 \cs_new:Npn \__fp_mul_significand_keep:NNNNNw #1#2#3#4#5 #6;
16210 { #1#2#3#4#5 ; #6 ; }

```

(End definition for `__fp_mul_significand_o:nnnnNnnnn`, `__fp_mul_significand_drop:NNNNNw`, and `__fp_mul_significand_keep:NNNNNw`.)

```

\__fp_mul_significand_test_f:NNN   \__fp_mul_significand_test_f:NNN <sign> 1 <digits 1-8> ; <digits 9-12> ;
                                   <digits 13-16> ; + <digits 17-20> + <digits 21-24> + <digits 25-28> + <digits
                                   29-32> ; \exp_after:wN ;

```

If the *<digit 1>* is non-zero, then for rounding we only care about the digits 16 and 17, and whether further digits are zero or not (check for exact ties). On the other hand, if *<digit 1>* is zero, we care about digits 17 and 18, and whether further digits are zero.

```

16211 \cs_new:Npn \__fp_mul_significand_test_f:NNN #1 #2 #3
16212 {
16213   \if_meaning:w 0 #3
16214   \exp_after:wN \__fp_mul_significand_small_f:NNwwwN
16215   \else:
16216   \exp_after:wN \__fp_mul_significand_large_f:NwwNNNN
16217   \fi:
16218   #1 #3
16219 }

```

(End definition for `__fp_mul_significand_test_f:NNN`.)

`_fp_mul_significand_large_f:NwwNNNN` In this branch, $\langle digit\ 1 \rangle$ is non-zero. The result is thus $\langle digits\ 1-16 \rangle$, plus some rounding which depends on the digits 16, 17, and whether all subsequent digits are zero or not. Here, `_fp_round_digit:Nw` takes digits 17 and further (as an integer expression), and replaces it by a $\langle rounding\ digit \rangle$, suitable for `_fp_round:NNN`.

```

16220 \cs_new:Npn \_fp_mul_significand_large_f:NwwNNNN #1 #2; #3; #4#5#6#7; +
16221 {
16222   \exp_after:wN \_fp_basics_pack_high:NNNNNw
16223   \int_value:w \_fp_int_eval:w 1#2
16224   \exp_after:wN \_fp_basics_pack_low:NNNNNw
16225   \int_value:w \_fp_int_eval:w 1#3#4#5#6#7
16226   + \exp_after:wN \_fp_round:NNN
16227   \exp_after:wN #1
16228   \exp_after:wN #7
16229   \int_value:w \_fp_round_digit:Nw
16230 }

```

(End definition for `_fp_mul_significand_large_f:NwwNNNN`.)

`_fp_mul_significand_small_f:NNwwwN` In this branch, $\langle digit\ 1 \rangle$ is zero. Our result is thus $\langle digits\ 2-17 \rangle$, plus some rounding which depends on the digits 17, 18, and whether all subsequent digits are zero or not. The 8 digits 1#3 are followed, after expansion of the `small_pack` auxiliary, by the next digit, to form a 9 digit number.

```

16231 \cs_new:Npn \_fp_mul_significand_small_f:NNwwwN #1 #2#3; #4#5; #6; + #7
16232 {
16233   - 1
16234   \exp_after:wN \_fp_basics_pack_high:NNNNNw
16235   \int_value:w \_fp_int_eval:w 1#3#4
16236   \exp_after:wN \_fp_basics_pack_low:NNNNNw
16237   \int_value:w \_fp_int_eval:w 1#5#6#7
16238   + \exp_after:wN \_fp_round:NNN
16239   \exp_after:wN #1
16240   \exp_after:wN #7
16241   \int_value:w \_fp_round_digit:Nw
16242 }

```

(End definition for `_fp_mul_significand_small_f:NNwwwN`.)

29.3 Division

29.3.1 Signs, and special numbers

Time is now ripe to tackle the hardest of the four elementary operations: division.

`_fp_/_o:ww` Filtering special floating point is very similar to what we did for multiplications, with a few variations. Invalid operation exceptions display `/` rather than `*`. In the formula for dispatch, we replace `- 2 +` by `-`. The case of normal numbers is treated using `_fp_div_npos_o:Nww` rather than `_fp_mul_npos_o:Nww`. There are two additional cases: if the first operand is normal and the second is a zero, then the division by zero exception is raised: cases 10 and 11 of the `\if_case:w` construction in `_fp_mul_cases_o:NnNww` are provided as the fourth argument here.

```

16243 \cs_new:cpn { \_fp_/_o:ww }
16244 {
16245   \_fp_mul_cases_o:NnNww

```

```

16246 /
16247 { - }
16248 \__fp_div_npos_o:Nww
16249 {
16250   \or:
16251     \__fp_case_use:nw
16252     { \__fp_division_by_zero_o:NNww \c_inf_fp / }
16253   \or:
16254     \__fp_case_use:nw
16255     { \__fp_division_by_zero_o:NNww \c_minus_inf_fp / }
16256 }
16257 }

```

(End definition for __fp/_o:ww.)

```

\__fp_div_npos_o:Nww \__fp_div_npos_o:Nww <final sign> \s__fp \__fp_chk:w 1 <sign_A> {<exp A>}
{<A_1>} {<A_2>} {<A_3>} {<A_4>} ; \s__fp \__fp_chk:w 1 <sign_Z> {<exp Z>}
{<Z_1>} {<Z_2>} {<Z_3>} {<Z_4>} ;

```

We want to compute A/Z . As for multiplication, `__fp_sanitize:Nw` checks for overflow or underflow; we provide it with the $\langle final\ sign \rangle$, and an integer expression in which we compute the exponent. We set up the arguments of `__fp_div_significand_i_o:wnnw`, namely an integer $\langle y \rangle$ obtained by adding 1 to the first 5 digits of Z (explanation given soon below), then the four $\{ \langle A_i \rangle \}$, then the four $\{ \langle Z_i \rangle \}$, a semi-colon, and the $\langle final\ sign \rangle$, used for rounding at the end.

```

16258 \cs_new:Npn \__fp_div_npos_o:Nww
16259   #1 \s__fp \__fp_chk:w 1 #2 #3 #4 ; \s__fp \__fp_chk:w 1 #5 #6 #7#8#9;
16260 {
16261   \exp_after:wN \__fp_sanitize:Nw
16262   \exp_after:wN #1
16263   \int_value:w \__fp_int_eval:w
16264   #3 - #6
16265   \exp_after:wN \__fp_div_significand_i_o:wnnw
16266   \int_value:w \__fp_int_eval:w #7 \use_i:nnnn #8 + 1 ;
16267   #4
16268   {#7}{#8}#9 ;
16269   #1
16270 }

```

(End definition for __fp_div_npos_o:Nww.)

29.3.2 Work plan

In this subsection, we explain how to avoid overflowing TeX's integers when performing the division of two positive normal numbers.

We are given two numbers, $A = 0.A_1A_2A_3A_4$ and $Z = 0.Z_1Z_2Z_3Z_4$, in blocks of 4 digits, and we know that the first digits of A_1 and of Z_1 are non-zero. To compute A/Z , we proceed as follows.

- Find an integer $Q_A \simeq 10^4 A/Z$.
- Replace A by $B = 10^4 A - Q_A Z$.
- Find an integer $Q_B \simeq 10^4 B/Z$.
- Replace B by $C = 10^4 B - Q_B Z$.

- Find an integer $Q_C \simeq 10^4 C/Z$.
- Replace C by $D = 10^4 C - Q_C Z$.
- Find an integer $Q_D \simeq 10^4 D/Z$.
- Consider $E = 10^4 D - Q_D Z$, and ensure correct rounding.

The result is then $Q = 10^{-4}Q_A + 10^{-8}Q_B + 10^{-12}Q_C + 10^{-16}Q_D + \text{rounding}$. Since the Q_i are integers, B , C , D , and E are all exact multiples of 10^{-16} , in other words, computing with 16 digits after the decimal separator yields exact results. The problem is the risk of overflow: in general B , C , D , and E may be greater than 1.

Unfortunately, things are not as easy as they seem. In particular, we want all intermediate steps to be positive, since negative results would require extra calculations at the end. This requires that $Q_A \leq 10^4 A/Z$ *etc.* A reasonable attempt would be to define Q_A as

$$\backslash\text{int_eval:n}\left\{\frac{A_1 A_2}{Z_1 + 1} - 1\right\} \leq 10^4 \frac{A}{Z}$$

Subtracting 1 at the end takes care of the fact that $\varepsilon\text{-TeX}$'s `_fp_int_eval:w` rounds divisions instead of truncating (really, $1/2$ would be sufficient, but we work with integers). We add 1 to Z_1 because $Z_1 \leq 10^4 Z < Z_1 + 1$ and we need Q_A to be an underestimate. However, we are now underestimating Q_A too much: it can be wrong by up to 100, for instance when $Z = 0.1$ and $A \simeq 1$. Then B could take values up to 10 (maybe more), and a few steps down the line, we would run into arithmetic overflow, since TeX can only handle integers less than roughly $2 \cdot 10^9$.

A better formula is to take

$$Q_A = \backslash\text{int_eval:n}\left\{\frac{10 \cdot A_1 A_2}{\lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1} - 1\right\}.$$

This is always less than $10^9 A/(10^5 Z)$, as we wanted. In words, we take the 5 first digits of Z into account, and the 8 first digits of A , using 0 as a 9-th digit rather than the true digit for efficiency reasons. We shall prove that using this formula to define all the Q_i avoids any overflow. For convenience, let us denote

$$y = \lfloor 10^{-3} \cdot Z_1 Z_2 \rfloor + 1,$$

so that, taking into account the fact that $\varepsilon\text{-TeX}$ rounds ties away from zero,

$$\begin{aligned} Q_A &= \left\lfloor \frac{A_1 A_2 0}{y} - \frac{1}{2} \right\rfloor \\ &> \frac{A_1 A_2 0}{y} - \frac{3}{2}. \end{aligned}$$

Note that $10^4 < y \leq 10^5$, and $999 \leq Q_A \leq 99989$. Also note that this formula does not cause an overflow as long as $A < (2^{31} - 1)/10^9 \simeq 2.147 \dots$, since the numerator involves an integer slightly smaller than $10^9 A$.

Let us bound B :

$$\begin{aligned}
10^5 B &= A_1 A_2 0 + 10 \cdot 0 \cdot A_3 A_4 - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 \cdot Q_A \\
&< A_1 A_2 0 \cdot \left(1 - 10 \cdot \frac{Z_1 \cdot Z_2 Z_3 Z_4}{y}\right) + \frac{3}{2} \cdot 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4 + 10 \\
&\leq \frac{A_1 A_2 0 \cdot (y - 10 \cdot Z_1 \cdot Z_2 Z_3 Z_4)}{y} + \frac{3}{2} y + 10 \\
&\leq \frac{A_1 A_2 0 \cdot 1}{y} + \frac{3}{2} y + 10 \leq \frac{10^9 A}{y} + 1.6 \cdot y.
\end{aligned}$$

At the last step, we hide 10 into the second term for later convenience. The same reasoning yields

$$\begin{aligned}
10^5 B &< 10^9 A/y + 1.6y, \\
10^5 C &< 10^9 B/y + 1.6y, \\
10^5 D &< 10^9 C/y + 1.6y, \\
10^5 E &< 10^9 D/y + 1.6y.
\end{aligned}$$

The goal is now to prove that none of B , C , D , and E can go beyond $(2^{31} - 1)/10^9 = 2.147 \dots$.

Combining the various inequalities together with $A < 1$, we get

$$\begin{aligned}
10^5 B &< 10^9/y + 1.6y, \\
10^5 C &< 10^{13}/y^2 + 1.6(y + 10^4), \\
10^5 D &< 10^{17}/y^3 + 1.6(y + 10^4 + 10^8/y), \\
10^5 E &< 10^{21}/y^4 + 1.6(y + 10^4 + 10^8/y + 10^{12}/y^2).
\end{aligned}$$

All of those bounds are convex functions of y (since every power of y involved is convex, and the coefficients are positive), and thus maximal at one of the end-points of the allowed range $10^4 < y \leq 10^5$. Thus,

$$\begin{aligned}
10^5 B &< \max(1.16 \cdot 10^5, 1.7 \cdot 10^5), \\
10^5 C &< \max(1.32 \cdot 10^5, 1.77 \cdot 10^5), \\
10^5 D &< \max(1.48 \cdot 10^5, 1.777 \cdot 10^5), \\
10^5 E &< \max(1.64 \cdot 10^5, 1.7777 \cdot 10^5).
\end{aligned}$$

All of those bounds are less than $2.147 \cdot 10^5$, and we are thus within $\text{T}_{\text{E}}\text{X}$'s bounds in all cases!

We later need to have a bound on the Q_i . Their definitions imply that $Q_A < 10^9 A/y - 1/2 < 10^5 A$ and similarly for the other Q_i . Thus, all of them are less than 177770.

The last step is to ensure correct rounding. We have

$$A/Z = \sum_{i=1}^4 (10^{-4i} Q_i) + 10^{-16} E/Z$$

exactly. Furthermore, we know that the result is in $[0.1, 10)$, hence will be rounded to a multiple of 10^{-16} or of 10^{-15} , so we only need to know the integer part of E/Z , and a “rounding” digit encoding the rest. Equivalently, we need to find the integer part of $2E/Z$, and determine whether it was an exact integer or not (this serves to detect ties). Since

$$\frac{2E}{Z} = 2 \frac{10^5 E}{10^5 Z} \leq 2 \frac{10^5 E}{10^4} < 36,$$

this integer part is between 0 and 35 inclusive. We let $\varepsilon\text{-TeX}$ round

$$P = \text{\texttt{\textbackslash int_eval:n}} \left\{ \frac{2 \cdot E_1 E_2}{Z_1 Z_2} \right\},$$

which differs from $2E/Z$ by at most

$$\frac{1}{2} + 2 \left| \frac{E}{Z} - \frac{E}{10^{-8} Z_1 Z_2} \right| + 2 \left| \frac{10^8 E - E_1 E_2}{Z_1 Z_2} \right| < 1,$$

($1/2$ comes from $\varepsilon\text{-TeX}$ ’s rounding) because each absolute value is less than 10^{-7} . Thus P is either the correct integer part, or is off by 1; furthermore, if $2E/Z$ is an integer, $P = 2E/Z$. We will check the sign of $2E - PZ$. If it is negative, then $E/Z \in ((P-1)/2, P/2)$. If it is zero, then $E/Z = P/2$. If it is positive, then $E/Z \in (P/2, (P+1)/2)$. In each case, we know how to round to an integer, depending on the parity of P , and the rounding mode.

29.3.3 Implementing the significand division

`_fp_div_significand_i_o:wnnw`

`_fp_div_significand_i_o:wnnw` $\langle y \rangle$; $\{\langle A_1 \rangle\} \{\langle A_2 \rangle\} \{\langle A_3 \rangle\} \{\langle A_4 \rangle\}$
 $\{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$; $\langle sign \rangle$

Compute $10^6 + Q_A$ (a 7 digit number thanks to the shift), unbrace $\langle A_1 \rangle$ and $\langle A_2 \rangle$, and prepare the $\langle continuation \rangle$ arguments for 4 consecutive calls to `_fp_div_significand_calc:wnnnnnnnn`. Each of these calls needs $\langle y \rangle$ (#1), and it turns out that we need post-expansion there, hence the `\int_value:w`. Here, #4 is six brace groups, which give the six first n-type arguments of the `calc` function.

```

16271 \cs_new:Npn \_fp\_div\_significand\_i\_o:wnnw #1 ; #2#3 #4 ;
16272 {
16273   \exp\_after:wN \_fp\_div\_significand\_test\_o:w
16274   \int\_value:w \_fp\_int\_eval:w
16275   \exp\_after:wN \_fp\_div\_significand\_calc:wnnnnnnnn
16276   \int\_value:w \_fp\_int\_eval:w 999999 + #2 #3 0 / #1 ;
16277   #2 #3 ;
16278   #4
16279   { \exp\_after:wN \_fp\_div\_significand\_ii:wN \int\_value:w #1 }
16280   { \exp\_after:wN \_fp\_div\_significand\_ii:wN \int\_value:w #1 }
16281   { \exp\_after:wN \_fp\_div\_significand\_ii:wN \int\_value:w #1 }
16282   { \exp\_after:wN \_fp\_div\_significand\_iii:wnnnnnn \int\_value:w #1 }
16283 }
```

(End definition for `_fp_div_significand_i_o:wnnw`.)

`_fp_div_significand_calc:wnnnnnnnn`
`_fp_div_significand_calc_i:wnnnnnnnn`
`_fp_div_significand_calc_ii:wnnnnnnnn`

`_fp_div_significand_calc:wnnnnnnnn` $\langle 10^6 + Q_A \rangle$; $\langle A_1 \rangle \langle A_2 \rangle$; $\{\langle A_3 \rangle\}$
 $\{\langle A_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\} \{\langle continuation \rangle\}$
 expands to

$$\langle 10^6 + Q_A \rangle \langle continuation \rangle ; \langle B_1 \rangle \langle B_2 \rangle ; \{\langle B_3 \rangle\} \{\langle B_4 \rangle\} \{\langle Z_1 \rangle\} \{\langle Z_2 \rangle\} \{\langle Z_3 \rangle\} \{\langle Z_4 \rangle\}$$

where $B = 10^4 A - Q_A \cdot Z$. This function is also used to compute C , D , E (with the input shifted accordingly), and is used in `l3fp-expo`.

We know that $0 < Q_A < 1.8 \cdot 10^5$, so the product of Q_A with each Z_i is within $\text{T}_{\text{E}}\text{X}$'s bounds. However, it is a little bit too large for our purposes: we would not be able to use the usual trick of adding a large power of 10 to ensure that the number of digits is fixed.

The bound on Q_A , implies that $10^6 + Q_A$ starts with the digit 1, followed by 0 or 1. We test, and call different auxiliaries for the two cases. An earlier implementation did the tests within the computation, but since we added a $\langle continuation \rangle$, this is not possible because the macro has 9 parameters.

The result we want is then (the overall power of 10 is arbitrary):

$$10^{-4}(\#2 - \#1 \cdot \#5 - 10 \cdot \langle i \rangle \cdot \#5\#6) + 10^{-8}(\#3 - \#1 \cdot \#6 - 10 \cdot \langle i \rangle \cdot \#7) \\ + 10^{-12}(\#4 - \#1 \cdot \#7 - 10 \cdot \langle i \rangle \cdot \#8) + 10^{-16}(-\#1 \cdot \#8),$$

where $\langle i \rangle$ stands for the 10^5 digit of Q_A , which is 0 or 1, and $\#1$, $\#2$, *etc.* are the parameters of either auxiliary. The factors of 10 come from the fact that $Q_A = 10 \cdot 10^4 \cdot \langle i \rangle + \#1$. As usual, to combine all the terms, we need to choose some shifts which must ensure that the number of digits of the second, third, and fourth terms are each fixed. Here, the positive contributions are at most 10^8 and the negative contributions can go up to 10^9 . Indeed, for the auxiliary with $\langle i \rangle = 1$, $\#1$ is at most 80000, leading to contributions of at worst $-8 \cdot 10^8$, while the other negative term is very small $< 10^6$ (except in the first expression, where we don't care about the number of digits); for the auxiliary with $\langle i \rangle = 0$, $\#1$ can go up to 99999, but there is no other negative term. Hence, a good choice is $2 \cdot 10^9$, which produces totals in the range $[10^9, 2.1 \cdot 10^9]$. We are flirting with $\text{T}_{\text{E}}\text{X}$'s limits once more.

```

16284 \cs_new:Npn \__fp_div_significand_calc:wwnnnnnnn #1
16285 {
16286   \if_meaning:w 1 #1
16287     \exp_after:wN \__fp_div_significand_calc_i:wwnnnnnnn
16288   \else:
16289     \exp_after:wN \__fp_div_significand_calc_ii:wwnnnnnnn
16290   \fi:
16291 }
16292 \cs_new:Npn \__fp_div_significand_calc_i:wwnnnnnnn
16293   #1; #2; #3 #4 #5 #6 #7 #8 #9
16294 {
16295   1 1 #1
16296   #9 \exp_after:wN ;
16297   \int_value:w \__fp_int_eval:w \c__fp_Bigg_leading_shift_int
16298     + #2 - #1 * #5 - #5#60
16299   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
16300   \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
16301     + #3 - #1 * #6 - #70
16302   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
16303   \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
16304     + #4 - #1 * #7 - #80
16305   \exp_after:wN \__fp_pack_Bigg:NNNNNNw
16306   \int_value:w \__fp_int_eval:w \c__fp_Bigg_trailing_shift_int

```

```

16307         - #1 * #8 ;
16308     {#5}{#6}{#7}{#8}
16309 }
16310 \cs_new:Npn \__fp_div_significand_calc_ii:wwnnnnnnn
16311 #1; #2;#3#4 #5#6#7#8 #9
16312 {
16313     1 0 #1
16314     #9 \exp_after:wN ;
16315     \int_value:w \__fp_int_eval:w \c__fp_Bigg_leading_shift_int
16316     + #2 - #1 * #5
16317     \exp_after:wN \__fp_pack_Bigg:NNNNNNw
16318     \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
16319     + #3 - #1 * #6
16320     \exp_after:wN \__fp_pack_Bigg:NNNNNNw
16321     \int_value:w \__fp_int_eval:w \c__fp_Bigg_middle_shift_int
16322     + #4 - #1 * #7
16323     \exp_after:wN \__fp_pack_Bigg:NNNNNNw
16324     \int_value:w \__fp_int_eval:w \c__fp_Bigg_trailing_shift_int
16325     - #1 * #8 ;
16326     {#5}{#6}{#7}{#8}
16327 }

```

(End definition for __fp_div_significand_calc:wwnnnnnnn, __fp_div_significand_calc_i:wwnnnnnnn, and __fp_div_significand_calc_ii:wwnnnnnnn.)

__fp_div_significand_ii:wnn __fp_div_significand_ii:wnn $\langle y \rangle$; $\langle B_1 \rangle$; $\{\langle B_2 \rangle\}$ $\{\langle B_3 \rangle\}$ $\{\langle B_4 \rangle\}$ $\{\langle Z_1 \rangle\}$ $\{\langle Z_2 \rangle\}$ $\{\langle Z_3 \rangle\}$ $\{\langle Z_4 \rangle\}$ $\langle continuations \rangle$ $\langle sign \rangle$

Compute Q_B by evaluating $\langle B_1 \rangle \langle B_2 \rangle 0 / y - 1$. The result is output to the left, in an __fp_int_eval:w which we start now. Once that is evaluated (and the other Q_i also, since later expansions are triggered by this one), a packing auxiliary takes care of placing the digits of Q_B in an appropriate way for the final addition to obtain Q . This auxiliary is also used to compute Q_C and Q_D with the inputs C and D instead of B .

```

16328 \cs_new:Npn \__fp_div_significand_ii:wnn #1; #2;#3
16329 {
16330     \exp_after:wN \__fp_div_significand_pack:NNN
16331     \int_value:w \__fp_int_eval:w
16332     \exp_after:wN \__fp_div_significand_calc:wwnnnnnnn
16333     \int_value:w \__fp_int_eval:w 999999 + #2 #3 0 / #1 ; #2 #3 ;
16334 }

```

(End definition for __fp_div_significand_ii:wnn.)

__fp_div_significand_iii:wwnnnnn __fp_div_significand_iii:wwnnnnn $\langle y \rangle$; $\langle E_1 \rangle$; $\{\langle E_2 \rangle\}$ $\{\langle E_3 \rangle\}$ $\{\langle E_4 \rangle\}$ $\{\langle Z_1 \rangle\}$ $\{\langle Z_2 \rangle\}$ $\{\langle Z_3 \rangle\}$ $\{\langle Z_4 \rangle\}$ $\langle sign \rangle$

We compute $P \simeq 2E/Z$ by rounding $2E_1E_2/Z_1Z_2$. Note the first 0, which multiplies Q_D by 10: we later add (roughly) $5 \cdot P$, which amounts to adding $P/2 \simeq E/Z$ to Q_D , the appropriate correction from a hypothetical Q_E .

```

16335 \cs_new:Npn \__fp_div_significand_iii:wwnnnnn #1; #2;#3#4#5 #6#7
16336 {
16337     0
16338     \exp_after:wN \__fp_div_significand_iv:wwnnnnnnn
16339     \int_value:w \__fp_int_eval:w ( 2 * #2 #3 ) / #6 #7 ; % <- P
16340     #2 ; {#3} {#4} {#5}
16341     {#6} {#7}

```

16342 }

(End definition for _fp_div_significand_iii:wwnnnnnn.)

_fp_div_significand_iv:wwnnnnnnnn
_fp_div_significand_v:NNw
_fp_div_significand_vi:Nw

_fp_div_significand_iv:wwnnnnnnnn $\langle P \rangle$; $\langle E_1 \rangle$; $\{\langle E_2 \rangle\}$ $\{\langle E_3 \rangle\}$ $\{\langle E_4 \rangle\}$
 $\{\langle Z_1 \rangle\}$ $\{\langle Z_2 \rangle\}$ $\{\langle Z_3 \rangle\}$ $\{\langle Z_4 \rangle\}$ $\langle sign \rangle$

This adds to the current expression $(10^7 + 10 \cdot Q_D)$ a contribution of $5 \cdot P + \text{sign}(T)$ with $T = 2E - PZ$. This amounts to adding $P/2$ to Q_D , with an extra $\langle \text{rounding} \rangle$ digit. This $\langle \text{rounding} \rangle$ digit is 0 or 5 if T does not contribute, *i.e.*, if $0 = T = 2E - PZ$, in other words if $10^{16}A/Z$ is an integer or half-integer. Otherwise it is in the appropriate range, $[1, 4]$ or $[6, 9]$. This is precise enough for rounding purposes (in any mode).

It seems an overkill to compute T exactly as I do here, but I see no faster way right now.

Once more, we need to be careful and show that the calculation $\#1 \cdot \#6\#7$ below does not cause an overflow: naively, P can be up to 35, and $\#6\#7$ up to 10^8 , but both cannot happen simultaneously. To show that things are fine, we split in two (non-disjoint) cases.

- For $P < 10$, the product obeys $P \cdot \#6\#7 < 10^8 \cdot P < 10^9$.
- For large $P \geq 3$, the rounding error on P , which is at most 1, is less than a factor of 2, hence $P \leq 4E/Z$. Also, $\#6\#7 \leq 10^8 \cdot Z$, hence $P \cdot \#6\#7 \leq 4E \cdot 10^8 < 10^9$.

Both inequalities could be made tighter if needed.

Note however that $P \cdot \#8\#9$ may overflow, since the two factors are now independent, and the result may reach $3.5 \cdot 10^9$. Thus we compute the two lower levels separately. The rest is standard, except that we use $+$ as a separator (ending integer expressions explicitly). T is negative if the first character is $-$, it is positive if the first character is neither 0 nor $-$. It is also positive if the first character is 0 and second argument of $_fp_div_significand_vi:Nw$, a sum of several terms, is also zero. Otherwise, there was an exact agreement: $T = 0$.

```

16343 \cs_new:Npn \_fp_div_significand_iv:wwnnnnnnnn #1; #2;#3#4#5 #6#7#8#9
16344 {
16345   + 5 * #1
16346   \exp_after:wN \_fp_div_significand_vi:Nw
16347   \int_value:w \_fp_int_eval:w -20 + 2*#2#3 - #1*#6#7 +
16348   \exp_after:wN \_fp_div_significand_v:NN
16349   \int_value:w \_fp_int_eval:w 199980 + 2*#4 - #1*#8 +
16350   \exp_after:wN \_fp_div_significand_v:NN
16351   \int_value:w \_fp_int_eval:w 200000 + 2*#5 - #1*#9 ;
16352 }
16353 \cs_new:Npn \_fp_div_significand_v:NN #1#2 { #1#2 \_fp_int_eval_end: + }
16354 \cs_new:Npn \_fp_div_significand_vi:Nw #1#2;
16355 {
16356   \if_meaning:w 0 #1
16357   \if_int_compare:w \_fp_int_eval:w #2 > 0 + 1 \fi:
16358   \else:
16359   \if_meaning:w - #1 - \else: + \fi: 1
16360   \fi:
16361   ;
16362 }
```

(End definition for _fp_div_significand_iv:wwnnnnnnnn, _fp_div_significand_v:NNw, and _fp_div_significand_vi:Nw.)

`_fp_div_significand_pack:NNN` At this stage, we are in the following situation: \TeX is in the process of expanding several integer expressions, thus functions at the bottom expand before those above.

```
\_fp_div_significand_test_o:w 10^6 + Q_A \_fp_div_significand_-
pack:NNN 10^6 + Q_B \_fp_div_significand_pack:NNN 10^6 + Q_C \_fp_-
div_significand_pack:NNN 10^7 + 10 \cdot Q_D + 5 \cdot P + \varepsilon ; \langle sign \rangle
```

Here, $\varepsilon = \text{sign}(T)$ is 0 in case $2E = PZ$, 1 in case $2E > PZ$, which means that P was the correct value, but not with an exact quotient, and -1 if $2E < PZ$, *i.e.*, P was an overestimate. The packing function we define now does nothing special: it removes the 10^6 and carries two digits (for the 10^5 's and the 10^4 's).

```
16363 \cs_new:Npn \_fp_div_significand_pack:NNN 1 #1 #2 { + #1 #2 ; }
```

(End definition for `_fp_div_significand_pack:NNN`.)

```
\_fp_div_significand_test_o:w \_fp_div_significand_test_o:w 1 0 \langle 5d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle ; \langle sign \rangle
```

The reason we know that the first two digits are 1 and 0 is that the final result is known to be between 0.1 (inclusive) and 10, hence \widetilde{Q}_A (the tilde denoting the contribution from the other Q_i) is at most 99999, and $10^6 + \widetilde{Q}_A = 10 \dots$.

It is now time to round. This depends on how many digits the final result will have.

```
16364 \cs_new:Npn \_fp_div_significand_test_o:w 10 #1
16365 {
16366   \if_meaning:w 0 #1
16367     \exp_after:wN \_fp_div_significand_small_o:wwwNNNNwN
16368   \else:
16369     \exp_after:wN \_fp_div_significand_large_o:wwwNNNNwN
16370   \fi:
16371   #1
16372 }
```

(End definition for `_fp_div_significand_test_o:w`.)

```
\_fp_div_significand_small_o:wwwNNNNwN \_fp_div_significand_small_o:wwwNNNNwN 0 \langle 4d \rangle ; \langle 4d \rangle ; \langle 4d \rangle ; \langle 5d \rangle
; \langle final sign \rangle
```

Standard use of the functions `_fp_basics_pack_low:NNNNw` and `_fp_basics_pack_high:NNNNw`. We finally get to use the $\langle final\ sign \rangle$ which has been sitting there for a while.

```
16373 \cs_new:Npn \_fp_div_significand_small_o:wwwNNNNwN
16374   0 #1; #2; #3; #4#5#6#7#8; #9
16375 {
16376   \exp_after:wN \_fp_basics_pack_high:NNNNw
16377   \int_value:w \_fp_int_eval:w 1 #1#2
16378   \exp_after:wN \_fp_basics_pack_low:NNNNw
16379   \int_value:w \_fp_int_eval:w 1 #3#4#5#6#7
16380   + \_fp_round:NNN #9 #7 #8
16381   \exp_after:wN ;
16382 }
```

(End definition for `_fp_div_significand_small_o:wwwNNNNwN`.)

`_fp_div_significand_large_o:wwwNNNNwN` `_fp_div_significand_large_o:wwwNNNNwN` $\langle 5d \rangle$; $\langle 4d \rangle$; $\langle 4d \rangle$; $\langle 5d \rangle$;
 $\langle sign \rangle$

We know that the final result cannot reach 10, hence $1\#1\#2$, together with contributions from the level below, cannot reach $2 \cdot 10^9$. For rounding, we build the $\langle rounding\ digit \rangle$ from the last two of our 18 digits.

```

16383 \cs_new:Npn \_fp_div_significand_large_o:wwwNNNNwN
16384 #1; #2; #3; #4#5#6#7#8; #9
16385 {
16386   + 1
16387   \exp_after:wN \_fp_basics_pack_weird_high:NNNNNNNNw
16388   \int_value:w \_fp_int_eval:w 1 #1 #2
16389   \exp_after:wN \_fp_basics_pack_weird_low:NNNNw
16390   \int_value:w \_fp_int_eval:w 1 #3 #4 #5 #6 +
16391   \exp_after:wN \_fp_round:NNN
16392   \exp_after:wN #9
16393   \exp_after:wN #6
16394   \int_value:w \_fp_round_digit:Nw #7 #8 ;
16395   \exp_after:wN ;
16396 }

```

(End definition for `_fp_div_significand_large_o:wwwNNNNwN`.)

29.4 Square root

`_fp_sqrt_o:w` Zeros are unchanged: $\sqrt{-0} = -0$ and $\sqrt{+0} = +0$. Negative numbers (other than -0) have no real square root. Positive infinity, and `nan`, are unchanged. Finally, for normal positive numbers, there is some work to do.

```

16397 \cs_new:Npn \_fp_sqrt_o:w #1 \s_fp \_fp_chk:w #2#3#4; @
16398 {
16399   \if_meaning:w 0 #2 \_fp_case_return_same_o:w \fi:
16400   \if_meaning:w 2 #3
16401     \_fp_case_use:nw { \_fp_invalid_operation_o:nw { sqrt } }
16402   \fi:
16403   \if_meaning:w 1 #2 \else: \_fp_case_return_same_o:w \fi:
16404   \_fp_sqrt_npos_o:w
16405   \s_fp \_fp_chk:w #2 #3 #4;
16406 }

```

(End definition for `_fp_sqrt_o:w`.)

`_fp_sqrt_npos_o:w` Prepare `_fp_sanitize:Nw` to receive the final sign 0 (the result is always positive) and
`_fp_sqrt_npos_auxi_o:wwwnnN` the exponent, equal to half of the exponent #1 of the argument. If the exponent #1 is even,
`_fp_sqrt_npos_auxii_o:wwwnnNNNN` find a first approximation of the square root of the significand $10^8 a_1 + a_2 = 10^8 \#2\#3 + \#4\#5$
 through Newton's method, starting at $x = 57234133 \simeq 10^{7.75}$. Otherwise, first shift the
 significand of of the argument by one digit, getting $a'_1 \in [10^6, 10^7)$ instead of $[10^7, 10^8)$,
 then use Newton's method starting at $17782794 \simeq 10^{7.25}$.

```

16407 \cs_new:Npn \_fp_sqrt_npos_o:w \s_fp \_fp_chk:w 1 0 #1#2#3#4#5;
16408 {
16409   \exp_after:wN \_fp_sanitize:Nw
16410   \exp_after:wN 0
16411   \int_value:w \_fp_int_eval:w
16412   \if_int_odd:w #1 \exp_stop_f:
16413     \exp_after:wN \_fp_sqrt_npos_auxi_o:wwwnnN

```

```

16414      \fi:
16415      #1 / 2
16416      \__fp_sqrt_Newton_o:wnn 56234133; 0; {#2#3} {#4#5} 0
16417    }
16418 \cs_new:Npn \__fp_sqrt_npos_auxi_o:wnnnN #1 / 2 #2; 0; #3#4#5
16419 {
16420   ( #1 + 1 ) / 2
16421   \__fp_pack_eight:wNNNNNNNN
16422   \__fp_sqrt_npos_auxii_o:wNNNNNNNN
16423   ;
16424   0 #3 #4
16425 }
16426 \cs_new:Npn \__fp_sqrt_npos_auxii_o:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
16427 { \__fp_sqrt_Newton_o:wnn 17782794; 0; {#1} {#2#3#4#5#6#7#8#9} }

```

(End definition for `__fp_sqrt_npos_o:w`, `__fp_sqrt_npos_auxi_o:wnnnN`, and `__fp_sqrt_npos_auxii_o:wNNNNNNNN`.)

`__fp_sqrt_Newton_o:wnn` Newton's method maps $x \mapsto [(x + [10^8 a_1/x])/2]$ in each iteration, where $[b/c]$ denotes ε -TeX's division. This division rounds the real number b/c to the closest integer, rounding ties away from zero, hence when c is even, $b/c - 1/2 + 1/c \leq [b/c] \leq b/c + 1/2$ and when c is odd, $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2 - 1/(2c)$. For all c , $b/c - 1/2 + 1/(2c) \leq [b/c] \leq b/c + 1/2$.

Let us prove that the method converges when implemented with ε -TeX integer division, for any $10^6 \leq a_1 < 10^8$ and starting value $10^6 \leq x < 10^8$. Using the inequalities above and the arithmetic-geometric inequality $(x + t)/2 \geq \sqrt{xt}$ for $t = 10^8 a_1/x$, we find

$$x' = \left\lceil \frac{x + [10^8 a_1/x]}{2} \right\rceil \geq \frac{x + 10^8 a_1/x - 1/2 + 1/(2x)}{2} \geq \sqrt{10^8 a_1} - \frac{1}{4} + \frac{1}{4x}.$$

After any step of iteration, we thus have $\delta = x - \sqrt{10^8 a_1} \geq -0.25 + 0.25 \cdot 10^{-8}$. The new difference $\delta' = x' - \sqrt{10^8 a_1}$ after one step is bounded above as

$$x' - \sqrt{10^8 a_1} \leq \frac{x + 10^8 a_1/x + 1/2}{2} + \frac{1}{2} - \sqrt{10^8 a_1} \leq \frac{\delta}{2} \frac{\delta}{\sqrt{10^8 a_1} + \delta} + \frac{3}{4}.$$

For $\delta > 3/2$, this last expression is $\leq \delta/2 + 3/4 < \delta$, hence δ decreases at each step: since all x are integers, δ must reach a value $-1/4 < \delta \leq 3/2$. In this range of values, we get $\delta' \leq \frac{3}{4} \frac{3}{2\sqrt{10^8 a_1}} + \frac{3}{4} \leq 0.75 + 1.125 \cdot 10^{-7}$. We deduce that the difference $\delta = x - \sqrt{10^8 a_1}$ eventually reaches a value in the interval $[-0.25 + 0.25 \cdot 10^{-8}, 0.75 + 11.25 \cdot 10^{-8}]$, whose width is $1 + 11 \cdot 10^{-8}$. The corresponding interval for x may contain two integers, hence x might oscillate between those two values.

However, the fact that $x \mapsto x - 1$ and $x - 1 \mapsto x$ puts stronger constraints, which are not compatible: the first implies

$$x + [10^8 a_1/x] \leq 2x - 2$$

hence $10^8 a_1/x \leq x - 3/2$, while the second implies

$$x - 1 + [10^8 a_1/(x - 1)] \geq 2x - 1$$

hence $10^8 a_1/(x - 1) \geq x - 1/2$. Combining the two inequalities yields $x^2 - 3x/2 \geq 10^8 a_1 \geq x - 3x/2 + 1/2$, which cannot hold. Therefore, the iteration always converges

to a single integer x . To stop the iteration when two consecutive results are equal, the function `_fp_sqrt_Newton_o:wnn` receives the newly computed result as `#1`, the previous result as `#2`, and a_1 as `#3`. Note that ε -TeX combines the computation of a multiplication and a following division, thus avoiding overflow in `#3 * 100000000 / #1`. In any case, the result is within $[10^7, 10^8]$.

```

16428 \cs_new:Npn \_fp_sqrt_Newton_o:wnn #1; #2; #3
16429 {
16430   \if_int_compare:w #1 = #2 \exp_stop_f:
16431     \exp_after:wN \_fp_sqrt_auxi_o:NNNNwnnnN
16432     \int_value:w \_fp_int_eval:w 9999 9999 +
16433     \exp_after:wN \_fp_use_none_until_s:w
16434   \fi:
16435   \exp_after:wN \_fp_sqrt_Newton_o:wnn
16436   \int_value:w \_fp_int_eval:w (#1 + #3 * 1 0000 0000 / #1) / 2 ;
16437   #1; {#3}
16438 }

```

(End definition for `_fp_sqrt_Newton_o:wnn`.)

`_fp_sqrt_auxi_o:NNNNwnnnN` This function is followed by $10^8 + x - 1$, which has 9 digits starting with 1, then ; $\{\langle a_1 \rangle\} \{\langle a_2 \rangle\} \langle a' \rangle$. Here, $x \simeq \sqrt{10^8 a_1}$ and we want to estimate the square root of $a = 10^{-8}a_1 + 10^{-16}a_2 + 10^{-17}a'$. We set up an initial underestimate

$$y = (x - 1)10^{-8} + 0.2499998875 \cdot 10^{-8} \lesssim \sqrt{a}.$$

From the inequalities shown earlier, we know that $y \leq \sqrt{10^{-8}a_1} \leq \sqrt{a}$ and that $\sqrt{10^{-8}a_1} \leq y + 10^{-8} + 11 \cdot 10^{-16}$ hence (using $0.1 \leq y \leq \sqrt{a} \leq 1$)

$$a - y^2 \leq 10^{-8}a_1 + 10^{-8} - y^2 \leq (y + 10^{-8} + 11 \cdot 10^{-16})^2 - y^2 + 10^{-8} < 3.2 \cdot 10^{-8},$$

and $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y) \leq 16 \cdot 10^{-8}$. Next, `_fp_sqrt_auxii_o:NnnnnnnnnN` is called several times to get closer and closer underestimates of \sqrt{a} . By construction, the underestimates y are always increasing, $a - y^2 < 3.2 \cdot 10^{-8}$ for all. Also, $y < 1$.

```

16439 \cs_new:Npn \_fp_sqrt_auxi_o:NNNNwnnnN 1 #1#2#3#4#5;
16440 {
16441   \_fp_sqrt_auxii_o:NnnnnnnnnN
16442   \_fp_sqrt_auxiii_o:wnnnnnnnnn
16443   {#1#2#3#4} {#5} {2499} {9988} {7500}
16444 }

```

(End definition for `_fp_sqrt_auxi_o:NNNNwnnnN`.)

`_fp_sqrt_auxii_o:NnnnnnnnnN` This receives a continuation function `#1`, then five blocks of 4 digits for y , then two 8-digit blocks and a single digit for a . A common estimate of $\sqrt{a} - y = (a - y^2)/(\sqrt{a} + y)$ is $(a - y^2)/(2y)$, which leads to alternating overestimates and underestimates. We tweak this, to only work with underestimates (no need then to worry about signs in the computation). Each step finds the largest integer $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then computes the integer (with ε -TeX's rounding division)

$$10^{4j}z = \left[([10^{4j}(a - y^2)] - 257) \cdot (0.5 \cdot 10^8) / [10^8 y + 1] \right].$$

The choice of j ensures that $10^{4j}z < 2 \cdot 10^8 \cdot 0.5 \cdot 10^8 / 10^7 = 10^9$, thus $10^9 + 10^{4j}z$ has exactly 10 digits, does not overflow TeX's integer range, and starts with 1. Incidentally, since all $a - y^2 \leq 3.2 \cdot 10^{-8}$, we know that $j \geq 3$.

Let us show that z is an underestimate of $\sqrt{a}-y$. On the one hand, $\sqrt{a}-y \leq 16 \cdot 10^{-8}$ because this holds for the initial y and values of y can only increase. On the other hand, the choice of j implies that $\sqrt{a}-y \leq 5(\sqrt{a}+y)(\sqrt{a}-y) = 5(a-y^2) < 10^{9-4j}$. For $j = 3$, the first bound is better, while for larger j , the second bound is better. For all $j \in [3, 6]$, we find $\sqrt{a}-y < 16 \cdot 10^{-2j}$. From this, we deduce that

$$10^{4j}(\sqrt{a}-y) = \frac{10^{4j}(a-y^2-(\sqrt{a}-y)^2)}{2y} \geq \frac{\lfloor 10^{4j}(a-y^2) \rfloor - 257}{2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor} + \frac{1}{2}$$

where we have replaced the bound $10^{4j}(16 \cdot 10^{-2j}) = 256$ by 257 and extracted the corresponding term $1/(2 \cdot 10^{-8} \lfloor 10^8 y + 1 \rfloor) \geq 1/2$. Given that ε -TeX's integer division obeys $\lfloor b/c \rfloor \leq b/c + 1/2$, we deduce that $10^{4j}z \leq 10^{4j}(\sqrt{a}-y)$, hence $y+z \leq \sqrt{a}$ is an underestimate of \sqrt{a} , as claimed. One implementation detail: because the computation involves $-4*4 - 2*3*5 - 2*2*6$ which may be as low as $-5 \cdot 10^8$, we need to use the `pack_big` functions, and the big shifts.

```

16445 \cs_new:Npn \__fp_sqrt_auxii_o:NnnnnnnN #1 #2#3#4#5#6 #7#8#9
16446 {
16447   \exp_after:wN #1
16448   \int_value:w \__fp_int_eval:w \c__fp_big_leading_shift_int
16449     + #7 - #2 * #2
16450   \exp_after:wN \__fp_pack_big:NnnnnNw
16451   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
16452     - 2 * #2 * #3
16453   \exp_after:wN \__fp_pack_big:NnnnnNw
16454   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
16455     + #8 - #3 * #3 - 2 * #2 * #4
16456   \exp_after:wN \__fp_pack_big:NnnnnNw
16457   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
16458     - 2 * #3 * #4 - 2 * #2 * #5
16459   \exp_after:wN \__fp_pack_big:NnnnnNw
16460   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
16461     + #9 000 0000 - #4 * #4 - 2 * #3 * #5 - 2 * #2 * #6
16462   \exp_after:wN \__fp_pack_big:NnnnnNw
16463   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
16464     - 2 * #4 * #5 - 2 * #3 * #6
16465   \exp_after:wN \__fp_pack_big:NnnnnNw
16466   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int
16467     - #5 * #5 - 2 * #4 * #6
16468   \exp_after:wN \__fp_pack_big:NnnnnNw
16469   \int_value:w \__fp_int_eval:w
16470     \c__fp_big_middle_shift_int
16471     - 2 * #5 * #6
16472   \exp_after:wN \__fp_pack_big:NnnnnNw
16473   \int_value:w \__fp_int_eval:w
16474     \c__fp_big_trailing_shift_int
16475     - #6 * #6 ;
16476   % (
16477   - 257 ) * 5000 0000 / (#2#3 + 1) + 10 0000 0000 ;
16478   {#2}{#3}{#4}{#5}{#6} {#7}{#8}#9
16479 }

```

(End definition for `__fp_sqrt_auxii_o:NnnnnnnN`.)

```

\__fp_sqrt_auxiii_o:wnnnnnnnn
\__fp_sqrt_auxiv_o:NNNNNw
\__fp_sqrt_auxv_o:NNNNNw
\__fp_sqrt_auxvi_o:NNNNNw
\__fp_sqrt_auxvii_o:NNNNNw

```

We receive here the difference $a - y^2 = d = \sum_i d_i \cdot 10^{-4i}$, as $\langle d_2 \rangle ; \{\langle d_3 \rangle\} \dots \{\langle d_{10} \rangle\}$, where each block has 4 digits, except $\langle d_2 \rangle$. This function finds the largest $j \leq 6$ such that $10^{4j}(a - y^2) < 2 \cdot 10^8$, then leaves an open parenthesis and the integer $\lfloor 10^{4j}(a - y^2) \rfloor$ in an integer expression. The closing parenthesis is provided by the caller `__fp_sqrt_auxii_o:NnnnnnnnN`, which completes the expression

$$10^{4j}z = \left[(\lfloor 10^{4j}(a - y^2) \rfloor - 257) \cdot (0.5 \cdot 10^8) / \lfloor 10^8 y + 1 \rfloor \right]$$

for an estimate of $10^{4j}(\sqrt{a} - y)$. If $d_2 \geq 2$, $j = 3$ and the `auxiv` auxiliary receives $10^{12}z$. If $d_2 \leq 1$ but $10^4 d_2 + d_3 \geq 2$, $j = 4$ and the `auxv` auxiliary is called, and receives $10^{16}z$, and so on. In all those cases, the `auxviii` auxiliary is set up to add z to y , then go back to the `auxii` step with continuation `auxiii` (the function we are currently describing). The maximum value of j is 6, regardless of whether $10^{12}d_2 + 10^8 d_3 + 10^4 d_4 + d_5 \geq 1$. In this last case, we detect when $10^{24}z < 10^7$, which essentially means $\sqrt{a} - y \lesssim 10^{-17}$: once this threshold is reached, there is enough information to find the correctly rounded \sqrt{a} with only one more call to `__fp_sqrt_auxii_o:NnnnnnnnN`. Note that the iteration cannot be stuck before reaching $j = 6$, because for $j < 6$, one has $2 \cdot 10^8 \leq 10^{4(j+1)}(a - y^2)$, hence

$$10^{4j}z \geq \frac{(20000 - 257)(0.5 \cdot 10^8)}{\lfloor 10^8 y + 1 \rfloor} \geq (20000 - 257) \cdot 0.5 > 0.$$

```

16480 \cs_new:Npn \__fp_sqrt_auxiii_o:wnnnnnnnn
16481   #1; #2#3#4#5#6#7#8#9
16482   {
16483     \if_int_compare:w #1 > 1 \exp_stop_f:
16484     \exp_after:wN \__fp_sqrt_auxiv_o:NNNNNw
16485     \int_value:w \__fp_int_eval:w (#1#2 %)
16486   \else:
16487     \if_int_compare:w #1#2 > 1 \exp_stop_f:
16488     \exp_after:wN \__fp_sqrt_auxv_o:NNNNNw
16489     \int_value:w \__fp_int_eval:w (#1#2#3 %)
16490   \else:
16491     \if_int_compare:w #1#2#3 > 1 \exp_stop_f:
16492     \exp_after:wN \__fp_sqrt_auxvi_o:NNNNNw
16493     \int_value:w \__fp_int_eval:w (#1#2#3#4 %)
16494   \else:
16495     \exp_after:wN \__fp_sqrt_auxvii_o:NNNNNw
16496     \int_value:w \__fp_int_eval:w (#1#2#3#4#5 %)
16497   \fi:
16498   \fi:
16499   \fi:
16500 }
16501 \cs_new:Npn \__fp_sqrt_auxiv_o:NNNNNw 1#1#2#3#4#5#6;
16502   { \__fp_sqrt_auxviii_o:nnnnnnn {#1#2#3#4#5#6} {00000000} }
16503 \cs_new:Npn \__fp_sqrt_auxv_o:NNNNNw 1#1#2#3#4#5#6;
16504   { \__fp_sqrt_auxviii_o:nnnnnnn {000#1#2#3#4#5} {#60000} }
16505 \cs_new:Npn \__fp_sqrt_auxvi_o:NNNNNw 1#1#2#3#4#5#6;
16506   { \__fp_sqrt_auxviii_o:nnnnnnn {0000000#1} {#2#3#4#5#6} }
16507 \cs_new:Npn \__fp_sqrt_auxvii_o:NNNNNw 1#1#2#3#4#5#6;
16508   {
16509     \if_int_compare:w #1#2 = 0 \exp_stop_f:
16510     \exp_after:wN \__fp_sqrt_auxx_o:Nnnnnnnn
16511   \fi:

```

```

16512     \_fp_sqrt_auxviii_o:nnnnnnnn {00000000} {000#1#2#3#4#5}
16513   }

```

(End definition for _fp_sqrt_auxiii_o:wnnnnnnn and others.)

_fp_sqrt_auxviii_o:nnnnnnnn Simply add the two 8-digit blocks of z , aligned to the last four of the five 4-digit blocks of y , then call the auxii auxiliary to evaluate $y'^2 = (y + z)^2$.

```

16514 \cs_new:Npn \_fp_sqrt_auxviii_o:nnnnnnnn #1#2 #3#4#5#6#7
16515 {
16516   \exp_after:wN \_fp_sqrt_auxix_o:wnwnw
16517   \int_value:w \_fp_int_eval:w #3
16518   \exp_after:wN \_fp_basics_pack_low:NNNNNw
16519   \int_value:w \_fp_int_eval:w #1 + 1#4#5
16520   \exp_after:wN \_fp_basics_pack_low:NNNNNw
16521   \int_value:w \_fp_int_eval:w #2 + 1#6#7 ;
16522 }
16523 \cs_new:Npn \_fp_sqrt_auxix_o:wnwnw #1; #2#3; #4#5;
16524 {
16525   \_fp_sqrt_auxii_o:NnnnnnnnN
16526   \_fp_sqrt_auxiii_o:wnnnnnnnnn {#1}{#2}{#3}{#4}{#5}
16527 }

```

(End definition for _fp_sqrt_auxviii_o:nnnnnnnn and _fp_sqrt_auxix_o:wnwnw.)

_fp_sqrt_auxx_o:Nnnnnnnnn At this stage, $j = 6$ and $10^{24}z < 10^7$, hence
 _fp_sqrt_auxxi_o:wwnnN

$$10^7 + 1/2 > 10^{24}z + 1/2 \geq (10^{24}(a - y^2) - 258) \cdot (0.5 \cdot 10^8) / (10^8y + 1),$$

then $10^{24}(a - y^2) - 258 < 2(10^7 + 1/2)(y + 10^{-8})$, and

$$10^{24}(a - y^2) < (10^7 + 1290.5)(1 + 10^{-8}/y)(2y) < (10^7 + 1290.5)(1 + 10^{-7})(y + \sqrt{a}),$$

which finally implies $0 \leq \sqrt{a} - y < 0.2 \cdot 10^{-16}$. In particular, y is an underestimate of \sqrt{a} and $y + 0.5 \cdot 10^{-16}$ is a (strict) overestimate. There is at exactly one multiple m of $0.5 \cdot 10^{-16}$ in the interval $[y, y + 0.5 \cdot 10^{-16})$. If $m^2 > a$, then the square root is inexact and is obtained by rounding $m - \epsilon$ to a multiple of 10^{-16} (the precise shift $0 < \epsilon < 0.5 \cdot 10^{-16}$ is irrelevant for rounding). If $m^2 = a$ then the square root is exactly m , and there is no rounding. If $m^2 < a$ then we round $m + \epsilon$. For now, discard a few irrelevant arguments #1, #2, #3, and find the multiple of $0.5 \cdot 10^{-16}$ within $[y, y + 0.5 \cdot 10^{-16})$; rather, only the last 4 digits #8 of y are considered, and we do not perform any carry yet. The auxxi auxiliary sets up auxii with a continuation function auxxii instead of auxiii as before. To prevent auxii from giving a negative results $a - m^2$, we compute $a + 10^{-16} - m^2$ instead, always positive since $m < \sqrt{a} + 0.5 \cdot 10^{-16}$ and $a \leq 1 - 10^{-16}$.

```

16528 \cs_new:Npn \_fp_sqrt_auxx_o:Nnnnnnnnn #1#2#3 #4#5#6#7#8
16529 {
16530   \exp_after:wN \_fp_sqrt_auxxi_o:wwnnN
16531   \int_value:w \_fp_int_eval:w
16532     (#8 + 2499) / 5000 * 5000 ;
16533   {#4} {#5} {#6} {#7} ;
16534 }
16535 \cs_new:Npn \_fp_sqrt_auxxi_o:wwnnN #1; #2; #3#4#5
16536 {
16537   \_fp_sqrt_auxii_o:NnnnnnnnN

```

```

16538     \_fp_sqrt_auxxii_o:nnnnnnnnw
16539     #2 {#1}
16540     {#3} { #4 + 1 } #5
16541 }

```

(End definition for _fp_sqrt_auxx_o:nnnnnnnn and _fp_sqrt_auxxi_o:wnnnN.)

```

\_fp_sqrt_auxxii_o:nnnnnnnnw
\_fp_sqrt_auxxiii_o:w

```

The difference $0 \leq a + 10^{-16} - m^2 \leq 10^{-16} + (\sqrt{a} - m)(\sqrt{a} + m) \leq 2 \cdot 10^{-16}$ was just computed: its first 8 digits vanish, as do the next four, #1, and most of the following four, #2. The guess m is an overestimate if $a + 10^{-16} - m^2 < 10^{-16}$, that is, #1#2 vanishes. Otherwise it is an underestimate, unless $a + 10^{-16} - m^2 = 10^{-16}$ exactly. For an underestimate, call the auxxiv function with argument 9998. For an exact result call it with 9999, and for an overestimate call it with 10000.

```

16542 \cs_new:Npn \_fp_sqrt_auxxii_o:nnnnnnnnw 0; #1#2#3#4#5#6#7#8 #9;
16543 {
16544   \if_int_compare:w #1#2 > 0 \exp_stop_f:
16545   \if_int_compare:w #1#2 = 1 \exp_stop_f:
16546   \if_int_compare:w #3#4 = 0 \exp_stop_f:
16547   \if_int_compare:w #5#6 = 0 \exp_stop_f:
16548   \if_int_compare:w #7#8 = 0 \exp_stop_f:
16549   \_fp_sqrt_auxxiii_o:w
16550   \fi:
16551   \fi:
16552   \fi:
16553   \fi:
16554   \exp_after:wN \_fp_sqrt_auxxiv_o:wnnnnnnnN
16555   \int_value:w 9998
16556   \else:
16557   \exp_after:wN \_fp_sqrt_auxxiv_o:wnnnnnnnN
16558   \int_value:w 10000
16559   \fi:
16560   ;
16561 }
16562 \cs_new:Npn \_fp_sqrt_auxxiii_o:w \fi: \fi: \fi: \fi: #1 \fi: ;
16563 {
16564   \fi: \fi: \fi: \fi: \fi:
16565   \_fp_sqrt_auxxiv_o:wnnnnnnnN 9999 ;
16566 }

```

(End definition for _fp_sqrt_auxxii_o:nnnnnnnnw and _fp_sqrt_auxxiii_o:w.)

```

\_fp_sqrt_auxxiv_o:wnnnnnnnN

```

This receives 9998, 9999 or 10000 as #1 when m is an underestimate, exact, or an overestimate, respectively. Then comes m as five blocks of 4 digits, but where the last block #6 may be 0, 5000, or 10000. In the latter case, we need to add a carry, unless m is an overestimate (#1 is then 10000). Then comes a as three arguments. Rounding is done by _fp_round:NNN, whose first argument is the final sign 0 (square roots are positive). We fake its second argument. It should be the last digit kept, but this is only used when ties are “rounded to even”, and only when the result is exactly half-way between two representable numbers rational square roots of numbers with 16 significant digits have: this situation never arises for the square root, as any exact square root of a 16 digit number has at most 8 significant digits. Finally, the last argument is the next digit, possibly shifted by 1 when there are further nonzero digits. This is achieved by _fp_round_digit:Nw, which receives (after removal of the 10000’s digit) one of 0000, 0001, 4999, 5000, 5001, or 9999, which it converts to 0, 1, 4, 5, 6, and 9, respectively.

```

16567 \cs_new:Npn \__fp_sqrt_auxxiv_o:wnnnnnnnN #1; #2#3#4#5#6 #7#8#9
16568 {
16569   \exp_after:wN \__fp_basics_pack_high:NNNNNw
16570   \int_value:w \__fp_int_eval:w 1 0000 0000 + #2#3
16571   \exp_after:wN \__fp_basics_pack_low:NNNNNw
16572   \int_value:w \__fp_int_eval:w 1 0000 0000
16573   + #4#5
16574   \if_int_compare:w #6 > #1 \exp_stop_f: + 1 \fi:
16575   + \exp_after:wN \__fp_round:NNN
16576   \exp_after:wN 0
16577   \exp_after:wN 0
16578   \int_value:w
16579   \exp_after:wN \use_i:nn
16580   \exp_after:wN \__fp_round_digit:Nw
16581   \int_value:w \__fp_int_eval:w #6 + 19999 - #1 ;
16582   \exp_after:wN ;
16583 }

```

(End definition for __fp_sqrt_auxxiv_o:wnnnnnnnN.)

29.5 About the sign and exponent

__fp_logb_o:w The exponent of a normal number is its *exponent* minus one.

__fp_logb_aux_o:w

```

16584 \cs_new:Npn \__fp_logb_o:w ? \s__fp \__fp_chk:w #1#2; @
16585 {
16586   \if_case:w #1 \exp_stop_f:
16587     \__fp_case_use:nw
16588     { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { logb } }
16589   \or: \exp_after:wN \__fp_logb_aux_o:w
16590   \or: \__fp_case_return_o:Nw \c_inf_fp
16591   \else: \__fp_case_return_same_o:w
16592   \fi:
16593   \s__fp \__fp_chk:w #1 #2;
16594 }
16595 \cs_new:Npn \__fp_logb_aux_o:w \s__fp \__fp_chk:w #1 #2 #3 #4 ;
16596 {
16597   \exp_after:wN \__fp_parse:n \exp_after:wN
16598   { \int_value:w \int_eval:w #3 - 1 \exp_after:wN }
16599 }

```

(End definition for __fp_logb_o:w and __fp_logb_aux_o:w.)

__fp_sign_o:w Find the sign of the floating point: nan, +0, -0, +1 or -1.

__fp_sign_aux_o:w

```

16600 \cs_new:Npn \__fp_sign_o:w ? \s__fp \__fp_chk:w #1#2; @
16601 {
16602   \if_case:w #1 \exp_stop_f:
16603     \__fp_case_return_same_o:w
16604   \or: \exp_after:wN \__fp_sign_aux_o:w
16605   \or: \exp_after:wN \__fp_sign_aux_o:w
16606   \else: \__fp_case_return_same_o:w
16607   \fi:
16608   \s__fp \__fp_chk:w #1 #2;
16609 }
16610 \cs_new:Npn \__fp_sign_aux_o:w \s__fp \__fp_chk:w #1 #2 #3 ;
16611 { \exp_after:wN \__fp_set_sign_o:w \exp_after:wN #2 \c_one_fp @ }

```

(End definition for `_fp_sign_o:w` and `_fp_sign_aux_o:w`.)

`_fp_set_sign_o:w` This function is used for the unary minus and for `abs`. It leaves the sign of `nan` invariant, turns negative numbers (sign 2) to positive numbers (sign 0) and positive numbers (sign 0) to positive or negative numbers depending on #1. It also expands after itself in the input stream, just like `_fp_+_o:ww`.

```

16612 \cs_new:Npn \_fp_set_sign_o:w #1 \s\_fp \_fp_chk:w #2#3#4; @
16613 {
16614   \exp_after:wN \_fp_exp_after_o:w
16615   \exp_after:wN \s\_fp
16616   \exp_after:wN \_fp_chk:w
16617   \exp_after:wN #2
16618   \int_value:w
16619   \if_case:w #3 \exp_stop_f: #1 \or: 1 \or: 0 \fi: \exp_stop_f:
16620   #4;
16621 }

```

(End definition for `_fp_set_sign_o:w`.)

29.6 Operations on tuples

`_fp_tuple_set_sign_o:w` Two cases: `abs(<tuple>)` for which #1 is 0 (invalid for tuples) and `-<tuple>` for which #1 is 2. In that case, map over all items in the tuple an auxiliary that dispatches to the type-appropriate sign-flipping function.

`_fp_tuple_set_sign_aux_o:Nnw`
`_fp_tuple_set_sign_aux_o:w`

```

16622 \cs_new:Npn \_fp_tuple_set_sign_o:w #1
16623 {
16624   \if_meaning:w 2 #1
16625     \exp_after:wN \_fp_tuple_set_sign_aux_o:Nnw
16626     \fi:
16627     \_fp_invalid_operation_o:nw { abs }
16628   }
16629 \cs_new:Npn \_fp_tuple_set_sign_aux_o:Nnw #1#2#3 @
16630 { \_fp_tuple_map_o:nw \_fp_tuple_set_sign_o:w #3 }
16631 \cs_new:Npn \_fp_tuple_set_sign_aux_o:w #1#2 ;
16632 {
16633   \_fp_change_func_type:NNN #1 \_fp_set_sign_o:w
16634   \_fp_parse_apply_unary_error:NNw
16635   2 #1 #2 ; @
16636 }

```

(End definition for `_fp_tuple_set_sign_o:w`, `_fp_tuple_set_sign_aux_o:Nnw`, and `_fp_tuple_set_sign_aux_o:w`.)

`_fp_*_tuple_o:ww` For `<number>*<tuple>` and `<tuple>*<number>` and `<tuple>/<number>`, loop through the `<tuple>` some code that multiplies or divides by the appropriate `<number>`. Importantly we need to dispatch according to the type, and we make sure to apply the operator in the correct order.

`_fp_tuple_*_o:ww`
`_fp_tuple_/_o:ww`

```

16637 \cs_new:cpn { \_fp\_*_tuple\_o:ww } #1 ;
16638 { \_fp_tuple_map_o:nw { \_fp_binary_type_o:Nww * #1 ; } }
16639 \cs_new:cpn { \_fp\_tuple\_*_o:ww } #1 ; #2 ;
16640 { \_fp_tuple_map_o:nw { \_fp_binary_rev_type_o:Nww * #2 ; } #1 ; }
16641 \cs_new:cpn { \_fp\_tuple\_/_o:ww } #1 ; #2 ;
16642 { \_fp_tuple_map_o:nw { \_fp_binary_rev_type_o:Nww / #2 ; } #1 ; }

```

(End definition for `_fp_tuple_o:ww`, `_fp_tuple_o:ww`, and `_fp_tuple_o:ww`.)

`_fp_tuple_+_tuple_o:ww` Check the two tuples have the same number of items and map through these a helper
`_fp_tuple_-_tuple_o:ww` that dispatches appropriately depending on the types. This means $(1,2)+((1,1),2)$
gives $(\text{nan},4)$.

```

16643 \cs_set_protected:Npn \_fp_tmp:w #1
16644 {
16645   \cs_new:cpn { \_fp_tuple_#1_tuple_o:ww }
16646     \s_fp_tuple \_fp_tuple_chk:w ##1 ;
16647     \s_fp_tuple \_fp_tuple_chk:w ##2 ;
16648   {
16649     \int_compare:nNnTF
16650       { \_fp_array_count:n {##1} } = { \_fp_array_count:n {##2} }
16651       { \_fp_tuple_mapthread_o:nww { \_fp_binary_type_o:Nww #1 } }
16652       { \_fp_invalid_operation_o:nww #1 }
16653     \s_fp_tuple \_fp_tuple_chk:w {##1} ;
16654     \s_fp_tuple \_fp_tuple_chk:w {##2} ;
16655   }
16656 }
16657 \_fp_tmp:w +
16658 \_fp_tmp:w -

```

(End definition for `_fp_tuple_+_tuple_o:ww` and `_fp_tuple_-_tuple_o:ww`.)

16659 \langle /initex | package \rangle

30 13fp-extended implementation

16660 \langle *initex | package \rangle

16661 \langle @@=fp \rangle

30.1 Description of fixed point numbers

This module provides a few functions to manipulate positive floating point numbers with extended precision (24 digits), but mostly provides functions for fixed-point numbers with this precision (24 digits). Those are used in the computation of Taylor series for the logarithm, exponential, and trigonometric functions. Since we eventually only care about the 16 first digits of the final result, some of the calculations are not performed with the full 24-digit precision. In other words, the last two blocks of each fixed point number may be wrong as long as the error is small enough to be rounded away when converting back to a floating point number. The fixed point numbers are expressed as

$$\{\langle a_1 \rangle\} \{\langle a_2 \rangle\} \{\langle a_3 \rangle\} \{\langle a_4 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\} ;$$

where each $\langle a_i \rangle$ is exactly 4 digits (ranging from 0000 to 9999), except $\langle a_1 \rangle$, which may be any “not-too-large” non-negative integer, with or without leading zeros. Here, “not-too-large” depends on the specific function (see the corresponding comments for details). Checking for overflow is the responsibility of the code calling those functions. The fixed point number a corresponding to the representation above is $a = \sum_{i=1}^6 \langle a_i \rangle \cdot 10^{-4i}$.

Most functions we define here have the form

`_fp_fixed_calculation:wnn` \langle operand₁ \rangle ; \langle operand₂ \rangle ; $\{\langle$ continuation $\rangle\}$

They perform the $\langle calculation \rangle$ on the two $\langle operands \rangle$, then feed the result (6 brace groups followed by a semicolon) to the $\langle continuation \rangle$, responsible for the next step of the calculation. Some functions only accept an N-type $\langle continuation \rangle$. This allows constructions such as

```

    \__fp_fixed_add:wnn  $\langle X_1 \rangle$  ;  $\langle X_2 \rangle$  ;
    \__fp_fixed_mul:wnn  $\langle X_3 \rangle$  ;
    \__fp_fixed_add:wnn  $\langle X_4 \rangle$  ;

```

to compute $(X_1 + X_2) \cdot X_3 + X_4$. This turns out to be very appropriate for computing continued fractions and Taylor series.

At the end of the calculation, the result is turned back to a floating point number using `__fp_fixed_to_float_o:wn`. This function has to change the exponent of the floating point number: it must be used after starting an integer expression for the overall exponent of the result.

30.2 Helpers for numbers with extended precision

`\c__fp_one_fixed_tl` The fixed-point number 1, used in l3fp-expo.

```

16662 \tl_const:Nn \c__fp_one_fixed_tl
16663 { {10000} {0000} {0000} {0000} {0000} {0000} ; }

```

(End definition for `\c__fp_one_fixed_tl`.)

`__fp_fixed_continue:wn` This function simply calls the next function.

```

16664 \cs_new:Npn \__fp_fixed_continue:wn #1; #2 { #2 #1; }

```

(End definition for `__fp_fixed_continue:wn`.)

`__fp_fixed_add_one:wn` `__fp_fixed_add_one:wn $\langle a \rangle$; $\langle continuation \rangle$`

This function adds 1 to the fixed point $\langle a \rangle$, by changing a_1 to $10000 + a_1$, then calls the $\langle continuation \rangle$. This requires $a_1 + 10000 < 2^{31}$.

```

16665 \cs_new:Npn \__fp_fixed_add_one:wn #1#2; #3
16666 {
16667   \exp_after:wn #3 \exp_after:wn
16668   { \int_value:w \__fp_int_eval:w \c__fp_myriad_int + #1 } #2 ;
16669 }

```

(End definition for `__fp_fixed_add_one:wn`.)

`__fp_fixed_div_myriad:wn` Divide a fixed point number by 10000. This is a little bit more subtle than just removing the last group and adding a leading group of zeros: the first group #1 may have any number of digits, and we must split #1 into the new first group and a second group of exactly 4 digits. The choice of shifts allows #1 to be in the range $[0, 5 \cdot 10^8 - 1]$.

```

16670 \cs_new:Npn \__fp_fixed_div_myriad:wn #1#2#3#4#5#6;
16671 {
16672   \exp_after:wn \__fp_fixed_mul_after:wnn
16673   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
16674   \exp_after:wn \__fp_pack:NNNNNw
16675   \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
16676   + #1 ; {#2}{#3}{#4}{#5};
16677 }

```


(End definition for _fp_fixed_div_myriad:wn.)

_fp_fixed_mul_after:wnn The fixed point operations which involve multiplication end by calling this auxiliary. It braces the last block of digits, and places the $\langle continuation \rangle$ #3 in front.

```
16678 \cs_new:Npn \_fp_fixed_mul_after:wnn #1; #2; #3 { #3 {#1} #2; }
```

(End definition for _fp_fixed_mul_after:wnn.)

30.3 Multiplying a fixed point number by a short one

_fp_fixed_mul_short:wnn
 $\{ \langle a_1 \rangle \} \{ \langle a_2 \rangle \} \{ \langle a_3 \rangle \} \{ \langle a_4 \rangle \} \{ \langle a_5 \rangle \} \{ \langle a_6 \rangle \} ;$
 $\{ \langle b_0 \rangle \} \{ \langle b_1 \rangle \} \{ \langle b_2 \rangle \} ; \{ \langle continuation \rangle \}$

Computes the product $c = ab$ of $a = \sum_i \langle a_i \rangle 10^{-4i}$ and $b = \sum_i \langle b_i \rangle 10^{-4i}$, rounds it to the closest multiple of 10^{-24} , and leaves $\langle continuation \rangle \{ \langle c_1 \rangle \} \dots \{ \langle c_6 \rangle \}$; in the input stream, where each of the $\langle c_i \rangle$ are blocks of 4 digits, except $\langle c_1 \rangle$, which is any TeX integer. Note that indices for $\langle b \rangle$ start at 0: for instance a second operand of {0001}{0000}{0000} leaves the first operand unchanged (rather than dividing it by 10^4 , as _fp_fixed_mul:wnn would).

```
16679 \cs_new:Npn \_fp_fixed_mul_short:wnn #1#2#3#4#5#6; #7#8#9;
16680 {
16681   \exp_after:wN \_fp_fixed_mul_after:wnn
16682   \int_value:w \_fp_int_eval:w \c__fp_leading_shift_int
16683   + #1*#7
16684   \exp_after:wN \_fp_pack:NNNNNw
16685   \int_value:w \_fp_int_eval:w \c__fp_middle_shift_int
16686   + #1*#8 + #2*#7
16687   \exp_after:wN \_fp_pack:NNNNNw
16688   \int_value:w \_fp_int_eval:w \c__fp_middle_shift_int
16689   + #1*#9 + #2*#8 + #3*#7
16690   \exp_after:wN \_fp_pack:NNNNNw
16691   \int_value:w \_fp_int_eval:w \c__fp_middle_shift_int
16692   + #2*#9 + #3*#8 + #4*#7
16693   \exp_after:wN \_fp_pack:NNNNNw
16694   \int_value:w \_fp_int_eval:w \c__fp_middle_shift_int
16695   + #3*#9 + #4*#8 + #5*#7
16696   \exp_after:wN \_fp_pack:NNNNNw
16697   \int_value:w \_fp_int_eval:w \c__fp_trailing_shift_int
16698   + #4*#9 + #5*#8 + #6*#7
16699   + ( #5*#9 + #6*#8 + #6*#9 / \c__fp_myriad_int )
16700   / \c__fp_myriad_int ; ;
16701 }
```

(End definition for _fp_fixed_mul_short:wnn.)

30.4 Dividing a fixed point number by a small integer

_fp_fixed_div_int:wnN _fp_fixed_div_int:wnN $\langle a \rangle ; \langle n \rangle ; \langle continuation \rangle$

Divides the fixed point number $\langle a \rangle$ by the (small) integer $0 < \langle n \rangle < 10^4$ and feeds the result to the $\langle continuation \rangle$. There is no bound on a_1 .

The arguments of the i auxiliary are 1: one of the a_i , 2: n , 3: the ii or the iii auxiliary. It computes a (somewhat tight) lower bound Q_i for the ratio a_i/n .

The `ii` auxiliary receives Q_i , n , and a_i as arguments. It adds Q_i to a surrounding integer expression, and starts a new one with the initial value 9999, which ensures that the result of this expression has 5 digits. The auxiliary also computes $a_i - n \cdot Q_i$, placing the result in front of the 4 digits of a_{i+1} . The resulting $a'_{i+1} = 10^4(a_i - n \cdot Q_i) + a_{i+1}$ serves as the first argument for a new call to the `i` auxiliary.

When the `iii` auxiliary is called, the situation looks like this:

```

\__fp_fixed_div_int_after:Nw <continuation>
-1 + Q_1
\__fp_fixed_div_int_pack:Nw 9999 + Q_2
\__fp_fixed_div_int_pack:Nw 9999 + Q_3
\__fp_fixed_div_int_pack:Nw 9999 + Q_4
\__fp_fixed_div_int_pack:Nw 9999 + Q_5
\__fp_fixed_div_int_pack:Nw 9999
\__fp_fixed_div_int_auxii:wnn Q_6 ; {\langle n \rangle} {\langle a_6 \rangle}

```

where expansion is happening from the last line up. The `iii` auxiliary adds $Q_6 + 2 \simeq a_6/n + 1$ to the last 9999, giving the integer closest to $10000 + a_6/n$.

Each `pack` auxiliary receives 5 digits followed by a semicolon. The first digit is added as a carry to the integer expression above, and the 4 other digits are braced. Each call to the `pack` auxiliary thus produces one brace group. The last brace group is produced by the `after` auxiliary, which places the $\langle continuation \rangle$ as appropriate.

```

16702 \cs_new:Npn \__fp_fixed_div_int:wN #1#2#3#4#5#6 ; #7 ; #8
16703 {
16704   \exp_after:wN \__fp_fixed_div_int_after:Nw
16705   \exp_after:wN #8
16706   \int_value:w \__fp_int_eval:w - 1
16707   \__fp_fixed_div_int:wN
16708   #1; {\#7} \__fp_fixed_div_int_auxi:wnn
16709   #2; {\#7} \__fp_fixed_div_int_auxi:wnn
16710   #3; {\#7} \__fp_fixed_div_int_auxi:wnn
16711   #4; {\#7} \__fp_fixed_div_int_auxi:wnn
16712   #5; {\#7} \__fp_fixed_div_int_auxi:wnn
16713   #6; {\#7} \__fp_fixed_div_int_auxii:wnn ;
16714 }
16715 \cs_new:Npn \__fp_fixed_div_int:wN #1; #2 #3
16716 {
16717   \exp_after:wN #3
16718   \int_value:w \__fp_int_eval:w #1 / #2 - 1 ;
16719   {\#2}
16720   {\#1}
16721 }
16722 \cs_new:Npn \__fp_fixed_div_int_auxi:wnn #1; #2 #3
16723 {
16724   + #1
16725   \exp_after:wN \__fp_fixed_div_int_pack:Nw
16726   \int_value:w \__fp_int_eval:w 9999
16727   \exp_after:wN \__fp_fixed_div_int:wN
16728   \int_value:w \__fp_int_eval:w #3 - #1*#2 \__fp_int_eval_end:
16729 }
16730 \cs_new:Npn \__fp_fixed_div_int_auxii:wnn #1; #2 #3 { + #1 + 2 ; }
16731 \cs_new:Npn \__fp_fixed_div_int_pack:Nw #1 #2; { + #1; {\#2} }
16732 \cs_new:Npn \__fp_fixed_div_int_after:Nw #1 #2; { #1 {\#2} }

```

(End definition for `_fp_fixed_div_int:wwN` and others.)

30.5 Adding and subtracting fixed points

`_fp_fixed_add:wwn`
`_fp_fixed_sub:wwn`
`_fp_fixed_add:Nnnnnwnn`
`_fp_fixed_add:nnNnnwnn`
`_fp_fixed_add_pack:NNNNNwn`
`_fp_fixed_add_after:NNNNNwn`

`_fp_fixed_add:wwn` $\langle a \rangle$; $\langle b \rangle$; $\{\langle continuation \rangle\}$

Computes $a + b$ (resp. $a - b$) and feeds the result to the $\langle continuation \rangle$. This function requires $0 \leq a_1, b_1 \leq 114748$, its result must be positive (this happens automatically for addition) and its first group must have at most 5 digits: $(a \pm b)_1 < 100000$. The two functions only differ by a sign, hence use a common auxiliary. It would be nice to grab the 12 brace groups in one go; only 9 parameters are allowed. Start by grabbing the sign, a_1, \dots, a_4 , the rest of a , and b_1 and b_2 . The second auxiliary receives the rest of a , the sign multiplying b , the rest of b , and the $\langle continuation \rangle$ as arguments. After going down through the various level, we go back up, packing digits and bringing the $\langle continuation \rangle$ (#8, then #7) from the end of the argument list to its start.

```

16733 \cs_new:Npn \_fp_fixed_add:wwn { \_fp_fixed_add:Nnnnnwnn + }
16734 \cs_new:Npn \_fp_fixed_sub:wwn { \_fp_fixed_add:Nnnnnwnn - }
16735 \cs_new:Npn \_fp_fixed_add:Nnnnnwnn #1 #2#3#4#5 #6; #7#8
16736 {
16737   \exp_after:wN \_fp_fixed_add_after:NNNNNwn
16738   \int_value:w \_fp_int_eval:w 9 9999 9998 + #2#3 #1 #7#8
16739   \exp_after:wN \_fp_fixed_add_pack:NNNNNwn
16740   \int_value:w \_fp_int_eval:w 1 9999 9998 + #4#5
16741   \_fp_fixed_add:nnNnnwn #6 #1
16742 }
16743 \cs_new:Npn \_fp_fixed_add:nnNnnwn #1#2 #3 #4#5 #6#7 ; #8
16744 {
16745   #3 #4#5
16746   \exp_after:wN \_fp_fixed_add_pack:NNNNNwn
16747   \int_value:w \_fp_int_eval:w 2 0000 0000 #3 #6#7 + #1#2 ; {#8} ;
16748 }
16749 \cs_new:Npn \_fp_fixed_add_pack:NNNNNwn #1 #2#3#4#5 #6; #7
16750 { + #1 ; {#7} {#2#3#4#5} {#6} }
16751 \cs_new:Npn \_fp_fixed_add_after:NNNNNwn 1 #1 #2#3#4#5 #6; #7
16752 { #7 {#1#2#3#4#5} {#6} }
```

(End definition for `_fp_fixed_add:wwn` and others.)

30.6 Multiplying fixed points

`_fp_fixed_mul:wwn`
`_fp_fixed_mul:nnnnnnnw`

`_fp_fixed_mul:wwn` $\langle a \rangle$; $\langle b \rangle$; $\{\langle continuation \rangle\}$

Computes $a \times b$ and feeds the result to $\langle continuation \rangle$. This function requires $0 \leq a_1, b_1 < 10000$. Once more, we need to play around the limit of 9 arguments for \TeX macros. Note that we don't need to obtain an exact rounding, contrarily to the $*$ operator,

so things could be harder. We wish to perform carries in

$$\begin{aligned}
a \times b = & a_1 \cdot b_1 \cdot 10^{-8} \\
& + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
& + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1) \cdot 10^{-16} \\
& + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
& + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
& \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
& \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 \right) \cdot 10^{-24} + O(10^{-24}),
\end{aligned}$$

where the $O(10^{-24})$ stands for terms which are at most $5 \cdot 10^{-24}$; ignoring those leads to an error of at most 5 ulp. Note how the first 15 terms only depend on a_1, \dots, a_4 and b_1, \dots, b_4 , while the last 6 terms only depend on a_1, a_2, a_5, a_6 , and the corresponding parts of b . Hence, the first function grabs a_1, \dots, a_4 , the rest of a , and b_1, \dots, b_4 , and writes the 15 first terms of the expression, including a left parenthesis for the fraction. The `i` auxiliary receives $a_5, a_6, b_1, b_2, a_1, a_2, b_5, b_6$ and finally the $\langle continuation \rangle$ as arguments. It writes the end of the expression, including the right parenthesis and the denominator of the fraction. The $\langle continuation \rangle$ is finally placed in front of the 6 brace groups by `__fp_fixed_mul_after:wnn`.

```

16753 \cs_new:Npn \__fp_fixed_mul:wnn #1#2#3#4 #5; #6#7#8#9
16754 {
16755   \exp_after:wN \__fp_fixed_mul_after:wnn
16756   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
16757   \exp_after:wN \__fp_pack:NNNNNw
16758   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
16759   + #1*#6
16760   \exp_after:wN \__fp_pack:NNNNNw
16761   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
16762   + #1*#7 + #2*#6
16763   \exp_after:wN \__fp_pack:NNNNNw
16764   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
16765   + #1*#8 + #2*#7 + #3*#6
16766   \exp_after:wN \__fp_pack:NNNNNw
16767   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
16768   + #1*#9 + #2*#8 + #3*#7 + #4*#6
16769   \exp_after:wN \__fp_pack:NNNNNw
16770   \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
16771   + #2*#9 + #3*#8 + #4*#7
16772   + ( #3*#9 + #4*#8
16773     + \__fp_fixed_mul:nnnnnnnw #5 {#6}{#7} {#1}{#2}
16774   )
16775 \cs_new:Npn \__fp_fixed_mul:nnnnnnnw #1#2 #3#4 #5#6 #7#8 ;
16776 {
16777   #1*#4 + #2*#3 + #5*#8 + #6*#7 ) / \c__fp_myriad_int
16778   + #1*#3 + #5*#7 ; ;
16779 }

```

(End definition for `__fp_fixed_mul:wnn` and `__fp_fixed_mul:nnnnnnnw`.)

30.7 Combining product and sum of fixed points

```

\__fp_fixed_mul_add:wwwn
\__fp_fixed_mul_sub_back:wwwn
\__fp_fixed_one_minus_mul:wwn
\__fp_fixed_mul_one_minus_mul:wwn

```

Sometimes called FMA (fused multiply-add), these functions compute $a \times b + c$, $c - a \times b$, and $1 - a \times b$ and feed the result to the $\langle continuation \rangle$. Those functions require $0 \leq a_1, b_1, c_1 \leq 10000$. Since those functions are at the heart of the computation of Taylor expansions, we over-optimize them a bit, and in particular we do not factor out the common parts of the three functions.

For definiteness, consider the task of computing $a \times b + c$. We perform carries in

$$\begin{aligned}
 a \times b + c = & (a_1 \cdot b_1 + c_1 c_2) \cdot 10^{-8} \\
 & + (a_1 \cdot b_2 + a_2 \cdot b_1) \cdot 10^{-12} \\
 & + (a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4) \cdot 10^{-16} \\
 & + (a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1) \cdot 10^{-20} \\
 & + \left(a_2 \cdot b_4 + a_3 \cdot b_3 + a_4 \cdot b_2 \right. \\
 & \quad \left. + \frac{a_3 \cdot b_4 + a_4 \cdot b_3 + a_1 \cdot b_6 + a_2 \cdot b_5 + a_5 \cdot b_2 + a_6 \cdot b_1}{10^4} \right. \\
 & \quad \left. + a_1 \cdot b_5 + a_5 \cdot b_1 + c_5 c_6 \right) \cdot 10^{-24} + O(10^{-24}),
 \end{aligned}$$

where $c_1 c_2$, $c_3 c_4$, $c_5 c_6$ denote the 8-digit number obtained by juxtaposing the two blocks of digits of c , and \cdot denotes multiplication. The task is obviously tough because we have 18 brace groups in front of us.

Each of the three function starts the first two levels (the first, corresponding to 10^{-4} , is empty), with $c_1 c_2$ in the first level, calls the `i` auxiliary with arguments described later, and adds a trailing $+ c_5 c_6 ; \{ \langle continuation \rangle \} ;$. The $+ c_5 c_6$ piece, which is omitted for `__fp_fixed_one_minus_mul:wwn`, is taken in the integer expression for the 10^{-24} level.

```

16780 \cs_new:Npn \__fp_fixed_mul_add:wwwn #1; #2; #3#4#5#6#7#8;
16781 {
16782   \exp_after:wN \__fp_fixed_mul_after:wwwn
16783   \int_value:w \__fp_int_eval:w \c__fp_big_leading_shift_int
16784   \exp_after:wN \__fp_pack_big:NNNNNNw
16785   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int + #3 #4
16786   \__fp_fixed_mul_add:Nwnnnwnnn +
16787     + #5 #6 ; #2 ; #1 ; #2 ; +
16788     + #7 #8 ; ;
16789 }
16790 \cs_new:Npn \__fp_fixed_mul_sub_back:wwwn #1; #2; #3#4#5#6#7#8;
16791 {
16792   \exp_after:wN \__fp_fixed_mul_after:wwwn
16793   \int_value:w \__fp_int_eval:w \c__fp_big_leading_shift_int
16794   \exp_after:wN \__fp_pack_big:NNNNNNw
16795   \int_value:w \__fp_int_eval:w \c__fp_big_middle_shift_int + #3 #4
16796   \__fp_fixed_mul_add:Nwnnnwnnn -
16797     + #5 #6 ; #2 ; #1 ; #2 ; -
16798     + #7 #8 ; ;
16799 }
16800 \cs_new:Npn \__fp_fixed_one_minus_mul:wwn #1; #2;
16801 {

```

```

16802 \exp_after:wN \_fp_fixed_mul_after:wwn
16803 \int_value:w \_fp_int_eval:w \c\_fp_big_leading_shift_int
16804 \exp_after:wN \_fp_pack_big:NNNNNNw
16805 \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int +
16806 1 0000 0000
16807 \_fp_fixed_mul_add:Nwnnnwnnn -
16808 ; #2 ; #1 ; #2 ; -
16809 ; ;
16810 }

```

(End definition for `_fp_fixed_mul_add:wwn`, `_fp_fixed_mul_sub_back:wwn`, and `_fp_fixed_mul_one_minus_mul:wnn`.)

```

\_fp_fixed_mul_add:Nwnnnwnnn \_fp_fixed_mul_add:Nwnnnwnnn <op> + <c3> <c4> ;
<b> ; <a> ; <b> ; <op>
+ <c5> <c6> ;

```

Here, $\langle op \rangle$ is either + or -. Arguments #3, #4, #5 are $\langle b_1 \rangle$, $\langle b_2 \rangle$, $\langle b_3 \rangle$; arguments #7, #8, #9 are $\langle a_1 \rangle$, $\langle a_2 \rangle$, $\langle a_3 \rangle$. We can build three levels: $a_1 \cdot b_1$ for 10^{-8} , $(a_1 \cdot b_2 + a_2 \cdot b_1)$ for 10^{-12} , and $(a_1 \cdot b_3 + a_2 \cdot b_2 + a_3 \cdot b_1 + c_3 c_4)$ for 10^{-16} . The a - b products use the sign #1. Note that #2 is empty for `_fp_fixed_one_minus_mul:wnn`. We call the *ii* auxiliary for levels 10^{-20} and 10^{-24} , keeping the pieces of $\langle a \rangle$ we've read, but not $\langle b \rangle$, since there is another copy later in the input stream.

```

16811 \cs_new:Npn \_fp_fixed_mul_add:Nwnnnwnnn #1 #2; #3#4#5#6; #7#8#9
16812 {
16813   #1 #7*#3
16814   \exp_after:wN \_fp_pack_big:NNNNNNw
16815   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int
16816   #1 #7*#4 #1 #8*#3
16817   \exp_after:wN \_fp_pack_big:NNNNNNw
16818   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int
16819   #1 #7*#5 #1 #8*#4 #1 #9*#3 #2
16820   \exp_after:wN \_fp_pack_big:NNNNNNw
16821   \int_value:w \_fp_int_eval:w \c\_fp_big_middle_shift_int
16822   #1 \_fp_fixed_mul_add:nnnnwnnnn {#7}{#8}{#9}
16823 }

```

(End definition for `_fp_fixed_mul_add:Nwnnnwnnn`.)

```

\_fp_fixed_mul_add:nnnnwnnnn \_fp_fixed_mul_add:nnnnwnnnn <a> ; <b> ; <op>
+ <c5> <c6> ;

```

Level 10^{-20} is $(a_1 \cdot b_4 + a_2 \cdot b_3 + a_3 \cdot b_2 + a_4 \cdot b_1)$, multiplied by the sign, which was inserted by the *i* auxiliary. Then we prepare level 10^{-24} . We don't have access to all parts of $\langle a \rangle$ and $\langle b \rangle$ needed to make all products. Instead, we prepare the partial expressions

$$b_1 + a_4 \cdot b_2 + a_3 \cdot b_3 + a_2 \cdot b_4 + a_1$$

$$b_2 + a_4 \cdot b_3 + a_3 \cdot b_4 + a_2.$$

Obviously, those expressions make no mathematical sense: we complete them with $a_5 \cdot$ and $\cdot b_5$, and with $a_6 \cdot b_1 + a_5 \cdot$ and $\cdot b_5 + a_1 \cdot b_6$, and of course with the trailing $+ c_5 c_6$. To do all this, we keep a_1 , a_5 , a_6 , and the corresponding pieces of $\langle b \rangle$.

```

16824 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnnn #1#2#3#4#5; #6#7#8#9
16825 {

```

```

16826      ( #1*#9 + #2*#8 + #3*#7 + #4*#6 )
16827      \exp_after:wN \_fp_pack_big:NNNNNNw
16828      \int_value:w \_fp_int_eval:w \c\_fp_big_trailing_shift_int
16829      \_fp_fixed_mul_add:nnnnwnnwN
16830      { #6 + #4*#7 + #3*#8 + #2*#9 + #1 }
16831      { #7 + #4*#8 + #3*#9 + #2 }
16832      {#1} #5;
16833      {#6}
16834  }

```

(End definition for _fp_fixed_mul_add:nnnnwnnwN.)

```

\_fp_fixed_mul_add:nnnnwnnwN {<partial1>} {<partial2>}
{<a1>} {<a5>} {<a6>} ; {<b1>} {<b5>} {<b6>} ;
<op> + <c5> <c6> ;

```

Complete the $\langle partial_1 \rangle$ and $\langle partial_2 \rangle$ expressions as explained for the `ii` auxiliary. The second one is divided by 10000: this is the carry from level 10^{-28} . The trailing $+ c_5 c_6$ is taken into the expression for level 10^{-24} . Note that the total of level 10^{-24} is in the interval $[-5 \cdot 10^8, 6 \cdot 10^8]$ (give or take a couple of 10000), hence adding it to the shift gives a 10-digit number, as expected by the packing auxiliaries. See `l3fp-aux` for the definition of the shifts and packing auxiliaries.

```

16835 \cs_new:Npn \_fp_fixed_mul_add:nnnnwnnwN #1#2 #3#4#5; #6#7#8; #9
16836 {
16837   #9 (#4* #1 *#7)
16838   #9 (#5*#6+#4* #2 *#7+#3*#8) / \c\_fp_myriad_int
16839 }

```

(End definition for _fp_fixed_mul_add:nnnnwnnwN.)

30.8 Extended-precision floating point numbers

In this section we manipulate floating point numbers with roughly 24 significant figures (“extended-precision” numbers, in short, “ep”), which take the form of an integer exponent, followed by a comma, then six groups of digits, ending with a semicolon. The first group of digit may be any non-negative integer, while other groups of digits have 4 digits. In other words, an extended-precision number is an exponent ending in a comma, then a fixed point number. The corresponding value is $0.\langle digits \rangle \cdot 10^{\langle exponent \rangle}$. This convention differs from floating points.

`_fp_ep_to_fixed:wwn` Converts an extended-precision number with an exponent at most 4 and a first block less than 10^8 to a fixed point number whose first block has 12 digits, hopefully starting with many zeros.

```

16840 \cs_new:Npn \_fp_ep_to_fixed:wwn #1,#2
16841 {
16842   \exp_after:wN \_fp_ep_to_fixed_auxi:www
16843   \int_value:w \_fp_int_eval:w 1 0000 0000 + #2 \exp_after:wN ;
16844   \exp:w \exp_end_continue_f:w
16845   \prg_replicate:nn { 4 - \int_max:nn {#1} { -32 } } { 0 } ;
16846 }
16847 \cs_new:Npn \_fp_ep_to_fixed_auxi:www 1#1; #2; #3#4#5#6#7;
16848 {
16849   \_fp_pack_eight:wNNNNNNNN
16850   \_fp_pack_twice_four:wNNNNNNNN

```

```

16851     \__fp_pack_twice_four:wNNNNNNNN
16852     \__fp_pack_twice_four:wNNNNNNNN
16853     \__fp_ep_to_fixed_auxii:nnnnnnwn ;
16854     #2 #1#3#4#5#6#7 0000 !
16855 }
16856 \cs_new:Npn \__fp_ep_to_fixed_auxii:nnnnnnwn #1#2#3#4#5#6#7; #8! #9
16857 { #9 {#1#2}{#3}{#4}{#5}{#6}{#7}; }

```

(End definition for __fp_ep_to_fixed:wwn, __fp_ep_to_fixed_auxi:www, and __fp_ep_to_fixed_auxii:nnnnnnwn.)

```

\__fp_ep_to_ep:wwN
\__fp_ep_to_ep_loop:N
\__fp_ep_to_ep_end:www
\__fp_ep_to_ep_zero:ww

```

Normalize an extended-precision number. More precisely, leading zeros are removed from the mantissa of the argument, decreasing its exponent as appropriate. Then the digits are packed into 6 groups of 4 (discarding any remaining digit, not rounding). Finally, the continuation #8 is placed before the resulting exponent-mantissa pair. The input exponent may in fact be given as an integer expression. The `loop` auxiliary grabs a digit: if it is 0, decrement the exponent and continue looping, and otherwise call the `end` auxiliary, which places all digits in the right order (the digit that was not 0, and any remaining digits), followed by some 0, then packs them up neatly in $3 \times 2 = 6$ blocks of four. At the end of the day, remove with `__fp_use_i:ww` any digit that did not make it in the final mantissa (typically only zeros, unless the original first block has more than 4 digits).

```

16858 \cs_new:Npn \__fp_ep_to_ep:wwN #1,#2#3#4#5#6#7; #8
16859 {
16860     \exp_after:wN #8
16861     \int_value:w \__fp_int_eval:w #1 + 4
16862     \exp_after:wN \use_i:nn
16863     \exp_after:wN \__fp_ep_to_ep_loop:N
16864     \int_value:w \__fp_int_eval:w 1 0000 0000 + #2 \__fp_int_eval_end:
16865     #3#4#5#6#7 ; ; !
16866 }
16867 \cs_new:Npn \__fp_ep_to_ep_loop:N #1
16868 {
16869     \if_meaning:w 0 #1
16870     - 1
16871     \else:
16872         \__fp_ep_to_ep_end:www #1
16873     \fi:
16874     \__fp_ep_to_ep_loop:N
16875 }
16876 \cs_new:Npn \__fp_ep_to_ep_end:www
16877 #1 \fi: \__fp_ep_to_ep_loop:N #2; #3!
16878 {
16879     \fi:
16880     \if_meaning:w ; #1
16881     - 2 * \c__fp_max_exponent_int
16882     \__fp_ep_to_ep_zero:ww
16883     \fi:
16884     \__fp_pack_twice_four:wNNNNNNNN
16885     \__fp_pack_twice_four:wNNNNNNNN
16886     \__fp_pack_twice_four:wNNNNNNNN
16887     \__fp_use_i:ww , ;
16888     #1 #2 0000 0000 0000 0000 0000 0000 ;
16889 }

```



```

16890 \cs_new:Npn \__fp_ep_to_ep_zero:ww \fi: #1; #2; #3;
16891 { \fi: , {1000}{0000}{0000}{0000}{0000}{0000} ; }

```

(End definition for __fp_ep_to_ep:wwN and others.)

```

\__fp_ep_compare:www
\__fp_ep_compare_aux:www

```

In l3fp-trig we need to compare two extended-precision numbers. This is based on the same function for positive floating point numbers, with an extra test if comparing only 16 decimals is not enough to distinguish the numbers. Note that this function only works if the numbers are normalized so that their first block is in [1000,9999].

```

16892 \cs_new:Npn \__fp_ep_compare:www #1,#2#3#4#5#6#7;
16893 { \__fp_ep_compare_aux:www {#1}{#2}{#3}{#4}{#5}; #6#7; }
16894 \cs_new:Npn \__fp_ep_compare_aux:www #1;#2;#3,#4#5#6#7#8#9;
16895 {
16896   \if_case:w
16897     \__fp_compare_npos:nwnw #1; {#3}{#4}{#5}{#6}{#7}; \exp_stop_f:
16898     \if_int_compare:w #2 = #8#9 \exp_stop_f:
16899       0
16900     \else:
16901       \if_int_compare:w #2 < #8#9 - \fi: 1
16902     \fi:
16903   \or:    1
16904   \else: -1
16905   \fi:
16906 }

```

(End definition for __fp_ep_compare:www and __fp_ep_compare_aux:www.)

```

\__fp_ep_mul:wwwN
\__fp_ep_mul_raw:wwwN

```

Multiply two extended-precision numbers: first normalize them to avoid losing too much precision, then multiply the mantissas #2 and #4 as fixed point numbers, and sum the exponents #1 and #3. The result's first block is in [100,9999].

```

16907 \cs_new:Npn \__fp_ep_mul:wwwN #1,#2; #3,#4;
16908 {
16909   \__fp_ep_to_ep:wwN #3,#4;
16910   \__fp_fixed_continue:wn
16911   {
16912     \__fp_ep_to_ep:wwN #1,#2;
16913     \__fp_ep_mul_raw:wwwN
16914   }
16915   \__fp_fixed_continue:wn
16916 }
16917 \cs_new:Npn \__fp_ep_mul_raw:wwwN #1,#2; #3,#4; #5
16918 {
16919   \__fp_fixed_mul:wn #2; #4;
16920   { \exp_after:wN #5 \int_value:w \__fp_int_eval:w #1 + #3 , }
16921 }

```

(End definition for __fp_ep_mul:wwwN and __fp_ep_mul_raw:wwwN.)

30.9 Dividing extended-precision numbers

Divisions of extended-precision numbers are difficult to perform with exact rounding: the technique used in l3fp-basics for 16-digit floating point numbers does not generalize easily to 24-digit numbers. Thankfully, there is no need for exact rounding.

Let us call $\langle n \rangle$ the numerator and $\langle d \rangle$ the denominator. After a simple normalization step, we can assume that $\langle n \rangle \in [0.1, 1)$ and $\langle d \rangle \in [0.1, 1)$, and compute $\langle n \rangle / (10 \langle d \rangle) \in (0.01, 1)$. In terms of the 6 blocks of digits $\langle n_1 \rangle \cdots \langle n_6 \rangle$ and the 6 blocks $\langle d_1 \rangle \cdots \langle d_6 \rangle$, the condition translates to $\langle n_1 \rangle, \langle d_1 \rangle \in [1000, 9999]$.

We first find an integer estimate $a \simeq 10^8 / \langle d \rangle$ by computing

$$\begin{aligned}\alpha &= \left\lfloor \frac{10^9}{\langle d_1 \rangle + 1} \right\rfloor \\ \beta &= \left\lfloor \frac{10^9}{\langle d_1 \rangle} \right\rfloor \\ a &= 10^3 \alpha + (\beta - \alpha) \cdot \left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) - 1250,\end{aligned}$$

where $\left\lfloor \frac{\cdot}{\cdot} \right\rfloor$ denotes ε -TEX's rounding division, which rounds ties away from zero. The idea is to interpolate between $10^3 \alpha$ and $10^3 \beta$ with a parameter $\langle d_2 \rangle / 10^4$, so that when $\langle d_2 \rangle = 0$ one gets $a = 10^3 \beta - 1250 \simeq 10^{12} / \langle d_1 \rangle \simeq 10^8 / \langle d \rangle$, while when $\langle d_2 \rangle = 9999$ one gets $a = 10^3 \alpha - 1250 \simeq 10^{12} / (\langle d_1 \rangle + 1) \simeq 10^8 / \langle d \rangle$. The shift by 1250 helps to ensure that a is an underestimate of the correct value. We shall prove that

$$1 - 1.755 \cdot 10^{-5} < \frac{\langle d \rangle a}{10^8} < 1.$$

We can then compute the inverse of $\langle d \rangle a / 10^8 = 1 - \epsilon$ using the relation $1 / (1 - \epsilon) \simeq (1 + \epsilon)(1 + \epsilon^2) + \epsilon^4$, which is correct up to a relative error of $\epsilon^5 < 1.6 \cdot 10^{-24}$. This allows us to find the desired ratio as

$$\frac{\langle n \rangle}{\langle d \rangle} = \frac{\langle n \rangle a}{10^8} ((1 + \epsilon)(1 + \epsilon^2) + \epsilon^4).$$

Let us prove the upper bound first (multiplied by 10^{15}). Note that $10^7 \langle d \rangle < 10^3 \langle d_1 \rangle + 10^{-1}(\langle d_2 \rangle + 1)$, and that ε -TEX's division $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$ underestimates $10^{-1}(\langle d_2 \rangle + 1)$ by 0.5 at most, as can be checked for each possible last digit of $\langle d_2 \rangle$. Then,

$$10^7 \langle d \rangle a < \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \left(\left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) \beta + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \alpha - 1250 \right) \quad (1)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \quad (2)$$

$$\left(\left(10^3 - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \right) \left(\frac{10^9}{\langle d_1 \rangle} + \frac{1}{2} \right) + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \left(\frac{10^9}{\langle d_1 \rangle + 1} + \frac{1}{2} \right) - 1250 \right) \quad (3)$$

$$< \left(10^3 \langle d_1 \rangle + \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 750 \right) \quad (4)$$

We recognize a quadratic polynomial in $\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor$ with a negative leading coefficient: this polynomial is bounded above, according to $(\left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor + a)(b - c \left\lfloor \frac{\langle d_2 \rangle}{10} \right\rfloor) \leq (b + ca)^2 / (4c)$. Hence,

$$10^7 \langle d \rangle a < \frac{10^{15}}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} \left(\langle d_1 \rangle + \frac{1}{2} + \frac{1}{4} 10^{-3} - \frac{3}{8} \cdot 10^{-9} \langle d_1 \rangle (\langle d_1 \rangle + 1) \right)^2$$

Since $\langle d_1 \rangle$ takes integer values within $[1000, 9999]$, it is a simple programming exercise to check that the squared expression is always less than $\langle d_1 \rangle (\langle d_1 \rangle + 1)$, hence $10^7 \langle d \rangle a < 10^{15}$.

The upper bound is proven. We also find that $\frac{3}{8}$ can be replaced by slightly smaller numbers, but nothing less than $0.374563\dots$, and going back through the derivation of the upper bound, we find that 1250 is as small a shift as we can obtain without breaking the bound.

Now, the lower bound. The same computation as for the upper bound implies

$$10^7 \langle d \rangle a > \left(10^3 \langle d_1 \rangle + \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil - \frac{1}{2} \right) \left(\frac{10^{12}}{\langle d_1 \rangle} - \left\lceil \frac{\langle d_2 \rangle}{10} \right\rceil \frac{10^9}{\langle d_1 \rangle (\langle d_1 \rangle + 1)} - 1750 \right)$$

This time, we want to find the minimum of this quadratic polynomial. Since the leading coefficient is still negative, the minimum is reached for one of the extreme values $[y/10] = 0$ or $[y/10] = 100$, and we easily check the bound for those values.

We have proven that the algorithm gives us a precise enough answer. Incidentally, the upper bound that we derived tells us that $a < 10^8 / \langle d \rangle \leq 10^9$, hence we can compute a safely as a $\text{T}_{\text{E}}\text{X}$ integer, and even add 10^9 to it to ease grabbing of all the digits. The lower bound implies $10^8 - 1755 < a$, which we do not care about.

`__fp_ep_div:wwwn` Compute the ratio of two extended-precision numbers. The result is an extended-precision number whose first block lies in the range $[100, 9999]$, and is placed after the $\langle continuation \rangle$ once we are done. First normalize the inputs so that both first block lie in $[1000, 9999]$, then call `__fp_ep_div_esti:wwwn` $\langle denominator \rangle$ $\langle numerator \rangle$, responsible for estimating the inverse of the denominator.

```

16922 \cs_new:Npn \__fp_ep_div:wwwn #1,#2; #3,#4;
16923 {
16924   \__fp_ep_to_ep:wwN #1,#2;
16925   \__fp_fixed_continue:wn
16926   {
16927     \__fp_ep_to_ep:wwN #3,#4;
16928     \__fp_ep_div_esti:wwwn
16929   }
16930 }
```

(End definition for `__fp_ep_div:wwwn`.)

`__fp_ep_div_esti:wwwn` The `esti` function evaluates $\alpha = 10^9 / (\langle d_1 \rangle + 1)$, which is used twice in the expression for a , and combines the exponents `#1` and `#4` (with a shift by 1 because we later compute $\langle n \rangle / (10 \langle d \rangle)$). Then the `estii` function evaluates $10^9 + a$, and puts the exponent `#2` after the continuation `#7`: from there on we can forget exponents and focus on the mantissa. The `estiii` function multiplies the denominator `#7` by $10^{-8}a$ (obtained as a split into the single digit `#1` and two blocks of 4 digits, `#2#3#4#5` and `#6`). The result $10^{-8}a \langle d \rangle = (1 - \epsilon)$, and a partially packed $10^{-9}a$ (as a block of four digits, and five individual digits, not packed by lack of available macro parameters here) are passed to `__fp_ep_div_epsilon:wnNNNNn`, which computes $10^{-9}a / (1 - \epsilon)$, that is, $1 / (10 \langle d \rangle)$ and we finally multiply this by the numerator `#8`.

```

16931 \cs_new:Npn \__fp_ep_div_esti:wwwn #1,#2#3; #4,
16932 {
16933   \exp_after:wN \__fp_ep_div_estii:wwnnwn
16934   \int_value:w \__fp_int_eval:w 10 0000 0000 / ( #2 + 1 )
16935   \exp_after:wN ;
16936   \int_value:w \__fp_int_eval:w #4 - #1 + 1 ,
16937   {#2} #3;
16938 }
```

```

16939 \cs_new:Npn \__fp_ep_div_estii:wnnnwnn #1; #2,#3#4#5; #6; #7
16940 {
16941   \exp_after:wN \__fp_ep_div_estiii:NNNNNwwwn
16942   \int_value:w \__fp_int_eval:w 10 0000 0000 - 1750
16943   + #1 000 + (10 0000 0000 / #3 - #1) * (1000 - #4 / 10) ;
16944   {#3}{#4}#5; #6; { #7 #2, }
16945 }
16946 \cs_new:Npn \__fp_ep_div_estiii:NNNNNwwwn 1#1#2#3#4#5#6; #7;
16947 {
16948   \__fp_fixed_mul_short:wnn #7; {#1}{#2#3#4#5}{#6};
16949   \__fp_ep_div_epsilon:wnNNNNNn {#1#2#3#4}#5#6
16950   \__fp_fixed_mul:wnn
16951 }

```

(End definition for `__fp_ep_div_esti:wwwwn`, `__fp_ep_div_estii:wnnnwnn`, and `__fp_ep_div_estiii:NNNNNwwwn`.)

```

\__fp_ep_div_epsilon:wnNNNNNn
\__fp_ep_div_eps_pack:NNNNNw
\__fp_ep_div_epsilon:wnnnwnn

```

The bounds shown above imply that the `epsilon` function's first operand is $(1 - \epsilon)$ with $\epsilon \in [0, 1.755 \cdot 10^{-5}]$. The `epsilon` function computes ϵ as $1 - (1 - \epsilon)$. Since $\epsilon < 10^{-4}$, its first block vanishes and there is no need to explicitly use `#1` (which is 9999). Then `epsii` evaluates $10^{-9}a/(1 - \epsilon)$ as $(1 + \epsilon^2)(1 + \epsilon)(10^{-9}a\epsilon) + 10^{-9}a$. Importantly, we compute $10^{-9}a\epsilon$ before multiplying it with the rest, rather than multiplying by ϵ and then $10^{-9}a$, as this second option loses more precision. Also, the combination of `short_mul` and `div_myriad` is both faster and more precise than a simple `mul`.

```

16952 \cs_new:Npn \__fp_ep_div_epsilon:wnNNNNNn #1#2#3#4#5#6;
16953 {
16954   \exp_after:wN \__fp_ep_div_epsilon:wnnnwnn
16955   \int_value:w \__fp_int_eval:w 1 9998 - #2
16956   \exp_after:wN \__fp_ep_div_eps_pack:NNNNNw
16957   \int_value:w \__fp_int_eval:w 1 9999 9998 - #3#4
16958   \exp_after:wN \__fp_ep_div_eps_pack:NNNNNw
16959   \int_value:w \__fp_int_eval:w 2 0000 0000 - #5#6 ; ;
16960 }
16961 \cs_new:Npn \__fp_ep_div_eps_pack:NNNNNw #1#2#3#4#5#6;
16962 { + #1 ; {#2#3#4#5} {#6} }
16963 \cs_new:Npn \__fp_ep_div_epsilon:wnnnwnn 1#1; #2; #3#4#5#6#7#8
16964 {
16965   \__fp_fixed_mul:wnn {0000}{#1}#2; {0000}{#1}#2;
16966   \__fp_fixed_add_one:wN
16967   \__fp_fixed_mul:wnn {10000} {#1} #2 ;
16968   {
16969     \__fp_fixed_mul_short:wnn {0000}{#1}#2; {#3}{#4#5#6#7}{#8000};
16970     \__fp_fixed_div_myriad:wn
16971     \__fp_fixed_mul:wnn
16972   }
16973   \__fp_fixed_add:wnn {#3}{#4#5#6#7}{#8000}{0000}{0000}{0000};
16974 }

```

(End definition for `__fp_ep_div_epsilon:wnNNNNNn`, `__fp_ep_div_eps_pack:NNNNNw`, and `__fp_ep_div_epsilon:wnnnwnn`.)

30.10 Inverse square root of extended precision numbers

The idea here is similar to division. Normalize the input, multiplying by powers of 100 until we have $x \in [0.01, 1)$. Then find an integer approximation $r \in [101, 1003]$ of $10^2/\sqrt{x}$,

as the fixed point of iterations of the Newton method: essentially $r \mapsto (r + 10^8/(x_1 r))/2$, starting from a guess that optimizes the number of steps before convergence. In fact, just as there is a slight shift when computing divisions to ensure that some inequalities hold, we replace 10^8 by a slightly larger number which ensures that $r^2 x \geq 10^4$. This also causes $r \in [101, 1003]$. Another correction to the above is that the input is actually normalized to $[0.1, 1)$, and we use either 10^8 or 10^9 in the Newton method, depending on the parity of the exponent. Skipping those technical hurdles, once we have the approximation r , we set $y = 10^{-4} r^2 x$ (or rather, the correct power of 10 to get $y \simeq 1$) and compute $y^{-1/2}$ through another application of Newton's method. This time, the starting value is $z = 1$, each step maps $z \mapsto z(1.5 - 0.5yz^2)$, and we perform a fixed number of steps. Our final result combines r with $y^{-1/2}$ as $x^{-1/2} = 10^{-2} r y^{-1/2}$.

First normalize the input, then check the parity of the exponent #1. If it is even, the result's exponent will be $-#1/2$, otherwise it will be $(#1 - 1)/2$ (except in the case where the input was an exact power of 100). The `auxii` function receives as #1 the result's exponent just computed, as #2 the starting value for the iteration giving r (the values 168 and 535 lead to the least number of iterations before convergence, on average), as #3 and #4 one empty argument and one 0, depending on the parity of the original exponent, as #5 and #6 the normalized mantissa (#5 $\in [1000, 9999]$), and as #7 the continuation. It sets up the iteration giving r : the `esti` function thus receives the initial two guesses #2 and 0, an approximation #5 of $10^4 x$ (its first block of digits), and the empty/zero arguments #3 and #4, followed by the mantissa and an altered continuation where we have stored the result's exponent.

```

16975 \cs_new:Npn \__fp_ep_isqrt:wwn #1,#2;
16976 {
16977   \__fp_ep_to_ep:wwN #1,#2;
16978   \__fp_ep_isqrt_auxi:wwn
16979 }
16980 \cs_new:Npn \__fp_ep_isqrt_auxi:wwn #1,
16981 {
16982   \exp_after:wN \__fp_ep_isqrt_auxii:wwnnwn
16983   \int_value:w \__fp_int_eval:w
16984   \int_if_odd:nTF {#1}
16985     { (1 - #1) / 2 , 535 , { 0 } { } }
16986     { 1 - #1 / 2 , 168 , { } { 0 } }
16987 }
16988 \cs_new:Npn \__fp_ep_isqrt_auxii:wwnnwn #1, #2, #3#4 #5#6; #7
16989 {
16990   \__fp_ep_isqrt_esti:wwnnwn #2, 0, #5, {#3} {#4}
16991   {#5} #6 ; { #7 #1 , }
16992 }

```

(End definition for `__fp_ep_isqrt:wwn`, `__fp_ep_isqrt_aux:wwn`, and `__fp_ep_isqrt_auxii:wwnnwn`.)

If the last two approximations gave the same result, we are done: call the `estii` function to clean up. Otherwise, evaluate $(\langle prev \rangle + 1.005 \cdot 10^8 \text{ or } 9 / (\langle prev \rangle \cdot x))/2$, as the next approximation: omitting the 1.005 factor, this would be Newton's method. We can check by brute force that if #4 is empty (the original exponent was even), the process computes an integer slightly larger than $100/\sqrt{x}$, while if #4 is 0 (the original exponent was odd), the result is an integer slightly larger than $100/\sqrt{x/10}$. Once we are done, we evaluate $100r^2/2$ or $10r^2/2$ (when the exponent is even or odd, respectively) and feed that to `estiii`. This third auxiliary finds $y_{\text{even}}/2 = 10^{-4} r^2 x/2$ or $y_{\text{odd}}/2 = 10^{-5} r^2 x/2$

(again, depending on earlier parity). A simple program shows that $y \in [1, 1.0201]$. The number $y/2$ is fed to `__fp_ep_isqrt_epsilon:wN`, which computes $1/\sqrt{y}$, and we finally multiply the result by r .

```

16993 \cs_new:Npn \__fp_ep_isqrt_esti:wwnnwn #1, #2, #3, #4
16994 {
16995   \if_int_compare:w #1 = #2 \exp_stop_f:
16996     \exp_after:wN \__fp_ep_isqrt_estii:wwnnwn
16997   \fi:
16998   \exp_after:wN \__fp_ep_isqrt_esti:wwnnwn
16999   \int_value:w \__fp_int_eval:w
17000     (#1 + 1 0050 0000 #4 / (#1 * #3)) / 2 ,
17001   #1, #3, {#4}
17002 }
17003 \cs_new:Npn \__fp_ep_isqrt_estii:wwnnwn #1, #2, #3, #4#5
17004 {
17005   \exp_after:wN \__fp_ep_isqrt_estiii:NNNNNwwn
17006   \int_value:w \__fp_int_eval:w 1000 0000 + #2 * #2 #5 * 5
17007   \exp_after:wN , \int_value:w \__fp_int_eval:w 10000 + #2 ;
17008 }
17009 \cs_new:Npn \__fp_ep_isqrt_estiii:NNNNNwwn 1#1#2#3#4#5#6, 1#7#8; #9;
17010 {
17011   \__fp_fixed_mul_short:wwn #9; {#1} {#2#3#4#5} {#600} ;
17012   \__fp_ep_isqrt_epsilon:wN
17013   \__fp_fixed_mul_short:wwn {#7} {#80} {0000} ;
17014 }

```

(End definition for `__fp_ep_isqrt_esti:wwnnwn`, `__fp_ep_isqrt_estii:wwnnwn`, and `__fp_ep_isqrt_estiii:NNNNNwwn`.)

`__fp_ep_isqrt_epsilon:wN`
`__fp_ep_isqrt_epsilonii:wwN`

Here, we receive a fixed point number $y/2$ with $y \in [1, 1.0201]$. Starting from $z = 1$ we iterate $z \mapsto z(3/2 - z^2 y/2)$. In fact, we start from the first iteration $z = 3/2 - y/2$ to avoid useless multiplications. The `epsii` auxiliary receives z as `#1` and y as `#2`.

```

17015 \cs_new:Npn \__fp_ep_isqrt_epsilon:wN #1;
17016 {
17017   \__fp_fixed_sub:wwn {15000}{0000}{0000}{0000}{0000}{0000}; #1;
17018   \__fp_ep_isqrt_epsilonii:wwN #1;
17019   \__fp_ep_isqrt_epsilonii:wwN #1;
17020   \__fp_ep_isqrt_epsilonii:wwN #1;
17021 }
17022 \cs_new:Npn \__fp_ep_isqrt_epsilonii:wwN #1; #2;
17023 {
17024   \__fp_fixed_mul:wwn #1; #1;
17025   \__fp_fixed_mul_sub_back:wwn #2;
17026   {15000}{0000}{0000}{0000}{0000}{0000};
17027   \__fp_fixed_mul:wwn #1;
17028 }

```

(End definition for `__fp_ep_isqrt_epsilon:wN` and `__fp_ep_isqrt_epsilonii:wwN`.)

30.11 Converting from fixed point to floating point

After computing Taylor series, we wish to convert the result from extended precision (with or without an exponent) to the public floating point format. The functions here

should be called within an integer expression for the overall exponent of the floating point.

`__fp_ep_to_float_o:wwN`
`__fp_ep_inv_to_float_o:wwN` An extended-precision number is simply a comma-delimited exponent followed by a fixed point number. Leave the exponent in the current integer expression then convert the fixed point number.

```
17029 \cs_new:Npn \__fp_ep_to_float_o:wwN #1,
17030 { + \__fp_int_eval:w #1 \__fp_fixed_to_float_o:wN }
17031 \cs_new:Npn \__fp_ep_inv_to_float_o:wwN #1,#2;
17032 {
17033   \__fp_ep_div:wwwN 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1,#2;
17034   \__fp_ep_to_float_o:wwN
17035 }
```

(End definition for `__fp_ep_to_float_o:wwN` and `__fp_ep_inv_to_float_o:wwN`.)

`__fp_fixed_inv_to_float_o:wN` Another function which reduces to converting an extended precision number to a float.

```
17036 \cs_new:Npn \__fp_fixed_inv_to_float_o:wN
17037 { \__fp_ep_inv_to_float_o:wwN 0, }
```

(End definition for `__fp_fixed_inv_to_float_o:wN`.)

`__fp_fixed_to_float_rad_o:wN` Converts the fixed point number #1 from degrees to radians then to a floating point number. This could perhaps remain in `l3fp-trig`.

```
17038 \cs_new:Npn \__fp_fixed_to_float_rad_o:wN #1;
17039 {
17040   \__fp_fixed_mul:wwN #1; {5729}{5779}{5130}{8232}{0876}{7981};
17041   { \__fp_ep_to_float_o:wwN 2, }
17042 }
```

(End definition for `__fp_fixed_to_float_rad_o:wN`.)

`__fp_fixed_to_float_o:wN` ... `__fp_int_eval:w` $\langle exponent \rangle$ `__fp_fixed_to_float_o:wN` $\{\langle a_1 \rangle\} \{\langle a_2 \rangle\} \{\langle a_3 \rangle\}$
`__fp_fixed_to_float_o:Nw` $\{\langle a_4 \rangle\} \{\langle a_5 \rangle\} \{\langle a_6 \rangle\}$; $\langle sign \rangle$
yields
 $\langle exponent' \rangle$; $\{\langle a'_1 \rangle\} \{\langle a'_2 \rangle\} \{\langle a'_3 \rangle\} \{\langle a'_4 \rangle\}$;

And the `to_fixed` version gives six brace groups instead of 4, ensuring that $1000 \leq \langle a'_1 \rangle \leq 9999$. At this stage, we know that $\langle a_1 \rangle$ is positive (otherwise, it is sign of an error before), and we assume that it is less than 10^8 .⁹

```
17043 \cs_new:Npn \__fp_fixed_to_float_o:Nw #1#2;
17044 { \__fp_fixed_to_float_o:wN #2; #1 }
17045 \cs_new:Npn \__fp_fixed_to_float_o:wN #1#2#3#4#5#6; #7
17046 { % for the 8-digit-at-the-start thing
17047   + \__fp_int_eval:w \c__fp_block_int
17048   \exp_after:wN \exp_after:wN
17049   \exp_after:wN \__fp_fixed_to_loop:N
17050   \exp_after:wN \use_none:n
17051   \int_value:w \__fp_int_eval:w
17052   1 0000 0000 + #1 \exp_after:wN \__fp_use_none_stop_f:n
17053   \int_value:w 1#2 \exp_after:wN \__fp_use_none_stop_f:n
17054   \int_value:w 1#3#4 \exp_after:wN \__fp_use_none_stop_f:n
```

⁹Bruno: I must double check this assumption.

```

17055     \int_value:w 1#5#6
17056     \exp_after:wN ;
17057     \exp_after:wN ;
17058   }
17059 \cs_new:Npn \__fp_fixed_to_loop:N #1
17060 {
17061   \if_meaning:w 0 #1
17062     - 1
17063     \exp_after:wN \__fp_fixed_to_loop:N
17064   \else:
17065     \exp_after:wN \__fp_fixed_to_loop_end:w
17066     \exp_after:wN #1
17067   \fi:
17068 }
17069 \cs_new:Npn \__fp_fixed_to_loop_end:w #1 #2 ;
17070 {
17071   \if_meaning:w ; #1
17072     \exp_after:wN \__fp_fixed_to_float_zero:w
17073   \else:
17074     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
17075     \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
17076     \exp_after:wN \__fp_fixed_to_float_pack:ww
17077     \exp_after:wN ;
17078   \fi:
17079   #1 #2 0000 0000 0000 0000 ;
17080 }
17081 \cs_new:Npn \__fp_fixed_to_float_zero:w ; 0000 0000 0000 0000 ;
17082 {
17083   - 2 * \c__fp_max_exponent_int ;
17084   {0000} {0000} {0000} {0000} ;
17085 }
17086 \cs_new:Npn \__fp_fixed_to_float_pack:ww #1 ; #2#3 ; ;
17087 {
17088   \if_int_compare:w #2 > 4 \exp_stop_f:
17089     \exp_after:wN \__fp_fixed_to_float_round_up:wnnnnw
17090   \fi:
17091   ; #1 ;
17092 }
17093 \cs_new:Npn \__fp_fixed_to_float_round_up:wnnnnw ; #1#2#3#4 ;
17094 {
17095   \exp_after:wN \__fp_basics_pack_high:NNNNNw
17096   \int_value:w \__fp_int_eval:w 1 #1#2
17097   \exp_after:wN \__fp_basics_pack_low:NNNNNw
17098   \int_value:w \__fp_int_eval:w 1 #3#4 + 1 ;
17099 }

```

(End definition for __fp_fixed_to_float_o:wN and __fp_fixed_to_float_o:Nw.)

```

17100 </initex | package>

```

31 l3fp-expo implementation

```

17101 <*initex | package>
17102 <@@=fp>

```



```

\__fp_parse_word_exp:N Unary functions.
\__fp_parse_word_ln:N
17103 \cs_new:Npn \__fp_parse_word_exp:N
17104 { \__fp_parse_unary_function:NNN \__fp_exp_o:w ? }
17105 \cs_new:Npn \__fp_parse_word_ln:N
17106 { \__fp_parse_unary_function:NNN \__fp_ln_o:w ? }

(End definition for \__fp_parse_word_exp:N and \__fp_parse_word_ln:N.)

```

31.1 Logarithm

31.1.1 Work plan

As for many other functions, we filter out special cases in `__fp_ln_o:w`. Then `__fp_ln_npos_o:w` receives a positive normal number, which we write in the form $a \cdot 10^b$ with $a \in [0.1, 1)$.

The rest of this section is actually not in sync with the code. Or is the code not in sync with the section? In the current code, $c \in [1, 10]$ is such that $0.7 \leq ac < 1.4$.

We are given a positive normal number, of the form $a \cdot 10^b$ with $a \in [0.1, 1)$. To compute its logarithm, we find a small integer $5 \leq c < 50$ such that $0.91 \leq ac/5 < 1.1$, and use the relation

$$\ln(a \cdot 10^b) = b \cdot \ln(10) - \ln(c/5) + \ln(ac/5).$$

The logarithms $\ln(10)$ and $\ln(c/5)$ are looked up in a table. The last term is computed using the following Taylor series of \ln near 1:

$$\ln\left(\frac{ac}{5}\right) = \ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + t^2 \left(\frac{1}{3} + t^2 \left(\frac{1}{5} + t^2 \left(\frac{1}{7} + t^2 \left(\frac{1}{9} + \dots\right)\right)\right)\right)\right)$$

where $t = 1 - 10/(ac + 5)$. We can now see one reason for the choice of $ac \sim 5$: then $ac + 5 = 10(1 - \epsilon)$ with $-0.05 < \epsilon \leq 0.045$, hence

$$t = \frac{\epsilon}{1 - \epsilon} = \epsilon(1 + \epsilon)(1 + \epsilon^2)(1 + \epsilon^4) \dots,$$

is not too difficult to compute.

31.1.2 Some constants

A few values of the logarithm as extended fixed point numbers. Those are needed in the implementation. It turns out that we don't need the value of $\ln(5)$.

```

\c__fp_ln_i_fixed_tl
\c__fp_ln_ii_fixed_tl
\c__fp_ln_iii_fixed_tl
\c__fp_ln_iv_fixed_tl
\c__fp_ln_v_fixed_tl
\c__fp_ln_vii_fixed_tl
\c__fp_ln_viii_fixed_tl
\c__fp_ln_ix_fixed_tl
\c__fp_ln_x_fixed_tl
17107 \tl_const:Nn \c__fp_ln_i_fixed_tl { {0000}{0000}{0000}{0000}{0000}{0000}; }
17108 \tl_const:Nn \c__fp_ln_ii_fixed_tl { {6931}{4718}{0559}{9453}{0941}{7232}; }
17109 \tl_const:Nn \c__fp_ln_iii_fixed_tl { {10986}{1228}{8668}{1096}{9139}{5245}; }
17110 \tl_const:Nn \c__fp_ln_iv_fixed_tl { {13862}{9436}{1119}{8906}{1883}{4464}; }
17111 \tl_const:Nn \c__fp_ln_v_fixed_tl { {17917}{5946}{9228}{0550}{0081}{2477}; }
17112 \tl_const:Nn \c__fp_ln_vii_fixed_tl { {19459}{1014}{9055}{3133}{0510}{5353}; }
17113 \tl_const:Nn \c__fp_ln_viii_fixed_tl { {20794}{4154}{1679}{8359}{2825}{1696}; }
17114 \tl_const:Nn \c__fp_ln_ix_fixed_tl { {21972}{2457}{7336}{2193}{8279}{0490}; }
17115 \tl_const:Nn \c__fp_ln_x_fixed_tl { {23025}{8509}{2994}{0456}{8401}{7991}; }

```

(End definition for `\c__fp_ln_i_fixed_tl` and others.)

31.1.3 Sign, exponent, and special numbers

`__fp_ln_o:w` The logarithm of negative numbers (including $-\infty$ and -0) raises the “invalid” exception. The logarithm of $+0$ is $-\infty$, raising a division by zero exception. The logarithm of $+\infty$ or a `nan` is itself. Positive normal numbers call `__fp_ln_npos_o:w`.

```

17116 \cs_new:Npn \__fp_ln_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
17117 {
17118   \if_meaning:w 2 #3
17119     \__fp_case_use:nw { \__fp_invalid_operation_o:nw { ln } }
17120   \fi:
17121   \if_case:w #2 \exp_stop_f:
17122     \__fp_case_use:nw
17123     { \__fp_division_by_zero_o:Nnw \c_minus_inf_fp { ln } }
17124   \or:
17125   \else:
17126     \__fp_case_return_same_o:w
17127   \fi:
17128   \__fp_ln_npos_o:w \s__fp \__fp_chk:w #2#3#4;
17129 }

```

(End definition for `__fp_ln_o:w`.)

31.1.4 Absolute ln

`__fp_ln_npos_o:w` We catch the case of a significand very close to 0.1 or to 1. In all other cases, the final result is at least 10^{-4} , and then an error of $0.5 \cdot 10^{-20}$ is acceptable.

```

17130 \cs_new:Npn \__fp_ln_npos_o:w \s__fp \__fp_chk:w 10#1#2#3;
17131 { %%^A todo: ln(1) should be "exact zero", not "underflow"
17132   \exp_after:wN \__fp_sanitizew
17133   \int_value:w % for the overall sign
17134   \if_int_compare:w #1 < 1 \exp_stop_f:
17135     2
17136   \else:
17137     0
17138   \fi:
17139   \exp_after:wN \exp_stop_f:
17140   \int_value:w \__fp_int_eval:w % for the exponent
17141   \__fp_ln_significand:NNNNnnnnN #2#3
17142   \__fp_ln_exponent:wn {#1}
17143 }

```

(End definition for `__fp_ln_npos_o:w`.)

`__fp_ln_significand:NNNNnnnnN` `__fp_ln_significand:NNNNnnnnN` $\langle X_1 \rangle$ $\{\langle X_2 \rangle\}$ $\{\langle X_3 \rangle\}$ $\{\langle X_4 \rangle\}$ $\langle continuation \rangle$
 This function expands to

$\langle continuation \rangle$ $\{\langle Y_1 \rangle\}$ $\{\langle Y_2 \rangle\}$ $\{\langle Y_3 \rangle\}$ $\{\langle Y_4 \rangle\}$ $\{\langle Y_5 \rangle\}$ $\{\langle Y_6 \rangle\}$;

where $Y = -\ln(X)$ as an extended fixed point.

```

17144 \cs_new:Npn \__fp_ln_significand:NNNNnnnnN #1#2#3#4
17145 {
17146   \exp_after:wN \__fp_ln_x_ii:wnnnn
17147   \int_value:w
17148   \if_case:w #1 \exp_stop_f:

```

```

17149     \or:
17150       \if_int_compare:w #2 < 4 \exp_stop_f:
17151         \__fp_int_eval:w 10 - #2
17152       \else:
17153         6
17154       \fi:
17155     \or: 4
17156     \or: 3
17157     \or: 2
17158     \or: 2
17159     \or: 2
17160     \else: 1
17161     \fi:
17162   ; { #1 #2 #3 #4 }
17163 }

```

(End definition for `__fp_ln_significand:NNNNnnnN`.)

`__fp_ln_x_ii:wnnnn` We have thus found $c \in [1, 10]$ such that $0.7 \leq ac < 1.4$ in all cases. Compute $1 + x = 1 + ac \in [1.7, 2.4)$.

```

17164 \cs_new:Npn \__fp_ln_x_ii:wnnnn #1; #2#3#4#5
17165 {
17166   \exp_after:wN \__fp_ln_div_after:Nw
17167   \cs:w c__fp_ln_ \__fp_int_to_roman:w #1 _fixed_tl \exp_after:wN \cs_end:
17168   \int_value:w
17169     \exp_after:wN \__fp_ln_x_iv:wnnnnnnnn
17170     \int_value:w \__fp_int_eval:w
17171     \exp_after:wN \__fp_ln_x_iii_var:NNNNNw
17172     \int_value:w \__fp_int_eval:w 9999 9990 + #1*#2#3 +
17173     \exp_after:wN \__fp_ln_x_iii:NNNNNw
17174     \int_value:w \__fp_int_eval:w 10 0000 0000 + #1*#4#5 ;
17175     {20000} {0000} {0000} {0000}
17176   } %^A todo: reoptimize (a generalization attempt failed).
17177 \cs_new:Npn \__fp_ln_x_iii:NNNNNw #1#2 #3#4#5#6 #7;
17178 { #1#2; {#3#4#5#6} {#7} }
17179 \cs_new:Npn \__fp_ln_x_iii_var:NNNNNw #1 #2#3#4#5 #6;
17180 {
17181   #1#2#3#4#5 + 1 ;
17182   {#1#2#3#4#5} {#6}
17183 }

```

The Taylor series to be used is expressed in terms of $t = (x - 1)/(x + 1) = 1 - 2/(x + 1)$. We now compute the quotient with extended precision, reusing some code from `__fp_-/_o:ww`. Note that $1 + x$ is known exactly.

To reuse notations from `l3fp-basics`, we want to compute A/Z with $A = 2$ and $Z = x + 1$. In `l3fp-basics`, we considered the case where both A and Z are arbitrary, in the range $[0.1, 1)$, and we had to monitor the growth of the sequence of remainders A , B , C , etc. to ensure that no overflow occurred during the computation of the next quotient. The main source of risk was our choice to define the quotient as roughly $10^9 \cdot A/10^5 \cdot Z$: then A was bound to be below $2.147 \dots$, and this limit was never far.

In our case, we can simply work with $10^8 \cdot A$ and $10^4 \cdot Z$, because our reason to work with higher powers has gone: we needed the integer $y \simeq 10^5 \cdot Z$ to be at least 10^4 , and now, the definition $y \simeq 10^4 \cdot Z$ suffices.

Let us thus define $y = \lfloor 10^4 \cdot Z \rfloor + 1 \in (1.7 \cdot 10^4, 2.4 \cdot 10^4]$, and

$$Q_1 = \left\lfloor \frac{\lfloor 10^8 \cdot A \rfloor}{y} - \frac{1}{2} \right\rfloor.$$

(The $1/2$ comes from how ε -TeX rounds.) As for division, it is easy to see that $Q_1 \leq 10^4 A/Z$, *i.e.*, Q_1 is an underestimate.

Exactly as we did for division, we set $B = 10^4 A - Q_1 Z$. Then

$$\begin{aligned} 10^4 B &\leq A_1 A_2 \cdot A_3 A_4 - \left(\frac{A_1 A_2}{y} - \frac{3}{2} \right) 10^4 Z \\ &\leq A_1 A_2 \left(1 - \frac{10^4 Z}{y} \right) + 1 + \frac{3}{2} y \\ &\leq 10^8 \frac{A}{y} + 1 + \frac{3}{2} y \end{aligned}$$

In the same way, and using $1.7 \cdot 10^4 \leq y \leq 2.4 \cdot 10^4$, and convexity, we get

$$\begin{aligned} 10^4 A &= 2 \cdot 10^4 \\ 10^4 B &\leq 10^8 \frac{A}{y} + 1.6y \leq 4.7 \cdot 10^4 \\ 10^4 C &\leq 10^8 \frac{B}{y} + 1.6y \leq 5.8 \cdot 10^4 \\ 10^4 D &\leq 10^8 \frac{C}{y} + 1.6y \leq 6.3 \cdot 10^4 \\ 10^4 E &\leq 10^8 \frac{D}{y} + 1.6y \leq 6.5 \cdot 10^4 \\ 10^4 F &\leq 10^8 \frac{E}{y} + 1.6y \leq 6.6 \cdot 10^4 \end{aligned}$$

Note that we compute more steps than for division: since t is not the end result, we need to know it with more accuracy (on the other hand, the ending is much simpler, as we don't need an exact rounding for transcendental functions, but just a faithful rounding).

`__fp_ln_x_iv:wnnnnnnnn <1 or 2> <8d> ; {\<4d>} {\<4d>} <fixed-tl>`

The number is x . Compute y by adding 1 to the five first digits.

```

17184 \cs_new:Npn \__fp_ln_x_iv:wnnnnnnnn #1; #2#3#4#5 #6#7#8#9
17185 {
17186   \exp_after:wN \__fp_div_significand_pack:NNN
17187   \int_value:w \__fp_int_eval:w
17188   \__fp_ln_div_i:w #1 ;
17189   #6 #7 ; {\#8} {\#9}
17190   {\#2} {\#3} {\#4} {\#5}
17191   { \exp_after:wN \__fp_ln_div_ii:wnn \int_value:w #1 }
17192   { \exp_after:wN \__fp_ln_div_ii:wnn \int_value:w #1 }
17193   { \exp_after:wN \__fp_ln_div_ii:wnn \int_value:w #1 }
17194   { \exp_after:wN \__fp_ln_div_ii:wnn \int_value:w #1 }
17195   { \exp_after:wN \__fp_ln_div_vi:wnn \int_value:w #1 }

```

```

17196   }
17197   \cs_new:Npn \__fp_ln_div_i:w #1;
17198   {
17199     \exp_after:wN \__fp_div_significand_calc:wwnnnnnnnn
17200     \int_value:w \__fp_int_eval:w 999999 + 2 0000 0000 / #1 ; % Q1
17201   }
17202   \cs_new:Npn \__fp_ln_div_ii:wwn #1; #2;#3 % y; B1;B2 <- for k=1
17203   {
17204     \exp_after:wN \__fp_div_significand_pack:NNN
17205     \int_value:w \__fp_int_eval:w
17206     \exp_after:wN \__fp_div_significand_calc:wwnnnnnnnn
17207     \int_value:w \__fp_int_eval:w 999999 + #2 #3 / #1 ; % Q2
17208     #2 #3 ;
17209   }
17210   \cs_new:Npn \__fp_ln_div_vi:wwn #1; #2;#3#4#5 #6#7#8#9 %y;F1;F2F3F4x1x2x3x4
17211   {
17212     \exp_after:wN \__fp_div_significand_pack:NNN
17213     \int_value:w \__fp_int_eval:w 1000000 + #2 #3 / #1 ; % Q6
17214   }

```

We now have essentially

```

\__fp_ln_div_after:Nw <fixed t1>
\__fp_div_significand_pack:NNN 106 + Q1
\__fp_div_significand_pack:NNN 106 + Q2
\__fp_div_significand_pack:NNN 106 + Q3
\__fp_div_significand_pack:NNN 106 + Q4
\__fp_div_significand_pack:NNN 106 + Q5
\__fp_div_significand_pack:NNN 106 + Q6 ;
<exponent> ; <continuation>

```

where $\langle \text{fixed } t1 \rangle$ holds the logarithm of a number in $[1, 10]$, and $\langle \text{exponent} \rangle$ is the exponent. Also, the expansion is done backwards. Then $\backslash_fp_div_significand_pack:NNN$ puts things in the correct order to add the Q_i together and put semicolons between each piece. Once those have been expanded, we get

```

\__fp_ln_div_after:Nw <fixed-t1> <1d> ; <4d> ; <4d> ;
<4d> ; <4d> ; <4d> ; <4d> ; <exponent> ;

```

Just as with division, we know that the first two digits are 1 and 0 because of bounds on the final result of the division $2/(x+1)$, which is between roughly 0.8 and 1.2. We then compute $1 - 2/(x+1)$, after testing whether $2/(x+1)$ is greater than or smaller than 1.

```

17215   \cs_new:Npn \__fp_ln_div_after:Nw #1#2;
17216   {
17217     \if_meaning:w 0 #2
17218     \exp_after:wN \__fp_ln_t_small:Nw
17219     \else:
17220     \exp_after:wN \__fp_ln_t_large:NNw
17221     \exp_after:wN -
17222     \fi:
17223     #1
17224   }
17225   \cs_new:Npn \__fp_ln_t_small:Nw #1 #2; #3; #4; #5; #6; #7;
17226   {
17227     \exp_after:wN \__fp_ln_t_large:NNw

```

```

17228 \exp_after:wN + % <sign>
17229 \exp_after:wN #1
17230 \int_value:w \_fp_int_eval:w 9999 - #2 \exp_after:wN ;
17231 \int_value:w \_fp_int_eval:w 9999 - #3 \exp_after:wN ;
17232 \int_value:w \_fp_int_eval:w 9999 - #4 \exp_after:wN ;
17233 \int_value:w \_fp_int_eval:w 9999 - #5 \exp_after:wN ;
17234 \int_value:w \_fp_int_eval:w 9999 - #6 \exp_after:wN ;
17235 \int_value:w \_fp_int_eval:w 1 0000 - #7 ;
17236 }

```

```

\_fp_ln_t_large:NNw <sign> <fixed t1>
<t1>; <t2>; <t3>; <t4>; <t5>; <t6>;
<exponent>; <continuation>

```

Compute the square t^2 , and keep t at the end with its sign. We know that $t < 0.1765$, so every piece has at most 4 digits. However, since we were not careful in `_fp_ln_t_small:w`, they can have less than 4 digits.

```

17237 \cs_new:Npn \_fp_ln_t_large:NNw #1 #2 #3; #4; #5; #6; #7; #8;
17238 {
17239 \exp_after:wN \_fp_ln_square_t_after:w
17240 \int_value:w \_fp_int_eval:w 9999 0000 + #3*#3
17241 \exp_after:wN \_fp_ln_square_t_pack:NNNNNw
17242 \int_value:w \_fp_int_eval:w 9999 0000 + 2*#3*#4
17243 \exp_after:wN \_fp_ln_square_t_pack:NNNNNw
17244 \int_value:w \_fp_int_eval:w 9999 0000 + 2*#3*#5 + #4*#4
17245 \exp_after:wN \_fp_ln_square_t_pack:NNNNNw
17246 \int_value:w \_fp_int_eval:w 9999 0000 + 2*#3*#6 + 2*#4*#5
17247 \exp_after:wN \_fp_ln_square_t_pack:NNNNNw
17248 \int_value:w \_fp_int_eval:w
17249 1 0000 0000 + 2*#3*#7 + 2*#4*#6 + #5*#5
17250 + (2*#3*#8 + 2*#4*#7 + 2*#5*#6) / 1 0000
17251 % ; ; ;
17252 \exp_after:wN \_fp_ln_twice_t_after:w
17253 \int_value:w \_fp_int_eval:w -1 + 2*#3
17254 \exp_after:wN \_fp_ln_twice_t_pack:Nw
17255 \int_value:w \_fp_int_eval:w 9999 + 2*#4
17256 \exp_after:wN \_fp_ln_twice_t_pack:Nw
17257 \int_value:w \_fp_int_eval:w 9999 + 2*#5
17258 \exp_after:wN \_fp_ln_twice_t_pack:Nw
17259 \int_value:w \_fp_int_eval:w 9999 + 2*#6
17260 \exp_after:wN \_fp_ln_twice_t_pack:Nw
17261 \int_value:w \_fp_int_eval:w 9999 + 2*#7
17262 \exp_after:wN \_fp_ln_twice_t_pack:Nw
17263 \int_value:w \_fp_int_eval:w 10000 + 2*#8 ; ;
17264 { \_fp_ln_c:NwNw #1 }
17265 #2
17266 }
17267 \cs_new:Npn \_fp_ln_twice_t_pack:Nw #1 #2; { + #1 ; {#2} }
17268 \cs_new:Npn \_fp_ln_twice_t_after:w #1; { ; ; ; {#1} }
17269 \cs_new:Npn \_fp_ln_square_t_pack:NNNNNw #1 #2#3#4#5 #6;
17270 { + #1#2#3#4#5 ; {#6} }
17271 \cs_new:Npn \_fp_ln_square_t_after:w 1 0 #1#2#3 #4;
17272 { \_fp_ln_Taylor:wwNw {0#1#2#3} {#4} }

```

(End definition for `_fp_ln_x_ii:wnnnn`.)

_fp_ln_Taylor:wwNw Denoting $T = t^2$, we get

```
\_fp_ln_Taylor:wwNw
{⟨T1⟩} {⟨T2⟩} {⟨T3⟩} {⟨T4⟩} {⟨T5⟩} {⟨T6⟩} ; ;
{⟨(2t)1⟩} {⟨(2t)2⟩} {⟨(2t)3⟩} {⟨(2t)4⟩} {⟨(2t)5⟩} {⟨(2t)6⟩} ;
{ \_fp_ln_c:NwNw ⟨sign⟩ }
⟨fixed t1⟩ ⟨exponent⟩ ; ⟨continuation⟩
```

And we want to compute

$$\ln\left(\frac{1+t}{1-t}\right) = 2t \left(1 + T \left(\frac{1}{3} + T \left(\frac{1}{5} + T \left(\frac{1}{7} + T \left(\frac{1}{9} + \cdots\right)\right)\right)\right)\right)$$

The process looks as follows

```
\loop 5; A;
\div_int 5; 1.0; \add A; \mul T; {\loop \eval 5-2;}
\add 0.2; A; \mul T; {\loop \eval 5-2;}
\mul B; T; {\loop 3;}
\loop 3; C;
```

This uses the routine for dividing a number by a small integer ($< 10^4$).

```
17273 \cs_new:Npn \_fp_ln_Taylor:wwNw
17274 { \_fp_ln_Taylor_loop:www 21 ; {0000}{0000}{0000}{0000}{0000} ; }
17275 \cs_new:Npn \_fp_ln_Taylor_loop:www #1; #2; #3;
17276 {
17277   \if_int_compare:w #1 = 1 \exp_stop_f:
17278   \_fp_ln_Taylor_break:w
17279   \fi:
17280   \exp_after:wN \_fp_fixed_div_int:wwN \c\_fp_one_fixed_t1 #1;
17281   \_fp_fixed_add:wwN #2;
17282   \_fp_fixed_mul:wwN #3;
17283   {
17284     \exp_after:wN \_fp_ln_Taylor_loop:www
17285     \int_value:w \_fp_int_eval:w #1 - 2 ;
17286   }
17287   #3;
17288 }
17289 \cs_new:Npn \_fp_ln_Taylor_break:w \fi: #1 \_fp_fixed_add:wwN #2#3; #4 ;;
17290 {
17291   \fi:
17292   \exp_after:wN \_fp_fixed_mul:wwN
17293   \exp_after:wN { \int_value:w \_fp_int_eval:w 10000 + #2 } #3;
17294 }
```

(End definition for _fp_ln_Taylor:wwNw.)

```
\_fp_ln_c:NwNw ⟨sign⟩
{⟨r1⟩} {⟨r2⟩} {⟨r3⟩} {⟨r4⟩} {⟨r5⟩} {⟨r6⟩} ;
⟨fixed t1⟩ ⟨exponent⟩ ; ⟨continuation⟩
```

We are now reduced to finding $\ln(c)$ and $\langle exponent \rangle \ln(10)$ in a table, and adding it to the mixture. The first step is to get $\ln(c) - \ln(x) = -\ln(a)$, then we get $\mathbf{b} \ln(10)$ and add or subtract.

For now, $\ln(x)$ is given as $\cdot 10^0$. Unless both the exponent is 1 and $c = 1$, we shift to working in units of $\cdot 10^4$, since the final result is at least $\ln(10/7) \simeq 0.35$.

```

17295 \cs_new:Npn \__fp_ln_c:NwNw #1 #2; #3
17296 {
17297   \if_meaning:w + #1
17298     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_sub:wnw
17299   \else:
17300     \exp_after:wN \exp_after:wN \exp_after:wN \__fp_fixed_add:wnw
17301   \fi:
17302   #3 #2 ;
17303 }

```

(End definition for $\backslash_fp_ln_c:NwNw$.)

```

\__fp_ln_exponent:wn
\__fp_ln_exponent:wn
  {\langle s_1 \rangle} {\langle s_2 \rangle} {\langle s_3 \rangle} {\langle s_4 \rangle} {\langle s_5 \rangle} {\langle s_6 \rangle} ;
  {\langle exponent \rangle}

```

Compute $\langle exponent \rangle$ times $\ln(10)$. Apart from the cases where $\langle exponent \rangle$ is 0 or 1, the result is necessarily at least $\ln(10) \simeq 2.3$ in magnitude. We can thus drop the least significant 4 digits. In the case of a very large (positive or negative) exponent, we can (and we need to) drop 4 additional digits, since the result is of order 10^4 . Naively, one would think that in both cases we can drop 4 more digits than we do, but that would be slightly too tight for rounding to happen correctly. Besides, we already have addition and subtraction for 24 digits fixed point numbers.

```

17304 \cs_new:Npn \__fp_ln_exponent:wn #1; #2
17305 {
17306   \if_case:w #2 \exp_stop_f:
17307     0 \__fp_case_return:nw { \__fp_fixed_to_float_o:Nw 2 }
17308   \or:
17309     \exp_after:wN \__fp_ln_exponent_one:ww \int_value:w
17310   \else:
17311     \if_int_compare:w #2 > 0 \exp_stop_f:
17312       \exp_after:wN \__fp_ln_exponent_small:NNww
17313       \exp_after:wN 0
17314       \exp_after:wN \__fp_fixed_sub:wnw \int_value:w
17315     \else:
17316       \exp_after:wN \__fp_ln_exponent_small:NNww
17317       \exp_after:wN 2
17318       \exp_after:wN \__fp_fixed_add:wnw \int_value:w -
17319     \fi:
17320   \fi:
17321   #2; #1;
17322 }

```

Now we painfully write all the cases.¹⁰ No overflow nor underflow can happen, except when computing $\ln(1)$.

```

17323 \cs_new:Npn \__fp_ln_exponent_one:ww 1; #1;
17324 {
17325   0
17326   \exp_after:wN \__fp_fixed_sub:wnw \c__fp_ln_x_fixed_t1 #1;
17327   \__fp_fixed_to_float_o:wN 0
17328 }

```

¹⁰Bruno: do rounding.

For small exponents, we just drop one block of digits, and set the exponent of the log to 4 (minus any shift coming from leading zeros in the conversion from fixed point to floating point). Note that here the exponent has been made positive.

```

17329 \cs_new:Npn \__fp_ln_exponent_small:NNww #1#2#3; #4#5#6#7#8#9;
17330 {
17331     4
17332     \exp_after:wN \__fp_fixed_mul:wwn
17333     \c__fp_ln_x_fixed_tl
17334     {#3}{0000}{0000}{0000}{0000}{0000} ;
17335     #2
17336     {0000}{#4}{#5}{#6}{#7}{#8};
17337     \__fp_fixed_to_float_o:wN #1
17338 }

```

(End definition for __fp_ln_exponent:wn.)

31.2 Exponential

31.2.1 Sign, exponent, and special numbers

__fp_exp_o:w

```

17339 \cs_new:Npn \__fp_exp_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
17340 {
17341     \if_case:w #2 \exp_stop_f:
17342     \__fp_case_return_o:Nw \c_one_fp
17343     \or:
17344     \exp_after:wN \__fp_exp_normal_o:w
17345     \or:
17346     \if_meaning:w 0 #3
17347     \exp_after:wN \__fp_case_return_o:Nw
17348     \exp_after:wN \c_inf_fp
17349     \else:
17350     \exp_after:wN \__fp_case_return_o:Nw
17351     \exp_after:wN \c_zero_fp
17352     \fi:
17353     \or:
17354     \__fp_case_return_same_o:w
17355     \fi:
17356     \s__fp \__fp_chk:w #2#3#4;
17357 }

```

(End definition for __fp_exp_o:w.)

__fp_exp_normal_o:w

__fp_exp_pos_o:NNwnw

__fp_exp_overflow:NN

```

17358 \cs_new:Npn \__fp_exp_normal_o:w \s__fp \__fp_chk:w 1#1
17359 {
17360     \if_meaning:w 0 #1
17361     \__fp_exp_pos_o:NNwnw + \__fp_fixed_to_float_o:wN
17362     \else:
17363     \__fp_exp_pos_o:NNwnw - \__fp_fixed_inv_to_float_o:wN
17364     \fi:
17365 }
17366 \cs_new:Npn \__fp_exp_pos_o:NNwnw #1#2#3 \fi: #4#5;
17367 {

```

```

17368 \fi:
17369 \if_int_compare:w #4 > \c__fp_max_exp_exponent_int
17370 \token_if_eq_charcode:NNTF + #1
17371 { \__fp_exp_overflow:NN \__fp_overflow:w \c_inf_fp }
17372 { \__fp_exp_overflow:NN \__fp_underflow:w \c_zero_fp }
17373 \exp:w
17374 \else:
17375 \exp_after:wN \__fp_sanitize:Nw
17376 \exp_after:wN 0
17377 \int_value:w #1 \__fp_int_eval:w
17378 \if_int_compare:w #4 < 0 \exp_stop_f:
17379 \exp_after:wN \use_i:nn
17380 \else:
17381 \exp_after:wN \use_ii:nn
17382 \fi:
17383 {
17384 0
17385 \__fp_decimate:nNnnnn { - #4 }
17386 \__fp_exp_Taylor:Nnnwn
17387 }
17388 {
17389 \__fp_decimate:nNnnnn { \c__fp_prec_int - #4 }
17390 \__fp_exp_pos_large:NnnNwn
17391 }
17392 #5
17393 {#4}
17394 #1 #2 0
17395 \exp:w
17396 \fi:
17397 \exp_after:wN \exp_end:
17398 }
17399 \cs_new:Npn \__fp_exp_overflow:NN #1#2
17400 {
17401 \exp_after:wN \exp_after:wN
17402 \exp_after:wN #1
17403 \exp_after:wN #2
17404 }

```

(End definition for __fp_exp_normal_o:w, __fp_exp_pos_o:Nnnwn, and __fp_exp_overflow:NN.)

```

\__fp_exp_Taylor:Nnnwn
\__fp_exp_Taylor_loop:www
\__fp_exp_Taylor_break:Nww

```

This function is called for numbers in the range $[10^{-9}, 10^{-1}]$. We compute 10 terms of the Taylor series. The first argument is irrelevant (rounding digit used by some other functions). The next three arguments, at least 16 digits, delimited by a semicolon, form a fixed point number, so we pack it in blocks of 4 digits.

```

17405 \cs_new:Npn \__fp_exp_Taylor:Nnnwn #1#2#3 #4; #5 #6
17406 {
17407 #6
17408 \__fp_pack_twice_four:wNNNNNNNN
17409 \__fp_pack_twice_four:wNNNNNNNN
17410 \__fp_pack_twice_four:wNNNNNNNN
17411 \__fp_exp_Taylor_ii:ww
17412 ; #2#3#4 0000 0000 ;
17413 }
17414 \cs_new:Npn \__fp_exp_Taylor_ii:ww #1; #2;

```

```

17415 { \__fp_exp_Taylor_loop:www 10 ; #1 ; #1 ; \s_stop }
17416 \cs_new:Npn \__fp_exp_Taylor_loop:www #1; #2; #3;
17417 {
17418   \if_int_compare:w #1 = 1 \exp_stop_f:
17419   \exp_after:wN \__fp_exp_Taylor_break:Nww
17420   \fi:
17421   \__fp_fixed_div_int:wwN #3 ; #1 ;
17422   \__fp_fixed_add_one:wN
17423   \__fp_fixed_mul:wwN #2 ;
17424   {
17425     \exp_after:wN \__fp_exp_Taylor_loop:www
17426     \int_value:w \__fp_int_eval:w #1 - 1 ;
17427     #2 ;
17428   }
17429 }
17430 \cs_new:Npn \__fp_exp_Taylor_break:Nww #1 #2; #3 \s_stop
17431 { \__fp_fixed_add_one:wN #2 ; }

```

(End definition for __fp_exp_Taylor:Nnnwn, __fp_exp_Taylor_loop:www, and __fp_exp_Taylor-break:Nww.)

\c__fp_exp_intarray The integer array has $6 \times 9 \times 4 = 216$ items encoding the values of $\exp(j \times 10^i)$ for $j = 1, \dots, 9$ and $i = -1, \dots, 4$. Each value is expressed as $\simeq 10^p \times 0.m_1m_2m_3$ with three 8-digit blocks m_1, m_2, m_3 and an integer exponent p (one more than the scientific exponent), and these are stored in the integer array as four items: $p, 10^8 + m_1, 10^8 + m_2, 10^8 + m_3$. The various exponentials are stored in increasing order of $j \times 10^i$.

Storing this data in an integer array makes it slightly harder to access (slower, too), but uses 16 bytes of memory per exponential stored, while storing as tokens used around 40 tokens; tokens have an especially large footprint in Unicode-aware engines.

```

17432 \intarray_const_from_clist:Nn \c__fp_exp_intarray
17433 {
17434   1 , 1 1105 1709 , 1 1807 5647 , 1 6248 1171 ,
17435   1 , 1 1221 4027 , 1 5816 0169 , 1 8339 2107 ,
17436   1 , 1 1349 8588 , 1 0757 6003 , 1 1039 8374 ,
17437   1 , 1 1491 8246 , 1 9764 1270 , 1 3178 2485 ,
17438   1 , 1 1648 7212 , 1 7070 0128 , 1 1468 4865 ,
17439   1 , 1 1822 1188 , 1 0039 0508 , 1 9748 7537 ,
17440   1 , 1 2013 7527 , 1 0747 0476 , 1 5216 2455 ,
17441   1 , 1 2225 5409 , 1 2849 2467 , 1 6045 7954 ,
17442   1 , 1 2459 6031 , 1 1115 6949 , 1 6638 0013 ,
17443   1 , 1 2718 2818 , 1 2845 9045 , 1 2353 6029 ,
17444   1 , 1 7389 0560 , 1 9893 0650 , 1 2272 3043 ,
17445   2 , 1 2008 5536 , 1 9231 8766 , 1 7740 9285 ,
17446   2 , 1 5459 8150 , 1 0331 4423 , 1 9078 1103 ,
17447   3 , 1 1484 1315 , 1 9102 5766 , 1 0342 1116 ,
17448   3 , 1 4034 2879 , 1 3492 7351 , 1 2260 8387 ,
17449   4 , 1 1096 6331 , 1 5842 8458 , 1 5992 6372 ,
17450   4 , 1 2980 9579 , 1 8704 1728 , 1 2747 4359 ,
17451   4 , 1 8103 0839 , 1 2757 5384 , 1 0077 1000 ,
17452   5 , 1 2202 6465 , 1 7948 0671 , 1 6516 9579 ,
17453   9 , 1 4851 6519 , 1 5409 7902 , 1 7796 9107 ,
17454   14 , 1 1068 6474 , 1 5815 2446 , 1 2146 9905 ,
17455   18 , 1 2353 8526 , 1 6837 0199 , 1 8540 7900 ,
17456   22 , 1 5184 7055 , 1 2858 7072 , 1 4640 8745 ,

```

```

17457      27 , 1 1142 0073 , 1 8981 5684 , 1 2836 6296 ,
17458      31 , 1 2515 4386 , 1 7091 9167 , 1 0062 6578 ,
17459      35 , 1 5540 6223 , 1 8439 3510 , 1 0525 7117 ,
17460      40 , 1 1220 4032 , 1 9431 7840 , 1 8020 0271 ,
17461      44 , 1 2688 1171 , 1 4181 6135 , 1 4484 1263 ,
17462      87 , 1 7225 9737 , 1 6812 5749 , 1 2581 7748 ,
17463     131 , 1 1942 4263 , 1 9524 1255 , 1 9365 8421 ,
17464     174 , 1 5221 4696 , 1 8976 4143 , 1 9505 8876 ,
17465     218 , 1 1403 5922 , 1 1785 2837 , 1 4107 3977 ,
17466     261 , 1 3773 0203 , 1 0092 9939 , 1 8234 0143 ,
17467     305 , 1 1014 2320 , 1 5473 5004 , 1 5094 5533 ,
17468     348 , 1 2726 3745 , 1 7211 2566 , 1 5673 6478 ,
17469     391 , 1 7328 8142 , 1 2230 7421 , 1 7051 8866 ,
17470     435 , 1 1970 0711 , 1 1401 7046 , 1 9938 8888 ,
17471     869 , 1 3881 1801 , 1 9428 4368 , 1 5764 8232 ,
17472    1303 , 1 7646 2009 , 1 8905 4704 , 1 8893 1073 ,
17473    1738 , 1 1506 3559 , 1 7005 0524 , 1 9009 7592 ,
17474    2172 , 1 2967 6283 , 1 8402 3667 , 1 0689 6630 ,
17475    2606 , 1 5846 4389 , 1 5650 2114 , 1 7278 5046 ,
17476    3041 , 1 1151 7900 , 1 5080 6878 , 1 2914 4154 ,
17477    3475 , 1 2269 1083 , 1 0850 6857 , 1 8724 4002 ,
17478    3909 , 1 4470 3047 , 1 3316 5442 , 1 6408 6591 ,
17479    4343 , 1 8806 8182 , 1 2566 2921 , 1 5872 6150 ,
17480    8686 , 1 7756 0047 , 1 2598 6861 , 1 0458 3204 ,
17481   13029 , 1 6830 5723 , 1 7791 4884 , 1 1932 7351 ,
17482   17372 , 1 6015 5609 , 1 3095 3052 , 1 3494 7574 ,
17483   21715 , 1 5297 7951 , 1 6443 0315 , 1 3251 3576 ,
17484   26058 , 1 4665 6719 , 1 0099 3379 , 1 5527 2929 ,
17485   30401 , 1 4108 9724 , 1 3326 3186 , 1 5271 5665 ,
17486   34744 , 1 3618 6973 , 1 3140 0875 , 1 3856 4102 ,
17487   39087 , 1 3186 9209 , 1 6113 3900 , 1 6705 9685 ,
17488   }

```

(End definition for `c__fp_exp_intarray`.)

`__fp_exp_pos_large:NnnNwn` The first two arguments are irrelevant (a rounding digit, and a brace group with 8 zeros).
`__fp_exp_large_after:wnn` The third argument is the integer part of our number, then we have the decimal part
`__fp_exp_large:NwN` delimited by a semicolon, and finally the exponent, in the range $[0, 5]$. Remove leading
`__fp_exp_intarray:w` zeros from the integer part: putting `#4` in there too ensures that an integer part of 0 is
`__fp_exp_intarray_aux:w` also removed. Then read digits one by one, looking up $\exp(\langle digit \rangle \cdot 10^{\langle exponent \rangle})$ in a table,
and multiplying that to the current total. The loop is done by `__fp_exp_large:NwN`,
whose `#1` is the $\langle exponent \rangle$, `#2` is the current mantissa, and `#3` is the $\langle digit \rangle$. At the end,
`__fp_exp_large_after:wnn` moves on to the Taylor series, eventually multiplied with
the mantissa that we have just computed.

```

17489 \cs_new:Npn \__fp_exp_pos_large:NnnNwn #1#2#3 #4#5; #6
17490 {
17491   \exp_after:wN \exp_after:wN \exp_after:wN \__fp_exp_large:NwN
17492   \exp_after:wN \exp_after:wN \exp_after:wN #6
17493   \exp_after:wN \c__fp_one_fixed_tl
17494   \int_value:w #3 #4 \exp_stop_f:
17495   #5 00000 ;
17496 }
17497 \cs_new:Npn \__fp_exp_large:NwN #1#2; #3
17498 {

```

```

17499 \if_case:w #3 ~
17500 \exp_after:wN \__fp_fixed_continue:wn
17501 \else:
17502 \exp_after:wN \__fp_exp_intarray:w
17503 \int_value:w \__fp_int_eval:w 36 * #1 + 4 * #3 \exp_after:wN ;
17504 \fi:
17505 #2;
17506 {
17507 \if_meaning:w 0 #1
17508 \exp_after:wN \__fp_exp_large_after:wnn
17509 \else:
17510 \exp_after:wN \__fp_exp_large:NwN
17511 \int_value:w \__fp_int_eval:w #1 - 1 \exp_after:wN \scan_stop:
17512 \fi:
17513 }
17514 }
17515 \cs_new:Npn \__fp_exp_intarray:w #1 ;
17516 {
17517 +
17518 \__kernel_intarray_item:Nn \c__fp_exp_intarray
17519 { \__fp_int_eval:w #1 - 3 \scan_stop: }
17520 \exp_after:wN \use_i:nnn
17521 \exp_after:wN \__fp_fixed_mul:wnn
17522 \int_value:w 0
17523 \exp_after:wN \__fp_exp_intarray_aux:w
17524 \int_value:w \__kernel_intarray_item:Nn
17525 \c__fp_exp_intarray { \__fp_int_eval:w #1 - 2 }
17526 \exp_after:wN \__fp_exp_intarray_aux:w
17527 \int_value:w \__kernel_intarray_item:Nn
17528 \c__fp_exp_intarray { \__fp_int_eval:w #1 - 1 }
17529 \exp_after:wN \__fp_exp_intarray_aux:w
17530 \int_value:w \__kernel_intarray_item:Nn \c__fp_exp_intarray {#1} ; ;
17531 }
17532 \cs_new:Npn \__fp_exp_intarray_aux:w 1 #1#2#3#4#5 ; { ; {#1#2#3#4} {#5} }
17533 \cs_new:Npn \__fp_exp_large_after:wnn #1; #2; #3
17534 {
17535 \__fp_exp_Taylor:Nnnwn ? { } { } 0 #2; {} #3
17536 \__fp_fixed_mul:wnn #1;
17537 }

```

(End definition for __fp_exp_pos_large:NnnNwn and others.)

31.3 Power

Raising a number a to a power b leads to many distinct situations.

a^b	$-\infty$	$(-\infty, -0)$	$-\text{integer}$	± 0	$+\text{integer}$	$(0, \infty)$	$+\infty$	NaN
$+\infty$	$+0$		$+0$	$+1$	$+\infty$		$+\infty$	NaN
$(1, \infty)$	$+0$		$+ a ^b$	$+1$	$+ a ^b$		$+\infty$	NaN
$+1$	$+1$		$+1$	$+1$	$+1$		$+1$	$+1$
$(0, 1)$	$+\infty$		$+ a ^b$	$+1$	$+ a ^b$		$+0$	NaN
$+0$	$+\infty$		$+\infty$	$+1$	$+0$		$+0$	NaN
-0	$+\infty$	NaN	$(-1)^b \infty$	$+1$	$(-1)^b 0$	$+0$	$+0$	NaN
$(-1, 0)$	$+\infty$	NaN	$(-1)^b a ^b$	$+1$	$(-1)^b a ^b$	NaN	$+0$	NaN
-1	$+1$	NaN	$(-1)^b$	$+1$	$(-1)^b$	NaN	$+1$	NaN
$(-\infty, -1)$	$+0$	NaN	$(-1)^b a ^b$	$+1$	$(-1)^b a ^b$	NaN	$+\infty$	NaN
$-\infty$	$+0$	$+0$	$(-1)^b 0$	$+1$	$(-1)^b \infty$	NaN	$+\infty$	NaN
NaN	NaN	NaN	NaN	$+1$	NaN	NaN	NaN	NaN

We distinguished in this table the cases of finite (positive or negative) integer exponents, as $(-1)^b$ is defined in that case. One peculiarity of this operation is that $\text{NaN}^0 = 1^{\text{NaN}} = 1$, because this relation is obeyed for any number, even $\pm\infty$.

`_fp_o:ww` We cram most of the tests into a single function to save csnames. First treat the case $b = 0$: $a^0 = 1$ for any a , even nan . Then test the sign of a .

- If it is positive, and a is a normal number, call `_fp_pow_normal_o:ww` followed by the two `fp` a and b . For $a = +0$ or $+\text{inf}$, call `_fp_pow_zero_or_inf:ww` instead, to return either $+0$ or $+\infty$ as appropriate.
- If a is a `nan`, then skip to the next semicolon (which happens to be conveniently the end of b) and return `nan`.
- Finally, if a is negative, compute a^b (`_fp_pow_normal_o:ww` which ignores the sign of its first operand), and keep an extra copy of a and b (the second brace group, containing $\{ b a \}$, is inserted between a and b). Then do some tests to find the final sign of the result if it exists.

```

17538 \cs_new:cpn { \_fp\_ \iow_char:N \^ \_o:ww }
17539   \s\_fp \_fp\_chk:w #1#2#3; \s\_fp \_fp\_chk:w #4#5#6;
17540   {
17541     \if_meaning:w 0 #4
17542       \_fp\_case\_return_o:Nw \c\_one\_fp
17543     \fi:
17544     \if_case:w #2 \exp\_stop\_f:
17545       \exp\_after:wN \use\_i:nn
17546     \or:
17547       \_fp\_case\_return_o:Nw \c\_nan\_fp
17548     \else:
17549       \exp\_after:wN \_fp\_pow\_neg:www
17550       \exp:w \exp\_end\_continue\_f:w \exp\_after:wN \use:nn
17551     \fi:
17552     {
17553       \if_meaning:w 1 #1
17554         \exp\_after:wN \_fp\_pow\_normal_o:ww
17555       \else:
17556         \exp\_after:wN \_fp\_pow\_zero\_or\_inf:ww
17557       \fi:
17558       \s\_fp \_fp\_chk:w #1#2#3;
17559     }

```

```

17560     { \s__fp \__fp_chk:w #4#5#6; \s__fp \__fp_chk:w #1#2#3; }
17561     \s__fp \__fp_chk:w #4#5#6;
17562   }

```

(End definition for __fp_~o:ww.)

__fp_pow_zero_or_inf:ww Raising -0 or $-\infty$ to `nan` yields `nan`. For other powers, the result is $+0$ if 0 is raised to a positive power or ∞ to a negative power, and $+\infty$ otherwise. Thus, if the type of a and the sign of b coincide, the result is 0 , since those conveniently take the same possible values, 0 and 2 . Otherwise, either $a = \pm\infty$ and $b > 0$ and the result is $+\infty$, or $a = \pm 0$ with $b < 0$ and we have a division by zero unless $b = -\infty$.

```

17563 \cs_new:Npn \__fp_pow_zero_or_inf:ww
17564   \s__fp \__fp_chk:w #1#2; \s__fp \__fp_chk:w #3#4
17565   {
17566     \if_meaning:w 1 #4
17567       \__fp_case_return_same_o:w
17568     \fi:
17569     \if_meaning:w #1 #4
17570       \__fp_case_return_o:Nw \c_zero_fp
17571     \fi:
17572     \if_meaning:w 2 #1
17573       \__fp_case_return_o:Nw \c_inf_fp
17574     \fi:
17575     \if_meaning:w 2 #3
17576       \__fp_case_return_o:Nw \c_inf_fp
17577     \else:
17578       \__fp_case_use:nw
17579       {
17580         \__fp_division_by_zero_o:NNww \c_inf_fp ^
17581         \s__fp \__fp_chk:w #1 #2 ;
17582       }
17583     \fi:
17584     \s__fp \__fp_chk:w #3#4
17585   }

```

(End definition for __fp_pow_zero_or_inf:ww.)

__fp_pow_normal_o:ww We have in front of us a , and $b \neq 0$, we know that a is a normal number, and we wish to compute $|a|^b$. If $|a| = 1$, we return 1 , unless $a = -1$ and b is `nan`. Indeed, returning 1 at this point would wrongly raise “invalid” when the sign is considered. If $|a| \neq 1$, test the type of b :

- 0 Impossible, we already filtered $b = \pm 0$.
- 1 Call `__fp_pow_npos_o:Nww`.
- 2 Return $+\infty$ or $+0$ depending on the sign of b and whether the exponent of a is positive or not.
- 3 Return b .

```

17586 \cs_new:Npn \__fp_pow_normal_o:ww
17587   \s__fp \__fp_chk:w 1 #1#2#3; \s__fp \__fp_chk:w #4#5
17588   {
17589     \if_int_compare:w \__fp_str_if_eq:nn { #2 #3 }

```

```

17590         { 1 {1000} {0000} {0000} {0000} } = 0 \exp_stop_f:
17591     \if_int_compare:w #4 #1 = 32 \exp_stop_f:
17592     \exp_after:wN \__fp_case_return_ii_o:ww
17593     \fi:
17594     \__fp_case_return_o:Nww \c_one_fp
17595 \fi:
17596 \if_case:w #4 \exp_stop_f:
17597 \or:
17598     \exp_after:wN \__fp_pow_npos_o:Nww
17599     \exp_after:wN #5
17600 \or:
17601     \if_meaning:w 2 #5 \exp_after:wN \reverse_if:N \fi:
17602     \if_int_compare:w #2 > 0 \exp_stop_f:
17603     \exp_after:wN \__fp_case_return_o:Nww
17604     \exp_after:wN \c_inf_fp
17605 \else:
17606     \exp_after:wN \__fp_case_return_o:Nww
17607     \exp_after:wN \c_zero_fp
17608 \fi:
17609 \or:
17610     \__fp_case_return_ii_o:ww
17611 \fi:
17612 \s__fp \__fp_chk:w 1 #1 {#2} #3 ;
17613 \s__fp \__fp_chk:w #4 #5
17614 }

```

(End definition for __fp_pow_normal_o:ww.)

__fp_pow_npos_o:Nww

We now know that $a \neq \pm 1$ is a normal number, and b is a normal number too. We want to compute $|a|^b = (|x| \cdot 10^n)^{y \cdot 10^p} = \exp((\ln|x| + n \ln(10)) \cdot y \cdot 10^p) = \exp(z)$. To compute the exponential accurately, we need to know the digits of z up to the 16-th position. Since the exponential of 10^5 is infinite, we only need at most 21 digits, hence the fixed point result of __fp_ln_o:w is precise enough for our needs. Start an integer expression for the decimal exponent of $e^{|z|}$. If z is negative, negate that decimal exponent, and prepare to take the inverse when converting from the fixed point to the floating point result.

```

17615 \cs_new:Npn \__fp_pow_npos_o:Nww #1 \s__fp \__fp_chk:w 1#2#3
17616 {
17617     \exp_after:wN \__fp_sanitize:Nw
17618     \exp_after:wN 0
17619     \int_value:w
17620     \if:w #1 \if_int_compare:w #3 > 0 \exp_stop_f: 0 \else: 2 \fi:
17621     \exp_after:wN \__fp_pow_npos_aux:NNnw
17622     \exp_after:wN +
17623     \exp_after:wN \__fp_fixed_to_float_o:wN
17624 \else:
17625     \exp_after:wN \__fp_pow_npos_aux:NNnw
17626     \exp_after:wN -
17627     \exp_after:wN \__fp_fixed_inv_to_float_o:wN
17628 \fi:
17629 {#3}
17630 }

```

(End definition for __fp_pow_npos_o:Nww.)

__fp_pow_npos_aux:NNnw The first argument is the conversion function from fixed point to float. Then comes an exponent and the 4 brace groups of x , followed by b . Compute $-\ln(x)$.

```

17631 \cs_new:Npn \__fp_pow_npos_aux:NNnw #1#2#3#4#5; \s_fp \__fp_chk:w 1#6#7#8;
17632 {
17633   #1
17634   \__fp_int_eval:w
17635   \__fp_ln_significand:NNNNnnN #4#5
17636   \__fp_pow_exponent:wnN {#3}
17637   \__fp_fixed_mul:wn #8 {0000}{0000} ;
17638   \__fp_pow_B:wn #7;
17639   #1 #2 0 % fixed_to_float_o:wn
17640 }
17641 \cs_new:Npn \__fp_pow_exponent:wnN #1; #2
17642 {
17643   \if_int_compare:w #2 > 0 \exp_stop_f:
17644     \exp_after:wN \__fp_pow_exponent:Nwnnnnw % n\ln(10) - (-\ln(x))
17645     \exp_after:wN +
17646   \else:
17647     \exp_after:wN \__fp_pow_exponent:Nwnnnnw % -(\ln|\ln(10) + (-\ln(x)))
17648     \exp_after:wN -
17649   \fi:
17650   #2; #1;
17651 }
17652 \cs_new:Npn \__fp_pow_exponent:Nwnnnnw #1#2; #3#4#5#6#7#8;
17653 { %^A todo: use that in ln.
17654   \exp_after:wN \__fp_fixed_mul_after:wn
17655   \int_value:w \__fp_int_eval:w \c__fp_leading_shift_int
17656   \exp_after:wN \__fp_pack:NNNNNw
17657   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
17658   #1#2*23025 - #1 #3
17659   \exp_after:wN \__fp_pack:NNNNNw
17660   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
17661   #1 #2*8509 - #1 #4
17662   \exp_after:wN \__fp_pack:NNNNNw
17663   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
17664   #1 #2*2994 - #1 #5
17665   \exp_after:wN \__fp_pack:NNNNNw
17666   \int_value:w \__fp_int_eval:w \c__fp_middle_shift_int
17667   #1 #2*0456 - #1 #6
17668   \exp_after:wN \__fp_pack:NNNNNw
17669   \int_value:w \__fp_int_eval:w \c__fp_trailing_shift_int
17670   #1 #2*8401 - #1 #7
17671   #1 ( #2*7991 - #8 ) / 1 0000 ; ;
17672 }
17673 \cs_new:Npn \__fp_pow_B:wnN #1#2#3#4#5#6; #7;
17674 {
17675   \if_int_compare:w #7 < 0 \exp_stop_f:
17676     \exp_after:wN \__fp_pow_C_neg:w \int_value:w -
17677   \else:
17678     \if_int_compare:w #7 < 22 \exp_stop_f:
17679       \exp_after:wN \__fp_pow_C_pos:w \int_value:w
17680     \else:
17681       \exp_after:wN \__fp_pow_C_overflow:w \int_value:w
17682     \fi:

```

```

17683 \fi:
17684 #7 \exp_after:wN ;
17685 \int_value:w \__fp_int_eval:w 10 0000 + #1 \__fp_int_eval_end:
17686 #2#3#4#5#6 0000 0000 0000 0000 0000 0000 ; %^A todo: how many 0?
17687 }
17688 \cs_new:Npn \__fp_pow_C_overflow:w #1; #2; #3
17689 {
17690 + 2 * \c__fp_max_exponent_int
17691 \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_tl
17692 }
17693 \cs_new:Npn \__fp_pow_C_neg:w #1 ; 1
17694 {
17695 \exp_after:wN \exp_after:wN \exp_after:wN \__fp_pow_C_pack:w
17696 \prg_replicate:nn {#1} {0}
17697 }
17698 \cs_new:Npn \__fp_pow_C_pos:w #1; 1
17699 { \__fp_pow_C_pos_loop:wN #1; }
17700 \cs_new:Npn \__fp_pow_C_pos_loop:wN #1; #2
17701 {
17702 \if_meaning:w 0 #1
17703 \exp_after:wN \__fp_pow_C_pack:w
17704 \exp_after:wN #2
17705 \else:
17706 \if_meaning:w 0 #2
17707 \exp_after:wN \__fp_pow_C_pos_loop:wN \int_value:w
17708 \else:
17709 \exp_after:wN \__fp_pow_C_overflow:w \int_value:w
17710 \fi:
17711 \__fp_int_eval:w #1 - 1 \exp_after:wN ;
17712 \fi:
17713 }
17714 \cs_new:Npn \__fp_pow_C_pack:w
17715 {
17716 \exp_after:wN \__fp_exp_large:NwN
17717 \exp_after:wN 5
17718 \c__fp_one_fixed_tl
17719 }

```

(End definition for __fp_pow_npos_aux:NNnww.)

__fp_pow_neg:www
__fp_pow_neg_aux:wNN

This function is followed by three floating point numbers: a^b , $a \in [-\infty, -0]$, and b . If b is an even integer (case -1), $a^b = a^b$. If b is an odd integer (case 0), $a^b = -a^b$, obtained by a call to __fp_pow_neg_aux:wNN. Otherwise, the sign is undefined. This is invalid, unless a^b turns out to be +0 or nan, in which case we return that as a^b . In particular, since the underflow detection occurs before __fp_pow_neg:www is called, $(-0.1)**(12345.67)$ gives +0 rather than complaining that the sign is not defined.

```

17720 \cs_new:Npn \__fp_pow_neg:www \s__fp \__fp_chk:w #1#2; #3; #4;
17721 {
17722 \if_case:w \__fp_pow_neg_case:w #4 ;
17723 \exp_after:wN \__fp_pow_neg_aux:wNN
17724 \or:
17725 \if_int_compare:w \__fp_int_eval:w #1 / 2 = 1 \exp_stop_f:
17726 \__fp_invalid_operation_o:Nww ^ #3; #4;
17727 \exp:w \exp_end_continue_f:w

```

```

17728         \exp_after:wN \exp_after:wN
17729         \exp_after:wN \__fp_use_none_until_s:w
17730         \fi:
17731     \fi:
17732     \__fp_exp_after_o:w
17733     \s__fp \__fp_chk:w #1#2;
17734 }
17735 \cs_new:Npn \__fp_pow_neg_aux:wNN #1 \s__fp \__fp_chk:w #2#3
17736 {
17737     \exp_after:wN \__fp_exp_after_o:w
17738     \exp_after:wN \s__fp
17739     \exp_after:wN \__fp_chk:w
17740     \exp_after:wN #2
17741     \int_value:w \__fp_int_eval:w 2 - #3 \__fp_int_eval_end:
17742 }

```

(End definition for __fp_pow_neg:www and __fp_pow_neg_aux:wNN.)

__fp_pow_neg_case:w This function expects a floating point number, and determines its “parity”. It should be used after \if_case:w or in an integer expression. It gives -1 if the number is an even integer, 0 if the number is an odd integer, and 1 otherwise. Zeros and $\pm\infty$ are even (because very large finite floating points are even), while `nan` is a non-integer. The sign of normal numbers is irrelevant to parity. After __fp_decimate:nNnnnn the argument `#1` of __fp_pow_neg_case_aux:Nnnw is a rounding digit, 0 if and only if the number was an integer, and `#3` is the 8 least significant digits of that integer.

```

17743 \cs_new:Npn \__fp_pow_neg_case:w \s__fp \__fp_chk:w #1#2#3;
17744 {
17745     \if_case:w #1 \exp_stop_f:
17746         -1
17747     \or: \__fp_pow_neg_case_aux:nnnnn #3
17748     \or: -1
17749     \else: 1
17750     \fi:
17751     \exp_stop_f:
17752 }
17753 \cs_new:Npn \__fp_pow_neg_case_aux:nnnnn #1#2#3#4#5
17754 {
17755     \if_int_compare:w #1 > \c__fp_prec_int
17756         -1
17757     \else:
17758         \__fp_decimate:nNnnnn { \c__fp_prec_int - #1 }
17759         \__fp_pow_neg_case_aux:Nnnw
17760         {#2} {#3} {#4} {#5}
17761     \fi:
17762 }
17763 \cs_new:Npn \__fp_pow_neg_case_aux:Nnnw #1#2#3#4 ;
17764 {
17765     \if_meaning:w 0 #1
17766         \if_int_odd:w #3 \exp_stop_f:
17767         0
17768     \else:
17769         -1
17770     \fi:
17771     \else:

```

```

17772      1
17773      \fi:
17774    }

```

(End definition for `_fp_pow_neg_case:w`, `_fp_pow_neg_case_aux:nnnnn`, and `_fp_pow_neg_case_aux:Nnnw`.)

```

17775 </initex | package>

```

32 l3fp-trig Implementation

```

17776 <*initex | package>

```

```

17777 <@@=fp>

```

Unary functions.

```

\__fp_parse_word_acos:N
\__fp_parse_word_acosd:N
\__fp_parse_word_acsc:N
\__fp_parse_word_acscd:N
\__fp_parse_word_asec:N
\__fp_parse_word_asecd:N
\__fp_parse_word_asin:N
\__fp_parse_word_asind:N
\__fp_parse_word_cos:N
\__fp_parse_word_cosd:N
\__fp_parse_word_cot:N
\__fp_parse_word_cotd:N
\__fp_parse_word_csc:N
\__fp_parse_word_cscd:N
\__fp_parse_word_sec:N
\__fp_parse_word_secd:N
\__fp_parse_word_sin:N
\__fp_parse_word_sind:N
\__fp_parse_word_tan:N
\__fp_parse_word_tand:N
17778 \tl_map_inline:nn
17779 {
17780   {acos} {acsc} {asec} {asin}
17781   {cos} {cot} {csc} {sec} {sin} {tan}
17782 }
17783 {
17784   \cs_new:cpx { __fp_parse_word_#1:N }
17785   {
17786     \exp_not:N \__fp_parse_unary_function:NNN
17787     \exp_not:c { __fp_#1_o:w }
17788     \exp_not:N \use_i:nn
17789   }
17790   \cs_new:cpx { __fp_parse_word_#1d:N }
17791   {
17792     \exp_not:N \__fp_parse_unary_function:NNN
17793     \exp_not:c { __fp_#1_o:w }
17794     \exp_not:N \use_ii:nn
17795   }
17796 }

```

(End definition for `_fp_parse_word_acos:N` and others.)

Those functions may receive a variable number of arguments.

```

\__fp_parse_word_acot:N
\__fp_parse_word_acotd:N
\__fp_parse_word_atan:N
\__fp_parse_word_atand:N
17797 \cs_new:Npn \__fp_parse_word_acot:N
17798 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_i:nn }
17799 \cs_new:Npn \__fp_parse_word_acotd:N
17800 { \__fp_parse_function:NNN \__fp_acot_o:Nw \use_ii:nn }
17801 \cs_new:Npn \__fp_parse_word_atan:N
17802 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_i:nn }
17803 \cs_new:Npn \__fp_parse_word_atand:N
17804 { \__fp_parse_function:NNN \__fp_atan_o:Nw \use_ii:nn }

```

(End definition for `_fp_parse_word_acot:N` and others.)

32.1 Direct trigonometric functions

The approach for all trigonometric functions (sine, cosine, tangent, cotangent, cosecant, and secant), with arguments given in radians or in degrees, is the same.

- Filter out special cases (± 0 , $\pm \infty$ and NaN).
- Keep the sign for later, and work with the absolute value $|x|$ of the argument.
- Small numbers ($|x| < 1$ in radians, $|x| < 10$ in degrees) are converted to fixed point numbers (and to radians if $|x|$ is in degrees).
- For larger numbers, we need argument reduction. Subtract a multiple of $\pi/2$ (in degrees, 90) to bring the number to the range to $[0, \pi/2)$ (in degrees, $[0, 90)$).
- Reduce further to $[0, \pi/4]$ (in degrees, $[0, 45]$) using $\sin x = \cos(\pi/2 - x)$, and when working in degrees, convert to radians.
- Use the appropriate power series depending on the octant $\lfloor \frac{x}{\pi/4} \rfloor \bmod 8$ (in degrees, the same formula with $\pi/4 \rightarrow 45$), the sign, and the function to compute.

32.1.1 Filtering special cases

`__fp_sin_o:w` This function, and its analogs for `cos`, `csc`, `sec`, `tan`, and `cot` instead of `sin`, are followed either by `\use_i:nn` and a float in radians or by `\use_ii:nn` and a float in degrees. The sine of ± 0 or NaN is the same float. The sine of $\pm \infty$ raises an invalid operation exception with the appropriate function name. Otherwise, call the `trig` function to perform argument reduction and if necessary convert the reduced argument to radians. Then, `__fp_sin_series_o:NNwww` is called to compute the Taylor series: this function receives a sign `#3`, an initial octant of 0, and the function `__fp_ep_to_float_o:wwN` which converts the result of the series to a floating point directly rather than taking its inverse, since $\sin(x) = \#3 \sin|x|$.

```

17805 \cs_new:Npn \__fp_sin_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
17806 {
17807     \if_case:w #2 \exp_stop_f:
17808         \__fp_case_return_same_o:w
17809     \or: \__fp_case_use:nw
17810         {
17811             \__fp_trig:NNNNwn #1 \__fp_sin_series_o:NNwww
17812             \__fp_ep_to_float_o:wwN #3 0
17813         }
17814     \or: \__fp_case_use:nw
17815         { \__fp_invalid_operation_o:fw { #1 { sin } { sind } } }
17816     \else: \__fp_case_return_same_o:w
17817     \fi:
17818     \s__fp \__fp_chk:w #2 #3 #4;
17819 }
```

(End definition for `__fp_sin_o:w`.)

`__fp_cos_o:w` The cosine of ± 0 is 1. The cosine of $\pm \infty$ raises an invalid operation exception. The cosine of NaN is itself. Otherwise, the `trig` function reduces the argument to at most half a right-angle and converts if necessary to radians. We then call the same series as

for sine, but using a positive sign 0 regardless of the sign of x , and with an initial octant of 2, because $\cos(x) = +\sin(\pi/2 + |x|)$.

```

17820 \cs_new:Npn \__fp_cos_o:w #1 \s__fp \__fp_chk:w #2#3; @
17821 {
17822   \if_case:w #2 \exp_stop_f:
17823     \__fp_case_return_o:Nw \c_one_fp
17824   \or: \__fp_case_use:nw
17825     {
17826       \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
17827       \__fp_ep_to_float_o:wwN 0 2
17828     }
17829   \or: \__fp_case_use:nw
17830     { \__fp_invalid_operation_o:fw { #1 { cos } { cosd } } }
17831   \else: \__fp_case_return_same_o:w
17832   \fi:
17833   \s__fp \__fp_chk:w #2 #3;
17834 }

```

(End definition for $\backslash_fp_cos_o:w$.)

$\backslash_fp_csc_o:w$ The cosecant of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see $\backslash_fp_cot_zero_o:Nfw$ defined below), which requires the function name. The cosecant of $\pm\infty$ raises an invalid operation exception. The cosecant of NaN is itself. Otherwise, the `trig` function performs the argument reduction, and converts if necessary to radians before calling the same series as for sine, using the sign #3, a starting octant of 0, and inverting during the conversion from the fixed point sine to the floating point result, because $\csc(x) = \#3(\sin|x|)^{-1}$.

```

17835 \cs_new:Npn \__fp_csc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
17836 {
17837   \if_case:w #2 \exp_stop_f:
17838     \__fp_cot_zero_o:Nfw #3 { #1 { csc } { cscd } }
17839   \or: \__fp_case_use:nw
17840     {
17841       \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
17842       \__fp_ep_inv_to_float_o:wwN #3 0
17843     }
17844   \or: \__fp_case_use:nw
17845     { \__fp_invalid_operation_o:fw { #1 { csc } { cscd } } }
17846   \else: \__fp_case_return_same_o:w
17847   \fi:
17848   \s__fp \__fp_chk:w #2 #3 #4;
17849 }

```

(End definition for $\backslash_fp_csc_o:w$.)

$\backslash_fp_sec_o:w$ The secant of ± 0 is 1. The secant of $\pm\infty$ raises an invalid operation exception. The secant of NaN is itself. Otherwise, the `trig` function reduces the argument and turns it to radians before calling the same series as for sine, using a positive sign 0, a starting octant of 2, and inverting upon conversion, because $\sec(x) = +1/\sin(\pi/2 + |x|)$.

```

17850 \cs_new:Npn \__fp_sec_o:w #1 \s__fp \__fp_chk:w #2#3; @
17851 {
17852   \if_case:w #2 \exp_stop_f:
17853     \__fp_case_return_o:Nw \c_one_fp

```

```

17854 \or: \__fp_case_use:nw
17855 {
17856     \__fp_trig:NNNNNwn #1 \__fp_sin_series_o:NNwww
17857     \__fp_ep_inv_to_float_o:wwN 0 2
17858 }
17859 \or: \__fp_case_use:nw
17860 { \__fp_invalid_operation_o:fw { #1 { sec } { secd } } }
17861 \else: \__fp_case_return_same_o:w
17862 \fi:
17863 \s__fp \__fp_chk:w #2 #3;
17864 }

```

(End definition for __fp_sec_o:w.)

__fp_tan_o:w The tangent of ± 0 or NaN is the same floating point number. The tangent of $\pm\infty$ raises an invalid operation exception. Once more, the `trig` function does the argument reduction step and conversion to radians before calling `__fp_tan_series_o:NNwww`, with a sign #3 and an initial octant of 1 (this shift is somewhat arbitrary). See `__fp_cot_o:w` for an explanation of the 0 argument.

```

17865 \cs_new:Npn \__fp_tan_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
17866 {
17867     \if_case:w #2 \exp_stop_f:
17868         \__fp_case_return_same_o:w
17869     \or: \__fp_case_use:nw
17870         {
17871             \__fp_trig:NNNNNwn #1
17872             \__fp_tan_series_o:NNwww 0 #3 1
17873         }
17874     \or: \__fp_case_use:nw
17875         { \__fp_invalid_operation_o:fw { #1 { tan } { tand } } }
17876     \else: \__fp_case_return_same_o:w
17877     \fi:
17878     \s__fp \__fp_chk:w #2 #3 #4;
17879 }

```

(End definition for __fp_tan_o:w.)

__fp_cot_o:w The cotangent of ± 0 is $\pm\infty$ with the same sign, with a division by zero exception (see `__fp_cot_zero_o:Nfw`). The cotangent of $\pm\infty$ raises an invalid operation exception. The cotangent of NaN is itself. We use $\cot x = -\tan(\pi/2 + x)$, and the initial octant for the tangent was chosen to be 1, so the octant here starts at 3. The change in sign is obtained by feeding `__fp_tan_series_o:NNwww` two signs rather than just the sign of the argument: the first of those indicates whether we compute tangent or cotangent. Those signs are eventually combined.

```

17880 \cs_new:Npn \__fp_cot_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
17881 {
17882     \if_case:w #2 \exp_stop_f:
17883         \__fp_cot_zero_o:Nfw #3 { #1 { cot } { cotd } }
17884     \or: \__fp_case_use:nw
17885         {
17886             \__fp_trig:NNNNNwn #1
17887             \__fp_tan_series_o:NNwww 2 #3 3
17888         }
17889     \or: \__fp_case_use:nw

```

```

17890         { \__fp_invalid_operation_o:fw { #1 { cot } { cotd } } }
17891     \else: \__fp_case_return_same_o:w
17892     \fi:
17893     \s__fp \__fp_chk:w #2 #3 #4;
17894 }
17895 \cs_new:Npn \__fp_cot_zero_o:Nfw #1#2#3 \fi:
17896 {
17897     \fi:
17898     \token_if_eq_meaning:NNTF 0 #1
17899     { \exp_args:NNf \__fp_division_by_zero_o:Nnw \c_inf_fp }
17900     { \exp_args:NNf \__fp_division_by_zero_o:Nnw \c_minus_inf_fp }
17901     {#2}
17902 }

```

(End definition for __fp_cot_o:w and __fp_cot_zero_o:Nfw.)

32.1.2 Distinguishing small and large arguments

__fp_trig:NNNNNwn The first argument is \use_i:nn if the operand is in radians and \use_ii:nn if it is in degrees. Arguments #2 to #5 control what trigonometric function we compute, and #6 to #8 are pieces of a normal floating point number. Call the `_series` function #2, with arguments #3, either a conversion function (`__fp_ep_to_float_o:wN` or `__fp_ep_inv_to_float_o:wN`) or a sign 0 or 2 when computing tangent or cotangent; #4, a sign 0 or 2; the octant, computed in an integer expression starting with #5 and stopped by a period; and a fixed point number obtained from the floating point number by argument reduction (if necessary) and conversion to radians (if necessary). Any argument reduction adjusts the octant accordingly by leaving a (positive) shift into its integer expression. Let us explain the integer comparison. Two of the four `\exp_after:wN` are expanded, the expansion hits the test, which is true if the float is at least 1 when working in radians, and at least 10 when working in degrees. Then one of the remaining `\exp_after:wN` hits #1, which picks the `trig` or `trigd` function in whichever branch of the conditional was taken. The final `\exp_after:wN` closes the conditional. At the end of the day, a number is `large` if it is ≥ 1 in radians or ≥ 10 in degrees, and `small` otherwise. All four `trig/trigd` auxiliaries receive the operand as an extended-precision number.

```

17903 \cs_new:Npn \__fp_trig:NNNNNwn #1#2#3#4#5 \s__fp \__fp_chk:w 1#6#7#8;
17904 {
17905     \exp_after:wN #2
17906     \exp_after:wN #3
17907     \exp_after:wN #4
17908     \int_value:w \__fp_int_eval:w #5
17909     \exp_after:wN \exp_after:wN \exp_after:wN \exp_after:wN
17910     \if_int_compare:w #7 > #1 0 1 \exp_stop_f:
17911     #1 \__fp_trig_large:ww \__fp_trigd_large:ww
17912     \else:
17913     #1 \__fp_trig_small:ww \__fp_trigd_small:ww
17914     \fi:
17915     #7,#8{0000}{0000};
17916 }

```

(End definition for __fp_trig:NNNNNwn.)

32.1.3 Small arguments

`__fp_trig_small:ww` This receives a small extended-precision number in radians and converts it to a fixed point number. Some trailing digits may be lost in the conversion, so we keep the original floating point number around: when computing sine or tangent (or their inverses), the last step is to multiply by the floating point number (as an extended-precision number) rather than the fixed point number. The period serves to end the integer expression for the octant.

```
17917 \cs_new:Npn \__fp_trig_small:ww #1,#2;
17918 { \__fp_ep_to_fixed:wwn #1,#2; . #1,#2; }
```

(End definition for `__fp_trig_small:ww`.)

`__fp_trigd_small:ww` Convert the extended-precision number to radians, then call `__fp_trig_small:ww` to massage it in the form appropriate for the `_series` auxiliary.

```
17919 \cs_new:Npn \__fp_trigd_small:ww #1,#2;
17920 {
17921   \__fp_ep_mul_raw:wwwN
17922   -1,{1745}{3292}{5199}{4329}{5769}{2369}; #1,#2;
17923   \__fp_trig_small:ww
17924 }
```

(End definition for `__fp_trigd_small:ww`.)

32.1.4 Argument reduction in degrees

`__fp_trigd_large:ww` Note that $25 \times 360 = 9000$, so $10^{k+1} \equiv 10^k \pmod{360}$ for $k \geq 3$. When the exponent `#1` is very large, we can thus safely replace it by 22 (or even 19). We turn the floating point number into a fixed point number with two blocks of 8 digits followed by five blocks of 4 digits. The original float is $100 \times \langle block_1 \rangle \cdots \langle block_3 \rangle . \langle block_4 \rangle \cdots \langle block_7 \rangle$, or is equal to it modulo 360 if the exponent `#1` is very large. The first auxiliary finds $\langle block_1 \rangle + \langle block_2 \rangle \pmod{9}$, a single digit, and prepends it to the 4 digits of $\langle block_3 \rangle$. It also unpacks $\langle block_4 \rangle$ and grabs the 4 digits of $\langle block_7 \rangle$. The second auxiliary grabs the $\langle block_3 \rangle$ plus any contribution from the first two blocks as `#1`, the first digit of $\langle block_4 \rangle$ (just after the decimal point in hundreds of degrees) as `#2`, and the three other digits as `#3`. It finds the quotient and remainder of `#1#2` modulo 9, adds twice the quotient to the integer expression for the octant, and places the remainder (between 0 and 8) before `#3` to form a new $\langle block_4 \rangle$. The resulting fixed point number is $x \in [0, 0.9]$. If $x \geq 0.45$, we add 1 to the octant and feed $0.9 - x$ with an exponent of 2 (to compensate the fact that we are working in units of hundreds of degrees rather than degrees) to `__fp_trigd_small:ww`. Otherwise, we feed it x with an exponent of 2. The third auxiliary also discards digits which were not packed into the various $\langle blocks \rangle$. Since the original exponent `#1` is at least 2, those are all 0 and no precision is lost (`#6` and `#7` are four 0 each).

```
17925 \cs_new:Npn \__fp_trigd_large:ww #1, #2#3#4#5#6#7;
17926 {
17927   \exp_after:wN \__fp_pack_eight:wNNNNNNNN
17928   \exp_after:wN \__fp_pack_eight:wNNNNNNNN
17929   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
17930   \exp_after:wN \__fp_pack_twice_four:wNNNNNNNN
17931   \exp_after:wN \__fp_trigd_large_auxi:nnnnwNNNN
17932   \exp_after:wN ;
17933   \exp:w \exp_end_continue_f:w
```

```

17934     \prg_replicate:nn { \int_max:nn { 22 - #1 } { 0 } } { 0 }
17935     #2#3#4#5#6#7 0000 0000 0000 !
17936   }
17937   \cs_new:Npn \__fp_trigd_large_auxi:nnnnwNNNN #1#2#3#4#5; #6#7#8#9
17938   {
17939     \exp_after:wN \__fp_trigd_large_auxii:wNw
17940     \int_value:w \__fp_int_eval:w #1 + #2
17941     - (#1 + #2 - 4) / 9 * 9 \__fp_int_eval_end:
17942     #3;
17943     #4; #5{#6#7#8#9};
17944   }
17945   \cs_new:Npn \__fp_trigd_large_auxii:wNw #1; #2#3;
17946   {
17947     + (#1#2 - 4) / 9 * 2
17948     \exp_after:wN \__fp_trigd_large_auxiii:www
17949     \int_value:w \__fp_int_eval:w #1#2
17950     - (#1#2 - 4) / 9 * 9 \__fp_int_eval_end: #3 ;
17951   }
17952   \cs_new:Npn \__fp_trigd_large_auxiii:www #1; #2; #3!
17953   {
17954     \if_int_compare:w #1 < 4500 \exp_stop_f:
17955     \exp_after:wN \__fp_use_i_until:s:nw
17956     \exp_after:wN \__fp_fixed_continue:wn
17957     \else:
17958       + 1
17959     \fi:
17960     \__fp_fixed_sub:wnn {9000}{0000}{0000}{0000}{0000}{0000};
17961     {#1}#2{0000}{0000};
17962     { \__fp_trigd_small:ww 2, }
17963   }

```

(End definition for `__fp_trigd_large:ww` and others.)

32.1.5 Argument reduction in radians

Arguments greater or equal to 1 need to be reduced to a range where we only need a few terms of the Taylor series. We reduce to the range $[0, 2\pi]$ by subtracting multiples of 2π , then to the smaller range $[0, \pi/2]$ by subtracting multiples of $\pi/2$ (keeping track of how many times $\pi/2$ is subtracted), then to $[0, \pi/4]$ by mapping $x \rightarrow \pi/2 - x$ if appropriate. When the argument is very large, say, 10^{100} , an equally large multiple of 2π must be subtracted, hence we must work with a very good approximation of 2π in order to get a sensible remainder modulo 2π .

Specifically, we multiply the argument by an approximation of $1/(2\pi)$ with 10048 digits, then discard the integer part of the result, keeping 52 digits of the fractional part. From the fractional part of $x/(2\pi)$ we deduce the octant (quotient of the first three digits by 125). We then multiply by 8 or -8 (the latter when the octant is odd), ignore any integer part (related to the octant), and convert the fractional part to an extended precision number, before multiplying by $\pi/4$ to convert back to a value in radians in $[0, \pi/4]$.

It is possible to prove that given the precision of floating points and their range of exponents, the 52 digits may start at most with 24 zeros. The 5 last digits are affected by carries from computations which are not done, hence we are left with at least $52 - 24 - 5 = 23$ significant digits, enough to round correctly up to $0.6 \cdot \text{ulp}$ in all cases.

`\c__fp_trig_intarray` This integer array stores blocks of 8 decimals of $10^{-16}/(2\pi)$. Each entry is 10^8 plus an 8 digit number storing 8 decimals. In total we store 10112 decimals of $10^{-16}/(2\pi)$. The number of decimals we really need is the maximum exponent plus the number of digits we later need, 52, plus 12 (4 – 1 groups of 4 digits). The memory footprint (1/2 byte per digit) is the same as an earlier method of storing the data as a control sequence name, but the major advantage is that we can unpack specific subsets of the digits without unpacking the 10112 decimals.

```

17964 \intarray_const_from_clist:Nn \c__fp_trig_intarray
17965 {
17966     100000000, 100000000, 115915494, 130918953, 135768883, 176337251,
17967     143620344, 159645740, 145644874, 176673440, 158896797, 163422653,
17968     150901138, 102766253, 108595607, 128427267, 157958036, 189291184,
17969     161145786, 152877967, 141073169, 198392292, 139966937, 140907757,
17970     130777463, 196925307, 168871739, 128962173, 197661693, 136239024,
17971     117236290, 111832380, 111422269, 197557159, 140461890, 108690267,
17972     139561204, 189410936, 193784408, 155287230, 199946443, 140024867,
17973     123477394, 159610898, 132309678, 130749061, 166986462, 180469944,
17974     186521878, 181574786, 156696424, 110389958, 174139348, 160998386,
17975     180991999, 162442875, 158517117, 188584311, 117518767, 116054654,
17976     175369880, 109739460, 136475933, 137680593, 102494496, 163530532,
17977     171567755, 103220324, 177781639, 171660229, 146748119, 159816584,
17978     106060168, 103035998, 113391198, 174988327, 186654435, 127975507,
17979     100162406, 177564388, 184957131, 108801221, 199376147, 168137776,
17980     147378906, 133068046, 145797848, 117613124, 127314069, 196077502,
17981     145002977, 159857089, 105690279, 167851315, 125210016, 131774602,
17982     109248116, 106240561, 145620314, 164840892, 148459191, 143521157,
17983     154075562, 100871526, 160680221, 171591407, 157474582, 172259774,
17984     162853998, 175155329, 139081398, 117724093, 158254797, 107332871,
17985     190406999, 175907657, 170784934, 170393589, 182808717, 134256403,
17986     166895116, 162545705, 194332763, 112686500, 126122717, 197115321,
17987     112599504, 138667945, 103762556, 108363171, 116952597, 158128224,
17988     194162333, 143145106, 112353687, 185631136, 136692167, 114206974,
17989     169601292, 150578336, 105311960, 185945098, 139556718, 170995474,
17990     165104316, 123815517, 158083944, 129799709, 199505254, 138756612,
17991     194458833, 106846050, 178529151, 151410404, 189298850, 163881607,
17992     176196993, 107341038, 199957869, 118905980, 193737772, 106187543,
17993     122271893, 101366255, 126123878, 103875388, 181106814, 106765434,
17994     108282785, 126933426, 179955607, 107903860, 160352738, 199624512,
17995     159957492, 176297023, 159409558, 143011648, 129641185, 157771240,
17996     157544494, 157021789, 176979240, 194903272, 194770216, 164960356,
17997     153181535, 144003840, 168987471, 176915887, 163190966, 150696440,
17998     147769706, 187683656, 177810477, 197954503, 153395758, 130188183,
17999     186879377, 166124814, 195305996, 155802190, 183598751, 103512712,
18000     190432315, 180498719, 168687775, 194656634, 162210342, 104440855,
18001     149785037, 192738694, 129353661, 193778292, 187359378, 143470323,
18002     102371458, 137923557, 111863634, 119294601, 183182291, 196416500,
18003     187830793, 131353497, 179099745, 186492902, 167450609, 189368909,
18004     145883050, 133703053, 180547312, 132158094, 131976760, 132283131,
18005     141898097, 149822438, 133517435, 169898475, 101039500, 168388003,
18006     197867235, 199608024, 100273901, 108749548, 154787923, 156826113,
18007     199489032, 168997427, 108349611, 149208289, 103776784, 174303550,
18008     145684560, 183671479, 130845672, 133270354, 185392556, 120208683,
18009     193240995, 162211753, 131839402, 109707935, 170774965, 149880868,

```

18010	160663609,	168661967,	103747454,	121028312,	119251846,	122483499,
18011	111611495,	166556037,	196967613,	199312829,	196077608,	127799010,
18012	107830360,	102338272,	198790854,	102387615,	157445430,	192601191,
18013	100543379,	198389046,	154921248,	129516070,	172853005,	122721023,
18014	160175233,	113173179,	175931105,	103281551,	109373913,	163964530,
18015	157926071,	180083617,	195487672,	146459804,	173977292,	144810920,
18016	109371257,	186918332,	189588628,	139904358,	168666639,	175673445,
18017	114095036,	137327191,	174311388,	106638307,	125923027,	159734506,
18018	105482127,	178037065,	133778303,	121709877,	134966568,	149080032,
18019	169885067,	141791464,	168350828,	116168533,	114336160,	173099514,
18020	198531198,	119733758,	144420984,	116559541,	152250643,	139431286,
18021	144403838,	183561508,	179771645,	101706470,	167518774,	156059160,
18022	187168578,	157939226,	123475633,	117111329,	198655941,	159689071,
18023	198506887,	144230057,	151919770,	156900382,	118392562,	120338742,
18024	135362568,	108354156,	151729710,	188117217,	195936832,	156488518,
18025	174997487,	108553116,	159830610,	113921445,	144601614,	188452770,
18026	125114110,	170248521,	173974510,	138667364,	103872860,	109967489,
18027	131735618,	112071174,	104788993,	168886556,	192307848,	150230570,
18028	157144063,	163863202,	136852010,	174100574,	185922811,	115721968,
18029	100397824,	175953001,	166958522,	112303464,	118773650,	143546764,
18030	164565659,	171901123,	108476709,	193097085,	191283646,	166919177,
18031	169387914,	133315566,	150669813,	121641521,	100895711,	172862384,
18032	126070678,	145176011,	113450800,	169947684,	122356989,	162488051,
18033	157759809,	153397080,	185475059,	175362656,	149034394,	145420581,
18034	178864356,	183042000,	131509559,	147434392,	152544850,	167491429,
18035	108647514,	142303321,	133245695,	111634945,	167753939,	142403609,
18036	105438335,	152829243,	142203494,	184366151,	146632286,	102477666,
18037	166049531,	140657343,	157553014,	109082798,	180914786,	169343492,
18038	127376026,	134997829,	195701816,	119643212,	133140475,	176289748,
18039	140828911,	174097478,	126378991,	181699939,	148749771,	151989818,
18040	172666294,	160183053,	195832752,	109236350,	168538892,	128468247,
18041	125997252,	183007668,	156937583,	165972291,	198244297,	147406163,
18042	181831139,	158306744,	134851692,	185973832,	137392662,	140243450,
18043	119978099,	140402189,	161348342,	173613676,	144991382,	171541660,
18044	163424829,	136374185,	106122610,	186132119,	198633462,	184709941,
18045	183994274,	129559156,	128333990,	148038211,	175011612,	111667205,
18046	119125793,	103552929,	124113440,	131161341,	112495318,	138592695,
18047	184904438,	146807849,	109739828,	108855297,	104515305,	139914009,
18048	188698840,	188365483,	166522246,	168624087,	125401404,	100911787,
18049	142122045,	123075334,	173972538,	114940388,	141905868,	142311594,
18050	163227443,	139066125,	116239310,	162831953,	123883392,	113153455,
18051	163815117,	152035108,	174595582,	101123754,	135976815,	153401874,
18052	107394340,	136339780,	138817210,	104531691,	182951948,	179591767,
18053	139541778,	179243527,	161740724,	160593916,	102732282,	187946819,
18054	136491289,	149714953,	143255272,	135916592,	198072479,	198580612,
18055	169007332,	118844526,	179433504,	155801952,	149256630,	162048766,
18056	116134365,	133992028,	175452085,	155344144,	109905129,	182727454,
18057	165911813,	122232840,	151166615,	165070983,	175574337,	129548631,
18058	120411217,	116380915,	160616116,	157320000,	183306114,	160618128,
18059	103262586,	195951602,	146321661,	138576614,	180471993,	127077713,
18060	116441201,	159496011,	106328305,	120759583,	148503050,	179095584,
18061	198298218,	167402898,	138551383,	123957020,	180763975,	150429225,
18062	198476470,	171016426,	197438450,	143091658,	164528360,	132493360,
18063	143546572,	137557916,	113663241,	120457809,	196971566,	134022158,

18064	180545794,	131328278,	100552461,	132088901,	187421210,	192448910,
18065	141005215,	149680971,	113720754,	100571096,	134066431,	135745439,
18066	191597694,	135788920,	179342561,	177830222,	137011486,	142492523,
18067	192487287,	113132021,	176673607,	156645598,	127260957,	141566023,
18068	143787436,	129132109,	174858971,	150713073,	191040726,	143541417,
18069	197057222,	165479803,	181512759,	157912400,	125344680,	148220261,
18070	173422990,	101020483,	106246303,	137964746,	178190501,	181183037,
18071	151538028,	179523433,	141955021,	135689770,	191290561,	143178787,
18072	192086205,	174499925,	178975690,	118492103,	124206471,	138519113,
18073	188147564,	102097605,	154895793,	178514140,	141453051,	151583964,
18074	128232654,	106020603,	131189158,	165702720,	186250269,	191639375,
18075	115278873,	160608114,	155694842,	110322407,	177272742,	116513642,
18076	134366992,	171634030,	194053074,	180652685,	109301658,	192136921,
18077	141431293,	171341061,	157153714,	106203978,	147618426,	150297807,
18078	186062669,	169960809,	118422347,	163350477,	146719017,	145045144,
18079	161663828,	146208240,	186735951,	102371302,	190444377,	194085350,
18080	134454426,	133413062,	163074595,	113830310,	122931469,	134466832,
18081	185176632,	182415152,	110179422,	164439571,	181217170,	121756492,
18082	119644493,	196532222,	118765848,	182445119,	109401340,	150443213,
18083	198586286,	121083179,	139396084,	143898019,	114787389,	177233102,
18084	186310131,	148695521,	126205182,	178063494,	157118662,	177825659,
18085	188310053,	151552316,	165984394,	109022180,	163144545,	121212978,
18086	197344714,	188741258,	126822386,	102360271,	109981191,	152056882,
18087	134723983,	158013366,	106837863,	128867928,	161973236,	172536066,
18088	185216856,	132011948,	197807339,	158419190,	166595838,	167852941,
18089	124187182,	117279875,	106103946,	106481958,	157456200,	160892122,
18090	184163943,	173846549,	158993202,	184812364,	133466119,	170732430,
18091	195458590,	173361878,	162906318,	150165106,	126757685,	112163575,
18092	188696307,	145199922,	100107766,	176830946,	198149756,	122682434,
18093	179367131,	108412102,	119520899,	148191244,	140487511,	171059184,
18094	141399078,	189455775,	118462161,	190415309,	134543802,	180893862,
18095	180732375,	178615267,	179711433,	123241969,	185780563,	176301808,
18096	184386640,	160717536,	183213626,	129671224,	126094285,	140110963,
18097	121826276,	151201170,	122552929,	128965559,	146082049,	138409069,
18098	107606920,	103954646,	119164002,	115673360,	117909631,	187289199,
18099	186343410,	186903200,	157966371,	103128612,	135698881,	176403642,
18100	152540837,	109810814,	183519031,	121318624,	172281810,	150845123,
18101	169019064,	166322359,	138872454,	163073727,	128087898,	130041018,
18102	194859136,	173742589,	141812405,	167291912,	138003306,	134499821,
18103	196315803,	186381054,	124578934,	150084553,	128031351,	118843410,
18104	107373060,	159565443,	173624887,	171292628,	198074235,	139074061,
18105	178690578,	144431052,	174262641,	176783005,	182214864,	162289361,
18106	192966929,	192033046,	169332843,	181580535,	164864073,	118444059,
18107	195496893,	153773183,	167266131,	130108623,	158802128,	180432893,
18108	144562140,	147978945,	142337360,	158506327,	104399819,	132635916,
18109	168734194,	136567839,	101281912,	120281622,	195003330,	112236091,
18110	185875592,	101959081,	122415367,	194990954,	148881099,	175891989,
18111	108115811,	163538891,	163394029,	123722049,	184837522,	142362091,
18112	100834097,	156679171,	100841679,	157022331,	178971071,	102928884,
18113	189701309,	195339954,	124415335,	106062584,	139214524,	133864640,
18114	134324406,	157317477,	155340540,	144810061,	177612569,	108474646,
18115	114329765,	143900008,	138265211,	145210162,	136643111,	197987319,
18116	102751191,	144121361,	169620456,	193602633,	161023559,	162140467,
18117	102901215,	167964187,	135746835,	187317233,	110047459,	163339773,

18118	124770449,	118885134,	141536376,	100915375,	164267438,	145016622,
18119	113937193,	106748706,	128815954,	164819775,	119220771,	102367432,
18120	189062690,	170911791,	194127762,	112245117,	123546771,	115640433,
18121	135772061,	166615646,	174474627,	130562291,	133320309,	153340551,
18122	138417181,	194605321,	150142632,	180008795,	151813296,	175497284,
18123	167018836,	157425342,	150169942,	131069156,	134310662,	160434122,
18124	105213831,	158797111,	150754540,	163290657,	102484886,	148697402,
18125	187203725,	198692811,	149360627,	140384233,	128749423,	132178578,
18126	177507355,	171857043,	178737969,	134023369,	102911446,	196144864,
18127	197697194,	134527467,	144296030,	189437192,	154052665,	188907106,
18128	162062575,	150993037,	199766583,	167936112,	181374511,	104971506,
18129	115378374,	135795558,	167972129,	135876446,	130937572,	103221320,
18130	124605656,	161129971,	131027586,	191128460,	143251843,	143269155,
18131	129284585,	173495971,	150425653,	199302112,	118494723,	121323805,
18132	116549802,	190991967,	168151180,	122483192,	151273721,	199792134,
18133	133106764,	121874844,	126215985,	112167639,	167793529,	182985195,
18134	185453921,	106957880,	158685312,	132775454,	133229161,	198905318,
18135	190537253,	191582222,	192325972,	178133427,	181825606,	148823337,
18136	160719681,	101448145,	131983362,	137910767,	112550175,	128826351,
18137	183649210,	135725874,	110356573,	189469487,	154446940,	118175923,
18138	106093708,	128146501,	185742532,	149692127,	164624247,	183221076,
18139	154737505,	168198834,	156410354,	158027261,	125228550,	131543250,
18140	139591848,	191898263,	104987591,	115406321,	103542638,	190012837,
18141	142615518,	178773183,	175862355,	117537850,	169565995,	170028011,
18142	158412588,	170150030,	117025916,	174630208,	142412449,	112839238,
18143	105257725,	114737141,	123102301,	172563968,	130555358,	132628403,
18144	183638157,	168682846,	143304568,	105994018,	170010719,	152092970,
18145	117799058,	132164175,	179868116,	158654714,	177489647,	116547948,
18146	183121404,	131836079,	184431405,	157311793,	149677763,	173989893,
18147	102277656,	107058530,	140837477,	152640947,	143507039,	152145247,
18148	101683884,	107090870,	161471944,	137225650,	128231458,	172995869,
18149	173831689,	171268519,	139042297,	111072135,	107569780,	137262545,
18150	181410950,	138270388,	198736451,	162848201,	180468288,	120582913,
18151	153390138,	135649144,	130040157,	106509887,	192671541,	174507066,
18152	186888783,	143805558,	135011967,	145862340,	180595327,	124727843,
18153	182925939,	157715840,	136885940,	198993925,	152416883,	178793572,
18154	179679516,	154076673,	192703125,	164187609,	162190243,	104699348,
18155	159891990,	160012977,	174692145,	132970421,	167781726,	115178506,
18156	153008552,	155999794,	102099694,	155431545,	127458567,	104403686,
18157	168042864,	184045128,	181182309,	179349696,	127218364,	192935516,
18158	120298724,	169583299,	148193297,	183358034,	159023227,	105261254,
18159	121144370,	184359584,	194433836,	138388317,	175184116,	108817112,
18160	151279233,	137457721,	193398208,	119005406,	132929377,	175306906,
18161	160741530,	149976826,	147124407,	176881724,	186734216,	185881509,
18162	191334220,	175930947,	117385515,	193408089,	157124410,	163472089,
18163	131949128,	180783576,	131158294,	100549708,	191802336,	165960770,
18164	170927599,	101052702,	181508688,	197828549,	143403726,	142729262,
18165	110348701,	139928688,	153550062,	106151434,	130786653,	196085995,
18166	100587149,	139141652,	106530207,	100852656,	124074703,	166073660,
18167	153338052,	163766757,	120188394,	197277047,	122215363,	138511354,
18168	183463624,	161985542,	159938719,	133367482,	104220974,	149956672,
18169	170250544,	164232439,	157506869,	159133019,	137469191,	142980999,
18170	134242305,	150172665,	121209241,	145596259,	160554427,	159095199,
18171	168243130,	184279693,	171132070,	121049823,	123819574,	171759855,

```

18172      119501864, 163094029, 175943631, 194450091, 191506160, 149228764,
18173      132319212, 197034460, 193584259, 126727638, 168143633, 109856853,
18174      127860243, 132141052, 133076065, 188414958, 158718197, 107124299,
18175      159592267, 181172796, 144388537, 196763139, 127431422, 179531145,
18176      100064922, 112650013, 132686230, 121550837,
18177  }

```

(End definition for \c__fp_trig_intarray.)

__fp_trig_large:ww The exponent #1 is between 1 and 10000. We wish to look up decimals $10^{\#1-16}/(2\pi)$ starting from the digit #1 + 1. Since they are stored in batches of 8, compute $\lceil \#1/8 \rceil$ and fetch blocks of 8 digits starting there. The numbering of items in \c__fp_trig_intarray starts at 1, so the block $\lceil \#1/8 \rceil + 1$ contains the digit we want, at one of the eight positions. Each call to \int_value:w __kernel_intarray_item:Nn expands the next, until being stopped by __fp_trig_large_auxiii:w using \exp_stop_f:. Once all these blocks are unpacked, the \exp_stop_f: and 0 to 7 digits are removed by \use_none:n...n. Finally, __fp_trig_large_auxii:w packs 64 digits (there are between 65 and 72 at this point) into groups of 4 and the auxv auxiliary is called.

```

18178 \cs_new:Npn \__fp_trig_large:ww #1, #2#3#4#5#6;
18179 {
18180   \exp_after:wN \__fp_trig_large_auxi:w
18181   \int_value:w \__fp_int_eval:w (#1 - 4) / 8 \exp_after:wN ,
18182   \int_value:w #1 , ;
18183   {#2}{#3}{#4}{#5} ;
18184 }
18185 \cs_new:Npn \__fp_trig_large_auxi:w #1, #2,
18186 {
18187   \exp_after:wN \exp_after:wN
18188   \exp_after:wN \__fp_trig_large_auxii:w
18189   \cs:w
18190     use_none:n \prg_replicate:nn { #2 - #1 * 8 } { n }
18191   \exp_after:wN
18192   \cs_end:
18193   \int_value:w
18194   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18195     { \__fp_int_eval:w #1 + 1 \scan_stop: }
18196   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
18197   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18198     { \__fp_int_eval:w #1 + 2 \scan_stop: }
18199   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
18200   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18201     { \__fp_int_eval:w #1 + 3 \scan_stop: }
18202   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
18203   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18204     { \__fp_int_eval:w #1 + 4 \scan_stop: }
18205   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
18206   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18207     { \__fp_int_eval:w #1 + 5 \scan_stop: }
18208   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
18209   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18210     { \__fp_int_eval:w #1 + 6 \scan_stop: }
18211   \exp_after:wN \__fp_trig_large_auxiii:w \int_value:w
18212   \__kernel_intarray_item:Nn \c__fp_trig_intarray
18213     { \__fp_int_eval:w #1 + 7 \scan_stop: }

```

```

18214 \exp_after:wN \_fp_trig_large_auxiii:w \int_value:w
18215 \_kernel_intarray_item:Nn \c\_fp_trig_intarray
18216 { \_fp_int_eval:w #1 + 8 \scan_stop: }
18217 \exp_after:wN \_fp_trig_large_auxiii:w \int_value:w
18218 \_kernel_intarray_item:Nn \c\_fp_trig_intarray
18219 { \_fp_int_eval:w #1 + 9 \scan_stop: }
18220 \exp_stop_f:
18221 }
18222 \cs_new:Npn \_fp_trig_large_auxii:w
18223 {
18224 \_fp_pack_twice_four:wNNNNNNNN \_fp_pack_twice_four:wNNNNNNNN
18225 \_fp_pack_twice_four:wNNNNNNNN \_fp_pack_twice_four:wNNNNNNNN
18226 \_fp_pack_twice_four:wNNNNNNNN \_fp_pack_twice_four:wNNNNNNNN
18227 \_fp_pack_twice_four:wNNNNNNNN \_fp_pack_twice_four:wNNNNNNNN
18228 \_fp_trig_large_auxv:www ;
18229 }
18230 \cs_new:Npn \_fp_trig_large_auxiii:w 1 { \exp_stop_f: }

```

(End definition for _fp_trig_large:ww and others.)

```

\_fp_trig_large_auxv:www
\_fp_trig_large_auxvi:wNNNNNNNN
\_fp_trig_large_pack:NNNNW

```

First come the first 64 digits of the fractional part of $10^{1-16}/(2\pi)$, arranged in 16 blocks of 4, and ending with a semicolon. Then a few more digits of the same fractional part, ending with a semicolon, then 4 blocks of 4 digits holding the significand of the original argument. Multiply the 16-digit significand with the 64-digit fractional part: the `auxvi` auxiliary receives the significand as `#2#3#4#5` and 16 digits of the fractional part as `#6#7#8#9`, and computes one step of the usual ladder of `pack` functions we use for multiplication (see *e.g.*, `_fp_fixed_mul:wN`), then discards one block of the fractional part to set things up for the next step of the ladder. We perform 13 such steps, replacing the last `middle` shift by the appropriate `trailing` shift, then discard the significand and remaining 3 blocks from the fractional part, as there are not enough digits to compute any more step in the ladder. The last semicolon closes the ladder, and we return control to the `auxvii` auxiliary.

```

18231 \cs_new:Npn \_fp_trig_large_auxv:www #1; #2; #3;
18232 {
18233 \exp_after:wN \_fp_use_i_until_s:nw
18234 \exp_after:wN \_fp_trig_large_auxvii:w
18235 \int_value:w \_fp_int_eval:w \c\_fp_leading_shift_int
18236 \prg_replicate:nn { 13 }
18237 { \_fp_trig_large_auxvi:wNNNNNNNN }
18238 + \c\_fp_trailing_shift_int - \c\_fp_middle_shift_int
18239 \_fp_use_i_until_s:nw
18240 ; #3 #1 ; ;
18241 }
18242 \cs_new:Npn \_fp_trig_large_auxvi:wNNNNNNNN #1; #2#3#4#5#6#7#8#9
18243 {
18244 \exp_after:wN \_fp_trig_large_pack:NNNNW
18245 \int_value:w \_fp_int_eval:w \c\_fp_middle_shift_int
18246 + #2*#9 + #3*#8 + #4*#7 + #5*#6
18247 #1; {#2}{#3}{#4}{#5} {#7}{#8}{#9}
18248 }
18249 \cs_new:Npn \_fp_trig_large_pack:NNNNW #1#2#3#4#5#6;
18250 { + #1#2#3#4#5 ; #6 }

```


(End definition for `_fp_trig_large_auxv:www`, `_fp_trig_large_auxvi:wnnnnnnnn`, and `_fp_trig_large_pack:NNNNNw`.)

`_fp_trig_large_auxvii:w`
`_fp_trig_large_auxviii:w`
`_fp_trig_large_auxix:Nw`
`_fp_trig_large_auxx:wnnnnn`
`_fp_trig_large_auxxi:w`

The `auxvii` auxiliary is followed by 52 digits and a semicolon. We find the octant as the integer part of 8 times what follows, or equivalently as the integer part of `#1#2#3/125`, and add it to the surrounding integer expression for the octant. We then compute 8 times the 52-digit number, with a minus sign if the octant is odd. Again, the last `middle` shift is converted to a `trailing` shift. Any integer part (including negative values which come up when the octant is odd) is discarded by `_fp_use_i_until_s:nw`. The resulting fractional part should then be converted to radians by multiplying by $2\pi/8$, but first, build an extended precision number by abusing `_fp_ep_to_ep_loop:N` with the appropriate trailing markers. Finally, `_fp_trig_small:ww` sets up the argument for the functions which compute the Taylor series.

```

18251 \cs_new:Npn \_fp_trig_large_auxvii:w #1#2#3
18252 {
18253   \exp_after:wN \_fp_trig_large_auxviii:ww
18254   \int_value:w \_fp_int_eval:w (#1#2#3 - 62) / 125 ;
18255   #1#2#3
18256 }
18257 \cs_new:Npn \_fp_trig_large_auxviii:ww #1;
18258 {
18259   + #1
18260   \if_int_odd:w #1 \exp_stop_f:
18261     \exp_after:wN \_fp_trig_large_auxix:Nw
18262     \exp_after:wN -
18263   \else:
18264     \exp_after:wN \_fp_trig_large_auxix:Nw
18265     \exp_after:wN +
18266   \fi:
18267 }
18268 \cs_new:Npn \_fp_trig_large_auxix:Nw
18269 {
18270   \exp_after:wN \_fp_use_i_until_s:nw
18271   \exp_after:wN \_fp_trig_large_auxxi:w
18272   \int_value:w \_fp_int_eval:w \c__fp_leading_shift_int
18273   \prg_replicate:nn { 13 }
18274     { \_fp_trig_large_auxx:wnnnnn }
18275   + \c__fp_trailing_shift_int - \c__fp_middle_shift_int
18276   ;
18277 }
18278 \cs_new:Npn \_fp_trig_large_auxx:wnnnnn #1; #2 #3#4#5#6
18279 {
18280   \exp_after:wN \_fp_trig_large_pack:NNNNNw
18281   \int_value:w \_fp_int_eval:w \c__fp_middle_shift_int
18282     #2 8 * #3#4#5#6
18283     #1; #2
18284 }
18285 \cs_new:Npn \_fp_trig_large_auxxi:w #1;
18286 {
18287   \exp_after:wN \_fp_ep_mul_raw:wwwN
18288   \int_value:w \_fp_int_eval:w 0 \_fp_ep_to_ep_loop:N #1 ; ; !
18289   0,{7853}{9816}{3397}{4483}{0961}{5661};
18290   \_fp_trig_small:ww

```

18291 }
 18292

(End definition for `_fp_trig_large_auxvii:w` and others.)

32.1.6 Computing the power series

`_fp_sin_series_o:NNwww` Here we receive a conversion function `_fp_ep_to_float_o:wwN` or `_fp_ep_inv_to_float_o:wwN`, a $\langle sign \rangle$ (0 or 2), a (non-negative) $\langle octant \rangle$ delimited by a dot, a $\langle fixed point \rangle$ number delimited by a semicolon, and an extended-precision number. The auxiliary receives:

- the conversion function #1;
- the final sign, which depends on the octant #3 and the sign #2;
- the octant #3, which controls the series we use;
- the square #4 * #4 of the argument as a fixed point number, computed with `_fp_fixed_mul:wn`;
- the number itself as an extended-precision number.

If the octant is in $\{1, 2, 5, 6, \dots\}$, we are near an extremum of the function and we use the series

$$\cos(x) = 1 - x^2 \left(\frac{1}{2!} - x^2 \left(\frac{1}{4!} - x^2 \left(\dots \right) \right) \right).$$

Otherwise, the series

$$\sin(x) = x \left(1 - x^2 \left(\frac{1}{3!} - x^2 \left(\frac{1}{5!} - x^2 \left(\dots \right) \right) \right) \right)$$

is used. Finally, the extended-precision number is converted to a floating point number with the given sign, and `_fp_sanitize:Nw` checks for overflow and underflow.

```

18292 \cs_new:Npn \_fp_sin_series_o:NNwww #1#2#3. #4;
18293 {
18294   \_fp_fixed_mul:wn #4; #4;
18295   {
18296     \exp_after:wN \_fp_sin_series_aux_o:NNwww
18297     \exp_after:wN #1
18298     \int_value:w
18299     \if_int_odd:w \_fp_int_eval:w (#3 + 2) / 4 \_fp_int_eval_end:
18300       #2
18301     \else:
18302       \if_meaning:w #2 0 2 \else: 0 \fi:
18303     \fi:
18304     {#3}
18305   }
18306 }
18307 \cs_new:Npn \_fp_sin_series_aux_o:NNwww #1#2#3 #4; #5,#6;
18308 {
18309   \if_int_odd:w \_fp_int_eval:w #3 / 2 \_fp_int_eval_end:
18310     \exp_after:wN \use_i:nn
18311   \else:
18312     \exp_after:wN \use_ii:nn
18313   \fi:

```

```

18314 { % 1/18!
18315   \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0001}{5619}{2070};
18316   #4;{0000}{0000}{0000}{0477}{9477}{3324};
18317   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0011}{4707}{4559}{7730};
18318   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{2087}{6756}{9878}{6810};
18319   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0027}{5573}{1922}{3985}{8907};
18320   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{2480}{1587}{3015}{8730}{1587};
18321   \__fp_fixed_mul_sub_back:wwwn #4;{0013}{8888}{8888}{8888}{8888}{8889};
18322   \__fp_fixed_mul_sub_back:wwwn #4;{0416}{6666}{6666}{6666}{6666}{6667};
18323   \__fp_fixed_mul_sub_back:wwwn #4;{5000}{0000}{0000}{0000}{0000}{0000};
18324   \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
18325   { \__fp_fixed_continue:wn 0, }
18326 }
18327 { % 1/17!
18328   \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{0000}{0028}{1145}{7254};
18329   #4;{0000}{0000}{0000}{7647}{1637}{3182};
18330   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0000}{0160}{5904}{3836}{8216};
18331   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0002}{5052}{1083}{8544}{1719};
18332   \__fp_fixed_mul_sub_back:wwwn #4;{0000}{0275}{5731}{9223}{9858}{9065};
18333   \__fp_fixed_mul_sub_back:wwwn #4;{0001}{9841}{2698}{4126}{9841}{2698};
18334   \__fp_fixed_mul_sub_back:wwwn #4;{0083}{3333}{3333}{3333}{3333}{3333};
18335   \__fp_fixed_mul_sub_back:wwwn #4;{1666}{6666}{6666}{6666}{6666}{6667};
18336   \__fp_fixed_mul_sub_back:wwwn#4;{10000}{0000}{0000}{0000}{0000}{0000};
18337   { \__fp_ep_mul:wwwn 0, } #5,#6;
18338 }
18339 {
18340   \exp_after:wN \__fp_sanitizewN
18341   \exp_after:wN #2
18342   \int_value:w \__fp_int_eval:w #1
18343 }
18344 #2
18345 }

```

(End definition for __fp_sin_series_o:NNwww and __fp_sin_series_aux_o:NNwww.)

__fp_tan_series_o:NNwww Contrarily to __fp_sin_series_o:NNwww which received a conversion auxiliary as #1, here, #1 is 0 for tangent and 2 for cotangent. Consider first the case of the tangent. The octant #3 starts at 1, which means that it is 1 or 2 for $|x| \in [0, \pi/2]$, it is 3 or 4 for $|x| \in [\pi/2, \pi]$, and so on: the intervals on which $\tan|x| \geq 0$ coincide with those for which $\lfloor (\#3 + 1)/2 \rfloor$ is odd. We also have to take into account the original sign of x to get the sign of the final result; it is straightforward to check that the first \int_value:w expansion produces 0 for a positive final result, and 2 otherwise. A similar story holds for $\cot(x)$.

The auxiliary receives the sign, the octant, the square of the (reduced) input, and the (reduced) input (an extended-precision number) as arguments. It then computes the numerator and denominator of

$$\tan(x) \simeq \frac{x(1 - x^2(a_1 - x^2(a_2 - x^2(a_3 - x^2(a_4 - x^2a_5))))))}{1 - x^2(b_1 - x^2(b_2 - x^2(b_3 - x^2(b_4 - x^2b_5)))}.$$

The ratio is computed by __fp_ep_div:wwwn, then converted to a floating point number. For octants #3 (really, quadrants) next to a pole of the functions, the fixed point numerator and denominator are exchanged before computing the ratio. Note that this \if_int_odd:w test relies on the fact that the octant is at least 1.

```

18346 \cs_new:Npn \__fp_tan_series_o:NNwww #1#2#3. #4;
18347 {
18348   \__fp_fixed_mul:wwn #4; #4;
18349   {
18350     \exp_after:wN \__fp_tan_series_aux_o:Nnwww
18351     \int_value:w
18352     \if_int_odd:w \__fp_int_eval:w #3 / 2 \__fp_int_eval_end:
18353     \exp_after:wN \reverse_if:N
18354     \fi:
18355     \if_meaning:w #1#2 2 \else: 0 \fi:
18356     {#3}
18357   }
18358 }
18359 \cs_new:Npn \__fp_tan_series_aux_o:Nnwww #1 #2 #3; #4,#5;
18360 {
18361   \__fp_fixed_mul_sub_back:wwwn {0000}{0000}{1527}{3493}{0856}{7059};
18362   #3; {0000}{0159}{6080}{0274}{5257}{6472};
18363   \__fp_fixed_mul_sub_back:wwwn #3; {0002}{4571}{2320}{0157}{2558}{8481};
18364   \__fp_fixed_mul_sub_back:wwwn #3; {0115}{5830}{7533}{5397}{3168}{2147};
18365   \__fp_fixed_mul_sub_back:wwwn #3; {1929}{8245}{6140}{3508}{7719}{2982};
18366   \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
18367   { \__fp_ep_mul:wwwn 0, } #4,#5;
18368   {
18369     \__fp_fixed_mul_sub_back:wwwn {0000}{0007}{0258}{0681}{9408}{4706};
18370     #3; {0000}{2343}{7175}{1399}{6151}{7670};
18371     \__fp_fixed_mul_sub_back:wwwn #3; {0019}{2638}{4588}{9232}{8861}{3691};
18372     \__fp_fixed_mul_sub_back:wwwn #3; {0536}{6357}{0691}{4344}{6852}{4252};
18373     \__fp_fixed_mul_sub_back:wwwn #3; {5263}{1578}{9473}{6842}{1052}{6315};
18374     \__fp_fixed_mul_sub_back:wwwn #3; {10000}{0000}{0000}{0000}{0000}{0000};
18375     {
18376       \reverse_if:N \if_int_odd:w
18377       \__fp_int_eval:w (#2 - 1) / 2 \__fp_int_eval_end:
18378       \exp_after:wN \__fp_reverse_args:Nww
18379       \fi:
18380       \__fp_ep_div:wwwn 0,
18381     }
18382   }
18383   {
18384     \exp_after:wN \__fp_sanitize:Nw
18385     \exp_after:wN #1
18386     \int_value:w \__fp_int_eval:w \__fp_ep_to_float_o:wwN
18387   }
18388   #1
18389 }

```

(End definition for __fp_tan_series_o:NNwww and __fp_tan_series_aux_o:Nnwww.)

32.2 Inverse trigonometric functions

All inverse trigonometric functions (arcsine, arccosine, arctangent, arccotangent, arcsecant, and arcsecant) are based on a function often denoted `atan2`. This function is accessed directly by feeding two arguments to arctangent, and is defined by $\text{atan}(y, x) = \text{atan}(y/x)$ for generic y and x . Its advantages over the conventional arctangent is that it takes values in $[-\pi, \pi]$ rather than $[-\pi/2, \pi/2]$, and that it is better

behaved in boundary cases. Other inverse trigonometric functions are expressed in terms of `atan` as

$$\operatorname{acos} x = \operatorname{atan}(\sqrt{1-x^2}, x) \quad (5)$$

$$\operatorname{asin} x = \operatorname{atan}(x, \sqrt{1-x^2}) \quad (6)$$

$$\operatorname{asec} x = \operatorname{atan}(\sqrt{x^2-1}, 1) \quad (7)$$

$$\operatorname{acsc} x = \operatorname{atan}(1, \sqrt{x^2-1}) \quad (8)$$

$$\operatorname{atan} x = \operatorname{atan}(x, 1) \quad (9)$$

$$\operatorname{acot} x = \operatorname{atan}(1, x). \quad (10)$$

Rather than introducing a new function, `atan2`, the arctangent function `atan` is overloaded: it can take one or two arguments. In the comments below, following many texts, we call the first argument y and the second x , because $\operatorname{atan}(y, x) = \operatorname{atan}(y/x)$ is the angular coordinate of the point (x, y) .

As for direct trigonometric functions, the first step in computing $\operatorname{atan}(y, x)$ is argument reduction. The sign of y gives that of the result. We distinguish eight regions where the point $(x, |y|)$ can lie, of angular size roughly $\pi/8$, characterized by their “octant”, between 0 and 7 included. In each region, we compute an arctangent as a Taylor series, then shift this arctangent by the appropriate multiple of $\pi/4$ and sign to get the result. Here is a list of octants, and how we compute the arctangent (we assume $y > 0$; otherwise replace y by $-y$ below):

0 $0 < |y| < 0.41421x$, then $\operatorname{atan} \frac{|y|}{x}$ is given by a nicely convergent Taylor series;

1 $0 < 0.41421x < |y| < x$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{4} - \operatorname{atan} \frac{x-|y|}{x+|y|}$;

2 $0 < 0.41421|y| < x < |y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{4} + \operatorname{atan} \frac{-x+|y|}{x+|y|}$;

3 $0 < x < 0.41421|y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{2} - \operatorname{atan} \frac{x}{|y|}$;

4 $0 < -x < 0.41421|y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{\pi}{2} + \operatorname{atan} \frac{-x}{|y|}$;

5 $0 < 0.41421|y| < -x < |y|$, then $\operatorname{atan} \frac{|y|}{x} = \frac{3\pi}{4} - \operatorname{atan} \frac{x+|y|}{-x+|y|}$;

6 $0 < -0.41421x < |y| < -x$, then $\operatorname{atan} \frac{|y|}{x} = \frac{3\pi}{4} + \operatorname{atan} \frac{-x-|y|}{-x+|y|}$;

7 $0 < |y| < -0.41421x$, then $\operatorname{atan} \frac{|y|}{x} = \pi - \operatorname{atan} \frac{|y|}{-x}$.

In the following, we denote by z the ratio among $|\frac{y}{x}|$, $|\frac{x}{y}|$, $|\frac{x+y}{x-y}|$, $|\frac{x-y}{x+y}|$ which appears in the right-hand side above.

32.2.1 Arctangent and arccotangent

`__fp_atan_o:Nw` The parsing step manipulates `atan` and `acot` like `min` and `max`, reading in an array of operands, but also leaves `\use_i:nn` or `\use_ii:nn` depending on whether the result should be given in radians or in degrees. The helper `__fp_parse_function_one_two:nnw` checks that the operand is one or two floating point numbers (not tuples) and leaves its second argument or its tail accordingly (its first argument is used for error

messages). More precisely if we are given a single floating point number `__fp_atan_default:w` places `\c_one_fp` (expanded) after it; otherwise `__fp_atan_default:w` is omitted by `__fp_parse_function_one_two:nnw`.

```

18390 \cs_new:Npn \__fp_atan_o:Nw #1
18391 {
18392   \__fp_parse_function_one_two:nnw
18393   { #1 { atan } { atand } }
18394   { \__fp_atan_default:w \__fp_atanii_o:Nww #1 }
18395 }
18396 \cs_new:Npn \__fp_acot_o:Nw #1
18397 {
18398   \__fp_parse_function_one_two:nnw
18399   { #1 { acot } { acotd } }
18400   { \__fp_atan_default:w \__fp_acotii_o:Nww #1 }
18401 }
18402 \cs_new:Npx \__fp_atan_default:w #1#2#3 @ { #1 #2 #3 \c_one_fp @ }

```

(End definition for `__fp_atan_o:Nw`, `__fp_acot_o:Nw`, and `__fp_atan_default:w`.)

`__fp_atanii_o:Nww`
`__fp_acotii_o:Nww`

If either operand is `nan`, we return it. If both are normal, we call `__fp_atan_normal_o:NNnwNnw`. If both are zero or both infinity, we call `__fp_atan_inf_o:NNNw` with argument 2, leading to a result among $\{\pm\pi/4, \pm3\pi/4\}$ (in degrees, $\{\pm45, \pm135\}$). Otherwise, one is much bigger than the other, and we call `__fp_atan_inf_o:NNNw` with either an argument of 4, leading to the values $\pm\pi/2$ (in degrees, ±90), or 0, leading to $\{\pm0, \pm\pi\}$ (in degrees, $\{\pm0, \pm180\}$). Since $\text{acot}(x, y) = \text{atan}(y, x)$, `__fp_acotii_o:ww` simply reverses its two arguments.

```

18403 \cs_new:Npn \__fp_atanii_o:Nww
18404   #1 \s__fp \__fp_chk:w #2#3#4; \s__fp \__fp_chk:w #5 #6 @
18405 {
18406   \if_meaning:w 3 #2 \__fp_case_return_i_o:ww \fi:
18407   \if_meaning:w 3 #5 \__fp_case_return_ii_o:ww \fi:
18408   \if_case:w
18409     \if_meaning:w #2 #5
18410       \if_meaning:w 1 #2 10 \else: 0 \fi:
18411     \else:
18412       \if_int_compare:w #2 > #5 \exp_stop_f: 1 \else: 2 \fi:
18413     \fi:
18414     \exp_stop_f:
18415     \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 2 }
18416   \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 4 }
18417   \or: \__fp_case_return:nw { \__fp_atan_inf_o:NNNw #1 #3 0 }
18418   \fi:
18419   \__fp_atan_normal_o:NNnwNnw #1
18420   \s__fp \__fp_chk:w #2#3#4;
18421   \s__fp \__fp_chk:w #5 #6
18422 }
18423 \cs_new:Npn \__fp_acotii_o:Nww #1#2; #3;
18424   { \__fp_atanii_o:Nww #1#3; #2; }

```

(End definition for `__fp_atanii_o:Nww` and `__fp_acotii_o:Nww`.)

`__fp_atan_inf_o:NNNw`

This auxiliary is called whenever one number is ± 0 or $\pm\infty$ (and neither is `NaN`). Then the result only depends on the signs, and its value is a multiple of $\pi/4$. We use the same auxiliary as for normal numbers, `__fp_atan_combine_o:NwwwwwN`, with arguments the

final sign #2; the octant #3; $\text{atan } z/z = 1$ as a fixed point number; $z = 0$ as a fixed point number; and $z = 0$ as an extended-precision number. Given the values we provide, $\text{atan } z$ is computed to be 0, and the result is $[\#3/2] \cdot \pi/4$ if the sign #5 of x is positive, and $[(7 - \#3)/2] \cdot \pi/4$ for negative x , where the divisions are rounded up.

```

18425 \cs_new:Npn \__fp_atan_inf_o:NNNw #1#2#3 \s_fp \__fp_chk:w #4#5#6;
18426 {
18427   \exp_after:wN \__fp_atan_combine_o:NwwwwwN
18428   \exp_after:wN #2
18429   \int_value:w \__fp_int_eval:w
18430   \if_meaning:w 2 #5 7 - \fi: #3 \exp_after:wN ;
18431   \c__fp_one_fixed_t1
18432   {0000}{0000}{0000}{0000}{0000}{0000};
18433   0,{0000}{0000}{0000}{0000}{0000}{0000}; #1
18434 }

```

(End definition for __fp_atan_inf_o:NNNw.)

__fp_atan_normal_o:NNwNnw

Here we simply reorder the floating point data into a pair of signed extended-precision numbers, that is, a sign, an exponent ending with a comma, and a six-block mantissa ending with a semi-colon. This extended precision is required by other inverse trigonometric functions, to compute things like $\text{atan}(x, \sqrt{1-x^2})$ without intermediate rounding errors.

```

18435 \cs_new_protected:Npn \__fp_atan_normal_o:NNwNnw
18436   #1 \s_fp \__fp_chk:w 1#2#3#4; \s_fp \__fp_chk:w 1#5#6#7;
18437 {
18438   \__fp_atan_test_o:NwwNwwN
18439   #2 #3, #4{0000}{0000};
18440   #5 #6, #7{0000}{0000}; #1
18441 }

```

(End definition for __fp_atan_normal_o:NNwNnw.)

__fp_atan_test_o:NwwNwwN

This receives: the sign #1 of y , its exponent #2, its 24 digits #3 in groups of 4, and similarly for x . We prepare to call __fp_atan_combine_o:NwwwwwN which expects the sign #1, the octant, the ratio $(\text{atan } z)/z = 1 - \dots$, and the value of z , both as a fixed point number and as an extended-precision floating point number with a mantissa in $[0.01, 1)$. For now, we place #1 as a first argument, and start an integer expression for the octant. The sign of x does not affect z , so we simply leave a contribution to the octant: $\langle \text{octant} \rangle \rightarrow 7 - \langle \text{octant} \rangle$ for negative x . Then we order $|y|$ and $|x|$ in a non-decreasing order: if $|y| > |x|$, insert 3- in the expression for the octant, and swap the two numbers. The finer test with 0.41421 is done by __fp_atan_div:wnwnw after the operands have been ordered.

```

18442 \cs_new:Npn \__fp_atan_test_o:NwwNwwN #1#2,#3; #4#5,#6;
18443 {
18444   \exp_after:wN \__fp_atan_combine_o:NwwwwwN
18445   \exp_after:wN #1
18446   \int_value:w \__fp_int_eval:w
18447   \if_meaning:w 2 #4
18448     7 - \__fp_int_eval:w
18449   \fi:
18450   \if_int_compare:w
18451     \__fp_ep_compare:www #2,#3; #5,#6; > 0 \exp_stop_f:
18452     3 -

```

```

18453     \exp_after:wN \__fp_reverse_args:Nww
18454     \fi:
18455     \__fp_atan_div:wnwnw #2,#3; #5,#6;
18456 }

```

(End definition for __fp_atan_test_o:NwwNwwN.)

```

\__fp_atan_div:wnwnw
\__fp_atan_near:wwwn
\__fp_atan_near_aux:wnw

```

This receives two positive numbers a and b (equal to $|x|$ and $|y|$ in some order), each as an exponent and 6 blocks of 4 digits, such that $0 < a < b$. If $0.41421b < a$, the two numbers are “near”, hence the point (y, x) that we started with is closer to the diagonals $\{|y| = |x|\}$ than to the axes $\{xy = 0\}$. In that case, the octant is 1 (possibly combined with the 7– and 3– inserted earlier) and we wish to compute $\operatorname{atan} \frac{b-a}{a+b}$. Otherwise, the octant is 0 (again, combined with earlier terms) and we wish to compute $\operatorname{atan} \frac{a}{b}$. In any case, call __fp_atan_auxi:ww followed by z , as a comma-delimited exponent and a fixed point number.

```

18457 \cs_new:Npn \__fp_atan_div:wnwnw #1,#2#3; #4,#5#6;
18458 {
18459     \if_int_compare:w
18460         \__fp_int_eval:w 41421 * #5 < #2 000
18461         \if_case:w \__fp_int_eval:w #4 - #1 \__fp_int_eval_end:
18462             00 \or: 0 \fi:
18463     \exp_stop_f:
18464     \exp_after:wN \__fp_atan_near:wwwn
18465     \fi:
18466     0
18467     \__fp_ep_div:wwwn #1,{#2}#3; #4,{#5}#6;
18468     \__fp_atan_auxi:ww
18469 }
18470 \cs_new:Npn \__fp_atan_near:wwwn
18471     0 \__fp_ep_div:wwwn #1,#2; #3,
18472     {
18473         1
18474         \__fp_ep_to_fixed:wnw #1 - #3, #2;
18475         \__fp_atan_near_aux:wnw
18476     }
18477 \cs_new:Npn \__fp_atan_near_aux:wnw #1; #2;
18478 {
18479     \__fp_fixed_add:wnw #1; #2;
18480     { \__fp_fixed_sub:wnw #2; #1; { \__fp_ep_div:wwwn 0, } 0, }
18481 }

```

(End definition for __fp_atan_div:wnwnw, __fp_atan_near:wwwn, and __fp_atan_near_aux:wnw.)

```

\__fp_atan_auxi:ww
\__fp_atan_auxii:w

```

Convert z from a representation as an exponent and a fixed point number in $[0.01, 1)$ to a fixed point number only, then set up the call to __fp_atan_Taylor_loop:www, followed by the fixed point representation of z and the old representation.

```

18482 \cs_new:Npn \__fp_atan_auxi:ww #1,#2;
18483 { \__fp_ep_to_fixed:wnw #1,#2; \__fp_atan_auxii:w #1,#2; }
18484 \cs_new:Npn \__fp_atan_auxii:w #1;
18485 {
18486     \__fp_fixed_mul:wnw #1; #1;
18487     {
18488         \__fp_atan_Taylor_loop:www 39 ;
18489         {0000}{0000}{0000}{0000}{0000}{0000} ;

```



```

18490     }
18491     ! #1;
18492   }

```

(End definition for `_fp_atan_auxi:ww` and `_fp_atan_auxii:w`.)

```

\_fp_atan_Taylor_loop:www
\_fp_atan_Taylor_break:w

```

We compute the series of $(\operatorname{atan} z)/z$. A typical intermediate stage has $\#1 = 2k - 1$, $\#2 = \frac{1}{2k+1} - z^2(\frac{1}{2k+3} - z^2(\dots - z^2\frac{1}{39}))$, and $\#3 = z^2$. To go to the next step $k \rightarrow k - 1$, we compute $\frac{1}{2k-1}$, then subtract from it z^2 times $\#2$. The loop stops when $k = 0$: then $\#2$ is $(\operatorname{atan} z)/z$, and there is a need to clean up all the unnecessary data, end the integer expression computing the octant with a semicolon, and leave the result $\#2$ afterwards.

```

18493 \cs_new:Npn \_fp_atan_Taylor_loop:www #1; #2; #3;
18494 {
18495   \if_int_compare:w #1 = -1 \exp_stop_f:
18496     \_fp_atan_Taylor_break:w
18497   \fi:
18498   \exp_after:wN \_fp_fixed_div_int:wwN \c_fp_one_fixed_tl #1;
18499   \_fp_rrot:www \_fp_fixed_mul_sub_back:wwwn #2; #3;
18500   {
18501     \exp_after:wN \_fp_atan_Taylor_loop:www
18502     \int_value:w \_fp_int_eval:w #1 - 2 ;
18503   }
18504   #3;
18505 }
18506 \cs_new:Npn \_fp_atan_Taylor_break:w
18507   \fi: #1 \_fp_fixed_mul_sub_back:wwwn #2; #3 !
18508   { \fi: ; #2 ; }

```

(End definition for `_fp_atan_Taylor_loop:www` and `_fp_atan_Taylor_break:w`.)

```

\_fp_atan_combine_o:NwwwwN
\_fp_atan_combine_aux:w

```

This receives a $\langle sign \rangle$, an $\langle octant \rangle$, a fixed point value of $(\operatorname{atan} z)/z$, a fixed point number z , and another representation of z , as an $\langle exponent \rangle$ and the fixed point number $10^{-\langle exponent \rangle} z$, followed by either `\use_i:nn` (when working in radians) or `\use_ii:nn` (when working in degrees). The function computes the floating point result

$$\langle sign \rangle \left(\left\lceil \frac{\langle octant \rangle}{2} \right\rceil \frac{\pi}{4} + (-1)^{\langle octant \rangle} \frac{\operatorname{atan} z}{z} \cdot z \right), \quad (11)$$

multiplied by $180/\pi$ if working in degrees, and using in any case the most appropriate representation of z . The floating point result is passed to `_fp_sanitize:Nw`, which checks for overflow or underflow. If the octant is 0, leave the exponent $\#5$ for `_fp_sanitize:Nw`, and multiply $\#3 = \frac{\operatorname{atan} z}{z}$ with $\#6$, the adjusted z . Otherwise, multiply $\#3 = \frac{\operatorname{atan} z}{z}$ with $\#4 = z$, then compute the appropriate multiple of $\frac{\pi}{4}$ and add or subtract the product $\#3 \cdot \#4$. In both cases, convert to a floating point with `_fp_fixed_to_float_o:wN`.

```

18509 \cs_new:Npn \_fp_atan_combine_o:NwwwwN #1 #2; #3; #4; #5,#6; #7
18510 {
18511   \exp_after:wN \_fp_sanitize:Nw
18512   \exp_after:wN #1
18513   \int_value:w \_fp_int_eval:w
18514   \if_meaning:w 0 #2
18515     \exp_after:wN \use_i:nn
18516   \else:

```

```

18517         \exp_after:wN \use_ii:nn
18518     \fi:
18519     { #5 \__fp_fixed_mul:wwn #3; #6; }
18520     {
18521         \__fp_fixed_mul:wwn #3; #4;
18522         {
18523             \exp_after:wN \__fp_atan_combine_aux:ww
18524             \int_value:w \__fp_int_eval:w #2 / 2 ; #2;
18525         }
18526     }
18527     { #7 \__fp_fixed_to_float_o:wN \__fp_fixed_to_float_rad_o:wN }
18528     #1
18529 }
18530 \cs_new:Npn \__fp_atan_combine_aux:ww #1; #2;
18531 {
18532     \__fp_fixed_mul_short:wwn
18533     {7853}{9816}{3397}{4483}{0961}{5661};
18534     {#1}{0000}{0000};
18535     {
18536         \if_int_odd:w #2 \exp_stop_f:
18537         \exp_after:wN \__fp_fixed_sub:wwn
18538         \else:
18539         \exp_after:wN \__fp_fixed_add:wwn
18540         \fi:
18541     }
18542 }

```

(End definition for __fp_atan_combine_o:NwwwwwN and __fp_atan_combine_aux:ww.)

32.2.2 Arcsine and arccosine

__fp_asin_o:w Again, the first argument provided by l3fp-parse is \use_i:nn if we are to work in radians and \use_ii:nn for degrees. Then comes a floating point number. The arcsine of ± 0 or NaN is the same floating point number. The arcsine of $\pm\infty$ raises an invalid operation exception. Otherwise, call an auxiliary common with __fp_acos_o:w, feeding it information about what function is being performed (for “invalid operation” exceptions).

```

18543 \cs_new:Npn \__fp_asin_o:w #1 \s__fp \__fp_chk:w #2#3; @
18544 {
18545     \if_case:w #2 \exp_stop_f:
18546     \__fp_case_return_same_o:w
18547     \or:
18548     \__fp_case_use:nw
18549     { \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { asin } { asind } } }
18550     \or:
18551     \__fp_case_use:nw
18552     { \__fp_invalid_operation_o:fw { #1 { asin } { asind } } }
18553     \else:
18554     \__fp_case_return_same_o:w
18555     \fi:
18556     \s__fp \__fp_chk:w #2 #3;
18557 }

```

(End definition for __fp_asin_o:w.)

`__fp_acos_o:w` The arccosine of ± 0 is $\pi/2$ (in degrees, 90). The arccosine of $\pm\infty$ raises an invalid operation exception. The arccosine of NaN is itself. Otherwise, call an auxiliary common with `__fp_sin_o:w`, informing it that it was called by `acos` or `acosd`, and preparing to swap some arguments down the line.

```

18558 \cs_new:Npn \__fp_acos_o:w #1 \s__fp \__fp_chk:w #2#3; @
18559 {
18560   \if_case:w #2 \exp_stop_f:
18561     \__fp_case_use:nw { \__fp_atan_inf_o:NNNw #1 0 4 }
18562   \or:
18563     \__fp_case_use:nw
18564     {
18565       \__fp_asin_normal_o:NfwNnnnnw #1 { #1 { acos } { acosd } }
18566       \__fp_reverse_args:Nww
18567     }
18568   \or:
18569     \__fp_case_use:nw
18570     { \__fp_invalid_operation_o:fw { #1 { acos } { acosd } } }
18571   \else:
18572     \__fp_case_return_same_o:w
18573   \fi:
18574   \s__fp \__fp_chk:w #2 #3;
18575 }

```

(End definition for `__fp_acos_o:w`.)

`__fp_asin_normal_o:NfwNnnnnw` If the exponent #5 is at most 0, the operand lies within $(-1, 1)$ and the operation is permitted: call `__fp_asin_auxi_o:NnNww` with the appropriate arguments. If the number is exactly ± 1 (the test works because we know that $\#5 \geq 1$, $\#6\#7 \geq 10000000$, $\#8\#9 \geq 0$, with equality only for ± 1), we also call `__fp_asin_auxi_o:NnNww`. Otherwise, `__fp_use_i:ww` gets rid of the `asin` auxiliary, and raises instead an invalid operation, because the operand is outside the domain of arcsine or arccosine.

```

18576 \cs_new:Npn \__fp_asin_normal_o:NfwNnnnnw
18577   #1#2#3 \s__fp \__fp_chk:w 1#4#5#6#7#8#9;
18578 {
18579   \if_int_compare:w #5 < 1 \exp_stop_f:
18580     \exp_after:wN \__fp_use_none_until_s:w
18581   \fi:
18582   \if_int_compare:w \__fp_int_eval:w #5 + #6#7 + #8#9 = 1000 0001 ~
18583     \exp_after:wN \__fp_use_none_until_s:w
18584   \fi:
18585   \__fp_use_i:ww
18586   \__fp_invalid_operation_o:fw {#2}
18587   \s__fp \__fp_chk:w 1#4{#5}{#6}{#7}{#8}{#9};
18588   \__fp_asin_auxi_o:NnNww
18589   #1 {#3} #4 #5,{#6}{#7}{#8}{#9}{0000}{0000};
18590 }

```

(End definition for `__fp_asin_normal_o:NfwNnnnnw`.)

`__fp_asin_auxi_o:NnNww` We compute $x/\sqrt{1-x^2}$. This function is used by `asin` and `acos`, but also by `acsc` and `asec` after inverting the operand, thus it must manipulate extended-precision numbers. First evaluate $1-x^2$ as $(1+x)(1-x)$: this behaves better near $x = 1$. We do the addition/subtraction with fixed point numbers (they are not implemented for extended-precision floats), but go back to extended-precision floats to multiply and compute the

inverse square root $1/\sqrt{1-x^2}$. Finally, multiply by the (positive) extended-precision float $|x|$, and feed the (signed) result, and the number +1, as arguments to the arctangent function. When computing the arccosine, the arguments $x/\sqrt{1-x^2}$ and +1 are swapped by #2 (`__fp_reverse_args:Nww` in that case) before `__fp_atan_test_o:NwwNwwN` is evaluated. Note that the arctangent function requires normalized arguments, hence the need for `ep_to_ep` and continue after `ep_mul`.

```

18591 \cs_new:Npn \__fp_asin_auxi_o:NnNww #1#2#3#4,#5;
18592 {
18593   \__fp_ep_to_fixed:wwn #4,#5;
18594   \__fp_asin_isqrt:wn
18595   \__fp_ep_mul:wwwwn #4,#5;
18596   \__fp_ep_to_ep:wwN
18597   \__fp_fixed_continue:wn
18598   { #2 \__fp_atan_test_o:NwwNwwN #3 }
18599   0 1,{1000}{0000}{0000}{0000}{0000}{0000}; #1
18600 }
18601 \cs_new:Npn \__fp_asin_isqrt:wn #1;
18602 {
18603   \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_tl #1;
18604   {
18605     \__fp_fixed_add_one:wn #1;
18606     \__fp_fixed_continue:wn { \__fp_ep_mul:wwwwn 0, } 0,
18607   }
18608   \__fp_ep_isqrt:wwn
18609 }

```

(End definition for `__fp_asin_auxi_o:NnNww` and `__fp_asin_isqrt:wn`.)

32.2.3 Arccosecant and arcsecant

`__fp_acsc_o:w` Cases are mostly labelled by #2, except when #2 is 2: then we use #3#2, which is 02 = 2 when the number is $+\infty$ and 22 when the number is $-\infty$. The arccosecant of ± 0 raises an invalid operation exception. The arccosecant of $\pm\infty$ is ± 0 with the same sign. The arcosecant of NaN is itself. Otherwise, `__fp_acsc_normal_o:NfwNnw` does some more tests, keeping the function name (acsc or acscd) as an argument for invalid operation exceptions.

```

18610 \cs_new:Npn \__fp_acsc_o:w #1 \s__fp \__fp_chk:w #2#3#4; @
18611 {
18612   \if_case:w \if_meaning:w 2 #2 #3 \fi: #2 \exp_stop_f:
18613     \__fp_case_use:nw
18614     { \__fp_invalid_operation_o:fw { #1 { acsc } { acscd } } }
18615   \or: \__fp_case_use:nw
18616     { \__fp_acsc_normal_o:NfwNnw #1 { #1 { acsc } { acscd } } }
18617   \or: \__fp_case_return_o:Nw \c_zero_fp
18618   \or: \__fp_case_return_same_o:w
18619   \else: \__fp_case_return_o:Nw \c_minus_zero_fp
18620   \fi:
18621   \s__fp \__fp_chk:w #2 #3 #4;
18622 }

```

(End definition for `__fp_acsc_o:w`.)

`__fp_asec_o:w` The arcsecant of ± 0 raises an invalid operation exception. The arcsecant of $\pm\infty$ is $\pi/2$ (in degrees, 90). The arcosecant of NaN is itself. Otherwise, do some more tests, keeping

the function name `asec` (or `asecd`) as an argument for invalid operation exceptions, and a `__fp_reverse_args:Nww` following precisely that appearing in `__fp_acos_o:w`.

```

18623 \cs_new:Npn \__fp_asec_o:w #1 \s__fp \__fp_chk:w #2#3; @
18624 {
18625   \if_case:w #2 \exp_stop_f:
18626     \__fp_case_use:nw
18627     { \__fp_invalid_operation_o:fw { #1 { asec } { asecd } } }
18628   \or:
18629     \__fp_case_use:nw
18630     {
18631       \__fp_acsc_normal_o:NfwNnw #1 { #1 { asec } { asecd } }
18632       \__fp_reverse_args:Nww
18633     }
18634   \or: \__fp_case_use:nw { \__fp_atan_inf_o:NNnw #1 0 4 }
18635   \else: \__fp_case_return_same_o:w
18636   \fi:
18637   \s__fp \__fp_chk:w #2 #3;
18638 }

```

(End definition for `__fp_asec_o:w`.)

`__fp_acsc_normal_o:NfwNnw`

If the exponent is non-positive, the operand is less than 1 in absolute value, which is always an invalid operation: complain. Otherwise, compute the inverse of the operand, and feed it to `__fp_asin_auxi_o:NnNww` (with all the appropriate arguments). This computes what we want thanks to $\operatorname{acsc}(x) = \operatorname{asin}(1/x)$ and $\operatorname{asec}(x) = \operatorname{acos}(1/x)$.

```

18639 \cs_new:Npn \__fp_acsc_normal_o:NfwNnw #1#2#3 \s__fp \__fp_chk:w 1#4#5#6;
18640 {
18641   \int_compare:nNnTF {#5} < 1
18642   {
18643     \__fp_invalid_operation_o:fw {#2}
18644     \s__fp \__fp_chk:w 1#4{#5}#6;
18645   }
18646   {
18647     \__fp_ep_div:wwwn
18648     1,{1000}{0000}{0000}{0000}{0000};
18649     #5,#6{0000}{0000};
18650     { \__fp_asin_auxi_o:NnNww #1 {#3} #4 }
18651   }
18652 }

```

(End definition for `__fp_acsc_normal_o:NfwNnw`.)

18653 `\</initex | package>`

33 13fp-convert implementation

18654 `<*initex | package>`

18655 `<@@=fp>`

33.1 Dealing with tuples

The first argument is for instance `__fp_to_t1_dispatch:w`, which converts any floating point object to the appropriate representation. We loop through all items, putting `,~` between all of them and making sure to remove the leading `,~`.

```

\__fp_tuple_convert:Nw
\__fp_tuple_convert_loop:nw
\__fp_tuple_convert_end:w

```

```

18656 \cs_new:Npn \__fp_tuple_convert:Nw #1 \s__fp_tuple \__fp_tuple_chk:w #2 ;
18657 {
18658   \int_case:nnF { \__fp_array_count:n {#2} }
18659   {
18660     { 0 } { ( ) }
18661     { 1 } { \__fp_tuple_convert_end:w @ { #1 #2 , } }
18662   }
18663   {
18664     \__fp_tuple_convert_loop:nNw { } #1
18665     #2 { ? \__fp_tuple_convert_end:w } ;
18666     @ { \use_none:nn }
18667   }
18668 }
18669 \cs_new:Npn \__fp_tuple_convert_loop:nNw #1#2#3#4; #5 @ #6
18670 {
18671   \use_none:n #3
18672   \exp_args:Nf \__fp_tuple_convert_loop:nNw { #2 #3#4 ; } #2 #5
18673   @ { #6 , ~ #1 }
18674 }
18675 \cs_new:Npn \__fp_tuple_convert_end:w #1 @ #2
18676 { \exp_after:wN ( \exp:w \exp_end_continue_f:w #2 ) }

```

(End definition for __fp_tuple_convert:Nw, __fp_tuple_convert_loop:nNw, and __fp_tuple_convert_end:w.)

33.2 Trimming trailing zeros

__fp_trim_zeros:w If #1 ends with a 0, the loop auxiliary takes that zero as an end-delimiter for its first argument, and the second argument is the same loop auxiliary. Once the last trailing zero is reached, the second argument is the dot auxiliary, which removes a trailing dot if any. We then clean-up with the end auxiliary, keeping only the number.

```

18677 \cs_new:Npn \__fp_trim_zeros:w #1 ;
18678 {
18679   \__fp_trim_zeros_loop:w #1
18680   ; \__fp_trim_zeros_loop:w 0; \__fp_trim_zeros_dot:w .; \s_stop
18681 }
18682 \cs_new:Npn \__fp_trim_zeros_loop:w #1 0; #2 { #2 #1 ; #2 }
18683 \cs_new:Npn \__fp_trim_zeros_dot:w #1 .; { \__fp_trim_zeros_end:w #1 ; }
18684 \cs_new:Npn \__fp_trim_zeros_end:w #1 ; #2 \s_stop { #1 }

```

(End definition for __fp_trim_zeros:w and others.)

33.3 Scientific notation

\fp_to_scientific:N The three public functions evaluate their argument, then pass it to __fp_to_scientific_dispatch:w.

```

\fp_to_scientific:c
\fp_to_scientific:n
18685 \cs_new:Npn \fp_to_scientific:N #1
18686 { \exp_after:wN \__fp_to_scientific_dispatch:w #1 }
18687 \cs_generate_variant:Nn \fp_to_scientific:N { c }
18688 \cs_new:Npn \fp_to_scientific:n
18689 {
18690   \exp_after:wN \__fp_to_scientific_dispatch:w
18691   \exp:w \exp_end_continue_f:w \__fp_parse:n
18692 }

```

(End definition for `\fp_to_scientific:N` and `\fp_to_scientific:n`. These functions are documented on page 186.)

```

\__fp_to_scientific_dispatch:w
\__fp_to_scientific_recover:w
\__fp_tuple_to_scientific:w
18693 \cs_new:Npn \__fp_to_scientific_dispatch:w #1
18694 {
18695   \__fp_change_func_type:NNN
18696   #1 \__fp_to_scientific:w \__fp_to_scientific_recover:w
18697   #1
18698 }
18699 \cs_new:Npn \__fp_to_scientific_recover:w #1 #2 ;
18700 {
18701   \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { }
18702   nan
18703 }
18704 \cs_new:Npn \__fp_tuple_to_scientific:w
18705 { \__fp_tuple_convert:Nw \__fp_to_scientific_dispatch:w }

```

(End definition for `__fp_to_scientific_dispatch:w`, `__fp_to_scientific_recover:w`, and `__fp_tuple_to_scientific:w`.)

`__fp_to_scientific:w` Expressing an internal floating point number in scientific notation is quite easy: no rounding, and the format is very well defined. First cater for the sign: negative numbers (#2 = 2) start with -; we then only need to care about positive numbers and `nan`. Then filter the special cases: ± 0 are represented as 0; infinities are converted to a number slightly larger than the largest after an “invalid_operation” exception; `nan` is represented as 0 after an “invalid_operation” exception. In the normal case, decrement the exponent and unbrace the 4 brace groups, then in a second step grab the first digit (previously hidden in braces) to order the various parts correctly.

```

18706 \cs_new:Npn \__fp_to_scientific:w \s__fp \__fp_chk:w #1#2
18707 {
18708   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
18709   \if_case:w #1 \exp_stop_f:
18710     \__fp_case_return:nw { 0.000000000000000e0 }
18711   \or: \exp_after:wN \__fp_to_scientific_normal:wnnnnn
18712   \or:
18713     \__fp_case_use:nw
18714     {
18715       \__fp_invalid_operation:nnw
18716       { \fp_to_scientific:N \c__fp_overflowing_fp }
18717       { fp_to_scientific }
18718     }
18719   \or:
18720     \__fp_case_use:nw
18721     {
18722       \__fp_invalid_operation:nnw
18723       { \fp_to_scientific:N \c_zero_fp }
18724       { fp_to_scientific }
18725     }
18726   \fi:
18727   \s__fp \__fp_chk:w #1 #2
18728 }
18729 \cs_new:Npn \__fp_to_scientific_normal:wnnnnn
18730 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;

```

```

18731 {
18732     \exp_after:wN \_fp_to_scientific_normal:wNw
18733     \exp_after:wN e
18734     \int_value:w \_fp_int_eval:w #2 - 1
18735     ; #3 #4 #5 #6 ;
18736 }
18737 \cs_new:Npn \_fp_to_scientific_normal:wNw #1 ; #2#3;
18738 { #2.#3 #1 }

```

(End definition for `_fp_to_scientific:w`, `_fp_to_scientific_normal:wnnnnn`, and `_fp_to_scientific_normal:wNw`.)

33.4 Decimal representation

`\fp_to_decimal:N` All three public variants are based on the same `_fp_to_decimal_dispatch:w` after evaluating their argument to an internal floating point.

```

\fp_to_decimal:c
\fp_to_decimal:n
18739 \cs_new:Npn \fp_to_decimal:N #1
18740 { \exp_after:wN \_fp_to_decimal_dispatch:w #1 }
18741 \cs_generate_variant:Nn \fp_to_decimal:N { c }
18742 \cs_new:Npn \fp_to_decimal:n
18743 {
18744     \exp_after:wN \_fp_to_decimal_dispatch:w
18745     \exp:w \exp_end_continue_f:w \_fp_parse:n
18746 }

```

(End definition for `\fp_to_decimal:N` and `\fp_to_decimal:n`. These functions are documented on page 186.)

```

\_fp_to_decimal_dispatch:w
\_fp_to_decimal_recover:w
\_fp_tuple_to_decimal:w
We allow tuples.
18747 \cs_new:Npn \_fp_to_decimal_dispatch:w #1
18748 {
18749     \_fp_change_func_type:NNN
18750     #1 \_fp_to_decimal:w \_fp_to_decimal_recover:w
18751     #1
18752 }
18753 \cs_new:Npn \_fp_to_decimal_recover:w #1 #2 ;
18754 {
18755     \_fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { } { }
18756     nan
18757 }
18758 \cs_new:Npn \_fp_tuple_to_decimal:w
18759 { \_fp_tuple_convert:Nw \_fp_to_decimal_dispatch:w }

```

(End definition for `_fp_to_decimal_dispatch:w`, `_fp_to_decimal_recover:w`, and `_fp_tuple_to_decimal:w`.)

```

\_fp_to_decimal:w
\_fp_to_decimal_normal:wnnnnn
\_fp_to_decimal_large:Nnnw
\_fp_to_decimal_huge:wnnnnn
The structure is similar to \_fp_to_scientific:w. Insert - for negative numbers. Zero gives 0,  $\pm\infty$  and NaN yield an “invalid operation” exception; note that  $\pm\infty$  produces a very large output, which we don’t expand now since it most likely won’t be needed. Normal numbers with an exponent in the range [1, 15] have that number of digits before the decimal separator: “decimate” them, and remove leading zeros with \int_value:w, then trim trailing zeros and dot. Normal numbers with an exponent 16 or larger have no decimal separator, we only need to add trailing zeros. When the exponent is non-positive, the result should be 0.<zeros><digits>, trimmed.

```



```

18760 \cs_new:Npn \__fp_to_decimal:w \s__fp \__fp_chk:w #1#2
18761 {
18762   \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
18763   \if_case:w #1 \exp_stop_f:
18764     \__fp_case_return:nw { 0 }
18765   \or: \exp_after:wN \__fp_to_decimal_normal:wnnnnn
18766   \or:
18767     \__fp_case_use:nw
18768     {
18769       \__fp_invalid_operation:nnw
18770       { \fp_to_decimal:N \c__fp_overflowing_fp }
18771       { fp_to_decimal }
18772     }
18773   \or:
18774     \__fp_case_use:nw
18775     {
18776       \__fp_invalid_operation:nnw
18777       { 0 }
18778       { fp_to_decimal }
18779     }
18780   \fi:
18781   \s__fp \__fp_chk:w #1 #2
18782 }
18783 \cs_new:Npn \__fp_to_decimal_normal:wnnnnn
18784 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
18785 {
18786   \int_compare:nNnTF {#2} > 0
18787   {
18788     \int_compare:nNnTF {#2} < \c__fp_prec_int
18789     {
18790       \__fp_decimate:nNnnnn { \c__fp_prec_int - #2 }
18791       \__fp_to_decimal_large:Nnnw
18792     }
18793     {
18794       \exp_after:wN \exp_after:wN
18795       \exp_after:wN \__fp_to_decimal_huge:wnnnnn
18796       \prg_replicate:nn { #2 - \c__fp_prec_int } { 0 } ;
18797     }
18798     {#3} {#4} {#5} {#6}
18799   }
18800   {
18801     \exp_after:wN \__fp_trim_zeros:w
18802     \exp_after:wN 0
18803     \exp_after:wN .
18804     \exp:w \exp_end_continue_f:w \prg_replicate:nn { - #2 } { 0 }
18805     #3#4#5#6 ;
18806   }
18807 }
18808 \cs_new:Npn \__fp_to_decimal_large:Nnnw #1#2#3#4;
18809 {
18810   \exp_after:wN \__fp_trim_zeros:w \int_value:w
18811   \if_int_compare:w #2 > 0 \exp_stop_f:
18812   #2
18813   \fi:

```

```

18814         \exp_stop_f:
18815         #3.#4 ;
18816     }
18817 \cs_new:Npn \__fp_to_decimal_huge:wnnnn #1; #2#3#4#5 { #2#3#4#5 #1 }

```

(End definition for __fp_to_decimal:w and others.)

33.5 Token list representation

\fp_to_tl:N These three public functions evaluate their argument, then pass it to __fp_to_tl_dispatch:w.

```

\fp_to_tl:c dispatch:w.
\fp_to_tl:n
18818 \cs_new:Npn \fp_to_tl:N #1 { \exp_after:wN \__fp_to_tl_dispatch:w #1 }
18819 \cs_generate_variant:Nn \fp_to_tl:N { c }
18820 \cs_new:Npn \fp_to_tl:n
18821 {
18822     \exp_after:wN \__fp_to_tl_dispatch:w
18823     \exp:w \exp_end_continue_f:w \__fp_parse:n
18824 }

```

(End definition for \fp_to_tl:N and \fp_to_tl:n. These functions are documented on page 186.)

```

\__fp_to_tl_dispatch:w We allow tuples.
\__fp_to_tl_recover:w
\__fp_tuple_to_tl:w
18825 \cs_new:Npn \__fp_to_tl_dispatch:w #1
18826 { \__fp_change_func_type:NNN #1 \__fp_to_tl:w \__fp_to_tl_recover:w #1 }
18827 \cs_new:Npn \__fp_to_tl_recover:w #1 #2 ;
18828 {
18829     \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { }
18830     nan
18831 }
18832 \cs_new:Npn \__fp_tuple_to_tl:w
18833 { \__fp_tuple_convert:Nw \__fp_to_tl_dispatch:w }

```

(End definition for __fp_to_tl_dispatch:w, __fp_to_tl_recover:w, and __fp_tuple_to_tl:w.)

__fp_to_tl:w A structure similar to __fp_to_scientific_dispatch:w and __fp_to_decimal_dispatch:w, but without the “invalid operation” exception. First filter special cases. We express normal numbers in decimal notation if the exponent is in the range $[-2, 16]$, and otherwise use scientific notation.

```

18834 \cs_new:Npn \__fp_to_tl:w \s__fp \__fp_chk:w #1#2
18835 {
18836     \if_meaning:w 2 #2 \exp_after:wN - \exp:w \exp_end_continue_f:w \fi:
18837     \if_case:w #1 \exp_stop_f:
18838         \__fp_case_return:nw { 0 }
18839     \or: \exp_after:wN \__fp_to_tl_normal:nnnnn
18840     \or: \__fp_case_return:nw { inf }
18841     \else: \__fp_case_return:nw { nan }
18842     \fi:
18843 }
18844 \cs_new:Npn \__fp_to_tl_normal:nnnnn #1
18845 {
18846     \int_compare:nTF
18847     { -2 <= #1 <= \c__fp_prec_int }
18848     { \__fp_to_decimal_normal:wnnnnn }
18849     { \__fp_to_tl_scientific:wnnnnn }

```

```

18850     \s__fp \__fp_chk:w 1 0 {#1}
18851   }
18852 \cs_new:Npn \__fp_to_tl_scientific:wnnnnn
18853   \s__fp \__fp_chk:w 1 #1 #2 #3#4#5#6 ;
18854   {
18855     \exp_after:wN \__fp_to_tl_scientific:wNw
18856     \exp_after:wN e
18857     \int_value:w \__fp_int_eval:w #2 - 1
18858     ; #3 #4 #5 #6 ;
18859   }
18860 \cs_new:Npn \__fp_to_tl_scientific:wNw #1 ; #2#3;
18861   { \__fp_trim_zeros:w #2.#3 ; #1 }

```

(End definition for `__fp_to_tl:w` and others.)

33.6 Formatting

This is not implemented yet, as it is not yet clear what a correct interface would be, for this kind of structured conversion from a floating point (or other types of variables) to a string. Ideas welcome.

33.7 Convert to dimension or integer

`\fp_to_dim:N` All three public variants are based on the same `__fp_to_dim_dispatch:w` after evaluating their argument to an internal floating point. We only allow floating point numbers, not tuples.

```

\__fp_to_dim_dispatch:w 18862 \cs_new:Npn \fp_to_dim:N #1
\__fp_to_dim_recover:w 18863   { \exp_after:wN \__fp_to_dim_dispatch:w #1 }
\__fp_to_dim:w 18864 \cs_generate_variant:Nn \fp_to_dim:N { c }
18865 \cs_new:Npn \fp_to_dim:n
18866   {
18867     \exp_after:wN \__fp_to_dim_dispatch:w
18868     \exp:w \exp_end_continue_f:w \__fp_parse:n
18869   }
18870 \cs_new:Npn \__fp_to_dim_dispatch:w #1#2 ;
18871   {
18872     \__fp_change_func_type:NNN #1 \__fp_to_dim:w \__fp_to_dim_recover:w
18873     #1 #2 ;
18874   }
18875 \cs_new:Npn \__fp_to_dim_recover:w #1
18876   { \__fp_invalid_operation:nnw { 0pt } { fp_to_dim } }
18877 \cs_new:Npn \__fp_to_dim:w #1 ; { \__fp_to_decimal:w #1 ; pt }

```

(End definition for `\fp_to_dim:N` and others. These functions are documented on page 186.)

`\fp_to_int:N` For the most part identical to `\fp_to_dim:N` but without `pt`, and where `__fp_to_int:w` does more work. To convert to an integer, first round to 0 places (to the nearest integer), then express the result as a decimal number: the definition of `__fp_to_decimal_dispatch:w` is such that there are no trailing dot nor zero.

```

\__fp_to_int_dispatch:w 18878 \cs_new:Npn \fp_to_int:N #1 { \exp_after:wN \__fp_to_int_dispatch:w #1 }
\__fp_to_int_recover:w 18879 \cs_generate_variant:Nn \fp_to_int:N { c }
18880 \cs_new:Npn \fp_to_int:n
18881   {

```

```

18882 \exp_after:wN \__fp_to_int_dispatch:w
18883 \exp:w \exp_end_continue_f:w \__fp_parse:n
18884 }
18885 \cs_new:Npn \__fp_to_int_dispatch:w #1#2 ;
18886 {
18887   \__fp_change_func_type:NNN #1 \__fp_to_int:w \__fp_to_int_recover:w
18888   #1 #2 ;
18889 }
18890 \cs_new:Npn \__fp_to_int_recover:w #1
18891 { \__fp_invalid_operation:nw { 0 } { fp_to_int } }
18892 \cs_new:Npn \__fp_to_int:w #1;
18893 {
18894   \exp_after:wN \__fp_to_decimal:w \exp:w \exp_end_continue_f:w
18895   \__fp_round:Nwn \__fp_round_to_nearest:NNN #1; { 0 }
18896 }

```

(End definition for `\fp_to_int:N` and others. These functions are documented on page 186.)

33.8 Convert from a dimension

```

\dim_to_fp:n
\__fp_from_dim_test:ww
\__fp_from_dim:wNw
\__fp_from_dim:wNNnnnnnn
\__fp_from_dim:wnnnnwNw

```

The dimension expression (which can in fact be a glue expression) is evaluated, converted to a number (*i.e.*, expressed in scaled points), then multiplied by $2^{-16} = 0.0000152587890625$ to give a value expressed in points. The auxiliary `__fp_mul_npos_o:Nww` expects the desired *final sign* and two floating point operands (of the form `\s__fp ...`;) as arguments. This set of functions is also used to convert dimension registers to floating points while parsing expressions: in this context there is an additional exponent, which is the first argument of `__fp_from_dim_test:ww`, and is combined with the exponent -4 of 2^{-16} . There is also a need to expand afterwards: this is performed by `__fp_mul_npos_o:Nww`, and cancelled by `\prg_do_nothing`: here.

```

18897 \__kernel_patch_args:nNNpn { { (#1) } }
18898 \cs_new:Npn \dim_to_fp:n #1
18899 {
18900   \exp_after:wN \__fp_from_dim_test:ww
18901   \exp_after:wN 0
18902   \exp_after:wN ,
18903   \int_value:w \tex_glueexpr:D #1 ;
18904 }
18905 \cs_new:Npn \__fp_from_dim_test:ww #1, #2
18906 {
18907   \if_meaning:w 0 #2
18908     \__fp_case_return:nw { \exp_after:wN \c_zero_fp }
18909   \else:
18910     \exp_after:wN \__fp_from_dim:wNw
18911     \int_value:w \__fp_int_eval:w #1 - 4
18912     \if_meaning:w - #2
18913       \exp_after:wN , \exp_after:wN 2 \int_value:w
18914     \else:
18915       \exp_after:wN , \exp_after:wN 0 \int_value:w #2
18916     \fi:
18917   \fi:
18918 }
18919 \cs_new:Npn \__fp_from_dim:wNw #1,#2#3;
18920 {

```

```

18921     \__fp_pack_twice_four:wNNNNNNNN \__fp_from_dim:wNNnnnnnn ;
18922     #3 000 0000 00 {10}987654321; #2 {#1}
18923 }
18924 \cs_new:Npn \__fp_from_dim:wNNnnnnnn #1; #2#3#4#5#6#7#8#9
18925 { \__fp_from_dim:wnnnnwNn #1 {#2#300} {0000} ; }
18926 \cs_new:Npn \__fp_from_dim:wnnnnwNn #1; #2#3#4#5#6; #7#8
18927 {
18928     \__fp_mul_npos_o:Nww #7
18929     \s__fp \__fp_chk:w 1 #7 {#5} #1 ;
18930     \s__fp \__fp_chk:w 1 0 {#8} {1525} {8789} {0625} {0000} ;
18931     \prg_do_nothing:
18932 }

```

(End definition for `\dim_to_fp:n` and others. This function is documented on page 160.)

33.9 Use and eval

\fp_use:N Those public functions are simple copies of the decimal conversions.
\fp_use:c 18933 \cs_new_eq:NN \fp_use:N \fp_to_decimal:N
\fp_eval:n 18934 \cs_generate_variant:Nn \fp_use:N { c }
18935 \cs_new_eq:NN \fp_eval:n \fp_to_decimal:n

(End definition for `\fp_use:N` and `\fp_eval:n`. These functions are documented on page 187.)

\fp_abs:n Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `__fp_parse:n`, namely, for better error reporting.
18936 \cs_new:Npn \fp_abs:n #1
18937 { \fp_to_decimal:n { abs __fp_parse:n {#1} } }

(End definition for `\fp_abs:n`. This function is documented on page 201.)

\fp_max:nn Similar to `\fp_abs:n`, for consistency with `\int_max:nn`, etc.
\fp_min:nn 18938 \cs_new:Npn \fp_max:nn #1#2
18939 { \fp_to_decimal:n { max (__fp_parse:n {#1} , __fp_parse:n {#2}) } }
18940 \cs_new:Npn \fp_min:nn #1#2
18941 { \fp_to_decimal:n { min (__fp_parse:n {#1} , __fp_parse:n {#2}) } }

(End definition for `\fp_max:nn` and `\fp_min:nn`. These functions are documented on page 201.)

33.10 Convert an array of floating points to a comma list

`__fp_array_to_clist:n` Converts an array of floating point numbers to a comma-list. If speed here ends up irrelevant, we can simplify the code for the auxiliary to become

```

\cs_new:Npn \__fp_array_to_clist_loop:Nw #1#2;
{
    \use_none:n #1
    { , ~ } \fp_to_tl:n { #1 #2 ; }
    \__fp_array_to_clist_loop:Nw
}

```

The `\use_ii:nn` function is expanded after `__fp_expand:n` is done, and it removes ,~ from the start of the representation.

```

18942 \cs_new:Npn \__fp_array_to_clist:n #1
18943 {
18944   \tl_if_empty:nF {#1}
18945   {
18946     \__fp_expand:n
18947     {
18948       { \use_ii:nn }
18949       \__fp_array_to_clist_loop:Nw #1 { ? \prg_break: } ;
18950       \prg_break_point:
18951     }
18952   }
18953 }
18954 \cs_new:Npx \__fp_array_to_clist_loop:Nw #1#2;
18955 {
18956   \exp_not:N \use_none:n #1
18957   \exp_not:N \exp_after:wN
18958   {
18959     \exp_not:N \exp_after:wN ,
18960     \exp_not:N \exp_after:wN \c_space_tl
18961     \exp_not:N \exp:w
18962     \exp_not:N \exp_end_continue_f:w
18963     \exp_not:N \__fp_to_tl_dispatch:w #1 #2 ;
18964   }
18965   \exp_not:N \__fp_array_to_clist_loop:Nw
18966 }

```

(End definition for `__fp_array_to_clist:n` and `__fp_array_to_clist_loop:Nw`.)

```

18967 </initex | package>

```

34 l3fp-random Implementation

```

18968 <*initex | package>

```

```

18969 <@@=fp>

```

`__fp_parse_word_rand:N` Those functions may receive a variable number of arguments. We won't use the argument ?.

```

18970 \cs_new:Npn \__fp_parse_word_rand:N
18971 { \__fp_parse_function:NNN \__fp_rand_o:Nw ? }
18972 \cs_new:Npn \__fp_parse_word_randint:N
18973 { \__fp_parse_function:NNN \__fp_randint_o:Nw ? }

```

(End definition for `__fp_parse_word_rand:N` and `__fp_parse_word_randint:N`.)

34.1 Engine support

Most engines provide random numbers, but not all. We write the test twice simply in order to write the `false` branch first.

```

18974 \sys_if_rand_exist:F
18975 {
18976   \__kernel_msg_new:nnn { kernel } { fp-no-random }

```

```

18977     { Random~numbers~unavailable~for~#1 }
18978 \cs_new:Npn \__fp_rand_o:Nw ? #1 @
18979     {
18980       \__kernel_msg_expandable_error:nnn { kernel } { fp-no-random }
18981       { fp~rand }
18982       \exp_after:wN \c_nan_fp
18983     }
18984 \cs_new_eq:NN \__fp_randint_o:Nw \__fp_rand_o:Nw
18985 \cs_new:Npn \int_rand:nn #1#2
18986     {
18987       \__kernel_msg_expandable_error:nnn { kernel } { fp-no-random }
18988       { \int_rand:nn {#1} {#2} }
18989       \int_eval:n {#1}
18990     }
18991 \cs_new:Npn \int_rand:n #1
18992     {
18993       \__kernel_msg_expandable_error:nnn { kernel } { fp-no-random }
18994       { \int_rand:n {#1} }
18995       1
18996     }
18997 }
18998 \sys_if_rand_exist:T
18999 {

```

Obviously, every word “random” below means “pseudo-random”, as we have no access to entropy (except a very unreliable source of entropy: the time it takes to run some code).

The primitive random number generator (RNG) is provided as `\tex_uniformdeviate:D`. Under the hood, it maintains an array of 55 28-bit numbers, updated with a linear recursion relation (similar to Fibonacci numbers) modulo 2^{28} . When `\tex_uniformdeviate:D` $\langle integer \rangle$ is called (for brevity denote by N the $\langle integer \rangle$), the next 28-bit number is read from the array, scaled by $N/2^{28}$, and rounded. To prevent 0 and N from appearing half as often as other numbers, they are both mapped to the result 0.

This process means that `\tex_uniformdeviate:D` only gives a uniform distribution from 0 to $N-1$ if N is a divisor of 2^{28} , so we will mostly call the RNG with such power of 2 arguments. If N does not divide 2^{28} , then the relative non-uniformity (difference between probabilities of getting different numbers) is about $N/2^{28}$. This implies that detecting deviation from $1/N$ of the probability of a fixed value X requires about $2^{56}/N$ random trials. But collective patterns can reduce this to about $2^{56}/N^2$. For instance with $N = 3 \times 2^k$, the modulo 3 repartition of such random numbers is biased with a non-uniformity about $2^k/2^{28}$ (which is much worse than the circa $3/2^{28}$ non-uniformity from taking directly $N = 3$). This is detectable after about $2^{56}/2^{2k} = 9 \cdot 2^{56}/N^2$ random numbers. For $k = 15$, $N = 98304$, this means roughly 2^{26} calls to the RNG (experimentally this takes at the very least 16 seconds on a 2 giga-hertz processor). While this bias is not quite problematic, it is uncomfortably close to being so, and it becomes worse as N is increased. In our code, we shall thus combine several results from the RNG.

The RNG has three types of unexpected correlations. First, everything is linear modulo 2^{28} , hence the lowest k bits of the random numbers only depend on the lowest k bits of the seed (and of course the number of times the RNG was called since setting the seed). The recommended way to get a number from 0 to $N-1$ is thus to scale the raw 28-bit integer, as the engine’s RNG does. We will go further and in fact typically we discard some of the lowest bits.

Second, suppose that we call the RNG with the same argument N to get a set of K integers in $[0, N - 1]$ (throwing away repeats), and suppose that $N > K^3$ and $K > 55$. The recursion used to construct more 28-bit numbers from previous ones is linear: $x_n = x_{n-55} - x_{n-24}$ or $x_n = x_{n-55} - x_{n-24} + 2^{28}$. After rescaling and rounding we find that the result $N_n \in [0, N - 1]$ is among $N_{n-55} - N_{n-24} + \{-1, 0, 1\}$ modulo N (a more detailed analysis shows that 0 appears with frequency close to $3/4$). The resulting set thus has more triplets (a, b, c) than expected obeying $a = b + c$ modulo N . Namely it will have of order $(K - 55) \times 3/4$ such triplets, when one would expect $K^3/(6N)$. This starts to be detectable around $N = 2^{18} > 55^3$ (earlier if one keeps track of positions too, but this is more subtle than it looks because the array of 28-bit integers is read backwards by the engine). Hopefully the correlation is subtle enough to not affect realistic documents so we do not specifically mitigate against this. Since we typically use two calls to the RNG per `\int_rand:nn` we would need to investigate linear relations between the x_{2n} on the one hand and between the x_{2n+1} on the other hand. Such relations will have more complicated coefficients than ± 1 , which alleviates the issue.

Third, consider successive batches of 165 calls to the RNG (with argument 2^{28} or with argument 2 for instance), then most batches have more odd than even numbers. Note that this does not mean that there are more odd than even numbers overall. Similar issues are discussed in Knuth's TAOCP volume 2 near exercise 3.3.2-31. We do not have any mitigation strategy for this.

Ideally, our algorithm should be:

- Uniform. The result should be as uniform as possible assuming that the RNG's underlying 28-bit integers are uniform.
- Uncorrelated. The result should not have detectable correlations between different seeds, similar to the lowest-bit ones mentioned earlier.
- Quick. The algorithm should be fast in $\text{T}_{\text{E}}\text{X}$, so no “bit twiddling”, but “digit twiddling” is ok.
- Simple. The behaviour must be documentable precisely.
- Predictable. The number of calls to the RNG should be the same for any `\int_rand:nn`, because then the algorithm can be modified later without changing the result of other uses of the RNG.
- Robust. It should work even for `\int_rand:nn { - \c_max_int } { \c_max_int }` where the range is not representable as an integer. In fact, we also provide later a floating-point `randint` whose range can go all the way up to $2 \times 10^{16} - 1$ possible values.

Some of these requirements conflict. For instance, uniformity cannot be achieved with a fixed number of calls to the RNG.

Denote by `random(N)` one call to `\tex_uniformdeviate:D` with argument N , and by `ediv(p, q)` the ε - $\text{T}_{\text{E}}\text{X}$ rounding division giving $\lfloor p/q + 1/2 \rfloor$. Denote by $\langle \min \rangle$, $\langle \max \rangle$ and $R = \langle \max \rangle - \langle \min \rangle + 1$ the arguments of `\int_min:nn` and the number of possible outcomes. Note that $R \in [1, 2^{32} - 1]$ cannot necessarily be represented as an integer (however, $R - 2^{31}$ can). Our strategy is to get two 28-bit integers X and Y from the RNG, split each into 14-bit integers, as $X = X_1 \times 2^{14} + X_0$ and $Y = Y_1 \times 2^{14} + Y_0$ then return essentially $\langle \min \rangle + \lfloor R(X_1 \times 2^{-14} + Y_1 \times 2^{-28} + Y_0 \times 2^{-42} + X_0 \times 2^{-56}) \rfloor$. For small R the X_0 term has a tiny effect so we ignore it and we can compute $R \times Y/2^{28}$ much more directly by `random(R)`.

- If $R \leq 2^{17} - 1$ then return $\text{ediv}(R \text{ random}(2^{14}) + \text{random}(R) + 2^{13}, 2^{14}) - 1 + \langle \min \rangle$. The shifts by 2^{13} and -1 convert $\varepsilon\text{-TeX}$ division to truncated division. The bound on R ensures that the number obtained after the shift is less than $\backslash\text{c_max_int}$. The non-uniformity is at most of order $2^{17}/2^{42} = 2^{-25}$.
- Split $R = R_2 \times 2^{28} + R_1 \times 2^{14} + R_0$, where $R_2 \in [0, 15]$. Compute $\langle \min \rangle + R_2 X_1 2^{14} + (R_2 Y_1 + R_1 X_1) + \text{ediv}(R_2 Y_0 + R_1 Y_1 + R_0 X_1 + \text{ediv}(R_2 X_0 + R_0 Y_1 + \text{ediv}((2^{14} R_1 + R_0)(2^{14} Y_0 + X_0), 2^{28}), 2^{14}), 2^{14})$ then map a result of $\langle \max \rangle + 1$ to $\langle \min \rangle$. Writing each ediv in terms of truncated division with a shift, and using $\lfloor (p + \lfloor r/s \rfloor)/q \rfloor = \lfloor (ps + r)/(sq) \rfloor$, what we compute is equal to $\lfloor \langle \text{exact} \rangle + 2^{-29} + 2^{-15} + 2^{-1} \rfloor$ with $\langle \text{exact} \rangle = \langle \min \rangle + R \times 0.X_1 Y_1 Y_0 X_0$. Given we map $\langle \max \rangle + 1$ to $\langle \min \rangle$, the shift has no effect on uniformity. The non-uniformity is bounded by $R/2^{56} < 2^{-24}$. It may be possible to speed up the code by dropping tiny terms such as $R_0 X_0$, but the analysis of non-uniformity proves too difficult.

To avoid the overflow when the computation yields $\langle \max \rangle + 1$ with $\langle \max \rangle = 2^{31} - 1$ (note that R is then arbitrary), we compute the result in two pieces. Compute $\langle \text{first} \rangle = \langle \min \rangle + R_2 X_1 2^{14}$ if $R_2 < 8$ or $\langle \min \rangle + 8 X_1 2^{14} + (R_2 - 8) X_1 2^{14}$ if $R_2 \geq 8$, the expressions being chosen to avoid overflow. Compute $\langle \text{second} \rangle = R_2 Y_1 + R_1 X_1 + \text{ediv}(\dots)$, at most $R_2 2^{14} + R_1 2^{14} + R_0 \leq 2^{28} + 15 \times 2^{14} - 1$, not at risk of overflowing. We have $\langle \text{first} \rangle + \langle \text{second} \rangle = \langle \max \rangle + 1 = \langle \min \rangle + R$ if and only if $\langle \text{second} \rangle = R 2^{14} + R_0 + R_2 2^{14}$ and $2^{14} R_2 X_1 = 2^{28} R_2 - 2^{14} R_2$ (namely $R_2 = 0$ or $X_1 = 2^{14} - 1$). In that case, return $\langle \min \rangle$, otherwise return $\langle \text{first} \rangle + \langle \text{second} \rangle$, which is safe because it is at most $\langle \max \rangle$. Note that the decision of what to return does not need $\langle \text{first} \rangle$ explicitly so we don't actually compute it, just put it in an integer expression in which $\langle \text{second} \rangle$ is eventually added (or not).

- To get a floating point number in $[0, 1)$ just call the $R = 10000 \leq 2^{17} - 1$ procedure above to produce four blocks of four digits.
- To get an integer floating point number in a range (whose size can be up to $2 \times 10^{16} - 1$), work with fixed-point numbers: get six times four digits to build a fixed point number, multiply by R and add $\langle \min \rangle$. This requires some care because `l3fp-extended` only supports non-negative numbers.

`\c__kernel_randint_max_int` Constant equal to $2^{17} - 1$, the maximal size of a range that `\int_range:nn` can do with its “simple” algorithm.

```
19000      \int_const:Nn \c__kernel_randint_max_int { 131071 }
```

(End definition for `\c__kernel_randint_max_int`.)

`__kernel_randint:n` Used in an integer expression, `__kernel_randint:n {R}` gives a random number $1 + \lfloor (R \text{ random}(2^{14}) + \text{random}(R))/2^{14} \rfloor$ that is in $[1, R]$. Previous code was computing $\lfloor p/2^{14} \rfloor$ as $\text{ediv}(p - 2^{13}, 2^{14})$ but that wrongly gives -1 for $p = 0$.

```
19001      \cs_new:Npn \__kernel_randint:n #1
19002      {
19003          (#1 * \tex_uniformdeviate:D 16384
19004          + \tex_uniformdeviate:D #1 + 8192 ) / 16384
19005      }
```

(End definition for `__kernel_randint:n`.)

Used as `__fp_rand_myriads:n {XXX}` with one letter X (specifically) per block of four digit we want; it expands to ; followed by the requested number of brace groups, each containing four (pseudo-random) digits. Digits are produced as a random number in [10000, 19999] for the usual reason of preserving leading zeros.

```

19006 \cs_new:Npn \__fp_rand_myriads:n #1
19007 { \__fp_rand_myriads_loop:w #1 \prg_break: X \prg_break_point: ; }
19008 \cs_new:Npn \__fp_rand_myriads_loop:w #1 X
19009 {
19010   #1
19011   \exp_after:wN \__fp_rand_myriads_get:w
19012   \int_value:w \__fp_int_eval:w 9999 +
19013   \__kernel_randint:n { 10000 }
19014   \__fp_rand_myriads_loop:w
19015 }
19016 \cs_new:Npn \__fp_rand_myriads_get:w 1 #1 ; { ; {#1} }

```

(End definition for `__fp_rand_myriads:n`, `__fp_rand_myriads_loop:w`, and `__fp_rand_myriads_get:w`.)

34.2 Random floating point

First we check that `random` was called without argument. Then get four blocks of four digits and convert that fixed point number to a floating point number (this correctly sets the exponent). This has a minor bug: if all of the random numbers are zero then the result is correctly 0 but it raises the underflow flag; it should not do that.

```

19017 \cs_new:Npn \__fp_rand_o:Nw ? #1 @
19018 {
19019   \tl_if_empty:nTF {#1}
19020   {
19021     \exp_after:wN \__fp_rand_o:w
19022     \exp:w \exp_end_continue_f:w
19023     \__fp_rand_myriads:n { XXXX } { 0000 } { 0000 } ; 0
19024   }
19025   {
19026     \__kernel_msg_expandable_error:nnnnn
19027     { kernel } { fp-num-args } { rand() } { 0 } { 0 }
19028     \exp_after:wN \c_nan_fp
19029   }
19030 }
19031 \cs_new:Npn \__fp_rand_o:w ;
19032 {
19033   \exp_after:wN \__fp_sanitise:Nw
19034   \exp_after:wN 0
19035   \int_value:w \__fp_int_eval:w \c_zero_int
19036   \__fp_fixed_to_float_o:wN
19037 }

```

(End definition for `__fp_rand_o:Nw` and `__fp_rand_o:w`.)

34.3 Random integer

Enforce that there is one argument (then add first argument 1) or two arguments. Call `__fp_randint_badarg:w` on each; this function inserts 1 `\exp_stop_f:` to end the

```

\__fp_randint_o:Nw
\__fp_randint_default:w
\__fp_randint_badarg:w
\__fp_randint_o:w
\__fp_randint_auxi_o:ww
\__fp_randint_auxii:wn
\__fp_randint_auxiii_o:ww
\__fp_randint_auxiv_o:ww
\__fp_randint_auxv_o:w

```

\if_case:w statement if either the argument is not an integer or if its absolute value is $\geq 10^{16}$. Also bail out if _fp_compare_back:ww yields 1, meaning that the bounds are not in the right order. Otherwise an auxiliary converts each argument times 10^{-16} (hence the shift in exponent) to a 24-digit fixed point number (see l3fp-extended). Then compute the number of choices, $\langle max \rangle + 1 - \langle min \rangle$. Create a random 24-digit fixed-point number with _fp_rand_myriads:n, then use a fused multiply-add instruction to multiply the number of choices to that random number and add it to $\langle min \rangle$. Then truncate to 16 digits (namely select the integer part of 10^{16} times the result) before converting back to a floating point number (_fp_sanitize:Nw takes care of zero). To avoid issues with negative numbers, add 1 to all fixed point numbers (namely 10^{16} to the integers they represent), except of course when it is time to convert back to a float.

```

19038 \cs_new:Npn \_fp_randint_o:Nw ?
19039 {
19040   \_fp_parse_function_one_two:nnw
19041   { randint }
19042   { \_fp_randint_default:w \_fp_randint_o:w }
19043 }
19044 \cs_new:Npn \_fp_randint_default:w #1 { \exp_after:wN #1 \c_one_fp }
19045 \cs_new:Npn \_fp_randint_badarg:w \s__fp \_fp_chk:w #1#2#3;
19046 {
19047   \_fp_int:wTF \s__fp \_fp_chk:w #1#2#3;
19048   {
19049     \if_meaning:w 1 #1
19050     \if_int_compare:w
19051       \_fp_use_i_until_s:nw #3 ; > \c__fp_prec_int
19052       1 \exp_stop_f:
19053     \fi:
19054     \fi:
19055   }
19056   { 1 \exp_stop_f: }
19057 }
19058 \cs_new:Npn \_fp_randint_o:w #1; #2; @
19059 {
19060   \if_case:w
19061     \_fp_randint_badarg:w #1;
19062     \_fp_randint_badarg:w #2;
19063     \if:w 1 \_fp_compare_back:ww #2; #1; 1 \exp_stop_f: \fi:
19064     0 \exp_stop_f:
19065     \_fp_randint_auxi_o:ww #1; #2;
19066   \or:
19067     \_fp_invalid_operation_tl_o:ff
19068     { randint } { \_fp_array_to_clist:n { #1; #2; } }
19069   \exp:w
19070   \fi:
19071   \exp_after:wN \exp_end:
19072 }
19073 \cs_new:Npn \_fp_randint_auxi_o:ww #1 ; #2 ; #3 \exp_end:
19074 {
19075   \fi:
19076   \_fp_randint_auxii:wn #2 ;
19077   { \_fp_randint_auxii:wn #1 ; \_fp_randint_auxiii_o:ww }
19078 }
19079 \cs_new:Npn \_fp_randint_auxii:wn \s__fp \_fp_chk:w #1#2#3#4 ;

```

```

19080 {
19081     \if_meaning:w 0 #1
19082     \exp_after:wN \use_i:nn
19083     \else:
19084     \exp_after:wN \use_ii:nn
19085     \fi:
19086     { \exp_after:wN \__fp_fixed_continue:wn \c__fp_one_fixed_tl }
19087     {
19088         \exp_after:wN \__fp_ep_to_fixed:wwn
19089         \int_value:w \__fp_int_eval:w
19090         #3 - \c__fp_prec_int , #4 {0000} {0000} ;
19091         {
19092             \if_meaning:w 0 #2
19093             \exp_after:wN \use_i:nnnn
19094             \exp_after:wN \__fp_fixed_add_one:wN
19095             \fi:
19096             \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_tl
19097         }
19098         \__fp_fixed_continue:wn
19099     }
19100 }
19101 \cs_new:Npn \__fp_randint_auxiii_o:ww #1 ; #2 ;
19102 {
19103     \__fp_fixed_add:wwn #2 ;
19104     {0000} {0000} {0000} {0001} {0000} {0000} ;
19105     \__fp_fixed_sub:wwn #1 ;
19106     {
19107         \exp_after:wN \use_i:nn
19108         \exp_after:wN \__fp_fixed_mul_add:wwwn
19109         \exp:w \exp_end_continue_f:w \__fp_rand_myriads:n { XXXXXX } ;
19110     }
19111     #1 ;
19112     \__fp_randint_auxiv_o:ww
19113     #2 ;
19114     \__fp_randint_auxv_o:w #1 ; @
19115 }
19116 \cs_new:Npn \__fp_randint_auxiv_o:ww #1#2#3#4#5 ; #6#7#8#9
19117 {
19118     \if_int_compare:w
19119         \if_int_compare:w #1#2 > #6#7 \exp_stop_f: 1 \else:
19120         \if_int_compare:w #1#2 < #6#7 \exp_stop_f: - \fi: \fi:
19121         #3#4 > #8#9 \exp_stop_f:
19122         \__fp_use_i_until_s:nw
19123     \fi:
19124     \__fp_randint_auxv_o:w {#1}{#2}{#3}{#4}#5
19125 }
19126 \cs_new:Npn \__fp_randint_auxv_o:w #1#2#3#4#5 ; #6 @
19127 {
19128     \exp_after:wN \__fp_sanitizew:Nw
19129     \int_value:w
19130     \if_int_compare:w #1 < 10000 \exp_stop_f:
19131         2
19132     \else:
19133         0

```

```

19134         \exp_after:wN \exp_after:wN
19135         \exp_after:wN \__fp_reverse_args:Nww
19136     \fi:
19137     \exp_after:wN \__fp_fixed_sub:wwn \c__fp_one_fixed_t1
19138     {#1} {#2} {#3} {#4} {0000} {0000} ;
19139     {
19140         \exp_after:wN \exp_stop_f:
19141         \int_value:w \__fp_int_eval:w \c__fp_prec_int
19142         \__fp_fixed_to_float_o:wN
19143     }
19144     0
19145     \exp:w \exp_after:wN \exp_end:
19146 }

```

(End definition for __fp_randint_o:Nw and others.)

\int_rand:nn Evaluate the argument and filter out the case where the lower bound #1 is more than the upper bound #2. Then determine whether the range is narrower than \c__kernel_randint_max_int; #2-#1 may overflow for very large positive #2 and negative #1. If the range is narrow, call __kernel_randint:n {<choices>} where <choices> is the number of possible outcomes. If the range is wide, use somewhat slower code.

__fp_randint:ww

```

19147     \cs_new:Npn \int_rand:nn #1#2
19148     {
19149         \int_eval:n
19150         {
19151             \exp_after:wN \__fp_randint:ww
19152             \int_value:w \int_eval:n {#1} \exp_after:wN ;
19153             \int_value:w \int_eval:n {#2} ;
19154         }
19155     }
19156     \cs_new:Npn \__fp_randint:ww #1; #2;
19157     {
19158         \if_int_compare:w #1 > #2 \exp_stop_f:
19159         \__kernel_msg_expandable_error:nnnn
19160         { kernel } { randint-backward-range } {#1} {#2}
19161         \__fp_randint:ww #2; #1;
19162     \else:
19163         \if_int_compare:w \__fp_int_eval:w #2
19164         \if_int_compare:w #1 > \c_zero_int
19165         - #1 < \__fp_int_eval:w
19166         \else:
19167             < \__fp_int_eval:w #1 +
19168         \fi:
19169         \c__kernel_randint_max_int
19170         \__fp_int_eval_end:
19171         \__kernel_randint:n
19172         { \__fp_int_eval:w #2 - #1 + 1 \__fp_int_eval_end: }
19173         - 1 + #1
19174     \else:
19175         \__kernel_randint:nn {#1} {#2}
19176     \fi:
19177     \fi:
19178 }

```

(End definition for \int_rand:nn and __fp_randint:ww. This function is documented on page 89.)

`__kernel_randint:nn`
`__fp_randint_split_o:Nw`
`__fp_randint_split_aux:w`
`__fp_randinat_wide_aux:w`
`__fp_randinat_wide_auxii:w`

Any $n \in [-2^{31} + 1, 2^{31} - 1]$ is uniquely written as $2^{14}n_1 + n_2$ with $n_1 \in [-2^{17}, 2^{17} - 1]$ and $n_2 \in [0, 2^{14} - 1]$. Calling `__fp_randint_split_o:Nw n ;` gives n_1 ; n_2 ; and expands the next token once. We do this for two random numbers and apply `__fp_randint_split_o:Nw` twice to fully decompose the range R . One subtlety is that we compute $R - 2^{31} = \langle \max \rangle - \langle \min \rangle - (2^{31} - 1) \in [-2^{31} + 1, 2^{31} - 1]$ rather than R to avoid overflow.

Then we have `__fp_randint_wide_aux:w` $\langle X_1 \rangle; \langle X_0 \rangle; \langle Y_1 \rangle; \langle Y_0 \rangle; \langle R_2 \rangle; \langle R_1 \rangle; \langle R_0 \rangle; .$ and we apply the algorithm described earlier.

```

19179 \cs_new:Npn \__kernel_randint:nn #1#2
19180 {
19181   #1
19182   \exp_after:wN \__fp_randint_wide_aux:w
19183   \int_value:w
19184   \exp_after:wN \__fp_randint_split_o:Nw
19185   \tex_uniformdeviate:D 268435456 ;
19186   \int_value:w
19187   \exp_after:wN \__fp_randint_split_o:Nw
19188   \tex_uniformdeviate:D 268435456 ;
19189   \int_value:w
19190   \exp_after:wN \__fp_randint_split_o:Nw
19191   \int_value:w \__fp_int_eval:w 131072 +
19192   \exp_after:wN \__fp_randint_split_o:Nw
19193   \int_value:w
19194   \__kernel_int_add:nnn {#2} { -#1 } { -\c_max_int } ;
19195   .
19196 }
19197 \cs_new:Npn \__fp_randint_split_o:Nw #1#2 ;
19198 {
19199   \if_meaning:w 0 #1
19200   0 \exp_after:wN ; \int_value:w 0
19201   \else:
19202   \exp_after:wN \__fp_randint_split_aux:w
19203   \int_value:w \__fp_int_eval:w (#1#2 - 8192) / 16384 ;
19204   + #1#2
19205   \fi:
19206   \exp_after:wN ;
19207 }
19208 \cs_new:Npn \__fp_randint_split_aux:w #1 ;
19209 {
19210   #1 \exp_after:wN ;
19211   \int_value:w \__fp_int_eval:w - #1 * 16384
19212 }
19213 \cs_new:Npn \__fp_randint_wide_aux:w #1;#2; #3;#4; #5;#6;#7; .
19214 {
19215   \exp_after:wN \__fp_randint_wide_auxii:w
19216   \int_value:w \__fp_int_eval:w #5 * #3 + #6 * #1 +
19217   (#5 * #4 + #6 * #3 + #7 * #1 +
19218   (#5 * #2 + #7 * #3 +
19219   (16384 * #6 + #7) * (16384 * #4 + #2) / 268435456) / 16384
19220   ) / 16384 \exp_after:wN ;
19221   \int_value:w \__fp_int_eval:w (#5 + #6) * 16384 + #7 ;
19222   #1 ; #5 ;
19223 }
19224 \cs_new:Npn \__fp_randint_wide_auxii:w #1; #2; #3; #4;

```

```

19225 {
19226   \if_int_odd:w 0
19227     \if_int_compare:w #1 = #2 \else: \exp_stop_f: \fi:
19228     \if_int_compare:w #4 = \c_zero_int 1 \fi:
19229     \if_int_compare:w #3 = 16383 ~ 1 \fi:
19230     \exp_stop_f:
19231     \exp_after:wN \prg_break:
19232   \fi:
19233   \if_int_compare:w #4 < 8 \exp_stop_f:
19234     + #4 * #3 * 16384
19235   \else:
19236     + 8 * #3 * 16384 + (#4 - 8) * #3 * 16384
19237   \fi:
19238   + #1
19239   \prg_break_point:
19240 }

```

(End definition for `__kernel_randint:nn` and others.)

`\int_rand:n` Similar to `\int_rand:nn`, but needs fewer checks.

```

\__fp_randint:n
19241   \cs_new:Npn \int_rand:n #1
19242   {
19243     \int_eval:n
19244     { \exp_args:Nf \__fp_randint:n { \int_eval:n {#1} } }
19245   }
19246   \cs_new:Npn \__fp_randint:n #1
19247   {
19248     \if_int_compare:w #1 < 1 \exp_stop_f:
19249     \__kernel_msg_expandable_error:nnnn
19250     { kernel } { randint-backward-range } { 1 } {#1}
19251     \__fp_randint:ww #1; 1;
19252   \else:
19253     \if_int_compare:w #1 > \c__kernel_randint_max_int
19254     \__kernel_randint:nn { 1 } {#1}
19255   \else:
19256     \__kernel_randint:n {#1}
19257   \fi:
19258   \fi:
19259 }

```

(End definition for `\int_rand:n` and `__fp_randint:n`. This function is documented on page 89.)

End the initial conditional that ensures these commands are only defined in engines that support random numbers.

```

19260 }
19261 </initex | package>

```

35 l3fparray implementation

```

19262 <*initex | package>
19263 <@@=fp>

```

In analogy to `l3intarray` it would make sense to have `<@@=fparray>`, but we need direct access to `__fp_parse:n` from `l3fp-parse`, and a few other (less crucial) internals of the `l3fp` family.

35.1 Allocating arrays

There are somewhat more than $(2^{31} - 1)^2$ floating point numbers so we store each floating point number as three entries in integer arrays. To avoid having to multiply indices by three or to add 1 etc, a floating point array is just a token list consisting of three tokens: integer arrays of the same size.

```
\g__fp_array_int Used to generate unique names for the three integer arrays.
19264 \int_new:N \g__fp_array_int
(End definition for \g__fp_array_int.)

\l__fp_array_loop_int Used to loop in \__fp_array_gzero:N.
19265 \int_new:N \l__fp_array_loop_int
(End definition for \l__fp_array_loop_int.)

\fparray_new:Nn Build a three token token list, then define all three tokens to be integer arrays of the
\__fp_array_new:nNNN same size. No need to initialize the data: the integer arrays start with zeros, and three
zeros denote precisely \c_zero_fp, as we want.
19266 \cs_new_protected:Npn \fparray_new:Nn #1#2
19267 {
19268   \tl_new:N #1
19269   \prg_replicate:nn { 3 }
19270   {
19271     \int_gincr:N \g__fp_array_int
19272     \exp_args:NNc \tl_gput_right:Nn #1
19273     { g__fp_array_ \__fp_int_to_roman:w \g__fp_array_int _intarray }
19274   }
19275   \exp_last_unbraced:Nfo \__fp_array_new:nNNNN
19276   { \int_eval:n {#2} } #1 #1
19277 }
19278 \cs_new_protected:Npn \__fp_array_new:nNNNN #1#2#3#4#5
19279 {
19280   \int_compare:nNnTF {#1} < 0
19281   {
19282     \__kernel_msg_error:nnn { kernel } { negative-array-size } {#1}
19283     \cs_undefine:N #1
19284     \int_gsub:Nn \g__fp_array_int { 3 }
19285   }
19286   {
19287     \intarray_new:Nn #2 {#1}
19288     \intarray_new:Nn #3 {#1}
19289     \intarray_new:Nn #4 {#1}
19290   }
19291 }
```

(End definition for `\fparray_new:Nn` and `__fp_array_new:nNNNN`. This function is documented on page 242.)

\fpararray_count:N Size of any of the intarrays, here we pick the third.

```

19292 \cs_new:Npn \fpararray_count:N #1
19293 {
19294     \exp_after:wN \use_i:nnn
19295     \exp_after:wN \intarray_count:N #1
19296 }

```

(End definition for \fpararray_count:N. This function is documented on page 242.)

35.2 Array items

__fp_array_bounds:NNnTF See the l3intarray analogue: only names change. The functions **\fpararray_gset:Nnn** and **__fp_array_bounds_error:NNn** share bounds checking. The T branch is used if #3 is within bounds of the array #2.

```

19297 \cs_new:Npn \__fp_array_bounds:NNnTF #1#2#3#4#5
19298 {
19299     \if_int_compare:w 1 > #3 \exp_stop_f:
19300     \__fp_array_bounds_error:NNn #1 #2 {#3}
19301     #5
19302     \else:
19303     \if_int_compare:w #3 > \fpararray_count:N #2 \exp_stop_f:
19304     \__fp_array_bounds_error:NNn #1 #2 {#3}
19305     #5
19306     \else:
19307     #4
19308     \fi:
19309     \fi:
19310 }
19311 \cs_new:Npn \__fp_array_bounds_error:NNn #1#2#3
19312 {
19313     #1 { kernel } { out-of-bounds }
19314     { \token_to_str:N #2 } {#3} { \fpararray_count:N #2 }
19315 }

```

(End definition for __fp_array_bounds:NNnTF and __fp_array_bounds_error:NNn.)

\fpararray_gset:Nnn Evaluate, then store exponent in one intarray, sign and 8 digits of mantissa in the next, and 8 trailing digits in the last.

```

\__fp_array_gset:NNNNww
\__fp_array_gset:w
\__fp_array_gset_recover:Nw
\__fp_array_gset_special:nnNNN
\__fp_array_gset_normal:w
19316 \cs_new_protected:Npn \fpararray_gset:Nnn #1#2#3
19317 {
19318     \exp_after:wN \exp_after:wN
19319     \exp_after:wN \__fp_array_gset:NNNNww
19320     \exp_after:wN #1
19321     \exp_after:wN #1
19322     \int_value:w \int_eval:n {#2} \exp_after:wN ;
19323     \exp:w \exp_end_continue_f:w \__fp_parse:n {#3}
19324 }
19325 \cs_new_protected:Npn \__fp_array_gset:NNNNww #1#2#3#4#5 ; #6 ;
19326 {
19327     \__fp_array_bounds:NNnTF \__kernel_msg_error:nnxxx #4 {#5}
19328     {
19329         \exp_after:wN \__fp_change_func_type:NNN
19330         \__fp_use_i_until_s:nw #6 ;
19331         \__fp_array_gset:w

```

```

19332         \__fp_array_gset_recover:Nw
19333         #6 ; {#5} #1 #2 #3
19334     }
19335     { }
19336 }
19337 \cs_new_protected:Npn \__fp_array_gset_recover:Nw #1#2 ;
19338 {
19339     \__fp_error:nffn { fp-unknown-type } { \tl_to_str:n { #2 ; } } { } { }
19340     \exp_after:wN #1 \c_nan_fp
19341 }
19342 \cs_new_protected:Npn \__fp_array_gset:w \s__fp \__fp_chk:w #1#2
19343 {
19344     \if_case:w #1 \exp_stop_f:
19345         \__fp_case_return:nw { \__fp_array_gset_special:nnNNN {#2} }
19346     \or: \exp_after:wN \__fp_array_gset_normal:w
19347     \or: \__fp_case_return:nw { \__fp_array_gset_special:nnNNN { #2 3 } }
19348     \or: \__fp_case_return:nw { \__fp_array_gset_special:nnNNN { 1 } }
19349     \fi:
19350     \s__fp \__fp_chk:w #1 #2
19351 }
19352 \cs_new_protected:Npn \__fp_array_gset_normal:w
19353 \s__fp \__fp_chk:w 1 #1 #2 #3#4#5 ; #6#7#8#9
19354 {
19355     \__kernel_intarray_gset:Nnn #7 {#6} {#2}
19356     \__kernel_intarray_gset:Nnn #8 {#6}
19357     { \if_meaning:w 2 #1 3 \else: 1 \fi: #3#4 }
19358     \__kernel_intarray_gset:Nnn #9 {#6} { 1 \use:nn #5 }
19359 }
19360 \cs_new_protected:Npn \__fp_array_gset_special:nnNNN #1#2#3#4#5
19361 {
19362     \__kernel_intarray_gset:Nnn #3 {#2} {#1}
19363     \__kernel_intarray_gset:Nnn #4 {#2} {0}
19364     \__kernel_intarray_gset:Nnn #5 {#2} {0}
19365 }

```

(End definition for \fpararray_gset:Nnn and others. This function is documented on page 243.)

\fpararray_gzero:N

```

19366 \cs_new_protected:Npn \fpararray_gzero:N #1
19367 {
19368     \int_zero:N \l__fp_array_loop_int
19369     \prg_replicate:nn { \fpararray_count:N #1 }
19370     {
19371         \int_incr:N \l__fp_array_loop_int
19372         \exp_after:wN \__fp_array_gset_special:nnNNN
19373         \exp_after:wN 0
19374         \exp_after:wN \l__fp_array_loop_int
19375         #1
19376     }
19377 }

```

(End definition for \fpararray_gzero:N. This function is documented on page 243.)

\fpararray_item:Nn

\fpararray_item_to_tl:Nn

```

\__fp_array_item:NwN
\__fp_array_item:NNNnN
\__fp_array_item:N
\__fp_array_item:w
\__fp_array_item_special:w
\__fp_array_item_normal:w

```

```

19378 \cs_new:Npn \fpararray_item:Nn #1#2
19379 {
19380   \exp_after:wN \__fp_array_item:NwN
19381   \exp_after:wN #1
19382   \int_value:w \int_eval:n {#2} ;
19383   \__fp_to_decimal:w
19384 }
19385 \cs_new:Npn \fpararray_item_to_tl:Nn #1#2
19386 {
19387   \exp_after:wN \__fp_array_item:NwN
19388   \exp_after:wN #1
19389   \int_value:w \int_eval:n {#2} ;
19390   \__fp_to_tl:w
19391 }
19392 \cs_new:Npn \__fp_array_item:NwN #1#2 ; #3
19393 {
19394   \__fp_array_bounds:NNnTF \__kernel_msg_expandable_error:nfff #1 {#2}
19395   { \exp_after:wN \__fp_array_item:NNNnN #1 {#2} #3 }
19396   { \exp_after:wN #3 \c_nan_fp }
19397 }
19398 \cs_new:Npn \__fp_array_item:NNNnN #1#2#3#4
19399 {
19400   \exp_after:wN \__fp_array_item:N
19401   \int_value:w \__kernel_intarray_item:Nn #2 {#4} \exp_after:wN ;
19402   \int_value:w \__kernel_intarray_item:Nn #3 {#4} \exp_after:wN ;
19403   \int_value:w \__kernel_intarray_item:Nn #1 {#4} ;
19404 }
19405 \cs_new:Npn \__fp_array_item:N #1
19406 {
19407   \if_meaning:w 0 #1 \exp_after:wN \__fp_array_item_special:w \fi:
19408   \__fp_array_item:w #1
19409 }
19410 \cs_new:Npn \__fp_array_item:w #1 #2#3#4#5 #6 ; 1 #7 ;
19411 {
19412   \exp_after:wN \__fp_array_item_normal:w
19413   \int_value:w \if_meaning:w #1 1 0 \else: 2 \fi: \exp_stop_f:
19414   #7 ; {#2#3#4#5} {#6} ;
19415 }
19416 \cs_new:Npn \__fp_array_item_special:w #1 ; #2 ; #3 ; #4
19417 {
19418   \exp_after:wN #4
19419   \exp:w \exp_end_continue_f:w
19420   \if_case:w #3 \exp_stop_f:
19421     \exp_after:wN \c_zero_fp
19422   \or: \exp_after:wN \c_nan_fp
19423   \or: \exp_after:wN \c_minus_zero_fp
19424   \or: \exp_after:wN \c_inf_fp
19425   \else: \exp_after:wN \c_minus_inf_fp
19426   \fi:
19427 }
19428 \cs_new:Npn \__fp_array_item_normal:w #1 #2#3#4#5 #6 ; #7 ; #8 ; #9
19429 { #9 \s__fp \__fp_chk:w 1 #1 {#8} #7 {#2#3#4#5} {#6} ; }

```

(End definition for `\fpararray_item:Nn` and others. These functions are documented on page 243.)

19430 $\langle /initex \mid package \rangle$

36 l3sort implementation

19431 $\langle *initex \mid package \rangle$

19432 $\langle @@=sort \rangle$

36.1 Variables

$\backslash g_sort_internal_seq$ Sorting happens in a group; the result is stored in those global variables before being copied outside the group to the proper places. For `seq` and `tl` this is more efficient than using `\use:x` (or some `\exp_args:NNNx`) to smuggle the definition outside the group since \TeX does not need to re-read tokens. For `clist` we don't gain anything since the result is converted from `seq` to `clist` anyways.

19433 $\backslash seq_new:N \backslash g_sort_internal_seq$

19434 $\backslash tl_new:N \backslash g_sort_internal_tl$

(End definition for $\backslash g_sort_internal_seq$ and $\backslash g_sort_internal_tl$.)

$\backslash l_sort_length_int$ The sequence has $\backslash l_sort_length_int$ items and is stored from $\backslash l_sort_min_int$ to $\backslash l_sort_top_int - 1$. While reading the sequence in memory, we check that $\backslash l_sort_top_int$ remains at most $\backslash l_sort_max_int$, precomputed by $\backslash_sort_compute_range:$. That bound is such that the merge sort only uses $\backslash toks$ registers less than $\backslash l_sort_true_max_int$, namely those that have not been allocated for use in other code: the user's comparison code could alter these.

19435 $\backslash int_new:N \backslash l_sort_length_int$

19436 $\backslash int_new:N \backslash l_sort_min_int$

19437 $\backslash int_new:N \backslash l_sort_top_int$

19438 $\backslash int_new:N \backslash l_sort_max_int$

19439 $\backslash int_new:N \backslash l_sort_true_max_int$

(End definition for $\backslash l_sort_length_int$ and others.)

$\backslash l_sort_block_int$ Merge sort is done in several passes. In each pass, blocks of size $\backslash l_sort_block_int$ are merged in pairs. The block size starts at 1, and, for a length in the range $[2^k + 1, 2^{k+1}]$, reaches 2^k in the last pass.

19440 $\backslash int_new:N \backslash l_sort_block_int$

(End definition for $\backslash l_sort_block_int$.)

$\backslash l_sort_begin_int$ When merging two blocks, $\backslash l_sort_begin_int$ marks the lowest index in the two blocks, and $\backslash l_sort_end_int$ marks the highest index, plus 1.

$\backslash l_sort_end_int$

19441 $\backslash int_new:N \backslash l_sort_begin_int$

19442 $\backslash int_new:N \backslash l_sort_end_int$

(End definition for $\backslash l_sort_begin_int$ and $\backslash l_sort_end_int$.)

$\backslash l_sort_A_int$ When merging two blocks (whose end-points are `beg` and `end`), A starts from the high end of the low block, and decreases until reaching `beg`. The index B starts from the top of the range and marks the register in which a sorted item should be put. Finally, C points to the copy of the high block in the interval of registers starting at $\backslash l_sort_length_int$, upwards. C starts from the upper limit of that range.

$\backslash l_sort_B_int$

$\backslash l_sort_C_int$

```

19443 \int_new:N \l__sort_A_int
19444 \int_new:N \l__sort_B_int
19445 \int_new:N \l__sort_C_int

```

(End definition for `\l__sort_A_int`, `\l__sort_B_int`, and `\l__sort_C_int`.)

36.2 Finding available `\toks` registers

`__sort_shrink_range:` After `__sort_compute_range:` (defined below) determines that `\toks` registers between `\l__sort_min_int` (included) and `\l__sort_true_max_int` (excluded) have not yet been assigned, `__sort_shrink_range:` computes `\l__sort_max_int` to reflect the need for a buffer when merging blocks in the merge sort. Given $2^n \leq A \leq 2^n + 2^{n-1}$ registers we can sort $\lfloor A/2 \rfloor + 2^{n-2}$ items while if we have $2^n + 2^{n-1} \leq A \leq 2^{n+1}$ registers we can sort $A - 2^{n-1}$ items. We first find out a power 2^n such that $2^n \leq A \leq 2^{n+1}$ by repeatedly halving `\l__sort_block_int`, starting at 2^{15} or 2^{14} namely half the total number of registers, then we use the formulas and set `\l__sort_max_int`.

```

19446 \cs_new_protected:Npn \__sort_shrink_range:
19447 {
19448   \int_set:Nn \l__sort_A_int
19449     { \l__sort_true_max_int - \l__sort_min_int + 1 }
19450   \int_set:Nn \l__sort_block_int { \c_max_register_int / 2 }
19451   \__sort_shrink_range_loop:
19452   \int_set:Nn \l__sort_max_int
19453     {
19454       \int_compare:nNnTF
19455         { \l__sort_block_int * 3 / 2 } > \l__sort_A_int
19456         {
19457           \l__sort_min_int
19458           + ( \l__sort_A_int - 1 ) / 2
19459           + \l__sort_block_int / 4
19460           - 1
19461         }
19462         { \l__sort_true_max_int - \l__sort_block_int / 2 }
19463     }
19464 }
19465 \cs_new_protected:Npn \__sort_shrink_range_loop:
19466 {
19467   \if_int_compare:w \l__sort_A_int < \l__sort_block_int
19468     \tex_divide:D \l__sort_block_int 2 \exp_stop_f:
19469     \exp_after:wN \__sort_shrink_range_loop:
19470   \fi:
19471 }

```

(End definition for `__sort_shrink_range:` and `__sort_shrink_range_loop:`.)

`__sort_compute_range:` First find out what `\toks` have not yet been assigned. There are many cases. In $\text{\LaTeX} 2_\epsilon$ with no package, available `\toks` range from `\count15 + 1` to `\c_max_register_int` included (this was not altered despite the 2015 changes). When `\loctoks` is defined, namely in plain (e) \TeX , or when the package `etex` is loaded in $\text{\LaTeX} 2_\epsilon$, redefine `__sort_compute_range:` to use the range `\count265` to `\count275 - 1`. The `elocalloc` package also defines `\loctoks` but uses yet another number for the upper bound, namely `\e@alloc@top` (minus one). We must check for `\loctoks` every time a sorting function is called, as `etex` or `elocalloc` could be loaded.

In ConT_EXt MkIV the range is from `\c_syst_last_allocated_toks+1` to `\c_max_register_int`, and in MkII it is from `\lastallocatedtoks+1` to `\c_max_register_int`. In all these cases, call `__sort_shrink_range:`. The L^AT_EX3 format mode is easiest: no `\toks` are ever allocated so available `\toks` range from 0 to `\c_max_register_int` and we precompute the result of `__sort_shrink_range:`.

```

19472 \begin{package}
19473 \cs_new_protected:Npn \__sort_compute_range:
19474 {
19475   \int_set:Nn \l__sort_min_int { \tex_count:D 15 + 1 }
19476   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
19477   \__sort_shrink_range:
19478   \if_meaning:w \loctoks \tex_undefined:D \else:
19479     \if_meaning:w \loctoks \scan_stop: \else:
19480       \__sort_redefine_compute_range:
19481       \__sort_compute_range:
19482     \fi:
19483   \fi:
19484 }
19485 \cs_new_protected:Npn \__sort_redefine_compute_range:
19486 {
19487   \cs_if_exist:cTF { ver@elocalloc.sty }
19488   {
19489     \cs_gset_protected:Npn \__sort_compute_range:
19490     {
19491       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
19492       \int_set_eq:NN \l__sort_true_max_int \e@alloc@top
19493       \__sort_shrink_range:
19494     }
19495   }
19496   {
19497     \cs_gset_protected:Npn \__sort_compute_range:
19498     {
19499       \int_set:Nn \l__sort_min_int { \tex_count:D 265 }
19500       \int_set:Nn \l__sort_true_max_int { \tex_count:D 275 }
19501       \__sort_shrink_range:
19502     }
19503   }
19504 }
19505 \cs_if_exist:NT \loctoks { \__sort_redefine_compute_range: }
19506 \tl_map_inline:nn { \lastallocatedtoks \c_syst_last_allocated_toks }
19507 {
19508   \cs_if_exist:NT #1
19509   {
19510     \cs_gset_protected:Npn \__sort_compute_range:
19511     {
19512       \int_set:Nn \l__sort_min_int { #1 + 1 }
19513       \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
19514       \__sort_shrink_range:
19515     }
19516   }
19517 }
19518 \end{package}
19519 \begin{initex}

```

```

19520 \int_const:Nn \c__sort_max_length_int
19521 { ( \c_max_register_int + 1 ) * 3 / 4 }
19522 \cs_new_protected:Npn \__sort_compute_range:
19523 {
19524   \int_set:Nn \l__sort_min_int { 0 }
19525   \int_set:Nn \l__sort_true_max_int { \c_max_register_int + 1 }
19526   \int_set:Nn \l__sort_max_int { \c__sort_max_length_int }
19527 }
19528 </initex>

```

(End definition for `__sort_compute_range:`, `__sort_redefine_compute_range:`, and `\c__sort_max_length_int`.)

36.3 Protected user commands

`__sort_main:NNNn` Sorting happens in three steps. First store items in `\toks` registers ranging from `\l__sort_min_int` to `\l__sort_top_int - 1`, while checking that the list is not too long. If we reach the maximum length, that's an error; exit the group. Secondly, sort the array of `\toks` registers, using the user-defined sorting function: `__sort_level:` calls `__sort_compare:nn` as needed. Finally, unpack the `\toks` registers (now sorted) into the target `tl`, or into `\g__sort_internal_seq` for `seq` and `clist`. This is done by `__sort_seq:NNNNn` and `__sort_tl:NNn`.

```

19529 \cs_new_protected:Npn \__sort_main:NNNn #1#2#3#4
19530 {
19531   (package)   \__sort_disable_toksdef:
19532   \__sort_compute_range:
19533   \int_set_eq:NN \l__sort_top_int \l__sort_min_int
19534   #1 #3
19535   {
19536     \if_int_compare:w \l__sort_top_int = \l__sort_max_int
19537       \__sort_too_long_error:NNw #2 #3
19538     \fi:
19539     \tex_toks:D \l__sort_top_int {##1}
19540     \int_incr:N \l__sort_top_int
19541   }
19542   \int_set:Nn \l__sort_length_int
19543   { \l__sort_top_int - \l__sort_min_int }
19544   \cs_set:Npn \__sort_compare:nn ##1 ##2 {#4}
19545   \int_set:Nn \l__sort_block_int { 1 }
19546   \__sort_level:
19547 }

```

(End definition for `__sort_main:NNNn`.)

`\tl_sort:Nn` Call the main sorting function then unpack `\toks` registers outside the group into the target token list. The unpacking is done by `__sort_tl_toks:w`; registers are numbered from `\l__sort_min_int` to `\l__sort_top_int - 1`. For expansion behaviour we need a couple of primitives. The `\tl_gclear:N` reduces memory usage. The `\prg_break_point:` is used by `__sort_main:NNNn` when the list is too long.

`\tl_sort:cn`

`\tl_gsort:Nn`

`\tl_gsort:cn`

`__sort_tl:NNn`

`__sort_tl_toks:w`

```

19548 \cs_new_protected:Npn \tl_sort:Nn { \__sort_tl:NNn \tl_set_eq:NN }
19549 \cs_generate_variant:Nn \tl_sort:Nn { c }
19550 \cs_new_protected:Npn \tl_gsort:Nn { \__sort_tl:NNn \tl_gset_eq:NN }
19551 \cs_generate_variant:Nn \tl_gsort:Nn { c }

```

```

19552 \cs_new_protected:Npn \__sort_tl:NNn #1#2#3
19553 {
19554   \group_begin:
19555     \__sort_main:NNNn \tl_map_inline:Nn \tl_map_break:n #2 {#3}
19556     \tl_gset:Nx \g__sort_internal_tl
19557       { \__sort_tl_toks:w \l__sort_min_int ; }
19558   \group_end:
19559   #1 #2 \g__sort_internal_tl
19560   \tl_gclear:N \g__sort_internal_tl
19561   \prg_break_point:
19562 }
19563 \cs_new:Npn \__sort_tl_toks:w #1 ;
19564 {
19565   \if_int_compare:w #1 < \l__sort_top_int
19566     { \tex_the:D \tex_toks:D #1 }
19567     \exp_after:wN \__sort_tl_toks:w
19568     \int_value:w \int_eval:n { #1 + 1 } \exp_after:wN ;
19569   \fi:
19570 }

```

(End definition for `\tl_sort:Nn` and others. These functions are documented on page 44.)

```

\seq_sort:Nn Use the same general framework for seq and clist. Apply the general sorting code, then
\seq_sort:cn unpack \toks into \g__sort_internal_seq. Outside the group copy or convert (for
\seq_gsort:Nn clist) the data to the target variable. The \seq_gclear:N reduces memory usage. The
\seq_gsort:cn \prg_break_point: is used by \__sort_main:NNNn when the list is too long.
\clist_sort:Nn
\clist_sort:cn
\clist_gsort:Nn
\clist_gsort:cn
\__sort_seq:NNNNn
19571 \cs_new_protected:Npn \seq_sort:Nn
19572 { \__sort_seq:NNNNn \seq_map_inline:Nn \seq_map_break:n \seq_set_eq:NN }
19573 \cs_generate_variant:Nn \seq_sort:Nn { c }
19574 \cs_new_protected:Npn \seq_gsort:Nn
19575 { \__sort_seq:NNNNn \seq_map_inline:Nn \seq_map_break:n \seq_gset_eq:NN }
19576 \cs_generate_variant:Nn \seq_gsort:Nn { c }
19577 \cs_new_protected:Npn \clist_sort:Nn
19578 {
19579   \__sort_seq:NNNNn \clist_map_inline:Nn \clist_map_break:n
19580     \clist_set_from_seq:NN
19581 }
19582 \cs_generate_variant:Nn \clist_sort:Nn { c }
19583 \cs_new_protected:Npn \clist_gsort:Nn
19584 {
19585   \__sort_seq:NNNNn \clist_map_inline:Nn \clist_map_break:n
19586     \clist_gset_from_seq:NN
19587 }
19588 \cs_generate_variant:Nn \clist_gsort:Nn { c }
19589 \cs_new_protected:Npn \__sort_seq:NNNNn #1#2#3#4#5
19590 {
19591   \group_begin:
19592     \__sort_main:NNNn #1 #2 #4 {#5}
19593     \seq_gset_from_inline_x:Nnn \g__sort_internal_seq
19594       {
19595         \int_step_function:nnN
19596           { \l__sort_min_int } { \l__sort_top_int - 1 }
19597       }
19598     { \tex_the:D \tex_toks:D ##1 }

```



```

19599   \group_end:
19600   #3 #4 \g__sort_internal_seq
19601   \seq_gclear:N \g__sort_internal_seq
19602   \prg_break_point:
19603 }

```

(End definition for `\seq_sort:Nn` and others. These functions are documented on page 72.)

36.4 Merge sort

`__sort_level:` This function is called once blocks of size `\l__sort_block_int` (initially 1) are each sorted. If the whole list fits in one block, then we are done (this also takes care of the case of an empty list or a list with one item). Otherwise, go through pairs of blocks starting from 0, then double the block size, and repeat.

```

19604 \cs_new_protected:Npn \__sort_level:
19605 {
19606   \if_int_compare:w \l__sort_block_int < \l__sort_length_int
19607     \l__sort_end_int \l__sort_min_int
19608     \__sort_merge_blocks:
19609     \tex_advance:D \l__sort_block_int \l__sort_block_int
19610     \exp_after:wN \__sort_level:
19611   \fi:
19612 }

```

(End definition for `__sort_level:.`)

`__sort_merge_blocks:` This function is called to merge a pair of blocks, starting at the last value of `\l__sort_end_int` (end-point of the previous pair of blocks). If shifting by one block to the right we reach the end of the list, then this pass has ended: the end of the list is sorted already. Otherwise, store the result of that shift in *A*, which indexes the first block starting from the top end. Then locate the end-point (maximum) of the second block: shift *end* upwards by one more block, but keeping it \leq *top*. Copy this upper block of `\toks` registers in registers above *length*, indexed by *C*: this is covered by `__sort_copy_block:.` Once this is done we are ready to do the actual merger using `__sort_merge_blocks_aux:`, after shifting *A*, *B* and *C* so that they point to the largest index in their respective ranges rather than pointing just beyond those ranges. Of course, once that pair of blocks is merged, move on to the next pair.

```

19613 \cs_new_protected:Npn \__sort_merge_blocks:
19614 {
19615   \l__sort_begin_int \l__sort_end_int
19616   \tex_advance:D \l__sort_end_int \l__sort_block_int
19617   \if_int_compare:w \l__sort_end_int < \l__sort_top_int
19618     \l__sort_A_int \l__sort_end_int
19619     \tex_advance:D \l__sort_end_int \l__sort_block_int
19620     \if_int_compare:w \l__sort_end_int > \l__sort_top_int
19621       \l__sort_end_int \l__sort_top_int
19622     \fi:
19623     \l__sort_B_int \l__sort_A_int
19624     \l__sort_C_int \l__sort_top_int
19625     \__sort_copy_block:
19626     \int_decr:N \l__sort_A_int
19627     \int_decr:N \l__sort_B_int
19628     \int_decr:N \l__sort_C_int

```

```

19629         \exp_after:wN \__sort_merge_blocks_aux:
19630         \exp_after:wN \__sort_merge_blocks:
19631     \fi:
19632 }

```

(End definition for __sort_merge_blocks:.)

__sort_copy_block: We wish to store a copy of the “upper” block of \toks registers, ranging between the initial value of \l__sort_B_int (included) and \l__sort_end_int (excluded) into a new range starting at the initial value of \l__sort_C_int, namely \l__sort_top_int.

```

19633 \cs_new_protected:Npn \__sort_copy_block:
19634 {
19635     \tex_toks:D \l__sort_C_int \tex_toks:D \l__sort_B_int
19636     \int_incr:N \l__sort_C_int
19637     \int_incr:N \l__sort_B_int
19638     \if_int_compare:w \l__sort_B_int = \l__sort_end_int
19639         \use_i:nn
19640     \fi:
19641     \__sort_copy_block:
19642 }

```

(End definition for __sort_copy_block:.)

__sort_merge_blocks_aux: At this stage, the first block starts at \l__sort_begin_int, and ends at \l__sort_A_int, and the second block starts at \l__sort_top_int and ends at \l__sort_C_int. The result of the merger is stored at positions indexed by \l__sort_B_int, which starts at \l__sort_end_int − 1 and decreases down to \l__sort_begin_int, covering the full range of the two blocks. In other words, we are building the merger starting with the largest values. The comparison function is defined to return either `swapped` or `same`. Of course, this means the arguments need to be given in the order they appear originally in the list.

```

19643 \cs_new_protected:Npn \__sort_merge_blocks_aux:
19644 {
19645     \exp_after:wN \__sort_compare:nn \exp_after:wN
19646     { \tex_the:D \tex_toks:D \exp_after:wN \l__sort_A_int \exp_after:wN }
19647     \exp_after:wN { \tex_the:D \tex_toks:D \l__sort_C_int }
19648     \prg_do_nothing:
19649     \__sort_return_mark:w
19650     \__sort_return_mark:w
19651     \q_mark
19652     \__sort_return_none_error:
19653 }

```

(End definition for __sort_merge_blocks_aux:.)

`\sort_return_same:` Each comparison should call `\sort_return_same:` or `\sort_return_swapped:` exactly once. If neither is called, `__sort_return_none_error:` is called, since the `return_mark` removes tokens until `\q_mark`. If one is called, the `return_mark` auxiliary removes everything except `__sort_return_same:w` (or its `swapped` analogue) followed by `__sort_return_none_error:`. Finally if two or more are called, `__sort_return_two_error:` ends up before any `__sort_return_mark:w`, so that it produces an error.

```

19654 \cs_new_protected:Npn \sort_return_same:
19655     #1 \__sort_return_mark:w #2 \q_mark

```

```

19656 {
19657   #1
19658   #2
19659   \__sort_return_two_error:
19660   \__sort_return_mark:w
19661   \q_mark
19662   \__sort_return_same:w
19663 }
19664 \cs_new_protected:Npn \sort_return_swapped:
19665   #1 \__sort_return_mark:w #2 \q_mark
19666 {
19667   #1
19668   #2
19669   \__sort_return_two_error:
19670   \__sort_return_mark:w
19671   \q_mark
19672   \__sort_return_swapped:w
19673 }
19674 \cs_new_protected:Npn \__sort_return_mark:w #1 \q_mark { }
19675 \cs_new_protected:Npn \__sort_return_none_error:
19676 {
19677   \__kernel_msg_error:nnxx { kernel } { return-none }
19678   { \tex_the:D \tex_toks:D \l__sort_A_int }
19679   { \tex_the:D \tex_toks:D \l__sort_C_int }
19680   \__sort_return_same:w \__sort_return_none_error:
19681 }
19682 \cs_new_protected:Npn \__sort_return_two_error:
19683 {
19684   \__kernel_msg_error:nnxx { kernel } { return-two }
19685   { \tex_the:D \tex_toks:D \l__sort_A_int }
19686   { \tex_the:D \tex_toks:D \l__sort_C_int }
19687 }

```

(End definition for `\sort_return_same:` and others. These functions are documented on page 205.)

`__sort_return_same:w` If the comparison function returns `same`, then the second argument fed to `__sort_compare:nn` should remain to the right of the other one. Since we build the merger starting from the right, we copy that `\toks` register into the allotted range, then shift the pointers *B* and *C*, and go on to do one more step in the merger, unless the second block has been exhausted: then the remainder of the first block is already in the correct registers and we are done with merging those two blocks.

```

19688 \cs_new_protected:Npn \__sort_return_same:w #1 \__sort_return_none_error:
19689 {
19690   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
19691   \int_decr:N \l__sort_B_int
19692   \int_decr:N \l__sort_C_int
19693   \if_int_compare:w \l__sort_C_int < \l__sort_top_int
19694     \use_i:nn
19695   \fi:
19696   \__sort_merge_blocks_aux:
19697 }

```

(End definition for `__sort_return_same:w`.)

`__sort_return_swapped:w` If the comparison function returns **swapped**, then the next item to add to the merger is the first argument, contents of the `\toks` register *A*. Then shift the pointers *A* and *B* to the left, and go for one more step for the merger, unless the left block was exhausted (*A* goes below the threshold). In that case, all remaining `\toks` registers in the second block, indexed by *C*, are copied to the merger by `__sort_merge_blocks_end:`.

```

19698 \cs_new_protected:Npn \__sort_return_swapped:w #1 \__sort_return_none_error:
19699 {
19700   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_A_int
19701   \int_decr:N \l__sort_B_int
19702   \int_decr:N \l__sort_A_int
19703   \if_int_compare:w \l__sort_A_int < \l__sort_begin_int
19704     \__sort_merge_blocks_end: \use_i:nn
19705   \fi:
19706   \__sort_merge_blocks_aux:
19707 }

```

(End definition for `__sort_return_swapped:w`.)

`__sort_merge_blocks_end:` This function’s task is to copy the `\toks` registers in the block indexed by *C* to the merger indexed by *B*. The end can equally be detected by checking when *B* reaches the threshold **begin**, or when *C* reaches **top**.

```

19708 \cs_new_protected:Npn \__sort_merge_blocks_end:
19709 {
19710   \tex_toks:D \l__sort_B_int \tex_toks:D \l__sort_C_int
19711   \int_decr:N \l__sort_B_int
19712   \int_decr:N \l__sort_C_int
19713   \if_int_compare:w \l__sort_B_int < \l__sort_begin_int
19714     \use_i:nn
19715   \fi:
19716   \__sort_merge_blocks_end:
19717 }

```

(End definition for `__sort_merge_blocks_end:`.)

36.5 Expandable sorting

Sorting expandably is very different from sorting and assigning to a variable. Since tokens cannot be stored, they must remain in the input stream, and be read through at every step. It is thus necessarily much slower (at best $O(n^2 \ln n)$) than non-expandable sorting functions ($O(n \ln n)$).

A prototypical version of expandable quicksort is as follows. If the argument has no item, return nothing, otherwise partition, using the first item as a pivot (argument **#4** of `__sort:nnNnn`). The arguments of `__sort:nnNnn` are 1. items less than **#4**, 2. items greater or equal to **#4**, 3. comparison, 4. pivot, 5. next item to test. If **#5** is the tail of the list, call `\tl_sort:nN` on **#1** and on **#2**, placing **#4** in between; `\use:ff` expands the parts to make `\tl_sort:nN` f-expandable. Otherwise, compare **#4** and **#5** using **#3**. If they are ordered, place **#5** amongst the “greater” items, otherwise amongst the “lesser” items, and continue partitioning.

```

\cs_new:Npn \tl_sort:nN #1#2
{
  \tl_if_blank:nF {#1}
  {

```

```

        \__sort:nnNnn { } { } #2
        #1 \q_recursion_tail \q_recursion_stop
    }
}
\cs_new:Npn \__sort:nnNnn #1#2#3#4#5
{
    \quark_if_recursion_tail_stop_do:nn {#5}
    { \use:ff { \tl_sort:nN {#1} #3 {#4} } { \tl_sort:nN {#2} #3 } }
    #3 {#4} {#5}
    { \__sort:nnNnn {#1} { #2 {#5} } #3 {#4} }
    { \__sort:nnNnn { #1 {#5} } {#2} #3 {#4} }
}
\cs_generate_variant:Nn \use:nn { ff }

```

There are quite a few optimizations available here: the code below is less legible, but more than twice as fast.

In the simple version of the code, `__sort:nnNnn` is called $O(n \ln n)$ times on average (the number of comparisons required by the quicksort algorithm). Hence most of our focus is on optimizing that function.

The first speed up is to avoid testing for the end of the list at every call to `__sort:nnNnn`. For this, the list is prepared by changing each *<item>* of the original token list into *<command>* {*<item>*}, just like sequences are stored. We arrange things such that the *<command>* is the *<conditional>* provided by the user: the loop over the *<prepared tokens>* then looks like

```

\cs_new:Npn \__sort_loop:wNn ... #6#7
{
    #6 {<pivot>} {#7} <loop big> <loop small>
    <extra arguments>
}
\__sort_loop:wNn ... <prepared tokens>
<end-loop> {} \q_stop

```

In this example, which matches the structure of `__sort_quick_split_i:NnnnnNn` and a few other functions below, the `__sort_loop:wNn` auxiliary normally receives the user's *<conditional>* as #6 and an *<item>* as #7. This is compared to the *<pivot>* (the argument #5, not shown here), and the *<conditional>* leaves the *<loop big>* or *<loop small>* auxiliary, which both have the same form as `__sort_loop:wNn`, receiving the next pair *<conditional>* {*<item>*} as #6 and #7. At the end, #6 is the *<end-loop>* function, which terminates the loop.

The second speed up is to minimize the duplicated tokens between the **true** and **false** branches of the conditional. For this, we introduce two versions of `__sort:nnNnn`, which receive the new item as #1 and place it either into the list #2 of items less than the pivot #4 or into the list #3 of items greater or equal to the pivot.

```

\cs_new:Npn \__sort_i:nnnnNn #1#2#3#4#5#6
{
    #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
    {#6} { #2 {#1} } {#3} {#4}
}
\cs_new:Npn \__sort_ii:nnnnNn #1#2#3#4#5#6

```

```

{
  #5 {#4} {#6} \__sort_ii:nnnnNn \__sort_i:nnnnNn
  {#6} {#2} { #3 {#1} } {#4}
}

```

Note that the two functions have the form of `__sort_loop:wNn` above, receiving as `#5` the conditional or a function to end the loop. In fact, the lists `#2` and `#3` must be made of pairs $\langle conditional \rangle \{ \langle item \rangle \}$, so we have to replace `{#6}` above by `{ #5 {#6} }`, and `{#1}` by `#1`. The actual functions have one more argument, so all argument numbers are shifted compared to this code.

The third speed up is to avoid `\use:ff` using a continuation-passing style: `__sort_quick_split:NnNn` expects a list followed by `\q_mark {<code>}`, and expands to $\langle code \rangle \langle sorted\ list \rangle$. Sorting the two parts of the list around the pivot is done with

```

\__sort_quick_split:NnNn #2 ... \q_mark
{
  \__sort_quick_split:NnNn #1 ... \q_mark {<code>}
  {<pivot>}
}

```

Items which are larger than the $\langle pivot \rangle$ are sorted, then placed after code that sorts the smaller items, and after the (braced) $\langle pivot \rangle$.

The fourth speed up is avoid the recursive call to `\tl_sort:nN` with an empty first argument. For this, we introduce functions similar to the `__sort_i:nnnnNn` of the last example, but aware of whether the list of $\langle conditional \rangle \{ \langle item \rangle \}$ read so far that are less than the pivot, and the list of those greater or equal, are empty or not: see `__sort_quick_split:NnNn` and functions defined below. Knowing whether the lists are empty or not is useless if we do not use distinct ending codes as appropriate. The splitting auxiliaries communicate to the $\langle end-loop \rangle$ function (that is initially placed after the “prepared” list) by placing a specific ending function, ignored when looping, but useful at the end. In fact, the $\langle end-loop \rangle$ function does nothing but place the appropriate ending function in front of all its arguments. The ending functions take care of sorting non-empty sublists, placing the pivot in between, and the continuation before.

The final change in fact slows down the code a little, but is required to avoid memory issues: schematically, when \TeX encounters

```

\use:n { \use:n { \use:n { ... } ... } ... }

```

the argument of the first `\use:n` is not completely read by the second `\use:n`, hence must remain in memory; then the argument of the second `\use:n` is not completely read when grabbing the argument of the third `\use:n`, hence must remain in memory, and so on. The memory consumption grows quadratically with the number of nested `\use:n`. In practice, this means that we must read everything until a trailing `\q_stop` once in a while, otherwise sorting lists of more than a few thousand items would exhaust a typical \TeX ’s memory.

`\tl_sort:nN`

```

\__sort_quick_prepare:Nnnn
  \__sort_quick_prepare_end:NNNnw
\__sort_quick_cleanup:w

```

The code within the `\exp_not:f` sorts the list, leaving in most cases a leading `\exp_not:f`, which stops the expansion, letting the result be return within `\exp_not:n`. We filter out the case of a list with no item, which would otherwise cause problems. Then prepare the token list `#1` by inserting the conditional `#2` before each item. The `prepare` auxiliary receives the conditional as `#1`, the prepared token list so far as `#2`, the next prepared item as `#3`, and the item after that as `#4`. The loop ends when `#4` contains

\prg_break_point:, then the prepare_end auxiliary finds the prepared token list as #4. The scene is then set up for __sort_quick_split:NnNn, which sorts the prepared list and perform the post action placed after \q_mark, namely removing the trailing \s_stop and \q_stop and leaving \exp_stop_f: to stop f-expansion.

```

19718 \cs_new:Npn \tl_sort:nN #1#2
19719 {
19720   \exp_not:f
19721   {
19722     \tl_if_blank:nF {#1}
19723     {
19724       \__sort_quick_prepare:Nnnn #2 { } { }
19725       #1
19726       { \prg_break_point: \__sort_quick_prepare_end:NNNnw }
19727       \q_stop
19728     }
19729   }
19730 }
19731 \cs_new:Npn \__sort_quick_prepare:Nnnn #1#2#3#4
19732 {
19733   \prg_break: #4 \prg_break_point:
19734   \__sort_quick_prepare:Nnnn #1 { #2 #3 } { #1 {#4} }
19735 }
19736 \cs_new:Npn \__sort_quick_prepare_end:NNNnw #1#2#3#4#5 \q_stop
19737 {
19738   \__sort_quick_split:NnNn #4 \__sort_quick_end:nnTFNn { }
19739   \q_mark { \__sort_quick_cleanup:w \exp_stop_f: }
19740   \s_stop \q_stop
19741 }
19742 \cs_new:Npn \__sort_quick_cleanup:w #1 \s_stop \q_stop {#1}

```

(End definition for \tl_sort:nN and others. This function is documented on page 44.)

```

\__sort_quick_split:NnNn
\__sort_quick_only_i:NnnnnNn
  \__sort_quick_only_ii:NnnnnNn
  \__sort_quick_split_i:NnnnnNn
  \__sort_quick_split_ii:NnnnnNn

```

The only_i, only_ii, split_i and split_ii auxiliaries receive a useless first argument, the new item #2 (that they append to either one of the next two arguments), the list #3 of items less than the pivot, bigger items #4, the pivot #5, a *function* #6, and an item #7. The *function* is the user's *conditional* except at the end of the list where it is __sort_quick_end:nnTFNn. The comparison is applied to the *pivot* and the *item*, and calls the only_i or split_i auxiliaries if the *item* is smaller, and the only_ii or split_ii auxiliaries otherwise. In both cases, the next auxiliary goes to work right away, with no intermediate expansion that would slow down operations. Note that the argument #2 left for the next call has the form *conditional* {*item*}, so that the lists #3 and #4 keep the right form to be fed to the next sorting function. The split auxiliary differs from these in that it is missing three of the arguments, which would be empty, and its first argument is always the user's *conditional* rather than an ending function.

```

19743 \cs_new:Npn \__sort_quick_split:NnNn #1#2#3#4
19744 {
19745   #3 {#2} {#4} \__sort_quick_only_ii:NnnnnNn
19746   \__sort_quick_only_i:NnnnnNn
19747   \__sort_quick_single_end:nnwnnw
19748   { #3 {#4} } { } { } {#2}
19749 }
19750 \cs_new:Npn \__sort_quick_only_i:NnnnnNn #1#2#3#4#5#6#7
19751 {

```

```

19752     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn
19753     \__sort_quick_only_i:NnnnnNn
19754     \__sort_quick_only_i_end:nnnwnw
19755     { #6 {#7} } { #3 #2 } { } {#5}
19756 }
19757 \cs_new:Npn \__sort_quick_only_ii:NnnnnNn #1#2#3#4#5#6#7
19758 {
19759     #6 {#5} {#7} \__sort_quick_only_ii:NnnnnNn
19760     \__sort_quick_split_i:NnnnnNn
19761     \__sort_quick_only_ii_end:nnnwnw
19762     { #6 {#7} } { } { #4 #2 } {#5}
19763 }
19764 \cs_new:Npn \__sort_quick_split_i:NnnnnNn #1#2#3#4#5#6#7
19765 {
19766     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn
19767     \__sort_quick_split_i:NnnnnNn
19768     \__sort_quick_split_end:nnnwnw
19769     { #6 {#7} } { #3 #2 } {#4} {#5}
19770 }
19771 \cs_new:Npn \__sort_quick_split_ii:NnnnnNn #1#2#3#4#5#6#7
19772 {
19773     #6 {#5} {#7} \__sort_quick_split_ii:NnnnnNn
19774     \__sort_quick_split_i:NnnnnNn
19775     \__sort_quick_split_end:nnnwnw
19776     { #6 {#7} } {#3} { #4 #2 } {#5}
19777 }

```

(End definition for __sort_quick_split:NnNn and others.)

__sort_quick_end:nnTFNn The __sort_quick_end:nnTFNn appears instead of the user's conditional, and receives as its arguments the pivot #1, a fake item #2, a true and a false branches #3 and #4, followed by an ending function #5 (one of the four auxiliaries here) and another copy #6 of the fake item. All those are discarded except the function #5. This function receives lists #1 and #2 of items less than or greater than the pivot #3, then a continuation code #5 just after \q_mark. To avoid a memory problem described earlier, all of the ending functions read #6 until \q_stop and place #6 back into the input stream. When the lists #1 and #2 are empty, the single auxiliary simply places the continuation #5 before the pivot {#3}. When #2 is empty, #1 is sorted and placed before the pivot {#3}, taking care to feed the continuation #5 as a continuation for the function sorting #1. When #1 is empty, #2 is sorted, and the continuation argument is used to place the continuation #5 and the pivot {#3} before the sorted result. Finally, when both lists are non-empty, items larger than the pivot are sorted, then items less than the pivot, and the continuations are done in such a way to place the pivot in between.

```

19778 \cs_new:Npn \__sort_quick_end:nnTFNn #1#2#3#4#5#6 {#5}
19779 \cs_new:Npn \__sort_quick_single_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
19780 { #5 {#3} #6 \q_stop }
19781 \cs_new:Npn \__sort_quick_only_i_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
19782 {
19783     \__sort_quick_split:NnNn #1
19784     \__sort_quick_end:nnTFNn { } \q_mark {#5}
19785     {#3}
19786     #6 \q_stop
19787 }

```



```

19788 \cs_new:Npn \__sort_quick_only_ii_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
19789 {
19790   \__sort_quick_split:NnNn #2
19791   \__sort_quick_end:nnTFNn { } \q_mark { #5 {#3} }
19792   #6 \q_stop
19793 }
19794 \cs_new:Npn \__sort_quick_split_end:nnnwnw #1#2#3#4 \q_mark #5#6 \q_stop
19795 {
19796   \__sort_quick_split:NnNn #2 \__sort_quick_end:nnTFNn { } \q_mark
19797   {
19798     \__sort_quick_split:NnNn #1
19799     \__sort_quick_end:nnTFNn { } \q_mark {#5}
19800     {#3}
19801   }
19802   #6 \q_stop
19803 }

```

(End definition for __sort_quick_end:nnTFNn and others.)

36.6 Messages

__sort_error: Bailing out of the sorting code is a bit tricky. It may not be safe to use a delimited argument, so instead we redefine many l3sort commands to be trivial, with __sort_level: jumping to the break point. This error recovery won't work in a group.

```

19804 \cs_new_protected:Npn \__sort_error:
19805 {
19806   \cs_set_eq:NN \__sort_merge_blocks_aux: \prg_do_nothing:
19807   \cs_set_eq:NN \__sort_merge_blocks: \prg_do_nothing:
19808   \cs_set_protected:Npn \__sort_level: { \group_end: \prg_break: }
19809 }

```

(End definition for __sort_error:.)

__sort_disable_toksdef: While sorting, \toksdef is locally disabled to prevent users from using \newtoks or similar commands in their comparison code: the \toks registers that would be assigned are in use by l3sort. In format mode, none of this is needed since there is no \toks allocator.

```

19810 (*package)
19811 \cs_new_protected:Npn \__sort_disable_toksdef:
19812 { \cs_set_eq:NN \toksdef \__sort_disabled_toksdef:n }
19813 \cs_new_protected:Npn \__sort_disabled_toksdef:n #1
19814 {
19815   \__kernel_msg_error:nnx { kernel } { toksdef }
19816   { \token_to_str:N #1 }
19817   \__sort_error:
19818   \tex_toksdef:D #1
19819 }
19820 \__kernel_msg_new:nnnn { kernel } { toksdef }
19821 { Allocation~of~\iow_char:N\{toks~registers~impossible~while~sorting. }
19822 {
19823   The~comparison~code~used~for~sorting~a~list~has~attempted~to~
19824   define~#1~as~a~new~\iow_char:N\{toks~register~using~
19825   \iow_char:N\newtoks~
19826   or~a~similar~command.~The~list~will~not~be~sorted.

```

```

19827 }
19828 </package>

```

(End definition for `_sort_disable_toksdef:` and `_sort_disabled_toksdef:n`.)

`_sort_too_long_error:NNw` When there are too many items in a sequence, this is an error, and we clean up properly the mapping over items in the list: break using the type-specific breaking function #1.

```

19829 \cs_new_protected:Npn \_sort_too_long_error:NNw #1#2 \fi:
19830 {
19831   \fi:
19832   \__kernel_msg_error:nnxxx { kernel } { too-large }
19833   { \token_to_str:N #2 }
19834   { \int_eval:n { \l__sort_true_max_int - \l__sort_min_int } }
19835   { \int_eval:n { \l__sort_top_int - \l__sort_min_int } }
19836   #1 \_sort_error:
19837 }
19838 \__kernel_msg_new:nnnn { kernel } { too-large }
19839 { The~list~#1~is~too~long~to~be~sorted~by~TeX. }
19840 {
19841   TeX~has~#2~toks~registers~still~available:~
19842   this~only~allows~to~sort~with~up~to~#3~
19843   items.~The~list~will~not~be~sorted.
19844 }

```

(End definition for `_sort_too_long_error:NNw`.)

```

19845 \__kernel_msg_new:nnnn { kernel } { return-none }
19846 { The~comparison~code~did~not~return. }
19847 {
19848   When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~
19849   did~not~call~
19850   \iow_char:N\sort_return_same: ~nor~
19851   \iow_char:N\sort_return_swapped: .~
19852   Exactly~one~of~these~should~be~called.
19853 }
19854 \__kernel_msg_new:nnnn { kernel } { return-two }
19855 { The~comparison~code~returned~multiple~times. }
19856 {
19857   When~sorting~a~list,~the~code~to~compare~items~#1~and~#2~called~
19858   \iow_char:N\sort_return_same: ~or~
19859   \iow_char:N\sort_return_swapped: ~multiple~times.~
19860   Exactly~one~of~these~should~be~called.
19861 }
19862 </initex | package>

```

37 l3tl-analysis implementation

```

19863 <@@=tl>

```

37.1 Internal functions

`\s__tl` The format used to store token lists internally uses the scan mark `\s__tl` as a delimiter.

(End definition for `\s__tl`.)

37.2 Internal format

The task of the `l3tl-analysis` module is to convert token lists to an internal format which allows us to extract all the relevant information about individual tokens (category code, character code), as well as reconstruct the token list quickly. This internal format is used in `l3regex` where we need to support arbitrary tokens, and it is used in conversion functions in `l3str-convert`, where we wish to support clusters of characters instead of single tokens.

We thus need a way to encode any $\langle token \rangle$ (even begin-group and end-group character tokens) in a way amenable to manipulating tokens individually. The best we can do is to find $\langle tokens \rangle$ which both *o*-expand and *x*-expand to the given $\langle token \rangle$. Collecting more information about the category code and character code is also useful for regular expressions, since most regexes are catcode-agnostic. The internal format thus takes the form of a succession of items of the form

$\langle tokens \rangle \backslash s_t1 \langle catcode \rangle \langle char\ code \rangle \backslash s_t1$

The $\langle tokens \rangle$ *o*- and *x*-expand to the original token in the token list or to the cluster of tokens corresponding to one Unicode character in the given encoding (for `l3str-convert`). The $\langle catcode \rangle$ is given as a single hexadecimal digit, 0 for control sequences. The $\langle char\ code \rangle$ is given as a decimal number, -1 for control sequences.

Using delimited arguments lets us build the $\langle tokens \rangle$ progressively when doing an encoding conversion in `l3str-convert`. On the other hand, the delimiter `\s_t1` may not appear unbraced in $\langle tokens \rangle$. This is not a problem because we are careful to wrap control sequences in braces (as an argument to `\exp_not:n`) when converting from a general token list to the internal format.

The current rule for converting a $\langle token \rangle$ to a balanced set of $\langle tokens \rangle$ which both *o*-expands and *x*-expands to it is the following.

- A control sequence `\cs` becomes `\exp_not:n { \cs } \s_t1 0 -1 \s_t1`.
- A begin-group character `{` becomes `\exp_after:wN { \if_false: } \fi: \s_t1 1 \langle char\ code \rangle \s_t1`.
- An end-group character `}` becomes `\if_false: { \fi: } \s_t1 2 \langle char\ code \rangle \s_t1`.
- A character with any other category code becomes `\exp_not:n {\langle character \rangle} \s_t1 \langle hex\ catcode \rangle \langle char\ code \rangle \s_t1`.

19864 `*initex | package`

37.3 Variables and helper functions

`\s_t1` The scan mark `\s_t1` is used as a delimiter in the internal format. This is more practical than using a quark, because we would then need to control expansion much more carefully: compare `\int_value:w '#1 \s_t1` with `\int_value:w '#1 \exp_stop_f: \exp_not:N \q_mark` to extract a character code followed by the delimiter in an *x*-expansion.

19865 `\scan_new:N \s_t1`

(End definition for \s_t1.)

`\l__tl_analysis_token` The tokens in the token list are probed with the TeX primitive `\futurelet`. We use `\l__tl_analysis_token` in that construction. In some cases, we convert the following token to a string before probing it: then the token variable used is `\l__tl_analysis_char_token`.

```

19866 \cs_new_eq:NN \l__tl_analysis_token ?
19867 \cs_new_eq:NN \l__tl_analysis_char_token ?

```

(End definition for `\l__tl_analysis_token` and `\l__tl_analysis_char_token`.)

`\l__tl_analysis_normal_int` The number of normal (N-type argument) tokens since the last special token.

```

19868 \int_new:N \l__tl_analysis_normal_int

```

(End definition for `\l__tl_analysis_normal_int`.)

`\l__tl_analysis_index_int` During the first pass, this is the index in the array being built. During the second pass, it is equal to the maximum index in the array from the first pass.

```

19869 \int_new:N \l__tl_analysis_index_int

```

(End definition for `\l__tl_analysis_index_int`.)

`\l__tl_analysis_nesting_int` Nesting depth of explicit begin-group and end-group characters during the first pass. This lets us detect the end of the token list without a reserved end-marker.

```

19870 \int_new:N \l__tl_analysis_nesting_int

```

(End definition for `\l__tl_analysis_nesting_int`.)

`\l__tl_analysis_type_int` When encountering special characters, we record their “type” in this integer.

```

19871 \int_new:N \l__tl_analysis_type_int

```

(End definition for `\l__tl_analysis_type_int`.)

`\g__tl_analysis_result_tl` The result of the conversion is stored in this token list, with a succession of items of the form

```

\tokens \s__tl \catcode \char code \s__tl

```

```

19872 \tl_new:N \g__tl_analysis_result_tl

```

(End definition for `\g__tl_analysis_result_tl`.)

`__tl_analysis_extract_charcode:` Extracting the character code from the meaning of `\l__tl_analysis_token`. This has no error checking, and should only be assumed to work for begin-group and end-group character tokens. It produces a number in the form ‘`\char`’.

```

19873 \cs_new:Npn \__tl_analysis_extract_charcode:
19874 {
19875   \exp_after:wN \__tl_analysis_extract_charcode_aux:w
19876   \token_to_meaning:N \l__tl_analysis_token
19877 }
19878 \cs_new:Npn \__tl_analysis_extract_charcode_aux:w #1 ~ #2 ~ { ‘ ’ }

```

(End definition for `__tl_analysis_extract_charcode:` and `__tl_analysis_extract_charcode_aux:w`.)

```

\__tl_analysis_cs_space_count:NN Counts the number of spaces in the string representation of its second argument, as well
\__tl_analysis_cs_space_count:w as the number of characters following the last space in that representation, and feeds the
\__tl_analysis_cs_space_count_end:w two numbers as semicolon-delimited arguments to the first argument. When this function
is used, the escape character is printable and non-space.

19879 \cs_new:Npn \__tl_analysis_cs_space_count:NN #1 #2
19880 {
19881   \exp_after:wN #1
19882   \int_value:w \int_eval:w 0
19883   \exp_after:wN \__tl_analysis_cs_space_count:w
19884   \token_to_str:N #2
19885   \fi: \__tl_analysis_cs_space_count_end:w ; ~ !
19886 }
19887 \cs_new:Npn \__tl_analysis_cs_space_count:w #1 ~
19888 {
19889   \if_false: #1 #1 \fi:
19890   + 1
19891   \__tl_analysis_cs_space_count:w
19892 }
19893 \cs_new:Npn \__tl_analysis_cs_space_count_end:w ; #1 \fi: #2 !
19894 { \exp_after:wN ; \int_value:w \str_count_ignore_spaces:n {#1} ; }

(End definition for \__tl_analysis_cs_space_count:NN, \__tl_analysis_cs_space_count:w, and \__-
tl_analysis_cs_space_count_end:w.)

```

37.4 Plan of attack

Our goal is to produce a token list of the form roughly

```

⟨token 1⟩ \s@_ ⟨catcode 1⟩ ⟨char code 1⟩ \s@_
⟨token 2⟩ \s__tl ⟨catcode 2⟩ ⟨char code 2⟩ \s__tl
... ⟨token N⟩ \s__tl ⟨catcode N⟩ ⟨char code N⟩ \s__tl

```

Most but not all tokens can be grabbed as an undelimited (N-type) argument by \TeX . The plan is to have a two pass system. In the first pass, locate special tokens, and store them in various `\toks` registers. In the second pass, which is done within an `x`-expanding assignment, normal tokens are taken in as N-type arguments, and special tokens are retrieved from the `\toks` registers, and removed from the input stream by some means. The whole process takes linear time, because we avoid building the result one item at a time.

We make the escape character printable (backslash, but this later oscillates between slash and backslash): this allows us to distinguish characters from control sequences.

A token has two characteristics: its `\meaning`, and what it looks like for \TeX when it is in scanning mode (*e.g.*, when capturing parameters for a macro). For our purposes, we distinguish the following meanings:

- begin-group token (category code 1), either space (character code 32), or non-space;
- end-group token (category code 2), either space (character code 32), or non-space;
- space token (category code 10, character code 32);
- anything else (then the token is always an N-type argument).

The token itself can “look like” one of the following

- a non-active character, in which case its meaning is automatically that associated to its character code and category code, we call it “true” character;
- an active character;
- a control sequence.

The only tokens which are not valid N-type arguments are true begin-group characters, true end-group characters, and true spaces. We detect those characters by scanning ahead with `\futurelet`, then distinguishing true characters from control sequences set equal to them using the `\string` representation.

The second pass is a simple exercise in expandable loops.

`__tl_analysis:n` Everything is done within a group, and all definitions are local. We use `\group_align_safe_begin/end:` to avoid problems in case `__tl_analysis:n` is used within an alignment and its argument contains alignment tab tokens.

```

19895 \cs_new_protected:Npn \__tl_analysis:n #1
19896 {
19897   \group_begin:
19898     \group_align_safe_begin:
19899     \__tl_analysis_a:n {#1}
19900     \__tl_analysis_b:n {#1}
19901     \group_align_safe_end:
19902     \group_end:
19903 }

```

(End definition for `__tl_analysis:n`.)

37.5 Disabling active characters

`__tl_analysis_disable:n` Active characters can cause problems later on in the processing, so we provide a way to disable them, by setting them to `undefined`. Since Unicode contains too many characters to loop over all of them, we instead do this whenever we encounter a character. For `pTeX` and `upTeX` we skip characters beyond [0, 255] because `\lccode` only allows those values.

```

19904 \group_begin:
19905   \char_set_catcode_active:N ^^@
19906   \cs_new_protected:Npn \__tl_analysis_disable:n #1
19907   {
19908     \tex_lccode:D 0 = #1 \exp_stop_f:
19909     \tex_lowercase:D { \tex_let:D ^^@ } \tex_undefined:D
19910   }
19911   \bool_lazy_or:nnT
19912   { \sys_if_engine_ptex_p: }
19913   { \sys_if_engine_uptex_p: }
19914   {
19915     \cs_gset_protected:Npn \__tl_analysis_disable:n #1
19916     {
19917       \if_int_compare:w 256 > #1 \exp_stop_f:
19918       \tex_lccode:D 0 = #1 \exp_stop_f:
19919       \tex_lowercase:D { \tex_let:D ^^@ } \tex_undefined:D
19920       \fi:
19921     }
19922   }
19923 \group_end:

```

(End definition for `_tl_analysis_disable:n`.)

37.6 First pass

The goal of this pass is to detect special (non-N-type) tokens, and count how many N-type tokens lie between special tokens. Also, we wish to store some representation of each special token in a `\toks` register.

We have 11 types of tokens:

1. a true non-space begin-group character;
2. a true space begin-group character;
3. a true non-space end-group character;
4. a true space end-group character;
5. a true space blank space character;
6. an active character;
7. any other true character;
8. a control sequence equal to a begin-group token (category code 1);
9. a control sequence equal to an end-group token (category code 2);
10. a control sequence equal to a space token (character code 32, category code 10);
11. any other control sequence.

Our first tool is `\futurelet`. This cannot distinguish case 8 from 1 or 2, nor case 9 from 3 or 4, nor case 10 from case 5. Those cases are later distinguished by applying the `\string` primitive to the following token, after possibly changing the escape character to ensure that a control sequence’s string representation cannot be mistaken for the true character.

In cases 6, 7, and 11, the following token is a valid N-type argument, so we grab it and distinguish the case of a character from a control sequence: in the latter case, `\str_tail:n {⟨token⟩}` is non-empty, because the escape character is printable.

`_tl_analysis_a:n` We read tokens one by one using `\futurelet`. While performing the loop, we keep track of the number of true begin-group characters minus the number of true end-group characters in `\l__tl_analysis_nesting_int`. This reaches `-1` when we read the closing brace.

```
19924 \cs_new_protected:Npn \_tl_analysis_a:n #1
19925 {
19926   \_tl_analysis_disable:n { 32 }
19927   \int_set:Nn \tex_escapechar:D { 92 }
19928   \int_zero:N \l__tl_analysis_normal_int
19929   \int_zero:N \l__tl_analysis_index_int
19930   \int_zero:N \l__tl_analysis_nesting_int
19931   \if_false: { \fi: \_tl_analysis_a_loop:w #1 }
19932   \int_decr:N \l__tl_analysis_index_int
19933 }
```

(End definition for `_tl_analysis_a:n`.)

`_tl_analysis_a_loop:w` Read one character and check its type.

```
19934 \cs_new_protected:Npn \_tl\_analysis\_a\_loop:w
19935 { \tex_futurelet:D \l\_tl\_analysis\_token \_tl\_analysis\_a\_type:w }
```

(End definition for `_tl_analysis_a_loop:w`.)

`_tl_analysis_a_type:w` At this point, `\l_tl_analysis_token` holds the meaning of the following token. We store in `\l_tl_analysis_type_int` information about the meaning of the token ahead:

- 0 space token;
- 1 begin-group token;
- -1 end-group token;
- 2 other.

The values 0, 1, -1 correspond to how much a true such character changes the nesting level (2 is used only here, and is irrelevant later). Then call the auxiliary for each case. Note that nesting conditionals here is safe because we only skip over `\l_tl_analysis_token` if it matches with one of the character tokens (hence is not a primitive conditional).

```
19936 \cs_new_protected:Npn \_tl\_analysis\_a\_type:w
19937 {
19938   \l\_tl\_analysis\_type\_int =
19939   \if_meaning:w \l\_tl\_analysis\_token \c\_space\_token
19940     0
19941   \else:
19942     \if_catcode:w \exp\_not:N \l\_tl\_analysis\_token \c\_group\_begin\_token
19943       1
19944     \else:
19945       \if_catcode:w \exp\_not:N \l\_tl\_analysis\_token \c\_group\_end\_token
19946         - 1
19947       \else:
19948         2
19949     \fi:
19950   \fi:
19951   \fi:
19952   \exp\_stop\_f:
19953   \if_case:w \l\_tl\_analysis\_type\_int
19954     \exp\_after:wN \_tl\_analysis\_a\_space:w
19955   \or: \exp\_after:wN \_tl\_analysis\_a\_bgroup:w
19956   \or: \exp\_after:wN \_tl\_analysis\_a\_safe:N
19957   \else: \exp\_after:wN \_tl\_analysis\_a\_egroup:w
19958   \fi:
19959 }
```

(End definition for `_tl_analysis_a_type:w`.)

`_tl_analysis_a_space:w` In this branch, the following token's meaning is a blank space. Apply `\string` to that token: a true blank space gives a space, a control sequence gives a result starting with the escape character, an active character gives something else than a space since we disabled the space. We grab as `\l_tl_analysis_char_token` the first character of the string representation then test it in `_tl_analysis_a_space_test:w`. Also, since

`__tl_analysis_a_store:` expects the special token to be stored in the relevant `\toks` register, we do that. The extra `\exp_not:n` is unnecessary of course, but it makes the treatment of all tokens more homogeneous. If we discover that the next token was actually a control sequence or an active character instead of a true space, then we step the counter of normal tokens. We now have in front of us the whole string representation of the control sequence, including potential spaces; those will appear to be true spaces later in this pass. Hence, all other branches of the code in this first pass need to consider the string representation, so that the second pass does not need to test the meaning of tokens, only strings.

```

19960 \cs_new_protected:Npn \__tl_analysis_a_space:w
19961 {
19962   \tex_afterassignment:D \__tl_analysis_a_space_test:w
19963   \exp_after:wN \cs_set_eq:NN
19964   \exp_after:wN \l__tl_analysis_char_token
19965   \token_to_str:N
19966 }
19967 \cs_new_protected:Npn \__tl_analysis_a_space_test:w
19968 {
19969   \if_meaning:w \l__tl_analysis_char_token \c_space_token
19970     \tex_toks:D \l__tl_analysis_index_int { \exp_not:n { ~ } }
19971     \__tl_analysis_a_store:
19972   \else:
19973     \int_incr:N \l__tl_analysis_normal_int
19974   \fi:
19975   \__tl_analysis_a_loop:w
19976 }

```

(End definition for `__tl_analysis_a_space:w` and `__tl_analysis_a_space_test:w`.)

```

\__tl_analysis_a_bgroup:w
\__tl_analysis_a_egroup:w
\__tl_analysis_a_group:nw
\__tl_analysis_a_group_aux:w
  \__tl_analysis_a_group_auxii:w
  \__tl_analysis_a_group_test:w

```

The token is most likely a true character token with catcode 1 or 2, but it might be a control sequence, or an active character. Optimizing for the first case, we store in a `\toks` register some code that expands to that token. Since we will turn what follows into a string, we make sure the escape character is different from the current character code (by switching between solidus and backslash). To detect the special case of an active character let to the catcode 1 or 2 character with the same character code, we disable the active character with that character code and re-test: if the following token has become undefined we can in fact safely grab it. We are finally ready to turn what follows to a string and test it. This is one place where we need `\l__tl_analysis_char_token` to be a separate control sequence from `\l__tl_analysis_token`, to compare them.

```

19977 \group_begin:
19978   \char_set_catcode_group_begin:N \^^@ % {
19979   \cs_new_protected:Npn \__tl_analysis_a_bgroup:w
19980     { \__tl_analysis_a_group:nw { \exp_after:wN \^^@ \if_false: } \fi: } }
19981   \char_set_catcode_group_end:N \^^@
19982   \cs_new_protected:Npn \__tl_analysis_a_egroup:w
19983     { \__tl_analysis_a_group:nw { \if_false: { \fi: \^^@ } } % }
19984 \group_end:
19985 \cs_new_protected:Npn \__tl_analysis_a_group:nw #1
19986 {
19987   \tex_lccode:D 0 = \__tl_analysis_extract_charcode: \scan_stop:
19988   \tex_lowercase:D { \tex_toks:D \l__tl_analysis_index_int {#1} }
19989   \if_int_compare:w \tex_lccode:D 0 = \tex_escapechar:D
19990     \int_set:Nn \tex_escapechar:D { 139 - \tex_escapechar:D }

```

```

19991 \fi:
19992 \__tl_analysis_disable:n { \tex_lccode:D 0 }
19993 \tex_futurelet:D \l__tl_analysis_token \__tl_analysis_a_group_aux:w
19994 }
19995 \cs_new_protected:Npn \__tl_analysis_a_group_aux:w
19996 {
19997 \if_meaning:w \l__tl_analysis_token \tex_undefined:D
19998 \exp_after:wN \__tl_analysis_a_safe:N
19999 \else:
20000 \exp_after:wN \__tl_analysis_a_group_auxii:w
20001 \fi:
20002 }
20003 \cs_new_protected:Npn \__tl_analysis_a_group_auxii:w
20004 {
20005 \tex_afterassignment:D \__tl_analysis_a_group_test:w
20006 \exp_after:wN \cs_set_eq:NN
20007 \exp_after:wN \l__tl_analysis_char_token
20008 \token_to_str:N
20009 }
20010 \cs_new_protected:Npn \__tl_analysis_a_group_test:w
20011 {
20012 \if_charcode:w \l__tl_analysis_token \l__tl_analysis_char_token
20013 \__tl_analysis_a_store:
20014 \else:
20015 \int_incr:N \l__tl_analysis_normal_int
20016 \fi:
20017 \__tl_analysis_a_loop:w
20018 }

```

(End definition for `__tl_analysis_a_bgroup:w` and others.)

`__tl_analysis_a_store:` This function is called each time we meet a special token; at this point, the `\toks` register `\l__tl_analysis_index_int` holds a token list which expands to the given special token. Also, the value of `\l__tl_analysis_type_int` indicates which case we are in:

- -1 end-group character;
- 0 space character;
- 1 begin-group character.

We need to distinguish further the case of a space character (code 32) from other character codes, because those behave differently in the second pass. Namely, after testing the `\lccode` of 0 (which holds the present character code) we change the cases above to

- -2 space end-group character;
- -1 non-space end-group character;
- 0 space blank space character;
- 1 non-space begin-group character;
- 2 space begin-group character.

This has the property that non-space characters correspond to odd values of `\l__tl_analysis_type_int`. The number of normal tokens until here and the type of special token are packed into a `\skip` register. Finally, we check whether we reached the last closing brace, in which case we stop by disabling the looping function (locally).

```

20019 \cs_new_protected:Npn \__tl_analysis_a_store:
20020 {
20021   \tex_advance:D \l__tl_analysis_nesting_int \l__tl_analysis_type_int
20022   \if_int_compare:w \tex_lccode:D 0 = '\ \exp_stop_f:
20023     \tex_advance:D \l__tl_analysis_type_int \l__tl_analysis_type_int
20024   \fi:
20025   \tex_skip:D \l__tl_analysis_index_int
20026     = \l__tl_analysis_normal_int sp
20027     plus \l__tl_analysis_type_int sp \scan_stop:
20028   \int_incr:N \l__tl_analysis_index_int
20029   \int_zero:N \l__tl_analysis_normal_int
20030   \if_int_compare:w \l__tl_analysis_nesting_int = -1 \exp_stop_f:
20031     \cs_set_eq:NN \__tl_analysis_a_loop:w \scan_stop:
20032   \fi:
20033 }

```

(End definition for __tl_analysis_a_store:.)

```

\__tl_analysis_a_safe:N
\__tl_analysis_a_cs:ww

```

This should be the simplest case: since the upcoming token is safe, we can simply grab it in a second pass. If the token is a single character (including space), the `\if_charcode:w` test yields true; we disable a potentially active character (that could otherwise masquerade as the true character in the next pass) and we count one “normal” token. On the other hand, if the token is a control sequence, we should replace it by its string representation for compatibility with other code branches. Instead of slowly looping through the characters with the main code, we use the knowledge of how the second pass works: if the control sequence name contains no space, count that token as a number of normal tokens equal to its string length. If the control sequence contains spaces, they should be registered as special characters by increasing `\l__tl_analysis_index_int` (no need to carefully count character between each space), and all characters after the last space should be counted in the following sequence of “normal” tokens.

```

20034 \cs_new_protected:Npn \__tl_analysis_a_safe:N #1
20035 {
20036   \if_charcode:w
20037     \scan_stop:
20038     \exp_after:wN \use_none:n \token_to_str:N #1 \prg_do_nothing:
20039     \scan_stop:
20040     \exp_after:wN \use_i:nn
20041   \else:
20042     \exp_after:wN \use_ii:nn
20043   \fi:
20044   {
20045     \__tl_analysis_disable:n { '#1 }
20046     \int_incr:N \l__tl_analysis_normal_int
20047   }
20048   { \__tl_analysis_cs_space_count:NN \__tl_analysis_a_cs:ww #1 }
20049   \__tl_analysis_a_loop:w
20050 }
20051 \cs_new_protected:Npn \__tl_analysis_a_cs:ww #1; #2;
20052 {

```

```

20053 \if_int_compare:w #1 > 0 \exp_stop_f:
20054 \tex_skip:D \l__tl_analysis_index_int
20055 = \int_eval:n { \l__tl_analysis_normal_int + 1 } sp \exp_stop_f:
20056 \tex_advance:D \l__tl_analysis_index_int #1 \exp_stop_f:
20057 \else:
20058 \tex_advance:D
20059 \fi:
20060 \l__tl_analysis_normal_int #2 \exp_stop_f:
20061 }

```

(End definition for `__tl_analysis_a_safe:N` and `__tl_analysis_a_cs:ww`.)

37.7 Second pass

The second pass is an exercise in expandable loops. All the necessary information is stored in `\skip` and `\toks` registers.

`__tl_analysis_b:n` Start the loop with the index 0. No need for an end-marker: the loop stops by itself when the last index is read. We repeatedly oscillate between reading long stretches of normal tokens, and reading special tokens.

```

20062 \cs_new_protected:Npn \__tl_analysis_b:n #1
20063 {
20064 \tl_gset:Nx \g__tl_analysis_result_tl
20065 {
20066 \__tl_analysis_b_loop:w 0; #1
20067 \prg_break_point:
20068 }
20069 }
20070 \cs_new:Npn \__tl_analysis_b_loop:w #1;
20071 {
20072 \exp_after:wN \__tl_analysis_b_normals:ww
20073 \int_value:w \tex_skip:D #1 ; #1 ;
20074 }

```

(End definition for `__tl_analysis_b:n` and `__tl_analysis_b_loop:w`.)

`__tl_analysis_b_normals:ww` The first argument is the number of normal tokens which remain to be read, and the second argument is the index in the array produced in the first step. A character's string representation is always one character long, while a control sequence is always longer (we have set the escape character to a printable value). In both cases, we leave `\exp_not:n` `{token}` `\s__tl` in the input stream (after x-expansion). Here, `\exp_not:n` is used rather than `\exp_not:N` because `#3` could be a macro parameter character or could be `\s__tl` (which must be hidden behind braces in the result).

```

20075 \cs_new:Npn \__tl_analysis_b_normals:ww #1;
20076 {
20077 \if_int_compare:w #1 = 0 \exp_stop_f:
20078 \__tl_analysis_b_special:w
20079 \fi:
20080 \__tl_analysis_b_normal:wwN #1;
20081 }
20082 \cs_new:Npn \__tl_analysis_b_normal:wwN #1; #2; #3
20083 {
20084 \exp_not:n { \exp_not:n { #3 } } \s__tl

```

```

20085 \if_charcode:w
20086 \scan_stop:
20087 \exp_after:wN \use_none:n \token_to_str:N #3 \prg_do_nothing:
20088 \scan_stop:
20089 \exp_after:wN \__tl_analysis_b_char:Nww
20090 \else:
20091 \exp_after:wN \__tl_analysis_b_cs:Nww
20092 \fi:
20093 #3 #1; #2;
20094 }

```

(End definition for __tl_analysis_b_normals:ww and __tl_analysis_b_normal:wwN.)

__tl_analysis_b_char:Nww If the normal token we grab is a character, leave $\langle catcode \rangle$ $\langle charcode \rangle$ followed by \s__tl in the input stream, and call __tl_analysis_b_normals:ww with its first argument decremented.

```

20095 \cs_new:Npx \__tl_analysis_b_char:Nww #1
20096 {
20097 \exp_not:N \if_meaning:w #1 \exp_not:N \tex_undefined:D
20098 \token_to_str:N D \exp_not:N \else:
20099 \exp_not:N \if_catcode:w #1 \c_catcode_other_token
20100 \token_to_str:N C \exp_not:N \else:
20101 \exp_not:N \if_catcode:w #1 \c_catcode_letter_token
20102 \token_to_str:N B \exp_not:N \else:
20103 \exp_not:N \if_catcode:w #1 \c_math_toggle_token 3
20104 \exp_not:N \else:
20105 \exp_not:N \if_catcode:w #1 \c_alignment_token 4
20106 \exp_not:N \else:
20107 \exp_not:N \if_catcode:w #1 \c_math_superscript_token 7
20108 \exp_not:N \else:
20109 \exp_not:N \if_catcode:w #1 \c_math_subscript_token 8
20110 \exp_not:N \else:
20111 \exp_not:N \if_catcode:w #1 \c_space_token
20112 \token_to_str:N A \exp_not:N \else:
20113 6
20114 \exp_not:n { \fi: \fi: \fi: \fi: \fi: \fi: \fi: }
20115 \exp_not:N \int_value:w '#1 \s__tl
20116 \exp_not:N \exp_after:wN \exp_not:N \__tl_analysis_b_normals:ww
20117 \exp_not:N \int_value:w \exp_not:N \int_eval:w - 1 +
20118 }

```

(End definition for __tl_analysis_b_char:Nww.)

__tl_analysis_b_cs:Nww __tl_analysis_b_cs_test:ww If the token we grab is a control sequence, leave 0 -1 (as category code and character code) in the input stream, followed by \s__tl, and call __tl_analysis_b_normals:ww with updated arguments.

```

20119 \cs_new:Npn \__tl_analysis_b_cs:Nww #1
20120 {
20121 0 -1 \s__tl
20122 \__tl_analysis_cs_space_count:NN \__tl_analysis_b_cs_test:ww #1
20123 }
20124 \cs_new:Npn \__tl_analysis_b_cs_test:ww #1 ; #2 ; #3 ; #4 ;
20125 {
20126 \exp_after:wN \__tl_analysis_b_normals:ww

```

```

20127 \int_value:w \int_eval:w
20128 \if_int_compare:w #1 = 0 \exp_stop_f:
20129 #3
20130 \else:
20131 \tex_skip:D \int_eval:n { #4 + #1 } \exp_stop_f:
20132 \fi:
20133 - #2
20134 \exp_after:wN ;
20135 \int_value:w \int_eval:n { #4 + #1 } ;
20136 }

```

(End definition for `__tl_analysis_b_cs:Nww` and `__tl_analysis_b_cs_test:ww`.)

`__tl_analysis_b_special:w` Here, #1 is the current index in the array built in the first pass. Check now whether we reached the end (we shouldn't keep the trailing end-group character that marked the end of the token list in the first pass). Unpack the `\toks` register: when x-expanding again, we will get the special token. Then leave the category code in the input stream, followed by the character code, and call `__tl_analysis_b_loop:w` with the next index.

```

20137 \group_begin:
20138 \char_set_catcode_other:N A
20139 \cs_new:Npn \__tl_analysis_b_special:w
20140 \fi: \__tl_analysis_b_normal:wwN 0 ; #1 ;
20141 {
20142 \fi:
20143 \if_int_compare:w #1 = \l__tl_analysis_index_int
20144 \exp_after:wN \prg_break:
20145 \fi:
20146 \tex_the:D \tex_toks:D #1 \s__tl
20147 \if_case:w \tex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
20148 \token_to_str:N A
20149 \or: 1
20150 \or: 1
20151 \else: 2
20152 \fi:
20153 \if_int_odd:w \tex_gluestretch:D \tex_skip:D #1 \exp_stop_f:
20154 \exp_after:wN \__tl_analysis_b_special_char:wN \int_value:w
20155 \else:
20156 \exp_after:wN \__tl_analysis_b_special_space:w \int_value:w
20157 \fi:
20158 \int_eval:n { 1 + #1 } \exp_after:wN ;
20159 \token_to_str:N
20160 }
20161 \group_end:
20162 \cs_new:Npn \__tl_analysis_b_special_char:wN #1 ; #2
20163 {
20164 \int_value:w '#2 \s__tl
20165 \__tl_analysis_b_loop:w #1 ;
20166 }
20167 \cs_new:Npn \__tl_analysis_b_special_space:w #1 ; ~
20168 {
20169 32 \s__tl
20170 \__tl_analysis_b_loop:w #1 ;
20171 }

```

(End definition for `_tl_analysis_b_special:w`, `_tl_analysis_b_special_char:wN`, and `_tl_analysis_b_special_space:w`.)

37.8 Mapping through the analysis

`\tl_analysis_map_inline:nn` First obtain the analysis of the token list into `\g_tl_analysis_result_tl`. To allow nested mappings, increase the nesting depth `\g_kernel_prg_map_int` (shared between all modules), then define the looping macro, which has a name specific to that nesting depth. That looping grabs the *<tokens>*, *<catcode>* and *<char code>*; it checks for the end of the loop with `\use_none:n ##2`, normally empty, but which becomes `\tl_map_break:` at the end; it then performs the user's code `#2`, and loops by calling itself. When the loop ends, remember to decrease the nesting depth.

```

20172 \cs_new_protected:Npn \tl_analysis_map_inline:nn #1
20173 {
20174   \_tl_analysis:n {#1}
20175   \int_gincr:N \g_kernel_prg_map_int
20176   \exp_args:Nc \_tl_analysis_map_inline_aux:Nn
20177     { \_tl_analysis_map_inline_ \int_use:N \g_kernel_prg_map_int :wNw }
20178 }
20179 \cs_new_protected:Npn \tl_analysis_map_inline:Nn #1
20180 { \exp_args:No \tl_analysis_map_inline:nn #1 }
20181 \cs_new_protected:Npn \_tl_analysis_map_inline_aux:Nn #1#2
20182 {
20183   \cs_gset_protected:Npn #1 ##1 \s__tl ##2 ##3 \s__tl
20184   {
20185     \use_none:n ##2
20186     \_tl_analysis_map_inline_aux:nnn {##1} {##3} {##2}
20187   }
20188   \cs_gset_protected:Npn \_tl_analysis_map_inline_aux:nnn ##1##2##3
20189   {
20190     #2
20191     #1
20192   }
20193   \exp_after:wN #1
20194     \g__tl_analysis_result_tl
20195     \s__tl { ? \tl_map_break: } \s__tl
20196   \prg_break_point:Nn \tl_map_break:
20197     { \int_gdecr:N \g_kernel_prg_map_int }
20198 }

```

(End definition for `\tl_analysis_map_inline:nn` and others. These functions are documented on page 206.)

37.9 Showing the results

`\tl_analysis_show:N` Add to `_tl_analysis:n` a third pass to display tokens to the terminal. If the token list variable is not defined, throw the same error as `\tl_show:N` by simply calling that function.

```

20199 \cs_new_protected:Npn \tl_analysis_show:N #1
20200 {
20201   \tl_if_exist:NTF #1
20202   {
20203     \exp_args:No \_tl_analysis:n {#1}

```

```

20204         \msg_show:nnxxxx { LaTeX / kernel } { show-tl-analysis }
20205         { \token_to_str:N #1 } { \__tl_analysis_show: } { } { }
20206     }
20207     { \tl_show:N #1 }
20208 }
20209 \cs_new_protected:Npn \tl_analysis_show:n #1
20210 {
20211     \__tl_analysis:n {#1}
20212     \msg_show:nnxxxx { LaTeX / kernel } { show-tl-analysis }
20213     { } { \__tl_analysis_show: } { } { }
20214 }

```

(End definition for `\tl_analysis_show:N` and `\tl_analysis_show:n`. These functions are documented on page 206.)

`__tl_analysis_show:` Here, `#1` o- and x-expands to the token; `#2` is the category code (one uppercase hexadecimal digit), 0 for control sequences; `#3` is the character code, which we ignore. In the cases of control sequences and active characters, the meaning may overflow one line, and we want to truncate it. Those cases are thus separated out.

```

20215 \cs_new:Npn \__tl_analysis_show:
20216 {
20217     \exp_after:wN \__tl_analysis_show_loop:wNw \g__tl_analysis_result_tl
20218     \s__tl { ? \prg_break: } \s__tl
20219     \prg_break_point:
20220 }
20221 \cs_new:Npn \__tl_analysis_show_loop:wNw #1 \s__tl #2 #3 \s__tl
20222 {
20223     \use_none:n #2
20224     \iow_newline: > \use:nn { ~ } { ~ }
20225     \if_int_compare:w "#2 = 0 \exp_stop_f:
20226         \exp_after:wN \__tl_analysis_show_cs:n
20227     \else:
20228         \if_int_compare:w "#2 = 13 \exp_stop_f:
20229             \exp_after:wN \exp_after:wN
20230             \exp_after:wN \__tl_analysis_show_active:n
20231         \else:
20232             \exp_after:wN \exp_after:wN
20233             \exp_after:wN \__tl_analysis_show_normal:n
20234         \fi:
20235     \fi:
20236     {#1}
20237     \__tl_analysis_show_loop:wNw
20238 }

```

(End definition for `__tl_analysis_show:` and `__tl_analysis_show_loop:wNw`.)

`__tl_analysis_show_normal:n` Non-active characters are a simple matter of printing the character, and its meaning. Our test suite checks that begin-group and end-group characters do not mess up TeX's alignment status.

```

20239 \cs_new:Npn \__tl_analysis_show_normal:n #1
20240 {
20241     \exp_after:wN \token_to_str:N #1 ~
20242     ( \exp_after:wN \token_to_meaning:N #1 )
20243 }

```


(End definition for `_tl_analysis_show_normal:n`.)

`_tl_analysis_show_value:N`

This expands to the value of #1 if it has any.

```

20244 \cs_new:Npn \_tl\_analysis\_show\_value:N #1
20245 {
20246   \token_if_expandable:NF #1
20247   {
20248     \token_if_chardef:NTF      #1 \prg_break: { }
20249     \token_if_mathchardef:NTF #1 \prg_break: { }
20250     \token_if_dim_register:NTF #1 \prg_break: { }
20251     \token_if_int_register:NTF #1 \prg_break: { }
20252     \token_if_skip_register:NTF #1 \prg_break: { }
20253     \token_if_toks_register:NTF #1 \prg_break: { }
20254     \use_none:nnn
20255     \prg_break_point:
20256     \use:n { \exp_after:wN = \tex_the:D #1 }
20257   }
20258 }

```

(End definition for `_tl_analysis_show_value:N`.)

`_tl_analysis_show_cs:n`
`_tl_analysis_show_active:n`
`_tl_analysis_show_long:nn`
`_tl_analysis_show_long_aux:nnnn`

Control sequences and active characters are printed in the same way, making sure not to go beyond the `\l_iow_line_count_int`. In case of an overflow, we replace the last characters by `\c_tl_analysis_show_etc_str`.

```

20259 \cs_new:Npn \_tl\_analysis\_show\_cs:n #1
20260 { \exp_args:No \_tl\_analysis\_show\_long:nn {#1} { control~sequence= } }
20261 \cs_new:Npn \_tl\_analysis\_show\_active:n #1
20262 { \exp_args:No \_tl\_analysis\_show\_long:nn {#1} { active~character= } }
20263 \cs_new:Npn \_tl\_analysis\_show\_long:nn #1
20264 {
20265   \_tl\_analysis\_show\_long\_aux:oofn
20266   { \token_to_str:N #1 }
20267   { \token_to_meaning:N #1 }
20268   { \_tl\_analysis\_show\_value:N #1 }
20269 }
20270 \cs_new:Npn \_tl\_analysis\_show\_long\_aux:nnnn #1#2#3#4
20271 {
20272   \int_compare:nNnTF
20273   { \str_count:n { #1 ~ ( #4 #2 #3 ) } }
20274   > { \l\_iow\_line\_count\_int - 3 }
20275   {
20276     \str_range:nnn { #1 ~ ( #4 #2 #3 ) } { 1 }
20277     {
20278       \l\_iow\_line\_count\_int - 3
20279       - \str_count:N \c\_tl\_analysis\_show\_etc\_str
20280     }
20281     \c\_tl\_analysis\_show\_etc\_str
20282   }
20283   { #1 ~ ( #4 #2 #3 ) }
20284 }
20285 \cs_generate_variant:Nn \_tl\_analysis\_show\_long\_aux:nnnn { oof }

```

(End definition for `_tl_analysis_show_cs:n` and others.)

37.10 Messages

`\c__tl_analysis_show_etc_str` When a control sequence (or active character) and its meaning are too long to fit in one line of the terminal, the end is replaced by this token list.

```
20286 \tl_const:Nx \c__tl_analysis_show_etc_str % (
20287   { \token_to_str:N \ETC.) }
```

(End definition for `\c__tl_analysis_show_etc_str`.)

```
20288 \__kernel_msg_new:nnn { kernel } { show-tl-analysis }
20289   {
20290     The-token-list~ \tl_if_empty:nF {#1} { #1 ~ }
20291     \tl_if_empty:nTF {#2}
20292       { is-empty }
20293       { contains-the-tokens: #2 }
20294   }
```

37.11 Deprecated functions

`\tl_show_analysis:N` Simple renames.

```
\tl_show_analysis:n
20295 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 }
20296   { \tl_analysis_show:N }
20297 \cs_new_protected:Npn \tl_show_analysis:N #1
20298   { \tl_analysis_show:N #1 }
20299 \__kernel_patch_deprecation:nnNNpn { 2019-12-31 }
20300   { \tl_analysis_show:n }
20301 \cs_new_protected:Npn \tl_show_analysis:n #1
20302   { \tl_analysis_show:n {#1} }
```

(End definition for `\tl_show_analysis:N` and `\tl_show_analysis:n`.)

```
20303 </initex | package>
```

38 l3regex implementation

```
20304 <*initex | package>
```

```
20305 <@@=regex>
```

38.1 Plan of attack

Most regex engines use backtracking. This allows to provide very powerful features (back-references come to mind first), but it is costly, and raises the problem of catastrophic backtracking. Since T_EX is not first and foremost a programming language, complicated code tends to run slowly, and we must use faster, albeit slightly more restrictive, techniques, coming from automata theory.

Given a regular expression of n characters, we do the following:

- (Compiling.) Analyse the regex, finding invalid input, and convert it to an internal representation.
- (Building.) Convert the compiled regex to a non-deterministic finite automaton (NFA) with $O(n)$ states which accepts precisely token lists matching that regex.

- (Matching.) Loop through the query token list one token (one “position”) at a time, exploring in parallel every possible path (“active thread”) through the NFA, considering active threads in an order determined by the quantifiers’ greediness.

We use the following vocabulary in the code comments (and in variable names).

- *Group*: index of the capturing group, -1 for non-capturing groups.
- *Position*: each token in the query is labelled by an integer $\langle position \rangle$, with $\text{min_pos} - 1 \leq \langle position \rangle \leq \text{max_pos}$. The lowest and highest positions correspond to imaginary begin and end markers (with inaccessible category code and character code).
- *Query*: the token list to which we apply the regular expression.
- *State*: each state of the NFA is labelled by an integer $\langle state \rangle$ with $\text{min_state} \leq \langle state \rangle < \text{max_state}$.
- *Active thread*: state of the NFA that is reached when reading the query token list for the matching. Those threads are ordered according to the greediness of quantifiers.
- *Step*: used when matching, starts at 0, incremented every time a character is read, and is not reset when searching for repeated matches. The integer `\l__regex_step_int` is a unique id for all the steps of the matching algorithm.

We use `l3intarray` to manipulate arrays of integers (stored into some dimension registers in scaled points). We also abuse TeX’s `\toks` registers, by accessing them directly by number rather than tying them to control sequence using the `\newtoks` allocation functions. Specifically, these arrays and `\toks` are used as follows. When building, `\toks\langle state \rangle` holds the tests and actions to perform in the $\langle state \rangle$ of the NFA. When matching,

- `\g__regex_state_active_intarray` holds the last $\langle step \rangle$ in which each $\langle state \rangle$ was active.
- `\g__regex_thread_state_intarray` maps each $\langle thread \rangle$ (with $\text{min_active} \leq \langle thread \rangle < \text{max_active}$) to the $\langle state \rangle$ in which the $\langle thread \rangle$ currently is. The $\langle threads \rangle$ are ordered starting from the best to the least preferred.
- `\toks\langle thread \rangle` holds the submatch information for the $\langle thread \rangle$, as the contents of a property list.
- `\g__regex_charcode_intarray` and `\g__regex_catcode_intarray` hold the character codes and category codes of tokens at each $\langle position \rangle$ in the query.
- `\g__regex_balance_intarray` holds the balance of begin-group and end-group character tokens which appear before that point in the token list.
- `\toks\langle position \rangle` holds $\langle tokens \rangle$ which o- and x-expand to the $\langle position \rangle$ -th token in the query.
- `\g__regex_submatch_prev_intarray`, `\g__regex_submatch_begin_intarray` and `\g__regex_submatch_end_intarray` hold, for each submatch (as would be extracted by `\regex_extract_all:nnN`), the place where the submatch started to be looked for and its two end-points. For historical reasons, the minimum index is

twice `max_state`, and the used registers go up to `\l__regex_submatch_int`. They are organized in blocks of `\l__regex_capturing_group_int` entries, each block corresponding to one match with all its submatches stored in consecutive entries.

The code is structured as follows. Variables are introduced in the relevant section. First we present some generic helper functions. Then comes the code for compiling a regular expression, and for showing the result of the compilation. The building phase converts a compiled regex to NFA states, and the automaton is run by the code in the following section. The only remaining brick is parsing the replacement text and performing the replacement. We are then ready for all the user functions. Finally, messages, and a little bit of tracing code.

38.2 Helpers

`__regex_int_eval:w` Access the primitive: performance is key here, so we do not use the slower route *via* `\int_eval:n`.

```
20306 \cs_new_eq:NN \__regex_int_eval:w \tex_numexpr:D
20307 % \end{macrocode}
20308 % \end{macro}
20309 %
20310 % \begin{macro}{\__regex_standard_escapechar:}
20311 % Make the \tn{escapechar} into the standard backslash.
20312 % \begin{macrocode}
20313 \cs_new_protected:Npn \__regex_standard_escapechar:
20314 { \int_set:Nn \tex_escapechar:D { '\ } }
```

(End definition for `__regex_int_eval:w`.)

`__regex_toks_use:w` Unpack a `\toks` given its number.

```
20315 \cs_new:Npn \__regex_toks_use:w { \tex_the:D \tex_toks:D }
```

(End definition for `__regex_toks_use:w`.)

`__regex_toks_clear:N` Empty a `\toks` or set it to a value, given its number.

```
\__regex_toks_set:Nn
\__regex_toks_set:No
20316 \cs_new_protected:Npn \__regex_toks_clear:N #1
20317 { \__regex_toks_set:Nn #1 { } }
20318 \cs_new_eq:NN \__regex_toks_set:Nn \tex_toks:D
20319 \cs_new_protected:Npn \__regex_toks_set:No #1
20320 { \__regex_toks_set:Nn #1 \exp_after:wN }
```

(End definition for `__regex_toks_clear:N` and `__regex_toks_set:Nn`.)

`__regex_toks_memcpy:NNn` Copy #3 `\toks` registers from #2 onwards to #1 onwards, like C's `memcpy`.

```
20321 \cs_new_protected:Npn \__regex_toks_memcpy:NNn #1#2#3
20322 {
20323   \prg_replicate:nn {#3}
20324   {
20325     \tex_toks:D #1 = \tex_toks:D #2
20326     \int_incr:N #1
20327     \int_incr:N #2
20328   }
20329 }
```

(End definition for `__regex_toks_memcpy:NNn`.)

`__regex_toks_put_left:Nx`
`__regex_toks_put_right:Nx`
`__regex_toks_put_right:Nn`

During the building phase we wish to add x-expanded material to `\toks`, either to the left or to the right. The expansion is done “by hand” for optimization (these operations are used quite a lot). The `Nn` version of `__regex_toks_put_right:Nx` is provided because it is more efficient than x-expanding with `\exp_not:n`.

```

20330 \cs_new_protected:Npn \__regex_toks_put_left:Nx #1#2
20331 {
20332   \cs_set:Npx \__regex_tmp:w { #2 }
20333   \tex_toks:D #1 \exp_after:wN \exp_after:wN \exp_after:wN
20334   { \exp_after:wN \__regex_tmp:w \tex_the:D \tex_toks:D #1 }
20335 }
20336 \cs_new_protected:Npn \__regex_toks_put_right:Nx #1#2
20337 {
20338   \cs_set:Npx \__regex_tmp:w {#2}
20339   \tex_toks:D #1 \exp_after:wN
20340   { \tex_the:D \tex_toks:D \exp_after:wN #1 \__regex_tmp:w }
20341 }
20342 \cs_new_protected:Npn \__regex_toks_put_right:Nn #1#2
20343 { \tex_toks:D #1 \exp_after:wN { \tex_the:D \tex_toks:D #1 #2 } }

```

(End definition for __regex_toks_put_left:Nx and __regex_toks_put_right:Nx.)

`__regex_curr_cs_to_str:`

Expands to the string representation of the token (known to be a control sequence) at the current position `\l__regex_curr_pos_int`. It should only be used in x-expansion to avoid losing a leading space.

```

20344 \cs_new:Npn \__regex_curr_cs_to_str:
20345 {
20346   \exp_after:wN \exp_after:wN \exp_after:wN \cs_to_str:N
20347   \tex_the:D \tex_toks:D \l__regex_curr_pos_int
20348 }

```

(End definition for __regex_curr_cs_to_str:.)

38.2.1 Constants and variables

`__regex_tmp:w`

Temporary function used for various short-term purposes.

```

20349 \cs_new:Npn \__regex_tmp:w { }

```

(End definition for __regex_tmp:w.)

`\l__regex_internal_a_tl`
`\l__regex_internal_b_tl`
`\l__regex_internal_a_int`
`\l__regex_internal_b_int`
`\l__regex_internal_c_int`
`\l__regex_internal_bool`
`\l__regex_internal_seq`
`\g__regex_internal_tl`

Temporary variables used for various purposes.

```

20350 \tl_new:N \l__regex_internal_a_tl
20351 \tl_new:N \l__regex_internal_b_tl
20352 \int_new:N \l__regex_internal_a_int
20353 \int_new:N \l__regex_internal_b_int
20354 \int_new:N \l__regex_internal_c_int
20355 \bool_new:N \l__regex_internal_bool
20356 \seq_new:N \l__regex_internal_seq
20357 \tl_new:N \g__regex_internal_tl

```

(End definition for \l__regex_internal_a_tl and others.)

`\l__regex_build_tl`

This temporary variable is specifically for use with the `tl_build` machinery.

```

20358 \tl_new:N \l__regex_build_tl

```

(End definition for \l__regex_build_tl.)

\c__regex_no_match_regex This regular expression matches nothing, but is still a valid regular expression. We could use a failing assertion, but I went for an empty class. It is used as the initial value for regular expressions declared using \regex_new:N.

```
20359 \tl_const:Nn \c__regex_no_match_regex
20360 {
20361   \__regex_branch:n
20362   { \__regex_class:NnnnN \c_true_bool { } { 1 } { 0 } \c_true_bool }
20363 }
```

(End definition for \c__regex_no_match_regex.)

\g__regex_charcode_intarray \g__regex_catcode_intarray \g__regex_balance_intarray The first thing we do when matching is to go once through the query token list and store the information for each token into \g__regex_charcode_intarray, \g__regex_catcode_intarray and \toks registers. We also store the balance of begin-group/end-group characters into \g__regex_balance_intarray.

```
20364 \intarray_new:Nn \g__regex_charcode_intarray { 65536 }
20365 \intarray_new:Nn \g__regex_catcode_intarray { 65536 }
20366 \intarray_new:Nn \g__regex_balance_intarray { 65536 }
```

(End definition for \g__regex_charcode_intarray, \g__regex_catcode_intarray, and \g__regex_balance_intarray.)

\l__regex_balance_int During this phase, \l__regex_balance_int counts the balance of begin-group and end-group character tokens which appear before a given point in the token list. This variable is also used to keep track of the balance in the replacement text.

```
20367 \int_new:N \l__regex_balance_int
```

(End definition for \l__regex_balance_int.)

\l__regex_cs_name_tl This variable is used in __regex_item_cs:n to store the csname of the currently-tested token when the regex contains a sub-regex for testing csnames.

```
20368 \tl_new:N \l__regex_cs_name_tl
```

(End definition for \l__regex_cs_name_tl.)

38.2.2 Testing characters

```
\c__regex_ascii_min_int
\c__regex_ascii_max_control_int 20369 \int_const:Nn \c__regex_ascii_min_int { 0 }
\c__regex_ascii_max_int          20370 \int_const:Nn \c__regex_ascii_max_control_int { 31 }
20371 \int_const:Nn \c__regex_ascii_max_int { 127 }
```

(End definition for \c__regex_ascii_min_int, \c__regex_ascii_max_control_int, and \c__regex_ascii_max_int.)

```
\c__regex_ascii_lower_int
20372 \int_const:Nn \c__regex_ascii_lower_int { 'a - 'A }
```

(End definition for \c__regex_ascii_lower_int.)

__regex_break_point:TF __regex_break_true:w When testing whether a character of the query token list matches a given character class in the regular expression, we often have to test it against several ranges of characters, checking if any one of those matches. This is done with a structure like

```

    <test1> ... <testn>
    \__regex_break_point:TF {<true code>} {<false code>}

```

If any of the tests succeeds, it calls `__regex_break_true:w`, which cleans up and leaves `<true code>` in the input stream. Otherwise, `__regex_break_point:TF` leaves the `<false code>` in the input stream.

```

20373 \cs_new_protected:Npn \__regex_break_true:w
20374     #1 \__regex_break_point:TF #2 #3 {#2}
20375 \cs_new_protected:Npn \__regex_break_point:TF #1 #2 { #2 }

```

(End definition for `__regex_break_point:TF` and `__regex_break_true:w`.)

`__regex_item_reverse:n` This function makes showing regular expressions easier, and lets us define `\D` in terms of `\d` for instance. There is a subtlety: the end of the query is marked by `-2`, and thus matches `\D` and other negated properties; this case is caught by another part of the code.

```

20376 \cs_new_protected:Npn \__regex_item_reverse:n #1
20377 {
20378     #1
20379     \__regex_break_point:TF { } \__regex_break_true:w
20380 }

```

(End definition for `__regex_item_reverse:n`.)

`__regex_item_caseful_equal:n` Simple comparisons triggering `__regex_break_true:w` when true.

```

\__regex_item_caseful_range:nn
20381 \cs_new_protected:Npn \__regex_item_caseful_equal:n #1
20382 {
20383     \if_int_compare:w #1 = \l__regex_curr_char_int
20384     \exp_after:wN \__regex_break_true:w
20385     \fi:
20386 }
20387 \cs_new_protected:Npn \__regex_item_caseful_range:nn #1 #2
20388 {
20389     \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
20390     \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
20391     \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
20392     \fi:
20393     \fi:
20394 }

```

(End definition for `__regex_item_caseful_equal:n` and `__regex_item_caseful_range:nn`.)

`__regex_item_caseless_equal:n` For caseless matching, we perform the test both on the `current_char` and on the `case_changed_char`. Before doing the second set of tests, we make sure that `case_changed_char` has been computed.

```

\__regex_item_caseless_range:nn
20395 \cs_new_protected:Npn \__regex_item_caseless_equal:n #1
20396 {
20397     \if_int_compare:w #1 = \l__regex_curr_char_int
20398     \exp_after:wN \__regex_break_true:w
20399     \fi:
20400     \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
20401     \__regex_compute_case_changed_char:
20402     \fi:
20403     \if_int_compare:w #1 = \l__regex_case_changed_char_int
20404     \exp_after:wN \__regex_break_true:w

```

```

20405     \fi:
20406   }
20407 \cs_new_protected:Npn \__regex_item_caseless_range:nn #1 #2
20408 {
20409   \reverse_if:N \if_int_compare:w #1 > \l__regex_curr_char_int
20410   \reverse_if:N \if_int_compare:w #2 < \l__regex_curr_char_int
20411   \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
20412   \fi:
20413   \fi:
20414   \if_int_compare:w \l__regex_case_changed_char_int = \c_max_int
20415     \__regex_compute_case_changed_char:
20416   \fi:
20417   \reverse_if:N \if_int_compare:w #1 > \l__regex_case_changed_char_int
20418   \reverse_if:N \if_int_compare:w #2 < \l__regex_case_changed_char_int
20419   \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
20420   \fi:
20421   \fi:
20422 }

```

(End definition for __regex_item_caseless_equal:n and __regex_item_caseless_range:nn.)

__regex_compute_case_changed_char: This function is called when \l__regex_case_changed_char_int has not yet been computed (or rather, when it is set to the marker value \c_max_int). If the current character code is in the range [65,90] (upper-case), then add 32, making it lowercase. If it is in the lower-case letter range [97,122], subtract 32.

```

20423 \cs_new_protected:Npn \__regex_compute_case_changed_char:
20424 {
20425   \int_set_eq:NN \l__regex_case_changed_char_int \l__regex_curr_char_int
20426   \if_int_compare:w \l__regex_curr_char_int > 'Z \exp_stop_f:
20427     \if_int_compare:w \l__regex_curr_char_int > 'z \exp_stop_f: \else:
20428       \if_int_compare:w \l__regex_curr_char_int < 'a \exp_stop_f: \else:
20429         \int_sub:Nn \l__regex_case_changed_char_int
20430         { \c__regex_ascii_lower_int }
20431       \fi:
20432     \fi:
20433   \else:
20434     \if_int_compare:w \l__regex_curr_char_int < 'A \exp_stop_f: \else:
20435       \int_add:Nn \l__regex_case_changed_char_int
20436       { \c__regex_ascii_lower_int }
20437     \fi:
20438   \fi:
20439 }

```

(End definition for __regex_compute_case_changed_char:.)

__regex_item_equal:n Those must always be defined to expand to a **caseful** (default) or **caseless** version, and not be protected: they must expand when compiling, to hard-code which tests are caseless or caseful.

```

20440 \cs_new_eq:NN \__regex_item_equal:n ?
20441 \cs_new_eq:NN \__regex_item_range:nn ?

```

(End definition for __regex_item_equal:n and __regex_item_range:nn.)

`__regex_item_catcode:nT` The argument is a sum of powers of 4 with exponents given by the allowed category codes (between 0 and 13). Dividing by a given power of 4 gives an odd result if and only if that category code is allowed. If the catcode does not match, then skip the character code tests which follow.

```

20442 \cs_new_protected:Npn \__regex_item_catcode:
20443 {
20444   "
20445   \if_case:w \l__regex_curr_catcode_int
20446     1      \or: 4      \or: 10      \or: 40
20447   \or: 100  \or:      \or: 1000    \or: 4000
20448   \or: 10000 \or:      \or: 100000 \or: 400000
20449   \or: 1000000 \or: 4000000 \else: 1*0
20450   \fi:
20451 }
20452 \cs_new_protected:Npn \__regex_item_catcode:nT #1
20453 {
20454   \if_int_odd:w \int_eval:n { #1 / \__regex_item_catcode: } \exp_stop_f:
20455   \exp_after:wN \use:n
20456   \else:
20457   \exp_after:wN \use_none:n
20458   \fi:
20459 }
20460 \cs_new_protected:Npn \__regex_item_catcode_reverse:nT #1#2
20461 { \__regex_item_catcode:nT {#1} { \__regex_item_reverse:n {#2} } }

```

(End definition for `__regex_item_catcode:nT`, `__regex_item_catcode_reverse:nT`, and `__regex_item_catcode:.`)

`__regex_item_exact:nn` This matches an exact *<category>-<character code>* pair, or an exact control sequence, more precisely one of several possible control sequences.

```

20462 \cs_new_protected:Npn \__regex_item_exact:nn #1#2
20463 {
20464   \if_int_compare:w #1 = \l__regex_curr_catcode_int
20465   \if_int_compare:w #2 = \l__regex_curr_char_int
20466   \exp_after:wN \exp_after:wN \exp_after:wN \__regex_break_true:w
20467   \fi:
20468   \fi:
20469 }
20470 \cs_new_protected:Npn \__regex_item_exact_cs:n #1
20471 {
20472   \int_compare:nNnTF \l__regex_curr_catcode_int = 0
20473   {
20474     \tl_set:Nx \l__regex_internal_a_tl
20475     { \scan_stop: \__regex_curr_cs_to_str: \scan_stop: }
20476     \tl_if_in:noTF { \scan_stop: #1 \scan_stop: }
20477     \l__regex_internal_a_tl
20478     { \__regex_break_true:w } { }
20479   }
20480   { }
20481 }

```

(End definition for `__regex_item_exact:nn` and `__regex_item_exact_cs:n`.)

`__regex_item_cs:n` Match a control sequence (the argument is a compiled regex). First test the catcode of the current token to be zero. Then perform the matching test, and break if the csname

indeed matches. The three `\exp_after:wN` expand the contents of the `\toks⟨current position⟩` (of the form `\exp_not:n {⟨control sequence⟩}`) to `⟨control sequence⟩`. We store the cs name before building states for the cs, as those states may overlap with toks registers storing the user's input.

```

20482 \cs_new_protected:Npn \__regex_item_cs:n #1
20483 {
20484   \int_compare:nNnT \l__regex_curr_catcode_int = 0
20485   {
20486     \group_begin:
20487       \tl_set:Nx \l__regex_cs_name_tl { \__regex_curr_cs_to_str: }
20488       \__regex_single_match:
20489       \__regex_disable_submatches:
20490       \__regex_build_for_cs:n {#1}
20491       \bool_set_eq:NN \l__regex_saved_success_bool
20492         \g__regex_success_bool
20493       \exp_args:NV \__regex_match_cs:n \l__regex_cs_name_tl
20494       \if_meaning:w \c_true_bool \g__regex_success_bool
20495         \group_insert_after:N \__regex_break_true:w
20496       \fi:
20497       \bool_gset_eq:NN \g__regex_success_bool
20498         \l__regex_saved_success_bool
20499     \group_end:
20500   }
20501 }

```

(End definition for `__regex_item_cs:n`.)

38.2.3 Character property tests

`__regex_prop_d:` Character property tests for `\d`, `\W`, *etc.* These character properties are not affected by the `(?i)` option. The characters recognized by each one are as follows: `\d=[0-9]`, `\w=[0-9A-Z_a-z]`, `\s=[_\^\^I\^\^J\^\^L\^\^M]`, `\h=[_\^\^I]`, `\v=[\^\^J-\^\^M]`, and the upper case counterparts match anything that the lower case does not match. The order in which the various tests appear is optimized for usual mostly lower case letter text.

```

\__regex_prop_N:
20502 \cs_new_protected:Npn \__regex_prop_d:
20503   { \__regex_item_caseful_range:nn { '0 } { '9 } }
20504 \cs_new_protected:Npn \__regex_prop_h:
20505   {
20506     \__regex_item_caseful_equal:n { '\ }
20507     \__regex_item_caseful_equal:n { '\^\^I }
20508   }
20509 \cs_new_protected:Npn \__regex_prop_s:
20510   {
20511     \__regex_item_caseful_equal:n { '\ }
20512     \__regex_item_caseful_equal:n { '\^\^I }
20513     \__regex_item_caseful_equal:n { '\^\^J }
20514     \__regex_item_caseful_equal:n { '\^\^L }
20515     \__regex_item_caseful_equal:n { '\^\^M }
20516   }
20517 \cs_new_protected:Npn \__regex_prop_v:
20518   { \__regex_item_caseful_range:nn { '\^\^J } { '\^\^M } } % lf, vtab, ff, cr
20519 \cs_new_protected:Npn \__regex_prop_w:
20520   {

```

```

20521     \_regex_item_caseful_range:nn { 'a } { 'z }
20522     \_regex_item_caseful_range:nn { 'A } { 'Z }
20523     \_regex_item_caseful_range:nn { '0 } { '9 }
20524     \_regex_item_caseful_equal:n { '_' }
20525   }
20526 \cs_new_protected:Npn \_regex_prop_N:
20527 {
20528   \_regex_item_reverse:n
20529   { \_regex_item_caseful_equal:n { '^~J } }
20530 }

```

(End definition for _regex_prop_d: and others.)

```

\_regex_posix_alnum: POSIX properties. No surprise.
\_regex_posix_alpha: 20531 \cs_new_protected:Npn \_regex_posix_alnum:
\_regex_posix_ascii: 20532 { \_regex_posix_alpha: \_regex_posix_digit: }
\_regex_posix_blank: 20533 \cs_new_protected:Npn \_regex_posix_alpha:
\_regex_posix_cntrl: 20534 { \_regex_posix_lower: \_regex_posix_upper: }
\_regex_posix_digit: 20535 \cs_new_protected:Npn \_regex_posix_ascii:
\_regex_posix_graph: 20536 {
\_regex_posix_lower: 20537   \_regex_item_caseful_range:nn
\_regex_posix_print: 20538   \c__regex_ascii_min_int
\_regex_posix_punct: 20539   \c__regex_ascii_max_int
20540 }
\_regex_posix_space: 20541 \cs_new_eq:NN \_regex_posix_blank: \_regex_prop_h:
\_regex_posix_upper: 20542 \cs_new_protected:Npn \_regex_posix_cntrl:
  \_regex_posix_word: 20543 {
\_regex_posix_xdigit: 20544   \_regex_item_caseful_range:nn
20545   \c__regex_ascii_min_int
20546   \c__regex_ascii_max_control_int
20547   \_regex_item_caseful_equal:n \c__regex_ascii_max_int
20548 }
20549 \cs_new_eq:NN \_regex_posix_digit: \_regex_prop_d:
20550 \cs_new_protected:Npn \_regex_posix_graph:
20551 { \_regex_item_caseful_range:nn { '!' } { '~ } }
20552 \cs_new_protected:Npn \_regex_posix_lower:
20553 { \_regex_item_caseful_range:nn { 'a } { 'z } }
20554 \cs_new_protected:Npn \_regex_posix_print:
20555 { \_regex_item_caseful_range:nn { '\' } { '~ } }
20556 \cs_new_protected:Npn \_regex_posix_punct:
20557 {
20558   \_regex_item_caseful_range:nn { '!' } { '/' }
20559   \_regex_item_caseful_range:nn { ':' } { '@' }
20560   \_regex_item_caseful_range:nn { '[' } { '[' }
20561   \_regex_item_caseful_range:nn { '\{ } { '~ }
20562 }
20563 \cs_new_protected:Npn \_regex_posix_space:
20564 {
20565   \_regex_item_caseful_equal:n { '\' }
20566   \_regex_item_caseful_range:nn { '^~I } { '^~M }
20567 }
20568 \cs_new_protected:Npn \_regex_posix_upper:
20569 { \_regex_item_caseful_range:nn { 'A } { 'Z } }
20570 \cs_new_eq:NN \_regex_posix_word: \_regex_prop_w:

```

```

20571 \cs_new_protected:Npn \__regex_posix_xdigit:
20572 {
20573   \__regex_posix_digit:
20574   \__regex_item_caseful_range:nn { 'A } { 'F }
20575   \__regex_item_caseful_range:nn { 'a } { 'f }
20576 }

```

(End definition for __regex_posix_alnum: and others.)

38.2.4 Simple character escape

Before actually parsing the regular expression or the replacement text, we go through them once, converting `\n` to the character 10, *etc.* In this pass, we also convert any special character (`*`, `?`, `{`, *etc.*) or escaped alphanumeric character into a marker indicating that this was a special sequence, and replace escaped special characters and non-escaped alphanumeric characters by markers indicating that those were “raw” characters. The rest of the code can then avoid caring about escaping issues (those can become quite complex to handle in combination with ranges in character classes).

Usage: `__regex_escape_use:nnnn` *<inline 1>* *<inline 2>* *<inline 3>* *{<token list>}*
The *<token list>* is converted to a string, then read from left to right, interpreting backslashes as escaping the next character. Unescaped characters are fed to the function *<inline 1>*, and escaped characters are fed to the function *<inline 2>* within an *x*-expansion context (typically those functions perform some tests on their argument to decide how to output them). The escape sequences `\a`, `\e`, `\f`, `\n`, `\r`, `\t` and `\x` are recognized, and those are replaced by the corresponding character, then fed to *<inline 3>*. The result is then left in the input stream. Spaces are ignored unless escaped.

The conversion is done within an *x*-expanding assignment.

`__regex_escape_use:nnnn` The result is built in `\l__regex_internal_a_tl`, which is then left in the input stream. Tracing code is added as appropriate inside this token list. Go through `#4` once, applying `#1`, `#2`, or `#3` as relevant to each character (after de-escaping it).

```

20577 \__kernel_patch:nnNn
20578 {
20579   \__regex_trace_push:nnN { regex } { 1 } \__regex_escape_use:nnnn
20580   \group_begin:
20581     \tl_set:Nx \l__regex_internal_a_tl
20582     { \__regex_trace_pop:nnN { regex } { 1 } \__regex_escape_use:nnnn }
20583     \use_none:nnn
20584   }
20585   { }
20586 \cs_new_protected:Npn \__regex_escape_use:nnnn #1#2#3#4
20587 {
20588   \group_begin:
20589     \tl_clear:N \l__regex_internal_a_tl
20590     \cs_set:Npn \__regex_escape_unescaped:N ##1 { #1 }
20591     \cs_set:Npn \__regex_escape_escaped:N ##1 { #2 }
20592     \cs_set:Npn \__regex_escape_raw:N ##1 { #3 }
20593     \__regex_standard_escapechar:
20594     \tl_gset:Nx \g__regex_internal_tl
20595     { \__kernel_str_to_other_fast:n {#4} }
20596     \tl_put_right:Nx \l__regex_internal_a_tl
20597     {
20598       \exp_after:wN \__regex_escape_loop:N \g__regex_internal_tl

```

```

20599         { break } \prg_break_point:
20600     }
20601     \exp_after:wN
20602     \group_end:
20603     \l__regex_internal_a_tl
20604 }

```

(End definition for __regex_escape_use:nnnn.)

__regex_escape_loop:N __regex_escape_loop:N reads one character: if it is special (space, backslash, or end-marker), perform the associated action, otherwise it is simply an unescaped character. After a backslash, the same is done, but unknown characters are “escaped”.

```

20605 \cs_new:Npn \__regex_escape_loop:N #1
20606 {
20607     \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
20608     { \__regex_escape_unescaped:N #1 }
20609     \__regex_escape_loop:N
20610 }
20611 \cs_new:cpn { __regex_escape\_c_backslash_str :w }
20612     \__regex_escape_loop:N #1
20613 {
20614     \cs_if_exist_use:cF { __regex_escape\_token_to_str:N #1:w }
20615     { \__regex_escape_escaped:N #1 }
20616     \__regex_escape_loop:N
20617 }

```

(End definition for __regex_escape_loop:N and __regex_escape_w.)

__regex_escape_unescaped:N Those functions are never called before being given a new meaning, so their definitions here don’t matter.

```

\__regex_escape_escaped:N
\__regex_escape_raw:N
20618 \cs_new_eq:NN \__regex_escape_unescaped:N ?
20619 \cs_new_eq:NN \__regex_escape_escaped:N ?
20620 \cs_new_eq:NN \__regex_escape_raw:N ?

```

(End definition for __regex_escape_unescaped:N, __regex_escape_escaped:N, and __regex_escape_raw:N.)

__regex_escape_break:w The loop is ended upon seeing the end-marker “break”, with an error if the string ended in a backslash. Spaces are ignored, and \a, \e, \f, \n, \r, \t take their meaning here.

```

\__regex_escape_/break:w
\__regex_escape_/a:w 20621 \cs_new_eq:NN \__regex_escape_break:w \prg_break:
\__regex_escape_/e:w 20622 \cs_new:cpn { __regex_escape_/break:w }
\__regex_escape_/f:w 20623 {
\__regex_escape_/n:w 20624     \__kernel_msg_expandable_error:nn { kernel } { trailing-backslash }
\__regex_escape_/r:w 20625     \prg_break:
\__regex_escape_/t:w 20626 }
\__regex_escape_\_w 20627 \cs_new:cpn { __regex_escape\_~:w } { }
20628 \cs_new:cpx { __regex_escape_/a:w }
20629     { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^G }
20630 \cs_new:cpx { __regex_escape_/t:w }
20631     { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^I }
20632 \cs_new:cpx { __regex_escape_/n:w }
20633     { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^J }
20634 \cs_new:cpx { __regex_escape_/f:w }
20635     { \exp_not:N \__regex_escape_raw:N \iow_char:N \^^L }

```

```

20636 \cs_new:cpx { __regex_escape_/r:w }
20637 { \exp_not:N __regex_escape_raw:N \iow_char:N ^^M }
20638 \cs_new:cpx { __regex_escape_/e:w }
20639 { \exp_not:N __regex_escape_raw:N \iow_char:N ^^[ }

```

(End definition for `__regex_escape_break:w` and others.)

```

__regex_escape_/x:w
__regex_escape_x_end:w
__regex_escape_x_large:n

```

When `\x` is encountered, `__regex_escape_x_test:N` is responsible for grabbing some hexadecimal digits, and feeding the result to `__regex_escape_x_end:w`. If the number is too big interrupt the assignment and produce an error, otherwise call `__regex_escape_raw:N` on the corresponding character token.

```

20640 \cs_new:cpn { __regex_escape_/x:w } __regex_escape_loop:N
20641 {
20642   \exp_after:wN __regex_escape_x_end:w
20643   \int_value:w "0 __regex_escape_x_test:N
20644 }
20645 \cs_new:Npn __regex_escape_x_end:w #1 ;
20646 {
20647   \int_compare:nNnTF {#1} > \c_max_char_int
20648   {
20649     \kernel_msg_expandable_error:nnff { kernel } { x-overflow }
20650     {#1} { \int_to_Hex:n {#1} }
20651   }
20652   {
20653     \exp_last_unbraced:Nf __regex_escape_raw:N
20654     { \char_generate:nn {#1} { 12 } }
20655   }
20656 }

```

(End definition for `__regex_escape_/x:w`, `__regex_escape_x_end:w`, and `__regex_escape_x_large:n`.)

```

__regex_escape_x_test:N
__regex_escape_x_testii:N

```

Find out whether the first character is a left brace (allowing any number of hexadecimal digits), or not (allowing up to two hexadecimal digits). We need to check for the end-of-string marker. Eventually, call either `__regex_escape_x_loop:N` or `__regex_escape_x:N`.

```

20657 \cs_new:Npn __regex_escape_x_test:N #1
20658 {
20659   \str_if_eq:nnTF {#1} { break } { ; }
20660   {
20661     \if_charcode:w \c_space_token #1
20662     \exp_after:wN __regex_escape_x_test:N
20663   \else:
20664     \exp_after:wN __regex_escape_x_testii:N
20665     \exp_after:wN #1
20666   \fi:
20667   }
20668 }
20669 \cs_new:Npn __regex_escape_x_testii:N #1
20670 {
20671   \if_charcode:w \c_left_brace_str #1
20672   \exp_after:wN __regex_escape_x_loop:N
20673 \else:
20674   __regex_hexadecimal_use:NTF #1
20675   { \exp_after:wN __regex_escape_x:N }

```

```

20676         { ; \exp_after:wN \_regex_escape_loop:N \exp_after:wN #1 }
20677     \fi:
20678 }

```

(End definition for _regex_escape_x_test:N and _regex_escape_x_testii:N.)

_regex_escape_x:N This looks for the second digit in the unbraced case.

```

20679 \cs_new:Npn \_regex_escape_x:N #1
20680 {
20681     \str_if_eq:nnTF {#1} { break } { ; }
20682     {
20683         \_regex_hexadecimal_use:NTF #1
20684         { ; \_regex_escape_loop:N }
20685         { ; \_regex_escape_loop:N #1 }
20686     }
20687 }

```

(End definition for _regex_escape_x:N.)

_regex_escape_x_loop:N Grab hexadecimal digits, skip spaces, and at the end, check that there is a right brace, otherwise raise an error outside the assignment.

_regex_escape_x_loop_error:

```

20688 \cs_new:Npn \_regex_escape_x_loop:N #1
20689 {
20690     \str_if_eq:nnTF {#1} { break }
20691     { ; \_regex_escape_x_loop_error:n { } {#1} }
20692     {
20693         \_regex_hexadecimal_use:NTF #1
20694         { \_regex_escape_x_loop:N }
20695         {
20696             \token_if_eq_charcode:NNTF \c_space_token #1
20697             { \_regex_escape_x_loop:N }
20698             {
20699                 ;
20700                 \exp_after:wN
20701                 \token_if_eq_charcode:NNTF \c_right_brace_str #1
20702                 { \_regex_escape_loop:N }
20703                 { \_regex_escape_x_loop_error:n {#1} }
20704             }
20705         }
20706     }
20707 }
20708 \cs_new:Npn \_regex_escape_x_loop_error:n #1
20709 {
20710     \__kernel_msg_expandable_error:nnn { kernel } { x-missing-rbrace } {#1}
20711     \_regex_escape_loop:N #1
20712 }

```

(End definition for _regex_escape_x_loop:N and _regex_escape_x_loop_error:.)

_regex_hexadecimal_use:NTF TEX detects uppercase hexadecimal digits for us but not the lowercase letters, which we need to detect and replace by their uppercase counterpart.

```

20713 \prg_new_conditional:Npnn \_regex_hexadecimal_use:N #1 { TF }
20714 {
20715     \if_int_compare:w 1 < "1 \token_to_str:N #1 \exp_stop_f:
20716     #1 \prg_return_true:

```

```

20717     \else:
20718         \if_case:w
20719             \int_eval:n { \exp_after:wN ‘ \token_to_str:N #1 - ‘a }
20720             A
20721         \or: B
20722         \or: C
20723         \or: D
20724         \or: E
20725         \or: F
20726     \else:
20727         \prg_return_false:
20728         \exp_after:wN \use_none:n
20729     \fi:
20730     \prg_return_true:
20731 \fi:
20732 }

```

(End definition for `__regex_hexadecimal_use:NTF`.)

`__regex_char_if_alphanumeric:NTF`

These two tests are used in the first pass when parsing a regular expression. That pass is responsible for finding escaped and non-escaped characters, and recognizing which ones have special meanings and which should be interpreted as “raw” characters. Namely,

- alphanumeric are “raw” if they are not escaped, and may have a special meaning when escaped;
- non-alphanumeric printable ascii characters are “raw” if they are escaped, and may have a special meaning when not escaped;
- characters other than printable ascii are always “raw”.

The code is ugly, and highly based on magic numbers and the ascii codes of characters. This is mostly unavoidable for performance reasons. Maybe the tests can be optimized a little bit more. Here, “alphanumeric” means 0–9, A–Z, a–z; “special” character means non-alphanumeric but printable ascii, from space (hex 20) to del (hex 7E).

```

20733 \prg_new_conditional:Npnn \__regex_char_if_special:N #1 { TF }
20734 {
20735     \if_int_compare:w ‘#1 > ‘Z \exp_stop_f:
20736     \if_int_compare:w ‘#1 > ‘z \exp_stop_f:
20737     \if_int_compare:w ‘#1 < \c__regex_ascii_max_int
20738         \prg_return_true: \else: \prg_return_false: \fi:
20739     \else:
20740         \if_int_compare:w ‘#1 < ‘a \exp_stop_f:
20741         \prg_return_true: \else: \prg_return_false: \fi:
20742     \fi:
20743 \else:
20744     \if_int_compare:w ‘#1 > ‘9 \exp_stop_f:
20745     \if_int_compare:w ‘#1 < ‘A \exp_stop_f:
20746     \prg_return_true: \else: \prg_return_false: \fi:
20747 \else:
20748     \if_int_compare:w ‘#1 < ‘0 \exp_stop_f:
20749     \if_int_compare:w ‘#1 < ‘\ \exp_stop_f:
20750     \prg_return_false: \else: \prg_return_true: \fi:
20751 \else: \prg_return_false: \fi:
20752 \fi:

```



```

20753     \fi:
20754   }
20755 \prg_new_conditional:Npnn \__regex_char_if_alphanumeric:N #1 { TF }
20756 {
20757   \if_int_compare:w '#1 > 'Z \exp_stop_f:
20758     \if_int_compare:w '#1 > 'z \exp_stop_f:
20759     \prg_return_false:
20760   \else:
20761     \if_int_compare:w '#1 < 'a \exp_stop_f:
20762     \prg_return_false: \else: \prg_return_true: \fi:
20763   \fi:
20764 \else:
20765   \if_int_compare:w '#1 > '9 \exp_stop_f:
20766   \if_int_compare:w '#1 < 'A \exp_stop_f:
20767   \prg_return_false: \else: \prg_return_true: \fi:
20768 \else:
20769   \if_int_compare:w '#1 < '0 \exp_stop_f:
20770   \prg_return_false: \else: \prg_return_true: \fi:
20771 \fi:
20772 \fi:
20773 }

```

(End definition for `__regex_char_if_alphanumeric:N` and `__regex_char_if_special:N`.)

38.3 Compiling

A regular expression starts its life as a string of characters. In this section, we convert it to internal instructions, resulting in a “compiled” regular expression. This compiled expression is then turned into states of an automaton in the building phase. Compiled regular expressions consist of the following:

- `__regex_class:NnnnN` $\langle \text{boolean} \rangle$ $\{ \langle \text{tests} \rangle \}$ $\{ \langle \text{min} \rangle \}$ $\{ \langle \text{more} \rangle \}$ $\langle \text{lazyness} \rangle$
- `__regex_group:nnnN` $\{ \langle \text{branches} \rangle \}$ $\{ \langle \text{min} \rangle \}$ $\{ \langle \text{more} \rangle \}$ $\langle \text{lazyness} \rangle$, also `__regex_group_no_capture:nnnN` and `__regex_group_resetting:nnnN` with the same syntax.
- `__regex_branch:n` $\{ \langle \text{contents} \rangle \}$
- `__regex_command_K:`
- `__regex_assertion:Nn` $\langle \text{boolean} \rangle$ $\{ \langle \text{assertion test} \rangle \}$, where the $\langle \text{assertion test} \rangle$ is `__regex_b_test:` or `__regex_anchor:N` $\langle \text{integer} \rangle$

Tests can be the following:

- `__regex_item_caseful_equal:n` $\{ \langle \text{char code} \rangle \}$
- `__regex_item_caseless_equal:n` $\{ \langle \text{char code} \rangle \}$
- `__regex_item_caseful_range:nn` $\{ \langle \text{min} \rangle \}$ $\{ \langle \text{max} \rangle \}$
- `__regex_item_caseless_range:nn` $\{ \langle \text{min} \rangle \}$ $\{ \langle \text{max} \rangle \}$
- `__regex_item_catcode:nT` $\{ \langle \text{catcode bitmap} \rangle \}$ $\{ \langle \text{tests} \rangle \}$

- `__regex_item_catcode_reverse:nT` $\{\langle catcode\ bitmap\rangle\}$ $\{\langle tests\rangle\}$
- `__regex_item_reverse:n` $\{\langle tests\rangle\}$
- `__regex_item_exact:nn` $\{\langle catcode\rangle\}$ $\{\langle char\ code\rangle\}$
- `__regex_item_exact_cs:n` $\{\langle csnames\rangle\}$, more precisely given as $\langle csname\rangle$ `\scan_stop:` $\langle csname\rangle$ `\scan_stop:` $\langle csname\rangle$ and so on in a brace group.
- `__regex_item_cs:n` $\{\langle compiled\ regex\rangle\}$

38.3.1 Variables used when compiling

`\l__regex_group_level_int` We make sure to open the same number of groups as we close.

```
20774 \int_new:N \l__regex_group_level_int
```

(End definition for `\l__regex_group_level_int`.)

`\l__regex_mode_int` While compiling, ten modes are recognized, labelled -63 , -23 , -6 , -2 , 0 , 2 , 3 , 6 , 23 , 63 .
`\c__regex_cs_in_class_mode_int` See section 38.3.3. We only define some of these as constants.

```
20775 \int_new:N \l__regex_mode_int
20776 \int_const:Nn \c__regex_cs_in_class_mode_int { -6 }
20777 \int_const:Nn \c__regex_cs_mode_int { -2 }
20778 \int_const:Nn \c__regex_outer_mode_int { 0 }
20779 \int_const:Nn \c__regex_catcode_mode_int { 2 }
20780 \int_const:Nn \c__regex_class_mode_int { 3 }
20781 \int_const:Nn \c__regex_catcode_in_class_mode_int { 6 }
```

(End definition for `\l__regex_mode_int` and others.)

`\l__regex_catcodes_int` We wish to allow constructions such as `\c[~BE](. . \cL[a-z] . .)`, where the outer catcode test applies to the whole group, but is superseded by the inner catcode test. For this to work, we need to keep track of lists of allowed category codes: `\l__regex_catcodes_int` and `\l__regex_default_catcodes_int` are bitmaps, sums of 4^c , for all allowed catcodes c . The latter is local to each capturing group, and we reset `\l__regex_catcodes_int` to that value after each character or class, changing it only when encountering a `\c` escape. The boolean records whether the list of categories of a catcode test has to be inverted: compare `\c[~BE]` and `\c[BE]`.

```
20782 \int_new:N \l__regex_catcodes_int
20783 \int_new:N \l__regex_default_catcodes_int
20784 \bool_new:N \l__regex_catcodes_bool
```

(End definition for `\l__regex_catcodes_int`, `\l__regex_default_catcodes_int`, and `\l__regex_catcodes_bool`.)

`\c__regex_catcode_C_int` Constants: 4^c for each category, and the sum of all powers of 4.

```
20785 \int_const:Nn \c__regex_catcode_C_int { "1 }
20786 \int_const:Nn \c__regex_catcode_B_int { "4 }
20787 \int_const:Nn \c__regex_catcode_E_int { "10 }
20788 \int_const:Nn \c__regex_catcode_M_int { "40 }
20789 \int_const:Nn \c__regex_catcode_T_int { "100 }
20790 \int_const:Nn \c__regex_catcode_P_int { "1000 }
20791 \int_const:Nn \c__regex_catcode_U_int { "4000 }
20792 \int_const:Nn \c__regex_catcode_D_int { "10000 }
20793 \int_const:Nn \c__regex_catcode_S_int { "100000 }
```

`\c__regex_catcode_O_int`
`\c__regex_catcode_A_int`
`\c__regex_all_catcodes_int`

```

20794 \int_const:Nn \c__regex_catcode_L_int { "400000 }
20795 \int_const:Nn \c__regex_catcode_O_int { "1000000 }
20796 \int_const:Nn \c__regex_catcode_A_int { "4000000 }
20797 \int_const:Nn \c__regex_all_catcodes_int { "5515155 }

```

(End definition for \c__regex_catcode_C_int and others.)

\l__regex_internal_regex The compilation step stores its result in this variable.

```

20798 \cs_new_eq:NN \l__regex_internal_regex \c__regex_no_match_regex

```

(End definition for \l__regex_internal_regex.)

\l__regex_show_prefix_seq This sequence holds the prefix that makes up the line displayed to the user. The various items must be removed from the right, which is tricky with a token list, hence we use a sequence.

```

20799 \seq_new:N \l__regex_show_prefix_seq

```

(End definition for \l__regex_show_prefix_seq.)

\l__regex_show_lines_int A hack. To know whether a given class has a single item in it or not, we count the number of lines when showing the class.

```

20800 \int_new:N \l__regex_show_lines_int

```

(End definition for \l__regex_show_lines_int.)

38.3.2 Generic helpers used when compiling

__regex_two_if_eq:NNNNTF Used to compare pairs of things like __regex_compile_special:N ? together. It's often inconvenient to get the catcodes of the character to match so we just compare the character code. Besides, the expanding behaviour of \if:w is very useful as that means we can use \c_left_brace_str and the like.

```

20801 \prg_new_conditional:Npnn \__regex_two_if_eq:NNNN #1#2#3#4 { TF }
20802 {
20803   \if_meaning:w #1 #3
20804   \if:w #2 #4
20805     \prg_return_true:
20806   \else:
20807     \prg_return_false:
20808   \fi:
20809 \else:
20810   \prg_return_false:
20811 \fi:
20812 }

```

(End definition for __regex_two_if_eq:NNNNTF.)

__regex_get_digits:NTFw If followed by some raw digits, collect them one by one in the integer variable #1, and take the true branch. Otherwise, take the false branch.

```

20813 \cs_new_protected:Npn \__regex_get_digits:NTFw #1#2#3#4#5
20814 {
20815   \__regex_if_raw_digit:NNTF #4 #5
20816   { #1 = #5 \__regex_get_digits_loop:nw {#2} }
20817   { #3 #4 #5 }
20818 }

```

```

20819 \cs_new:Npn \__regex_get_digits_loop:nw #1#2#3
20820 {
20821   \__regex_if_raw_digit:NNTF #2 #3
20822   { #3 \__regex_get_digits_loop:nw {#1} }
20823   { \scan_stop: #1 #2 #3 }
20824 }

```

(End definition for `__regex_get_digits:NNTFw` and `__regex_get_digits_loop:w`.)

`__regex_if_raw_digit:NNTF` Test used when grabbing digits for the `{m,n}` quantifier. It only accepts non-escaped digits.

```

20825 \prg_new_conditional:Npnn \__regex_if_raw_digit:NN #1#2 { TF }
20826 {
20827   \if_meaning:w \__regex_compile_raw:N #1
20828   \if_int_compare:w 1 < 1 #2 \exp_stop_f:
20829   \prg_return_true:
20830   \else:
20831   \prg_return_false:
20832   \fi:
20833   \else:
20834   \prg_return_false:
20835   \fi:
20836 }

```

(End definition for `__regex_if_raw_digit:NNTF`.)

38.3.3 Mode

When compiling the NFA corresponding to a given regex string, we can be in ten distinct modes, which we label by some magic numbers:

- 6 `[\c{...}]` control sequence in a class,
- 2 `\c{...}` control sequence,
- 0 ... outer,
- 2 `\c...` catcode test,
- 6 `[\c...]` catcode test in a class,
- 63 `[\c{[...]}]` class inside mode -6,
- 23 `\c{[...]}` class inside mode -2,
- 3 `[...]` class inside mode 0,
- 23 `\c[...]` class inside mode 2,
- 63 `[\c[...]]` class inside mode 6.

This list is exhaustive, because `\c` escape sequences cannot be nested, and character classes cannot be nested directly. The choice of numbers is such as to optimize the most useful tests, and make transitions from one mode to another as simple as possible.

- Even modes mean that we are not directly in a character class. In this case, a left bracket appends 3 to the mode. In a character class, a right bracket changes the mode as $m \rightarrow (m - 15)/13$, truncated.
- Grouping, assertion, and anchors are allowed in non-positive even modes (0, -2, -6), and do not change the mode. Otherwise, they trigger an error.
- A left bracket is special in even modes, appending 3 to the mode; in those modes, quantifiers and the dot are recognized, and the right bracket is normal. In odd modes (within classes), the left bracket is normal, but the right bracket ends the class, changing the mode from m to $(m - 15)/13$, truncated; also, ranges are recognized.
- In non-negative modes, left and right braces are normal. In negative modes, however, left braces trigger a warning; right braces end the control sequence, going from -2 to 0 or -6 to 3, with error recovery for odd modes.
- Properties (such as the `\d` character class) can appear in any mode.

`_regex_if_in_class:TF` Test whether we are directly in a character class (at the innermost level of nesting). There, many escape sequences are not recognized, and special characters are normal. Also, for every raw character, we must look ahead for a possible raw dash.

```

20837 \cs_new:Npn \_regex_if_in_class:TF
20838   {
20839     \if_int_odd:w \l__regex_mode_int
20840       \exp_after:wN \use_i:nn
20841     \else:
20842       \exp_after:wN \use_ii:nn
20843     \fi:
20844   }

```

(End definition for `_regex_if_in_class:TF`.)

`_regex_if_in_cs:TF` Right braces are special only directly inside control sequences (at the inner-most level of nesting, not counting groups).

```

20845 \cs_new:Npn \_regex_if_in_cs:TF
20846   {
20847     \if_int_odd:w \l__regex_mode_int
20848       \exp_after:wN \use_ii:nn
20849     \else:
20850       \if_int_compare:w \l__regex_mode_int < \c__regex_outer_mode_int
20851         \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
20852       \else:
20853         \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
20854       \fi:
20855     \fi:
20856   }

```

(End definition for `_regex_if_in_cs:TF`.)

`_regex_if_in_class_or_catcode:TF` Assertions are only allowed in modes 0, -2, and -6, *i.e.*, even, non-positive modes.

```

20857 \cs_new:Npn \_regex_if_in_class_or_catcode:TF
20858   {
20859     \if_int_odd:w \l__regex_mode_int

```

```

20860     \exp_after:wN \use_i:nn
20861 \else:
20862     \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
20863     \exp_after:wN \exp_after:wN \exp_after:wN \use_i:nn
20864 \else:
20865     \exp_after:wN \exp_after:wN \exp_after:wN \use_ii:nn
20866 \fi:
20867 \fi:
20868 }

```

(End definition for __regex_if_in_class_or_catcode:TF.)

__regex_if_within_catcode:TF This test takes the true branch if we are in a catcode test, either immediately following it (modes 2 and 6) or in a class on which it applies (modes 23 and 63). This is used to tweak how left brackets behave in modes 2 and 6.

```

20869 \cs_new:Npn \__regex_if_within_catcode:TF
20870 {
20871     \if_int_compare:w \l__regex_mode_int > \c__regex_outer_mode_int
20872     \exp_after:wN \use_i:nn
20873 \else:
20874     \exp_after:wN \use_ii:nn
20875 \fi:
20876 }

```

(End definition for __regex_if_within_catcode:TF.)

__regex_chk_c_allowed:T The \c escape sequence is only allowed in modes 0 and 3, *i.e.*, not within any other \c escape sequence.

```

20877 \cs_new_protected:Npn \__regex_chk_c_allowed:T
20878 {
20879     \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
20880     \exp_after:wN \use:n
20881 \else:
20882     \if_int_compare:w \l__regex_mode_int = \c__regex_class_mode_int
20883     \exp_after:wN \exp_after:wN \exp_after:wN \use:n
20884 \else:
20885     \__kernel_msg_error:nn { kernel } { c-bad-mode }
20886     \exp_after:wN \exp_after:wN \exp_after:wN \use_none:n
20887 \fi:
20888 \fi:
20889 }

```

(End definition for __regex_chk_c_allowed:T.)

__regex_mode_quit_c: This function changes the mode as it is needed just after a catcode test.

```

20890 \cs_new_protected:Npn \__regex_mode_quit_c:
20891 {
20892     \if_int_compare:w \l__regex_mode_int = \c__regex_catcode_mode_int
20893     \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
20894 \else:
20895     \if_int_compare:w \l__regex_mode_int =
20896     \c__regex_catcode_in_class_mode_int
20897     \int_set_eq:NN \l__regex_mode_int \c__regex_class_mode_int
20898 \fi:
20899 \fi:
20900 }

```

(End definition for _regex_mode_quit_c:.)

38.3.4 Framework

_regex_compile:w Used when compiling a user regex or a regex for the \c{...} escape sequence within
_regex_compile_end: another regex. Start building a token list within a group (with x-expansion at the outset),
and set a few variables (group level, catcodes), then start the first branch. At the end,
make sure there are no dangling classes nor groups, close the last branch: we are done
building \l_regex_internal_regex.

```

20901 \cs_new_protected:Npn \_regex_compile:w
20902   {
20903     \group_begin:
20904       \tl_build_begin:N \l__regex_build_tl
20905       \int_zero:N \l__regex_group_level_int
20906       \int_set_eq:NN \l__regex_default_catcodes_int
20907         \c__regex_all_catcodes_int
20908       \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
20909       \cs_set:Npn \_regex_item_equal:n { \_regex_item_caseful_equal:n }
20910       \cs_set:Npn \_regex_item_range:nn { \_regex_item_caseful_range:nn }
20911       \tl_build_put_right:Nn \l__regex_build_tl
20912         { \_regex_branch:n { \if_false: } \fi: }
20913     }
20914 \cs_new_protected:Npn \_regex_compile_end:
20915   {
20916     \__regex_if_in_class:TF
20917     {
20918       \__kernel_msg_error:nn { kernel } { missing-rbrack }
20919       \use:c { __regex_compile_]: }
20920       \prg_do_nothing: \prg_do_nothing:
20921     }
20922     { }
20923     \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
20924       \__kernel_msg_error:nnx { kernel } { missing-rparen }
20925       { \int_use:N \l__regex_group_level_int }
20926       \prg_replicate:nn
20927         { \l__regex_group_level_int }
20928       {
20929         \tl_build_put_right:Nn \l__regex_build_tl
20930         {
20931           \if_false: { \fi: }
20932           \if_false: { \fi: } { 1 } { 0 } \c_true_bool
20933         }
20934         \tl_build_end:N \l__regex_build_tl
20935         \exp_args:NNNo
20936         \group_end:
20937         \tl_build_put_right:Nn \l__regex_build_tl
20938           { \l__regex_build_tl }
20939       }
20940     \fi:
20941     \tl_build_put_right:Nn \l__regex_build_tl { \if_false: { \fi: } }
20942     \tl_build_end:N \l__regex_build_tl
20943     \exp_args:NNNx
20944     \group_end:

```

```

20945 \tl_set:Nn \l__regex_internal_regex { \l__regex_build_tl }
20946 }

```

(End definition for __regex_compile:w and __regex_compile_end:.)

__regex_compile:n The compilation is done between __regex_compile:w and __regex_compile_end:, starting in mode 0. Then __regex_escape_use:nnnn distinguishes special characters, escaped alphanumerics, and raw characters, interpreting \a, \x and other sequences. The 4 trailing \prg_do_nothing: are needed because some functions defined later look up to 4 tokens ahead. Before ending, make sure that any \c{...} is properly closed. No need to check that brackets are closed properly since __regex_compile_end: does that. However, catch the case of a trailing \cL construction.

```

20947 \cs_new_protected:Npn \__regex_compile:n #1
20948 {
20949   \__regex_compile:w
20950   \__regex_standard_escapechar:
20951   \int_set_eq:NN \l__regex_mode_int \c__regex_outer_mode_int
20952   \__regex_escape_use:nnnn
20953   {
20954     \__regex_char_if_special:NTF ##1
20955     \__regex_compile_special:N \__regex_compile_raw:N ##1
20956   }
20957   {
20958     \__regex_char_if_alphanumeric:NTF ##1
20959     \__regex_compile_escaped:N \__regex_compile_raw:N ##1
20960   }
20961   { \__regex_compile_raw:N ##1 }
20962   { #1 }
20963   \prg_do_nothing: \prg_do_nothing:
20964   \prg_do_nothing: \prg_do_nothing:
20965   \int_compare:nNnT \l__regex_mode_int = \c__regex_catcode_mode_int
20966   { \__kernel_msg_error:nn { kernel } { c-trailing } }
20967   \int_compare:nNnT \l__regex_mode_int < \c__regex_outer_mode_int
20968   {
20969     \__kernel_msg_error:nn { kernel } { c-missing-rbrace }
20970     \__regex_compile_end_cs:
20971     \prg_do_nothing: \prg_do_nothing:
20972     \prg_do_nothing: \prg_do_nothing:
20973   }
20974   \__regex_compile_end:
20975 }

```

(End definition for __regex_compile:n.)

__regex_compile_escaped:N If the special character or escaped alphanumeric has a particular meaning in regexes, the corresponding function is used. Otherwise, it is interpreted as a raw character. We distinguish special characters from escaped alphanumeric characters because they behave differently when appearing as an end-point of a range.

```

20976 \cs_new_protected:Npn \__regex_compile_special:N #1
20977 {
20978   \cs_if_exist_use:cF { __regex_compile_#1: }
20979   { \__regex_compile_raw:N #1 }
20980 }
20981 \cs_new_protected:Npn \__regex_compile_escaped:N #1

```



```

20982 {
20983   \cs_if_exist_use:cF { __regex_compile_/#1: }
20984   { \__regex_compile_raw:N #1 }
20985 }

```

(End definition for __regex_compile_escaped:N and __regex_compile_special:N.)

__regex_compile_one:n This is used after finding one “test”, such as \d, or a raw character. If that followed a catcode test (e.g., \cL), then restore the mode. If we are not in a class, then the test is “standalone”, and we need to add __regex_class:NnnnN and search for quantifiers. In any case, insert the test, possibly together with a catcode test if appropriate.

```

20986 \cs_new_protected:Npn \__regex_compile_one:n #1
20987 {
20988   \__regex_mode_quit_c:
20989   \__regex_if_in_class:TF { }
20990   {
20991     \tl_build_put_right:Nn \l__regex_build_tl
20992     { \__regex_class:NnnnN \c_true_bool { \if_false: } \fi: }
20993   }
20994   \tl_build_put_right:Nx \l__regex_build_tl
20995   {
20996     \if_int_compare:w \l__regex_catcodes_int <
20997     \c__regex_all_catcodes_int
20998     \__regex_item_catcode:nT { \int_use:N \l__regex_catcodes_int }
20999     { \exp_not:N \exp_not:n {#1} }
21000     \else:
21001     \exp_not:N \exp_not:n {#1}
21002     \fi:
21003   }
21004   \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
21005   \__regex_if_in_class:TF { } { \__regex_compile_quantifier:w }
21006 }

```

(End definition for __regex_compile_one:n.)

__regex_compile_abort_tokens:n This function places the collected tokens back in the input stream, each as a raw character.
__regex_compile_abort_tokens:x Spaces are not preserved.

```

21007 \cs_new_protected:Npn \__regex_compile_abort_tokens:n #1
21008 {
21009   \use:x
21010   {
21011     \exp_args:No \tl_map_function:nN { \tl_to_str:n {#1} }
21012     \__regex_compile_raw:N
21013   }
21014 }
21015 \cs_generate_variant:Nn \__regex_compile_abort_tokens:n { x }

```

(End definition for __regex_compile_abort_tokens:n.)

38.3.5 Quantifiers

__regex_compile_quantifier:w This looks ahead and finds any quantifier (special character equal to either of ?+*{).

```

21016 \cs_new_protected:Npn \__regex_compile_quantifier:w #1#2
21017 {

```

```

21018 \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
21019 {
21020   \cs_if_exist_use:cF { __regex_compile_quantifier_#2:w }
21021   { \__regex_compile_quantifier_none: #1 #2 }
21022 }
21023 { \__regex_compile_quantifier_none: #1 #2 }
21024 }

```

(End definition for __regex_compile_quantifier:w.)

__regex_compile_quantifier_none: Those functions are called whenever there is no quantifier, or a braced construction is invalid (equivalent to no quantifier, and whatever characters were grabbed are left raw).

```

21025 \cs_new_protected:Npn \__regex_compile_quantifier_none:
21026 {
21027   \tl_build_put_right:Nn \l__regex_build_tl
21028   { \if_false: { \fi: } { 1 } { 0 } \c_false_bool }
21029 }
21030 \cs_new_protected:Npn \__regex_compile_quantifier_abort:xNN #1#2#3
21031 {
21032   \__regex_compile_quantifier_none:
21033   \__kernel_msg_warning:nxxx { kernel } { invalid-quantifier } {#1} {#3}
21034   \__regex_compile_abort_tokens:x {#1}
21035   #2 #3
21036 }

```

(End definition for __regex_compile_quantifier_none: and __regex_compile_quantifier_abort:xNN.)

__regex_compile_quantifier_lazyness:nnNN Once the “main” quantifier (?, *, + or a braced construction) is found, we check whether it is lazy (followed by a question mark). We then add to the compiled regex a closing brace (ending __regex_class:NnnnN and friends), the start-point of the range, its end-point, and a boolean, true for lazy and false for greedy operators.

```

21037 \cs_new_protected:Npn \__regex_compile_quantifier_lazyness:nnNN #1#2#3#4
21038 {
21039   \__regex_two_if_eq:NNNTF #3 #4 \__regex_compile_special:N ?
21040   {
21041     \tl_build_put_right:Nn \l__regex_build_tl
21042     { \if_false: { \fi: } { #1 } { #2 } \c_true_bool }
21043   }
21044   {
21045     \tl_build_put_right:Nn \l__regex_build_tl
21046     { \if_false: { \fi: } { #1 } { #2 } \c_false_bool }
21047     #3 #4
21048   }
21049 }

```

(End definition for __regex_compile_quantifier_lazyness:nnNN.)

__regex_compile_quantifier?:w For each “basic” quantifier, ?, *, +, feed the correct arguments to __regex_compile_quantifier_lazyness:nnNN, -1 means that there is no upper bound on the number of repetitions.

```

21050 \cs_new_protected:cpn { __regex_compile_quantifier?:w }
21051 { \__regex_compile_quantifier_lazyness:nnNN { 0 } { 1 } }
21052 \cs_new_protected:cpn { __regex_compile_quantifier*:w }
21053 { \__regex_compile_quantifier_lazyness:nnNN { 0 } { -1 } }

```

```

21054 \cs_new_protected:cpn { __regex_compile_quantifier_+:w }
21055 { \__regex_compile_quantifier_lazyness:nnNN { 1 } { -1 } }

```

(End definition for `__regex_compile_quantifier_?:w`, `__regex_compile_quantifier_+:w`, and `__regex_compile_quantifier_+:w`.)

```

\__regex_compile_quantifier_{:w
\__regex_compile_quantifier_braced_auxi:w
\__regex_compile_quantifier_braced_auxii:w
\__regex_compile_quantifier_braced_auxiii:w

```

Three possible syntaxes: $\{\langle int \rangle\}$, $\{\langle int \rangle, \}$, or $\{\langle int \rangle, \langle int \rangle\}$. Any other syntax causes us to abort and put whatever we collected back in the input stream, as `raw` characters, including the opening brace. Grab a number into `\l__regex_internal_a_int`. If the number is followed by a right brace, the range is $[a, a]$. If followed by a comma, grab one more number, and call the `_ii` or `_iii` auxiliary. Those auxiliaries check for a closing brace, leading to the range $[a, \infty]$ or $[a, b]$, encoded as $\{a\}\{-1\}$ and $\{a\}\{b-a\}$.

```

21056 \cs_new_protected:cpn { __regex_compile_quantifier_ \c_left_brace_str :w }
21057 {
21058   \__regex_get_digits:NTFw \l__regex_internal_a_int
21059   { \__regex_compile_quantifier_braced_auxi:w }
21060   { \__regex_compile_quantifier_abort:xNN { \c_left_brace_str } }
21061 }
21062 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxi:w #1#2
21063 {
21064   \str_case_e:nnF { #1 #2 }
21065   {
21066     { \__regex_compile_special:N \c_right_brace_str }
21067     {
21068       \exp_args:No \__regex_compile_quantifier_lazyness:nnNN
21069       { \int_use:N \l__regex_internal_a_int } { 0 }
21070     }
21071     { \__regex_compile_special:N , }
21072     {
21073       \__regex_get_digits:NTFw \l__regex_internal_b_int
21074       { \__regex_compile_quantifier_braced_auxiii:w }
21075       { \__regex_compile_quantifier_braced_auxii:w }
21076     }
21077   }
21078   {
21079     \__regex_compile_quantifier_abort:xNN
21080     { \c_left_brace_str \int_use:N \l__regex_internal_a_int }
21081     #1 #2
21082   }
21083 }
21084 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxii:w #1#2
21085 {
21086   \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N \c_right_brace_str
21087   {
21088     \exp_args:No \__regex_compile_quantifier_lazyness:nnNN
21089     { \int_use:N \l__regex_internal_a_int } { -1 }
21090   }
21091   {
21092     \__regex_compile_quantifier_abort:xNN
21093     { \c_left_brace_str \int_use:N \l__regex_internal_a_int , }
21094     #1 #2
21095   }
21096 }
21097 \cs_new_protected:Npn \__regex_compile_quantifier_braced_auxiii:w #1#2

```

```

21098 {
21099   \_regex_two_if_eq:NNNTF #1 #2 \_regex_compile_special:N \c_right_brace_str
21100   {
21101     \if_int_compare:w \l__regex_internal_a_int >
21102     \l__regex_internal_b_int
21103     \_kernel_msg_error:nnxx { kernel } { backwards-quantifier }
21104     { \int_use:N \l__regex_internal_a_int }
21105     { \int_use:N \l__regex_internal_b_int }
21106     \int_zero:N \l__regex_internal_b_int
21107   \else:
21108     \int_sub:Nn \l__regex_internal_b_int \l__regex_internal_a_int
21109   \fi:
21110   \exp_args:Noo \_regex_compile_quantifier_lazyness:nnNN
21111   { \int_use:N \l__regex_internal_a_int }
21112   { \int_use:N \l__regex_internal_b_int }
21113 }
21114 {
21115   \_regex_compile_quantifier_abort:xNN
21116   {
21117     \c_left_brace_str
21118     \int_use:N \l__regex_internal_a_int ,
21119     \int_use:N \l__regex_internal_b_int
21120   }
21121   #1 #2
21122 }
21123 }

```

(End definition for _regex_compile_quantifier_{:w and others.)

38.3.6 Raw characters

_regex_compile_raw_error:N Within character classes, and following catcode tests, some escaped alphanumeric sequences such as \b do not have any meaning. They are replaced by a raw character, after spitting out an error.

```

21124 \cs_new_protected:Npn \_regex_compile_raw_error:N #1
21125 {
21126   \_kernel_msg_error:nnx { kernel } { bad-escape } {#1}
21127   \_regex_compile_raw:N #1
21128 }

```

(End definition for _regex_compile_raw_error:N.)

_regex_compile_raw:N If we are in a character class and the next character is an unescaped dash, this denotes a range. Otherwise, the current character #1 matches itself.

```

21129 \cs_new_protected:Npn \_regex_compile_raw:N #1#2#3
21130 {
21131   \_regex_if_in_class:TF
21132   {
21133     \_regex_two_if_eq:NNNTF #2 #3 \_regex_compile_special:N -
21134     { \_regex_compile_range:Nw #1 }
21135     {
21136       \_regex_compile_one:n
21137       { \_regex_item_equal:n { \int_value:w '#1 } }
21138       #2 #3

```

```

21139     }
21140   }
21141   {
21142     \_regex_compile_one:n
21143     { \_regex_item_equal:n { \int_value:w '#1 } }
21144     #2 #3
21145   }
21146 }

```

(End definition for _regex_compile_raw:N.)

_regex_compile_range:Nw
_regex_if_end_range:NNTF

We have just read a raw character followed by a dash; this should be followed by an end-point for the range. Valid end-points are: any raw character; any special character, except a right bracket. In particular, escaped characters are forbidden.

```

21147 \prg_new_protected_conditional:Npnn \_regex_if_end_range:NN #1#2 { TF }
21148 {
21149   \if_meaning:w \_regex_compile_raw:N #1
21150   \prg_return_true:
21151   \else:
21152     \if_meaning:w \_regex_compile_special:N #1
21153     \if_charcode:w ] #2
21154     \prg_return_false:
21155     \else:
21156       \prg_return_true:
21157     \fi:
21158     \else:
21159       \prg_return_false:
21160     \fi:
21161   \fi:
21162 }
21163 \cs_new_protected:Npn \_regex_compile_range:Nw #1#2#3
21164 {
21165   \_regex_if_end_range:NNTF #2 #3
21166   {
21167     \if_int_compare:w '#1 > '#3 \exp_stop_f:
21168     \_kernel_msg_error:nxxx { kernel } { range-backwards } {#1} {#3}
21169     \else:
21170       \tl_build_put_right:Nx \l__regex_build_tl
21171       {
21172         \if_int_compare:w '#1 = '#3 \exp_stop_f:
21173         \_regex_item_equal:n
21174         \else:
21175           \_regex_item_range:nn { \int_value:w '#1 }
21176         \fi:
21177         { \int_value:w '#3 }
21178       }
21179     \fi:
21180   }
21181   {
21182     \_kernel_msg_warning:nxxx { kernel } { range-missing-end }
21183     {#1} { \c_backslash_str #3 }
21184     \tl_build_put_right:Nx \l__regex_build_tl
21185     {
21186       \_regex_item_equal:n { \int_value:w '#1 \exp_stop_f: }

```

```

21187         \_regex_item_equal:n { \int_value:w ‘- \exp_stop_f: }
21188     }
21189     #2#3
21190 }
21191 }

```

(End definition for _regex_compile_range:Nw and _regex_if_end_range:NNTF.)

38.3.7 Character properties

_regex_compile_.: In a class, the dot has no special meaning. Outside, insert _regex_prop_., which matches any character or control sequence, and refuses -2 (end-marker).

```

21192 \cs_new_protected:cpx { \_regex_compile_.: }
21193 {
21194     \exp_not:N \_regex_if_in_class:TF
21195     { \_regex_compile_raw:N . }
21196     { \_regex_compile_one:n \exp_not:c { \_regex_prop_.: } }
21197 }
21198 \cs_new_protected:cpn { \_regex_prop_.: }
21199 {
21200     \if_int_compare:w \l__regex_curr_char_int > - 2 \exp_stop_f:
21201     \exp_after:wN \_regex_break_true:w
21202     \fi:
21203 }

```

(End definition for _regex_compile_.: and _regex_prop_.:)

_regex_compile_/d: The constants _regex_prop_d:, etc. hold a list of tests which match the corresponding character class, and jump to the _regex_break_point:TF marker. As for a normal character, we check for quantifiers.

```

\_regex_compile_/d: 21204 \cs_set_protected:Npn \_regex_tmp:w #1#2
\_regex_compile_/D: 21205 {
\_regex_compile_/h: 21206     \cs_new_protected:cpx { \_regex_compile_/#1: }
\_regex_compile_/S: 21207     { \_regex_compile_one:n \exp_not:c { \_regex_prop_#1: } }
\_regex_compile_/v: 21208     \cs_new_protected:cpx { \_regex_compile_/#2: }
\_regex_compile_/V: 21209     {
\_regex_compile_/w: 21210         \_regex_compile_one:n
\_regex_compile_/W: 21211         { \_regex_item_reverse:n \exp_not:c { \_regex_prop_#1: } }
\_regex_compile_/N: 21212     }
21213 }
21214 \_regex_tmp:w d D
21215 \_regex_tmp:w h H
21216 \_regex_tmp:w s S
21217 \_regex_tmp:w v V
21218 \_regex_tmp:w w W
21219 \cs_new_protected:cpn { \_regex_compile_/N: }
21220 { \_regex_compile_one:n \_regex_prop_N: }

```

(End definition for _regex_compile_/d: and others.)

38.3.8 Anchoring and simple assertions

`__regex_compile_anchor:NF` In modes where assertions are allowed, anchor to the start of the query, the start of the match, or the end of the query, depending on the integer #1. In other modes, #2 treats the character as raw, with an error for escaped letters (\$ is valid in a class, but \A is definitely a mistake on the user's part).

```

__regex_compile_~:
__regex_compile_/A:
__regex_compile_/G:
__regex_compile_$: 21221 \cs_new_protected:Npn __regex_compile_anchor:NF #1#2
__regex_compile_/Z: 21222 {
__regex_compile_/z: 21223   __regex_if_in_class_or_catcode:TF {#2}
21224   {
21225     \tl_build_put_right:Nn \l__regex_build_tl
21226     { __regex_assertion:Nn \c_true_bool { __regex_anchor:N #1 } }
21227   }
21228 }
21229 \cs_set_protected:Npn __regex_tmp:w #1#2
21230 {
21231   \cs_new_protected:cpn { __regex_compile_/#1: }
21232   { __regex_compile_anchor:NF #2 { __regex_compile_raw_error:N #1 } }
21233 }
21234 __regex_tmp:w A \l__regex_min_pos_int
21235 __regex_tmp:w G \l__regex_start_pos_int
21236 __regex_tmp:w Z \l__regex_max_pos_int
21237 __regex_tmp:w z \l__regex_max_pos_int
21238 \cs_set_protected:Npn __regex_tmp:w #1#2
21239 {
21240   \cs_new_protected:cpn { __regex_compile_#1: }
21241   { __regex_compile_anchor:NF #2 { __regex_compile_raw:N #1 } }
21242 }
21243 \exp_args:Nx __regex_tmp:w { \iow_char:N ^ } \l__regex_min_pos_int
21244 \exp_args:Nx __regex_tmp:w { \iow_char:N $ } \l__regex_max_pos_int

```

(End definition for `__regex_compile_anchor:NF` and others.)

`__regex_compile_/b:` Contrarily to `~` and `$`, which could be implemented without really knowing what precedes in the token list, this requires more information, namely, the knowledge of the last character code.

`__regex_compile_/B:`

```

21245 \cs_new_protected:cpn { __regex_compile_/b: }
21246 {
21247   __regex_if_in_class_or_catcode:TF
21248   { __regex_compile_raw_error:N b }
21249   {
21250     \tl_build_put_right:Nn \l__regex_build_tl
21251     { __regex_assertion:Nn \c_true_bool { __regex_b_test: } }
21252   }
21253 }
21254 \cs_new_protected:cpn { __regex_compile_/B: }
21255 {
21256   __regex_if_in_class_or_catcode:TF
21257   { __regex_compile_raw_error:N B }
21258   {
21259     \tl_build_put_right:Nn \l__regex_build_tl
21260     { __regex_assertion:Nn \c_false_bool { __regex_b_test: } }
21261   }
21262 }

```

(End definition for `_regex_compile/b:` and `_regex_compile/B:.`)

38.3.9 Character classes

`_regex_compile_:` Outside a class, right brackets have no meaning. In a class, change the mode ($m \rightarrow (m - 15)/13$, truncated) to reflect the fact that we are leaving the class. Look for quantifiers, unless we are still in a class after leaving one (the case of `[... \cL[...] ...]`). quantifiers.

```

21263 \cs_new_protected:cpn { \_regex_compile_ }
21264 {
21265   \_regex_if_in_class:TF
21266   {
21267     \if_int_compare:w \l__regex_mode_int >
21268       \c__regex_catcode_in_class_mode_int
21269       \tl_build_put_right:Nn \l__regex_build_tl { \if_false: { \fi: } }
21270     \fi:
21271     \tex_advance:D \l__regex_mode_int - 15 \exp_stop_f:
21272     \tex_divide:D \l__regex_mode_int 13 \exp_stop_f:
21273     \if_int_odd:w \l__regex_mode_int \else:
21274       \exp_after:wN \_regex_compile_quantifier:w
21275     \fi:
21276   }
21277   { \_regex_compile_raw:N ] }
21278 }

```

(End definition for `_regex_compile_:`)

`_regex_compile_[:` In a class, left brackets might introduce a POSIX character class, or mean nothing. Immediately following `\c<category>`, we must insert the appropriate catcode test, then parse the class; we pre-expand the catcode as an optimization. Otherwise (modes 0, -2 and -6) just parse the class. The mode is updated later.

```

21279 \cs_new_protected:cpn { \_regex_compile_[: }
21280 {
21281   \_regex_if_in_class:TF
21282   { \_regex_compile_class_posix_test:w }
21283   {
21284     \_regex_if_within_catcode:TF
21285     {
21286       \exp_after:wN \_regex_compile_class_catcode:w
21287       \int_use:N \l__regex_catcodes_int ;
21288     }
21289     { \_regex_compile_class_normal:w }
21290   }
21291 }

```

(End definition for `_regex_compile_[:`)

`_regex_compile_class_normal:w` In the “normal” case, we insert `_regex_class:NnnnN` *<boolean>* in the compiled code. The *<boolean>* is true for positive classes, and false for negative classes, characterized by a leading `^`. The auxiliary `_regex_compile_class:TFNN` also checks for a leading `]` which has a special meaning.

```

21292 \cs_new_protected:Npn \_regex_compile_class_normal:w
21293 {
21294   \_regex_compile_class:TFNN

```



```

21295     { \_regex\_class:NnnnN \c\_true\_bool }
21296     { \_regex\_class:NnnnN \c\_false\_bool }
21297   }

```

(End definition for _regex_compile_class_normal:w.)

_regex_compile_class_catcode:w This function is called for a left bracket in modes 2 or 6 (catcode test, and catcode test within a class). In mode 2 the whole construction needs to be put in a class (like single character). Then determine if the class is positive or negative, inserting _regex_item_catcode:nT or the reverse variant as appropriate, each with the current catcodes bitmap #1 as an argument, and reset the catcodes.

```

21298 \cs\_new\_protected:Npn \_regex\_compile\_class\_catcode:w #1;
21299 {
21300   \if\_int\_compare:w \l\_regex\_mode\_int = \c\_regex\_catcode\_mode\_int
21301     \tl\_build\_put\_right:Nn \l\_regex\_build\_tl
21302       { \_regex\_class:NnnnN \c\_true\_bool { \if\_false: } \fi: }
21303   \fi:
21304   \int\_set\_eq:NN \l\_regex\_catcodes\_int \l\_regex\_default\_catcodes\_int
21305   \_regex\_compile\_class:TFNN
21306     { \_regex\_item\_catcode:nT {#1} }
21307     { \_regex\_item\_catcode\_reverse:nT {#1} }
21308 }

```

(End definition for _regex_compile_class_catcode:w.)

_regex_compile_class:TFNN If the first character is ^, then the class is negative (use #2), otherwise it is positive (use #1). If the next character is a right bracket, then it should be changed to a raw one.

```

21309 \cs\_new\_protected:Npn \_regex\_compile\_class:TFNN #1#2#3#4
21310 {
21311   \l\_regex\_mode\_int = \int\_value:w \l\_regex\_mode\_int 3 \exp\_stop\_f:
21312   \_regex\_two\_if\_eq:NNNNTF #3 #4 \_regex\_compile\_special:N ^
21313   {
21314     \tl\_build\_put\_right:Nn \l\_regex\_build\_tl { #2 { \if\_false: } \fi: }
21315     \_regex\_compile\_class:NN
21316   }
21317   {
21318     \tl\_build\_put\_right:Nn \l\_regex\_build\_tl { #1 { \if\_false: } \fi: }
21319     \_regex\_compile\_class:NN #3 #4
21320   }
21321 }
21322 \cs\_new\_protected:Npn \_regex\_compile\_class:NN #1#2
21323 {
21324   \token\_if\_eq\_charcode:NNTF #2 ]
21325   { \_regex\_compile\_raw:N #2 }
21326   { #1 #2 }
21327 }

```

(End definition for _regex_compile_class:TFNN and _regex_compile_class:NN.)

_regex_compile_class_posix_test:w Here we check for a syntax such as [:alpha:]. We also detect [= and [. which have a meaning in POSIX regular expressions, but are not implemented in l3regex. In case we see [:, grab raw characters until hopefully reaching :]. If that's missing, or the POSIX class is unknown, abort. If all is right, add the test to the current class, with an extra _regex_item_reverse:n for negative classes.

```

21328 \cs_new_protected:Npn \__regex_compile_class_posix_test:w #1#2
21329 {
21330   \token_if_eq_meaning:NNT \__regex_compile_special:N #1
21331   {
21332     \str_case:nn { #2 }
21333     {
21334       : { \__regex_compile_class_posix:NNNNw }
21335       = {
21336         \__kernel_msg_warning:nxx { kernel }
21337         { posix-unsupported } { = }
21338       }
21339       . {
21340         \__kernel_msg_warning:nxx { kernel }
21341         { posix-unsupported } { . }
21342       }
21343     }
21344   }
21345   \__regex_compile_raw:N [ #1 #2
21346 }
21347 \cs_new_protected:Npn \__regex_compile_class_posix:NNNNw #1#2#3#4#5#6
21348 {
21349   \__regex_two_if_eq:NNNNTF #5 #6 \__regex_compile_special:N ^
21350   {
21351     \bool_set_false:N \l__regex_internal_bool
21352     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
21353     \__regex_compile_class_posix_loop:w
21354   }
21355   {
21356     \bool_set_true:N \l__regex_internal_bool
21357     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
21358     \__regex_compile_class_posix_loop:w #5 #6
21359   }
21360 }
21361 \cs_new:Npn \__regex_compile_class_posix_loop:w #1#2
21362 {
21363   \token_if_eq_meaning:NNTF \__regex_compile_raw:N #1
21364   { #2 \__regex_compile_class_posix_loop:w }
21365   { \if_false: { \fi: } \__regex_compile_class_posix_end:w #1 #2 }
21366 }
21367 \cs_new_protected:Npn \__regex_compile_class_posix_end:w #1#2#3#4
21368 {
21369   \__regex_two_if_eq:NNNNTF #1 #2 \__regex_compile_special:N :
21370   { \__regex_two_if_eq:NNNNTF #3 #4 \__regex_compile_special:N ] }
21371   { \use_ii:nn }
21372   {
21373     \cs_if_exist:cTF { __regex_posix_ \l__regex_internal_a_tl : }
21374     {
21375       \__regex_compile_one:n
21376       {
21377         \bool_if:NF \l__regex_internal_bool \__regex_item_reverse:n
21378         \exp_not:c { __regex_posix_ \l__regex_internal_a_tl : }
21379       }
21380     }
21381   }

```

```

21382         \_kernel_msg_warning:nxx { kernel } { posix-unknown }
21383         { \l__regex_internal_a_tl }
21384         \_regex_compile_abort_tokens:x
21385         {
21386             [: \bool_if:NF \l__regex_internal_bool { ^ }
21387             \l__regex_internal_a_tl :]
21388         }
21389     }
21390 }
21391 {
21392     \_kernel_msg_error:nxxx { kernel } { posix-missing-close }
21393     { [: \l__regex_internal_a_tl ] { #2 #4 }
21394     \_regex_compile_abort_tokens:x { [: \l__regex_internal_a_tl ]
21395     #1 #2 #3 #4
21396     }
21397 }

```

(End definition for `_regex_compile_class_posix_test:w` and others.)

38.3.10 Groups and alternations

`_regex_compile_group_begin:N` The contents of a regex group are turned into compiled code in `\l__regex_build_tl`, which ends up with items of the form `_regex_branch:n {⟨concatenation⟩}`. This construction is done using `\tl_build_...` functions within a `TeX` group, which automatically makes sure that options (case-sensitivity and default catcode) are reset at the end of the group. The argument `#1` is `_regex_group:nnnN` or a variant thereof. A small subtlety to support `\cL(abc)` as a shorthand for `(\cLa\cLb\cLc)`: exit any pending catcode test, save the category code at the start of the group as the default catcode for that group, and make sure that the catcode is restored to the default outside the group.

```

21398 \cs_new_protected:Npn \_regex_compile_group_begin:N #1
21399 {
21400     \tl_build_put_right:Nn \l__regex_build_tl { #1 { \if_false: } \fi: }
21401     \_regex_mode_quit_c:
21402     \group_begin:
21403         \tl_build_begin:N \l__regex_build_tl
21404         \int_set_eq:NN \l__regex_default_catcodes_int \l__regex_catcodes_int
21405         \int_incr:N \l__regex_group_level_int
21406         \tl_build_put_right:Nn \l__regex_build_tl
21407         { \_regex_branch:n { \if_false: } \fi: }
21408     }
21409 \cs_new_protected:Npn \_regex_compile_group_end:
21410 {
21411     \if_int_compare:w \l__regex_group_level_int > 0 \exp_stop_f:
21412         \tl_build_put_right:Nn \l__regex_build_tl { \if_false: { \fi: } }
21413         \tl_build_end:N \l__regex_build_tl
21414         \exp_args:NNNx
21415         \group_end:
21416         \tl_build_put_right:Nn \l__regex_build_tl { \l__regex_build_tl }
21417         \int_set_eq:NN \l__regex_catcodes_int \l__regex_default_catcodes_int
21418         \exp_after:wN \_regex_compile_quantifier:w
21419     \else:
21420         \_kernel_msg_warning:nn { kernel } { extra-rparen }

```

```

21421     \exp_after:wN \__regex_compile_raw:N \exp_after:wN )
21422   \fi:
21423 }

```

(End definition for __regex_compile_group_begin:N and __regex_compile_group_end:.)

__regex_compile(: In a class, parentheses are not special. In a catcode test inside a class, a left parenthesis gives an error, to catch [a\cL(bcd)e]. Otherwise check for a ?, denoting special groups, and run the code for the corresponding special group.

```

21424 \cs_new_protected:cpn { __regex_compile(: }
21425 {
21426   \__regex_if_in_class:TF { \__regex_compile_raw:N ( }
21427   {
21428     \if_int_compare:w \l__regex_mode_int =
21429       \c__regex_catcode_in_class_mode_int
21430       \__kernel_msg_error:nn { kernel } { c-lparen-in-class }
21431       \exp_after:wN \__regex_compile_raw:N \exp_after:wN (
21432     \else:
21433       \exp_after:wN \__regex_compile_lparen:w
21434     \fi:
21435   }
21436 }
21437 \cs_new_protected:Npn \__regex_compile_lparen:w #1#2#3#4
21438 {
21439   \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N ?
21440   {
21441     \cs_if_exist_use:cF
21442       { __regex_compile_special_group\_token_to_str:N #4 :w }
21443       {
21444         \__kernel_msg_warning:nnx { kernel } { special-group-unknown }
21445         { (? #4 }
21446         \__regex_compile_group_begin:N \__regex_group:nnnN
21447         \__regex_compile_raw:N ? #3 #4
21448       }
21449   }
21450   {
21451     \__regex_compile_group_begin:N \__regex_group:nnnN
21452     #1 #2 #3 #4
21453   }
21454 }

```

(End definition for __regex_compile(:.)

__regex_compile_|: In a class, the pipe is not special. Otherwise, end the current branch and open another one.

```

21455 \cs_new_protected:cpn { __regex_compile_|: }
21456 {
21457   \__regex_if_in_class:TF { \__regex_compile_raw:N | }
21458   {
21459     \tl_build_put_right:Nn \l__regex_build_tl
21460       { \if_false: { \fi: } \__regex_branch:n { \if_false: } \fi: }
21461   }
21462 }

```

(End definition for __regex_compile_|:.)

`__regex_compile_)`: Within a class, parentheses are not special. Outside, close a group.

```
21463 \cs_new_protected:cpn { __regex_compile_): }
21464 {
21465     \__regex_if_in_class:TF { \__regex_compile_raw:N ) }
21466     { \__regex_compile_group_end: }
21467 }
```

(End definition for `__regex_compile_)`.)

`__regex_compile_special_group::w` Non-capturing, and resetting groups are easy to take care of during compilation; for those
`__regex_compile_special_group|:w` groups, the harder parts come when building.

```
21468 \cs_new_protected:cpn { __regex_compile_special_group::w }
21469 { \__regex_compile_group_begin:N \__regex_group_no_capture:nnnN }
21470 \cs_new_protected:cpn { __regex_compile_special_group|:w }
21471 { \__regex_compile_group_begin:N \__regex_group_resetting:nnnN }
```

(End definition for `__regex_compile_special_group::w` and `__regex_compile_special_group|:w`.)

`__regex_compile_special_group_i:w` The match can be made case-insensitive by setting the option with `(?i)`; the original
`__regex_compile_special_group-:w` behaviour is restored by `(?-i)`. This is the only supported option.

```
21472 \cs_new_protected:Npn \__regex_compile_special_group_i:w #1#2
21473 {
21474     \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N )
21475     {
21476         \cs_set:Npn \__regex_item_equal:n
21477         { \__regex_item_caseless_equal:n }
21478         \cs_set:Npn \__regex_item_range:nn
21479         { \__regex_item_caseless_range:nn }
21480     }
21481     {
21482         \__kernel_msg_warning:nnx { kernel } { unknown-option } { (?i #2 }
21483         \__regex_compile_raw:N (
21484         \__regex_compile_raw:N ?
21485         \__regex_compile_raw:N i
21486         #1 #2
21487     }
21488 }
21489 \cs_new_protected:cpn { __regex_compile_special_group-:w } #1#2#3#4
21490 {
21491     \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_raw:N i
21492     { \__regex_two_if_eq:NNNTF #3 #4 \__regex_compile_special:N ) }
21493     { \use_ii:nn }
21494     {
21495         \cs_set:Npn \__regex_item_equal:n
21496         { \__regex_item_caseful_equal:n }
21497         \cs_set:Npn \__regex_item_range:nn
21498         { \__regex_item_caseful_range:nn }
21499     }
21500     {
21501         \__kernel_msg_warning:nnx { kernel } { unknown-option } { (?-#2#4 }
21502         \__regex_compile_raw:N (
21503         \__regex_compile_raw:N ?
21504         \__regex_compile_raw:N -
21505         #1 #2 #3 #4
```

```

21506     }
21507 }

```

(End definition for `__regex_compile_special_group_i:w` and `__regex_compile_special_group_~:w`.)

38.3.11 Catcodes and csnames

`__regex_compile/c:` The `\c` escape sequence can be followed by a capital letter representing a character category, by a left bracket which starts a list of categories, or by a brace group holding a regular expression for a control sequence name. Otherwise, raise an error.

```

21508 \cs_new_protected:cpn { __regex_compile/c: }
21509 { \__regex_chk_c_allowed:T { \__regex_compile_c_test:NN } }
21510 \cs_new_protected:Npn \__regex_compile_c_test:NN #1#2
21511 {
21512   \token_if_eq_meaning:NNTF #1 \__regex_compile_raw:N
21513   {
21514     \int_if_exist:cTF { c__regex_catcode_#2_int }
21515     {
21516       \int_set_eq:Nc \l__regex_catcodes_int
21517       { c__regex_catcode_#2_int }
21518       \l__regex_mode_int
21519       = \if_case:w \l__regex_mode_int
21520       \c__regex_catcode_mode_int
21521       \else:
21522       \c__regex_catcode_in_class_mode_int
21523       \fi:
21524       \token_if_eq_charcode:NNT C #2 { \__regex_compile_c_C:NN }
21525     }
21526   }
21527   { \cs_if_exist_use:cF { __regex_compile_c_#2:w } }
21528   {
21529     \__kernel_msg_error:nnx { kernel } { c-missing-category } {#2}
21530     #1 #2
21531   }
21532 }

```

(End definition for `__regex_compile/c:` and `__regex_compile_c_test:NN`.)

`__regex_compile_c_C:NN` If `\cC` is not followed by `.` or `(...)` then complain because that construction cannot match anything, except in cases like `\cC[\c{...}]`, where it has no effect.

```

21533 \cs_new_protected:Npn \__regex_compile_c_C:NN #1#2
21534 {
21535   \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
21536   {
21537     \token_if_eq_charcode:NNTF #2 .
21538     { \use_none:n }
21539     { \token_if_eq_charcode:NNTF #2 ( } % )
21540   }
21541   { \use:n }
21542   { \__kernel_msg_error:nnn { kernel } { c-C-invalid } {#2} }
21543   #1 #2
21544 }

```

(End definition for `__regex_compile_c_C:NN`.)

```

\__regex_compile_c[:w
\__regex_compile_c_lbrack_loop:NN
\__regex_compile_c_lbrack_add:N
\__regex_compile_c_lbrack_end:

```

When encountering \c[, the task is to collect uppercase letters representing character categories. First check for ^ which negates the list of category codes.

```

21545 \cs_new_protected:cpn { \__regex_compile_c[:w } #1#2
21546 {
21547   \l__regex_mode_int
21548   = \if_case:w \l__regex_mode_int
21549     \c__regex_catcode_mode_int
21550     \else:
21551       \c__regex_catcode_in_class_mode_int
21552     \fi:
21553   \int_zero:N \l__regex_catcodes_int
21554   \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N ^
21555   {
21556     \bool_set_false:N \l__regex_catcodes_bool
21557     \__regex_compile_c_lbrack_loop:NN
21558   }
21559   {
21560     \bool_set_true:N \l__regex_catcodes_bool
21561     \__regex_compile_c_lbrack_loop:NN
21562     #1 #2
21563   }
21564 }
21565 \cs_new_protected:Npn \__regex_compile_c_lbrack_loop:NN #1#2
21566 {
21567   \token_if_eq_meaning:NNTF #1 \__regex_compile_raw:N
21568   {
21569     \int_if_exist:cTF { c__regex_catcode_#2_int }
21570     {
21571       \exp_args:Nc \__regex_compile_c_lbrack_add:N
21572       { c__regex_catcode_#2_int }
21573       \__regex_compile_c_lbrack_loop:NN
21574     }
21575   }
21576   {
21577     \token_if_eq_charcode:NNTF #2 ]
21578     { \__regex_compile_c_lbrack_end: }
21579   }
21580   {
21581     \__kernel_msg_error:nmx { kernel } { c-missing-rbrack } {#2}
21582     \__regex_compile_c_lbrack_end:
21583     #1 #2
21584   }
21585 }
21586 \cs_new_protected:Npn \__regex_compile_c_lbrack_add:N #1
21587 {
21588   \if_int_odd:w \int_eval:n { \l__regex_catcodes_int / #1 } \exp_stop_f:
21589   \else:
21590     \int_add:Nn \l__regex_catcodes_int {#1}
21591   \fi:
21592 }
21593 \cs_new_protected:Npn \__regex_compile_c_lbrack_end:
21594 {
21595   \if_meaning:w \c_false_bool \l__regex_catcodes_bool
21596   \int_set:Nn \l__regex_catcodes_int

```

```

21597         { \c__regex_all_catcodes_int - \l__regex_catcodes_int }
21598     \fi:
21599 }

```

(End definition for __regex_compile_c[:w and others.]

__regex_compile_c_{: The case of a left brace is easy, based on what we have done so far: in a group, compile the regular expression, after changing the mode to forbid nesting \c. Additionally, disable submatch tracking since groups don't escape the scope of \c{...}.

```

21600 \cs_new_protected:cpn { __regex_compile_c_ \c_left_brace_str :w }
21601 {
21602     \__regex_compile:w
21603     \__regex_disable_submatches:
21604     \l__regex_mode_int
21605     = \if_case:w \l__regex_mode_int
21606       \c__regex_cs_mode_int
21607     \else:
21608       \c__regex_cs_in_class_mode_int
21609     \fi:
21610 }

```

(End definition for __regex_compile_c{:.)

__regex_compile_{: Non-escaped right braces are only special if they appear when compiling the regular expression for a csname, but not within a class: \c{[{}]} matches the control sequences \{ and \}. So, end compiling the inner regex (this closes any dangling class or group). __regex_compile_cs_aux:Nn Then insert the corresponding test in the outer regex. As an optimization, if the control sequence test simply consists of several explicit possibilities (branches) then use __regex_item_exact_cs:n with an argument consisting of all possibilities separated by \scan_stop:.

```

21611 \flag_new:n { __regex_cs }
21612 \cs_new_protected:cpn { __regex_compile_ \c_right_brace_str : }
21613 {
21614     \__regex_if_in_cs:TF
21615     { \__regex_compile_end_cs: }
21616     { \exp_after:wN \__regex_compile_raw:N \c_right_brace_str }
21617 }
21618 \cs_new_protected:Npn \__regex_compile_end_cs:
21619 {
21620     \__regex_compile_end:
21621     \flag_clear:n { __regex_cs }
21622     \tl_set:Nx \l__regex_internal_a_tl
21623     {
21624         \exp_after:wN \__regex_compile_cs_aux:Nn \l__regex_internal_regex
21625         \q_nil \q_nil \q_recursion_stop
21626     }
21627     \exp_args:Nx \__regex_compile_one:n
21628     {
21629         \flag_if_raised:nTF { __regex_cs }
21630         { \__regex_item_cs:n { \exp_not:o \l__regex_internal_regex } }
21631         {
21632             \__regex_item_exact_cs:n
21633             { \tl_tail:N \l__regex_internal_a_tl }
21634         }
21635     }
21636 }

```



```

21635     }
21636   }
21637   \cs_new:Npn \__regex_compile_cs_aux:Nn #1#2
21638   {
21639     \cs_if_eq:NNTF #1 \__regex_branch:n
21640     {
21641       \scan_stop:
21642       \__regex_compile_cs_aux:NNnnnN #2
21643       \q_nil \q_nil \q_nil \q_nil \q_nil \q_nil \q_recursion_stop
21644       \__regex_compile_cs_aux:Nn
21645     }
21646     {
21647       \quark_if_nil:NF #1 { \flag_raise_if_clear:n { __regex_cs } }
21648       \use_none_delimit_by_q_recursion_stop:w
21649     }
21650   }
21651   \cs_new:Npn \__regex_compile_cs_aux:NNnnnN #1#2#3#4#5#6
21652   {
21653     \bool_lazy_all:nTF
21654     {
21655       { \cs_if_eq_p:NN #1 \__regex_class:NnnnN }
21656       {#2}
21657       { \tl_if_head_eq_meaning_p:nN {#3} \__regex_item_caseful_equal:n }
21658       { \int_compare_p:nNn { \tl_count:n {#3} } = { 2 } }
21659       { \int_compare_p:nNn {#5} = { 0 } }
21660     }
21661     {
21662       \prg_replicate:nn {#4}
21663       { \char_generate:nn { \use_ii:nn #3 } {12} }
21664       \__regex_compile_cs_aux:NNnnnN
21665     }
21666     {
21667       \quark_if_nil:NF #1
21668       {
21669         \flag_raise_if_clear:n { __regex_cs }
21670         \use_i_delimit_by_q_recursion_stop:nw
21671       }
21672       \use_none_delimit_by_q_recursion_stop:w
21673     }
21674   }

```

(End definition for __regex_compile_}: and others.)

38.3.12 Raw token lists with \u

__regex_compile_/u: The \u escape is invalid in classes and directly following a catcode test. Otherwise, it must be followed by a left brace. We then collect the characters for the argument of \u within an x-expanding assignment. In principle we could just wait to encounter a right brace, but this is unsafe: if the right brace was missing, then we would reach the end-markers of the regex, and continue, leading to obscure fatal errors. Instead, we only allow raw and special characters, and stop when encountering a special right brace, any escaped character, or the end-marker.

```

21675   \cs_new_protected:cpn { __regex_compile_/u: } #1#2
21676   {

```

```

21677 \__regex_if_in_class_or_catcode:TF
21678 { \__regex_compile_raw_error:N u #1 #2 }
21679 {
21680   \__regex_two_if_eq:NNNTF #1 #2 \__regex_compile_special:N \c_left_brace_str
21681   {
21682     \tl_set:Nx \l__regex_internal_a_tl { \if_false: } \fi:
21683     \__regex_compile_u_loop:NN
21684   }
21685   {
21686     \__kernel_msg_error:nn { kernel } { u-missing-lbrace }
21687     \__regex_compile_raw:N u #1 #2
21688   }
21689 }
21690 }
21691 \cs_new:Npn \__regex_compile_u_loop:NN #1#2
21692 {
21693   \token_if_eq_meaning:NNTF #1 \__regex_compile_raw:N
21694   { #2 \__regex_compile_u_loop:NN }
21695   {
21696     \token_if_eq_meaning:NNTF #1 \__regex_compile_special:N
21697     {
21698       \exp_after:wN \token_if_eq_charcode:NNTF \c_right_brace_str #2
21699       { \if_false: { \fi: } \__regex_compile_u_end: }
21700       { #2 \__regex_compile_u_loop:NN }
21701     }
21702     {
21703       \if_false: { \fi: }
21704       \__kernel_msg_error:nnx { kernel } { u-missing-rbrace } {#2}
21705       \__regex_compile_u_end:
21706       #1 #2
21707     }
21708   }
21709 }

```

(End definition for __regex_compile_/u: and __regex_compile_u_loop:NN.)

__regex_compile_u_end: Once we have extracted the variable's name, we store the contents of that variable in \l__regex_internal_a_tl. The behaviour of \u then depends on whether we are within a \c{...} escape (in this case, the variable is turned to a string), or not.

```

21710 \cs_new_protected:Npn \__regex_compile_u_end:
21711 {
21712   \tl_set:Nv \l__regex_internal_a_tl { \l__regex_internal_a_tl }
21713   \if_int_compare:w \l__regex_mode_int = \c__regex_outer_mode_int
21714   \__regex_compile_u_not_cs:
21715   \else:
21716   \__regex_compile_u_in_cs:
21717   \fi:
21718 }

```

(End definition for __regex_compile_u_end:.)

__regex_compile_u_in_cs: When \u appears within a control sequence, we convert the variable to a string with escaped spaces. Then for each character insert a class matching exactly that character, once.

```

21719 \cs_new_protected:Npn \__regex_compile_u_in_cs:
21720 {
21721   \tl_gset:Nx \g__regex_internal_tl
21722   {
21723     \exp_args:No \__kernel_str_to_other_fast:n
21724     { \l__regex_internal_a_tl }
21725   }
21726   \tl_build_put_right:Nx \l__regex_build_tl
21727   {
21728     \tl_map_function:NN \g__regex_internal_tl
21729     \__regex_compile_u_in_cs_aux:n
21730   }
21731 }
21732 \cs_new:Npn \__regex_compile_u_in_cs_aux:n #1
21733 {
21734   \__regex_class:NnnN \c_true_bool
21735   { \__regex_item_caseful_equal:n { \int_value:w '#1 } }
21736   { 1 } { 0 } \c_false_bool
21737 }

```

(End definition for __regex_compile_u_in_cs:.)

__regex_compile_u_not_cs: In mode 0, the \u escape adds one state to the NFA for each token in \l__regex_internal_a_tl. If a given *<token>* is a control sequence, then insert a string comparison test, otherwise, __regex_item_exact:nn which compares catcode and character code.

```

21738 \cs_new_protected:Npn \__regex_compile_u_not_cs:
21739 {
21740   \tl_analysis_map_inline:Nn \l__regex_internal_a_tl
21741   {
21742     \tl_build_put_right:Nx \l__regex_build_tl
21743     {
21744       \__regex_class:NnnN \c_true_bool
21745       {
21746         \if_int_compare:w "##3 = 0 \exp_stop_f:
21747         \__regex_item_exact_cs:n
21748         { \exp_after:wN \cs_to_str:N ##1 }
21749         \else:
21750         \__regex_item_exact:nn { \int_value:w "##3 } { ##2 }
21751         \fi:
21752       }
21753       { 1 } { 0 } \c_false_bool
21754     }
21755   }
21756 }

```

(End definition for __regex_compile_u_not_cs:.)

38.3.13 Other

__regex_compile_/K: The \K control sequence is currently the only “command”, which performs some action, rather than matching something. It is allowed in the same contexts as \b. At the compilation stage, we leave it as a single control sequence, defined later.

```

21757 \cs_new_protected:cpn { __regex_compile_/K: }
21758 {

```

```

21759 \int_compare:nNnTF \l__regex_mode_int = \c__regex_outer_mode_int
21760 { \tl_build_put_right:Nn \l__regex_build_tl { \__regex_command_K: } }
21761 { \__regex_compile_raw_error:N K }
21762 }

```

(End definition for __regex_compile_/K:.)

38.3.14 Showing regexes

__regex_show:N Within a group and within \tl_build_begin:N ... \tl_build_end:N we redefine all the function that can appear in a compiled regex, then run the regex. The result stored in \l__regex_internal_a_tl is then meant to be shown.

```

21763 \cs_new_protected:Npn \__regex_show:N #1
21764 {
21765   \group_begin:
21766   \tl_build_begin:N \l__regex_build_tl
21767   \cs_set_protected:Npn \__regex_branch:n
21768   {
21769     \seq_pop_right:NN \l__regex_show_prefix_seq
21770     \l__regex_internal_a_tl
21771     \__regex_show_one:n { +-branch }
21772     \seq_put_right:No \l__regex_show_prefix_seq
21773     \l__regex_internal_a_tl
21774     \use:n
21775   }
21776   \cs_set_protected:Npn \__regex_group:nnnN
21777   { \__regex_show_group_aux:nnnnN { } }
21778   \cs_set_protected:Npn \__regex_group_no_capture:nnnN
21779   { \__regex_show_group_aux:nnnnN { ~(no~capture) } }
21780   \cs_set_protected:Npn \__regex_group_resetting:nnnN
21781   { \__regex_show_group_aux:nnnnN { ~(resetting) } }
21782   \cs_set_eq:NN \__regex_class:NnnnN \__regex_show_class:NnnnN
21783   \cs_set_protected:Npn \__regex_command_K:
21784   { \__regex_show_one:n { reset~match~start~(\iow_char:N\K) } }
21785   \cs_set_protected:Npn \__regex_assertion:Nn ##1##2
21786   {
21787     \__regex_show_one:n
21788     { \bool_if:NF ##1 { negative~ } assertion:~##2 }
21789   }
21790   \cs_set:Npn \__regex_b_test: { word~boundary }
21791   \cs_set_eq:NN \__regex_anchor:N \__regex_show_anchor_to_str:N
21792   \cs_set_protected:Npn \__regex_item_caseful_equal:n ##1
21793   { \__regex_show_one:n { char~code~\int_eval:n{##1} } }
21794   \cs_set_protected:Npn \__regex_item_caseful_range:nn ##1##2
21795   {
21796     \__regex_show_one:n
21797     { range~[\int_eval:n{##1}, \int_eval:n{##2}] }
21798   }
21799   \cs_set_protected:Npn \__regex_item_caseless_equal:n ##1
21800   { \__regex_show_one:n { char~code~\int_eval:n{##1}~(caseless) } }
21801   \cs_set_protected:Npn \__regex_item_caseless_range:nn ##1##2
21802   {
21803     \__regex_show_one:n
21804     { Range~[\int_eval:n{##1}, \int_eval:n{##2}]~(caseless) }

```

```

21805     }
21806     \cs_set_protected:Npn \__regex_item_catcode:nT
21807     { \__regex_show_item_catcode:NnT \c_true_bool }
21808     \cs_set_protected:Npn \__regex_item_catcode_reverse:nT
21809     { \__regex_show_item_catcode:NnT \c_false_bool }
21810     \cs_set_protected:Npn \__regex_item_reverse:n
21811     { \__regex_show_scope:nn { Reversed~match } }
21812     \cs_set_protected:Npn \__regex_item_exact:nn ##1##2
21813     { \__regex_show_one:n { char~##2,~catcode~##1 } }
21814     \cs_set_eq:NN \__regex_item_exact_cs:n \__regex_show_item_exact_cs:n
21815     \cs_set_protected:Npn \__regex_item_cs:n
21816     { \__regex_show_scope:nn { control~sequence } }
21817     \cs_set:cpn { \__regex_prop.: } { \__regex_show_one:n { any~token } }
21818     \seq_clear:N \l__regex_show_prefix_seq
21819     \__regex_show_push:n { ~ }
21820     \cs_if_exist_use:N #1
21821     \tl_build_end:N \l__regex_build_tl
21822     \exp_args:NNNo
21823     \group_end:
21824     \tl_set:Nn \l__regex_internal_a_tl { \l__regex_build_tl }
21825 }

```

(End definition for __regex_show:N.)

__regex_show_one:n Every part of the final message go through this function, which adds one line to the output, with the appropriate prefix.

```

21826 \cs_new_protected:Npn \__regex_show_one:n #1
21827 {
21828     \int_incr:N \l__regex_show_lines_int
21829     \tl_build_put_right:Nx \l__regex_build_tl
21830     {
21831         \exp_not:N \iow_newline:
21832         \seq_map_function:NN \l__regex_show_prefix_seq \use:n
21833         #1
21834     }
21835 }

```

(End definition for __regex_show_one:n.)

__regex_show_push:n Enter and exit levels of nesting. The scope function prints its first argument as an “introduction”, then performs its second argument in a deeper level of nesting.

```

\__regex_show_pop:
\__regex_show_scope:nn
21836 \cs_new_protected:Npn \__regex_show_push:n #1
21837 { \seq_put_right:Nx \l__regex_show_prefix_seq { #1 ~ } }
21838 \cs_new_protected:Npn \__regex_show_pop:
21839 { \seq_pop_right:NN \l__regex_show_prefix_seq \l__regex_internal_a_tl }
21840 \cs_new_protected:Npn \__regex_show_scope:nn #1#2
21841 {
21842     \__regex_show_one:n {#1}
21843     \__regex_show_push:n { ~ }
21844     #2
21845     \__regex_show_pop:
21846 }

```

(End definition for __regex_show_push:n, __regex_show_pop:, and __regex_show_scope:nn.)

`__regex_show_group_aux:nnnnN` We display all groups in the same way, simply adding a message, (no capture) or (resetting), to special groups. The odd `\use_ii:nn` avoids printing a spurious +-branch for the first branch.

```

21847 \cs_new_protected:Npn \__regex_show_group_aux:nnnnN #1#2#3#4#5
21848 {
21849     \__regex_show_one:n { , -group~begin #1 }
21850     \__regex_show_push:n { | }
21851     \use_ii:nn #2
21852     \__regex_show_pop:
21853     \__regex_show_one:n
21854     { '-group~end \__regex_msg_repeated:nnN {#3} {#4} #5 }
21855 }

```

(End definition for `__regex_show_group_aux:nnnnN`.)

`__regex_show_class:NnnnN` I'm entirely unhappy about this function: I couldn't find a way to test if a class is a single test. Instead, collect the representation of the tests in the class. If that had more than one line, write Match or Don't match on its own line, with the repeating information if any. Then the various tests on lines of their own, and finally a line. Otherwise, we need to evaluate the representation of the tests again (since the prefix is incorrect). That's clunky, but not too expensive, since it's only one test.

```

21856 \cs_set:Npn \__regex_show_class:NnnnN #1#2#3#4#5
21857 {
21858     \group_begin:
21859     \tl_build_begin:N \l__regex_build_tl
21860     \int_zero:N \l__regex_show_lines_int
21861     \__regex_show_push:n {~}
21862     #2
21863     \int_compare:nTF { \l__regex_show_lines_int = 0 }
21864     {
21865         \group_end:
21866         \__regex_show_one:n { \bool_if:NTF #1 { Fail } { Pass } }
21867     }
21868     {
21869         \bool_if:nTF
21870         { #1 && \int_compare_p:n { \l__regex_show_lines_int = 1 } }
21871         {
21872             \group_end:
21873             #2
21874             \tl_build_put_right:Nn \l__regex_build_tl
21875             { \__regex_msg_repeated:nnN {#3} {#4} #5 }
21876         }
21877         {
21878             \tl_build_end:N \l__regex_build_tl
21879             \exp_args:NNNo
21880             \group_end:
21881             \tl_set:Nn \l__regex_internal_a_tl \l__regex_build_tl
21882             \__regex_show_one:n
21883             {
21884                 \bool_if:NTF #1 { Match } { Don't~match }
21885                 \__regex_msg_repeated:nnN {#3} {#4} #5
21886             }
21887             \tl_build_put_right:Nx \l__regex_build_tl

```

```

21888         { \exp_not:o \l__regex_internal_a_tl }
21889     }
21890 }
21891 }

```

(End definition for __regex_show_class:NnnnN.)

__regex_show_anchor_to_str:N The argument is an integer telling us where the anchor is. We convert that to the relevant info.

```

21892 \cs_new:Npn \__regex_show_anchor_to_str:N #1
21893 {
21894     anchor~at~
21895     \str_case:nnF { #1 }
21896     {
21897         { \l__regex_min_pos_int } { start~(\iow_char:N\A) }
21898         { \l__regex_start_pos_int } { start~of~match~(\iow_char:N\G) }
21899         { \l__regex_max_pos_int } { end~(\iow_char:N\Z) }
21900     }
21901     { <error:~'#1'~not~recognized> }
21902 }

```

(End definition for __regex_show_anchor_to_str:N.)

__regex_show_item_catcode:NnT Produce a sequence of categories which the catcode bitmap #2 contains, and show it, indenting the tests on which this catcode constraint applies.

```

21903 \cs_new_protected:Npn \__regex_show_item_catcode:NnT #1#2
21904 {
21905     \seq_set_split:Nnn \l__regex_internal_seq { } { CBEMTPUDSLOA }
21906     \seq_set_filter:NNn \l__regex_internal_seq \l__regex_internal_seq
21907     { \int_if_odd_p:n { #2 / \int_use:c { c__regex_catcode_##1_int } } }
21908     \__regex_show_scope:nn
21909     {
21910         categories~
21911         \seq_map_function:NN \l__regex_internal_seq \use:n
21912         , ~
21913         \bool_if:NF #1 { negative~ } class
21914     }
21915 }

```

(End definition for __regex_show_item_catcode:NnT.)

__regex_show_item_exact_cs:n

```

21916 \cs_new_protected:Npn \__regex_show_item_exact_cs:n #1
21917 {
21918     \seq_set_split:Nnn \l__regex_internal_seq { \scan_stop: } {#1}
21919     \seq_set_map:NNn \l__regex_internal_seq
21920     \l__regex_internal_seq { \iow_char:N\##1 }
21921     \__regex_show_one:n
21922     { control~sequence~ \seq_use:Nn \l__regex_internal_seq { ~or~ } }
21923 }

```

(End definition for __regex_show_item_exact_cs:n.)

38.4 Building

38.4.1 Variables used while building

`\l__regex_min_state_int` The last state that was allocated is `\l__regex_max_state_int - 1`, so that `\l__regex_max_state_int` always points to a free state. The `min_state` variable is 1 to begin with, but gets shifted in nested calls to the matching code, namely in `\c{...}` constructions.

```
21924 \int_new:N \l__regex_min_state_int
21925 \int_set:Nn \l__regex_min_state_int { 1 }
21926 \int_new:N \l__regex_max_state_int
```

(End definition for `\l__regex_min_state_int` and `\l__regex_max_state_int`.)

`\l__regex_left_state_int` Alternatives are implemented by branching from a `left` state into the various choices, then merging those into a `right` state. We store information about those states in two sequences. Those states are also used to implement group quantifiers. Most often, the `\l__regex_right_state_int` left and right pointers only differ by 1.
`\l__regex_left_state_seq`
`\l__regex_right_state_seq`

```
21927 \int_new:N \l__regex_left_state_int
21928 \int_new:N \l__regex_right_state_int
21929 \seq_new:N \l__regex_left_state_seq
21930 \seq_new:N \l__regex_right_state_seq
```

(End definition for `\l__regex_left_state_int` and others.)

`\l__regex_capturing_group_int` `\l__regex_capturing_group_int` is the next ID number to be assigned to a capturing group. This starts at 0 for the group enclosing the full regular expression, and groups are counted in the order of their left parenthesis, except when encountering `resetting` groups.

```
21931 \int_new:N \l__regex_capturing_group_int
```

(End definition for `\l__regex_capturing_group_int`.)

38.4.2 Framework

This phase is about going from a compiled regex to an NFA. Each state of the NFA is stored in a `\toks`. The operations which can appear in the `\toks` are

- `__regex_action_start_wildcard`: inserted at the start of the regular expression to make it unanchored.
- `__regex_action_success`: marks the exit state of the NFA.
- `__regex_action_cost:n {⟨shift⟩}` is a transition from the current $\langle state \rangle$ to $\langle state \rangle + \langle shift \rangle$, which consumes the current character: the target state is saved and will be considered again when matching at the next position.
- `__regex_action_free:n {⟨shift⟩}`, and `__regex_action_free_group:n {⟨shift⟩}` are free transitions, which immediately perform the actions for the state $\langle state \rangle + \langle shift \rangle$ of the NFA. They differ in how they detect and avoid infinite loops. For now, we just need to know that the `group` variant must be used for transitions back to the start of a group.
- `__regex_action_submatch:n {⟨key⟩}` where the $\langle key \rangle$ is a group number followed by `<` or `>` for the beginning or end of group. This causes the current position in the query to be stored as the $\langle key \rangle$ submatch boundary.

We strive to preserve the following properties while building.

- The current capturing group is `capturing_group - 1`, and if a group opened now it would be labelled `capturing_group`.
- The last allocated state is `max_state - 1`, so `max_state` is a free state.
- The `left_state` points to a state to the left of the current group or of the last class.
- The `right_state` points to a newly created, empty state, with some transitions leading to it.
- The `left/right` sequences hold a list of the corresponding end-points of nested groups.

`__regex_build:n` The `n`-type function first compiles its argument. Reset some variables. Allocate two states, and put a wildcard in state 0 (transitions to state 1 and 0 state). Then build the regex within a (capturing) group numbered 0 (current value of `capturing_group`). Finally, if the match reaches the last state, it is successful.

```

21932 \cs_new_protected:Npn \__regex_build:n #1
21933 {
21934     \__regex_compile:n {#1}
21935     \__regex_build:N \l__regex_internal_regex
21936 }
21937 \__kernel_patch:nnNNpn
21938 { \__regex_trace_push:nnN { regex } { 1 } \__regex_build:N }
21939 {
21940     \__regex_trace_states:n { 2 }
21941     \__regex_trace_pop:nnN { regex } { 1 } \__regex_build:N
21942 }
21943 \cs_new_protected:Npn \__regex_build:N #1
21944 {
21945     \__regex_standard_escapechar:
21946     \int_zero:N \l__regex_capturing_group_int
21947     \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
21948     \__regex_build_new_state:
21949     \__regex_build_new_state:
21950     \__regex_toks_put_right:Nn \l__regex_left_state_int
21951     { \__regex_action_start_wildcard: }
21952     \__regex_group:nnnN {#1} { 1 } { 0 } \c_false_bool
21953     \__regex_toks_put_right:Nn \l__regex_right_state_int
21954     { \__regex_action_success: }
21955 }
```

(End definition for `__regex_build:n` and `__regex_build:N`.)

`__regex_build_for_cs:n` The matching code relies on some global intarray variables, but only uses a range of their entries. Specifically,

- `\g__regex_state_active_intarray` from `\l__regex_min_state_int` to `\l__regex_max_state_1`;
- `\g__regex_thread_state_intarray` from `\l__regex_min_active_int` to `\l__regex_max_activ_1`.

In fact, some data is stored in `\toks` registers (local) in the same ranges so these ranges mustn't overlap. This is done by setting `\l__regex_min_active_int` to `\l__regex_max_state_int` after building the NFA. Here, in this nested call to the matching code, we need the new versions of these ranges to involve completely new entries of the intarray variables, so we begin by setting (the new) `\l__regex_min_state_int` to (the old) `\l__regex_max_active_int` to use higher entries.

When using a regex to match a cs, we don't insert a wildcard, we anchor at the end, and since we ignore submatches, there is no need to surround the expression with a group. However, for branches to work properly at the outer level, we need to put the appropriate left and right states in their sequence.

```

21956 \__kernel_patch:nnNNpn
21957 { \__regex_trace_push:nnN { regex } { 1 } \__regex_build_for_cs:n }
21958 {
21959   \__regex_trace_states:n { 2 }
21960   \__regex_trace_pop:nnN { regex } { 1 } \__regex_build_for_cs:n
21961 }
21962 \cs_new_protected:Npn \__regex_build_for_cs:n #1
21963 {
21964   \int_set_eq:NN \l__regex_min_state_int \l__regex_max_active_int
21965   \int_set_eq:NN \l__regex_max_state_int \l__regex_min_state_int
21966   \__regex_build_new_state:
21967   \__regex_build_new_state:
21968   \__regex_push_lr_states:
21969   #1
21970   \__regex_pop_lr_states:
21971   \__regex_toks_put_right:Nn \l__regex_right_state_int
21972   {
21973     \if_int_compare:w \l__regex_curr_pos_int = \l__regex_max_pos_int
21974       \exp_after:wN \__regex_action_success:
21975     \fi:
21976   }
21977 }

```

(End definition for `__regex_build_for_cs:n`.)

38.4.3 Helpers for building an nfa

`__regex_push_lr_states:` When building the regular expression, we keep track of pointers to the left-end and right-end of each group without help from T_EX's grouping.

```

21978 \cs_new_protected:Npn \__regex_push_lr_states:
21979 {
21980   \seq_push:No \l__regex_left_state_seq
21981   { \int_use:N \l__regex_left_state_int }
21982   \seq_push:No \l__regex_right_state_seq
21983   { \int_use:N \l__regex_right_state_int }
21984 }
21985 \cs_new_protected:Npn \__regex_pop_lr_states:
21986 {
21987   \seq_pop:NN \l__regex_left_state_seq \l__regex_internal_a_tl
21988   \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
21989   \seq_pop:NN \l__regex_right_state_seq \l__regex_internal_a_tl
21990   \int_set:Nn \l__regex_right_state_int \l__regex_internal_a_tl
21991 }

```

(End definition for `_regex_push_lr_states:` and `_regex_pop_lr_states:`)

`_regex_build_transition_left:NNN` Add a transition from #2 to #3 using the function #1. The `left` function is used for higher priority transitions, and the `right` function for lower priority transitions (which should be performed later). The signatures differ to reflect the differing usage later on. Both functions could be optimized.

`_regex_build_transition_right:nNn`

```
21992 \cs_new_protected:Npn \_regex_build_transition_left:NNN #1#2#3
21993   { \_regex_toks_put_left:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }
21994 \cs_new_protected:Npn \_regex_build_transition_right:nNn #1#2#3
21995   { \_regex_toks_put_right:Nx #2 { #1 { \int_eval:n { #3 - #2 } } } }
```

(End definition for `_regex_build_transition_left:NNN` and `_regex_build_transition_right:nNn`.)

`_regex_build_new_state:` Add a new empty state to the NFA. Then update the `left`, `right`, and `max` states, so that the `right` state is the new empty state, and the `left` state points to the previously “current” state.

```
21996 \__kernel_patch:nnNNpn
21997   {
21998     \_regex_trace:nxx { regex } { 2 }
21999     {
22000       regex~new~state~
22001       L=\int_use:N \l__regex_left_state_int ~ -> ~
22002       R=\int_use:N \l__regex_right_state_int ~ -> ~
22003       M=\int_use:N \l__regex_max_state_int ~ -> ~
22004       \int_eval:n { \l__regex_max_state_int + 1 }
22005     }
22006   }
22007 { }
22008 \cs_new_protected:Npn \_regex_build_new_state:
22009   {
22010     \_regex_toks_clear:N \l__regex_max_state_int
22011     \int_set_eq:NN \l__regex_left_state_int \l__regex_right_state_int
22012     \int_set_eq:NN \l__regex_right_state_int \l__regex_max_state_int
22013     \int_incr:N \l__regex_max_state_int
22014   }
```

(End definition for `_regex_build_new_state:`.)

`_regex_build_transitions_lazyess:NNNNN` This function creates a new state, and puts two transitions starting from the old current state. The order of the transitions is controlled by #1, true for lazy quantifiers, and false for greedy quantifiers.

```
22015 \cs_new_protected:Npn \_regex_build_transitions_lazyess:NNNNN #1#2#3#4#5
22016   {
22017     \_regex_build_new_state:
22018     \_regex_toks_put_right:Nx \l__regex_left_state_int
22019     {
22020       \if_meaning:w \c_true_bool #1
22021         #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
22022         #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
22023       \else:
22024         #4 { \int_eval:n { #5 - \l__regex_left_state_int } }
22025         #2 { \int_eval:n { #3 - \l__regex_left_state_int } }
22026       \fi:
22027     }
22028   }
```

(End definition for `_regex_build_transitions_lazy:NNNN`.)

38.4.4 Building classes

`_regex_class:NnnnN` The arguments are: $\langle \text{boolean} \rangle$ $\{\langle \text{tests} \rangle\}$ $\{\langle \text{min} \rangle\}$ $\{\langle \text{more} \rangle\}$ $\langle \text{laziness} \rangle$. First store the tests with a trailing `_regex_action_cost:n`, in the true branch of `_regex_break_point:TF` for positive classes, or the false branch for negative classes. The integer $\langle \text{more} \rangle$ is 0 for fixed repetitions, -1 for unbounded repetitions, and $\langle \text{max} \rangle - \langle \text{min} \rangle$ for a range of repetitions.

```

22029 \cs_new_protected:Npn \_regex_class:NnnnN #1#2#3#4#5
22030 {
22031   \cs_set:Npx \_regex_tests_action_cost:n ##1
22032   {
22033     \exp_not:n { \exp_not:n {#2} }
22034     \bool_if:NTF #1
22035       { \_regex_break_point:TF { \_regex_action_cost:n {##1} } { } }
22036       { \_regex_break_point:TF { } { \_regex_action_cost:n {##1} } }
22037   }
22038   \if_case:w - #4 \exp_stop_f:
22039     \_regex_class_repeat:n {#3}
22040   \or: \_regex_class_repeat:nN {#3} #5
22041   \else: \_regex_class_repeat:nnN {#3} {#4} #5
22042   \fi:
22043 }
22044 \cs_new:Npn \_regex_tests_action_cost:n { \_regex_action_cost:n }

```

(End definition for `_regex_class:NnnnN` and `_regex_tests_action_cost:n`.)

`_regex_class_repeat:n` This is used for a fixed number of repetitions. Build one state for each repetition, with a transition controlled by the tests that we have collected. That works just fine for $\#1 = 0$ repetitions: nothing is built.

```

22045 \cs_new_protected:Npn \_regex_class_repeat:n #1
22046 {
22047   \prg_replicate:nn {#1}
22048   {
22049     \_regex_build_new_state:
22050     \_regex_build_transition_right:nNn \_regex_tests_action_cost:n
22051     \l__regex_left_state_int \l__regex_right_state_int
22052   }
22053 }

```

(End definition for `_regex_class_repeat:n`.)

`_regex_class_repeat:nN` This implements unbounded repetitions of a single class (e.g. the $*$ and $+$ quantifiers). If the minimum number $\#1$ of repetitions is 0, then build a transition from the current state to itself governed by the tests, and a free transition to a new state (hence skipping the tests). Otherwise, call `_regex_class_repeat:n` for the code to match $\#1$ repetitions, and add free transitions from the last state to the previous one, and to a new one. In both cases, the order of transitions is controlled by the laziness boolean $\#2$.

```

22054 \cs_new_protected:Npn \_regex_class_repeat:nN #1#2
22055 {
22056   \if_int_compare:w #1 = 0 \exp_stop_f:
22057   \_regex_build_transitions_lazy:NNNN #2

```

```

22058     \_regex_action_free:n      \l__regex_right_state_int
22059     \_regex_tests_action_cost:n \l__regex_left_state_int
22060   \else:
22061     \_regex_class_repeat:n {#1}
22062     \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
22063     \_regex_build_transitions_lazyness:NNNN #2
22064     \_regex_action_free:n \l__regex_right_state_int
22065     \_regex_action_free:n \l__regex_internal_a_int
22066   \fi:
22067 }

```

(End definition for _regex_class_repeat:nN.)

_regex_class_repeat:nnN We want to build the code to match from #1 to #1 + #2 repetitions. Match #1 repetitions (can be 0). Compute the final state of the next construction as **a**. Build #2 > 0 states, each with a transition to the next state governed by the tests, and a transition to the final state **a**. The computation of **a** is safe because states are allocated in order, starting from **max_state**.

```

22068 \cs_new_protected:Npn \_regex_class_repeat:nnN #1#2#3
22069 {
22070   \_regex_class_repeat:n {#1}
22071   \int_set:Nn \l__regex_internal_a_int
22072     { \l__regex_max_state_int + #2 - 1 }
22073   \prg_replicate:nn { #2 }
22074   {
22075     \_regex_build_transitions_lazyness:NNNN #3
22076     \_regex_action_free:n      \l__regex_internal_a_int
22077     \_regex_tests_action_cost:n \l__regex_right_state_int
22078   }
22079 }

```

(End definition for _regex_class_repeat:nnN.)

38.4.5 Building groups

_regex_group_aux:nnnnN Arguments: {<label>} {<contents>} {<min>} {<more>} <lazyness>. If <min> is 0, we need to add a state before building the group, so that the thread which skips the group does not also set the start-point of the submatch. After adding one more state, the **left_state** is the left end of the group, from which all branches stem, and the **right_state** is the right end of the group, and all branches end their course in that state. We store those two integers to be queried for each branch, we build the NFA states for the contents #2 of the group, and we forget about the two integers. Once this is done, perform the repetition: either exactly #3 times, or #3 or more times, or between #3 and #3 + #4 times, with lazyness #5. The <label> #1 is used for submatch tracking. Each of the three auxiliaries expects **left_state** and **right_state** to be set properly.

```

22080 \_kernel_patch:nnNnpn
22081 { \_regex_trace_push:nnN { regex } { 1 } \_regex_group_aux:nnnnN }
22082 { \_regex_trace_pop:nnN { regex } { 1 } \_regex_group_aux:nnnnN }
22083 \cs_new_protected:Npn \_regex_group_aux:nnnnN #1#2#3#4#5
22084 {
22085   \if_int_compare:w #3 = 0 \exp_stop_f:
22086     \_regex_build_new_state:
22087   <assert>\assert_int:n { \l__regex_max_state_int = \l__regex_right_state_int + 1 }

```

```

22088     \_regex_build_transition_right:nNn \_regex_action_free_group:n
22089     \l__regex_left_state_int \l__regex_right_state_int
22090 \fi:
22091 \_regex_build_new_state:
22092 \_regex_push_lr_states:
22093 #2
22094 \_regex_pop_lr_states:
22095 \if_case:w - #4 \exp_stop_f:
22096     \_regex_group_repeat:nn {#1} {#3}
22097 \or:  \_regex_group_repeat:nnN {#1} {#3} #5
22098 \else: \_regex_group_repeat:nnnN {#1} {#3} {#4} #5
22099 \fi:
22100 }

```

(End definition for _regex_group_aux:nnnnN.)

_regex_group:nnnN Hand to _regex_group_aux:nnnnN the label of that group (expanded), and the group itself, with some extra commands to perform.

```

22101 \cs_new_protected:Npn \_regex_group:nnnN #1
22102 {
22103     \exp_args:Nn \_regex_group_aux:nnnnN
22104     { \int_use:N \l__regex_capturing_group_int }
22105     {
22106         \int_incr:N \l__regex_capturing_group_int
22107         #1
22108     }
22109 }
22110 \cs_new_protected:Npn \_regex_group_no_capture:nnnN
22111 { \_regex_group_aux:nnnnN { -1 } }

```

(End definition for _regex_group:nnnN and _regex_group_no_capture:nnnN.)

_regex_group_resetting:nnnN Again, hand the label -1 to _regex_group_aux:nnnnN, but this time we work a little bit harder to keep track of the maximum group label at the end of any branch, and to reset the group number at each branch. This relies on the fact that a compiled regex always is a sequence of items of the form _regex_branch:n {<branch>}.
_regex_group_resetting_loop:nnNn

```

22112 \cs_new_protected:Npn \_regex_group_resetting:nnnN #1
22113 {
22114     \_regex_group_aux:nnnnN { -1 }
22115     {
22116         \exp_args:Noo \_regex_group_resetting_loop:nnNn
22117         { \int_use:N \l__regex_capturing_group_int }
22118         { \int_use:N \l__regex_capturing_group_int }
22119         #1
22120         { ?? \prg_break:n } { }
22121         \prg_break_point:
22122     }
22123 }
22124 \cs_new_protected:Npn \_regex_group_resetting_loop:nnNn #1#2#3#4
22125 {
22126     \use_none:nn #3 { \int_set:Nn \l__regex_capturing_group_int {#1} }
22127     \int_set:Nn \l__regex_capturing_group_int {#2}
22128     #3 {#4}
22129     \exp_args:Nf \_regex_group_resetting_loop:nnNn

```

```

22130     { \int_max:nn {#1} { \l__regex_capturing_group_int } }
22131     {#2}
22132 }

```

(End definition for __regex_group_resetting:nnnN and __regex_group_resetting_loop:nnNn.)

__regex_branch:n Add a free transition from the left state of the current group to a brand new state, starting point of this branch. Once the branch is built, add a transition from its last state to the right state of the group. The left and right states of the group are extracted from the relevant sequences.

```

22133 \__kernel_patch:nnNNpn
22134 { \__regex_trace_push:nnN { regex } { 1 } \__regex_branch:n }
22135 { \__regex_trace_pop:nnN { regex } { 1 } \__regex_branch:n }
22136 \cs_new_protected:Npn \__regex_branch:n #1
22137 {
22138   \__regex_build_new_state:
22139   \seq_get:NN \l__regex_left_state_seq \l__regex_internal_a_tl
22140   \int_set:Nn \l__regex_left_state_int \l__regex_internal_a_tl
22141   \__regex_build_transition_right:nNn \__regex_action_free:n
22142   \l__regex_left_state_int \l__regex_right_state_int
22143   #1
22144   \seq_get:NN \l__regex_right_state_seq \l__regex_internal_a_tl
22145   \__regex_build_transition_right:nNn \__regex_action_free:n
22146   \l__regex_right_state_int \l__regex_internal_a_tl
22147 }

```

(End definition for __regex_branch:n.)

__regex_group_repeat:nn This function is called to repeat a group a fixed number of times #2; if this is 0 we remove the group altogether (but don't reset the capturing_group label). Otherwise, the auxiliary __regex_group_repeat_aux:n copies #2 times the \toks for the group, and leaves internal_a pointing to the left end of the last repetition. We only record the submatch information at the last repetition. Finally, add a state at the end (the transition to it has been taken care of by the replicating auxiliary).

```

22148 \cs_new_protected:Npn \__regex_group_repeat:nn #1#2
22149 {
22150   \if_int_compare:w #2 = 0 \exp_stop_f:
22151   \int_set:Nn \l__regex_max_state_int
22152   { \l__regex_left_state_int - 1 }
22153   \__regex_build_new_state:
22154   \else:
22155     \__regex_group_repeat_aux:n {#2}
22156     \__regex_group_submatches:nnN {#1}
22157     \l__regex_internal_a_int \l__regex_right_state_int
22158     \__regex_build_new_state:
22159   \fi:
22160 }

```

(End definition for __regex_group_repeat:nn.)

__regex_group_submatches:nnN This inserts in states #2 and #3 the code for tracking submatches of the group #1, unless inhibited by a label of -1.

```

22161 \cs_new_protected:Npn \__regex_group_submatches:nnN #1#2#3
22162 {

```

```

22163     \if_int_compare:w #1 > - 1 \exp_stop_f:
22164         \__regex_toks_put_left:Nx #2 { \__regex_action_submatch:n { #1 < } }
22165         \__regex_toks_put_left:Nx #3 { \__regex_action_submatch:n { #1 > } }
22166     \fi:
22167 }

```

(End definition for __regex_group_submatches:nNN.)

__regex_group_repeat_aux:n Here we repeat \toks ranging from left_state to max_state, #1 > 0 times. First add a transition so that the copies “chain” properly. Compute the shift c between the original copy and the last copy we want. Shift the right_state and max_state to their final values. We then want to perform c copy operations. At the end, b is equal to the max_state, and a points to the left of the last copy of the group.

```

22168 \cs_new_protected:Npn \__regex_group_repeat_aux:n #1
22169 {
22170     \__regex_build_transition_right:nNn \__regex_action_free:n
22171     \l__regex_right_state_int \l__regex_max_state_int
22172     \int_set_eq:NN \l__regex_internal_a_int \l__regex_left_state_int
22173     \int_set_eq:NN \l__regex_internal_b_int \l__regex_max_state_int
22174     \if_int_compare:w \int_eval:n {#1} > 1 \exp_stop_f:
22175         \int_set:Nn \l__regex_internal_c_int
22176         {
22177             ( #1 - 1 )
22178             * ( \l__regex_internal_b_int - \l__regex_internal_a_int )
22179         }
22180     \int_add:Nn \l__regex_right_state_int { \l__regex_internal_c_int }
22181     \int_add:Nn \l__regex_max_state_int { \l__regex_internal_c_int }
22182     \__regex_toks_memcpy:NNn
22183     \l__regex_internal_b_int
22184     \l__regex_internal_a_int
22185     \l__regex_internal_c_int
22186     \fi:
22187 }

```

(End definition for __regex_group_repeat_aux:n.)

__regex_group_repeat:nnN This function is called to repeat a group at least n times; the case n = 0 is very different from n > 0. Assume first that n = 0. Insert submatch tracking information at the start and end of the group, add a free transition from the right end to the “true” left state a (remember: in this case we had added an extra state before the left state). This forms the loop, which we break away from by adding a free transition from a to a new state.

Now consider the case n > 0. Repeat the group n times, chaining various copies with a free transition. Add submatch tracking only to the last copy, then add a free transition from the right end back to the left end of the last copy, either before or after the transition to move on towards the rest of the NFA. This transition can end up before submatch tracking, but that is irrelevant since it only does so when going again through the group, recording new matches. Finally, add a state; we already have a transition pointing to it from __regex_group_repeat_aux:n.

```

22188 \cs_new_protected:Npn \__regex_group_repeat:nnN #1#2#3
22189 {
22190     \if_int_compare:w #2 = 0 \exp_stop_f:
22191         \__regex_group_submatches:nnN {#1}
22192         \l__regex_left_state_int \l__regex_right_state_int

```



```

22193     \int_set:Nn \l__regex_internal_a_int
22194     { \l__regex_left_state_int - 1 }
22195     \__regex_build_transition_right:nNn \__regex_action_free:n
22196     \l__regex_right_state_int \l__regex_internal_a_int
22197     \__regex_build_new_state:
22198     \if_meaning:w \c_true_bool #3
22199     \__regex_build_transition_left:NNN \__regex_action_free:n
22200     \l__regex_internal_a_int \l__regex_right_state_int
22201     \else:
22202     \__regex_build_transition_right:nNn \__regex_action_free:n
22203     \l__regex_internal_a_int \l__regex_right_state_int
22204     \fi:
22205     \else:
22206     \__regex_group_repeat_aux:n {#2}
22207     \__regex_group_submatches:nNN {#1}
22208     \l__regex_internal_a_int \l__regex_right_state_int
22209     \if_meaning:w \c_true_bool #3
22210     \__regex_build_transition_right:nNn \__regex_action_free_group:n
22211     \l__regex_right_state_int \l__regex_internal_a_int
22212     \else:
22213     \__regex_build_transition_left:NNN \__regex_action_free_group:n
22214     \l__regex_right_state_int \l__regex_internal_a_int
22215     \fi:
22216     \__regex_build_new_state:
22217     \fi:
22218   }

```

(End definition for __regex_group_repeat:nnN.)

__regex_group_repeat:nnnN We wish to repeat the group between #2 and #2 + #3 times, with a laziness controlled by #4. We insert submatch tracking up front: in principle, we could avoid recording submatches for the first #2 copies of the group, but that forces us to treat specially the case #2 = 0. Repeat that group with submatch tracking #2 + #3 times (the maximum number of repetitions). Then our goal is to add #3 transitions from the end of the #2-th group, and each subsequent groups, to the end. For a lazy quantifier, we add those transitions to the left states, before submatch tracking. For the greedy case, we add the transitions to the right states, after submatch tracking and the transitions which go on with more repetitions. In the greedy case with #2 = 0, the transition which skips over all copies of the group must be added separately, because its starting state does not follow the normal pattern: we had to add it “by hand” earlier.

```

22219 \cs_new_protected:Npn \__regex_group_repeat:nnnN #1#2#3#4
22220 {
22221   \__regex_group_submatches:nNN {#1}
22222   \l__regex_left_state_int \l__regex_right_state_int
22223   \__regex_group_repeat_aux:n { #2 + #3 }
22224   \if_meaning:w \c_true_bool #4
22225   \int_set_eq:NN \l__regex_left_state_int \l__regex_max_state_int
22226   \prg_replicate:nn { #3 }
22227   {
22228     \int_sub:Nn \l__regex_left_state_int
22229     { \l__regex_internal_b_int - \l__regex_internal_a_int }
22230     \__regex_build_transition_left:NNN \__regex_action_free:n
22231     \l__regex_left_state_int \l__regex_max_state_int

```

```

22232     }
22233 \else:
22234   \prg_replicate:nn { #3 - 1 }
22235   {
22236     \int_sub:Nn \l__regex_right_state_int
22237     { \l__regex_internal_b_int - \l__regex_internal_a_int }
22238     \__regex_build_transition_right:nNn \__regex_action_free:n
22239     \l__regex_right_state_int \l__regex_max_state_int
22240   }
22241   \if_int_compare:w #2 = 0 \exp_stop_f:
22242     \int_set:Nn \l__regex_right_state_int
22243     { \l__regex_left_state_int - 1 }
22244   \else:
22245     \int_sub:Nn \l__regex_right_state_int
22246     { \l__regex_internal_b_int - \l__regex_internal_a_int }
22247   \fi:
22248   \__regex_build_transition_right:nNn \__regex_action_free:n
22249   \l__regex_right_state_int \l__regex_max_state_int
22250 \fi:
22251 \__regex_build_new_state:
22252 }

```

(End definition for __regex_group_repeat:nnnN.)

38.4.6 Others

__regex_assertion:Nn
 __regex_b_test:
 __regex_anchor:N

Usage: __regex_assertion:Nn *<boolean>* {*<test>*}, where the *<test>* is either of the two other functions. Add a free transition to a new state, conditionally to the assertion test. The __regex_b_test: test is used by the \b and \B escape: check if the last character was a word character or not, and do the same to the current character. The boundary-markers of the string are non-word characters for this purpose. Anchors at the start or end of match use __regex_anchor:N, with a position controlled by the integer #1.

```

22253 \cs_new_protected:Npn \__regex_assertion:Nn #1#2
22254 {
22255   \__regex_build_new_state:
22256   \__regex_toks_put_right:Nx \l__regex_left_state_int
22257   {
22258     \exp_not:n {#2}
22259     \__regex_break_point:TF
22260     \bool_if:NF #1 { { } }
22261     {
22262       \__regex_action_free:n
22263       {
22264         \int_eval:n
22265         { \l__regex_right_state_int - \l__regex_left_state_int }
22266       }
22267     }
22268     \bool_if:NT #1 { { } }
22269   }
22270 }
22271 \cs_new_protected:Npn \__regex_anchor:N #1
22272 {
22273   \if_int_compare:w #1 = \l__regex_curr_pos_int
22274     \exp_after:wN \__regex_break_true:w

```

```

22275     \fi:
22276   }
22277   \cs_new_protected:Npn \__regex_b_test:
22278   {
22279     \group_begin:
22280     \int_set_eq:NN \l__regex_curr_char_int \l__regex_last_char_int
22281     \__regex_prop_w:
22282     \__regex_break_point:TF
22283     { \group_end: \__regex_item_reverse:n \__regex_prop_w: }
22284     { \group_end: \__regex_prop_w: }
22285   }

```

(End definition for `__regex_assertion:Nn`, `__regex_b_test:`, and `__regex_anchor:N`.)

`__regex_command_K:` Change the starting point of the 0-th submatch (full match), and transition to a new state, pretending that this is a fresh thread.

```

22286   \cs_new_protected:Npn \__regex_command_K:
22287   {
22288     \__regex_build_new_state:
22289     \__regex_toks_put_right:Nx \l__regex_left_state_int
22290     {
22291       \__regex_action_submatch:n { 0< }
22292       \bool_set_true:N \l__regex_fresh_thread_bool
22293       \__regex_action_free:n
22294       {
22295         \int_eval:n
22296         { \l__regex_right_state_int - \l__regex_left_state_int }
22297       }
22298       \bool_set_false:N \l__regex_fresh_thread_bool
22299     }
22300   }

```

(End definition for `__regex_command_K:.`)

38.5 Matching

We search for matches by running all the execution threads through the NFA in parallel, reading one token of the query at each step. The NFA contains “free” transitions to other states, and transitions which “consume” the current token. For free transitions, the instruction at the new state of the NFA is performed immediately. When a transition consumes a character, the new state is appended to a list of “active states”, stored in `\g__regex_thread_state_intarray`: this thread is made active again when the next token is read from the query. At every step (for each token in the query), we unpack that list of active states and the corresponding submatch props, and empty those.

If two paths through the NFA “collide” in the sense that they reach the same state after reading a given token, then they only differ in how they previously matched, and any future execution would be identical for both. (Note that this would be wrong in the presence of back-references.) Hence, we only need to keep one of the two threads: the thread with the highest priority. Our NFA is built in such a way that higher priority actions always come before lower priority actions, which makes things work.

The explanation in the previous paragraph may make us think that we simply need to keep track of which states were visited at a given step: after all, the loop generated when matching `(a?)*` against `a` is broken, isn’t it? No. The group first matches `a`, as

it should, then repeats; it attempts to match **a** again but fails; it skips **a**, and finds out that this state has already been seen at this position in the query: the match stops. The capturing group is (wrongly) **a**. What went wrong is that a thread collided with itself, and the later version, which has gone through the group one more times with an empty match, should have a higher priority than not going through the group.

We solve this by distinguishing “normal” free transitions `_regex_action_free:n` from transitions `_regex_action_free_group:n` which go back to the start of the group. The former keeps threads unless they have been visited by a “completed” thread, while the latter kind of transition also prevents going back to a state visited by the current thread.

38.5.1 Variables used when matching

<code>\l__regex_min_pos_int</code> <code>\l__regex_max_pos_int</code> <code>\l__regex_curr_pos_int</code> <code>\l__regex_start_pos_int</code> <code>\l__regex_success_pos_int</code>	<p>The tokens in the query are indexed from <code>min_pos</code> for the first to <code>max_pos - 1</code> for the last, and their information is stored in several arrays and <code>\toks</code> registers with those numbers. We don’t start from 0 because the <code>\toks</code> registers with low numbers are used to hold the states of the NFA. We match without backtracking, keeping all threads in lockstep at the <code>current_pos</code> in the query. The starting point of the current match attempt is <code>start_pos</code>, and <code>success_pos</code>, updated whenever a thread succeeds, is used as the next starting position.</p>
---	--

```

22301 \int_new:N \l__regex_min_pos_int
22302 \int_new:N \l__regex_max_pos_int
22303 \int_new:N \l__regex_curr_pos_int
22304 \int_new:N \l__regex_start_pos_int
22305 \int_new:N \l__regex_success_pos_int

```

(End definition for `\l__regex_min_pos_int` and others.)

<code>\l__regex_curr_char_int</code> <code>\l__regex_curr_catcode_int</code> <code>\l__regex_last_char_int</code> <code>\l__regex_case_changed_char_int</code>	<p>The character and category codes of the token at the current position; the character code of the token at the previous position; and the character code of the result of changing the case of the current token (<code>A-Z↔a-z</code>). This last integer is only computed when necessary, and is otherwise <code>\c_max_int</code>. The <code>current_char</code> variable is also used in various other phases to hold a character code.</p>
---	---

```

22306 \int_new:N \l__regex_curr_char_int
22307 \int_new:N \l__regex_curr_catcode_int
22308 \int_new:N \l__regex_last_char_int
22309 \int_new:N \l__regex_case_changed_char_int

```

(End definition for `\l__regex_curr_char_int` and others.)

<code>\l__regex_curr_state_int</code>	<p>For every character in the token list, each of the active states is considered in turn. The variable <code>\l__regex_curr_state_int</code> holds the state of the NFA which is currently considered: transitions are then given as shifts relative to the current state.</p>
---------------------------------------	---

```

22310 \int_new:N \l__regex_curr_state_int

```

(End definition for `\l__regex_curr_state_int`.)

<code>\l__regex_curr_submatches_prop</code> <code>\l__regex_success_submatches_prop</code>	<p>The submatches for the thread which is currently active are stored in the <code>current_submatches</code> property list variable. This property list is stored by <code>_regex_action_cost:n</code> into the <code>\toks</code> register for the target state of the transition, to be retrieved when matching at the next position. When a thread succeeds, this property list is copied to <code>\l__regex_success_submatches_prop</code>: only the last successful thread remains there.</p>
---	---

```

22311 \prop_new:N \l__regex_curr_submatches_prop
22312 \prop_new:N \l__regex_success_submatches_prop

```

(End definition for `\l__regex_curr_submatches_prop` and `\l__regex_success_submatches_prop`.)

`\l__regex_step_int` This integer, always even, is increased every time a character in the query is read, and not reset when doing multiple matches. We store in `\g__regex_state_active_intarray` the last step in which each $\langle state \rangle$ in the NFA was encountered. This lets us break infinite loops by not visiting the same state twice in the same step. In fact, the step we store is equal to `step` when we have started performing the operations of `\toks\langle state \rangle`, but not finished yet. However, once we finish, we store `step + 1` in `\g__regex_state_active_intarray`. This is needed to track submatches properly (see building phase). The `step` is also used to attach each set of submatch information to a given iteration (and automatically discard it when it corresponds to a past step).

```

22313 \int_new:N \l__regex_step_int

```

(End definition for `\l__regex_step_int`.)

`\l__regex_min_active_int` All the currently active threads are kept in order of precedence in `\g__regex_thread_state_intarray`, and the corresponding submatches in the `\toks`. For our purposes, those serve as an array, indexed from `min_active` (inclusive) to `max_active` (excluded).
`\l__regex_max_active_int` At the start of every step, the whole array is unpacked, so that the space can immediately be reused, and `max_active` is reset to `min_active`, effectively clearing the array.

```

22314 \int_new:N \l__regex_min_active_int
22315 \int_new:N \l__regex_max_active_int

```

(End definition for `\l__regex_min_active_int` and `\l__regex_max_active_int`.)

`\g__regex_state_active_intarray` `\g__regex_state_active_intarray` stores the last $\langle step \rangle$ in which each $\langle state \rangle$ was active.
`\g__regex_thread_state_intarray` `\g__regex_thread_state_intarray` stores threads to be considered in the next step, more precisely the states in which these threads are.

```

22316 \intarray_new:Nn \g__regex_state_active_intarray { 65536 }
22317 \intarray_new:Nn \g__regex_thread_state_intarray { 65536 }

```

(End definition for `\g__regex_state_active_intarray` and `\g__regex_thread_state_intarray`.)

`\l__regex_every_match_tl` Every time a match is found, this token list is used. For single matching, the token list is empty. For multiple matching, the token list is set to repeat the matching, after performing some operation which depends on the user function. See `__regex_single_match:` and `__regex_multi_match:n`.

```

22318 \tl_new:N \l__regex_every_match_tl

```

(End definition for `\l__regex_every_match_tl`.)

`\l__regex_fresh_thread_bool` When doing multiple matches, we need to avoid infinite loops where each iteration matches the same empty token list. When an empty token list is matched, the next
`\l__regex_empty_success_bool` successful match of the same empty token list is suppressed. We detect empty matches
`__regex_if_two_empty_matches:F` by setting `\l__regex_fresh_thread_bool` to `true` for threads which directly come from the start of the regex or from the `\K` command, and testing that boolean whenever a thread succeeds. The function `__regex_if_two_empty_matches:F` is redefined at every match attempt, depending on whether the previous match was empty or not: if it was, then the function must cancel a purported success if it is empty and at the same spot

as the previous match; otherwise, we definitely don't have two identical empty matches, so the function is `\use:n`.

```
22319 \bool_new:N \l__regex_fresh_thread_bool
22320 \bool_new:N \l__regex_empty_success_bool
22321 \cs_new_eq:NN \__regex_if_two_empty_matches:F \use:n
```

(End definition for \l__regex_fresh_thread_bool, \l__regex_empty_success_bool, and __regex_if_two_empty_matches:F.)

```
\g__regex_success_bool
\l__regex_saved_success_bool
\l__regex_match_success_bool
```

The boolean `\l__regex_match_success_bool` is true if the current match attempt was successful, and `\g__regex_success_bool` is true if there was at least one successful match. This is the only global variable in this whole module, but we would need it to be local when matching a control sequence with `\c{...}`. This is done by saving the global variable into `\l__regex_saved_success_bool`, which is local, hence not affected by the changes due to inner regex functions.

```
22322 \bool_new:N \g__regex_success_bool
22323 \bool_new:N \l__regex_saved_success_bool
22324 \bool_new:N \l__regex_match_success_bool
```

(End definition for \g__regex_success_bool, \l__regex_saved_success_bool, and \l__regex_match_success_bool.)

38.5.2 Matching: framework

```
\__regex_match:n
\__regex_match_cs:n
\__regex_match_init:
```

First store the query into `\toks` registers and arrays (see `__regex_query_set:nnn`). Then initialize the variables that should be set once for each user function (even for multiple matches). Namely, the overall matching is not yet successful; none of the states should be marked as visited (`\g__regex_state_active_intarray`), and we start at step 0; we pretend that there was a previous match ending at the start of the query, which was not empty (to avoid smothering an empty match at the start). Once all this is set up, we are ready for the ride. Find the first match.

```
22325 \__kernel_patch:nnNNpn
22326 {
22327   \__regex_trace_push:nnN { regex } { 1 } \__regex_match:n
22328   \__regex_trace:nnx { regex } { 1 } { analyzing-query-token-list }
22329 }
22330 { \__regex_trace_pop:nnN { regex } { 1 } \__regex_match:n }
22331 \cs_new_protected:Npn \__regex_match:n #1
22332 {
22333   \int_zero:N \l__regex_balance_int
22334   \int_set:Nn \l__regex_curr_pos_int { 2 * \l__regex_max_state_int }
22335   \__regex_query_set:nnn { } { -1 } { -2 }
22336   \int_set_eq:NN \l__regex_min_pos_int \l__regex_curr_pos_int
22337   \tl_analysis_map_inline:nn {#1}
22338   { \__regex_query_set:nnn {##1} {"##3"} {##2} }
22339   \int_set_eq:NN \l__regex_max_pos_int \l__regex_curr_pos_int
22340   \__regex_query_set:nnn { } { -1 } { -2 }
22341   \__regex_match_init:
22342   \__regex_match_once:
22343 }
22344 \__kernel_patch:nnNNpn
22345 {
22346   \__regex_trace_push:nnN { regex } { 1 } \__regex_match_cs:n
```

```

22347     \__regex_trace:nnx { regex } { 1 } { analyzing-query~token~list }
22348 }
22349 { \__regex_trace_pop:nnN { regex } { 1 } \__regex_match_cs:n }
22350 \cs_new_protected:Npn \__regex_match_cs:n #1
22351 {
22352     \int_zero:N \l__regex_balance_int
22353     \int_set:Nn \l__regex_curr_pos_int
22354     {
22355         \int_max:nn { 2 * \l__regex_max_state_int - \l__regex_min_state_int }
22356         { \l__regex_max_pos_int }
22357         + 1
22358     }
22359     \__regex_query_set:nnn { } { -1 } { -2 }
22360     \int_set_eq:NN \l__regex_min_pos_int \l__regex_curr_pos_int
22361     \str_map_inline:nn {#1}
22362     {
22363         \__regex_query_set:nnn { \exp_not:n {##1} }
22364         { \tl_if_blank:nTF {##1} { 10 } { 12 } }
22365         { '##1 }
22366     }
22367     \int_set_eq:NN \l__regex_max_pos_int \l__regex_curr_pos_int
22368     \__regex_query_set:nnn { } { -1 } { -2 }
22369     \__regex_match_init:
22370     \__regex_match_once:
22371 }
22372 \__kernel_patch:nnNNpn
22373 { \__regex_trace:nnx { regex } { 1 } { initializing } }
22374 { }
22375 \cs_new_protected:Npn \__regex_match_init:
22376 {
22377     \bool_gset_false:N \g__regex_success_bool
22378     \int_step_inline:nnn
22379     \l__regex_min_state_int { \l__regex_max_state_int - 1 }
22380     {
22381         \__kernel_intarray_gset:Nnn
22382         \g__regex_state_active_intarray {##1} { 1 }
22383     }
22384     \int_set_eq:NN \l__regex_min_active_int \l__regex_max_state_int
22385     \int_zero:N \l__regex_step_int
22386     \int_set_eq:NN \l__regex_success_pos_int \l__regex_min_pos_int
22387     \int_set:Nn \l__regex_min_submatch_int
22388     { 2 * \l__regex_max_state_int }
22389     \int_set_eq:NN \l__regex_submatch_int \l__regex_min_submatch_int
22390     \bool_set_false:N \l__regex_empty_success_bool
22391 }

```

(End definition for __regex_match:n, __regex_match_cs:n, and __regex_match_init:.)

__regex_match_once: This function finds one match, then does some action defined by the `every_match` token list, which may recursively call `__regex_match_once:`. First initialize some variables: set the conditional which detects identical empty matches; this match attempt starts at the previous `success_pos`, is not yet successful, and has no submatches yet; clear the array of active threads, and put the starting state 0 in it. We are then almost ready to read our first token in the query, but we actually start one position earlier than the

start, and get that token, to set `last_char` properly for word boundaries. Then call `__regex_match_loop:`, which runs through the query until the end or until a successful match breaks early.

```

22392 \cs_new_protected:Npn \__regex_match_once:
22393 {
22394   \if_meaning:w \c_true_bool \l__regex_empty_success_bool
22395   \cs_set:Npn \__regex_if_two_empty_matches:F
22396   {
22397     \int_compare:nNnF
22398       \l__regex_start_pos_int = \l__regex_curr_pos_int
22399   }
22400   \else:
22401     \cs_set_eq:NN \__regex_if_two_empty_matches:F \use:n
22402   \fi:
22403   \int_set_eq:NN \l__regex_start_pos_int \l__regex_success_pos_int
22404   \bool_set_false:N \l__regex_match_success_bool
22405   \prop_clear:N \l__regex_curr_submatches_prop
22406   \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
22407   \__regex_store_state:n { \l__regex_min_state_int }
22408   \int_set:Nn \l__regex_curr_pos_int
22409     { \l__regex_start_pos_int - 1 }
22410   \__regex_query_get:
22411   \__regex_match_loop:
22412   \l__regex_every_match_tl
22413 }

```

(End definition for `__regex_match_once:`.)

`__regex_single_match:` For a single match, the overall success is determined by whether the only match attempt is a success. When doing multiple matches, the overall matching is successful as soon as any match succeeds. Perform the action #1, then find the next match.

`__regex_multi_match:n`

```

22414 \cs_new_protected:Npn \__regex_single_match:
22415 {
22416   \tl_set:Nn \l__regex_every_match_tl
22417   {
22418     \bool_gset_eq:NN
22419       \g__regex_success_bool
22420       \l__regex_match_success_bool
22421   }
22422 }
22423 \cs_new_protected:Npn \__regex_multi_match:n #1
22424 {
22425   \tl_set:Nn \l__regex_every_match_tl
22426   {
22427     \if_meaning:w \c_true_bool \l__regex_match_success_bool
22428     \bool_gset_true:N \g__regex_success_bool
22429     #1
22430     \exp_after:wN \__regex_match_once:
22431   \fi:
22432 }
22433 }

```

(End definition for `__regex_single_match:` and `__regex_multi_match:n`.)

`__regex_match_loop:` At each new position, set some variables and get the new character and category from the query. Then unpack the array of active threads, and clear it by resetting its length (`max_active`). This results in a sequence of `__regex_use_state_and_submatches:nn` `{<state>}` `{<prop>}`, and we consider those states one by one in order. As soon as a thread succeeds, exit the step, and, if there are threads to consider at the next position, and we have not reached the end of the string, repeat the loop. Otherwise, the last thread that succeeded is what `__regex_match_once:` matches. We explain the `fresh_thread` business when describing `__regex_action_wildcard:`.

```

22434 \cs_new_protected:Npn \__regex_match_loop:
22435 {
22436   \int_add:Nn \l__regex_step_int { 2 }
22437   \int_incr:N \l__regex_curr_pos_int
22438   \int_set_eq:NN \l__regex_last_char_int \l__regex_curr_char_int
22439   \int_set_eq:NN \l__regex_case_changed_char_int \c_max_int
22440   \__regex_query_get:
22441   \use:x
22442   {
22443     \int_set_eq:NN \l__regex_max_active_int \l__regex_min_active_int
22444     \int_step_function:nnN
22445       { \l__regex_min_active_int }
22446       { \l__regex_max_active_int - 1 }
22447     \__regex_match_one_active:n
22448   }
22449   \prg_break_point:
22450   \bool_set_false:N \l__regex_fresh_thread_bool
22451   \if_int_compare:w \l__regex_max_active_int > \l__regex_min_active_int
22452     \if_int_compare:w \l__regex_curr_pos_int < \l__regex_max_pos_int
22453       \exp_after:wN \exp_after:wN \exp_after:wN \__regex_match_loop:
22454     \fi:
22455   \fi:
22456 }
22457 \cs_new:Npn \__regex_match_one_active:n #1
22458 {
22459   \__regex_use_state_and_submatches:nn
22460     { \__kernel_intarray_item:Nn \g__regex_thread_state_intarray {#1} }
22461     { \__regex_toks_use:w #1 }
22462 }

```

(End definition for `__regex_match_loop:` and `__regex_match_one_active:n`.)

`__regex_query_set:nnn` The arguments are: tokens that `o` and `x` expand to one token of the query, the catcode, and the character code. Store those, and the current brace balance (used later to check for overall brace balance) in a `\toks` register and some arrays, then update the `balance`.

```

22463 \cs_new_protected:Npn \__regex_query_set:nnn #1#2#3
22464 {
22465   \__kernel_intarray_gset:Nnn \g__regex_charcode_intarray
22466     { \l__regex_curr_pos_int } {#3}
22467   \__kernel_intarray_gset:Nnn \g__regex_catcode_intarray
22468     { \l__regex_curr_pos_int } {#2}
22469   \__kernel_intarray_gset:Nnn \g__regex_balance_intarray
22470     { \l__regex_curr_pos_int } { \l__regex_balance_int }
22471   \__regex_toks_set:Nn \l__regex_curr_pos_int {#1}
22472   \int_incr:N \l__regex_curr_pos_int

```

```

22473     \if_case:w #2 \exp_stop_f:
22474     \or: \int_incr:N \l__regex_balance_int
22475     \or: \int_decr:N \l__regex_balance_int
22476     \fi:
22477 }

```

(End definition for __regex_query_set:nnn.)

__regex_query_get: Extract the current character and category codes at the current position from the appropriate arrays.

```

22478 \cs_new_protected:Npn \__regex_query_get:
22479 {
22480     \l__regex_curr_char_int
22481     = \__kernel_intarray_item:Nn \g__regex_charcode_intarray
22482       { \l__regex_curr_pos_int } \scan_stop:
22483     \l__regex_curr_catcode_int
22484     = \__kernel_intarray_item:Nn \g__regex_catcode_intarray
22485       { \l__regex_curr_pos_int } \scan_stop:
22486 }

```

(End definition for __regex_query_get:.)

38.5.3 Using states of the nfa

__regex_use_state: Use the current NFA instruction. The state is initially marked as belonging to the current **step**: this allows normal free transition to repeat, but group-repeating transitions won't. Once we are done exploring all the branches it spawned, the state is marked as **step + 1**: any thread hitting it at that point will be terminated.

```

22487 \__kernel_patch:nnNNpn
22488 {
22489     \__regex_trace:nnx { regex } { 2 }
22490     { state~\int_use:N \l__regex_curr_state_int }
22491 }
22492 { }
22493 \cs_new_protected:Npn \__regex_use_state:
22494 {
22495     \__kernel_intarray_gset:Nnn \g__regex_state_active_intarray
22496       { \l__regex_curr_state_int } { \l__regex_step_int }
22497     \__regex_toks_use:w \l__regex_curr_state_int
22498     \__kernel_intarray_gset:Nnn \g__regex_state_active_intarray
22499       { \l__regex_curr_state_int }
22500       { \int_eval:n { \l__regex_step_int + 1 } }
22501 }

```

(End definition for __regex_use_state:.)

__regex_use_state_and_submatches:nn This function is called as one item in the array of active threads after that array has been unpacked for a new step. Update the **current_state** and **current_submatches** and use the state if it has not yet been encountered at this step.

```

22502 \cs_new_protected:Npn \__regex_use_state_and_submatches:nn #1 #2
22503 {
22504     \int_set:Nn \l__regex_curr_state_int {#1}
22505     \if_int_compare:w
22506         \__kernel_intarray_item:Nn \g__regex_state_active_intarray

```

```

22507         { \l__regex_curr_state_int }
22508             < \l__regex_step_int
22509         \tl_set:Nn \l__regex_curr_submatches_prop {#2}
22510         \exp_after:wN \__regex_use_state:
22511     \fi:
22512     \scan_stop:
22513 }

```

(End definition for __regex_use_state_and_submatches:nn.)

38.5.4 Actions when matching

__regex_action_start_wildcard: For an unanchored match, state 0 has a free transition to the next and a costly one to itself, to repeat at the next position. To catch repeated identical empty matches, we need to know if a successful thread corresponds to an empty match. The instruction resetting \l__regex_fresh_thread_bool may be skipped by a successful thread, hence we had to add it to __regex_match_loop: too.

```

22514 \cs_new_protected:Npn \__regex_action_start_wildcard:
22515 {
22516     \bool_set_true:N \l__regex_fresh_thread_bool
22517     \__regex_action_free:n {1}
22518     \bool_set_false:N \l__regex_fresh_thread_bool
22519     \__regex_action_cost:n {0}
22520 }

```

(End definition for __regex_action_start_wildcard:.)

```

\__regex_action_free:n
\__regex_action_free_group:n
\__regex_action_free_aux:nn

```

These functions copy a thread after checking that the NFA state has not already been used at this position. If not, store submatches in the new state, and insert the instructions for that state in the input stream. Then restore the old value of \l__regex_curr_state_int and of the current submatches. The two types of free transitions differ by how they test that the state has not been encountered yet: the **group** version is stricter, and will not use a state if it was used earlier in the current thread, hence forcefully breaking the loop, while the “normal” version will revisit a state even within the thread itself.

```

22521 \cs_new_protected:Npn \__regex_action_free:n
22522 { \__regex_action_free_aux:nn { > \l__regex_step_int \else: } }
22523 \cs_new_protected:Npn \__regex_action_free_group:n
22524 { \__regex_action_free_aux:nn { < \l__regex_step_int } }
22525 \cs_new_protected:Npn \__regex_action_free_aux:nn #1#2
22526 {
22527     \use:x
22528     {
22529         \int_add:Nn \l__regex_curr_state_int {#2}
22530         \exp_not:n
22531         {
22532             \if_int_compare:w
22533                 \__kernel_intarray_item:Nn \g__regex_state_active_intarray
22534                 { \l__regex_curr_state_int }
22535                 #1
22536                 \exp_after:wN \__regex_use_state:
22537             \fi:
22538         }
22539         \int_set:Nn \l__regex_curr_state_int

```

```

22540         { \int_use:N \l__regex_curr_state_int }
22541         \tl_set:Nn \exp_not:N \l__regex_curr_submatches_prop
22542         { \exp_not:o \l__regex_curr_submatches_prop }
22543     }
22544 }

```

(End definition for __regex_action_free:n, __regex_action_free_group:n, and __regex_action_free_aux:nn.)

__regex_action_cost:n A transition which consumes the current character and shifts the state by #1. The resulting state is stored in the appropriate array for use at the next position, and we also store the current submatches.

```

22545 \cs_new_protected:Npn \__regex_action_cost:n #1
22546 {
22547     \exp_args:Nx \__regex_store_state:n
22548     { \int_eval:n { \l__regex_curr_state_int + #1 } }
22549 }

```

(End definition for __regex_action_cost:n.)

__regex_store_state:n Put the given state in \g__regex_thread_state_intarray, and increment the length of the array. Also store the current submatch in the appropriate \toks.

```

22550 \cs_new_protected:Npn \__regex_store_state:n #1
22551 {
22552     \__regex_store_submatches:
22553     \__kernel_intarray_gset:Nnn \g__regex_thread_state_intarray
22554     { \l__regex_max_active_int } {#1}
22555     \int_incr:N \l__regex_max_active_int
22556 }
22557 \cs_new_protected:Npn \__regex_store_submatches:
22558 {
22559     \__regex_toks_set:No \l__regex_max_active_int
22560     { \l__regex_curr_submatches_prop }
22561 }

```

(End definition for __regex_store_state:n and __regex_store_submatches:.)

__regex_disable_submatches: Some user functions don't require tracking submatches. We get a performance improvement by simply defining the relevant functions to remove their argument and do nothing with it.

```

22562 \cs_new_protected:Npn \__regex_disable_submatches:
22563 {
22564     \cs_set_protected:Npn \__regex_store_submatches: { }
22565     \cs_set_protected:Npn \__regex_action_submatch:n ##1 { }
22566 }

```

(End definition for __regex_disable_submatches:.)

__regex_action_submatch:n Update the current submatches with the information from the current position. Maybe a bottleneck.

```

22567 \cs_new_protected:Npn \__regex_action_submatch:n #1
22568 {
22569     \prop_put:Nno \l__regex_curr_submatches_prop {#1}
22570     { \int_use:N \l__regex_curr_pos_int }
22571 }

```

(End definition for `_regex_action_submatch:n`.)

`_regex_action_success:` There is a successful match when an execution path reaches the last state in the NFA, unless this marks a second identical empty match. Then mark that there was a successful match; it is empty if it is “fresh”; and we store the current position and submatches. The current step is then interrupted with `\prg_break:`, and only paths with higher precedence are pursued further. The values stored here may be overwritten by a later success of a path with higher precedence.

```

22572 \cs_new_protected:Npn \_regex_action_success:
22573 {
22574   \_regex_if_two_empty_matches:F
22575   {
22576     \bool_set_true:N \l__regex_match_success_bool
22577     \bool_set_eq:NN \l__regex_empty_success_bool
22578     \l__regex_fresh_thread_bool
22579     \int_set_eq:NN \l__regex_success_pos_int \l__regex_curr_pos_int
22580     \prop_set_eq:NN \l__regex_success_submatches_prop
22581     \l__regex_curr_submatches_prop
22582     \prg_break:
22583   }
22584 }
```

(End definition for `_regex_action_success:.`)

38.6 Replacement

38.6.1 Variables and helpers used in replacement

`\l__regex_replacement_csnames_int` The behaviour of closing braces inside a replacement text depends on whether a sequences `\c{` or `\u{` has been encountered. The number of “open” such sequences that should be closed by `}` is stored in `\l__regex_replacement_csnames_int`, and decreased by 1 by each `}`.

```

22585 \int_new:N \l__regex_replacement_csnames_int
```

(End definition for `\l__regex_replacement_csnames_int`.)

`\l__regex_replacement_category_tl` This sequence of letters is used to correctly restore categories in nested constructions such as `\cL(abc\cD(_)d)`.

```

22586 \tl_new:N \l__regex_replacement_category_tl
22587 \seq_new:N \l__regex_replacement_category_seq
```

(End definition for `\l__regex_replacement_category_tl` and `\l__regex_replacement_category_seq`.)

`\l__regex_balance_tl` This token list holds the replacement text for `_regex_replacement_balance_one_match:n` while it is being built incrementally.

```

22588 \tl_new:N \l__regex_balance_tl
```

(End definition for `\l__regex_balance_tl`.)

`_regex_replacement_balance_one_match:n` This expects as an argument the first index of a set of entries in `\g__regex_submatch_begin_intarray` (and related arrays) which hold the submatch information for a given match. It can be used within an integer expression to obtain the brace balance incurred by performing the replacement on that match. This combines the braces lost by removing the match, braces added by all the submatches appearing in the replacement, and braces

appearing explicitly in the replacement. Even though it is always redefined before use, we initialize it as for an empty replacement. An important property is that concatenating several calls to that function must result in a valid integer expression (hence a leading + in the actual definition).

```
22589 \cs_new:Npn \__regex_replacement_balance_one_match:n #1
22590 { - \__regex_submatch_balance:n {#1} }
```

(End definition for __regex_replacement_balance_one_match:n.)

__regex_replacement_do_one_match:n

The input is the same as __regex_replacement_balance_one_match:n. This function is redefined to expand to the part of the token list from the end of the previous match to a given match, followed by the replacement text. Hence concatenating the result of this function with all possible arguments (one call for each match), as well as the range from the end of the last match to the end of the string, produces the fully replaced token list. The initialization does not matter, but (as an example) we set it as for an empty replacement.

```
22591 \cs_new:Npn \__regex_replacement_do_one_match:n #1
22592 {
22593   \__regex_query_range:nn
22594   { \__kernel_intarray_item:Nn \g__regex_submatch_prev_intarray {#1} }
22595   { \__kernel_intarray_item:Nn \g__regex_submatch_begin_intarray {#1} }
22596 }
```

(End definition for __regex_replacement_do_one_match:n.)

__regex_replacement_exp_not:N

This function lets us navigate around the fact that the primitive \exp_not:n requires a braced argument. As far as I can tell, it is only needed if the user tries to include in the replacement text a control sequence set equal to a macro parameter character, such as \c_parameter_token. Indeed, within an x-expanding assignment, \exp_not:N # behaves as a single #, whereas \exp_not:n {#} behaves as a doubled ##.

```
22597 \cs_new:Npn \__regex_replacement_exp_not:N #1 { \exp_not:n {#1} }
```

(End definition for __regex_replacement_exp_not:N.)

38.6.2 Query and brace balance

__regex_query_range:nn
__regex_query_range_loop:ww

When it is time to extract submatches from the token list, the various tokens are stored in \toks registers numbered from \l__regex_min_pos_int inclusive to \l__regex_max_pos_int exclusive. The function __regex_query_range:nn {<min>} {<max>} unpacks registers from the position <min> to the position <max> - 1 included. Once this is expanded, a second x-expansion results in the actual tokens from the query. That second expansion is only done by user functions at the very end of their operation, after checking (and correcting) the brace balance first.

```
22598 \cs_new:Npn \__regex_query_range:nn #1#2
22599 {
22600   \exp_after:wN \__regex_query_range_loop:ww
22601   \int_value:w \__regex_int_eval:w #1 \exp_after:wN ;
22602   \int_value:w \__regex_int_eval:w #2 ;
22603   \prg_break_point:
22604 }
22605 \cs_new:Npn \__regex_query_range_loop:ww #1 ; #2 ;
22606 {
22607   \if_int_compare:w #1 < #2 \exp_stop_f:
```

```

22608 \else:
22609 \exp_after:wN \prg_break:
22610 \fi:
22611 \__regex_toks_use:w #1 \exp_stop_f:
22612 \exp_after:wN \__regex_query_range_loop:ww
22613 \int_value:w \__regex_int_eval:w #1 + 1 ; #2 ;
22614 }

```

(End definition for __regex_query_range:nn and __regex_query_range_loop:ww.)

__regex_query_submatch:n Find the start and end positions for a given submatch (of a given match).

```

22615 \cs_new:Npn \__regex_query_submatch:n #1
22616 {
22617 \__regex_query_range:nn
22618 { \__kernel_intarray_item:Nn \g__regex_submatch_begin_intarray {#1} }
22619 { \__kernel_intarray_item:Nn \g__regex_submatch_end_intarray {#1} }
22620 }

```

(End definition for __regex_query_submatch:n.)

__regex_submatch_balance:n Every user function must result in a balanced token list (unbalanced token lists cannot be stored by TeX). When we unpacked the query, we kept track of the brace balance, hence the contribution from a given range is the difference between the brace balances at the $\langle \text{max pos} \rangle$ and $\langle \text{min pos} \rangle$. These two positions are found in the corresponding “submatch” arrays.

```

22621 \cs_new_protected:Npn \__regex_submatch_balance:n #1
22622 {
22623 \int_eval:n
22624 {
22625 \int_compare:nNnTF
22626 {
22627 \__kernel_intarray_item:Nn
22628 \g__regex_submatch_end_intarray {#1}
22629 }
22630 = 0
22631 { 0 }
22632 {
22633 \__kernel_intarray_item:Nn \g__regex_balance_intarray
22634 {
22635 \__kernel_intarray_item:Nn
22636 \g__regex_submatch_end_intarray {#1}
22637 }
22638 }
22639 -
22640 \int_compare:nNnTF
22641 {
22642 \__kernel_intarray_item:Nn
22643 \g__regex_submatch_begin_intarray {#1}
22644 }
22645 = 0
22646 { 0 }
22647 {
22648 \__kernel_intarray_item:Nn \g__regex_balance_intarray
22649 {

```

```

22650         \__kernel_intarray_item:Nn
22651         \g__regex_submatch_begin_intarray {#1}
22652     }
22653 }
22654 }
22655 }

```

(End definition for __regex_submatch_balance:n.)

38.6.3 Framework

```

\__regex_replacement:n
\__regex_replacement_aux:n

```

The replacement text is built incrementally. We keep track in \l__regex_balance_int of the balance of explicit begin- and end-group tokens and we store in \l__regex_balance_tl some code to compute the brace balance from submatches (see its description). Detect unescaped right braces, and escaped characters, with trailing \prg_do_nothing: because some of the later function look-ahead. Once the whole replacement text has been parsed, make sure that there is no open csname. Finally, define the balance_one_match and do_one_match functions.

```

22656 \__kernel_patch:nnNNpn
22657 { \__regex_trace_push:nnN { regex } { 1 } \__regex_replacement:n }
22658 { \__regex_trace_pop:nnN { regex } { 1 } \__regex_replacement:n }
22659 \cs_new_protected:Npn \__regex_replacement:n #1
22660 {
22661   \group_begin:
22662     \tl_build_begin:N \l__regex_build_tl
22663     \int_zero:N \l__regex_balance_int
22664     \tl_clear:N \l__regex_balance_tl
22665     \__regex_escape_use:nnnn
22666     {
22667       \if_charcode:w \c_right_brace_str ##1
22668         \__regex_replacement_rbrace:N
22669       \else:
22670         \__regex_replacement_normal:n
22671       \fi:
22672       ##1
22673     }
22674     { \__regex_replacement_escaped:N ##1 }
22675     { \__regex_replacement_normal:n ##1 }
22676     {#1}
22677   \prg_do_nothing: \prg_do_nothing:
22678   \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
22679     \__kernel_msg_error:nnx { kernel } { replacement-missing-rbrace }
22680     { \int_use:N \l__regex_replacement_csnames_int }
22681     \tl_build_put_right:Nx \l__regex_build_tl
22682     { \prg_replicate:nn \l__regex_replacement_csnames_int \cs_end: }
22683   \fi:
22684   \seq_if_empty:NF \l__regex_replacement_category_seq
22685   {
22686     \__kernel_msg_error:nnx { kernel } { replacement-missing-rparen }
22687     { \seq_count:N \l__regex_replacement_category_seq }
22688     \seq_clear:N \l__regex_replacement_category_seq
22689   }
22690   \cs_gset:Npx \__regex_replacement_balance_one_match:n ##1
22691   {

```



```

22692         + \int_use:N \l__regex_balance_int
22693         \l__regex_balance_tl
22694         - \__regex_submatch_balance:n {##1}
22695     }
22696     \tl_build_end:N \l__regex_build_tl
22697     \exp_args:NNo
22698     \group_end:
22699     \__regex_replacement_aux:n \l__regex_build_tl
22700 }
22701 \cs_new_protected:Npn \__regex_replacement_aux:n #1
22702 {
22703     \cs_set:Npn \__regex_replacement_do_one_match:n ##1
22704     {
22705         \__regex_query_range:nn
22706         {
22707             \__kernel_intarray_item:Nn
22708             \g__regex_submatch_prev_intarray {##1}
22709         }
22710         {
22711             \__kernel_intarray_item:Nn
22712             \g__regex_submatch_begin_intarray {##1}
22713         }
22714     }
22715     #1
22716 }

```

(End definition for `__regex_replacement:n` and `__regex_replacement_aux:n`.)

`__regex_replacement_normal:n` Most characters are simply sent to the output by `\tl_build_put_right:Nn`, unless a particular category code has been requested: then `__regex_replacement_c_A:w` or a similar auxiliary is called. One exception is right parentheses, which restore the category code in place before the group started. Note that the sequence is non-empty there: it contains an empty entry corresponding to the initial value of `\l__regex_replacement_category_tl`.

```

22717 \cs_new_protected:Npn \__regex_replacement_normal:n #1
22718 {
22719     \tl_if_empty:NTF \l__regex_replacement_category_tl
22720     { \tl_build_put_right:Nn \l__regex_build_tl {##1} }
22721     { % (
22722         \token_if_eq_charcode:NNTF #1 )
22723         {
22724             \seq_pop:NN \l__regex_replacement_category_seq
22725             \l__regex_replacement_category_tl
22726         }
22727         {
22728             \use:c
22729             {
22730                 __regex_replacement_c_
22731                 \l__regex_replacement_category_tl :w
22732             }
22733             \__regex_replacement_normal:n {##1}
22734         }
22735     }
22736 }

```

(End definition for `_regex_replacement_normal:n`.)

`_regex_replacement_escaped:N` As in parsing a regular expression, we use an auxiliary built from #1 if defined. Otherwise, check for escaped digits (standing from submatches from 0 to 9): anything else is a raw character. We use `\token_to_str:N` to give spaces the right category code.

```

22737 \cs_new_protected:Npn \_regex_replacement_escaped:N #1
22738 {
22739   \cs_if_exist_use:cF { \_regex_replacement_#1:w }
22740   {
22741     \if_int_compare:w 1 < 1#1 \exp_stop_f:
22742     \_regex_replacement_put_submatch:n {#1}
22743   \else:
22744     \exp_args:No \_regex_replacement_normal:n
22745     { \token_to_str:N #1 }
22746   \fi:
22747 }
22748 }
```

(End definition for `_regex_replacement_escaped:N`.)

38.6.4 Submatches

`_regex_replacement_put_submatch:n` Insert a submatch in the replacement text. This is dropped if the submatch number is larger than the number of capturing groups. Unless the submatch appears inside a `\c{...}` or `\u{...}` construction, it must be taken into account in the brace balance. Later on, `##1` will be replaced by a pointer to the 0-th submatch for a given match. There is an `\exp_not:N` here as at the point-of-use of `\l__regex_balance_tl` there is an x-type expansion which is needed to get `##1` in correctly.

```

22749 \cs_new_protected:Npn \_regex_replacement_put_submatch:n #1
22750 {
22751   \if_int_compare:w #1 < \l__regex_capturing_group_int
22752   \tl_build_put_right:Nn \l__regex_build_tl
22753   { \_regex_query_submatch:n { \int_eval:n { #1 + ##1 } } }
22754   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
22755   \tl_put_right:Nn \l__regex_balance_tl
22756   {
22757     + \_regex_submatch_balance:n
22758     { \exp_not:N \int_eval:n { #1 + ##1 } }
22759   }
22760   \fi:
22761 \fi:
22762 }
```

(End definition for `_regex_replacement_put_submatch:n`.)

`__regex_replacement_g:w` Grab digits for the `\g` escape sequence in a primitive assignment to the integer `\l__regex_internal_a_int`. At the end of the run of digits, check that it ends with a right brace.

`_regex_replacement_g_digits:NN`

```

22763 \cs_new_protected:Npn \__regex_replacement_g:w #1#2
22764 {
22765   \__regex_two_if_eq:NNNTF
22766   #1 #2 \_regex_replacement_normal:n \c_left_brace_str
22767   { \l__regex_internal_a_int = \_regex_replacement_g_digits:NN }
```

```

22768     { \_regex_replacement_error:NNN g #1 #2 }
22769   }
22770 \cs_new:Npn \_regex_replacement_g_digits:NN #1#2
22771 {
22772   \token_if_eq_meaning:NNTF #1 \_regex_replacement_normal:n
22773   {
22774     \if_int_compare:w 1 < 1#2 \exp_stop_f:
22775     #2
22776     \exp_after:wN \use_i:nnn
22777     \exp_after:wN \_regex_replacement_g_digits:NN
22778   \else:
22779     \exp_stop_f:
22780     \exp_after:wN \_regex_replacement_error:NNN
22781     \exp_after:wN g
22782   \fi:
22783 }
22784 {
22785   \exp_stop_f:
22786   \if_meaning:w \_regex_replacement_rbrace:N #1
22787   \exp_args:No \_regex_replacement_put_submatch:n
22788   { \int_use:N \l__regex_internal_a_int }
22789   \exp_after:wN \use_none:nn
22790   \else:
22791     \exp_after:wN \_regex_replacement_error:NNN
22792     \exp_after:wN g
22793   \fi:
22794 }
22795 #1 #2
22796 }

```

(End definition for _regex_replacement_g:w and _regex_replacement_g_digits:NN.)

38.6.5 Csnames in replacement

_regex_replacement_c:w \c may only be followed by an unescaped character. If followed by a left brace, start a control sequence by calling an auxiliary common with \u. Otherwise test whether the category is known; if it is not, complain.

```

22797 \cs_new_protected:Npn \_regex_replacement_c:w #1#2
22798 {
22799   \token_if_eq_meaning:NNTF #1 \_regex_replacement_normal:n
22800   {
22801     \exp_after:wN \token_if_eq_charcode:NNTF \c_left_brace_str #2
22802     { \_regex_replacement_cu_aux:Nw \_regex_replacement_exp_not:N }
22803     {
22804       \cs_if_exist:cTF { \_regex_replacement_c_#2:w }
22805       { \_regex_replacement_cat:NNN #2 }
22806       { \_regex_replacement_error:NNN c #1#2 }
22807     }
22808   }
22809   { \_regex_replacement_error:NNN c #1#2 }
22810 }

```

(End definition for _regex_replacement_c:w.)

`_regex_replacement_cu_aux:Nw` Start a control sequence with `\cs:w`, protected from expansion by #1 (either `_regex_replacement_exp_not:N` or `\exp_not:V`), or turned to a string by `\tl_to_str:V` if inside another csname construction `\c` or `\u`. We use `\tl_to_str:V` rather than `\tl_to_str:N` to deal with integers and other registers.

```

22811 \cs_new_protected:Npn \_regex_replacement_cu_aux:Nw #1
22812 {
22813   \if_case:w \l__regex_replacement_csnames_int
22814     \tl_build_put_right:Nn \l__regex_build_tl
22815       { \exp_not:n { \exp_after:wN #1 \cs:w } }
22816   \else:
22817     \tl_build_put_right:Nn \l__regex_build_tl
22818       { \exp_not:n { \exp_after:wN \tl_to_str:V \cs:w } }
22819   \fi:
22820   \int_incr:N \l__regex_replacement_csnames_int
22821 }

```

(End definition for `_regex_replacement_cu_aux:Nw`.)

`_regex_replacement_u:w` Check that `\u` is followed by a left brace. If so, start a control sequence with `\cs:w`, which is then unpacked either with `\exp_not:V` or `\tl_to_str:V` depending on the current context.

```

22822 \cs_new_protected:Npn \_regex_replacement_u:w #1#2
22823 {
22824   \_regex_two_if_eq:NNNTF
22825     #1 #2 \_regex_replacement_normal:n \c_left_brace_str
22826     { \_regex_replacement_cu_aux:Nw \exp_not:V }
22827     { \_regex_replacement_error:NNN u #1#2 }
22828 }

```

(End definition for `_regex_replacement_u:w`.)

`_regex_replacement_rbrace:N` Within a `\c{...}` or `\u{...}` construction, end the control sequence, and decrease the brace count. Otherwise, this is a raw right brace.

```

22829 \cs_new_protected:Npn \_regex_replacement_rbrace:N #1
22830 {
22831   \if_int_compare:w \l__regex_replacement_csnames_int > 0 \exp_stop_f:
22832     \tl_build_put_right:Nn \l__regex_build_tl { \cs_end: }
22833     \int_decr:N \l__regex_replacement_csnames_int
22834   \else:
22835     \_regex_replacement_normal:n {#1}
22836   \fi:
22837 }

```

(End definition for `_regex_replacement_rbrace:N`.)

38.6.6 Characters in replacement

`_regex_replacement_cat:NNN` Here, #1 is a letter among BEMTPUDSLOA and #2#3 denote the next character. Complain if we reach the end of the replacement or if the construction appears inside `\c{...}` or `\u{...}`, and detect the case of a parenthesis. In that case, store the current category in a sequence and switch to a new one.

```

22838 \cs_new_protected:Npn \_regex_replacement_cat:NNN #1#2#3
22839 {

```

```

22840 \token_if_eq_meaning:NNTF \prg_do_nothing: #3
22841 { \__kernel_msg_error:nn { kernel } { replacement-catcode-end } }
22842 {
22843   \int_compare:nNnTF { \l__regex_replacement_csnames_int } > 0
22844   {
22845     \__kernel_msg_error:nnnn
22846     { kernel } { replacement-catcode-in-cs } {#1} {#3}
22847     #2 #3
22848   }
22849   {
22850     \__regex_two_if_eq:NNNNTF #2 #3 \__regex_replacement_normal:n (
22851     {
22852       \seq_push:NV \l__regex_replacement_category_seq
22853       \l__regex_replacement_category_tl
22854       \tl_set:Nn \l__regex_replacement_category_tl {#1}
22855     }
22856     {
22857       \token_if_eq_meaning:NNT #2 \__regex_replacement_escaped:N
22858       {
22859         \__regex_char_if_alphanumeric:NNTF #3
22860         {
22861           \__kernel_msg_error:nnnn
22862           { kernel } { replacement-catcode-escaped }
22863           {#1} {#3}
22864         }
22865         { }
22866       }
22867       \use:c { __regex_replacement_c_#1:w } #2 #3
22868     }
22869   }
22870 }
22871 }

```

(End definition for `__regex_replacement_cat:NNN`.)

We now need to change the category code of the null character many times, hence work in a group. The catcode-specific macros below are defined in alphabetical order; if you are trying to understand the code, start from the end of the alphabet as those categories are simpler than active or begin-group.

```

22872 \group_begin:

```

`__regex_replacement_char:nnN` The only way to produce an arbitrary character–catcode pair is to use the `\lowercase` or `\uppercase` primitives. This is a wrapper for our purposes. The first argument is the null character with various catcodes. The second and third arguments are grabbed from the input stream: `#3` is the character whose character code to reproduce. We could use `\char_generate:nn` but only for some catcodes (active characters and spaces are not supported).

```

22873 \cs_new_protected:Npn \__regex_replacement_char:nnN #1#2#3
22874 {
22875   \tex_lccode:D 0 = '#3 \scan_stop:
22876   \tex_lowercase:D { \tl_build_put_right:Nn \l__regex_build_tl {#1} }
22877 }

```

(End definition for `__regex_replacement_char:nnN`.)

`__regex_replacement_c_A:w` For an active character, expansion must be avoided, twice because we later do two x-expansions, to unpack `\toks` for the query, and to expand their contents to tokens of the query.

```
22878 \char_set_catcode_active:N \^^@
22879 \cs_new_protected:Npn \__regex_replacement_c_A:w
22880 { \__regex_replacement_char:nNN { \exp_not:n { \exp_not:N \^^@ } } }
```

(End definition for `__regex_replacement_c_A:w`.)

`__regex_replacement_c_B:w` An explicit begin-group token increases the balance, unless within a `\c{...}` or `\u{...}` construction. Add the desired begin-group character, using the standard `\if_false:` trick. We eventually x-expand twice. The first time must yield a balanced token list, and the second one gives the bare begin-group token. The `\exp_after:wN` is not strictly needed, but is more consistent with l3tl-analysis.

```
22881 \char_set_catcode_group_begin:N \^^@
22882 \cs_new_protected:Npn \__regex_replacement_c_B:w
22883 {
22884   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
22885     \int_incr:N \l__regex_balance_int
22886   \fi:
22887   \__regex_replacement_char:nNN
22888     { \exp_not:n { \exp_after:wN \^^@ \if_false: } \fi: } }
22889 }
```

(End definition for `__regex_replacement_c_B:w`.)

`__regex_replacement_c_C:w` This is not quite catcode-related: when the user requests a character with category “control sequence”, the one-character control symbol is returned. As for the active character, we prepare for two x-expansions.

```
22890 \cs_new_protected:Npn \__regex_replacement_c_C:w #1#2
22891 {
22892   \tl_build_put_right:Nn \l__regex_build_tl
22893     { \exp_not:N \exp_not:N \exp_not:c {#2} }
22894 }
```

(End definition for `__regex_replacement_c_C:w`.)

`__regex_replacement_c_D:w` Subscripts fit the mould: `\lowercase` the null byte with the correct category.

```
22895 \char_set_catcode_math_subscript:N \^^@
22896 \cs_new_protected:Npn \__regex_replacement_c_D:w
22897 { \__regex_replacement_char:nNN { \^^@ } }
```

(End definition for `__regex_replacement_c_D:w`.)

`__regex_replacement_c_E:w` Similar to the begin-group case, the second x-expansion produces the bare end-group token.

```
22898 \char_set_catcode_group_end:N \^^@
22899 \cs_new_protected:Npn \__regex_replacement_c_E:w
22900 {
22901   \if_int_compare:w \l__regex_replacement_csnames_int = 0 \exp_stop_f:
22902     \int_decr:N \l__regex_balance_int
22903   \fi:
22904   \__regex_replacement_char:nNN
22905     { \exp_not:n { \if_false: { \fi: \^^@ } } }
22906 }
```

(End definition for `_regex_replacement_c_E:w`.)

`_regex_replacement_c_L:w` Simply `\lowercase` a letter null byte to produce an arbitrary letter.

```
22907 \char_set_catcode_letter:N \^^@
22908 \cs_new_protected:Npn \_regex_replacement_c_L:w
22909 { \_regex_replacement_char:nNN { ^^@ } }
```

(End definition for `_regex_replacement_c_L:w`.)

`_regex_replacement_c_M:w` No surprise here, we lowercase the null math toggle.

```
22910 \char_set_catcode_math_toggle:N \^^@
22911 \cs_new_protected:Npn \_regex_replacement_c_M:w
22912 { \_regex_replacement_char:nNN { ^^@ } }
```

(End definition for `_regex_replacement_c_M:w`.)

`_regex_replacement_c_O:w` Lowercase an other null byte.

```
22913 \char_set_catcode_other:N \^^@
22914 \cs_new_protected:Npn \_regex_replacement_c_O:w
22915 { \_regex_replacement_char:nNN { ^^@ } }
```

(End definition for `_regex_replacement_c_O:w`.)

`_regex_replacement_c_P:w` For macro parameters, expansion is a tricky issue. We need to prepare for two x-expansions and passing through various macro definitions. Note that we cannot replace one `\exp_not:n` by doubling the macro parameter characters because this would misbehave if a mischievous user asks for `\c{cP\#}`, since that macro parameter character would be doubled.

```
22916 \char_set_catcode_parameter:N \^^@
22917 \cs_new_protected:Npn \_regex_replacement_c_P:w
22918 {
22919   \_regex_replacement_char:nNN
22920   { \exp_not:n { \exp_not:n { ^^@^^@^^@^^@ } } }
22921 }
```

(End definition for `_regex_replacement_c_P:w`.)

`_regex_replacement_c_S:w` Spaces are normalized on input by \TeX to have character code 32. It is in fact impossible to get a token with character code 0 and category code 10. Hence we use 32 instead of 0 as our base character.

```
22922 \cs_new_protected:Npn \_regex_replacement_c_S:w #1#2
22923 {
22924   \if_int_compare:w '#2 = 0 \exp_stop_f:
22925   \_kernel_msg_error:nn { kernel } { replacement-null-space }
22926   \fi:
22927   \tex_lccode:D '\ = '#2 \scan_stop:
22928   \tex_lowercase:D { \tl_build_put_right:Nn \l__regex_build_tl {~} }
22929 }
```

(End definition for `_regex_replacement_c_S:w`.)

`_regex_replacement_c_T:w` No surprise for alignment tabs here. Those are surrounded by the appropriate braces whenever necessary, hence they don't cause trouble in alignment settings.

```
22930 \char_set_catcode_alignment:N \^^@
22931 \cs_new_protected:Npn \_regex_replacement_c_T:w
22932 { \_regex_replacement_char:nNN { ^^@ } }
```

(End definition for `_regex_replacement_c_T:w`.)

`_regex_replacement_c_U:w` Simple call to `_regex_replacement_char:nNN` which lowercases the math superscript `^^@`.

```
22933 \char_set_catcode_math_superscript:N \^^@
22934 \cs_new_protected:Npn \_regex_replacement_c_U:w
22935 { \_regex_replacement_char:nNN { ^^@ } }
```

(End definition for `_regex_replacement_c_U:w`.)

Restore the catcode of the null byte.

```
22936 \group_end:
```

38.6.7 An error

`_regex_replacement_error:NNN` Simple error reporting by calling one of the messages `replacement-c`, `replacement-g`, or `replacement-u`.

```
22937 \cs_new_protected:Npn \_regex_replacement_error:NNN #1#2#3
22938 {
22939     \__kernel_msg_error:nxx { kernel } { replacement-#1 } {#3}
22940     #2 #3
22941 }
```

(End definition for `_regex_replacement_error:NNN`.)

38.7 User functions

`\regex_new:N` Before being assigned a sensible value, a regex variable matches nothing.

```
22942 \cs_new_protected:Npn \regex_new:N #1
22943 { \cs_new_eq:NN #1 \c__regex_no_match_regex }
```

(End definition for `\regex_new:N`. This function is documented on page 214.)

`\l_tmpa_regex` The usual scratch space.

```
22944 \regex_new:N \l_tmpa_regex
22945 \regex_new:N \l_tmpb_regex
22946 \regex_new:N \g_tmpa_regex
22947 \regex_new:N \g_tmpb_regex
```

(End definition for `\l_tmpa_regex` and others. These variables are documented on page 216.)

`\regex_set:Nn` Compile, then store the result in the user variable with the appropriate assignment function.
`\regex_gset:Nn`
`\regex_const:Nn`

```
22948 \cs_new_protected:Npn \regex_set:Nn #1#2
22949 {
22950     \__regex_compile:n {#2}
22951     \tl_set_eq:NN #1 \l__regex_internal_regex
22952 }
22953 \cs_new_protected:Npn \regex_gset:Nn #1#2
22954 {
22955     \__regex_compile:n {#2}
22956     \tl_gset_eq:NN #1 \l__regex_internal_regex
22957 }
22958 \cs_new_protected:Npn \regex_const:Nn #1#2
22959 {
```



```

22960     \__regex_compile:n {#2}
22961     \tl_const:Nx #1 { \exp_not:o \l__regex_internal_regex }
22962 }

```

(End definition for `\regex_set:Nn`, `\regex_gset:Nn`, and `\regex_const:Nn`. These functions are documented on page 214.)

\regex_show:N User functions: the `n` variant requires compilation first. Then show the variable with
\regex_show:n some appropriate text. The auxiliary is defined in a different section.

```

22963 \cs_new_protected:Npn \regex_show:n #1
22964 {
22965     \__regex_compile:n {#1}
22966     \__regex_show:N \l__regex_internal_regex
22967     \msg_show:nnxxxx { LaTeX / kernel } { show-regex }
22968     { \tl_to_str:n {#1} } { }
22969     { \l__regex_internal_a_tl } { }
22970 }
22971 \cs_new_protected:Npn \regex_show:N #1
22972 {
22973     \__kernel_chk_defined:NT #1
22974     {
22975         \__regex_show:N #1
22976         \msg_show:nnxxxx { LaTeX / kernel } { show-regex }
22977         { } { \token_to_str:N #1 }
22978         { \l__regex_internal_a_tl } { }
22979     }
22980 }

```

(End definition for `\regex_show:N` and `\regex_show:n`. These functions are documented on page 214.)

\regex_match:nnTF Those conditionals are based on a common auxiliary defined later. Its first argument
\regex_match:NnTF builds the NFA corresponding to the regex, and the second argument is the query token
list. Once we have performed the match, convert the resulting boolean to `\prg_return_`
`true:` or `false`.

```

22981 \prg_new_protected_conditional:Npnn \regex_match:nn #1#2 { T , F , TF }
22982 {
22983     \__regex_if_match:nn { \__regex_build:n {#1} } {#2}
22984     \__regex_return:
22985 }
22986 \prg_new_protected_conditional:Npnn \regex_match:Nn #1#2 { T , F , TF }
22987 {
22988     \__regex_if_match:nn { \__regex_build:N #1 } {#2}
22989     \__regex_return:
22990 }

```

(End definition for `\regex_match:nnTF` and `\regex_match:NnTF`. These functions are documented on page 214.)

\regex_count:nnN Again, use an auxiliary whose first argument builds the NFA.
\regex_count:NnN

```

22991 \cs_new_protected:Npn \regex_count:nnN #1
22992 { \__regex_count:nnN { \__regex_build:n {#1} } }
22993 \cs_new_protected:Npn \regex_count:NnN #1
22994 { \__regex_count:nnN { \__regex_build:N #1 } }

```

(End definition for `\regex_count:nnN` and `\regex_count:NnN`. These functions are documented on page 215.)

```

\regex_extract_once:nnN
\regex_extract_once:nnNTF
\regex_extract_once:NnN
\regex_extract_once:NnNTF
\regex_extract_all:nnN
\regex_extract_all:nnNTF
\regex_extract_all:NnN
\regex_extract_all:NnNTF
\regex_replace_once:nnN
\regex_replace_once:nnNTF
\regex_replace_once:NnN
\regex_replace_once:NnNTF
\regex_replace_all:nnN
\regex_replace_all:nnNTF
\regex_replace_all:NnN
\regex_replace_all:NnNTF
\regex_split:nnN
\regex_split:nnNTF
\regex_split:NnN
\regex_split:NnNTF

```

We define here 40 user functions, following a common pattern in terms of :nnN auxiliaries, defined in the coming subsections. The auxiliary is handed __regex_build:n or __-regex_build:N with the appropriate regex argument, then all other necessary arguments (replacement text, token list, etc. The conditionals call __regex_return: to return either true or false once matching has been performed.

```

22995 \cs_set_protected:Npn \__regex_tmp:w #1#2#3
22996 {
22997   \cs_new_protected:Npn #2 ##1 { #1 { \__regex_build:n {##1} } }
22998   \cs_new_protected:Npn #3 ##1 { #1 { \__regex_build:N ##1 } }
22999   \prg_new_protected_conditional:Npnn #2 ##1##2##3 { T , F , TF }
23000     { #1 { \__regex_build:n {##1} } {##2} ##3 \__regex_return: }
23001   \prg_new_protected_conditional:Npnn #3 ##1##2##3 { T , F , TF }
23002     { #1 { \__regex_build:N ##1 } {##2} ##3 \__regex_return: }
23003 }
23004 \__regex_tmp:w \__regex_extract_once:nnN
23005 \regex_extract_once:nnN \regex_extract_once:NnN
23006 \__regex_tmp:w \__regex_extract_all:nnN
23007 \regex_extract_all:nnN \regex_extract_all:NnN
23008 \__regex_tmp:w \__regex_replace_once:nnN
23009 \regex_replace_once:nnN \regex_replace_once:NnN
23010 \__regex_tmp:w \__regex_replace_all:nnN
23011 \regex_replace_all:nnN \regex_replace_all:NnN
23012 \__regex_tmp:w \__regex_split:nnN \regex_split:nnN \regex_split:NnN

```

(End definition for \regex_extract_once:nnNTF and others. These functions are documented on page 215.)

38.7.1 Variables and helpers for user functions

\l__regex_match_count_int The number of matches found so far is stored in \l__regex_match_count_int. This is only used in the \regex_count:nnN functions.

```
23013 \int_new:N \l__regex_match_count_int
```

(End definition for \l__regex_match_count_int.)

__regex_begin Those flags are raised to indicate extra begin-group or end-group tokens when extracting submatches.

```
23014 \flag_new:n { __regex_begin }
23015 \flag_new:n { __regex_end }
```

(End definition for __regex_begin and __regex_end.)

\l__regex_min_submatch_int The end-points of each submatch are stored in two arrays whose index *<submatch>* ranges from \l__regex_min_submatch_int (inclusive) to \l__regex_submatch_int (exclusive). Each successful match comes with a 0-th submatch (the full match), and one match for each capturing group: submatches corresponding to the last successful match are labelled starting at zeroth_submatch. The entry \l__regex_zeroth_submatch_int in \g__regex_submatch_prev_intarray holds the position at which that match attempt started: this is used for splitting and replacements.

```
23016 \int_new:N \l__regex_min_submatch_int
23017 \int_new:N \l__regex_submatch_int
23018 \int_new:N \l__regex_zeroth_submatch_int
```

(End definition for `\l__regex_min_submatch_int`, `\l__regex_submatch_int`, and `\l__regex_zeroth_submatch_int`.)

`\g__regex_submatch_prev_intarray` Hold the place where the match attempt begun and the end-points of each submatch.
`\g__regex_submatch_begin_intarray` 23019 `\intarray_new:Nn \g__regex_submatch_prev_intarray { 65536 }`
`\g__regex_submatch_end_intarray` 23020 `\intarray_new:Nn \g__regex_submatch_begin_intarray { 65536 }`
23021 `\intarray_new:Nn \g__regex_submatch_end_intarray { 65536 }`

(End definition for `\g__regex_submatch_prev_intarray`, `\g__regex_submatch_begin_intarray`, and `\g__regex_submatch_end_intarray`.)

`__regex_return:` This function triggers either `\prg_return_false:` or `\prg_return_true:` as appropriate to whether a match was found or not. It is used by all user conditionals.

```
23022 \cs_new_protected:Npn \__regex_return:
23023 {
23024   \if_meaning:w \c_true_bool \g__regex_success_bool
23025     \prg_return_true:
23026   \else:
23027     \prg_return_false:
23028   \fi:
23029 }
```

(End definition for `__regex_return:`.)

38.7.2 Matching

`__regex_if_match:nn` We don't track submatches, and stop after a single match. Build the NFA with #1, and perform the match on the query #2.

```
23030 \cs_new_protected:Npn \__regex_if_match:nn #1#2
23031 {
23032   \group_begin:
23033     \__regex_disable_submatches:
23034     \__regex_single_match:
23035     #1
23036     \__regex_match:n {#2}
23037   \group_end:
23038 }
```

(End definition for `__regex_if_match:nn`.)

`__regex_count:nnN` Again, we don't care about submatches. Instead of aborting after the first "longest match" is found, we search for multiple matches, incrementing `\l__regex_match_count_int` every time to record the number of matches. Build the NFA and match. At the end, store the result in the user's variable.

```
23039 \cs_new_protected:Npn \__regex_count:nnN #1#2#3
23040 {
23041   \group_begin:
23042     \__regex_disable_submatches:
23043     \int_zero:N \l__regex_match_count_int
23044     \__regex_multi_match:n { \int_incr:N \l__regex_match_count_int }
23045     #1
23046     \__regex_match:n {#2}
23047     \exp_args:NNNo
23048   \group_end:
23049   \int_set:Nn #3 { \int_use:N \l__regex_match_count_int }
23050 }
```

(End definition for `_regex_count:nnN`.)

38.7.3 Extracting submatches

`_regex_extract_once:nnN` Match once or multiple times. After each match (or after the only match), extract the submatches using `_regex_extract:.` At the end, store the sequence containing all the submatches into the user variable `#3` after closing the group.

```

23051 \cs_new_protected:Npn \_regex_extract_once:nnN #1#2#3
23052 {
23053   \group_begin:
23054     \_regex_single_match:
23055     #1
23056     \_regex_match:n {#2}
23057     \_regex_extract:
23058     \_regex_group_end_extract_seq:N #3
23059   }
23060 \cs_new_protected:Npn \_regex_extract_all:nnN #1#2#3
23061 {
23062   \group_begin:
23063     \_regex_multi_match:n { \_regex_extract: }
23064     #1
23065     \_regex_match:n {#2}
23066     \_regex_group_end_extract_seq:N #3
23067   }

```

(End definition for `_regex_extract_once:nnN` and `_regex_extract_all:nnN`.)

`_regex_split:nnN` Splitting at submatches is a bit more tricky. For each match, extract all submatches, and replace the zeroth submatch by the part of the query between the start of the match attempt and the start of the zeroth submatch. This is inhibited if the delimiter matched an empty token list at the start of this match attempt. After the last match, store the last part of the token list, which ranges from the start of the match attempt to the end of the query. This step is inhibited if the last match was empty and at the very end: decrement `\l__regex_submatch_int`, which controls which matches will be used.

```

23068 \cs_new_protected:Npn \_regex_split:nnN #1#2#3
23069 {
23070   \group_begin:
23071     \_regex_multi_match:n
23072     {
23073       \if_int_compare:w
23074         \l__regex_start_pos_int < \l__regex_success_pos_int
23075         \_regex_extract:
23076         \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
23077         { \l__regex_zeroth_submatch_int } { 0 }
23078         \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray
23079         { \l__regex_zeroth_submatch_int }
23080         {
23081           \__kernel_intarray_item:Nn \g__regex_submatch_begin_intarray
23082           { \l__regex_zeroth_submatch_int }
23083         }
23084         \__kernel_intarray_gset:Nnn \g__regex_submatch_begin_intarray
23085         { \l__regex_zeroth_submatch_int }
23086         { \l__regex_start_pos_int }

```

```

23087         \fi:
23088     }
23089     #1
23090     \__regex_match:n {#2}
23091 (assert)\assert_int:n { \l__regex_curr_pos_int = \l__regex_max_pos_int }
23092     \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
23093     { \l__regex_submatch_int } { 0 }
23094     \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray
23095     { \l__regex_submatch_int }
23096     { \l__regex_max_pos_int }
23097     \__kernel_intarray_gset:Nnn \g__regex_submatch_begin_intarray
23098     { \l__regex_submatch_int }
23099     { \l__regex_start_pos_int }
23100     \int_incr:N \l__regex_submatch_int
23101     \if_meaning:w \c_true_bool \l__regex_empty_success_bool
23102     \if_int_compare:w \l__regex_start_pos_int = \l__regex_max_pos_int
23103     \int_decr:N \l__regex_submatch_int
23104     \fi:
23105     \fi:
23106     \__regex_group_end_extract_seq:N #3
23107 }

```

(End definition for __regex_split:nnN.)

__regex_group_end_extract_seq:N The end-points of submatches are stored as entries of two arrays from \l__regex_min_submatch_int to \l__regex_submatch_int (exclusive). Extract the relevant ranges into \l__regex_internal_a_tl. We detect unbalanced results using the two flags __regex_begin and __regex_end, raised whenever we see too many begin-group or end-group tokens in a submatch.

```

23108 \cs_new_protected:Npn \__regex_group_end_extract_seq:N #1
23109 {
23110     \flag_clear:n { __regex_begin }
23111     \flag_clear:n { __regex_end }
23112     \seq_set_from_function:NnN \l__regex_internal_seq
23113     {
23114         \int_step_function:nnN { \l__regex_min_submatch_int }
23115         { \l__regex_submatch_int - 1 }
23116     }
23117     \__regex_extract_seq_aux:n
23118     \int_compare:nNnF
23119     {
23120         \flag_height:n { __regex_begin } +
23121         \flag_height:n { __regex_end }
23122     }
23123     = 0
23124     {
23125         \__kernel_msg_error:nnxxx { kernel } { result-unbalanced }
23126         { splitting~or~extracting~submatches }
23127         { \flag_height:n { __regex_end } }
23128         { \flag_height:n { __regex_begin } }
23129     }
23130     \seq_set_map:NnN \l__regex_internal_seq \l__regex_internal_seq {##1}
23131     \exp_args:NNNo
23132     \group_end:

```

```

23133     \tl_set:Nn #1 { \l__regex_internal_seq }
23134 }

```

(End definition for `__regex_group_end_extract_seq:N`.)

`__regex_extract_seq_aux:n` The `:n` auxiliary builds one item of the sequence of submatches. First compute the brace balance of the submatch, then extract the submatch from the query, adding the appropriate braces and raising a flag if the submatch is not balanced.

`__regex_extract_seq_aux:ww`

```

23135 \cs_new:Npn \__regex_extract_seq_aux:n #1
23136 {
23137     \exp_after:wN \__regex_extract_seq_aux:ww
23138     \int_value:w \__regex_submatch_balance:n {#1} ; #1;
23139 }
23140 \cs_new:Npn \__regex_extract_seq_aux:ww #1; #2;
23141 {
23142     \if_int_compare:w #1 < 0 \exp_stop_f:
23143         \flag_raise:n { __regex_end }
23144         \prg_replicate:nn {-#1} { \exp_not:n { { \if_false: } \fi: } }
23145     \fi:
23146     \__regex_query_submatch:n {#2}
23147     \if_int_compare:w #1 > 0 \exp_stop_f:
23148         \flag_raise:n { __regex_begin }
23149         \prg_replicate:nn {#1} { \exp_not:n { \if_false: { \fi: } } }
23150     \fi:
23151 }

```

(End definition for `__regex_extract_seq_aux:n` and `__regex_extract_seq_aux:ww`.)

`__regex_extract:`
`__regex_extract_b:wn`
`__regex_extract_e:wn`

Our task here is to extract from the property list `\l__regex_success_submatches_prop` the list of end-points of submatches, and store them in appropriate array entries, from `\l__regex_zeroth_submatch_int` upwards. We begin by emptying those entries. Then for each *<key>*–*<value>* pair in the property list update the appropriate entry. This is somewhat a hack: the *<key>* is a non-negative integer followed by `<` or `>`, which we use in a comparison to `-1`. At the end, store the information about the position at which the match attempt started, in `\g__regex_submatch_prev_intarray`.

```

23152 \cs_new_protected:Npn \__regex_extract:
23153 {
23154     \if_meaning:w \c_true_bool \g__regex_success_bool
23155         \int_set_eq:NN \l__regex_zeroth_submatch_int \l__regex_submatch_int
23156         \prg_replicate:nn \l__regex_capturing_group_int
23157         {
23158             \__kernel_intarray_gset:Nnn \g__regex_submatch_begin_intarray
23159             { \l__regex_submatch_int } { 0 }
23160             \__kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray
23161             { \l__regex_submatch_int } { 0 }
23162             \__kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
23163             { \l__regex_submatch_int } { 0 }
23164             \int_incr:N \l__regex_submatch_int
23165         }
23166     \prop_map_inline:Nn \l__regex_success_submatches_prop
23167     {
23168         \if_int_compare:w ##1 - 1 \exp_stop_f:
23169             \exp_after:wN \__regex_extract_e:wn \int_value:w
23170         \else:

```

```

23171         \exp_after:wN \_regex_extract_b:wn \int_value:w
23172         \fi:
23173         \_regex_int_eval:w \l__regex_zeroth_submatch_int + ##1 {##2}
23174     }
23175     \_kernel_intarray_gset:Nnn \g__regex_submatch_prev_intarray
23176     { \l__regex_zeroth_submatch_int } { \l__regex_start_pos_int }
23177 \fi:
23178 }
23179 \cs_new_protected:Npn \_regex_extract_b:wn #1 < #2
23180 {
23181     \_kernel_intarray_gset:Nnn
23182     \g__regex_submatch_begin_intarray {#1} {#2}
23183 }
23184 \cs_new_protected:Npn \_regex_extract_e:wn #1 > #2
23185 { \_kernel_intarray_gset:Nnn \g__regex_submatch_end_intarray {#1} {#2} }

```

(End definition for `_regex_extract:`, `_regex_extract_b:wn`, and `_regex_extract_e:wn`.)

38.7.4 Replacement

`_regex_replace_once:nnN` Build the NFA and the replacement functions, then find a single match. If the match failed, simply exit the group. Otherwise, we do the replacement. Extract submatches. Compute the brace balance corresponding to replacing this match by the replacement (this depends on submatches). Prepare the replaced token list: the replacement function produces the tokens from the start of the query to the start of the match and the replacement text for this match; we need to add the tokens from the end of the match to the end of the query. Finally, store the result in the user's variable after closing the group: this step involves an additional x-expansion, and checks that braces are balanced in the final result.

```

23186 \cs_new_protected:Npn \_regex_replace_once:nnN #1#2#3
23187 {
23188     \group_begin:
23189     \_regex_single_match:
23190     #1
23191     \_regex_replacement:n {#2}
23192     \exp_args:No \_regex_match:n { #3 }
23193     \if_meaning:w \c_false_bool \g__regex_success_bool
23194     \group_end:
23195     \else:
23196     \_regex_extract:
23197     \int_set:Nn \l__regex_balance_int
23198     {
23199         \_regex_replacement_balance_one_match:n
23200         { \l__regex_zeroth_submatch_int }
23201     }
23202     \tl_set:Nx \l__regex_internal_a_tl
23203     {
23204         \_regex_replacement_do_one_match:n
23205         { \l__regex_zeroth_submatch_int }
23206         \_regex_query_range:nn
23207         {
23208             \_kernel_intarray_item:Nn \g__regex_submatch_end_intarray
23209             { \l__regex_zeroth_submatch_int }
23210         }
23211         { \l__regex_max_pos_int }

```

```

23212     }
23213     \_\_regex_group_end_replace:N #3
23214   \fi:
23215 }

```

(End definition for __regex_replace_once:nnN.)

__regex_replace_all:nnN Match multiple times, and for every match, extract submatches and additionally store the position at which the match attempt started. The entries from \l__regex_min_submatch_int to \l__regex_submatch_int hold information about submatches of every match in order; each match corresponds to \l__regex_capturing_group_int consecutive entries. Compute the brace balance corresponding to doing all the replacements: this is the sum of brace balances for replacing each match. Join together the replacement texts for each match (including the part of the query before the match), and the end of the query.

```

23216 \cs_new_protected:Npn \_\_regex_replace_all:nnN #1#2#3
23217 {
23218   \group_begin:
23219   \_\_regex_multi_match:n { \_\_regex_extract: }
23220   #1
23221   \_\_regex_replacement:n {#2}
23222   \exp_args:No \_\_regex_match:n {#3}
23223   \int_set:Nn \l_\_regex_balance_int
23224   {
23225     0
23226     \int_step_function:nnnN
23227       { \l_\_regex_min_submatch_int }
23228       \l_\_regex_capturing_group_int
23229       { \l_\_regex_submatch_int - 1 }
23230       \_\_regex_replacement_balance_one_match:n
23231   }
23232   \tl_set:Nx \l_\_regex_internal_a_tl
23233   {
23234     \int_step_function:nnnN
23235       { \l_\_regex_min_submatch_int }
23236       \l_\_regex_capturing_group_int
23237       { \l_\_regex_submatch_int - 1 }
23238       \_\_regex_replacement_do_one_match:n
23239       \_\_regex_query_range:nn
23240       \l_\_regex_start_pos_int \l_\_regex_max_pos_int
23241   }
23242   \_\_regex_group_end_replace:N #3
23243 }

```

(End definition for __regex_replace_all:nnN.)

__regex_group_end_replace:N If the brace balance is not 0, raise an error. Then set the user's variable #1 to the x-expansion of \l__regex_internal_a_tl, adding the appropriate braces to produce a balanced result. And end the group.

```

23244 \cs_new_protected:Npn \_\_regex_group_end_replace:N #1
23245 {
23246   \if_int_compare:w \l_\_regex_balance_int = 0 \exp_stop_f:
23247   \else:
23248     \__kernel_msg_error:nnxxx { kernel } { result-unbalanced }

```


Messages for missing or extra closing brackets and parentheses, with some fancy singular/plural handling for the case of parentheses.

```

23292 \__kernel_msg_new:nnnn { kernel } { missing-rbrack }
23293 { Missing-right-bracket-inserted-in-regular-expression. }
23294 {
23295     LaTeX-was-given-a-regular-expression-where-a-character-class-
23296     was-started-with~'[,~but~the~matching~'~is~missing.
23297 }
23298 \__kernel_msg_new:nnnn { kernel } { missing-rparen }
23299 {
23300     Missing-right~
23301     \int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } ~
23302     inserted-in-regular-expression.
23303 }
23304 {
23305     LaTeX-was-given-a-regular-expression-with~\int_eval:n {#1} ~
23306     more-left-parentheses-than-right-parentheses.
23307 }
23308 \__kernel_msg_new:nnnn { kernel } { extra-rparen }
23309 { Extra-right-parenthesis-ignored-in-regular-expression. }
23310 {
23311     LaTeX-came-across-a-closing-parenthesis-when-no-submatch-group-
23312     was-open.~The-parenthesis-will-be-ignored.
23313 }

```

Some escaped alphanumerics are not allowed everywhere.

```

23314 \__kernel_msg_new:nnnn { kernel } { bad-escape }
23315 {
23316     Invalid-escape~'\iow_char:N\\#1'~
23317     \__regex_if_in_cs:TF { within-a-control-sequence. }
23318     {
23319         \__regex_if_in_class:TF
23320         { in-a-character-class. }
23321         { following-a-category-test. }
23322     }
23323 }
23324 {
23325     The-escape-sequence~'\iow_char:N\\#1'~may-not-appear~
23326     \__regex_if_in_cs:TF
23327     {
23328         within-a-control-sequence-test-introduced-by~
23329         '\iow_char:N\\c\iow_char:N{'~
23330     }
23331     {
23332         \__regex_if_in_class:TF
23333         { within-a-character-class~ }
23334         { following-a-category-test-such-as~'\iow_char:N\\cL'~ }
23335         because-it-does-not-match-exactly-one-character.
23336     }
23337 }

```

Range errors.

```

23338 \__kernel_msg_new:nnnn { kernel } { range-missing-end }
23339 { Invalid-end-point-for-range~'#1-#2'~in-character-class. }
23340 {

```

```

23341     The~end~point~'#2'~of~the~range~'#1-#2'~may~not~serve~as~an~
23342     end~point~for~a~range:~alphanumeric~characters~should~not~be~
23343     escaped,~and~non~alphanumeric~characters~should~be~escaped.
23344 }
23345 \__kernel_msg_new:nnnn { kernel } { range-backwards }
23346 { Range~'#1-#2'~out~of~order~in~character~class. }
23347 {
23348     In~ranges~of~characters~'[x-y]'~appearing~in~character~classes,~
23349     the~first~character~code~must~not~be~larger~than~the~second.~
23350     Here,~'#1'~has~character~code~\int_eval:n {'#1},~while~
23351     '#2'~has~character~code~\int_eval:n {'#2}.
23352 }
    Errors related to \c and \u.
23353 \__kernel_msg_new:nnnn { kernel } { c-bad-mode }
23354 { Invalid~nested~'\iow_char:N\\c'~escape~in~regular~expression. }
23355 {
23356     The~'\iow_char:N\\c'~escape~cannot~be~used~within~
23357     a~control~sequence~test~'\iow_char:N\\c{...}'~
23358     nor~another~category~test.~
23359     To~combine~several~category~tests,~use~'\iow_char:N\\c[...]'.
23360 }
23361 \__kernel_msg_new:nnnn { kernel } { c-C-invalid }
23362 { '\iow_char:N\\c'~should~be~followed~by~'.'~or~'(',~not~'#1'. }
23363 {
23364     The~'\iow_char:N\\c'~construction~restricts~the~next~item~to~be~a~
23365     control~sequence~or~the~next~group~to~be~made~of~control~sequences.~
23366     It~only~makes~sense~to~follow~it~by~'.'~or~by~a~group.
23367 }
23368 \__kernel_msg_new:nnnn { kernel } { c-lparen-in-class }
23369 { Catcode~test~cannot~apply~to~group~in~character~class }
23370 {
23371     Construction~such~as~'\iow_char:N\\cL(abc)'~are~not~allowed~inside~a~
23372     class~'[...]'~because~classes~do~not~match~multiple~characters~at~once.
23373 }
23374 \__kernel_msg_new:nnnn { kernel } { c-missing-rbrace }
23375 { Missing~right~brace~inserted~for~'\iow_char:N\\c'~escape. }
23376 {
23377     LaTeX~was~given~a~regular~expression~where~a~
23378     '\iow_char:N\\c\iow_char:N{...}'~construction~was~not~ended~
23379     with~a~closing~brace~'\iow_char:N}'.
23380 }
23381 \__kernel_msg_new:nnnn { kernel } { c-missing-rbrack }
23382 { Missing~right~bracket~inserted~for~'\iow_char:N\\c'~escape. }
23383 {
23384     A~construction~'\iow_char:N\\c[...]~appears~in~a~
23385     regular~expression,~but~the~closing~'~is~not~present.
23386 }
23387 \__kernel_msg_new:nnnn { kernel } { c-missing-category }
23388 { Invalid~character~'#1'~following~'\iow_char:N\\c'~escape. }
23389 {
23390     In~regular~expressions,~the~'\iow_char:N\\c'~escape~sequence~
23391     may~only~be~followed~by~a~left~brace,~a~left~bracket,~or~a~
23392     capital~letter~representing~a~character~category,~namely~
23393     one~of~'ABCDELMOPTU'.

```

```

23394 }
23395 \__kernel_msg_new:nnnn { kernel } { c-trailing }
23396 { Trailing~category~code~escape~'\iow_char:N\\c'... }
23397 {
23398   A~regular~expression~ends~with~'\iow_char:N\\c'~followed~
23399   by~a~letter.~It~will~be~ignored.
23400 }
23401 \__kernel_msg_new:nnnn { kernel } { u-missing-lbrace }
23402 { Missing~left~brace~following~'\iow_char:N\\u'~escape. }
23403 {
23404   The~'\iow_char:N\\u'~escape~sequence~must~be~followed~by~
23405   a~brace~group~with~the~name~of~the~variable~to~use.
23406 }
23407 \__kernel_msg_new:nnnn { kernel } { u-missing-rbrace }
23408 { Missing~right~brace~inserted~for~'\iow_char:N\\u'~escape. }
23409 {
23410   LaTeX~
23411   \str_if_eq:eeTF { } {#2}
23412   { reached~the~end~of~the~string~ }
23413   { encountered~an~escaped~alphanumeric~character '\iow_char:N\\#2'~ }
23414   when~parsing~the~argument~of~an~
23415   '\iow_char:N\\u\iow_char:N{...}\}'~escape.
23416 }

```

Errors when encountering the POSIX syntax [:...:].

```

23417 \__kernel_msg_new:nnnn { kernel } { posix-unsupported }
23418 { POSIX~collating~element~'[#1 ~ #1]}'~not~supported. }
23419 {
23420   The~'[.foo.]'~and~'[=bar=]}'~syntaxes~have~a~special~meaning~
23421   in~POSIX~regular~expressions.~This~is~not~supported~by~LaTeX.~
23422   Maybe~you~forgot~to~escape~a~left~bracket~in~a~character~class?
23423 }
23424 \__kernel_msg_new:nnnn { kernel } { posix-unknown }
23425 { POSIX~class~'[:#1:]}'~unknown. }
23426 {
23427   '[:#1:]}'~is~not~among~the~known~POSIX~classes~
23428   '[:alnum:]',~'[:alpha:]',~'[:ascii:]',~'[:blank:]',~
23429   '[:cntrl:]',~'[:digit:]',~'[:graph:]',~'[:lower:]',~
23430   '[:print:]',~'[:punct:]',~'[:space:]',~'[:upper:]',~
23431   '[:word:]',~and~'[:xdigit:]'.
23432 }
23433 \__kernel_msg_new:nnnn { kernel } { posix-missing-close }
23434 { Missing~closing~'}'~for~POSIX~class. }
23435 { The~POSIX~syntax~'#1'~must~be~followed~by~':]',~not~'#2'. }

```

In various cases, the result of a `l3regex` operation can leave us with an unbalanced token list, which we must re-balance by adding begin-group or end-group character tokens.

```

23436 \__kernel_msg_new:nnnn { kernel } { result-unbalanced }
23437 { Missing~brace~inserted~when~#1. }
23438 {
23439   LaTeX~was~asked~to~do~some~regular~expression~operation,~
23440   and~the~resulting~token~list~would~not~have~the~same~number~
23441   of~begin~group~and~end~group~tokens.~Braces~were~inserted:~
23442   #2~left,~#3~right.

```

```

23443 }
Error message for unknown options.
23444 \_kernel_msg_new:nnnn { kernel } { unknown-option }
23445 { Unknown~option~'#1'~for~regular~expressions. }
23446 {
23447     The~only~available~option~is~'case-insensitive',~toggled-by~
23448     '(?i)'~and~'(?-i)'.
23449 }
23450 \_kernel_msg_new:nnnn { kernel } { special-group-unknown }
23451 { Unknown~special~group~'#1...'~in~a~regular~expression. }
23452 {
23453     The~only~valid~constructions~starting~with~'?'~are~
23454     '(:~...~)',~'(?|~...~)',~'(?i)',~and~'(?-i)'.
23455 }
Errors in the replacement text.
23456 \_kernel_msg_new:nnnn { kernel } { replacement-c }
23457 { Misused~'\iow_char:N\\c'~command~in~a~replacement~text. }
23458 {
23459     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
23460     can~be~followed~by~one~of~the~letters~'ABCDELMPSTU'~
23461     or~a~brace~group,~not~by~'#1'.
23462 }
23463 \_kernel_msg_new:nnnn { kernel } { replacement-u }
23464 { Misused~'\iow_char:N\\u'~command~in~a~replacement~text. }
23465 {
23466     In~a~replacement~text,~the~'\iow_char:N\\u'~escape~sequence~
23467     must~be~followed~by~a~brace~group~holding~the~name~of~the~
23468     variable~to~use.
23469 }
23470 \_kernel_msg_new:nnnn { kernel } { replacement-g }
23471 {
23472     Missing~brace~for~the~'\iow_char:N\\g'~construction~
23473     in~a~replacement~text.
23474 }
23475 {
23476     In~the~replacement~text~for~a~regular~expression~search,~
23477     submatches~are~represented~either~as~'\iow_char:N \\g{dd..d}',~
23478     or~'\d',~where~'d'~are~single~digits.~Here,~a~brace~is~missing.
23479 }
23480 \_kernel_msg_new:nnnn { kernel } { replacement-catcode-end }
23481 {
23482     Missing~character~for~the~'\iow_char:N\\c<category><character>'~
23483     construction~in~a~replacement~text.
23484 }
23485 {
23486     In~a~replacement~text,~the~'\iow_char:N\\c'~escape~sequence~
23487     can~be~followed~by~one~of~the~letters~'ABCDELMPSTU'~representing~
23488     the~character~category.~Then,~a~character~must~follow.~LaTeX~
23489     reached~the~end~of~the~replacement~when~looking~for~that.
23490 }
23491 \_kernel_msg_new:nnnn { kernel } { replacement-catcode-escaped }
23492 {
23493     Escaped~letter~or~digit~after~category~code~in~replacement~text.

```

```

23494 }
23495 {
23496   In~a~replacement~text,~the~'\iow_char:N\c'~escape~sequence~
23497   can~be~followed~by~one~of~the~letters~'ABCDELMOPTU'~representing~
23498   the~character~category.~Then,~a~character~must~follow,~not~
23499   '\iow_char:N\#2'.
23500 }
23501 \__kernel_msg_new:nnnn { kernel } { replacement-catcode-in-cs }
23502 {
23503   Category~code~'\iow_char:N\c#1#3'~ignored~inside~
23504   '\iow_char:N\c\{...\}'~in~a~replacement~text.
23505 }
23506 {
23507   In~a~replacement~text,~the~category~codes~of~the~argument~of~
23508   '\iow_char:N\c\{...\}'~are~ignored~when~building~the~control~
23509   sequence~name.
23510 }
23511 \__kernel_msg_new:nnnn { kernel } { replacement-null-space }
23512 { TeX~cannot~build~a~space~token~with~character~code~0. }
23513 {
23514   You~asked~for~a~character~token~with~category~space,~
23515   and~character~code~0,~for~instance~through~
23516   '\iow_char:N\cS\iow_char:N\#x00'.~
23517   This~specific~case~is~impossible~and~will~be~replaced~
23518   by~a~normal~space.
23519 }
23520 \__kernel_msg_new:nnnn { kernel } { replacement-missing-rbrace }
23521 { Missing~right~brace~inserted~in~replacement~text. }
23522 {
23523   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
23524   missing~right~\int_compare:nTF { #1 = 1 } { brace } { braces } .
23525 }
23526 \__kernel_msg_new:nnnn { kernel } { replacement-missing-rparen }
23527 { Missing~right~parenthesis~inserted~in~replacement~text. }
23528 {
23529   There~ \int_compare:nTF { #1 = 1 } { was } { were } ~ #1~
23530   missing~right~
23531   \int_compare:nTF { #1 = 1 } { parenthesis } { parentheses } .
23532 }

```

Used when showing a regex.

```

23533 \__kernel_msg_new:nnn { kernel } { show-regex }
23534 {
23535   >~Compiled~regex~
23536   \tl_if_empty:nTF {#1} { variable~ #2 } { {#1} } :
23537   #3
23538 }

```

`__regex_msg_repeated:nnN` This is not technically a message, but seems related enough to go there. The arguments are: #1 is the minimum number of repetitions; #2 is the number of allowed extra repetitions (−1 for infinite number), and #3 tells us about laziness.

```

23539 \cs_new:Npn \__regex_msg_repeated:nnN #1#2#3
23540 {
23541   \str_if_eq:eeF { #1 #2 } { 1 0 }

```

```

23542     {
23543     , ~ repeated ~
23544     \int_case:nnF {#2}
23545     {
23546     { -1 } { #1~or-more-times,~\bool_if:NTF #3 { lazy } { greedy } }
23547     { 0 } { #1~times }
23548     }
23549     {
23550     between~#1~and~\int_eval:n {#1+#2}~times,~
23551     \bool_if:NTF #3 { lazy } { greedy }
23552     }
23553     }
23554 }

```

(End definition for _regex_msg_repeated:nnN.)

38.9 Code for tracing

There is a more extensive implementation of tracing in the l3trial package l3trace. Function names are a bit different but could be merged.

_regex_trace_push:nnN Here #1 is the module name (regex) and #2 is typically 1. If the module's current tracing level is less than #2 show nothing, otherwise write #3 to the terminal.

```

\_regex_trace_pop:nnN
\_regex_trace:nnx
23555 \_kernel_if_debug:TF
23556 {
23557   \cs_new_protected:Npn \_regex_trace_push:nnN #1#2#3
23558   { \_regex_trace:nnx {#1} {#2} { entering~ \token_to_str:N #3 } }
23559   \cs_new_protected:Npn \_regex_trace_pop:nnN #1#2#3
23560   { \_regex_trace:nnx {#1} {#2} { leaving~ \token_to_str:N #3 } }
23561   \cs_new_protected:Npn \_regex_trace:nnx #1#2#3
23562   {
23563     \int_compare:nNnF
23564     { \int_use:c { g\_regex_trace_#1_int } } < {#2}
23565     { \iow_term:x { Trace:~#3 } }
23566   }
23567 }
23568 { }

```

(End definition for _regex_trace_push:nnN, _regex_trace_pop:nnN, and _regex_trace:nnx.)

\g__regex_trace_regex_int No tracing when that is zero.

```

23569 \int_new:N \g__regex_trace_regex_int

```

(End definition for \g__regex_trace_regex_int.)

_regex_trace_states:n This function lists the contents of all states of the NFA, stored in \toks from 0 to \l__-regex_max_state_int (excluded).

```

23570 \_kernel_if_debug:TF
23571 {
23572   \cs_new_protected:Npn \_regex_trace_states:n #1
23573   {
23574     \int_step_inline:nnn
23575     \l__regex_min_state_int
23576     { \l__regex_max_state_int - 1 }

```

```

23577         {
23578             \__regex_trace:nmx { regex } {#1}
23579             { \iow_char:N \toks ##1 = { \__regex_toks_use:w ##1 } }
23580         }
23581     }
23582 }
23583 { }

```

(End definition for __regex_trace_states:n.)

```
23584 </initex | package>
```

39 l3box implementation

```
23585 <*initex | package>
```

```
23586 <@@=box>
```

39.1 Support code

__box_dim_eval:w Evaluating a dimension expression expandably. The only difference with \dim_eval:n is the lack of \dim_use:N, to produce an internal dimension rather than expand it into characters.

```

23587 \cs_new_eq:NN \__box_dim_eval:w \tex_dimexpr:D
23588 \__kernel_patch_args:nNnpn
23589 {
23590     {
23591         \__kernel_chk_expr:nNnN {#1}
23592         \__box_dim_eval:w { } \__box_dim_eval:n
23593     }
23594 }
23595 \cs_new:Npn \__box_dim_eval:n #1
23596 { \__box_dim_eval:w #1 \scan_stop: }

```

(End definition for __box_dim_eval:w and __box_dim_eval:n.)

39.2 Creating and initialising boxes

The following test files are used for this code: m3box001.lvt.

\box_new:N Defining a new $\langle box \rangle$ register: remember that box 255 is not generally available.

```

\box_new:c 23597 <*package>
23598 \cs_new_protected:Npn \box_new:N #1
23599 {
23600     \__kernel_chk_if_free_cs:N #1
23601     \cs:w newbox \cs_end: #1
23602 }
23603 </package>
23604 \cs_generate_variant:Nn \box_new:N { c }

```

Clear a $\langle box \rangle$ register.

```

23605 \cs_new_protected:Npn \box_clear:N #1
23606 { \box_set_eq:NN #1 \c_empty_box }
\box_clear:c 23607 \cs_new_protected:Npn \box_gclear:N #1
\box_gclear:N 23608 { \box_gset_eq:NN #1 \c_empty_box }
\box_gclear:c

```



```

23609 \cs_generate_variant:Nn \box_clear:N { c }
23610 \cs_generate_variant:Nn \box_gclear:N { c }

```

Clear or new.

```

23611 \cs_new_protected:Npn \box_clear_new:N #1
\box_clear_new:N  { \box_if_exist:NTF #1 { \box_clear:N #1 } { \box_new:N #1 } }
23612
23613 \cs_new_protected:Npn \box_gclear_new:N #1
\box_gclear_new:N { \box_if_exist:NTF #1 { \box_gclear:N #1 } { \box_new:N #1 } }
23614
23615 \cs_generate_variant:Nn \box_clear_new:N { c }
\box_gclear_new:c
23616 \cs_generate_variant:Nn \box_gclear_new:N { c }

```

Assigning the contents of a box to be another box.

```

23617 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\box_set_eq:NN
23618 \cs_new_protected:Npn \box_set_eq:NN #1#2
\box_set_eq:cN { \tex_setbox:D #1 \tex_copy:D #2 }
23619
\box_set_eq:Nc
23620 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
\box_set_eq:cc
23621 \cs_new_protected:Npn \box_gset_eq:NN #1#2
\box_gset_eq:NN { \tex_global:D \tex_setbox:D #1 \tex_copy:D #2 }
23622
\box_gset_eq:cN
23623 \cs_generate_variant:Nn \box_set_eq:NN { c , Nc , cc }
\box_gset_eq:Nc
23624 \cs_generate_variant:Nn \box_gset_eq:NN { c , Nc , cc }
\box_gset_eq:cc

```

Assigning the contents of a box to be another box. This clears the second box globally (that's how \TeX does it).

```

\box_set_eq_clear:NN
23625 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\box_set_eq_clear:cN
23626 \cs_new_protected:Npn \box_set_eq_clear:NN #1#2
\box_set_eq_clear:Nc
23627 { \tex_setbox:D #1 \tex_box:D #2 }
\box_set_eq_clear:cc
23628 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
\box_gset_eq_clear:NN
23629 \cs_new_protected:Npn \box_gset_eq_clear:NN #1#2
\box_gset_eq_clear:cN
23630 { \tex_global:D \tex_setbox:D #1 \tex_box:D #2 }
\box_gset_eq_clear:Nc
23631 \cs_generate_variant:Nn \box_set_eq_clear:NN { c , Nc , cc }
\box_gset_eq_clear:cc
23632 \cs_generate_variant:Nn \box_gset_eq_clear:NN { c , Nc , cc }

```

Copies of the `cs` functions defined in `l3basics`.

```

23633 \prg_new_eq_conditional:NNn \box_if_exist:N \cs_if_exist:N
\box_if_exist_p:N { TF , T , F , p }
23634
\box_if_exist_p:c
23635 \prg_new_eq_conditional:NNn \box_if_exist:c \cs_if_exist:c
\box_if_exist:N $\underline{TF}$ 
23636 { TF , T , F , p }
\box_if_exist:c $\underline{TF}$ 

```

39.3 Measuring and setting box dimensions

Accessing the height, depth, and width of a $\langle box \rangle$ register.

```

23637 \cs_new_eq:NN \box_ht:N \tex_ht:D
\box_ht:N
23638 \cs_new_eq:NN \box_dp:N \tex_dp:D
\box_ht:c
23639 \cs_new_eq:NN \box_wd:N \tex_wd:D
\box_dp:N
23640 \cs_generate_variant:Nn \box_ht:N { c }
\box_dp:c
23641 \cs_generate_variant:Nn \box_dp:N { c }
\box_wd:N
23642 \cs_generate_variant:Nn \box_wd:N { c }
\box_wd:c

```

Setting the size is easy: all primitive work. These primitives are not expandable, so the derived functions are not either. When debugging, the dimension expression `#2` is surrounded by parentheses to catch early termination.

```

\box_set_ht:NN
23643 \cs_new_protected:Npn \box_set_dp:Nn #1#2
\box_set_ht:cN { \box_dp:N #1 \__box_dim_eval:n {#2} }
23644
\box_set_dp:Nn
\box_set_dp:cN
\box_set_wd:NN
\box_set_wd:cN

```

```

23645 \cs_new_protected:Npn \box_set_ht:Nn #1#2
23646 { \box_ht:N #1 \__box_dim_eval:n {#2} }
23647 \cs_new_protected:Npn \box_set_wd:Nn #1#2
23648 { \box_wd:N #1 \__box_dim_eval:n {#2} }
23649 \cs_generate_variant:Nn \box_set_ht:Nn { c }
23650 \cs_generate_variant:Nn \box_set_dp:Nn { c }
23651 \cs_generate_variant:Nn \box_set_wd:Nn { c }

```

39.4 Using boxes

Using a $\langle box \rangle$. These are just TeX primitives with meaningful names.

```

23652 \cs_new_eq:NN \box_use_drop:N \tex_box:D
\box_use_drop:N 23653 \cs_new_eq:NN \box_use:N \tex_copy:D
\box_use_drop:c 23654 \cs_generate_variant:Nn \box_use_drop:N { c }
\box_use:N 23655 \cs_generate_variant:Nn \box_use:N { c }
\box_use:c

```

Move box material in different directions. When debugging, the dimension expression #1 is surrounded by parentheses to catch early termination.

```

\box_move_left:nn 23656 \cs_new_protected:Npn \box_move_left:nn #1#2
\box_move_right:nn 23657 { \tex_moveleft:D \__box_dim_eval:n {#1} #2 }
\box_move_up:nn 23658 \cs_new_protected:Npn \box_move_right:nn #1#2
\box_move_down:nn 23659 { \tex_moveright:D \__box_dim_eval:n {#1} #2 }
23660 \cs_new_protected:Npn \box_move_up:nn #1#2
23661 { \tex_raise:D \__box_dim_eval:n {#1} #2 }
23662 \cs_new_protected:Npn \box_move_down:nn #1#2
23663 { \tex_lower:D \__box_dim_eval:n {#1} #2 }

```

39.5 Box conditionals

The primitives for testing if a $\langle box \rangle$ is empty/void or which type of box it is.

```

23664 \cs_new_eq:NN \if_hbox:N \tex_ifhbox:D
\if_hbox:N 23665 \cs_new_eq:NN \if_vbox:N \tex_ifvbox:D
\if_vbox:N 23666 \cs_new_eq:NN \if_box_empty:N \tex_ifvoid:D
\if_box_empty:N

23667 \prg_new_conditional:Npnn \box_if_horizontal:N #1 { p , T , F , TF }
23668 { \if_hbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal_p:N 23669 \prg_new_conditional:Npnn \box_if_vertical:N #1 { p , T , F , TF }
\box_if_horizontal_p:c 23670 { \if_vbox:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_horizontal:N $\underline{TF}$  23671 \prg_generate_conditional_variant:Nnn \box_if_horizontal:N
\box_if_vertical_p:N 23672 { c } { p , T , F , TF }
\box_if_vertical_p:c 23673 \prg_generate_conditional_variant:Nnn \box_if_vertical:N
\box_if_vertical:N $\underline{TF}$  23674 { c } { p , T , F , TF }
\box_if_vertical:c $\underline{TF}$ 

```

Testing if a $\langle box \rangle$ is empty/void.

```

23675 \prg_new_conditional:Npnn \box_if_empty:N #1 { p , T , F , TF }
\box_if_empty_p:N 23676 { \if_box_empty:N #1 \prg_return_true: \else: \prg_return_false: \fi: }
\box_if_empty_p:c 23677 \prg_generate_conditional_variant:Nnn \box_if_empty:N
\box_if_empty:N $\underline{TF}$  23678 { c } { p , T , F , TF }
\box_if_empty:c $\underline{TF}$ 

```

(End definition for $\backslash box_new:N$ and others. These functions are documented on page 220.)

39.6 The last box inserted

`\box_set_to_last:N` Set a box to the previous box.
`\box_set_to_last:c`
`\box_gset_to_last:N`
`\box_gset_to_last:c`

```

23679 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
23680 \cs_new_protected:Npn \box_set_to_last:N #1
23681   { \tex_setbox:D #1 \tex_lastbox:D }
23682 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23683 \cs_new_protected:Npn \box_gset_to_last:N #1
23684   { \tex_global:D \tex_setbox:D #1 \tex_lastbox:D }
23685 \cs_generate_variant:Nn \box_set_to_last:N { c }
23686 \cs_generate_variant:Nn \box_gset_to_last:N { c }

```

(End definition for `\box_set_to_last:N` and `\box_gset_to_last:N`. These functions are documented on page 223.)

39.7 Constant boxes

`\c_empty_box` A box we never use.

```

23687 \box_new:N \c_empty_box

```

(End definition for `\c_empty_box`. This variable is documented on page 223.)

39.8 Scratch boxes

`\l_tmpa_box` Scratch boxes.
`\l_tmpb_box`
`\g_tmpa_box`
`\g_tmpb_box`

```

23688 \box_new:N \l_tmpa_box
23689 \box_new:N \l_tmpb_box
23690 \box_new:N \g_tmpa_box
23691 \box_new:N \g_tmpb_box

```

(End definition for `\l_tmpa_box` and others. These variables are documented on page 223.)

39.9 Viewing box contents

T_EX's `\showbox` is not really that helpful in many cases, and it is also inconsistent with other L^AT_EX3 show functions as it does not actually shows material in the terminal. So we provide a richer set of functionality.

`\box_show:N` Essentially a wrapper around the internal function, but evaluating the breadth and depth arguments now outside the group.
`\box_show:c`
`\box_show:Nnn`
`\box_show:cnn`

```

23692 \cs_new_protected:Npn \box_show:N #1
23693   { \box_show:Nnn #1 \c_max_int \c_max_int }
23694 \cs_generate_variant:Nn \box_show:N { c }
23695 \cs_new_protected:Npn \box_show:Nnn #1#2#3
23696   { \__box_show:NNff 1 #1 { \int_eval:n {#2} } { \int_eval:n {#3} } }
23697 \cs_generate_variant:Nn \box_show:Nnn { c }

```

(End definition for `\box_show:N` and `\box_show:Nnn`. These functions are documented on page 223.)

\box_log:N Getting TeX to write to the log without interruption the run is done by altering the
\box_log:c interaction mode. For that, the ϵ -TeX extensions are needed.
\box_log:Nnn
\box_log:cnn
__box_log:nNnn

```

23698 \cs_new_protected:Npn \box_log:N #1
23699 { \box_log:Nnn #1 \c_max_int \c_max_int }
23700 \cs_generate_variant:Nn \box_log:N { c }
23701 \cs_new_protected:Npn \box_log:Nnn
23702 { \exp_args:No \__box_log:nNnn { \tex_the:D \tex_interactionmode:D } }
23703 \cs_new_protected:Npn \__box_log:nNnn #1#2#3#4
23704 {
23705   \int_set:Nn \tex_interactionmode:D { 0 }
23706   \__box_show:NNff 0 #2 { \int_eval:n {#3} } { \int_eval:n {#4} }
23707   \int_set:Nn \tex_interactionmode:D {#1}
23708 }
23709 \cs_generate_variant:Nn \box_log:Nnn { c }

```

(End definition for `\box_log:N`, `\box_log:Nnn`, and `__box_log:nNnn`. These functions are documented on page 224.)

__box_show:NNnn The internal auxiliary to actually do the output uses a group to deal with breadth and
__box_show:NNff depth values. The `\use:n` here gives better output appearance. Setting `\tracingonline` and `\errorcontextlines` is used to control what appears in the terminal.

```

23710 \cs_new_protected:Npn \__box_show:NNnn #1#2#3#4
23711 {
23712   \box_if_exist:NTF #2
23713   {
23714     \group_begin:
23715       \int_set:Nn \tex_showboxbreadth:D {#3}
23716       \int_set:Nn \tex_showboxdepth:D {#4}
23717       \int_set:Nn \tex_tracingonline:D {#1}
23718       \int_set:Nn \tex_errorcontextlines:D { -1 }
23719       \tex_showbox:D \use:n {#2}
23720     \group_end:
23721   }
23722   {
23723     \__kernel_msg_error:nxx { kernel } { variable-not-defined }
23724     { \token_to_str:N #2 }
23725   }
23726 }
23727 \cs_generate_variant:Nn \__box_show:NNnn { NNff }

```

(End definition for `__box_show:NNnn`.)

39.10 Horizontal mode boxes

\hbox:n (The test suite for this command, and others in this file, is `m3box002.lvt`.)
 Put a horizontal box directly into the input stream.

```

23728 \cs_new_protected:Npn \hbox:n #1
23729 { \tex_hbox:D \scan_stop: { \color_group_begin: #1 \color_group_end: } }

```

(End definition for `\hbox:n`. This function is documented on page 224.)

\hbox_set:Nn
\hbox_set:cn
\hbox_gset:Nn
\hbox_gset:cn

```

23730 \__kernel_patch:nnNnpn { \__kernel_chk_var_local:N #1 } { }
23731 \cs_new_protected:Npn \hbox_set:Nn #1#2

```

```

23732 {
23733   \tex_setbox:D #1 \tex_hbox:D
23734   { \color_group_begin: #2 \color_group_end: }
23735 }
23736 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23737 \cs_new_protected:Npn \hbox_gset:Nn #1#2
23738 {
23739   \tex_global:D \tex_setbox:D #1 \tex_hbox:D
23740   { \color_group_begin: #2 \color_group_end: }
23741 }
23742 \cs_generate_variant:Nn \hbox_set:Nn { c }
23743 \cs_generate_variant:Nn \hbox_gset:Nn { c }

```

(End definition for `\hbox_set:Nn` and `\hbox_gset:Nn`. These functions are documented on page 224.)

`\hbox_set_to_wd:Nnn` Storing material in a horizontal box with a specified width. Again, put the dimension expression in parentheses when debugging.

```

\hbox_set_to_wd:cnn
\hbox_gset_to_wd:Nnn
\hbox_gset_to_wd:cnn
23744 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
23745 \cs_new_protected:Npn \hbox_set_to_wd:Nnn #1#2#3
23746 {
23747   \tex_setbox:D #1 \tex_hbox:D to \__box_dim_eval:n {#2}
23748   { \color_group_begin: #3 \color_group_end: }
23749 }
23750 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23751 \cs_new_protected:Npn \hbox_gset_to_wd:Nnn #1#2#3
23752 {
23753   \tex_global:D \tex_setbox:D #1 \tex_hbox:D to \__box_dim_eval:n {#2}
23754   { \color_group_begin: #3 \color_group_end: }
23755 }
23756 \cs_generate_variant:Nn \hbox_set_to_wd:Nnn { c }
23757 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnn { c }

```

(End definition for `\hbox_set_to_wd:Nnn` and `\hbox_gset_to_wd:Nnn`. These functions are documented on page 224.)

`\hbox_set:Nw` Storing material in a horizontal box. This type is useful in environment definitions.

```

\hbox_set:cw
\hbox_gset:Nw
\hbox_gset:cw
\hbox_set_end:
\hbox_gset_end:
23758 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
23759 \cs_new_protected:Npn \hbox_set:Nw #1
23760 {
23761   \tex_setbox:D #1 \tex_hbox:D
23762   \c_group_begin_token
23763   \color_group_begin:
23764 }
23765 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23766 \cs_new_protected:Npn \hbox_gset:Nw #1
23767 {
23768   \tex_global:D \tex_setbox:D #1 \tex_hbox:D
23769   \c_group_begin_token
23770   \color_group_begin:
23771 }
23772 \cs_generate_variant:Nn \hbox_set:Nw { c }
23773 \cs_generate_variant:Nn \hbox_gset:Nw { c }
23774 \cs_new_protected:Npn \hbox_set_end:
23775 {
23776   \color_group_end:

```

```

23777 \c_group_end_token
23778 }
23779 \cs_new_eq:NN \hbox_gset_end: \hbox_set_end:

```

(End definition for `\hbox_set:Nw` and others. These functions are documented on page 225.)

`\hbox_set_to_wd:Nnw`
`\hbox_set_to_wd:cnw`
`\hbox_gset_to_wd:Nnw`
`\hbox_gset_to_wd:cnw`

Combining the above ideas.

```

23780 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
23781 \cs_new_protected:Npn \hbox_set_to_wd:Nnw #1#2
23782 {
23783   \tex_setbox:D #1 \tex_hbox:D to \__box_dim_eval:n {#2}
23784   \c_group_begin_token
23785   \color_group_begin:
23786 }
23787 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23788 \cs_new_protected:Npn \hbox_gset_to_wd:Nnw #1#2
23789 {
23790   \tex_global:D \tex_setbox:D #1 \tex_hbox:D to \__box_dim_eval:n {#2}
23791   \c_group_begin_token
23792   \color_group_begin:
23793 }
23794 \cs_generate_variant:Nn \hbox_set_to_wd:Nnw { c }
23795 \cs_generate_variant:Nn \hbox_gset_to_wd:Nnw { c }

```

(End definition for `\hbox_set_to_wd:Nnw` and `\hbox_gset_to_wd:Nnw`. These functions are documented on page 225.)

`\hbox_to_wd:nn`
`\hbox_to_zero:n`

Put a horizontal box directly into the input stream.

```

23796 \cs_new_protected:Npn \hbox_to_wd:nn #1#2
23797 {
23798   \tex_hbox:D to \__box_dim_eval:n {#1}
23799   { \color_group_begin: #2 \color_group_end: }
23800 }
23801 \cs_new_protected:Npn \hbox_to_zero:n #1
23802 {
23803   \tex_hbox:D to \c_zero_dim
23804   { \color_group_begin: #1 \color_group_end: }
23805 }

```

(End definition for `\hbox_to_wd:nn` and `\hbox_to_zero:n`. These functions are documented on page 224.)

`\hbox_overlap_left:n`
`\hbox_overlap_right:n`

Put a zero-sized box with the contents pushed against one side (which makes it stick out on the other) directly into the input stream.

```

23806 \cs_new_protected:Npn \hbox_overlap_left:n #1
23807 { \hbox_to_zero:n { \tex_hss:D #1 } }
23808 \cs_new_protected:Npn \hbox_overlap_right:n #1
23809 { \hbox_to_zero:n { #1 \tex_hss:D } }

```

(End definition for `\hbox_overlap_left:n` and `\hbox_overlap_right:n`. These functions are documented on page 225.)

`\hbox_unpack:N`
`\hbox_unpack:c`
`\hbox_unpack_clear:N`
`\hbox_unpack_clear:c`

Unpacking a box and if requested also clear it.

```

23810 \cs_new_eq:NN \hbox_unpack:N \tex_unhcopy:D
23811 \cs_new_eq:NN \hbox_unpack_clear:N \tex_unhbox:D
23812 \cs_generate_variant:Nn \hbox_unpack:N { c }
23813 \cs_generate_variant:Nn \hbox_unpack_clear:N { c }

```

(End definition for `\hbox_unpack:N` and `\hbox_unpack_clear:N`. These functions are documented on page 225.)

39.11 Vertical mode boxes

TeX ends these boxes directly with the internal `end_graf` routine. This means that there is no `\par` at the end of vertical boxes unless we insert one. Thus all vertical boxes include a `\par` just before closing the color group.

`\vbox:n` The following test files are used for this code: `m3box003.lvt`.

The following test files are used for this code: `m3box003.lvt`.

`\vbox_top:n` Put a vertical box directly into the input stream.

```
23814 \cs_new_protected:Npn \vbox:n #1
23815 { \tex_vbox:D { \color_group_begin: #1 \par \color_group_end: } }
23816 \cs_new_protected:Npn \vbox_top:n #1
23817 { \tex_vtop:D { \color_group_begin: #1 \par \color_group_end: } }
```

(End definition for `\vbox:n` and `\vbox_top:n`. These functions are documented on page 225.)

`\vbox_to_ht:nn` Put a vertical box directly into the input stream.

```
\vbox_to_zero:n 23818 \cs_new_protected:Npn \vbox_to_ht:nn #1#2
\vbox_to_ht:nn 23819 {
\vbox_to_zero:n 23820 \tex_vbox:D to \__box_dim_eval:n {#1}
23821 { \color_group_begin: #2 \par \color_group_end: }
23822 }
23823 \cs_new_protected:Npn \vbox_to_zero:n #1
23824 {
23825 \tex_vbox:D to \c_zero_dim
23826 { \color_group_begin: #1 \par \color_group_end: }
23827 }
```

(End definition for `\vbox_to_ht:nn` and others. These functions are documented on page 226.)

`\vbox_set:Nn` Storing material in a vertical box with a natural height.

```
\vbox_set:cn 23828 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\vbox_gset:Nn 23829 \cs_new_protected:Npn \vbox_set:Nn #1#2
\vbox_gset:cn 23830 {
23831 \tex_setbox:D #1 \tex_vbox:D
23832 { \color_group_begin: #2 \par \color_group_end: }
23833 }
23834 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23835 \cs_new_protected:Npn \vbox_gset:Nn #1#2
23836 {
23837 \tex_global:D \tex_setbox:D #1 \tex_vbox:D
23838 { \color_group_begin: #2 \par \color_group_end: }
23839 }
23840 \cs_generate_variant:Nn \vbox_set:Nn { c }
23841 \cs_generate_variant:Nn \vbox_gset:Nn { c }
```

(End definition for `\vbox_set:Nn` and `\vbox_gset:Nn`. These functions are documented on page 226.)

\vbox_set_top:Nn Storing material in a vertical box with a natural height and reference point at the baseline
\vbox_set_top:cn of the first object in the box.

\vbox_gset_top:Nn 23842 __kernel_patch:nnNNpn { __kernel_chk_var_local:N #1 } { }
\vbox_gset_top:cn 23843 \cs_new_protected:Npn \vbox_set_top:Nn #1#2
23844 {
23845 \tex_setbox:D #1 \tex_vtop:D
23846 { \color_group_begin: #2 \par \color_group_end: }
23847 }
23848 __kernel_patch:nnNNpn { __kernel_chk_var_global:N #1 } { }
23849 \cs_new_protected:Npn \vbox_gset_top:Nn #1#2
23850 {
23851 \tex_global:D \tex_setbox:D #1 \tex_vtop:D
23852 { \color_group_begin: #2 \par \color_group_end: }
23853 }
23854 \cs_generate_variant:Nn \vbox_set_top:Nn { c }
23855 \cs_generate_variant:Nn \vbox_gset_top:Nn { c }

(End definition for \vbox_set_top:Nn and \vbox_gset_top:Nn. These functions are documented on page 226.)

\vbox_set_to_ht:Nnn Storing material in a vertical box with a specified height.

\vbox_set_to_ht:cnn 23856 __kernel_patch:nnNNpn { __kernel_chk_var_local:N #1 } { }
\vbox_gset_to_ht:Nnn 23857 \cs_new_protected:Npn \vbox_set_to_ht:Nnn #1#2#3
\vbox_gset_to_ht:cnn 23858 {
23859 \tex_setbox:D #1 \tex_vbox:D to __box_dim_eval:n {#2}
23860 { \color_group_begin: #3 \par \color_group_end: }
23861 }
23862 __kernel_patch:nnNNpn { __kernel_chk_var_global:N #1 } { }
23863 \cs_new_protected:Npn \vbox_gset_to_ht:Nnn #1#2#3
23864 {
23865 \tex_global:D \tex_setbox:D #1 \tex_vbox:D to __box_dim_eval:n {#2}
23866 { \color_group_begin: #3 \par \color_group_end: }
23867 }
23868 \cs_generate_variant:Nn \vbox_set_to_ht:Nnn { c }
23869 \cs_generate_variant:Nn \vbox_gset_to_ht:Nnn { c }

(End definition for \vbox_set_to_ht:Nnn and \vbox_gset_to_ht:Nnn. These functions are documented on page 226.)

\vbox_set:Nw Storing material in a vertical box. This type is useful in environment definitions.

\vbox_set:cw 23870 __kernel_patch:nnNNpn { __kernel_chk_var_local:N #1 } { }
\vbox_gset:Nw 23871 \cs_new_protected:Npn \vbox_set:Nw #1
\vbox_gset:cw 23872 {
\vbox_set_end: 23873 \tex_setbox:D #1 \tex_vbox:D
\vbox_gset_end: 23874 \c_group_begin_token
23875 \color_group_begin:
23876 }
23877 __kernel_patch:nnNNpn { __kernel_chk_var_global:N #1 } { }
23878 \cs_new_protected:Npn \vbox_gset:Nw #1
23879 {
23880 \tex_global:D \tex_setbox:D #1 \tex_vbox:D
23881 \c_group_begin_token
23882 \color_group_begin:
23883 }


```

23884 \cs_generate_variant:Nn \vbox_set:Nw { c }
23885 \cs_generate_variant:Nn \vbox_gset:Nw { c }
23886 \cs_new_protected:Npn \vbox_set_end:
23887 {
23888     \par
23889     \color_group_end:
23890     \c_group_end_token
23891 }
23892 \cs_new_eq:NN \vbox_gset_end: \vbox_set_end:

```

(End definition for `\vbox_set:Nw` and others. These functions are documented on page 226.)

```

\boxed_set_to_ht:Nnw A combination of the above ideas.
\boxed_set_to_ht:cnw 23893 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\boxed_gset_to_ht:Nnw 23894 \cs_new_protected:Npn \boxed_set_to_ht:Nnw #1#2
\boxed_gset_to_ht:cnw 23895 {
23896     \tex_setbox:D #1 \tex_vbox:D to \__box_dim_eval:n {#2}
23897     \c_group_begin_token
23898     \color_group_begin:
23899 }
23900 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
23901 \cs_new_protected:Npn \boxed_gset_to_ht:Nnw #1#2
23902 {
23903     \tex_global:D \tex_setbox:D #1 \tex_vbox:D to \__box_dim_eval:n {#2}
23904     \c_group_begin_token
23905     \color_group_begin:
23906 }
23907 \cs_generate_variant:Nn \boxed_set_to_ht:Nnw { c }
23908 \cs_generate_variant:Nn \boxed_gset_to_ht:Nnw { c }

```

(End definition for `\boxed_set_to_ht:Nnw` and `\boxed_gset_to_ht:Nnw`. These functions are documented on page 226.)

```

\boxed_unpack:N Unpacking a box and if requested also clear it.
\boxed_unpack:c 23909 \cs_new_eq:NN \boxed_unpack:N \tex_unvcopy:D
\boxed_unpack_clear:N 23910 \cs_new_eq:NN \boxed_unpack_clear:N \tex_unvbox:D
\boxed_unpack_clear:c 23911 \cs_generate_variant:Nn \boxed_unpack:N { c }
23912 \cs_generate_variant:Nn \boxed_unpack_clear:N { c }

```

(End definition for `\boxed_unpack:N` and `\boxed_unpack_clear:N`. These functions are documented on page 227.)

```

\boxed_set_split_to_ht:NNn Splitting a vertical box in two.
\boxed_set_split_to_ht:cnw 23913 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
\boxed_set_split_to_ht:Ncn 23914 \cs_new_protected:Npn \boxed_set_split_to_ht:NNn #1#2#3
\boxed_set_split_to_ht:ccn 23915 { \tex_setbox:D #1 \tex_vsplit:D #2 to \__box_dim_eval:n {#3} }
\boxed_gset_split_to_ht:NNn 23916 \cs_generate_variant:Nn \boxed_set_split_to_ht:NNn { c , Nc , cc }
\boxed_gset_split_to_ht:cnw 23917 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
\boxed_gset_split_to_ht:Ncn 23918 \cs_new_protected:Npn \boxed_gset_split_to_ht:NNn #1#2#3
\boxed_gset_split_to_ht:ccn 23919 {
23920     \tex_global:D \tex_setbox:D #1
23921     \tex_vsplit:D #2 to \__box_dim_eval:n {#3}
23922 }
23923 \cs_generate_variant:Nn \boxed_gset_split_to_ht:NNn { c , Nc , cc }

```

(End definition for `\boxed_set_split_to_ht:NNn` and `\boxed_gset_split_to_ht:NNn`. These functions are documented on page 226.)

39.12 Affine transformations

`\l__box_angle_fp` When rotating boxes, the angle itself may be needed by the engine-dependent code. This is done using the `fp` module so that the value is tidied up properly.

```
23924 \fp_new:N \l__box_angle_fp
```

(End definition for `\l__box_angle_fp`.)

`\l__box_cos_fp` `\l__box_sin_fp` These are used to hold the calculated sine and cosine values while carrying out a rotation.

```
23925 \fp_new:N \l__box_cos_fp
```

```
23926 \fp_new:N \l__box_sin_fp
```

(End definition for `\l__box_cos_fp` and `\l__box_sin_fp`.)

`\l__box_top_dim` `\l__box_bottom_dim` `\l__box_left_dim` `\l__box_right_dim` These are the positions of the four edges of a box before manipulation.

```
23927 \dim_new:N \l__box_top_dim
```

```
23928 \dim_new:N \l__box_bottom_dim
```

```
23929 \dim_new:N \l__box_left_dim
```

```
23930 \dim_new:N \l__box_right_dim
```

(End definition for `\l__box_top_dim` and others.)

`\l__box_top_new_dim` `\l__box_bottom_new_dim` `\l__box_left_new_dim` `\l__box_right_new_dim` These are the positions of the four edges of a box after manipulation.

```
23931 \dim_new:N \l__box_top_new_dim
```

```
23932 \dim_new:N \l__box_bottom_new_dim
```

```
23933 \dim_new:N \l__box_left_new_dim
```

```
23934 \dim_new:N \l__box_right_new_dim
```

(End definition for `\l__box_top_new_dim` and others.)

`\l__box_internal_box` Scratch space, but also needed by some parts of the driver.

```
23935 \box_new:N \l__box_internal_box
```

(End definition for `\l__box_internal_box`.)

`\box_rotate:Nn` `__box_rotate:N` Rotation of a box starts with working out the relevant sine and cosine. The actual rotation is in an auxiliary to keep the flow slightly clearer

```
\__box_rotate_xdir:nnN
```

```
23936 \cs_new_protected:Npn \box_rotate:Nn #1#2
```

```
\__box_rotate_ydir:nnN
```

```
23937 {
```

```
\__box_rotate_quadrant_one:
```

```
23938 \hbox_set:Nn #1
```

```
\__box_rotate_quadrant_two:
```

```
23939 {
```

```
\__box_rotate_quadrant_three:
```

```
23940 \fp_set:Nn \l__box_angle_fp {#2}
```

```
\__box_rotate_quadrant_four:
```

```
23941 \fp_set:Nn \l__box_sin_fp { sind ( \l__box_angle_fp ) }
```

```
23942 \fp_set:Nn \l__box_cos_fp { cosd ( \l__box_angle_fp ) }
```

```
23943 \__box_rotate:N #1
```

```
23944 }
```

```
23945 }
```

The edges of the box are then recorded: the left edge is always at zero. Rotation of the four edges then takes place: this is most efficiently done on a quadrant by quadrant basis.

```
23946 \cs_new_protected:Npn \__box_rotate:N #1
```

```
23947 {
```

```
23948 \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
```

```
23949 \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
```

```
23950 \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
```

```
23951 \dim_zero:N \l__box_left_dim
```




Figure 1: Co-ordinates of a box prior to rotation.

The next step is to work out the x and y coordinates of vertices of the rotated box in relation to its original coordinates. The box can be visualized with vertices B , C , D and E is illustrated (Figure 1). The vertex O is the reference point on the baseline, and in this implementation is also the centre of rotation. The formulae are, for a point P and angle α :

$$\begin{aligned}
 P'_x &= P_x - O_x \\
 P'_y &= P_y - O_y \\
 P''_x &= (P'_x \cos(\alpha)) - (P'_y \sin(\alpha)) \\
 P''_y &= (P'_x \sin(\alpha)) + (P'_y \cos(\alpha)) \\
 P'''_x &= P''_x + O_x + L_x \\
 P'''_y &= P''_y + O_y
 \end{aligned}$$

The “extra” horizontal translation L_x at the end is calculated so that the leftmost point of the resulting box has x -coordinate 0. This is desirable as T_EX boxes must have the reference point at the left edge of the box. (As O is always $(0,0)$, this part of the calculation is omitted here.)

```

23952 \fp_compare:nNnTF \l__box_sin_fp > \c_zero_fp
23953 {
23954   \fp_compare:nNnTF \l__box_cos_fp > \c_zero_fp
23955   { \__box_rotate_quadrant_one: }
23956   { \__box_rotate_quadrant_two: }
23957 }
23958 {
23959   \fp_compare:nNnTF \l__box_cos_fp < \c_zero_fp
23960   { \__box_rotate_quadrant_three: }
23961   { \__box_rotate_quadrant_four: }
23962 }

```

The position of the box edges are now known, but the box at this stage be misplaced relative to the current T_EX reference point. So the content of the box is moved such that the reference point of the rotated box is in the same place as the original.

```

23963 \hbox_set:Nn \l__box_internal_box { \box_use:N #1 }
23964 \hbox_set:Nn \l__box_internal_box
23965 {
23966   \tex_kern:D -\l__box_left_new_dim
23967   \hbox:n
23968   {
23969     \driver_box_use_rotate:Nn
23970     \l__box_internal_box
23971     \l__box_angle_fp

```

```

23972     }
23973 }

```

Tidy up the size of the box so that the material is actually inside the bounding box. The result can then be used to reset the original box.

```

23974 \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
23975 \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
23976 \box_set_wd:Nn \l__box_internal_box
23977 { \l__box_right_new_dim - \l__box_left_new_dim }
23978 \box_use_drop:N \l__box_internal_box
23979 }

```

These functions take a general point (#1,#2) and rotate its location about the origin, using the previously-set sine and cosine values. Each function gives only one component of the location of the updated point. This is because for rotation of a box each step needs only one value, and so performance is gained by avoiding working out both x' and y' at the same time. Contrast this with the equivalent function in the `l3coffins` module, where both parts are needed.

```

23980 \cs_new_protected:Npn \__box_rotate_xdir:nnN #1#2#3
23981 {
23982   \dim_set:Nn #3
23983   {
23984     \fp_to_dim:n
23985     {
23986       \l__box_cos_fp * \dim_to_fp:n {#1}
23987       - \l__box_sin_fp * \dim_to_fp:n {#2}
23988     }
23989   }
23990 }
23991 \cs_new_protected:Npn \__box_rotate_ydir:nnN #1#2#3
23992 {
23993   \dim_set:Nn #3
23994   {
23995     \fp_to_dim:n
23996     {
23997       \l__box_sin_fp * \dim_to_fp:n {#1}
23998       + \l__box_cos_fp * \dim_to_fp:n {#2}
23999     }
24000   }
24001 }

```

Rotation of the edges is done using a different formula for each quadrant. In every case, the top and bottom edges only need the resulting y -values, whereas the left and right edges need the x -values. Each case is a question of picking out which corner ends up at with the maximum top, bottom, left and right value. Doing this by hand means a lot less calculating and avoids lots of comparisons.

```

24002 \cs_new_protected:Npn \__box_rotate_quadrant_one:
24003 {
24004   \__box_rotate_ydir:nnN \l__box_right_dim \l__box_top_dim
24005   \l__box_top_new_dim
24006   \__box_rotate_ydir:nnN \l__box_left_dim \l__box_bottom_dim
24007   \l__box_bottom_new_dim
24008   \__box_rotate_xdir:nnN \l__box_left_dim \l__box_top_dim
24009   \l__box_left_new_dim

```

```

24010     \__box_rotate_xdir:nnN \l__box_right_dim \l__box_bottom_dim
24011     \l__box_right_new_dim
24012 }
24013 \cs_new_protected:Npn \__box_rotate_quadrant_two:
24014 {
24015     \__box_rotate_ydir:nnN \l__box_right_dim \l__box_bottom_dim
24016     \l__box_top_new_dim
24017     \__box_rotate_ydir:nnN \l__box_left_dim \l__box_top_dim
24018     \l__box_bottom_new_dim
24019     \__box_rotate_xdir:nnN \l__box_right_dim \l__box_top_dim
24020     \l__box_left_new_dim
24021     \__box_rotate_xdir:nnN \l__box_left_dim \l__box_bottom_dim
24022     \l__box_right_new_dim
24023 }
24024 \cs_new_protected:Npn \__box_rotate_quadrant_three:
24025 {
24026     \__box_rotate_ydir:nnN \l__box_left_dim \l__box_bottom_dim
24027     \l__box_top_new_dim
24028     \__box_rotate_ydir:nnN \l__box_right_dim \l__box_top_dim
24029     \l__box_bottom_new_dim
24030     \__box_rotate_xdir:nnN \l__box_right_dim \l__box_bottom_dim
24031     \l__box_left_new_dim
24032     \__box_rotate_xdir:nnN \l__box_left_dim \l__box_top_dim
24033     \l__box_right_new_dim
24034 }
24035 \cs_new_protected:Npn \__box_rotate_quadrant_four:
24036 {
24037     \__box_rotate_ydir:nnN \l__box_left_dim \l__box_top_dim
24038     \l__box_top_new_dim
24039     \__box_rotate_ydir:nnN \l__box_right_dim \l__box_bottom_dim
24040     \l__box_bottom_new_dim
24041     \__box_rotate_xdir:nnN \l__box_left_dim \l__box_bottom_dim
24042     \l__box_left_new_dim
24043     \__box_rotate_xdir:nnN \l__box_right_dim \l__box_top_dim
24044     \l__box_right_new_dim
24045 }

```

(End definition for \box_rotate:Nn and others. This function is documented on page 229.)

\l__box_scale_x_fp Scaling is potentially-different in the two axes.
 \l__box_scale_y_fp

```

24046 \fp_new:N \l__box_scale_x_fp
24047 \fp_new:N \l__box_scale_y_fp

```

(End definition for \l__box_scale_x_fp and \l__box_scale_y_fp.)

\box_resize_to_wd_and_ht_plus_dp:Nnn Resizing a box starts by working out the various dimensions of the existing box.

```

\box_resize_to_wd_and_ht_plus_dp:cnm
\__box_resize_set_corners:N
  \__box_resize:N
  \__box_resize:NNN
24048 \cs_new_protected:Npn \box_resize_to_wd_and_ht_plus_dp:Nnn #1#2#3
24049 {
24050     \hbox_set:Nn #1
24051     {
24052         \__box_resize_set_corners:N #1

```

The x -scaling and resulting box size is easy enough to work out: the dimension is that given as #2, and the scale is simply the new width divided by the old one.

```

24053     \fp_set:Nn \l__box_scale_x_fp
24054     { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }

```

The y -scaling needs both the height and the depth of the current box.

```

24055     \fp_set:Nn \l__box_scale_y_fp
24056     {
24057         \dim_to_fp:n {#3}
24058         / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
24059     }

```

Hand off to the auxiliary which does the rest of the work.

```

24060     \__box_resize:N #1
24061 }
24062 }
24063 \cs_generate_variant:Nn \box_resize_to_wd_and_ht_plus_dp:Nnn { c }
24064 \cs_new_protected:Npn \__box_resize_set_corners:N #1
24065 {
24066     \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
24067     \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
24068     \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
24069     \dim_zero:N \l__box_left_dim
24070 }

```

With at least one real scaling to do, the next phase is to find the new edge co-ordinates. In the x direction this is relatively easy: just scale the right edge. In the y direction, both dimensions have to be scaled, and this again needs the absolute scale value. Once that is all done, the common resize/rescale code can be employed.

```

24071 \cs_new_protected:Npn \__box_resize:N #1
24072 {
24073     \__box_resize:NNN \l__box_right_new_dim
24074     \l__box_scale_x_fp \l__box_right_dim
24075     \__box_resize:NNN \l__box_bottom_new_dim
24076     \l__box_scale_y_fp \l__box_bottom_dim
24077     \__box_resize:NNN \l__box_top_new_dim
24078     \l__box_scale_y_fp \l__box_top_dim
24079     \__box_resize_common:N #1
24080 }
24081 \cs_new_protected:Npn \__box_resize:NNN #1#2#3
24082 {
24083     \dim_set:Nn #1
24084     { \fp_to_dim:n { \fp_abs:n { #2 } * \dim_to_fp:n { #3 } } }
24085 }

```

(End definition for \box_resize_to_wd_and_ht_plus_dp:Nnn and others. This function is documented on page 229.)

\box_resize_to_ht:Nn Scaling to a (total) height or to a width is a simplified version of the main resizing operation, with the scale simply copied between the two parts. The internal auxiliary is called using the scaling value twice, as the sign for both parts is needed (as this allows the same internal code to be used as for the general case).

```

\box_resize_to_ht:cn
\box_resize_to_ht_plus_dp:Nn
\box_resize_to_ht_plus_dp:cn
\box_resize_to_wd:Nn
\box_resize_to_wd:cn
\box_resize_to_wd_and_ht:Nnn
\box_resize_to_wd_and_ht:cnn
24086 \cs_new_protected:Npn \box_resize_to_ht:Nn #1#2
24087 {
24088     \hbox_set:Nn #1
24089     {
24090         \__box_resize_set_corners:N #1
24091         \fp_set:Nn \l__box_scale_y_fp
24092         {

```

```

24093         \dim_to_fp:n {#2}
24094         / \dim_to_fp:n { \l__box_top_dim }
24095     }
24096     \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
24097     \__box_resize:N #1
24098 }
24099 }
24100 \cs_generate_variant:Nn \box_resize_to_ht:Nn { c }
24101 \cs_new_protected:Npn \box_resize_to_ht_plus_dp:Nn #1#2
24102 {
24103     \hbox_set:Nn #1
24104     {
24105         \__box_resize_set_corners:N #1
24106         \fp_set:Nn \l__box_scale_y_fp
24107         {
24108             \dim_to_fp:n {#2}
24109             / \dim_to_fp:n { \l__box_top_dim - \l__box_bottom_dim }
24110         }
24111         \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp
24112         \__box_resize:N #1
24113     }
24114 }
24115 \cs_generate_variant:Nn \box_resize_to_ht_plus_dp:Nn { c }
24116 \cs_new_protected:Npn \box_resize_to_wd:Nn #1#2
24117 {
24118     \hbox_set:Nn #1
24119     {
24120         \__box_resize_set_corners:N #1
24121         \fp_set:Nn \l__box_scale_x_fp
24122         { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
24123         \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp
24124         \__box_resize:N #1
24125     }
24126 }
24127 \cs_generate_variant:Nn \box_resize_to_wd:Nn { c }
24128 \cs_new_protected:Npn \box_resize_to_wd_and_ht:Nnn #1#2#3
24129 {
24130     \hbox_set:Nn #1
24131     {
24132         \__box_resize_set_corners:N #1
24133         \fp_set:Nn \l__box_scale_x_fp
24134         { \dim_to_fp:n {#2} / \dim_to_fp:n { \l__box_right_dim } }
24135         \fp_set:Nn \l__box_scale_y_fp
24136         {
24137             \dim_to_fp:n {#3}
24138             / \dim_to_fp:n { \l__box_top_dim }
24139         }
24140         \__box_resize:N #1
24141     }
24142 }
24143 \cs_generate_variant:Nn \box_resize_to_wd_and_ht:Nnn { c }

```

(End definition for `\box_resize_to_ht:Nn` and others. These functions are documented on page 228.)

`\box_scale:Nnn` When scaling a box, setting the scaling itself is easy enough. The new dimensions are
`\box_scale:cnn`
`__box_scale_aux:N`

also relatively easy to find, allowing only for the need to keep them positive in all cases. Once that is done then after a check for the trivial scaling a hand-off can be made to the common code. The code here is split into two as this allows sharing with the auto-resizing functions.

```

24144 \cs_new_protected:Npn \box_scale:Nnn #1#2#3
24145 {
24146   \hbox_set:Nn #1
24147   {
24148     \fp_set:Nn \l__box_scale_x_fp {#2}
24149     \fp_set:Nn \l__box_scale_y_fp {#3}
24150     \__box_scale_aux:N #1
24151   }
24152 }
24153 \cs_generate_variant:Nn \box_scale:Nnn { c }
24154 \cs_new_protected:Npn \__box_scale_aux:N #1
24155 {
24156   \dim_set:Nn \l__box_top_dim { \box_ht:N #1 }
24157   \dim_set:Nn \l__box_bottom_dim { -\box_dp:N #1 }
24158   \dim_set:Nn \l__box_right_dim { \box_wd:N #1 }
24159   \dim_zero:N \l__box_left_dim
24160   \dim_set:Nn \l__box_top_new_dim
24161     { \fp_abs:n { \l__box_scale_y_fp } \l__box_top_dim }
24162   \dim_set:Nn \l__box_bottom_new_dim
24163     { \fp_abs:n { \l__box_scale_y_fp } \l__box_bottom_dim }
24164   \dim_set:Nn \l__box_right_new_dim
24165     { \fp_abs:n { \l__box_scale_x_fp } \l__box_right_dim }
24166   \__box_resize_common:N #1
24167 }

```

(End definition for `\box_scale:Nnn` and `__box_scale_aux:N`. This function is documented on page 229.)

`\box_autosize_to_wd_and_ht:Nnn`
`\box_autosize_to_wd_and_ht:cn`
`\box_autosize_to_wd_and_ht_plus_dp:Nnn`
`\box_autosize_to_wd_and_ht_plus_dp:cn`
`__box_autosize:Nnnn`

Although autosizing a box uses dimensions, it has more in common in implementation with scaling. As such, most of the real work here is done elsewhere.

```

24168 \cs_new_protected:Npn \box_autosize_to_wd_and_ht:Nnn #1#2#3
24169 { \__box_autosize:Nnnn #1 {#2} {#3} { \box_ht:N #1 } }
24170 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht:Nnn { c }
24171 \cs_new_protected:Npn \box_autosize_to_wd_and_ht_plus_dp:Nnn #1#2#3
24172 { \__box_autosize:Nnnn #1 {#2} {#3} { \box_ht:N #1 + \box_dp:N #1 } }
24173 \cs_generate_variant:Nn \box_autosize_to_wd_and_ht_plus_dp:Nnn { c }
24174 \cs_new_protected:Npn \__box_autosize:Nnnn #1#2#3#4
24175 {
24176   \hbox_set:Nn #1
24177   {
24178     \fp_set:Nn \l__box_scale_x_fp { ( #2 ) / \box_wd:N #1 }
24179     \fp_set:Nn \l__box_scale_y_fp { ( #3 ) / ( #4 ) }
24180     \fp_compare:nNnTF \l__box_scale_x_fp > \l__box_scale_y_fp
24181       { \fp_set_eq:NN \l__box_scale_x_fp \l__box_scale_y_fp }
24182       { \fp_set_eq:NN \l__box_scale_y_fp \l__box_scale_x_fp }
24183     \__box_scale_aux:N #1
24184   }
24185 }

```

(End definition for `\box_autosize_to_wd_and_ht:Nnn`, `\box_autosize_to_wd_and_ht_plus_dp:Nnn`, and `__box_autosize:Nnnn`. These functions are documented on page 227.)

`_box_resize_common:N` The main resize function places its input into a box which start off with zero width, and includes the handles for engine rescaling.

```

24186 \cs_new_protected:Npn \_box_resize_common:N #1
24187 {
24188   \hbox_set:Nn \l__box_internal_box
24189   {
24190     \driver_box_use_scale:Nnn
24191     #1
24192     \l__box_scale_x_fp
24193     \l__box_scale_y_fp
24194   }

```

The new height and depth can be applied directly.

```

24195   \fp_compare:nNnTF \l__box_scale_y_fp > \c_zero_fp
24196   {
24197     \box_set_ht:Nn \l__box_internal_box { \l__box_top_new_dim }
24198     \box_set_dp:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
24199   }
24200   {
24201     \box_set_dp:Nn \l__box_internal_box { \l__box_top_new_dim }
24202     \box_set_ht:Nn \l__box_internal_box { -\l__box_bottom_new_dim }
24203   }

```

Things are not quite as obvious for the width, as the reference point needs to remain unchanged. For positive scaling factors resizing the box is all that is needed. However, for case of a negative scaling the material must be shifted such that the reference point ends up in the right place.

```

24204   \fp_compare:nNnTF \l__box_scale_x_fp < \c_zero_fp
24205   {
24206     \hbox_to_wd:nn { \l__box_right_new_dim }
24207     {
24208       \tex_kern:D \l__box_right_new_dim
24209       \box_use_drop:N \l__box_internal_box
24210       \tex_hss:D
24211     }
24212   }
24213   {
24214     \box_set_wd:Nn \l__box_internal_box { \l__box_right_new_dim }
24215     \hbox:n
24216     {
24217       \tex_kern:D \c_zero_dim
24218       \box_use_drop:N \l__box_internal_box
24219       \tex_hss:D
24220     }
24221   }
24222 }

```

(End definition for _box_resize_common:N.)

```

24223 \</initex | package>

```

40 l3coffins Implementation

```

24224 \<*/initex | package>

```

24225 <@@=coffin>

40.1 Coffins: data structures and general variables

`\l__coffin_internal_box` Scratch variables.

`\l__coffin_internal_dim` 24226 `\box_new:N \l__coffin_internal_box`
`\l__coffin_internal_tl` 24227 `\dim_new:N \l__coffin_internal_dim`
24228 `\tl_new:N \l__coffin_internal_tl`

(End definition for `\l__coffin_internal_box`, `\l__coffin_internal_dim`, and `\l__coffin_internal_tl`.)

`\c__coffin_corners_prop` The “corners”; of a coffin define the real content, as opposed to the TeX bounding box. They all start off in the same place, of course.

24229 `\prop_const_from_keyval:Nn \c__coffin_corners_prop`
24230 `{`
24231 `tl = { Opt } { Opt } ,`
24232 `tr = { Opt } { Opt } ,`
24233 `bl = { Opt } { Opt } ,`
24234 `br = { Opt } { Opt } ,`
24235 `}`

(End definition for `\c__coffin_corners_prop`.)

`\c__coffin_poles_prop` Pole positions are given for horizontal, vertical and reference-point based values.

24236 `\prop_const_from_keyval:Nn \c__coffin_poles_prop`
24237 `{`
24238 `l = { Opt } { Opt } { Opt } { 1000pt } ,`
24239 `hc = { Opt } { Opt } { Opt } { 1000pt } ,`
24240 `r = { Opt } { Opt } { Opt } { 1000pt } ,`
24241 `b = { Opt } { Opt } { 1000pt } { Opt } ,`
24242 `vc = { Opt } { Opt } { 1000pt } { Opt } ,`
24243 `t = { Opt } { Opt } { 1000pt } { Opt } ,`
24244 `B = { Opt } { Opt } { 1000pt } { Opt } ,`
24245 `H = { Opt } { Opt } { 1000pt } { Opt } ,`
24246 `T = { Opt } { Opt } { 1000pt } { Opt } ,`
24247 `}`

(End definition for `\c__coffin_poles_prop`.)

`\l__coffin_slope_x_fp` Used for calculations of intersections.

`\l__coffin_slope_y_fp` 24248 `\fp_new:N \l__coffin_slope_x_fp`
24249 `\fp_new:N \l__coffin_slope_y_fp`

(End definition for `\l__coffin_slope_x_fp` and `\l__coffin_slope_y_fp`.)

`\l__coffin_error_bool` For propagating errors so that parts of the code can work around them.

24250 `\bool_new:N \l__coffin_error_bool`

(End definition for `\l__coffin_error_bool`.)

`\l__coffin_offset_x_dim` The offset between two sets of coffin handles when typesetting. These values are corrected from those requested in an alignment for the positions of the handles.

`\l__coffin_offset_y_dim` 24251 `\dim_new:N \l__coffin_offset_x_dim`
24252 `\dim_new:N \l__coffin_offset_y_dim`

(End definition for `\l__coffin_offset_x_dim` and `\l__coffin_offset_y_dim`.)

`\l__coffin_pole_a_tl` Needed for finding the intersection of two poles.

`\l__coffin_pole_b_tl` 24253 `\tl_new:N \l__coffin_pole_a_tl`
24254 `\tl_new:N \l__coffin_pole_b_tl`

(End definition for `\l__coffin_pole_a_tl` and `\l__coffin_pole_b_tl`.)

`\l__coffin_x_dim` For calculating intersections and so forth.

`\l__coffin_y_dim` 24255 `\dim_new:N \l__coffin_x_dim`
`\l__coffin_x_prime_dim` 24256 `\dim_new:N \l__coffin_y_dim`
`\l__coffin_y_prime_dim` 24257 `\dim_new:N \l__coffin_x_prime_dim`
24258 `\dim_new:N \l__coffin_y_prime_dim`

(End definition for `\l__coffin_x_dim` and others.)

40.2 Basic coffin functions

There are a number of basic functions needed for creating coffins and placing material in them. This all relies on the following data structures.

`__coffin_to_value:N` Coffins are a two-part structure and we rely on the internal nature of box allocation to make everything work. As such, we need an interface to turn coffin identifiers into numbers. For the purposes here, the signature allowed is N despite the nature of the underlying primitive.

24259 `\cs_new_eq:NN __coffin_to_value:N \tex_number:D`

(End definition for `__coffin_to_value:N`.)

`\coffin_if_exist_p:N` Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. A cleaner way to handle this is provided here: both the box and the coffin structure are checked.

`\coffin_if_exist_p:c`
`\coffin_if_exist:NTF`
`\coffin_if_exist:cTF` 24260 `\prg_new_conditional:Npnn \coffin_if_exist:N #1 { p , T , F , TF }`
24261 `{`
24262 `\cs_if_exist:NTF #1`
24263 `{`
24264 `\cs_if_exist:cTF { l__coffin_poles_ __coffin_to_value:N #1 _prop }`
24265 `{ \prg_return_true: }`
24266 `{ \prg_return_false: }`
24267 `}`
24268 `{ \prg_return_false: }`
24269 `}`
24270 `\prg_generate_conditional_variant:Nnn \coffin_if_exist:N`
24271 `{ c } { p , T , F , TF }`

(End definition for `\coffin_if_exist:NTF`. This function is documented on page 231.)

`__coffin_if_exist:NT` Several of the higher-level coffin functions would give multiple errors if the coffin does not exist. So a wrapper is provided to deal with this correctly, issuing an error on erroneous use.

24272 `\cs_new_protected:Npn __coffin_if_exist:NT #1#2`
24273 `{`
24274 `\coffin_if_exist:NTF #1`
24275 `{ #2 }`

```

24276     {
24277         \__kernel_msg_error:nnx { kernel } { unknown-coffin }
24278         { \token_to_str:N #1 }
24279     }
24280 }

```

(End definition for __coffin_if_exist:NT.)

\coffin_clear:N Clearing coffins means emptying the box and resetting all of the structures.

```

\coffin_clear:c
24281 \cs_new_protected:Npn \coffin_clear:N #1
24282 {
24283     \__coffin_if_exist:NT #1
24284     {
24285         \box_clear:N #1
24286         \__coffin_reset_structure:N #1
24287     }
24288 }
24289 \cs_generate_variant:Nn \coffin_clear:N { c }

```

(End definition for \coffin_clear:N. This function is documented on page 231.)

\coffin_new:N Creating a new coffin means making the underlying box and adding the data structures.

\coffin_new:c These are created globally, as there is a need to avoid any strange effects if the coffin is created inside a group. This means that the usual rule about \l_... variables has to be broken. The \debug_suspend: and \debug_resume: functions prevent these checks. They also prevent \prop_clear_new:c from writing useless information to the log file.

```

24290 \cs_new_protected:Npn \coffin_new:N #1
24291 {
24292     \box_new:N #1
24293     \debug_suspend:
24294     \prop_clear_new:c { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24295     \prop_clear_new:c { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
24296     \prop_gset_eq:cN { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24297         \c__coffin_corners_prop
24298     \prop_gset_eq:cN { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
24299         \c__coffin_poles_prop
24300     \debug_resume:
24301 }
24302 \cs_generate_variant:Nn \coffin_new:N { c }

```

(End definition for \coffin_new:N. This function is documented on page 231.)

\hcoffin_set:Nn Horizontal coffins are relatively easy: set the appropriate box, reset the structures then
\hcoffin_set:cn update the handle positions.

```

24303 \cs_new_protected:Npn \hcoffin_set:Nn #1#2
24304 {
24305     \__coffin_if_exist:NT #1
24306     {
24307         \hbox_set:Nn #1
24308         {
24309             \color_ensure_current:
24310             #2
24311         }
24312         \__coffin_reset_structure:N #1

```

```

24313         \_coffin_update_poles:N #1
24314         \_coffin_update_corners:N #1
24315     }
24316 }
24317 \cs_generate_variant:Nn \hcoffin_set:Nn { c }

```

(End definition for \hcoffin_set:Nn. This function is documented on page 231.)

\vcoffin_set:Nnn Setting vertical coffins is more complex. First, the material is typeset with a given width. **\vcoffin_set:cnn** The default handles and poles are set as for a horizontal coffin, before finding the top baseline using a temporary box. No `\color_ensure_current:` here as that would add a whatsit to the start of the vertical box and mess up the location of the T pole (see *TEX by Topic* for discussion of the `\vtop` primitive, used to do the measuring).

```

24318 \cs_new_protected:Npn \vcoffin_set:Nnn #1#2#3
24319 {
24320     \__coffin_if_exist:NT #1
24321     {
24322         \vbox_set:Nn #1
24323         {
24324             \dim_set:Nn \tex_hsize:D {#2}
24325             \*package
24326             \dim_set_eq:NN \linewidth \tex_hsize:D
24327             \dim_set_eq:NN \columnwidth \tex_hsize:D
24328             \*package
24329             #3
24330         }
24331         \_coffin_reset_structure:N #1
24332         \_coffin_update_poles:N #1
24333         \_coffin_update_corners:N #1
24334         \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
24335         \_coffin_set_pole:Nnx #1 { T }
24336         {
24337             { Opt }
24338             {
24339                 \dim_eval:n
24340                 { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
24341             }
24342             { 1000pt }
24343             { Opt }
24344         }
24345         \box_clear:N \l__coffin_internal_box
24346     }
24347 }
24348 \cs_generate_variant:Nn \vcoffin_set:Nnn { c }

```

(End definition for \vcoffin_set:Nnn. This function is documented on page 232.)

\hcoffin_set:Nw These are the “begin”/“end” versions of the above: watch the grouping!
\hcoffin_set:cw
\hcoffin_set_end:

```

24349 \cs_new_protected:Npn \hcoffin_set:Nw #1
24350 {
24351     \__coffin_if_exist:NT #1
24352     {
24353         \hbox_set:Nw #1 \color_ensure_current:
24354         \cs_set_protected:Npn \hcoffin_set_end:

```

```

24355         {
24356             \hbox_set_end:
24357             \__coffin_reset_structure:N #1
24358             \__coffin_update_poles:N #1
24359             \__coffin_update_corners:N #1
24360         }
24361     }
24362 }
24363 \cs_new_protected:Npn \hcoffin_set_end: { }
24364 \cs_generate_variant:Nn \hcoffin_set:Nw { c }

```

(End definition for \hcoffin_set:Nw and \hcoffin_set_end:. These functions are documented on page 231.)

\vcoffin_set:Nnw The same for vertical coffins.

```

\vcoffin_set:cnw 24365 \cs_new_protected:Npn \vcoffin_set:Nnw #1#2
\vcoffin_set_end: 24366 {
24367     \__coffin_if_exist:NT #1
24368     {
24369         \vbox_set:Nw #1
24370         \dim_set:Nn \tex_hsize:D {#2}
24371     }*package)
24372         \dim_set_eq:NN \linewidth \tex_hsize:D
24373         \dim_set_eq:NN \columnwidth \tex_hsize:D
24374     }/package)
24375     \cs_set_protected:Npn \vcoffin_set_end:
24376     {
24377         \vbox_set_end:
24378         \__coffin_reset_structure:N #1
24379         \__coffin_update_poles:N #1
24380         \__coffin_update_corners:N #1
24381         \vbox_set_top:Nn \l__coffin_internal_box { \vbox_unpack:N #1 }
24382         \__coffin_set_pole:Nnx #1 { T }
24383         {
24384             { Opt }
24385             {
24386                 \dim_eval:n
24387                 { \box_ht:N #1 - \box_ht:N \l__coffin_internal_box }
24388             }
24389             { 1000pt }
24390             { Opt }
24391         }
24392         \box_clear:N \l__coffin_internal_box
24393     }
24394 }
24395 }
24396 \cs_new_protected:Npn \vcoffin_set_end: { }
24397 \cs_generate_variant:Nn \vcoffin_set:Nnw { c }

```

(End definition for \vcoffin_set:Nnw and \vcoffin_set_end:. These functions are documented on page 232.)

\coffin_set_eq:NN Setting two coffins equal is just a wrapper around other functions.

```

\coffin_set_eq:Nc 24398 \cs_new_protected:Npn \coffin_set_eq:NN #1#2
\coffin_set_eq:cN 24399 {
\coffin_set_eq:cc

```

```

24400     \__coffin_if_exist:NT #1
24401     {
24402         \box_set_eq:NN #1 #2
24403         \__coffin_set_eq_structure:NN #1 #2
24404     }
24405 }
24406 \cs_generate_variant:Nn \coffin_set_eq:NN { c , Nc , cc }

```

(End definition for `\coffin_set_eq:NN`. This function is documented on page 231.)

`\c_empty_coffin` Special coffins: these cannot be set up earlier as they need `\coffin_new:N`. The empty coffin is set as a box as the full coffin-setting system needs some material which is not yet available. The empty coffin is created entirely by hand: not everything is in place yet.

```

24407 \coffin_new:N \c_empty_coffin
24408 \tex_setbox:D \c_empty_coffin = \tex_hbox:D { }
24409 \coffin_new:N \l__coffin_aligned_coffin
24410 \coffin_new:N \l__coffin_aligned_internal_coffin

```

(End definition for `\c_empty_coffin`, `\l__coffin_aligned_coffin`, and `\l__coffin_aligned_internal_coffin`. This variable is documented on page 234.)

`\l_tmpa_coffin` The usual scratch space.

```

24411 \coffin_new:N \l_tmpa_coffin
24412 \coffin_new:N \l_tmpb_coffin

```

(End definition for `\l_tmpa_coffin` and `\l_tmpb_coffin`. These variables are documented on page 234.)

40.3 Measuring coffins

`\coffin_dp:N` Coffins are just boxes when it comes to measurement. However, semantically a separate set of functions are required.

```

24413 \cs_new_eq:NN \coffin_dp:N \box_dp:N
24414 \cs_new_eq:NN \coffin_dp:c \box_dp:c
24415 \cs_new_eq:NN \coffin_ht:N \box_ht:N
24416 \cs_new_eq:NN \coffin_ht:c \box_ht:c
24417 \cs_new_eq:NN \coffin_wd:N \box_wd:N
24418 \cs_new_eq:NN \coffin_wd:c \box_wd:c

```

(End definition for `\coffin_dp:N`, `\coffin_ht:N`, and `\coffin_wd:N`. These functions are documented on page 233.)

40.4 Coffins: handle and pole management

`__coffin_get_pole:NnN` A simple wrapper around the recovery of a coffin pole, with some error checking and recovery built-in.

```

24419 \cs_new_protected:Npn \__coffin_get_pole:NnN #1#2#3
24420 {
24421     \prop_get:cnNF
24422     { l__coffin_poles_ \__coffin_to_value:N #1 _prop } {#2} #3
24423     {
24424         \__kernel_msg_error:nxxx { kernel } { unknown-coffin-pole }
24425         { \exp_not:n {#2} } { \token_to_str:N #1 }
24426         \tl_set:Nn #3 { { Opt } { Opt } { Opt } { Opt } }
24427     }
24428 }

```

(End definition for _coffin_get_pole:NnN.)

_coffin_reset_structure:N Resetting the structure is a simple copy job.

```

24429 \cs_new_protected:Npn \_coffin_reset_structure:N #1
24430 {
24431   \prop_set_eq:cN { l__coffin_corners_ \_coffin_to_value:N #1 _prop }
24432   \c__coffin_corners_prop
24433   \prop_set_eq:cN { l__coffin_poles_ \_coffin_to_value:N #1 _prop }
24434   \c__coffin_poles_prop
24435 }

```

(End definition for _coffin_reset_structure:N.)

_coffin_set_eq_structure:NN Setting coffin structures equal simply means copying the property list.

```

\_coffin_gset_eq_structure:NN
24436 \cs_new_protected:Npn \_coffin_set_eq_structure:NN #1#2
24437 {
24438   \prop_set_eq:cc { l__coffin_corners_ \_coffin_to_value:N #1 _prop }
24439   { l__coffin_corners_ \_coffin_to_value:N #2 _prop }
24440   \prop_set_eq:cc { l__coffin_poles_ \_coffin_to_value:N #1 _prop }
24441   { l__coffin_poles_ \_coffin_to_value:N #2 _prop }
24442 }
24443 \cs_new_protected:Npn \_coffin_gset_eq_structure:NN #1#2
24444 {
24445   \prop_gset_eq:cc { l__coffin_corners_ \_coffin_to_value:N #1 _prop }
24446   { l__coffin_corners_ \_coffin_to_value:N #2 _prop }
24447   \prop_gset_eq:cc { l__coffin_poles_ \_coffin_to_value:N #1 _prop }
24448   { l__coffin_poles_ \_coffin_to_value:N #2 _prop }
24449 }

```

(End definition for _coffin_set_eq_structure:NN and _coffin_gset_eq_structure:NN.)

\coffin_set_horizontal_pole:Nnn

\coffin_set_horizontal_pole:cnm

\coffin_set_vertical_pole:Nnn

\coffin_set_vertical_pole:cnm

_coffin_set_pole:Nnn

_coffin_set_pole:Nnx

Setting the pole of a coffin at the user/designer level requires a bit more care. The idea here is to provide a reasonable interface to the system, then to do the setting with full expansion. The three-argument version is used internally to do a direct setting.

```

24450 \cs_new_protected:Npn \coffin_set_horizontal_pole:Nnn #1#2#3
24451 {
24452   \_coffin_if_exist:NT #1
24453   {
24454     \_coffin_set_pole:Nnx #1 {#2}
24455     {
24456       { Opt } { \dim_eval:n {#3} }
24457       { 1000pt } { Opt }
24458     }
24459   }
24460 }
24461 \cs_new_protected:Npn \coffin_set_vertical_pole:Nnn #1#2#3
24462 {
24463   \_coffin_if_exist:NT #1
24464   {
24465     \_coffin_set_pole:Nnx #1 {#2}
24466     {
24467       { \dim_eval:n {#3} } { Opt }
24468       { Opt } { 1000pt }
24469     }

```



```

24470     }
24471   }
24472   \cs_new_protected:Npn \__coffin_set_pole:Nnn #1#2#3
24473   {
24474     \prop_put:cnn { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
24475     {#2} {#3}
24476   }
24477   \cs_generate_variant:Nn \coffin_set_horizontal_pole:Nnn { c }
24478   \cs_generate_variant:Nn \coffin_set_vertical_pole:Nnn { c }
24479   \cs_generate_variant:Nn \__coffin_set_pole:Nnn { Nnx }

```

(End definition for `\coffin_set_horizontal_pole:Nnn`, `\coffin_set_vertical_pole:Nnn`, and `__coffin_set_pole:Nnn`. These functions are documented on page 232.)

`__coffin_update_corners:N` Updating the corners of a coffin is straight-forward as at this stage there can be no rotation. So the corners of the content are just those of the underlying \TeX box.

```

24480   \cs_new_protected:Npn \__coffin_update_corners:N #1
24481   {
24482     \prop_put:cnx { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24483     { tl }
24484     { { Opt } { \dim_eval:n { \box_ht:N #1 } } }
24485     \prop_put:cnx { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24486     { tr }
24487     {
24488       { \dim_eval:n { \box_wd:N #1 } }
24489       { \dim_eval:n { \box_ht:N #1 } }
24490     }
24491     \prop_put:cnx { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24492     { bl }
24493     { { Opt } { \dim_eval:n { -\box_dp:N #1 } } }
24494     \prop_put:cnx { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24495     { br }
24496     {
24497       { \dim_eval:n { \box_wd:N #1 } }
24498       { \dim_eval:n { -\box_dp:N #1 } }
24499     }
24500   }

```

(End definition for `__coffin_update_corners:N`.)

`__coffin_update_poles:N` This function is called when a coffin is set, and updates the poles to reflect the nature of size of the box. Thus this function only alters poles where the default position is dependent on the size of the box. It also does not set poles which are relevant only to vertical coffins.

```

24501   \cs_new_protected:Npn \__coffin_update_poles:N #1
24502   {
24503     \prop_put:cnx { l__coffin_poles_ \__coffin_to_value:N #1 _prop } { hc }
24504     {
24505       { \dim_eval:n { 0.5 \box_wd:N #1 } }
24506       { Opt } { Opt } { 1000pt }
24507     }
24508     \prop_put:cnx { l__coffin_poles_ \__coffin_to_value:N #1 _prop } { r }
24509     {
24510       { \dim_eval:n { \box_wd:N #1 } }

```

```

24511         { Opt } { Opt } { 1000pt }
24512     }
24513     \prop_put:cnx { l__coffin_poles_ \_coffin_to_value:N #1 _prop } { vc }
24514     {
24515         { Opt }
24516         { \dim_eval:n { ( \box_ht:N #1 - \box_dp:N #1 ) / 2 } }
24517         { 1000pt }
24518         { Opt }
24519     }
24520     \prop_put:cnx { l__coffin_poles_ \_coffin_to_value:N #1 _prop } { t }
24521     {
24522         { Opt }
24523         { \dim_eval:n { \box_ht:N #1 } }
24524         { 1000pt }
24525         { Opt }
24526     }
24527     \prop_put:cnx { l__coffin_poles_ \_coffin_to_value:N #1 _prop } { b }
24528     {
24529         { Opt }
24530         { \dim_eval:n { -\box_dp:N #1 } }
24531         { 1000pt }
24532         { Opt }
24533     }
24534 }

```

(End definition for _coffin_update_poles:N.)

40.5 Coffins: calculation of pole intersections

```

\_coffin_calculate_intersection:Nnn
\_coffin_calculate_intersection:nnnnnnnn
\_coffin_calculate_intersection_aux:nnnnnN

```

The lead off in finding intersections is to recover the two poles and then hand off to the auxiliary for the actual calculation. There may of course not be an intersection, for which an error trap is needed.

```

24535 \cs_new_protected:Npn \_coffin_calculate_intersection:Nnn #1#2#3
24536 {
24537     \_coffin_get_pole:NnN #1 {#2} \l__coffin_pole_a_tl
24538     \_coffin_get_pole:NnN #1 {#3} \l__coffin_pole_b_tl
24539     \bool_set_false:N \l__coffin_error_bool
24540     \exp_last_two_unbraced:Noo
24541         \_coffin_calculate_intersection:nnnnnnnn
24542         \l__coffin_pole_a_tl \l__coffin_pole_b_tl
24543     \bool_if:NT \l__coffin_error_bool
24544     {
24545         \_kernel_msg_error:nn { kernel } { no-pole-intersection }
24546         \dim_zero:N \l__coffin_x_dim
24547         \dim_zero:N \l__coffin_y_dim
24548     }
24549 }

```

The two poles passed here each have four values (as dimensions), (a, b, c, d) and (a', b', c', d') . These are arguments 1–4 and 5–8, respectively. In both cases a and b are the co-ordinates of a point on the pole and c and d define the direction of the pole. Finding the intersection depends on the directions of the poles, which are given by d/c and d'/c' . However, if one of the poles is either horizontal or vertical then one or more of c, d, c' and d' are zero and a special case is needed.

```

24550 \cs_new_protected:Npn \__coffin_calculate_intersection:nnnnnnnn
24551   #1#2#3#4#5#6#7#8
24552   {
24553     \dim_compare:nNnTF {#3} = { \c_zero_dim }

```

The case where the first pole is vertical. So the x -component of the interaction is at a . There is then a test on the second pole: if it is also vertical then there is an error.

```

24554     {
24555       \dim_set:Nn \l__coffin_x_dim {#1}
24556       \dim_compare:nNnTF {#7} = \c_zero_dim
24557       { \bool_set_true:N \l__coffin_error_bool }

```

The second pole may still be horizontal, in which case the y -component of the intersection is b' . If not,

$$y = \frac{d'}{c'}(x - a') + b'$$

with the x -component already known to be #1. This calculation is done as a generalised auxiliary.

```

24558     {
24559       \dim_compare:nNnTF {#8} = \c_zero_dim
24560       { \dim_set:Nn \l__coffin_y_dim {#6} }
24561       {
24562         \__coffin_calculate_intersection_aux:nnnnnnN
24563         {#1} {#5} {#6} {#7} {#8} \l__coffin_y_dim
24564       }
24565     }
24566   }

```

If the first pole is not vertical then it may be horizontal. If so, then the procedure is essentially the same as that already done but with the x - and y -components interchanged.

```

24567   {
24568     \dim_compare:nNnTF {#4} = \c_zero_dim
24569     {
24570       \dim_set:Nn \l__coffin_y_dim {#2}
24571       \dim_compare:nNnTF {#8} = { \c_zero_dim }
24572       { \bool_set_true:N \l__coffin_error_bool }
24573       {
24574         \dim_compare:nNnTF {#7} = \c_zero_dim
24575         { \dim_set:Nn \l__coffin_x_dim {#5} }

```

The formula for the case where the second pole is neither horizontal nor vertical is

$$x = \frac{c'}{d'}(y - b') + a'$$

which is again handled by the same auxiliary.

```

24576     {
24577       \__coffin_calculate_intersection_aux:nnnnnnN
24578       {#2} {#6} {#5} {#8} {#7} \l__coffin_x_dim
24579     }
24580   }
24581 }

```

The first pole is neither horizontal nor vertical. This still leaves the second pole, which may be a special case. For those possibilities, the calculations are the same as above with the first and second poles interchanged.

```

24582     {
24583         \dim_compare:nNnTF {#7} = \c_zero_dim
24584         {
24585             \dim_set:Nn \l__coffin_x_dim {#5}
24586             \__coffin_calculate_intersection_aux:nnnnnN
24587             {#5} {#1} {#2} {#3} {#4} \l__coffin_y_dim
24588         }
24589         {
24590             \dim_compare:nNnTF {#8} = \c_zero_dim
24591             {
24592                 \dim_set:Nn \l__coffin_y_dim {#6}
24593                 \__coffin_calculate_intersection_aux:nnnnnN
24594                 {#6} {#2} {#1} {#4} {#3} \l__coffin_x_dim
24595             }

```

If none of the special cases apply then there is still a need to check that there is a unique intersection between the two pole. This is the case if they have different slopes.

```

24596     {
24597         \fp_set:Nn \l__coffin_slope_x_fp
24598         { \dim_to_fp:n {#4} / \dim_to_fp:n {#3} }
24599         \fp_set:Nn \l__coffin_slope_y_fp
24600         { \dim_to_fp:n {#8} / \dim_to_fp:n {#7} }
24601         \fp_compare:nNnTF
24602         { \l__coffin_slope_x_fp = \l__coffin_slope_y_fp
24603         { \bool_set_true:N \l__coffin_error_bool }

```

All of the tests pass, so there is the full complexity of the calculation:

$$x = \frac{a(d/c) - a'(d'/c') - b + b'}{(d/c) - (d'/c')}$$

and noting that the two ratios are already worked out from the test just performed. There is quite a bit of shuffling from dimensions to floating points in order to do the work. The y -values is then worked out using the standard auxiliary starting from the x -position.

```

24604     {
24605         \dim_set:Nn \l__coffin_x_dim
24606         {
24607             \fp_to_dim:n
24608             {
24609                 (
24610                     \dim_to_fp:n {#1} *
24611                     \l__coffin_slope_x_fp
24612                     - ( \dim_to_fp:n {#5} *
24613                         \l__coffin_slope_y_fp )
24614                     - \dim_to_fp:n {#2}
24615                     + \dim_to_fp:n {#6}
24616                 )
24617                 /
24618                 (
24619                     \l__coffin_slope_x_fp -
24620                     \l__coffin_slope_y_fp
24621                 )
24622             }
24623         }

```

```

24624         \__coffin_calculate_intersection_aux:nnnnnN
24625         { \l__coffin_x_dim }
24626         {#5} {#6} {#8} {#7} \l__coffin_y_dim
24627     }
24628 }
24629 }
24630 }
24631 }
24632 }

```

The formula for finding the intersection point is in most cases the same. The formula here is

$$\#6 = \#4 \cdot \left(\frac{\#1 - \#2}{\#5} \right) \#3$$

Thus #4 and #5 should be the directions of the pole while #2 and #3 are co-ordinates.

```

24633 \cs_new_protected:Npn \__coffin_calculate_intersection_aux:nnnnnN
24634     #1#2#3#4#5#6
24635     {
24636     \dim_set:Nn #6
24637     {
24638     \fp_to_dim:n
24639     {
24640     \dim_to_fp:n {#4} *
24641     ( \dim_to_fp:n {#1} - \dim_to_fp:n {#2} ) /
24642     \dim_to_fp:n {#5}
24643     + \dim_to_fp:n {#3}
24644     }
24645     }
24646 }

```

(End definition for __coffin_calculate_intersection:Nnn, __coffin_calculate_intersection:nnnnnnnn, and __coffin_calculate_intersection_aux:nnnnnN.)

40.6 Aligning and typesetting of coffins

\coffin_join:NnnNnnnn
\coffin_join:cnnNnnnn
\coffin_join:Nnnncnnnn
\coffin_join:cnncnnnn

This command joins two coffins, using a horizontal and vertical pole from each coffin and making an offset between the two. The result is stored as the as a third coffin, which has all of its handles reset to standard values. First, the more basic alignment function is used to get things started.

```

24647 \cs_new_protected:Npn \coffin_join:NnnNnnnn #1#2#3#4#5#6#7#8
24648 {
24649     \__coffin_align:NnnNnnnnN
24650     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin

```

Correct the placement of the reference point. If the x -offset is negative then the reference point of the second box is to the left of that of the first, which is corrected using a kern. On the right side the first box might stick out, which would show up if it is wider than the sum of the x -offset and the width of the second box. So a second kern may be needed.

```

24651     \hbox_set:Nn \l__coffin_aligned_coffin
24652     {
24653     \dim_compare:nNnT { \l__coffin_offset_x_dim } < \c_zero_dim
24654     { \tex_kern:D -\l__coffin_offset_x_dim }
24655     \hbox_unpack:N \l__coffin_aligned_coffin
24656     \dim_set:Nn \l__coffin_internal_dim

```

```

24657         { \l__coffin_offset_x_dim - \box_wd:N #1 + \box_wd:N #4 }
24658         \dim_compare:nNnT \l__coffin_internal_dim < \c_zero_dim
24659         { \tex_kern:D -\l__coffin_internal_dim }
24660     }

```

The coffin structure is reset, and the corners are cleared: only those from the two parent coffins are needed.

```

24661     \__coffin_reset_structure:N \l__coffin_aligned_coffin
24662     \prop_clear:c
24663     {
24664         l__coffin_corners_
24665         \__coffin_to_value:N \l__coffin_aligned_coffin
24666         _prop
24667     }
24668     \__coffin_update_poles:N \l__coffin_aligned_coffin

```

The structures of the parent coffins are now transferred to the new coffin, which requires that the appropriate offsets are applied. That then depends on whether any shift was needed.

```

24669     \dim_compare:nNnTF \l__coffin_offset_x_dim < \c_zero_dim
24670     {
24671         \__coffin_offset_poles:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
24672         \__coffin_offset_poles:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
24673         \__coffin_offset_corners:Nnn #1 { -\l__coffin_offset_x_dim } { Opt }
24674         \__coffin_offset_corners:Nnn #4 { Opt } { \l__coffin_offset_y_dim }
24675     }
24676     {
24677         \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
24678         \__coffin_offset_poles:Nnn #4
24679         { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
24680         \__coffin_offset_corners:Nnn #1 { Opt } { Opt }
24681         \__coffin_offset_corners:Nnn #4
24682         { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
24683     }
24684     \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
24685     \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
24686 }
24687 \cs_generate_variant:Nn \coffin_join:NnnNnnnn { c , Nnnnc , cnnnc }

```

(End definition for `\coffin_join:NnnNnnnn`. This function is documented on page 233.)

`\coffin_attach:NnnNnnnn`
`\coffin_attach:cnnNnnnn`
`\coffin_attach:Nnnncnnnn`
`\coffin_attach:cnnncnnnn`

A more simple version of the above, as it simply uses the size of the first coffin for the new one. This means that the work here is rather simplified compared to the above code. The function used when marking a position is hear also as it is similar but without the structure updates.

`\coffin_attach_mark:NnnNnnnn`

```

24688 \cs_new_protected:Npn \coffin_attach:NnnNnnnn #1#2#3#4#5#6#7#8
24689 {
24690     \__coffin_align:NnnNnnnnN
24691     #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
24692     \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
24693     \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
24694     \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
24695     \__coffin_reset_structure:N \l__coffin_aligned_coffin
24696     \prop_set_eq:cc
24697     {

```

```

24698     l__coffin_corners_
24699     \__coffin_to_value:N \l__coffin_aligned_coffin _prop
24700   }
24701   { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24702   \__coffin_update_poles:N \l__coffin_aligned_coffin
24703   \__coffin_offset_poles:Nnn #1 { Opt } { Opt }
24704   \__coffin_offset_poles:Nnn #4
24705   { \l__coffin_offset_x_dim } { \l__coffin_offset_y_dim }
24706   \__coffin_update_vertical_poles:NNN #1 #4 \l__coffin_aligned_coffin
24707   \coffin_set_eq:NN #1 \l__coffin_aligned_coffin
24708 }
24709 \cs_new_protected:Npn \coffin_attach_mark:NnnNnnnn #1#2#3#4#5#6#7#8
24710 {
24711   \__coffin_align:NnnNnnnnN
24712   #1 {#2} {#3} #4 {#5} {#6} {#7} {#8} \l__coffin_aligned_coffin
24713   \box_set_ht:Nn \l__coffin_aligned_coffin { \box_ht:N #1 }
24714   \box_set_dp:Nn \l__coffin_aligned_coffin { \box_dp:N #1 }
24715   \box_set_wd:Nn \l__coffin_aligned_coffin { \box_wd:N #1 }
24716   \box_set_eq:NN #1 \l__coffin_aligned_coffin
24717 }
24718 \cs_generate_variant:Nn \coffin_attach:NnnNnnnn { c , Nnnc , cnnc }

```

(End definition for `\coffin_attach:NnnNnnnn` and `\coffin_attach_mark:NnnNnnnn`. These functions are documented on page 232.)

`__coffin_align:NnnNnnnnN`

The internal function aligns the two coffins into a third one, but performs no corrections on the resulting coffin poles. The process begins by finding the points of intersection for the poles for each of the input coffins. Those for the first coffin are worked out after those for the second coffin, as this allows the ‘primed’ storage area to be used for the second coffin. The ‘real’ box offsets are then calculated, before using these to re-box the input coffins. The default poles are then set up, but the final result depends on how the bounding box is being handled.

```

24719 \cs_new_protected:Npn \__coffin_align:NnnNnnnnN #1#2#3#4#5#6#7#8#9
24720 {
24721   \__coffin_calculate_intersection:Nnn #4 {#5} {#6}
24722   \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
24723   \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
24724   \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
24725   \dim_set:Nn \l__coffin_offset_x_dim
24726   { \l__coffin_x_dim - \l__coffin_x_prime_dim + #7 }
24727   \dim_set:Nn \l__coffin_offset_y_dim
24728   { \l__coffin_y_dim - \l__coffin_y_prime_dim + #8 }
24729   \hbox_set:Nn \l__coffin_aligned_internal_coffin
24730   {
24731     \box_use:N #1
24732     \tex_kern:D -\box_wd:N #1
24733     \tex_kern:D \l__coffin_offset_x_dim
24734     \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #4 }
24735   }
24736   \coffin_set_eq:NN #9 \l__coffin_aligned_internal_coffin
24737 }

```

(End definition for `__coffin_align:NnnNnnnnN`.)

```

\__coffin_offset_poles:Nnn
  \__coffin_offset_pole:Nnnnnnn

```

Transferring structures from one coffin to another requires that the positions are updated by the offset between the two coffins. This is done by mapping to the property list of the source coffins, moving as appropriate and saving to the new coffin data structures. The test for a - means that the structures from the parent coffins are uniquely labelled and do not depend on the order of alignment. The pay off for this is that - should not be used in coffin pole or handle names, and that multiple alignments do not result in a whole set of values.

```

24738 \cs_new_protected:Npn \__coffin_offset_poles:Nnn #1#2#3
24739 {
24740   \prop_map_inline:cn { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
24741   { \__coffin_offset_pole:Nnnnnnn #1 {##1} ##2 {#2} {#3} }
24742 }
24743 \cs_new_protected:Npn \__coffin_offset_pole:Nnnnnnn #1#2#3#4#5#6#7#8
24744 {
24745   \dim_set:Nn \l__coffin_x_dim { #3 + #7 }
24746   \dim_set:Nn \l__coffin_y_dim { #4 + #8 }
24747   \tl_if_in:nnTF {#2} { - }
24748   { \tl_set:Nn \l__coffin_internal_tl { {#2} } }
24749   { \tl_set:Nn \l__coffin_internal_tl { { #1 - #2 } } }
24750   \exp_last_unbraced:NNo \__coffin_set_pole:Nnx \l__coffin_aligned_coffin
24751   { \l__coffin_internal_tl }
24752   {
24753     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
24754     {#5} {#6}
24755   }
24756 }

```

(End definition for __coffin_offset_poles:Nnn and __coffin_offset_pole:Nnnnnnn.)

```

\__coffin_offset_corners:Nnn
  \__coffin_offset_corner:Nnnnn

```

Saving the offset corners of a coffin is very similar, except that there is no need to worry about naming: every corner can be saved here as order is unimportant.

```

24757 \cs_new_protected:Npn \__coffin_offset_corners:Nnn #1#2#3
24758 {
24759   \prop_map_inline:cn { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
24760   { \__coffin_offset_corner:Nnnnn #1 {##1} ##2 {#2} {#3} }
24761 }
24762 \cs_new_protected:Npn \__coffin_offset_corner:Nnnnn #1#2#3#4#5#6
24763 {
24764   \prop_put:cnx
24765   {
24766     l__coffin_corners_
24767     \__coffin_to_value:N \l__coffin_aligned_coffin _prop
24768   }
24769   { #1 - #2 }
24770   {
24771     { \dim_eval:n { #3 + #5 } }
24772     { \dim_eval:n { #4 + #6 } }
24773   }
24774 }

```

(End definition for __coffin_offset_corners:Nnn and __coffin_offset_corner:Nnnnn.)


```

\__coffin_update_vertical_poles:NNN
\__coffin_update_T:nnnnnnnnN
\__coffin_update_B:nnnnnnnnN

```

The T and B poles need to be recalculated after alignment. These functions find the larger absolute value for the poles, but this is of course only logical when the poles are horizontal.

```

24775 \cs_new_protected:Npn \__coffin_update_vertical_poles:NNN #1#2#3
24776 {
24777   \__coffin_get_pole:NnN #3 { #1 -T } \l__coffin_pole_a_tl
24778   \__coffin_get_pole:NnN #3 { #2 -T } \l__coffin_pole_b_tl
24779   \exp_last_two_unbraced:Noo \__coffin_update_T:nnnnnnnnN
24780   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
24781   \__coffin_get_pole:NnN #3 { #1 -B } \l__coffin_pole_a_tl
24782   \__coffin_get_pole:NnN #3 { #2 -B } \l__coffin_pole_b_tl
24783   \exp_last_two_unbraced:Noo \__coffin_update_B:nnnnnnnnN
24784   \l__coffin_pole_a_tl \l__coffin_pole_b_tl #3
24785 }
24786 \cs_new_protected:Npn \__coffin_update_T:nnnnnnnnN #1#2#3#4#5#6#7#8#9
24787 {
24788   \dim_compare:nNnTF {#2} < {#6}
24789   {
24790     \__coffin_set_pole:Nnx #9 { T }
24791     { { Opt } {#6} { 1000pt } { Opt } }
24792   }
24793   {
24794     \__coffin_set_pole:Nnx #9 { T }
24795     { { Opt } {#2} { 1000pt } { Opt } }
24796   }
24797 }
24798 \cs_new_protected:Npn \__coffin_update_B:nnnnnnnnN #1#2#3#4#5#6#7#8#9
24799 {
24800   \dim_compare:nNnTF {#2} < {#6}
24801   {
24802     \__coffin_set_pole:Nnx #9 { B }
24803     { { Opt } {#2} { 1000pt } { Opt } }
24804   }
24805   {
24806     \__coffin_set_pole:Nnx #9 { B }
24807     { { Opt } {#6} { 1000pt } { Opt } }
24808   }
24809 }

```

(End definition for `__coffin_update_vertical_poles:NNN`, `__coffin_update_T:nnnnnnnnN`, and `__coffin_update_B:nnnnnnnnN`.)

```

\coffin_typeset:Nnnnn
\coffin_typeset:cnnnn

```

Typesetting a coffin means aligning it with the current position, which is done using a coffin with no content at all. As well as aligning to the empty coffin, there is also a need to leave vertical mode, if necessary.

```

24810 \cs_new_protected:Npn \coffin_typeset:Nnnnn #1#2#3#4#5
24811 {
24812   \mode_leave_vertical:
24813   \__coffin_align:NnnNnnnnN \c_empty_coffin { H } { 1 }
24814   #1 {#2} {#3} {#4} {#5} \l__coffin_aligned_coffin
24815   \box_use_drop:N \l__coffin_aligned_coffin
24816 }
24817 \cs_generate_variant:Nn \coffin_typeset:Nnnnn { c }

```

(End definition for `\coffin_typeset:Nnnnn`. This function is documented on page [233](#).)

40.7 Coffin diagnostics

`\l__coffin_display_coffin` Used for printing coffins with data structures attached.

```

\l__coffin_display_coord_coffin 24818 \coffin_new:N \l__coffin_display_coffin
\l__coffin_display_pole_coffin 24819 \coffin_new:N \l__coffin_display_coord_coffin
24820 \coffin_new:N \l__coffin_display_pole_coffin

```

(End definition for \l__coffin_display_coffin, \l__coffin_display_coord_coffin, and \l__coffin_display_pole_coffin.)

`\l__coffin_display_handles_prop` This property list is used to print coffin handles at suitable positions. The offsets are expressed as multiples of the basic offset value, which therefore acts as a scale-factor.

```

24821 \prop_new:N \l__coffin_display_handles_prop
24822 \prop_put:Nnn \l__coffin_display_handles_prop { tl }
24823 { { b } { r } { -1 } { 1 } }
24824 \prop_put:Nnn \l__coffin_display_handles_prop { thc }
24825 { { b } { hc } { 0 } { 1 } }
24826 \prop_put:Nnn \l__coffin_display_handles_prop { tr }
24827 { { b } { l } { 1 } { 1 } }
24828 \prop_put:Nnn \l__coffin_display_handles_prop { vcl }
24829 { { vc } { r } { -1 } { 0 } }
24830 \prop_put:Nnn \l__coffin_display_handles_prop { vhc }
24831 { { vc } { hc } { 0 } { 0 } }
24832 \prop_put:Nnn \l__coffin_display_handles_prop { vcr }
24833 { { vc } { l } { 1 } { 0 } }
24834 \prop_put:Nnn \l__coffin_display_handles_prop { bl }
24835 { { t } { r } { -1 } { -1 } }
24836 \prop_put:Nnn \l__coffin_display_handles_prop { bhc }
24837 { { t } { hc } { 0 } { -1 } }
24838 \prop_put:Nnn \l__coffin_display_handles_prop { br }
24839 { { t } { l } { 1 } { -1 } }
24840 \prop_put:Nnn \l__coffin_display_handles_prop { Tl }
24841 { { t } { r } { -1 } { -1 } }
24842 \prop_put:Nnn \l__coffin_display_handles_prop { Thc }
24843 { { t } { hc } { 0 } { -1 } }
24844 \prop_put:Nnn \l__coffin_display_handles_prop { Tr }
24845 { { t } { l } { 1 } { -1 } }
24846 \prop_put:Nnn \l__coffin_display_handles_prop { Hl }
24847 { { vc } { r } { -1 } { 1 } }
24848 \prop_put:Nnn \l__coffin_display_handles_prop { Hhc }
24849 { { vc } { hc } { 0 } { 1 } }
24850 \prop_put:Nnn \l__coffin_display_handles_prop { Hr }
24851 { { vc } { l } { 1 } { 1 } }
24852 \prop_put:Nnn \l__coffin_display_handles_prop { Bl }
24853 { { b } { r } { -1 } { -1 } }
24854 \prop_put:Nnn \l__coffin_display_handles_prop { Bhc }
24855 { { b } { hc } { 0 } { -1 } }
24856 \prop_put:Nnn \l__coffin_display_handles_prop { Br }
24857 { { b } { l } { 1 } { -1 } }

```

(End definition for \l__coffin_display_handles_prop.)

`\l__coffin_display_offset_dim` The standard offset for the label from the handle position when displaying handles.

```

24858 \dim_new:N \l__coffin_display_offset_dim
24859 \dim_set:Nn \l__coffin_display_offset_dim { 2pt }

```

(End definition for \l__coffin_display_offset_dim.)

\l__coffin_display_x_dim As the intersections of poles have to be calculated to find which ones to print, there is
 \l__coffin_display_y_dim a need to avoid repetition. This is done by saving the intersection into two dedicated values.

```
24860 \dim_new:N \l__coffin_display_x_dim
24861 \dim_new:N \l__coffin_display_y_dim
```

(End definition for \l__coffin_display_x_dim and \l__coffin_display_y_dim.)

\l__coffin_display_poles_prop A property list for printing poles: various things need to be deleted from this to get a “nice” output.

```
24862 \prop_new:N \l__coffin_display_poles_prop
```

(End definition for \l__coffin_display_poles_prop.)

\l__coffin_display_font_tl Stores the settings used to print coffin data: this keeps things flexible.

```
24863 \tl_new:N \l__coffin_display_font_tl
24864 \*initex
24865 \tl_set:Nn \l__coffin_display_font_tl { } % TODO
24866 \*initex
24867 \*package
24868 \tl_set:Nn \l__coffin_display_font_tl { \sfamily \tiny }
24869 \*package
```

(End definition for \l__coffin_display_font_tl.)

\coffin_mark_handle:Nnnn Marking a single handle is relatively easy. The standard attachment function is used,
 \coffin_mark_handle:cnnn meaning that there are two calculations for the location. However, this is likely to be
 __coffin_mark_handle_aux:nnnnNnn okay given the load expected. Contrast with the more optimised version for showing all
 handles which comes next.

```
24870 \cs_new_protected:Npn \coffin_mark_handle:Nnnn #1#2#3#4
24871 {
24872   \hcoffin_set:Nn \l__coffin_display_pole_coffin
24873   {
24874     \*initex
24875     \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
24876     \*initex
24877     \*package
24878     \color {#4}
24879     \rule { 1pt } { 1pt }
24880     \*package
24881   }
24882   \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
24883   \l__coffin_display_pole_coffin { hc } { vc } { Opt } { Opt }
24884   \hcoffin_set:Nn \l__coffin_display_coord_coffin
24885   {
24886     \*initex
24887     % TODO
24888     \*initex
24889     \*package
24890     \color {#4}
24891     \*package
24892     \l__coffin_display_font_tl
```

```

24893      ( \tl_to_str:n { #2 , #3 } )
24894    }
24895    \prop_get:NnN \l__coffin_display_handles_prop
24896      { #2 #3 } \l__coffin_internal_tl
24897    \quark_if_no_value:NTF \l__coffin_internal_tl
24898      {
24899        \prop_get:NnN \l__coffin_display_handles_prop
24900          { #3 #2 } \l__coffin_internal_tl
24901        \quark_if_no_value:NTF \l__coffin_internal_tl
24902          {
24903            \coffin_attach_mark:NnnNnnnn #1 {#2} {#3}
24904            \l__coffin_display_coord_coffin { 1 } { vc }
24905            { 1pt } { 0pt }
24906          }
24907          {
24908            \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
24909              \l__coffin_internal_tl #1 {#2} {#3}
24910          }
24911        }
24912        {
24913          \exp_last_unbraced:No \__coffin_mark_handle_aux:nnnnNnn
24914            \l__coffin_internal_tl #1 {#2} {#3}
24915        }
24916      }
24917    \cs_new_protected:Npn \__coffin_mark_handle_aux:nnnnNnn #1#2#3#4#5#6#7
24918      {
24919        \coffin_attach_mark:NnnNnnnn #5 {#6} {#7}
24920        \l__coffin_display_coord_coffin {#1} {#2}
24921        { #3 \l__coffin_display_offset_dim }
24922        { #4 \l__coffin_display_offset_dim }
24923      }
24924    \cs_generate_variant:Nn \coffin_mark_handle:Nnnn { c }

```

(End definition for \coffin_mark_handle:Nnnn and __coffin_mark_handle_aux:nnnnNnn. This function is documented on page 234.)

\coffin_display_handles:Nn
\coffin_display_handles:cn
 __coffin_display_handles_aux:nnnnnn
 __coffin_display_handles_aux:nnnn
 __coffin_display_attach:Nnnnn

Printing the poles starts by removing any duplicates, for which the H poles is used as the definitive version for the baseline and bottom. Two loops are then used to find the combinations of handles for all of these poles. This is done such that poles are removed during the loops to avoid duplication.

```

24925    \cs_new_protected:Npn \coffin_display_handles:Nn #1#2
24926      {
24927        \hcoffin_set:Nn \l__coffin_display_pole_coffin
24928          {
24929            <*initex>
24930              \hbox:n { \tex_vrule:D width 1pt height 1pt \scan_stop: } % TODO
24931            </initex>
24932            <*package>
24933              \color {#2}
24934              \rule { 1pt } { 1pt }
24935            </package>
24936          }
24937        \prop_set_eq:Nc \l__coffin_display_poles_prop
24938          { l__coffin_poles_ \__coffin_to_value:N #1 _prop }

```

```

24939 \__coffin_get_pole:NnN #1 { H } \l__coffin_pole_a_tl
24940 \__coffin_get_pole:NnN #1 { T } \l__coffin_pole_b_tl
24941 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
24942 { \prop_remove:Nn \l__coffin_display_poles_prop { T } }
24943 \__coffin_get_pole:NnN #1 { B } \l__coffin_pole_b_tl
24944 \tl_if_eq:NNT \l__coffin_pole_a_tl \l__coffin_pole_b_tl
24945 { \prop_remove:Nn \l__coffin_display_poles_prop { B } }
24946 \coffin_set_eq:NN \l__coffin_display_coffin #1
24947 \prop_map_inline:Nn \l__coffin_display_poles_prop
24948 {
24949   \prop_remove:Nn \l__coffin_display_poles_prop {##1}
24950   \__coffin_display_handles_aux:nnnnnn {##1} ##2 {##2}
24951 }
24952 \box_use_drop:N \l__coffin_display_coffin
24953 }

```

For each pole there is a check for an intersection, which here does not give an error if none is found. The successful values are stored and used to align the pole coffin with the main coffin for output. The positions are recovered from the preset list if available.

```

24954 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnnnn #1#2#3#4#5#6
24955 {
24956   \prop_map_inline:Nn \l__coffin_display_poles_prop
24957   {
24958     \bool_set_false:N \l__coffin_error_bool
24959     \__coffin_calculate_intersection:nnnnnnnn {##2} {##3} {##4} {##5} ##2
24960     \bool_if:NF \l__coffin_error_bool
24961     {
24962       \dim_set:Nn \l__coffin_display_x_dim { \l__coffin_x_dim }
24963       \dim_set:Nn \l__coffin_display_y_dim { \l__coffin_y_dim }
24964       \__coffin_display_attach:Nnnnn
24965       \l__coffin_display_pole_coffin { hc } { vc }
24966       { Opt } { Opt }
24967       \hcoffin_set:Nn \l__coffin_display_coord_coffin
24968       {
24969         \*initex
24970         % TODO
24971         \*initex
24972         \*package
24973         \color {##6}
24974         \*package
24975         \l__coffin_display_font_tl
24976         ( \tl_to_str:n { #1 , ##1 } )
24977       }
24978       \prop_get:NnN \l__coffin_display_handles_prop
24979       { #1 ##1 } \l__coffin_internal_tl
24980       \quark_if_no_value:NTF \l__coffin_internal_tl
24981       {
24982         \prop_get:NnN \l__coffin_display_handles_prop
24983         { ##1 #1 } \l__coffin_internal_tl
24984         \quark_if_no_value:NTF \l__coffin_internal_tl
24985         {
24986           \__coffin_display_attach:Nnnnn
24987           \l__coffin_display_coord_coffin { l } { vc }
24988           { 1pt } { Opt }

```

```

24989         }
24990         {
24991             \exp_last_unbraced:No
24992             \__coffin_display_handles_aux:nnnn
24993             \l__coffin_internal_tl
24994         }
24995     }
24996     {
24997         \exp_last_unbraced:No \__coffin_display_handles_aux:nnnn
24998         \l__coffin_internal_tl
24999     }
25000 }
25001 }
25002 }
25003 \cs_new_protected:Npn \__coffin_display_handles_aux:nnnn #1#2#3#4
25004 {
25005     \__coffin_display_attach:Nnnnn
25006     \l__coffin_display_coord_coffin {#1} {#2}
25007     { #3 \l__coffin_display_offset_dim }
25008     { #4 \l__coffin_display_offset_dim }
25009 }
25010 \cs_generate_variant:Nn \coffin_display_handles:Nn { c }

```

This is a dedicated version of `\coffin_attach:NnnNnnnn` with a hard-wired first coffin. As the intersection is already known and stored for the display coffin the code simply uses it directly, with no calculation.

```

25011 \cs_new_protected:Npn \__coffin_display_attach:Nnnnn #1#2#3#4#5
25012 {
25013     \__coffin_calculate_intersection:Nnn #1 {#2} {#3}
25014     \dim_set:Nn \l__coffin_x_prime_dim { \l__coffin_x_dim }
25015     \dim_set:Nn \l__coffin_y_prime_dim { \l__coffin_y_dim }
25016     \dim_set:Nn \l__coffin_offset_x_dim
25017     { \l__coffin_display_x_dim - \l__coffin_x_prime_dim + #4 }
25018     \dim_set:Nn \l__coffin_offset_y_dim
25019     { \l__coffin_display_y_dim - \l__coffin_y_prime_dim + #5 }
25020     \hbox_set:Nn \l__coffin_aligned_coffin
25021     {
25022         \box_use:N \l__coffin_display_coffin
25023         \tex_kern:D -\box_wd:N \l__coffin_display_coffin
25024         \tex_kern:D \l__coffin_offset_x_dim
25025         \box_move_up:nn { \l__coffin_offset_y_dim } { \box_use:N #1 }
25026     }
25027     \box_set_ht:Nn \l__coffin_aligned_coffin
25028     { \box_ht:N \l__coffin_display_coffin }
25029     \box_set_dp:Nn \l__coffin_aligned_coffin
25030     { \box_dp:N \l__coffin_display_coffin }
25031     \box_set_wd:Nn \l__coffin_aligned_coffin
25032     { \box_wd:N \l__coffin_display_coffin }
25033     \box_set_eq:NN \l__coffin_display_coffin \l__coffin_aligned_coffin
25034 }

```

(End definition for `\coffin_display_handles:Nn` and others. This function is documented on page 233.)

`\coffin_show_structure:N`

`\coffin_show_structure:c`

`\coffin_log_structure:N`

`\coffin_log_structure:c`

`__coffin_show_structure:NN`

For showing the various internal structures attached to a coffin in a way that keeps things

relatively readable. If there is no apparent structure then the code complains.

```

25035 \cs_new_protected:Npn \coffin_show_structure:N
25036 { \__coffin_show_structure:NN \msg_show:nnxxxx }
25037 \cs_generate_variant:Nn \coffin_show_structure:N { c }
25038 \cs_new_protected:Npn \coffin_log_structure:N
25039 { \__coffin_show_structure:NN \msg_log:nnxxxx }
25040 \cs_generate_variant:Nn \coffin_log_structure:N { c }
25041 \cs_new_protected:Npn \__coffin_show_structure:NN #1#2
25042 {
25043   \__coffin_if_exist:NT #2
25044   {
25045     #1 { LaTeX / kernel } { show-coffin }
25046     { \token_to_str:N #2 }
25047     {
25048       \iow_newline: >~ ht ~~~ \dim_eval:n { \coffin_ht:N #2 }
25049       \iow_newline: >~ dp ~~~ \dim_eval:n { \coffin_dp:N #2 }
25050       \iow_newline: >~ wd ~~~ \dim_eval:n { \coffin_wd:N #2 }
25051     }
25052     {
25053       \prop_map_function:cN
25054       { l__coffin_poles_ \__coffin_to_value:N #2 _prop }
25055       \msg_show_item_unbraced:nn
25056     }
25057   }
25058 }
25059 }

```

(End definition for `\coffin_show_structure:N`, `\coffin_log_structure:N`, and `__coffin_show_structure:NN`. These functions are documented on page [234](#).)

40.8 Messages

```

25060 \__kernel_msg_new:nnnn { kernel } { no-pole-intersection }
25061 { No-intersection-between-coffin-poles. }
25062 {
25063   LaTeX~was~asked~to~find~the~intersection~between~two~poles,~
25064   but~they~do~not~have~a~unique~meeting~point:~
25065   the~value~(0pt,~0pt)~will~be~used.
25066 }
25067 \__kernel_msg_new:nnnn { kernel } { unknown-coffin }
25068 { Unknown-coffin~'#1'. }
25069 { The-coffin~'#1'~was~never~defined. }
25070 \__kernel_msg_new:nnnn { kernel } { unknown-coffin-pole }
25071 { Pole~'#1'~unknown-for-coffin~'#2'. }
25072 {
25073   LaTeX~was~asked~to~find~a~typesetting~pole~for~a~coffin,~
25074   but~either~the~coffin~does~not~exist~or~the~pole~name~is~wrong.
25075 }
25076 \__kernel_msg_new:nnn { kernel } { show-coffin }
25077 {
25078   Size-of-coffin~#1 : #2 \\
25079   Poles-of-coffin~#1 : #3 .
25080 }
25081 </initex | package>

```

41 l3color-base Implementation

25082 $\langle *initex \mid package \rangle$

25083 $\langle @@=color \rangle$

$\backslash l_color_current_tl$ The color currently active for foreground (text, *etc.*) material. This is stored in the form of a color model followed by one or more values. There are four pre-defined models, three of which take numerical values in the range $[0, 1]$:

- **gray** $\langle gray \rangle$ Grayscale color with the $\langle gray \rangle$ value running from 0 (fully black) to 1 (fully white)
- **cmyk** $\langle cyan \rangle \langle magenta \rangle \langle yellow \rangle \langle black \rangle$
- **rgb** $\langle red \rangle \langle green \rangle \langle blue \rangle$

Notice that the value are separated by spaces. There is a fourth pre-defined model using a string value and a numerical one:

- **spot** $\langle name \rangle \langle tint \rangle$ A pre-defined spot color, where the $\langle name \rangle$ should be a pre-defined string color name and the $\langle tint \rangle$ should be in the range $[0, 1]$.

Additional models may be created to allow mixing of spot colors. The number of data entries these require will depend on the number of colors to be mixed.

T_EXhackers note: The content of $\backslash l_color_current_tl$ is space-separated as this allows it to be used directly in specials in many common cases. This internal representation is close to that used by the **dvips** program.

(End definition for $\backslash l_color_current_tl$.)

$\backslash color_group_begin$: Grouping for color is the same as using the basic $\backslash group_begin$: and $\backslash group_end$: functions. However, for semantic reasons, they are renamed here.

25084 $\backslash cs_new_eq:NN \backslash color_group_begin: \backslash group_begin:$

25085 $\backslash cs_new_eq:NN \backslash color_group_end: \backslash group_end:$

(End definition for $\backslash color_group_begin$: and $\backslash color_group_end$:. These functions are documented on page 235.)

$\backslash color_ensure_current$: A driver-independent wrapper for setting the foreground color to the current color “now”.

25086 $\backslash cs_new_protected:Npn \backslash color_ensure_current:$

25087 {

25088 $\langle *package \rangle$

25089 $\backslash driver_color_pickup:N \backslash l_color_current_tl$

25090 $\langle /package \rangle$

25091 $\backslash _color_select:V \backslash l_color_current_tl$

25092 }

(End definition for $\backslash color_ensure_current$:. This function is documented on page 235.)


```

    \_color\_select:n Take an internal color specification and pass it to the driver. This code is needed to
    \_color\_select:V ensure the current color but will also be used by the higher-level experimental material.
    \_color\_select:w
25093 \cs\_new\_protected:Npn \_color\_select:n #1
    \_color\_select\_cmyk:w 25094 { \_color\_select:w #1 \q\_stop }
    \_color\_select\_gray:w 25095 \cs\_generate\_variant:Nn \_color\_select:n { V }
    \_color\_select\_rgb:w 25096 \cs\_new\_protected:Npn \_color\_select:w #1 ~ #2 \q\_stop
    \_color\_select\_spot:w 25097 { \use:c { \_color\_select\_ #1 :w } #2 \q\_stop }
25098 \cs\_new\_protected:Npn \_color\_select\_cmyk:w #1 ~ #2 ~ #3 ~ #4 \q\_stop
25099 { \driver\_color\_cmyk:nnnn {#1} {#2} {#3} {#4} }
25100 \cs\_new\_protected:Npn \_color\_select\_gray:w #1 \q\_stop
25101 { \driver\_color\_gray:n {#1} }
25102 \cs\_new\_protected:Npn \_color\_select\_rgb:w #1 ~ #2 ~ #3 \q\_stop
25103 { \driver\_color\_rgb:nnn {#1} {#2} {#3} }
25104 \cs\_new\_protected:Npn \_color\_select\_spot:w #1 ~ #2 \q\_stop
25105 { \driver\_color\_spot:nn {#1} {#2} }

(End definition for \_color\_select:n and others.)

```

```

\l\_color\_current\_tl As the setting data is used only for specials, and those are always space-separated, it
                        makes most sense to hold the internal information in that form.
25106 \tl\_new:N \l\_color\_current\_tl
25107 \tl\_set:Nn \l\_color\_current\_tl { gray~0 }

(End definition for \l\_color\_current\_tl.)
25108 </initex | package>

```

42 l3luatex implementation

```
25109 <*initex | package>
```

42.1 Breaking out to Lua

```

25110 <*tex>
25111 <@@=lua>

\_lua\_escape:n Copies of primitives.
    \_lua\_now:n
\_lua\_shipout:n
25112 \cs\_new\_eq:NN \_lua\_escape:n \tex\_luaescapestring:D
25113 \cs\_new\_eq:NN \_lua\_now:n \tex\_directlua:D
25114 \cs\_new\_eq:NN \_lua\_shipout:n \tex\_latelua:D

(End definition for \_lua\_escape:n, \_lua\_now:n, and \_lua\_shipout:n.)

```

These functions are set up in l3str for bootstrapping: we want to replace them with a “proper” version at this stage, so clean up.

```

25115 \cs\_undefine:N \lua\_escape:e
25116 \cs\_undefine:N \lua\_now:e

\lua\_now:n Wrappers around the primitives. As with engines other than LuaTeX these have to be
\lua\_now:e macros, we give them the same status in all cases. When LuaTeX is not in use, simply
\lua\_shipout\_e:n give an error message/
    \lua\_shipout:n
    \lua\_escape:n
    \lua\_escape:e
25117 \cs\_new:Npn \lua\_now:e #1 { \_lua\_now:n {#1} }
25118 \cs\_new:Npn \lua\_now:n #1 { \lua\_now:e { \exp\_not:n {#1} } }
25119 \cs\_new\_protected:Npn \lua\_shipout\_e:n #1 { \_lua\_shipout:n {#1} }
25120 \cs\_new\_protected:Npn \lua\_shipout:n #1

```

```

25121 { \lua_shipout_e:n { \exp_not:n {#1} } }
25122 \cs_new:Npn \lua_escape:e #1 { \_lua_escape:n {#1} }
25123 \cs_new:Npn \lua_escape:n #1 { \lua_escape:e { \exp_not:n {#1} } }
25124 \sys_if_engine luatex:F
25125 {
25126   \clist_map_inline:nn
25127   {
25128     \lua_escape:n , \lua_escape:e ,
25129     \lua_now:n , \lua_now:e
25130   }
25131   {
25132     \cs_set:Npn #1 ##1
25133     {
25134       \_kernel_msg_expandable_error:nnn
25135       { kernel } { luatex-required } { #1 }
25136     }
25137   }
25138   \clist_map_inline:nn
25139   { \lua_shipout_e:n , \lua_shipout:n }
25140   {
25141     \cs_set_protected:Npn #1 ##1
25142     {
25143       \_kernel_msg_error:nnn
25144       { kernel } { luatex-required } { #1 }
25145     }
25146   }
25147 }

```

(End definition for `\lua_now:n` and others. These functions are documented on page 236.)

42.2 Messages

```

25148 \_kernel_msg_new:nnnn { kernel } { luatex-required }
25149 { LuaTeX-engine-not-in-use!~Ignoring~#1. }
25150 {
25151   The~feature~you~are~using~is~only~available~
25152   with~the~LuaTeX-engine.~LaTeX3~ignored~'~#1'.
25153 }

```

42.3 Deprecated functions

```

\lua_now_x:n For removal after 2019-12-31.
\lua_escape_x:n
\lua_shipout_x:n
25154 \_kernel_patch_deprecation:nnNpn { 2019-12-31 } { \lua_now:e }
25155 \cs_new:Npn \lua_now_x:n #1 { \_lua_now:n {#1} }
25156 \_kernel_patch_deprecation:nnNpn { 2019-12-31 } { \lua_escape:e }
25157 \cs_new:Npn \lua_escape_x:n #1 { \_lua_escape:n {#1} }
25158 \_kernel_patch_deprecation:nnNpn { 2019-12-31 } { \lua_shipout_e:n }
25159 \cs_new_protected:Npn \lua_shipout_x:n #1 { \_lua_shipout:n {#1} }

```

(End definition for `\lua_now_x:n`, `\lua_escape_x:n`, and `\lua_shipout_x:n`.)

```

25160 </tex>

```

42.4 Lua functions for internal use

25161 `<*lua>`

Most of the emulation of pdfTeX here is based heavily on Heiko Oberdiek's pdfTeX-cmds package.

13kernel Create a table for the kernel's own use.

25162 `13kernel = 13kernel or { }`

(End definition for 13kernel. This function is documented on page 237.)

Local copies of global tables.

```
25163 local io      = io
25164 local kpse     = kpse
25165 local lfs      = lfs
25166 local math     = math
25167 local md5      = md5
25168 local os       = os
25169 local string   = string
25170 local tex      = tex
25171 local unicode  = unicode
```

Local copies of standard functions.

```
25172 local abs      = math.abs
25173 local byte     = string.byte
25174 local floor    = math.floor
25175 local format   = string.format
25176 local gsub     = string.gsub
25177 if not resolvers then
25178   local kpse_find = kpse.find_file
25179 end
25180 local lfs_attr  = lfs.attributes
25181 local md5_sum   = md5.sum
25182 local open     = io.open
25183 local os_clock  = os.clock
25184 local os_date   = os.date
25185 local setcatcode = tex.setcatcode
25186 local sprint   = tex.sprint
25187 local write    = tex.write
25188 local utf8_char = unicode.utf8.char
```

Deal with ConTeXt: doesn't use kpse library.

```
25189 if resolvers then
25190   kpse_find = resolvers.findfile
25191 end
```

escapehex An internal auxiliary to convert a string to the matching hex escape. This works on a byte basis: extension to handled UTF-8 input is covered in pdfTeXcmds but is not currently required here.

```
25192 local function escapehex(str)
25193   write((gsub(str, ".",
25194     function (ch) return format("%02X", byte(ch)) end)))
25195 end
```

(End definition for escapehex.)

l3kernel.charcat Creating arbitrary chars needs a category code table. As set up here, one may have been assigned earlier (see `l3bootstrap`) or a hard-coded one is used. The latter is intended for format mode and should be adjusted to match an eventual allocator.

```

25196 local charcat_table = l3kernel.charcat_table or 1
25197 local function charcat(charcode, catcode)
25198   setcatcode(charcat_table, charcode, catcode)
25199   sprint(charcat_table, utf8_char(charcode))
25200 end
25201 l3kernel.charcat = charcat

```

(End definition for `l3kernel.charcat`. This function is documented on page 237.)

l3kernel.elapsedtime Simple timing set up: give the result from the system clock in scaled seconds.
l3kernel.resettimer

```

25202 local base_time = 0
25203 local function elapsedtime()
25204   local val = (os_clock() - base_time) * 65536 + 0.5
25205   if val > 2147483647 then
25206     val = 2147483647
25207   end
25208   write(format("%d", floor(val)))
25209 end
25210 l3kernel.elapsedtime = elapsedtime
25211 local function resettimer()
25212   base_time = 0
25213 end
25214 l3kernel.resettimer = resettimer

```

(End definition for `l3kernel.elapsedtime` and `l3kernel.resettimer`. These functions are documented on page 237.)

l3kernel.filemdfivesum Read an entire file and hash it: the hash function itself is a built-in. As Lua is byte-based there is no work needed here in terms of UTF-8 (see `pdftexcmds` and how it handles strings that have passed through Lua_{TEX}). The file is read in binary mode so that no line ending normalisation occurs.

```

25215 local function filemdfivesum(name)
25216   local file = kpse_find(name, "tex", true)
25217   if file then
25218     local f = open(file, "rb")
25219     if f then
25220       local data = f:read("*a")
25221       escapehex(md5_sum(data))
25222       f:close()
25223     end
25224   end
25225 end
25226 l3kernel.filemdfivesum = filemdfivesum

```

(End definition for `l3kernel.filemdfivesum`. This function is documented on page 237.)

l3kernel.filemoddate See procedure `makepdftime` in `utils.c` of pdf_{TEX}.

```

25227 local function filemoddate(name)
25228   local file = kpse_find(name, "tex", true)
25229   if file then
25230     local date = lfs_attr(file, "modification")

```

```

25231     if date then
25232         local d = os_date("!*t", date)
25233         if d.sec >= 60 then
25234             d.sec = 59
25235         end
25236         local u = os_date("!*t", date)
25237         local off = 60 * (d.hour - u.hour) + d.min - u.min
25238         if d.year ~= u.year then
25239             if d.year > u.year then
25240                 off = off + 1440
25241             else
25242                 off = off - 1440
25243             end
25244         elseif d.yday ~= u.yday then
25245             if d.yday > u.yday then
25246                 off = off + 1440
25247             else
25248                 off = off - 1440
25249             end
25250         end
25251         local timezone
25252         if off == 0 then
25253             timezone = "Z"
25254         else
25255             local hours = floor(off / 60)
25256             local mins = abs(off - hours * 60)
25257             timezone = format("%+03d", hours)
25258             .. " " .. format("%02d", mins) .. ""
25259         end
25260         write("D:"
25261             .. format("%04d", d.year)
25262             .. format("%02d", d.month)
25263             .. format("%02d", d.day)
25264             .. format("%02d", d.hour)
25265             .. format("%02d", d.min)
25266             .. format("%02d", d.sec)
25267             .. timezone)
25268     end
25269 end
25270 end
25271 l3kernel.filemoddate = filemoddate

```

(End definition for l3kernel.filemoddate. This function is documented on page [237](#).)

l3kernel.filesize A simple disk lookup.

```

25272 local function filesize(name)
25273     local file = kpse_find(name, "tex", true)
25274     if file then
25275         local size = lfs_attr(file, "size")
25276         if size then
25277             write(size)
25278         end
25279     end
25280 end
25281 l3kernel.filesize = filesize

```

(End definition for `l3kernel.filesize`. This function is documented on page 237.)

l3kernel.strcmp String comparison which gives the same results as pdfTeX’s `\pdfstrcmp`, although the ordering should likely not be relied upon!

```

25282 local function strcmp(A, B)
25283   if A == B then
25284     write("0")
25285   elseif A < B then
25286     write("-1")
25287   else
25288     write("1")
25289   end
25290 end
25291 l3kernel.strcmp = strcmp

```

(End definition for `l3kernel.strcmp`. This function is documented on page 237.)

42.5 Generic Lua and font support

```

25292 ⟨*initex⟩
25293 ⟨@@=alloc⟩

```

A small amount of generic code is used by almost all LuaTeX material so needs to be loaded by the format.

```

25294 attribute_count_name = "g__alloc_attribute_int"
25295 bytecode_count_name  = "g__alloc_bytecode_int"
25296 chunkname_count_name = "g__alloc_chunkname_int"
25297 whatsit_count_name   = "g__alloc_whatsit_int"
25298 require("ltxlua")

```

With the above available the font loader code used by plain TeX and L^AT_EX 2_ε when used with LuaTeX can be loaded here. This is thus being treated more-or-less as part of the engine itself.

```

25299 require("luaotfload-main")
25300 local _void = luaotfload.main()
25301 ⟨/initex⟩
25302 ⟨/lua⟩
25303 ⟨/initex | package⟩

```

43 l3unicode implementation

```

25304 ⟨*initex | package⟩
25305 ⟨@@=char⟩

```

Case changing both for strings and “text” requires data from the Unicode Consortium. Some of this is build in to the format (as `\lccode` and `\uccode` values) but this covers only the simple one-to-one situations and does not fully handle for example case folding.

As only the data needs to remain at the end of this process, everything is set up inside a group. The only thing that is outside is creating a stream: they are global anyway and it is best to force a stream for all engines. For performance reasons, some of the code here is very low-level: the material is read during loading `expl3` in package mode.

```

25306 \ior_new:N \g__char_data_ior
25307 \bool_lazy_or:nnTF { \sys_if_engine luatex_p: } { \sys_if_engine xetex_p: }
25308 {
25309   \group_begin:

```

Set up a private copy of the char-generation primitive.

```

25310   \cs_set_eq:NN \__char_generate:w \tex_Uchar:D

```

A fast local implementation for generating characters.

```

25311   \cs_set:Npx \__char_generate:n #1
25312   {
25313     \sys_if_engine luatex:TF
25314     {
25315       \exp_not:N \lua_now:e
25316       {
25317         l3kernel.charcat
25318         (
25319           \exp_not:N \tex_number:D #1 ,
25320           \exp_not:N \tex_the:D \tex_catcode:D #1
25321         )
25322       }
25323     }
25324     {
25325       \exp_not:N \tex_Ucharcat:D
25326       #1 ~
25327       \tex_catcode:D #1 ~
25328     }
25329   }

```

Parse the main Unicode data file for title case exceptions (the one-to-one lower and upper case mappings it contains are all be covered by the $\mathrm{T}_{\mathrm{E}}\mathrm{X}$ data). There are no comments in the main data file so this can be done using a standard mapping and no checks.

```

25330   \ior_open:Nn \g__char_data_ior { UnicodeData.txt }
25331   \cs_set_protected:Npn \__char_data_auxi:w
25332     #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 ; #8 ; #9 ;
25333     { \__char_data_auxii:w #1 ; }
25334   \cs_set_protected:Npn \__char_data_auxii:w
25335     #1 ; #2 ; #3 ; #4 ; #5 ; #6 ; #7 \q_stop
25336   {
25337     \cs_set_nopar:Npn \l__char_tmpa_tl {#7}
25338     \reverse_if:N \if_meaning:w \l__char_tmpa_tl \c_empty_tl
25339     \cs_set_nopar:Npn \l__char_tmpb_tl {#5}
25340     \reverse_if:N \if_meaning:w \l__char_tmpa_tl \l__char_tmpb_tl
25341     \tl_const:cx
25342       { c__char_mixed_case_ \__char_generate:w "#1 _tl }
25343       { \__char_generate:n { "#7 } }
25344     \fi:
25345     \fi:
25346   }
25347   \ior_map_variable:NNn \g__char_data_ior \l__char_tmpa_tl
25348   {
25349     \if_meaning:w \l__char_tmpa_tl \c_space_tl
25350       \exp_after:wN \ior_map_break:
25351     \fi:
25352     \exp_after:wN \__char_data_auxi:w \l__char_tmpa_tl \q_stop
25353   }

```

```
25354 \ior_close:N \g__char_data_ior
```

The other data files all use C-style comments so we have to worry about # tokens (and reading as strings). The set up for case folding is in two parts. For the basic (core) mappings, folding is the same as lower casing in most positions so only store the differences. For the more complex foldings, always store the result, splitting up the two or three code points in the input as required.

```
25355 \ior_open:Nn \g__char_data_ior { CaseFolding.txt }
25356 \cs_set_protected:Npn \__char_data_auxi:w #1 ;~ #2 ;~ #3 ; #4 \q_stop
25357 {
25358   \if:w \tl_head:n { #2 ? } C
25359   \reverse_if:N \if_int_compare:w
25360     \char_value_lccode:n {"#1} = "#3 ~
25361     \tl_const:cx
25362       { c__char_fold_case_ \__char_generate:w "#1 _tl }
25363       { \__char_generate:n { "#3 } }
25364   \fi:
25365   \else:
25366     \if:w \tl_head:n { #2 ? } F
25367     \__char_data_auxii:w #1 ~ #3 ~ \q_stop
25368   \fi:
25369   \fi:
25370 }
25371 \cs_set_protected:Npn \__char_data_auxii:w #1 ~ #2 ~ #3 ~ #4 \q_stop
25372 {
25373   \tl_const:cx { c__char_fold_case_ \__char_generate:w "#1 _tl }
25374   {
25375     \__char_generate:n { "#2 }
25376     \__char_generate:n { "#3 }
25377     \tl_if_blank:nF {#4}
25378       { \__char_generate:n { \int_value:w "#4 } }
25379   }
25380 }
25381 \ior_str_map_inline:Nn \g__char_data_ior
25382 {
25383   \reverse_if:N \if:w \c_hash_str \tl_head:w #1 \c_hash_str \q_stop
25384   \__char_data_auxi:w #1 \q_stop
25385   \fi:
25386 }
25387 \ior_close:N \g__char_data_ior
```

For upper and lower casing special situations, there is a bit more to do as we also have title casing to consider, plus we need to stop part-way through the file.

```
25388 \ior_open:Nn \g__char_data_ior { SpecialCasing.txt }
25389 \cs_set_protected:Npn \__char_data_auxi:w
25390   #1 ;~ #2 ;~ #3 ;~ #4 ; #5 \q_stop
25391 {
25392   \use:n { \__char_data_auxii:w #1 ~ lower ~ #2 ~ } ~ \q_stop
25393   \use:n { \__char_data_auxii:w #1 ~ upper ~ #4 ~ } ~ \q_stop
25394   \str_if_eq:nnF {#3} {#4}
25395     { \use:n { \__char_data_auxii:w #1 ~ mixed ~ #3 ~ } ~ \q_stop }
25396 }
25397 \cs_set_protected:Npn \__char_data_auxii:w
25398   #1 ~ #2 ~ #3 ~ #4 ~ #5 \q_stop
25399 {
```



```

25400     \tl_if_empty:nF {#4}
25401     {
25402         \tl_const:cx { c__char_ #2 _case_ \__char_generate:w "#1 _tl }
25403         {
25404             \__char_generate:n { "#3 }
25405             \__char_generate:n { "#4 }
25406             \tl_if_blank:nF {#5}
25407             { \__char_generate:n { "#5 } }
25408         }
25409     }
25410 }
25411 \ior_str_map_inline:Nn \g__char_data_ior
25412 {
25413     \str_if_eq:eeTF
25414     { \tl_head:w #1 \c_hash_str \q_stop }
25415     { \c_hash_str }
25416     {
25417         \str_if_eq:eeT
25418         {#1}
25419         { \c_hash_str \c_space_tl Conditional~Mappings }
25420         { \ior_map_break: }
25421     }
25422     { \__char_data_auxi:w #1 \q_stop }
25423 }
25424 \ior_close:N \g__char_data_ior
25425 \group_end:
25426 }

```

For the 8-bit engines, the above is skipped but there is still some set up required. As case changing can only be applied to bytes, and they have to be in the ASCII range, we define a series of data stores to represent them, and the data are used such that only these are ever case-changed. We do open and close one file to force allocation of a read: this keeps all engines in line.

```

25427 {
25428     \group_begin:
25429     \cs_set_protected:Npn \__char_tmp:NN #1#2
25430     {
25431         \quark_if_recursion_tail_stop:N #2
25432         \tl_const:cn { c__char_upper_case_ #2 _tl } {#1}
25433         \tl_const:cn { c__char_lower_case_ #1 _tl } {#2}
25434         \tl_const:cn { c__char_fold_case_ #1 _tl } {#2}
25435         \__char_tmp:NN
25436     }
25437     \__char_tmp:NN
25438     AaBbCcDdEeFfGgHhIiJjKkLlMmNnOoPpQqRrSsTtUuVvWwXxYyZz
25439     ? \q_recursion_tail \q_recursion_stop
25440     \ior_open:Nn \g__char_data_ior { UnicodeData.txt }
25441     \ior_close:N \g__char_data_ior
25442     \group_end:
25443 }
25444 \</initex | package>

```

44 l3candidates Implementation

25445 $\langle *initex | package \rangle$

44.1 Additions to l3basics

`\mode_leave_vertical:` The approach here is different to that used by L^AT_EX 2_ε or plain T_EX, which unbox a void box to force horizontal mode. That inserts the `\everypar` tokens *before* the re-inserted unboxing tokens. The approach here uses either the `\quitvmode` primitive or the equivalent protected macro. In vertical mode, the `\indent` primitive is inserted: this will switch to horizontal mode and insert `\everypar` tokens and nothing else. Unlike the L^AT_EX 2_ε version, the availability of ε-T_EX means using a mode test can be done at for example the start of an `\halign`.

```
25446 \cs_new_protected:Npn \mode_leave_vertical:
25447 {
25448   \if_mode_vertical:
25449     \exp_after:wN \tex_indent:D
25450   \fi:
25451 }
```

(End definition for `\mode_leave_vertical:`. This function is documented on page 240.)

44.2 Additions to l3box

25452 $\langle @@=box \rangle$

44.2.1 Viewing part of a box

`\box_clip:N` A wrapper around the driver-dependent code.

```
\box_clip:c
25453 \cs_new_protected:Npn \box_clip:N #1
25454 { \hbox_set:Nn #1 { \driver_box_use_clip:N #1 } }
25455 \cs_generate_variant:Nn \box_clip:N { c }
```

(End definition for `\box_clip:N`. This function is documented on page 241.)

`\box_trim:Nnnnn` Trimming from the left- and right-hand edges of the box is easy: kern the appropriate parts off each side.

`\box_trim:cnnnn`

```
25456 \cs_new_protected:Npn \box_trim:Nnnnn #1#2#3#4#5
25457 {
25458   \hbox_set:Nn \l__box_internal_box
25459   {
25460     \tex_kern:D - \__box_dim_eval:n {#2}
25461     \box_use:N #1
25462     \tex_kern:D - \__box_dim_eval:n {#4}
25463   }
```

For the height and depth, there is a need to watch the baseline is respected. Material always has to stay on the correct side, so trimming has to check that there is enough material to trim. First, the bottom edge. If there is enough depth, simply set the depth, or if not move down so the result is zero depth. `\box_move_down:nn` is used in both cases so the resulting box always contains a `\lower` primitive. The internal box is used here as it allows safe use of `\box_set_dp:Nn`.

```
25464   \dim_compare:nNnTF { \box_dp:N #1 } > {#3}
25465   {
25466     \hbox_set:Nn \l__box_internal_box
25467     {
25468       \box_move_down:nn \c_zero_dim
```

```

25469         { \box_use:N \l__box_internal_box }
25470     }
25471     \box_set_dp:Nn \l__box_internal_box { \box_dp:N #1 - (#3) }
25472 }
25473 {
25474     \hbox_set:Nn \l__box_internal_box
25475     {
25476         \box_move_down:nn { (#3) - \box_dp:N #1 }
25477         { \box_use:N \l__box_internal_box }
25478     }
25479     \box_set_dp:Nn \l__box_internal_box \c_zero_dim
25480 }

```

Same thing, this time from the top of the box.

```

25481     \dim_compare:nNnTF { \box_ht:N \l__box_internal_box } > {#5}
25482     {
25483         \hbox_set:Nn \l__box_internal_box
25484         {
25485             \box_move_up:nn \c_zero_dim
25486             { \box_use:N \l__box_internal_box }
25487         }
25488         \box_set_ht:Nn \l__box_internal_box
25489         { \box_ht:N \l__box_internal_box - (#5) }
25490     }
25491     {
25492         \hbox_set:Nn \l__box_internal_box
25493         {
25494             \box_move_up:nn { (#5) - \box_ht:N \l__box_internal_box }
25495             { \box_use:N \l__box_internal_box }
25496         }
25497         \box_set_ht:Nn \l__box_internal_box \c_zero_dim
25498     }
25499     \box_set_eq:NN #1 \l__box_internal_box
25500 }
25501 \cs_generate_variant:Nn \box_trim:Nnnnn { c }

```

(End definition for `\box_trim:Nnnnn`. This function is documented on page 241.)

`\box_viewport:Nnnnn` The same general logic as for the trim operation, but with absolute dimensions. As a result, there are some things to watch out for in the vertical direction.

```

\box_viewport:cnnnn
25502 \cs_new_protected:Npn \box_viewport:Nnnnn #1#2#3#4#5
25503 {
25504     \hbox_set:Nn \l__box_internal_box
25505     {
25506         \tex_kern:D - \__box_dim_eval:n {#2}
25507         \box_use:N #1
25508         \tex_kern:D \__box_dim_eval:n { #4 - \box_wd:N #1 }
25509     }
25510     \dim_compare:nNnTF {#3} < \c_zero_dim
25511     {
25512         \hbox_set:Nn \l__box_internal_box
25513         {
25514             \box_move_down:nn \c_zero_dim
25515             { \box_use:N \l__box_internal_box }
25516         }

```

```

25517     \box_set_dp:Nn \l__box_internal_box { - \__box_dim_eval:n {#3} }
25518   }
25519   {
25520     \hbox_set:Nn \l__box_internal_box
25521       { \box_move_down:nn {#3} { \box_use:N \l__box_internal_box } }
25522     \box_set_dp:Nn \l__box_internal_box \c_zero_dim
25523   }
25524   \dim_compare:nNnTF {#5} > \c_zero_dim
25525   {
25526     \hbox_set:Nn \l__box_internal_box
25527     {
25528       \box_move_up:nn \c_zero_dim
25529       { \box_use:N \l__box_internal_box }
25530     }
25531     \box_set_ht:Nn \l__box_internal_box
25532     {
25533       (#5)
25534       \dim_compare:nNnT {#3} > \c_zero_dim
25535       { - (#3) }
25536     }
25537   }
25538   {
25539     \hbox_set:Nn \l__box_internal_box
25540     {
25541       \box_move_up:nn { - \__box_dim_eval:n {#5} }
25542       { \box_use:N \l__box_internal_box }
25543     }
25544     \box_set_ht:Nn \l__box_internal_box \c_zero_dim
25545   }
25546   \box_set_eq:NN #1 \l__box_internal_box
25547 }
25548 \cs_generate_variant:Nn \box_viewport:Nnnnn { c }

```

(End definition for `\box_viewport:Nnnnn`. This function is documented on page 241.)

44.3 Additions to `l3coffins`

25549 `<@@=coffin>`

44.3.1 Rotating coffins

`\l__coffin_sin_fp` Used for rotations to get the sine and cosine values.

```

\l__coffin_cos_fp 25550 \fp_new:N \l__coffin_sin_fp
25551 \fp_new:N \l__coffin_cos_fp

```

(End definition for `\l__coffin_sin_fp` and `\l__coffin_cos_fp`.)

`\l__coffin_bounding_prop` A property list for the bounding box of a coffin. This is only needed during the rotation, so there is just the one.

```
25552 \prop_new:N \l__coffin_bounding_prop
```

(End definition for `\l__coffin_bounding_prop`.)

`\l__coffin_bounding_shift_dim` The shift of the bounding box of a coffin from the real content.

```
25553 \dim_new:N \l__coffin_bounding_shift_dim
```

(End definition for \l__coffin_bounding_shift_dim.)

\l__coffin_left_corner_dim These are used to hold maxima for the various corner values: these thus define the
\l__coffin_right_corner_dim minimum size of the bounding box after rotation.

```

\l__coffin_bottom_corner_dim 25554 \dim_new:N \l__coffin_left_corner_dim
\l__coffin_top_corner_dim     25555 \dim_new:N \l__coffin_right_corner_dim
                              25556 \dim_new:N \l__coffin_bottom_corner_dim
                              25557 \dim_new:N \l__coffin_top_corner_dim

```

(End definition for \l__coffin_left_corner_dim and others.)

\coffin_rotate:Nn Rotating a coffin requires several steps which can be conveniently run together. The sine
\coffin_rotate:cn and cosine of the angle in degrees are computed. This is then used to set \l__coffin_
sin_fp and \l__coffin_cos_fp, which are carried through unchanged for the rest of
the procedure.

```

25558 \cs_new_protected:Npn \coffin_rotate:Nn #1#2
25559 {
25560   \fp_set:Nn \l__coffin_sin_fp { sind ( #2 ) }
25561   \fp_set:Nn \l__coffin_cos_fp { cosd ( #2 ) }

```

The corners and poles of the coffin can now be rotated around the origin. This is best
achieved using mapping functions.

```

25562 \prop_map_inline:cn { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
25563 { \__coffin_rotate_corner:Nnnn #1 {##1} ##2 }
25564 \prop_map_inline:cn { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
25565 { \__coffin_rotate_pole:Nnnnn #1 {##1} ##2 }

```

The bounding box of the coffin needs to be rotated, and to do this the corners have to be
found first. They are then rotated in the same way as the corners of the coffin material
itself.

```

25566 \__coffin_set_bounding:N #1
25567 \prop_map_inline:Nn \l__coffin_bounding_prop
25568 { \__coffin_rotate_bounding:nnn {##1} ##2 }

```

At this stage, there needs to be a calculation to find where the corners of the content
and the box itself will end up.

```

25569 \__coffin_find_corner_maxima:N #1
25570 \__coffin_find_bounding_shift:
25571 \box_rotate:Nn #1 {#2}

```

The correction of the box position itself takes place here. The idea is that the bounding
box for a coffin is tight up to the content, and has the reference point at the bottom-left.
The x -direction is handled by moving the content by the difference in the positions of
the bounding box and the content left edge. The y -direction is dealt with by moving the
box down by any depth it has acquired. The internal box is used here to allow for the
next step.

```

25572 \hbox_set:Nn \l__coffin_internal_box
25573 {
25574   \tex_kern:D
25575   \dim_eval:n
25576   { \l__coffin_bounding_shift_dim - \l__coffin_left_corner_dim }
25577   \exp_stop_f:
25578   \box_move_down:nn { \l__coffin_bottom_corner_dim }
25579   { \box_use:N #1 }
25580 }

```

If there have been any previous rotations then the size of the bounding box will be bigger than the contents. This can be corrected easily by setting the size of the box to the height and width of the content. As this operation requires setting box dimensions and these transcend grouping, the safe way to do this is to use the internal box and to reset the result into the target box.

```

25581 \box_set_ht:Nn \l__coffin_internal_box
25582 { \l__coffin_top_corner_dim - \l__coffin_bottom_corner_dim }
25583 \box_set_dp:Nn \l__coffin_internal_box { 0 pt }
25584 \box_set_wd:Nn \l__coffin_internal_box
25585 { \l__coffin_right_corner_dim - \l__coffin_left_corner_dim }
25586 \hbox_set:Nn #1 { \box_use:N \l__coffin_internal_box }

```

The final task is to move the poles and corners such that they are back in alignment with the box reference point.

```

25587 \prop_map_inline:cn { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
25588 { \__coffin_shift_corner:Nnnn #1 {##1} ##2 }
25589 \prop_map_inline:cn { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
25590 { \__coffin_shift_pole:Nnnnnn #1 {##1} ##2 }
25591 }
25592 \cs_generate_variant:Nn \coffin_rotate:Nn { c }

```

(End definition for \coffin_rotate:Nn. This function is documented on page 241.)

__coffin_set_bounding:N

The bounding box corners for a coffin are easy enough to find: this is the same code as for the corners of the material itself, but using a dedicated property list.

```

25593 \cs_new_protected:Npn \__coffin_set_bounding:N #1
25594 {
25595   \prop_put:Nnx \l__coffin_bounding_prop { tl }
25596   { { 0 pt } { \dim_eval:n { \box_ht:N #1 } } }
25597   \prop_put:Nnx \l__coffin_bounding_prop { tr }
25598   {
25599     { \dim_eval:n { \box_wd:N #1 } }
25600     { \dim_eval:n { \box_ht:N #1 } }
25601   }
25602   \dim_set:Nn \l__coffin_internal_dim { -\box_dp:N #1 }
25603   \prop_put:Nnx \l__coffin_bounding_prop { bl }
25604   { { 0 pt } { \dim_use:N \l__coffin_internal_dim } }
25605   \prop_put:Nnx \l__coffin_bounding_prop { br }
25606   {
25607     { \dim_eval:n { \box_wd:N #1 } }
25608     { \dim_use:N \l__coffin_internal_dim }
25609   }
25610 }

```

(End definition for __coffin_set_bounding:N.)

__coffin_rotate_bounding:nnn

__coffin_rotate_corner:Nnnn

Rotating the position of the corner of the coffin is just a case of treating this as a vector from the reference point. The same treatment is used for the corners of the material itself and the bounding box.

```

25611 \cs_new_protected:Npn \__coffin_rotate_bounding:nnn #1#2#3
25612 {
25613   \__coffin_rotate_vector:nnNN {#2} {#3} \l__coffin_x_dim \l__coffin_y_dim
25614   \prop_put:Nnx \l__coffin_bounding_prop {#1}
25615   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }

```

```

25616 }
25617 \cs_new_protected:Npn \__coffin_rotate_corner:Nnnn #1#2#3#4
25618 {
25619   \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
25620   \prop_put:cnx { \l__coffin_corners_ \__coffin_to_value:N #1 _prop } {#2}
25621   { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
25622 }

```

(End definition for __coffin_rotate_bounding:nnn and __coffin_rotate_corner:Nnnn.)

__coffin_rotate_pole:Nnnnnn Rotating a single pole simply means shifting the co-ordinate of the pole and its direction. The rotation here is about the bottom-left corner of the coffin.

```

25623 \cs_new_protected:Npn \__coffin_rotate_pole:Nnnnnn #1#2#3#4#5#6
25624 {
25625   \__coffin_rotate_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
25626   \__coffin_rotate_vector:nnNN {#5} {#6}
25627   \l__coffin_x_prime_dim \l__coffin_y_prime_dim
25628   \__coffin_set_pole:Nnx #1 {#2}
25629   {
25630     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
25631     { \dim_use:N \l__coffin_x_prime_dim }
25632     { \dim_use:N \l__coffin_y_prime_dim }
25633   }
25634 }

```

(End definition for __coffin_rotate_pole:Nnnnnn.)

__coffin_rotate_vector:nnNN A rotation function, which needs only an input vector (as dimensions) and an output space. The values \l__coffin_cos_fp and \l__coffin_sin_fp should previously have been set up correctly. Working this way means that the floating point work is kept to a minimum: for any given rotation the sin and cosine values do no change, after all.

```

25635 \cs_new_protected:Npn \__coffin_rotate_vector:nnNN #1#2#3#4
25636 {
25637   \dim_set:Nn #3
25638   {
25639     \fp_to_dim:n
25640     {
25641       \dim_to_fp:n {#1} * \l__coffin_cos_fp
25642       - \dim_to_fp:n {#2} * \l__coffin_sin_fp
25643     }
25644   }
25645   \dim_set:Nn #4
25646   {
25647     \fp_to_dim:n
25648     {
25649       \dim_to_fp:n {#1} * \l__coffin_sin_fp
25650       + \dim_to_fp:n {#2} * \l__coffin_cos_fp
25651     }
25652   }
25653 }

```

(End definition for __coffin_rotate_vector:nnNN.)

`_coffin_find_corner_maxima:N
 _coffin_find_corner_maxima_aux:nn`

The idea here is to find the extremities of the content of the coffin. This is done by looking for the smallest values for the bottom and left corners, and the largest values for the top and right corners. The values start at the maximum dimensions so that the case where all are positive or all are negative works out correctly.

```

25654 \cs_new_protected:Npn \_coffin_find_corner_maxima:N #1
25655 {
25656   \dim_set:Nn \l__coffin_top_corner_dim { -\c_max_dim }
25657   \dim_set:Nn \l__coffin_right_corner_dim { -\c_max_dim }
25658   \dim_set:Nn \l__coffin_bottom_corner_dim { \c_max_dim }
25659   \dim_set:Nn \l__coffin_left_corner_dim { \c_max_dim }
25660   \prop_map_inline:cn { l__coffin_corners_ \_coffin_to_value:N #1 _prop }
25661     { \_coffin_find_corner_maxima_aux:nn ##2 }
25662 }
25663 \cs_new_protected:Npn \_coffin_find_corner_maxima_aux:nn #1#2
25664 {
25665   \dim_set:Nn \l__coffin_left_corner_dim
25666     { \dim_min:nn { \l__coffin_left_corner_dim } {#1} }
25667   \dim_set:Nn \l__coffin_right_corner_dim
25668     { \dim_max:nn { \l__coffin_right_corner_dim } {#1} }
25669   \dim_set:Nn \l__coffin_bottom_corner_dim
25670     { \dim_min:nn { \l__coffin_bottom_corner_dim } {#2} }
25671   \dim_set:Nn \l__coffin_top_corner_dim
25672     { \dim_max:nn { \l__coffin_top_corner_dim } {#2} }
25673 }
    
```

(End definition for `_coffin_find_corner_maxima:N` and `_coffin_find_corner_maxima_aux:nn`.)

`_coffin_find_bounding_shift:
 _coffin_find_bounding_shift_aux:nn`

The approach to finding the shift for the bounding box is similar to that for the corners. However, there is only one value needed here and a fixed input property list, so things are a bit clearer.

```

25674 \cs_new_protected:Npn \_coffin_find_bounding_shift:
25675 {
25676   \dim_set:Nn \l__coffin_bounding_shift_dim { \c_max_dim }
25677   \prop_map_inline:Nn \l__coffin_bounding_prop
25678     { \_coffin_find_bounding_shift_aux:nn ##2 }
25679 }
25680 \cs_new_protected:Npn \_coffin_find_bounding_shift_aux:nn #1#2
25681 {
25682   \dim_set:Nn \l__coffin_bounding_shift_dim
25683     { \dim_min:nn { \l__coffin_bounding_shift_dim } {#1} }
25684 }
    
```

(End definition for `_coffin_find_bounding_shift:` and `_coffin_find_bounding_shift_aux:nn`.)

`_coffin_shift_corner:Nnnn
 _coffin_shift_pole:Nnnnnn`

Shifting the corners and poles of a coffin means subtracting the appropriate values from the x - and y -components. For the poles, this means that the direction vector is unchanged.

```

25685 \cs_new_protected:Npn \_coffin_shift_corner:Nnnn #1#2#3#4
25686 {
25687   \prop_put:cnx { l__coffin_corners_ \_coffin_to_value:N #1 _prop } {#2}
25688     {
25689       { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
25690       { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
25691     }
    
```



```

25692 }
25693 \cs_new_protected:Npn \__coffin_shift_pole:Nnnnnn #1#2#3#4#5#6
25694 {
25695   \prop_put:cnx { l__coffin_poles_ \__coffin_to_value:N #1 _ prop } {#2}
25696   {
25697     { \dim_eval:n { #3 - \l__coffin_left_corner_dim } }
25698     { \dim_eval:n { #4 - \l__coffin_bottom_corner_dim } }
25699     {#5} {#6}
25700   }
25701 }

```

(End definition for __coffin_shift_corner:Nnnn and __coffin_shift_pole:Nnnnnn.)

44.3.2 Resizing coffins

\l__coffin_scale_x_fp Storage for the scaling factors in x and y , respectively.
 \l__coffin_scale_y_fp

```

25702 \fp_new:N \l__coffin_scale_x_fp
25703 \fp_new:N \l__coffin_scale_y_fp

```

(End definition for \l__coffin_scale_x_fp and \l__coffin_scale_y_fp.)

\l__coffin_scaled_total_height_dim When scaling, the values given have to be turned into absolute values.
 \l__coffin_scaled_width_dim

```

25704 \dim_new:N \l__coffin_scaled_total_height_dim
25705 \dim_new:N \l__coffin_scaled_width_dim

```

(End definition for \l__coffin_scaled_total_height_dim and \l__coffin_scaled_width_dim.)

\coffin_resize:Nnn Resizing a coffin begins by setting up the user-friendly names for the dimensions of the coffin box. The new sizes are then turned into scale factor. This is the same operation as takes place for the underlying box, but that operation is grouped and so the same calculation is done here.
\coffin_resize:cnn

```

25706 \cs_new_protected:Npn \coffin_resize:Nnn #1#2#3
25707 {
25708   \fp_set:Nn \l__coffin_scale_x_fp
25709   { \dim_to_fp:n {#2} / \dim_to_fp:n { \coffin_wd:N #1 } }
25710   \fp_set:Nn \l__coffin_scale_y_fp
25711   {
25712     \dim_to_fp:n {#3}
25713     / \dim_to_fp:n { \coffin_ht:N #1 + \coffin_dp:N #1 }
25714   }
25715   \box_resize_to_wd_and_ht_plus_dp:Nnn #1 {#2} {#3}
25716   \__coffin_resize_common:Nnn #1 {#2} {#3}
25717 }
25718 \cs_generate_variant:Nn \coffin_resize:Nnn { c }

```

(End definition for \coffin_resize:Nnn. This function is documented on page 241.)

__coffin_resize_common:Nnn The poles and corners of the coffin are scaled to the appropriate places before actually resizing the underlying box.

```

25719 \cs_new_protected:Npn \__coffin_resize_common:Nnn #1#2#3
25720 {
25721   \prop_map_inline:cn { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
25722   { \__coffin_scale_corner:Nnnn #1 {##1} ##2 }
25723   \prop_map_inline:cn { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
25724   { \__coffin_scale_pole:Nnnnnn #1 {##1} ##2 }

```

Negative x -scaling values place the poles in the wrong location: this is corrected here.

```

25725 \fp_compare:nNnT \l__coffin_scale_x_fp < \c_zero_fp
25726 {
25727   \prop_map_inline:cn
25728     { l__coffin_corners_ \__coffin_to_value:N #1 _prop }
25729     { \__coffin_x_shift_corner:Nnnn #1 {##1} ##2 }
25730   \prop_map_inline:cn
25731     { l__coffin_poles_ \__coffin_to_value:N #1 _prop }
25732     { \__coffin_x_shift_pole:Nnnnnn #1 {##1} ##2 }
25733 }
25734 }

```

(End definition for `__coffin_resize_common:Nnn`.)

`\coffin_scale:Nnn`
`\coffin_scale:cnn`

For scaling, the opposite calculation is done to find the new dimensions for the coffin. Only the total height is needed, as this is the shift required for corners and poles. The scaling is done the T_EX way as this works properly with floating point values without needing to use the `fp` module.

```

25735 \cs_new_protected:Npn \coffin_scale:Nnn #1#2#3
25736 {
25737   \fp_set:Nn \l__coffin_scale_x_fp {#2}
25738   \fp_set:Nn \l__coffin_scale_y_fp {#3}
25739   \box_scale:Nnn #1 { \l__coffin_scale_x_fp } { \l__coffin_scale_y_fp }
25740   \dim_set:Nn \l__coffin_internal_dim
25741     { \coffin_ht:N #1 + \coffin_dp:N #1 }
25742   \dim_set:Nn \l__coffin_scaled_total_height_dim
25743     { \fp_abs:n { \l__coffin_scale_y_fp } \l__coffin_internal_dim }
25744   \dim_set:Nn \l__coffin_scaled_width_dim
25745     { -\fp_abs:n { \l__coffin_scale_x_fp } \coffin_wd:N #1 }
25746   \__coffin_resize_common:Nnn #1
25747     { \l__coffin_scaled_width_dim } { \l__coffin_scaled_total_height_dim }
25748 }
25749 \cs_generate_variant:Nn \coffin_scale:Nnn { c }

```

(End definition for `\coffin_scale:Nnn`. This function is documented on page 241.)

`__coffin_scale_vector:nnNN`

This functions scales a vector from the origin using the pre-set scale factors in x and y . This is a much less complex operation than rotation, and as a result the code is a lot clearer.

```

25750 \cs_new_protected:Npn \__coffin_scale_vector:nnNN #1#2#3#4
25751 {
25752   \dim_set:Nn #3
25753     { \fp_to_dim:n { \dim_to_fp:n {#1} * \l__coffin_scale_x_fp } }
25754   \dim_set:Nn #4
25755     { \fp_to_dim:n { \dim_to_fp:n {#2} * \l__coffin_scale_y_fp } }
25756 }

```

(End definition for `__coffin_scale_vector:nnNN`.)

`__coffin_scale_corner:Nnnn`
`__coffin_scale_pole:Nnnnnn`

Scaling both corners and poles is a simple calculation using the preceding vector scaling.

```

25757 \cs_new_protected:Npn \__coffin_scale_corner:Nnnn #1#2#3#4
25758 {
25759   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
25760   \prop_put:cnx { l__coffin_corners_ \__coffin_to_value:N #1 _prop } {#2}

```

```

25761     { { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim } }
25762   }
25763 \cs_new_protected:Npn \__coffin_scale_pole:Nnnnnn #1#2#3#4#5#6
25764 {
25765   \__coffin_scale_vector:nnNN {#3} {#4} \l__coffin_x_dim \l__coffin_y_dim
25766   \__coffin_set_pole:Nnx #1 {#2}
25767   {
25768     { \dim_use:N \l__coffin_x_dim } { \dim_use:N \l__coffin_y_dim }
25769     {#5} {#6}
25770   }
25771 }

```

(End definition for `__coffin_scale_corner:Nnnn` and `__coffin_scale_pole:Nnnnnn`.)

`__coffin_x_shift_corner:Nnnn` These functions correct for the x displacement that takes place with a negative horizontal scaling.
`__coffin_x_shift_pole:Nnnnnn`

```

25772 \cs_new_protected:Npn \__coffin_x_shift_corner:Nnnn #1#2#3#4
25773 {
25774   \prop_put:cnx { l__coffin_corners_ \__coffin_to_value:N #1 _prop } {#2}
25775   {
25776     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
25777   }
25778 }
25779 \cs_new_protected:Npn \__coffin_x_shift_pole:Nnnnnn #1#2#3#4#5#6
25780 {
25781   \prop_put:cnx { l__coffin_poles_ \__coffin_to_value:N #1 _prop } {#2}
25782   {
25783     { \dim_eval:n { #3 + \box_wd:N #1 } } {#4}
25784     {#5} {#6}
25785   }
25786 }

```

(End definition for `__coffin_x_shift_corner:Nnnn` and `__coffin_x_shift_pole:Nnnnnn`.)

44.4 Additions to l3fp-convert

25787 `<@@=fp>`

`\fp_sign:n` Trivial but useful. See the implementation of `\fp_add:Nn` for an explanation of why to use `__fp_parse:n`, namely, for better error reporting.

```

25788 \cs_new:Npn \fp_sign:n #1
25789 { \fp_to_decimal:n { sign \__fp_parse:n {#1} } }

```

(End definition for `\fp_sign:n`. This function is documented on page 242.)

44.5 Additions to l3file

25790 `<@@=file>`

`\file_get_md5five_hash:nN` These are all wrappers around the pdfTeX primitives doing the same jobs: as we want
`\file_get_size:nN` consistent file paths to be found, they are all set up using `\file_get_full_name:nN`
`\file_get_timestamp:nN` and so are non-expandable `get` functions. Much of the code is repetitive but we need
`__file_get_details:nnN` to branch for LuaTeX (emulation in Lua), for the slightly different syntax needed for `\tex_md5fivesum:D` and for the fact that primitive coverage varies in other engines.

```

25791 \cs_new_protected:Npn \file_get_md5five_hash:nN #1#2

```

```

25792 { \_file_get_details:nnN {#1} { mdfivesum } {#2} }
25793 \cs_new_protected:Npn \file_get_size:nN #1#2
25794 { \_file_get_details:nnN {#1} { size } {#2} }
25795 \cs_new_protected:Npn \file_get_timestamp:nN #1#2
25796 { \_file_get_details:nnN {#1} { moddate } {#2} }
25797 \cs_new_protected:Npn \_file_get_details:nnN #1#2#3
25798 {
25799   \file_get_full_name:nN {#1} \l__file_full_name_str
25800   \str_set:Nx #3
25801   {
25802     \use:c { tex_file #2 :D } \exp_after:wN
25803     { \l__file_full_name_str }
25804   }
25805 }
25806 \sys_if_engine luatex:TF
25807 {
25808   \cs_set_protected:Npn \_file_get_details:nnN #1#2#3
25809   {
25810     \file_get_full_name:nN {#1} \l__file_full_name_str
25811     \str_set:Nx #3
25812     {
25813       \lua_now:e
25814       {
25815         l3kernel.file#2
25816         ( " \lua_escape:e { \l__file_full_name_str } " )
25817       }
25818     }
25819   }
25820 }
25821 {
25822   \cs_set_protected:Npn \file_get_md5sum:nN #1#2
25823   {
25824     \file_get_full_name:nN {#1} \l__file_full_name_str
25825     \tl_set:Nx #2
25826     {
25827       \tex_md5sum:D file \exp_after:wN
25828       { \l__file_full_name_str }
25829     }
25830   }
25831   \cs_if_exist:NF \tex_filesize:D
25832   {
25833     \cs_set_protected:Npn \_file_get_details:nnN #1#2#3
25834     {
25835       \tl_clear:N #3
25836       \__kernel_msg_error:nnx
25837       { kernel } { primitive-not-available }
25838       { \exp_not:c { (pdf)file #2 } }
25839     }
25840   }
25841 }
25842 \__kernel_msg_new:nnnn { kernel } { primitive-not-available }
25843 { Primitive~\token_to_str:N #1 not~available }
25844 {
25845   The~version~of~XeTeX~in~use~does~not~provide~functionality~equivalent~to~

```

```

25846     the~\token_to_str:N #1 primitive.
25847 }

```

(End definition for `\file_get_md5five_hash:nN` and others. These functions are documented on page 243.)

`\file_if_exist_input:n` Input of a file with a test for existence. We do not define the T or TF variants because the most useful place to place the *<true code>* would be inconsistent with other conditionals.

`\file_if_exist_input:nF`

```

25848 \cs_new_protected:Npn \file_if_exist_input:n #1
25849 {
25850     \file_get_full_name:nN {#1} \l__file_full_name_str
25851     \str_if_empty:NF \l__file_full_name_str
25852     { \__file_input:V \l__file_full_name_str }
25853 }
25854 \cs_new_protected:Npn \file_if_exist_input:nF #1#2
25855 {
25856     \file_get_full_name:nN {#1} \l__file_full_name_str
25857     \str_if_empty:NTF \l__file_full_name_str
25858     {#2}
25859     { \__file_input:V \l__file_full_name_str }
25860 }

```

(End definition for `\file_if_exist_input:n` and `\file_if_exist_input:nF`. These functions are documented on page 243.)

`\file_input_stop:` A simple rename.

```

25861 \cs_new_protected:Npn \file_input_stop: { \tex_endinput:D }

```

(End definition for `\file_input_stop:.` This function is documented on page 244.)

44.6 Additions to l3flag

```

25862 <@@=flag>

```

`\flag_raise_if_clear:n`

It might be faster to just call the “trap” function in all cases but conceptually the function name suggests we should only run it if the flag is zero in case the “trap” made customizable in the future.

```

25863 \__kernel_patch:nnNNpn { \__flag_chk_exist:n {#1} } { }
25864 \cs_new:Npn \flag_raise_if_clear:n #1
25865 {
25866     \if_cs_exist:w flag~#1~0 \cs_end:
25867     \else:
25868         \cs:w flag~#1 \cs_end: 0 ;
25869     \fi:
25870 }

```

(End definition for `\flag_raise_if_clear:n`. This function is documented on page 244.)

44.7 Additions to l3msg

25871 `<@@=int>`

`\int_sign:n` See `\int_abs:n`. Evaluate the expression once (and when debugging is enabled, check that the expression is well-formed), then test the first character to determine the sign. This is wrapped in `\int_value:w ... \exp_stop_f:` to ensure a fixed number of expansions and to avoid dealing with closing the conditionals.

`__int_sign:Nw`

```
25872 \__kernel_patch_args:nNpN
25873 { { \__kernel_chk_expr:nNnN {#1} \__int_eval:w { } \int_sign:n } }
25874 \cs_new:Npn \int_sign:n #1
25875 {
25876   \int_value:w \exp_after:wN \__int_sign:Nw
25877   \int_value:w \__int_eval:w #1 \__int_eval_end: ;
25878   \exp_stop_f:
25879 }
25880 \cs_new:Npn \__int_sign:Nw #1#2 ;
25881 {
25882   \if_meaning:w 0 #1
25883   0
25884   \else:
25885     \if_meaning:w - #1 - \fi: 1
25886   \fi:
25887 }
```

(End definition for `\int_sign:n` and `__int_sign:Nw`. This function is documented on page 244.)

44.8 Additions to l3msg

25888 `<@@=msg>`

`\msg_expandable_error:nnnnnn` Pass to an auxiliary the message to display and the module name

`\msg_expandable_error:nnffff`

`\msg_expandable_error:nnnnn`

`\msg_expandable_error:nnfff`

`\msg_expandable_error:nnnn`

`\msg_expandable_error:nnff`

`\msg_expandable_error:nnn`

`\msg_expandable_error:nnf`

`\msg_expandable_error:nn`

`__msg_expandable_error_module:nn`

```
25889 \cs_new:Npn \msg_expandable_error:nnnnnn #1#2#3#4#5#6
25890 {
25891   \exp_args:Nf \__msg_expandable_error_module:nn
25892   {
25893     \exp_args:Nf \tl_to_str:n
25894     { \use:c { \c_msg_text_prefix_tl #1 / #2 } {#3} {#4} {#5} {#6} }
25895   }
25896   {#1}
25897 }
25898 \cs_new:Npn \msg_expandable_error:nnnnn #1#2#3#4#5
25899 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} {#5} { } }
25900 \cs_new:Npn \msg_expandable_error:nnnn #1#2#3#4
25901 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} {#4} { } { } }
25902 \cs_new:Npn \msg_expandable_error:nnn #1#2#3
25903 { \msg_expandable_error:nnnnnn {#1} {#2} {#3} { } { } { } }
25904 \cs_new:Npn \msg_expandable_error:nn #1#2
25905 { \msg_expandable_error:nnnnnn {#1} {#2} { } { } { } { } }
25906 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnffff }
25907 \cs_generate_variant:Nn \msg_expandable_error:nnnnnn { nnfff }
25908 \cs_generate_variant:Nn \msg_expandable_error:nnnn { nnff }
25909 \cs_generate_variant:Nn \msg_expandable_error:nnn { nnf }
25910 \cs_new:Npn \__msg_expandable_error_module:nn #1#2
25911 {
```

```

25912 \exp_after:wN \exp_after:wN
25913 \exp_after:wN \use_none_delimit_by_q_stop:w
25914 \use:n { \::error ! ~ #2 : ~ #1 } \q_stop
25915 }

```

(End definition for `\msg_expandable_error:nnnnn` and others. These functions are documented on page 246.)

`\msg_show_eval:Nn` A short-hand used for `\int_show:n` and similar functions that passes to `\tl_show:n` the result of applying #1 (a function such as `\int_eval:n`) to the expression #2. The use of `f`-expansion ensures that #1 is expanded in the scope in which the show command is called, rather than in the group created by `\iow_wrap:nnnN`. This is only important for expressions involving the `\currentgrouplevel` or `\currentgrouptype`. On the other hand we want the expression to be converted to a string with the usual escape character, hence within the wrapping code.

```

25916 \cs_new_protected:Npn \msg_show_eval:Nn #1#2
25917 { \exp_args:Nf \_msg_show_eval:nnN { #1 {#2} } {#2} \tl_show:n }
25918 \cs_new_protected:Npn \msg_log_eval:Nn #1#2
25919 { \exp_args:Nf \_msg_show_eval:nnN { #1 {#2} } {#2} \tl_log:n }
25920 \cs_new_protected:Npn \_msg_show_eval:nnN #1#2#3 { #3 { #2 = #1 } }

```

(End definition for `\msg_show_eval:Nn`, `\msg_log_eval:Nn`, and `_msg_show_eval:nnN`. These functions are documented on page 246.)

`\msg_show_item:n` Each item in the variable is formatted using one of the following functions. We cannot use `\` and so on because these short-hands cannot be used inside the arguments of messages, only when defining the messages.

```

25921 \cs_new:Npx \msg_show_item:n #1
25922 { \iow_newline: > ~ \c_space_tl \exp_not:N \tl_to_str:n { {#1} } }
25923 \cs_new:Npx \msg_show_item_unbraced:n #1
25924 { \iow_newline: > ~ \c_space_tl \exp_not:N \tl_to_str:n {#1} }
25925 \cs_new:Npx \msg_show_item:nn #1#2
25926 {
25927   \iow_newline: > \use:nn { ~ } { ~ }
25928   \exp_not:N \tl_to_str:n { {#1} }
25929   \use:nn { ~ } { ~ } => \use:nn { ~ } { ~ }
25930   \exp_not:N \tl_to_str:n { {#2} }
25931 }
25932 \cs_new:Npx \msg_show_item_unbraced:nn #1#2
25933 {
25934   \iow_newline: > \use:nn { ~ } { ~ }
25935   \exp_not:N \tl_to_str:n {#1}
25936   \use:nn { ~ } { ~ } => \use:nn { ~ } { ~ }
25937   \exp_not:N \tl_to_str:n {#2}
25938 }

```

(End definition for `\msg_show_item:n` and others. These functions are documented on page 246.)

44.9 Additions to `l3prg`

`\bool_const:Nn` A merger between `\tl_const:Nn` and `\bool_set:Nn`.

```

\bool_const:cn 25939 \_kernel_patch:nnNn { \_kernel_chk_var_scope:NN c #1 } { }
25940 \cs_new_protected:Npn \bool_const:Nn #1#2
25941 {

```

```

25942 \__kernel_chk_if_free_cs:N #1
25943 \tex_global:D \tex_chardef:D #1 = \bool_if_p:n {#2}
25944 }
25945 \cs_generate_variant:Nn \bool_const:Nn { c }

```

(End definition for `\bool_const:Nn`. This function is documented on page 246.)

```

\bool_set_inverse:N Set to false or true locally or globally.
\bool_set_inverse:c 25946 \cs_new_protected:Npn \bool_set_inverse:N #1
\bool_gset_inverse:N 25947 { \bool_if:NTF #1 { \bool_set_false:N } { \bool_set_true:N } #1 }
\bool_gset_inverse:c 25948 \cs_generate_variant:Nn \bool_set_inverse:N { c }
25949 \cs_new_protected:Npn \bool_gset_inverse:N #1
25950 { \bool_if:NTF #1 { \bool_gset_false:N } { \bool_gset_true:N } #1 }
25951 \cs_generate_variant:Nn \bool_gset_inverse:N { c }

```

(End definition for `\bool_set_inverse:N` and `\bool_gset_inverse:N`. These functions are documented on page 247.)

44.10 Additions to l3prop

```

25952 <@@=prop>

```

`\prop_count:N` Counting the key–value pairs in a property list is done using the same approach as for other count functions: turn each entry into a +1 then use integer evaluation to actually do the mathematics.

```

\prop_count:c 25953 \cs_new:Npn \prop_count:N #1
\__prop_count:nn 25954 {
25955 \int_eval:n
25956 {
25957 0
25958 \prop_map_function:NN #1 \__prop_count:nn
25959 }
25960 }
25961 \cs_new:Npn \__prop_count:nn #1#2 { + 1 }
25962 \cs_generate_variant:Nn \prop_count:N { c }

```

(End definition for `\prop_count:N` and `__prop_count:nn`. This function is documented on page 247.)

`\prop_map_tokens:Nn` The mapping is very similar to `\prop_map_function:NN`. The `\use_i:nn` removes the leading `\s__prop`. The odd construction `\use:n {#1}` allows #1 to contain any token without interfering with `\prop_map_break:.` The loop stops when the argument delimited by `__prop_pair:wn` is `\prg_break:` instead of being empty.

```

25963 \cs_new:Npn \prop_map_tokens:Nn #1#2
25964 {
25965 \exp_last_unbraced:Nno
25966 \use_i:nn { \__prop_map_tokens:nwn {#2} } #1
25967 \prg_break: \__prop_pair:wn \s__prop { } \prg_break_point:
25968 \prg_break_point:Nn \prop_map_break: { }
25969 }
25970 \cs_new:Npn \__prop_map_tokens:nwn #1#2 \__prop_pair:wn #3 \s__prop #4
25971 {
25972 #2
25973 \use:n {#1} {#3} {#4}
25974 \__prop_map_tokens:nwn {#1}
25975 }
25976 \cs_generate_variant:Nn \prop_map_tokens:Nn { c }

```


(End definition for `\prop_map_tokens:Nn` and `_prop_map_tokens:nwn`. This function is documented on page 247.)

`\prop_rand_key_value:N` Contrarily to `clist`, `seq` and `tl`, there is no function to get an item of a `prop` given an integer between 1 and the number of items, so we write the appropriate code. There is no bounds checking because `\int_rand:nn` is always within bounds. The initial `\int_value:w` is stopped by the first `\s__prop` in #1.

```
\prop_rand_key_value:c
  \_prop_rand_item:w
25977 \cs_new:Npn \prop_rand_key_value:N #1
25978 {
25979   \prop_if_empty:NF #1
25980   {
25981     \exp_after:wN \_prop_rand_item:w
25982     \int_value:w \int_rand:nn { 1 } { \prop_count:N #1 }
25983     #1 \q_stop
25984   }
25985 }
25986 \cs_generate_variant:Nn \prop_rand_key_value:N { c }
25987 \cs_new:Npn \_prop_rand_item:w #1 \s__prop \_prop_pair:wn #2 \s__prop #3
25988 {
25989   \int_compare:nNnF {#1} > 1
25990   { \use_i_delimit_by_q_stop:nw { \exp_not:n { {#2} {#3} } } }
25991   \exp_after:wN \_prop_rand_item:w
25992   \int_value:w \int_eval:n { #1 - 1 } \s__prop
25993 }
```

(End definition for `\prop_rand_key_value:N` and `_prop_rand_item:w`. This function is documented on page 247.)

44.11 Additions to l3seq

25994 `<@@=seq>`

`\seq_mapthread_function:NNN` The idea is to first expand both sequences, adding the usual `{ ? \prg_break: } { }` to the end of each one. This is most conveniently done in two steps using an auxiliary function. The mapping then throws away the first tokens of #2 and #5, which for items in both sequences are `\s__seq _seq_item:n`. The function to be mapped are then be applied to the two entries. When the code hits the end of one of the sequences, the break material stops the entire loop and tidy up. This avoids needing to find the count of the two sequences, or worrying about which is longer.

```
\seq_mapthread_function:NcN
\seq_mapthread_function:cNN
\seq_mapthread_function:ccN
  \_seq_mapthread_function:wNN
  \_seq_mapthread_function:wNw
  \_seq_mapthread_function:Nnnwnn
25995 \cs_new:Npn \seq_mapthread_function:NNN #1#2#3
25996 { \exp_after:wN \_seq_mapthread_function:wNN #2 \q_stop #1 #3 }
25997 \cs_new:Npn \_seq_mapthread_function:wNN \s__seq #1 \q_stop #2#3
25998 {
25999   \exp_after:wN \_seq_mapthread_function:wNw #2 \q_stop #3
26000   #1 { ? \prg_break: } { }
26001   \prg_break_point:
26002 }
26003 \cs_new:Npn \_seq_mapthread_function:wNw \s__seq #1 \q_stop #2
26004 {
26005   \_seq_mapthread_function:Nnnwnn #2
26006   #1 { ? \prg_break: } { }
26007   \q_stop
26008 }
26009 \cs_new:Npn \_seq_mapthread_function:Nnnwnn #1#2#3#4 \q_stop #5#6
```

```

26010 {
26011   \use_none:n #2
26012   \use_none:n #5
26013   #1 {#3} {#6}
26014   \__seq_mapthread_function:Nnnwnn #1 #4 \q_stop
26015 }
26016 \cs_generate_variant:Nn \seq_mapthread_function:NNN { Nc , c , cc }

```

(End definition for `\seq_mapthread_function:NNN` and others. This function is documented on page 248.)

`\seq_set_filter:NNn` Similar to `\seq_map_inline:Nn`, without a `\prg_break_point:` because the user's code is performed within the evaluation of a boolean expression, and skipping out of that would break horribly. The `__seq_wrap_item:n` function inserts the relevant `__seq_item:n` without expansion in the input stream, hence in the x-expanding assignment.

`\seq_gset_filter:NNn`

`__seq_set_filter:NNNn`

```

26017 \cs_new_protected:Npn \seq_set_filter:NNn
26018 { \__seq_set_filter:NNNn \tl_set:Nx }
26019 \cs_new_protected:Npn \seq_gset_filter:NNn
26020 { \__seq_set_filter:NNNn \tl_gset:Nx }
26021 \cs_new_protected:Npn \__seq_set_filter:NNNn #1#2#3#4
26022 {
26023   \__seq_push_item_def:n { \bool_if:nT {#4} { \__seq_wrap_item:n {##1} } }
26024   #1 #2 { #3 }
26025   \__seq_pop_item_def:
26026 }

```

(End definition for `\seq_set_filter:NNn`, `\seq_gset_filter:NNn`, and `__seq_set_filter:NNNn`. These functions are documented on page 248.)

`\seq_set_map:NNn` Very similar to `\seq_set_filter:NNn`. We could actually merge the two within a single function, but it would have weird semantics.

`\seq_gset_map:NNn`

`__seq_set_map:NNNn`

```

26027 \cs_new_protected:Npn \seq_set_map:NNn
26028 { \__seq_set_map:NNNn \tl_set:Nx }
26029 \cs_new_protected:Npn \seq_gset_map:NNn
26030 { \__seq_set_map:NNNn \tl_gset:Nx }
26031 \cs_new_protected:Npn \__seq_set_map:NNNn #1#2#3#4
26032 {
26033   \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
26034   #1 #2 { #3 }
26035   \__seq_pop_item_def:
26036 }

```

(End definition for `\seq_set_map:NNn`, `\seq_gset_map:NNn`, and `__seq_set_map:NNNn`. These functions are documented on page 248.)

`\seq_set_from_inline_x:Nnn` Set `__seq_item:n` then map it using the loop code.

`\seq_gset_from_inline_x:Nnn`

`__seq_set_from_inline_x:NNnn`

```

26037 \cs_new_protected:Npn \seq_set_from_inline_x:Nnn
26038 { \__seq_set_from_inline_x:NNnn \tl_set:Nx }
26039 \cs_new_protected:Npn \seq_gset_from_inline_x:Nnn
26040 { \__seq_set_from_inline_x:NNnn \tl_gset:Nx }
26041 \cs_new_protected:Npn \__seq_set_from_inline_x:NNnn #1#2#3#4
26042 {
26043   \__seq_push_item_def:n { \exp_not:N \__seq_item:n {#4} }
26044   #1 #2 { \s_seq #3 \__seq_item:n }
26045   \__seq_pop_item_def:
26046 }

```

(End definition for `\seq_set_from_inline_x:Nnn`, `\seq_gset_from_inline_x:Nnn`, and `__seq_set_from_inline_x:Nnn`. These functions are documented on page 249.)

`\seq_set_from_function:NnN`
`\seq_gset_from_function:NnN`

Reuse `\seq_set_from_inline_x:Nnn`.

```
26047 \cs_new_protected:Npn \seq_set_from_function:NnN #1#2#3
26048   { \seq_set_from_inline_x:Nnn #1 {#2} { #3 {##1} } }
26049 \cs_new_protected:Npn \seq_gset_from_function:NnN #1#2#3
26050   { \seq_gset_from_inline_x:Nnn #1 {#2} { #3 {##1} } }
```

(End definition for `\seq_set_from_function:NnN` and `\seq_gset_from_function:NnN`. These functions are documented on page 248.)

`\seq_const_from_clist:Nn`
`\seq_const_from_clist:cn`

Almost identical to `\seq_set_from_clist:Nn`.

```
26051 \cs_new_protected:Npn \seq_const_from_clist:Nn #1#2
26052   {
26053     \tl_const:Nx #1
26054     { \__seq \clist_map_function:nN {#2} \__seq_wrap_item:n }
26055   }
26056 \cs_generate_variant:Nn \seq_const_from_clist:Nn { c }
```

(End definition for `\seq_const_from_clist:Nn`. This function is documented on page 248.)

`\seq_shuffle:N`
`\seq_gshuffle:N`

We apply the Fisher–Yates shuffle, storing items in `\toks` registers. We use the primitive `\tex_uniformdeviate:D` for speed reasons. Its non-uniformity is of order its argument divided by 2^{28} , not too bad for small lists. For sequences with more than 13 elements there are more possible permutations than possible seeds ($13! > 2^{28}$) so the question of uniformity is somewhat moot.

`__seq_shuffle:NN`
`__seq_shuffle_item:n`
`\g__seq_internal_seq`
`\l__seq_internal_a_int`
`\l__seq_internal_b_int`

```
26057 \cs_if_exist:NTF \tex_uniformdeviate:D
26058   {
26059     \int_new:N \l__seq_internal_a_int
26060     \int_new:N \l__seq_internal_b_int
26061     \seq_new:N \g__seq_internal_seq
26062     \cs_new_protected:Npn \seq_shuffle:N { \__seq_shuffle:NN \seq_set_eq:NN }
26063     \cs_new_protected:Npn \seq_gshuffle:N { \__seq_shuffle:NN \seq_gset_eq:NN }
26064     \cs_new_protected:Npn \__seq_shuffle:NN #1#2
26065       {
26066         \int_compare:nNnTF { \seq_count:N #2 } > \c_max_register_int
26067         {
26068           \__kernel_msg_error:nmx { kernel } { shuffle-too-large }
26069           { \token_to_str:N #2 }
26070         }
26071         {
26072           \group_begin:
26073             \cs_set_eq:NN \__seq_item:n \__seq_shuffle_item:n
26074             \int_zero:N \l__seq_internal_a_int
26075             #2
26076             \seq_gset_from_inline_x:Nnn \g__seq_internal_seq
26077               { \int_step_function:nN { \l__seq_internal_a_int } }
26078               { \tex_the:D \tex_toks:D ##1 }
26079           \group_end:
26080           #1 #2 \g__seq_internal_seq
26081           \seq_gclear:N \g__seq_internal_seq
26082         }
26083       }
```

```

26084 \cs_new_protected:Npn \__seq_shuffle_item:n
26085 {
26086   \int_incr:N \l__seq_internal_a_int
26087   \int_set:Nn \l__seq_internal_b_int
26088     { 1 + \tex_uniformdeviate:D \l__seq_internal_a_int }
26089   \tex_toks:D \l__seq_internal_a_int
26090     = \tex_toks:D \l__seq_internal_b_int
26091   \tex_toks:D \l__seq_internal_b_int
26092 }
26093 \__kernel_msg_new:nnnn { kernel } { shuffle-too-large }
26094 { The~sequence~#1~is~too~long~to~be~shuffled~by~TeX. }
26095 {
26096   TeX~has~ \int_eval:n { \c_max_register_int + 1 } ~
26097   toks~registers:~this~only~allows~to~shuffle~up~to~
26098   \int_use:N \c_max_register_int \ items.~
26099   The~list~will~not~be~shuffled.
26100 }
26101 }
26102 {
26103   \cs_new_protected:Npn \seq_shuffle:N #1
26104   {
26105     \__kernel_msg_error:nnn { kernel } { fp-no-random }
26106     { \seq_shuffle:N #1 }
26107   }
26108   \cs_new_eq:NN \seq_gshuffle:N \seq_shuffle:N
26109 }

```

(End definition for `\seq_shuffle:N` and others. These functions are documented on page 249.)

`\seq_indexed_map_function:NN` Similar to `\seq_map_function:NN` but we keep track of the item index as a ;-delimited argument of `__seq_indexed_map:Nw`.

`\seq_indexed_map_inline:Nn`

```

\__seq_indexed_map:nNN 26110 \cs_new:Npn \seq_indexed_map_function:NN #1#2
\__seq_indexed_map:Nw 26111 {
26112   \__seq_indexed_map:NN #1#2
26113   \prg_break_point:Nn \seq_map_break: { }
26114 }
26115 \cs_new_protected:Npn \seq_indexed_map_inline:Nn #1#2
26116 {
26117   \int_gincr:N \g__kernel_prg_map_int
26118   \cs_gset_protected:cpn
26119     { __seq_map_ \int_use:N \g__kernel_prg_map_int :w } ##1##2 {#2}
26120   \exp_args:NNc \__seq_indexed_map:NN #1
26121     { __seq_map_ \int_use:N \g__kernel_prg_map_int :w }
26122   \prg_break_point:Nn \seq_map_break:
26123     { \int_gdecr:N \g__kernel_prg_map_int }
26124 }
26125 \cs_new:Npn \__seq_indexed_map:NN #1#2
26126 {
26127   \exp_after:wN \__seq_indexed_map:Nw
26128   \exp_after:wN #2
26129   \int_value:w 1
26130   \exp_after:wN \use_i:nn
26131   \exp_after:wN ;
26132   #1

```

```

26133 \prg_break: \__seq_item:n { } \prg_break_point:
26134 }
26135 \cs_new:Npn \__seq_indexed_map:Nw #1#2 ; #3 \__seq_item:n #4
26136 {
26137     #3
26138     #1 {#2} {#4}
26139     \exp_after:wN \__seq_indexed_map:Nw
26140     \exp_after:wN #1
26141     \int_value:w \int_eval:w 1 + #2 ;
26142 }

```

(End definition for `\seq_indexed_map_function:NN` and others. These functions are documented on page 249.)

44.12 Additions to l3skip

26143 $\langle @@ = \text{dim} \rangle$

`\dim_sign:n` See `\dim_abs:n`. Contrarily to `\int_sign:n` the case of a zero dimension cannot be distinguished from a positive dimension by looking only at the first character, since `0.2pt` and `0pt` start the same way. We need explicit comparisons. We start by distinguishing the most common case of a positive dimension.

```

26144 \__kernel_patch_args:nNNpn
26145 { { \__kernel_chk_expr:nNnN {#1} \__dim_eval:w { } \dim_sign:n } }
26146 \cs_new:Npn \dim_sign:n #1
26147 {
26148     \int_value:w \exp_after:wN \__dim_sign:Nw
26149     \dim_use:N \__dim_eval:w #1 \__dim_eval_end: ;
26150     \exp_stop_f:
26151 }
26152 \cs_new:Npn \__dim_sign:Nw #1#2 ;
26153 {
26154     \if_dim:w #1#2 > \c_zero_dim
26155     1
26156     \else:
26157         \if_meaning:w - #1
26158         -1
26159         \else:
26160         0
26161         \fi:
26162     \fi:
26163 }

```

(End definition for `\dim_sign:n` and `__dim_sign:Nw`. This function is documented on page 249.)

26164 $\langle @@ = \text{skip} \rangle$

`\skip_split_finite_else_action:nnNN` This macro is useful when performing error checking in certain circumstances. If the $\langle \text{skip} \rangle$ register holds finite glue it sets #3 and #4 to the stretch and shrink component, resp. If it holds infinite glue set #3 and #4 to zero and issue the special action #2 which is probably an error message. Assignments are local.

```

26165 \cs_new:Npn \skip_split_finite_else_action:nnNN #1#2#3#4
26166 {
26167     \skip_if_finite:nTF {#1}
26168     {

```

```

26169         #3 = \tex_gluestretch:D #1 \scan_stop:
26170         #4 = \tex_glueshrink:D #1 \scan_stop:
26171     }
26172     {
26173         #3 = \c_zero_skip
26174         #4 = \c_zero_skip
26175         #2
26176     }
26177 }

```

(End definition for `\skip_split_finite_else_action:nmNN`. This function is documented on page 249.)

44.13 Additions to l3sys

```

26178 <@@=sys>

```

`\c_sys_engine_version_str` Various different engines, various different ways to extract the data!

```

26179 \str_const:Nx \c_sys_engine_version_str
26180 {
26181     \str_case:on \c_sys_engine_str
26182     {
26183         { pdftex }
26184         {
26185             \fp_eval:n { round(\int_use:N \tex_pdftexversion:D / 100 , 2) }
26186             .
26187             \tex_pdftexrevision:D
26188         }
26189         { ptex }
26190         {
26191             \cs_if_exist:NT \tex_ptexversion:D
26192             {
26193                 P
26194                 \int_use:N \tex_ptexversion:D
26195                 \int_use:N \tex_ptexminorversion:D
26196                 \tex_ptexrevision:D
26197                 -
26198                 \int_use:N \tex_epTeXversion:D
26199             }
26200         }
26201         { luatex }
26202         {
26203             \fp_eval:n { round(\int_use:N \tex_luatexversion:D / 100 , 2) }
26204             .
26205             \tex_luatexrevision:D
26206         }
26207         { uptex }
26208         {
26209             \cs_if_exist:NT \tex_ptexversion:D
26210             {
26211                 P
26212                 \int_use:N \tex_ptexversion:D
26213                 \int_use:N \tex_ptexminorversion:D
26214                 \tex_ptexrevision:D
26215                 -
26216                 u

```

```

26217         \int_use:N \tex_uptexversion:D
26218         \tex_uptexrevision:D
26219         -
26220         \int_use:N \tex_epTeXversion:D
26221     }
26222 }
26223 { xetex }
26224 {
26225     \int_use:N \tex_XeTeXversion:D
26226     \tex_XeTeXrevision:D
26227 }
26228 }
26229 }

```

(End definition for `\c_sys_engine_version_str`. This variable is documented on page 250.)

`\sys_rand_seed:` Unpack the primitive. When random numbers are not available, we return zero after an error (and incidentally make sure the number of expansions needed is the same as with random numbers available).

```

26230 \sys_if_rand_exist:TF
26231 { \cs_new:Npn \sys_rand_seed: { \tex_the:D \tex_randomseed:D } }
26232 {
26233     \cs_new:Npn \sys_rand_seed:
26234     {
26235         \int_value:w
26236         \__kernel_msg_expandable_error:nnn { kernel } { fp-no-random }
26237         { \sys_rand_seed: }
26238         \c_zero_int
26239     }
26240 }

```

(End definition for `\sys_rand_seed:.` This function is documented on page 250.)

`\sys_gset_rand_seed:n` The primitive always assigns the seed globally.

```

26241 \sys_if_rand_exist:TF
26242 {
26243     \cs_new_protected:Npn \sys_gset_rand_seed:n #1
26244     { \tex_setrandomseed:D \int_eval:n {#1} \exp_stop_f: }
26245 }
26246 {
26247     \cs_new_protected:Npn \sys_gset_rand_seed:n #1
26248     {
26249         \__kernel_msg_error:nnn { kernel } { fp-no-random }
26250         { \sys_gset_rand_seed:n {#1} }
26251     }
26252 }

```

(End definition for `\sys_gset_rand_seed:n`. This function is documented on page 250.)

`\c_sys_shell_escape_int` Expose the engine's shell escape status to the user.

```

26253 \int_const:Nn \c_sys_shell_escape_int
26254 {
26255     \sys_if_engine luatex:TF
26256     {
26257         \tex_directlua:D

```

```

26258         { tex.sprint(status.shell_escape~or~os.execute()) }
26259     }
26260     {
26261         \tex_shellescape:D
26262     }
26263 }

```

(End definition for `\c_sys_shell_escape_int`. This variable is documented on page 251.)

`\c_sys_platform_str` Detecting the platform on LuaTeX is easy: for other engines, we use the fact that the two common cases have special null files. It is possible to probe further (see package `platform`), but that requires shell escape and seems unlikely to be useful.

```

26264 \sys_if_engine luatex:TF
26265 {
26266     \str_const:Nx \c_sys_platform_str
26267     { \lua_now:n { tex.print(os.type) } }
26268 }
26269 {
26270     \file_if_exist:nTF { nul: }
26271     {
26272         \file_if_exist:nF { /dev/null }
26273         { \str_const:Nn \c_sys_platform_str { windows } }
26274     }
26275     {
26276         \file_if_exist:nT { /dev/null }
26277         { \str_const:Nn \c_sys_platform_str { unix } }
26278     }
26279 }
26280 \cs_if_exist:NF \c_sys_platform_str
26281 { \str_const:Nn \c_sys_platform_str { unknown } }

```

(End definition for `\c_sys_platform_str`. This variable is documented on page 250.)

`\sys_if_platform_unix_p` We can now set up the tests.

```

\sys_if_platform_unix:TF
\sys_if_platform_unix_p:
\sys_if_platform_windows_p:
\sys_if_platform_windows:TF
26282 \clist_map_inline:nn { unix , windows }
26283 {
26284     \__sys_const:nn { sys_if_platform_ #1 }
26285     { \str_if_eq_p:Vn \c_sys_platform_str { #1 } }
26286 }

```

(End definition for `\sys_if_platform_unix:TF` and `\sys_if_platform_windows:TF`. These functions are documented on page 250.)

`\sys_if_shell_p` Performs a check for whether shell escape is enabled. The first set of functions returns true if either of restricted or unrestricted shell escape is enabled, while the other two sets of functions return true in only one of these two cases.

```

\sys_if_shell:TF
\sys_if_shell_unrestricted_p:
\sys_if_shell_unrestricted:TF
\sys_if_shell_restricted_p:
\sys_if_shell_restricted:TF
26287 \__sys_const:nn { sys_if_shell }
26288 { \int_compare_p:nNn \c_sys_shell_escape_int > 0 }
26289 \__sys_const:nn { sys_if_shell_unrestricted }
26290 { \int_compare_p:nNn \c_sys_shell_escape_int = 1 }
26291 \__sys_const:nn { sys_if_shell_restricted }
26292 { \int_compare_p:nNn \c_sys_shell_escape_int = 2 }

```

(End definition for `\sys_if_shell:TF`, `\sys_if_shell_unrestricted:TF`, and `\sys_if_shell_restricted:TF`. These functions are documented on page 251.)

`\c__sys_shell_stream_int` This is not needed for LuaTeX: shell escape there isn't done using a TeX interface.

```
26293 \sys_if_engine luatex:F
26294 { \int_const:Nn \c__sys_shell_stream_int { 18 } }
```

(End definition for `\c__sys_shell_stream_int`.)

`\sys_shell_now:n` Execute commands through shell escape immediately.

```
26295 \sys_if_engine luatex:TF
26296 {
26297   \cs_new_protected:Npn \sys_shell_now:n #1
26298   {
26299     \lua_now:e
26300     { os.execute(" \lua_escape:e { \tl_to_str:n {#1} } ") }
26301   }
26302 }
26303 {
26304   \cs_new_protected:Npn \sys_shell_now:n #1
26305   { \iow_now:Nn \c__sys_shell_stream_int {#1} }
26306 }
26307 \cs_generate_variant:Nn \sys_shell_now:n { x }
```

(End definition for `\sys_shell_now:n`. This function is documented on page 251.)

`\sys_shell_shipout:n` Execute commands through shell escape at shipout.

```
26308 \sys_if_engine luatex:TF
26309 {
26310   \cs_new_protected:Npn \sys_shell_shipout:n #1
26311   {
26312     \lua_shipout_e:n
26313     { os.execute(" \lua_escape:e { \tl_to_str:n {#1} } ") }
26314   }
26315 }
26316 {
26317   \cs_new_protected:Npn \sys_shell_shipout:n #1
26318   { \iow_shipout:Nn \c__sys_shell_stream_int {#1} }
26319 }
26320 \cs_generate_variant:Nn \sys_shell_shipout:n { x }
```

(End definition for `\sys_shell_shipout:n`. This function is documented on page 251.)

44.14 Additions to l3tl

```
26321 <@@=tl>
```

`\tl_if_single_token_p:n` There are four cases: empty token list, token list starting with a normal token, with a brace group, or with a space token. If the token list starts with a normal token, remove it and check for emptiness. For the next case, an empty token list is not a single token. Finally, we have a non-empty token list starting with a space or a brace group. Applying f-expansion yields an empty result if and only if the token list is a single space.

`\tl_if_single_token:nTF`

```
26322 \prg_new_conditional:Npnn \tl_if_single_token:n #1 { p , T , F , TF }
26323 {
26324   \tl_if_head_is_N_type:nTF {#1}
26325   { \__tl_if_empty_if:o { \use_none:n #1 } }
26326   {
```

```

26327         \tl_if_empty:nTF {#1}
26328         { \if_false: }
26329         { \__tl_if_empty_if:o { \exp:w \exp_end_continue_f:w #1 } }
26330     }
26331     \prg_return_true:
26332 \else:
26333     \prg_return_false:
26334 \fi:
26335 }

```

(End definition for `\tl_if_single_token:nTF`. This function is documented on page 251.)

\tl_reverse_tokens:n The same as `\tl_reverse:n` but with recursion within brace groups.

```

\__tl_reverse_group:nn
26336 \cs_new:Npn \tl_reverse_tokens:n #1
26337 {
26338     \__kernel_exp_not:w \exp_after:wN
26339     {
26340         \exp:w
26341         \__tl_act:NNNnn
26342         \__tl_reverse_normal:nN
26343         \__tl_reverse_group:nn
26344         \__tl_reverse_space:n
26345         { }
26346         {#1}
26347     }
26348 }
26349 \cs_new:Npn \__tl_reverse_group:nn #1
26350 {
26351     \__tl_act_group_recurse:Nnn
26352     \__tl_act_reverse_output:n
26353     { \tl_reverse_tokens:n }
26354 }

```

`__tl_act_group_recurse:Nnn` In many applications of `__tl_act:NNNnn`, we need to recursively apply some transformation within brace groups, then output. In this code, `#1` is the output function, `#2` is the transformation, which should expand in two steps, and `#3` is the group.

```

26355 \cs_new:Npn \__tl_act_group_recurse:Nnn #1#2#3
26356 {
26357     \exp_args:Nf #1
26358     { \exp_after:wN \exp_after:wN \exp_after:wN { #2 {#3} } }
26359 }

```

(End definition for `\tl_reverse_tokens:n`, `__tl_reverse_group:nn`, and `__tl_act_group_recurse:Nnn`. This function is documented on page 252.)

\tl_count_tokens:n The token count is computed through an `\int_eval:n` construction. Each `1+` is output to the *left*, into the integer expression, and the sum is ended by the `\exp_end:` inserted by `__tl_act_end:wn` (which is technically implemented as `\c_zero_int`). Somewhat a hack!

```

26360 \cs_new:Npn \tl_count_tokens:n #1
26361 {
26362     \int_eval:n
26363     {
26364         \__tl_act:NNNnn

```

```

26365         \tl_act_count_normal:nN
26366         \tl_act_count_group:nn
26367         \tl_act_count_space:n
26368         { }
26369         {#1}
26370     }
26371 }
26372 \cs_new:Npn \tl_act_count_normal:nN #1 #2 { 1 + }
26373 \cs_new:Npn \tl_act_count_space:n #1 { 1 + }
26374 \cs_new:Npn \tl_act_count_group:nn #1 #2
26375     { 2 + \tl_count_tokens:n {#2} + }

```

(End definition for `\tl_count_tokens:n` and others. This function is documented on page 252.)

```

\tl_set_from_file:Nnn The approach here is similar to that for doing a rescan, and so the same internals can
\tl_set_from_file:cnn be reused. Thus the plan is to insert a pair of tokens of the same charcode but different
\tl_gset_from_file:Nnn catcodes after the file has been read. This plus \exp_not:N allows the primitive to be
\tl_gset_from_file:cnn used to carry out a set operation.
__tl_set_from_file:NNnn
  __tl_from_file_do:w
  __tl_set_from:nNNn
26376 \cs_new_protected:Npn \tl_set_from_file:Nnn
26377     { __tl_set_from_file:NNnn \tl_set:Nn }
26378 \cs_new_protected:Npn \tl_gset_from_file:Nnn
26379     { __tl_set_from_file:NNnn \tl_gset:Nn }
26380 \cs_generate_variant:Nn \tl_set_from_file:Nnn { c }
26381 \cs_generate_variant:Nn \tl_gset_from_file:Nnn { c }
26382 \cs_new_protected:Npn \tl_set_from_file:NNnn #1#2#3#4
26383     {
26384         \file_get_full_name:nN {#4} \l__tl_file_name_str
26385         \str_if_empty:NTF \l__tl_file_name_str
26386             { \kernel_file_missing:n {#4} }
26387             {
26388                 \exp_args:NV __tl_set_from:nNNn
26389                 \l__tl_file_name_str
26390                 #1 #2 {#3}
26391             }
26392     }
26393 \exp_args:Nno \use:nn
26394     { \cs_new_protected:Npn \tl_from_file_do:w #1 }
26395     { \c__tl_rescan_marker_tl }
26396     { \tl_set:No \l__tl_internal_a_tl {#1} }
26397 \cs_new_protected:Npn \tl_set_from:nNNn #1#2#3#4
26398     {
26399         \group_begin:
26400         \exp_args:No \tex_everyeof:D
26401         { \c__tl_rescan_marker_tl \exp_not:N }
26402         #4 \scan_stop:
26403         \exp_after:wN __tl_from_file_do:w
26404         \exp_after:wN \prg_do_nothing:
26405         \tex_input:D #1 \scan_stop:
26406         \exp_args:NNNo \group_end:
26407         #2 #3 \l__tl_internal_a_tl
26408     }

```

(End definition for `\tl_set_from_file:Nnn` and others. These functions are documented on page 255.)

`\tl_set_from_file_x:Nnn` When reading a file and allowing expansion of the content, the set up only needs to prevent TeX complaining about the end of the file. That is done simply, with a group then used to trap the definition needed. Once the business is done using some scratch space, the tokens can be transferred to the real target.

```

\__tl_set_from_file_x:NNnn
26409 \cs_new_protected:Npn \tl_set_from_file_x:Nnn
26410 { \__tl_set_from_file_x:NNnn \tl_set:Nn }
26411 \cs_new_protected:Npn \tl_gset_from_file_x:Nnn
26412 { \__tl_set_from_file_x:NNnn \tl_gset:Nn }
26413 \cs_generate_variant:Nn \tl_set_from_file_x:Nnn { c }
26414 \cs_generate_variant:Nn \tl_gset_from_file_x:Nnn { c }
26415 \cs_new_protected:Npn \__tl_set_from_file_x:NNnn #1#2#3#4
26416 {
26417   \file_get_full_name:nN {#4} \l__tl_file_name_str
26418   \str_if_empty:NTF \l__tl_file_name_str
26419     { \__kernel_file_missing:n {#4} }
26420   {
26421     \group_begin:
26422       \tex_everyeof:D { \exp_not:N }
26423       #3 \scan_stop:
26424       \tl_set:Nx \l__tl_internal_a_tl
26425         { \tex_input:D \l__tl_file_name_str \c_space_token }
26426       \exp_args:NNNo \group_end:
26427       #1 #2 \l__tl_internal_a_tl
26428     }
26429   }

```

(End definition for `\tl_set_from_file_x:Nnn`, `\tl_gset_from_file_x:Nnn`, and `__tl_set_from_file_x:NNnn`. These functions are documented on page 255.)

`\l__tl_file_name_str`

```

26430 \str_new:N \l__tl_file_name_str

```

(End definition for `\l__tl_file_name_str`.)

`\tl_set_from_shell:Nnn` Setting using a shell is at this level just a slightly specialised file operation.

```

\__tl_set_from_shell:NNnn
\__tl_set_from_shell:cnn
\__tl_gset_from_shell:Nnn
\__tl_set_from_shell:NNnn
26431 \cs_new_protected:Npn \tl_set_from_shell:Nnn
26432 { \__tl_set_from_shell:NNnn \tl_set:Nn }
26433 \cs_generate_variant:Nn \tl_set_from_shell:Nnn { c }
26434 \cs_new_protected:Npn \tl_gset_from_shell:Nnn
26435 { \__tl_set_from_shell:NNnn \tl_gset:Nn }
26436 \cs_generate_variant:Nn \tl_gset_from_shell:Nnn { c }
26437 \cs_new_protected:Npn \__tl_set_from_shell:NNnn #1#2#3#4
26438 {
26439   \sys_if_shell:TF
26440   {
26441     \tl_set:Nn \l__tl_internal_a_tl {#4}
26442     \tl_if_in:NnTF \l__tl_internal_a_tl { " }
26443     {
26444       \__kernel_msg_error:nxx
26445         { kernel } { quote-in-shell } {#4}
26446     }
26447     { \__tl_set_from:nNNn { | " #4 " } #1 #2 {#3} }
26448   }
26449   { #1 #2 { } }

```

```

26450 }
26451 \kernel_msg_new:nnnn { kernel } { quote-in-shell }
26452 { Quotes~in~shell~command~'#1'. }
26453 { Shell~commands~cannot~contain~quotes~("). }

```

(End definition for `\tl_set_from_shell:Nnn`, `\tl_gset_from_shell:Nnn`, and `_tl_set_from_shell:NNnn`. These functions are documented on page 255.)

44.14.1 Unicode case changing

The mechanisms needed for case changing are somewhat involved, particularly to allow for all of the special cases. These functions also require the appropriate data extracted from the Unicode documentation (either manually or automatically).

First, some code which “belongs” in `l3tokens` but has to come here.

```

26454 (@@=char)

```

```

\char_lower_case:N Expandable character generation is done using a two-part approach. First, see if the
\char_upper_case:N current character has a special mapping for the current transformation. If it does, insert
\char_mixed_case:N that. Otherwise, use the TEX data to look up the one-to-one mapping, and generate the
\char_fold_case:N appropriate character with the appropriate category code. Mixed case needs an extra step
\_char_change_case:nNN as it may be special-cased or might be a special upper case outcome. The internal when
\_char_change_case:nN using non-Unicode engines has to be set up to only do anything with ASCII characters.

```

```

26455 \cs_new:Npn \char_lower_case:N #1
26456 { \_char_change_case:nNN { lower } \char_value_lccode:n #1 }
26457 \cs_new:Npn \char_upper_case:N #1
26458 { \_char_change_case:nNN { upper } \char_value_uccode:n #1 }
26459 \cs_new:Npn \char_mixed_case:N #1
26460 {
26461   \tl_if_exist:cTF { c__char_mixed_case_ \token_to_str:N #1 _tl }
26462   { \tl_use:c { c__char_mixed_case_ \token_to_str:N #1 _tl } }
26463   { \char_upper_case:N #1 }
26464 }
26465 \cs_new:Npn \char_fold_case:N #1
26466 { \_char_change_case:nNN { fold } \char_value_lccode:n #1 }
26467 \cs_new:Npn \_char_change_case:nNN #1#2#3
26468 {
26469   \tl_if_exist:cTF { c__char_ #1 _case_ \token_to_str:N #3 _tl }
26470   { \tl_use:c { c__char_ #1 _case_ \token_to_str:N #3 _tl } }
26471   { \exp_args:Nf \_char_change_case:nN { #2 { '#3 } } #3 }
26472 }
26473 \cs_new:Npn \_char_change_case:nN #1#2
26474 {
26475   \int_compare:nNnTF {#1} = 0
26476   {#2}
26477   { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
26478 }
26479 \bool_lazy_or:nnF { \sys_if_engine luatex_p: } { \sys_if_engine xetex_p: }
26480 {
26481   \cs_set_eq:NN \_char_change_case:nN \use_ii:nn
26482 }

```

(End definition for `\char_lower_case:N` and others. These functions are documented on page 257.)

\char_codepoint_to_bytes:n

This code converts a codepoint into the correct UTF-8 representation. In terms of the algorithm itself, see <https://en.wikipedia.org/wiki/UTF-8> for the octet pattern.

```
\__char_codepoint_to_bytes_auxi:n
\__char_codepoint_to_bytes_auxii:Nnn
\__char_codepoint_to_bytes_auxiii:n
\__char_codepoint_to_bytes_outputi:nw
\__char_codepoint_to_bytes_outputii:nw
\__char_codepoint_to_bytes_outputiii:nw
\__char_codepoint_to_bytes_outputiv:nw
\__char_codepoint_to_bytes_output:nwn
\__char_codepoint_to_bytes_output:fnw
\__char_codepoint_to_bytes_end:

26483 \cs_new:Npn \char_codepoint_to_bytes:n #1
26484 {
26485   \exp_args:Nf \__char_codepoint_to_bytes_auxi:n
26486   { \int_eval:n {#1} }
26487 }
26488 \cs_new:Npn \__char_codepoint_to_bytes_auxi:n #1
26489 {
26490   \if_int_compare:w #1 > "80 \exp_stop_f:
26491   \if_int_compare:w #1 < "800 \exp_stop_f:
26492     \__char_codepoint_to_bytes_outputi:nw
26493     { \__char_codepoint_to_bytes_auxii:Nnn C {#1} { 64 } }
26494     \__char_codepoint_to_bytes_outputii:nw
26495     { \__char_codepoint_to_bytes_auxiii:n {#1} }
26496   \else:
26497     \if_int_compare:w #1 < "10000 \exp_stop_f:
26498     \__char_codepoint_to_bytes_outputi:nw
26499     { \__char_codepoint_to_bytes_auxii:Nnn E {#1} { 64 * 64 } }
26500     \__char_codepoint_to_bytes_outputii:nw
26501     {
26502       \__char_codepoint_to_bytes_auxiii:n
26503       { \int_div_truncate:nn {#1} { 64 } }
26504     }
26505     \__char_codepoint_to_bytes_outputiii:nw
26506     { \__char_codepoint_to_bytes_auxiii:n {#1} }
26507   \else:
26508     \__char_codepoint_to_bytes_outputi:nw
26509     {
26510       \__char_codepoint_to_bytes_auxii:Nnn F
26511       {#1} { 64 * 64 * 64 }
26512     }
26513     \__char_codepoint_to_bytes_outputii:nw
26514     {
26515       \__char_codepoint_to_bytes_auxiii:n
26516       { \int_div_truncate:nn {#1} { 64 * 64 } }
26517     }
26518     \__char_codepoint_to_bytes_outputiii:nw
26519     {
26520       \__char_codepoint_to_bytes_auxiii:n
26521       { \int_div_truncate:nn {#1} { 64 } }
26522     }
26523     \__char_codepoint_to_bytes_outputiv:nw
26524     { \__char_codepoint_to_bytes_auxiii:n {#1} }
26525   \fi:
26526   \fi:
26527   \else:
26528     \__char_codepoint_to_bytes_outputi:nw {#1}
26529   \fi:
26530   \__char_codepoint_to_bytes_end: { } { } { } { } { }
26531 }
26532 \cs_new:Npn \__char_codepoint_to_bytes_auxii:Nnn #1#2#3
26533 { "#10 + \int_div_truncate:nn {#2} {#3} }
26534 \cs_new:Npn \__char_codepoint_to_bytes_auxiii:n #1
```

```

26535 { \int_mod:nn {#1} { 64 } + 128 }
26536 \cs_new:Npn \__char_codepoint_to_bytes_outputi:nw
26537 #1 #2 \__char_codepoint_to_bytes_end: #3
26538 { \__char_codepoint_to_bytes_output:fnn { \int_eval:n {#1} } { } {#2} }
26539 \cs_new:Npn \__char_codepoint_to_bytes_outputii:nw
26540 #1 #2 \__char_codepoint_to_bytes_end: #3#4
26541 { \__char_codepoint_to_bytes_output:fnn { \int_eval:n {#1} } { {#3} } {#2} }
26542 \cs_new:Npn \__char_codepoint_to_bytes_outputiii:nw
26543 #1 #2 \__char_codepoint_to_bytes_end: #3#4#5
26544 {
26545   \__char_codepoint_to_bytes_output:fnn
26546   { \int_eval:n {#1} } { {#3} {#4} } {#2}
26547 }
26548 \cs_new:Npn \__char_codepoint_to_bytes_outputiv:nw
26549 #1 #2 \__char_codepoint_to_bytes_end: #3#4#5#6
26550 {
26551   \__char_codepoint_to_bytes_output:fnn
26552   { \int_eval:n {#1} } { {#3} {#4} {#5} } {#2}
26553 }
26554 \cs_new:Npn \__char_codepoint_to_bytes_output:nnn #1#2#3
26555 {
26556   #3
26557   \__char_codepoint_to_bytes_end: #2 {#1}
26558 }
26559 \cs_generate_variant:Nn \__char_codepoint_to_bytes_output:nnn { f }
26560 \cs_new:Npn \__char_codepoint_to_bytes_end: { }

```

(End definition for `\char_codepoint_to_bytes:n` and others. This function is documented on page 257.)

```

26561 <@@=tl>

```

`\tl_if_head_eq_catcode:oNTF` Extra variants.

```

26562 \cs_generate_variant:Nn \tl_if_head_eq_catcode:nNTF { o }

```

(End definition for `\tl_if_head_eq_catcode:nNTF`. This function is documented on page 46.)

`\tl_lower_case:n` `\tl_upper_case:n` `\tl_mixed_case:n` The user level functions here are all wrappers around the internal functions for case changing.

```

26563 \cs_new:Npn \tl_lower_case:n { \__tl_change_case:nnn { lower } { } }
26564 \cs_new:Npn \tl_upper_case:n { \__tl_change_case:nnn { upper } { } }
26565 \cs_new:Npn \tl_mixed_case:n { \__tl_change_case:nnn { mixed } { } }
26566 \cs_new:Npn \tl_lower_case:nn { \__tl_change_case:nnn { lower } }
26567 \cs_new:Npn \tl_upper_case:nn { \__tl_change_case:nnn { upper } }
26568 \cs_new:Npn \tl_mixed_case:nn { \__tl_change_case:nnn { mixed } }

```

(End definition for `\tl_lower_case:n` and others. These functions are documented on page 252.)

The mechanism for the core conversion of case is based on the idea that we can use a loop to grab the entire token list plus a quark: the latter is used as an end marker and to avoid any brace stripping. Depending on the nature of the first item in the grabbed argument, it can either processed as a single token, treated as a group or treated as a space. These different cases all work by re-reading #1 in the appropriate way, hence the repetition of #1 `\q_recursion_stop`.

```

26569 \cs_new:Npn \__tl_change_case:nnn #1#2#3

```

```

\__tl_change_case:nnn
\__tl_change_case_aux:nnn
\__tl_change_case_loop:wnn
\__tl_change_case_output:nwn
\__tl_change_case_output:Vwn
\__tl_change_case_output:own
\__tl_change_case_output:vwn
\__tl_change_case_output:fwon
\__tl_change_case_end:wn
\__tl_change_case_group:nwnn
\__tl_change_case_group_lower:nnnn
\__tl_change_case_group_upper:nnnn
\__tl_change_case_group_mixed:nnnn
\__tl_change_case_space:wnn
\__tl_change_case_N_type:Nwnn
\__tl_change_case_N_type:NNNnnn
\__tl_change_case_math:NNNnnn

```

```

26570 {
26571   \__kernel_exp_not:w \exp_after:wN
26572   {
26573     \exp:w
26574     \__tl_change_case_aux:nnn {#1} {#2} {#3}
26575   }
26576 }
26577 \cs_new:Npn \__tl_change_case_aux:nnn #1#2#3
26578 {
26579   \group_align_safe_begin:
26580   \__tl_change_case_loop:wnn
26581   #3 \q_recursion_tail \q_recursion_stop {#1} {#2}
26582   \__tl_change_case_result:n { }
26583 }
26584 \cs_new:Npn \__tl_change_case_loop:wnn #1 \q_recursion_stop
26585 {
26586   \tl_if_head_is_N_type:nTF {#1}
26587   { \__tl_change_case_N_type:Nwnn }
26588   {
26589     \tl_if_head_is_group:nTF {#1}
26590     { \__tl_change_case_group:nwnn }
26591     { \__tl_change_case_space:wnn }
26592   }
26593   #1 \q_recursion_stop
26594 }

```

Earlier versions of the code where only x-type expandable rather than f-type: this causes issues with nesting and so the slight performance hit is taken for a better outcome in usability terms. Setting up for f-type expandability has two requirements: a marker token after the main loop (see above) and a mechanism to “load” and finalise the result. That is handled in the code below, which includes the necessary material to end the `\exp:w` expansion.

```

26595 \cs_new:Npn \__tl_change_case_output:nwn #1#2 \__tl_change_case_result:n #3
26596 { #2 \__tl_change_case_result:n { #3 #1 } }
26597 \cs_generate_variant:Nn \__tl_change_case_output:nwn { V , o , v , f }
26598 \cs_new:Npn \__tl_change_case_end:wn #1 \__tl_change_case_result:n #2
26599 {
26600   \group_align_safe_end:
26601   \exp_end:
26602   #2
26603 }

```

Handling for the cases where the current argument is a brace group or a space is relatively easy. For the brace case, the routine works recursively, using the expandability of the mechanism to ensure that the result is finalised before storage. For the space case it is simply a question of removing the space in the input and storing it in the output. In both cases, and indeed for the N-type grabber, after removing the current item from the input `__tl_change_case_loop:wnn` is inserted in front of the remaining tokens.

```

26604 \cs_new:Npn \__tl_change_case_group:nwnn #1#2 \q_recursion_stop #3#4
26605 {
26606   \use:c { \__tl_change_case_group_ #3 : nnnn } {#1} {#2} {#3} {#4}
26607 }
26608 \cs_new:Npn \__tl_change_case_group_lower:nnnn #1#2#3#4
26609 {

```



```

26610 \_tl_change_case_output:own
26611 {
26612   \exp_after:wN
26613   {
26614     \exp:w
26615     \_tl_change_case_aux:nnn {#3} {#4} {#1}
26616   }
26617 }
26618 \_tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
26619 }
26620 \cs_new_eq:NN \_tl_change_case_group_upper:nnnn
26621 \_tl_change_case_group_lower:nnnn

```

For the “mixed” case, a group is taken as forcing a switch to lower casing. That means we need a separate auxiliary. (Tracking whether we have found a first character inside a group and transferring the information out looks pretty horrible.)

```

26622 \cs_new:Npn \_tl_change_case_group_mixed:nnnn #1#2#3#4
26623 {
26624   \_tl_change_case_output:own
26625   {
26626     \exp_after:wN
26627     {
26628       \exp:w
26629       \_tl_change_case_aux:nnn {#3} {#4} {#1}
26630     }
26631   }
26632   \_tl_change_case_loop:wnn #2 \q_recursion_stop { lower } {#4}
26633 }
26634 \exp_last_unbraced:NNo \cs_new:Npn \_tl_change_case_space:wnn \c_space_tl
26635 {
26636   \_tl_change_case_output:nwn { ~ }
26637   \_tl_change_case_loop:wnn
26638 }

```

For N-type arguments there are several stages to the approach. First, a simply check for the end-of-input marker, which if found triggers the final clean up and output step. Assuming that is not the case, the first check is for math-mode escaping: this test can encompass control sequences or other N-type tokens so is handled up front.

```

26639 \cs_new:Npn \_tl_change_case_N_type:Nwnn #1#2 \q_recursion_stop
26640 {
26641   \quark_if_recursion_tail_stop_do:Nn #1
26642   { \_tl_change_case_end:wN }
26643   \exp_after:wN \_tl_change_case_N_type:NNNnnn
26644   \exp_after:wN #1 \l_tl_case_change_math_tl
26645   \q_recursion_tail ? \q_recursion_stop {#2}
26646 }

```

Looking for math mode escape first requires a loop over the possible token pairs to see if the current input (#1) matches an open-math case (#2). If it does then this test loop is ended and a new input-gathering one is begun. The latter simply transfers material from the input to the output without any expansion, testing each N-type token to see if it matches the close-math case required. If that is the situation then the “math loop” stops and resumes the main loop: as that might be either the standard case-changing one or the mixed-case alternative, it is not hard-coded into the math loop but is rather passed

as argument #3 to `__tl_change_case_math:NNNnnn`. If no close-math token is found then the final clean-up is forced (*i.e.* there is no assumption of “well-behaved” input in terms of math mode).

```

26647 \cs_new:Npn \__tl_change_case_N_type:NNNnnn #1#2#3
26648 {
26649   \quark_if_recursion_tail_stop_do:Nn #2
26650   { \__tl_change_case_N_type:Nnnn #1 }
26651   \token_if_eq_meaning:NNTF #1 #2
26652   {
26653     \use_i_delimit_by_q_recursion_stop:nw
26654     {
26655       \__tl_change_case_math:NNNnnn
26656       #1 #3 \__tl_change_case_loop:wnn
26657     }
26658   }
26659   { \__tl_change_case_N_type:NNNnnn #1 }
26660 }
26661 \cs_new:Npn \__tl_change_case_math:NNNnnn #1#2#3#4
26662 {
26663   \__tl_change_case_output:nwn {#1}
26664   \__tl_change_case_math_loop:wNNnn #4 \q_recursion_stop #2 #3
26665 }
26666 \cs_new:Npn \__tl_change_case_math_loop:wNNnn #1 \q_recursion_stop
26667 {
26668   \tl_if_head_is_N_type:nTF {#1}
26669   { \__tl_change_case_math:NwNNnn }
26670   {
26671     \tl_if_head_is_group:nTF {#1}
26672     { \__tl_change_case_math_group:nwNNnn }
26673     { \__tl_change_case_math_space:wNNnn }
26674   }
26675   #1 \q_recursion_stop
26676 }
26677 \cs_new:Npn \__tl_change_case_math:NwNNnn #1#2 \q_recursion_stop #3#4
26678 {
26679   \token_if_eq_meaning:NNTF \q_recursion_tail #1
26680   { \__tl_change_case_end:wn }
26681   {
26682     \__tl_change_case_output:nwn {#1}
26683     \token_if_eq_meaning:NNTF #1 #3
26684     { #4 #2 \q_recursion_stop }
26685     { \__tl_change_case_math_loop:wNNnn #2 \q_recursion_stop #3#4 }
26686   }
26687 }
26688 \cs_new:Npn \__tl_change_case_math_group:nwNNnn #1#2 \q_recursion_stop
26689 {
26690   \__tl_change_case_output:nwn { {#1} }
26691   \__tl_change_case_math_loop:wNNnn #2 \q_recursion_stop
26692 }
26693 \exp_last_unbraced:NNo
26694 \cs_new:Npn \__tl_change_case_math_space:wNNnn \c_space_tl
26695 {
26696   \__tl_change_case_output:nwn { ~ }
26697   \__tl_change_case_math_loop:wNNnn

```

```
26698 }
```

Once potential math-mode cases are filtered out the next stage is to test if the token grabbed is a control sequence: they cannot be used in the lookup table and also may require expansion. At this stage the loop code starting `__tl_change_case_loop:wnn` is inserted: all subsequent steps in the code which need a look-ahead are coded to rely on this and thus have w-type arguments if they may do a look-ahead.

```
26699 \cs_new:Npn \__tl_change_case_N_type:Nnnn #1#2#3#4
26700 {
26701   \token_if_cs:NTF #1
26702   { \__tl_change_case_cs_letterlike:Nn #1 {#3} }
26703   { \use:c { \__tl_change_case_char_ #3 :Nnn } #1 {#3} {#4} }
26704   \__tl_change_case_loop:wnn #2 \q_recursion_stop {#3} {#4}
26705 }
```

For character tokens there are some special cases to deal with then the majority of changes are covered by using the T_EX data as a lookup along with expandable character generation. This avoids needing a very large number of macros or (as seen in earlier versions) a somewhat tricky split of the characters into various blocks. Notice that the special case code may do a look-ahead so requires a final w-type argument whereas the core lookup table does not and also guarantees an output so f-type expansion may be used to obtain the case-changed result.

```
26706 \cs_new:Npn \__tl_change_case_char_lower:Nnn #1#2#3
26707 {
26708   \cs_if_exist_use:cF { \__tl_change_case_ #2 _ #3 :Nnw }
26709   { \use_ii:nn }
26710   #1
26711   {
26712     \use:c { \__tl_change_case_ #2 _ sigma:Nnw } #1
26713     { \__tl_change_case_char:nN {#2} #1 }
26714   }
26715 }
26716 \cs_new_eq:NN \__tl_change_case_char_upper:Nnn
26717 \__tl_change_case_char_lower:Nnn
```

For mixed case, the code is somewhat different: there is a need to look up both mixed and upper case chars and we have to cover the situation where there is a character to skip over.

```
26718 \cs_new:Npn \__tl_change_case_char_mixed:Nnn #1#2#3
26719 {
26720   \__tl_change_case_mixed_switch:w
26721   \cs_if_exist_use:cF { \__tl_change_case_mixed_ #3 :Nnw }
26722   {
26723     \cs_if_exist_use:cF { \__tl_change_case_upper_ #3 :Nnw }
26724     { \use_ii:nn }
26725   }
26726   #1
26727   { \__tl_change_case_mixed_skip:N #1 }
26728 }
```

For Unicode engines we can handle all characters directly. However, for the 8-bit engines the aim is to deal with (a subset of) Unicode (UTF-8) input. They deal with that by making the upper half of the range active, so we look for that and if found work out how many UTF-8 octets there are to deal with. Those can then be grabbed to reconstruct the

full Unicode character, which is then used in a lookup. (As will become obvious below, there is no intention here of covering all of Unicode.)

```

26729 \bool_lazy_or:nnTF
26730 { \sys_if_engine luatex_p: }
26731 { \sys_if_engine xetex_p: }
26732 {
26733   \cs_new:Npn \__tl_change_case_char:nN #1#2
26734   {
26735     \__tl_change_case_output:fwn
26736     { \use:c { char_ #1 _case:N } #2 }
26737   }
26738 }
26739 {
26740   \cs_new:Npn \__tl_change_case_char:nN #1#2
26741   {
26742     \int_compare:nNnTF { '#2 } > { "80 }
26743     {
26744       \int_compare:nNnTF { '#2 } < { "EO }
26745       { \__tl_change_case_char_UTFviii:nNNN {#1} #2 }
26746       {
26747         \int_compare:nNnTF { '#2 } < { "FO }
26748         { \__tl_change_case_char_UTFviii:nNNNN {#1} #2 }
26749         { \__tl_change_case_char_UTFviii:nNNNNN {#1} #2 }
26750       }
26751     }
26752     {
26753       \__tl_change_case_output:fwn
26754       { \use:c { char_ #1 _case:N } #2 }
26755     }
26756   }
26757 }

```

To allow for the special case of mixed case, we insert here a action-dependent auxiliary.

```

26758 \bool_lazy_or:nnF
26759 { \sys_if_engine luatex_p: }
26760 { \sys_if_engine xetex_p: }
26761 {
26762   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNN #1#2#3#4
26763   { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4} #3 }
26764   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNN #1#2#3#4#5
26765   { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5} #3 }
26766   \cs_new:Npn \__tl_change_case_char_UTFviii:nNNNNN #1#2#3#4#5#6
26767   { \__tl_change_case_char_UTFviii:nnN {#1} {#2#4#5#6} #3 }
26768   \cs_new:Npn \__tl_change_case_char_UTFviii:nnN #1#2#3
26769   {
26770     \cs_if_exist:cTF { c__tl_ #1 _case_ \tl_to_str:n {#2} _tl }
26771     {
26772       \__tl_change_case_output:vnw
26773       { c__tl_ #1 _case_ \tl_to_str:n {#2} _tl }
26774     }
26775     { \__tl_change_case_output:nwn {#2} }
26776     #3
26777   }
26778 }

```

Before dealing with general control sequences there are the special ones to deal with. Letter-like control sequences are a simple look-up, while for accents the loop is much as done elsewhere. Notice that we have a no-op test to make sure there is no unexpected expansion of letter-like input. The split into two parts here allows us to insert the “switch” code for mixed casing.

```

26779 \cs_new:Npn \__tl_change_case_cs_letterlike:Nn #1#2
26780 {
26781   \str_if_eq:nnTF {#2} { mixed }
26782   {
26783     \__tl_change_case_cs_letterlike:NnN #1 { upper }
26784     \__tl_change_case_mixed_switch:w
26785   }
26786   { \__tl_change_case_cs_letterlike:NnN #1 {#2} \prg_do_nothing: }
26787 }
26788 \cs_new:Npn \__tl_change_case_cs_letterlike:NnN #1#2#3
26789 {
26790   \cs_if_exist:cTF { c__tl_change_case_ #2 _ \token_to_str:N #1 _tl }
26791   {
26792     \__tl_change_case_output:vwN
26793     { c__tl_change_case_ #2 _ \token_to_str:N #1 _tl }
26794     #3
26795   }
26796   {
26797     \cs_if_exist:cTF
26798     {
26799       c__tl_change_case_
26800       \str_if_eq:nnTF {#2} { lower } { upper } { lower }
26801       _ \token_to_str:N #1 _tl
26802     }
26803     {
26804       \__tl_change_case_output:nwn {#1}
26805       #3
26806     }
26807     {
26808       \exp_after:wN \__tl_change_case_cs_accents:NN
26809       \exp_after:wN #1 \l_tl_change_case_accents_tl
26810       \q_recursion_tail \q_recursion_stop
26811     }
26812   }
26813 }
26814 \cs_new:Npn \__tl_change_case_cs_accents:NN #1#2
26815 {
26816   \quark_if_recursion_tail_stop_do:Nn #2
26817   { \__tl_change_case_cs:N #1 }
26818   \str_if_eq:nnTF {#1} {#2}
26819   {
26820     \use_i_delimit_by_q_recursion_stop:nw
26821     { \__tl_change_case_output:nwn {#1} }
26822   }
26823   { \__tl_change_case_cs_accents:NN #1 }
26824 }

```

To deal with a control sequence there is first a need to test if it is on the list which indicate that case changing should be skipped. That’s done using a loop as for the other

special cases. If a hit is found then the argument is grabbed: that comes *after* the loop function which is therefore rearranged. In a L^AT_EX 2_ε context, `\protect` needs to be treated specially, to prevent expansion of the next token but output it without braces.

```

26825 \cs_new:Npn \__tl_change_case_cs:N #1
26826 {
26827   (*package)
26828   \str_if_eq:nnTF {#1} { \protect } { \__tl_change_case_protect:wNN }
26829   (/package)
26830   \exp_after:wN \__tl_change_case_cs:NN
26831   \exp_after:wN #1 \l_tl_case_change_exclude_tl
26832   \q_recursion_tail \q_recursion_stop
26833 }
26834 \cs_new:Npn \__tl_change_case_cs:NN #1#2
26835 {
26836   \quark_if_recursion_tail_stop_do:Nn #2
26837   {
26838     \__tl_change_case_cs_expand:Nnw #1
26839     { \__tl_change_case_output:nwn {#1} }
26840   }
26841   \str_if_eq:nnTF {#1} {#2}
26842   {
26843     \use_i_delimit_by_q_recursion_stop:nw
26844     { \__tl_change_case_cs:NNn #1 }
26845   }
26846   { \__tl_change_case_cs:NN #1 }
26847 }
26848 \cs_new:Npn \__tl_change_case_cs:NNn #1#2#3
26849 {
26850   \__tl_change_case_output:nwn { #1 {#3} }
26851   #2
26852 }
26853 (*package)
26854 \cs_new:Npn \__tl_change_case_protect:wNN #1 \q_recursion_stop #2 #3
26855 { \__tl_change_case_output:nwn { \protect #3 } #2 }
26856 (/package)

```

When a control sequence is not on the exclude list the other test if to see if it is expandable. Once again, if there is a hit then the loop function is grabbed as part of the clean-up and reinserted before the now expanded material. The test for expandability has to check for end-of-recursion as it is needed by the look-ahead code which might hit the end of the input. The test is done in two parts as `\bool_if:nTF` would choke if #1 was (!

```

26857 \cs_new:Npn \__tl_change_case_if_expandable:NTF #1
26858 {
26859   \token_if_expandable:NTF #1
26860   {
26861     \bool_lazy_any:nTF
26862     {
26863       { \token_if_eq_meaning_p:NN \q_recursion_tail #1 }
26864       { \token_if_protected_macro_p:N #1 }
26865       { \token_if_protected_long_macro_p:N #1 }
26866     }
26867     { \use_ii:nn }
26868     { \use_i:nn }
26869   }

```

```

26870     { \use_ii:nn }
26871   }
26872 \cs_new:Npn \__tl_change_case_cs_expand:Nnw #1#2
26873 {
26874   \__tl_change_case_if_expandable:NTF #1
26875   { \__tl_change_case_cs_expand:NN #1 }
26876   { #2 }
26877 }
26878 \cs_new:Npn \__tl_change_case_cs_expand:NN #1#2
26879 { \exp_after:wN #2 #1 }

```

For mixed case, there is an additional list of exceptions to deal with: once that is sorted, we can move on back to the main loop.

```

26880 \cs_new:Npn \__tl_change_case_mixed_skip:N #1
26881 {
26882   \exp_after:wN \__tl_change_case_mixed_skip:NN
26883   \exp_after:wN #1 \l_tl_mixed_case_ignore_tl
26884   \q_recursion_tail \q_recursion_stop
26885 }
26886 \cs_new:Npn \__tl_change_case_mixed_skip:NN #1#2
26887 {
26888   \quark_if_recursion_tail_stop_do:nn {#2}
26889   { \__tl_change_case_char:nN { mixed } #1 }
26890   \int_compare:nNnT { '#1 } = { '#2 }
26891   {
26892     \use_i_delimit_by_q_recursion_stop:nw
26893     {
26894       \__tl_change_case_output:nwn {#1}
26895       \__tl_change_case_mixed_skip_tidy:Nwn
26896     }
26897   }
26898   \__tl_change_case_mixed_skip:NN #1
26899 }
26900 \cs_new:Npn \__tl_change_case_mixed_skip_tidy:Nwn #1#2 \q_recursion_stop #3
26901 {
26902   \__tl_change_case_loop:wnn #2 \q_recursion_stop { mixed }
26903 }

```

Needed to switch from mixed to lower casing when we have found a first character in the former mode.

```

26904 \cs_new:Npn \__tl_change_case_mixed_switch:w
26905   #1 \__tl_change_case_loop:wnn #2 \q_recursion_stop #3
26906 {
26907   #1
26908   \__tl_change_case_loop:wnn #2 \q_recursion_stop { lower }
26909 }

```

(End definition for __tl_change_case:nnn and others.)

```

\__tl_change_case_lower_sigma:Nnw If the current char is an upper case sigma, then a check is made on the next item in the
\__tl_change_case_lower_sigma:w input. If it is N-type and not a control sequence then there is a look-ahead phase.
\__tl_change_case_lower_sigma:Nw
\__tl_change_case_upper_sigma:Nnw
26910 \cs_new:Npn \__tl_change_case_lower_sigma:Nnw #1#2#3#4 \q_recursion_stop
26911 {
26912   \int_compare:nNnTF { '#1 } = { "03A3 }
26913   {

```

```

26914         \_tl_change_case_output:fwn
26915         { \_tl_change_case_lower_sigma:w #4 \q_recursion_stop }
26916     }
26917     {#2}
26918     #3 #4 \q_recursion_stop
26919 }
26920 \cs_new:Npn \_tl_change_case_lower_sigma:w #1 \q_recursion_stop
26921 {
26922     \tl_if_head_is_N_type:nTF {#1}
26923     { \_tl_change_case_lower_sigma:Nw #1 \q_recursion_stop }
26924     { \c_tl_final_sigma_tl }
26925 }
26926 \cs_new:Npn \_tl_change_case_lower_sigma:Nw #1#2 \q_recursion_stop
26927 {
26928     \_tl_change_case_if_expandable:NTF #1
26929     {
26930         \exp_after:wN \_tl_change_case_lower_sigma:w #1
26931         #2 \q_recursion_stop
26932     }
26933     {
26934         \token_if_letter:NTF #1
26935         { \c_tl_std_sigma_tl }
26936         { \c_tl_final_sigma_tl }
26937     }
26938 }

```

Simply skip to the final step for upper casing.

```

26939 \cs_new_eq:NN \_tl_change_case_upper_sigma:Nnw \use_ii:nn

```

(End definition for _tl_change_case_lower_sigma:Nnw and others.)

```

\_tl_change_case_lower_tr:Nnw
\_tl_change_case_lower_tr_auxi:Nw
\_tl_change_case_lower_tr_auxii:Nw
\_tl_change_case_upper_tr:Nnw
\_tl_change_case_lower_az:Nnw
\_tl_change_case_upper_az:Nnw

```

The Turkic languages need special treatment for dotted-i and dotless-i. The lower casing rule can be expressed in terms of searching first for either a dotless-I or a dotted-I. In the latter case the mapping is easy, but in the former there is a second stage search.

```

26940 \bool_lazy_or:nnTF
26941 { \sys_if_engine luatex_p: }
26942 { \sys_if_engine xetex_p: }
26943 {
26944     \cs_new:Npn \_tl_change_case_lower_tr:Nnw #1#2
26945     {
26946         \int_compare:nNnTF { '#1 } = { "0049 }
26947         { \_tl_change_case_lower_tr_auxi:Nw }
26948         {
26949             \int_compare:nNnTF { '#1 } = { "0130 }
26950             { \_tl_change_case_output:nwn { i } }
26951             {#2}
26952         }
26953     }

```

After a dotless-I there may be a dot-above character. If there is then a dotted-i should be produced, otherwise output a dotless-i. When the combination is found both the dotless-I and the dot-above char have to be removed from the input, which is done by the `\use_i:nn` (it grabs `_tl_change_case_loop:wn` and the dot-above char and discards the latter).


```

26954 \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2 \q_recursion_stop
26955 {
26956   \tl_if_head_is_N_type:nTF {#2}
26957   { \__tl_change_case_lower_tr_auxii:Nw #2 \q_recursion_stop }
26958   { \__tl_change_case_output:Vwn \c__tl_dotless_i_tl }
26959   #1 #2 \q_recursion_stop
26960 }
26961 \cs_new:Npn \__tl_change_case_lower_tr_auxii:Nw #1#2 \q_recursion_stop
26962 {
26963   \__tl_change_case_if_expandable:NTF #1
26964   {
26965     \exp_after:wN \__tl_change_case_lower_tr_auxi:Nw #1
26966     #2 \q_recursion_stop
26967   }
26968   {
26969     \bool_lazy_or:nnTF
26970     { \token_if_cs_p:N #1 }
26971     { ! \int_compare_p:nNn { '#1 } = { "0307 } }
26972     { \__tl_change_case_output:Vwn \c__tl_dotless_i_tl }
26973     {
26974       \__tl_change_case_output:nwn { i }
26975       \use_i:nn
26976     }
26977   }
26978 }
26979 }

```

For 8-bit engines, dot-above is not available so there is a simple test for an upper-case I. Then we can look for the UTF-8 representation of an upper case dotted-I without the combining char. If it's not there, preserve the UTF-8 sequence as-is.

```

26980 {
26981   \cs_new:Npn \__tl_change_case_lower_tr:Nnw #1#2
26982   {
26983     \int_compare:nNnTF { '#1 } = { "0049 }
26984     { \__tl_change_case_output:Vwn \c__tl_dotless_i_tl }
26985     {
26986       \int_compare:nNnTF { '#1 } = { 196 }
26987       { \__tl_change_case_lower_tr_auxi:Nw #1 {#2} }
26988       {#2}
26989     }
26990   }
26991   \cs_new:Npn \__tl_change_case_lower_tr_auxi:Nw #1#2#3#4
26992   {
26993     \int_compare:nNnTF { '#4 } = { 176 }
26994     {
26995       \__tl_change_case_output:nwn { i }
26996       #3
26997     }
26998     {
26999       #2
27000       #3 #4
27001     }
27002   }
27003 }

```

Upper casing is easier: just one exception with no context.

```

27004 \cs_new:Npn \__tl_change_case_upper_tr:Nnw #1#2
27005 {
27006     \int_compare:nNnTF { '#1 } = { "0069 }
27007     { \__tl_change_case_output:Vwn \c__tl_dotted_I_tl }
27008     {#2}
27009 }

```

Straight copies.

```

27010 \cs_new_eq:NN \__tl_change_case_lower_az:Nnw \__tl_change_case_lower_tr:Nnw
27011 \cs_new_eq:NN \__tl_change_case_upper_az:Nnw \__tl_change_case_upper_tr:Nnw

```

(End definition for __tl_change_case_lower_tr:Nnw and others.)

__tl_change_case_lower_lt:Nnw For Lithuanian, the issue to be dealt with is dots over lower case letters: these should be present if there is another accent. That means that there is some work to do when lower casing I and J. The first step is a simple match attempt: \c__tl_accents_lt_tl contains accented upper case letters which should gain a dot-above char in their lower case form. This is done using f-type expansion so only one pass is needed to find if it works or not. If there was no hit, the second stage is to check for I, J and I-ogonek, and if the current char is a match to look for a following accent.

```

\__tl_change_case_lower_lt:Nnw
\__tl_change_case_lower_lt:nNnw
\__tl_change_case_lower_lt:nnw
\__tl_change_case_lower_lt:Nw
\__tl_change_case_lower_lt:Nnw
\__tl_change_case_upper_lt:Nnw
\__tl_change_case_upper_lt:nnw
\__tl_change_case_upper_lt:Nw
\__tl_change_case_upper_lt:Nnw
27012 \cs_new:Npn \__tl_change_case_lower_lt:Nnw #1
27013 {
27014     \exp_args:Nf \__tl_change_case_lower_lt:nNnw
27015     { \str_case:nVF #1 \c__tl_accents_lt_tl \exp_stop_f: }
27016     #1
27017 }
27018 \cs_new:Npn \__tl_change_case_lower_lt:nNnw #1#2
27019 {
27020     \tl_if_blank:nTF {#1}
27021     {
27022         \exp_args:Nf \__tl_change_case_lower_lt:nnw
27023         {
27024             \int_case:nnF { '#2 }
27025             {
27026                 { "0049 } i
27027                 { "004A } j
27028                 { "012E } \c__tl_i_ogonek_tl
27029             }
27030             \exp_stop_f:
27031         }
27032     }
27033     {
27034         \__tl_change_case_output:nwn {#1}
27035         \use_none:n
27036     }
27037 }
27038 \cs_new:Npn \__tl_change_case_lower_lt:nnw #1#2
27039 {
27040     \tl_if_blank:nTF {#1}
27041     {#2}
27042     {
27043         \__tl_change_case_output:nwn {#1}
27044         \__tl_change_case_lower_lt:Nw

```

```

27045     }
27046 }

```

Grab the next char and see if it is one of the accents used in Lithuanian: if it is, add the dot-above char into the output.

```

27047 \cs_new:Npn \__tl_change_case_lower_lt:Nw #1#2 \q_recursion_stop
27048 {
27049     \tl_if_head_is_N_type:nT {#2}
27050     { \__tl_change_case_lower_lt:NNw }
27051     #1 #2 \q_recursion_stop
27052 }
27053 \cs_new:Npn \__tl_change_case_lower_lt:NNw #1#2#3 \q_recursion_stop
27054 {
27055     \__tl_change_case_if_expandable:NTF #2
27056     {
27057         \exp_after:wN \__tl_change_case_lower_lt:Nw \exp_after:wN #1 #2
27058         #3 \q_recursion_stop
27059     }
27060     {
27061         \bool_lazy_and:nnT
27062         { ! \token_if_cs_p:N #2 }
27063         {
27064             \bool_lazy_any_p:n
27065             {
27066                 { \int_compare_p:nNn { '#2 } = { "0300 } }
27067                 { \int_compare_p:nNn { '#2 } = { "0301 } }
27068                 { \int_compare_p:nNn { '#2 } = { "0303 } }
27069             }
27070         }
27071         { \__tl_change_case_output:Vwn \c__tl_dot_above_tl }
27072         #1 #2#3 \q_recursion_stop
27073     }
27074 }

```

For upper casing, the test required is for a dot-above char after an I, J or I-ogonek. First a test for the appropriate letter, and if found a look-ahead and potentially one token dropped.

```

27075 \cs_new:Npn \__tl_change_case_upper_lt:Nnw #1
27076 {
27077     \exp_args:Nf \__tl_change_case_upper_lt:nnw
27078     {
27079         \int_case:nnF { '#1 }
27080         {
27081             { "0069 } I
27082             { "006A } J
27083             { "012F } \c__tl_I_ogonek_tl
27084         }
27085         \exp_stop_f:
27086     }
27087 }
27088 \cs_new:Npn \__tl_change_case_upper_lt:nnw #1#2
27089 {
27090     \tl_if_blank:nTF {#1}
27091     {#2}
27092     {

```

```

27093     \_tl_change_case_output:nwn {#1}
27094     \_tl_change_case_upper_lt:Nw
27095   }
27096 }
27097 \cs_new:Npn \_tl_change_case_upper_lt:Nw #1#2 \q_recursion_stop
27098 {
27099   \tl_if_head_is_N_type:nT {#2}
27100   { \_tl_change_case_upper_lt:NNw }
27101   #1 #2 \q_recursion_stop
27102 }
27103 \cs_new:Npn \_tl_change_case_upper_lt:NNw #1#2#3 \q_recursion_stop
27104 {
27105   \_tl_change_case_if_expandable:NTF #2
27106   {
27107     \exp_after:wN \_tl_change_case_upper_lt:Nw \exp_after:wN #1 #2
27108     #3 \q_recursion_stop
27109   }
27110   {
27111     \bool_lazy_and:nnTF
27112     { ! \token_if_cs_p:N #2 }
27113     { \int_compare_p:nNn { '#2 } = { "0307 } }
27114     { #1 }
27115     { #1 #2 }
27116     #3 \q_recursion_stop
27117   }
27118 }

```

(End definition for _tl_change_case_lower_lt:Nnw and others.)

_tl_change_case_upper_de-alt:Nnw A simple alternative version for German.

```

27119 \cs_new:cpn { \_tl_change_case_upper_de-alt:Nnw } #1#2
27120 {
27121   \int_compare:nNnTF { '#1 } = { 223 }
27122   { \_tl_change_case_output:Vwn \c__tl_upper_Eszett_tl }
27123   {#2}
27124 }

```

(End definition for _tl_change_case_upper_de-alt:Nnw.)

\c__tl_std_sigma_tl The above needs various special token lists containing pre-formed characters. This set
 \c__tl_final_sigma_tl are only available in Unicode engines, with no-op definitions for 8-bit use.
 \c__tl_accents_lt_tl
 \c__tl_dot_above_tl
 \c__tl_upper_Eszett_tl

```

27125 \bool_lazy_or:nnTF
27126 { \sys_if_engine luatex_p: }
27127 { \sys_if_engine xetex_p: }
27128 {
27129   \group_begin:
27130   \cs_set:Npn \_tl_tmp:n #1
27131   { \char_generate:nn {#1} { \char_value_catcode:n {#1} } }
27132   \tl_const:Nx \c__tl_std_sigma_tl { \_tl_tmp:n { "03C3 } }
27133   \tl_const:Nx \c__tl_final_sigma_tl { \_tl_tmp:n { "03C2 } }
27134   \tl_const:Nx \c__tl_accents_lt_tl
27135   {
27136     \_tl_tmp:n { "00CC }
27137   }

```

```

27138         \__tl_tmp:n { "0069 }
27139         \__tl_tmp:n { "0307 }
27140         \__tl_tmp:n { "0300 }
27141     }
27142     \__tl_tmp:n { "00CD }
27143     {
27144         \__tl_tmp:n { "0069 }
27145         \__tl_tmp:n { "0307 }
27146         \__tl_tmp:n { "0301 }
27147     }
27148     \__tl_tmp:n { "0128 }
27149     {
27150         \__tl_tmp:n { "0069 }
27151         \__tl_tmp:n { "0307 }
27152         \__tl_tmp:n { "0303 }
27153     }
27154 }
27155 \tl_const:Nx \c__tl_dot_above_tl { \__tl_tmp:n { "0307 } }
27156 \tl_const:Nx \c__tl_upper_Eszett_tl { \__tl_tmp:n { "1E9E } }
27157 \group_end:
27158 }
27159 {
27160     \tl_const:Nn \c__tl_std_sigma_tl { }
27161     \tl_const:Nn \c__tl_final_sigma_tl { }
27162     \tl_const:Nn \c__tl_accents_lt_tl { }
27163     \tl_const:Nn \c__tl_dot_above_tl { }
27164     \tl_const:Nn \c__tl_upper_Eszett_tl { }
27165 }

```

(End definition for \c__tl_std_sigma_tl and others.)

\c__tl_dotless_i_tl For cases where there is an 8-bit option in the T1 font set up, a variant is provided in both cases.

```

\c__tl_dotted_I_tl
\c__tl_i_ogonek_tl
\c__tl_I_ogonek_tl
27166 \group_begin:
27167     \bool_lazy_or:nnTF
27168     { \sys_if_engine_luatex_p: }
27169     { \sys_if_engine_xetex_p: }
27170     {
27171         \cs_set_protected:Npn \__tl_tmp:w #1#2
27172         {
27173             \tl_const:Nx #1
27174             {
27175                 \exp_after:wN \exp_after:wN \exp_after:wN
27176                 \exp_not:N \char_generate:nn
27177                 {"#2} { \char_value_catcode:n {"#2} }
27178             }
27179         }
27180     }
27181     {
27182         \cs_set_protected:Npn \__tl_tmp:w #1#2
27183         {
27184             \group_begin:
27185             \cs_set_protected:Npn \__tl_tmp:w ##1##2##3##4
27186             {

```

```

27187         \tl_const:Nx #1
27188         {
27189             \exp_after:wN \exp_after:wN \exp_after:wN
27190             \exp_not:N \char_generate:nn {##1} { 13 }
27191             \exp_after:wN \exp_after:wN \exp_after:wN
27192             \exp_not:N \char_generate:nn {##2} { 13 }
27193         }
27194     }
27195     \tl_set:Nx \l__tl_internal_a_tl
27196     { \char_codepoint_to_bytes:n {"#2} }
27197     \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
27198 \group_end:
27199 }
27200 }
27201 \__tl_tmp:w \c__tl_dotless_i_tl { 0131 }
27202 \__tl_tmp:w \c__tl_dotted_I_tl { 0130 }
27203 \__tl_tmp:w \c__tl_i_ogonek_tl { 012F }
27204 \__tl_tmp:w \c__tl_I_ogonek_tl { 012E }
27205 \group_end:

```

(End definition for `\c__tl_dotless_i_tl` and others.)

For 8-bit engines we now need to define the case-change data for the multi-octet mappings. These need a list of what code points are doable in T1 so the list is hard coded (there's no saving in loading the mappings dynamically). All of the straight-forward ones have two octets, so that is taken as read.

```

27206 \group_begin:
27207     \bool_lazy_or:nnT
27208     { \sys_if_engine_pdftex_p: }
27209     { \sys_if_engine_uptex_p: }
27210     {
27211         \cs_set_protected:Npn \__tl_loop:nn #1#2
27212         {
27213             \quark_if_recursion_tail_stop:n {#1}
27214             \tl_set:Nx \l__tl_internal_a_tl
27215             {
27216                 \char_codepoint_to_bytes:n {"#1}
27217                 \char_codepoint_to_bytes:n {"#2}
27218             }
27219             \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
27220             \__tl_loop:nn
27221         }
27222         \cs_set_protected:Npn \__tl_tmp:nnnn #1#2#3#4#5
27223         {
27224             \tl_const:cx
27225             {
27226                 c__tl_ #1 _case_
27227                 \char_generate:nn {#2} { 12 }
27228                 \char_generate:nn {#3} { 12 }
27229                 _tl
27230             }
27231             {
27232                 \exp_after:wN \exp_after:wN \exp_after:wN
27233                 \exp_not:N \char_generate:nn {#4} { 13 }
27234                 \exp_after:wN \exp_after:wN \exp_after:wN

```

```

27235         \exp_not:N \char_generate:nn {#5} { 13 }
27236     }
27237 }
27238 \cs_set_protected:Npn \__tl_tmp:w #1#2#3#4#5#6#7#8
27239 {
27240     \tl_const:cx
27241     {
27242         c__tl_lower_case_
27243         \char_generate:nn {#1} { 12 }
27244         \char_generate:nn {#2} { 12 }
27245         _tl
27246     }
27247     {
27248         \exp_after:wN \exp_after:wN \exp_after:wN
27249         \exp_not:N \char_generate:nn {#5} { 13 }
27250         \exp_after:wN \exp_after:wN \exp_after:wN
27251         \exp_not:N \char_generate:nn {#6} { 13 }
27252     }
27253     \__tl_tmp:nnnn { upper } {#5} {#6} {#1} {#2}
27254     \__tl_tmp:nnnn { mixed } {#5} {#6} {#1} {#2}
27255 }
27256 \__tl_loop:nn
27257 { 00C0 } { 00E0 }
27258 { 00C2 } { 00E2 }
27259 { 00C3 } { 00E3 }
27260 { 00C4 } { 00E4 }
27261 { 00C5 } { 00E5 }
27262 { 00C6 } { 00E6 }
27263 { 00C7 } { 00E7 }
27264 { 00C8 } { 00E8 }
27265 { 00C9 } { 00E9 }
27266 { 00CA } { 00EA }
27267 { 00CB } { 00EB }
27268 { 00CC } { 00EC }
27269 { 00CD } { 00ED }
27270 { 00CE } { 00EE }
27271 { 00CF } { 00EF }
27272 { 00D0 } { 00F0 }
27273 { 00D1 } { 00F1 }
27274 { 00D2 } { 00F2 }
27275 { 00D3 } { 00F3 }
27276 { 00D4 } { 00F4 }
27277 { 00D5 } { 00F5 }
27278 { 00D6 } { 00F6 }
27279 { 00D8 } { 00F8 }
27280 { 00D9 } { 00F9 }
27281 { 00DA } { 00FA }
27282 { 00DB } { 00FB }
27283 { 00DC } { 00FC }
27284 { 00DD } { 00FD }
27285 { 00DE } { 00FE }
27286 { 0100 } { 0101 }
27287 { 0102 } { 0103 }
27288 { 0104 } { 0105 }

```

27289	{ 0106 }	{ 0107 }
27290	{ 0108 }	{ 0109 }
27291	{ 010A }	{ 010B }
27292	{ 010C }	{ 010D }
27293	{ 010E }	{ 010F }
27294	{ 0110 }	{ 0111 }
27295	{ 0112 }	{ 0113 }
27296	{ 0114 }	{ 0115 }
27297	{ 0116 }	{ 0117 }
27298	{ 0118 }	{ 0119 }
27299	{ 011A }	{ 011B }
27300	{ 011C }	{ 011D }
27301	{ 011E }	{ 011F }
27302	{ 0120 }	{ 0121 }
27303	{ 0122 }	{ 0123 }
27304	{ 0124 }	{ 0125 }
27305	{ 0128 }	{ 0129 }
27306	{ 012A }	{ 012B }
27307	{ 012C }	{ 012D }
27308	{ 012E }	{ 012F }
27309	{ 0132 }	{ 0133 }
27310	{ 0134 }	{ 0135 }
27311	{ 0136 }	{ 0137 }
27312	{ 0139 }	{ 013A }
27313	{ 013B }	{ 013C }
27314	{ 013E }	{ 013F }
27315	{ 0141 }	{ 0142 }
27316	{ 0143 }	{ 0144 }
27317	{ 0145 }	{ 0146 }
27318	{ 0147 }	{ 0148 }
27319	{ 014A }	{ 014B }
27320	{ 014C }	{ 014D }
27321	{ 014E }	{ 014F }
27322	{ 0150 }	{ 0151 }
27323	{ 0152 }	{ 0153 }
27324	{ 0154 }	{ 0155 }
27325	{ 0156 }	{ 0157 }
27326	{ 0158 }	{ 0159 }
27327	{ 015A }	{ 015B }
27328	{ 015C }	{ 015D }
27329	{ 015E }	{ 015F }
27330	{ 0160 }	{ 0161 }
27331	{ 0162 }	{ 0163 }
27332	{ 0164 }	{ 0165 }
27333	{ 0168 }	{ 0169 }
27334	{ 016A }	{ 016B }
27335	{ 016C }	{ 016D }
27336	{ 016E }	{ 016F }
27337	{ 0170 }	{ 0171 }
27338	{ 0172 }	{ 0173 }
27339	{ 0174 }	{ 0175 }
27340	{ 0176 }	{ 0177 }
27341	{ 0178 }	{ 00FF }
27342	{ 0179 }	{ 017A }


```

27343     { 017B } { 017C }
27344     { 017D } { 017E }
27345     { 01CD } { 01CE }
27346     { 01CF } { 01D0 }
27347     { 01D1 } { 01D2 }
27348     { 01D3 } { 01D4 }
27349     { 01E2 } { 01E3 }
27350     { 01E6 } { 01E7 }
27351     { 01E8 } { 01E9 }
27352     { 01EA } { 01EB }
27353     { 01F4 } { 01F5 }
27354     { 0218 } { 0219 }
27355     { 021A } { 021B }
27356     \q_recursion_tail ?
27357     \q_recursion_stop
27358     \cs_set_protected:Npn \__tl_tmp:w #1#2#3
27359     {
27360         \group_begin:
27361         \cs_set_protected:Npn \__tl_tmp:w ##1##2##3##4
27362         {
27363             \tl_const:cx
27364             {
27365                 c__tl_ #3 _case_
27366                 \char_generate:nn {##1} { 12 }
27367                 \char_generate:nn {##2} { 12 }
27368                 _tl
27369             }
27370             {#2}
27371         }
27372         \tl_set:Nx \l__tl_internal_a_tl
27373         { \char_codepoint_to_bytes:n { "#1 } }
27374         \exp_after:wN \__tl_tmp:w \l__tl_internal_a_tl
27375         \group_end:
27376     }
27377     \__tl_tmp:w { OODF } { SS } { upper }
27378     \__tl_tmp:w { OODF } { Ss } { mixed }
27379     \__tl_tmp:w { 0131 } { I } { upper }
27380 }
27381 \group_end:

```

The (fixed) look-up mappings for letter-like control sequences.

```

27382 \group_begin:
27383     \cs_set_protected:Npn \__tl_change_case_setup:NN #1#2
27384     {
27385         \quark_if_recursion_tail_stop:N #1
27386         \tl_const:cn { c__tl_change_case_lower_ \token_to_str:N #1 _tl }
27387         { #2 }
27388         \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N #2 _tl }
27389         { #1 }
27390         \__tl_change_case_setup:NN
27391     }
27392     \__tl_change_case_setup:NN
27393     \AA \aa
27394     \AE \ae
27395     \DH \dh

```

```

27396 \DJ \dj
27397 \IJ \ij
27398 \L \l
27399 \NG \ng
27400 \O \o
27401 \OE \oe
27402 \SS \ss
27403 \TH \th
27404 \q_recursion_tail ?
27405 \q_recursion_stop
27406 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \i _tl } { I }
27407 \tl_const:cn { c__tl_change_case_upper_ \token_to_str:N \j _tl } { J }
27408 \group_end:

```

\l_tl_case_change_accents_tl A list of accents to leave alone.

```

27409 \tl_new:N \l_tl_case_change_accents_tl
27410 \tl_set:Nn \l_tl_case_change_accents_tl
27411 { \" \' \. \^ \' \~ \c \H \k \r \t \u \v }

```

(End definition for \l_tl_case_change_accents_tl. This variable is documented on page 254.)

_tl_change_case_mixed_n1:Nnw For Dutch, there is a single look-ahead test for ij when title casing. If the appropriate letters are found, produce IJ and gobble the j/J.

```

\_tl_change_case_mixed_n1:Nw
\_tl_change_case_mixed_n1:NNw
\_tl_change_case_mixed_n1:NNw
27412 \cs_new:Npn \__tl_change_case_mixed_n1:Nnw #1
27413 {
27414   \bool_lazy_or:nnTF
27415     { \int_compare_p:nNn { '#1 } = { 'i } }
27416     { \int_compare_p:nNn { '#1 } = { 'I } }
27417     {
27418       \__tl_change_case_output:nwn { I }
27419       \__tl_change_case_mixed_n1:Nw
27420     }
27421 }
27422 \cs_new:Npn \__tl_change_case_mixed_n1:Nw #1#2 \q_recursion_stop
27423 {
27424   \tl_if_head_is_N_type:nT {#2}
27425   { \__tl_change_case_mixed_n1:NNw }
27426   #1 #2 \q_recursion_stop
27427 }
27428 \cs_new:Npn \__tl_change_case_mixed_n1:NNw #1#2#3 \q_recursion_stop
27429 {
27430   \__tl_change_case_if_expandable:NTF #2
27431   {
27432     \exp_after:wN \__tl_change_case_mixed_n1:Nw \exp_after:wN #1 #2
27433     #3 \q_recursion_stop
27434   }
27435   {
27436     \bool_lazy_and:nnTF
27437       { ! ( \token_if_cs_p:N #2 ) }
27438       {
27439         \bool_lazy_or_p:nn
27440         { \int_compare_p:nNn { '#2 } = { 'j } }
27441         { \int_compare_p:nNn { '#2 } = { 'J } }
27442       }

```

```

27443     {
27444         \_tl_change_case_output:nwn { J }
27445         #1
27446     }
27447     { #1 #2 }
27448     #3 \q_recursion_stop
27449 }
27450 }

```

(End definition for `_tl_change_case_mixed_n1:Nnw`, `_tl_change_case_mixed_n1:Nw`, and `_tl_change_case_mixed_n1:NNw`.)

`\l_tl_case_change_math_tl` The list of token pairs which are treated as math mode and so not case changed.

```

27451 \tl_new:N \l_tl_case_change_math_tl
27452 \*package
27453 \tl_set:Nn \l_tl_case_change_math_tl
27454 { $ $ \ ( \ ) }
27455 \package

```

(End definition for `\l_tl_case_change_math_tl`. This variable is documented on page 253.)

`\l_tl_case_change_exclude_tl` The list of commands for which an argument is not case changed.

```

27456 \tl_new:N \l_tl_case_change_exclude_tl
27457 \*package
27458 \tl_set:Nn \l_tl_case_change_exclude_tl
27459 { \cite \ensuremath \label \ref }
27460 \package

```

(End definition for `\l_tl_case_change_exclude_tl`. This variable is documented on page 253.)

`\l_tl_mixed_case_ignore_tl` Characters to skip over when finding the first letter in a word to be mixed cased.

```

27461 \tl_new:N \l_tl_mixed_case_ignore_tl
27462 \tl_set:Nx \l_tl_mixed_case_ignore_tl
27463 {
27464     ( % )
27465     [ % ]
27466     \cs_to_str:N \{ % \}
27467     '
27468     -
27469 }

```

(End definition for `\l_tl_mixed_case_ignore_tl`. This variable is documented on page 254.)

44.14.2 Building a token list

Between `\tl_build_begin:N <tl var>` and `\tl_build_end:N <tl var>`, the `<tl var>` has the structure

```

\exp_end: ... \exp_end: \_tl_build_last:NNn <assignment> <next tl>
{\<left>} <right>

```

where `<right>` is not braced. The “data” it represents is `<left>` followed by the “data” of `<next tl>` followed by `<right>`. The `<next tl>` is a token list variable whose name is that of `<tl var>` followed by `'`. There are between 0 and 4 `\exp_end:` to keep track of when `<left>` and `<right>` should be put into the `<next tl>`. The `<assignment>` is `\cs_set_nopar:Npx` if the variable is local, and `\cs_gset_nopar:Npx` if it is global.

`\tl_build_begin:N` First construct the $\langle next\ tl \rangle$: using a prime here conflicts with the usual `expl3` convention
`\tl_build_gbegin:N` but we need a name that can be derived from `#1` without any external data such as a
`__tl_build_begin:NN` counter. Empty that $\langle next\ tl \rangle$ and setup the structure. The local and global versions
`__tl_build_begin:NNN` only differ by a single function `\cs_(g)set_nopar:Npx` used for all assignments: this is
important because only that function is stored in the $\langle tl\ var \rangle$ and $\langle next\ tl \rangle$ for subsequent
assignments. In principle `__tl_build_begin:NNN` could use `\tl_(g)clear_new:N` to
empty `#1` and make sure it is defined, but logging the definition does not seem useful so
we just do `#3 #1 { }` to clear it locally or globally as appropriate.

```

27470 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
27471 \cs_new_protected:Npn \tl_build_begin:N #1
27472 { \__tl_build_begin:NN \cs_set_nopar:Npx #1 }
27473 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
27474 \cs_new_protected:Npn \tl_build_gbegin:N #1
27475 { \__tl_build_begin:NN \cs_gset_nopar:Npx #1 }
27476 \cs_new_protected:Npn \__tl_build_begin:NN #1#2
27477 { \exp_args:Nc \__tl_build_begin:NNN { \cs_to_str:N #2 ' } #2 #1 }
27478 \cs_new_protected:Npn \__tl_build_begin:NNN #1#2#3
27479 {
27480   #3 #1 { }
27481   #3 #2
27482   {
27483     \exp_not:n { \exp_end: \exp_end: \exp_end: \exp_end: }
27484     \exp_not:n { \__tl_build_last:NNn #3 #1 { } }
27485   }
27486 }

```

(End definition for `\tl_build_begin:N` and others. These functions are documented on page 256.)

`\tl_build_clear:N` The `begin` and `gbegin` functions already clear enough to make the token list variable
`\tl_build_gclear:N` effectively empty. Eventually the `begin` and `gbegin` functions should check that `#1'` is
empty or undefined, while the `clear` and `gclear` functions ought to empty `#1'`, `#1''`
and so on, similar to `\tl_build_end:N`. This only affects memory usage.

```

27487 \cs_new_eq:NN \tl_build_clear:N \tl_build_begin:N
27488 \cs_new_eq:NN \tl_build_gclear:N \tl_build_gbegin:N

```

(End definition for `\tl_build_clear:N` and `\tl_build_gclear:N`. These functions are documented on page 256.)

`\tl_build_put_right:Nn` Similar to `\tl_put_right:Nn`, but apply `\exp:w` to `#1`. Most of the time this just removes
`\tl_build_put_right:Nx` one `\exp_end:`. When there are none left, `__tl_build_last:NNn` is expanded instead.
`\tl_build_gput_right:Nn` It resets the definition of the $\langle tl\ var \rangle$ by ending the `\exp_not:n` and the definition early.
`\tl_build_gput_right:Nx` Then it makes sure the $\langle next\ tl \rangle$ (its argument `#1`) is set-up and starts a new definition.
`__tl_build_last:NNn` Then `__tl_build_put:nn` and `__tl_build_put:nw` place the $\langle left \rangle$ part of the original
`__tl_build_put:nn` $\langle tl\ var \rangle$ as appropriate for the definition of the $\langle next\ tl \rangle$ (the $\langle right \rangle$ part is left in the right
`__tl_build_put:nw` place without ever becoming a macro argument). We use `\exp_after:wN` rather than
some `\exp_args:No` to avoid reading arguments that are likely very long token lists. We
use `\cs_(g)set_nopar:Npx` rather than `\tl_(g)set:Nx` partly for the same reason and
partly because the assignments are interrupted by brace tricks, which implies that the
assignment does not simply set the token list to an x-expansion of the second argument.

```

27489 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
27490 \cs_new_protected:Npn \tl_build_put_right:Nn #1#2
27491 {
27492   \cs_set_nopar:Npx #1

```

```

27493     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 #2 } }
27494   }
27495   \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
27496   \cs_new_protected:Npn \tl_build_put_right:Nx #1#2
27497   {
27498     \cs_set_nopar:Npx #1
27499     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 } #2 }
27500   }
27501   \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
27502   \cs_new_protected:Npn \tl_build_gput_right:Nn #1#2
27503   {
27504     \cs_gset_nopar:Npx #1
27505     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 #2 } }
27506   }
27507   \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
27508   \cs_new_protected:Npn \tl_build_gput_right:Nx #1#2
27509   {
27510     \cs_gset_nopar:Npx #1
27511     { \exp_after:wN \exp_not:n \exp_after:wN { \exp:w #1 } #2 }
27512   }
27513   \cs_new_protected:Npn \__tl_build_last:NNn #1#2
27514   {
27515     \if_false: { { \fi:
27516       \exp_end: \exp_end: \exp_end: \exp_end: \exp_end:
27517       \__tl_build_last:NNn #1 #2 { }
27518     }
27519   }
27520   \if_meaning:w \c_empty_tl #2
27521   \__tl_build_begin:NN #1 #2
27522   \fi:
27523   #1 #2
27524   {
27525     \exp_after:wN \exp_not:n \exp_after:wN
27526     {
27527       \exp:w \if_false: } } \fi:
27528     \exp_after:wN \__tl_build_put:nn \exp_after:wN {#2}
27529   }
27530   \cs_new_protected:Npn \__tl_build_put:nn #1#2 { \__tl_build_put:nw {#2} #1 }
27531   \cs_new_protected:Npn \__tl_build_put:nw #1#2 \__tl_build_last:NNn #3#4#5
27532   { #2 \__tl_build_last:NNn #3 #4 { #1 #5 } }

```

(End definition for \tl_build_put_right:Nn and others. These functions are documented on page 257.)

\tl_build_put_left:Nn See \tl_build_put_right:Nn for all the machinery. We could easily provide \tl_build_put_left:Nx, by just add the *<right>* material after the *<left>* in the x-expanding assignment.

```

\tl_build_gput_left:Nn
\__tl_build_put_left:NNn
27533 \__kernel_patch:nnNNpn { \__kernel_chk_var_local:N #1 } { }
27534 \cs_new_protected:Npn \tl_build_put_left:Nn #1
27535   { \__tl_build_put_left:NNn \cs_set_nopar:Npx #1 }
27536 \cs_generate_variant:Nn \tl_build_put_left:Nn { Nx }
27537 \__kernel_patch:nnNNpn { \__kernel_chk_var_global:N #1 } { }
27538 \cs_new_protected:Npn \tl_build_gput_left:Nn #1
27539   { \__tl_build_put_left:NNn \cs_gset_nopar:Npx #1 }
27540 \cs_generate_variant:Nn \tl_build_gput_left:Nn { Nx }

```

```

27541 \cs_new_protected:Npn \__tl_build_put_left:NNn #1#2#3
27542 {
27543     #1 #2
27544     {
27545         \exp_after:wN \exp_not:n \exp_after:wN
27546         {
27547             \exp:w \exp_after:wN \__tl_build_put:nn
27548             \exp_after:wN {#2} {#3}
27549         }
27550     }
27551 }

```

(End definition for `\tl_build_put_left:Nn`, `\tl_build_gput_left:Nn`, and `__tl_build_put_left:NNn`. These functions are documented on page 257.)

`\tl_build_get:NN` The idea is to expand the $\langle tl\ var \rangle$ then the $\langle next\ tl \rangle$ and so on, all within an x-expanding assignment, and wrap as appropriate in `\exp_not:n`. The various $\langle left \rangle$ parts are left in the assignment as we go, which enables us to expand the $\langle next\ tl \rangle$ at the right place. The various $\langle right \rangle$ parts are eventually picked up in one last `\exp_not:n`, with a brace trick to wrap all the $\langle right \rangle$ parts together.

```

27552 \cs_new_protected:Npn \tl_build_get:NN
27553 { \__tl_build_get:NNN \tl_set:Nx }
27554 \cs_new_protected:Npn \__tl_build_get:NNN #1#2#3
27555 { #1 #3 { \if_false: { \fi: \exp_after:wN \__tl_build_get:w #2 } } }
27556 \cs_new:Npn \__tl_build_get:w #1 \__tl_build_last:NNn #2#3#4
27557 {
27558     \exp_not:n {#4}
27559     \if_meaning:w \c_empty_tl #3
27560     \exp_after:wN \__tl_build_get_end:w
27561     \fi:
27562     \exp_after:wN \__tl_build_get:w #3
27563 }
27564 \cs_new:Npn \__tl_build_get_end:w #1#2#3
27565 { \exp_after:wN \exp_not:n \exp_after:wN { \if_false: } \fi: }

```

(End definition for `\tl_build_get:NN` and others. This function is documented on page 257.)

`\tl_build_end:N` Get the data then clear the $\langle next\ tl \rangle$ recursively until finding an empty one. It is perhaps wasteful to repeatedly use `\cs_to_sr:N`. The local/global scope is checked by `\tl_set:Nx` or `\tl_gset:Nx`.

`\tl_build_gend:N`

`__tl_build_end_loop:NN`

```

27566 \cs_new_protected:Npn \tl_build_end:N #1
27567 {
27568     \__tl_build_get:NNN \tl_set:Nx #1 #1
27569     \exp_args:Nc \__tl_build_end_loop:NN { \cs_to_str:N #1 ' } \tl_clear:N
27570 }
27571 \cs_new_protected:Npn \tl_build_gend:N #1
27572 {
27573     \__tl_build_get:NNN \tl_gset:Nx #1 #1
27574     \exp_args:Nc \__tl_build_end_loop:NN { \cs_to_str:N #1 ' } \tl_gclear:N
27575 }
27576 \cs_new_protected:Npn \__tl_build_end_loop:NN #1#2
27577 {
27578     \if_meaning:w \c_empty_tl #1
27579     \exp_after:wN \use_none:nnnnnn

```

```

27580 \fi:
27581 #2 #1
27582 \exp_args:Nc \__tl_build_end_loop:NN { \cs_to_str:N #1 ' } #2
27583 }

```

(End definition for `\tl_build_end:N`, `\tl_build_gend:N`, and `__tl_build_end_loop:NN`. These functions are documented on page 257.)

44.14.3 Other additions to `l3tl`

`\tl_range_braced:Nnn` For the braced version `__tl_range_braced:w` sets up `__tl_range_collect_braced:w` which stores items one by one in an argument after the semicolon. The unbraced version is almost identical. The version preserving braces and spaces starts by deleting spaces before the argument to avoid collecting them, and sets up `__tl_range_collect:nn` with a first argument of the form `{ {⟨collected⟩} ⟨tokens⟩ }`, whose head is the collected tokens and whose tail is what remains of the original token list. This form makes it easier to move tokens to the `⟨collected⟩` tokens.

```

\__tl_range_collect_braced:w
\__tl_range_unbraced:w
\__tl_range_collect_unbraced:w
27584 \cs_new:Npn \tl_range_braced:Nnn { \exp_args:No \tl_range_braced:nnn }
27585 \cs_generate_variant:Nn \tl_range_braced:Nnn { c }
27586 \cs_new:Npn \tl_range_braced:nnn { \__tl_range:Nnnn \__tl_range_braced:w }
27587 \cs_new:Npn \tl_range_unbraced:Nnn
27588 { \exp_args:No \tl_range_unbraced:nnn }
27589 \cs_generate_variant:Nn \tl_range_unbraced:Nnn { c }
27590 \cs_new:Npn \tl_range_unbraced:nnn
27591 { \__tl_range:Nnnn \__tl_range_unbraced:w }
27592 \cs_new:Npn \__tl_range_braced:w #1 ; #2
27593 { \__tl_range_collect_braced:w #1 ; { } #2 }
27594 \cs_new:Npn \__tl_range_unbraced:w #1 ; #2
27595 { \__tl_range_collect_unbraced:w #1 ; { } #2 }
27596 \cs_new:Npn \__tl_range_collect_braced:w #1 ; #2#3
27597 {
27598   \if_int_compare:w #1 > 1 \exp_stop_f:
27599     \exp_after:wN \__tl_range_collect_braced:w
27600     \int_value:w \int_eval:n { #1 - 1 } \exp_after:wN ;
27601   \fi:
27602   { #2 {#3} }
27603 }
27604 \cs_new:Npn \__tl_range_collect_unbraced:w #1 ; #2#3
27605 {
27606   \if_int_compare:w #1 > 1 \exp_stop_f:
27607     \exp_after:wN \__tl_range_collect_unbraced:w
27608     \int_value:w \int_eval:n { #1 - 1 } \exp_after:wN ;
27609   \fi:
27610   { #2 #3 }
27611 }

```

(End definition for `\tl_range_braced:Nnn` and others. These functions are documented on page 256.)

44.15 Additions to `l3token`

`\c_catcode_active_space_tl` While `\char_generate:nn` can produce active characters in some engines it cannot in general. It would be possible to simply change the catcode of space but then the code

would need to avoid all spaces, making it quite unreadable. Instead we use the primitive `\tex_lowercase:D` trick.

```

27612 \group_begin:
27613   \char_set_catcode_active:N *
27614   \char_set_lccode:nn { '*' } { '\ }
27615   \tex_lowercase:D { \tl_const:Nn \c_catcode_active_space_tl { * } }
27616 \group_end:

```

(End definition for `\c_catcode_active_space_tl`. This variable is documented on page 257.)

```

27617 <@@=peek>

```

\peek_N_type:TF All tokens are N-type tokens, except in four cases: begin-group tokens, end-group tokens, space tokens with character code 32, and outer tokens. Since `\l_peek_token` might be outer, we cannot use the convenient `\bool_if:nTF` function, and must resort to the old trick of using `\ifodd` to expand a set of tests. The **false** branch of this test is taken if the token is one of the first three kinds of non-N-type tokens (explicit or implicit), thus we call `__peek_false:w`. In the **true** branch, we must detect outer tokens, without impacting performance too much for non-outer tokens. The first filter is to search for **outer** in the `\meaning` of `\l_peek_token`. If that is absent, `\use_none_delimit_by_q_stop:w` cleans up, and we call `__peek_true:w`. Otherwise, the token can be a non-outer macro or a primitive mark whose parameter or replacement text contains **outer**, it can be the primitive `\outer`, or it can be an outer token. Macros and marks would have **ma** in the part before the first occurrence of **outer**; the meaning of `\outer` has nothing after **outer**, contrarily to outer macros; and that covers all cases, calling `__peek_true:w` or `__peek_false:w` as appropriate. Here, there is no *<search token>*, so we feed a dummy `\scan_stop:` to the `__peek_token_generic:NNTF` function.

```

27618 \group_begin:
27619   \cs_set_protected:Npn \__peek_tmp:w #1 \q_stop
27620   {
27621     \cs_new_protected:Npn \__peek_execute_branches_N_type:
27622     {
27623       \if_int_odd:w
27624         \if_catcode:w \exp_not:N \l_peek_token { 0 \exp_stop_f: \fi:
27625         \if_catcode:w \exp_not:N \l_peek_token } 0 \exp_stop_f: \fi:
27626         \if_meaning:w \l_peek_token \c_space_token 0 \exp_stop_f: \fi:
27627         1 \exp_stop_f:
27628         \exp_after:wN \__peek_N_type:w
27629         \token_to_meaning:N \l_peek_token
27630         \q_mark \__peek_N_type_aux:nnw
27631         #1 \q_mark \use_none_delimit_by_q_stop:w
27632         \q_stop
27633         \exp_after:wN \__peek_true:w
27634       \else:
27635         \exp_after:wN \__peek_false:w
27636       \fi:
27637     }
27638     \cs_new_protected:Npn \__peek_N_type:w ##1 #1 ##2 \q_mark ##3
27639     { ##3 {##1} {##2} }
27640   }
27641   \exp_after:wN \__peek_tmp:w \tl_to_str:n { outer } \q_stop
27642 \group_end:
27643 \cs_new_protected:Npn \__peek_N_type_aux:nnw #1 #2 #3 \fi:

```



```

27644 {
27645   \fi:
27646   \tl_if_in:noTF {#1} { \tl_to_str:n {ma} }
27647     { \__peek_true:w }
27648     { \tl_if_empty:nTF {#2} { \__peek_true:w } { \__peek_false:w } }
27649 }
27650 \cs_new_protected:Npn \peek_N_type:TF
27651 {
27652   \__peek_token_generic:NNTF
27653   \__peek_execute_branches_N_type: \scan_stop:
27654 }
27655 \cs_new_protected:Npn \peek_N_type:T
27656 { \__peek_token_generic:NNT \__peek_execute_branches_N_type: \scan_stop: }
27657 \cs_new_protected:Npn \peek_N_type:F
27658 { \__peek_token_generic:NNTF \__peek_execute_branches_N_type: \scan_stop: }

```

(End definition for `\peek_N_type:TF` and others. This function is documented on page 258.)

`\l__peek_collect_tl`

```

27659 \tl_new:N \l__peek_collect_tl

```

(End definition for `\l__peek_collect_tl`.)

`\peek_catcode_collect_inline:Nn`
`\peek_charcode_collect_inline:Nn`
`\peek_meaning_collect_inline:Nn`
`__peek_collect:NNn`
`__peek_collect_true:w`
`__peek_collect_remove:nw`
`__peek_collect:N`

Most of the work is done by `__peek_execute_branches_...`, which calls either `__peek_true:w` or `__peek_false:w` according to whether the next token `\l__peek_token` matches the search token (stored in `\l__peek_search_token` and `\l__peek_search_tl`). Here, in the true case we run `__peek_collect_true:w`, which generally calls `__peek_collect:N` to store the peeked token into `\l__peek_collect_tl`, except in special non-N-type cases (begin-group, end-group, or space), where a frozen token is stored. The true branch calls `__peek_execute_branches_...` to fetch more matching tokens. Once there are no more, `__peek_false_aux:n` closes the safe-align group and runs the user's inline code.

```

27660 \cs_new_protected:Npn \peek_catcode_collect_inline:Nn
27661 { \__peek_collect:NNn \__peek_execute_branches_catcode: }
27662 \cs_new_protected:Npn \peek_charcode_collect_inline:Nn
27663 { \__peek_collect:NNn \__peek_execute_branches_charcode: }
27664 \cs_new_protected:Npn \peek_meaning_collect_inline:Nn
27665 { \__peek_collect:NNn \__peek_execute_branches_meaning: }
27666 \cs_new_protected:Npn \__peek_collect:NNn #1#2#3
27667 {
27668   \group_align_safe_begin:
27669   \cs_set_eq:NN \l__peek_search_token #2
27670   \tl_set:Nn \l__peek_search_tl {#2}
27671   \tl_clear:N \l__peek_collect_tl
27672   \cs_set:Npn \__peek_false:w
27673     { \exp_args:No \__peek_false_aux:n \l__peek_collect_tl }
27674   \cs_set:Npn \__peek_false_aux:n ##1
27675     {
27676       \group_align_safe_end:
27677       #3
27678     }
27679   \cs_set_eq:NN \__peek_true:w \__peek_collect_true:w
27680   \cs_set:Npn \__peek_true_aux:w { \peek_after:Nw #1 }
27681   \__peek_true_aux:w

```

```

27682 }
27683 \cs_new_protected:Npn \__peek_collect_true:w
27684 {
27685   \if_case:w
27686     \if_catcode:w \exp_not:N \l_peek_token { 1 \exp_stop_f: \fi:
27687     \if_catcode:w \exp_not:N \l_peek_token } 2 \exp_stop_f: \fi:
27688     \if_meaning:w \l_peek_token \c_space_token 3 \exp_stop_f: \fi:
27689     0 \exp_stop_f:
27690     \exp_after:wN \__peek_collect:N
27691   \or: \__peek_collect_remove:nw { \c_group_begin_token }
27692   \or: \__peek_collect_remove:nw { \c_group_end_token }
27693   \or: \__peek_collect_remove:nw { ~ }
27694   \fi:
27695 }
27696 \cs_new_protected:Npn \__peek_collect:N #1
27697 {
27698   \tl_put_right:Nn \l__peek_collect_tl {#1}
27699   \__peek_true_aux:w
27700 }
27701 \cs_new_protected:Npn \__peek_collect_remove:nw #1
27702 {
27703   \tl_put_right:Nn \l__peek_collect_tl {#1}
27704   \exp_after:wN \__peek_true_remove:w
27705 }

```

(End definition for `\peek_catcode_collect_inline:Nn` and others. These functions are documented on page 258.)

```

27706 \</initex | package>

```

45 l3drivers Implementation

```

27707 \<*initex | package>
27708 \<@@=driver>

```

Whilst there is a reasonable amount of code overlap between drivers, it is much clearer to have the blocks more-or-less separated than run in together and DocStripped out in parts. As such, most of the following is set up on a per-driver basis, though there is some common code (again given in blocks not interspersed with other material).

All the file identifiers are up-front so that they come out in the right place in the files.

```

27709 \<*package>
27710 \ProvidesExplFile
27711 \<*dvipdfmx>
27712 {l3dvidpfmx.def}{2019-01-13}{ }
27713 {L3 Experimental driver: dvipdfmx}
27714 \</dvipdfmx>
27715 \<*dvips>
27716 {l3dvips.def}{2019-01-13}{ }
27717 {L3 Experimental driver: dvips}
27718 \</dvips>
27719 \<*dvisvgm>
27720 {l3dvisvgm.def}{2019-01-13}{ }
27721 {L3 Experimental driver: dvisvgm}

```

```

27722 </dvisvgm>
27723 <{*pdfmode>
27724   {l3pdfmode.def}{2019-01-13}{ }
27725   {L3 Experimental driver: PDF mode}
27726 </pdfmode>
27727 <{*xdvipdfmx>
27728   {l3xdvipdfmx.def}{2019-01-13}{ }
27729   {L3 Experimental driver: xdvipdfmx}
27730 </xdvipdfmx>
27731 </package>

```

The order of the driver code here is such that we get somewhat logical outcomes in terms of code sharing whilst keeping things readable. (Trying to mix all of the code by concept is almost unmanageable.) The key parts which are shared are

- Color support is either `dvips`-like or `pdfmode`-like.
- `pdfmode` and `(x)dvipdfmx` share drawing routines.
- `xdvipdfmx` is largely the same as `dvipdfmx` so takes most of the same code.

`__driver_literal:e` The one shared function for all drivers is access to the basic `\special` primitive: it has slightly odd expansion behaviour so a wrapper is provided.

```

__driver_literal:n
__driver_literal:x
27732 \cs_new_eq:NN __driver_literal:e \tex_special:D
27733 \cs_new_protected:Npn __driver_literal:n #1
27734   { __driver_literal:e { \exp_not:n {#1} } }
27735 \cs_generate_variant:Nn __driver_literal:n { x }

```

(End definition for `__driver_literal:e` and `__driver_literal:n`.)

45.1 Color support

Color support is split into two parts: a “general” concept and one directly linked to drawings (or rather the split between filling and stroking). General color is relatively easy to handle: we have a color stack available with all modern drivers, and can use that. Whilst `(x)dvipdfmx` does have its own approach to color specials, it is easier to use `dvips`-like ones for all cases except direct PDF output.

45.1.1 dvips-style

```

27736 (*dvisvgm | dvipdfmx | dvips | xdvipdfmx)

```

`\driver_color_pickup:N` Allow for L^AT_EX 2_ε color. Here, the possible input values are limited: `dvips`-style colors can mainly be taken as-is with the exception spot ones (here we need a model and a tint).

`__driver_color_pickup:w`

```

27737 (*package)
27738 \cs_new_protected:Npn \driver_color_pickup:N #1 { }
27739 \AtBeginDocument
27740 {
27741   \@ifpackageloaded { color }
27742   {
27743     \cs_set_protected:Npn \driver_color_pickup:N #1
27744     {
27745       \exp_args:NV \tl_if_head_is_space:nTF \current@color
27746       {
27747         \tl_set:Nx #1
27748         {

```

```

27749         spot ~
27750         \exp_after:wN \use:n \current@color \c_space_tl 1
27751     }
27752 }
27753 {
27754     \exp_last_unbraced:Nx \__driver_color_pickup:w
27755     { \current@color } \q_stop #1
27756 }
27757 }
27758 \cs_new_protected:Npn \__driver_color_pickup:w #1 ~ #2 \q_stop #3
27759 { \tl_set:Nn #3 { #1 ~ #2 } }
27760 }
27761 { }
27762 }
27763 </package>

```

(End definition for `\driver_color_pickup:N` and `__driver_color_pickup:w`. This function is documented on page 260.)

`\driver_color_cmyk:nnnn` Push the data to the stack. In the case of dvips also reset the drawing fill color in raw PostScript.

```

\driver_color_gray:n
\driver_color_rgb:nnn
\driver_color_spot:nn
\__driver_color_select:n
\__driver_color_select:x
\__driver_color_reset:
27764 \cs_new_protected:Npn \driver_color_cmyk:nnnn #1#2#3#4
27765 {
27766     \__driver_color_select:x
27767     {
27768         cmyk~
27769         \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
27770         \fp_eval:n {#3} ~ \fp_eval:n {#4}
27771     }
27772 }
27773 \cs_new_protected:Npn \driver_color_gray:n #1
27774 { \__driver_color_select:x { gray~ \fp_eval:n {#1} } }
27775 \cs_new_protected:Npn \driver_color_rgb:nnn #1#2#3
27776 {
27777     \__driver_color_select:x
27778     { rgb~ \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} }
27779 }
27780 \cs_new_protected:Npn \driver_color_spot:nn #1#2
27781 { \__driver_color_select:n { #1 } }
27782 \cs_new_protected:Npn \__driver_color_select:n #1
27783 {
27784     \__driver_literal:n { color~push~ #1 }
27785     <*dvips>
27786     \__driver_literal_postscript:n { /l3fc~{ }~def }
27787     </dvips>
27788     \group_insert_after:N \__driver_color_reset:
27789 }
27790 \cs_generate_variant:Nn \__driver_color_select:n { x }
27791 \cs_new_protected:Npn \__driver_color_reset:
27792 { \__driver_literal:n { color~pop } }

```

(End definition for `\driver_color_cmyk:nnnn` and others. These functions are documented on page 260.)

```

27793 </dvisvgm | dvipdfmx | dvips | xdvipdfmx>

```

45.1.2 pdfmode

27794 `<*pdfmode>`

`\driver_color_pickup:N`
`_driver_color_pickup:w`

The current color in driver-dependent format: pick up the package-mode data if available. We end up converting back and forward in this route as we store our color data in dvips format. The `\current@color` needs to be x-expanded before `_driver_color_pickup:w` breaks it apart, because for instance xcolor sets it to be instructions to generate a colour

```

27795 <*package>
27796 \cs_new_protected:Npn \driver_color_pickup:N #1 { }
27797 \AtBeginDocument
27798 {
27799   \@ifpackageloaded { color }
27800   {
27801     \cs_set_protected:Npn \driver_color_pickup:N #1
27802     {
27803       \exp_last_unbraced:Nx \_driver_color_pickup:w
27804       { \current@color } ~ 0 ~ 0 ~ 0 \q_stop #1
27805     }
27806     \cs_new_protected:Npn \_driver_color_pickup:w
27807     #1 ~ #2 ~ #3 ~ #4 ~ #5 ~ #6 \q_stop #7
27808     {
27809       \str_if_eq:nnTF {#2} { g }
27810       { \tl_set:Nn #7 { gray ~ #1 } }
27811       {
27812         \str_if_eq:nnTF {#4} { rg }
27813         { \tl_set:Nn #7 { rgb ~ #1 ~ #2 ~ #3 } }
27814         {
27815           \str_if_eq:nnTF {#5} { k }
27816           { \tl_set:Nn #7 { cmyk ~ #1 ~ #2 ~ #3 ~ #4 } }
27817           {
27818             \str_if_eq:nnTF {#2} { cs }
27819             {
27820               \tl_set:Nx #7 { spot ~ \use_none:n #1 ~ #5 }
27821             }
27822             {
27823               \tl_set:Nn #7 { gray ~ 0 }
27824             }
27825           }
27826         }
27827       }
27828     }
27829   }
27830 { }
27831 }
27832 </package>

```

(End definition for `\driver_color_pickup:N` and `_driver_color_pickup:w`. This function is documented on page 260.)

`\l_driver_color_stack_int`

pdfTeX and LuaTeX have multiple stacks available, and to track which one is in use a variable is required.

27833 `\int_new:N \l_driver_color_stack_int`

(End definition for \l__driver_color_stack_int.)

\driver_color_cmyk:nnnn Simply dump the data, but allowing for LuaTeX.

```

27834 \cs_new_protected:Npn \driver_color_cmyk:nnnn #1#2#3#4
27835 {
27836   \use:x
27837   {
27838     \__driver_color_cmyk:nnnn
27839     { \fp_eval:n {#1} }
27840     { \fp_eval:n {#2} }
27841     { \fp_eval:n {#3} }
27842     { \fp_eval:n {#4} }
27843   }
27844 }
27845 \cs_new_protected:Npn \__driver_color_cmyk:nnnn #1#2#3#4
27846 {
27847   \__driver_color_select:n
27848   { #1 ~ #2 ~ #3 ~ #4 ~ k ~ #1 ~ #2 ~ #3 ~ #4 ~ K }
27849 }
27850 \cs_new_protected:Npn \driver_color_gray:n #1
27851 { \exp_args:Nx \__driver_color_gray:n { \fp_eval:n {#1} } }
27852 \cs_new_protected:Npn \__driver_color_gray:n #1
27853 { \__driver_color_select:n { #1 ~ g ~ #1 ~ G } }
27854 \cs_new_protected:Npn \driver_color_rgb:nnn #1#2#3
27855 {
27856   \use:x
27857   {
27858     \__driver_color_rgb:nnn
27859     { \fp_eval:n {#1} }
27860     { \fp_eval:n {#2} }
27861     { \fp_eval:n {#3} }
27862   }
27863 }
27864 \cs_new_protected:Npn \__driver_color_rgb:nnn #1#2#3
27865 { \__driver_color_select:n { #1 ~ #2 ~ #3 ~ rg ~ #1 ~ #2 ~ #3 ~ RG } }
27866 \cs_new_protected:Npn \driver_color_spot:nn #1#2
27867 { \__driver_color_select:n { /#1 ~ cs ~ /#1 ~ CS ~ #2 ~ sc ~ #2 ~ SC } }
27868 \cs_new_protected:Npx \__driver_color_select:n #1
27869 {
27870   \cs_if_exist:NTF \tex_pdfextension:D
27871   { \tex_pdfextension:D colorstack }
27872   { \tex_pdfcolorstack:D }
27873   \exp_not:N \l__driver_color_stack_int push {#1}
27874   \group_insert_after:N \exp_not:N \__driver_color_reset:
27875 }
27876 \cs_generate_variant:Nn \__driver_color_select:n { x }
27877 \cs_new_protected:Npx \__driver_color_reset:
27878 {
27879   \cs_if_exist:NTF \tex_pdfextension:D
27880   { \tex_pdfextension:D colorstack }
27881   { \tex_pdfcolorstack:D }
27882   \exp_not:N \l__driver_color_stack_int pop \scan_stop:
27883 }

```

(End definition for `\driver_color_cmyk:n` and others. These functions are documented on page 260.)

27884 `</pdfmode>`

45.2 dvips driver

27885 `<*dvips>`

45.2.1 Basics

`_driver_literal_postscript:n` Literal PostScript can be included using a few low-level formats. Here, we use the form with no positioning: this is overall more convenient as a wrapper. Note that this does require that where position is important, an appropriate wrapper is included.

27886 `\cs_new_protected:Npn _driver_literal_postscript:n #1`
 27887 `{ _driver_literal:n { ps:: #1 } }`
 27888 `\cs_generate_variant:Nn _driver_literal_postscript:n { x }`

(End definition for `_driver_literal_postscript:n`.)

`_driver_align_currentpoint_begin:` In `dvips` there is no build-in saving of the current position, and so some additional PostScript is required to set up the transformation matrix and also to restore it afterwards. Notice the use of the stack to save the current position “up front” and to move back to it at the end of the process. Notice that the `[begin]/[end]` pair here mean that we can use a run of PostScript statements in separate lines: not *required* but does make the code and output more clear.

27889 `\cs_new_protected:Npn _driver_align_currentpoint_begin:`
 27890 `{`
 27891 `_driver_literal:n { ps::[begin] }`
 27892 `_driver_literal_postscript:n { currentpoint }`
 27893 `_driver_literal_postscript:n { currentpoint~translate }`
 27894 `}`
 27895 `\cs_new_protected:Npn _driver_align_currentpoint_end:`
 27896 `{`
 27897 `_driver_literal_postscript:n { neg~exch~neg~exch~translate }`
 27898 `_driver_literal:n { ps::[end] }`
 27899 `}`

(End definition for `_driver_align_currentpoint_begin:` and `_driver_align_currentpoint_end:.`)

`_driver_scope_begin:` Saving/restoring scope for general operations needs to be done with `dvips` positioning (try without to see this!). Thus we need the `ps:` version of the special here. As only the graphics state is ever altered within this pairing, we use the lower-cost `g`-versions.

27900 `\cs_new_protected:Npn _driver_scope_begin:`
 27901 `{ _driver_literal:n { ps:gsave } }`
 27902 `\cs_new_protected:Npn _driver_scope_end:`
 27903 `{ _driver_literal:n { ps:grestore } }`

(End definition for `_driver_scope_begin:` and `_driver_scope_end:.`)

45.2.2 Box operations

`\driver_box_use_clip:N` The `dvips` driver scales all absolute dimensions based on the output resolution selected and any \TeX magnification. Thus for any operation involving absolute lengths there is a correction to make. See `normalscale` from `special.pro` for the variables, noting that here everything is saved on the stack rather than as a separate variable. Once all of that is done, the actual clipping is trivial.

```

27904 \cs_new_protected:Npn \driver_box_use_clip:N #1
27905 {
27906   \__driver_scope_begin:
27907   \__driver_align_currentpoint_begin:
27908   \__driver_literal_postscript:n { matrix~currentmatrix }
27909   \__driver_literal_postscript:n
27910     { Resolution~72~div~VResolution~72~div~scale }
27911   \__driver_literal_postscript:n { DVIImag~dup~scale }
27912   \__driver_literal_postscript:x
27913     {
27914       0 ~
27915       \dim_to_decimal_in_bp:n { \box_dp:N #1 } ~
27916       \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
27917       \dim_to_decimal_in_bp:n { -\box_ht:N #1 - \box_dp:N #1 } ~
27918       rectclip
27919     }
27920   \__driver_literal_postscript:n { setmatrix }
27921   \__driver_align_currentpoint_end:
27922   \hbox_overlap_right:n { \box_use:N #1 }
27923   \__driver_scope_end:
27924   \skip_horizontal:n { \box_wd:N #1 }
27925 }

```

(End definition for `\driver_box_use_clip:N`. This function is documented on page 259.)

`\driver_box_use_rotate:Nn` Rotating using `dvips` does not require that the box dimensions are altered and has a very convenient built-in operation. Zero rotation must be written as 0 not -0 so there is a quick test.

`__driver_box_use_rotate:Nn`

```

27926 \cs_new_protected:Npn \driver_box_use_rotate:Nn #1#2
27927 { \exp_args:NNf \__driver_box_use_rotate:Nn #1 { \fp_eval:n {#2} } }
27928 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
27929 {
27930   \__driver_scope_begin:
27931   \__driver_align_currentpoint_begin:
27932   \__driver_literal_postscript:x
27933     {
27934       \fp_compare:nNnTF {#2} = \c_zero_fp
27935       { 0 }
27936       { \fp_eval:n { round ( -(#2) , 5 ) } } ~
27937       rotate
27938     }
27939   \__driver_align_currentpoint_end:
27940   \box_use:N #1
27941   \__driver_scope_end:
27942 }

```

(End definition for `\driver_box_use_rotate:Nn` and `__driver_box_use_rotate:Nn`. This function is documented on page 260.)

`\driver_box_use_scale:Nnn` The dvips driver once again has a dedicated operation we can use here.

```

27943 \cs_new_protected:Npn \driver_box_use_scale:Nnn #1#2#3
27944 {
27945   \__driver_scope_begin:
27946   \__driver_align_currentpoint_begin:
27947   \__driver_literal_postscript:x
27948   {
27949     \fp_eval:n { round ( #2 , 5 ) } ~
27950     \fp_eval:n { round ( #3 , 5 ) } ~
27951     scale
27952   }
27953   \__driver_align_currentpoint_end:
27954   \hbox_overlap_right:n { \box_use:N #1 }
27955   \__driver_scope_end:
27956 }

```

(End definition for `\driver_box_use_scale:Nnn`. This function is documented on page 260.)

45.2.3 Images

`__driver_image_getbb_eps:n` Simply use the generic function.

```

27957 \cs_new_eq:NN \__driver_image_getbb_eps:n \image_read_bb:n

```

(End definition for `__driver_image_getbb_eps:n`.)

`__driver_image_include_eps:n` The special syntax is relatively clear here: remember we need PostScript sizes here.

```

27958 \cs_new_protected:Npn \__driver_image_include_eps:n #1
27959 { \__driver_literal:n { PSfile = #1 } }

```

(End definition for `__driver_image_include_eps:n`.)

45.2.4 Drawing

`__driver_draw_literal:n` The same as literal PostScript: same arguments about positioning apply her.

```

\__driver_draw_literal:x
27960 \cs_new_eq:NN \__driver_draw_literal:n \__driver_literal_postscript:n
27961 \cs_generate_variant:Nn \__driver_draw_literal:n { x }

```

(End definition for `__driver_draw_literal:n`.)

`\driver_draw_begin:` The `ps::[begin]` special here deals with positioning but allows us to continue on to a matching `ps::[end]`: contrast with `ps:`, which positions but where we can't split material between separate calls. The `@beginspecial/@endspecial` pair are from `special.pro` and correct the scale and *y*-axis direction. The definition of `/l3fc` deals with fill color in paths. In contrast to `pgf`, we don't save the current point: discussion with Tom Rokici suggested a better way to handle the necessary translations (see `\driver_draw_box_use:Nnnnn`). (Note that `@beginspecial/@endspecial` forms a driver scope.) The `[begin]/[end]` lines are handled differently from the rest as they are conceptually different: not really drawing literals but instructions to dvips itself.

```

27962 \cs_new_protected:Npn \driver_draw_begin:
27963 {
27964   \__driver_literal:n { ps::[begin] }
27965   \__driver_draw_literal:n { @beginspecial }
27966   \__driver_draw_literal:n { /l3fc~{ }~def }
27967 }

```

```

27968 \cs_new_protected:Npn \driver_draw_end:
27969 {
27970   \__driver_draw_literal:n { @endspecial }
27971   \__driver_literal:n { ps::[end] }
27972 }

```

(End definition for \driver_draw_begin: and \driver_draw_end:. These functions are documented on page 261.)

\driver_draw_scope_begin: Scope here may need to contain saved definitions, so the entire memory rather than just the graphic state has to be sent to the stack.

```

27973 \cs_new_protected:Npn \driver_draw_scope_begin:
27974 { \__driver_draw_literal:n { save } }
27975 \cs_new_protected:Npn \driver_draw_scope_end:
27976 { \__driver_draw_literal:n { restore } }

```

(End definition for \driver_draw_scope_begin: and \driver_draw_scope_end:. These functions are documented on page 261.)

\driver_draw_moveto:nn Path creation operations mainly resolve directly to PostScript primitive steps, with only the need to convert to bp. Notice that x-type expansion is included here to ensure that any variable values are forced to literals before any possible caching. There is no native rectangular path command (without also clipping, filling or stroking), so that task is done using a small amount of PostScript.

```

27977 \cs_new_protected:Npn \driver_draw_moveto:nn #1#2
27978 {
27979   \__driver_draw_literal:x
27980   {
27981     \dim_to_decimal_in_bp:n {#1} ~
27982     \dim_to_decimal_in_bp:n {#2} ~ moveto
27983   }
27984 }
27985 \cs_new_protected:Npn \driver_draw_lineto:nn #1#2
27986 {
27987   \__driver_draw_literal:x
27988   {
27989     \dim_to_decimal_in_bp:n {#1} ~
27990     \dim_to_decimal_in_bp:n {#2} ~ lineto
27991   }
27992 }
27993 \cs_new_protected:Npn \driver_draw_rectangle:nnnn #1#2#3#4
27994 {
27995   \__driver_draw_literal:x
27996   {
27997     \dim_to_decimal_in_bp:n {#4} ~ \dim_to_decimal_in_bp:n {#3} ~
27998     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~
27999     moveto~dup~0~rlineto~exch~0~exch~rlineto~neg~0~rlineto~closepath
28000   }
28001 }
28002 \cs_new_protected:Npn \driver_draw_curveto:nnnnnn #1#2#3#4#5#6
28003 {
28004   \__driver_draw_literal:x
28005   {
28006     \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~

```

```

28007         \dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~
28008         \dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~
28009         curveto
28010     }
28011 }

```

(End definition for `\driver_draw_moveto:nn` and others. These functions are documented on page 261.)

`\driver_draw_evenodd_rule:` The even-odd rule here can be implemented as a simply switch.

```

\driver_draw_nonzero_rule:
  \g__driver_draw_eor_bool
28012 \cs_new_protected:Npn \driver_draw_evenodd_rule:
28013 { \bool_gset_true:N \g__driver_draw_eor_bool }
28014 \cs_new_protected:Npn \driver_draw_nonzero_rule:
28015 { \bool_gset_false:N \g__driver_draw_eor_bool }
28016 \bool_new:N \g__driver_draw_eor_bool

```

(End definition for `\driver_draw_evenodd_rule:`, `\driver_draw_nonzero_rule:`, and `\g__driver_draw_eor_bool`. These functions are documented on page 262.)

`\driver_draw_closepath:` Unlike PDF, PostScript doesn't track separate colors for strokes and other elements. It is also desirable to have the `clip` keyword after a stroke or fill. To achieve those outcomes, there is some work to do. For color, the stroke color is simple but the fill one has to be inserted by hand. For clipping, the required ordering is achieved using a `TEX` switch.

`\driver_draw_fillstroke:` All of the operations end with a new path instruction as they do not terminate (again in contrast to PDF).

`\driver_draw_clip:`

```

\driver_draw_discardpath:
\g__driver_draw_clip_bool
28017 \cs_new_protected:Npn \driver_draw_closepath:
28018 { \__driver_draw_literal:n { closepath } }
28019 \cs_new_protected:Npn \driver_draw_stroke:
28020 {
28021   \__driver_draw_literal:n { stroke }
28022   \bool_if:NT \g__driver_draw_clip_bool
28023   {
28024     \__driver_draw_literal:x
28025     {
28026       \bool_if:NT \g__driver_draw_eor_bool { eo }
28027       clip
28028     }
28029   }
28030   \__driver_draw_literal:n { newpath }
28031   \bool_gset_false:N \g__driver_draw_clip_bool
28032 }
28033 \cs_new_protected:Npn \driver_draw_closestroke:
28034 {
28035   \driver_draw_closepath:
28036   \driver_draw_stroke:
28037 }
28038 \cs_new_protected:Npn \driver_draw_fill:
28039 {
28040   \__driver_draw_literal:n { gsave }
28041   \__driver_draw_literal:n { l3fc }
28042   \__driver_draw_literal:x
28043   {
28044     \bool_if:NT \g__driver_draw_eor_bool { eo }
28045     fill
28046   }

```

```

28047 \__driver_draw_literal:n { grestore }
28048 \bool_if:NT \g__driver_draw_clip_bool
28049 {
28050   \__driver_draw_literal:x
28051   {
28052     \bool_if:NT \g__driver_draw_eor_bool { eo }
28053     clip
28054   }
28055 }
28056 \__driver_draw_literal:n { newpath }
28057 \bool_gset_false:N \g__driver_draw_clip_bool
28058 }
28059 \cs_new_protected:Npn \driver_draw_fillstroke:
28060 {
28061   \__driver_draw_literal:n { gsave }
28062   \__driver_draw_literal:n { l3fc }
28063   \__driver_draw_literal:x
28064   {
28065     \bool_if:NT \g__driver_draw_eor_bool { eo }
28066     fill
28067   }
28068   \__driver_draw_literal:n { grestore }
28069   \__driver_draw_literal:n { stroke }
28070   \bool_if:NT \g__driver_draw_clip_bool
28071   {
28072     \__driver_draw_literal:x
28073     {
28074       \bool_if:NT \g__driver_draw_eor_bool { eo }
28075       clip
28076     }
28077   }
28078   \__driver_draw_literal:n { newpath }
28079   \bool_gset_false:N \g__driver_draw_clip_bool
28080 }
28081 \cs_new_protected:Npn \driver_draw_clip:
28082 { \bool_gset_true:N \g__driver_draw_clip_bool }
28083 \bool_new:N \g__driver_draw_clip_bool
28084 \cs_new_protected:Npn \driver_draw_discardpath:
28085 {
28086   \bool_if:NT \g__driver_draw_clip_bool
28087   {
28088     \__driver_draw_literal:x
28089     {
28090       \bool_if:NT \g__driver_draw_eor_bool { eo }
28091       clip
28092     }
28093   }
28094   \__driver_draw_literal:n { newpath }
28095   \bool_gset_false:N \g__driver_draw_clip_bool
28096 }

```

(End definition for \driver_draw_closepath: and others. These functions are documented on page 261.)

\driver_draw_dash_pattern:nn Converting paths to output is again a case of mapping directly to PostScript operations.

```

\__driver_draw_dash:n
\driver_draw_linewidth:n
\driver_draw_miterlimit:n
\driver_draw_cap_butt:
\driver_draw_cap_round:
\driver_draw_cap_rectangle:
\driver_draw_join_miter:
\driver_draw_join_round:
\driver_draw_join_bevel:

```

```

28097 \cs_new_protected:Npn \driver_draw_dash_pattern:nn #1#2
28098 {
28099   \__driver_draw_literal:x
28100   {
28101     [
28102       \exp_args:Nf \use:n
28103       { \clist_map_function:nN {#1} \__driver_draw_dash:n }
28104     ] ~
28105     \dim_to_decimal_in_bp:n {#2} ~ setdash
28106   }
28107 }
28108 \cs_new:Npn \__driver_draw_dash:n #1
28109 { ~ \dim_to_decimal_in_bp:n {#1} }
28110 \cs_new_protected:Npn \driver_draw_linewidth:n #1
28111 {
28112   \__driver_draw_literal:x
28113   { \dim_to_decimal_in_bp:n {#1} ~ setlinewidth }
28114 }
28115 \cs_new_protected:Npn \driver_draw_miterlimit:n #1
28116 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ setmiterlimit } }
28117 \cs_new_protected:Npn \driver_draw_cap_but:
28118 { \__driver_draw_literal:n { 0 ~ setlinecap } }
28119 \cs_new_protected:Npn \driver_draw_cap_round:
28120 { \__driver_draw_literal:n { 1 ~ setlinecap } }
28121 \cs_new_protected:Npn \driver_draw_cap_rectangle:
28122 { \__driver_draw_literal:n { 2 ~ setlinecap } }
28123 \cs_new_protected:Npn \driver_draw_join_miter:
28124 { \__driver_draw_literal:n { 0 ~ setlinejoin } }
28125 \cs_new_protected:Npn \driver_draw_join_round:
28126 { \__driver_draw_literal:n { 1 ~ setlinejoin } }
28127 \cs_new_protected:Npn \driver_draw_join_bevel:
28128 { \__driver_draw_literal:n { 2 ~ setlinejoin } }

```

(End definition for \driver_draw_dash_pattern:nn and others. These functions are documented on page 263.)

\driver_draw_color_fill_cmyk:nmmn For dvips, we can use the standard color stack to deal with stroke color, but for fills have to switch to raw PostScript. This is thus not handled by the stack, but the context is very restricted. See also how fills are implemented.

```

\driver_draw_color_stroke_cmyk:nmmn
\driver_draw_color_fill_gray:n
\driver_draw_color_stroke_gray:n
\driver_draw_color_fill_rgb:nmmn
\driver_draw_color_stroke_rgb:nmmn
\__driver_draw_color_fill:n
\__driver_draw_color_fill:x
\__driver_draw_color_stroke:n
\__driver_draw_color_stroke:x
28129 \cs_new_protected:Npn \driver_draw_color_fill_cmyk:nnnn #1#2#3#4
28130 {
28131   \__driver_draw_color_fill:x
28132   {
28133     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
28134     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
28135     setcmykcolor
28136   }
28137 }
28138 \cs_new_protected:Npn \driver_draw_color_stroke_cmyk:nnnn #1#2#3#4
28139 {
28140   \__driver_draw_color_stroke:x
28141   {
28142     cmyk ~
28143     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~

```

```

28144     \fp_eval:n {#3} ~ \fp_eval:n {#4}
28145   }
28146 }
28147 \cs_new_protected:Npn \driver_draw_color_fill_gray:n #1
28148 { \__driver_draw_color_fill:x { \fp_eval:n {#1} ~ setgray } }
28149 \cs_new_protected:Npn \driver_draw_color_stroke_gray:n #1
28150 { \__driver_draw_color_stroke:x { gray ~ \fp_eval:n {#1} } }
28151 \cs_new_protected:Npn \driver_draw_color_fill_rgb:nnn #1#2#3
28152 {
28153   \__driver_draw_color_fill:x
28154   { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ setrgbcolor }
28155 }
28156 \cs_new_protected:Npn \driver_draw_color_stroke_rgb:nnn #1#2#3
28157 {
28158   \__driver_draw_color_stroke:x
28159   { rgb ~ \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} }
28160 }
28161 \cs_new_protected:Npn \__driver_draw_color_fill:n #1
28162 { \__driver_draw_literal:n { /l3fc ~ { #1 } ~ def } }
28163 \cs_generate_variant:Nn \__driver_draw_color_fill:n { x }
28164 \cs_new_protected:Npn \__driver_draw_color_stroke:n #1
28165 {
28166   \__driver_literal:n { color-push-#1 }
28167   \group_insert_after:N \__driver_color_reset:
28168 }
28169 \cs_generate_variant:Nn \__driver_draw_color_stroke:n { x }

```

(End definition for `\driver_draw_color_fill_cmyk:nnnn` and others. These functions are documented on page 263.)

`\driver_draw_cm:nnnn` In dvips, keeping the transformations in line with the engine is unfortunately not possible for scaling and rotations: even if we decompose the matrix into those operations, there is still no driver tracking (cf. (x)dvipdfmx). Thus we take the shortest path available and simply dump the matrix as given.

```

28170 \cs_new_protected:Npn \driver_draw_cm:nnnn #1#2#3#4
28171 {
28172   \__driver_draw_literal:n
28173   {
28174     [
28175       \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
28176       \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
28177       0 ~ 0
28178     ] ~
28179     concat
28180   }
28181 }

```

(End definition for `\driver_draw_cm:nnnn`. This function is documented on page 264.)

`\driver_draw_box_use:Nnnnn` Inside a picture `@beginspecial/@endspecial` are active, which is normally a good thing but means that the position and scaling would be off if the box was inserted directly. To deal with that, there are a number of possible approaches. The implementation here was suggested by Tom Rokici (author of dvips). We end the current special placement, then set the current point with a literal `[begin]`. As for general literals, we then use the stack

to store the current point and move to it. To insert the required transformation, we have to flip the y -axis, once before and once after it. Then we get back to the \TeX reference point to insert our content. The clean up has to happen in the right places, hence the `[begin]/[end]` pair around `restore`. Finally, we can return to “normal” drawing mode. Notice that the set up here is very similar to that in `__driver_align_currentpoint_...`, but the ordering of saving and restoring is different (intermixed).

```

28182 \cs_new_protected:Npn \driver_draw_box_use:Nnnnn #1#2#3#4#5
28183 {
28184   \__driver_draw_literal:n { @endspecial }
28185   \__driver_draw_literal:n { [end] }
28186   \__driver_draw_literal:n { [begin] }
28187   \__driver_draw_literal:n { save }
28188   \__driver_draw_literal:n { currentpoint }
28189   \__driver_draw_literal:n { currentpoint~translate }
28190   \driver_draw_cm:nnnn { 1 } { 0 } { 0 } { -1 }
28191   \driver_draw_cm:nnnn { #2 } { #3 } { #4 } { #5 }
28192   \driver_draw_cm:nnnn { 1 } { 0 } { 0 } { -1 }
28193   \__driver_draw_literal:n { neg~exch~neg~exch~translate }
28194   \__driver_draw_literal:n { [end] }
28195   \hbox_overlap_right:n { \box_use:N #1 }
28196   \__driver_draw_literal:n { [begin] }
28197   \__driver_draw_literal:n { restore }
28198   \__driver_draw_literal:n { [end] }
28199   \__driver_draw_literal:n { [begin] }
28200   \__driver_draw_literal:n { @beginspecial }
28201 }

```

(End definition for `\driver_draw_box_use:Nnnnn`. This function is documented on page 264.)

45.2.5 PDF Features

`\g__driver_pdf_object_int`
`\g__driver_pdf_object_prop`

For tracking objects to allow finalisation.

```

28202 \int_new:N \g__driver_pdf_object_int
28203 \prop_new:N \g__driver_pdf_object_prop

```

(End definition for `\g__driver_pdf_object_int` and `\g__driver_pdf_object_prop`.)

`\driver_pdf_object_new:nn`
`\driver_pdf_object_ref:n`

Tracking objects is similar to `dvipdfmx`.

```

28204 \cs_new_protected:Npn \driver_pdf_object_new:nn #1#2
28205 {
28206   \int_gincr:N \g__driver_pdf_object_int
28207   \int_const:cn
28208     { g__driver_pdf_object_ \tl_to_str:n {#1} _int }
28209     { \g__driver_pdf_object_int }
28210   \prop_gput:Nnn \g__driver_pdf_object_prop {#1} {#2}
28211 }
28212 \cs_new:Npn \driver_pdf_object_ref:n #1
28213 { { l3obj \int_use:c { g__driver_pdf_object_ \tl_to_str:n {#1} _int } } }

```

(End definition for `\driver_pdf_object_new:nn` and `\driver_pdf_object_ref:n`. These functions are documented on page 264.)

\driver_pdf_object_write:nn

This is where we choose the actual type: some work to get things right.

```
\_driver_pdf_object_write_array:nn 28214 \cs_new_protected:Npn \driver_pdf_object_write:nn #1#2
\_driver_pdf_object_write_dict:nn 28215 {
\_driver_pdf_object_write_stream:nn 28216 \__driver_literal_postscript:x
\_driver_pdf_object_write_stream:nnn 28217 {
28218   mark ~ /_objdef ~ \driver_pdf_object_ref:n {#1} ~
28219   /type
28220   \str_case_e:nn
28221   { \prop_item:Nn \g__driver_pdf_object_prop {#1} }
28222   {
28223     { array } { /array }
28224     { dict } { /dict }
28225     { fstream } { /stream }
28226     { stream } { /stream }
28227   }
28228   /OBJ ~ pdfmark
28229 }
28230 \use:c
28231 { \__driver_pdf_object_write_ \prop_item:Nn \g__driver_pdf_object_prop {#1} :nn }
28232 {#1} {#2}
28233 }
28234 \cs_new_protected:Npn \__driver_pdf_object_write_array:nn #1#2
28235 {
28236   \__driver_literal_postscript:x
28237   {
28238     mark ~ \driver_pdf_object_ref:n {#1} ~
28239     [ ~ \exp_not:n {#2} ~ ] ~ /PUTINTERVAL ~ pdfmark
28240   }
28241 }
28242 \cs_new_protected:Npn \__driver_pdf_object_write_dict:nn #1#2
28243 {
28244   \__driver_literal_postscript:x
28245   {
28246     mark ~ \driver_pdf_object_ref:n {#1} ~
28247     << ~ \exp_not:n {#2} ~ >> ~ /PUT ~ pdfmark
28248   }
28249 }
28250 \cs_new_protected:Npn \__driver_pdf_object_write_stream:nn #1#2
28251 {
28252   \exp_args:Nx
28253   \__driver_pdf_object_write_stream:nnn
28254   { \driver_pdf_object_ref:n {#1} }
28255   #2
28256 }
28257 \cs_new_protected:Npn \__driver_pdf_object_write_stream:nnn #1#2#3
28258 {
28259   \__driver_literal_postscript:n
28260   {
28261     [nobreak] ~
28262     mark ~ #1 ~ ( #3 ) ~ /PUT ~ pdfmark ~
28263     mark ~ #1 ~ << #2 >> ~ /PUT ~ pdfmark
28264   }
28265 }
```


(End definition for `\driver_pdf_object_write:n` and others. This function is documented on page 265.)

```

\driver_pdf_compresslevel:n These are all no-ops.
\driver_pdf_objects_enable: 28266 \cs_new_protected:Npn \driver_pdf_compresslevel:n #1 { }
\driver_pdf_objects_disable: 28267 \cs_new_protected:Npn \driver_pdf_objects_enable: { }
                             28268 \cs_new_protected:Npn \driver_pdf_objects_disable: { }

```

(End definition for `\driver_pdf_compresslevel:n`, `\driver_pdf_objects_enable:`, and `\driver_pdf_objects_disable:`. These functions are documented on page 265.)

```
28269 \</dvips>
```

45.3 pdfmode driver

```
28270 \*pdfmode>
```

The direct PDF driver covers both pdfTeX and LuaTeX. The latter renames and restructures the driver primitives but this can be handled at one level of abstraction. As such, we avoid using two separate drivers for this material at the cost of some x-type definitions to get everything expanded up-front.

45.3.1 Basics

```

\__driver_literal_pdf:n This is equivalent to \special{pdf:} but the engine can track it. Without the direct
\__driver_literal_pdf:x keyword everything is kept in sync: the transformation matrix is set to the current point
                        automatically. Note that this is still inside the text (BT ...ET block).

```

```

28271 \cs_new_protected:Npx \__driver_literal_pdf:n #1
28272 {
28273   \cs_if_exist:NTF \tex_pdfextension:D
28274     { \tex_pdfextension:D literal }
28275     { \tex_pdfliteral:D }
28276     { \exp_not:N \exp_not:n {#1} }
28277 }
28278 \cs_generate_variant:Nn \__driver_literal_pdf:n { x }

```

(End definition for `__driver_literal_pdf:n`.)

```

\__driver_scope_begin: Higher-level interfaces for saving and restoring the graphic state.
\__driver_scope_end:

```

```

28279 \cs_new_protected:Npx \__driver_scope_begin:
28280 {
28281   \cs_if_exist:NTF \tex_pdfextension:D
28282     { \tex_pdfextension:D save \scan_stop: }
28283     { \tex_pdfsave:D }
28284 }
28285 \cs_new_protected:Npx \__driver_scope_end:
28286 {
28287   \cs_if_exist:NTF \tex_pdfextension:D
28288     { \tex_pdfextension:D restore \scan_stop: }
28289     { \tex_pdfrestore:D }
28290 }

```

(End definition for `__driver_scope_begin:` and `__driver_scope_end:`.)

`_driver_matrix:n` Here the appropriate function is set up to insert an affine matrix into the PDF. With
`_driver_matrix:x` pdfTeX and LuaTeX in direct PDF output mode there is a primitive for this, which only
needs the rotation/scaling/skew part.

```

28291 \cs_new_protected:Npx \_driver_matrix:n #1
28292 {
28293   \cs_if_exist:NTF \tex_pdfextension:D
28294     { \tex_pdfextension:D setmatrix }
28295     { \tex_pdfsetmatrix:D }
28296     { \exp_not:N \exp_not:n {#1} }
28297 }
28298 \cs_generate_variant:Nn \_driver_matrix:n { x }

```

(End definition for `_driver_matrix:n`.)

45.3.2 Box operations

`\driver_box_use_clip:N` The general method is to save the current location, define a clipping path equivalent to
the bounding box, then insert the content at the current position and in a zero width box.
The “real” width is then made up using a horizontal skip before tidying up. There are
other approaches that can be taken (for example using XForm objects), but the logic here
shares as much code as possible and uses the same conversions (and so same rounding
errors) in all cases.

```

28299 \cs_new_protected:Npn \driver_box_use_clip:N #1
28300 {
28301   \_driver_scope_begin:
28302   \_driver_literal_pdf:x
28303   {
28304     0~
28305     \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
28306     \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
28307     \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
28308     re~W~n
28309   }
28310   \hbox_overlap_right:n { \box_use:N #1 }
28311   \_driver_scope_end:
28312   \skip_horizontal:n { \box_wd:N #1 }
28313 }

```

(End definition for `\driver_box_use_clip:N`. This function is documented on page 259.)

`\driver_box_use_rotate:Nn` Rotations are set using an affine transformation matrix which therefore requires
`_driver_box_use_rotate:Nn` sine/cosine values not the angle itself. We store the rounded values to avoid round-
`\l__driver_cos_fp` ing twice. There are also a couple of comparisons to ensure that -0 is not written to the
`\l__driver_sin_fp` output, as this avoids any issues with problematic display programs. Note that numbers
are compared to 0 after rounding.

```

28314 \cs_new_protected:Npn \driver_box_use_rotate:Nn #1#2
28315 { \exp_args:Nnf \_driver_box_use_rotate:Nn #1 { \fp_eval:n {#2} } }
28316 \cs_new_protected:Npn \_driver_box_use_rotate:Nn #1#2
28317 {
28318   \_driver_scope_begin:
28319   \box_set_wd:Nn #1 { Opt }
28320   \fp_set:Nn \l__driver_cos_fp { round ( cosd ( #2 ) , 5 ) }
28321   \fp_compare:nNnT \l__driver_cos_fp = \c_zero_fp

```

```

28322     { \fp_zero:N \l__driver_cos_fp }
28323 \fp_set:Nn \l__driver_sin_fp { round ( sind ( #2 ) , 5 ) }
28324 \__driver_matrix:x
28325 {
28326   \fp_use:N \l__driver_cos_fp \c_space_tl
28327   \fp_compare:nNnTF \l__driver_sin_fp = \c_zero_fp
28328     { 0~0 }
28329     {
28330       \fp_use:N \l__driver_sin_fp
28331       \c_space_tl
28332       \fp_eval:n { -\l__driver_sin_fp }
28333     }
28334   \c_space_tl
28335   \fp_use:N \l__driver_cos_fp
28336 }
28337 \box_use:N #1
28338 \__driver_scope_end:
28339 }
28340 \fp_new:N \l__driver_cos_fp
28341 \fp_new:N \l__driver_sin_fp

```

(End definition for `\driver_box_use_rotate:Nn` and others. This function is documented on page 260.)

`\driver_box_use_scale:Nnn` The same idea as for rotation but without the complexity of signs and cosines.

```

28342 \cs_new_protected:Npn \driver_box_use_scale:Nnn #1#2#3
28343 {
28344   \__driver_scope_begin:
28345   \__driver_matrix:x
28346   {
28347     \fp_eval:n { round ( #2 , 5 ) } ~
28348     0~0~
28349     \fp_eval:n { round ( #3 , 5 ) }
28350   }
28351   \hbox_overlap_right:n { \box_use:N #1 }
28352   \__driver_scope_end:
28353 }

```

(End definition for `\driver_box_use_scale:Nnn`. This function is documented on page 260.)

45.3.3 Images

`\l__driver_image_attr_tl` In PDF mode, additional attributes of an image (such as page number) are needed both to obtain the bounding box and when inserting the image: this occurs as the image dictionary approach means they are read as part of the bounding box operation. As such, it is easier to track additional attributes using a dedicated `tl` rather than build up the same data twice.

```

28354 \tl_new:N \l__driver_image_attr_tl

```

(End definition for `\l__driver_image_attr_tl`.)

`__driver_image_getbb_jpg:n`
`__driver_image_getbb_pdf:n`
`__driver_image_getbb_png:n`
`__driver_image_getbb_auxi:n`
`__driver_image_getbb_auxii:n`

Getting the bounding box here requires us to box up the image and measure it. To deal with the difference in feature support in bitmap and vector images but keeping the common parts, there is a little work to do in terms of auxiliaries. The key here is to

notice that we need two forms of the attributes: a “short” set to allow us to track for caching, and the full form to pass to the primitive.

```

28355 \cs_new_protected:Npn \__driver_image_getbb_jpg:n #1
28356 {
28357   \int_zero:N \l_image_page_int
28358   \tl_clear:N \l_image_pagebox_tl
28359   \tl_set:Nx \l__driver_image_attr_tl
28360   {
28361     \tl_if_empty:NF \l_image_decode_tl
28362     { :D \l_image_decodearray_tl }
28363     \bool_if:NT \l_image_interpolate_bool
28364     { :I }
28365   }
28366   \tl_clear:N \l__driver_image_attr_tl
28367   \__driver_image_getbb_auxi:n {#1}
28368 }
28369 \cs_new_eq:NN \__driver_image_getbb_png:n \__driver_image_getbb_jpg:n
28370 \cs_new_protected:Npn \__driver_image_getbb_pdf:n #1
28371 {
28372   \tl_clear:N \l_image_decode_tl
28373   \bool_set_false:N \l_image_interpolate_bool
28374   \tl_set:Nx \l__driver_image_attr_tl
28375   {
28376     : \l_image_pagebox_tl
28377     \int_compare:nNnT \l_image_page_int > 1
28378     { :P \int_use:N \l_image_page_int }
28379   }
28380   \__driver_image_getbb_auxi:n {#1}
28381 }
28382 \cs_new_protected:Npn \__driver_image_getbb_auxi:n #1
28383 {
28384   \image_bb_restore:xF { #1 \l__driver_image_attr_tl }
28385   { \__driver_image_getbb_auxii:n {#1} }
28386 }
28387 % \begin{macrocode}
28388 % Measuring the image is done by boxing up: for PDF images we could
28389 % use |\tex_pdfximagebbox:D|, but if doesn't work for other types.
28390 % As the box always starts at $(0,0)$ there is no need to worry about
28391 % the lower-left position.
28392 % \begin{macrocode}
28393 \cs_new_protected:Npn \__driver_image_getbb_auxii:n #1
28394 {
28395   \tex_immediate:D \tex_pdfximage:D
28396   \bool_lazy_or:nnT
28397   { \l_image_interpolate_bool }
28398   { ! \tl_if_empty_p:N \l_image_decodearray_tl }
28399   {
28400     attr ~
28401     {
28402       \tl_if_empty:NF \l_image_decode_tl
28403       { /Decode~[ \l_image_decodearray_tl ] }
28404       \bool_if:NT \l_image_interpolate_bool
28405       { /Interpolate~true }
28406     }

```

```

28407     }
28408     \int_compare:nNnT \l_image_page_int > 0
28409     { page ~ \int_use:N \l_image_page_int }
28410     \tl_if_empty:NF \l_image_pagebox_tl
28411     { \l_image_pagebox_tl }
28412     {#1}
28413     \hbox_set:Nn \l__driver_tmp_box
28414     { \tex_pdfrefximage:D \tex_pdflastximage:D }
28415     \dim_set:Nn \l_image_urx_dim { \box_wd:N \l__driver_tmp_box }
28416     \dim_set:Nn \l_image_ury_dim { \box_ht:N \l__driver_tmp_box }
28417     \int_const:cn { c__driver_image_ #1 \l__driver_image_attr_tl _int }
28418     { \tex_the:D \tex_pdflastximage:D }
28419     \image_bb_save:x { #1 \l__driver_image_attr_tl }
28420 }

```

(End definition for `__driver_image_getbb_jpg:n` and others.)

`__driver_image_include_jpg:n` Images are already loaded for the measurement part of the code, so inclusion is straightforward, with only any attributes to worry about. The latter carry through from determination of the bounding box.

```

28421 \cs_new_protected:Npn \__driver_image_include_jpg:n #1
28422 {
28423     \tex_pdfrefximage:D
28424     \int_use:c { c__driver_image_ #1 \l__driver_image_attr_tl _int }
28425 }
28426 \cs_new_eq:NN \__driver_image_include_pdf:n \__driver_image_include_jpg:n
28427 \cs_new_eq:NN \__driver_image_include_png:n \__driver_image_include_jpg:n

```

(End definition for `__driver_image_include_jpg:n`, `__driver_image_include_pdf:n`, and `__driver_image_include_png:n`.)

45.3.4 PDF Objects

`\g__driver_pdf_object_prop` For tracking objects to allow finalisation.

```

28428 \prop_new:N \g__driver_pdf_object_prop

```

(End definition for `\g__driver_pdf_object_prop`.)

`\driver_pdf_object_new:nn` Declaring objects means reserving at the PDF level plus starting tracking.

`\driver_pdf_object_ref:n`

```

28429 \group_begin:
28430 \cs_set_protected:Npn \__driver_tmp:w #1#2
28431 {
28432     \cs_new_protected:Npx \driver_pdf_object_new:nn ##1##2
28433     {
28434         #1 reserveobjnum ~
28435         \int_const:cn
28436         { g__driver_pdf_object_ \exp_not:N \tl_to_str:n {##1} _int }
28437         {#2}
28438         \prop_gput:Nnn \exp_not:N \g__driver_pdf_object_prop {##1} {##2}
28439     }
28440 }
28441 \cs_if_exist:NTF \tex_pdfextension:D
28442 {
28443     \__driver_tmp:w

```

```

28444 { \tex_pdfextension:D obj ~ }
28445 { \tex_pdffeedback:D lastobj \scan_stop: }
28446 }
28447 { \__driver_tmp:w { \tex_pdfobj:D } { \tex_pdflastobj:D } }
28448 \group_end:
28449 \cs_new:Npn \driver_pdf_object_ref:n #1
28450 { \int_use:c { g__driver_pdf_object_ \tl_to_str:n {#1} _int } ~ 0 ~ R }

```

(End definition for \driver_pdf_object_new:nn and \driver_pdf_object_ref:n. These functions are documented on page 264.)

\driver_pdf_object_write:nn Writing the data needs a little information about the structure of the object.

```

\__driver_exp_not_i:nn
\__driver_exp_not_ii:nn
28451 \group_begin:
28452 \cs_set_protected:Npn \__driver_tmp:w #1
28453 {
28454   \cs_new_protected:Npn \driver_pdf_object_write:nn ##1##2
28455   {
28456     \tex_immediate:D #1 useobjnum ~
28457     \int_use:c
28458     { g__driver_pdf_object_ \tl_to_str:n {##1} _int }
28459     \str_case_e:nn
28460     { \prop_item:Nn \g__driver_pdf_object_prop {##1} }
28461     {
28462       { array } { { [ ~ \exp_not:n {##2} ~ ] } }
28463       { dict } { { << ~ \exp_not:n {##2} ~ >> } }
28464       { fstream }
28465       {
28466         stream ~ attr ~ { \__driver_exp_not_i:nn ##2 } ~
28467         file ~ { \__driver_exp_not_ii:nn ##2 }
28468       }
28469       { stream }
28470       {
28471         stream ~ attr ~ { \__driver_exp_not_i:nn ##2 } ~
28472         { \__driver_exp_not_ii:nn ##2 }
28473       }
28474     }
28475   }
28476 }
28477 \cs_if_exist:NTF \tex_pdfextension:D
28478 { \__driver_tmp:w { \tex_pdfextension:D obj ~ } }
28479 { \__driver_tmp:w { \tex_pdfobj:D } }
28480 \group_end:
28481 \cs_new:Npn \__driver_exp_not_i:nn #1#2 { \exp_not:n {#1} }
28482 \cs_new:Npn \__driver_exp_not_ii:nn #1#2 { \exp_not:n {#2} }

```

(End definition for \driver_pdf_object_write:nn, __driver_exp_not_i:nn, and __driver_exp_not_ii:nn. This function is documented on page 265.)

45.3.5 PDF Structure

\driver_pdf_compresslevel:n Simply pass data to the engine.

```

\driver_pdf_objects_enable:
\driver_pdf_objects_disable:
\__driver_pdf_objectlevel:n
28483 \cs_new_protected:Npx \driver_pdf_compresslevel:n #1
28484 {
28485   \cs_if_exist:NTF \tex_pdfcompresslevel:D
28486   { \tex_pdfcompresslevel:D }

```

```

28487     { \tex_pdfvariable:D compresslevel }
28488     \exp_not:N \int_value:w \exp_not:N \int_eval:n {#1} \scan_stop:
28489   }
28490   \cs_new_protected:Npn \driver_pdf_objects_enable:
28491     { \__driver_pdf_objectlevel:n { 2 } }
28492   \cs_new_protected:Npn \driver_pdf_objects_disable:
28493     { \__driver_pdf_objectlevel:n { 0 } }
28494   \cs_new_protected:Npx \__driver_pdf_objectlevel:n #1
28495     {
28496       \cs_if_exist:NTF \tex_pdfobjcompresslevel:D
28497         { \tex_pdfobjcompresslevel:D }
28498         { \tex_pdfvariable:D objcompresslevel }
28499       #1 \scan_stop:
28500     }

```

(End definition for `\driver_pdf_compresslevel:n` and others. These functions are documented on page 265.)

```

28501 \pdfmode

```

45.4 dvipdfmx driver

```

28502 (*dvipdfmx | xdvipdfmx)

```

The `dvipdfmx` shares code with the PDF mode one (using the common section to this file) but also with `xdvipdfmx`. The latter is close to identical to `dvipdfmx` and so all of the code here is extracted for both drivers, with some `clean up` for `xdvipdfmx` as required.

45.4.1 Basics

`__driver_literal_pdf:n` Equivalent to `pdf:content` but favored as the link to the pdfTeX primitive approach is clearer.

```

28503 \cs_new_protected:Npn \__driver_literal_pdf:n #1
28504   { \__driver_literal:n { pdf:literal~ #1 } }
28505 \cs_generate_variant:Nn \__driver_literal_pdf:n { x }

```

(End definition for `__driver_literal_pdf:n`.)

`__driver_scope_begin:` Scoping is done using the driver-specific specials.

```

\__driver_scope_end:
28506 \cs_new_protected:Npn \__driver_scope_begin:
28507   { \__driver_literal:n { x:gsave } }
28508 \cs_new_protected:Npn \__driver_scope_end:
28509   { \__driver_literal:n { x:grestore } }

```

(End definition for `__driver_scope_begin:` and `__driver_scope_end:.`)

45.4.2 Box operations

`\driver_box_use_clip:N` The code here is identical to that for `pdfmode`: unlike rotation and scaling, there is no higher-level support in the driver for clipping.

```

28510 \cs_new_protected:Npn \driver_box_use_clip:N #1
28511   {
28512     \__driver_scope_begin:
28513     \__driver_literal_pdf:x
28514     {

```

```

28515      0~
28516      \dim_to_decimal_in_bp:n { -\box_dp:N #1 } ~
28517      \dim_to_decimal_in_bp:n { \box_wd:N #1 } ~
28518      \dim_to_decimal_in_bp:n { \box_ht:N #1 + \box_dp:N #1 } ~
28519      re~W~n
28520    }
28521    \hbox_overlap_right:n { \box_use:N #1 }
28522    \__driver_scope_end:
28523    \skip_horizontal:n { \box_wd:N #1 }
28524  }

```

(End definition for `\driver_box_use_clip:N`. This function is documented on page 259.)

`\driver_box_use_rotate:Nn`
`__driver_box_use_rotate:Nn`

Rotating in (x)dvipdmtx can be implemented using either PDF or driver-specific code. The former approach however is not “aware” of the content of boxes: this means that any embedded links would not be adjusted by the rotation. As such, the driver-native approach is preferred: the code therefore is similar (though not identical) to the `dvips` version (notice the rotation angle here is positive). As for `dvips`, zero rotation is written as 0 not -0.

```

28525 \cs_new_protected:Npn \driver_box_use_rotate:Nn #1#2
28526 { \exp_args:Nnf \__driver_box_use_rotate:Nn #1 { \fp_eval:n {#2} } }
28527 \cs_new_protected:Npn \__driver_box_use_rotate:Nn #1#2
28528 {
28529   \__driver_scope_begin:
28530   \__driver_literal:x
28531   {
28532     x:rotate~
28533     \fp_compare:nNnTF {#2} = \c_zero_fp
28534       { 0 }
28535       { \fp_eval:n { round ( #2 , 5 ) } }
28536   }
28537   \box_use:N #1
28538   \__driver_scope_end:
28539 }

```

(End definition for `\driver_box_use_rotate:Nn` and `__driver_box_use_rotate:Nn`. This function is documented on page 260.)

`\driver_box_use_scale:Nnn`

Much the same idea for scaling: use the higher-level driver operation to allow for box content.

```

28540 \cs_new_protected:Npn \driver_box_use_scale:Nnn #1#2#3
28541 {
28542   \__driver_scope_begin:
28543   \__driver_literal:x
28544   {
28545     x:scale~
28546     \fp_eval:n { round ( #2 , 5 ) } ~
28547     \fp_eval:n { round ( #3 , 5 ) }
28548   }
28549   \hbox_overlap_right:n { \box_use:N #1 }
28550   \__driver_scope_end:
28551 }

```

(End definition for `\driver_box_use_scale:Nnn`. This function is documented on page 260.)

45.4.3 Images

Simply use the generic functions: only for dvipdfmx in the extraction cases.

```

28552 \cs_new_eq:NN \__driver_image_getbb_eps:n \image_read_bb:n
28553 (*dvipdfmx)
28554 \cs_new_protected:Npn \__driver_image_getbb_jpg:n #1
28555 {
28556   \int_zero:N \l_image_page_int
28557   \tl_clear:N \l_image_pagebox_tl
28558   \image_extract_bb:n {#1}
28559 }
28560 \cs_new_eq:NN \__driver_image_getbb_png:n \__driver_image_getbb_jpg:n
28561 \cs_new_protected:Npn \__driver_image_getbb_pdf:n #1
28562 {
28563   \tl_clear:N \l_image_decode_tl
28564   \bool_set_false:N \l_image_interpolate_bool
28565   \image_extract_bb:n {#1}
28566 }
28567 </dvipdfmx>

```

(End definition for __driver_image_getbb_eps:n and others.)

\g__driver_image_int Used to track the object number associated with each image.

```

28568 \int_new:N \g__driver_image_int

```

(End definition for \g__driver_image_int.)

<pre> __driver_image_include_eps:n __driver_image_include_jpg:n __driver_image_include_pdf:n __driver_image_include_png:n __driver_image_include_auxi:nn __driver_image_include_auxii:nnn __driver_image_include_auxiii:nnn </pre>	<p>The special syntax depends on the file type. There is a difference in how PDF images are best handled between dvipdfmx and xdvipdfmx: for the latter it is better to use the primitive route. The relevant code for that is included later in this file.</p> <pre> 28569 \cs_new_protected:Npn __driver_image_include_eps:n #1 28570 { 28571 __driver_literal:n { PSfile = #1 } 28572 } 28573 \cs_new_protected:Npn __driver_image_include_jpg:n #1 28574 { __driver_image_include_auxi:nn {#1} { image } } 28575 \cs_new_eq:NN __driver_image_include_png:n __driver_image_include_jpg:n 28576 (*dvipdfmx) 28577 \cs_new_protected:Npn __driver_image_include_pdf:n #1 28578 { __driver_image_include_auxi:nn {#1} { epdf } } 28579 </dvipdfmx> </pre>
---	--

Image inclusion is set up to use the fact that each image is stored in the PDF as an XObject. This means that we can include repeated images only once and refer to them. To allow that, track the nature of each image: much the same as for the direct PDF mode case.

```

28580 \cs_new_protected:Npn \__driver_image_include_auxi:nn #1#2
28581 {
28582   \__driver_image_include_auxii:nnn
28583   {
28584     \tl_if_empty:NF \l_image_pagebox_tl
28585     { : \l_image_pagebox_tl }
28586     \int_compare:nNnT \l_image_page_int > 1
28587     { :P \int_use:N \l_image_page_int }

```

```

28588         \tl_if_empty:NF \l_image_decode_tl
28589         { :D \l_image_decodearray_tl }
28590         \bool_if:NT \l_image_interpolate_bool
28591         { :I }
28592     }
28593     {#1} {#2}
28594 }
28595 \cs_new_protected:Npn \__driver_image_include_auxii:nnn #1#2#3
28596 {
28597     \int_if_exist:cTF { c__driver_image_ #2#1 _int }
28598     {
28599         \__driver_literal:x
28600         { pdf:useobj~@image \int_use:c { c__driver_image_ #2#1 _int } }
28601     }
28602     { \__driver_image_include_auxiii:nn {#2} {#1} {#3} }
28603 }
28604 \cs_generate_variant:Nn \__driver_image_include_auxii:nnn { x }

```

Inclusion using the specials is relatively straight-forward, but there is one wrinkle. To get the `pagebox` correct for PDF images in all cases, it is necessary to provide both that information and the `bbox` argument: odd things happen otherwise!

```

28605 \cs_new_protected:Npn \__driver_image_include_auxiii:nnn #1#2#3
28606 {
28607     \int_gincr:N \g__driver_image_int
28608     \int_const:cn { c__driver_image_ #1#2 _int } { \g__driver_image_int }
28609     \__driver_literal:x
28610     {
28611         pdf:#3~
28612         @image \int_use:c { c__driver_image_ #1#2 _int }
28613         \int_compare:nNnT \l_image_page_int > 1
28614         { page ~ \int_use:N \l_image_page_int \c_space_tl }
28615         \tl_if_empty:NF \l_image_pagebox_tl
28616         {
28617             pagebox ~ \l_image_pagebox_tl \c_space_tl
28618             bbox ~
28619             \dim_to_decimal_in_bp:n \l_image_llx_dim \c_space_tl
28620             \dim_to_decimal_in_bp:n \l_image_lly_dim \c_space_tl
28621             \dim_to_decimal_in_bp:n \l_image_urx_dim \c_space_tl
28622             \dim_to_decimal_in_bp:n \l_image_ury_dim \c_space_tl
28623         }
28624         (#1)
28625         \bool_lazy_or:nnT
28626         { \l_image_interpolate_bool }
28627         { ! \tl_if_empty_p:N \l_image_decodearray_tl }
28628         {
28629             <<
28630             \tl_if_empty:NF \l_image_decode_tl
28631             { /Decode~[ \l_image_decodearray_tl ] }
28632             \bool_if:NT \l_image_interpolate_bool
28633             { /Interpolate~true> }
28634             >>
28635         }
28636     }
28637 }

```

(End definition for _driver_image_include_eps:n and others.)

45.4.4 PDF Objects

\g__driver_pdf_object_int
\g__driver_pdf_object_prop

For tracking objects to allow finalisation.

```
28638 \int_new:N \g__driver_pdf_object_int
28639 \prop_new:N \g__driver_pdf_object_prop
```

(End definition for \g__driver_pdf_object_int and \g__driver_pdf_object_prop.)

\driver_pdf_object_new:nn
\driver_pdf_object_ref:n

Objects are tracked at the macro level, but we don't have to do anything at this stage.

```
28640 \cs_new_protected:Npn \driver_pdf_object_new:nn #1#2
28641 {
28642   \int_gincr:N \g__driver_pdf_object_int
28643   \int_const:cn
28644     { g__driver_pdf_object_ \tl_to_str:n {#1} _int }
28645   { \g__driver_pdf_object_int }
28646   \prop_gput:Nnn \g__driver_pdf_object_prop {#1} {#2}
28647 }
28648 \cs_new:Npn \driver_pdf_object_ref:n #1
28649 { @l3obj \int_use:c { g__driver_pdf_object_ \tl_to_str:n {#1} _int } }
```

(End definition for \driver_pdf_object_new:nn and \driver_pdf_object_ref:n. These functions are documented on page 264.)

\driver_pdf_object_write:nn

This is where we choose the actual type.

_driver_pdf_object_write:nnn
_driver_pdf_object_write_array:nn
_driver_pdf_object_write_dict:nn
_driver_pdf_object_write_fstream:nn
_driver_pdf_object_write_stream:nn
_driver_pdf_object_write_stream:nnnn

```
28650 \cs_new_protected:Npn \driver_pdf_object_write:nn #1#2
28651 {
28652   \exp_args:Nx \_driver_pdf_object_write:nnn
28653     { \prop_item:Nn \g__driver_pdf_object_prop {#1} } {#1} {#2}
28654 }
28655 \cs_new_protected:Npn \_driver_pdf_object_write:nnn #1#2#3
28656 { \use:c { \_driver_pdf_object_write_ #1 :nn } {#2} {#3} }
28657 \cs_new_protected:Npn \_driver_pdf_object_write_array:nn #1#2
28658 {
28659   \_driver_literal:x
28660   {
28661     pdf:obj ~ \driver_pdf_object_ref:n {#1} ~
28662     [ ~ \exp_not:n {#2} ~ ]
28663   }
28664 }
28665 \cs_new_protected:Npn \_driver_pdf_object_write_dict:nn #1#2
28666 {
28667   \_driver_literal:x
28668   {
28669     pdf:obj ~ \driver_pdf_object_ref:n {#1} ~
28670     << ~ \exp_not:n {#2} ~ >>
28671   }
28672 }
28673 \cs_new_protected:Npn \_driver_pdf_object_write_fstream:nn #1#2
28674 { \_driver_pdf_object_write_stream:nnnn { f } {#1} #2 }
28675 \cs_new_protected:Npn \_driver_pdf_object_write_stream:nn #1#2
28676 { \_driver_pdf_object_write_stream:nnnn { } {#1} #2 }
28677 \cs_new_protected:Npn \_driver_pdf_object_write_stream:nnnn #1#2#3#4
```

```

28678 {
28679   \_driver_literal:x
28680   {
28681     pdf: #1 stream ~ \driver_pdf_object_ref:n {#2} ~
28682     ( \exp_not:n {#4} ) ~ << \exp_not:n {#3} >>
28683   }
28684 }
28685 }

```

(End definition for \driver_pdf_object_write:nn and others. This function is documented on page 265.)

45.4.5 PDF Structure

Pass data to the driver: these are a one-shot.

```

28686 \cs_new_protected:Npn \driver_pdf_compresslevel:n #1
28687 { \_driver_literal:x { dvipdfmx:config~z~ \int_eval:n {#1} } }
28688 \cs_new_protected:Npn \driver_pdf_objects_enable: { }
28689 \cs_new_protected:Npn \driver_pdf_objects_disable:
28690 { \_driver_literal:n { dvipdfmx:config~C~0x40 } }

```

(End definition for \driver_pdf_compresslevel:n, \driver_pdf_objects_enable:, and \driver_pdf_objects_disable:. These functions are documented on page 265.)

```

28691 </dvipdfmx | xdvipdfmx>

```

45.5 xdvipdfmx driver

```

28692 (*xdvipdfmx)

```

45.5.1 Images

For xdvipdfmx, there are two primitives that allow us to obtain the bounding box without needing extractbb. The only complexity is passing the various minor variations to a common core process. The X_YTeX primitive omits the text box from the page box specification, so there is also some “trimming” to do here.

```

28693 \cs_new_protected:Npn \_driver_image_getbb_jpg:n #1
28694 {
28695   \int_zero:N \l_image_page_int
28696   \tl_clear:N \l_image_pagebox_tl
28697   \_driver_image_getbb_auxi:nN {#1} \tex_XeTeXpicfile:D
28698 }
28699 \cs_new_eq:NN \_driver_image_getbb_png:n \_driver_image_getbb_jpg:n
28700 \cs_new_protected:Npn \_driver_image_getbb_pdf:n #1
28701 {
28702   \tl_clear:N \l_image_decode_tl
28703   \bool_set_false:N \l_image_interpolate_bool
28704   \_driver_image_getbb_auxi:nN {#1} \tex_XeTeXpdffile:D
28705 }
28706 \cs_new_protected:Npn \_driver_image_getbb_auxi:nN #1#2
28707 {
28708   \int_compare:nNnTF \l_image_page_int > 1
28709   { \_driver_image_getbb_auxii:VnN \l_image_page_int {#1} #2 }
28710   { \_driver_image_getbb_auxiii:nNnn {#1} #2 }
28711 }

```

```

28712 \cs_new_protected:Npn \__driver_image_getbb_auxii:nnN #1#2#3
28713 { \__driver_image_getbb_aux:nNnn {#2} #3 { :P #1 } { page #1 } }
28714 \cs_generate_variant:Nn \__driver_image_getbb_auxii:nnN { V }
28715 \cs_new_protected:Npn \__driver_image_getbb_auxiii:nNnn #1#2#3#4
28716 {
28717   \tl_if_empty:NTF \l_image_pagebox_tl
28718   { \__driver_image_getbb_auxiv:VnNnn \l_image_pagebox_tl }
28719   { \__driver_image_getbb_auxv:nNnn }
28720   {#1} #2 {#3} {#4}
28721 }
28722 \cs_new_protected:Npn \__driver_image_getbb_auxiv:nnNnn #1#2#3#4#5
28723 {
28724   \use:x
28725   {
28726     \__driver_image_getbb_auxv:nNnn {#2} #3 { : #1 #4 }
28727     { #5 ~ \__driver_image_getbb_pagebox:w #1 }
28728   }
28729 }
28730 \cs_generate_variant:Nn \__driver_image_getbb_auxiv:nnNnn { V }
28731 \cs_new_protected:Npn \__driver_image_getbb_auxv:nNnn #1#2#3#4
28732 {
28733   \image_bb_restore:nF {#1#3}
28734   { \__driver_image_getbb_auxvi:nNnn {#1} #2 {#3} {#4} }
28735 }
28736 \cs_new_protected:Npn \__driver_image_getbb_auxvi:nNnn #1#2#3#4
28737 {
28738   \hbox_set:Nn \l__driver_tmp_box { #2 #1 ~ #4 }
28739   \dim_set:Nn \l_image_utx_dim { \box_wd:N \l__driver_tmp_box }
28740   \dim_set:Nn \l_image_ury_dim { \box_ht:N \l__driver_tmp_box }
28741   \image_bb_save:n {#1#3}
28742 }
28743 \cs_new:Npn \__driver_image_getbb_pagebox:w #1 box {#1}

```

(End definition for __driver_image_getbb_jpg:n and others.)

__driver_image_include_pdf:n For PDF images, properly supporting the `pagebox` concept in \XeTeX is best done using the `\tex_XeTeXpdffile:D` primitive. The syntax here is the same as for the image measurement part, although we know at this stage that there must be some valid setting for `\l_image_pagebox_tl`.

```

28744 \cs_new_protected:Npn \__driver_image_include_pdf:n #1
28745 {
28746   \tex_XeTeXpdffile:D "#1" ~
28747   \int_compare:nNnT \l_image_page_int > 0
28748   { page~ \int_use:N \l_image_page_int }
28749   \__driver_image_getbb_auxiv:VnNnn \l_image_pagebox_tl
28750 }

```

(End definition for __driver_image_include_pdf:n.)

```

28751 </xdvipdfmx>

```

45.6 Drawing commands: pdfmode and (x)dvipdfmx

Both `pdfmode` and `(x)dvipdfmx` directly produce PDF output and understand a shared set of specials for drawing commands.

28752 `\dvipdfmx | pdfmode | xdvipdfmx`

45.6.1 Drawing

`_driver_draw_literal:n` Pass data through using a dedicated interface.
`_driver_draw_literal:x` 28753 `\cs_new_eq:NN _driver_draw_literal:n _driver_literal_pdf:n`
28754 `\cs_generate_variant:Nn _driver_draw_literal:n { x }`

(End definition for `_driver_draw_literal:n`.)

`\driver_draw_begin:` No special requirements here, so simply set up a drawing scope.

`\driver_draw_end:` 28755 `\cs_new_protected:Npn \driver_draw_begin:`
28756 `{ \driver_draw_scope_begin: }`
28757 `\cs_new_protected:Npn \driver_draw_end:`
28758 `{ \driver_draw_scope_end: }`

(End definition for `\driver_draw_begin:` and `\driver_draw_end:`. These functions are documented on page 261.)

`\driver_draw_scope_begin:` Use the driver-level scope mechanisms.

`\driver_draw_scope_end:` 28759 `\cs_new_eq:NN \driver_draw_scope_begin: _driver_scope_begin:`
28760 `\cs_new_eq:NN \driver_draw_scope_end: _driver_scope_end:`

(End definition for `\driver_draw_scope_begin:` and `\driver_draw_scope_end:`. These functions are documented on page 261.)

`\driver_draw_moveto:nn` Path creation operations all resolve directly to PDF primitive steps, with only the need
`\driver_draw_lineto:nn` to convert to bp.

`\driver_draw_curveto:nnnnnn` 28761 `\cs_new_protected:Npn \driver_draw_moveto:nn #1#2`
`\driver_draw_rectangle:nnnn` 28762 `{`
28763 `_driver_draw_literal:x`
28764 `{ \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ m }`
28765 `}`
28766 `\cs_new_protected:Npn \driver_draw_lineto:nn #1#2`
28767 `{`
28768 `_driver_draw_literal:x`
28769 `{ \dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~ l }`
28770 `}`
28771 `\cs_new_protected:Npn \driver_draw_curveto:nnnnnn #1#2#3#4#5#6`
28772 `{`
28773 `_driver_draw_literal:x`
28774 `{`
28775 `\dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~`
28776 `\dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~`
28777 `\dim_to_decimal_in_bp:n {#5} ~ \dim_to_decimal_in_bp:n {#6} ~`
28778 `c`
28779 `}`
28780 `}`
28781 `\cs_new_protected:Npn \driver_draw_rectangle:nnnn #1#2#3#4`
28782 `{`
28783 `_driver_draw_literal:x`
28784 `{`
28785 `\dim_to_decimal_in_bp:n {#1} ~ \dim_to_decimal_in_bp:n {#2} ~`
28786 `\dim_to_decimal_in_bp:n {#3} ~ \dim_to_decimal_in_bp:n {#4} ~`
28787 `re`

```

28788     }
28789 }

```

(End definition for `\driver_draw_moveto:nn` and others. These functions are documented on page 261.)

`\driver_draw_evenodd_rule:` The even-odd rule here can be implemented as a simply switch.

```

\driver_draw_nonzero_rule: 28790 \cs_new_protected:Npn \driver_draw_evenodd_rule:
\g__driver_draw_eor_bool 28791 { \bool_gset_true:N \g__driver_draw_eor_bool }
28792 \cs_new_protected:Npn \driver_draw_nonzero_rule:
28793 { \bool_gset_false:N \g__driver_draw_eor_bool }
28794 \bool_new:N \g__driver_draw_eor_bool

```

(End definition for `\driver_draw_evenodd_rule:`, `\driver_draw_nonzero_rule:`, and `\g__driver_draw_eor_bool`. These functions are documented on page 262.)

`\driver_draw_closepath:` Converting paths to output is again a case of mapping directly to PDF operations.

```

\driver_draw_stroke: 28795 \cs_new_protected:Npn \driver_draw_closepath:
\driver_draw_closestroke: 28796 { \__driver_draw_literal:n { h } }
\driver_draw_fill: 28797 \cs_new_protected:Npn \driver_draw_stroke:
\driver_draw_fillstroke: 28798 { \__driver_draw_literal:n { S } }
\driver_draw_clip: 28799 \cs_new_protected:Npn \driver_draw_closestroke:
\driver_draw_discardpath: 28800 { \__driver_draw_literal:n { s } }
28801 \cs_new_protected:Npn \driver_draw_fill:
28802 {
28803   \__driver_draw_literal:x
28804   { f \bool_if:NT \g__driver_draw_eor_bool * }
28805 }
28806 \cs_new_protected:Npn \driver_draw_fillstroke:
28807 {
28808   \__driver_draw_literal:x
28809   { B \bool_if:NT \g__driver_draw_eor_bool * }
28810 }
28811 \cs_new_protected:Npn \driver_draw_clip:
28812 {
28813   \__driver_draw_literal:x
28814   { W \bool_if:NT \g__driver_draw_eor_bool * }
28815 }
28816 \cs_new_protected:Npn \driver_draw_discardpath:
28817 { \__driver_draw_literal:n { n } }

```

(End definition for `\driver_draw_closepath:` and others. These functions are documented on page 261.)

`\driver_draw_dash_pattern:nn` Converting paths to output is again a case of mapping directly to PDF operations.

```

\__driver_draw_dash:n 28818 \cs_new_protected:Npn \driver_draw_dash_pattern:nn #1#2
\driver_draw_linewidth:n 28819 {
\driver_draw_miterlimit:n 28820   \__driver_draw_literal:x
\driver_draw_cap_butt: 28821   {
\driver_draw_cap_round: 28822     [
\driver_draw_cap_rectangle: 28823     \exp_args:Nf \use:n
\driver_draw_join_miter: 28824     { \clist_map_function:nN {#1} \__driver_draw_dash:n }
\driver_draw_join_round: 28825   ] ~
\driver_draw_join_bevel: 28826   \dim_to_decimal_in_bp:n {#2} ~ d
28827   }
28828 }

```

```

28829 \cs_new:Npn \__driver_draw_dash:n #1
28830 { ~ \dim_to_decimal_in_bp:n {#1} }
28831 \cs_new_protected:Npn \driver_draw_linewidth:n #1
28832 {
28833   \__driver_draw_literal:x
28834   { \dim_to_decimal_in_bp:n {#1} ~ w }
28835 }
28836 \cs_new_protected:Npn \driver_draw_miterlimit:n #1
28837 { \__driver_draw_literal:x { \fp_eval:n {#1} ~ M } }
28838 \cs_new_protected:Npn \driver_draw_cap_but:
28839 { \__driver_draw_literal:n { 0 ~ J } }
28840 \cs_new_protected:Npn \driver_draw_cap_round:
28841 { \__driver_draw_literal:n { 1 ~ J } }
28842 \cs_new_protected:Npn \driver_draw_cap_rectangle:
28843 { \__driver_draw_literal:n { 2 ~ J } }
28844 \cs_new_protected:Npn \driver_draw_join_miter:
28845 { \__driver_draw_literal:n { 0 ~ j } }
28846 \cs_new_protected:Npn \driver_draw_join_round:
28847 { \__driver_draw_literal:n { 1 ~ j } }
28848 \cs_new_protected:Npn \driver_draw_join_bevel:
28849 { \__driver_draw_literal:n { 2 ~ j } }

```

(End definition for \driver_draw_dash_pattern:nn and others. These functions are documented on page 263.)

\driver_draw_color_fill_cmyk:nnnn For the stroke color, all engines here can use the color stack to handle the setting. However, that is not the case for fill color: the stack in (x)dvipdfmx only covers one type of color. So we have to use different approaches for the two sets of engines.

```

\driver_draw_color_fill_gray:n 28850 \cs_new_protected:Npn \driver_draw_color_fill_cmyk:nnnn #1#2#3#4
\driver_draw_color_stroke_cmyk:nnnn 28851 {
\driver_draw_color_fill_gray:n 28852   \__driver_color_fill_select:x
\driver_draw_color_stroke_gray:n 28853   {
\driver_draw_color_fill_rgb:nnnn 28854     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
\driver_draw_color_stroke_rgb:nnnn 28855     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
28856     k
28857   }
28858 }
28859 \cs_new_protected:Npn \driver_draw_color_stroke_cmyk:nnnn #1#2#3#4
28860 {
28861   \__driver_color_select:x
28862   {
28863     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
28864     \fp_eval:n {#3} ~ \fp_eval:n {#4} ~
28865     k
28866   }
28867 }
28868 \cs_new_protected:Npn \driver_draw_color_fill_gray:n #1
28869 { \__driver_color_fill_select:x { \fp_eval:n {#1} ~ g } }
28870 \cs_new_protected:Npn \driver_draw_color_stroke_gray:n #1
28871 { \__driver_color_select:x { \fp_eval:n {#1} ~ G } }
28872 \cs_new_protected:Npn \driver_draw_color_fill_rgb:nnn #1#2#3
28873 {
28874   \__driver_color_fill_select:x
28875   { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ rg }

```



```

28876 }
28877 \cs_new_protected:Npn \driver_draw_color_stroke_rgb:nnn #1#2#3
28878 {
28879   \__driver_color_select:x
28880   { \fp_eval:n {#1} ~ \fp_eval:n {#2} ~ \fp_eval:n {#3} ~ RG }
28881 }
28882 \*pdfmode>
28883 \cs_new_eq:NN \__driver_color_fill_select:n \__driver_color_select:n
28884 \*pdfmode>
28885 \*dvipdfmx|xdvipdfmx>
28886 \cs_new_eq:NN \__driver_color_fill_select:n \__driver_draw_literal:n
28887 \*dvipdfmx|xdvipdfmx>
28888 \cs_generate_variant:Nn \__driver_color_fill_select:n { x }

```

(End definition for \driver_draw_color_fill_cmyk:nnnn and others. These functions are documented on page 263.)

\driver_draw_cm:nnnn
 __driver_draw_cm:nnnn

Another split here between pdfmode and (x)dvipdfmx. In the former, we have a direct method to maintain alignment: the driver can use a matrix itself. For (x)dvipdfmx, we can to decompose the matrix into rotations and a scaling, then use those operations as they are handled by the driver. (There is driver support for matrix operations in (x)dvipdfmx, but as a matched pair so not suitable for the “stand alone” transformation set up here.)

```

28889 \cs_new_protected:Npn \driver_draw_cm:nnnn #1#2#3#4
28890 {
28891   \*pdfmode>
28892   \__driver_matrix:x
28893   {
28894     \fp_eval:n {#1} ~ \fp_eval:n {#2} ~
28895     \fp_eval:n {#3} ~ \fp_eval:n {#4}
28896   }
28897   \*pdfmode>
28898   \*dvipdfmx|xdvipdfmx>
28899   \__driver_draw_cm_decompose:nnnnN {#1} {#2} {#3} {#4}
28900   \__driver_draw_cm:nnnn
28901   \*dvipdfmx|xdvipdfmx>
28902   }
28903   \*dvipdfmx|xdvipdfmx>
28904   \cs_new_protected:Npn \__driver_draw_cm:nnnn #1#2#3#4
28905   {
28906     \__driver_literal:x
28907     {
28908       x:rotate~
28909       \fp_compare:nNnTF {#1} = \c_zero_fp
28910       { 0 }
28911       { \fp_eval:n { round ( -#1 , 5 ) } }
28912     }
28913     \__driver_literal:x
28914     {
28915       x:scale~
28916       \fp_eval:n { round ( #2 , 5 ) } ~
28917       \fp_eval:n { round ( #3 , 5 ) }
28918     }
28919     \__driver_literal:x

```

```

28920     {
28921       x:rotate~
28922       \fp_compare:nNnTF {#4} = \c_zero_fp
28923       { 0 }
28924       { \fp_eval:n { round ( -#4 , 5 ) } }
28925     }
28926   }
28927 </dvipdfmx | xdvipdfmx>

```

(End definition for `\driver_draw_cm:nnnn` and `_driver_draw_cm:nnnn`. This function is documented on page 264.)

```

\_driver_draw_cm_decompose:nnnnN
\_driver_draw_cm_decompose_auxi:nnnnN
\_driver_draw_cm_decompose_auxii:nnnnN
\_driver_draw_cm_decompose_auxiii:nnnnN

```

Internally, transformations for drawing are tracked as a matrix. Not all engines provide a way of dealing with this: if we use a raw matrix, the engine loses track of positions (for example for hyperlinks), and this is not desirable. They do, however, allow us to track rotations and scalings. Luckily, we can decompose any (two-dimensional) matrix into two rotations and a single scaling:

$$\begin{bmatrix} A & B \\ C & D \end{bmatrix} = \begin{bmatrix} \cos \beta & \sin \beta \\ -\sin \beta & \cos \beta \end{bmatrix} \begin{bmatrix} w_1 & 0 \\ 0 & w_2 \end{bmatrix} \begin{bmatrix} \cos \gamma & \sin \gamma \\ -\sin \gamma & \cos \gamma \end{bmatrix}$$

The parent matrix can be converted to

$$\begin{bmatrix} A & B \\ C & D \end{bmatrix} = \begin{bmatrix} E & H \\ -H & E \end{bmatrix} + \begin{bmatrix} F & G \\ G & -F \end{bmatrix}$$

From these, we can find that

$$\begin{aligned} \frac{w_1 + w_2}{2} &= \sqrt{E^2 + H^2} \\ \frac{w_1 - w_2}{2} &= \sqrt{F^2 + G^2} \\ \gamma - \beta &= \tan^{-1}(G/F) \\ \gamma + \beta &= \tan^{-1}(H/E) \end{aligned}$$

at which point we just have to do various pieces of re-arrangement to get all of the values. (See J. Blinn, *IEEE Comput. Graph. Appl.*, 1996, **16**, 82–88.) There is one wrinkle: the PostScript (and PDF) way of specifying a transformation matrix exchanges where one would normally expect B and C to be.

```

28928 <*dvipdfmx | xdvipdfmx>
28929 \cs_new_protected:Npn \_driver_draw_cm_decompose:nnnnN #1#2#3#4#5
28930 {
28931   \use:x
28932   {
28933     \_driver_draw_cm_decompose_auxi:nnnnN
28934     { \fp_eval:n { (#1 + #4) / 2 } }
28935     { \fp_eval:n { (#1 - #4) / 2 } }
28936     { \fp_eval:n { (#3 + #2) / 2 } }
28937     { \fp_eval:n { (#3 - #2) / 2 } }
28938   }
28939   #5
28940 }
28941 \cs_new_protected:Npn \_driver_draw_cm_decompose_auxi:nnnnN #1#2#3#4#5

```

```

28942 {
28943   \use:x
28944   {
28945     \_driver_draw_cm_decompose_auxii:nnnnN
28946     { \fp_eval:n { 2 * sqrt ( #1 * #1 + #4 * #4 ) } }
28947     { \fp_eval:n { 2 * sqrt ( #2 * #2 + #3 * #3 ) } }
28948     { \fp_eval:n { atand ( #3 , #2 ) } }
28949     { \fp_eval:n { atand ( #4 , #1 ) } }
28950   }
28951   #5
28952 }
28953 \cs_new_protected:Npn \_driver_draw_cm_decompose_auxii:nnnnN #1#2#3#4#5
28954 {
28955   \use:x
28956   {
28957     \_driver_draw_cm_decompose_auxiii:nnnnN
28958     { \fp_eval:n { ( #4 - #3 ) / 2 } }
28959     { \fp_eval:n { ( #1 + #2 ) / 2 } }
28960     { \fp_eval:n { ( #1 - #2 ) / 2 } }
28961     { \fp_eval:n { ( #4 + #3 ) / 2 } }
28962   }
28963   #5
28964 }
28965 \cs_new_protected:Npn \_driver_draw_cm_decompose_auxiii:nnnnN #1#2#3#4#5
28966 {
28967   \fp_compare:nNnTF { abs ( #2 ) } > { abs ( #3 ) }
28968   { #5 {#1} {#2} {#3} {#4} }
28969   { #5 {#1} {#3} {#2} {#4} }
28970 }
28971 \</dvipdfmx | xdvipdfmx>

```

(End definition for _driver_draw_cm_decompose:nnnnN and others.)

\driver_draw_box_use:Nnnnn Inserting a T_EX box transformed to the requested position and using the current matrix is done using a mixture of T_EX and low-level manipulation. The offset can be handled by T_EX, so only any rotation/skew/scaling component needs to be done using the matrix operation. As this operation can never be cached, the scope is set directly not using the **draw** version.

```

28972 \cs_new_protected:Npn \driver_draw_box_use:Nnnnn #1#2#3#4#5
28973 {
28974   \_driver_scope_begin:
28975   \<pdfmode>
28976   \driver_draw_cm:nnnn {#2} {#3} {#4} {#5}
28977   \</pdfmode>
28978   \<dvipdfmx | xdvipdfmx>
28979   \_driver_literal:x
28980   {
28981     pdf:btrans~matrix~
28982     \fp_eval:n {#2} ~ \fp_eval:n {#3} ~
28983     \fp_eval:n {#4} ~ \fp_eval:n {#5} ~
28984     0 ~ 0
28985   }
28986   \</dvipdfmx | xdvipdfmx>
28987   \hbox_overlap_right:n { \box_use:N #1 }

```

```

28988 <*dvipdfmx | xdvipdfmx>
28989     \__driver_literal:n { pdf:etrans }
28990 </dvipdfmx | xdvipdfmx>
28991     \__driver_scope_end:
28992 }

```

(End definition for \driver_draw_box_use:Nnnnn. This function is documented on page 264.)

```

28993 </dvipdfmx | pdfmode | xdvipdfmx>

```

45.7 dvisvgm driver

```

28994 <*dvisvgm>

```

45.7.1 Basics

__driver_literal_svg:n Unlike the other drivers, the requirements for making SVG files mean that we can't conveniently transform all operations to the current point. That makes life a bit more tricky later as that needs to be accounted for. A new line is added after each call to help to keep the output readable for debugging.

```

28995 \cs_new_protected:Npn \__driver_literal_svg:n #1
28996 { \__driver_literal:n { dvisvgm:raw~ #1 { ?nl } } }
28997 \cs_generate_variant:Nn \__driver_literal_svg:n { x }

```

(End definition for __driver_literal_svg:n.)

__driver_scope_begin: A scope in SVG terms is slightly different to the other drivers as operations have to be “tied” to these not simply inside them.

```

28998 \cs_new_protected:Npn \__driver_scope_begin:
28999 { \__driver_literal_svg:n { <g> } }
29000 \cs_new_protected:Npn \__driver_scope_end:
29001 { \__driver_literal_svg:n { </g> } }

```

(End definition for __driver_scope_begin: and __driver_scope_end:.)

45.7.2 Driver-specific auxiliaries

__driver_scope_begin:n In SVG transformations, clips and so on are attached directly to scopes so we need a way or allowing for that. This is rather more useful than __driver_scope_begin: as a result. No assumptions are made about the nature of the scoped operation(s).

```

29002 \cs_new_protected:Npn \__driver_scope_begin:n #1
29003 { \__driver_literal_svg:n { <g~ #1 > } }
29004 \cs_generate_variant:Nn \__driver_scope_begin:n { x }

```

(End definition for __driver_scope_begin:n.)

45.7.3 Box operations

\driver_box_use_clip:N Clipping in SVG is more involved than with other drivers. The first issue is that the clipping path must be defined separately from where it is used, so we need to track how many paths have applied. The naming here uses 13cp as the namespace with a number following. Rather than use a rectangular operation, we define the path manually as this allows it to have a depth: easier than the alternative approach of shifting content up and down using scopes to allow for the depth of the T_EX box and keep the reference point the same!

```

29005 \cs_new_protected:Npn \driver_box_use_clip:N #1
29006 {
29007   \int_gincr:N \g__driver_clip_path_int
29008   \__driver_literal_svg:x
29009   { < clipPath~id = " l3cp \int_use:N \g__driver_clip_path_int " > }
29010   \__driver_literal_svg:x
29011   {
29012     <
29013     path ~ d =
29014     "
29015         M ~ 0 ~
29016         \dim_to_decimal:n { -\box_dp:N #1 } ~
29017         L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
29018         \dim_to_decimal:n { -\box_dp:N #1 } ~
29019         L ~ \dim_to_decimal:n { \box_wd:N #1 } ~
29020         \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
29021         L ~ 0 ~
29022         \dim_to_decimal:n { \box_ht:N #1 + \box_dp:N #1 } ~
29023         Z
29024     "
29025   />
29026   }
29027   \__driver_literal_svg:n
29028   { < /clipPath > }

```

In general the SVG set up does not try to transform coordinates to the current point. For clipping we need to do that, so have a transformation here to get us to the right place, and a matching one just before the \TeX box is inserted to get things back on track. The clip path needs to come between those two such that it lines up with the current point, as does the \TeX box.

```

29029   \__driver_scope_begin:n
29030   {
29031     transform =
29032     "
29033         translate ( { ?x } , { ?y } ) ~
29034         scale ( 1 , -1 )
29035     "
29036   }
29037   \__driver_scope_begin:x
29038   {
29039     clip-path =
29040     "url ( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int ) "
29041   }
29042   \__driver_scope_begin:n
29043   {
29044     transform =
29045     "
29046         scale ( -1 , 1 ) ~
29047         translate ( { ?x } , { ?y } ) ~
29048         scale ( -1 , -1 )
29049     "
29050   }
29051   \box_use:N #1
29052   \__driver_scope_end:

```

```

29053     \__driver_scope_end:
29054     \__driver_scope_end:
29055     % \skip_horizontal:n { \box_wd:N #1 }
29056     }
29057     \int_new:N \g__driver_clip_path_int

```

(End definition for `\driver_box_use_clip:N` and `\g__driver_clip_path_int`. This function is documented on page 259.)

`\driver_box_use_rotate:Nn` Rotation has a dedicated operation which includes a centre-of-rotation optional pair. That can be picked up from the driver syntax, so there is no need to worry about the transformation matrix.

```

29058 \cs_new_protected:Npn \driver_box_use_rotate:Nn #1#2
29059 {
29060     \__driver_scope_begin:x
29061     {
29062         transform =
29063         "
29064             rotate
29065             ( \fp_eval:n { round ( -(#2) , 5 ) } , ~ { ?x } , ~ { ?y } )
29066         "
29067     }
29068     \box_use:N #1
29069     \__driver_scope_end:
29070 }

```

(End definition for `\driver_box_use_rotate:Nn`. This function is documented on page 260.)

`\driver_box_use_scale:Nnn` In contrast to rotation, we have to account for the current position in this case. That is done using a couple of translations in addition to the scaling (which is therefore done backward with a flip).

```

29071 \cs_new_protected:Npn \driver_box_use_scale:Nnn #1#2#3
29072 {
29073     \__driver_scope_begin:x
29074     {
29075         transform =
29076         "
29077             translate ( { ?x } , { ?y } ) ~
29078             scale
29079             (
29080                 \fp_eval:n { round ( -#2 , 5 ) } ,
29081                 \fp_eval:n { round ( -#3 , 5 ) }
29082             ) ~
29083             translate ( { ?x } , { ?y } ) ~
29084             scale ( -1 )
29085         "
29086     }
29087     \hbox_overlap_right:n { \box_use:N #1 }
29088     \__driver_scope_end:
29089 }

```

(End definition for `\driver_box_use_scale:Nnn`. This function is documented on page 260.)

45.7.4 Images

These can be included by extracting the bounding box data.

```
29090 \cs_new_eq:NN \__driver_image_getbb_png:n \image_extract_bb:n
29091 \cs_new_eq:NN \__driver_image_getbb_jpg:n \image_extract_bb:n
```

(End definition for __driver_image_getbb_png:n and __driver_image_getbb_jpg:n.)

The driver here has built-in support for basic image inclusion (see `dvisvgm.def` for a more complex approach, needed if clipping, *etc.*, is covered at the image driver level). The only issue is that `#1` must be quote-corrected. The `dvisvgm:img` operation quotes the file name, but if it is already quoted (contains spaces) then we have an issue: we simply strip off any quotes as a result.

```
29092 \cs_new_protected:Npn \__driver_image_include_png:n #1
29093 {
29094   \__driver_literal:x
29095   {
29096     dvisvgm:img~
29097     \dim_to_decimal:n { \l_image_ury_dim } ~
29098     \dim_to_decimal:n { \l_image_ury_dim } ~
29099     \__driver_image_include_bitmap_quote:w #1 " " \q_stop
29100   }
29101 }
29102 \cs_new_eq:NN \__driver_image_include_jpg:n \__driver_image_include_png:n
29103 \cs_new:Npn \__driver_image_include_bitmap_quote:w #1 " #2 " #3 \q_stop
29104 { #1#2 }
```

(End definition for __driver_image_include_png:n, __driver_image_include_jpg:n, and __driver_image_include_bitmap_quote:w.)

45.7.5 PDF Features

These are all no-ops.

```
\driver_pdf_object_new:n
\driver_pdf_object_ref:n 29105 \cs_new_protected:Npn \driver_pdf_object_new:n #1 { }
\driver_pdf_object_write:nn 29106 \cs_new:Npn \driver_pdf_object_ref:n #1 { }
\driver_pdf_compresslevel:n 29107 \cs_new_protected:Npn \driver_pdf_object_write:nn #1#2 { }
\driver_pdf_objects_enable: 29108 \cs_new_protected:Npn \driver_pdf_compresslevel:n #1 { }
\driver_pdf_objects_disable: 29109 \cs_new_protected:Npn \driver_pdf_objects_enable: { }
29110 \cs_new_protected:Npn \driver_pdf_objects_disable: { }
```

(End definition for \driver_pdf_object_new:n and others. These functions are documented on page ??.)

45.7.6 Drawing

The same as the more general literal call.

```
29111 \cs_new_eq:NN \__driver_draw_literal:n \__driver_literal_svg:n
29112 \cs_generate_variant:Nn \__driver_draw_literal:n { x }
```

(End definition for __driver_draw_literal:n.)

`\driver_draw_begin:` A drawing needs to be set up such that the co-ordinate system is translated. That is
`\driver_draw_end:` done inside a scope, which as described below

```

29113 \cs_new_protected:Npn \driver_draw_begin:
29114 {
29115     \driver_draw_scope_begin:
29116     \__driver_draw_scope:n { transform="translate({?x},{?y})~scale(1,-1)" }
29117 }
29118 \cs_new_protected:Npn \driver_draw_end:
29119 { \driver_draw_scope_end: }

```

(End definition for `\driver_draw_begin:` and `\driver_draw_end:`. These functions are documented on page 261.)

`\driver_draw_scope_begin:` Several settings that with other drivers are “stand alone” have to be given as part of
`\driver_draw_scope_end:` a scope in SVG. As a result, there is a need to provide a mechanism to automatically
`__driver_draw_scope:n` close these extra scopes. That is done using a dedicated function and a pair of tracking
`__driver_draw_scope:x` variables. Within each graphics scope we use a global variable to do the work, with a
`\g__driver_draw_scope_int` group used to save the value between scopes. The result is that no direct action is needed
`\l__driver_draw_scope_int` when creating a scope.

```

29120 \cs_new_protected:Npn \driver_draw_scope_begin:
29121 {
29122     \int_set_eq:NN
29123     \l__driver_draw_scope_int
29124     \g__driver_draw_scope_int
29125     \group_begin:
29126     \int_gzero:N \g__driver_draw_scope_int
29127 }
29128 \cs_new_protected:Npn \driver_draw_scope_end:
29129 {
29130     \prg_replicate:nn
29131     { \g__driver_draw_scope_int }
29132     { \__driver_draw_literal:n { </g> } }
29133     \group_end:
29134     \int_gset_eq:NN
29135     \g__driver_draw_scope_int
29136     \l__driver_draw_scope_int
29137 }
29138 \cs_new_protected:Npn \__driver_draw_scope:n #1
29139 {
29140     \__driver_draw_literal:n { <g~ #1 > }
29141     \int_gincr:N \g__driver_draw_scope_int
29142 }
29143 \cs_generate_variant:Nn \__driver_draw_scope:n { x }
29144 \int_new:N \g__driver_draw_scope_int
29145 \int_new:N \l__driver_draw_scope_int

```

(End definition for `\driver_draw_scope_begin:` and others. These functions are documented on page 261.)

`\driver_draw_moveto:nn` Once again, some work is needed to get path constructs correct. Rather than write the
`\driver_draw_lineto:nn` values as they are given, the entire path needs to be collected up before being output
`\driver_draw_rectangle:nnnn` in one go. For that we use a dedicated storage routine, which adds spaces as required.
`\driver_draw_curveto:nnnnnn` Since paths should be fully expanded there is no need to worry about the internal x-type
`__driver_draw_add_to_path:n` expansion.
`\g__driver_draw_path_tl`


```

29146 \cs_new_protected:Npn \driver_draw_moveto:nn #1#2
29147 {
29148   \__driver_draw_add_to_path:n
29149   { M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
29150 }
29151 \cs_new_protected:Npn \driver_draw_lineto:nn #1#2
29152 {
29153   \__driver_draw_add_to_path:n
29154   { L ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} }
29155 }
29156 \cs_new_protected:Npn \driver_draw_rectangle:nnnn #1#2#3#4
29157 {
29158   \__driver_draw_add_to_path:n
29159   {
29160     M ~ \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2}
29161     h ~ \dim_to_decimal:n {#3} ~
29162     v ~ \dim_to_decimal:n {#4} ~
29163     h ~ \dim_to_decimal:n { -#3 } ~
29164     Z
29165   }
29166 }
29167 \cs_new_protected:Npn \driver_draw_curveto:nnnnnn #1#2#3#4#5#6
29168 {
29169   \__driver_draw_add_to_path:n
29170   {
29171     C ~
29172     \dim_to_decimal:n {#1} ~ \dim_to_decimal:n {#2} ~
29173     \dim_to_decimal:n {#3} ~ \dim_to_decimal:n {#4} ~
29174     \dim_to_decimal:n {#5} ~ \dim_to_decimal:n {#6}
29175   }
29176 }
29177 \cs_new_protected:Npn \__driver_draw_add_to_path:n #1
29178 {
29179   \tl_gset:Nx \g__driver_draw_path_tl
29180   {
29181     \g__driver_draw_path_tl
29182     \tl_if_empty:NF \g__driver_draw_path_tl { \c_space_tl }
29183     #1
29184   }
29185 }
29186 \tl_new:N \g__driver_draw_path_tl

```

(End definition for \driver_draw_moveto:nn and others. These functions are documented on page 261.)

\driver_draw_evenodd_rule: The fill rules here have to be handled as scopes.

```

\driver_draw_nonzero_rule:
29187 \cs_new_protected:Npn \driver_draw_evenodd_rule:
29188 { \__driver_draw_scope:n { fill-rule="evenodd" } }
29189 \cs_new_protected:Npn \driver_draw_nonzero_rule:
29190 { \__driver_draw_scope:n { fill-rule="nonzero" } }

```

(End definition for \driver_draw_evenodd_rule: and \driver_draw_nonzero_rule:. These functions are documented on page 262.)

__driver_draw_path:n Setting fill and stroke effects and doing clipping all has to be done using scopes. This means setting up the various requirements in a shared auxiliary which deals with the

```

\driver_draw_closepath:
\driver_draw_stroke:
\driver_draw_closestroke:
\driver_draw_fill:
\driver_draw_fillstroke:
\driver_draw_clip:
\driver_draw_discardpath:
\g__driver_draw_clip_bool
\g__driver_draw_path_int

```

bits and pieces. Clipping paths are reused for path drawing: not essential but avoids constructing them twice. Discarding a path needs a separate function as it's not quite the same.

```

29191 \cs_new_protected:Npn \driver_draw_closepath:
29192 { \__driver_draw_add_to_path:n { Z } }
29193 \cs_new_protected:Npn \__driver_draw_path:n #1
29194 {
29195   \bool_if:NTF \g__driver_draw_clip_bool
29196   {
29197     \int_gincr:N \g__driver_clip_path_int
29198     \__driver_draw_literal:x
29199     {
29200       < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
29201       { ?nl }
29202       <path-d=" \g__driver_draw_path_tl "/> { ?nl }
29203       < /clipPath > { ? nl }
29204       <
29205         use-xlink:href =
29206         "\c_hash_str l3path \int_use:N \g__driver_path_int " ~
29207         #1
29208       />
29209     }
29210     \__driver_draw_scope:x
29211     {
29212       clip-path =
29213       "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
29214     }
29215   }
29216   {
29217     \__driver_draw_literal:x
29218     { <path ~ d=" \g__driver_draw_path_tl " ~ #1 /> }
29219   }
29220   \tl_gclear:N \g__driver_draw_path_tl
29221   \bool_gset_false:N \g__driver_draw_clip_bool
29222 }
29223 \int_new:N \g__driver_path_int
29224 \cs_new_protected:Npn \driver_draw_stroke:
29225 { \__driver_draw_path:n { style="fill:none" } }
29226 \cs_new_protected:Npn \driver_draw_closestroke:
29227 {
29228   \driver_draw_closepath:
29229   \driver_draw_stroke:
29230 }
29231 \cs_new_protected:Npn \driver_draw_fill:
29232 { \__driver_draw_path:n { style="stroke:none" } }
29233 \cs_new_protected:Npn \driver_draw_fillstroke:
29234 { \__driver_draw_path:n { } }
29235 \cs_new_protected:Npn \driver_draw_clip:
29236 { \bool_gset_true:N \g__driver_draw_clip_bool }
29237 \bool_new:N \g__driver_draw_clip_bool
29238 \cs_new_protected:Npn \driver_draw_discardpath:
29239 {
29240   \bool_if:NT \g__driver_draw_clip_bool
29241   {

```

```

29242         \int_gincr:N \g__driver_clip_path_int
29243         \__driver_draw_literal:x
29244         {
29245             < clipPath-id = " l3cp \int_use:N \g__driver_clip_path_int " >
29246             { ?nl }
29247             <path-d=" \g__driver_draw_path_tl "/> { ?nl }
29248             < /clipPath >
29249         }
29250         \__driver_draw_scope:x
29251         {
29252             clip-path =
29253             "url( \c_hash_str l3cp \int_use:N \g__driver_clip_path_int)"
29254         }
29255     }
29256     \tl_gclear:N \g__driver_draw_path_tl
29257     \bool_gset_false:N \g__driver_draw_clip_bool
29258 }

```

(End definition for __driver_draw_path:n and others. These functions are documented on page 261.)

```

\driver_draw_dash_pattern:nn
  \__driver_draw_dash:n
  \__driver_draw_dash_aux:nn
  \driver_draw_linewidth:n
  \driver_draw_miterlimit:n
  \driver_draw_cap_butt:
  \driver_draw_cap_round:
\driver_draw_cap_rectangle:
  \driver_draw_join_miter:
  \driver_draw_join_round:
  \driver_draw_join_bevel:

```

All of these ideas are properties of scopes in SVG. The only slight complexity is converting the dash array properly (doing any required maths).

```

29259 \cs_new_protected:Npn \driver_draw_dash_pattern:nn #1#2
29260 {
29261     \use:x
29262     {
29263         \__driver_draw_dash_aux:nn
29264         { \clist_map_function:nn {#1} \__driver_draw_dash:n }
29265         { \dim_to_decimal:n {#2} }
29266     }
29267 }
29268 \cs_new:Npn \__driver_draw_dash:n #1
29269 { , \dim_to_decimal_in_bp:n {#1} }
29270 \cs_new_protected:Npn \__driver_draw_dash_aux:nn #1#2
29271 {
29272     \__driver_draw_scope:x
29273     {
29274         stroke-dasharray =
29275         "
29276         \tl_if_empty:oTF { \use_none:n #1 }
29277         { none }
29278         { \use_none:n #1 }
29279         " ~
29280         stroke-offset=" #2 "
29281     }
29282 }
29283 \cs_new_protected:Npn \driver_draw_linewidth:n #1
29284 { \__driver_draw_scope:x { stroke-width=" \dim_to_decimal:n {#1} " } }
29285 \cs_new_protected:Npn \driver_draw_miterlimit:n #1
29286 { \__driver_draw_scope:x { stroke-miterlimit=" \fp_eval:n {#1} " } }
29287 \cs_new_protected:Npn \driver_draw_cap_butt:
29288 { \__driver_draw_scope:n { stroke-linecap="butt" } }
29289 \cs_new_protected:Npn \driver_draw_cap_round:
29290 { \__driver_draw_scope:n { stroke-linecap="round" } }

```

```

29291 \cs_new_protected:Npn \driver_draw_cap_rectangle:
29292 { \__driver_draw_scope:n { stroke-linecap="square" } }
29293 \cs_new_protected:Npn \driver_draw_join_miter:
29294 { \__driver_draw_scope:n { stroke-linejoin="miter" } }
29295 \cs_new_protected:Npn \driver_draw_join_round:
29296 { \__driver_draw_scope:n { stroke-linejoin="round" } }
29297 \cs_new_protected:Npn \driver_draw_join_bevel:
29298 { \__driver_draw_scope:n { stroke-linejoin="bevel" } }

```

(End definition for \driver_draw_dash_pattern:nn and others. These functions are documented on page 263.)

\driver_draw_color_fill_cmyk:nnnn SVG fill color has to be covered outside of the stack, as for dvips. Here, we are only allowed RGB colors so there is some conversion to do.

```

\driver_draw_color_fill_cmyk:nnnn
\driver_draw_color_stroke_cmyk:nnnn
\driver_draw_color_fill_gray:n
\driver_draw_color_stroke_gray:n
\driver_draw_color_fill_rgb:nnn
\driver_draw_color_stroke_rgb:nnn
\__driver_draw_color_fill:nnn
29299 \cs_new_protected:Npn \driver_draw_color_stroke_cmyk:nnnn #1#2#3#4
29300 {
29301   \use:x
29302   {
29303     \__driver_draw_color_fill:nnn
29304     { \fp_eval:n { -100 * ( (#1) * ( 1 - (#4) ) - 1 ) } }
29305     { \fp_eval:n { -100 * ( (#2) * ( 1 - (#4) ) + #4 - 1 ) } }
29306     { \fp_eval:n { -100 * ( (#3) * ( 1 - (#4) ) + #4 - 1 ) } }
29307   }
29308 }
29309 \cs_new_eq:NN \driver_draw_color_stroke_cmyk:nnnn \driver_color_cmyk:nnnn
29310 \cs_new_protected:Npn \driver_draw_color_gray:n #1
29311 {
29312   \use:x
29313   {
29314     \__driver_draw_color_gray_aux:n
29315     { \fp_eval:n { 100 * (#3) } }
29316   }
29317 }
29318 \cs_new_protected:Npn \__driver_draw_color_gray_aux:n #1
29319 { \__driver_draw_color_fill:nnn {#1} {#1} {#1} }
29320 \cs_new_eq:NN \driver_draw_color_stroke_gray:n \driver_color_gray:n
29321 \cs_new_protected:Npn \driver_draw_color_rgb:nnn #1#2#3
29322 {
29323   \use:x
29324   {
29325     \__driver_draw_color_fill:nnn
29326     { \fp_eval:n { 100 * (#1) } }
29327     { \fp_eval:n { 100 * (#2) } }
29328     { \fp_eval:n { 100 * (#3) } }
29329   }
29330 }
29331 \cs_new_protected:Npn \__driver_draw_color_fill:nnn #1#2#3
29332 {
29333   \__driver_draw_scope:x
29334   {
29335     fill =
29336     "
29337     rgb
29338     (

```

```

29339         #1 \c_percent_str ,
29340         #2 \c_percent_str ,
29341         #3 \c_percent_str
29342     )
29343     "
29344 }
29345 }
29346 \cs_new_eq:NN \driver_draw_color_stroke_rgb:nnn \driver_color_rgb:nnn

```

(End definition for \driver_draw_color_fill_cmyk:nnnn and others. These functions are documented on page 263.)

\driver_draw_cm:nnnn The four arguments here are floats (the affine matrix), the last two are a displacement vector.

```

29347 \cs_new_protected:Npn \driver_draw_cm:nnnn #1#2#3#4
29348 {
29349     \__driver_draw_scope:n
29350     {
29351         transform =
29352         "
29353         matrix
29354         (
29355             \fp_eval:n {#1} , \fp_eval:n {#2} ,
29356             \fp_eval:n {#3} , \fp_eval:n {#4} ,
29357             Opt , Opt
29358         )
29359         "
29360     }
29361 }

```

(End definition for \driver_draw_cm:nnnn. This function is documented on page 264.)

\driver_draw_box_use:Nnnnn No special savings can be made here: simply displace the box inside a scope. As there is nothing to re-box, just make the box passed of zero size.

```

29362 \cs_new_protected:Npn \driver_draw_box_use:Nnnnn #1#2#3#4#5#6#7
29363 {
29364     \__driver_scope_begin:
29365     \driver_draw_cm:nnnn {#2} {#3} {#4} {#5}
29366     \__driver_literal_svg:n
29367     {
29368         < g~
29369         stroke="none"~
29370         transform="scale(-1,1)~translate({?x},{?y})~scale(-1,-1)"
29371         >
29372     }
29373     \box_set_wd:Nn #1 { Opt }
29374     \box_set_ht:Nn #1 { Opt }
29375     \box_set_dp:Nn #1 { Opt }
29376     \box_use:N #1
29377     \__driver_literal_svg:n { </g> }
29378     \__driver_scope_end:
29379 }

```

(End definition for \driver_draw_box_use:Nnnnn. This function is documented on page 264.)

```

29380 </dvisvgm>

```

```

29381 </initex | package>

```

46 l3deprecation implementation

```

29382 (*initex | package)
29383 (@@=deprecation)

\__kernel_deprecation_error:Nnn The \outer definition here ensures the command cannot appear in an argument. Use
this auxiliary on all commands that have been removed since 2015.

29384 \cs_new_protected:Npn \__kernel_deprecation_error:Nnn #1#2#3
29385 {
29386   \tex_protected:D \tex_outer:D \tex_edef:D #1
29387   {
29388     \exp_not:N \__kernel_msg_expandable_error:nnnnn
29389     { kernel } { deprecated-command }
29390     { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
29391     \exp_not:N \__kernel_msg_error:nnxxx
29392     { kernel } { deprecated-command }
29393     { \tl_to_str:n {#3} } { \token_to_str:N #1 } { \tl_to_str:n {#2} }
29394   }
29395 }
29396 \__kernel_deprecation_error:Nnn \box_resize:cnn
29397 { \box_resize_to_wd_and_ht_plus_dp:cnn } { 2018-12-27 }
29398 \__kernel_deprecation_error:Nnn \box_resize:Nnn
29399 { \box_resize_to_wd_and_ht_plus_dp:Nnn } { 2018-12-27 }
29400 \__kernel_deprecation_error:Nnn \box_use_clear:c
29401 { \box_use_drop:c } { 2018-12-27 }
29402 \__kernel_deprecation_error:Nnn \box_use_clear:N
29403 { \box_use_drop:N } { 2018-12-27 }
29404 \__kernel_deprecation_error:Nnn \c_job_name_tl
29405 { \c_sys_jobname_str } { 2017-01-01 }
29406 \__kernel_deprecation_error:Nnn \c_minus_one
29407 { -1 } { 2018-12-27 }
29408 \__kernel_deprecation_error:Nnn \dim_case:nnn
29409 { \dim_case:nnF } { 2015-07-14 }
29410 \__kernel_deprecation_error:Nnn \file_add_path:nN
29411 { \file_get_full_name:nN } { 2018-12-27 }
29412 \__kernel_deprecation_error:Nnn \file_if_exist_input:nT
29413 { \file_if_exist:nT and~ \file_input:n } { 2018-03-05 }
29414 \__kernel_deprecation_error:Nnn \file_if_exist_input:nTF
29415 { \file_if_exist:nT and~ \file_input:n } { 2018-03-05 }
29416 \__kernel_deprecation_error:Nnn \file_list:
29417 { \file_log_list: } { 2018-12-27 }
29418 \__kernel_deprecation_error:Nnn \file_path_include:n
29419 { \seq_put_right:Nn \l_file_search_path_seq } { 2018-12-27 }
29420 \__kernel_deprecation_error:Nnn \file_path_remove:n
29421 { \seq_remove_all:Nn \l_file_search_path_seq } { 2018-12-27 }
29422 \__kernel_deprecation_error:Nnn \g_file_current_name_tl
29423 { \g_file_current_name_str } { 2018-12-27 }
29424 \__kernel_deprecation_error:Nnn \int_case:nnn
29425 { \int_case:nnF } { 2015-07-14 }
29426 \__kernel_deprecation_error:Nnn \int_from_binary:n
29427 { \int_from_bin:n } { 2016-01-05 }
29428 \__kernel_deprecation_error:Nnn \int_from_hexadecimal:n
29429 { \int_from_hex:n } { 2016-01-05 }
29430 \__kernel_deprecation_error:Nnn \int_from_octal:n

```

```

29431 { \int_from_oct:n } { 2016-01-05 }
29432 \__kernel_deprecation_error:Nnn \int_to_binary:n
29433 { \int_to_bin:n } { 2016-01-05 }
29434 \__kernel_deprecation_error:Nnn \int_to_hexadecimal:n
29435 { \int_to_hex:n } { 2016-01-05 }
29436 \__kernel_deprecation_error:Nnn \int_to_octal:n
29437 { \int_to_oct:n } { 2016-01-05 }
29438 \__kernel_deprecation_error:Nnn \ior_get_str:NN
29439 { \ior_str_get:NN } { 2018-03-05 }
29440 \__kernel_deprecation_error:Nnn \ior_list_streams:
29441 { \ior_show_list: } { 2018-12-27 }
29442 \__kernel_deprecation_error:Nnn \ior_log_streams:
29443 { \ior_log_list: } { 2018-12-27 }
29444 \__kernel_deprecation_error:Nnn \luatex_if_engine_p:
29445 { \sys_if_engine luatex_p: } { 2017-01-01 }
29446 \__kernel_deprecation_error:Nnn \luatex_if_engine:F
29447 { \sys_if_engine luatex:F } { 2017-01-01 }
29448 \__kernel_deprecation_error:Nnn \luatex_if_engine:T
29449 { \sys_if_engine luatex:T } { 2017-01-01 }
29450 \__kernel_deprecation_error:Nnn \luatex_if_engine:TF
29451 { \sys_if_engine luatex:TF } { 2017-01-01 }
29452 \__kernel_deprecation_error:Nnn \pdfTeX_if_engine_p:
29453 { \sys_if_engine pdfTeX_p: } { 2017-01-01 }
29454 \__kernel_deprecation_error:Nnn \pdfTeX_if_engine:F
29455 { \sys_if_engine pdfTeX:F } { 2017-01-01 }
29456 \__kernel_deprecation_error:Nnn \pdfTeX_if_engine:T
29457 { \sys_if_engine pdfTeX:T } { 2017-01-01 }
29458 \__kernel_deprecation_error:Nnn \pdfTeX_if_engine:TF
29459 { \sys_if_engine pdfTeX:TF } { 2017-01-01 }
29460 \__kernel_deprecation_error:Nnn \prop_get:cn
29461 { \prop_item:cn } { 2016-01-05 }
29462 \__kernel_deprecation_error:Nnn \prop_get:Nn
29463 { \prop_item:Nn } { 2016-01-05 }
29464 \__kernel_deprecation_error:Nnn \quark_if_recursion_tail_break:N
29465 { } { 2015-07-14 }
29466 \__kernel_deprecation_error:Nnn \quark_if_recursion_tail_break:n
29467 { } { 2015-07-14 }
29468 \__kernel_deprecation_error:Nnn \scan_align_safe_stop:
29469 { protected~commands } { 2017-01-01 }
29470 \__kernel_deprecation_error:Nnn \sort_ordered:
29471 { \sort_return_same: } { 2018-12-27 }
29472 \__kernel_deprecation_error:Nnn \sort_reversed:
29473 { \sort_return_swapped: } { 2018-12-27 }
29474 \__kernel_deprecation_error:Nnn \str_case:nnn
29475 { \str_case:nnF } { 2015-07-14 }
29476 \__kernel_deprecation_error:Nnn \str_case:onn
29477 { \str_case:onF } { 2015-07-14 }
29478 \__kernel_deprecation_error:Nnn \str_case_x:nnn
29479 { \str_case_e:nnF } { 2015-07-14 }
29480 \__kernel_deprecation_error:Nnn \tl_case:cnn
29481 { \tl_case:cnF } { 2015-07-14 }
29482 \__kernel_deprecation_error:Nnn \tl_case:Nnn
29483 { \tl_case:NnF } { 2015-07-14 }
29484 \__kernel_deprecation_error:Nnn \tl_to_lowercase:n

```

```

29485 { \tex_lowercase:D } { 2018-03-05 }
29486 \__kernel_deprecation_error:Nnn \tl_to_uppercase:n
29487 { \tex_uppercase:D } { 2018-03-05 }
29488 \__kernel_deprecation_error:Nnn \token_new:Nn
29489 { \cs_new_eq:NN } { 2018-12-29 }
29490 \__kernel_deprecation_error:Nnn \xetex_if_engine_p:
29491 { \sys_if_engine_xetex_p: } { 2017-01-01 }
29492 \__kernel_deprecation_error:Nnn \xetex_if_engine:F
29493 { \sys_if_engine_xetex:F } { 2017-01-01 }
29494 \__kernel_deprecation_error:Nnn \xetex_if_engine:T
29495 { \sys_if_engine_xetex:T } { 2017-01-01 }
29496 \__kernel_deprecation_error:Nnn \xetex_if_engine:TF
29497 { \sys_if_engine_xetex:TF } { 2017-01-01 }

```

(End definition for __kernel_deprecation_error:Nnn.)

\etex_beginL:D

__deprecation_primitive:NN
__deprecation_primitive:w

We renamed all primitives to \tex_...:D so all others are deprecated. In l3names, __kernel_primitives: is defined to contain __kernel_primitive:NN \beginL \etex_beginL:D and so on, one for each deprecated primitive. We apply \exp_not:N to the second argument of __kernel_primitive:NN because it may be outer (both when doing and undoing deprecation actually), then __deprecation_primitive:NN uses \tex_let:D to change the meaning of this potentially outer token. Then, either turn it into an error or make it equal to the primitive #1. To be more precise, #1 may not be defined, so try a \tex_...:D command as well.

```

29498 \cs_new_protected:Npn \__deprecation_primitive:NN #1#2 { }
29499 \exp_last_unbraced:NNNNo
29500 \cs_new:Npn \__deprecation_primitive:w #1 { \token_to_str:N _ } { }
29501 \__kernel_deprecation_code:nn
29502 {
29503   \cs_set_protected:Npn \__kernel_primitive:NN #1
29504   {
29505     \exp_after:wN \__deprecation_primitive:NN
29506     \exp_after:wN #1
29507     \exp_not:N
29508   }
29509   \cs_set_protected:Npn \__deprecation_primitive:NN #1#2
29510   {
29511     \tex_let:D #2 \scan_stop:
29512     \exp_args:NNx \__kernel_deprecation_error:Nnn #2
29513     {
29514       \iow_char:N \
29515       \cs_if_exist:NTF #1
29516       { \cs_to_str:N #1 }
29517       {
29518         tex_
29519         \exp_last_unbraced:Nf
29520         \__deprecation_primitive:w { \cs_to_str:N #2 }
29521       }
29522     }
29523     { 2019-12-31 }
29524   }
29525   \__kernel_primitives:
29526 }
29527 {

```



```

29528 \cs_set_protected:Npn \__kernel_primitive:NN #1
29529 {
29530   \exp_after:wN \__deprecation_primitive:NN
29531   \exp_after:wN #1
29532   \exp_not:N
29533 }
29534 \cs_set_protected:Npn \__deprecation_primitive:NN #1#2
29535 {
29536   \tex_let:D #2 #1
29537   \cs_if_exist:cT { tex_ \cs_to_str:N #1 :D }
29538   {
29539     \exp_args:NNc \cs_set_eq:NN #2
29540     { tex_ \cs_to_str:N #1 :D }
29541   }
29542 }
29543 \__kernel_primitives:
29544 }

```

(End definition for \etex_beginL:D, __deprecation_primitive:NN, and __deprecation_primitive:w.)

```

29545 </initex | package>

```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
!	196
\!	10363
\"	8456, 8459, 27411
\#	6, 5696, 8456, 10779
\\$	5695, 8456, 8459, 21244
\%	5697, 8456, 10781
\&	5688, 8456, 8459, 9509, 10363, 10364
&&	195
\'	27411
\(27454
\)	27454
*	196
*	5381, 5404, 8631, 8633, 8637, 8645
**	196
+	195, 196
\,	11984
-	195, 196
\-	292
\.	27411
/	196
\/	291
\:	5694
\::	34, 347, 371, 372, 3153, 3154, <u>3155</u> , 3156, 3157, 3158, 3159, 3161, 3165, 3166, 3169, 3172, 3179, 3182, 3185, 3191, 3278, 3344, 3345, 3346, 3347, 3348, 3349, 3350, 3351, 3352, 3353, 3354, 3355, 3356, 3357, 3358, 3359, 3360, 3361, 3362, 3363, 3364, 3365, 3366, 3367, 3368, 3369, 3370, 3371, 3372, 3373, 3374, 3375, 3376, 3377, 3378, 3379, 3380, 3381, 3382, 3383, 3384, 3385, 3386, 3388, 3390, 3395, 3402, 3406, 3409, 3414, 3429, 3470, 3471, 3472, 3473, 3484
\:N	34, <u>3157</u> , 3278, 3357, 3363, 3364, 3365, 3366, 3367, 3379, 3380, 3381, 3473
\:V	34, <u>3185</u> , 3347, 3354, 3365, 3367, 3369, 3371
\:V_unbraced	34, <u>3387</u>
\:c	34, <u>3159</u> , 3345, 3351, 3358, 3363, 3368, 3369, 3370, 3371, 3372, 3384, 3385
\:e	34, <u>3163</u> , 3278, 3349
\:e_unbraced	34, <u>3387</u> , 3429
\:error	246, 25914
\:f	34, <u>3172</u> , 3350, 3353, 3355, 3356, 3363, 3374, 3375, 3377, 3378, 3472
\:f_unbraced	34, <u>3387</u>
\:n	34, <u>3156</u> , 3345, 3346, 3347, 3348, 3349, 3350, 3359, 3364, 3365, 3368, 3369, 3372, 3373, 3374, 3375, 3380, 3382, 3383, 3385, 3470, 3473
\:o	34, <u>3161</u> , 3346, 3351, 3352, 3353, 3354, 3355, 3360, 3361, 3364, 3366, 3368, 3370, 3373, 3376, 3377, 3378, 3381, 3383, 3386, 3471
\:o_unbraced	34, <u>3387</u> , 3470, 3471, 3472, 3473
\:p	34, 347, <u>3158</u>
\:v	34, <u>3185</u> , 3348
\:v_unbraced	34, <u>3387</u>
\:x	34, <u>3179</u> , 3344, 3357, 3358, 3359, 3360, 3361, 3362, 3379, 3380, 3381, 3382, 3383, 3384, 3385, 3386
\:x_unbraced	34, <u>3387</u> , 3484
<	195
=	195
>	195
?	195
?:	195
\\	2340, 3131, 5690, 8456, 9425, 9443, 9445, 9450, 9451, 9479, 9494, 9947, 9955, 9962, 9974, 9975, 10000, 10001, 10008, 10034, 10036, 10037, 10082, 10083, 10096, 10140, 10161, 10162, 10183, 10184, 10185, 10186, 10187, 10239, 10243, 10248, 10255, 10338, 10339, 10342, 10343, 10784, 11301, 11307, 11314, 12893, 12905, 12911, 13703, 13706, 13707, 13708, 13715, 13718, 13719, 19821, 19824, 19825, 19850, 19851, 19858, 19859, 20314, 21784, 21897, 21898, 21899, 21920, 23273, 23277, 23282, 23316, 23325, 23329, 23334, 23354, 23356, 23357, 23359, 23362, 23364, 23371, 23375, 23378, 23382, 23384, 23388, 23390, 23396, 23398, 23402, 23404, 23408, 23413, 23415, 23457, 23459, 23464, 23466, 23472, 23477, 23478, 23482, 23486, 23496, 23499, 23503, 23504, 23508, 23516, 23579, 25078, 29514

- $\backslash{}$ 4, 5691, 8456, 10184, 10361,
 10778, 20561, 23277, 23282, 23329,
 23378, 23415, 23504, 23508, 27466
 $\backslash}$ 5, 5692, 8456,
 10184, 10362, 10780, 23276, 23282,
 23379, 23415, 23504, 23508, 27466
 \backsim 7, 10,
 110, 201, 202, 203, 204, 2814, 3514,
 4274, 5693, 8456, 8459, 8461, 8467,
 8519, 9516, 10377, 10696, 10732,
 17538, 19905, 19978, 19981, 20507,
 20512, 20513, 20514, 20515, 20518,
 20529, 20566, 20629, 20631, 20633,
 20635, 20637, 20639, 21243, 22878,
 22881, 22895, 22898, 22907, 22910,
 22913, 22916, 22930, 22933, 27411
 $\hat{}$ 196
 $\backslash_$ 5699, 8456, 8459
 \backslash' 27411
 \parallel 195
 $\backslash\sim$ 4295, 5698, 8456, 8459,
 10782, 20551, 20555, 20561, 27411
 \backslashsqcup 290, 2718, 5381, 5404, 8456,
 8624, 10002, 10026, 10170, 10176,
 10184, 10186, 10284, 10361, 10362,
 10785, 20022, 20506, 20511, 20555,
 20565, 20749, 22927, 26098, 27614
- ### A
- $\backslash A$ 5382, 5405
 $\backslash AA$ 27393
 $\backslash aa$ 27393
 $\backslash above$ 293
 $\backslash abovedisplayshortskip$ 294
 $\backslash abovedisplayskip$ 295
 $\backslash abovewithdelims$ 296
 $\backslash abs$ 196
 $\backslash accent$ 297
 $\backslash acos$ 198
 $\backslash acosd$ 198
 $\backslash acot$ 199
 $\backslash acotd$ 199
 $\backslash acsc$ 198
 $\backslash acscd$ 198
 $\backslash adjdemerits$ 298
 $\backslash adjustspacing$ 1012, 1621
 $\backslash advance$ 175, 191, 299
 $\backslash AE$ 27394
 $\backslash ae$ 27394
 $\backslash afterassignment$ 300
 $\backslash aftergroup$ 301
 $\backslash alignmark$ 889, 1713
 $\backslash aligntab$ 890, 1714
 $\backslash asec$ 198
 $\backslash ascd$ 198
 $\backslash asin$ 198
 $\backslash asind$ 198
 assert commands:
 $\backslash assert_int:n$ 22087, 23091
 $\backslash atan$ 199
 $\backslash atand$ 199
 $\backslash AtBeginDocument$ 581, 11282, 27739, 27797
 $\backslash atop$ 302
 $\backslash atopwithdelims$ 303
 $\backslash attribute$ 891, 1715
 $\backslash attributedef$ 892, 1716
 $\backslash automaticdiscretionary$ 893, 1717
 $\backslash automatichyphenmode$ 895, 1719
 $\backslash automatichyphenpenalty$ 896, 1721
 $\backslash autospacing$ 1211, 1993
 $\backslash autoxspacing$ 1212, 1994
- ### B
- $\backslash badness$ 304
 $\backslash baselineskip$ 305
 $\backslash batchmode$ 306
 $\backslash begin$ 207,
 211, 15624, 20310, 20312, 28387, 28392
 begin internal commands:
 $\backslash _regex_begin$ 23014
 $\backslash begincsname$ 898, 1723
 $\backslash begingroup$ 13,
 20, 38, 42, 48, 73, 149, 169, 280, 307
 $\backslash beginL$ 615, 1112, 1428
 $\backslash beginR$ 616, 1429
 $\backslash belowdisplayshortskip$ 308
 $\backslash belowdisplayskip$ 309
 $\backslash binoppenalty$ 310
 $\backslash bodydir$ 899, 1812
 $\backslash bodydirection$ 900
 bool commands:
 $\backslash bool_const:Nn$ 246, 25939
 $\backslash bool_do_until:Nn$ 101, 7593
 $\backslash bool_do_until:nn$ 101, 7599
 $\backslash bool_do_while:Nn$ 101, 7593
 $\backslash bool_do_while:nn$ 101, 7599
 $\backslash .bool_gset:N$ 170, 12436
 $\backslash bool_gset:Nn$ 98, 7421
 $\backslash bool_gset_eq:NN$ 98, 7417, 20497, 22418
 $\backslash bool_gset_false:N$ 97, 7401,
 22377, 25950, 28015, 28031, 28057,
 28079, 28095, 28793, 29221, 29257
 $\backslash .bool_gset_inverse:N$ 170, 12444
 $\backslash bool_gset_inverse:N$ 247, 25946
 $\backslash bool_gset_true:N$ 97, 7401, 22428,
 25950, 28013, 28082, 28791, 29236

- \bool_if:NTF 98, 244, 3000,
7435, 7588, 7590, 7594, 7596, 10999,
11006, 12213, 12408, 12417, 12583,
12608, 12622, 12639, 12673, 12701,
12720, 12722, 12727, 12734, 12755,
12809, 21377, 21386, 21788, 21866,
21884, 21913, 22034, 22260, 22268,
23546, 23551, 24543, 24960, 25947,
25950, 28022, 28026, 28044, 28048,
28052, 28065, 28070, 28074, 28086,
28090, 28363, 28404, 28590, 28632,
28804, 28809, 28814, 29195, 29240
- \bool_if:nTF . . . 98, 100, 101, 101,
101, 102, 1046, 1064, 7449, 7467,
7538, 7545, 7564, 7571, 7580, 7601,
7610, 7614, 7623, 7721, 21869, 26023
- \bool_if_exist:NTF
. 98, 7463, 12231, 12247
- \bool_if_exist_p:N 98, 7463
- \bool_if_p:N 98, 7435
- \bool_if_p:n
. 100, 475, 7425, 7431, 7467,
7475, 7545, 7571, 7577, 7581, 25943
- \bool_lazy_all:nTF
. 99, 100, 100, 7525, 21653
- \bool_lazy_all_p:n 100, 7525
- \bool_lazy_and:nnTF . 99, 100, 100,
7542, 7741, 10584, 27061, 27111, 27436
- \bool_lazy_and_p:nn . . 100, 100, 7542
- \bool_lazy_any:nTF
. 99, 100, 100, 7551, 26861
- \bool_lazy_any_p:n
. 100, 100, 7551, 27064
- \bool_lazy_or:nnTF 99, 100,
100, 7568, 19911, 25307, 26479,
26729, 26758, 26940, 26969, 27125,
27167, 27207, 27414, 28396, 28625
- \bool_lazy_or_p:nn . . 100, 7568, 27439
- \bool_log:N 98, 7450
- \bool_log:n 98, 7444
- \bool_new:N
. 97, 7399, 7459, 7460, 7461, 7462,
10727, 12126, 12127, 12131, 12132,
12136, 12231, 12247, 20355, 20784,
22319, 22320, 22322, 22323, 22324,
24250, 28016, 28083, 28794, 29237
- \bool_not_p:n 100, 7577
- .bool_set:N 170, 12436
- \bool_set:Nn 98, 1023, 7421
- \bool_set_eq:NN 98, 7417, 20491, 22577
- \bool_set_false:N
. 97, 259, 7401, 10833,
10975, 10983, 10991, 11001, 11008,
12153, 12593, 12618, 12630, 12650,
12659, 12708, 21351, 21556, 22298,
22390, 22404, 22450, 22518, 24539,
24958, 25947, 28373, 28564, 28703
- .bool_set_inverse:N 170, 12444
- \bool_set_inverse:N 247, 25946
- \bool_set_true:N
. 97, 273, 7401, 10961, 12148,
12591, 12616, 12632, 12648, 12654,
12715, 21356, 21560, 22292, 22516,
22576, 24557, 24572, 24603, 25947
- \bool_show:N 98, 7450
- \bool_show:n 98, 7444
- \bool_until_do:Nn 101, 7587
- \bool_until_do:nn 101, 7599
- \bool_while_do:Nn 101, 7587
- \bool_while_do:nn 102, 7599
- \bool_xor:nnTF 101, 7578
- \bool_xor_p:nn 101, 7578
- \c_false_bool . . . 20, 97, 334, 366,
469, 472, 472, 472, 473, 2564, 2616,
2617, 2648, 2667, 2672, 2712, 2731,
2937, 2944, 3797, 3991, 7399, 7406,
7412, 7516, 7539, 7545, 7563, 7732,
21028, 21046, 21260, 21296, 21595,
21736, 21753, 21809, 21952, 23193
- \g_tmpa_bool 99, 7459
- \l_tmpa_bool 98, 7459
- \g_tmpb_bool 99, 7459
- \l_tmpb_bool 98, 7459
- \c_true_bool 20, 97, 334, 386,
469, 472, 472, 472, 473, 2616, 2648,
2712, 2730, 2958, 7403, 7409, 7517,
7518, 7537, 7565, 7571, 7726, 20362,
20494, 20932, 20992, 21042, 21226,
21251, 21295, 21302, 21734, 21744,
21807, 22020, 22198, 22209, 22224,
22394, 22427, 23024, 23101, 23154
- bool internal commands:
- __bool_!:Nw 7496
- __bool_&_0: 7508
- __bool_&_1: 7508
- __bool_&_2: 7508
- __bool_(:Nw 7501
- __bool_)_0: 7508
- __bool_)_1: 7508
- __bool_)_2: 7508
- __bool_choose:NNN . . 7503, 7507, 7508
- __bool_get_next:NN
. 472, 472, 7483, 7486, 7498, 7504,
7519, 7520, 7521, 7522, 7523, 7524
- __bool_if_p:n 7475
- __bool_if_p_aux:w 472, 7475
- __bool_lazy_all:n 7525
- __bool_lazy_any:n 7551

- _bool_p:Nw [7506](#)
- _bool_show:NN [7450](#)
- _bool_to_str:n [7444](#), [7457](#)
- _bool_l_0: [7508](#)
- _bool_l_1: [7508](#)
- _bool_l_2: [7508](#)
- \botmark [311](#)
- \botmarks [617](#), [1430](#)
- \box [312](#)
- box commands:
 - \box_autosize_to_wd_and_ht:Nnn ..
..... [227](#), [24168](#)
 - \box_autosize_to_wd_and_ht_plus_+
dp:Nnn [227](#), [24168](#)
 - \box_clear:N [220](#),
[220](#), [23605](#), [23612](#), [24285](#), [24345](#), [24392](#)
 - \box_clear_new:N [220](#), [23611](#)
 - \box_clip:N [241](#), [241](#), [241](#), [25453](#)
 - \box_dp:N [222](#),
[14184](#), [23637](#), [23644](#), [23949](#), [24067](#),
[24157](#), [24172](#), [24413](#), [24414](#), [24493](#),
[24498](#), [24516](#), [24530](#), [24693](#), [24714](#),
[25030](#), [25464](#), [25471](#), [25476](#), [25602](#),
[27915](#), [27917](#), [28305](#), [28307](#), [28516](#),
[28518](#), [29016](#), [29018](#), [29020](#), [29022](#)
 - \box_gclear:N [220](#), [23605](#), [23614](#)
 - \box_gclear_new:N [220](#), [23611](#)
 - \box_gset_eq:NN ... [220](#), [23608](#), [23617](#)
 - \box_gset_eq_clear:NN ... [220](#), [23625](#)
 - \box_gset_to_last:N [223](#), [23679](#)
 - \box_ht:N [222](#), [14183](#),
[23637](#), [23646](#), [23948](#), [24066](#), [24156](#),
[24169](#), [24172](#), [24340](#), [24387](#), [24415](#),
[24416](#), [24484](#), [24489](#), [24516](#), [24523](#),
[24692](#), [24713](#), [25028](#), [25481](#), [25489](#),
[25494](#), [25596](#), [25600](#), [27917](#), [28307](#),
[28416](#), [28518](#), [28740](#), [29020](#), [29022](#)
 - \box_if_empty:NTF [222](#), [23675](#)
 - \box_if_empty_p:N [222](#), [23675](#)
 - \box_if_exist:NTF
..... [220](#), [23612](#), [23614](#), [23633](#), [23712](#)
 - \box_if_exist_p:N [220](#), [23633](#)
 - \box_if_horizontal:NTF ... [222](#), [23667](#)
 - \box_if_horizontal_p:N ... [222](#), [23667](#)
 - \box_if_vertical:NTF [223](#), [23667](#)
 - \box_if_vertical_p:N [223](#), [23667](#)
 - \box_log:N [224](#), [23698](#)
 - \box_log:Nnn [224](#), [23698](#)
 - \box_move_down:nn [221](#), [1010](#), [23656](#),
[25468](#), [25476](#), [25514](#), [25521](#), [25578](#)
 - \box_move_left:nn [221](#), [23656](#)
 - \box_move_right:nn [221](#), [23656](#)
 - \box_move_up:nn [221](#), [23656](#), [24734](#),
[25025](#), [25485](#), [25494](#), [25528](#), [25541](#)
 - \box_new:N [220](#),
[220](#), [23597](#), [23687](#), [23688](#), [23689](#),
[23690](#), [23691](#), [23935](#), [24226](#), [24292](#)
 - \box_resize:Nnn [29396](#), [29398](#)
 - \box_resize_to_ht:Nn [228](#), [24086](#)
 - \box_resize_to_ht_plus_dp:Nn ...
..... [228](#), [24086](#)
 - \box_resize_to_wd:Nn [228](#), [24086](#)
 - \box_resize_to_wd_and_ht:Nnn ...
..... [228](#), [24086](#)
 - \box_resize_to_wd_and_ht_plus_+
dp:Nnn
..... [229](#), [24048](#), [25715](#), [29397](#), [29399](#)
 - \box_rotate:Nn [229](#), [23936](#), [25571](#)
 - \box_scale:Nnn [229](#), [24144](#), [25739](#)
 - \box_set_dp:Nn
.. [222](#), [1010](#), [23643](#), [23975](#), [24198](#),
[24201](#), [24693](#), [24714](#), [25029](#), [25471](#),
[25479](#), [25517](#), [25522](#), [25583](#), [29375](#)
 - \box_set_eq:NN . [220](#), [23606](#), [23617](#),
[24402](#), [24716](#), [25033](#), [25499](#), [25546](#)
 - \box_set_eq_clear:NN [220](#), [23625](#)
 - \box_set_ht:Nn
..... [222](#), [23643](#), [23974](#), [24197](#),
[24202](#), [24692](#), [24713](#), [25027](#), [25488](#),
[25497](#), [25531](#), [25544](#), [25581](#), [29374](#)
 - \box_set_to_last:N [223](#), [23679](#)
 - \box_set_wd:Nn
.. [222](#), [23643](#), [23976](#), [24214](#), [24694](#),
[24715](#), [25031](#), [25584](#), [28319](#), [29373](#)
 - \box_show:N [221](#), [223](#), [23692](#)
 - \box_show:Nnn [223](#), [23692](#)
 - \box_trim:Nnnnn [241](#), [25456](#)
 - \box_use:N [221](#),
[221](#), [221](#), [23652](#), [23963](#), [24731](#),
[24734](#), [25022](#), [25025](#), [25461](#), [25469](#),
[25477](#), [25486](#), [25495](#), [25507](#), [25515](#),
[25521](#), [25529](#), [25542](#), [25579](#), [25586](#),
[27922](#), [27940](#), [27954](#), [28195](#), [28310](#),
[28337](#), [28351](#), [28521](#), [28537](#), [28549](#),
[28987](#), [29051](#), [29068](#), [29087](#), [29376](#)
 - \box_use_clear:N [29400](#), [29402](#)
 - \box_use_drop:N
..... [221](#), [23652](#), [23978](#), [24209](#),
[24218](#), [24815](#), [24952](#), [29401](#), [29403](#)
 - \box_viewport:Nnnnn [241](#), [25502](#)
 - \box_wd:N [222](#),
[14182](#), [23637](#), [23648](#), [23950](#), [24068](#),
[24158](#), [24178](#), [24417](#), [24418](#), [24488](#),
[24497](#), [24505](#), [24510](#), [24657](#), [24694](#),
[24715](#), [24732](#), [25023](#), [25032](#), [25508](#),
[25599](#), [25607](#), [25776](#), [25783](#), [27916](#),
[27924](#), [28306](#), [28312](#), [28415](#), [28517](#),
[28523](#), [28739](#), [29017](#), [29019](#), [29055](#)

- \c_empty_box
.. [220](#), [222](#), [223](#), [23606](#), [23608](#), [23687](#)
- \g_tmpa_box [223](#), [23688](#)
- \l_tmpa_box [223](#), [23688](#)
- \g_tmpb_box [223](#), [23688](#)
- \l_tmpb_box [223](#), [23688](#)
- box internal commands:
- \l__box_angle_fp
.. [23924](#), [23940](#), [23941](#), [23942](#), [23971](#)
- __box_autosize:Nnnn [24168](#)
- \l__box_bottom_dim [23927](#),
[23949](#), [24006](#), [24010](#), [24015](#), [24021](#),
[24026](#), [24030](#), [24039](#), [24041](#), [24058](#),
[24067](#), [24076](#), [24109](#), [24157](#), [24163](#)
- \l__box_bottom_new_dim
[23931](#), [23975](#), [24007](#), [24018](#), [24029](#),
[24040](#), [24075](#), [24162](#), [24198](#), [24202](#)
- \l__box_cos_fp [23925](#),
[23942](#), [23954](#), [23959](#), [23986](#), [23998](#)
- __box_dim_eval:n [23587](#),
[23644](#), [23646](#), [23648](#), [23657](#), [23659](#),
[23661](#), [23663](#), [23747](#), [23753](#), [23783](#),
[23790](#), [23798](#), [23820](#), [23859](#), [23865](#),
[23896](#), [23903](#), [23915](#), [23921](#), [25460](#),
[25462](#), [25506](#), [25508](#), [25517](#), [25541](#)
- __box_dim_eval:w [23587](#)
- \l__box_internal_box [23935](#), [23963](#),
[23964](#), [23970](#), [23974](#), [23975](#), [23976](#),
[23978](#), [24188](#), [24197](#), [24198](#), [24201](#),
[24202](#), [24209](#), [24214](#), [24218](#), [25458](#),
[25466](#), [25469](#), [25471](#), [25474](#), [25477](#),
[25479](#), [25481](#), [25483](#), [25486](#), [25488](#),
[25489](#), [25492](#), [25494](#), [25495](#), [25497](#),
[25499](#), [25504](#), [25512](#), [25515](#), [25517](#),
[25520](#), [25521](#), [25522](#), [25526](#), [25529](#),
[25531](#), [25539](#), [25542](#), [25544](#), [25546](#)
- \l__box_left_dim ... [23927](#), [23951](#),
[24006](#), [24008](#), [24017](#), [24021](#), [24026](#),
[24032](#), [24037](#), [24041](#), [24069](#), [24159](#)
- \l__box_left_new_dim [23931](#), [23966](#),
[23977](#), [24009](#), [24020](#), [24031](#), [24042](#)
- __box_log:nNnn [23698](#)
- __box_resize:N
.. [24048](#), [24097](#), [24112](#), [24124](#), [24140](#)
- __box_resize:NNN [24048](#)
- __box_resize_common:N
..... [24079](#), [24166](#), [24186](#)
- __box_resize_set_corners:N
.. [24048](#), [24090](#), [24105](#), [24120](#), [24132](#)
- \l__box_right_dim .. [23927](#), [23950](#),
[24004](#), [24010](#), [24015](#), [24019](#), [24028](#),
[24030](#), [24039](#), [24043](#), [24054](#), [24068](#),
[24074](#), [24122](#), [24134](#), [24158](#), [24165](#)
- \l__box_right_new_dim ... [23931](#),
[23977](#), [24011](#), [24022](#), [24033](#), [24044](#),
[24073](#), [24164](#), [24206](#), [24208](#), [24214](#)
- __box_rotate:N [23936](#)
- __box_rotate_quadrant_four: ...
..... [23936](#), [24035](#)
- __box_rotate_quadrant_one:
..... [23936](#), [24002](#)
- __box_rotate_quadrant_three: ...
..... [23936](#), [24024](#)
- __box_rotate_quadrant_two:
..... [23936](#), [24013](#)
- __box_rotate_xdir:nnN
[23936](#), [23980](#), [24008](#), [24010](#), [24019](#),
[24021](#), [24030](#), [24032](#), [24041](#), [24043](#)
- __box_rotate_ydir:nnN
[23936](#), [23991](#), [24004](#), [24006](#), [24015](#),
[24017](#), [24026](#), [24028](#), [24037](#), [24039](#)
- __box_scale_aux:N [24144](#), [24183](#)
- \l__box_scale_x_fp [24046](#),
[24053](#), [24074](#), [24096](#), [24111](#), [24121](#),
[24123](#), [24133](#), [24148](#), [24165](#), [24178](#),
[24180](#), [24181](#), [24182](#), [24192](#), [24204](#)
- \l__box_scale_y_fp
.... [24046](#), [24055](#), [24076](#), [24078](#),
[24091](#), [24096](#), [24106](#), [24111](#), [24123](#),
[24135](#), [24149](#), [24161](#), [24163](#), [24179](#),
[24180](#), [24181](#), [24182](#), [24193](#), [24195](#)
- __box_show:NNnn . [23696](#), [23706](#), [23710](#)
- \l__box_sin_fp
.. [23925](#), [23941](#), [23952](#), [23987](#), [23997](#)
- \l__box_top_dim [23927](#), [23948](#), [24004](#),
[24008](#), [24017](#), [24019](#), [24028](#), [24032](#),
[24037](#), [24043](#), [24058](#), [24066](#), [24078](#),
[24094](#), [24109](#), [24138](#), [24156](#), [24161](#)
- \l__box_top_new_dim
[23931](#), [23974](#), [24005](#), [24016](#), [24027](#),
[24038](#), [24077](#), [24160](#), [24197](#), [24201](#)
- \boxdir [901](#), [1813](#)
- \boxdirection [902](#)
- \boxmaxdepth [313](#)
- bp [200](#)
- \breakafterdirmode [903](#), [1724](#)
- \brokenpenalty [314](#)
- C
- \c [27411](#)
- \catcode 4, 5, 6, 7, 10, 218, 219, 220, 221,
[222](#), [223](#), [224](#), [225](#), [226](#), [231](#), [232](#),
[233](#), [234](#), [235](#), [236](#), [237](#), [238](#), [239](#), [315](#)
- catcode commands:
- \c_catcode_active_space_tl [257](#), [27612](#)
- \c_catcode_active_tl
..... [122](#), [509](#), [8644](#), [8704](#)

- \c_catcode_letter_token
..... [122](#), [509](#), [8626](#), [8694](#), [20101](#)
- \c_catcode_other_space_tl
..... [118](#), [569](#), [8624](#),
[10741](#), [10785](#), [10865](#), [10954](#), [11030](#)
- \c_catcode_other_token
..... [122](#), [509](#), [8626](#), [8699](#), [20099](#)
- \catcodetable [904](#), [1725](#)
- cc [200](#)
- ceil [197](#)
- \char [316](#), [8809](#)
- char commands:
- \l_char_active_seq
 [121](#), [144](#), [8454](#), [11092](#)
- \char_codepoint_to_bytes:n
 [257](#), [26483](#), [27196](#), [27216](#), [27217](#), [27373](#)
- \char_fold_case:N [257](#), [26455](#)
- \char_generate:nn . [118](#), [941](#), [1063](#),
 [8481](#), [8624](#), [10284](#), [20654](#), [21663](#),
 [26477](#), [27131](#), [27176](#), [27190](#), [27192](#),
 [27227](#), [27228](#), [27233](#), [27235](#), [27243](#),
 [27244](#), [27249](#), [27251](#), [27366](#), [27367](#)
- \char_gset_active_eq:NN ... [117](#), [8460](#)
- \char_gset_active_eq:nN ... [117](#), [8460](#)
- \char_lower_case:N [257](#), [26455](#)
- \char_mixed_case:N [257](#), [26455](#)
- \char_set_active_eq:NN
 [117](#), [8460](#), [11095](#)
- \char_set_active_eq:nN [117](#), [8460](#)
- \char_set_catcode:nn
 [120](#), [248](#), [249](#), [250](#), [251](#), [252](#), [253](#),
 [254](#), [255](#), [256](#), [8360](#), [8367](#), [8369](#),
 [8371](#), [8373](#), [8375](#), [8377](#), [8379](#), [8381](#),
 [8383](#), [8385](#), [8387](#), [8389](#), [8391](#), [8393](#),
 [8395](#), [8397](#), [8399](#), [8401](#), [8403](#), [8405](#),
 [8407](#), [8409](#), [8411](#), [8413](#), [8415](#), [8417](#),
 [8419](#), [8421](#), [8423](#), [8425](#), [8427](#), [8429](#)
- \char_set_catcode_active:N
 [119](#), [8366](#), [8461](#), [8519](#),
 [8645](#), [9509](#), [10364](#), [19905](#), [22878](#), [27613](#)
- \char_set_catcode_active:n
 [119](#), [8398](#), [8587](#), [11983](#), [11984](#)
- \char_set_catcode_alignment:N ...
 [119](#), [8366](#), [8633](#), [22930](#)
- \char_set_catcode_alignment:n ...
 [119](#), [266](#), [8398](#), [8566](#)
- \char_set_catcode_comment:N [119](#), [8366](#)
- \char_set_catcode_comment:n [119](#), [8398](#)
- \char_set_catcode_end_line:N ...
 [119](#), [8366](#)
- \char_set_catcode_end_line:n ...
 [119](#), [8398](#)
- \char_set_catcode_escape:N [119](#), [8366](#)
- \char_set_catcode_escape:n [119](#), [8398](#)
- \char_set_catcode_group_begin:N .
 [119](#), [8366](#), [19978](#), [22881](#)
- \char_set_catcode_group_begin:n .
 [119](#), [8398](#), [8559](#)
- \char_set_catcode_group_end:N ...
 [119](#), [8366](#), [19981](#), [22898](#)
- \char_set_catcode_group_end:n ...
 [119](#), [8398](#), [8561](#)
- \char_set_catcode_ignore:N [119](#), [8366](#)
- \char_set_catcode_ignore:n
 [119](#), [263](#), [264](#), [8398](#)
- \char_set_catcode_invalid:N [119](#), [8366](#)
- \char_set_catcode_invalid:n [119](#), [8398](#)
- \char_set_catcode_letter:N
 [119](#), [8366](#), [15765](#), [15766](#), [22907](#)
- \char_set_catcode_letter:n
 [119](#), [267](#), [269](#), [8398](#), [8583](#)
- \char_set_catcode_math_subscript:N
 [119](#), [8366](#), [8637](#), [22895](#)
- \char_set_catcode_math_subscript:n
 [119](#), [8398](#), [8578](#)
- \char_set_catcode_math_superscript:N
 [119](#), [8366](#), [22933](#)
- \char_set_catcode_math_superscript:n
 [119](#), [268](#), [8398](#), [8576](#)
- \char_set_catcode_math_toggle:N .
 [119](#), [8366](#), [8631](#), [22910](#)
- \char_set_catcode_math_toggle:n .
 [119](#), [8398](#), [8564](#)
- \char_set_catcode_other:N
 [119](#), [8366](#), [20138](#), [22913](#)
- \char_set_catcode_other:n
 [119](#), [265](#), [270](#), [8398](#), [8522](#), [8585](#)
- \char_set_catcode_parameter:N ...
 [119](#), [8366](#), [22916](#)
- \char_set_catcode_parameter:n ...
 [119](#), [8398](#), [8574](#)
- \char_set_catcode_space:N . [119](#), [8366](#)
- \char_set_catcode_space:n
 [119](#), [271](#), [8398](#), [8581](#)
- \char_set_lccode:nn [120](#), [4280](#), [4297](#),
 [8430](#), [8467](#), [8591](#), [8592](#), [9505](#), [9506](#),
 [9507](#), [9508](#), [10361](#), [10362](#), [10363](#), [27614](#)
- \char_set_mathcode:nn [121](#), [8430](#)
- \char_set_sfcode:nn [121](#), [8430](#)
- \char_set_uccode:nn [120](#), [8430](#)
- \char_show_value_catcode:n [120](#), [8360](#)
- \char_show_value_lccode:n . [120](#), [8430](#)
- \char_show_value_mathcode:n [121](#), [8430](#)
- \char_show_value_sfcode:n . [121](#), [8430](#)
- \char_show_value_uccode:n . [121](#), [8430](#)
- \l_char_special_seq [121](#), [8454](#)
- \char_upper_case:N [257](#), [26455](#)

- \char_value_catcode:n [120](#), [248](#), [249](#),
[250](#), [251](#), [252](#), [253](#), [254](#), [255](#), [256](#),
[4292](#), [4322](#), [8360](#), [26477](#), [27131](#), [27177](#)
- \char_value_lccode:n
..... [120](#), [8430](#), [25360](#), [26456](#), [26466](#)
- \char_value_mathcode:n [121](#), [8430](#)
- \char_value_sfcode:n [121](#), [8430](#)
- \char_value_uccode:n [121](#), [8430](#), [26458](#)
- char internal commands:
- __char_change_case:nN [26455](#)
- __char_change_case:NN [26455](#)
- __char_codepoint_to_bytes_-
 auxi:n [26483](#)
- __char_codepoint_to_bytes_-
 auxii:Nnn [26483](#)
- __char_codepoint_to_bytes_-
 auxiii:n [26483](#)
- __char_codepoint_to_bytes_end: .
 [26483](#)
- __char_codepoint_to_bytes_-
 output:nnn [26483](#)
- __char_codepoint_to_bytes_-
 outputi:nw [26483](#)
- __char_codepoint_to_bytes_-
 outputii:nw [26483](#)
- __char_codepoint_to_bytes_-
 outputiii:nw [26483](#)
- __char_codepoint_to_bytes_-
 outputiv:nw [26483](#)
- __char_data_auxi:w [25331](#),
 [25352](#), [25356](#), [25384](#), [25389](#), [25422](#)
- __char_data_auxii:w
 [25333](#), [25334](#), [25367](#),
 [25371](#), [25392](#), [25393](#), [25395](#), [25397](#)
- \g__char_data_ior .. [25306](#), [25330](#),
 [25347](#), [25354](#), [25355](#), [25381](#), [25387](#),
 [25388](#), [25411](#), [25424](#), [25440](#), [25441](#)
- __char_generate:n
 [25311](#), [25343](#), [25363](#), [25375](#),
 [25376](#), [25378](#), [25404](#), [25405](#), [25407](#)
- __char_generate:w
 .. [25310](#), [25342](#), [25362](#), [25373](#), [25402](#)
- __char_generate_aux:nn [8481](#)
- __char_generate_aux:nnw [8481](#)
- __char_generate_aux:w ... [8483](#), [8487](#)
- __char_generate_auxii:nnw ... [8481](#)
- __char_generate_invalid_-
 catcode: [8481](#)
- __char_int_to_roman:w
 [8480](#), [8596](#), [8619](#)
- __char_tmp:n
 [8589](#), [8601](#), [8604](#), [8606](#), [8609](#)
- __char_tmp:NN .. [25429](#), [25435](#), [25437](#)
- __char_tmp:nN [8462](#), [8473](#), [8474](#)
- \l__char_tmp_tl [8481](#)
- \l__char_tmpa_tl [25337](#),
 [25338](#), [25340](#), [25347](#), [25349](#), [25352](#)
- \l__char_tmpp_tl [25339](#), [25340](#)
- \chardef [228](#), [241](#), [317](#)
- choice commands:
 .choice: [170](#), [12452](#)
- choices commands:
 .choices:nn [170](#), [12454](#)
- \cite [27459](#)
- \cleaders [318](#)
- \clearmarks [905](#), [1726](#)
- clist commands:
- \clist_clear:N [108](#),
 [108](#), [7822](#), [7839](#), [8002](#), [12575](#), [12600](#)
- \clist_clear_new:N [108](#), [7826](#)
- \clist_concat:NNN [108](#), [7865](#), [7891](#), [7904](#)
- \clist_const:Nn [108](#), [7819](#)
- \clist_count:N
 [112](#), [115](#), [8202](#), [8231](#), [8263](#), [8329](#)
- \clist_count:n . [112](#), [8202](#), [8294](#), [8320](#)
- \clist_gclear:N [108](#), [7822](#), [7841](#)
- \clist_gclear_new:N [108](#), [7826](#)
- \clist_gconcat:NNN
 [108](#), [7865](#), [7893](#), [7906](#)
- \clist_get:NN [114](#), [7916](#)
- \clist_get:NNTF [114](#), [7953](#)
- \clist_gpop:NN [114](#), [7927](#)
- \clist_gpop:NNTF [114](#), [7953](#)
- \clist_gpush:Nn [114](#), [7978](#)
- \clist_gput_left:Nn
 [109](#), [7890](#), [7986](#), [7987](#),
 [7988](#), [7989](#), [7990](#), [7991](#), [7992](#), [7993](#)
- \clist_gput_right:Nn [109](#), [7903](#)
- \clist_gremove_all:Nn [110](#), [8012](#)
- \clist_gremove_duplicates:N [110](#), [7996](#)
- \clist_greverse:N [110](#), [8051](#)
- .clist_gset:N [170](#), [12464](#)
- \clist_gset:Nn [109](#), [7884](#)
- \clist_gset_eq:NN ... [108](#), [7830](#), [7999](#)
- \clist_gset_from_seq:NN
 [108](#), [7838](#), [8015](#), [19586](#)
- \clist_gsort:Nn [110](#), [8069](#), [19571](#)
- \clist_if_empty:NNTF [110](#), [7874](#), [8036](#),
 [8069](#), [8126](#), [8156](#), [8176](#), [8328](#), [12339](#)
- \clist_if_empty:NNTF [111](#), [8073](#)
- \clist_if_empty_p:N [110](#), [8069](#)
- \clist_if_empty_p:n [111](#), [8073](#)
- \clist_if_exist:NNTF
 [108](#), [7880](#), [8229](#), [11183](#), [11268](#)
- \clist_if_exist_p:N [108](#), [7880](#)
- \clist_if_in:NnNTF [107](#), [111](#), [8005](#), [8087](#)
- \clist_if_in:nnNTF ... [111](#), [8087](#), [13576](#)
- \clist_item:Nn [115](#), [498](#), [498](#), [8260](#), [8329](#)

- \clist_item:nn .. [115](#), [498](#), [8291](#), [8324](#)
- \clist_log:N [115](#), [8332](#)
- \clist_log:n [115](#), [8346](#)
- \clist_map_break: [112](#), [8130](#),
[8135](#), [8144](#), [8148](#), [8164](#), [8182](#), [8198](#)
- \clist_map_break:n [112](#),
[8107](#), [8198](#), [12716](#), [12777](#), [19579](#), [19585](#)
- \clist_map_function:NN [63](#),
[111](#), [5886](#), [5896](#), [8110](#), [8124](#), [8207](#), [8342](#)
- \clist_map_function:Nn [494](#)
- \clist_map_function:nN
.. [111](#), [248](#), [249](#), [495](#), [5891](#), [5901](#),
[8140](#), [8351](#), [12829](#), [26054](#), [28103](#), [28824](#)
- \clist_map_function:nn [29264](#)
- \clist_map_inline:Nn [111](#), [111](#), [493](#),
[8003](#), [8154](#), [12711](#), [12767](#), [19579](#), [19585](#)
- \clist_map_inline:nn
[111](#), [2189](#), [2197](#), [4029](#), [8154](#), [12300](#),
[12370](#), [13046](#), [25126](#), [25138](#), [26282](#)
- \clist_map_variable:NNn ... [112](#), [8174](#)
- \clist_map_variable:nNn ... [112](#), [8174](#)
- \clist_new:N .. [107](#), [108](#), [482](#), [7817](#),
[7994](#), [8353](#), [8354](#), [8355](#), [8356](#), [12123](#)
- \clist_pop:NN [114](#), [7927](#)
- \clist_pop:NNTF [114](#), [7953](#)
- \clist_push:Nn [114](#), [7978](#)
- \clist_put_left:Nn
..... [109](#), [7890](#), [7978](#), [7979](#),
[7980](#), [7981](#), [7982](#), [7983](#), [7984](#), [7985](#)
- \clist_put_right:Nn
..... [109](#), [7903](#), [8006](#), [12806](#)
- \clist_rand_item:N [115](#), [8319](#)
- \clist_rand_item:n ... [115](#), [250](#), [8319](#)
- \clist_remove_all:Nn [110](#), [8012](#)
- \clist_remove_duplicates:N
..... [107](#), [110](#), [7996](#)
- \clist_reverse:N [110](#), [8051](#)
- \clist_reverse:n
..... [110](#), [491](#), [8052](#), [8054](#), [8057](#)
- .clist_set:N [170](#), [12464](#)
- \clist_set:Nn [109](#), [7884](#), [7891](#), [7893](#),
[7904](#), [7906](#), [8093](#), [8170](#), [8187](#), [12338](#)
- \clist_set_eq:NN [108](#), [7830](#), [7997](#), [12696](#)
- \clist_set_from_seq:NN
..... [108](#), [7838](#), [8013](#), [19580](#)
- \clist_show:N [115](#), [115](#), [8332](#)
- \clist_show:n [115](#), [115](#), [8346](#)
- \clist_sort:Nn [110](#), [8069](#), [19571](#)
- \clist_use:Nn [113](#), [8227](#)
- \clist_use:Nnnn [113](#), [439](#), [8227](#)
- \c_empty_clist
... [116](#), [7770](#), [7918](#), [7933](#), [7955](#), [7969](#)
- \l_foo_clist [205](#)
- \g_tmpa_clist [116](#), [8353](#)
- \l_tmpa_clist [116](#), [8353](#)
- \g_tmpb_clist [116](#), [8353](#)
- \l_tmpb_clist [116](#), [8353](#)
- clist internal commands:
- __clist_concat:NNNN [7865](#)
- __clist_count:n [8202](#)
- __clist_count:w [8202](#)
- __clist_get:wN [7916](#), [7958](#)
- __clist_if_empty_n:w [8073](#)
- __clist_if_empty_n:wNw [8073](#)
- __clist_if_in_return:nnN [8087](#)
- __clist_if_wrap:nTF
... [483](#), [7792](#), [7816](#), [7857](#), [8018](#), [8099](#)
- __clist_if_wrap:w [483](#), [7792](#)
- \l__clist_internal_clist ... [486](#),
[7771](#), [7896](#), [7897](#), [7909](#), [7910](#), [8093](#),
[8094](#), [8095](#), [8170](#), [8171](#), [8187](#), [8188](#)
- \l__clist_internal_remove_clist .
..... [7994](#), [8002](#), [8005](#), [8006](#), [8008](#)
- \l__clist_internal_remove_seq ...
..... [7994](#), [8020](#), [8021](#), [8022](#)
- __clist_item:nnnN [8260](#), [8293](#)
- __clist_item_n:nw [8291](#)
- __clist_item_n_end:n [8291](#)
- __clist_item_N_loop:nw [8260](#)
- __clist_item_n_loop:nw [8291](#)
- __clist_item_n_strip:n [8291](#)
- __clist_item_n_strip:w [8291](#)
- __clist_map_function:Nw
..... [493](#), [8124](#), [8161](#)
- __clist_map_function_n:Nn [494](#), [8140](#)
- __clist_map_unbrace:Nw ... [494](#), [8140](#)
- __clist_map_variable:Nnw [8174](#)
- __clist_pop:NNN [7927](#)
- __clist_pop:wN [7927](#)
- __clist_pop:wwNNN .. [487](#), [7927](#), [7972](#)
- __clist_pop_TF:NNN [7953](#)
- __clist_put_left:NNNn [7890](#)
- __clist_put_right:NNNn [7903](#)
- __clist_rand_item:nn [8319](#)
- __clist_remove_all: [8012](#)
- __clist_remove_all:NNNn [8012](#)
- __clist_remove_all:w [490](#), [8012](#)
- __clist_remove_duplicates:NN . [7996](#)
- __clist_reverse:wwNww [491](#), [8057](#)
- __clist_reverse_end:ww ... [491](#), [8057](#)
- __clist_sanitize:n
..... [7779](#), [7820](#), [7885](#), [7887](#)
- __clist_sanitize:Nn [483](#), [7779](#)
- __clist_set_from_seq:n [7838](#)
- __clist_set_from_seq:NNNN ... [7838](#)
- __clist_show:NN [8332](#)
- __clist_show:Nn [8346](#)

- __clist_tmp:w [490](#), [7772](#),
8025, 8047, 8101, 8110, 8114, 8116
- __clist_trim_next:w
[483](#), [493](#), [7773](#), [7782](#), [7790](#), 8143, 8151
- __clist_use:nwn [8227](#)
- __clist_use:nwwwnwn [496](#), [8227](#)
- __clist_use:wn [8227](#)
- __clist_wrap_item:w [483](#), [7788](#), [7815](#)
- \closein [319](#)
- \closeout [320](#)
- \clubpenalties [618](#), [1431](#)
- \clubpenalty [321](#)
- cm [200](#)
- code commands:
- .code:n [170](#), [12462](#)
- coffin commands:
- \coffin_attach:NnnNnnnn
..... [232](#), [998](#), [24688](#)
- \coffin_attach_mark:NnnNnnnn ...
..... [24688](#), [24882](#), [24903](#), [24919](#)
- \coffin_clear:N [231](#), [24281](#)
- \coffin_display_handles:Nn [233](#), [24925](#)
- \coffin_dp:N
.... [233](#), [24413](#), [25049](#), [25713](#), [25741](#)
- \coffin_ht:N
.... [233](#), [24413](#), [25048](#), [25713](#), [25741](#)
- \coffin_if_exist:NTF [231](#), [24260](#), [24274](#)
- \coffin_if_exist_p:N [231](#), [24260](#)
- \coffin_join:NnnNnnnn ... [233](#), [24647](#)
- \coffin_log_structure:N .. [234](#), [25035](#)
- \coffin_mark_handle:Nnnn . [234](#), [24870](#)
- \coffin_new:N [231](#),
[983](#), [24290](#), [24407](#), [24409](#), [24410](#),
[24411](#), [24412](#), [24818](#), [24819](#), [24820](#)
- \coffin_resize:Nnn [241](#), [25706](#)
- \coffin_rotate:Nn [241](#), [25558](#)
- \coffin_scale:Nnn [241](#), [25735](#)
- \coffin_set_eq:NN
[231](#), [24398](#), [24685](#), [24707](#), [24736](#), [24946](#)
- \coffin_set_horizontal_pole:Nnn .
..... [232](#), [24450](#)
- \coffin_set_vertical_pole:Nnn ...
..... [232](#), [24450](#)
- \coffin_show_structure:N
..... [234](#), [234](#), [25035](#)
- \coffin_typeset:Nnnnn ... [233](#), [24810](#)
- \coffin_wd:N
.... [233](#), [24413](#), [25050](#), [25709](#), [25745](#)
- \c_empty_coffin ... [234](#), [24407](#), [24813](#)
- \l_tmpa_coffin [234](#), [24411](#)
- \l_tmpp_coffin [234](#), [24411](#)
- coffin internal commands:
- __coffin_align:NnnNnnnnN
.. [24649](#), [24690](#), [24711](#), [24719](#), [24813](#)
- \l__coffin_aligned_coffin
..... [24407](#), [24650](#),
[24651](#), [24655](#), [24661](#), [24665](#), [24668](#),
[24684](#), [24685](#), [24691](#), [24692](#), [24693](#),
[24694](#), [24695](#), [24699](#), [24702](#), [24706](#),
[24707](#), [24712](#), [24713](#), [24714](#), [24715](#),
[24716](#), [24750](#), [24767](#), [24814](#), [24815](#),
[25020](#), [25027](#), [25029](#), [25031](#), [25033](#)
- \l__coffin_aligned_internal_-
 coffin [24407](#), [24729](#), [24736](#)
- \l__coffin_bottom_corner_dim ...
..... [25554](#), [25578](#), [25582](#),
[25658](#), [25669](#), [25670](#), [25690](#), [25698](#)
- \l__coffin_bounding_prop
..... [25552](#), [25567](#), [25595](#),
[25597](#), [25603](#), [25605](#), [25614](#), [25677](#)
- \l__coffin_bounding_shift_dim ...
.. [25553](#), [25576](#), [25676](#), [25682](#), [25683](#)
- __coffin_calculate_intersection:Nnn
..... [24535](#), [24721](#), [24724](#), [25013](#)
- __coffin_calculate_intersection:nnnnnnnn
..... [24535](#), [24959](#)
- __coffin_calculate_intersection_-
 aux:nnnnnN [24535](#)
- \c__coffin_corners_prop
..... [24229](#), [24297](#), [24432](#)
- \l__coffin_cos_fp
[1013](#), [1015](#), [25550](#), [25561](#), [25641](#), [25650](#)
- __coffin_display_attach:Nnnnn [24925](#)
- \l__coffin_display_coffin
.... [24818](#), [24946](#), [24952](#), [25022](#),
[25023](#), [25028](#), [25030](#), [25032](#), [25033](#)
- \l__coffin_display_coord_coffin .
..... [24818](#), [24884](#),
[24904](#), [24920](#), [24967](#), [24987](#), [25006](#)
- \l__coffin_display_font_tl
..... [24863](#), [24892](#), [24975](#)
- __coffin_display_handles_-
 aux:nnnn [24925](#)
- __coffin_display_handles_-
 aux:nnnnnn [24925](#)
- \l__coffin_display_handles_prop .
.. [24821](#), [24895](#), [24899](#), [24978](#), [24982](#)
- \l__coffin_display_offset_dim ...
.. [24858](#), [24921](#), [24922](#), [25007](#), [25008](#)
- \l__coffin_display_pole_coffin ..
.. [24818](#), [24872](#), [24883](#), [24927](#), [24965](#)
- \l__coffin_display_poles_prop ...
..... [24862](#), [24937](#),
[24942](#), [24945](#), [24947](#), [24949](#), [24956](#)
- \l__coffin_display_x_dim
..... [24860](#), [24962](#), [25017](#)
- \l__coffin_display_y_dim
..... [24860](#), [24963](#), [25019](#)

- \l__coffin_error_bool [24250](#), [24539](#), [24543](#),
[24557](#), [24572](#), [24603](#), [24958](#), [24960](#)
- __coffin_find_bounding_shift: ..
..... [25570](#), [25674](#)
- __coffin_find_bounding_shift_
aux:nn [25674](#)
- __coffin_find_corner_maxima:N ..
..... [25569](#), [25654](#)
- __coffin_find_corner_maxima_
aux:nn [25654](#)
- __coffin_get_pole:NnN
[24419](#), [24537](#), [24538](#), [24777](#), [24778](#),
[24781](#), [24782](#), [24939](#), [24940](#), [24943](#)
- __coffin_gset_eq_structure:NN [24436](#)
- __coffin_if_exist:NTF
[24272](#), [24283](#), [24305](#), [24320](#), [24351](#),
[24367](#), [24400](#), [24452](#), [24463](#), [25043](#)
- \l__coffin_internal_box
..... [24226](#), [24334](#),
[24340](#), [24345](#), [24381](#), [24387](#), [24392](#),
[25572](#), [25581](#), [25583](#), [25584](#), [25586](#)
- \l__coffin_internal_dim
.... [24226](#), [24656](#), [24658](#), [24659](#),
[25602](#), [25604](#), [25608](#), [25740](#), [25743](#)
- \l__coffin_internal_tl ... [24226](#),
[24748](#), [24749](#), [24751](#), [24896](#), [24897](#),
[24900](#), [24901](#), [24909](#), [24914](#), [24979](#),
[24980](#), [24983](#), [24984](#), [24993](#), [24998](#)
- \l__coffin_left_corner_dim
..... [25554](#), [25576](#), [25585](#),
[25659](#), [25665](#), [25666](#), [25689](#), [25697](#)
- __coffin_mark_handle_aux:nnnnNnn
..... [24870](#)
- __coffin_offset_corner:Nnnnn . [24757](#)
- __coffin_offset_corners:Nnn ...
.. [24673](#), [24674](#), [24680](#), [24681](#), [24757](#)
- __coffin_offset_pole:Nnnnnnn . [24738](#)
- __coffin_offset_poles:Nnn
..... [24671](#), [24672](#),
[24677](#), [24678](#), [24703](#), [24704](#), [24738](#)
- \l__coffin_offset_x_dim
.... [24251](#), [24653](#), [24654](#), [24657](#),
[24669](#), [24671](#), [24673](#), [24679](#), [24682](#),
[24705](#), [24725](#), [24733](#), [25016](#), [25024](#)
- \l__coffin_offset_y_dim
[24251](#), [24672](#), [24674](#), [24679](#), [24682](#),
[24705](#), [24727](#), [24734](#), [25018](#), [25025](#)
- \l__coffin_pole_a_tl
[24253](#), [24537](#), [24542](#), [24777](#), [24780](#),
[24781](#), [24784](#), [24939](#), [24941](#), [24944](#)
- \l__coffin_pole_b_tl [24253](#),
[24538](#), [24542](#), [24778](#), [24780](#), [24782](#),
[24784](#), [24940](#), [24941](#), [24943](#), [24944](#)
- \c__coffin_poles_prop
..... [24236](#), [24299](#), [24434](#)
- __coffin_reset_structure:N
..... [24286](#), [24312](#), [24331](#),
[24357](#), [24378](#), [24429](#), [24661](#), [24695](#)
- __coffin_resize_common:Nnn
..... [25716](#), [25719](#), [25746](#)
- \l__coffin_right_corner_dim
.. [25554](#), [25585](#), [25657](#), [25667](#), [25668](#)
- __coffin_rotate_bounding:nnn ...
..... [25568](#), [25611](#)
- __coffin_rotate_corner:Nnnnn ...
..... [25563](#), [25611](#)
- __coffin_rotate_pole:Nnnnnnn ...
..... [25565](#), [25623](#)
- __coffin_rotate_vector:nnNN ...
.. [25613](#), [25619](#), [25625](#), [25626](#), [25635](#)
- __coffin_scale_corner:Nnnnn
..... [25722](#), [25757](#)
- __coffin_scale_pole:Nnnnnnn
..... [25724](#), [25757](#)
- __coffin_scale_vector:nnNN
..... [25750](#), [25759](#), [25765](#)
- \l__coffin_scale_x_fp [25702](#), [25708](#),
[25725](#), [25737](#), [25739](#), [25745](#), [25753](#)
- \l__coffin_scale_y_fp ... [25702](#),
[25710](#), [25738](#), [25739](#), [25743](#), [25755](#)
- \l__coffin_scaled_total_height_
dim [25704](#), [25742](#), [25747](#)
- \l__coffin_scaled_width_dim
..... [25704](#), [25744](#), [25747](#)
- __coffin_set_bounding:N [25566](#), [25593](#)
- __coffin_set_eq_structure:NN ...
..... [24403](#), [24436](#)
- __coffin_set_pole:Nnn
[24335](#), [24382](#), [24450](#), [24750](#), [24790](#),
[24794](#), [24802](#), [24806](#), [25628](#), [25766](#)
- __coffin_shift_corner:Nnnn
..... [25588](#), [25685](#)
- __coffin_shift_pole:Nnnnnnn
..... [25590](#), [25685](#)
- __coffin_show_structure:NN .. [25035](#)
- \l__coffin_sin_fp
[1013](#), [1015](#), [25550](#), [25560](#), [25642](#), [25649](#)
- \l__coffin_slope_x_fp
.. [24248](#), [24597](#), [24602](#), [24611](#), [24619](#)
- \l__coffin_slope_y_fp
.. [24248](#), [24599](#), [24602](#), [24613](#), [24620](#)
- __coffin_to_value:N
[24259](#), [24264](#), [24294](#), [24295](#), [24296](#),
[24298](#), [24422](#), [24431](#), [24433](#), [24438](#),
[24439](#), [24440](#), [24441](#), [24445](#), [24446](#),
[24447](#), [24448](#), [24474](#), [24482](#), [24485](#),
[24491](#), [24494](#), [24503](#), [24508](#), [24513](#),

- 24520, 24527, 24665, 24699, 24701,
 24740, 24759, 24767, 24938, 25054,
 25562, 25564, 25587, 25589, 25620,
 25660, 25687, 25695, 25721, 25723,
 25728, 25731, 25760, 25774, 25781
 \l_coffin_top_corner_dim
 .. 25554, 25582, 25656, 25671, 25672
 _coffin_update_B:nnnnnnnnN . 24775
 _coffin_update_corners:N
 .. 24314, 24333, 24359, 24380, 24480
 _coffin_update_poles:N
 24313, 24332,
 24358, 24379, 24501, 24668, 24702
 _coffin_update_T:nnnnnnnnN . 24775
 _coffin_update_vertical_-
 poles:NNN 24684, 24706, 24775
 \l_coffin_x_dim
 24255, 24546, 24555, 24575, 24578,
 24585, 24594, 24605, 24625, 24722,
 24726, 24745, 24753, 24962, 25014,
 25613, 25615, 25619, 25621, 25625,
 25630, 25759, 25761, 25765, 25768
 \l_coffin_x_prime_dim
 24255, 24722,
 24726, 25014, 25017, 25627, 25631
 _coffin_x_shift_corner:Nnnn ...
 25729, 25772
 _coffin_x_shift_pole:Nnnnnn ...
 25732, 25772
 \l_coffin_y_dim
 24255, 24547, 24560, 24563,
 24570, 24587, 24592, 24626, 24723,
 24728, 24746, 24753, 24963, 25015,
 25613, 25615, 25619, 25621, 25625,
 25630, 25759, 25761, 25765, 25768
 \l_coffin_y_prime_dim
 24255, 24723,
 24728, 25015, 25019, 25627, 25632
 \color 24878, 24890, 24933, 24973
 color commands:
 \color_ensure_current:
 235, 981, 24309, 24353, 25086
 \color_group_begin:
 235, 235, 23729,
 23734, 23740, 23748, 23754, 23763,
 23770, 23785, 23792, 23799, 23804,
 23815, 23817, 23821, 23826, 23832,
 23838, 23846, 23852, 23860, 23866,
 23875, 23882, 23898, 23905, 25084
 \color_group_end: 235, 235,
 23729, 23734, 23740, 23748, 23754,
 23776, 23799, 23804, 23815, 23817,
 23821, 23826, 23832, 23838, 23846,
 23852, 23860, 23866, 23889, 25084
 color internal commands:
 \l__color_current_tl
 1000, 25084, 25089, 25091, 25106
 _color_select:n 25091, 25093
 _color_select:w 25093
 _color_select_cmyk:w 25093
 _color_select_gray:w 25093
 _color_select_rgb:w 25093
 _color_select_spot:w 25093
 \columnwidth 24327, 24373
 \copy 322
 \copyfont 1013, 1622
 cos 197
 cosd 198
 cot 197
 cotd 198
 \count 171, 173, 174, 175,
 179, 180, 182, 183, 186, 188, 189,
 190, 191, 195, 196, 198, 199, 323, 8817
 \countdef 324
 \cr 325
 \crampeddisplaystyle 906, 1727
 \crampedscriptscriptstyle 907, 1729
 \crampedscriptstyle 909, 1731
 \crampedtextstyle 910, 1732
 \crr 326
 \creationdate 879
 \cs 15619
 cs commands:
 \cs:w 16, 940,
 940, 2063, 2085, 2087, 2136, 2760,
 2788, 2986, 3050, 3160, 3209, 3218,
 3220, 3224, 3225, 3226, 3288, 3294,
 3300, 3306, 3326, 3328, 3333, 3340,
 3341, 3447, 3451, 3490, 3978, 6506,
 6620, 7321, 7391, 7634, 7636, 11340,
 11674, 11730, 11823, 11864, 12751,
 12774, 12787, 12799, 13325, 13344,
 13411, 14240, 14429, 14461, 14878,
 14904, 14917, 14953, 15464, 17167,
 18189, 22815, 22818, 23601, 25868
 \cs_end: 16, 371, 2063,
 2085, 2087, 2091, 2136, 2754, 2760,
 2782, 2788, 2913, 2986, 3050, 3160,
 3209, 3218, 3220, 3224, 3225, 3226,
 3288, 3294, 3300, 3306, 3326, 3328,
 3333, 3340, 3341, 3447, 3451, 3490,
 3978, 6506, 6620, 7321, 7328, 7371,
 7381, 7391, 7631, 7637, 7639, 7641,
 7643, 7645, 7647, 7649, 7651, 7653,
 7655, 7657, 11340, 11674, 11730,
 11823, 11864, 12424, 12751, 12775,
 12788, 12799, 13328, 13344, 13419,
 14243, 14433, 14465, 14884, 14910,

- 14923, 14956, 15470, 17167, 18192,
22682, 22832, 23601, 25866, 25868
- `\cs_generate_from_arg_count:NNnn`
..... 13, 2966, 3008
- `\cs_generate_variant:Nn`
..... 9, 22, 24, 25, 242, 242,
366, 367, 3756, 4020, 4022, 4024,
4026, 4060, 4073, 4074, 4079, 4080,
4085, 4086, 4106, 4107, 4124, 4125,
4157, 4158, 4159, 4160, 4161, 4162,
4187, 4188, 4189, 4190, 4191, 4192,
4193, 4194, 4219, 4220, 4221, 4222,
4223, 4224, 4225, 4226, 4269, 4270,
4271, 4272, 4340, 4341, 4342, 4343,
4405, 4406, 4411, 4412, 4554, 4572,
4586, 4602, 4607, 4609, 4618, 4630,
4631, 4650, 4653, 4658, 4659, 4759,
4770, 4771, 4793, 4803, 4938, 4945,
4947, 5024, 5045, 5047, 5083, 5098,
5099, 5102, 5103, 5114, 5136, 5137,
5138, 5139, 5172, 5173, 5178, 5179,
5268, 5326, 5344, 5370, 5421, 5482,
5560, 5579, 5617, 5632, 5649, 5650,
5651, 5664, 5706, 5768, 5769, 5862,
5865, 5868, 5871, 5874, 5903, 5904,
5905, 5906, 5907, 5908, 5944, 5945,
5950, 5951, 5973, 5974, 5975, 5976,
5981, 5982, 5983, 5984, 6001, 6002,
6027, 6028, 6045, 6046, 6106, 6119,
6120, 6138, 6164, 6165, 6217, 6223,
6243, 6272, 6283, 6284, 6308, 6331,
6345, 6379, 6381, 6509, 6534, 6552,
6553, 6558, 6559, 6562, 6565, 6590,
6591, 6592, 6593, 6606, 6607, 6608,
6609, 6616, 6617, 6619, 7251, 7255,
7400, 7413, 7414, 7415, 7416, 7419,
7420, 7433, 7434, 7451, 7453, 7591,
7592, 7597, 7598, 7821, 7861, 7862,
7863, 7864, 7878, 7879, 7888, 7889,
7899, 7900, 7901, 7902, 7912, 7913,
7914, 7915, 7926, 7951, 7952, 8010,
8011, 8049, 8050, 8055, 8056, 8139,
8173, 8197, 8210, 8250, 8259, 8283,
8290, 8331, 8333, 8335, 8476, 8477,
8478, 8479, 9069, 9072, 9075, 9078,
9081, 9096, 9099, 9102, 9169, 9170,
9171, 9172, 9179, 9180, 9199, 9200,
9201, 9202, 9215, 9251, 9253, 9255,
9257, 9274, 9275, 9337, 9352, 9358,
9360, 9887, 10315, 10316, 10317,
10318, 10426, 10431, 10473, 10491,
10619, 10644, 10651, 10663, 10678,
10681, 10699, 10807, 11148, 11191,
11343, 11350, 11356, 11357, 11362,
11363, 11382, 11383, 11387, 11391,
11401, 11402, 11412, 11413, 11673,
11712, 11733, 11740, 11745, 11746,
11751, 11752, 11771, 11772, 11774,
11776, 11783, 11784, 11791, 11792,
11822, 11844, 11845, 11847, 11867,
11874, 11881, 11882, 11887, 11888,
11913, 11914, 11917, 11920, 11927,
11928, 11935, 11936, 11947, 11949,
12145, 12244, 12260, 12321, 12435,
12568, 12569, 12572, 12580, 12588,
12597, 12605, 12613, 12627, 12645,
12678, 12832, 13075, 13077, 13111,
13693, 13696, 15361, 15368, 15369,
15370, 15373, 15374, 15377, 15378,
15383, 15384, 15391, 15392, 15393,
15394, 15396, 15398, 15614, 15676,
18687, 18741, 18819, 18864, 18879,
18934, 19549, 19551, 19573, 19576,
19582, 19588, 20285, 21015, 23604,
23609, 23610, 23615, 23616, 23623,
23624, 23631, 23632, 23640, 23641,
23642, 23649, 23650, 23651, 23654,
23655, 23685, 23686, 23694, 23697,
23700, 23709, 23727, 23742, 23743,
23756, 23757, 23772, 23773, 23794,
23795, 23812, 23813, 23840, 23841,
23854, 23855, 23868, 23869, 23884,
23885, 23907, 23908, 23911, 23912,
23916, 23923, 24063, 24100, 24115,
24127, 24143, 24153, 24170, 24173,
24289, 24302, 24317, 24348, 24364,
24397, 24406, 24477, 24478, 24479,
24687, 24718, 24817, 24924, 25010,
25037, 25040, 25095, 25455, 25501,
25548, 25592, 25718, 25749, 25906,
25907, 25908, 25909, 25945, 25948,
25951, 25962, 25976, 25986, 26016,
26056, 26307, 26320, 26380, 26381,
26413, 26414, 26433, 26436, 26559,
26562, 26597, 27536, 27540, 27585,
27589, 27735, 27790, 27876, 27888,
27961, 28163, 28169, 28278, 28298,
28505, 28604, 28714, 28730, 28754,
28888, 28997, 29004, 29112, 29143
- `\cs_gset:Nn` 13, 2981, 3045
- `\cs_gset:Npn` 9,
11, 311, 2120, 2861, 2875, 2877,
6247, 8545, 9415, 9417, 9455, 14119
- `\cs_gset:Npx` 11,
2120, 2862, 2875, 2878, 6252, 22690
- `\cs_gset_eq:NN`
. 14, 2893, 2910, 2918, 4058, 4099,
4104, 5860, 6257, 6262, 7409, 7412,

- 8474, 9067, 9340, 9348, 10488, 10660
- \cs_gset_nopar:Nn [13](#), [2981](#), [3045](#)
- \cs_gset_nopar:Npn
- [11](#), [2120](#), [2337](#), [2859](#), [2867](#), [2871](#), [5730](#)
- \cs_gset_nopar:Npx
- [11](#), [1059](#), [2120](#), [2860](#), [2867](#),
- [2872](#), [4065](#), [4071](#), [4150](#), [4153](#), [4156](#),
- [4177](#), [4180](#), [4183](#), [4186](#), [4209](#), [4212](#),
- [4215](#), [4218](#), [27475](#), [27504](#), [27510](#), [27539](#)
- \cs_gset_protected:Nn [13](#), [2981](#), [3045](#)
- \cs_gset_protected:Npn
- [11](#), [2120](#), [2445](#), [2865](#), [2887](#),
- [2889](#), [4576](#), [5330](#), [6869](#), [8159](#), [9343](#),
- [10548](#), [11647](#), [15681](#), [19489](#), [19497](#),
- [19510](#), [19915](#), [20183](#), [20188](#), [26118](#)
- \cs_gset_protected:Npx . . [11](#), [2120](#),
- [2866](#), [2887](#), [2890](#), [6880](#), [11654](#), [15688](#)
- \cs_gset_protected_nopar:Nn
- [13](#), [2981](#), [3045](#)
- \cs_gset_protected_nopar:Npn . . .
- [11](#), [2120](#), [2863](#), [2881](#), [2883](#)
- \cs_gset_protected_nopar:Npx . . .
- [11](#), [2120](#), [2864](#), [2881](#), [2884](#)
- \cs_if_eq:NNTF [20](#),
- [3077](#), [3084](#), [3085](#), [3088](#), [3089](#), [3092](#),
- [3093](#), [9664](#), [12390](#), [13892](#), [13902](#),
- [13928](#), [13930](#), [13932](#), [14124](#), [21639](#)
- \cs_if_eq_p:NN [20](#), [3077](#), [21655](#)
- \cs_if_exist [218](#)
- \cs_if_exist:N [20](#),
- [4126](#), [4127](#), [5952](#), [5954](#), [6566](#), [6568](#),
- [7463](#), [7465](#), [7880](#), [7882](#), [9276](#), [9278](#),
- [11364](#), [11366](#), [11753](#), [11755](#), [11889](#),
- [11891](#), [15423](#), [15424](#), [23633](#), [23635](#)
- \cs_if_exist:NTF
- [15](#), [20](#), [308](#), [364](#), [512](#), [540](#),
- [2266](#), [2275](#), [2740](#), [2797](#), [2799](#), [2801](#),
- [2803](#), [2805](#), [2807](#), [2809](#), [2811](#), [3097](#),
- [3163](#), [3233](#), [3269](#), [3400](#), [3424](#), [3492](#),
- [3523](#), [3730](#), [4045](#), [5189](#), [6536](#), [6537](#),
- [6539](#), [6540](#), [7263](#), [7264](#), [7365](#), [7737](#),
- [7738](#), [7739](#), [7747](#), [8542](#), [8782](#), [8801](#),
- [9381](#), [10230](#), [10414](#), [10418](#), [10447](#),
- [10507](#), [10607](#), [10611](#), [11045](#), [11068](#),
- [11125](#), [12159](#), [12267](#), [12315](#), [12694](#),
- [12736](#), [12748](#), [12758](#), [12770](#), [12784](#),
- [12797](#), [12824](#), [12845](#), [12853](#), [12993](#),
- [14117](#), [14292](#), [15350](#), [19487](#), [19505](#),
- [19508](#), [21373](#), [22804](#), [24262](#), [24264](#),
- [25831](#), [26057](#), [26191](#), [26209](#), [26280](#),
- [26770](#), [26790](#), [26797](#), [27870](#), [27879](#),
- [28273](#), [28281](#), [28287](#), [28293](#), [28441](#),
- [28477](#), [28485](#), [28496](#), [29515](#), [29537](#)
- \cs_if_exist_p:N
- [20](#), [308](#), [308](#), [2740](#), [7742](#), [7766](#)
- \cs_if_exist_use:N
- [15](#), [336](#), [2796](#), [12750](#), [21820](#)
- \cs_if_exist_use:NTF
- [15](#), [2191](#), [2199](#), [2796](#),
- [2798](#), [2800](#), [2806](#), [2808](#), [4009](#), [7757](#),
- [12356](#), [13574](#), [14250](#), [14252](#), [20607](#),
- [20614](#), [20978](#), [20983](#), [21020](#), [21441](#),
- [21527](#), [22739](#), [26708](#), [26721](#), [26723](#)
- \cs_if_free:NTF [20](#), [95](#),
- [540](#), [2768](#), [2842](#), [3931](#), [3945](#), [3974](#), [9757](#)
- \cs_if_free_p:N [19](#), [20](#), [95](#), [2768](#)
- \cs_log:N [15](#), [345](#), [3122](#)
- \cs_meaning:N
- [14](#), [315](#), [2072](#), [2088](#), [2096](#), [3134](#)
- \cs_new:Nn [11](#), [96](#), [2981](#), [3045](#)
- \cs_new:Npn
- [9](#), [10](#), [13](#), [95](#), [95](#), [311](#), [312](#), [324](#),
- [325](#), [845](#), [2417](#), [2461](#), [2519](#), [2536](#),
- [2851](#), [2875](#), [2879](#), [2952](#), [2954](#), [2956](#),
- [2964](#), [3016](#), [3082](#), [3083](#), [3084](#), [3085](#),
- [3086](#), [3087](#), [3088](#), [3089](#), [3090](#), [3091](#),
- [3092](#), [3093](#), [3136](#), [3139](#), [3148](#), [3149](#),
- [3153](#), [3154](#), [3155](#), [3156](#), [3157](#), [3158](#),
- [3159](#), [3161](#), [3165](#), [3169](#), [3172](#), [3185](#),
- [3191](#), [3197](#), [3208](#), [3210](#), [3217](#), [3219](#),
- [3221](#), [3228](#), [3229](#), [3231](#), [3235](#), [3239](#),
- [3245](#), [3247](#), [3252](#), [3257](#), [3263](#), [3271](#),
- [3278](#), [3279](#), [3285](#), [3291](#), [3297](#), [3303](#),
- [3309](#), [3316](#), [3323](#), [3330](#), [3337](#), [3345](#),
- [3346](#), [3347](#), [3348](#), [3349](#), [3350](#), [3351](#),
- [3352](#), [3353](#), [3354](#), [3355](#), [3356](#), [3363](#),
- [3364](#), [3365](#), [3366](#), [3367](#), [3368](#), [3369](#),
- [3370](#), [3371](#), [3372](#), [3373](#), [3374](#), [3375](#),
- [3376](#), [3377](#), [3378](#), [3387](#), [3388](#), [3390](#),
- [3395](#), [3402](#), [3406](#), [3409](#), [3419](#), [3420](#),
- [3422](#), [3426](#), [3429](#), [3430](#), [3432](#), [3434](#),
- [3440](#), [3446](#), [3448](#), [3454](#), [3456](#), [3463](#),
- [3470](#), [3471](#), [3472](#), [3473](#), [3474](#), [3476](#),
- [3485](#), [3487](#), [3490](#), [3491](#), [3494](#), [3498](#),
- [3501](#), [3503](#), [3508](#), [3518](#), [3521](#), [3525](#),
- [3543](#), [3544](#), [3546](#), [3552](#), [3557](#), [3559](#),
- [3565](#), [3585](#), [3587](#), [3589](#), [3595](#), [3600](#),
- [3601](#), [3624](#), [3654](#), [3661](#), [3667](#), [3695](#),
- [3701](#), [3706](#), [3712](#), [3824](#), [3845](#), [3867](#),
- [3870](#), [3879](#), [3892](#), [3907](#), [3918](#), [3976](#),
- [4051](#), [4267](#), [4444](#), [4508](#), [4511](#), [4512](#),
- [4513](#), [4514](#), [4525](#), [4526](#), [4531](#), [4536](#),
- [4541](#), [4546](#), [4548](#), [4557](#), [4559](#), [4565](#),
- [4567](#), [4603](#), [4605](#), [4608](#), [4610](#), [4619](#),
- [4624](#), [4629](#), [4632](#), [4639](#), [4646](#), [4648](#),
- [4651](#), [4662](#), [4674](#), [4682](#), [4688](#), [4694](#),
- [4700](#), [4707](#), [4718](#), [4727](#), [4729](#), [4736](#),

4742, 4744, 4746, 4760, 4762, 4764,
4772, 4777, 4782, 4794, 4795, 4796,
4804, 4848, 4857, 4888, 4909, 4916,
4924, 4930, 4937, 4939, 4944, 4946,
4948, 4949, 4957, 4969, 4978, 4987,
4992, 4998, 5021, 5022, 5023, 5025,
5067, 5188, 5204, 5246, 5251, 5256,
5261, 5266, 5271, 5277, 5282, 5287,
5292, 5297, 5299, 5305, 5307, 5315,
5317, 5319, 5345, 5371, 5373, 5375,
5386, 5395, 5398, 5409, 5418, 5420,
5422, 5430, 5432, 5439, 5460, 5470,
5475, 5480, 5481, 5483, 5491, 5493,
5501, 5507, 5513, 5532, 5534, 5543,
5549, 5556, 5558, 5561, 5571, 5578,
5580, 5588, 5593, 5598, 5609, 5616,
5618, 5624, 5626, 5631, 5633, 5639,
5640, 5645, 5646, 5647, 5648, 5652,
5657, 5662, 5665, 5667, 5675, 5680,
5708, 5710, 5712, 5714, 5716, 5718,
5720, 5722, 5738, 5744, 5752, 5759,
5766, 5770, 5776, 5809, 5819, 5822,
5843, 5848, 5936, 5942, 5972, 5985,
6040, 6074, 6104, 6132, 6137, 6159,
6194, 6196, 6204, 6210, 6218, 6224,
6226, 6228, 6237, 6285, 6303, 6307,
6309, 6332, 6333, 6334, 6341, 6343,
6406, 6408, 6411, 6417, 6445, 6458,
6466, 6479, 6486, 6493, 6495, 6620,
6627, 6641, 6646, 6652, 6663, 6668,
6675, 6677, 6679, 6681, 6683, 6685,
6687, 6703, 6708, 6713, 6718, 6723,
6725, 6731, 6753, 6761, 6769, 6775,
6781, 6789, 6797, 6803, 6824, 6831,
6847, 6857, 6859, 6895, 6909, 6915,
6947, 6979, 6981, 6983, 6989, 6995,
7007, 7015, 7027, 7035, 7068, 7101,
7103, 7105, 7107, 7109, 7114, 7119,
7124, 7129, 7130, 7131, 7132, 7133,
7134, 7135, 7136, 7137, 7138, 7139,
7140, 7141, 7142, 7143, 7144, 7145,
7154, 7155, 7164, 7170, 7172, 7181,
7188, 7194, 7196, 7198, 7214, 7225,
7248, 7320, 7352, 7378, 7379, 7388,
7389, 7448, 7475, 7476, 7485, 7486,
7496, 7501, 7506, 7508, 7516, 7517,
7518, 7519, 7520, 7521, 7522, 7523,
7524, 7525, 7535, 7551, 7561, 7577,
7587, 7589, 7593, 7595, 7599, 7607,
7612, 7620, 7626, 7633, 7635, 7637,
7638, 7640, 7642, 7644, 7646, 7648,
7650, 7652, 7654, 7656, 7658, 7663,
7664, 7665, 7666, 7667, 7668, 7669,
7670, 7671, 7672, 7682, 7684, 7689,
7691, 7693, 7696, 7698, 7773, 7779,
7785, 7814, 7815, 7854, 7950, 8046,
8048, 8057, 8064, 8067, 8080, 8086,
8124, 8133, 8140, 8146, 8153, 8198,
8200, 8202, 8220, 8227, 8251, 8252,
8255, 8257, 8260, 8268, 8284, 8291,
8299, 8301, 8315, 8317, 8318, 8319,
8321, 8326, 8362, 8432, 8438, 8444,
8450, 8481, 8487, 8528, 8536, 8611,
8731, 8761, 8836, 8848, 8849, 8857,
8866, 8875, 8888, 8889, 8890, 8891,
8947, 8955, 8957, 8959, 8969, 8979,
9026, 9029, 9038, 9047, 9060, 9103,
9109, 9116, 9121, 9123, 9128, 9130,
9156, 9203, 9209, 9294, 9300, 9322,
9331, 9353, 9355, 9454, 9540, 9545,
9550, 9552, 9554, 9556, 9562, 9571,
9582, 9588, 9668, 9736, 9738, 9755,
9888, 10272, 10281, 10286, 10295,
10300, 10305, 10310, 10532, 10534,
10704, 10712, 10750, 10767, 10822,
10873, 10882, 10901, 10902, 10910,
10916, 10924, 10934, 10939, 10945,
10951, 11024, 11026, 11028, 11116,
11280, 11416, 11421, 11428, 11441,
11449, 11457, 11459, 11477, 11483,
11496, 11498, 11500, 11502, 11504,
11512, 11517, 11522, 11527, 11532,
11534, 11540, 11542, 11550, 11558,
11564, 11570, 11578, 11586, 11592,
11613, 11620, 11634, 11670, 11674,
11677, 11684, 11692, 11701, 11703,
11814, 11819, 11823, 11832, 11842,
11944, 12096, 12104, 12106, 12227,
12795, 12813, 12822, 12828, 12830,
12833, 12841, 12953, 12954, 12956,
12970, 13025, 13027, 13033, 13039,
13056, 13057, 13065, 13160, 13161,
13162, 13163, 13164, 13165, 13166,
13167, 13168, 13169, 13200, 13202,
13204, 13213, 13215, 13227, 13228,
13230, 13240, 13250, 13260, 13270,
13278, 13280, 13287, 13289, 13290,
13295, 13302, 13316, 13318, 13334,
13335, 13343, 13345, 13354, 13356,
13368, 13373, 13377, 13382, 13384,
13386, 13388, 13390, 13397, 13399,
13407, 13409, 13421, 13423, 13425,
13427, 13451, 13453, 13455, 13456,
13457, 13459, 13461, 13463, 13465,
13483, 13498, 13499, 13505, 13520,
13527, 13533, 13548, 13554, 13680,
13681, 13682, 13683, 13684, 13685,
13686, 13691, 13694, 13740, 13742,

13744, 13746, 13752, 13756, 13758,
13767, 13768, 13777, 13790, 13803,
13810, 13824, 13840, 13852, 13863,
13873, 13879, 13890, 13900, 13926,
13937, 13946, 13957, 13962, 13982,
13984, 13995, 14000, 14013, 14035,
14036, 14040, 14057, 14058, 14082,
14090, 14108, 14139, 14165, 14169,
14172, 14174, 14180, 14192, 14204,
14211, 14217, 14225, 14248, 14263,
14282, 14290, 14305, 14320, 14331,
14341, 14351, 14356, 14365, 14382,
14395, 14400, 14406, 14408, 14415,
14445, 14473, 14489, 14500, 14505,
14523, 14541, 14552, 14567, 14572,
14582, 14592, 14602, 14618, 14666,
14671, 14678, 14686, 14692, 14697,
14701, 14718, 14726, 14758, 14775,
14789, 14808, 14816, 14825, 14834,
14845, 14847, 14861, 14871, 14872,
14889, 14896, 14901, 14914, 14927,
14932, 14979, 14980, 14984, 15001,
15023, 15025, 15036, 15066, 15070,
15085, 15102, 15126, 15128, 15130,
15132, 15142, 15147, 15158, 15170,
15181, 15194, 15214, 15232, 15234,
15246, 15252, 15260, 15274, 15281,
15292, 15299, 15313, 15419, 15421,
15430, 15452, 15457, 15474, 15501,
15502, 15503, 15504, 15520, 15531,
15539, 15551, 15557, 15563, 15571,
15579, 15585, 15591, 15599, 15607,
15625, 15638, 15660, 15708, 15714,
15725, 15749, 15751, 15753, 15755,
15763, 15767, 15774, 15781, 15782,
15783, 15784, 15785, 15786, 15789,
15791, 15820, 15828, 15839, 15841,
15843, 15845, 15852, 15876, 15878,
15888, 15903, 15912, 15926, 15934,
15942, 15949, 15956, 15964, 15974,
15988, 15999, 16000, 16006, 16023,
16030, 16032, 16039, 16044, 16061,
16062, 16063, 16082, 16088, 16098,
16110, 16117, 16131, 16139, 16177,
16186, 16207, 16209, 16211, 16220,
16231, 16243, 16258, 16271, 16284,
16292, 16310, 16328, 16335, 16343,
16353, 16354, 16363, 16364, 16373,
16383, 16397, 16407, 16418, 16426,
16428, 16439, 16445, 16480, 16501,
16503, 16505, 16507, 16514, 16523,
16528, 16535, 16542, 16562, 16567,
16584, 16595, 16600, 16610, 16612,
16622, 16629, 16631, 16637, 16639,
16641, 16645, 16664, 16665, 16670,
16678, 16679, 16702, 16715, 16722,
16730, 16731, 16732, 16733, 16734,
16735, 16743, 16749, 16751, 16753,
16775, 16780, 16790, 16800, 16811,
16824, 16835, 16840, 16847, 16856,
16858, 16867, 16876, 16890, 16892,
16894, 16907, 16917, 16922, 16931,
16939, 16946, 16952, 16961, 16963,
16975, 16980, 16988, 16993, 17003,
17009, 17015, 17022, 17029, 17031,
17036, 17038, 17043, 17045, 17059,
17069, 17081, 17086, 17093, 17103,
17105, 17116, 17130, 17144, 17164,
17177, 17179, 17184, 17197, 17202,
17210, 17215, 17225, 17237, 17267,
17268, 17269, 17271, 17273, 17275,
17289, 17295, 17304, 17323, 17329,
17339, 17358, 17366, 17399, 17405,
17414, 17416, 17430, 17489, 17497,
17515, 17532, 17533, 17538, 17563,
17586, 17615, 17631, 17641, 17652,
17673, 17688, 17693, 17698, 17700,
17714, 17720, 17735, 17743, 17753,
17763, 17797, 17799, 17801, 17803,
17805, 17820, 17835, 17850, 17865,
17880, 17895, 17903, 17917, 17919,
17925, 17937, 17945, 17952, 18178,
18185, 18222, 18230, 18231, 18242,
18249, 18251, 18257, 18268, 18278,
18285, 18292, 18307, 18346, 18359,
18390, 18396, 18403, 18423, 18425,
18442, 18457, 18470, 18477, 18482,
18484, 18493, 18506, 18509, 18530,
18543, 18558, 18576, 18591, 18601,
18610, 18623, 18639, 18656, 18669,
18675, 18677, 18682, 18683, 18684,
18685, 18688, 18693, 18699, 18704,
18706, 18729, 18737, 18739, 18742,
18747, 18753, 18758, 18760, 18783,
18808, 18817, 18818, 18820, 18825,
18827, 18832, 18834, 18844, 18852,
18860, 18862, 18865, 18870, 18875,
18877, 18878, 18880, 18885, 18890,
18892, 18898, 18905, 18919, 18924,
18926, 18936, 18938, 18940, 18942,
18970, 18972, 18978, 18985, 18991,
19001, 19006, 19008, 19016, 19017,
19031, 19038, 19044, 19045, 19058,
19073, 19079, 19101, 19116, 19126,
19147, 19156, 19179, 19197, 19208,
19213, 19224, 19241, 19246, 19292,
19297, 19311, 19378, 19385, 19392,
19398, 19405, 19410, 19416, 19428,

19563, 19718, 19731, 19736, 19742,
 19743, 19750, 19757, 19764, 19771,
 19778, 19779, 19781, 19788, 19794,
 19873, 19878, 19879, 19887, 19893,
 20070, 20075, 20082, 20119, 20124,
 20139, 20162, 20167, 20215, 20221,
 20239, 20244, 20259, 20261, 20263,
 20270, 20315, 20344, 20349, 20605,
 20611, 20622, 20627, 20640, 20645,
 20657, 20669, 20679, 20688, 20708,
 20819, 20837, 20845, 20857, 20869,
 21361, 21637, 21651, 21691, 21732,
 21892, 22044, 22457, 22589, 22591,
 22597, 22598, 22605, 22615, 22770,
 23135, 23140, 23539, 23595, 25117,
 25118, 25122, 25123, 25155, 25157,
 25788, 25864, 25874, 25880, 25889,
 25898, 25900, 25902, 25904, 25910,
 25953, 25961, 25963, 25970, 25977,
 25987, 25995, 25997, 26003, 26009,
 26110, 26125, 26135, 26146, 26152,
 26165, 26231, 26233, 26336, 26349,
 26355, 26360, 26372, 26373, 26374,
 26455, 26457, 26459, 26465, 26467,
 26473, 26483, 26488, 26532, 26534,
 26536, 26539, 26542, 26548, 26554,
 26560, 26563, 26564, 26565, 26566,
 26567, 26568, 26569, 26577, 26584,
 26595, 26598, 26604, 26608, 26622,
 26634, 26639, 26647, 26661, 26666,
 26677, 26688, 26694, 26699, 26706,
 26718, 26733, 26740, 26762, 26764,
 26766, 26768, 26779, 26788, 26814,
 26825, 26834, 26848, 26854, 26857,
 26872, 26878, 26880, 26886, 26900,
 26904, 26910, 26920, 26926, 26944,
 26954, 26961, 26981, 26991, 27004,
 27012, 27018, 27038, 27047, 27053,
 27075, 27088, 27097, 27103, 27119,
 27412, 27422, 27428, 27556, 27564,
 27584, 27586, 27587, 27590, 27592,
 27594, 27596, 27604, 28108, 28212,
 28449, 28481, 28482, 28648, 28743,
 28829, 29103, 29106, 29268, 29500
 \cs_new:Npx 10, 31, 31, 365,
 365, 2851, 2875, 2880, 3783, 3961,
 4047, 8211, 8221, 10749, 10761,
 13309, 14151, 14738, 14962, 15847,
 17784, 17790, 18402, 18954, 20095,
 20628, 20630, 20632, 20634, 20636,
 20638, 25921, 25923, 25925, 25932
 \cs_new_eq:NN
 14, 96, 337, 339, 506, 2652,
 2893, 3138, 3147, 3178, 3489, 3739,
 3740, 3741, 3742, 3743, 3744, 3745,
 3746, 3747, 3748, 3749, 3750, 3751,
 3752, 3753, 4103, 4104, 4399, 4400,
 5082, 5096, 5097, 5100, 5101, 5167,
 5704, 5705, 5839, 5855, 5875, 5876,
 5877, 5878, 5879, 5880, 5881, 5882,
 6346, 6347, 6348, 6349, 6350, 6351,
 6352, 6353, 6354, 6355, 6356, 6357,
 6358, 6359, 6360, 6361, 6362, 6363,
 6364, 6365, 6366, 6367, 6368, 6369,
 6370, 6371, 6399, 6400, 6401, 6402,
 6403, 6541, 6542, 6545, 6618, 6894,
 7250, 7254, 7314, 7396, 7397, 7399,
 7417, 7418, 7723, 7724, 7725, 7726,
 7729, 7730, 7731, 7732, 7770, 7817,
 7818, 7822, 7823, 7824, 7825, 7826,
 7827, 7828, 7829, 7830, 7831, 7832,
 7833, 7834, 7835, 7836, 7837, 7978,
 7979, 7980, 7981, 7982, 7983, 7984,
 7985, 7986, 7987, 7988, 7989, 7990,
 7991, 7992, 7993, 8480, 8544, 8632,
 8634, 8635, 8636, 8638, 8641, 8642,
 8884, 8885, 8886, 9082, 9083, 9084,
 9085, 9086, 9087, 9088, 9089, 10425,
 10449, 10504, 10618, 10705, 11207,
 11215, 11333, 11334, 11335, 11672,
 11711, 11715, 11716, 11821, 11824,
 11834, 11846, 11850, 11851, 11946,
 11948, 11952, 11953, 12924, 12925,
 13157, 13158, 13159, 13353, 13823,
 13851, 13859, 13860, 13861, 13870,
 13872, 14665, 14784, 14785, 14786,
 15360, 15371, 15372, 18933, 18935,
 18984, 19866, 19867, 20306, 20318,
 20440, 20441, 20541, 20549, 20570,
 20618, 20619, 20620, 20621, 20798,
 22321, 22943, 23587, 23637, 23638,
 23639, 23652, 23653, 23664, 23665,
 23666, 23779, 23810, 23811, 23892,
 23909, 23910, 24259, 24413, 24414,
 24415, 24416, 24417, 24418, 25084,
 25085, 25112, 25113, 25114, 26108,
 26620, 26716, 26939, 27010, 27011,
 27487, 27488, 27732, 27957, 27960,
 28369, 28426, 28427, 28552, 28560,
 28575, 28699, 28753, 28759, 28760,
 28883, 28886, 29090, 29091, 29102,
 29111, 29309, 29320, 29346, 29489
 \cs_new_nopar:Nn 12, 2981, 3045
 \cs_new_nopar:Npn 10,
 337, 338, 2851, 2867, 2873, 4698, 4699
 \cs_new_nopar:Npx 10, 2851, 2867, 2874
 \cs_new_protected:Nn . 12, 2981, 3045
 \cs_new_protected:Npn 10,

324, 2414, 2523, 2540, 2851, 2887,
2891, 2893, 2894, 2895, 2896, 2897,
2898, 2899, 2900, 2901, 2906, 2907,
2908, 2909, 2911, 2966, 2976, 2978,
2989, 2998, 3095, 3104, 3106, 3108,
3110, 3112, 3120, 3122, 3123, 3125,
3126, 3128, 3179, 3344, 3357, 3358,
3359, 3360, 3361, 3362, 3379, 3380,
3381, 3382, 3383, 3384, 3385, 3386,
3414, 3484, 3515, 3757, 3770, 3788,
3792, 3795, 3804, 3941, 3970, 3981,
3989, 4000, 4019, 4021, 4023, 4025,
4027, 4043, 4055, 4062, 4068, 4075,
4077, 4081, 4083, 4089, 4095, 4114,
4122, 4140, 4143, 4146, 4149, 4152,
4155, 4164, 4167, 4170, 4173, 4176,
4179, 4182, 4185, 4196, 4199, 4202,
4205, 4208, 4211, 4214, 4217, 4228,
4230, 4232, 4234, 4257, 4275, 4287,
4289, 4303, 4332, 4334, 4336, 4338,
4344, 4366, 4372, 4401, 4403, 4407,
4409, 4482, 4483, 4484, 4573, 4584,
4587, 4593, 4595, 4654, 4656, 4766,
4768, 5044, 5046, 5048, 5053, 5055,
5068, 5128, 5130, 5132, 5134, 5140,
5155, 5168, 5170, 5174, 5176, 5327,
5342, 5351, 5361, 5363, 5727, 5830,
5857, 5863, 5866, 5869, 5872, 5883,
5888, 5893, 5898, 5909, 5911, 5913,
5946, 5948, 5956, 5964, 5977, 5979,
5987, 5989, 5991, 6003, 6005, 6007,
6029, 6031, 6033, 6078, 6086, 6096,
6107, 6109, 6111, 6113, 6121, 6139,
6141, 6143, 6244, 6249, 6254, 6260,
6266, 6273, 6378, 6380, 6382, 6503,
6514, 6549, 6551, 6554, 6556, 6561,
6564, 6579, 6582, 6585, 6588, 6595,
6598, 6601, 6604, 6611, 6614, 6621,
6861, 6863, 6865, 6872, 6874, 6876,
6888, 7252, 7256, 7274, 7318, 7325,
7326, 7337, 7339, 7340, 7341, 7399,
7402, 7405, 7408, 7411, 7422, 7428,
7444, 7446, 7450, 7452, 7454, 7719,
7772, 7819, 7838, 7840, 7842, 7865,
7867, 7869, 7884, 7886, 7890, 7892,
7894, 7903, 7905, 7907, 7916, 7924,
7927, 7929, 7931, 7939, 7967, 7996,
7998, 8000, 8012, 8014, 8016, 8051,
8053, 8097, 8154, 8168, 8174, 8185,
8190, 8332, 8334, 8336, 8346, 8347,
8348, 8360, 8364, 8366, 8368, 8370,
8372, 8374, 8376, 8378, 8380, 8382,
8384, 8386, 8388, 8390, 8392, 8394,
8396, 8398, 8400, 8402, 8404, 8406,
8408, 8410, 8412, 8414, 8416, 8418,
8420, 8422, 8424, 8426, 8428, 8430,
8434, 8436, 8440, 8442, 8446, 8448,
8452, 8464, 8892, 8894, 8896, 8901,
8908, 8917, 8935, 8937, 8939, 8941,
8943, 8945, 9064, 9070, 9073, 9076,
9079, 9094, 9097, 9100, 9146, 9148,
9157, 9163, 9173, 9181, 9190, 9238,
9239, 9240, 9259, 9261, 9263, 9338,
9357, 9359, 9361, 9389, 9397, 9402,
9404, 9411, 9413, 9420, 9461, 9477,
9497, 9502, 9513, 9597, 9599, 9662,
9726, 9740, 9765, 9787, 9788, 9801,
9806, 9832, 9841, 9843, 9845, 9862,
9889, 9891, 9893, 9895, 9902, 10320,
10327, 10334, 10346, 10351, 10368,
10425, 10429, 10445, 10457, 10474,
10480, 10492, 10493, 10494, 10521,
10523, 10536, 10538, 10540, 10546,
10553, 10562, 10564, 10566, 10571,
10618, 10623, 10627, 10645, 10652,
10664, 10665, 10666, 10676, 10679,
10682, 10688, 10694, 10701, 10703,
10713, 10744, 10755, 10773, 10808,
10831, 10843, 10862, 10866, 10955,
10971, 10980, 10988, 10997, 11004,
11010, 11089, 11103, 11118, 11149,
11164, 11170, 11177, 11192, 11209,
11217, 11223, 11228, 11241, 11262,
11263, 11264, 11337, 11345, 11352,
11354, 11358, 11360, 11377, 11380,
11385, 11389, 11393, 11396, 11404,
11407, 11506, 11643, 11650, 11662,
11713, 11717, 11727, 11735, 11742,
11744, 11747, 11749, 11766, 11769,
11773, 11775, 11778, 11781, 11786,
11789, 11848, 11852, 11861, 11869,
11876, 11879, 11883, 11885, 11908,
11911, 11916, 11919, 11922, 11925,
11930, 11933, 11950, 11954, 11968,
11985, 11991, 11996, 12009, 12015,
12020, 12034, 12037, 12047, 12059,
12086, 12097, 12099, 12137, 12139,
12146, 12151, 12156, 12169, 12175,
12199, 12211, 12229, 12245, 12261,
12263, 12265, 12281, 12292, 12294,
12296, 12319, 12322, 12336, 12349,
12354, 12358, 12366, 12368, 12378,
12406, 12415, 12424, 12425, 12436,
12438, 12440, 12442, 12444, 12446,
12448, 12450, 12452, 12454, 12456,
12458, 12460, 12462, 12464, 12466,
12468, 12470, 12472, 12474, 12476,
12478, 12480, 12482, 12484, 12486,

12488, 12490, 12492, 12494, 12496,
12498, 12500, 12502, 12504, 12506,
12508, 12510, 12512, 12514, 12516,
12518, 12520, 12522, 12524, 12526,
12528, 12530, 12532, 12534, 12536,
12538, 12540, 12542, 12544, 12546,
12548, 12550, 12552, 12554, 12556,
12558, 12560, 12562, 12570, 12573,
12581, 12589, 12595, 12598, 12606,
12614, 12620, 12628, 12634, 12636,
12646, 12652, 12657, 12662, 12679,
12692, 12706, 12732, 12746, 12765,
12782, 12804, 12858, 12860, 12862,
12931, 12941, 12975, 12977, 12984,
12995, 13003, 13010, 13016, 13042,
13050, 13074, 13076, 13078, 13089,
13093, 13098, 13112, 13117, 13122,
13137, 13148, 13170, 13173, 13274,
13572, 13589, 13591, 13593, 13595,
13623, 13625, 13627, 13629, 13649,
13651, 13653, 13655, 13657, 13659,
13661, 13663, 13665, 15359, 15362,
15364, 15366, 15375, 15376, 15379,
15381, 15385, 15386, 15387, 15388,
15389, 15395, 15397, 15399, 15404,
15406, 15677, 15684, 15696, 18435,
19266, 19278, 19316, 19325, 19337,
19342, 19352, 19360, 19366, 19446,
19465, 19473, 19485, 19522, 19529,
19548, 19550, 19552, 19571, 19574,
19577, 19583, 19589, 19604, 19613,
19633, 19643, 19654, 19664, 19674,
19675, 19682, 19688, 19698, 19708,
19804, 19811, 19813, 19829, 19895,
19906, 19924, 19934, 19936, 19960,
19967, 19979, 19982, 19985, 19995,
20003, 20010, 20019, 20034, 20051,
20062, 20172, 20179, 20181, 20199,
20209, 20297, 20301, 20313, 20316,
20319, 20321, 20330, 20336, 20342,
20373, 20375, 20376, 20381, 20387,
20395, 20407, 20423, 20442, 20452,
20460, 20462, 20470, 20482, 20502,
20504, 20509, 20517, 20519, 20526,
20531, 20533, 20535, 20542, 20550,
20552, 20554, 20556, 20563, 20568,
20571, 20586, 20813, 20877, 20890,
20901, 20914, 20947, 20976, 20981,
20986, 21007, 21016, 21025, 21030,
21037, 21050, 21052, 21054, 21056,
21062, 21084, 21097, 21124, 21129,
21163, 21198, 21219, 21221, 21231,
21240, 21245, 21254, 21263, 21279,
21292, 21298, 21309, 21322, 21328,
21347, 21367, 21398, 21409, 21424,
21437, 21455, 21463, 21468, 21470,
21472, 21489, 21508, 21510, 21533,
21545, 21565, 21586, 21593, 21600,
21612, 21618, 21675, 21710, 21719,
21738, 21757, 21763, 21826, 21836,
21838, 21840, 21847, 21903, 21916,
21932, 21943, 21962, 21978, 21985,
21992, 21994, 22008, 22015, 22029,
22045, 22054, 22068, 22083, 22101,
22110, 22112, 22124, 22136, 22148,
22161, 22168, 22188, 22219, 22253,
22271, 22277, 22286, 22331, 22350,
22375, 22392, 22414, 22423, 22434,
22463, 22478, 22493, 22502, 22514,
22521, 22523, 22525, 22545, 22550,
22557, 22562, 22567, 22572, 22621,
22659, 22701, 22717, 22737, 22749,
22763, 22797, 22811, 22822, 22829,
22838, 22873, 22879, 22882, 22890,
22896, 22899, 22908, 22911, 22914,
22917, 22922, 22931, 22934, 22937,
22942, 22948, 22953, 22958, 22963,
22971, 22991, 22993, 22997, 22998,
23022, 23030, 23039, 23051, 23060,
23068, 23108, 23152, 23179, 23184,
23186, 23216, 23244, 23557, 23559,
23561, 23572, 23598, 23605, 23607,
23611, 23613, 23618, 23621, 23626,
23629, 23643, 23645, 23647, 23656,
23658, 23660, 23662, 23680, 23683,
23692, 23695, 23698, 23701, 23703,
23710, 23728, 23731, 23737, 23745,
23751, 23759, 23766, 23774, 23781,
23788, 23796, 23801, 23806, 23808,
23814, 23816, 23818, 23823, 23829,
23835, 23843, 23849, 23857, 23863,
23871, 23878, 23886, 23894, 23901,
23914, 23918, 23936, 23946, 23980,
23991, 24002, 24013, 24024, 24035,
24048, 24064, 24071, 24081, 24086,
24101, 24116, 24128, 24144, 24154,
24168, 24171, 24174, 24186, 24272,
24281, 24290, 24303, 24318, 24349,
24363, 24365, 24396, 24398, 24419,
24429, 24436, 24443, 24450, 24461,
24472, 24480, 24501, 24535, 24550,
24633, 24647, 24688, 24709, 24719,
24738, 24743, 24757, 24762, 24775,
24786, 24798, 24810, 24870, 24917,
24925, 24954, 25003, 25011, 25035,
25038, 25041, 25086, 25093, 25096,
25098, 25100, 25102, 25104, 25119,
25120, 25159, 25446, 25453, 25456,

25502, 25558, 25593, 25611, 25617,
 25623, 25635, 25654, 25663, 25674,
 25680, 25685, 25693, 25706, 25719,
 25735, 25750, 25757, 25763, 25772,
 25779, 25791, 25793, 25795, 25797,
 25848, 25854, 25861, 25916, 25918,
 25920, 25940, 25946, 25949, 26017,
 26019, 26021, 26027, 26029, 26031,
 26037, 26039, 26041, 26047, 26049,
 26051, 26062, 26063, 26064, 26084,
 26103, 26115, 26243, 26247, 26297,
 26304, 26310, 26317, 26376, 26378,
 26382, 26394, 26397, 26409, 26411,
 26415, 26431, 26434, 26437, 27471,
 27474, 27476, 27478, 27490, 27496,
 27502, 27508, 27513, 27530, 27531,
 27534, 27538, 27541, 27552, 27554,
 27566, 27571, 27576, 27621, 27638,
 27643, 27650, 27655, 27657, 27660,
 27662, 27664, 27666, 27683, 27696,
 27701, 27733, 27738, 27758, 27764,
 27773, 27775, 27780, 27782, 27791,
 27796, 27806, 27834, 27845, 27850,
 27852, 27854, 27864, 27866, 27886,
 27889, 27895, 27900, 27902, 27904,
 27926, 27928, 27943, 27958, 27962,
 27968, 27973, 27975, 27977, 27985,
 27993, 28002, 28012, 28014, 28017,
 28019, 28033, 28038, 28059, 28081,
 28084, 28097, 28110, 28115, 28117,
 28119, 28121, 28123, 28125, 28127,
 28129, 28138, 28147, 28149, 28151,
 28156, 28161, 28164, 28170, 28182,
 28204, 28214, 28234, 28242, 28250,
 28257, 28266, 28267, 28268, 28299,
 28314, 28316, 28342, 28355, 28370,
 28382, 28393, 28421, 28454, 28490,
 28492, 28503, 28506, 28508, 28510,
 28525, 28527, 28540, 28554, 28561,
 28569, 28573, 28577, 28580, 28595,
 28605, 28640, 28650, 28655, 28657,
 28665, 28673, 28675, 28677, 28686,
 28688, 28689, 28693, 28700, 28706,
 28712, 28715, 28722, 28731, 28736,
 28744, 28755, 28757, 28761, 28766,
 28771, 28781, 28790, 28792, 28795,
 28797, 28799, 28801, 28806, 28811,
 28816, 28818, 28831, 28836, 28838,
 28840, 28842, 28844, 28846, 28848,
 28850, 28859, 28868, 28870, 28872,
 28877, 28889, 28904, 28929, 28941,
 28953, 28965, 28972, 28995, 28998,
 29000, 29002, 29005, 29058, 29071,
 29092, 29105, 29107, 29108, 29109,
 29110, 29113, 29118, 29120, 29128,
 29138, 29146, 29151, 29156, 29167,
 29177, 29187, 29189, 29191, 29193,
 29224, 29226, 29231, 29233, 29235,
 29238, 29259, 29270, 29283, 29285,
 29287, 29289, 29291, 29293, 29295,
 29297, 29299, 29310, 29318, 29321,
 29331, 29347, 29362, 29384, 29498
 \cs_new_protected:Npx
 . . . 10, 365, 365, 370, 2440, 2851,
 2887, 2892, 2983, 3047, 3772, 3776,
 3781, 3953, 3957, 3958, 4047, 5109,
 8470, 8994, 9009, 9014, 9019, 9608,
 9610, 9612, 9614, 9616, 9625, 9627,
 9629, 9911, 9913, 9915, 9917, 9919,
 9928, 9930, 9932, 21192, 21206,
 21208, 27868, 27877, 28271, 28279,
 28285, 28291, 28432, 28483, 28494
 \cs_new_protected_nopar:Nn
 12, 2981, 3045
 \cs_new_protected_nopar:Npn
 10, 2851, 2868, 2881, 2885
 \cs_new_protected_nopar:Npx
 10, 2851, 2881, 2886
 \cs_set:Nn 12, 342, 2981, 3045
 \cs_set:Npn 9, 10, 95, 95, 311, 330,
 339, 342, 524, 2106, 2136, 2143,
 2145, 2148, 2149, 2150, 2151, 2152,
 2153, 2154, 2155, 2156, 2157, 2158,
 2159, 2160, 2161, 2162, 2163, 2164,
 2165, 2166, 2167, 2169, 2170, 2171,
 2172, 2173, 2174, 2175, 2176, 2177,
 2253, 2350, 2359, 2361, 2459, 2493,
 2499, 2512, 2514, 2517, 2534, 2583,
 2586, 2648, 2698, 2702, 2706, 2710,
 2715, 2721, 2722, 2726, 2733, 2736,
 2796, 2798, 2800, 2802, 2804, 2806,
 2808, 2810, 2829, 2851, 2867, 2875,
 2875, 2981, 3045, 4310, 4375, 4490,
 4660, 5157, 5193, 6424, 6437, 8025,
 8114, 8520, 8905, 9150, 9406, 9408,
 10720, 11055, 12077, 13536, 13598,
 13606, 13615, 13632, 13640, 13668,
 19544, 20590, 20591, 20592, 20909,
 20910, 21476, 21478, 21495, 21497,
 21790, 21817, 21856, 22395, 22703,
 25132, 27130, 27672, 27674, 27680
 \cs_set:Npx 10, 347,
 611, 2106, 2875, 2876, 4377, 8101,
 8903, 8922, 8928, 10778, 10779,
 10780, 10781, 10782, 12062, 12070,
 12331, 20332, 20338, 22031, 25311
 \cs_set_eq:NN 14, 96, 323, 339, 469,
 2242, 2250, 2650, 2893, 3776, 3794,

- 3957, 4093, 4103, 5191, 5192, 6035,
6036, 6038, 6145, 6146, 6157, 7329,
7403, 7406, 8473, 8669, 8899, 8920,
8927, 10784, 10785, 10786, 10787,
10789, 10791, 10792, 12326, 12341,
12345, 12373, 12384, 12394, 19806,
19807, 19812, 19963, 20006, 20031,
21782, 21791, 21814, 22401, 25310,
26073, 26481, 27669, 27679, 29539
`\cs_set_nopar:Nn` [12](#), [2981](#), [3045](#)
`\cs_set_nopar:Npn` . [9](#), [10](#), [122](#), [321](#),
[338](#), [2106](#), 2135, 2238, 2399, 2400,
[2867](#), [2869](#), [12283](#), [12352](#), [25337](#), [25339](#)
`\cs_set_nopar:Npx`
. [10](#), [1059](#), [2106](#), 2139, [2867](#),
2870, 3181, 3416, 4141, 4144, 4147,
4165, 4168, 4171, 4174, 4197, 4200,
4203, 4206, 27472, 27492, 27498, 27535
`\cs_set_protected:Nn` . [12](#), [2981](#), [3045](#)
`\cs_set_protected:Npn`
[9](#), [10](#), 260, [339](#), [2106](#), 2122, 2124,
2126, 2128, 2130, 2132, 2137, 2179,
2182, 2187, 2195, 2203, 2213, 2225,
2230, 2239, 2244, 2256, 2257, 2261,
2263, 2272, 2281, 2286, 2292, 2299,
2301, 2302, 2303, 2304, 2305, 2307,
2318, 2320, 2332, 2348, 2358, 2379,
2381, 2384, 2385, 2395, 2397, 2401,
2408, 2412, 2428, 2438, 2449, 2464,
2467, 2469, 2471, 2473, 2477, 2478,
2480, 2482, 2486, 2488, 2491, 2497,
2503, 2507, 2508, 2516, 2518, 2520,
2521, 2522, 2524, 2533, 2535, 2537,
2538, 2539, 2541, 2550, 2562, 2588,
2605, 2624, 2632, 2640, 2649, 2651,
2653, 2665, 2679, 2724, 2812, 2825,
2827, 2831, 2833, 2840, 2848, 2853,
[2887](#), [2887](#), 2921, 2942, 4497, 5078,
5105, 6062, 6570, 8462, 8589, 8757,
8775, 9521, 9594, 9898, 9900, 10270,
10382, 10450, 10700, 10702, 10841,
10922, 11022, 11051, 11243, 11368,
11757, 11799, 11893, 12320, 13553,
14038, 14115, 14699, 14773, 14787,
14982, 14999, 15034, 15068, 15083,
15100, 16643, 19808, 21204, 21229,
21238, 21767, 21776, 21778, 21780,
21783, 21785, 21792, 21794, 21799,
21801, 21806, 21808, 21810, 21812,
21815, 22564, 22565, 22995, 24354,
24375, 25141, 25331, 25334, 25356,
25371, 25389, 25397, 25429, 25808,
25822, 25833, 27171, 27182, 27185,
27211, 27222, 27238, 27358, 27361,
27383, 27619, 27743, 27801, 28430,
28452, 29503, 29509, 29528, 29534
`\cs_set_protected:Npx`
. [10](#), 246, [2106](#), [2887](#), 2888, [9773](#)
`\cs_set_protected_nopar:Nn`
. [13](#), [2981](#), [3045](#)
`\cs_set_protected_nopar:Npn`
. [11](#), [339](#), [2106](#), [2881](#), 2881
`\cs_set_protected_nopar:Npx`
. [11](#), [2106](#), [2881](#), 2882
`\cs_show:N` [15](#), [15](#), [20](#), [345](#), [3122](#)
`\cs_split_function:N`
. [16](#), 2529, 2546, 2658,
2659, [2724](#), 2953, 2994, 3763, 3986
`\cs_to_sr:N` [1062](#)
`\cs_to_str:N` [4](#), [16](#), [42](#), [51](#),
[333](#), [334](#), [334](#), [364](#), [419](#), 2319, [2715](#),
2730, 3733, 5688, 5689, 5690, 5691,
5692, 5693, 5694, 5695, 5696, 5697,
5698, 5699, 10705, 13551, 20346,
21748, 27466, 27477, 27569, 27574,
27582, 29516, 29520, 29537, 29540
`\cs_undefine:N`
. [14](#), [466](#), [612](#), [2909](#), 9936,
9937, 9938, 10452, 19283, 25115, 25116
cs internal commands:
`__cs_args_generate:n` [4027](#)
`__cs_args_generate:Nn` [4027](#)
`__cs_count_signature:N` [332](#), [2952](#)
`__cs_count_signature:n` [2952](#)
`__cs_count_signature:nnN` [2952](#)
`__cs_generate_from_signature:n` .
. [3003](#), [3016](#)
`__cs_generate_from_signature:NNn`
. [2985](#), [2989](#)
`__cs_generate_from_signature:nnNNn`
. [2993](#), [2998](#)
`__cs_generate_internal_variant:n`
. [3948](#), [3953](#)
`__cs_generate_internal_variant:wnNwnn`
. [3955](#), [3970](#)
`__cs_generate_internal_variant:wnnw`
. [3953](#)
`__cs_generate_internal_variant_-`
loop:n [3953](#)
`__cs_generate_variant:N` . [3759](#), [3772](#)
`__cs_generate_variant:n` [3981](#)
`__cs_generate_variant:nnNN`
. [3762](#), [3795](#)
`__cs_generate_variant:nnNnn` . [3981](#)
`__cs_generate_variant:Nnnw`
. [3802](#), [3804](#)
`__cs_generate_variant:w` [3981](#)
`__cs_generate_variant:ww` [3772](#)

- __cs_generate_variant:wwNN [367, 367, 368, 3811, 3929](#)
 - __cs_generate_variant:wwNw . . . [3772](#)
 - __cs_generate_variant_F_-
form:nnn [3981](#)
 - __cs_generate_variant_loop:nNwN
. [367, 367, 3812, 3824](#)
 - __cs_generate_variant_loop_-
base:N [3824](#)
 - __cs_generate_variant_loop_-
end:nwwwNNnn . . . [367, 368, 3814, 3824](#)
 - __cs_generate_variant_loop_-
invalid:NNwNNnn [367, 3824](#)
 - __cs_generate_variant_loop_-
long:wNNnn [368, 3817, 3824](#)
 - __cs_generate_variant_loop_-
same:w [367, 3824](#)
 - __cs_generate_variant_loop_-
special:NNwNNnn [3824, 3924](#)
 - __cs_generate_variant_p_-
form:nnn [3981](#)
 - __cs_generate_variant_same:N . . .
. [367, 3869, 3918](#)
 - __cs_generate_variant_T_-
form:nnn [3981](#)
 - __cs_generate_variant_TF_-
form:nnn [3981](#)
 - __cs_get_function_name:N [333](#)
 - __cs_get_function_signature:N . . [333](#)
 - __cs_parm_from_arg_count_-
test:nnTF [2921](#)
 - __cs_split_function_auxi:w . . . [2724](#)
 - __cs_split_function_auxii:w . . . [2724](#)
 - __cs_tmp:w [333](#),
[365, 370, 2724, 2739, 2851, 2867](#),
[2869, 2870, 2871, 2872, 2873, 2874](#),
[2875, 2876, 2877, 2878, 2879, 2880](#),
[2881, 2882, 2883, 2884, 2885, 2886](#),
[2887, 2888, 2889, 2890, 2891, 2892](#),
[2981, 3021, 3022, 3023, 3024, 3025](#),
[3026, 3027, 3028, 3029, 3030, 3031](#),
[3032, 3033, 3034, 3035, 3036, 3037](#),
[3038, 3039, 3040, 3041, 3042, 3043](#),
[3044, 3045, 3053, 3054, 3055, 3056](#),
[3057, 3058, 3059, 3060, 3061, 3062](#),
[3063, 3064, 3065, 3066, 3067, 3068](#),
[3069, 3070, 3071, 3072, 3073, 3074](#),
[3075, 3076, 3776, 3794, 3949, 3957](#)
 - __cs_to_str:N [333, 2715](#)
 - __cs_to_str:w [333, 2715](#)
 - csc [197](#)
 - cscd [198](#)
 - \csname [14, 21, 39, 43, 49, 68, 90](#),
[92, 93, 94, 105, 130, 153, 157, 228, 327](#)
 - \csstring [911](#)
 - \currentgrouplevel [619, 1432](#)
 - \currentgrouptype [620, 1433](#)
 - \currentifbranch [621, 1434](#)
 - \currentiflevel [622, 1435](#)
 - \currentifttype [623, 1436](#)
- D**
- \day [328](#)
 - dd [200](#)
 - \deadcycles [329](#)
 - debug commands:
 - \debug_off: [309](#)
 - \debug_off:n [240, 479, 2185](#)
 - \debug_on: [309](#)
 - \debug_on:n [240, 296, 479, 2185](#)
 - \debug_resume:
. [240, 319, 980, 2236, 24300](#)
 - \debug_suspend:
. [240, 319, 980, 2236, 24293](#)
 - debug internal commands:
 - __debug_all_off: [2185](#)
 - __debug_all_on: [2185](#)
 - __debug_check-declarations_off:
. [2259](#)
 - __debug_check-declarations_on: [2259](#)
 - __debug_check-expressions_off: [2346](#)
 - __debug_check-expressions_on: [2346](#)
 - __debug_chk_expr_aux:nNnN . . . [2346](#)
 - __debug_chk_var_scope_aux:NN . . .
. [2284, 2290, 2296, 2316](#)
 - __debug_chk_var_scope_aux:Nn . [2316](#)
 - __debug_chk_var_scope_aux:NNn . .
. [321, 2316](#)
 - __debug_deprecation_aux:nnNnn [2410](#)
 - __debug_deprecation_expandable:nnNnn
. [2426, 2449](#)
 - __debug_deprecation_off: [2393](#)
 - \g__debug_deprecation_off_tl . . .
. [324, 2393, 2435, 2456](#)
 - __debug_deprecation_on: [2393](#)
 - \g__debug_deprecation_on_tl . . .
. [324, 2393, 2430, 2451](#)
 - __debug_log-functions_off: . . . [2377](#)
 - __debug_log-functions_on: . . . [2377](#)
 - __debug_patch_args_aux:nnnn . [2480](#)
 - __debug_patch_args_aux:nnnNNnn [2480](#)
 - __debug_patch_args_aux:nnnNNnnn
. [2480](#)
 - __debug_patch_aux:nnnn [2465](#)
 - __debug_patch_auxii:nnnn [2465](#)
 - __debug_suspended:TF
. [320, 2236, 2265](#),
[2274, 2283, 2288, 2294, 2352, 2382](#)

- `\l__debug_suspended_tl` [2236](#)
- `__debug_tmp:w` [2480](#)
- `\def` [74](#),
[75](#), [76](#), [112](#), [129](#), [131](#), [132](#), [150](#), [151](#),
[154](#), [170](#), [185](#), [213](#), [217](#), [242](#), [281](#), [330](#)
- default commands:
 - `.default:n` [171](#), [12472](#)
- `\defaultshyphenchar` [331](#)
- `\defaultskewchar` [332](#)
- `deg` [200](#)
- `\delcode` [333](#)
- `\delimiter` [334](#)
- `\delimiterfactor` [335](#)
- `\delimitershortfall` [336](#)
- deprecation internal commands:
 - `__deprecation_primitive:NN`
[1112](#), [29498](#)
 - `__deprecation_primitive:w` ... [29498](#)
- `\detokenize` [68](#), [228](#), [624](#), [1437](#)
- `\DH` [27395](#)
- `\dh` [27395](#)
- dim commands:
 - `\dim_abs:n` [154](#), [1029](#), [11414](#)
 - `\dim_add:Nn` [154](#), [11392](#)
 - `\dim_case:nn` [157](#), [11512](#)
 - `\dim_case:nnn` [29408](#)
 - `\dim_case:nnTF`
[157](#), [11512](#), [11517](#), [11522](#), [29409](#)
 - `\dim_compare:nNnTF` [155](#),
[157](#), [157](#), [157](#), [158](#), [11461](#), [11536](#),
[11572](#), [11580](#), [11589](#), [11595](#), [11622](#),
[11625](#), [11636](#), [24553](#), [24556](#), [24559](#),
[24568](#), [24571](#), [24574](#), [24583](#), [24590](#),
[24653](#), [24658](#), [24669](#), [24788](#), [24800](#),
[25464](#), [25481](#), [25510](#), [25524](#), [25534](#)
 - `\dim_compare:nTF` [156](#), [158](#), [158](#), [158](#),
[158](#), [11472](#), [11544](#), [11552](#), [11561](#), [11567](#)
 - `\dim_compare_p:n` [156](#), [11472](#)
 - `\dim_compare_p:nNn` [155](#), [11461](#)
 - `\dim_const:Nn` [153](#),
[583](#), [593](#), [11344](#), [11719](#), [11720](#), [12927](#)
 - `\dim_do_until:nn` [158](#), [11542](#)
 - `\dim_do_until:nNnn` [157](#), [11570](#)
 - `\dim_do_while:nn` [158](#), [11542](#)
 - `\dim_do_while:nNnn` [157](#), [11570](#)
 - `\dim_eval:n`
[155](#), [156](#), [159](#), [159](#), [583](#), [960](#),
[11348](#), [11515](#), [11520](#), [11525](#), [11530](#),
[11640](#), [11668](#), [11714](#), [11718](#), [24339](#),
[24386](#), [24456](#), [24467](#), [24484](#), [24488](#),
[24489](#), [24493](#), [24497](#), [24498](#), [24505](#),
[24510](#), [24516](#), [24523](#), [24530](#), [24771](#),
[24772](#), [25048](#), [25049](#), [25050](#), [25575](#),
[25596](#), [25599](#), [25600](#), [25607](#), [25689](#),
[25690](#), [25697](#), [25698](#), [25776](#), [25783](#)
 - `\dim_gadd:Nn` [154](#), [11392](#)
 - `.dim_gset:N` [171](#), [12480](#)
 - `\dim_gset:Nn` [154](#), [583](#), [11376](#)
 - `\dim_gset_eq:NN` [154](#), [11384](#)
 - `\dim_gsub:Nn` [154](#), [11392](#)
 - `\dim_gzero:N` [153](#), [11351](#), [11361](#)
 - `\dim_gzero_new:N` [153](#), [11358](#)
 - `\dim_if_exist:NTF`
[153](#), [11359](#), [11361](#), [11364](#)
 - `\dim_if_exist_p:N` [153](#), [11364](#)
 - `\dim_log:N` [161](#), [11715](#)
 - `\dim_log:n` [161](#), [11715](#)
 - `\dim_max:nn` .. [154](#), [11414](#), [25668](#), [25672](#)
 - `\dim_min:nn`
[154](#), [11414](#), [25666](#), [25670](#), [25683](#)
 - `\dim_new:N`
[153](#), [153](#), [11336](#), [11347](#), [11359](#),
[11361](#), [11721](#), [11722](#), [11723](#), [11724](#),
[23927](#), [23928](#), [23929](#), [23930](#), [23931](#),
[23932](#), [23933](#), [23934](#), [24227](#), [24251](#),
[24252](#), [24255](#), [24256](#), [24257](#), [24258](#),
[24858](#), [24860](#), [24861](#), [25553](#), [25554](#),
[25555](#), [25556](#), [25557](#), [25704](#), [25705](#)
 - `\dim_ratio:nn` . [155](#), [592](#), [11457](#), [11708](#)
 - `.dim_set:N` [171](#), [12480](#)
 - `\dim_set:Nn` [154](#), [11376](#), [23948](#),
[23949](#), [23950](#), [23982](#), [23993](#), [24066](#),
[24067](#), [24068](#), [24083](#), [24156](#), [24157](#),
[24158](#), [24160](#), [24162](#), [24164](#), [24324](#),
[24370](#), [24555](#), [24560](#), [24570](#), [24575](#),
[24585](#), [24592](#), [24605](#), [24636](#), [24656](#),
[24722](#), [24723](#), [24725](#), [24727](#), [24745](#),
[24746](#), [24859](#), [24962](#), [24963](#), [25014](#),
[25015](#), [25016](#), [25018](#), [25602](#), [25637](#),
[25645](#), [25656](#), [25657](#), [25658](#), [25659](#),
[25665](#), [25667](#), [25669](#), [25671](#), [25676](#),
[25682](#), [25740](#), [25742](#), [25744](#), [25752](#),
[25754](#), [28415](#), [28416](#), [28739](#), [28740](#)
 - `\dim_set_eq:NN`
[154](#), [11384](#), [24326](#), [24327](#), [24372](#), [24373](#)
 - `\dim_show:N` [160](#), [11711](#)
 - `\dim_show:n` [161](#), [593](#), [11713](#)
 - `\dim_sign:n` [249](#), [26144](#)
 - `\dim_step_function:nnnN`
[158](#), [590](#), [11598](#), [11665](#)
 - `\dim_step_inline:nnnn` ... [158](#), [11643](#)
 - `\dim_step_variable:nnnN` . [159](#), [11643](#)
 - `\dim_sub:Nn` [154](#), [11392](#)
 - `\dim_to_decimal:n` [159](#), [11675](#), [11693](#),
[11705](#), [29016](#), [29017](#), [29018](#), [29019](#),
[29020](#), [29022](#), [29097](#), [29098](#), [29149](#),

- 29154, 29160, 29161, 29162, 29163,
 29172, 29173, 29174, 29265, 29284
 \dim_to_decimal_in_bp:n
 [160](#), [160](#), [11692](#), 27915,
 27916, 27917, 27981, 27982, 27989,
 27990, 27997, 27998, 28006, 28007,
 28008, 28105, 28109, 28113, 28305,
 28306, 28307, 28516, 28517, 28518,
 28619, 28620, 28621, 28622, 28764,
 28769, 28775, 28776, 28777, 28785,
 28786, 28826, 28830, 28834, 29269
 \dim_to_decimal_in_sp:n [160](#),
 [160](#), [675](#), [11694](#), 14178, 14215, 14812
 \dim_to_decimal_in_unit:nn [160](#), [11703](#)
 \dim_to_fp:n
 [160](#), [675](#), [694](#), [11711](#), [18897](#),
 23986, 23987, 23997, 23998, 24054,
 24057, 24058, 24084, 24093, 24094,
 24108, 24109, 24122, 24134, 24137,
 24138, 24598, 24600, 24610, 24612,
 24614, 24615, 24640, 24641, 24642,
 24643, 25641, 25642, 25649, 25650,
 25709, 25712, 25713, 25753, 25755
 \dim_until_do:nn [158](#), [11542](#)
 \dim_until_do:nNnn [157](#), [11570](#)
 \dim_use:N
 [159](#), [159](#), [960](#), 11419, 11430, 11431,
 11432, 11443, 11444, 11445, 11475,
 11494, 11671, [11672](#), 11680, 24753,
 25604, 25608, 25615, 25621, 25630,
 25631, 25632, 25761, 25768, 26149
 \dim_while_do:nn [158](#), [11542](#)
 \dim_while_do:nNnn [158](#), [11570](#)
 \dim_zero:N [153](#), [153](#), [11351](#), 11359,
 23951, 24069, 24159, 24546, 24547
 \dim_zero_new:N [153](#), [11358](#)
 \c_max_dim [161](#), [164](#), [627](#),
 [11719](#), 11855, 12955, 12997, 13005,
 25656, 25657, 25658, 25659, 25676
 \g_tmpa_dim [161](#), [11721](#)
 \l_tmpa_dim [161](#), [11721](#)
 \g_tmpb_dim [161](#), [11721](#)
 \l_tmpb_dim [161](#), [11721](#)
 \c_zero_dim [161](#), 11622,
 11625, [11719](#), 11854, 13022, 23803,
 23825, 24217, 24553, 24556, 24559,
 24568, 24571, 24574, 24583, 24590,
 24653, 24658, 24669, 25468, 25479,
 25485, 25497, 25510, 25514, 25522,
 25524, 25528, 25534, 25544, 26154
 dim internal commands:
 __dim_abs:N [11414](#)
 __dim_case:nnTF [11512](#)
 __dim_case:nw [11512](#)
 __dim_case_end:nw [11512](#)
 __dim_compare:w [11472](#)
 __dim_compare:wNN [586](#), [11472](#)
 __dim_compare_!:w [11472](#)
 __dim_compare_<:w [11472](#)
 __dim_compare_=:w [11472](#)
 __dim_compare_>:w [11472](#)
 __dim_compare_end:w .. [11480](#), [11504](#)
 __dim_compare_error: ... [586](#), [11472](#)
 __dim_eval:w [592](#), [11333](#),
 11373, 11378, 11381, 11394, 11399,
 11405, 11410, 11415, 11419, 11425,
 11426, 11430, 11431, 11432, 11438,
 11439, 11443, 11444, 11445, 11460,
 11463, 11465, 11469, 11475, 11494,
 11499, 11601, 11605, 11609, 11616,
 11617, 11618, 11669, 11671, 11676,
 11680, 11697, 11702, 26145, 26149
 __dim_eval_end: ... [11333](#), 11378,
 11381, 11394, 11399, 11405, 11410,
 11419, 11434, 11447, 11460, 11464,
 11469, 11671, 11680, 11702, 26149
 __dim_maxmin:wwN [11414](#)
 __dim_ratio:n [11457](#)
 __dim_sign:Nw [26144](#)
 __dim_step:NnnnN [11598](#)
 __dim_step:NNnnnn [11643](#)
 __dim_step:wwwN [11598](#)
 __dim_tmp:w [584](#), [584](#), 11368, 11376,
 11379, 11392, 11395, 11403, 11406
 __dim_to_decimal:w [11675](#)
 \dimen [337](#), 8816
 \dimendef [338](#)
 \dimexpr [625](#), 1438
 \directlua .. [16](#), [23](#), [53](#), [59](#), [61](#), [912](#), [1733](#)
 \disablecjktoken [1251](#), [2033](#)
 \discretionary [339](#)
 \displayindent [340](#)
 \displaylimits [341](#)
 \displaystyle [342](#)
 \displaywidowpenalties [626](#), [1439](#)
 \displaywidowpenalty [343](#)
 \displaywidth [344](#)
 \divide [345](#)
 \DJ [27396](#)
 \dj [27396](#)
 \do [1291](#)
 \doublehyphendemerits [346](#)
 \dp [347](#)
 \draftmode [1014](#), [1623](#)
 driver commands:
 \driver_box_use_clip:N
 [259](#), [25454](#), [27904](#), [28299](#), [28510](#), [29005](#)

- \driver_box_use_rotate:Nn
260, 23969, 27926, 28314, 28525, 29058
- \driver_box_use_scale:Nnn
260, 24190, 27943, 28342, 28540, 29071
- \driver_color_cmyk:nnnn
260, 25099, 27764, 27834, 29309
- \driver_color_gray:n
260, 25101, 27764, 27834, 29320
- \driver_color_pickup:N
260, 25089, 27737, 27795
- \driver_color_rgb:nnn
260, 25103, 27764, 27834, 29346
- \driver_color_spot:nn
25105, 27764, 27834
- \driver_draw_begin:
261, 27962, 28755, 29113
- \driver_draw_box:Nnnnnnn 264
- \driver_draw_box_use:Nnnnn
264, 1073, 28182, 28972, 29362
- \driver_draw_cap_but:
263, 28097, 28818, 29259
- \driver_draw_cap_rectangle:
263, 28097, 28818, 29259
- \driver_draw_cap_round:
263, 28097, 28818, 29259
- \driver_draw_clip:
262, 28017, 28795, 29191
- \driver_draw_closepath:
261, 28017, 28795, 29191
- \driver_draw_closestroke:
262, 28017, 28795, 29191
- \driver_draw_cm:nnnn
264, 28170, 28190, 28191,
28192, 28889, 28976, 29347, 29365
- \driver_draw_color_fill_cmyk:nnnn
263, 28129, 28850, 29299
- \driver_draw_color_fill_gray:n ..
263, 28129, 28850, 29299
- \driver_draw_color_fill_rgb:nnn .
263, 28129, 28850, 29299
- \driver_draw_color_gray:n 29310
- \driver_draw_color_rgb:nnn ... 29321
- \driver_draw_color_stroke_-
cmyk:nnnn 263, 28129, 28850, 29299
- \driver_draw_color_stroke_gray:n
263, 28129, 28850, 29299
- \driver_draw_color_stroke_-
rgb:nnn .. 263, 28129, 28850, 29299
- \driver_draw_curveto:nnnnnn
261, 27977, 28761, 29146
- \driver_draw_dash:nn 263
- \driver_draw_dash_pattern:nn ...
263, 28097, 28818, 29259
- \driver_draw_discardpath:
262, 28017, 28795, 29191
- \driver_draw_end:
261, 27962, 28755, 29113
- \driver_draw_evenodd_rule:
262, 28012, 28790, 29187
- \driver_draw_fill:
262, 28017, 28795, 29191
- \driver_draw_fillstroke:
262, 28017, 28795, 29191
- \driver_draw_join_bevel:
263, 28097, 28818, 29259
- \driver_draw_join_miter:
263, 28097, 28818, 29259
- \driver_draw_join_round:
263, 28097, 28818, 29259
- \driver_draw_lineto:nn
261, 27977, 28761, 29146
- \driver_draw_linewidth:n
263, 28097, 28818, 29259
- \driver_draw_miterlimit:n
263, 28097, 28818, 29259
- \driver_draw_move:nn 261
- \driver_draw_moveto:nn
261, 27977, 28761, 29146
- \driver_draw_nonzero_rule:
262, 28012, 28790, 29187
- \driver_draw_rectangle:nnnn
261, 27977, 28761, 29146
- \driver_draw_scope_begin:
261, 27973, 28756, 28759, 29115, 29120
- \driver_draw_scope_end:
261, 27973, 28758, 28759, 29119, 29120
- \driver_draw_stroke:
262, 262, 28017, 28795, 29191
- \driver_draw_stroke_cmyk:nnnn .. 260
- \driver_draw_stroke_gray:n 260
- \driver_draw_stroke_rgb:nnn ... 260
- \driver_pdf_compresslevel:n
265, 28266, 28483, 28686, 29105
- \driver_pdf_object_new:n . 264, 29105
- \driver_pdf_object_new:nn
264, 28204, 28429, 28640
- \driver_pdf_object_ref:n
264, 28204,
28218, 28238, 28246, 28254, 28429,
28640, 28661, 28669, 28681, 29105
- \driver_pdf_object_write:nn
265, 28214, 28451, 28650, 29107
- \driver_pdf_objects_disable: ...
265, 28266, 28483, 28686, 29105
- \driver_pdf_objects_enable:
265, 28266, 28483, 28686, 29105
- \driver_pdf_object_write:nn .. 29105

driver internal commands:

- __driver_align_currentpoint:...
..... 1079
- __driver_align_currentpoint_-
begin: .. 27889, 27907, 27931, 27946
- __driver_align_currentpoint_-
end: 27889, 27921, 27939, 27953
- __driver_box_use_rotate:Nn
..... 27926, 28314, 28525
- \g__driver_clip_path_int
..... 29005, 29197,
29200, 29213, 29242, 29245, 29253
- __driver_color_cmyk:nnnn 27834
- __driver_color_fill_select:n . 28850
- __driver_color_gray:n 27834
- __driver_color_pickup:w
..... 1069, 27737, 27795
- __driver_color_reset:
..... 27764, 27834, 28167
- __driver_color_rgb:nnn 27834
- __driver_color_select:n . 27764,
27834, 28861, 28871, 28879, 28883
- \l__driver_color_stack_int
..... 27833, 27873, 27882
- \l__driver_cos_fp 28314
- __driver_draw_add_to_path:n ...
..... 29146, 29192
- \g__driver_draw_clip_bool
..... 28017, 29191
- __driver_draw_cm:nnnn 28889
- __driver_draw_cm_decompose:nnnnN
..... 28899, 28928
- __driver_draw_cm_decompose_-
auxi:nnnnN 28928
- __driver_draw_cm_decompose_-
auxii:nnnnN 28928
- __driver_draw_cm_decompose_-
auxiii:nnnnN 28928
- __driver_draw_color_fill:n .. 28129
- __driver_draw_color_fill:nnn . 29299
- __driver_draw_color_gray_aux:n .
..... 29314, 29318
- __driver_draw_color_stroke:n . 28129
- __driver_draw_dash:n
..... 28097, 28818, 29259
- __driver_draw_dash_aux:nn ... 29259
- \g__driver_draw_eor_bool . 28012,
28026, 28044, 28052, 28065, 28074,
28090, 28790, 28804, 28809, 28814
- __driver_draw_literal:n . 27960,
27965, 27966, 27970, 27974, 27976,
27979, 27987, 27995, 28004, 28018,
28021, 28024, 28030, 28040, 28041,
28042, 28047, 28050, 28056, 28061,
28062, 28063, 28068, 28069, 28072,
28078, 28088, 28094, 28099, 28112,
28116, 28118, 28120, 28122, 28124,
28126, 28128, 28162, 28172, 28184,
28185, 28186, 28187, 28188, 28189,
28193, 28194, 28196, 28197, 28198,
28199, 28200, 28753, 28763, 28768,
28773, 28783, 28796, 28798, 28800,
28803, 28808, 28813, 28817, 28820,
28833, 28837, 28839, 28841, 28843,
28845, 28847, 28849, 28886, 29111,
29132, 29140, 29198, 29217, 29243
- __driver_draw_path:n 29191
- \g__driver_draw_path_int 29191
- \g__driver_draw_path_tl .. 29146,
29202, 29218, 29220, 29247, 29256
- __driver_draw_scope:n
..... 29116, 29120,
29188, 29190, 29210, 29250, 29272,
29284, 29286, 29288, 29290, 29292,
29294, 29296, 29298, 29333, 29349
- \g__driver_draw_scope_int 29120
- \l__driver_draw_scope_int 29120
- __driver_exp_not_i:nn 28451
- __driver_exp_not_ii:nn 28451
- \l__driver_image_attr_tl
..... 28354, 28359, 28366,
28374, 28384, 28417, 28419, 28424
- __driver_image_getbb_aux:nNnn 28713
- __driver_image_getbb_auxi:n . 28355
- __driver_image_getbb_auxii:n . 28693
- __driver_image_getbb_auxiii:n . 28355
- __driver_image_getbb_auxii:nnN .
..... 28693
- __driver_image_getbb_auxiii:nnN
..... 28693
- __driver_image_getbb_auxiv:nnNnn
..... 28693, 28749
- __driver_image_getbb_auxv:nNnn .
..... 28693
- __driver_image_getbb_auxvi:nNnn
..... 28734, 28736
- __driver_image_getbb_eps:n
..... 27957, 28552
- __driver_image_getbb_jpg:n
..... 28355, 28552, 28693, 29090
- __driver_image_getbb_pagebox:w .
..... 28693
- __driver_image_getbb_pdf:n
..... 28355, 28552, 28693
- __driver_image_getbb_png:n
..... 28355, 28552, 28693, 29090
- __driver_image_include_auxi:nn .
..... 28569

- _driver_image_include_auxii:nnn [28569](#)
 - _driver_image_include_auxiii:nn [28569](#)
 - _driver_image_include_auxiii:nnn [28605](#)
 - _driver_image_include_bitmap_-quote:w [29092](#)
 - _driver_image_include_eps:n ... [27958](#), [28569](#)
 - _driver_image_include_jpg:n ... [28421](#), [28569](#), [29092](#)
 - _driver_image_include_pdf:n ... [28421](#), [28569](#), [28744](#)
 - _driver_image_include_png:n ... [28421](#), [28569](#), [29092](#)
 - \g_driver_image_int [28568](#), [28607](#), [28608](#)
 - _driver_literal:e [27732](#)
 - _driver_literal:n [27732](#), [27784](#), [27792](#), [27887](#), [27891](#), [27898](#), [27901](#), [27903](#), [27959](#), [27964](#), [27971](#), [28166](#), [28504](#), [28507](#), [28509](#), [28530](#), [28543](#), [28571](#), [28599](#), [28609](#), [28659](#), [28667](#), [28679](#), [28687](#), [28690](#), [28906](#), [28913](#), [28919](#), [28979](#), [28989](#), [28996](#), [29094](#)
 - _driver_literal_pdf:n [28271](#), [28302](#), [28503](#), [28513](#), [28753](#)
 - _driver_literal_postscript:n ... [27786](#), [27886](#), [27892](#), [27893](#), [27897](#), [27908](#), [27909](#), [27911](#), [27912](#), [27920](#), [27932](#), [27947](#), [27960](#), [28216](#), [28236](#), [28244](#), [28259](#)
 - _driver_literal_svg:n [28995](#), [28999](#), [29001](#), [29003](#), [29008](#), [29010](#), [29027](#), [29111](#), [29366](#), [29377](#)
 - _driver_matrix:n [28291](#), [28324](#), [28345](#), [28892](#)
 - \g_driver_path_int ... [29206](#), [29223](#)
 - \g_driver_pdf_object_int [28202](#), [28206](#), [28209](#), [28638](#), [28642](#), [28645](#)
 - \g_driver_pdf_object_prop [28202](#), [28210](#), [28221](#), [28231](#), [28428](#), [28438](#), [28460](#), [28638](#), [28646](#), [28653](#)
 - _driver_pdf_object_write:nnn [28650](#)
 - _driver_pdf_object_write_-array:nn [28214](#), [28650](#)
 - _driver_pdf_object_write_-dict:nn [28214](#), [28650](#)
 - _driver_pdf_object_write_-fstream:nn [28650](#)
 - _driver_pdf_object_write_-stream:nn [28214](#), [28650](#)
 - _driver_pdf_object_write_-stream:nnn [28214](#)
 - _driver_pdf_object_write_-stream:nnnn [28650](#)
 - _driver_pdf_objectlevel:n ... [28483](#)
 - _driver_scope_begin: [1100](#), [27900](#), [27906](#), [27930](#), [27945](#), [28279](#), [28301](#), [28318](#), [28344](#), [28506](#), [28512](#), [28529](#), [28542](#), [28759](#), [28974](#), [28998](#), [29364](#)
 - _driver_scope_begin:n ... [29002](#), [29029](#), [29037](#), [29042](#), [29060](#), [29073](#)
 - _driver_scope_end: ... [27900](#), [27923](#), [27941](#), [27955](#), [28279](#), [28311](#), [28338](#), [28352](#), [28506](#), [28522](#), [28538](#), [28550](#), [28760](#), [28991](#), [28998](#), [29052](#), [29053](#), [29054](#), [29069](#), [29088](#), [29378](#)
 - \l_driver_sin_fp [28314](#)
 - _driver_tmp:w [28430](#), [28443](#), [28447](#), [28452](#), [28478](#), [28479](#)
 - \l_driver_tmp_box [28413](#), [28415](#), [28416](#), [28738](#), [28739](#), [28740](#)
 - \dtou [1213](#), [1995](#)
 - \dump [348](#)
 - \dviextension [913](#), [1734](#)
 - \dvifedback [914](#), [1735](#)
 - \dvivariable [915](#), [1736](#)
- E**
- \edef [4](#), [113](#), [138](#), [215](#), [349](#)
 - \efcode [793](#), [1607](#)
 - \elapsedtime [880](#)
 - \else [15](#), [22](#), [44](#), [46](#), [91](#), [95](#), [98](#), [101](#), [102](#), [106](#), [107](#), [168](#), [172](#), [187](#), [350](#)
 - else commands:
 - \else: [20](#), [91](#), [91](#), [92](#), [96](#), [102](#), [102](#), [151](#), [167](#), [229](#), [229](#), [230](#), [327](#), [328](#), [335](#), [365](#), [385](#), [397](#), [397](#), [474](#), [718](#), [2049](#), [2093](#), [2311](#), [2326](#), [2335](#), [2338](#), [2388](#), [2416](#), [2419](#), [2576](#), [2584](#), [2610](#), [2744](#), [2747](#), [2756](#), [2762](#), [2772](#), [2775](#), [2784](#), [2790](#), [2915](#), [2937](#), [2946](#), [2960](#), [3018](#), [3019](#), [3080](#), [3203](#), [3517](#), [3628](#), [3656](#), [3671](#), [3679](#), [3716](#), [3777](#), [3828](#), [3829](#), [3831](#), [3835](#), [3847](#), [3848](#), [3849](#), [3850](#), [3851](#), [3852](#), [3853](#), [3854](#), [3855](#), [3920](#), [3921](#), [3923](#), [4008](#), [4417](#), [4427](#), [4438](#), [4453](#), [4461](#), [4476](#), [4521](#), [4787](#), [4816](#), [4837](#), [4853](#), [4861](#), [4871](#), [4884](#), [4900](#), [4971](#), [4983](#), [5032](#), [5035](#), [5038](#), [5215](#), [5222](#), [5228](#), [5464](#), [5520](#), [5523](#), [5526](#), [5538](#), [5553](#), [5748](#), [5786](#), [5794](#), [5805](#), [5815](#), [6051](#), [6082](#), [6091](#), [6418](#), [6449](#), [6470](#), [6473](#), [6499](#), [6544](#), [6666](#), [6699](#), [6739](#), [6749](#), [7065](#), [7098](#),

- 7149, 7266, 7332, 7373, 7383, 7439,
7471, 7491, 7513, 7531, 7547, 7557,
7573, 7583, 7675, 7677, 7679, 7681,
7920, 7935, 7957, 7971, 8492, 8495,
8503, 8509, 8550, 8557, 8651, 8656,
8661, 8666, 8673, 8680, 8685, 8690,
8695, 8700, 8705, 8710, 8715, 8720,
8742, 8748, 8751, 8786, 8789, 8853,
8862, 8870, 8879, 8912, 8951, 8965,
8974, 8984, 9304, 10170, 10173,
10174, 10513, 11422, 11453, 11470,
11480, 11505, 11999, 12023, 12041,
12052, 12064, 12076, 12092, 12961,
12965, 13208, 13218, 13219, 13234,
13244, 13339, 13415, 13477, 13480,
13494, 13512, 13516, 13781, 13794,
13814, 13842, 13843, 13865, 13886,
13909, 13910, 13952, 13970, 14005,
14009, 14044, 14061, 14067, 14071,
14075, 14236, 14269, 14277, 14310,
14314, 14326, 14336, 14346, 14377,
14390, 14425, 14435, 14454, 14467,
14480, 14484, 14495, 14518, 14535,
14547, 14561, 14577, 14585, 14587,
14597, 14608, 14624, 14640, 14646,
14651, 14658, 14680, 14710, 14733,
14761, 14764, 14940, 14944, 14951,
14971, 14990, 15007, 15013, 15045,
15075, 15091, 15111, 15152, 15167,
15200, 15202, 15208, 15223, 15276,
15437, 15448, 15486, 15489, 15492,
15495, 15526, 15535, 15544, 15547,
15718, 15731, 15734, 15741, 15759,
15783, 15784, 15799, 15809, 15858,
15861, 15870, 15882, 15893, 15907,
15920, 15960, 15994, 16014, 16051,
16069, 16072, 16078, 16092, 16127,
16145, 16148, 16151, 16154, 16215,
16288, 16358, 16359, 16368, 16403,
16486, 16490, 16494, 16556, 16591,
16606, 16871, 16900, 16904, 17064,
17073, 17125, 17136, 17152, 17160,
17219, 17299, 17310, 17315, 17349,
17362, 17374, 17380, 17501, 17509,
17548, 17555, 17577, 17605, 17620,
17624, 17646, 17677, 17680, 17705,
17708, 17749, 17757, 17768, 17771,
17816, 17831, 17846, 17861, 17876,
17891, 17912, 17957, 18263, 18301,
18302, 18311, 18355, 18410, 18411,
18412, 18516, 18538, 18553, 18571,
18619, 18635, 18841, 18909, 18914,
19083, 19119, 19132, 19162, 19166,
19174, 19201, 19227, 19235, 19252,
19255, 19302, 19306, 19357, 19413,
19425, 19478, 19479, 19941, 19944,
19947, 19957, 19972, 19999, 20014,
20041, 20057, 20090, 20098, 20100,
20102, 20104, 20106, 20108, 20110,
20112, 20130, 20151, 20155, 20227,
20231, 20427, 20428, 20433, 20434,
20449, 20456, 20663, 20673, 20717,
20726, 20738, 20739, 20741, 20743,
20746, 20747, 20750, 20751, 20760,
20762, 20764, 20767, 20768, 20770,
20806, 20809, 20830, 20833, 20841,
20849, 20852, 20861, 20864, 20873,
20881, 20884, 20894, 21000, 21107,
21151, 21155, 21158, 21169, 21174,
21273, 21419, 21432, 21521, 21550,
21589, 21607, 21715, 21749, 22023,
22041, 22060, 22098, 22154, 22201,
22205, 22212, 22233, 22244, 22400,
22522, 22608, 22669, 22743, 22778,
22790, 22816, 22834, 23026, 23170,
23195, 23247, 23668, 23670, 23676,
25365, 25867, 25884, 26156, 26159,
26332, 26496, 26507, 26527, 27634
- em 200
- \emergencystretch 351
- \enablecjktoken 1252, 2034
- \end 125, 295, 352, 15615, 20307, 20308
- end internal commands:
- __regex_end 23014
- \endcsname .. 14, 21, 39, 43, 49, 68, 90,
92, 93, 94, 105, 130, 153, 157, 228, 353
- \endgroup 13, 36,
38, 42, 48, 74, 124, 142, 161, 210, 354
- \endinput 143, 355
- \endL 627, 1441
- \endlinechar 227, 240, 356
- \endR 628, 1442
- \enquote 15617
- \ensuremath 27459
- \epTeXinputencoding 1214, 1996
- \epTeXversion 1215, 1997
- \eqno 357
- \errhelp 115, 134, 358
- \errmessage 123, 135, 359
- \ERROR 8603
- \errorcontextlines 360
- \errorstopmode 361
- \escapechar 362
- escapehex 25192
- \ETC 20287
- etex commands:
- \etex_beginL:D 1112, 1428, 29498
- \etex_beginR:D 1429

<code>\etex_botmarks:D</code>	1430	<code>\etex_TeXeTstate:D</code>	1485
<code>\etex_clubpenalties:D</code>	1431	<code>\etex_topmarks:D</code>	1486
<code>\etex_currentgrouplevel:D</code>	1432	<code>\etex_tracingassigns:D</code>	1487
<code>\etex_currentgrouptype:D</code>	1433	<code>\etex_tracinggroups:D</code>	1488
<code>\etex_currentifbranch:D</code>	1434	<code>\etex_tracingifs:D</code>	1489
<code>\etex_currentiflevel:D</code>	1435	<code>\etex_tracingnesting:D</code>	1490
<code>\etex_currentifttype:D</code>	1436	<code>\etex_tracingscantokens:D</code>	1491
<code>\etex_detokenize:D</code>	1437	<code>\etex_unexpanded:D</code>	1492
<code>\etex_dimexpr:D</code>	1438	<code>\etex_unless:D</code>	1493
<code>\etex_displaywidowpenalties:D</code> .	1440	<code>\etex_widowpenalties:D</code>	1494
<code>\etex_endL:D</code>	1441	<code>\eTeXrevision</code>	629, 1443
<code>\etex_endR:D</code>	1442	<code>\eTeXversion</code>	630, 1444
<code>\etex_eTeXrevision:D</code>	1443	<code>\etoksapp</code>	916, 1737
<code>\etex_eTeXversion:D</code>	1444	<code>\etokspre</code>	917, 1738
<code>\etex_everyeof:D</code>	1445	<code>\euc</code>	1216, 1998
<code>\etex_firstmarks:D</code>	1446	<code>\everycr</code>	363
<code>\etex_fontchardp:D</code>	1447	<code>\everydisplay</code>	364
<code>\etex_fontcharht:D</code>	1448	<code>\everyeof</code>	631, 1445
<code>\etex_fontcharic:D</code>	1449	<code>\everyhbox</code>	365
<code>\etex_fontcharwd:D</code>	1450	<code>\everyjob</code>	66, 67, 366
<code>\etex_glueexpr:D</code>	1451	<code>\everymath</code>	367
<code>\etex_glueshrink:D</code>	1452	<code>\everypar</code>	368
<code>\etex_glueshrinkorder:D</code>	1453	<code>\everyvbox</code>	369
<code>\etex_gluestretch:D</code>	1454	<code>ex</code>	200
<code>\etex_gluestretchorder:D</code>	1455	<code>\exceptionpenalty</code>	918
<code>\etex_gluetomu:D</code>	1456	<code>\exhyphenpenalty</code>	370
<code>\etex_ifcsname:D</code>	1457	<code>exp</code>	196
<code>\etex_ifdefined:D</code>	1458	<code>exp commands:</code>	
<code>\etex_iffontchar:D</code>	1459	<code>\exp:w</code>	33,
<code>\etex_interactionmode:D</code>	1460		33, 34, 327, 333, 348, 349, 350,
<code>\etex_interlinepenalties:D</code> ...	1461		358, 393, 393, 399, 413, 477, 483,
<code>\etex_lastlinefit:D</code>	1462		552, 570, 665, 668, 671, 672, 690,
<code>\etex_lastnodetype:D</code>	1463		695, 696, 1040, 1060, 2070, 2513,
<code>\etex_marks:D</code>	1464		2515, 3175, 3188, 3194, 3242, 3246,
<code>\etex_middle:D</code>	1465		3250, 3255, 3261, 3267, 3283, 3295,
<code>\etex_muexpr:D</code>	1466		3301, 3307, 3312, 3314, 3321, 3393,
<code>\etex_mutoglue:D</code>	1467		3398, 3407, 3412, 3421, 3423, 3431,
<code>\etex_numexpr:D</code>	1468		3438, 3444, 3452, 3461, 3468, 3482,
<code>\etex_pagediscards:D</code>	1469		3502, 3506, 3511, 3513, 3550, 3691,
<code>\etex_parshapedimen:D</code>	1470		4528, 4533, 4538, 4543, 4750, 4906,
<code>\etex_parshapeindent:D</code>	1471		4976, 5248, 5253, 5258, 5263, 5279,
<code>\etex_parshapelength:D</code>	1472		5284, 5289, 5294, 5447, 5456, 5511,
<code>\etex_predisplaydirection:D</code> ..	1473		6705, 6710, 6715, 6720, 7482, 7628,
<code>\etex_protected:D</code>	1474		7782, 7790, 7849, 8143, 8151, 8483,
<code>\etex_readline:D</code>	1475		10274, 10887, 11479, 11514, 11519,
<code>\etex_savinghyphcodes:D</code>	1476		11524, 11529, 13247, 13362, 13366,
<code>\etex_savingvdiscards:D</code>	1477		13529, 13757, 13883, 13884, 13885,
<code>\etex_scantokens:D</code>	1478		13886, 13997, 14015, 14043, 14087,
<code>\etex_showgroups:D</code>	1479		14099, 14104, 14112, 14121, 14143,
<code>\etex_showifs:D</code>	1480		14149, 14221, 14234, 14235, 14244,
<code>\etex_showtokens:D</code>	1481		14257, 14275, 14276, 14296, 14309,
<code>\etex_splitbotmarks:D</code>	1482		14313, 14335, 14363, 14376, 14389,
<code>\etex_splitdiscards:D</code>	1483		14413, 14424, 14434, 14453, 14466,
<code>\etex_splitfirstmarks:D</code>	1484		14479, 14482, 14494, 14517, 14546,

14560, 14576, 14596, 14607, 14613,
 14623, 14669, 14676, 14707, 14722,
 14730, 14747, 14763, 14767, 14776,
 14813, 14822, 14831, 14836, 14838,
 14849, 14851, 14866, 14869, 14876,
 14887, 14974, 14994, 15012, 15015,
 15029, 15042, 15090, 15108, 15179,
 15191, 15220, 15222, 15226, 15228,
 15286, 15296, 15306, 15318, 15428,
 15445, 15455, 15610, 15611, 15612,
 15803, 15806, 15814, 15824, 15832,
 16844, 17373, 17395, 17550, 17727,
 17933, 18676, 18691, 18708, 18745,
 18762, 18804, 18823, 18836, 18868,
 18883, 18894, 18961, 19022, 19069,
 19109, 19145, 19323, 19419, 26329,
 26340, 26573, 26614, 26628, 27493,
 27499, 27505, 27511, 27527, 27547
 \exp_after:wN
 30, 32, 33, 327, 330, 347,
 349, 398, 403, 458, 540, 642, 665,
 668, 731, 732, 792, 851, 874, 942,
 1060, 2067, 2085, 2087, 2092, 2094,
 2323, 2353, 2354, 2366, 2415, 2418,
 2422, 2494, 2500, 2513, 2515, 2567,
 2591, 2609, 2611, 2630, 2638, 2646,
 2670, 2675, 2682, 2719, 2723, 2728,
 2739, 2755, 2757, 2760, 2783, 2785,
 2788, 2914, 2916, 2925, 2945, 2947,
 2986, 3050, 3143, 3153, 3160, 3162,
 3174, 3175, 3187, 3188, 3193, 3194,
 3199, 3204, 3206, 3209, 3218, 3220,
 3223, 3224, 3225, 3228, 3230, 3232,
 3236, 3241, 3246, 3249, 3254, 3259,
 3260, 3261, 3265, 3266, 3267, 3273,
 3274, 3281, 3282, 3283, 3287, 3288,
 3289, 3293, 3294, 3295, 3299, 3300,
 3301, 3305, 3306, 3307, 3311, 3312,
 3313, 3314, 3318, 3319, 3320, 3321,
 3325, 3326, 3327, 3332, 3333, 3334,
 3335, 3339, 3340, 3341, 3342, 3389,
 3392, 3393, 3397, 3398, 3411, 3412,
 3419, 3421, 3423, 3427, 3431, 3433,
 3436, 3437, 3442, 3443, 3447, 3450,
 3451, 3455, 3458, 3459, 3460, 3465,
 3466, 3467, 3475, 3478, 3479, 3480,
 3481, 3486, 3488, 3490, 3491, 3502,
 3505, 3510, 3535, 3536, 3537, 3548,
 3549, 3561, 3562, 3563, 3568, 3576,
 3577, 3578, 3579, 3580, 3581, 3626,
 3627, 3629, 3651, 3656, 3657, 3669,
 3670, 3672, 3676, 3677, 3678, 3681,
 3683, 3686, 3690, 3691, 3692, 3697,
 3698, 3709, 3715, 3717, 3721, 3723,
 3724, 3733, 3774, 3778, 3800, 3807,
 3827, 3978, 3996, 4007, 4261, 4262,
 4311, 4312, 4326, 4327, 4386, 4387,
 4388, 4393, 4435, 4446, 4447, 4472,
 4517, 4519, 4608, 4721, 4748, 4779,
 4784, 4785, 4786, 4788, 4801, 4811,
 4828, 4850, 4860, 4863, 4880, 4881,
 4891, 4896, 4897, 4912, 4913, 4914,
 4972, 4974, 4975, 4976, 4981, 4982,
 4984, 5062, 5063, 5309, 5310, 5322,
 5377, 5400, 5434, 5435, 5446, 5447,
 5455, 5463, 5465, 5472, 5477, 5495,
 5496, 5497, 5509, 5510, 5537, 5539,
 5545, 5551, 5565, 5585, 5596, 5612,
 5620, 5628, 5635, 5642, 5654, 5741,
 5747, 5749, 5773, 5824, 5825, 5947,
 5949, 5961, 5969, 6066, 6100, 6112,
 6125, 6126, 6127, 6149, 6150, 6195,
 6230, 6231, 6232, 6289, 6290, 6316,
 6317, 6320, 6413, 6418, 6426, 6427,
 6439, 6440, 6461, 6462, 6488, 6489,
 6498, 6638, 6643, 6648, 6671, 6673,
 6826, 6827, 6828, 6853, 6854, 7037,
 7065, 7070, 7098, 7111, 7121, 7148,
 7150, 7151, 7159, 7176, 7220, 7309,
 7310, 7321, 7330, 7382, 7384, 7391,
 7480, 7498, 7503, 7507, 7629, 7703,
 7781, 7789, 7849, 7921, 7936, 7958,
 7972, 8033, 8041, 8047, 8142, 8150,
 8234, 8235, 8238, 8239, 8483, 8484,
 8531, 8539, 8570, 8571, 8614, 8615,
 8616, 8727, 8746, 8793, 8831, 8860,
 8861, 8863, 8869, 8872, 8911, 8914,
 8950, 8952, 8962, 8963, 8964, 8966,
 8972, 8973, 8975, 8982, 8983, 8985,
 9033, 9042, 9051, 9142, 9153, 9324,
 9325, 9326, 9530, 9749, 9750, 10275,
 10276, 10277, 10278, 10290, 10391,
 10446, 10557, 10575, 10624, 10817,
 10820, 10870, 10879, 10882, 10885,
 10886, 10888, 10928, 10994, 11025,
 11038, 11059, 11069, 11074, 11212,
 11225, 11418, 11422, 11430, 11431,
 11443, 11444, 11474, 11479, 11490,
 11493, 11615, 11616, 11617, 11679,
 11810, 11977, 11978, 11987, 11989,
 12006, 12011, 12013, 12030, 12039,
 12043, 12044, 12051, 12053, 12054,
 12055, 12056, 12067, 12090, 12093,
 12172, 12215, 12362, 12363, 12671,
 12751, 12752, 12775, 12788, 12799,
 12800, 12979, 12980, 12981, 12998,
 13006, 13029, 13030, 13071, 13207,
 13209, 13210, 13221, 13222, 13223,

13233, 13235, 13243, 13245, 13252,
13253, 13254, 13255, 13256, 13257,
13262, 13263, 13264, 13265, 13266,
13267, 13268, 13311, 13324, 13327,
13338, 13340, 13355, 13359, 13360,
13361, 13364, 13365, 13429, 13431,
13458, 13462, 13487, 13491, 13508,
13515, 13517, 13529, 13612, 13620,
13637, 13646, 13692, 13757, 13826,
13827, 13828, 13888, 13898, 13917,
13923, 13949, 13950, 13953, 13964,
13968, 13975, 13976, 13987, 13988,
13997, 14004, 14006, 14007, 14015,
14043, 14061, 14062, 14065, 14066,
14068, 14069, 14073, 14074, 14076,
14077, 14086, 14087, 14092, 14098,
14104, 14112, 14121, 14141, 14142,
14145, 14146, 14148, 14155, 14156,
14158, 14176, 14177, 14205, 14208,
14213, 14214, 14219, 14220, 14222,
14231, 14232, 14233, 14234, 14237,
14238, 14239, 14242, 14257, 14274,
14275, 14285, 14286, 14296, 14308,
14312, 14325, 14327, 14335, 14345,
14347, 14353, 14358, 14360, 14362,
14368, 14369, 14373, 14375, 14387,
14388, 14410, 14412, 14418, 14421,
14423, 14427, 14432, 14437, 14438,
14448, 14449, 14451, 14452, 14455,
14459, 14464, 14478, 14481, 14493,
14502, 14509, 14510, 14511, 14512,
14514, 14516, 14527, 14528, 14529,
14530, 14532, 14534, 14536, 14537,
14538, 14544, 14545, 14555, 14559,
14560, 14562, 14563, 14564, 14569,
14575, 14586, 14588, 14595, 14596,
14598, 14599, 14606, 14612, 14622,
14690, 14703, 14704, 14705, 14706,
14720, 14721, 14723, 14728, 14729,
14744, 14746, 14763, 14767, 14776,
14810, 14811, 14812, 14818, 14819,
14820, 14821, 14827, 14828, 14829,
14830, 14837, 14850, 14858, 14864,
14865, 14867, 14868, 14874, 14875,
14877, 14903, 14916, 14938, 14939,
14941, 14942, 14949, 14950, 14952,
14955, 14967, 14969, 14970, 14972,
14973, 14975, 14987, 14988, 14989,
14992, 14993, 14994, 15004, 15005,
15006, 15009, 15010, 15011, 15014,
15018, 15027, 15028, 15039, 15040,
15041, 15044, 15046, 15047, 15048,
15073, 15074, 15076, 15077, 15078,
15088, 15089, 15090, 15092, 15093,
15094, 15106, 15107, 15110, 15112,
15113, 15114, 15134, 15135, 15136,
15137, 15138, 15139, 15140, 15150,
15151, 15153, 15154, 15155, 15161,
15172, 15173, 15174, 15175, 15176,
15177, 15178, 15179, 15184, 15185,
15186, 15187, 15188, 15189, 15190,
15206, 15207, 15209, 15210, 15217,
15218, 15219, 15224, 15225, 15227,
15243, 15258, 15267, 15277, 15283,
15284, 15285, 15290, 15303, 15304,
15305, 15311, 15427, 15444, 15454,
15479, 15480, 15527, 15609, 15717,
15719, 15758, 15760, 15763, 15798,
15800, 15802, 15805, 15812, 15813,
15816, 15817, 15822, 15823, 15830,
15831, 15866, 15867, 15868, 15870,
15881, 15906, 15908, 15914, 15915,
15919, 15922, 15944, 15946, 15959,
15961, 15967, 15969, 15972, 15978,
15980, 15982, 15983, 15984, 15986,
15991, 15993, 15995, 15999, 16002,
16008, 16009, 16013, 16015, 16016,
16017, 16025, 16027, 16028, 16035,
16041, 16048, 16049, 16054, 16055,
16056, 16057, 16076, 16077, 16078,
16084, 16085, 16086, 16091, 16093,
16101, 16103, 16105, 16106, 16108,
16119, 16121, 16123, 16124, 16129,
16180, 16181, 16188, 16189, 16191,
16193, 16195, 16198, 16201, 16203,
16205, 16214, 16216, 16222, 16224,
16226, 16227, 16228, 16234, 16236,
16238, 16239, 16240, 16261, 16262,
16265, 16273, 16275, 16279, 16280,
16281, 16282, 16287, 16289, 16296,
16299, 16302, 16305, 16314, 16317,
16320, 16323, 16330, 16332, 16338,
16346, 16348, 16350, 16367, 16369,
16376, 16378, 16381, 16387, 16389,
16391, 16392, 16393, 16395, 16409,
16410, 16413, 16431, 16433, 16435,
16447, 16450, 16453, 16456, 16459,
16462, 16465, 16468, 16472, 16484,
16488, 16492, 16495, 16510, 16516,
16518, 16520, 16530, 16554, 16557,
16569, 16571, 16575, 16576, 16577,
16579, 16580, 16582, 16589, 16597,
16598, 16604, 16605, 16611, 16614,
16615, 16616, 16617, 16625, 16667,
16672, 16674, 16681, 16684, 16687,
16690, 16693, 16696, 16704, 16705,
16717, 16725, 16727, 16737, 16739,
16746, 16755, 16757, 16760, 16763,

16766, 16769, 16782, 16784, 16792,
16794, 16802, 16804, 16814, 16817,
16820, 16827, 16842, 16843, 16860,
16862, 16863, 16920, 16933, 16935,
16941, 16954, 16956, 16958, 16982,
16996, 16998, 17005, 17007, 17048,
17049, 17050, 17052, 17053, 17054,
17056, 17057, 17063, 17065, 17066,
17072, 17074, 17075, 17076, 17077,
17089, 17095, 17097, 17132, 17139,
17146, 17166, 17167, 17169, 17171,
17173, 17186, 17191, 17192, 17193,
17194, 17195, 17199, 17204, 17206,
17212, 17218, 17220, 17221, 17227,
17228, 17229, 17230, 17231, 17232,
17233, 17234, 17239, 17241, 17243,
17245, 17247, 17252, 17254, 17256,
17258, 17260, 17262, 17280, 17284,
17292, 17293, 17298, 17300, 17309,
17312, 17313, 17314, 17316, 17317,
17318, 17326, 17332, 17344, 17347,
17348, 17350, 17351, 17375, 17376,
17379, 17381, 17397, 17401, 17402,
17403, 17419, 17425, 17491, 17492,
17493, 17500, 17502, 17503, 17508,
17510, 17511, 17520, 17521, 17523,
17526, 17529, 17545, 17549, 17550,
17554, 17556, 17592, 17598, 17599,
17601, 17603, 17604, 17606, 17607,
17617, 17618, 17621, 17622, 17623,
17625, 17626, 17627, 17644, 17645,
17647, 17648, 17654, 17656, 17659,
17662, 17665, 17668, 17676, 17679,
17681, 17684, 17691, 17695, 17703,
17704, 17707, 17709, 17711, 17716,
17717, 17723, 17728, 17729, 17737,
17738, 17739, 17740, 17905, 17906,
17907, 17909, 17927, 17928, 17929,
17930, 17931, 17932, 17939, 17948,
17955, 17956, 18180, 18181, 18187,
18188, 18191, 18196, 18199, 18202,
18205, 18208, 18211, 18214, 18217,
18233, 18234, 18244, 18253, 18261,
18262, 18264, 18265, 18270, 18271,
18280, 18287, 18296, 18297, 18310,
18312, 18340, 18341, 18350, 18353,
18378, 18384, 18385, 18427, 18428,
18430, 18444, 18445, 18453, 18464,
18498, 18501, 18511, 18512, 18515,
18517, 18523, 18537, 18539, 18580,
18583, 18603, 18676, 18686, 18690,
18708, 18711, 18732, 18733, 18740,
18744, 18762, 18765, 18794, 18795,
18801, 18802, 18803, 18810, 18818,
18822, 18836, 18839, 18855, 18856,
18863, 18867, 18878, 18882, 18894,
18900, 18901, 18902, 18908, 18910,
18913, 18915, 18957, 18959, 18960,
18982, 19011, 19021, 19028, 19033,
19034, 19044, 19071, 19082, 19084,
19086, 19088, 19093, 19094, 19096,
19107, 19108, 19128, 19134, 19135,
19137, 19140, 19145, 19151, 19152,
19182, 19184, 19187, 19190, 19192,
19200, 19202, 19206, 19210, 19215,
19220, 19231, 19294, 19295, 19318,
19319, 19320, 19321, 19322, 19329,
19340, 19346, 19372, 19373, 19374,
19380, 19381, 19387, 19388, 19395,
19396, 19400, 19401, 19402, 19407,
19412, 19418, 19421, 19422, 19423,
19424, 19425, 19469, 19567, 19568,
19610, 19629, 19630, 19645, 19646,
19647, 19875, 19881, 19883, 19894,
19954, 19955, 19956, 19957, 19963,
19964, 19980, 19998, 20000, 20006,
20007, 20038, 20040, 20042, 20072,
20087, 20089, 20091, 20116, 20126,
20134, 20144, 20154, 20156, 20158,
20193, 20217, 20226, 20229, 20230,
20232, 20233, 20241, 20242, 20256,
20320, 20333, 20334, 20339, 20340,
20343, 20346, 20384, 20391, 20398,
20404, 20411, 20419, 20455, 20457,
20466, 20598, 20601, 20642, 20662,
20664, 20665, 20672, 20675, 20676,
20700, 20719, 20728, 20840, 20842,
20848, 20851, 20853, 20860, 20863,
20865, 20872, 20874, 20880, 20883,
20886, 21201, 21274, 21286, 21418,
21421, 21431, 21433, 21616, 21624,
21698, 21748, 21974, 22274, 22430,
22453, 22510, 22536, 22600, 22601,
22609, 22612, 22776, 22777, 22780,
22781, 22789, 22791, 22792, 22801,
22815, 22818, 22888, 23137, 23169,
23171, 25350, 25352, 25449, 25802,
25827, 25876, 25912, 25913, 25981,
25991, 25996, 25999, 26127, 26128,
26130, 26131, 26139, 26140, 26148,
26338, 26358, 26403, 26404, 26571,
26612, 26626, 26643, 26644, 26808,
26809, 26830, 26831, 26879, 26882,
26883, 26930, 26965, 27057, 27107,
27175, 27189, 27191, 27197, 27219,
27232, 27234, 27248, 27250, 27374,
27432, 27493, 27499, 27505, 27511,
27525, 27528, 27545, 27547, 27548,

- 27555, 27560, 27562, 27565, 27579,
 27599, 27600, 27607, 27608, 27628,
 27633, 27635, 27641, 27690, 27704,
 27750, 29505, 29506, 29530, 29531
 \exp_args:cc 26, 2084, [3217](#)
 \exp_args:Nc 24, 26, [343](#),
 2084, 2088, 2096, 2261, 2299, 2308,
 2327, 2348, 2358, 2379, 2384, 2615,
 2628, 2636, 2644, 2849, 2868, 2894,
 2899, 2906, 2965, 2977, 3049, 3082,
 3083, 3084, 3085, 3107, 3111, [3217](#),
 3771, 4040, 4355, 4578, 5083, 7324,
 7343, 10543, 12871, 13906, 14137,
 14998, 15022, 15052, 15054, 15056,
 15058, 15060, 15062, 15064, 15082,
 15098, 15099, 15118, 15120, 20176,
 21571, 27477, 27569, 27574, 27582
 \exp_args:Ncc 28, 2896, 2900,
 2908, 3090, 3091, 3092, 3093, [3217](#)
 \exp_args:Nccc 29, [3217](#)
 \exp_args:Ncco 29, [3316](#)
 \exp_args:Nccx 29, [3363](#)
 \exp_args:Ncf 28, [3257](#)
 \exp_args:NcNc 29, [3316](#)
 \exp_args:NcNo 29, [3316](#)
 \exp_args:Ncno 29, [3363](#)
 \exp_args:NcnV 29, [3363](#)
 \exp_args:Ncnx 29, [3363](#)
 \exp_args:Nco 28, [352](#), [3257](#)
 \exp_args:Ncoo 29, [3363](#)
 \exp_args:NcV 28, [3257](#)
 \exp_args:Ncv 28, [3257](#)
 \exp_args:NcVV 29, [3363](#)
 \exp_args:Ncx 28, [3345](#), 10283
 \exp_args:Ne
 27, [348](#), 2145, 3170, [3233](#), 3499
 \exp_args:Nf
 27, 2953, [3245](#), 3545, 3605,
 3619, 4918, 4919, 4935, 4953, 4961,
 4965, 4989, 4995, 5005, 5424, 5426,
 5485, 5487, 5503, 6198, 6199, 6215,
 6706, 6711, 6716, 6721, 6911, 6980,
 6982, 7000, 7009, 7020, 7029, 7167,
 7184, 7475, 8223, 8274, 8288, 8309,
 8320, 8365, 8435, 8441, 8447, 8453,
 9558, 10288, 10920, 10978, 11515,
 11520, 11525, 11530, 13047, 15670,
 18672, 19244, 22129, 25891, 25893,
 25917, 25919, 26357, 26471, 26485,
 27014, 27022, 27077, 28102, 28823
 \exp_args:Nff .. 28, [3345](#), 4959, 13555
 \exp_args:Nffo 29, [3363](#)
 \exp_args:Nfo 28, [3345](#)
 \exp_args:NNc 28, [315](#), 2895,
 2898, 2907, 2979, 3086, 3087, 3088,
 3089, 3124, 3127, [3217](#), 6868, 6879,
 10290, 10446, 10624, 11646, 11653,
 15680, 15687, 19272, 26120, 29539
 \exp_args:Nnc 28, [3345](#)
 \exp_args:NNcf 29, [3363](#)
 \exp_args:NNe 28, [3257](#)
 \exp_args:Nne 28, [3345](#)
 \exp_args:NNf 28, 2319, [3257](#), 10445,
 10623, 10804, 11639, 13119, 13124,
 17899, 17900, 27927, 28315, 28526
 \exp_args:Nnf 28, [3345](#), 12869
 \exp_args:Nnff 29, [3363](#)
 \exp_args:Nnnc 29, [3363](#)
 \exp_args:Nnnf 29, [3363](#)
 \exp_args:NNNo
 ... 29, [3228](#), 4252, 20935, 21822,
 21879, 23047, 23131, 26406, 26426
 \exp_args:NNno 29, [3363](#)
 \exp_args:Nnno 29, [3363](#)
 \exp_args:NNNV 29, [3316](#), 11100
 \exp_args:NNnV 29, [3363](#)
 \exp_args:NNNx
 29, [836](#), [3363](#), 20943, 21414
 \exp_args:NNnx 29, [3363](#)
 \exp_args:Nnnx 29, [3363](#)
 \exp_args:NNo
 22, 28, [3228](#), 3554, 6899, 9147, 22697
 \exp_args:Nno
 28, [3345](#), 4266, 8178, 9025, 10525,
 11482, 13597, 13605, 13614, 13631,
 13639, 13667, 14164, 14168, 26393
 \exp_args:NNoo 29, [3363](#)
 \exp_args:NNox 29, [3363](#)
 \exp_args:Nnox 29, [3363](#)
 \exp_args:NNV 28, [3257](#)
 \exp_args:NNv 28, [3257](#)
 \exp_args:NnV 28, [3345](#)
 \exp_args:Nnv 28, [3345](#)
 \exp_args:NNVV 29, [3363](#)
 \exp_args:NNx
 . 28, 3132, [3345](#), 11270, 11284, 29512
 \exp_args:Nnx 28, [3345](#), 10592
 \exp_args:No 24, 27,
 1060, 2189, 2197, 3116, 3121, [3228](#),
 3554, 3558, 3588, 3648, 3665, 3703,
 4029, 4245, 4251, 4482, 4483, 4484,
 4510, 4511, 4512, 4513, 4514, 4566,
 4585, 4594, 4652, 4655, 4657, 4767,
 4769, 4795, 4804, 4937, 4944, 4946,
 5003, 5012, 5316, 5343, 5348, 5362,
 5420, 5431, 5481, 5492, 5559, 5578,
 5616, 5631, 5939, 6899, 6986, 6992,

- 8040, 8052, 8054, 8089, 8094, 8303,
8307, 9743, 10559, 10686, 10716,
10812, 11234, 11816, 12459, 12477,
12505, 12527, 20180, 20203, 20260,
20262, 21011, 21068, 21088, 21723,
22103, 22744, 22787, 23192, 23222,
23702, 26400, 27584, 27588, 27673
\exp_args:Noc 28, [3345](#)
\exp_args:Nof 28, [3345](#)
\exp_args:Noo . 28, [3345](#), 21110, 22116
\exp_args:Noof 29, 3363
\exp_args:Nooo 29, 3363
\exp_args:Noox 29, [3363](#)
\exp_args:Nox 28, [3345](#)
\exp_args:NV 27, [3245](#),
10954, 11030, 11135, 12457, 12475,
12503, 12525, 20493, 26388, 27745
\exp_args:Nv 27, [3245](#)
\exp_args:NVo 28, [3345](#)
\exp_args:NVV 28, [3257](#), [10865](#)
\exp_args:Nx 28,
2923, [3344](#), 5051, 7345, 7457, 8593,
9503, 10353, 10722, 12461, 12479,
12507, 12529, 15402, 21243, 21244,
21627, 22547, 27851, 28252, 28652
\exp_args:Nxo 28, [3345](#)
\exp_args:Nxx 28, [3345](#)
\exp_args_generate:n 242, [4027](#)
\exp_end: ... 33, 33, 327, 330, 333,
349, 350, 358, 358, 393, 393, 399,
413, 414, 478, 552, 665, 695, 1034,
1059, 1060, 2071, 2616, 2629, 2637,
2645, 3206, 3215, [3513](#), 3543, 3692,
4558, 4728, 4912, 4913, 4984, 5306,
5480, 6732, 7660, 7663, 7664, 7665,
7666, 7667, 7668, 7669, 7670, 7671,
7673, 7777, 8514, 8528, 8531, 8536,
8539, 8545, 8553, 8611, 8615, 10278,
11541, 13888, 14843, 17397, 19071,
19073, 19145, 26601, 27483, 27516
\exp_end_continue_f:nw 34, [3513](#)
\exp_end_continue_f:w
..... 33, 34, 348, 668, 3175,
3246, 3283, 3307, 3412, 3431, 3444,
3468, 3482, 3502, [3513](#), 7482, 7849,
10215, 10887, 11479, 13247, 13362,
13366, 13529, 13997, 14015, 14035,
14099, 14104, 14112, 14121, 14143,
14221, 14257, 14265, 14296, 14669,
14676, 14722, 14769, 14776, 14813,
14857, 14863, 14866, 14876, 14887,
15029, 15220, 15222, 15226, 15228,
15286, 15296, 15306, 15318, 15428,
15445, 15455, 15610, 15611, 15612,
15803, 15814, 15824, 15832, 16844,
17550, 17727, 17933, 18676, 18691,
18708, 18745, 18762, 18804, 18823,
18836, 18868, 18883, 18894, 18962,
19022, 19109, 19323, 19419, 26329
\exp_last_two_unbraced:Nnn
..... 30, [3485](#), 24540, 24779, 24783
\exp_last_unbraced:Ne 30, 3426, 3429
\exp_last_unbraced:Nn ... 30, 30,
[3419](#), 4323, 6998, 7018, 8618, 13061,
13550, 15896, 20653, 24908, 24913,
24991, 24997, 27754, 27803, 29519
\exp_last_unbraced:NNn
..... 30, [3419](#), 4735,
8128, 8161, 10719, 24750, 26634, 26693
\exp_last_unbraced:Nnn
.. 30, [3419](#), 9205, 9289, 19275, 25965
\exp_last_unbraced:NNNn 30, [3419](#), 7424
\exp_last_unbraced:NnNn ... 30, [3419](#)
\exp_last_unbraced:NNNNn
..... 30, [3419](#), 3787, 3791, 3969,
5674, 7430, 12226, 13315, 13333, 29499
\exp_not:e 32, [3490](#)
\exp_not:N
.. 31, 31, 150, 201, 349, 357, 361,
378, 380, 396, 397, 465, 510, 517,
673, 851, 860, 934, 938, 1035, 1112,
[2067](#), 2442, 2446, 2571, 2657, 2660,
2985, 2986, 3049, 3050, [3153](#), 3199,
[3490](#), 3490, 3568, 3572, 3626, 3646,
3656, 3669, 3764, 3766, 3767, 3774,
3775, 3776, 3777, 3778, 3779, 3780,
3781, 3783, 3784, 3785, 3811, 3820,
3874, 3875, 3876, 3877, 3949, 3955,
3956, 3957, 3959, 3962, 3965, 3966,
3978, 4051, 4246, 4308, 4379, 4808,
4811, 4825, 4828, 4859, 4866, 5111,
5112, 5334, 5335, 5938, 5940, 6277,
6884, 7147, 7310, 8103, 8213, 8216,
8224, 8225, 8471, 8558, 8562, 8596,
8646, 8650, 8655, 8660, 8665, 8672,
8679, 8684, 8689, 8694, 8699, 8704,
8714, 8719, 8724, 8727, 8728, 8729,
8731, 8732, 8741, 8746, 8761, 8762,
8779, 8784, 8785, 8786, 8787, 8788,
8789, 8791, 8793, 8794, 8795, 8796,
8799, 8800, 8803, 8804, 8825, 8828,
8829, 8831, 8832, 8833, 8836, 8837,
8839, 8840, 8842, 8843, 8845, 8924,
8930, 8961, 8964, 8971, 8972, 8981,
8982, 8996, 8997, 9012, 9017, 9022,
9136, 9244, 9267, 9609, 9611, 9613,
9615, 9620, 9621, 9626, 9628, 9630,
9912, 9914, 9916, 9918, 9923, 9924,

- 9929, 9931, 9933, 11658, 11684,
 12063, 12072, 12234, 12236, 12250,
 12252, 12306, 12307, 12430, 12431,
 13311, 13312, 13313, 14060, 14061,
 14158, 14159, 14160, 14161, 14162,
 14267, 14307, 14311, 14333, 14426,
 14458, 14543, 14557, 14574, 14584,
 14594, 14631, 14634, 14740, 14741,
 14743, 14744, 14745, 14746, 14747,
 14748, 14751, 14753, 14755, 14934,
 14936, 14964, 14965, 14967, 14968,
 14969, 14970, 14971, 14972, 14973,
 14974, 14975, 14976, 14977, 15072,
 15087, 15692, 15849, 17786, 17787,
 17788, 17792, 17793, 17794, 18956,
 18957, 18959, 18960, 18961, 18962,
 18963, 18965, 19942, 19945, 20097,
 20098, 20099, 20100, 20101, 20102,
 20103, 20104, 20105, 20106, 20107,
 20108, 20109, 20110, 20111, 20112,
 20115, 20116, 20117, 20629, 20631,
 20633, 20635, 20637, 20639, 20999,
 21001, 21194, 21196, 21207, 21211,
 21378, 21831, 22541, 22758, 22880,
 22893, 23256, 25315, 25319, 25320,
 25325, 25838, 25922, 25924, 25928,
 25930, 25935, 25937, 26033, 26043,
 26401, 26422, 27176, 27190, 27192,
 27233, 27235, 27249, 27251, 27624,
 27625, 27686, 27687, 27873, 27874,
 27882, 28276, 28296, 28436, 28438,
 28488, 29388, 29391, 29507, 29532
- \exp_not:n 15, 26, 27,
 31, 31, 31, 31, 31, 32, 32, 32, 44,
 45, 45, 47, 47, 48, 70, 70, 74, 75,
 113, 113, 115, 115, 134, 150, 247,
 252, 253, 256, 309, 324, 376, 378,
 383, 392, 401, 431, 434, 484, 485,
 487, 491, 525, 846, 851, 857, 860,
 869, 874, 934, 940, 940, 943, 1060,
 1062, 2067, 2445, 2572, 2578, 2580,
 2586, 2587, 2662, 2925, 3153, 3166,
 3182, 3403, 3416, 3490, 3571, 3881,
 3896, 3911, 4065, 4115, 4123, 4141,
 4144, 4150, 4153, 4165, 4168, 4171,
 4174, 4177, 4180, 4183, 4186, 4197,
 4200, 4203, 4206, 4209, 4212, 4215,
 4218, 4268, 4310, 4317, 4376, 4380,
 4381, 4382, 4647, 4649, 4934, 5051,
 5149, 5213, 5355, 5960, 5961, 5968,
 5969, 5985, 6017, 6037, 6040, 6043,
 6105, 6137, 6161, 6214, 6278, 6332,
 6342, 6885, 7816, 7858, 7859, 7873,
 7875, 7945, 8040, 8048, 8068, 8104,
 8217, 8223, 8251, 8256, 8287, 8318,
 8597, 8798, 8903, 8925, 8931, 9137,
 9212, 9245, 9248, 9249, 9268, 9272,
 9603, 9620, 9775, 9906, 9923, 10680,
 10697, 11114, 11659, 12002, 12004,
 12026, 12028, 12063, 12073, 12074,
 12106, 12309, 12333, 12432, 12577,
 12602, 12808, 12810, 14153, 15363,
 15365, 15367, 15693, 15850, 19720,
 19970, 20084, 20114, 20999, 21001,
 21630, 21888, 22033, 22258, 22363,
 22530, 22542, 22597, 22815, 22818,
 22826, 22880, 22888, 22905, 22920,
 22961, 23144, 23149, 24425, 25118,
 25121, 25123, 25990, 27483, 27484,
 27493, 27499, 27505, 27511, 27525,
 27545, 27558, 27565, 27734, 28239,
 28247, 28276, 28296, 28462, 28463,
 28481, 28482, 28662, 28670, 28682
- \exp_stop_f:
 ... 32, 33, 91, 348, 395, 431, 570,
 634, 646, 712, 713, 799, 826, 847,
 851, 1022, 3172, 3633, 3636, 3651,
 3659, 3714, 4971, 4980, 5029, 5030,
 5036, 5214, 5221, 5228, 5462, 5478,
 5517, 5518, 5524, 5536, 5552, 5553,
 5972, 6415, 6430, 6443, 6665, 6670,
 6849, 7312, 8361, 8363, 8431, 8433,
 8437, 8439, 8443, 8445, 8449, 8451,
 8489, 8490, 8497, 8498, 8499, 8500,
 8505, 8506, 8525, 8540, 8548, 8618,
 9142, 10290, 10446, 10624, 10875,
 10889, 10901, 11488, 12958, 12962,
 13128, 13132, 13160, 13355, 13470,
 13485, 13510, 13757, 13761, 13765,
 13767, 13771, 13775, 13783, 13788,
 13801, 13808, 13821, 13832, 13833,
 13844, 13845, 13854, 13857, 13868,
 13910, 13966, 13971, 14042, 14072,
 14230, 14273, 14324, 14344, 14371,
 14385, 14420, 14447, 14456, 14475,
 14491, 14507, 14525, 14585, 14604,
 14620, 14635, 14649, 14858, 14937,
 14948, 15201, 15205, 15493, 15499,
 15501, 15516, 15525, 15533, 15541,
 15542, 15739, 15859, 15865, 15880,
 15917, 15990, 16012, 16066, 16067,
 16075, 16412, 16430, 16483, 16487,
 16491, 16509, 16544, 16545, 16546,
 16547, 16548, 16574, 16586, 16602,
 16619, 16897, 16898, 16995, 17088,
 17121, 17134, 17139, 17148, 17150,
 17277, 17306, 17311, 17341, 17378,
 17418, 17494, 17544, 17590, 17591,

- 17596, 17602, 17620, 17643, 17675,
 17678, 17725, 17745, 17751, 17766,
 17807, 17822, 17837, 17852, 17867,
 17882, 17910, 17954, 18220, 18230,
 18260, 18412, 18414, 18451, 18463,
 18495, 18536, 18545, 18560, 18579,
 18612, 18625, 18709, 18763, 18811,
 18814, 18837, 19052, 19056, 19063,
 19064, 19119, 19120, 19121, 19130,
 19140, 19158, 19227, 19230, 19233,
 19248, 19299, 19303, 19344, 19413,
 19420, 19468, 19739, 19908, 19917,
 19918, 19952, 20022, 20030, 20053,
 20055, 20056, 20060, 20077, 20128,
 20131, 20147, 20153, 20225, 20228,
 20426, 20427, 20428, 20434, 20454,
 20715, 20735, 20736, 20740, 20744,
 20745, 20748, 20749, 20757, 20758,
 20761, 20765, 20766, 20769, 20828,
 20923, 21167, 21172, 21186, 21187,
 21200, 21271, 21272, 21311, 21411,
 21588, 21746, 22038, 22056, 22085,
 22095, 22150, 22163, 22174, 22190,
 22241, 22473, 22607, 22611, 22678,
 22741, 22754, 22774, 22779, 22785,
 22831, 22884, 22901, 22924, 23142,
 23147, 23168, 23246, 23258, 23263,
 25577, 25878, 26150, 26244, 26490,
 26491, 26497, 27015, 27030, 27085,
 27598, 27606, 27624, 27625, 27626,
 27627, 27686, 27687, 27688, 27689
- exp internal commands:
- _exp_arg_last_unbraced:nn . . . 3387
 - _exp_arg_next:Nnn 3153, 3160
 - _exp_arg_next:nnn
 - 349, 3153, 3162, 3170, 3174, 3187, 3193
 - _exp_e:N 3529, 3559
 - _exp_e:nn 351, 358,
 - 3242, 3407, 3525, 3545, 3550, 3558,
 - 3586, 3588, 3593, 3598, 3665, 3683
 - _exp_e:Nnn 359, 3561, 3565
 - _exp_e_end:nn 358, 3535, 3543, 3617
 - _exp_e_expandable:Nnn
 - 360, 3576, 3587
 - _exp_e_group:n 3532, 3546
 - _exp_e_if_toks_register:N . . 3726
 - _exp_e_if_toks_register:NTF
 - 3680, 3726
 - _exp_e_noexpand:Nnn . . . 3579, 3595
 - _exp_e_primitive:Nnn . . . 3581, 3589
 - _exp_e_protected:Nnn 360, 3577, 3585
 - _exp_e_put:nn
 - 359, 360, 362, 3546, 3598, 3610, 3697
 - _exp_e_put:nnn 363, 3546, 3703
 - _exp_e_space:nn 3536, 3544
 - _exp_e_the:N 3661
 - _exp_e_the:Nnn 3580, 3661
 - _exp_e_the_errhelp: 3740
 - _exp_e_the_everycr: 3741
 - _exp_e_the_everydisplay: . . . 3742
 - _exp_e_the_veryeof: 3743
 - _exp_e_the_veryhbox: 3744
 - _exp_e_the_veryjob: 3745
 - _exp_e_the_verymath: 3746
 - _exp_e_the_verypar: 3747
 - _exp_e_the_veryvbox: 3748
 - _exp_e_the_output: 3749
 - _exp_e_the_pdfpageattr: 3750
 - _exp_e_the_pdfpageresources: 3751
 - _exp_e_the_pdfpagesattr: . . . 3752
 - _exp_e_the_pdfpkmode: 3753
 - _exp_e_the_toks:N 363, 3701
 - _exp_e_the_toks:n 363, 3677, 3701
 - _exp_e_the_toks:wnn 363, 3676, 3701
 - _exp_e_the_toks_reg:N 3661
 - _exp_e_the_XeTeXinterchartoks: 3739
 - _exp_e_unexpanded:N 3600
 - _exp_e_unexpanded:nN 361, 3600
 - _exp_e_unexpanded:nn 3600
 - _exp_e_unexpanded:Nnn . . . 3578, 3600
 - _exp_eval_error_msg:w 3197
 - _exp_eval_register:N
 - 3188, 3194, 3197,
 - 3250, 3255, 3261, 3267, 3295, 3301,
 - 3313, 3314, 3321, 3393, 3398, 3421,
 - 3423, 3438, 3452, 3461, 3506, 3511
 - \l_exp_internal_tl
 - 317, 2135, 2139, 2140,
 - 3153, 3153, 3181, 3183, 3416, 3417
 - _exp_last_two_unbraced:nnN . 3485
 - \expandafter 13, 14, 21,
 - 38, 39, 42, 43, 48, 49, 66, 67, 90, 92,
 - 93, 94, 105, 130, 153, 161, 176, 192, 371
 - \expanded 920, 1741
 - \expandglyphsinfont 1015, 1624
 - \ExplFileDate 6
 - \ExplFileDescription 6
 - \ExplFileName 6
 - \ExplFileVersion 6
 - \explicitdiscretionary 921, 1742
 - \explicithyphenpenalty 919, 1739
 - \ExplSyntaxOff 3,
 - 6, 6, 107, 213, 246, 260, 271, 272, 309
 - \ExplSyntaxOn 3,
 - 6, 6, 107, 242, 271, 272, 309, 379, 502

F

false 201
 \fam 372
 \fi 17, 35, 41, 51, 70, 71,
 72, 97, 100, 102, 103, 104, 107, 108,
 137, 146, 159, 160, 177, 193, 211, 373
 fi commands:
 \fi: 20, 91, 91,
 92, 96, 102, 102, 151, 167, 229, 229,
 230, 327, 328, 330, 333, 335, 383,
 385, 414, 415, 418, 448, 458, 479,
 646, 672, 688, 718, 851, 2049, 2095,
 2183, 2313, 2330, 2341, 2342, 2390,
 2423, 2424, 2568, 2576, 2584, 2592,
 2612, 2617, 2630, 2638, 2646, 2648,
 2671, 2676, 2683, 2718, 2723, 2749,
 2750, 2758, 2764, 2777, 2778, 2786,
 2792, 2917, 2938, 2948, 2962, 3019,
 3080, 3144, 3202, 3205, 3212, 3213,
 3520, 3527, 3537, 3550, 3563, 3568,
 3571, 3572, 3573, 3574, 3582, 3630,
 3658, 3664, 3673, 3678, 3684, 3687,
 3691, 3699, 3709, 3718, 3724, 3785,
 3801, 3808, 3817, 3831, 3832, 3837,
 3838, 3839, 3857, 3858, 3859, 3860,
 3861, 3862, 3863, 3864, 3865, 3873,
 3893, 3895, 3925, 3926, 3927, 3995,
 4006, 4016, 4392, 4393, 4419, 4429,
 4440, 4455, 4463, 4478, 4489, 4493,
 4523, 4722, 4775, 4780, 4789, 4791,
 4818, 4839, 4855, 4864, 4873, 4879,
 4886, 4891, 4902, 4906, 4914, 4973,
 4985, 5034, 5040, 5041, 5215, 5222,
 5228, 5323, 5391, 5395, 5396, 5414,
 5467, 5480, 5522, 5528, 5529, 5540,
 5553, 5554, 5575, 5613, 5639, 5742,
 5750, 5774, 5788, 5796, 5807, 5817,
 6013, 6016, 6053, 6067, 6084, 6094,
 6148, 6153, 6418, 6451, 6473, 6474,
 6476, 6498, 6499, 6538, 6547, 6623,
 6631, 6658, 6666, 6672, 6701, 6741,
 6751, 6851, 7066, 7099, 7147, 7152,
 7268, 7334, 7375, 7385, 7441, 7473,
 7491, 7513, 7533, 7549, 7559, 7575,
 7585, 7675, 7677, 7679, 7681, 7683,
 7685, 7922, 7937, 7960, 7974, 8494,
 8497, 8498, 8499, 8500, 8505, 8506,
 8511, 8512, 8513, 8552, 8562, 8620,
 8622, 8651, 8656, 8661, 8666, 8673,
 8680, 8685, 8690, 8695, 8700, 8705,
 8710, 8715, 8720, 8742, 8753, 8754,
 8803, 8804, 8855, 8864, 8873, 8881,
 8915, 8953, 8967, 8976, 8986, 9306,
 10170, 10174, 10175, 10515, 10558,

10576, 10827, 10868, 10877, 10898,
 10908, 10912, 10919, 10927, 11422,
 11455, 11470, 11487, 11491, 11505,
 11508, 12007, 12031, 12045, 12057,
 12082, 12083, 12094, 12967, 12968,
 12999, 13007, 13069, 13211, 13220,
 13224, 13236, 13246, 13341, 13394,
 13397, 13398, 13403, 13417, 13455,
 13456, 13457, 13458, 13459, 13460,
 13461, 13462, 13463, 13464, 13465,
 13466, 13479, 13481, 13492, 13495,
 13509, 13514, 13518, 13672, 13763,
 13764, 13773, 13774, 13785, 13786,
 13787, 13798, 13799, 13800, 13807,
 13818, 13819, 13820, 13830, 13831,
 13835, 13836, 13844, 13847, 13848,
 13856, 13867, 13887, 13910, 13954,
 13973, 13974, 13983, 13989, 14009,
 14010, 14037, 14046, 14063, 14070,
 14078, 14079, 14182, 14183, 14184,
 14187, 14190, 14229, 14245, 14271,
 14272, 14279, 14287, 14316, 14317,
 14320, 14322, 14323, 14328, 14338,
 14341, 14343, 14348, 14379, 14392,
 14397, 14403, 14406, 14407, 14441,
 14442, 14469, 14470, 14483, 14486,
 14497, 14520, 14539, 14549, 14565,
 14579, 14585, 14589, 14594, 14600,
 14615, 14626, 14645, 14655, 14657,
 14663, 14684, 14712, 14735, 14768,
 14770, 14893, 14943, 14947, 14957,
 14958, 14977, 14995, 15016, 15019,
 15049, 15079, 15095, 15115, 15156,
 15168, 15181, 15183, 15203, 15204,
 15211, 15229, 15268, 15278, 15439,
 15450, 15479, 15480, 15481, 15488,
 15490, 15491, 15497, 15498, 15501,
 15528, 15536, 15537, 15545, 15546,
 15548, 15549, 15720, 15733, 15743,
 15744, 15749, 15750, 15751, 15752,
 15753, 15754, 15761, 15771, 15778,
 15789, 15790, 15801, 15818, 15863,
 15864, 15871, 15884, 15899, 15909,
 15923, 15953, 15962, 15996, 16018,
 16036, 16053, 16070, 16071, 16073,
 16074, 16079, 16094, 16127, 16156,
 16157, 16158, 16159, 16160, 16173,
 16217, 16290, 16357, 16359, 16360,
 16370, 16399, 16402, 16403, 16414,
 16434, 16497, 16498, 16499, 16511,
 16550, 16551, 16552, 16553, 16559,
 16562, 16564, 16574, 16592, 16607,
 16619, 16626, 16873, 16877, 16879,
 16883, 16890, 16891, 16901, 16902,

- 16905, 16997, 17067, 17078, 17090,
 17120, 17127, 17138, 17154, 17161,
 17222, 17279, 17289, 17291, 17301,
 17319, 17320, 17352, 17355, 17364,
 17366, 17368, 17382, 17396, 17420,
 17504, 17512, 17543, 17551, 17557,
 17568, 17571, 17574, 17583, 17593,
 17595, 17601, 17608, 17611, 17620,
 17628, 17649, 17682, 17683, 17710,
 17712, 17730, 17731, 17750, 17761,
 17770, 17773, 17817, 17832, 17847,
 17862, 17877, 17892, 17895, 17897,
 17914, 17959, 18266, 18302, 18303,
 18313, 18354, 18355, 18379, 18406,
 18407, 18410, 18412, 18413, 18418,
 18430, 18449, 18454, 18462, 18465,
 18497, 18507, 18508, 18518, 18540,
 18555, 18573, 18581, 18584, 18612,
 18620, 18636, 18708, 18726, 18762,
 18780, 18813, 18836, 18842, 18916,
 18917, 19053, 19054, 19063, 19070,
 19075, 19085, 19095, 19120, 19123,
 19136, 19168, 19176, 19177, 19205,
 19227, 19228, 19229, 19232, 19237,
 19257, 19258, 19308, 19309, 19349,
 19357, 19407, 19413, 19426, 19470,
 19482, 19483, 19538, 19569, 19611,
 19622, 19631, 19640, 19695, 19705,
 19715, 19829, 19831, 19885, 19889,
 19893, 19920, 19931, 19949, 19950,
 19951, 19958, 19974, 19980, 19983,
 19991, 20001, 20016, 20024, 20032,
 20043, 20059, 20079, 20092, 20114,
 20132, 20140, 20142, 20145, 20152,
 20157, 20234, 20235, 20385, 20392,
 20393, 20399, 20402, 20405, 20412,
 20413, 20416, 20420, 20421, 20431,
 20432, 20437, 20438, 20450, 20458,
 20467, 20468, 20496, 20666, 20677,
 20729, 20731, 20738, 20741, 20742,
 20746, 20750, 20751, 20752, 20753,
 20762, 20763, 20767, 20770, 20771,
 20772, 20808, 20811, 20832, 20835,
 20843, 20854, 20855, 20866, 20867,
 20875, 20887, 20888, 20898, 20899,
 20912, 20931, 20932, 20940, 20941,
 20992, 21002, 21028, 21042, 21046,
 21109, 21157, 21160, 21161, 21176,
 21179, 21202, 21269, 21270, 21275,
 21302, 21303, 21314, 21318, 21352,
 21357, 21365, 21400, 21407, 21412,
 21422, 21434, 21460, 21523, 21552,
 21591, 21598, 21609, 21682, 21699,
 21703, 21717, 21751, 21975, 22026,
 22042, 22066, 22090, 22099, 22159,
 22166, 22186, 22204, 22215, 22217,
 22247, 22250, 22275, 22402, 22431,
 22454, 22455, 22476, 22511, 22537,
 22610, 22671, 22683, 22746, 22760,
 22761, 22782, 22793, 22819, 22836,
 22886, 22888, 22903, 22905, 22926,
 23028, 23087, 23104, 23105, 23144,
 23145, 23149, 23150, 23172, 23177,
 23214, 23252, 23260, 23261, 23265,
 23266, 23668, 23670, 23676, 25344,
 25345, 25351, 25364, 25368, 25369,
 25385, 25450, 25869, 25885, 25886,
 26161, 26162, 26334, 26525, 26526,
 26529, 27515, 27522, 27527, 27555,
 27561, 27565, 27580, 27601, 27609,
 27624, 27625, 27626, 27636, 27643,
 27645, 27686, 27687, 27688, 27694
- file commands:
- \file_add_path:nN 29410
 - \g_file_curr_dir_str
 151, 11034, 11196, 11202, 11219
 - \g_file_curr_ext_str
 151, 11034, 11198, 11204, 11221
 - \g_file_curr_name_str . 151, 9430,
 11034, 11077, 11197, 11203, 11220
 - \g_file_current_name_str 29423
 - \g_file_current_name_tl 29422
 - \file_get_full_name:nN
 ... 152, 310, 1019, 10435, 11118,
 11159, 11172, 25799, 25810, 25824,
 25850, 25856, 26384, 26417, 29411
 - \file_get_md5five_hash:nN . 243, 25791
 - \file_get_size:nN 243, 25791
 - \file_get_timestamp:nN ... 243, 25791
 - \file_if_exist:nTF
 152, 152, 152, 11157,
 26270, 26272, 26276, 29413, 29415
 - \file_if_exist_input:n ... 243, 25848
 - \file_if_exist_input:nTF
 243, 25848, 29412, 29414
 - \file_input:n
 152, 152, 243, 244, 11170, 29413, 29415
 - \file_input_stop: 244, 25861
 - \file_list: 29416
 - \file_log_list: ... 152, 11262, 29417
 - \file_parse_full_name:nNNN
 152, 11135, 11200, 11223
 - \file_path_include:n
 243, 243, 243, 243, 29418
 - \file_path_remove:n 29420
 - \l_file_search_path_seq
 152, 152, 11085, 11122, 29419, 29421
 - \file_show_list: 152, 11262

file internal commands:

\l__file_base_name_str
 .. [11080](#), [11120](#), [11152](#), [11166](#), [11168](#)
 \l__file_dir_str
 [11082](#), [11136](#), [11201](#), [11202](#)
 \l__file_ext_str
 .. [11082](#), [11136](#), [11137](#), [11201](#), [11204](#)
 \l__file_full_name_str ... [11080](#),
 [11131](#), [11133](#), [11135](#), [11140](#), [11142](#),
 [11145](#), [11153](#), [11154](#), [11159](#), [11160](#),
 [11172](#), [11173](#), [11175](#), [25799](#), [25803](#),
 [25810](#), [25816](#), [25824](#), [25828](#), [25850](#),
 [25851](#), [25852](#), [25856](#), [25857](#), [25859](#)
 __file_get_details:nnN [25791](#)
 __file_get_full_name_search:nN .
 [11118](#)
 __file_input:n . [11170](#), [25852](#), [25859](#)
 __file_input_pop: [11170](#)
 __file_input_pop:nnn [11170](#)
 __file_input_push:n [11170](#)
 \g__file_internal_ior ... [11033](#),
 [11139](#), [11141](#), [11146](#), [11154](#), [11155](#)
 \l__file_internal_tl
 [11032](#), [11094](#), [11095](#), [11097](#),
 [11098](#), [11099](#), [11101](#), [11211](#), [11212](#)
 __file_list:N [11262](#)
 __file_list_aux:n [11262](#)
 __file_name_quote:nN . [11089](#), [11151](#)
 __file_name_quote_aux:n [11107](#), [11116](#)
 __file_name_sanitizе_aux:n .. [11089](#)
 \l__file_name_str
 [11082](#), [11136](#), [11201](#), [11203](#)
 __file_parse_full_name_auxi:w [11223](#)
 __file_parse_full_name_split:nNNTF
 [11223](#)
 \g__file_record_seq
 [579](#), [581](#), [581](#), [11072](#),
 [11180](#), [11185](#), [11274](#), [11287](#), [11288](#)
 \g__file_stack_seq
 [579](#), [11048](#), [11194](#), [11211](#)
 __file_tmp:w [11051](#), [11055](#), [11059](#),
 [11065](#), [11069](#), [11243](#), [11258](#), [11260](#)
 \l__file_tmp_seq
 [11086](#), [11266](#), [11270](#),
 [11274](#), [11275](#), [11277](#), [11284](#), [11289](#)
 \filedump [881](#)
 \filemoddate [882](#)
 \filesize [883](#)
 \finalhyphendemerits [374](#)
 \firstmark [375](#)
 \firstmarks [632](#), [1446](#)
 \firstvalidlanguage [922](#), [1744](#)

flag commands:

\flag_clear:n [93](#),
 [93](#), [7323](#), [7338](#), [21621](#), [23110](#), [23111](#)
 \flag_clear_new:n [93](#), [7337](#)
 \flag_height:n [94](#), [7346](#),
 [7377](#), [7392](#), [23120](#), [23121](#), [23127](#), [23128](#)
 \flag_if_exist:n [94](#)
 \flag_if_exist:nTF [94](#), [7338](#), [7354](#), [7363](#)
 \flag_if_exist_p:n [94](#), [7363](#)
 \flag_if_raised:n [94](#)
 \flag_if_raised:nTF . [94](#), [7368](#), [21629](#)
 \flag_if_raised_p:n [94](#), [7368](#)
 \flag_log:n [93](#), [7339](#)
 \flag_new:n [93](#),
 [93](#), [466](#), [7318](#), [7338](#), [13568](#), [13569](#),
 [13570](#), [13571](#), [21611](#), [23014](#), [23015](#)
 \flag_raise:n . [94](#), [7389](#), [23143](#), [23148](#)
 \flag_raise_if_clear:n
 . [244](#), [13602](#), [13611](#), [13619](#), [13636](#),
 [13645](#), [13676](#), [21647](#), [21669](#), [25863](#)
 \flag_show:n [93](#), [7339](#)

flag fp commands:

flag_fp_division_by_zero . [192](#), [13568](#)
 flag_fp_invalid_operation [192](#), [13568](#)
 flag_fp_overflow [192](#), [13568](#)
 flag_fp_underflow [192](#), [13568](#)

flag internal commands:

__flag_chk_exist:n
 [7349](#), [7368](#), [7377](#), [25863](#)
 __flag_clear:wn [7323](#)
 __flag_height_end:wn [7377](#)
 __flag_height_loop:wn [7377](#)
 __flag_show:Nn [7339](#)
 \floatingpenalty [376](#)
 floor [197](#)
 \fmtname [152](#)
 \font [377](#)
 \fontchardp [633](#), [1447](#)
 \fontcharht [634](#), [1448](#)
 \fontcharic [635](#), [1449](#)
 \fontcharwd [636](#), [1450](#)
 \fontdimen [378](#)
 \fontid [923](#), [1745](#)
 \fontname [379](#)
 \forcecjktoken [1253](#), [2035](#)
 \formatname [924](#), [1746](#)

fp commands:

\c_e_fp [191](#), [193](#), [15408](#)
 \fp_abs:n [196](#), [201](#), [821](#), [18936](#), [24084](#),
 [24161](#), [24163](#), [24165](#), [25743](#), [25745](#)
 \fp_add:Nn [185](#), [821](#), [1019](#), [15385](#)
 \fp_compare:nNnTF [187](#),
 [188](#), [188](#), [189](#), [189](#), [15441](#), [15582](#),
 [15588](#), [15593](#), [15601](#), [15662](#), [15668](#),

- 23952, 23954, 23959, 24180, 24195,
 24204, 24601, 25725, 27934, 28321,
 28327, 28533, 28909, 28922, 28967
 \fp_compare:nTF
 188, 189, 189, 189, 189,
 195, 15425, 15554, 15560, 15565, 15573
 \fp_compare_p:n 188, 15425
 \fp_compare_p:nNn 187, 15441
 \fp_const:Nn
 184, 15362, 15408, 15409, 15410, 15411
 \fp_do_until:nn 189, 15551
 \fp_do_until:nNnn 188, 15579
 \fp_do_while:nn 189, 15551
 \fp_do_while:nNnn 188, 15579
 \fp_eval:n 185, 188,
 195, 195, 195, 195, 195, 196, 196,
 196, 196, 196, 196, 196, 197, 197,
 197, 198, 198, 198, 199, 199, 199,
 200, 200, 201, 201, 242, 242, 708,
 18933, 26185, 26203, 27769, 27770,
 27774, 27778, 27839, 27840, 27841,
 27842, 27851, 27859, 27860, 27861,
 27927, 27936, 27949, 27950, 28116,
 28133, 28134, 28143, 28144, 28148,
 28150, 28154, 28159, 28175, 28176,
 28315, 28332, 28347, 28349, 28526,
 28535, 28546, 28547, 28837, 28854,
 28855, 28863, 28864, 28869, 28871,
 28875, 28880, 28894, 28895, 28911,
 28916, 28917, 28924, 28934, 28935,
 28936, 28937, 28946, 28947, 28948,
 28949, 28958, 28959, 28960, 28961,
 28982, 28983, 29065, 29080, 29081,
 29286, 29304, 29305, 29306, 29315,
 29326, 29327, 29328, 29355, 29356
 \fp_format:nn 201
 \fp_gadd:Nn 185, 15385
 .fp_gset:N 171, 12488
 \fp_gset:Nn .. 185, 15362, 15386, 15388
 \fp_gset_eq:NN 185, 15371, 15376
 \fp_gsub:Nn 185, 15385
 \fp_gzero:N 184, 15375, 15382
 \fp_gzero_new:N 185, 15379
 \fp_if_exist:NnTF
 187, 15380, 15382, 15423
 \fp_if_exist_p:N 187, 15423
 \fp_if_nan:nTF 202
 \fp_log:N 192, 15395
 \fp_log:n 192, 15404
 \fp_max:nn 201, 18938
 \fp_min:nn 201, 18938
 \fp_new:N 184, 185,
 15359, 15380, 15382, 15412, 15413,
 15414, 15415, 23924, 23925, 23926,
 24046, 24047, 24248, 24249, 25550,
 25551, 25702, 25703, 28340, 28341
 .fp_set:N 171, 12488
 \fp_set:Nn 185, 15362, 15385,
 15387, 23940, 23941, 23942, 24053,
 24055, 24091, 24106, 24121, 24133,
 24135, 24148, 24149, 24178, 24179,
 24597, 24599, 25560, 25561, 25708,
 25710, 25737, 25738, 28320, 28323
 \fp_set_eq:NN .. 185, 15371, 15375,
 24096, 24111, 24123, 24181, 24182
 \fp_show:N 192, 15395
 \fp_show:n 192, 15404
 \fp_sign:n 242, 25788
 \fp_step_function:nnnN
 190, 15607, 15699
 \fp_step_inline:nnnn 190, 15677
 \fp_step_variable:nnnNn .. 190, 15677
 \fp_sub:Nn 185, 15385
 \fp_to_decimal:N
 186, 187, 13561, 18739, 18770, 18933
 \fp_to_decimal:n
 .. 185, 186, 186, 186, 187, 18739,
 18935, 18937, 18939, 18941, 25789
 \fp_to_dim:N 186, 819, 18862
 \fp_to_dim:n 186, 191,
 18862, 23984, 23995, 24084, 24607,
 24638, 25639, 25647, 25753, 25755
 \fp_to_int:N 186, 18878
 \fp_to_int:n 186, 18878
 \fp_to_scientific:N
 186, 18685, 18716, 18723
 \fp_to_scientific:n . 186, 186, 18685
 \fp_to_tl:N
 186, 243, 13562, 15402, 18818
 \fp_to_tl:n 186,
 13171, 13601, 13610, 13635, 13644,
 13673, 15241, 15256, 15405, 15407,
 15634, 15635, 15654, 15665, 18818
 \fp_trap:nn 192, 192,
 651, 13572, 13687, 13688, 13689, 13690
 \fp_until_do:nn 189, 15551
 \fp_until_do:nNnn 189, 15579
 \fp_use:N
 187, 243, 18933, 28326, 28330, 28335
 \fp_while_do:nn 189, 15551
 \fp_while_do:nNnn 189, 15579
 \fp_zero:N 184, 185, 15375, 15380, 28322
 \fp_zero_new:N 185, 15379
 \c_inf_fp
 .. 191, 200, 13182, 14778, 16170,
 16252, 16590, 17348, 17371, 17573,
 17576, 17580, 17604, 17899, 19424

- \c_nan_fp [200](#), [654](#), [678](#),
[13182](#), [13612](#), [13620](#), [13692](#), [13898](#),
[13917](#), [13923](#), [14104](#), [14112](#), [14121](#),
[14200](#), [14257](#), [14296](#), [14690](#), [14767](#),
[14779](#), [15243](#), [15258](#), [15658](#), [17547](#),
[18982](#), [19028](#), [19340](#), [19396](#), [19422](#)
- \c_one_fp
[190](#), [705](#), [806](#), [14782](#), [15186](#), [15207](#),
[15408](#), [15758](#), [16611](#), [17342](#), [17542](#),
[17594](#), [17823](#), [17853](#), [18402](#), [19044](#)
- \c_pi_fp .. [191](#), [200](#), [687](#), [14780](#), [15410](#)
- \g_tmpa_fp [191](#), [15412](#)
- \l_tmpa_fp [191](#), [15412](#)
- \g_tmpb_fp [191](#), [15412](#)
- \l_tmpb_fp [191](#), [15412](#)
- \c_zero_fp
.. [190](#), [708](#), [722](#), [832](#), [13182](#), [13229](#),
[14783](#), [15198](#), [15210](#), [15360](#), [15375](#),
[15376](#), [15760](#), [15763](#), [15999](#), [16166](#),
[17351](#), [17372](#), [17570](#), [17607](#), [18617](#),
[18723](#), [18908](#), [19421](#), [23952](#), [23954](#),
[23959](#), [24195](#), [24204](#), [25725](#), [27934](#),
[28321](#), [28327](#), [28533](#), [28909](#), [28922](#)
- fp internal commands:
 - __fp_&o:ww [710](#), [718](#), [15764](#)
 - __fp_&tuple_o:ww [15764](#)
 - __fp_*_o:ww [16131](#)
 - __fp*_tuple_o:ww [16637](#)
 - __fp+_o:ww [721](#), [721](#), [750](#), [15852](#)
 - __fp-_o:ww [721](#), [721](#), [15847](#)
 - __fp/_o:ww [730](#), [771](#), [16243](#)
 - __fp^_o:ww [17538](#)
 - __fp_acos_o:w [810](#), [813](#), [18558](#)
 - __fp_acot_o:Nw . [17798](#), [17800](#), [18390](#)
 - __fp_acotii_o:Nww [18400](#), [18403](#)
 - __fp_acotii_o:ww [806](#)
 - __fp_acsc_normal_o:NnwNnw
..... [812](#), [18616](#), [18631](#), [18639](#)
 - __fp_acsc_o:w [18610](#)
 - __fp_add:NNNn [15385](#)
 - __fp_add_big_i:wNww [723](#)
 - __fp_add_big_i_o:wNww
..... [721](#), [724](#), [15919](#), [15926](#)
 - __fp_add_big_ii:wNww [723](#)
 - __fp_add_big_ii_o:wNww [15922](#), [15926](#)
 - __fp_add_inf_o:Nww ... [15868](#), [15888](#)
 - __fp_add_normal_o:Nww
..... [723](#), [15867](#), [15903](#)
 - __fp_add_npos_o:NnwNnw
..... [723](#), [15906](#), [15912](#)
 - __fp_add_return_ii_o:Nww
..... [15870](#), [15876](#), [15881](#)
 - __fp_add_significand_carry_-
o:wwwNN [725](#), [15959](#), [15974](#)
 - __fp_add_significand_no_carry_-
o:wwwNN [725](#), [15961](#), [15964](#)
 - __fp_add_significand_o:NnnwnnnnN
..... [724](#), [724](#), [15929](#), [15937](#), [15942](#)
 - __fp_add_significand_pack:NNNNNN
..... [15942](#)
 - __fp_add_significand_test_o:N [15942](#)
 - __fp_add_zeros_o:Nww . [15866](#), [15878](#)
 - __fp_and_return:wNw [15764](#)
 - __fp_array_bounds:NNnTF
..... [19297](#), [19327](#), [19394](#)
 - __fp_array_bounds_error:NNn . [19297](#)
 - __fp_array_count:n [13278](#),
[13882](#), [15508](#), [15509](#), [16650](#), [18658](#)
 - __fp_array_gset:NNNww [19316](#)
 - __fp_array_gset:w [19316](#)
 - __fp_array_gset_normal:w [19316](#)
 - __fp_array_gset_recover:Nw .. [19316](#)
 - __fp_array_gset_special:nnNNN ..
..... [19316](#), [19372](#)
 - __fp_array_gzero:N [832](#)
 - __fp_array_if_all_fp:nTF
..... [13290](#), [15236](#)
 - __fp_array_if_all_fp_loop:w . [13290](#)
 - \g__fp_array_int
..... [19264](#), [19271](#), [19273](#), [19284](#)
 - __fp_array_item:N [19378](#)
 - __fp_array_item:NNNnN [19378](#)
 - __fp_array_item:NwN [19378](#)
 - __fp_array_item:w [19378](#)
 - __fp_array_item_normal:w [19378](#)
 - __fp_array_item_special:w ... [19378](#)
 - \l__fp_array_loop_int
..... [19265](#), [19368](#), [19371](#), [19374](#)
 - __fp_array_new:nnNN [19266](#)
 - __fp_array_new:nnNNN . [19275](#), [19278](#)
 - __fp_array_to_clist:n
..... [13943](#), [18942](#), [19068](#)
 - __fp_array_to_clist_loop:Nw . [18942](#)
 - __fp_asec_o:w [18623](#)
 - __fp_asin_auxi_o:NnNww
..... [811](#), [813](#), [18588](#), [18591](#), [18650](#)
 - __fp_asin_isqrt:wn [18591](#)
 - __fp_asin_normal_o:NnwNnnnw ...
..... [18549](#), [18565](#), [18576](#)
 - __fp_asin_o:w [18543](#)
 - __fp_atan_auxi:ww . [808](#), [18468](#), [18482](#)
 - __fp_atan_auxii:w [18482](#)
 - __fp_atan_combine_aux:ww [18509](#)
 - __fp_atan_combine_o:NwwwwN ...
..... [806](#), [807](#), [18427](#), [18444](#), [18509](#)
 - __fp_atan_default:w . [705](#), [806](#), [18390](#)
 - __fp_atan_div:wNwnw
..... [807](#), [18455](#), [18457](#)

- __fp_atan_inf_o:NNNw 806, 18415,
18416, 18417, 18425, 18561, 18634
- __fp_atan_near:wwn 18457
- __fp_atan_near_aux:wwn 18457
- __fp_atan_normal_o:NNnwNnw
..... 806, 18419, 18435
- __fp_atan_o:Nw . 17802, 17804, 18390
- __fp_atan_Taylor_break:w 18493
- __fp_atan_Taylor_loop:www
..... 808, 18488, 18493
- __fp_atan_test_o:NwwNwN
..... 812, 18438, 18442, 18598
- __fp_atanii_o:Nww 18394, 18403
- __fp_basics_pack_high:NNNNNw ...
.. 725, 741, 13388, 15967, 16119,
16222, 16234, 16376, 16569, 17095
- __fp_basics_pack_high_carry:w ..
..... 643, 13388
- __fp_basics_pack_low:NNNNNw ...
..... 731, 741,
13388, 15969, 16121, 16224, 16236,
16378, 16518, 16520, 16571, 17097
- __fp_basics_pack_weird_high:NNNNNNNw
..... 202, 13399, 15978, 16387
- __fp_basics_pack_weird_low:NNNNw
..... 202, 13399, 15980, 16389
- \c__fp_big_leading_shift_int ...
.. 13374, 16448, 16783, 16793, 16803
- \c__fp_big_middle_shift_int
.... 13374, 16451, 16454, 16457,
16460, 16463, 16466, 16470, 16785,
16795, 16805, 16815, 16818, 16821
- \c__fp_big_trailing_shift_int ...
..... 13374, 16474, 16828
- \c__fp_Bigg_leading_shift_int ...
..... 13379, 16297, 16315
- \c__fp_Bigg_middle_shift_int ...
.. 13379, 16300, 16303, 16318, 16321
- \c__fp_Bigg_trailing_shift_int ..
..... 13379, 16306, 16324
- __fp_binary_rev_type_o:Nww
..... 14901, 16640, 16642
- __fp_binary_type_o:Nww
..... 14901, 16638, 16651
- \c__fp_block_int 13187, 17047
- __fp_case_return:nw
..... 646, 13456, 13486, 13489,
13494, 14003, 17307, 18415, 18416,
18417, 18710, 18764, 18838, 18840,
18841, 18908, 19345, 19347, 19348
- __fp_case_return_i_o:ww . 13463,
15869, 15883, 15892, 16164, 18406
- __fp_case_return_ii_o:ww
.. 13463, 16165, 17592, 17610, 18407
- __fp_case_return_o:Nw 646,
647, 13457, 16590, 17342, 17347,
17350, 17542, 17547, 17570, 17573,
17576, 17823, 17853, 18617, 18619
- __fp_case_return_o:Nww
..... 13461, 16166, 16167,
16170, 16171, 17594, 17603, 17606
- __fp_case_return_same_o:w
..... 646, 647, 13459, 16399,
16403, 16591, 16603, 16606, 17126,
17354, 17567, 17808, 17816, 17831,
17846, 17861, 17868, 17876, 17891,
18546, 18554, 18572, 18618, 18635
- __fp_case_use:nw
.. 646, 13455, 15894, 16162, 16163,
16168, 16169, 16251, 16254, 16401,
16587, 17119, 17122, 17578, 17809,
17814, 17824, 17829, 17839, 17844,
17854, 17859, 17869, 17874, 17884,
17889, 18548, 18551, 18561, 18563,
18569, 18613, 18615, 18626, 18629,
18634, 18713, 18720, 18767, 18774
- __fp_change_func_type:NNN
.... 13318, 14694, 16633, 18695,
18749, 18826, 18872, 18887, 19329
- __fp_change_func_type_aux:w . 13318
- __fp_change_func_type_chk:NNN 13318
- __fp_chk:w
.... 633, 634, 635, 687, 721, 723,
723, 725, 731, 734, 13172, 13182,
13183, 13184, 13185, 13186, 13196,
13201, 13203, 13204, 13225, 13228,
13230, 13240, 13253, 13272, 13467,
13483, 13668, 13673, 13900, 13946,
13955, 13957, 14792, 15475, 15476,
15638, 15654, 15658, 15722, 15723,
15726, 15737, 15738, 15746, 15747,
15755, 15767, 15770, 15774, 15777,
15853, 15873, 15874, 15876, 15877,
15878, 15886, 15889, 15900, 15901,
15903, 15912, 15988, 16140, 16174,
16175, 16178, 16259, 16397, 16405,
16407, 16584, 16593, 16595, 16600,
16608, 16610, 16612, 16616, 17116,
17128, 17130, 17339, 17356, 17358,
17539, 17558, 17560, 17561, 17564,
17581, 17584, 17587, 17612, 17613,
17615, 17631, 17720, 17733, 17735,
17739, 17743, 17805, 17818, 17820,
17833, 17835, 17848, 17850, 17863,
17865, 17878, 17880, 17893, 17903,
18404, 18420, 18421, 18425, 18436,
18543, 18556, 18558, 18574, 18577,
18587, 18610, 18621, 18623, 18637,

- 18639, 18644, 18706, 18727, 18730,
18760, 18781, 18784, 18834, 18850,
18853, 18929, 18930, 19045, 19047,
19079, 19342, 19350, 19353, 19429
- __fp_compare:wNNNNw [15126](#)
- __fp_compare_aux:wn [15441](#)
- __fp_compare_back:ww
..... [827](#), [15457](#), [15736](#), [19063](#)
- __fp_compare_back_any:ww .. [711](#),
[711](#), [712](#), [15201](#), [15454](#), [15457](#), [15525](#)
- __fp_compare_back_tuple:ww .. [15502](#)
- __fp_compare_nan:w [711](#), [15457](#)
- __fp_compare_npos:nwnw [710](#),
[711](#), [713](#), [15485](#), [15531](#), [15990](#), [16897](#)
- __fp_compare_return:w [15425](#)
- __fp_compare_significand:nnnnnnnn
..... [15531](#)
- __fp_cos_o:w [17820](#)
- __fp_cot_o:w [791](#), [17880](#)
- __fp_cot_zero_o:Nnw
..... [790](#), [791](#), [17838](#), [17880](#)
- __fp_csc_o:w [17835](#)
- __fp_decimate:nNnnnn
..... [644](#), [648](#), [787](#), [13409](#),
[13474](#), [13501](#), [13959](#), [15928](#), [15936](#),
[16015](#), [17385](#), [17389](#), [17758](#), [18790](#)
- __fp_decimate:Nnnnn [13421](#)
- __fp_decimate_auxi:Nnnnn [645](#), [13425](#)
- __fp_decimate_auxii:Nnnnn .. [13425](#)
- __fp_decimate_auxiii:Nnnnn .. [13425](#)
- __fp_decimate_auxiv:Nnnnn .. [13425](#)
- __fp_decimate_auxix:Nnnnn .. [13425](#)
- __fp_decimate_auxv:Nnnnn [13425](#)
- __fp_decimate_auxvi:Nnnnn [13425](#)
- __fp_decimate_auxvii:Nnnnn .. [13425](#)
- __fp_decimate_auxviii:Nnnnn . [13425](#)
- __fp_decimate_auxxi:Nnnnn [13425](#)
- __fp_decimate_auxxii:Nnnnn .. [13425](#)
- __fp_decimate_auxxiii:Nnnnn . [13425](#)
- __fp_decimate_auxxiv:Nnnnn .. [13425](#)
- __fp_decimate_auxxv:Nnnnn [13425](#)
- __fp_decimate_auxxvi:Nnnnn .. [13425](#)
- __fp_decimate_pack:nnnnnnnnnw .
..... [645](#), [13432](#), [13451](#)
- __fp_decimate_pack:nnnnnnw
..... [13452](#), [13453](#)
- __fp_decimate_tiny:Nnnnn [13421](#)
- __fp_div_npos_o:Nww
..... [733](#), [734](#), [16248](#), [16258](#)
- __fp_div_significand_calc:wnnnnnnn
..... [737](#),
[737](#), [16275](#), [16284](#), [16332](#), [17199](#), [17206](#)
- __fp_div_significand_calc_-
i:wnnnnnnn [16284](#)
- __fp_div_significand_calc_-
ii:wnnnnnnn [16284](#)
- __fp_div_significand_i_o:wnnw ..
..... [734](#), [737](#), [16265](#), [16271](#)
- __fp_div_significand_ii:wnw ...
..... [739](#), [16279](#), [16280](#), [16281](#), [16328](#)
- __fp_div_significand_iii:wnnnnn
..... [739](#), [16282](#), [16335](#)
- __fp_div_significand_iv:wnnnnnnn
..... [740](#), [16338](#), [16343](#)
- __fp_div_significand_large_-
o:wnnnnnwN [742](#), [16369](#), [16383](#)
- __fp_div_significand_pack:NNN ..
..... [741](#),
[773](#), [16330](#), [16363](#), [17186](#), [17204](#), [17212](#)
- __fp_div_significand_small_-
o:wnnnnnwN [741](#), [16367](#), [16373](#)
- __fp_div_significand_test_o:w ..
..... [741](#), [741](#), [16273](#), [16364](#)
- __fp_div_significand_v:NN
..... [16348](#), [16350](#), [16353](#)
- __fp_div_significand_v:NNw .. [16343](#)
- __fp_div_significand_vi:Nw
..... [740](#), [16343](#)
- __fp_division_by_zero_o:Nnw ...
..... [651](#), [13632](#),
[13680](#), [16588](#), [17123](#), [17899](#), [17900](#)
- __fp_division_by_zero_o:NNww ...
[651](#), [13640](#), [13680](#), [16252](#), [16255](#), [17580](#)
- \c__fp_empty_tuple_fp
..... [13273](#), [14098](#), [14753](#), [14763](#)
- __fp_ep_compare:www .. [16892](#), [18451](#)
- __fp_ep_compare_aux:www [16892](#)
- __fp_ep_div:wwwwn
..... [803](#), [16922](#), [17033](#),
[18380](#), [18467](#), [18471](#), [18480](#), [18647](#)
- __fp_ep_div_eps_pack:NNNNw .. [16952](#)
- __fp_ep_div_epsilon:wnNNNNn [763](#)
- __fp_ep_div_epsilon:wnNNNNNn
..... [16949](#), [16952](#)
- __fp_ep_div_epsilonii:wnNNNNNn . [16952](#)
- __fp_ep_div_esti:wwwwn
..... [763](#), [16928](#), [16931](#)
- __fp_ep_div_estii:wnnnwn .. [16931](#)
- __fp_ep_div_estiii:NNNNwnwn . [16931](#)
- __fp_ep_inv_to_float_o:wN [792](#)
- __fp_ep_inv_to_float_o:wwN
..... [802](#), [17029](#), [17037](#), [17842](#), [17857](#)
- __fp_ep_isqrt:wnw [16975](#), [18608](#)
- __fp_ep_isqrt_aux:wnw [16975](#)
- __fp_ep_isqrt_auxi:wnw [16978](#), [16980](#)
- __fp_ep_isqrt_auxii:wnnnwn . [16975](#)

__fp_ep_isqrt_epsilon:wN [766](#), [17012](#), [17015](#)
 __fp_ep_isqrt_epsilon:wwN [17015](#)
 __fp_ep_isqrt_esti:wwwnnwn [16990](#), [16993](#)
 __fp_ep_isqrt_estii:wwwnnwn . [16993](#)
 __fp_ep_isqrt_estiii:NNNNNwwnn . [16993](#)
 __fp_ep_mul:wwwwn [16907](#), [18337](#), [18367](#), [18595](#), [18606](#)
 __fp_ep_mul_raw:wwwN [16907](#), [17921](#), [18287](#)
 __fp_ep_to_ep:wwN . [16858](#), [16909](#), [16912](#), [16924](#), [16927](#), [16977](#), [18596](#)
 __fp_ep_to_ep_end:www [16858](#)
 __fp_ep_to_ep_loop:N [801](#), [16858](#), [18288](#)
 __fp_ep_to_ep_zero:ww [16858](#)
 __fp_ep_to_fixed:wn [16840](#), [17918](#), [18474](#), [18483](#), [18593](#), [19088](#)
 __fp_ep_to_fixed_auxi:www ... [16840](#)
 __fp_ep_to_fixed_auxii:nnnnnnnnwn [16840](#)
 __fp_ep_to_float_o:wN [792](#)
 __fp_ep_to_float_o:wwN [789](#), [802](#), [17029](#), [17041](#), [17812](#), [17827](#), [18386](#)
 __fp_error:nnnn [13601](#), [13609](#), [13618](#), [13635](#), [13643](#), [13671](#), [13694](#), [13893](#), [13895](#), [13916](#), [13921](#), [14689](#), [15239](#), [15254](#), [15634](#), [15653](#), [15664](#), [18701](#), [18755](#), [18829](#), [19339](#)
 __fp_exp_after_?_f:nw [641](#), [674](#), [14082](#)
 __fp_exp_after_any_f:Nnw [13343](#)
 __fp_exp_after_any_f:nw [641](#), [13343](#), [13369](#), [14084](#), [14858](#)
 __fp_exp_after_array_f:w [641](#), [13354](#), [14743](#), [15804](#), [15815](#), [15825](#), [15833](#)
 __fp_exp_after_f:nw [637](#), [674](#), [13230](#), [13348](#), [14791](#), [14929](#)
 __fp_exp_after_mark_f:nw [674](#), [14082](#)
 __fp_exp_after_normal:nnnw [13233](#), [13243](#), [13260](#)
 __fp_exp_after_normal:Nwwwww ... [13262](#), [13270](#)
 __fp_exp_after_o:w .. [637](#), [13230](#), [13460](#), [13464](#), [13466](#), [13953](#), [13997](#), [14015](#), [15221](#), [15754](#), [15772](#), [15781](#), [15790](#), [15877](#), [16614](#), [17732](#), [17737](#)
 __fp_exp_after_special:nnnw ... [638](#), [13235](#), [13245](#), [13250](#)
 __fp_exp_after_stop_f:nw [13343](#)
 __fp_exp_after_tuple_f:nw [13354](#), [15030](#)
 __fp_exp_after_tuple_o:w [13354](#), [15779](#), [15782](#), [15785](#), [15787](#)
 \c__fp_exp_intarray [17432](#), [17518](#), [17525](#), [17528](#), [17530](#)
 __fp_exp_intarray:w [17489](#)
 __fp_exp_intarray_aux:w [17489](#)
 __fp_exp_large:NwN [780](#), [17489](#), [17716](#)
 __fp_exp_large_after:wn [780](#), [17489](#)
 __fp_exp_normal_o:w .. [17344](#), [17358](#)
 __fp_exp_o:w [17104](#), [17339](#)
 __fp_exp_overflow:NN [17358](#)
 __fp_exp_pos_large:NnnNwn [17390](#), [17489](#)
 __fp_exp_pos_o:NNwnw [17361](#), [17363](#), [17366](#)
 __fp_exp_pos_o:Nnnwn [17358](#)
 __fp_exp_Taylor:Nnnwn [17386](#), [17405](#), [17535](#)
 __fp_exp_Taylor_break:Nww ... [17405](#)
 __fp_exp_Taylor_ii:ww . [17411](#), [17414](#)
 __fp_exp_Taylor_loop:www [17405](#)
 __fp_expand:n [822](#), [13520](#), [18946](#)
 __fp_expand_loop:nnwN [13520](#)
 __fp_exponent:w [13204](#)
 \c__fp_five_int [13755](#), [13779](#), [13792](#), [13805](#), [13812](#), [13865](#)
 __fp_fixed(<calculation>):wnn .. [751](#)
 __fp_fixed_add:nnNnnwn [16733](#)
 __fp_fixed_add:Nnnnnwnn [16733](#)
 __fp_fixed_add:wnn [752](#), [755](#), [16733](#), [16973](#), [17281](#), [17289](#), [17300](#), [17318](#), [18479](#), [18539](#), [19103](#)
 __fp_fixed_add_after:NNNNNwn . [16733](#)
 __fp_fixed_add_one:wN [752](#), [16665](#), [16966](#), [17422](#), [17431](#), [18605](#), [19094](#)
 __fp_fixed_add_pack:NNNNNwn . [16733](#)
 __fp_fixed_continue:wn [16664](#), [16910](#), [16915](#), [16925](#), [17500](#), [17691](#), [17956](#), [18325](#), [18597](#), [18606](#), [19086](#), [19098](#)
 __fp_fixed_div_int:wnN [16702](#)
 __fp_fixed_div_int:wwN [753](#), [16702](#), [17280](#), [17421](#), [18498](#)
 __fp_fixed_div_int_after:Nw ... [754](#), [16702](#)
 __fp_fixed_div_int_auxi:wnn . [16702](#)
 __fp_fixed_div_int_auxii:wnn ... [754](#), [16702](#)
 __fp_fixed_div_int_pack:Nw [754](#), [16702](#)
 __fp_fixed_div_myriad:wn [16670](#), [16970](#)
 __fp_fixed_inv_to_float_o:wN ... [17036](#), [17363](#), [17627](#)

- __fp_fixed_mul:nnnnnnnw [16753](#)
- __fp_fixed_mul:wnn
 - .. [752](#), [753](#), [755](#), [800](#), [802](#), [16753](#),
 - [16919](#), [16950](#), [16965](#), [16967](#), [16971](#),
 - [17024](#), [17027](#), [17040](#), [17282](#), [17292](#),
 - [17332](#), [17423](#), [17521](#), [17536](#), [17637](#),
 - [18294](#), [18348](#), [18486](#), [18519](#), [18521](#)
- __fp_fixed_mul_add:nnnnwnnnn ...
 - [758](#), [16822](#), [16824](#)
- __fp_fixed_mul_add:nnnnwnnwN ...
 - [759](#), [16829](#), [16835](#)
- __fp_fixed_mul_add:Nwnnnwnnn ...
 - [758](#), [16786](#), [16796](#), [16807](#), [16811](#)
- __fp_fixed_mul_add:wnwn
 - [757](#), [16780](#), [19108](#)
- __fp_fixed_mul_after:wnn
 - [756](#), [16672](#), [16678](#), [16681](#),
 - [16755](#), [16782](#), [16792](#), [16802](#), [17654](#)
- __fp_fixed_mul_one_minus_-
 - mul:wnn [16780](#)
- __fp_fixed_mul_short:wnn
 - [753](#), [16679](#),
 - [16948](#), [16969](#), [17011](#), [17013](#), [18532](#)
- __fp_fixed_mul_sub_back:wnwn ...
 - [757](#), [16780](#),
 - [17025](#), [18315](#), [18317](#), [18318](#), [18319](#),
 - [18320](#), [18321](#), [18322](#), [18323](#), [18324](#),
 - [18328](#), [18330](#), [18331](#), [18332](#), [18333](#),
 - [18334](#), [18335](#), [18336](#), [18361](#), [18363](#),
 - [18364](#), [18365](#), [18366](#), [18369](#), [18371](#),
 - [18372](#), [18373](#), [18374](#), [18499](#), [18507](#)
- __fp_fixed_one_minus_mul:wnn ...
 - [757](#), [758](#), [16800](#)
- __fp_fixed_sub:wnn [16733](#), [17017](#),
 - [17298](#), [17314](#), [17326](#), [17960](#), [18480](#),
 - [18537](#), [18603](#), [19096](#), [19105](#), [19137](#)
- __fp_fixed_to_float_o:Nw
 - [17043](#), [17307](#)
- __fp_fixed_to_float_o:wN
 - [752](#), [767](#),
 - [809](#), [17030](#), [17043](#), [17327](#), [17337](#),
 - [17361](#), [17623](#), [18527](#), [19036](#), [19142](#)
- __fp_fixed_to_float_pack:ww ...
 - [17076](#), [17086](#)
- __fp_fixed_to_float_rad_o:wN ...
 - [17038](#), [18527](#)
- __fp_fixed_to_float_round_-
 - up:wnnnnw [17089](#), [17093](#)
- __fp_fixed_to_float_zero:w
 - [17072](#), [17081](#)
- __fp_fixed_to_loop:N
 - [17049](#), [17059](#), [17063](#)
- __fp_fixed_to_loop_end:w
 - [17065](#), [17069](#)
- __fp_from_dim:wNNnnnnnn [18897](#)
- __fp_from_dim:wnnnnwNn [18925](#), [18926](#)
- __fp_from_dim:wnnnnwNw [18897](#)
- __fp_from_dim:wNw [18897](#)
- __fp_from_dim_test:ww
 - [820](#), [14176](#), [14213](#), [14810](#), [18897](#)
- __fp_func_to_name:N
 - [13548](#), [14689](#), [14698](#)
- __fp_func_to_name_aux:w [13548](#)
- \c__fp_half_prec_int
 - [13187](#), [14417](#), [14449](#)
- __fp_if_type_fp:NTwFw [639](#),
 - [705](#), [13289](#), [13297](#), [13304](#), [13320](#),
 - [13347](#), [15248](#), [15262](#), [15433](#), [15459](#),
 - [15460](#), [15627](#), [15628](#), [15629](#), [15795](#)
- __fp_inf_fp:N [13200](#), [13656](#)
- __fp_int:wTF [13467](#), [19047](#)
- __fp_int_eval:w [642](#), [657](#),
 - [658](#), [659](#), [672](#), [688](#), [723](#), [731](#), [731](#),
 - [732](#), [735](#), [739](#), [767](#), [13157](#), [13214](#),
 - [13282](#), [13413](#), [13416](#), [13829](#), [13833](#),
 - [13845](#), [13846](#), [13882](#), [13965](#), [13969](#),
 - [14008](#), [14223](#), [14228](#), [14270](#), [14359](#),
 - [14370](#), [14419](#), [14450](#), [14456](#), [14457](#),
 - [14503](#), [14513](#), [14515](#), [14531](#), [14533](#),
 - [14556](#), [14558](#), [14724](#), [14946](#), [15161](#),
 - [15446](#), [15916](#), [15924](#), [15945](#), [15947](#),
 - [15968](#), [15970](#), [15979](#), [15981](#), [16010](#),
 - [16016](#), [16026](#), [16028](#), [16102](#), [16104](#),
 - [16120](#), [16122](#), [16126](#), [16142](#), [16182](#),
 - [16190](#), [16192](#), [16194](#), [16196](#), [16199](#),
 - [16202](#), [16204](#), [16223](#), [16225](#), [16235](#),
 - [16237](#), [16263](#), [16266](#), [16274](#), [16276](#),
 - [16297](#), [16300](#), [16303](#), [16306](#), [16315](#),
 - [16318](#), [16321](#), [16324](#), [16331](#), [16333](#),
 - [16339](#), [16347](#), [16349](#), [16351](#), [16357](#),
 - [16377](#), [16379](#), [16388](#), [16390](#), [16411](#),
 - [16432](#), [16436](#), [16448](#), [16451](#), [16454](#),
 - [16457](#), [16460](#), [16463](#), [16466](#), [16469](#),
 - [16473](#), [16485](#), [16489](#), [16493](#), [16496](#),
 - [16517](#), [16519](#), [16521](#), [16531](#), [16570](#),
 - [16572](#), [16581](#), [16668](#), [16673](#), [16675](#),
 - [16682](#), [16685](#), [16688](#), [16691](#), [16694](#),
 - [16697](#), [16706](#), [16718](#), [16726](#), [16728](#),
 - [16738](#), [16740](#), [16747](#), [16756](#), [16758](#),
 - [16761](#), [16764](#), [16767](#), [16770](#), [16783](#),
 - [16785](#), [16793](#), [16795](#), [16803](#), [16805](#),
 - [16815](#), [16818](#), [16821](#), [16828](#), [16843](#),
 - [16861](#), [16864](#), [16920](#), [16934](#), [16936](#),
 - [16942](#), [16955](#), [16957](#), [16959](#), [16983](#),
 - [16999](#), [17006](#), [17007](#), [17030](#), [17047](#),
 - [17051](#), [17096](#), [17098](#), [17140](#), [17151](#),
 - [17170](#), [17172](#), [17174](#), [17187](#), [17200](#),
 - [17205](#), [17207](#), [17213](#), [17230](#), [17231](#),

- 17232, 17233, 17234, 17235, 17240,
 17242, 17244, 17246, 17248, 17253,
 17255, 17257, 17259, 17261, 17263,
 17285, 17293, 17377, 17426, 17503,
 17511, 17519, 17525, 17528, 17634,
 17655, 17657, 17660, 17663, 17666,
 17669, 17685, 17711, 17725, 17741,
 17908, 17940, 17949, 18181, 18195,
 18198, 18201, 18204, 18207, 18210,
 18213, 18216, 18219, 18235, 18245,
 18254, 18272, 18281, 18288, 18299,
 18309, 18342, 18352, 18377, 18386,
 18429, 18446, 18448, 18460, 18461,
 18502, 18513, 18524, 18582, 18734,
 18857, 18911, 19012, 19035, 19089,
 19141, 19163, 19165, 19167, 19172,
 19191, 19203, 19211, 19216, 19221
 __fp_int_eval_end:
 13157, 13214, 13285, 13404, 13882,
 13979, 13983, 15162, 15446, 16126,
 16161, 16353, 16728, 16864, 17685,
 17741, 17941, 17950, 18299, 18309,
 18352, 18377, 18461, 19170, 19172
 __fp_int_p:w 13467
 __fp_int_to_roman:w 13157,
 13416, 14431, 14463, 17167, 19273
 __fp_invalid_operation:nw
 . 651, 13598, 13680, 13692, 18715,
 18722, 18769, 18776, 18876, 18891
 __fp_invalid_operation_o:nw ...
 651, 13691, 14698,
 16401, 16627, 17119, 17815, 17830,
 17845, 17860, 17875, 17890, 18552,
 18570, 18586, 18614, 18627, 18643
 __fp_invalid_operation_o:Nw ...
 651, 13606, 13680,
 14899, 15896, 16168, 16169, 17726
 __fp_invalid_operation_o:nw . 16652
 __fp_invalid_operation_tl_o:nn .
 651, 13615, 13680, 13941, 19067
 \c_fp_leading_shift_int
 13370, 16673,
 16682, 16756, 17655, 18235, 18272
 __fp_ln_c:NwNw 775, 775, 17264, 17295
 __fp_ln_div_after:Nw
 773, 17166, 17215
 __fp_ln_div_i:w 17188, 17197
 __fp_ln_div_ii:wn
 .. 17191, 17192, 17193, 17194, 17202
 __fp_ln_div_vi:wn ... 17195, 17210
 __fp_ln_exponent:wn 776, 17142, 17304
 __fp_ln_exponent_one:ww 17309, 17323
 __fp_ln_exponent_small:NNww ...
 17312, 17316, 17329
 \c_fp_ln_i_fixed_tl 17107
 \c_fp_ln_ii_fixed_tl 17107
 \c_fp_ln_iii_fixed_tl 17107
 \c_fp_ln_iv_fixed_tl 17107
 \c_fp_ln_ix_fixed_tl 17107
 __fp_ln_npos_o:w
 769, 770, 17128, 17130
 __fp_ln_o:w .. 769, 784, 17106, 17116
 __fp_ln_significand:NNNNnnN ...
 770, 17141, 17144, 17635
 __fp_ln_square_t_after:w
 17239, 17271
 __fp_ln_square_t_pack:NNNNnw ...
 .. 17241, 17243, 17245, 17247, 17269
 __fp_ln_t_large:NNw
 774, 17220, 17227, 17237
 __fp_ln_t_small:Nw ... 17218, 17225
 __fp_ln_t_small:w 774
 __fp_ln_Taylor:wwNw 775, 17272, 17273
 __fp_ln_Taylor_break:w 17278, 17289
 __fp_ln_Taylor_loop:www
 17274, 17275, 17284
 __fp_ln_twice_t_after:w 17252, 17268
 __fp_ln_twice_t_pack:Nw . 17254,
 17256, 17258, 17260, 17262, 17267
 \c_fp_ln_vi_fixed_tl 17107
 \c_fp_ln_vii_fixed_tl 17107
 \c_fp_ln_viii_fixed_tl 17107
 \c_fp_ln_x_fixed_tl
 17107, 17326, 17333
 __fp_ln_x_ii:wnnnn ... 17146, 17164
 __fp_ln_x_iii:NNNNNw . 17173, 17177
 __fp_ln_x_iii_var:NNNNw
 17171, 17179
 __fp_ln_x_iv:wnnnnnnnn
 772, 17169, 17184
 __fp_logb_aux_o:w 16584
 __fp_logb_o:w 15842, 16584
 \c_fp_max_exp_exponent_int
 13193, 17369
 \c_fp_max_exponent_int .. 13191,
 13197, 13218, 16881, 17083, 17690
 \c_fp_middle_shift_int
 13370, 16685,
 16688, 16691, 16694, 16758, 16761,
 16764, 16767, 17657, 17660, 17663,
 17666, 18238, 18245, 18275, 18281
 __fp_minmax_aux_o:Nw 15708
 __fp_minmax_auxi:ww
 15730, 15742, 15749
 __fp_minmax_auxii:ww
 15732, 15740, 15749
 __fp_minmax_break_o:w . 15723, 15753

- __fp_minmax_loop:Nww [1717](#), [15717](#), [15719](#), [15725](#)
- __fp_minmax_o:Nw [710](#), [15420](#), [15422](#), [15708](#)
- \c_fp_minus_min_exponent_int ... [13191](#), [13219](#)
- __fp_misused:n . [13170](#), [13174](#), [13275](#)
- __fp_mul_cases_o:NnNnw [733](#), [16133](#), [16139](#), [16245](#)
- __fp_mul_cases_o:nNnw [16139](#)
- __fp_mul_npos_o:Nw [730](#), [731](#), [733](#), [820](#), [16136](#), [16177](#), [18928](#)
- __fp_mul_significand_drop:NNNNw [731](#), [16186](#)
- __fp_mul_significand_keep:NNNNw [16186](#)
- __fp_mul_significand_large_-f:NwNNNN [16216](#), [16220](#)
- __fp_mul_significand_o:nnnnNnnn [731](#), [731](#), [16184](#), [16186](#)
- __fp_mul_significand_small_-f:NNwwN [16214](#), [16231](#)
- __fp_mul_significand_test_f:NNN [732](#), [16188](#), [16211](#)
- \c_fp_myriad_int [13190](#), [16668](#), [16699](#), [16700](#), [16777](#), [16838](#)
- __fp_neg_sign:N [721](#), [13213](#), [15850](#), [16003](#)
- __fp_not_o:w [710](#), [14717](#), [15755](#)
- \c_fp_one_fixed_tl [16662](#), [17280](#), [17493](#), [17691](#), [17718](#), [18431](#), [18498](#), [18603](#), [19086](#), [19096](#), [19137](#)
- __fp_overflow:w [637](#), [651](#), [653](#), [13221](#), [13680](#), [17371](#)
- \c_fp_overflowing_fp [13194](#), [18716](#), [18770](#)
- __fp_pack:NNNNw .. [13370](#), [16674](#), [16684](#), [16687](#), [16690](#), [16693](#), [16696](#), [16757](#), [16760](#), [16763](#), [16766](#), [16769](#), [17656](#), [17659](#), [17662](#), [17665](#), [17668](#)
- __fp_pack_big:NNNNNw ... [13374](#), [16450](#), [16453](#), [16456](#), [16459](#), [16462](#), [16465](#), [16468](#), [16472](#), [16784](#), [16794](#), [16804](#), [16814](#), [16817](#), [16820](#), [16827](#)
- __fp_pack_Bigg:NNNNNw [13379](#), [16299](#), [16302](#), [16305](#), [16317](#), [16320](#), [16323](#)
- __fp_pack_eight:wNNNNNNN [643](#), [728](#), [13386](#), [16112](#), [16421](#), [16849](#), [17927](#), [17928](#)
- __fp_pack_twice_four:wNNNNNNN [643](#), [13384](#), [13990](#), [13991](#), [16054](#), [16055](#), [16850](#), [16851](#), [16852](#), [16884](#), [16885](#), [16886](#), [17074](#), [17075](#), [17408](#), [17409](#), [17410](#), [17929](#), [17930](#), [18224](#), [18225](#), [18226](#), [18227](#), [18921](#)
- __fp_parse:n [663](#), [675](#), [687](#), [695](#), [707](#), [708](#), [714](#), [821](#), [832](#), [1019](#), [14021](#), [14173](#), [14834](#), [15363](#), [15365](#), [15367](#), [15390](#), [15428](#), [15445](#), [15455](#), [15612](#), [15672](#), [16597](#), [18691](#), [18745](#), [18823](#), [18868](#), [18883](#), [18937](#), [18939](#), [18941](#), [19323](#), [25789](#)
- __fp_parse_after:ww [14834](#)
- __fp_parse_apply_binary:NwNwN .. [667](#), [668](#), [671](#), [672](#), [699](#), [14872](#), [15040](#)
- __fp_parse_apply_binary_chk:NN [14872](#), [14903](#), [14916](#)
- __fp_parse_apply_binary_-error:NNN [14872](#)
- __fp_parse_apply_comma:NwNwN ... [699](#), [14999](#)
- __fp_parse_apply_compare:NwNNNNNwN [15185](#), [15194](#)
- __fp_parse_apply_compare_-aux:NNwN [15206](#), [15209](#), [15214](#)
- __fp_parse_apply_function:NNNwN [691](#), [14666](#), [14827](#)
- __fp_parse_apply_unary:NNNwN ... [14671](#), [14703](#), [14818](#)
- __fp_parse_apply_unary_chk:nNNNw [14682](#), [14683](#), [14686](#)
- __fp_parse_apply_unary_chk:nNNw [14671](#)
- __fp_parse_apply_unary_chk:NwNw [14671](#)
- __fp_parse_apply_unary_error:NNw [14671](#), [16634](#)
- __fp_parse_apply_unary_type:NNN [14671](#)
- __fp_parse_caseless_inf:N ... [14784](#)
- __fp_parse_caseless_infinity:N . [14784](#)
- __fp_parse_caseless_nan:N ... [14784](#)
- __fp_parse_compare:NNNNNNN .. [15126](#)
- __fp_parse_compare_auxi:NNNNNNN [15126](#)
- __fp_parse_compare_auxii:NNNNN . [15126](#)
- __fp_parse_compare_end:NNNNw . [15126](#)
- __fp_parse_continue:NwN [668](#), [696](#), [14861](#), [14874](#), [15027](#), [15224](#), [15812](#), [15822](#), [15830](#)
- __fp_parse_continue_compare:NNwN [15217](#), [15232](#)
- __fp_parse_digits:N [14038](#)
- __fp_parse_digits_i:N [14038](#)
- __fp_parse_digits_ii:N [14038](#)

- __fp_parse_digits_iii:N [14038](#)
- __fp_parse_digits_iv:N [14038](#)
- __fp_parse_digits_v:N [14038](#)
- __fp_parse_digits_vi:N
..... [14038](#), [14375](#), [14423](#)
- __fp_parse_digits_vii:N
..... [681](#), [14038](#), [14362](#), [14412](#)
- __fp_parse_excl_error: [15126](#)
- __fp_parse_expand:w
 . [671](#), [671](#), [672](#), [672](#), [14035](#), [14037](#),
 [14047](#), [14087](#), [14149](#), [14193](#), [14202](#),
 [14205](#), [14209](#), [14246](#), [14280](#), [14318](#),
 [14320](#), [14339](#), [14341](#), [14363](#), [14380](#),
 [14393](#), [14413](#), [14443](#), [14471](#), [14487](#),
 [14498](#), [14521](#), [14550](#), [14560](#), [14567](#),
 [14580](#), [14596](#), [14616](#), [14627](#), [14713](#),
 [14736](#), [14748](#), [14823](#), [14832](#), [14840](#),
 [14853](#), [14976](#), [14994](#), [15018](#), [15044](#),
 [15090](#), [15110](#), [15179](#), [15192](#), [15808](#)
- __fp_parse_exponent:N
 [685](#), [14148](#), [14354](#), [14503](#), [14570](#), [14572](#)
- __fp_parse_exponent:Nw
 [14378](#), [14391](#),
 [14440](#), [14468](#), [14519](#), [14548](#), [14567](#)
- __fp_parse_exponent_aux:N ... [14572](#)
- __fp_parse_exponent_body:N
 [14598](#), [14602](#)
- __fp_parse_exponent_digits:N ...
 [14606](#), [14618](#)
- __fp_parse_exponent_keep:N .. [14629](#)
- __fp_parse_exponent_keep:NTF ...
 [14609](#), [14629](#)
- __fp_parse_exponent_sign:N
 [14588](#), [14592](#)
- __fp_parse_function:NNN
 [13741](#), [13743](#), [13745](#),
 [13748](#), [14816](#), [15420](#), [15422](#), [17798](#),
 [17800](#), [17802](#), [17804](#), [18971](#), [18973](#)
- __fp_parse_function_all_fp_-
 o:nnw [13875](#), [15234](#), [15710](#)
- __fp_parse_function_one_two:nnw
 [805](#), [806](#), [15246](#), [18392](#), [18398](#), [19040](#)
- __fp_parse_function_one_two_-
 aux:nnw [15246](#)
- __fp_parse_function_one_two_-
 auxii:nnw [15246](#)
- __fp_parse_function_one_two_-
 error_o:w [15246](#)
- __fp_parse_infix:NN
 [674](#), [677](#), [693](#), [698](#), [14086](#),
 [14258](#), [14297](#), [14745](#), [14771](#), [14776](#),
 [14791](#), [14813](#), [14929](#), [14932](#), [14992](#)
- __fp_parse_infix_!:N [15126](#)
- __fp_parse_infix_&:Nw [15083](#)
- __fp_parse_infix_(:N [15066](#)
- __fp_parse_infix_):N [14982](#)
- __fp_parse_infix_*:N [15068](#)
- __fp_parse_infix_+:N
 [671](#), [672](#), [14035](#), [15034](#)
- __fp_parse_infix_,:N [14999](#)
- __fp_parse_infix_-:N [15034](#)
- __fp_parse_infix_/:N [15034](#)
- __fp_parse_infix::N . [15100](#), [15793](#)
- __fp_parse_infix_<:N [15126](#)
- __fp_parse_infix_=:N [15126](#)
- __fp_parse_infix_>:N [15126](#)
- __fp_parse_infix_?:N [15100](#)
- __fp_parse_infix_⟨operation⟩:N [671](#)
- __fp_parse_infix_^:N [15034](#)
- __fp_parse_infix_after_operand:NwN
 [677](#), [14141](#), [14219](#), [14720](#), [14927](#)
- __fp_parse_infix_and:N [15034](#), [15099](#)
- __fp_parse_infix_check:NNN
 [14952](#), [14962](#)
- __fp_parse_infix_comma:w [699](#), [14999](#)
- __fp_parse_infix_end:N
 [695](#), [699](#), [14841](#), [14846](#), [14854](#), [14980](#)
- __fp_parse_infix_mark:NNN
 [14939](#), [14979](#)
- __fp_parse_infix_mul:N
 [701](#), [14942](#), [14950](#), [15034](#), [15067](#), [15076](#)
- __fp_parse_infix_or:N . [15034](#), [15098](#)
- __fp_parse_infix_|:Nw [15083](#)
- __fp_parse_large:N [679](#), [14325](#), [14408](#)
- __fp_parse_large_leading:wwNN ..
 [683](#), [14410](#), [14415](#)
- __fp_parse_large_round:NN
 [684](#), [14451](#), [14523](#)
- __fp_parse_large_round_aux:wNN .
 [14523](#)
- __fp_parse_large_round_test:NN .
 [14523](#)
- __fp_parse_large_trailing:wwNN .
 [684](#), [14421](#), [14445](#)
- __fp_parse_letters:N
 [677](#), [678](#), [14234](#), [14248](#)
- __fp_parse_lparen_after:NwN . [14726](#)
- __fp_parse_o:n
 [663](#), [14834](#), [15610](#), [15611](#)
- __fp_parse_one:Nw
 [667](#)–[670](#), [672](#), [679](#), [693](#),
 [696](#), [14035](#), [14058](#), [14302](#), [14665](#), [14867](#)
- __fp_parse_one_digit:NN
 [692](#), [14074](#), [14217](#)
- __fp_parse_one_fp:NN
 [673](#), [14066](#), [14082](#)
- __fp_parse_one_other:NN [14077](#), [14225](#)

__fp_parse_one_register:NN
 [14069](#), [14139](#)
 __fp_parse_one_register_aux:Nw .
 [14139](#)
 __fp_parse_one_register_-
 auxii:wwwNw [14139](#)
 __fp_parse_one_register_dim:ww .
 [14139](#)
 __fp_parse_one_register_int:www
 [14139](#)
 __fp_parse_one_register_-
 math:NNw [14180](#)
 __fp_parse_one_register_mu:www .
 [14139](#)
 __fp_parse_one_register_-
 special:N [14144](#), [14180](#)
 __fp_parse_one_register_wd:Nw [14180](#)
 __fp_parse_one_register_wd:w . [14180](#)
 __fp_parse_operand:Nw
 [667](#), [669](#), [670](#), [671](#), [695](#), [699](#),
 [14035](#), [14709](#), [14711](#), [14732](#), [14734](#),
 [14823](#), [14832](#), [14839](#), [14852](#), [14861](#),
 [15017](#), [15043](#), [15109](#), [15192](#), [15807](#)
 __fp_parse_pack_carry:w . [682](#), [14395](#)
 __fp_parse_pack_leading:NNNNNww
 [14358](#), [14395](#), [14418](#)
 __fp_parse_pack_trailing:NNNNNNww
 [14368](#), [14395](#), [14437](#), [14448](#), [14455](#)
 __fp_parse_prefix:NNN . [14237](#), [14282](#)
 __fp_parse_prefix!:Nw [14699](#)
 __fp_parse_prefix(:Nw [14726](#)
 __fp_parse_prefix):Nw [14758](#)
 __fp_parse_prefix+:Nw [14665](#)
 __fp_parse_prefix-:Nw [14699](#)
 __fp_parse_prefix_:Nw [14718](#)
 __fp_parse_prefix_unknown:NNN [14282](#)
 __fp_parse_return_semicolon:w . .
 [14036](#), [14045](#), [14278](#),
 [14485](#), [14496](#), [14578](#), [14610](#), [14625](#)
 __fp_parse_round:Nw [13746](#)
 __fp_parse_round_after:wN
 [686](#), [14500](#), [14505](#), [14555](#)
 __fp_parse_round_loop:N [685](#),
 [686](#), [686](#), [14473](#), [14516](#), [14534](#), [14559](#)
 __fp_parse_round_up:N [14473](#)
 __fp_parse_small:N [680](#), [14345](#), [14356](#)
 __fp_parse_small_leading:wwNN . .
 [681](#), [14360](#), [14365](#), [14427](#)
 __fp_parse_small_round:NN
 [14387](#), [14505](#), [14544](#)
 __fp_parse_small_trailing:wwNN .
 [682](#), [14373](#), [14382](#), [14459](#)
 __fp_parse_strim_end:w [14331](#)
 __fp_parse_strim_zeros:N
 [679](#), [692](#), [14312](#), [14331](#), [14724](#)
 __fp_parse_trim_end:w [14305](#)
 __fp_parse_trim_zeros:N [14223](#), [14305](#)
 __fp_parse_unary_function:NNN . .
 [14816](#), [15840](#), [15842](#), [15844](#),
 [15846](#), [17104](#), [17106](#), [17786](#), [17792](#)
 __fp_parse_word:Nw [677](#), [14231](#), [14248](#)
 __fp_parse_word_abs:N [15839](#)
 __fp_parse_word_acos:N [17778](#)
 __fp_parse_word_acosd:N [17778](#)
 __fp_parse_word_acot:N [17797](#)
 __fp_parse_word_acotd:N [17797](#)
 __fp_parse_word_acsc:N [17778](#)
 __fp_parse_word_acscd:N [17778](#)
 __fp_parse_word_asec:N [17778](#)
 __fp_parse_word_asecd:N [17778](#)
 __fp_parse_word_asin:N [17778](#)
 __fp_parse_word_asind:N [17778](#)
 __fp_parse_word_atan:N [17797](#)
 __fp_parse_word_atand:N [17797](#)
 __fp_parse_word_bp:N [14787](#)
 __fp_parse_word_cc:N [14787](#)
 __fp_parse_word_ceil:N [13740](#)
 __fp_parse_word_cm:N [14787](#)
 __fp_parse_word_cos:N [17778](#)
 __fp_parse_word_cosd:N [17778](#)
 __fp_parse_word_cot:N [17778](#)
 __fp_parse_word_cotd:N [17778](#)
 __fp_parse_word_csc:N [17778](#)
 __fp_parse_word_cscd:N [17778](#)
 __fp_parse_word_dd:N [14787](#)
 __fp_parse_word_deg:N [14773](#)
 __fp_parse_word_em:N [14806](#)
 __fp_parse_word_ex:N [14806](#)
 __fp_parse_word_exp:N [17103](#)
 __fp_parse_word_false:N [14773](#)
 __fp_parse_word_floor:N [13740](#)
 __fp_parse_word_in:N [14787](#)
 __fp_parse_word_inf:N
 [14773](#), [14784](#), [14785](#)
 __fp_parse_word_ln:N [17103](#)
 __fp_parse_word_logb:N [15839](#)
 __fp_parse_word_max:N [15419](#)
 __fp_parse_word_min:N [15419](#)
 __fp_parse_word_mm:N [14787](#)
 __fp_parse_word_nan:N . [14773](#), [14786](#)
 __fp_parse_word_nc:N [14787](#)
 __fp_parse_word_nd:N [14787](#)
 __fp_parse_word_pc:N [14787](#)
 __fp_parse_word_pi:N [14773](#)
 __fp_parse_word_pt:N [14787](#)
 __fp_parse_word_rand:N [18970](#)
 __fp_parse_word_randint:N [18970](#)

- __fp_parse_word_round:N [13746](#)
- __fp_parse_word_sec:N [17778](#)
- __fp_parse_word_secd:N [17778](#)
- __fp_parse_word_sign:N [15839](#)
- __fp_parse_word_sin:N [17778](#)
- __fp_parse_word_sind:N [17778](#)
- __fp_parse_word_sp:N [14787](#)
- __fp_parse_word_sqrt:N [15839](#)
- __fp_parse_word_tan:N [17778](#)
- __fp_parse_word_tand:N [17778](#)
- __fp_parse_word_true:N [14773](#)
- __fp_parse_word_trunc:N [13740](#)
- __fp_parse_zero:
..... [679](#), [14327](#), [14347](#), [14351](#)
- __fp_pow_B:wwN [17638](#), [17673](#)
- __fp_pow_C_neg:w [17676](#), [17693](#)
- __fp_pow_C_overflow:w
..... [17681](#), [17688](#), [17709](#)
- __fp_pow_C_pack:w [17695](#), [17703](#), [17714](#)
- __fp_pow_C_pos:w [17679](#), [17698](#)
- __fp_pow_C_pos_loop:wN
..... [17699](#), [17700](#), [17707](#)
- __fp_pow_exponent:Nwnnnnw
..... [17644](#), [17647](#), [17652](#)
- __fp_pow_exponent:wnN . [17636](#), [17641](#)
- __fp_pow_neg:www .. [786](#), [17549](#), [17720](#)
- __fp_pow_neg_aux:wNN . . . [786](#), [17720](#)
- __fp_pow_neg_case:w .. [17722](#), [17743](#)
- __fp_pow_neg_case_aux:nnnnn . [17743](#)
- __fp_pow_neg_case_aux:Nnnw
..... [787](#), [17743](#)
- __fp_pow_normal_o:ww
..... [782](#), [17554](#), [17586](#)
- __fp_pow_npos_aux:NNnw
..... [17621](#), [17625](#), [17631](#)
- __fp_pow_npos_o:Nww [783](#), [17598](#), [17615](#)
- __fp_pow_zero_or_inf:ww
..... [782](#), [17556](#), [17563](#)
- \c__fp_prec_and_int ... [14021](#), [15063](#)
- \c__fp_prec_colon_int
..... [14021](#), [15121](#), [15807](#)
- \c__fp_prec_comma_int
..... [692](#), [14021](#), [14094](#),
[14732](#), [14760](#), [15003](#), [15008](#), [15017](#)
- \c__fp_prec_comp_int
..... [14021](#), [15149](#), [15192](#)
- \c__fp_prec_end_int [695](#),
[699](#), [14021](#), [14096](#), [14839](#), [14852](#), [14986](#)
- \c__fp_prec_func_int
.... [692](#), [14021](#), [14731](#), [14823](#), [14832](#)
- \c__fp_prec_hat_int ... [14021](#), [15053](#)
- \c__fp_prec_hatii_int . [14021](#), [15053](#)
- \c__fp_prec_int
[13187](#), [13413](#), [13474](#), [13501](#), [13959](#),
[17389](#), [17755](#), [17758](#), [18788](#), [18790](#),
[18796](#), [18847](#), [19051](#), [19090](#), [19141](#)
- \c__fp_prec_not_int
..... [691](#), [14021](#), [14716](#), [14717](#)
- \c__fp_prec_or_int [14021](#), [15065](#)
- \c__fp_prec_plus_int
..... [666](#), [14021](#), [15059](#), [15061](#)
- \c__fp_prec_quest_int
..... [14021](#), [15104](#), [15119](#)
- \c__fp_prec_times_int
..... [14021](#), [15055](#), [15057](#)
- \c__fp_prec_tuple_int
.... [692](#), [14021](#), [14095](#), [14734](#), [14762](#)
- __fp_rand_myriads:n
..... [826](#), [827](#), [19006](#), [19023](#), [19109](#)
- __fp_rand_myriads_get:w [19006](#)
- __fp_rand_myriads_loop:w [19006](#)
- __fp_rand_o:Nw
..... [18971](#), [18978](#), [18984](#), [19017](#)
- __fp_rand_o:w [19017](#)
- __fp_randinat_wide_aux:w [19179](#)
- __fp_randinat_wide_auxii:w .. [19179](#)
- __fp_randint:n [19241](#)
- __fp_randint:ww [19147](#), [19251](#)
- __fp_randint_auxi_o:ww [19038](#)
- __fp_randint_auxii:wn [19038](#)
- __fp_randint_auxiii_o:ww [19038](#)
- __fp_randint_auxiv_o:ww [19038](#)
- __fp_randint_auxv_o:w [19038](#)
- __fp_randint_badarg:w ... [826](#), [19038](#)
- __fp_randint_default:w [19038](#)
- __fp_randint_o:Nw [18973](#), [18984](#), [19038](#)
- __fp_randint_o:w [19038](#)
- __fp_randint_split_aux:w [19179](#)
- __fp_randint_split_o:Nw . [830](#), [19179](#)
- __fp_randint_wide_aux:w
..... [830](#), [19182](#), [19213](#)
- __fp_randint_wide_auxii:w
..... [19215](#), [19224](#)
- __fp_reverse_args:Nww
..... [812](#), [813](#), [13166](#),
[18378](#), [18453](#), [18566](#), [18632](#), [19135](#)
- __fp_round:NNN [656](#), [657](#), [658](#), [733](#),
[748](#), [13756](#), [13826](#), [15971](#), [15982](#),
[16226](#), [16238](#), [16380](#), [16391](#), [16575](#)
- __fp_round:Nwn . [13884](#), [13937](#), [18895](#)
- __fp_round:Nww . [13885](#), [13906](#), [13937](#)
- __fp_round:Nwww [13886](#), [13900](#)
- __fp_round_aux_o:Nw [13873](#)
- __fp_round_digit:Nw .. [645](#), [659](#),
[731](#), [733](#), [748](#), [13431](#), [13840](#), [15985](#),
[16128](#), [16229](#), [16241](#), [16394](#), [16580](#)
- __fp_round_name_from_cs:N
.. [13876](#), [13896](#), [13922](#), [13926](#), [13942](#)

__fp_round_neg:NNN [657](#),
 [659](#), [729](#), [13851](#), [16090](#), [16105](#), [16123](#)
 __fp_round_no_arg_o:Nw [13883](#), [13890](#)
 __fp_round_normal:NnnwNNnn .. [13937](#)
 __fp_round_normal:NNwNnn [13937](#)
 __fp_round_normal:NwNNnw [13937](#)
 __fp_round_normal_end:wwNnn . [13937](#)
 __fp_round_o:Nw
 .. [13741](#), [13743](#), [13745](#), [13749](#), [13873](#)
 __fp_round_pack:Nw [13937](#)
 __fp_round_return_one:
 [657](#), [13756](#), [13762](#),
 [13772](#), [13780](#), [13784](#), [13793](#), [13797](#),
 [13806](#), [13813](#), [13817](#), [13855](#), [13866](#)
 __fp_round_s:NNNw
 .. [657](#), [658](#), [685](#), [13824](#), [14509](#), [14527](#)
 __fp_round_special:NwwNnn ... [13937](#)
 __fp_round_special_aux:Nw ... [13937](#)
 __fp_round_to_nearest:NNN
 [660](#), [661](#), [13749](#), [13752](#),
 [13756](#), [13860](#), [13892](#), [13902](#), [18895](#)
 __fp_round_to_nearest_neg:NNN [13851](#)
 __fp_round_to_nearest_ninf:NNN .
 [661](#), [13756](#), [13871](#)
 __fp_round_to_nearest_ninf_-
 neg:NNN [13851](#)
 __fp_round_to_nearest_pinf:NNN .
 [661](#), [13756](#), [13862](#)
 __fp_round_to_nearest_pinf_-
 neg:NNN [13851](#)
 __fp_round_to_nearest_zero:NNN .
 [661](#), [13756](#)
 __fp_round_to_nearest_zero_-
 neg:NNN [13851](#)
 __fp_round_to_ninf:NNN
 [13743](#), [13756](#), [13859](#), [13930](#)
 __fp_round_to_ninf_neg:NNN .. [13851](#)
 __fp_round_to_pinf:NNN
 [13745](#), [13756](#), [13851](#), [13932](#)
 __fp_round_to_pinf_neg:NNN .. [13851](#)
 __fp_round_to_zero:NNN
 [13741](#), [13756](#), [13928](#)
 __fp_round_to_zero_neg:NNN .. [13851](#)
 __fp_rrot:www [13167](#), [18499](#)
 __fp_sanitize:Nw [723](#), [726](#),
 [731](#), [734](#), [742](#), [802](#), [809](#), [827](#), [13215](#),
 [13998](#), [14016](#), [15914](#), [16008](#), [16180](#),
 [16261](#), [16409](#), [17132](#), [17375](#), [17617](#),
 [18340](#), [18384](#), [18511](#), [19033](#), [19128](#)
 __fp_sanitize:wN
 [677](#), [680](#), [13215](#), [14222](#), [14723](#)
 __fp_sanitize_zero:w [13215](#)
 __fp_sec_o:w [17850](#)

__fp_set_sign_o:w
 .. [14716](#), [15840](#), [16611](#), [16612](#), [16633](#)
 __fp_show:NN [15395](#)
 __fp_sign_aux_o:w [16600](#)
 __fp_sign_o:w [15844](#), [16600](#)
 __fp_sin_o:w [650](#), [690](#), [691](#), [811](#), [17805](#)
 __fp_sin_series_aux_o:NNnwww . [18292](#)
 __fp_sin_series_o:NNnwww .. [789](#),
 [803](#), [17811](#), [17826](#), [17841](#), [17856](#), [18292](#)
 __fp_small_int:wTF ... [13483](#), [13939](#)
 __fp_small_int_normal:NnwTF . [13483](#)
 __fp_small_int_test:NnnwNTF . [13483](#)
 __fp_small_int_test:NnnwNw
 [13502](#), [13505](#)
 __fp_small_int_true:wTF [13483](#)
 __fp_sqrt_auxi_o:NNNNwnnnN
 [16431](#), [16439](#)
 __fp_sqrt_auxii_o:NnnnnnnnnN ...
 [744](#), [746](#), [16441](#), [16445](#), [16525](#), [16537](#)
 __fp_sqrt_auxiii_o:wnnnnnnnnn
 [16442](#), [16480](#), [16526](#)
 __fp_sqrt_auxiv_o:NNNNNw [16480](#)
 __fp_sqrt_auxix_o:wnwnw [16514](#)
 __fp_sqrt_auxv_o:NNNNNw [16480](#)
 __fp_sqrt_auxvi_o:NNNNNw [16480](#)
 __fp_sqrt_auxvii_o:NNNNNw ... [16480](#)
 __fp_sqrt_auxviii_o:nnnnnnnn
 .. [16502](#), [16504](#), [16506](#), [16512](#), [16514](#)
 __fp_sqrt_auxx_o:Nnnnnnnnn
 [16510](#), [16528](#)
 __fp_sqrt_auxxi_o:wnnnN [16528](#)
 __fp_sqrt_auxxii_o:nnnnnnnnnw ...
 [16538](#), [16542](#)
 __fp_sqrt_auxxiii_o:w [16542](#)
 __fp_sqrt_auxxiv_o:wnnnnnnnnnN ...
 [16554](#), [16557](#), [16565](#), [16567](#)
 __fp_sqrt_Newton_o:wnn
 [744](#), [16416](#), [16427](#), [16428](#)
 __fp_sqrt_npos_auxi_o:wnnnN . [16407](#)
 __fp_sqrt_npos_auxii_o:wnnnnnnnnn
 [16407](#)
 __fp_sqrt_npos_o:w ... [16404](#), [16407](#)
 __fp_sqrt_o:w [15846](#), [16397](#)
 __fp_step:NNnnnn [15677](#)
 __fp_step:NnnnnN [15607](#)
 __fp_step:wwwN [15607](#)
 __fp_step_fp:wwwN [15607](#)
 __fp_str_if_eq:nn
 .. [13533](#), [14634](#), [14648](#), [14936](#), [17589](#)
 __fp_sub_back_far_o:NnnwnnnnnN ..
 [728](#), [16017](#), [16063](#)
 __fp_sub_back_near_after:wnnnNw
 [16023](#), [16101](#)

- _fp_sub_back_near_o:nnnnnnnnN .
..... [726](#), [16013](#), [16023](#)
- _fp_sub_back_near_pack:NNNNNNw
..... [16023](#), [16103](#)
- _fp_sub_back_not_far_o:wwwNN .
..... [16078](#), [16098](#)
- _fp_sub_back_quite_far_ii:NN [16082](#)
- _fp_sub_back_quite_far_o:wwNN .
..... [16076](#), [16082](#)
- _fp_sub_back_shift:wnnnn .
..... [727](#), [16035](#), [16039](#)
- _fp_sub_back_shift_ii:ww . [16039](#)
- _fp_sub_back_shift_iii:NNNNNNNw
..... [16039](#)
- _fp_sub_back_shift_iv:nnnnw . [16039](#)
- _fp_sub_back_very_far_ii-
o:nnNwwNN [16110](#)
- _fp_sub_back_very_far_o:wwwNN
..... [16077](#), [16110](#)
- _fp_sub_eq_o:Nnnnw [15988](#)
- _fp_sub_npos_i_o:Nnnnw
..... [725](#), [15993](#), [16002](#), [16006](#)
- _fp_sub_npos_ii_o:Nnnnw [15988](#)
- _fp_sub_npos_o:NnwNnw
..... [725](#), [15908](#), [15988](#)
- _fp_tan_o:w [17865](#)
- _fp_tan_series_aux_o:Nnwww . [18346](#)
- _fp_tan_series_o:Nnwww
..... [791](#), [791](#), [17872](#), [17887](#), [18346](#)
- _fp_ternary:NwwN . [710](#), [15119](#), [15791](#)
- _fp_ternary_auxi:NwwN
..... [710](#), [719](#), [15791](#)
- _fp_ternary_auxii:NwwN
..... [710](#), [719](#), [15121](#), [15791](#)
- _fp_tmp:w [645](#),
[700](#), [13425](#), [13435](#), [13436](#), [13437](#),
[13438](#), [13439](#), [13440](#), [13441](#), [13442](#),
[13443](#), [13444](#), [13445](#), [13446](#), [13447](#),
[13448](#), [13449](#), [13450](#), [13553](#), [13555](#),
[14038](#), [14050](#), [14051](#), [14052](#), [14053](#),
[14054](#), [14055](#), [14056](#), [14115](#), [14137](#),
[14699](#), [14716](#), [14717](#), [14773](#), [14778](#),
[14779](#), [14780](#), [14781](#), [14782](#), [14783](#),
[14787](#), [14795](#), [14796](#), [14797](#), [14798](#),
[14799](#), [14800](#), [14801](#), [14802](#), [14803](#),
[14804](#), [14805](#), [14982](#), [14998](#), [14999](#),
[15022](#), [15034](#), [15052](#), [15054](#), [15056](#),
[15058](#), [15060](#), [15062](#), [15064](#), [15068](#),
[15082](#), [15083](#), [15098](#), [15099](#), [15100](#),
[15118](#), [15120](#), [16643](#), [16657](#), [16658](#)
- _fp_to_decimal:w
.. [18750](#), [18760](#), [18877](#), [18894](#), [19383](#)
- _fp_to_decimal_dispatch:w [816](#),
[818](#), [819](#), [15670](#), [18740](#), [18744](#), [18747](#)
- _fp_to_decimal_huge:wnnnn .. [18760](#)
- _fp_to_decimal_large:Nnnw .. [18760](#)
- _fp_to_decimal_normal:wnnnnn ..
..... [18760](#), [18848](#)
- _fp_to_decimal_recover:w ... [18747](#)
- _fp_to_dim:w [18862](#)
- _fp_to_dim_dispatch:w .. [819](#), [18862](#)
- _fp_to_dim_recover:w [18862](#)
- _fp_to_int:w [819](#), [18887](#), [18892](#)
- _fp_to_int_dispatch:w [18878](#)
- _fp_to_int_recover:w [18878](#)
- _fp_to_scientific:w
..... [816](#), [18696](#), [18706](#)
- _fp_to_scientific_dispatch:w ..
..... [814](#), [818](#), [18686](#), [18690](#), [18693](#)
- _fp_to_scientific_normal:wnnnnn
..... [18706](#)
- _fp_to_scientific_normal:wNw [18706](#)
- _fp_to_scientific_recover:w . [18693](#)
- _fp_to_tl:w ... [18826](#), [18834](#), [19390](#)
- _fp_to_tl_dispatch:w
[813](#), [818](#), [18818](#), [18822](#), [18825](#), [18963](#)
- _fp_to_tl_normal:nnnnn [18834](#)
- _fp_to_tl_recover:w [18825](#)
- _fp_to_tl_scientific:wnnnnn . [18834](#)
- _fp_to_tl_scientific:wNw ... [18834](#)
- \c_fp_trailing_shift_int
..... [13370](#), [16675](#),
[16697](#), [16770](#), [17669](#), [18238](#), [18275](#)
- _fp_trap_division_by_zero_-
set:N [13623](#)
- _fp_trap_division_by_zero_set_-
error: [13623](#)
- _fp_trap_division_by_zero_set_-
flag: [13623](#)
- _fp_trap_division_by_zero_set_-
none: [13623](#)
- _fp_trap_invalid_operation_-
set:N [13589](#)
- _fp_trap_invalid_operation_-
set_error: [13589](#)
- _fp_trap_invalid_operation_-
set_flag: [13589](#)
- _fp_trap_invalid_operation_-
set_none: [13589](#)
- _fp_trap_overflow_set:N [13649](#)
- _fp_trap_overflow_set:NnNn . [13649](#)
- _fp_trap_overflow_set_error: [13649](#)
- _fp_trap_overflow_set_flag: . [13649](#)
- _fp_trap_overflow_set_none: . [13649](#)
- _fp_trap_underflow_set:N ... [13649](#)
- _fp_trap_underflow_set_error: .
..... [13649](#)
- _fp_trap_underflow_set_flag: [13649](#)

```

\__fp_trap_underflow_set_none: 13649
\__fp_trig:NNNNNwn . 17811, 17826,
17841, 17856, 17871, 17886, 17903
\c__fp_trig_intarray . . . . . 799,
17964, 18194, 18197, 18200, 18203,
18206, 18209, 18212, 18215, 18218
\__fp_trig_large:ww . . . 17911, 18178
\__fp_trig_large_auxi:w . . . . . 18178
\__fp_trig_large_auxii:w . 799, 18178
\__fp_trig_large_auxiii:w 799, 18178
\__fp_trig_large_auxix:Nw . . . . 18251
\__fp_trig_large_auxv:www . . . . .
. . . . . 18228, 18231
\__fp_trig_large_auxvi:wnnnnnnnn
. . . . . 18231
\__fp_trig_large_auxvii:w . . . . .
. . . . . 18234, 18251
\__fp_trig_large_auxviii:w . . . 18251
\__fp_trig_large_auxviii:ww . . . .
. . . . . 18253, 18257
\__fp_trig_large_auxx:wNNNNN . 18251
\__fp_trig_large_auxxi:w . . . . 18251
\__fp_trig_large_pack:NNNNNw . . .
. . . . . 18231, 18280
\__fp_trig_small:ww . . . . .
793, 801, 17913, 17917, 17923, 18290
\__fp_trigd_large:ww . . 17911, 17925
\__fp_trigd_large_auxi:nnnnwNNNN
. . . . . 17925
\__fp_trigd_large_auxii:wNw . . 17925
\__fp_trigd_large_auxiii:www . 17925
\__fp_trigd_small:ww . . . . .
. . . . . 793, 17913, 17919, 17962
\__fp_trim_zeros:w . . . . .
. . . . . 18677, 18801, 18810, 18861
\__fp_trim_zeros_dot:w . . . . . 18677
\__fp_trim_zeros_end:w . . . . . 18677
\__fp_trim_zeros_loop:w . . . . . 18677
\__fp_tuple_ 15781, 15782, 15785, 15786
\__fp_tuple_&o:ww . . . . . 15764
\__fp_tuple_&tuple_o:ww . . . . . 15764
\__fp_tuple_*o:ww . . . . . 16637
\__fp_tuple_+_tuple_o:ww . . . . . 16643
\__fp_tuple_-_tuple_o:ww . . . . . 16643
\__fp_tuple_/o:ww . . . . . 16637
\__fp_tuple_chk:w . . . . . 639,
13273, 13279, 13280, 13357, 13360,
15031, 15241, 15256, 15281, 15284,
15300, 15301, 15304, 15505, 15506,
16646, 16647, 16653, 16654, 18656
\__fp_tuple_compare_back:ww . . 15502
\__fp_tuple_compare_back_loop:w .
. . . . . 15502

\__fp_tuple_compare_back_
tuple:ww . . . . . 15502
\__fp_tuple_convert:Nw . . . . .
. . . . . 18656, 18705, 18759, 18833
\__fp_tuple_convert_end:w . . . . 18656
\__fp_tuple_convert_loop:nNw . 18656
\__fp_tuple_count:w . . . . . 13278
\__fp_tuple_count_loop:Nw . . . . 13278
\__fp_tuple_map_loop_o:nw . . . . 15281
\__fp_tuple_map_o:nw . . . . .
. . . . . 15281, 16630, 16638, 16640, 16642
\__fp_tuple_maphread_loop_o:nw .
. . . . . 15299
\__fp_tuple_maphread_o:nww . . . .
. . . . . 15299, 16651
\__fp_tuple_not_o:w . . . . . 15755
\__fp_tuple_set_sign_aux_o:Nnw 16622
\__fp_tuple_set_sign_aux_o:w . 16622
\__fp_tuple_set_sign_o:w . . . . . 16622
\__fp_tuple_to_decimal:w . . . . . 18747
\__fp_tuple_to_scientific:w . . 18693
\__fp_tuple_to_tl:w . . . . . 18825
\__fp_tuple_l_o:ww . . . . . 15764
\__fp_tuple_l_tuple_o:ww . . . . . 15764
\__fp_type_from_scan:N . . . . .
. . . . . 640, 13302, 14880, 14882, 14906,
14908, 14919, 14921, 15466, 15468
\__fp_type_from_scan:w . . . . . 13302
\__fp_type_from_scan_other:N . . .
. . . . . 13302, 13326, 13344
\__fp_underflow:w . . . . .
. . . . . 637, 651, 653, 13222, 13680, 17372
\__fp_use_i:ww . . . . .
. . . . . 760, 811, 13168, 16887, 18585
\__fp_use_i:www . . . . . 13168
\__fp_use_i_until_s:nw 801, 13163,
13209, 13475, 13525, 17955, 18233,
18239, 18270, 19051, 19122, 19330
\__fp_use_ii_until_s:nnw 13163, 13207
\__fp_use_none_stop_f:n . . . . .
. . . . . 13160, 17052, 17053, 17054
\__fp_use_none_until_s:w . . . . .
. . . . . 13163, 16433, 17729, 18580, 18583
\__fp_use_s:n . . . . . 13161
\__fp_use_s:nn . . . . . 13161
\__fp_zero_fp:N . 13200, 13664, 14004
\__fp_l_o:ww . . . . . 710, 15764
\__fp_l_tuple_o:ww . . . . . 15764
\__fp_ . . . . . 15767, 15774, 15783, 15784
fparray commands:
\fparray_count:N . . . . . 242,
243, 243, 19292, 19303, 19314, 19369
\fparray_gset:Nnn . . . 243, 833, 19316
\fparray_gzero:N . . . . . 243, 19366

```

\fpararray_item:Nn 243, 833, 19378
 \fpararray_item_to_tl:Nn . . . 243, 19378
 \fpararray_new:Nn 242, 19266
 \futurelet 380

G

\gdef 381
 \GetIdInfo 6
 \gleaders 930, 1752
 \global 173,
 174, 188, 189, 190, 201, 202, 203,
 204, 205, 206, 207, 208, 209, 278, 382
 \globaldefs 383
 \glueexpr 637, 1451
 \glueshrink 638, 1452
 \glueshrinkorder 639, 1453
 \gluestretch 640, 1454
 \gluestretchorder 641, 1455
 \gluetomu 642, 1456

group commands:

\group_align_safe_begin/end: 479, 854
 \group_align_safe_begin: . . . 104,
 383, 387, 472, 4374, 4702, 7479,
 7682, 8904, 8919, 19898, 26579, 27668
 \group_align_safe_end: 104,
 383, 387, 4397, 4728, 7481, 7682,
 8913, 8924, 8930, 19901, 26600, 27676
 \group_begin: 8, 1000,
 2077, 3124, 3127, 3130, 3513, 3947,
 4129, 4238, 4244, 4273, 4469, 5077,
 5104, 5380, 5403, 6060, 8460, 8466,
 8517, 8602, 8626, 8644, 8668, 8756,
 8774, 9480, 9504, 9520, 9593, 9897,
 10269, 10360, 10381, 10729, 10775,
 11050, 11091, 11982, 15764, 19554,
 19591, 19897, 19904, 19977, 20137,
 20486, 20580, 20588, 20903, 21402,
 21765, 21858, 22279, 22661, 22872,
 23032, 23041, 23053, 23062, 23070,
 23188, 23218, 23714, 25084, 25309,
 25428, 26072, 26399, 26421, 27129,
 27166, 27184, 27206, 27360, 27382,
 27612, 27618, 28429, 28451, 29125
 \c_group_begin_token 46, 122, 258,
 397, 507, 4833, 4868, 8626, 8650,
 19942, 23762, 23769, 23784, 23791,
 23874, 23881, 23897, 23904, 27691
 \group_end: 8, 8,
 432, 1000, 2077, 3124, 3127, 3133,
 3522, 3950, 4135, 4240, 4253, 4331,
 4473, 5095, 5127, 5385, 5408, 6070,
 6075, 8468, 8475, 8605, 8623, 8643,
 8647, 8675, 8773, 8821, 9499, 9512,
 9531, 9754, 9942, 10285, 10367,

10392, 10733, 10804, 11070, 11100,
 12033, 15788, 19558, 19599, 19808,
 19902, 19923, 19984, 20161, 20499,
 20602, 20936, 20944, 21415, 21823,
 21865, 21872, 21880, 22283, 22284,
 22698, 22936, 23037, 23048, 23132,
 23194, 23255, 23720, 25085, 25425,
 25442, 26079, 26406, 26426, 27157,
 27198, 27205, 27375, 27381, 27408,
 27616, 27642, 28448, 28480, 29133

\c_group_end_token . 122, 258, 507,
 8626, 8655, 19945, 23777, 23890, 27692

\group_insert_after:N
 . 8, 2083, 20495, 27788, 27874, 28167

groups commands:

.groups:n 171, 12496

H

\H 27411
 \halign 384
 \hangafter 385
 \hangindent 386
 \hbadness 387
 \hbox 388

hbox commands:

\hbox:n
 224, 23728, 23967, 24215, 24875, 24930
 \hbox_gset:Nn 224, 23730
 \hbox_gset:Nw 225, 23758
 \hbox_gset_end: 225, 23758
 \hbox_gset_to_wd:Nnn 224, 23744
 \hbox_gset_to_wd:Nnw 225, 23780
 \hbox_overlap_left:n 225, 23806
 \hbox_overlap_right:n 224,
 23806, 27922, 27954, 28195, 28310,
 28351, 28521, 28549, 28987, 29087
 \hbox_set:Nn 224, 225, 23730,
 23938, 23963, 23964, 24050, 24088,
 24103, 24118, 24130, 24146, 24176,
 24188, 24307, 24651, 24729, 25020,
 25454, 25458, 25466, 25474, 25483,
 25492, 25504, 25512, 25520, 25526,
 25539, 25572, 25586, 28413, 28738
 \hbox_set:Nw 225, 23758, 24353
 \hbox_set_end: 225, 225, 23758, 24356
 \hbox_set_to_wd:Nnn . 224, 225, 23744
 \hbox_set_to_wd:Nnw 225, 23780
 \hbox_to_wd:nn 224, 23796, 24206
 \hbox_to_zero:n
 224, 23796, 23807, 23809
 \hbox_unpack:N 225, 23810, 24655
 \hbox_unpack_clear:N 225, 23810

hcoffin commands:

`\hcoffin_set:Nn` [231](#), [24303](#), [24872](#), [24884](#), [24927](#), [24967](#)
`\hcoffin_set:Nw` [231](#), [24349](#)
`\hcoffin_set_end:` [231](#), [24349](#)
`\hfil` [389](#)
`\hfill` [390](#)
`\hfilneg` [391](#)
`\hfuzz` [392](#)
`\hjcode` [925](#), [1747](#)
`\hoffset` [393](#)
`\holdinginserts` [394](#)
`\hpack` [926](#), [1748](#)
`\hrule` [395](#)
`\hsize` [396](#)
`\hskip` [397](#)
`\hss` [398](#)
`\ht` [399](#)

hundred commands:

`\c_one_hundred` [7274](#)
`\hyphenation` [400](#)
`\hyphenationbounds` [927](#), [1749](#)
`\hyphenationmin` [928](#), [1750](#)
`\hyphenchar` [401](#)
`\hyphenpenalty` [402](#)
`\hyphenpenaltymode` [929](#), [1751](#)

I

`\I` [202](#)
`\i` [205](#), [27406](#)
`\if` [403](#)

if commands:

`\if:w`
[21](#), [117](#), [332](#), [333](#), [368](#), [883](#), [2049](#),
[2322](#), [2334](#), [2336](#), [2718](#), [3018](#), [3019](#),
[3826](#), [3829](#), [3830](#), [3831](#), [3832](#), [3847](#),
[3848](#), [3849](#), [3850](#), [3851](#), [3852](#), [3853](#),
[3854](#), [3855](#), [3920](#), [3921](#), [3923](#), [7147](#),
[8868](#), [10170](#), [10172](#), [10174](#), [12061](#),
[12065](#), [12088](#), [14307](#), [14311](#), [14333](#),
[14426](#), [14458](#), [14477](#), [14543](#), [14557](#),
[14574](#), [14594](#), [15072](#), [15087](#), [17620](#),
[19063](#), [20804](#), [25358](#), [25366](#), [25383](#)
`\if_bool:N` [102](#), [102](#), [7396](#), [7437](#)
`\if_box_empty:N` ... [230](#), [23664](#), [23676](#)
`\if_case:w`
... [91](#), [413](#), [414](#), [415](#), [458](#), [646](#),
[733](#), [787](#), [827](#), [2926](#), [3567](#), [5478](#),
[5552](#), [6399](#), [7038](#), [7071](#), [8617](#), [10889](#),
[13217](#), [13470](#), [13485](#), [13881](#), [13910](#),
[15160](#), [15201](#), [15855](#), [15990](#), [16065](#),
[16090](#), [16142](#), [16586](#), [16602](#), [16619](#),
[16896](#), [17121](#), [17148](#), [17306](#), [17341](#),
[17499](#), [17544](#), [17596](#), [17722](#), [17745](#),

[17807](#), [17822](#), [17837](#), [17852](#), [17867](#),
[17882](#), [18408](#), [18461](#), [18545](#), [18560](#),
[18612](#), [18625](#), [18709](#), [18763](#), [18837](#),
[19060](#), [19344](#), [19420](#), [19953](#), [20147](#),
[20445](#), [20718](#), [21519](#), [21548](#), [21605](#),
[22038](#), [22095](#), [22473](#), [22813](#), [27685](#)
`\if_catcode:w`
... [21](#), [388](#), [397](#), [398](#), [517](#), [2049](#),
[4517](#), [4824](#), [4866](#), [4878](#), [4895](#), [8650](#),
[8655](#), [8660](#), [8665](#), [8672](#), [8679](#), [8684](#),
[8689](#), [8694](#), [8699](#), [8704](#), [8714](#), [8741](#),
[8956](#), [8961](#), [14060](#), [14267](#), [14584](#),
[14631](#), [14934](#), [19942](#), [19945](#), [20099](#),
[20101](#), [20103](#), [20105](#), [20107](#), [20109](#),
[20111](#), [27624](#), [27625](#), [27686](#), [27687](#)
`\if_charcode:w`
... [21](#), [117](#), [396](#), [397](#), [418](#), [517](#), [859](#),
[2049](#), [4807](#), [4859](#), [5636](#), [8719](#), [8958](#),
[13473](#), [15432](#), [15794](#), [20012](#), [20036](#),
[20085](#), [20661](#), [20671](#), [21153](#), [22667](#)
`\if_cs_exist:N`
[21](#), [2063](#), [2745](#), [2773](#), [3516](#), [8749](#), [8877](#)
`\if_cs_exist:w` [21](#), [2063](#), [2091](#), [2754](#),
[2782](#), [2913](#), [7328](#), [7371](#), [7381](#), [25866](#)
`\if_dim:w`
[167](#), [11333](#), [11451](#), [11469](#), [11492](#), [26154](#)
`\if_eof:w`
[151](#), [560](#), [10504](#), [10511](#), [10556](#), [10574](#)
`\if_false:` [20](#),
[97](#), [383](#), [387](#), [395](#), [434](#), [448](#), [479](#),
[851](#), [942](#), [2049](#), [3527](#), [3537](#), [3550](#),
[3563](#), [3664](#), [3678](#), [3684](#), [3691](#), [3699](#),
[3709](#), [3724](#), [4392](#), [4393](#), [4489](#), [4493](#),
[4775](#), [4780](#), [4791](#), [4879](#), [4891](#), [4906](#),
[4914](#), [6013](#), [6016](#), [6148](#), [6153](#), [6643](#),
[7683](#), [8560](#), [10868](#), [10908](#), [10912](#),
[10919](#), [10927](#), [11479](#), [19889](#), [19931](#),
[19980](#), [19983](#), [20912](#), [20931](#), [20932](#),
[20941](#), [20992](#), [21028](#), [21042](#), [21046](#),
[21269](#), [21302](#), [21314](#), [21318](#), [21352](#),
[21357](#), [21365](#), [21400](#), [21407](#), [21412](#),
[21460](#), [21682](#), [21699](#), [21703](#), [22888](#),
[22905](#), [23144](#), [23149](#), [23260](#), [23265](#),
[26328](#), [27515](#), [27527](#), [27555](#), [27565](#)
`\if_hbox:N` [229](#), [23664](#), [23668](#)
`\if_int_compare:w` ... [20](#), [91](#), [448](#),
[449](#), [2081](#), [3714](#), [4971](#), [4980](#), [5029](#),
[5030](#), [5036](#), [5212](#), [5221](#), [5226](#), [5462](#),
[5517](#), [5518](#), [5524](#), [5536](#), [5552](#), [6399](#),
[6447](#), [6498](#), [6499](#), [6538](#), [6623](#), [6676](#),
[6678](#), [6680](#), [6682](#), [6684](#), [6686](#), [6688](#),
[6697](#), [6849](#), [7683](#), [7685](#), [8489](#), [8490](#),
[8497](#), [8498](#), [8499](#), [8500](#), [8505](#), [8506](#),
[8548](#), [8859](#), [10875](#), [11508](#), [12958](#),

12962, 13005, 13067, 13218, 13219,
 13413, 13510, 13761, 13771, 13779,
 13792, 13805, 13812, 13833, 13845,
 13854, 13865, 13966, 13971, 14042,
 14072, 14227, 14229, 14266, 14271,
 14324, 14344, 14371, 14385, 14420,
 14447, 14475, 14491, 14507, 14525,
 14584, 14604, 14620, 14633, 14647,
 14708, 14731, 14760, 14762, 14935,
 14945, 14947, 14986, 15003, 15008,
 15038, 15104, 15149, 15443, 15490,
 15493, 15524, 15533, 15536, 15541,
 15542, 15545, 15548, 15735, 15859,
 15880, 15917, 16012, 16066, 16067,
 16070, 16073, 16143, 16152, 16357,
 16430, 16483, 16487, 16491, 16509,
 16544, 16545, 16546, 16547, 16548,
 16574, 16898, 16901, 16995, 17088,
 17134, 17150, 17277, 17311, 17369,
 17378, 17418, 17589, 17591, 17602,
 17620, 17643, 17675, 17678, 17725,
 17755, 17910, 17954, 18412, 18450,
 18459, 18495, 18579, 18582, 18811,
 19050, 19118, 19119, 19120, 19130,
 19158, 19163, 19164, 19227, 19228,
 19229, 19233, 19248, 19253, 19299,
 19303, 19467, 19536, 19565, 19606,
 19617, 19620, 19638, 19693, 19703,
 19713, 19917, 19989, 20022, 20030,
 20053, 20077, 20128, 20143, 20225,
 20228, 20383, 20389, 20390, 20397,
 20400, 20403, 20409, 20410, 20414,
 20417, 20418, 20426, 20427, 20428,
 20434, 20464, 20465, 20715, 20735,
 20736, 20737, 20740, 20744, 20745,
 20748, 20749, 20757, 20758, 20761,
 20765, 20766, 20769, 20828, 20850,
 20862, 20871, 20879, 20882, 20892,
 20895, 20923, 20996, 21101, 21167,
 21172, 21200, 21267, 21300, 21411,
 21428, 21713, 21746, 21973, 22056,
 22085, 22150, 22163, 22174, 22190,
 22241, 22273, 22451, 22452, 22505,
 22532, 22607, 22678, 22741, 22751,
 22754, 22774, 22831, 22884, 22901,
 22924, 23073, 23102, 23142, 23147,
 23168, 23246, 23258, 23263, 25359,
 26490, 26491, 26497, 27598, 27606
 20847, 20859, 21273, 21588, 27623
 \if_meaning:w . . 21, 384, 385, 397,
 718, 2049, 2414, 2417, 2564, 2590,
 2608, 2667, 2672, 2681, 2742, 2760,
 2770, 2788, 2944, 2958, 3079, 3142,
 3199, 3200, 3568, 3571, 3572, 3573,
 3574, 3626, 3656, 3669, 3675, 3774,
 3797, 3806, 3991, 4003, 4004, 4425,
 4435, 4446, 4459, 4474, 4720, 4784,
 4850, 5321, 5389, 5412, 5573, 5611,
 5740, 5746, 5772, 5784, 5792, 5824,
 6049, 6065, 6080, 6088, 6418, 6468,
 6473, 6474, 6658, 7491, 7513, 7918,
 7933, 7955, 7969, 8709, 8746, 8784,
 8787, 8851, 8910, 8949, 9302, 10825,
 11422, 11485, 11998, 12022, 12039,
 12050, 13206, 13220, 13232, 13242,
 13337, 13392, 13401, 13492, 13507,
 13509, 13672, 13760, 13770, 13782,
 13795, 13796, 13815, 13816, 13830,
 13831, 13842, 13843, 13909, 13948,
 13983, 13986, 14002, 14009, 14061,
 14064, 14182, 14183, 14184, 14185,
 14188, 14284, 14397, 14403, 14632,
 14680, 14891, 14964, 15198, 15216,
 15266, 15276, 15479, 15480, 15481,
 15482, 15483, 15484, 15716, 15728,
 15729, 15757, 15769, 15776, 15793,
 15856, 15891, 15905, 15951, 15958,
 16034, 16046, 16146, 16149, 16160,
 16213, 16286, 16356, 16359, 16366,
 16399, 16400, 16403, 16624, 16869,
 16880, 17061, 17071, 17118, 17217,
 17297, 17346, 17360, 17507, 17541,
 17553, 17566, 17569, 17572, 17575,
 17601, 17702, 17706, 17765, 18302,
 18355, 18406, 18407, 18409, 18410,
 18430, 18447, 18514, 18612, 18708,
 18762, 18836, 18907, 18912, 19049,
 19081, 19092, 19199, 19357, 19407,
 19413, 19478, 19479, 19939, 19969,
 19997, 20097, 20494, 20803, 20827,
 21149, 21152, 21595, 22020, 22198,
 22209, 22224, 22394, 22427, 22786,
 23024, 23101, 23154, 23193, 25338,
 25340, 25349, 25882, 25885, 26157,
 27520, 27559, 27578, 27626, 27688
 \if_mode_horizontal: . 21, 2059, 7677
 \if_mode_inner: 21, 2059, 7679
 \if_mode_math: 21, 2059, 7681
 \if_mode_vertical:
 21, 2059, 7675, 25448
 \if_predicate:w 95, 97, 102, 7396,
 7469, 7529, 7544, 7555, 7570, 7581

- `\if_true:` [20](#), [97](#), [385](#), [2049](#)
- `\if_vbox:N` [229](#), [23664](#), [23670](#)
- `\ifabsdim` [1016](#), [1625](#)
- `\ifabsnum` [1017](#), [1626](#)
- `\ifcase` [404](#)
- `\ifcat` [405](#)
- `\ifcondition` [931](#)
- `\ifcsname` [643](#), [1457](#)
- `\ifdbbox` [1217](#), [1999](#)
- `\ifddir` [1218](#), [2000](#)
- `\ifdefined` [165](#), [644](#), [1458](#)
- `\ifdim` [406](#)
- `\ifeof` [407](#)
- `\iffalse` [408](#)
- `\iffontchar` [645](#), [1459](#)
- `\ifhbox` [409](#)
- `\ifhmode` [410](#)
- `\ifincsname` [794](#), [1608](#)
- `\ifinner` [411](#)
- `\ifmdir` [1219](#), [2001](#)
- `\ifmmode` [412](#)
- `\ifnum` .. [45](#), [60](#), [89](#), [102](#), [107](#), [171](#), [186](#), [413](#)
- `\ifodd` [414](#)
- `\ifpdfabsdim` [750](#), [1567](#)
- `\ifpdfabsnum` [751](#), [1568](#)
- `\ifpdfprimitive` [752](#), [1569](#)
- `\ifprimitive` [885](#), [1618](#)
- `\iftbox` [1220](#), [2002](#)
- `\iftdir` [1221](#), [2003](#)
- `\iftrue` [415](#)
- `\ifvbox` [416](#)
- `\ifvmode` [417](#)
- `\ifvoid` [418](#)
- `\ifx` [14](#), [21](#), [39](#), [43](#), [49](#),
[90](#), [92](#), [93](#), [94](#), [105](#), [130](#), [152](#), [153](#), [419](#)
- `\ifybox` [1222](#), [2004](#)
- `\ifydir` [1223](#), [2005](#)
- `\ignoreligaturesinfont` [1018](#), [1627](#)
- `\ignorespaces` [420](#)
- `\IJ` [27397](#)
- `\ij` [27397](#)
- image commands:
 - `\image_bb_restore:nTF` . [28384](#), [28733](#)
 - `\image_bb_save:n` [28419](#), [28741](#)
 - `\l_image_decode_tl` . [28361](#), [28372](#),
[28402](#), [28563](#), [28588](#), [28630](#), [28702](#)
 - `\l_image_decodearray_tl` .. [28362](#),
[28398](#), [28403](#), [28589](#), [28627](#), [28631](#)
 - `\image_extract_bb:n`
[28558](#), [28565](#), [29090](#), [29091](#)
 - `\l_image_interpolate_bool`
[28363](#), [28373](#), [28397](#), [28404](#),
[28564](#), [28590](#), [28626](#), [28632](#), [28703](#)
 - `\l_image_llx_dim` [28619](#)
 - `\l_image_lly_dim` [28620](#)
 - `\l_image_page_int`
[28357](#), [28377](#), [28378](#), [28408](#), [28409](#),
[28556](#), [28586](#), [28587](#), [28613](#), [28614](#),
[28695](#), [28708](#), [28709](#), [28747](#), [28748](#)
 - `\l_image_pagebox_tl`
[1093](#), [28358](#), [28376](#), [28410](#),
[28411](#), [28557](#), [28584](#), [28585](#), [28615](#),
[28617](#), [28696](#), [28717](#), [28718](#), [28749](#)
 - `\image_read_bb:n` [27957](#), [28552](#)
 - `\l_image_urx_dim` [28415](#), [28621](#)
 - `\l_image_ury_dim`
[28416](#), [28622](#), [28740](#), [29097](#), [29098](#)
 - `\l_image_utx_dim` [28739](#)
- `\immediate` [421](#)
- `\immediateassigned` [932](#)
- `\immediateassignment` [933](#)
- `in` [200](#)
- `\indent` [422](#)
- `inf` [200](#)
- `\infty` [14185](#), [14186](#)
- inherit commands:
 - `.inherit:n` [171](#), [12498](#)
- `\inhibitglue` [1224](#), [2006](#)
- `\inhibitxspcode` [1225](#), [2007](#)
- `\initcatcodetable` [934](#), [1753](#)
- initial commands:
 - `.initial:n` [172](#), [12500](#)
- `\input` [50](#), [166](#), [167](#), [423](#)
- `\inputlineno` [424](#)
- `\insert` [425](#)
- `\insertht` [1019](#), [1629](#)
- `\insertpenalties` [426](#)
- int commands:
 - `\c_eight` [7274](#)
 - `\c_eleven` [7274](#)
 - `\c_fifteen` [7274](#)
 - `\c_five` [7274](#)
 - `\l_foo_int` [215](#)
 - `\c_four` [7274](#)
 - `\c_fourteen` [7274](#)
 - `\int_abs:n` [79](#), [1022](#), [6409](#), [13005](#)
 - `\int_add:Nn` [81](#), [6578](#), [10984](#), [20435](#),
[21590](#), [22180](#), [22181](#), [22436](#), [22529](#)
 - `\int_case:nn` [84](#), [458](#), [6703](#), [6901](#), [6907](#)
 - `\int_case:nnn` [29424](#)
 - `\int_case:nnTF` [84](#),
[6313](#), [6703](#), [6708](#), [6713](#), [8231](#), [14092](#),
[18658](#), [23544](#), [27024](#), [27079](#), [29425](#)
 - `\int_compare:nNnTF` ... [82](#), [82](#), [84](#),
[84](#), [85](#), [85](#), [4247](#), [4277](#), [4291](#), [4295](#),
[4320](#), [4926](#), [4933](#), [5000](#), [5441](#), [5443](#),
[5452](#), [6206](#), [6213](#), [6516](#), [6522](#), [6689](#),
[6727](#), [6783](#), [6791](#), [6800](#), [6806](#), [6833](#),

- 6836, 6897, 6985, 6991, 6997, 7017,
7171, 7190, 7192, 7234, 7756, 8270,
8272, 8277, 8286, 8306, 8323, 10598,
10684, 10797, 11688, 12945, 12950,
12955, 13059, 13100, 13126, 15508,
16649, 18641, 18786, 18788, 19280,
19454, 20272, 20472, 20484, 20647,
20965, 20967, 21759, 22397, 22625,
22640, 22843, 23118, 23563, 25989,
26066, 26475, 26742, 26744, 26747,
26890, 26912, 26946, 26949, 26983,
26986, 26993, 27006, 27121, 28377,
28408, 28586, 28613, 28708, 28747
- `\int_compare:nTF`
..... 83, 85, 85, 85, 85, 188,
586, 6636, 6755, 6763, 6772, 6778,
10482, 10509, 10654, 18846, 21863,
23301, 23523, 23524, 23529, 23531
- `\int_compare_p:n` 83, 6636, 21870
- `\int_compare_p:nNn`
..... 20, 82, 6689, 7743,
10586, 21658, 21659, 26288, 26290,
26292, 26971, 27066, 27067, 27068,
27113, 27415, 27416, 27440, 27441
- `\int_const:Nn` 80, 465, 6510,
7200, 7201, 7202, 7203, 7204, 7205,
7206, 7207, 7208, 7209, 7210, 7211,
7212, 7213, 7258, 7259, 7260, 7300,
7712, 7714, 7716, 7717, 7718, 10402,
10581, 10582, 13187, 13188, 13189,
13190, 13191, 13192, 13193, 13370,
13371, 13372, 13374, 13375, 13376,
13379, 13380, 13381, 13755, 14021,
14022, 14023, 14024, 14025, 14026,
14027, 14028, 14029, 14030, 14031,
14032, 14033, 14034, 19000, 19520,
20369, 20370, 20371, 20372, 20776,
20777, 20778, 20779, 20780, 20781,
20785, 20786, 20787, 20788, 20789,
20790, 20791, 20792, 20793, 20794,
20795, 20796, 20797, 26253, 26294,
28207, 28417, 28435, 28608, 28643
- `\int_decr:N` 81,
6594, 19626, 19627, 19628, 19691,
19692, 19701, 19702, 19711, 19712,
19932, 22475, 22833, 22902, 23103
- `\int_div_round:nn` 80, 6453
- `\int_div_truncate:nn`
..... 80, 80, 6453, 6912, 7010,
7030, 7715, 26503, 26516, 26521, 26533
- `\int_do_until:nn` 85, 6753
- `\int_do_until:nNnn` 84, 6781
- `\int_do_while:nn` 85, 6753
- `\int_do_while:nNnn` 84, 6781
- `\int_eval:n` 13, 25,
79, 79, 79, 80, 81, 82, 83, 84, 91,
91, 246, 308, 312, 340, 444, 461,
628, 629, 633, 665, 711, 735, 737,
868, 1023, 1034, 2926, 2955, 2971,
4621, 4626, 4919, 4927, 4935, 4962,
4966, 4975, 4982, 5017, 5027, 5435,
5448, 5473, 5497, 5498, 5510, 5515,
5546, 5563, 5600, 6199, 6207, 6215,
6287, 6404, 6706, 6711, 6716, 6721,
6894, 6980, 6982, 7112, 7122, 7157,
7168, 7174, 7185, 7216, 7253, 7257,
7630, 8204, 8213, 8264, 8274, 8288,
8295, 8310, 8361, 8363, 8431, 8433,
8437, 8439, 8443, 8445, 8449, 8451,
8484, 8485, 10468, 10639, 10920,
10978, 12944, 12981, 12982, 13031,
13047, 13096, 13120, 13129, 13133,
13197, 18989, 19149, 19152, 19153,
19243, 19244, 19276, 19322, 19382,
19389, 19568, 19834, 19835, 20055,
20131, 20135, 20158, 20454, 20719,
21588, 21793, 21797, 21800, 21804,
21993, 21995, 22004, 22021, 22022,
22024, 22025, 22174, 22264, 22295,
22500, 22548, 22623, 22753, 22758,
23305, 23350, 23351, 23550, 23696,
23706, 25955, 25992, 26096, 26244,
26362, 26486, 26538, 26541, 26546,
26552, 27600, 27608, 28488, 28687
- `\int_eval:w` 79, 309,
312, 312, 5466, 6404, 7331, 7382,
10871, 10880, 10905, 10917, 13072,
16598, 19882, 20117, 20127, 26141
- `\int_from_alph:n` 88, 7155
- `\int_from_base:nn`
..... 89, 7172, 7195, 7197, 7199
- `\int_from_bin:n` 88, 7194, 29427
- `\int_from_binary:n` 29426
- `\int_from_hex:n` 89, 7194, 29429
- `\int_from_hexadecimal:n` 29428
- `\int_from_oct:n` 89, 7194, 29431
- `\int_from_octal:n` 29430
- `\int_from_roman:n` 89, 7214
- `\int_gadd:Nn` 81, 6578
- `\int_gdecr:N` 81, 4582,
5340, 6264, 6594, 6892, 8165, 9347,
10551, 11666, 15700, 20197, 26123
- `\int_gincr:N` . 81, 4575, 5329, 6256,
6594, 6867, 6878, 8158, 9342, 10542,
11645, 11652, 12934, 15679, 15686,
19271, 20175, 26117, 28206, 28607,
28642, 29007, 29141, 29197, 29242
- `.int_gset:N` 172, 12508

- \int_gset:Nn [81](#), [444](#), [6610](#), [9538](#)
- \int_gset_eq:NN [81](#), [6560](#), [29134](#)
- \int_gsub:Nn [81](#), [6578](#), [19284](#)
- \int_gzero:N [80](#), [6548](#), [6557](#), [29126](#)
- \int_gzero_new:N [80](#), [6554](#)
- \int_if_even:nTF [84](#), [6733](#), [11106](#)
- \int_if_even_p:n [84](#), [6733](#)
- \int_if_exist:NTF [81](#), [6555](#), [6557](#),
[6566](#), [7228](#), [7232](#), [21514](#), [21569](#), [28597](#)
- \int_if_exist_p:N [81](#), [6566](#)
- \int_if_odd:nTF [84](#), [6733](#), [16984](#)
- \int_if_odd_p:n [84](#), [6733](#), [21907](#)
- \int_incr:N
. [81](#), [6594](#), [12302](#), [13021](#), [13052](#),
[13142](#), [19371](#), [19540](#), [19636](#), [19637](#),
[19973](#), [20015](#), [20028](#), [20046](#), [20326](#),
[20327](#), [21405](#), [21828](#), [22013](#), [22106](#),
[22437](#), [22472](#), [22474](#), [22555](#), [22820](#),
[22885](#), [23044](#), [23100](#), [23164](#), [26086](#)
- \int_log:N [90](#), [7254](#)
- \int_log:n [90](#), [7256](#)
- \int_max:nn [80](#), [821](#), [6409](#), [16845](#),
[17934](#), [22130](#), [22355](#), [23250](#), [23251](#)
- \int_min:nn [80](#), [824](#), [6409](#)
- \int_mod:nn [80](#),
[6453](#), [6902](#), [7001](#), [7021](#), [7713](#), [26535](#)
- \int_new:N [80](#), [80](#), [6502](#),
[6518](#), [6524](#), [6555](#), [6557](#), [7270](#), [7271](#),
[7272](#), [7273](#), [7687](#), [10706](#), [10709](#),
[10711](#), [10724](#), [12121](#), [12926](#), [12928](#),
[19264](#), [19265](#), [19435](#), [19436](#), [19437](#),
[19438](#), [19439](#), [19440](#), [19441](#), [19442](#),
[19443](#), [19444](#), [19445](#), [19868](#), [19869](#),
[19870](#), [19871](#), [20352](#), [20353](#), [20354](#),
[20367](#), [20774](#), [20775](#), [20782](#), [20783](#),
[20800](#), [21924](#), [21926](#), [21927](#), [21928](#),
[21931](#), [22301](#), [22302](#), [22303](#), [22304](#),
[22305](#), [22306](#), [22307](#), [22308](#), [22309](#),
[22310](#), [22313](#), [22314](#), [22315](#), [22585](#),
[23013](#), [23016](#), [23017](#), [23018](#), [23569](#),
[26059](#), [26060](#), [27833](#), [28202](#), [28568](#),
[28638](#), [29057](#), [29144](#), [29145](#), [29223](#)
- \int_rand:n
. [89](#), [245](#), [13040](#), [18991](#), [18994](#), [19241](#)
- \int_rand:nn [89](#), [245](#), [250](#), [824](#), [831](#),
[1025](#), [4942](#), [6221](#), [7258](#), [8324](#), [8329](#),
[10069](#), [18985](#), [18988](#), [19147](#), [25982](#)
- \int_range:nn [825](#)
- .int_set:N [172](#), [12508](#)
- \int_set:Nn [81](#), [308](#), [3131](#), [4248](#),
[4305](#), [6610](#), [10527](#), [10529](#), [10690](#),
[10692](#), [10707](#), [10717](#), [10730](#), [10777](#),
[10783](#), [10795](#), [10800](#), [12307](#), [19448](#),
[19450](#), [19452](#), [19475](#), [19476](#), [19491](#),
[19499](#), [19500](#), [19512](#), [19513](#), [19524](#),
[19525](#), [19526](#), [19542](#), [19545](#), [19927](#),
[19990](#), [20314](#), [21596](#), [21925](#), [21988](#),
[21990](#), [22071](#), [22126](#), [22127](#), [22140](#),
[22151](#), [22175](#), [22193](#), [22242](#), [22334](#),
[22353](#), [22387](#), [22408](#), [22504](#), [22539](#),
[23049](#), [23197](#), [23223](#), [23705](#), [23707](#),
[23715](#), [23716](#), [23717](#), [23718](#), [26087](#)
- \int_set_eq:NN
. [81](#), [6560](#), [19492](#), [19533](#), [20425](#),
[20893](#), [20897](#), [20906](#), [20908](#), [20951](#),
[21004](#), [21304](#), [21404](#), [21417](#), [21516](#),
[21947](#), [21964](#), [21965](#), [22011](#), [22012](#),
[22062](#), [22172](#), [22173](#), [22225](#), [22280](#),
[22336](#), [22339](#), [22360](#), [22367](#), [22384](#),
[22386](#), [22389](#), [22403](#), [22406](#), [22438](#),
[22439](#), [22443](#), [22579](#), [23155](#), [29122](#)
- \int_show:N [89](#), [7250](#)
- \int_show:n [90](#), [463](#), [1023](#), [7252](#)
- \int_sign:n [244](#), [1029](#), [25872](#)
- \int_step... [217](#)
- \int_step_function:nN [86](#), [6809](#), [26077](#)
- \int_step_function:nnN
. [86](#), [6809](#), [8601](#),
[8606](#), [8609](#), [10595](#), [19595](#), [22444](#), [23114](#)
- \int_step_function:nnnN [86](#), [248](#),
[249](#), [454](#), [714](#), [6809](#), [6891](#), [23226](#), [23234](#)
- \int_step_inline:nn
. [86](#), [629](#), [6861](#), [12937](#)
- \int_step_inline:nnn
. [86](#), [6861](#), [10411](#), [10604](#), [22378](#), [23574](#)
- \int_step_inline:nnnn [86](#), [716](#), [6861](#)
- \int_step_variable:nNn [86](#), [6861](#)
- \int_step_variable:nnNn [86](#), [6861](#)
- \int_step_variable:nnnnNn [86](#), [6861](#)
- \int_sub:Nn [81](#), [6578](#), [9481](#), [10992](#),
[20429](#), [21108](#), [22228](#), [22236](#), [22245](#)
- \int_to_Alph:n [87](#), [88](#), [6915](#)
- \int_to_alph:n [87](#), [87](#), [88](#), [6915](#)
- \int_to_arabic:n [87](#), [6894](#)
- \int_to_Base:n [88](#)
- \int_to_base:n [88](#)
- \int_to_Base:nn [88](#), [89](#), [6979](#), [7106](#)
- \int_to_base:nn
. [88](#), [89](#), [6979](#), [7102](#), [7104](#), [7108](#)
- \int_to_bin:n [88](#), [88](#), [88](#), [7101](#), [29433](#)
- \int_to_binary:n [29432](#)
- \int_to_Hex:n [88](#), [89](#), [7101](#), [20650](#)
- \int_to_hex:n [88](#), [89](#), [7101](#), [29435](#)
- \int_to_hexadecimal:n [29434](#)
- \int_to_oct:n [88](#), [89](#), [7101](#), [29437](#)
- \int_to_octal:n [29436](#)
- \int_to_Roman:n [88](#), [89](#), [7109](#)
- \int_to_roman:n [88](#), [89](#), [7109](#)

- \int_to_symbols:nnn
 87, 87, 6895, 6917, 6949
- \int_until_do:nn 85, 6753
- \int_until_do:nNnn 85, 6781
- \int_use:N 79, 82, 658,
 663, 4577, 4579, 5331, 5335, 6257,
 6263, 6618, 6870, 6881, 8160, 8162,
 9341, 9349, 9454, 10026, 10530,
 10544, 10686, 11648, 11655, 12308,
 15682, 15689, 20177, 20925, 20998,
 21069, 21080, 21089, 21093, 21104,
 21105, 21111, 21112, 21118, 21119,
 21287, 21907, 21981, 21983, 22001,
 22002, 22003, 22104, 22117, 22118,
 22490, 22540, 22570, 22680, 22692,
 22788, 23049, 23564, 26098, 26119,
 26121, 26185, 26194, 26195, 26198,
 26203, 26212, 26213, 26217, 26220,
 26225, 28213, 28378, 28409, 28424,
 28450, 28457, 28587, 28600, 28612,
 28614, 28649, 28748, 29009, 29040,
 29200, 29206, 29213, 29245, 29253
- \int_value:w
 91, 312, 312, 363, 448, 473,
 586, 628, 629, 637, 642, 646, 659,
 665, 672, 675, 681, 688, 712, 713,
 721, 729, 737, 799, 803, 816, 851,
 1022, 1025, 2367, 2723, 3676, 3678,
 4975, 4982, 5435, 5436, 5448, 5466,
 5473, 5496, 5497, 5498, 5510, 5546,
 6399, 6407, 6408, 6413, 6414, 6426,
 6427, 6428, 6439, 6440, 6441, 6460,
 6462, 6463, 6480, 6488, 6489, 6490,
 6497, 6639, 6643, 6673, 6827, 6828,
 6829, 6855, 7065, 7098, 7314, 7331,
 7382, 7392, 7504, 7507, 7630, 8484,
 8485, 10871, 10880, 11460, 11702,
 12953, 12955, 12981, 12982, 13026,
 13031, 13072, 13264, 13265, 13266,
 13267, 13268, 13282, 13430, 13491,
 13509, 13829, 13951, 13965, 13967,
 13969, 13972, 14008, 14147, 14177,
 14178, 14215, 14223, 14354, 14359,
 14361, 14370, 14374, 14411, 14419,
 14422, 14428, 14439, 14450, 14456,
 14457, 14460, 14503, 14513, 14515,
 14531, 14533, 14556, 14570, 14648,
 14650, 14724, 14812, 15478, 15511,
 15866, 15867, 15868, 15870, 15916,
 15919, 15922, 15945, 15947, 15968,
 15970, 15979, 15981, 15985, 16003,
 16010, 16016, 16026, 16028, 16042,
 16050, 16058, 16102, 16104, 16120,
 16122, 16125, 16128, 16182, 16190,
 16192, 16194, 16196, 16199, 16202,
 16204, 16223, 16225, 16229, 16235,
 16237, 16241, 16263, 16266, 16274,
 16276, 16279, 16280, 16281, 16282,
 16297, 16300, 16303, 16306, 16315,
 16318, 16321, 16324, 16331, 16333,
 16339, 16347, 16349, 16351, 16377,
 16379, 16388, 16390, 16394, 16411,
 16432, 16436, 16448, 16451, 16454,
 16457, 16460, 16463, 16466, 16469,
 16473, 16485, 16489, 16493, 16496,
 16517, 16519, 16521, 16531, 16555,
 16558, 16570, 16572, 16578, 16581,
 16598, 16618, 16668, 16673, 16675,
 16682, 16685, 16688, 16691, 16694,
 16697, 16706, 16718, 16726, 16728,
 16738, 16740, 16747, 16756, 16758,
 16761, 16764, 16767, 16770, 16783,
 16785, 16793, 16795, 16803, 16805,
 16815, 16818, 16821, 16828, 16843,
 16861, 16864, 16920, 16934, 16936,
 16942, 16955, 16957, 16959, 16983,
 16999, 17006, 17007, 17051, 17053,
 17054, 17055, 17096, 17098, 17133,
 17140, 17147, 17168, 17170, 17172,
 17174, 17187, 17191, 17192, 17193,
 17194, 17195, 17200, 17205, 17207,
 17213, 17230, 17231, 17232, 17233,
 17234, 17235, 17240, 17242, 17244,
 17246, 17248, 17253, 17255, 17257,
 17259, 17261, 17263, 17285, 17293,
 17309, 17314, 17318, 17377, 17426,
 17494, 17503, 17511, 17522, 17524,
 17527, 17530, 17619, 17655, 17657,
 17660, 17663, 17666, 17669, 17676,
 17679, 17681, 17685, 17707, 17709,
 17741, 17908, 17940, 17949, 18181,
 18182, 18193, 18196, 18199, 18202,
 18205, 18208, 18211, 18214, 18217,
 18235, 18245, 18254, 18272, 18281,
 18288, 18298, 18342, 18351, 18386,
 18429, 18446, 18502, 18513, 18524,
 18734, 18810, 18857, 18903, 18911,
 18913, 18915, 19012, 19035, 19089,
 19129, 19141, 19152, 19153, 19183,
 19186, 19189, 19191, 19193, 19200,
 19203, 19211, 19216, 19221, 19322,
 19382, 19389, 19401, 19402, 19403,
 19413, 19568, 19882, 19894, 20073,
 20115, 20117, 20127, 20135, 20154,
 20156, 20164, 20643, 21137, 21143,
 21175, 21177, 21186, 21187, 21311,
 21735, 21750, 22601, 22602, 22613,
 23138, 23169, 23171, 25378, 25876,

- 25877, 25982, 25992, 26129, 26141,
 26148, 26235, 27600, 27608, 28488
 \int_while_do:nn 85, [6753](#)
 \int_while_do:nNnn 85, [6781](#)
 \int_zero:N 80, 80, [6548](#),
 6555, 10837, 12299, 13018, 13045,
 13139, 19368, 19928, 19929, 19930,
 20029, 20905, 21106, 21553, 21860,
 21946, 22333, 22352, 22385, 22663,
 23043, 26074, 28357, 28556, 28695
 \int_zero_new:N 80, [6554](#)
 \c_max_int 90, 181, 631,
 824, 825, 872, 924, [7259](#), 19194,
 20400, 20414, 22439, 23693, 23699
 \c_nine [7274](#)
 \c_one [7274](#)
 \c_one_int 90,
 6596, 6599, 6602, 6605, [7258](#), 13072
 \c_seven [7274](#)
 \c_six [7274](#)
 \c_sixteen [7274](#)
 \c_ten [7274](#)
 \c_thirteen [7274](#)
 \c_three [7274](#)
 \g_tpa_int 90, [7270](#)
 \l_tpa_int 2, 90, 210, [7270](#)
 \g_tpb_int 90, [7270](#)
 \l_tpb_int 2, 90, [7270](#)
 \c_twelve [7274](#)
 \c_two [7274](#)
 \c_zero 465, [7274](#)
 \c_zero_int
 90, 315, 333, 333, 334, 1034,
 2100, 2721, 2723, 6498, 6499, 6516,
 6549, 6551, 6623, 6631, 6833, 6836,
[7258](#), 7683, 7685, 11508, 12938,
 13059, 19035, 19164, 19228, 26238
 int internal commands:
 __int_abs:N 6409
 __int_case:nnTF 6703
 __int_case:nw 6703
 __int_case_end:nw 6703
 __int_compare:nnN 449, 6636
 __int_compare:NNw ... 449, 449, 6636
 __int_compare:Nw ... 448, 449, 6636
 __int_compare:w 448, 6636
 __int_compare_!=:NNw 6636
 __int_compare_<:NNw 6636
 __int_compare_<=:NNw 6636
 __int_compare_=:NNw 6636
 __int_compare_==:NNw 6636
 __int_compare_>:NNw 6636
 __int_compare_>=:NNw 6636
 __int_compare_end=:NNw .. 449, 6636
 __int_compare_error:
 448, 448, 6621, 6639, 6641
 __int_compare_error:Nw
 448, 449, 450, 6621, 6661
 __int_constdef:Nw .. 465, 6510, 7310
 __int_deprecated_constants:nn [7274](#)
 __int_div_truncate:NwNw [6453](#)
 __int_eval:w 308,
 442, 443, 448, 6399, 6405, 6407,
 6408, 6410, 6414, 6421, 6422, 6427,
 6428, 6434, 6435, 6440, 6441, 6455,
 6456, 6460, 6462, 6463, 6480, 6483,
 6484, 6488, 6489, 6490, 6497, 6513,
 6532, 6575, 6580, 6583, 6586, 6589,
 6612, 6615, 6639, 6673, 6691, 6693,
 6697, 6734, 6737, 6744, 6747, 6812,
 6816, 6820, 6827, 6828, 6829, 6855,
 7038, 7065, 7071, 7098, 25873, 25877
 __int_eval_end:
 ... 6399, 6407, 6414, 6464, 6480,
 6491, 6500, 6532, 6580, 6583, 6586,
 6589, 6612, 6615, 6692, 6697, 6737,
 6747, 7038, 7065, 7071, 7098, 25877
 __int_from_alpha:N 461, [7155](#)
 __int_from_alpha:nN 461, [7155](#)
 __int_from_base:N 461, [7172](#)
 __int_from_base:nnN 461, [7172](#)
 __int_from_roman:NN [7214](#)
 \c__int_from_roman_C_int [7200](#)
 \c__int_from_roman_c_int [7200](#)
 \c__int_from_roman_D_int [7200](#)
 \c__int_from_roman_d_int [7200](#)
 __int_from_roman_error:w [7214](#)
 \c__int_from_roman_I_int [7200](#)
 \c__int_from_roman_i_int [7200](#)
 \c__int_from_roman_L_int [7200](#)
 \c__int_from_roman_l_int [7200](#)
 \c__int_from_roman_M_int [7200](#)
 \c__int_from_roman_m_int [7200](#)
 \c__int_from_roman_V_int [7200](#)
 \c__int_from_roman_v_int [7200](#)
 \c__int_from_roman_X_int [7200](#)
 \c__int_from_roman_x_int [7200](#)
 \c__int_max_constdef_int 6510
 __int_maxmin:wwN 6409
 __int_mod:ww 6453
 __int_pass_signs:wn
 460, 7145, 7159, 7176
 __int_pass_signs_end:wn 7145
 __int_show:nN 7250
 __int_sign:Nw 25872
 __int_step:NNnnnn 6861
 __int_step:NwnnN 6809
 __int_step:wwN 6809

- __int_tmp:w [446](#), [446](#), [6570](#),
[6578](#), [6581](#), [6584](#), [6587](#), [6610](#), [6613](#)
- __int_to_Base:nn [6979](#)
- __int_to_base:nn [6979](#)
- __int_to_Base:nnN [6979](#)
- __int_to_base:nnN [6979](#)
- __int_to_Base:nnnN [6979](#)
- __int_to_base:nnnN [6979](#)
- __int_to_Letter:n [6979](#)
- __int_to_letter:n [6979](#)
- __int_to_roman:N [7109](#)
- __int_to_roman:w
[449](#), [460](#), [2081](#), [6399](#), [6649](#), [7112](#), [7122](#)
- __int_to_Roman_aux:N [7121](#), [7124](#), [7127](#)
- __int_to_Roman_c:w [7109](#)
- __int_to_roman_c:w [7109](#)
- __int_to_Roman_d:w [7109](#)
- __int_to_roman_d:w [7109](#)
- __int_to_Roman_i:w [7109](#)
- __int_to_roman_i:w [7109](#)
- __int_to_Roman_l:w [7109](#)
- __int_to_roman_l:w [7109](#)
- __int_to_Roman_m:w [7109](#)
- __int_to_roman_m:w [7109](#)
- __int_to_Roman_Q:w [7109](#)
- __int_to_roman_Q:w [7109](#)
- __int_to_Roman_v:w [7109](#)
- __int_to_roman_v:w [7109](#)
- __int_to_Roman_x:w [7109](#)
- __int_to_roman_x:w [7109](#)
- __int_to_symbols:nnnn [6895](#)
- __int_value:w [7314](#)
- intarray commands:
 - \intarray_const_from_clist:Nn ...
..... [245](#), [630](#), [13041](#), [17432](#), [17964](#)
 - \intarray_count:N
[181](#), [181](#), [181](#), [12945](#), [12948](#), [12950](#),
[12951](#), [12953](#), [12962](#), [12973](#), [13019](#),
[13040](#), [13059](#), [13084](#), [13140](#), [19295](#)
 - \intarray_gset:Nnn [181](#), [628](#), [630](#), [12975](#)
 - \intarray_gset_rand:Nn ... [245](#), [13089](#)
 - \intarray_gset_rand:Nnn .. [245](#), [13089](#)
 - \intarray_gzero:N [181](#), [13016](#)
 - \intarray_item:Nn
..... [181](#), [628](#), [630](#), [13025](#), [13040](#)
 - \intarray_log:N [245](#), [13074](#)
 - \intarray_new:Nn
.... [181](#), [627](#), [630](#), [12931](#), [19287](#),
[19288](#), [19289](#), [20364](#), [20365](#), [20366](#),
[22316](#), [22317](#), [23019](#), [23020](#), [23021](#)
 - \intarray_rand_item:N ... [181](#), [13039](#)
 - \intarray_show:N [245](#), [630](#), [13074](#)
 - \intarray_to_clist:N [245](#), [13056](#)
- intarray internal commands:
 - __intarray_bounds:NNnTF
..... [12956](#), [12986](#), [13035](#)
 - __intarray_bounds_error:NNn . [12956](#)
 - __intarray_const_from_clist:nN .
..... [13041](#)
 - __intarray_count:w
.. [12924](#), [12944](#), [12953](#), [13048](#), [13067](#)
 - __intarray_entry:w
..... [12924](#), [12976](#), [13022](#), [13026](#)
 - \g__intarray_font_int
..... [12928](#), [12934](#), [12936](#)
 - __intarray_gset:Nnn [12975](#)
 - __intarray_gset:Nww .. [12979](#), [12984](#)
 - __intarray_gset_all_same:Nn . [13089](#)
 - __intarray_gset_overflow:Nnn . [12975](#)
 - __intarray_gset_overflow:NNnn ..
..... [12998](#), [13006](#), [13010](#)
 - __intarray_gset_overflow_-
test:nw [630](#), [631](#), [12988](#),
[12995](#), [13003](#), [13053](#), [13107](#), [13114](#)
 - __intarray_gset_rand:Nnn [13089](#)
 - __intarray_gset_rand_auxi:Nnnn .
..... [13089](#)
 - __intarray_gset_rand_auxii:Nnnn
..... [13089](#)
 - __intarray_gset_rand_auxiii:Nnnn
..... [13089](#)
 - __intarray_item:Nn [13025](#)
 - __intarray_item:Nw ... [13029](#), [13033](#)
 - \l__intarray_loop_int ... [12926](#),
[13018](#), [13021](#), [13022](#), [13045](#), [13048](#),
[13052](#), [13054](#), [13139](#), [13142](#), [13143](#)
 - __intarray_new:N [12931](#), [13044](#)
 - __intarray_show:NN
..... [13074](#), [13076](#), [13078](#)
 - __intarray_signed_max_dim:n ...
..... [12954](#), [13013](#), [13014](#)
 - \c__intarray_sp_dim
..... [12927](#), [12936](#), [12976](#)
 - __intarray_to_clist:Nn [13056](#), [13085](#)
 - __intarray_to_clist:w [13056](#)
 - \interactionmode [646](#), [1460](#)
 - \interlinepenalties [647](#), [1461](#)
 - \interlinepenalty [427](#)
 - ior commands:
 - \ior_close:N
.... [144](#), [145](#), [145](#), [10459](#), [10480](#),
[11146](#), [25354](#), [25387](#), [25424](#), [25441](#)
 - \ior_get:NN [146](#),
[146](#), [147](#), [151](#), [244](#), [10521](#), [10537](#), [10563](#)
 - \ior_get_str:NN [29438](#)
 - \ior_if_eof:N [560](#)

- \ior_if_eof:NTF 148, [10505](#), [10549](#), [10568](#), [11141](#), [11155](#)
- \ior_if_eof_p:N [148](#), [10505](#)
- \ior_list_streams: [29440](#)
- \ior_log_list: [145](#), [10492](#), [29443](#)
- \ior_log_streams: [29442](#)
- \ior_map_break: [147](#), [10532](#), [10550](#),
[10557](#), [10569](#), [10575](#), [25350](#), [25420](#)
- \ior_map_break:n [148](#), [10532](#)
- \ior_map_inline:Nn .. [147](#), [244](#), [10536](#)
- \ior_map_variable:NNn
..... [244](#), [10562](#), [25347](#)
- \ior_new:N
[144](#), [10425](#), [10427](#), [10428](#), [11033](#), [25306](#)
- \ior_open:Nn [144](#),
[578](#), [10429](#), [25330](#), [25355](#), [25388](#), [25440](#)
- \ior_open:NnTF [145](#), [10430](#), [10433](#)
- \ior_show_list: ... [145](#), [10492](#), [29441](#)
- \ior_str_get:NN
..... [146](#), [10523](#), [10539](#), [10565](#), [29439](#)
- \ior_str_map_inline:Nn
..... [147](#), [244](#), [10536](#), [25381](#), [25411](#)
- \ior_str_map_variable:NNn [244](#), [10562](#)
- \c_term_ior
[151](#), [10402](#), [10425](#), [10482](#), [10488](#), [10509](#)
- \g_tpa_ior [151](#), [10427](#)
- \g_tpb_ior [151](#), [10427](#)
- ior internal commands:
 - \l_ior_file_name_str
..... [10432](#), [10435](#), [10436](#), [10439](#)
 - \l_ior_internal_tl
..... [10401](#), [10555](#), [10559](#)
 - __ior_list:N [10492](#)
 - __ior_map_inline:NNn [10536](#)
 - __ior_map_inline:NNNn [10536](#)
 - __ior_map_inline_loop:NNN ... [10536](#)
 - __ior_map_variable:NNNn [10562](#)
 - __ior_map_variable_loop:NNNn . [10562](#)
 - __ior_new:N [557](#), [10444](#), [10467](#)
 - __ior_new_aux:N [10449](#), [10453](#)
 - __ior_open_stream:Nn [10457](#)
 - \l_ior_stream_tl
..... [10408](#), [10460](#), [10468](#), [10476](#)
 - \g__ior_streams_prop
..... [10409](#), [10477](#), [10485](#), [10499](#)
 - \g__ior_streams_seq
..... [10403](#), [10460](#), [10486](#), [10487](#)
- iorw commands:
 - \iorw_allow_break:
..... [150](#), [244](#), [10744](#), [10786](#), [10791](#)
 - \iorw_allow_break:n [567](#)
 - \iorw_char:N [149](#),
[2340](#), [10034](#), [10036](#), [10037](#), [10140](#),
[10161](#), [10162](#), [10705](#), [11094](#), [17538](#),
[19821](#), [19824](#), [19825](#), [19850](#), [19851](#),
[19858](#), [19859](#), [20629](#), [20631](#), [20633](#),
[20635](#), [20637](#), [20639](#), [21243](#), [21244](#),
[21784](#), [21897](#), [21898](#), [21899](#), [21920](#),
[23273](#), [23276](#), [23277](#), [23282](#), [23316](#),
[23325](#), [23329](#), [23334](#), [23354](#), [23356](#),
[23357](#), [23359](#), [23362](#), [23364](#), [23371](#),
[23375](#), [23378](#), [23379](#), [23382](#), [23384](#),
[23388](#), [23390](#), [23396](#), [23398](#), [23402](#),
[23404](#), [23408](#), [23413](#), [23415](#), [23457](#),
[23459](#), [23464](#), [23466](#), [23472](#), [23477](#),
[23482](#), [23486](#), [23496](#), [23499](#), [23503](#),
[23504](#), [23508](#), [23516](#), [23579](#), [29514](#)
 - \iorw_close:N .. [145](#), [145](#), [10630](#), [10652](#)
 - \iorw_indent:n
. [150](#), [150](#), [567](#), [568](#), [9975](#), [10083](#),
[10755](#), [10787](#), [10792](#), [13704](#), [13716](#)
 - \l_iorw_line_count_int
. [150](#), [150](#), [568](#), [865](#), [9481](#), [10706](#),
[10796](#), [10801](#), [10839](#), [20274](#), [20278](#)
 - \iorw_log:n [148](#), [309](#), [323](#), [2382](#),
[2831](#), [5069](#), [9695](#), [9710](#), [9711](#), [9717](#),
[10319](#), [10322](#), [10323](#), [10324](#), [10700](#)
 - \iorw_log_list: [145](#), [10664](#)
 - \iorw_new:N ... [144](#), [10618](#), [10620](#), [10621](#)
 - \iorw_newline:
..... [149](#), [149](#), [149](#), [150](#), [310](#),
[403](#), [534](#), [565](#), [9503](#), [10356](#), [10372](#),
[10374](#), [10704](#), [10784](#), [10793](#), [10799](#),
[11280](#), [20224](#), [21831](#), [25048](#), [25049](#),
[25050](#), [25922](#), [25924](#), [25927](#), [25934](#)
 - \iorw_now:Nn
.. [148](#), [148](#), [148](#), [149](#), [149](#), [10694](#),
[10700](#), [10701](#), [10702](#), [10703](#), [26305](#)
 - \iorw_open:Nn [145](#), [10627](#)
 - \iorw_shipout:Nn
..... [149](#), [149](#), [149](#), [565](#), [10679](#), [26318](#)
 - \iorw_shipout_x:Nn
..... [149](#), [149](#), [149](#), [565](#), [10676](#)
 - \iorw_show_list: [145](#), [10664](#)
 - \iorw_term:n . [148](#), [2831](#), [9515](#), [9673](#),
[9688](#), [9689](#), [9743](#), [10326](#), [10329](#),
[10330](#), [10331](#), [10370](#), [10700](#), [23565](#)
 - \iorw_wrap:nnnN
..... [149](#), [149](#), [150](#), [150](#), [150](#),
[244](#), [403](#), [568](#), [1023](#), [5054](#), [5069](#),
[9479](#), [9482](#), [9494](#), [9674](#), [9696](#), [9715](#),
[9722](#), [10323](#), [10330](#), [10348](#), [10349](#),
[10747](#), [10753](#), [10758](#), [10770](#), [10773](#)
 - \iorw_wrap:nnnN\iorw_wrap:nxnN .. [150](#)
 - \c_log_ior
[151](#), [561](#), [10581](#), [10654](#), [10700](#), [10701](#)
 - \c_term_ior
.. [151](#), [561](#), [10581](#), [10595](#), [10598](#),

- 10618, 10654, 10660, 10702, 10703
- \g_tmpa_iow 151, 10620
- \g_tmpb_iow 151, 10620
- iow internal commands:
 - __iow_allow_break: 567, 10744, 10786
 - __iow_allow_break_error: 567, 10744, 10791
 - \l__iow_file_name_str 10626, 10629, 10632, 10640
 - __iow_indent:n ... 567, 10755, 10787
 - __iow_indent_error:n 567, 10755, 10792
 - \l__iow_indent_int 10723, 10837, 10855, 10967, 10984, 10992
 - \l__iow_indent_tl .. 10723, 10838, 10854, 10966, 10985, 10993, 10994
 - \l__iow_line_break_bool 10727, 10833, 10961, 10975, 10983, 10991, 10999, 11001, 11006, 11008
 - \l__iow_line_part_tl 570, 572, 573, 10725, 10835, 10847, 10868, 10926, 10929, 10960, 10974, 10976, 10982, 10990, 11013
 - \l__iow_line_target_int 574, 10709, 10795, 10797, 10800, 10962, 10967, 11002
 - \l__iow_line_tl 10725, 10834, 10851, 10941, 10957, 10973, 10974, 10982, 10990, 11012, 11013, 11018, 11020
 - __iow_list:N 10664
 - __iow_new:N 10622, 10638
 - \l__iow_newline_tl 10708, 10793, 10794, 10796, 10799, 11017
 - \l__iow_one_indent_int 10710, 10984, 10992
 - \l__iow_one_indent_tl 566, 10710, 10985
 - __iow_open_stream:Nn 10627
 - __iow_set_indent:n 566, 10710
 - \l__iow_stream_tl 10601, 10631, 10639, 10647
 - \g__iow_streams_prop 10602, 10648, 10657, 10671
 - \g__iow_streams_seq 10590, 10631, 10658, 10659
 - __iow_tmp:w 572, 10841, 10865, 10922, 10954, 11022, 11030
 - __iow_unindent:w .. 566, 10710, 10994
 - __iow_with:nNnn 10682
 - __iow_wrap_allow_break:n 10971
 - \c__iow_wrap_allow_break_marker_tl 10729, 10749
 - __iow_wrap_break:w ... 10908, 10922
 - __iow_wrap_break_end:w .. 572, 10922
 - __iow_wrap_break_first:w 10922
 - __iow_wrap_break_loop:w 10922
 - __iow_wrap_break_none:w 10922
 - __iow_wrap_chunk:nw 10839, 10841, 10977, 10978, 10986, 10995, 11002
 - __iow_wrap_do: 10803, 10808
 - __iow_wrap_end:n 10997
 - __iow_wrap_end_chunk:w 570, 10859, 10866, 10958
 - \c__iow_wrap_end_marker_tl 10729, 10813
 - __iow_wrap_fix_newline:w 10808
 - __iow_wrap_indent:n 10980
 - \c__iow_wrap_indent_marker_tl ... 10729, 10763
 - __iow_wrap_line:nw 570, 572, 10853, 10857, 10866, 10965
 - __iow_wrap_line_aux:Nw 10866
 - __iow_wrap_line_end:NnnnnnnN 10866
 - __iow_wrap_line_end:nw 572, 10866, 10942, 10943, 10952
 - __iow_wrap_line_loop:w 10866
 - __iow_wrap_line_seven:nnnnnnn 10866
 - \c__iow_wrap_marker_tl 566, 569, 10729, 10865
 - __iow_wrap_newline:n 10997
 - \c__iow_wrap_newline_marker_tl .. 569, 10729, 10828
 - __iow_wrap_next:nw 10841, 10920, 10962
 - __iow_wrap_next_line:w 10914, 10955
 - __iow_wrap_start:w 10808
 - __iow_wrap_store_do:n 10913, 11000, 11007, 11010
 - \l__iow_wrap_tl 568, 569, 574, 574, 10728, 10790, 10805, 10810, 10812, 10815, 10817, 10820, 10836, 11014, 11016
 - __iow_wrap_trim:N 574, 10943, 10974, 11000, 11007, 11022
 - __iow_wrap_trim:w 11022
 - __iow_wrap_trim_aux:w 11022
 - __iow_wrap_unindent:n 10980
 - \c__iow_wrap_unindent_marker_tl . 10729, 10765
- J
- \J 204
- \j 27407
- \jcharwidowpenalty 1226, 2008
- \jfam 1227, 2009
- \jfont 1228, 2010
- \jis 1229, 2011

job commands:

\c_job_name_tl 29404
 \jobname 428

K

\k 27411
 \kanjiskip 1230, 2012
 \kansuji 1231, 2013
 \kansujichar 1232, 2014
 \kcatcode 1233, 2015
 \kchar 1254, 2036
 \kchardef 1255, 2037
 \kern 429

kernel internal commands:

__kernel_chk_cs_exist:N ... 308,
 320, 2259, 2697, 2701, 2705, 2709, 3756
 __kernel_chk_defined:NTF
 308, 499,
 530, 3095, 3114, 5050, 6384, 7343,
 7456, 8338, 9363, 13080, 15401, 22973
 __kernel_chk_expr:nNnN
 308, 322, 2346,
 6405, 6410, 6421, 6422, 6434, 6435,
 6455, 6456, 6483, 6484, 6513, 6575,
 6691, 6693, 6734, 6744, 6812, 6816,
 6820, 11373, 11415, 11425, 11426,
 11438, 11439, 11463, 11465, 11601,
 11605, 11609, 11669, 11676, 11697,
 11762, 11804, 11818, 11828, 11838,
 11901, 11940, 23591, 25873, 26145
 __kernel_chk_if_free_cs:N
 506, 531, 2835, 2855, 2903,
 4057, 4064, 4070, 5729, 5859, 6505,
 6528, 8627, 8629, 8639, 9066, 11339,
 11729, 11863, 12933, 23600, 25942
 __kernel_chk_var_exist:N
 .. 308, 308, 320, 467, 2259, 4092,
 4098, 4110, 4111, 4118, 4119, 7324
 __kernel_chk_var_global:N
 308, 320,
 2259, 4097, 4148, 4151, 4154, 4175,
 4178, 4181, 4184, 4207, 4210, 4213,
 4216, 6550, 6563, 6584, 6587, 6600,
 6603, 6613, 7407, 7410, 7427, 11353,
 11379, 11388, 11395, 11406, 11743,
 11768, 11780, 11788, 11878, 11910,
 11918, 11924, 11932, 23620, 23628,
 23682, 23736, 23750, 23765, 23787,
 23834, 23848, 23862, 23877, 23900,
 23917, 27473, 27501, 27507, 27537
 __kernel_chk_var_local:N
 308, 320,
 2259, 4091, 4139, 4142, 4145, 4163,
 4166, 4169, 4172, 4195, 4198, 4201,

4204, 6548, 6560, 6578, 6581, 6594,
 6597, 6610, 7401, 7404, 7421, 11351,
 11376, 11384, 11392, 11403, 11741,
 11765, 11777, 11785, 11875, 11907,
 11915, 11921, 11929, 23617, 23625,
 23679, 23730, 23744, 23758, 23780,
 23828, 23842, 23856, 23870, 23893,
 23913, 27470, 27489, 27495, 27533
 __kernel_chk_var_scope:NN
 308, 308, 320, 2259,
 4061, 4067, 5726, 5829, 6511, 11344,
 11734, 11868, 12940, 13041, 25939
 __kernel_cs_parm_from_arg_-
 count:nnTF .. 308, 2552, 2921, 2968
 __kernel_debug_log:n
 309, 323, 2377, 2837, 3933, 9386, 12316
 __kernel_deprecation_code:nn ...
 309, 2393, 7301, 29501
 __kernel_deprecation_error:Nnn ..
 . 465, 2433, 2454, 7304, 29384, 29512
 __kernel_exp_not:w
 309, 357, 3489, 3491,
 3495, 3499, 3502, 3505, 3510, 4748,
 4774, 4798, 6654, 8570, 26338, 26571
 \l__kernel_expl_bool
 241, 244, 259, 273, 2048
 __kernel_file_input_pop: 309, 11170
 __kernel_file_input_push:n
 309, 11170
 __kernel_file_missing:n
 309, 10430, 11164, 11174, 26386, 26419
 __kernel_file_name_sanitize:nN ..
 309, 309, 10629, 11089, 11120, 11166
 __kernel_if_debug:TF
 309, 2179, 2185, 2236, 2259,
 2316, 2346, 2377, 2393, 2410, 2465,
 2484, 4087, 7350, 10156, 23555, 23570
 __kernel_int_add:nnn 309, 6495, 19194
 __kernel_intarray_gset:Nnn 628,
 12938, 12951, 12975, 13054, 13143,
 19355, 19356, 19358, 19362, 19363,
 19364, 22381, 22465, 22467, 22469,
 22495, 22498, 22553, 23076, 23078,
 23084, 23092, 23094, 23097, 23158,
 23160, 23162, 23175, 23181, 23185
 __kernel_intarray_item:Nn
 629, 799, 13025, 13070,
 17518, 17524, 17527, 17530, 18194,
 18197, 18200, 18203, 18206, 18209,
 18212, 18215, 18218, 19401, 19402,
 19403, 22460, 22481, 22484, 22506,
 22533, 22594, 22595, 22618, 22619,
 22627, 22633, 22635, 22642, 22648,
 22650, 22707, 22711, 23081, 23208

- __kernel_ior_open:Nn
 [310](#), [10439](#), [10457](#), [11139](#), [11154](#)
- __kernel_iow_with:Nnn . [310](#), [403](#),
 [534](#), [564](#), [5058](#), [5060](#), [9516](#), [9518](#),
 [9745](#), [9747](#), [10377](#), [10379](#), [10682](#), [10696](#)
- __kernel_msg_error:nn
 [310](#), [2812](#), [9935](#), [12079](#),
 [12098](#), [20885](#), [20918](#), [20966](#), [20969](#),
 [21430](#), [21686](#), [22841](#), [22925](#), [24545](#)
- __kernel_msg_error:nnnn
 [310](#), [2192](#), [2200](#), [2227](#), [2232](#),
 [2268](#), [2277](#), [2420](#), [2565](#), [2620](#), [2668](#),
 [2673](#), [2812](#), [3005](#), [3012](#), [3100](#), [3798](#),
 [3992](#), [4348](#), [5144](#), [5834](#), [9758](#), [9935](#),
 [11109](#), [11167](#), [12180](#), [12239](#), [12255](#),
 [12401](#), [12419](#), [12947](#), [13150](#), [13171](#),
 [13584](#), [19282](#), [19815](#), [20924](#), [21126](#),
 [21529](#), [21542](#), [21581](#), [21704](#), [22679](#),
 [22686](#), [22939](#), [23723](#), [24277](#), [25143](#),
 [25836](#), [26068](#), [26105](#), [26249](#), [26444](#)
- __kernel_msg_error:nnnn
 [310](#), [2556](#),
 [2596](#), [2687](#), [2812](#), [2844](#), [2970](#), [3884](#),
 [4012](#), [4035](#), [9393](#), [9784](#), [9935](#), [10746](#),
 [12164](#), [12219](#), [12274](#), [12288](#), [12410](#),
 [12791](#), [13580](#), [19677](#), [19684](#), [21103](#),
 [21168](#), [21392](#), [22845](#), [22861](#), [24424](#)
- __kernel_msg_error:nnnnnn
 ... [310](#), [2339](#), [9935](#), [10757](#), [12986](#),
 [19327](#), [19832](#), [23125](#), [23248](#), [29391](#)
- __kernel_msg_error:nnnnnn
 [310](#), [3899](#), [3913](#), [9935](#), [13012](#)
- __kernel_msg_expandable_
 error:nn [311](#),
 [3519](#), [5850](#), [7661](#), [8491](#), [8493](#), [8501](#),
 [8507](#), [8549](#), [9061](#), [10286](#), [14103](#), [20624](#)
- __kernel_msg_expandable_
 error:nnn
 [311](#), [3214](#), [3591](#), [3614](#), [3638](#),
 [4614](#), [6327](#), [6632](#), [6838](#), [7356](#), [8246](#),
 [9140](#), [10286](#), [11627](#), [14110](#), [14126](#),
 [14131](#), [14198](#), [14255](#), [14294](#), [14300](#),
 [14637](#), [14642](#), [14653](#), [14660](#), [14751](#),
 [14765](#), [14965](#), [14991](#), [15649](#), [18980](#),
 [18987](#), [18993](#), [20710](#), [25134](#), [26236](#)
- __kernel_msg_expandable_
 error:nnnn [311](#),
 [2370](#), [10286](#), [10752](#), [13102](#), [15123](#),
 [15144](#), [15810](#), [19159](#), [19249](#), [20649](#)
- __kernel_msg_expandable_
 error:nnnnnn . [311](#), [10286](#), [10769](#),
 [13035](#), [13695](#), [19026](#), [19394](#), [29388](#)
- __kernel_msg_expandable_
 error:nnnnnn [311](#), [10286](#)
- __kernel_msg_fatal:nn
 [310](#), [9935](#), [10463](#), [10634](#)
- __kernel_msg_fatal:nnn ... [310](#), [9935](#)
- __kernel_msg_fatal:nnnn ... [310](#), [9935](#)
- __kernel_msg_fatal:nnnnn . [310](#), [9935](#)
- __kernel_msg_fatal:nnnnnn [310](#), [9935](#)
- __kernel_msg_info:nn [311](#), [9940](#)
- __kernel_msg_info:nnn [311](#), [9940](#)
- __kernel_msg_info:nnnn ... [311](#), [9940](#)
- __kernel_msg_info:nnnnn . [311](#), [9940](#)
- __kernel_msg_info:nnnnnn . [311](#), [9940](#)
- __kernel_msg_new:nnn
 [310](#), [9889](#), [9985](#), [9987](#), [9989](#),
 [9991](#), [9993](#), [10011](#), [10068](#), [10144](#),
 [10165](#), [10214](#), [10216](#), [10218](#), [10220](#),
 [10222](#), [10224](#), [10226](#), [10228](#), [10232](#),
 [10235](#), [10242](#), [10244](#), [10251](#), [10258](#),
 [11298](#), [12914](#), [12929](#), [13723](#), [13725](#),
 [13727](#), [13729](#), [13731](#), [13733](#), [13735](#),
 [15321](#), [15323](#), [15325](#), [15327](#), [15329](#),
 [15331](#), [15333](#), [15335](#), [15337](#), [15339](#),
 [15341](#), [15343](#), [15345](#), [15347](#), [15352](#),
 [15702](#), [15704](#), [15706](#), [18976](#), [20288](#),
 [23272](#), [23274](#), [23279](#), [23533](#), [25076](#)
- __kernel_msg_new:nnnn . [310](#), [9889](#),
 [9943](#), [9951](#), [9959](#), [9966](#), [9977](#), [9995](#),
 [10004](#), [10016](#), [10023](#), [10030](#), [10039](#),
 [10048](#), [10055](#), [10061](#), [10070](#), [10077](#),
 [10086](#), [10092](#), [10099](#), [10106](#), [10113](#),
 [10120](#), [10128](#), [10136](#), [10158](#), [10166](#),
 [10179](#), [10192](#), [10204](#), [11292](#), [11304](#),
 [11311](#), [11318](#), [11323](#), [12107](#), [12881](#),
 [12884](#), [12890](#), [12896](#), [12902](#), [12908](#),
 [13557](#), [13697](#), [13712](#), [19820](#), [19838](#),
 [19845](#), [19854](#), [23285](#), [23292](#), [23298](#),
 [23308](#), [23314](#), [23338](#), [23345](#), [23353](#),
 [23361](#), [23368](#), [23374](#), [23381](#), [23387](#),
 [23395](#), [23401](#), [23407](#), [23417](#), [23424](#),
 [23433](#), [23436](#), [23444](#), [23450](#), [23456](#),
 [23463](#), [23470](#), [23480](#), [23491](#), [23501](#),
 [23511](#), [23520](#), [23526](#), [25060](#), [25067](#),
 [25070](#), [25148](#), [25842](#), [26093](#), [26451](#)
- __kernel_msg_set:nnn [310](#), [9889](#)
- __kernel_msg_set:nnnn [310](#), [9889](#)
- __kernel_msg_warning:nn
 [311](#), [9940](#), [21420](#)
- __kernel_msg_warning:nnn
 [311](#), [9940](#), [21336](#),
 [21340](#), [21382](#), [21444](#), [21482](#), [21501](#)
- __kernel_msg_warning:nnnn
 [311](#), [9940](#), [21033](#), [21182](#)
- __kernel_msg_warning:nnnnnn
 [311](#), [2442](#), [9940](#)

- __kernel_msg_warning:nnnnnn . . . 11652, 11655, 11666, 15679, 15682, 15686, 15689, 15700, 20175, 20177, 20197, 26117, 26119, 26121, 26123
- __kernel_patch:nnNNpn 311, 311, 312, 312, 312, 325, 326, 376, 2465, 2696, 2700, 2704, 2708, 2835, 3756, 3929, 4061, 4067, 4108, 4116, 4139, 4142, 4145, 4148, 4151, 4154, 4163, 4166, 4169, 4172, 4175, 4178, 4181, 4184, 4195, 4198, 4201, 4204, 4207, 4210, 4213, 4216, 5726, 5829, 6548, 6550, 6560, 6563, 6594, 6597, 6600, 6603, 7323, 7377, 7401, 7404, 7407, 7410, 7421, 7427, 9384, 11344, 11351, 11353, 11384, 11388, 11734, 11741, 11743, 11868, 11875, 11878, 11915, 11918, 12313, 12940, 13041, 20577, 21937, 21956, 21996, 22080, 22133, 22325, 22344, 22372, 22487, 22656, 23617, 23620, 23625, 23628, 23679, 23682, 23730, 23736, 23744, 23750, 23758, 23765, 23780, 23787, 23828, 23834, 23842, 23848, 23856, 23862, 23870, 23877, 23893, 23900, 23913, 23917, 25863, 25939, 27470, 27473, 27489, 27495, 27501, 27507, 27533, 27537
- __kernel_patch_args:nnnNNpn 312, 2480, 6510, 6572, 11370, 11759, 11895
- __kernel_patch_args:nNNpn 312, 312, 2480, 6404, 6409, 6419, 6432, 6453, 6481, 6809, 11414, 11423, 11436, 11598, 11668, 11675, 11694, 11817, 11825, 11835, 11937, 18897, 23588, 25872, 26144
- __kernel_patch_conditional:nNNpnn 311, 325, 2465, 7368
- __kernel_patch_conditional_-args:nnnNNpnn 312, 2480
- __kernel_patch_conditional_-args:nNNpnn 312, 2480, 6689, 6733, 6743, 11461, 11801
- __kernel_patch_deprecation:nnNNpn 312, 323, 324, 2410, 5707, 5709, 5711, 5713, 5715, 5717, 5719, 5721, 7688, 7690, 7692, 7695, 7697, 10319, 10326, 10333, 20295, 20299, 25154, 25156, 25158
- \g__kernel_prg_map_int . 312, 389, 454, 590, 863, 2048, 4575, 4577, 4579, 4582, 5329, 5331, 5335, 5340, 6256, 6257, 6263, 6264, 6867, 6870, 6878, 6881, 6892, 7687, 8158, 8160, 8162, 8165, 9341, 9342, 9347, 9349, 10542, 10544, 10551, 11645, 11648, 11652, 11655, 11666, 15679, 15682, 15686, 15689, 15700, 20175, 20177, 20197, 26117, 26119, 26121, 26123
- __kernel_primitive:NN 273, 281, 290, 291, 292, 293, 294, 295, 296, 297, 298, 299, 300, 301, 302, 303, 304, 305, 306, 307, 308, 309, 310, 311, 312, 313, 314, 315, 316, 317, 318, 319, 320, 321, 322, 323, 324, 325, 326, 327, 328, 329, 330, 331, 332, 333, 334, 335, 336, 337, 338, 339, 340, 341, 342, 343, 344, 345, 346, 347, 348, 349, 350, 351, 352, 353, 354, 355, 356, 357, 358, 359, 360, 361, 362, 363, 364, 365, 366, 367, 368, 369, 370, 371, 372, 373, 374, 375, 376, 377, 378, 379, 380, 381, 382, 383, 384, 385, 386, 387, 388, 389, 390, 391, 392, 393, 394, 395, 396, 397, 398, 399, 400, 401, 402, 403, 404, 405, 406, 407, 408, 409, 410, 411, 412, 413, 414, 415, 416, 417, 418, 419, 420, 421, 422, 423, 424, 425, 426, 427, 428, 429, 430, 431, 432, 433, 434, 435, 436, 437, 438, 439, 440, 441, 442, 443, 444, 445, 446, 447, 448, 449, 450, 451, 452, 453, 454, 455, 456, 457, 458, 459, 460, 461, 462, 463, 464, 465, 466, 467, 468, 469, 470, 471, 472, 473, 474, 475, 476, 477, 478, 479, 480, 481, 482, 483, 484, 485, 486, 487, 488, 489, 490, 491, 492, 493, 494, 495, 496, 497, 498, 499, 500, 501, 502, 503, 504, 505, 506, 507, 508, 509, 510, 511, 512, 513, 514, 515, 516, 517, 518, 519, 520, 521, 522, 523, 524, 525, 526, 527, 528, 529, 530, 531, 532, 533, 534, 535, 536, 537, 538, 539, 540, 541, 542, 543, 544, 545, 546, 547, 548, 549, 550, 551, 552, 553, 554, 555, 556, 557, 558, 559, 560, 561, 562, 563, 564, 565, 566, 567, 568, 569, 570, 571, 572, 573, 574, 575, 576, 577, 578, 579, 580, 581, 582, 583, 584, 585, 586, 587, 588, 589, 590, 591, 592, 593, 594, 595, 596, 597, 598, 599, 600, 601, 602, 603, 604, 605, 606, 607, 608, 609, 610, 611, 612, 613, 614, 615, 616, 617, 618, 619, 620, 621, 622, 623, 624, 625, 626, 627, 628, 629, 630, 631, 632, 633, 634, 635, 636, 637, 638,

639, 640, 641, 642, 643, 644, 645,
646, 647, 648, 649, 650, 651, 652,
653, 654, 655, 656, 657, 658, 659,
660, 661, 662, 663, 664, 665, 666,
667, 668, 669, 670, 671, 672, 673,
674, 675, 676, 677, 678, 679, 680,
681, 682, 683, 684, 685, 686, 687,
688, 689, 690, 691, 692, 693, 694,
695, 696, 697, 698, 699, 700, 701,
702, 703, 704, 705, 707, 708, 709,
710, 711, 712, 713, 715, 716, 717,
718, 719, 720, 721, 722, 723, 724,
725, 726, 727, 728, 729, 730, 731,
732, 733, 734, 735, 736, 737, 738,
739, 740, 741, 742, 743, 744, 745,
746, 747, 748, 749, 750, 751, 752,
753, 754, 755, 756, 757, 758, 759,
760, 761, 762, 763, 764, 765, 766,
767, 768, 769, 770, 771, 772, 773,
774, 775, 776, 777, 778, 779, 780,
781, 782, 783, 784, 785, 786, 787,
788, 789, 790, 791, 792, 793, 794,
795, 796, 797, 798, 799, 800, 801,
802, 807, 819, 821, 822, 823, 824,
825, 826, 827, 828, 829, 830, 831,
833, 835, 837, 838, 839, 841, 842,
843, 844, 845, 846, 848, 850, 851,
853, 855, 856, 857, 858, 859, 860,
861, 862, 863, 864, 865, 866, 867,
868, 869, 870, 871, 872, 873, 874,
875, 876, 877, 878, 879, 880, 881,
882, 883, 884, 885, 886, 887, 888,
889, 890, 891, 892, 893, 895, 896,
898, 899, 900, 901, 902, 903, 904,
905, 906, 907, 909, 910, 911, 912,
913, 914, 915, 916, 917, 918, 919,
920, 921, 922, 923, 924, 925, 926,
927, 928, 929, 930, 931, 932, 933,
934, 935, 936, 937, 938, 939, 940,
941, 942, 943, 944, 945, 946, 947,
948, 949, 950, 951, 952, 953, 954,
955, 956, 957, 958, 959, 960, 961,
962, 963, 964, 965, 966, 967, 968,
969, 970, 971, 972, 973, 974, 975,
976, 977, 978, 979, 980, 981, 982,
983, 984, 985, 986, 987, 988, 989,
990, 991, 992, 993, 994, 995, 996,
997, 998, 999, 1000, 1001, 1002,
1003, 1004, 1006, 1007, 1008, 1009,
1010, 1011, 1012, 1013, 1014, 1015,
1016, 1017, 1018, 1019, 1020, 1022,
1024, 1026, 1027, 1028, 1029, 1030,
1031, 1032, 1033, 1034, 1035, 1036,
1037, 1038, 1039, 1040, 1041, 1042,
1043, 1044, 1045, 1046, 1047, 1048,
1049, 1050, 1051, 1052, 1053, 1054,
1055, 1056, 1057, 1058, 1059, 1060,
1061, 1062, 1063, 1064, 1065, 1066,
1067, 1068, 1069, 1071, 1073, 1074,
1075, 1076, 1078, 1079, 1080, 1081,
1083, 1084, 1086, 1088, 1089, 1090,
1091, 1092, 1094, 1096, 1097, 1098,
1099, 1101, 1102, 1103, 1104, 1105,
1106, 1107, 1108, 1109, 1110, 1111,
1112, 1112, 1113, 1114, 1115, 1116,
1117, 1118, 1119, 1120, 1121, 1122,
1123, 1124, 1125, 1126, 1127, 1128,
1129, 1130, 1131, 1132, 1133, 1134,
1135, 1136, 1137, 1138, 1140, 1142,
1143, 1145, 1147, 1148, 1149, 1150,
1152, 1153, 1154, 1156, 1158, 1160,
1161, 1162, 1163, 1164, 1165, 1166,
1167, 1168, 1169, 1170, 1171, 1173,
1175, 1176, 1177, 1178, 1179, 1180,
1181, 1182, 1183, 1184, 1185, 1186,
1187, 1188, 1189, 1190, 1191, 1193,
1195, 1196, 1197, 1198, 1199, 1200,
1201, 1202, 1203, 1204, 1205, 1206,
1207, 1208, 1209, 1210, 1211, 1212,
1213, 1214, 1215, 1216, 1217, 1218,
1219, 1220, 1221, 1222, 1223, 1224,
1225, 1226, 1227, 1228, 1229, 1230,
1231, 1232, 1233, 1234, 1235, 1236,
1237, 1238, 1239, 1240, 1241, 1242,
1243, 1244, 1245, 1246, 1247, 1248,
1249, 1250, 1251, 1252, 1253, 1254,
1255, 1256, 1257, 1258, 1259, 1417,
1428, 1429, 1430, 1431, 1432, 1433,
1434, 1435, 1436, 1437, 1438, 1439,
1441, 1442, 1443, 1444, 1445, 1446,
1447, 1448, 1449, 1450, 1451, 1452,
1453, 1454, 1455, 1456, 1457, 1458,
1459, 1460, 1461, 1462, 1463, 1464,
1465, 1466, 1467, 1468, 1469, 1470,
1471, 1472, 1473, 1474, 1475, 1476,
1477, 1478, 1479, 1480, 1481, 1482,
1483, 1484, 1485, 1486, 1487, 1488,
1489, 1490, 1491, 1492, 1493, 1494,
1495, 1496, 1497, 1498, 1499, 1500,
1501, 1502, 1503, 1504, 1505, 1506,
1507, 1508, 1509, 1510, 1511, 1512,
1513, 1514, 1515, 1516, 1517, 1518,
1520, 1522, 1523, 1524, 1525, 1526,
1527, 1528, 1530, 1531, 1532, 1533,
1534, 1535, 1536, 1538, 1539, 1540,
1541, 1542, 1543, 1544, 1545, 1546,
1547, 1548, 1549, 1550, 1551, 1552,
1553, 1554, 1556, 1557, 1558, 1559,

1560, 1561, 1562, 1563, 1564, 1565,
 1566, 1567, 1568, 1569, 1570, 1571,
 1572, 1573, 1574, 1575, 1576, 1577,
 1578, 1579, 1580, 1581, 1582, 1583,
 1584, 1585, 1586, 1587, 1588, 1589,
 1590, 1591, 1592, 1593, 1594, 1595,
 1596, 1597, 1598, 1599, 1600, 1601,
 1602, 1603, 1604, 1605, 1606, 1607,
 1608, 1609, 1610, 1611, 1612, 1613,
 1614, 1615, 1616, 1617, 1618, 1619,
 1620, 1621, 1622, 1623, 1624, 1625,
 1626, 1627, 1629, 1630, 1632, 1634,
 1636, 1637, 1638, 1639, 1640, 1641,
 1642, 1643, 1644, 1645, 1646, 1647,
 1648, 1649, 1650, 1651, 1652, 1653,
 1655, 1656, 1657, 1658, 1659, 1660,
 1661, 1662, 1663, 1664, 1665, 1667,
 1669, 1671, 1672, 1673, 1675, 1676,
 1677, 1678, 1679, 1680, 1682, 1684,
 1685, 1687, 1689, 1690, 1691, 1692,
 1693, 1694, 1695, 1696, 1697, 1698,
 1699, 1700, 1701, 1702, 1703, 1704,
 1705, 1706, 1707, 1708, 1709, 1710,
 1711, 1712, 1713, 1714, 1715, 1716,
 1717, 1719, 1721, 1723, 1724, 1725,
 1726, 1727, 1729, 1731, 1732, 1733,
 1734, 1735, 1736, 1737, 1738, 1739,
 1741, 1742, 1744, 1745, 1746, 1747,
 1748, 1749, 1750, 1751, 1752, 1753,
 1754, 1755, 1756, 1757, 1758, 1759,
 1760, 1761, 1762, 1763, 1765, 1766,
 1767, 1768, 1769, 1770, 1771, 1772,
 1773, 1774, 1775, 1776, 1777, 1778,
 1779, 1780, 1781, 1782, 1783, 1784,
 1785, 1786, 1787, 1788, 1789, 1790,
 1791, 1793, 1794, 1795, 1796, 1797,
 1798, 1799, 1800, 1802, 1803, 1805,
 1806, 1808, 1809, 1810, 1811, 1812,
 1813, 1814, 1815, 1816, 1817, 1819,
 1820, 1821, 1822, 1823, 1824, 1825,
 1826, 1827, 1828, 1829, 1830, 1831,
 1832, 1833, 1834, 1835, 1836, 1837,
 1838, 1839, 1840, 1841, 1842, 1843,
 1844, 1845, 1846, 1847, 1848, 1849,
 1850, 1851, 1852, 1854, 1856, 1857,
 1858, 1859, 1861, 1862, 1863, 1864,
 1866, 1867, 1869, 1871, 1872, 1873,
 1874, 1875, 1877, 1879, 1880, 1881,
 1882, 1884, 1885, 1886, 1887, 1888,
 1889, 1890, 1891, 1892, 1893, 1894,
 1895, 1896, 1897, 1898, 1899, 1900,
 1901, 1902, 1903, 1904, 1905, 1906,
 1907, 1908, 1909, 1910, 1911, 1912,
 1913, 1914, 1915, 1916, 1917, 1918,
 1919, 1920, 1921, 1923, 1925, 1926,
 1928, 1930, 1931, 1932, 1933, 1934,
 1935, 1936, 1938, 1940, 1942, 1943,
 1944, 1945, 1946, 1947, 1948, 1949,
 1950, 1951, 1952, 1953, 1955, 1957,
 1958, 1959, 1960, 1961, 1962, 1963,
 1964, 1965, 1966, 1967, 1968, 1969,
 1970, 1971, 1972, 1973, 1975, 1977,
 1978, 1979, 1980, 1981, 1982, 1983,
 1984, 1985, 1986, 1987, 1988, 1989,
 1990, 1991, 1992, 1993, 1994, 1995,
 1996, 1997, 1998, 1999, 2000, 2001,
 2002, 2003, 2004, 2005, 2006, 2007,
 2008, 2009, 2010, 2011, 2012, 2013,
 2014, 2015, 2016, 2017, 2018, 2019,
 2020, 2021, 2022, 2023, 2024, 2025,
 2026, 2027, 2028, 2029, 2030, 2031,
 2032, 2033, 2034, 2035, 2036, 2037,
 2038, 2039, 2040, 2041, 29503, 29528
 __kernel_primitives:
 . 296, 1112, 1424, 2044, 29525, 29543
 __kernel_randint:n
 312, 312, 312, 631, 825,
 829, 13133, 19001, 19013, 19171, 19256
 __kernel_randint:nn
 312, 631, 13129, 19175, 19179, 19254
 \c__kernel_randint_max_int
 829, 2048, 13126, 19000, 19169, 19253
 __kernel_register_log:N
 313, 3104, 7254, 11715,
 11716, 11850, 11851, 11952, 11953
 __kernel_register_show:N
 313, 313,
 403, 3104, 7250, 11711, 11846, 11948
 __kernel_register_show_aux:NN 3104
 __kernel_register_show_aux:nNN 3104
 __kernel_show:NN 3122
 __kernel_str_to_other:n ... 313,
 313, 410, 412, 416, 5375, 5427, 5488
 __kernel_str_to_other_fast:n ...
 313, 5336,
 5356, 5398, 10716, 10812, 20595, 21723
 __kernel_str_to_other_fast_-
 loop:w 5398
 __kernel_tl_to_str:w
 . 313, 388, 2074, 4447, 4518, 4608,
 4785, 5207, 5311, 5825, 12067, 12090
 keys commands:
 \l_keys_choice_int
 170, 172, 174, 174,
 175, 12121, 12299, 12302, 12307, 12308
 \l_keys_choice_tl
 170, 172, 174, 175, 12121, 12306
 \keys_define:nn ... 169, 10081, 12137

- \keys_if_choice_exist:nnnTF [178](#), [12850](#)
- \keys_if_choice_exist_p:nnn [178](#), [12850](#)
- \keys_if_exist:nnTF [178](#), [624](#), [12843](#), [12867](#)
- \keys_if_exist_p:nn [178](#), [12843](#)
- \l_keys_key_tl [176](#), [12124](#), [12240](#), [12256](#), [12682](#), [12771](#), [12774](#), [12808](#), [12819](#)
- \keys_log:nn [178](#), [12858](#)
- \l_keys_path_tl [176](#), [12128](#), [12165](#), [12185](#), [12194](#), [12203](#), [12207](#), [12221](#), [12233](#), [12235](#), [12237](#), [12249](#), [12251](#), [12253](#), [12268](#), [12271](#), [12275](#), [12283](#), [12285](#), [12286](#), [12289](#), [12304](#), [12327](#), [12332](#), [12341](#), [12345](#), [12352](#), [12356](#), [12360](#), [12367](#), [12374](#), [12385](#), [12391](#), [12395](#), [12411](#), [12420](#), [12428](#), [12463](#), [12664](#), [12671](#), [12694](#), [12697](#), [12736](#), [12740](#), [12748](#), [12750](#), [12751](#), [12759](#), [12768](#), [12792](#), [12816](#)
- \keys_set:nn [168](#), [172](#), [176](#), [176](#), [177](#), [12362](#), [12367](#), [12560](#), [12584](#), [12592](#), [12640](#), [12649](#)
- \keys_set_filter:nnn [178](#), [12595](#)
- \keys_set_filter:nnnN ... [178](#), [12595](#)
- \keys_set_groups:nnn [178](#), [12595](#)
- \keys_set_known:nn [177](#), [12570](#)
- \keys_set_known:nnN . [177](#), [619](#), [12570](#)
- \keys_show:nn [178](#), [178](#), [12858](#)
- \l_keys_value_tl [176](#), [12135](#), [12411](#), [12739](#), [12742](#), [12744](#), [12752](#), [12776](#), [12788](#), [12800](#), [12810](#)
- keys internal commands:
 - _keys_bool_set:Nn [12229](#), [12437](#), [12439](#), [12441](#), [12443](#)
 - _keys_bool_set_inverse:Nn [12245](#), [12445](#), [12447](#), [12449](#), [12451](#)
 - _keys_check_groups: . [12698](#), [12706](#)
 - _keys_choice_find:n . [12262](#), [12813](#)
 - _keys_choice_find:nn [12813](#)
 - _keys_choice_make: [12232](#), [12248](#), [12261](#), [12293](#), [12453](#)
 - _keys_choice_make:N [12261](#)
 - _keys_choice_make_aux:N [12261](#)
 - _keys_choices_make:nn [12292](#), [12455](#), [12457](#), [12459](#), [12461](#)
 - _keys_choices_make:Nnn [12292](#)
 - _keys_cmd_set:nn [12233](#), [12235](#), [12237](#), [12249](#), [12251](#), [12253](#), [12285](#), [12286](#), [12303](#), [12313](#), [12360](#), [12367](#), [12428](#), [12463](#)
 - \c__keys_code_root_tl [12114](#), [12315](#), [12320](#), [12356](#), [12748](#), [12751](#), [12771](#), [12774](#), [12785](#), [12787](#), [12797](#), [12799](#), [12824](#), [12825](#), [12826](#), [12846](#), [12854](#), [12873](#)
 - \c__keys_default_root_tl [12114](#), [12327](#), [12332](#), [12736](#), [12740](#)
 - _keys_default_set:n [12242](#), [12258](#), [12322](#), [12473](#), [12475](#), [12477](#), [12479](#)
 - _keys_define:n [12142](#), [12146](#)
 - _keys_define:nn [12142](#), [12146](#)
 - _keys_define:nnn [12137](#)
 - _keys_define_aux:nn [12146](#)
 - _keys_define_code:n . [12160](#), [12211](#)
 - _keys_define_code:w [12211](#)
 - _keys_execute: [12675](#), [12702](#), [12724](#), [12728](#), [12746](#)
 - _keys_execute:nn [12746](#)
 - _keys_execute_inherit: [12746](#)
 - _keys_execute_unknown: . [622](#), [12746](#)
 - \l_keys_filtered_bool [12131](#), [12608](#), [12616](#), [12618](#), [12622](#), [12630](#), [12632](#), [12701](#), [12722](#), [12727](#)
 - _keys_find_key_module:w [12652](#)
 - \l_keys_groups_clist ... [12123](#), [12338](#), [12339](#), [12346](#), [12696](#), [12711](#)
 - \c__keys_groups_root_tl [12114](#), [12341](#), [12345](#), [12694](#), [12697](#)
 - _keys_groups_set:n .. [12336](#), [12497](#)
 - _keys_inherit:n [12349](#), [12499](#)
 - \c__keys_inherit_root_tl [12114](#), [12352](#), [12759](#), [12768](#)
 - \l_keys_inherit_tl [12129](#), [12773](#), [12815](#), [12819](#)
 - _keys_initialise:n [12354](#), [12501](#), [12503](#), [12505](#), [12507](#)
 - _keys_keys_set_known:nn [12570](#)
 - _keys_meta_make:n ... [12358](#), [12517](#)
 - _keys_meta_make:nn .. [12358](#), [12519](#)
 - \l_keys_module_tl [12125](#), [12138](#), [12141](#), [12143](#), [12187](#), [12188](#), [12194](#), [12363](#), [12561](#), [12564](#), [12566](#), [12655](#), [12660](#), [12670](#), [12676](#), [12684](#), [12686](#), [12785](#), [12787](#), [12792](#)
 - _keys_multichoice_find:n [12264](#), [12813](#)
 - _keys_multichoice_make: [12261](#), [12295](#), [12521](#)
 - _keys_multichoices_make:nn ... [12292](#), [12523](#), [12525](#), [12527](#), [12529](#)
 - \l_keys_no_value_bool [12126](#), [12148](#), [12153](#), [12213](#), [12408](#), [12417](#), [12654](#), [12659](#), [12734](#), [12809](#)

```

\l__keys_only_known_bool .....
.. 12127, 12583, 12591, 12593, 12755
\__keys_parent:n ..... 12268,
12271, 12275, 12759, 12768, 12830
\__keys_parent:w ..... 12830
\__keys_property_find:n 12158, 12169
\__keys_property_find:w ..... 12169
\__keys_property_search:w .....
..... 12195, 12199, 12208
\l__keys_property_tl .....
..... 12130, 12159, 12162,
12165, 12171, 12172, 12179, 12191,
12204, 12216, 12217, 12220, 12224
\c__keys_props_root_tl ... 12120,
12159, 12217, 12224, 12436, 12438,
12440, 12442, 12444, 12446, 12448,
12450, 12452, 12454, 12456, 12458,
12460, 12462, 12464, 12466, 12468,
12470, 12472, 12474, 12476, 12478,
12480, 12482, 12484, 12486, 12488,
12490, 12492, 12494, 12496, 12498,
12500, 12502, 12504, 12506, 12508,
12510, 12512, 12514, 12516, 12518,
12520, 12522, 12524, 12526, 12528,
12530, 12532, 12534, 12536, 12538,
12540, 12542, 12544, 12546, 12548,
12550, 12552, 12554, 12556, 12558
\__keys_remove_spaces:n .....
..... 12141, 12171,
12304, 12564, 12668, 12824, 12825,
12841, 12846, 12854, 12865, 12874
\l__keys_selective_bool .....
.. 12131, 12639, 12648, 12650, 12673
\l__keys_selective_seq .....
.. 12133, 12635, 12638, 12643, 12709
\__keys_set:n ..... 12565, 12652
\__keys_set:nn ..... 12565, 12652
\__keys_set:nnn ..... 12560
\__keys_set_aux: ..... 12652
\__keys_set_aux:nnn ..... 12652
\__keys_set_filter:nnn ..... 12595
\__keys_set_filter:nnnnN ..... 12595
\__keys_set_groups:nnn ..... 12595
\__keys_set_known:nn .. 12585, 12589
\__keys_set_known:nnnN ..... 12570
\__keys_set_selective: ..... 12652
\__keys_set_selective:nn ..... 12595
\__keys_set_selective:nnn .... 12595
\__keys_set_selective:nnnn ... 12595
\__keys_show:Nnn ..... 12858
\__keys_store_unused: .....
..... 12703, 12723, 12729, 12746
\l__keys_tmp_bool .....
..... 12136, 12708, 12715, 12720
\c__keys_type_root_tl .....
..... 12114, 12268, 12271, 12283
\__keys_undefine: 12351, 12368, 12555
\l__keys_unused_clist ..... 618,
12134, 12571, 12575, 12577, 12578,
12596, 12600, 12602, 12603, 12806
\__keys_validate_cleanup:w ... 12378
\__keys_validate_forbidden: .. 12378
\__keys_validate_required: ... 12378
\c__keys_validate_root_tl .....
.. 12114, 12385, 12391, 12395, 12750
\__keys_value_or_default:n .....
..... 12672, 12732
\__keys_value_requirement:nn ...
..... 12378, 12557, 12559
\__keys_variable_set:NnnN .....
.... 12425, 12465, 12467, 12469,
12471, 12481, 12483, 12485, 12487,
12489, 12491, 12493, 12495, 12509,
12511, 12513, 12515, 12531, 12533,
12535, 12537, 12539, 12541, 12543,
12545, 12547, 12549, 12551, 12553
keyval commands:
\keyval_parse:Nnn .....
..... 180, 11968, 12142, 12565
keyval internal commands:
\__keyval_action: ..... 12047
\__keyval_def:Nn . 12049, 12069, 12099
\__keyval_def_aux:n ..... 12099
\__keyval_def_aux:w ..... 12099
\__keyval_empty_key: .. 12093, 12097
\l__keyval_key_tl .....
.. 11965, 12049, 12050, 12063, 12073
\__keyval_loop:NNw 11971, 11977, 12037
\__keyval_sanitise_aux:w ..... 11981
\__keyval_sanitise_comma: .....
..... 11976, 11981
\__keyval_sanitise_comma_auxi:w .
..... 11981
\__keyval_sanitise_comma_auxii:w
..... 11981
\__keyval_sanitise_equals: .....
..... 11975, 11981
\__keyval_sanitise_equals_auxi:w
..... 11981
\__keyval_sanitise_equals_-
auxii:w ..... 11981
\l__keyval_sanitise_tl .....
.... 11967, 11974, 11978, 11987,
11989, 11993, 12000, 12002, 12011,
12013, 12017, 12024, 12026, 12035
\__keyval_split:NNw ... 12042, 12047
\__keyval_split_tidy:w ..... 12047
\__keyval_split_value:NNw .... 12047

```


- `\l__keyval_value_tl` [11965](#), [12069](#), [12074](#)
- `\kuten` [1234](#), [1256](#), [2016](#), [2038](#)
- L**
- `\L` [27398](#)
- `\l` [27398](#)
- `l3kernel` [237](#), [25162](#)
- `l3kernel.charcat` [237](#), [25196](#)
- `l3kernel.elapsedtime` [237](#), [25202](#)
- `l3kernel.filemdfivesum` [237](#), [25215](#)
- `l3kernel.filemoddate` [237](#), [25227](#)
- `l3kernel.filesize` [237](#), [25272](#)
- `l3kernel.resettimer` [237](#), [25202](#)
- `l3kernel.strcmp` [237](#), [25282](#)
- `\label` [27459](#)
- `\language` [430](#)
- `\lastallocatedtoks` [19506](#)
- `\lastbox` [431](#)
- `\lastkern` [432](#)
- `\lastlinefit` [648](#), [1462](#)
- `\lastnamedcs` [935](#), [1754](#)
- `\lastnodetype` [649](#), [1463](#)
- `\lastpenalty` [433](#)
- `\lastsavedboxresourceindex` .. [1020](#), [1630](#)
- `\lastsavedimageresourceindex` [1022](#), [1632](#)
- `\lastsavedimageresourcepages` [1024](#), [1634](#)
- `\lastskip` [434](#)
- `\lastxpos` [1026](#), [1636](#)
- `\lastypos` [1027](#), [1637](#)
- `\latelua` [936](#), [1755](#)
- `\lateluafunction` [937](#)
- LaTeX3 error commands:
 - `\LaTeX3_error:` [552](#)
- `\lccode` [173](#), [188](#), [201](#), [203](#), [205](#), [207](#), [209](#), [435](#)
- `\leaders` [436](#)
- `\left` [437](#)
- left commands:
 - `\c_left_brace_str` [62](#), [883](#), [5688](#), [20671](#), [21056](#), [21060](#), [21080](#), [21093](#), [21117](#), [21600](#), [21680](#), [22766](#), [22801](#), [22825](#)
 - `\leftghost` [938](#), [1814](#)
 - `\lefthyphenmin` [438](#)
 - `\leftmarginkern` [795](#), [1609](#)
 - `\leftskip` [439](#)
 - `\leqno` [440](#)
 - `\let` [1](#), [40](#), [278](#), [279](#), [441](#)
 - `\latcharcode` [939](#), [1756](#)
 - `\letterspacefont` [796](#), [1610](#)
 - `\limits` [442](#)
 - `\LineBreak` [80](#), [81](#), [82](#), [83](#), [84](#), [85](#), [86](#), [87](#), [112](#), [119](#), [120](#), [121](#), [129](#), [131](#)
 - `\linedir` [940](#), [1815](#)
 - `\linedirection` [941](#)
 - `\linepenalty` [443](#)
 - `\lineskip` [444](#)
 - `\lineskiplimit` [445](#)
 - `\linewidth` [24326](#), [24372](#)
 - `\ln` [17644](#), [17647](#)
 - `ln` [196](#)
 - `\localbrokenpenalty` [942](#), [1816](#)
 - `\localinterlinepenalty` [943](#), [1817](#)
 - `\lcalleftbox` [948](#), [1819](#)
 - `\lcalrightbox` [949](#), [1820](#)
 - `\loccount` [10418](#), [10611](#)
 - `\loctoks` [19478](#), [19479](#), [19505](#)
 - `logb` [242](#)
 - `\long` [281](#), [446](#), [8811](#), [8815](#)
 - `\LongText` [76](#), [117](#), [141](#)
 - `\looseness` [447](#)
 - `\lower` [448](#)
 - `\lowercase` [449](#)
 - `\lpcode` [797](#), [1611](#)
 - lua commands:
 - `\lua_escape:e` [236](#), [5191](#), [5206](#), [25115](#), [25117](#), [25156](#), [25816](#), [26300](#), [26313](#)
 - `\lua_escape:n` [236](#), [25117](#)
 - `\lua_escape_x:n` [25154](#)
 - `\lua_now:e` [236](#), [5192](#), [5195](#), [8532](#), [25116](#), [25117](#), [25154](#), [25315](#), [25813](#), [26299](#)
 - `\lua_now:n` [236](#), [25117](#), [26267](#)
 - `\lua_now_x:n` [25154](#)
 - `\lua_shipout:n` [236](#), [25117](#)
 - `\lua_shipout_e:n` [236](#), [25117](#), [25158](#), [26312](#)
 - `\lua_shipout_x:n` [25154](#)
 - lua internal commands:
 - `__lua_escape:n` . [25112](#), [25122](#), [25157](#)
 - `__lua_now:n` . . . [25112](#), [25117](#), [25155](#)
 - `__lua_shipout:n` . [25112](#), [25119](#), [25159](#)
 - `\luabytecode` [944](#)
 - `\luabytecodecall` [945](#)
 - `\luacopyinputnodes` [946](#)
 - `\luadef` [947](#)
 - `\luaescapestring` [950](#), [1757](#)
 - `\luafunction` [951](#), [1758](#)
 - `\luafunctioncall` [952](#)
 - luatex commands:
 - `\luatex_alignmark:D` [1713](#)
 - `\luatex_aligntab:D` [1714](#)
 - `\luatex_attribute:D` [1715](#)
 - `\luatex_attributedef:D` [1716](#)
 - `\luatex_automaticdiscretionary:D` [1718](#)
 - `\luatex_automatichyphenmode:D` . [1720](#)

<code>\luatex_automatichyphenpenalty:D</code>	1722	<code>\luatex_mathoption:D</code>	1767
<code>\luatex_begincsname:D</code>	1723	<code>\luatex_mathpenaltiesmode:D</code>	1768
<code>\luatex_bodydir:D</code>	1812	<code>\luatex_mathrulesfam:D</code>	1769
<code>\luatex_boxdir:D</code>	1813	<code>\luatex_mathscriptboxmode:D</code>	1771
<code>\luatex_breakafterdirmode:D</code>	1724	<code>\luatex_mathscriptsmode:D</code>	1770
<code>\luatex_catcodetable:D</code>	1725	<code>\luatex_mathstyle:D</code>	1772
<code>\luatex_clearmarks:D</code>	1726	<code>\luatex_mathsurroundmode:D</code>	1773
<code>\luatex_crampeddisplaystyle:D</code>	1728	<code>\luatex_mathsurroundskip:D</code>	1774
<code>\luatex_crampedscriptscriptstyle:D</code>	1730	<code>\luatex_nohrule:D</code>	1775
<code>\luatex_crampedscriptstyle:D</code>	1731	<code>\luatex_nokerns:D</code>	1776
<code>\luatex_crampedtextstyle:D</code>	1732	<code>\luatex_noligs:D</code>	1777
<code>\luatex_directlua:D</code>	1733	<code>\luatex_nospaces:D</code>	1778
<code>\luatex_dviextension:D</code>	1734	<code>\luatex_novrule:D</code>	1779
<code>\luatex_dvifeedback:D</code>	1735	<code>\luatex_outputbox:D</code>	1780
<code>\luatex_dvivariable:D</code>	1736	<code>\luatex_pagebottomoffset:D</code>	1781
<code>\luatex_etoksapp:D</code>	1737	<code>\luatex_pagedir:D</code>	1822
<code>\luatex_etokspre:D</code>	1738	<code>\luatex_pageleftoffset:D</code>	1782
<code>\luatex_expanded:D</code>	1741	<code>\luatex_pagerightoffset:D</code>	1783
<code>\luatex_explicitdiscretionary:D</code>	1743	<code>\luatex_pagetopoffset:D</code>	1784
<code>\luatex_explicithyphenpenalty:D</code>	1740	<code>\luatex_pardir:D</code>	1823
<code>\luatex_firstvalidlanguage:D</code>	1744	<code>\luatex_pdfextension:D</code>	1785
<code>\luatex_fontid:D</code>	1745	<code>\luatex_pdffeedback:D</code>	1786
<code>\luatex_formatname:D</code>	1746	<code>\luatex_pdfvariable:D</code>	1787
<code>\luatex_gleaders:D</code>	1752	<code>\luatex_postexhyphenchar:D</code>	1788
<code>\luatex_hjcode:D</code>	1747	<code>\luatex_posthyphenchar:D</code>	1789
<code>\luatex_hpack:D</code>	1748	<code>\luatex_prebinoppenalty:D</code>	1790
<code>\luatex_hyphenationbounds:D</code>	1749	<code>\luatex_predisplaygapfactor:D</code>	1792
<code>\luatex_hyphenationmin:D</code>	1750	<code>\luatex_preexhyphenchar:D</code>	1793
<code>\luatex_hyphenpenaltymode:D</code>	1751	<code>\luatex_prehyphenchar:D</code>	1794
<code>\luatex_if_engine:TF</code>	29446, 29448, 29450	<code>\luatex_prerelpenalty:D</code>	1795
<code>\luatex_if_engine_p:</code>	29444	<code>\luatex_rightghost:D</code>	1824
<code>\luatex_initcatcodetable:D</code>	1753	<code>\luatex_savecatcodetable:D</code>	1796
<code>\luatex_lastnamedcs:D</code>	1754	<code>\luatex_scantextokens:D</code>	1797
<code>\luatex_latelua:D</code>	1755	<code>\luatex_setfontid:D</code>	1798
<code>\luatex_leftghost:D</code>	1814	<code>\luatex_shapemode:D</code>	1799
<code>\luatex_letcharcode:D</code>	1756	<code>\luatex_suppressifcsnameerror:D</code>	1801
<code>\luatex_linedir:D</code>	1815	<code>\luatex_suppresslongerror:D</code>	1802
<code>\luatex_localbrokenpenalty:D</code>	1816	<code>\luatex_suppressmathparerror:D</code>	1804
<code>\luatex_localinterlinepenalty:D</code>	1818	<code>\luatex_suppressoutererror:D</code>	1805
<code>\luatex_localleftbox:D</code>	1819	<code>\luatex_suppressprimitiveerror:D</code>	1807
<code>\luatex_localrightbox:D</code>	1820	<code>\luatex_textdir:D</code>	1825
<code>\luatex_luaescapestring:D</code>	1757	<code>\luatex_toksapp:D</code>	1808
<code>\luatex_luafunction:D</code>	1758	<code>\luatex_tokspre:D</code>	1809
<code>\luatex luatexbanner:D</code>	1759	<code>\luatex_tpack:D</code>	1810
<code>\luatex luatexrevision:D</code>	1760	<code>\luatex_vpack:D</code>	1811
<code>\luatex luatexversion:D</code>	1761	<code>\luatexalignmark</code>	1313
<code>\luatex_mathdelimitersmode:D</code>	1762	<code>\luatexalignntab</code>	1314
<code>\luatex_mathdir:D</code>	1821	<code>\luatexattribute</code>	1315
<code>\luatex_mathdisplayskipmode:D</code>	1764	<code>\luatexattributedef</code>	1316
<code>\luatex_matheqnogapstep:D</code>	1765	<code>\luatexbanner</code>	953, 1759
<code>\luatex_mathnolimitsmode:D</code>	1766	<code>\luatexbodydir</code>	1352
		<code>\luatexboxdir</code>	1353
		<code>\luatexcatcodetable</code>	1317

<code>\luatexclearmarks</code>	1318	math commands:	
<code>\luatexcrampeddisplaystyle</code>	1319	<code>\c_math_subscript_token</code>	
<code>\luatexcrampedscriptscriptstyle</code> ..	1321	122, 508, 8626 , 8684, 20109
<code>\luatexcrampedscriptstyle</code>	1322	<code>\c_math_superscript_token</code>	
<code>\luatexcrampedtextstyle</code>	1323	122, 508, 8626 , 8679, 20107
<code>\luatexfontid</code>	1324	<code>\c_math_toggle_token</code>	
<code>\luatexformatname</code>	1325	122, 507, 8626 , 8660, 20103
<code>\luatexgladers</code>	1326	<code>\mathaccent</code>	452
<code>\luatexinitcatcodetable</code>	1327	<code>\mathbin</code>	453
<code>\luatexlatalua</code>	1328	<code>\mathchar</code>	454, 8810
<code>\luatexleftghost</code>	1354	<code>\mathchardef</code>	455
<code>\luatexlocalbrokenpenalty</code>	1355	<code>\mathchoice</code>	456
<code>\luatexlocalinterlinepenalty</code>	1357	<code>\mathclose</code>	457
<code>\luatexlocalleftbox</code>	1358	<code>\mathcode</code>	458
<code>\luatexlocalrightbox</code>	1359	<code>\mathdelimitersmode</code>	956, 1762
<code>\luatexluaescapestring</code>	1329	<code>\mathdir</code>	957, 1821
<code>\luatexluafunction</code>	1330	<code>\mathdirection</code>	958
<code>\luatexmathdir</code>	1360	<code>\mathdisplayskipmode</code>	959, 1763
<code>\luatexmathstyle</code>	1331	<code>\matheqnogapstep</code>	960, 1765
<code>\luatexnokerns</code>	1332	<code>\mathinner</code>	459
<code>\luatexnoligs</code>	1333	<code>\mathnolimitsmode</code>	961, 1766
<code>\luatexoutputbox</code>	1334	<code>\mathop</code>	460
<code>\luatexpagebottomoffset</code>	1361	<code>\mathopen</code>	461
<code>\luatexpagedir</code>	1362	<code>\mathoption</code>	962, 1767
<code>\luatexpageheight</code>	1363	<code>\mathord</code>	462
<code>\luatexpageleftoffset</code>	1335	<code>\mathpenaltiesmode</code>	963, 1768
<code>\luatexpagerightoffset</code>	1364	<code>\mathpunct</code>	463
<code>\luatexpagetopoffset</code>	1336	<code>\mathrel</code>	464
<code>\luatexpagewidth</code>	1365	<code>\mathrulesfam</code>	964, 1769
<code>\luatexpardir</code>	1366	<code>\mathscriptboxmode</code>	966, 1771
<code>\luatexpostexhyphenchar</code>	1337	<code>\mathscriptcharmode</code>	967
<code>\luatexpostthyphenchar</code>	1338	<code>\mathscriptsmode</code>	965, 1770
<code>\luatexpreehyphenchar</code>	1339	<code>\mathstyle</code>	968, 1772
<code>\luatexprehyphenchar</code>	1340	<code>\mathsurround</code>	465
<code>\luatexrevision</code>	954, 1760	<code>\mathsurroundmode</code>	969, 1773
<code>\luatexrightghost</code>	1367	<code>\mathsurroundskip</code>	970, 1774
<code>\luatexsavecatcodetable</code>	1341	max	196
<code>\luatexscantexttokens</code>	1342	max commands:	
<code>\luatexsuppressfontnotfounderror</code> ...	1312, 1351	<code>\c_max_char_int</code>	90, 7260 , 8506, 20647
<code>\luatexsuppressifcsnameerror</code>	1344	<code>\c_max_register_int</code>	
<code>\luatexsuppresslongerror</code>	1345	90, 217 , 837 , 838 , 2101 , 6399, 10026, 19450, 19476, 19513, 19521, 19525, 26066, 26096, 26098
<code>\luatexsuppressmathparerror</code>	1347	<code>\maxdeadcycles</code>	466
<code>\luatexsuppressoutererror</code>	1348	<code>\maxdepth</code>	467
<code>\luatextextdir</code>	1368	<code>\mdfivesum</code>	884, 1617
<code>\luatextracingfonts</code>	1308	<code>\meaning</code>	468
<code>\luatexUchar</code>	1349	<code>\medmuskip</code>	469
<code>\luatexversion</code>	45, 107, 955, 1761	<code>\message</code>	470
		<code>\MessageBreak</code>	129
		meta commands:	
<code>\mag</code>	450	<code>.meta:n</code>	172, 12516
<code>\mark</code>	451	<code>.meta:nn</code>	172, 12518
<code>\marks</code>	650, 1464	<code>\middle</code>	651, 1465

- min 196
- minus commands:
 - \c_minus_inf_fp 191, 200, 13182, 16171, 16255, 16588, 17123, 17900, 19425
 - \c_minus_zero_fp 190, 13182, 16167, 18619, 19423
- \mkern 471
- mm 200
- mode commands:
 - \mode_if_horizontal:TF 102, 7676
 - \mode_if_horizontal_p: 102, 7676
 - \mode_if_inner:TF 102, 7678
 - \mode_if_inner_p: 102, 7678
 - \mode_if_math:TF 102, 7680
 - \mode_if_math_p: 102, 7680
 - \mode_if_vertical:TF 102, 7674
 - \mode_if_vertical_p: 102, 7674
 - \mode_leave_vertical: 240, 24812, 25446
- \month 472
- \moveleft 473
- \moveright 474
- msg commands:
 - \msg_critical:nn 141, 9641
 - \msg_critical:nn(nn) 244
 - \msg_critical:nnnn 141, 9641
 - \msg_critical:nnnnn 141, 9641
 - \msg_critical:nnnnnn 141, 9641
 - \msg_critical_text:n 139, 9540, 9644
 - \msg_error:nn 141, 9650
 - \msg_error:nnn 141, 9650
 - \msg_error:nnnn 141, 9650
 - \msg_error:nnnnn 141, 9650
 - \msg_error:nnnnnn 141, 245, 9650
 - \msg_error_text:n ... 139, 9540, 9657
 - \msg_expandable_error:nn . 246, 25889
 - \msg_expandable_error:nnn 246, 25889
 - \msg_expandable_error:nnnn 246, 25889
 - \msg_expandable_error:nnnnn 246, 25889
 - \msg_fatal:nn 141, 9632
 - \msg_fatal:nnn 141, 9632
 - \msg_fatal:nnnn 141, 9632
 - \msg_fatal:nnnnn 141, 9632
 - \msg_fatal:nnnnnn 141, 9632
 - \msg_fatal_text:n ... 139, 9540, 9635
 - \msg_gset:nnn 138, 9397
 - \msg_gset:nnnn 138, 9397
 - \msg_if_exist:nnTF 139, 9379, 9391, 9768
 - \msg_if_exist_p:nn 139, 9379
 - \msg_info:nn 142, 9691
 - \msg_info:nnn 142, 9691
 - \msg_info:nnnn 142, 9691
 - \msg_info:nnnnn 142, 9691
 - \msg_info:nnnnnn . 142, 142, 9691, 9941
 - \msg_info_text:n 140, 9540, 9693
 - \msg_interrupt:nnn 10333
 - \msg_line_context: 139, 533, 2829, 2838, 3936, 9387, 9454, 10159, 10180, 12316
 - \msg_line_number: ... 139, 9454, 12108
 - \msg_log:n 10319
 - \msg_log:nn 142, 9713
 - \msg_log:nnn 142, 9713
 - \msg_log:nnnn 142, 9713
 - \msg_log:nnnnn 142, 9713
 - \msg_log:nnnnnn 142, 6380, 8334, 8347, 9359, 9713, 10493, 10665, 11263, 12861, 13076, 25039
 - \msg_log_eval:Nn . 246, 7257, 7447, 11718, 11853, 11955, 15407, 25916
 - \g_msg_module_documentation_prop 140
 - \msg_module_name:n 140, 9464, 9559, 9582, 9672, 9694
 - \g_msg_module_name_prop 140, 140, 9567, 9584, 9585
 - \msg_module_type:n 139, 140, 140, 9558, 9571
 - \g_msg_module_type_prop 140, 140, 9567, 9573, 9574
 - \msg_new:nnn 138, 9397, 9892
 - \msg_new:nnnn ... 138, 531, 9397, 9890
 - \msg_none:nn 142, 9719
 - \msg_none:nnn 142, 9719
 - \msg_none:nnnn 142, 9719
 - \msg_none:nnnnn 142, 9719
 - \msg_none:nnnnnn 142, 9719
 - \msg_redirect_class:nn 143, 9841
 - \msg_redirect_module:nnn .. 143, 9841
 - \msg_redirect_name:nnn 143, 9832
 - \msg_see_documentation_text:n ... 140, 9582
 - \msg_set:nnn 138, 9397, 9896
 - \msg_set:nnnn 138, 9397, 9894
 - \msg_show:nn 246, 9720
 - \msg_show:nnn 246, 9720
 - \msg_show:nnnn 246, 9720
 - \msg_show:nnnnn 246, 9720
 - \msg_show:nnnnnn 246, 246, 440, 499, 530, 6378, 8332, 8346, 9357, 9720, 10492, 10664, 11262, 12859, 13074, 20204, 20212, 22967, 22976, 25036

- \msg_show_eval:Nn [246](#), [7253](#), [7445](#),
[11714](#), [11849](#), [11951](#), [15405](#), [25916](#)
- \msg_show_item:n
... [246](#), [246](#), [6388](#), [8342](#), [8351](#), [25921](#)
- \msg_show_item:nn [246](#), [530](#), [9367](#), [25921](#)
- \msg_show_item_unbraced:n [246](#), [25921](#)
- \msg_show_item_unbraced:nn . [246](#),
[558](#), [10500](#), [10672](#), [12869](#), [25055](#), [25921](#)
- \msg_term:n [10319](#)
- \msg_warning:nn [141](#), [9669](#)
- \msg_warning:nnn [141](#), [9669](#)
- \msg_warning:nnnn [141](#), [9669](#)
- \msg_warning:nnnnn [141](#), [9669](#)
- \msg_warning:nnnnnn . [141](#), [9669](#), [9940](#)
- \msg_warning_text:n . [139](#), [9540](#), [9671](#)
- msg internal commands:
- _msg_chk_free:nn [9389](#), [9399](#)
- _msg_chk_if_free:nn [9384](#)
- _msg_class_chk_exist:nTF
..... [9755](#), [9770](#), [9837](#), [9847](#), [9852](#)
- \l_msg_class_loop_seq . [543](#), [9764](#),
[9856](#), [9864](#), [9874](#), [9875](#), [9878](#), [9880](#)
- _msg_class_new:nn
..... [540](#), [545](#), [9593](#), [9632](#), [9641](#),
[9650](#), [9669](#), [9691](#), [9713](#), [9719](#), [9720](#)
- \l_msg_class_tl [541](#),
[543](#), [9760](#), [9777](#), [9790](#), [9811](#), [9815](#),
[9818](#), [9826](#), [9865](#), [9867](#), [9869](#), [9883](#)
- \c_msg_coding_error_text_tl ...
..... [9422](#), [9946](#),
[9954](#), [9980](#), [9998](#), [10007](#), [10019](#),
[10033](#), [10042](#), [10064](#), [10073](#), [10080](#),
[10089](#), [10095](#), [10102](#), [10109](#), [10116](#),
[10123](#), [10131](#), [10139](#), [10169](#), [10182](#)
- \c_msg_continue_text_tl
..... [9422](#), [9468](#), [10339](#)
- \c_msg_critical_text_tl . [9422](#), [9647](#)
- \l_msg_current_class_tl
..... [543](#), [9760](#), [9772](#),
[9810](#), [9815](#), [9818](#), [9826](#), [9855](#), [9869](#)
- _msg_error:Nnnnnn [9650](#)
- _msg_error_code:nnnnnn [9939](#)
- _msg_expandable_error:n
..... [553](#), [10269](#), [10288](#)
- _msg_expandable_error:w [552](#), [10269](#)
- _msg_expandable_error_module:nn
..... [25889](#)
- _msg_fatal_code:nnnnnn [9935](#)
- \c_msg_fatal_text_tl ... [9422](#), [9638](#)
- \c_msg_help_text_tl [9422](#), [9473](#), [10343](#)
- \l_msg_hierarchy_seq
..... [542](#), [542](#), [9763](#), [9793](#), [9803](#), [9808](#)
- _msg_interrupt:n [9495](#), [9504](#)
- _msg_interrupt:Nnnn
..... [9461](#), [9634](#), [9643](#), [9656](#)
- _msg_interrupt_more_text:n ...
..... [533](#), [9477](#)
- _msg_interrupt_text:n [9477](#)
- _msg_interrupt_wrap:nnn
..... [9467](#), [9472](#), [9477](#)
- _msg_kernel_class_new:nN
... [546](#), [9897](#), [9935](#), [9939](#), [9940](#), [9941](#)
- _msg_kernel_class_new_aux:nN [9897](#)
- \c_msg_more_text_prefix_tl
..... [9377](#), [9408](#), [9417](#), [9653](#)
- \l_msg_name_str
..... [9375](#), [9464](#), [9484](#), [9488](#),
[9672](#), [9680](#), [9684](#), [9694](#), [9702](#), [9706](#)
- \c_msg_no_info_text_tl
..... [9422](#), [9469](#), [10338](#)
- _msg_no_more_text:nnnn [9650](#)
- _msg_old_interrupt_more_text:n
..... [10348](#), [10351](#)
- _msg_old_interrupt_text:n
..... [10349](#), [10368](#)
- _msg_old_interrupt_wrap:nn ...
..... [10338](#), [10342](#), [10346](#)
- \c_msg_on_line_text_tl .. [9422](#), [9457](#)
- _msg_redirect:nnn [9841](#)
- _msg_redirect_loop_chk:nnn ...
..... [9841](#), [9883](#)
- _msg_redirect_loop_list:n .. [9841](#)
- \l_msg_redirect_prop
..... [9762](#), [9790](#), [9835](#), [9838](#)
- \c_msg_return_text_tl
..... [9422](#), [9949](#), [9957](#), [9964](#)
- _msg_show:n [540](#), [9720](#)
- _msg_show:nn [9720](#)
- _msg_show:w [9720](#)
- _msg_show_dot:w [9720](#)
- _msg_show_eval:nnN [25916](#)
- _msg_text:n [9540](#)
- _msg_text:nn [9540](#)
- \c_msg_text_prefix_tl . [553](#), [9377](#),
[9381](#), [9406](#), [9415](#), [9637](#), [9646](#), [9659](#),
[9677](#), [9699](#), [9716](#), [9723](#), [10291](#), [25894](#)
- \l_msg_text_str
..... [9375](#), [9463](#), [9482](#), [9487](#),
[9671](#), [9676](#), [9683](#), [9693](#), [9698](#), [9705](#)
- _msg_tmp:w [10270](#), [10283](#)
- \l_msg_tmp_tl
..... [9374](#), [9494](#), [9500](#), [9744](#), [9750](#)
- \c_msg_trouble_text_tl [9422](#)
- _msg_use:nnnnnnn [9603](#), [9765](#)
- _msg_use_code: [541](#), [9765](#)
- _msg_use_hierarchy:nwN [9765](#)

_msg_use_redirect_module:n . . .		\newcount	444
.	542, 9765	\newdimen	444
_msg_use_redirect_name:n . . .	9765	\newlinechar	110, 479
\mskip	475	\next	74, 113,
\muexpr	652, 1466	129, 129, 129, 138, 147, 151, 154, 162
multichoice commands:		\NG	27399
.multichoice:	172, 12520	\ng	27399
multichoices commands:		\noalign	480
.multichoices:nn	172, 12520	\noautospacing	1235, 2017
\multiply	476	\noautoxspacing	1236, 2018
\muskip	477, 8818	\noboundary	481
muskip commands:		\noexpand	125, 129, 140, 143, 482
\c_max_muskip	167, 11956	\nohrule	971, 1775
\muskip_add:Nn	165, 11921	\noindent	483
\muskip_const:Nn		\nokerns	972, 1776
.	165, 11868, 11956, 11957	\noligs	973, 1777
\muskip_eval:n		\nolimits	484
.	166, 166, 11872, 11937, 11951, 11955	\nonscript	485
\muskip_gadd:Nn	165, 11921	\nonstopmode	486
\muskip_gset:Nn	165, 11907	\normaldeviate	1028, 1638
\muskip_gset_eq:NN	165, 11915	\normalend	1386, 1387, 10414, 10447, 10607
\muskip_gsub:Nn	166, 11921	\normaleveryjob	1388
\muskip_gzero:N	165, 11875, 11886	\normalexpanded	1397
\muskip_gzero_new:N	165, 11883	\normalhoffset	1400
\muskip_if_exist:NTF		\normalinput	1389
.	165, 11884, 11886, 11889	\normalitaliccorrection	1399, 1401
\muskip_if_exist_p:N	165, 11889	\normallanguage	1390
\muskip_log:N	166, 11952	\normalleft	1407, 1408
\muskip_log:n	166, 11952	\normalmathop	1391
\muskip_new:N		\normalmiddle	1409
.	165, 165, 11860, 11871, 11884,	\normalmonth	1392
.	11886, 11958, 11959, 11960, 11961	\normalouter	1393
\muskip_set:Nn	165, 11907	\normalover	1394
\muskip_set_eq:NN	165, 11915	\normalright	1410
\muskip_show:N	166, 11948	\normalshowtokens	1403
\muskip_show:n	166, 600, 11950	\normalunexpanded	1396
\muskip_sub:Nn	166, 11921	\normalvcenter	1395
\muskip_use:N	166, 166, 11945, 11946	\normalvoffset	1402
\muskip_zero:N	165, 165, 11875, 11884	\nospaces	974, 1778
\muskip_zero_new:N	165, 11883	notexpanded commands:	
\g_tmpa_muskip	167, 11958	\notexpanded: <token>	130
\l_tmpa_muskip	167, 11958	\novrule	975, 1779
\g_tmpb_muskip	167, 11958	\nulldelimiterspace	487
\l_tmpb_muskip	167, 11958	\nullfont	488
\c_zero_muskip	167, 11877, 11880, 11956	\num	184
\muskipdef	478	\number	55, 489
\mutoglu	653, 1467	\numexpr	174, 188, 654, 1468

N

nan	200
nc	200
nd	200
\newbox	444
\newcatcodetable	52

O

\O	27400
\o	27400
\OE	27401
\oe	27401
\omit	490

one commands:

\c_minus_one	29406
\c_one_degree_fp	191, 200, 14781, 15410
\openin	491
\openout	492
\or	493
or commands:	
\or:	91, 413, 415, 646, 2049, 2928, 2929, 2930, 2931, 2932, 2933, 2934, 2935, 2936, 3577, 3578, 3579, 3580, 3581, 5478, 5554, 6399, 7040, 7041, 7042, 7043, 7044, 7045, 7046, 7047, 7048, 7049, 7050, 7051, 7052, 7053, 7054, 7055, 7056, 7057, 7058, 7059, 7060, 7061, 7062, 7063, 7064, 7073, 7074, 7075, 7076, 7077, 7078, 7079, 7080, 7081, 7082, 7083, 7084, 7085, 7086, 7087, 7088, 7089, 7090, 7091, 7092, 7093, 7094, 7095, 7096, 7097, 8558, 8562, 8565, 8569, 8573, 8575, 8577, 8579, 8580, 8582, 8584, 8586, 8588, 10891, 10892, 10893, 10894, 10895, 10896, 10897, 13221, 13222, 13223, 13472, 13487, 13488, 13884, 13885, 13910, 15164, 15165, 15166, 15202, 15867, 15868, 15869, 15992, 16077, 16163, 16164, 16165, 16166, 16167, 16168, 16169, 16170, 16171, 16250, 16253, 16589, 16590, 16604, 16605, 16619, 16903, 17124, 17149, 17155, 17156, 17157, 17158, 17159, 17308, 17343, 17345, 17353, 17546, 17597, 17600, 17609, 17724, 17747, 17748, 17809, 17814, 17824, 17829, 17839, 17844, 17854, 17859, 17869, 17874, 17884, 17889, 18416, 18417, 18462, 18547, 18550, 18562, 18568, 18615, 18617, 18618, 18628, 18634, 18711, 18712, 18719, 18765, 18766, 18773, 18839, 18840, 19066, 19346, 19347, 19348, 19422, 19423, 19424, 19955, 19956, 20149, 20150, 20446, 20447, 20448, 20449, 20721, 20722, 20723, 20724, 20725, 22040, 22097, 22474, 22475, 27691, 27692, 27693
\outer	5, 444, 494
\output	495
\outputbox	976, 1780
\outputmode	1029, 1639
\outputpenalty	496
\over	497
\overfullrule	498
\overline	499
\overwithdelims	500

P

\PackageError	132, 140
\pagebottomoffset	977, 1781
\pagedepth	501
\pagedir	978, 1822
\pagedirection	979
\pagediscards	655, 1469
\pagefilllstretch	502
\pagefillstretch	503
\pagefilstretch	504
\pagegoal	505
\pageheight	1030, 1640
\pageleftoffset	980, 1782
\pagerightoffset	981, 1783
\pageshrink	506
\pagestretch	507
\pagetopoffset	982, 1784
\pagetotal	508
\pagewidth	1031, 1641
\par	9, 10, 10, 10, 11, 11, 11, 12, 12, 12, 13, 13, 13, 146, 339, 509, 967, 23815, 23817, 23821, 23826, 23832, 23838, 23846, 23852, 23860, 23866, 23888
\pardir	983, 1823
\pardirection	984
\parfillskip	510
\parindent	511
\parshape	512
\parshapedimen	656, 1470
\parshapeindent	657, 1471
\parshapelength	658, 1472
\parskip	513
\patterns	514
\pausing	515
pc	200
\pdfadjustspacing	753, 1570
\pdfannot	681, 1495
\pdfcatalog	682, 1496
\pdfcolorstack	684, 1498
\pdfcolorstackinit	685, 1499
\pdfcompresslevel	683, 1497
\pdfcopyfont	754, 1571
\pdfcreationdate	686, 1500
\pdfdecimaldigits	687, 1501
\pdfdest	688, 1502
\pdfdestmargin	689, 1503
\pdfdraftmode	755, 1572
\pdfeachlinedepth	756, 1573
\pdfeachlineheight	757, 1574
\pdfelapsedtime	758
\pdfendlink	690, 1504
\pdfendthread	691, 1505
\pdfextension	985, 1785

<code>\pdffeedback</code>	986, 1786	<code>\pdfpkmode</code>	777, 1592
<code>\pdffiledump</code>	759	<code>\pdfpkresolution</code>	778, 1593
<code>\pdffilemoddate</code>	760, 1575	<code>\pdfprimitive</code>	779, 1594
<code>\pdffilesize</code>	761, 1576	<code>\pdfprotrudechars</code>	780, 1595
<code>\pdffirstlineheight</code>	762, 1577	<code>\pdfpxdimen</code>	781, 1596
<code>\pdffontattr</code>	692, 1506	<code>\pdfrandomseed</code>	782, 1597
<code>\pdffontexpand</code>	763, 1578	<code>\pdfrefobj</code>	729, 1545
<code>\pdffontname</code>	693, 1507	<code>\pdfrefxform</code>	730, 1546
<code>\pdffontobjnum</code>	694, 1508	<code>\pdfrefximage</code>	731, 1547
<code>\pdffontsize</code>	764, 1579	<code>\pdfresettimer</code>	783
<code>\pdfgamma</code>	695, 1509	<code>\pdfrestore</code>	732, 1548
<code>\pdfgentounicode</code>	698, 1512	<code>\pdfretval</code>	733, 1549
<code>\pdfglyphtounicode</code>	699, 1513	<code>\pdfsave</code>	734, 1550
<code>\pdfhorigin</code>	700, 1514	<code>\pdfsavepos</code>	784, 1598
<code>\pdfignoreddimen</code>	765, 1580	<code>\pdfsetmatrix</code>	735, 1551
<code>\pdfimageapplygamma</code>	696, 1510	<code>\pdfsetrandomseed</code>	786, 1600
<code>\pdfimagegamma</code>	697, 1511	<code>\pdfshellescape</code>	787, 1601
<code>\pdfimagehicolor</code>	701, 1515	<code>\pdfstartlink</code>	736, 1552
<code>\pdfimageresolution</code>	702, 1516	<code>\pdfstartthread</code>	737, 1553
<code>\pdfincludechars</code>	703, 1517	<code>\pdfstrcmp</code>	40, 407, 785, 1599
<code>\pdfinclusioncopyfonts</code>	704, 1518	<code>\pdfsuppressptexinfo</code>	738, 1554
<code>\pdfinclusionerrorlevel</code>	705, 1520	pdftex commands:	
<code>\pdfinfo</code>	707, 1522	<code>\pdftex_adjustspacing:D</code> ..	1570, 1621
<code>\pdfinsertht</code>	766, 1581	<code>\pdftex_copyfont:D</code>	1571, 1622
<code>\pdflastannot</code>	708, 1523	<code>\pdftex_draftmode:D</code>	1572, 1623
<code>\pdflastlinedepth</code>	767, 1582	<code>\pdftex_eachlinedepth:D</code>	1573
<code>\pdflastlink</code>	709, 1524	<code>\pdftex_eachlineheight:D</code>	1574
<code>\pdflastobj</code>	710, 1525	<code>\pdftex_efcode:D</code>	1607
<code>\pdflastxform</code>	711, 1526	<code>\pdftex_filemoddate:D</code>	1575
<code>\pdflastximage</code>	712, 1527	<code>\pdftex_filesize:D</code>	1576
<code>\pdflastximagecolordepth</code>	713, 1528	<code>\pdftex_firstlineheight:D</code>	1577
<code>\pdflastximagepages</code>	715, 1530	<code>\pdftex_fontexpand:D</code>	1578, 1624
<code>\pdflastxpos</code>	768, 1583	<code>\pdftex_fontsize:D</code>	1579
<code>\pdflastypos</code>	769, 1584	<code>\pdftex_if_engine:TF</code>	
<code>\pdflinkmargin</code>	716, 1531	29454, 29456, 29458
<code>\pdfliteral</code>	717, 1532	<code>\pdftex_if_engine_p:</code>	29452
<code>\pdfmapfile</code>	770, 1585	<code>\pdftex_ifabsdim:D</code>	1567, 1625
<code>\pdfmapline</code>	771, 1586	<code>\pdftex_ifabsnum:D</code>	1568, 1626
<code>\pdfmdfivesum</code>	772, 1587	<code>\pdftex_ifincsname:D</code>	1608
<code>\pdfminorversion</code>	718, 1533	<code>\pdftex_ifprimitive:D</code>	1569, 1618
<code>\pdfnames</code>	719, 1534	<code>\pdftex_ignoredimen:D</code>	1580
<code>\pdfnoligatures</code>	773, 1588	<code>\pdftex_ignoreligaturesinfont:D</code>	1628
<code>\pdfnormaldeviate</code>	774, 1589	<code>\pdftex_insertht:D</code>	1581, 1629
<code>\pdfobj</code>	720, 1535	<code>\pdftex_lastlinedepth:D</code>	1582
<code>\pdfobjcompresslevel</code>	721, 1536	<code>\pdftex_lastxpos:D</code>	1583, 1636
<code>\pdfoutline</code>	722, 1538	<code>\pdftex_lastypos:D</code>	1584, 1637
<code>\pdfoutput</code>	723, 1539	<code>\pdftex_leftmarginkern:D</code>	1609
<code>\pdfpageattr</code>	724, 1540	<code>\pdftex_letterspacefont:D</code>	1610
<code>\pdfpagebox</code>	725, 1541	<code>\pdftex_lpcode:D</code>	1611
<code>\pdfpageheight</code>	775, 1590	<code>\pdftex_mapfile:D</code>	1585
<code>\pdfpageref</code>	726, 1542	<code>\pdftex_mapline:D</code>	1586
<code>\pdfpageresources</code>	727, 1543	<code>\pdftex_mdfivesum:D</code>	1587, 1617
<code>\pdfpagesattr</code>	728, 1544	<code>\pdftex_noligatures:D</code>	1588
<code>\pdfpagewidth</code>	776, 1591	<code>\pdftex_normaldeviate:D</code> ..	1589, 1638

\pdfTeX_pageheight:D	1590, 1640	\pdfTeX_pdfrefximage:D	1547, 1646
\pdfTeX_pagewidth:D	1591	\pdfTeX_pdfrestore:D	1548
\pdfTeX_pagewith:D	1641	\pdfTeX_pdfretval:D	1549
\pdfTeX_pdfannot:D	1495	\pdfTeX_pdfsave:D	1550
\pdfTeX_pdfcatalog:D	1496	\pdfTeX_pdfsetmatrix:D	1551
\pdfTeX_pdfcolorstack:D	1498	\pdfTeX_pdfstartlink:D	1552
\pdfTeX_pdfcolorstackinit:D	1499	\pdfTeX_pdfstartthread:D	1553
\pdfTeX_pdfcompresslevel:D	1497	\pdfTeX_pdfsuppressptexinfo:D	1555
\pdfTeX_pdfcreationdate:D	1500	\pdfTeX_pdftexbanner:D	1604
\pdfTeX_pdfdecimaldigits:D	1501	\pdfTeX_pdftexrevision:D	1605
\pdfTeX_pdfdest:D	1502	\pdfTeX_pdftexversion:D	1606
\pdfTeX_pdfdestmargin:D	1503	\pdfTeX_pdfthread:D	1556
\pdfTeX_pdfendlink:D	1504	\pdfTeX_pdfthreadmargin:D	1557
\pdfTeX_pdfendthread:D	1505	\pdfTeX_pdftrailer:D	1558
\pdfTeX_pdffontattr:D	1506	\pdfTeX_pdfuniqueresname:D	1559
\pdfTeX_pdffontname:D	1507	\pdfTeX_pdfvorigin:D	1560
\pdfTeX_pdffontobjnum:D	1508	\pdfTeX_pdfxform:D	1561, 1648
\pdfTeX_pdfgamma:D	1509	\pdfTeX_pdfxformattr:D	1562
\pdfTeX_pdfgentounicode:D	1512	\pdfTeX_pdfxformname:D	1563
\pdfTeX_pdfglyptounicode:D	1513	\pdfTeX_pdfxformresources:D	1564
\pdfTeX_pdfhorigin:D	1514	\pdfTeX_pdfximage:D	1565, 1649
\pdfTeX_pdfimageapplygamma:D	1510	\pdfTeX_pdfximagebbox:D	1566
\pdfTeX_pdfimagegamma:D	1511	\pdfTeX_pkmcode:D	1592
\pdfTeX_pdfimagehicolor:D	1515	\pdfTeX_pkmresolution:D	1593
\pdfTeX_pdfimageresolution:D	1516	\pdfTeX_primitive:D	1594, 1619
\pdfTeX_pdfincludechars:D	1517	\pdfTeX_protrudechars:D	1595, 1642
\pdfTeX_pdfinclusioncopyfonts:D	1519	\pdfTeX_pxdimen:D	1596, 1643
\pdfTeX_pdfinclusionerrorlevel:D	1521	\pdfTeX_quitvmode:D	1612
\pdfTeX_pdfinfo:D	1522	\pdfTeX_randomseed:D	1597, 1644
\pdfTeX_pdflastannot:D	1523	\pdfTeX_rightmarginkern:D	1613
\pdfTeX_pdflastlink:D	1524	\pdfTeX_rpcode:D	1614
\pdfTeX_pdflastobj:D	1525	\pdfTeX_savepos:D	1598, 1647
\pdfTeX_pdflastxform:D	1526, 1631	\pdfTeX_setrandomseed:D	1600, 1650
\pdfTeX_pdflastximage:D	1527, 1633	\pdfTeX_shellescape:D	1601, 1620
\pdfTeX_pdflastximagecolordepth:D	1529	\pdfTeX_strcmp:D	1599
\pdfTeX_pdflastximagepages:D	1530, 1635	\pdfTeX_synctex:D	1615
\pdfTeX_pdflinkmargin:D	1531	\pdfTeX_tagcode:D	1616
\pdfTeX_pdfliteral:D	1532	\pdfTeX_tracingfonts:D	1602, 1651
\pdfTeX_pdfminorversion:D	1533	\pdfTeX_uniformdeviate:D	1603, 1652
\pdfTeX_pdfnames:D	1534	\pdfTexbanner	790, 1604
\pdfTeX_pdfobj:D	1535	\pdfTexrevision	791, 1605
\pdfTeX_pdfobjcompresslevel:D	1537	\pdfTexversion	102, 792, 1606
\pdfTeX_pdfoutline:D	1538	\pdfThread	739, 1556
\pdfTeX_pdfoutput:D	1539, 1639	\pdfThreadmargin	740, 1557
\pdfTeX_pdfpageattr:D	1540	\pdfTracingfonts	788, 1303, 1304, 1602
\pdfTeX_pdfpagebox:D	1541	\pdfTrailer	741, 1558
\pdfTeX_pdfpageref:D	1542	\pdfUniformdeviate	789, 1603
\pdfTeX_pdfpageresources:D	1543	\pdfUniqueresname	742, 1559
\pdfTeX_pdfpagesattr:D	1544	\pdfVariable	987, 1787
\pdfTeX_pdfrefobj:D	1545	\pdfVorigin	743, 1560
\pdfTeX_pdfrefxform:D	1546, 1645	\pdfXform	744, 1561
		\pdfXformattr	745, 1562
		\pdfXformname	746, 1563
		\pdfXformresources	747, 1564

- \pdfimage 748, 1565
- \pdfimagebbox 749, 1566
- peek commands:
 - \peek_after:Nw 104,
126, 126, 126, 8892, 8905, 8933, 27680
 - \peek_catcode:NTF 126, 8988
 - \peek_catcode_collect_inline:Nn .
..... 258, 27660
 - \peek_catcode_ignore_spaces:NTF .
..... 127, 9002
 - \peek_catcode_remove:NTF .. 127, 8988
 - \peek_catcode_remove_ignore_
spaces:NTF 127, 9002
 - \peek_charcode:NTF 127, 8988
 - \peek_charcode_collect_inline:Nn
..... 258, 27660
 - \peek_charcode_ignore_spaces:NTF
..... 127, 9002
 - \peek_charcode_remove:NTF . 127, 8988
 - \peek_charcode_remove_ignore_
spaces:NTF 128, 9002
 - \peek_gafter:Nw 126, 126, 8892
 - \peek_meaning:NTF 128, 8988
 - \peek_meaning_collect_inline:Nn .
..... 258, 27660
 - \peek_meaning_ignore_spaces:NTF .
..... 128, 9002
 - \peek_meaning_remove:NTF .. 128, 8988
 - \peek_meaning_remove_ignore_
spaces:NTF 128, 9002
 - \peek_N_type:TF
..... 258, 27618, 27655, 27657
 - \peek_remove_spaces:n
.... 258, 518, 8901, 9011, 9016, 9021
- peek internal commands:
 - __peek_collect:N 1065, 27660
 - __peek_collect:NNn 27660
 - __peek_collect_remove:nw 27660
 - \l__peek_collect_tl 1065,
27659, 27671, 27673, 27698, 27703
 - __peek_collect_true:w .. 1065, 27660
 - __peek_execute_branches....: . 1065
 - __peek_execute_branches_
catcode: 518, 8955, 27661
 - __peek_execute_branches_
catcode_aux: 8955
 - __peek_execute_branches_
catcode_auxii:N 8955
 - __peek_execute_branches_
catcode_auxiii: 8955
 - __peek_execute_branches_
charcode: 518, 8955, 27663
 - __peek_execute_branches_
meaning: 518, 8947, 27665
 - __peek_execute_branches_N_type:
..... 27618
 - __peek_false:w
1064, 1065, 8888, 8903, 8914, 8928,
8952, 8975, 8985, 27635, 27648, 27672
 - __peek_false_aux:n 1065, 27673, 27674
 - __peek_get_prefix_arg_replacement:wN
..... 9025
 - __peek_N_type:w 27618
 - __peek_N_type_aux:nw 27618
 - __peek_remove_spaces: 8901
 - \l__peek_search_tl 515, 517,
1065, 8887, 8921, 8972, 8982, 27670
 - \l__peek_search_token
.. 515, 1065, 8886, 8920, 8949, 27669
 - __peek_tmp:w 8888, 8899, 27619, 27641
 - __peek_token_generic:NNTF
..... 518, 1064,
8935, 8937, 8939, 27652, 27656, 27658
 - __peek_token_generic_aux:NNNTF .
..... 8917, 8936, 8942
 - __peek_token_remove_generic:NNTF
..... 518, 8935, 8943, 8945
 - __peek_true:w
... 1064, 1065, 8888, 8927, 8950,
8973, 8983, 27633, 27647, 27648, 27679
 - __peek_true_aux:w
.... 516, 516, 8888, 8898, 8905,
8906, 8922, 8936, 27680, 27681, 27699
 - __peek_true_remove:w
... 516, 516, 8896, 8911, 8942, 27704
- \penalty 516
- \pi 14188, 14189
- pi 200
- \pm 15617, 15618
- \postbreakpenalty 1237, 2019
- \postdisplaypenalty 517
- \postexhyphenchar 988, 1788
- \posthyphenchar 989, 1789
- \prebinoppenalty 990, 1790
- \prebreakpenalty 1238, 2020
- \predisplaydirection 659, 1473
- \predisplaygapfactor 991, 1791
- \predisplaypenalty 518
- \predisplaysize 519
- \preexhyphenchar 992, 1793
- \prehyphenchar 993, 1794
- \prerelpenalty 994, 1795
- \pretolerance 520
- \prevdepth 521
- \prevgraf 522
- prg commands:
 - \prg_break:
103, 435, 436, 529, 933, 1024, 3147,

- 4932, 6201, 6234, 6840, 7688, 7695,
9307, 9328, 11155, 13283, 13292,
15288, 15308, 15309, 15513, 15514,
15527, 15627, 15628, 15629, 18949,
19007, 19231, 19733, 19808, 20144,
20218, 20248, 20249, 20250, 20251,
20252, 20253, 20621, 20625, 22582,
22609, 25967, 26000, 26006, 26133
- \prg_break:n 103,
103, 3147, 4934, 6075, 6214, 6850,
7688, 7697, 9212, 13068, 13299, 22120
- \prg_break_point: .. 103, 103, 577,
839, 840, 847, 1026, 3147, 4922,
6072, 6202, 6234, 6300, 6307, 6845,
7688, 7690, 7691, 9207, 9292, 9328,
11132, 13062, 13284, 13293, 15289,
15310, 15515, 15631, 18950, 19007,
19239, 19561, 19602, 19726, 19733,
20067, 20219, 20255, 20599, 22121,
22449, 22603, 25967, 26001, 26133
- \prg_break_point:Nn 65, 103,
103, 346, 436, 454, 479, 590, 3138,
4563, 4581, 4591, 5313, 5339, 5359,
6235, 6270, 6281, 6892, 7688, 7688,
7689, 7694, 8130, 8144, 8164, 8182,
9329, 9345, 10550, 10569, 11666,
15700, 20196, 25968, 26113, 26122
- \prg_do_nothing: 8, 103,
378, 427, 483, 498, 653, 820, 888,
936, 3136, 3147, 3499, 3841, 3868,
4233, 4262, 4312, 4327, 5129, 5131,
5923, 5930, 6167, 6169, 7776, 7782,
7790, 7944, 8143, 8151, 8300, 8304,
8311, 10596, 10890, 12040, 13523,
13590, 13624, 13650, 13658, 15173,
18931, 19648, 19806, 19807, 20038,
20087, 20920, 20963, 20964, 20971,
20972, 22677, 22840, 26404, 26786
- \prg_generate_conditional_-
variant:Nnn
.... 242, 3981, 4421, 4431, 4442,
4465, 4485, 4495, 4555, 4820, 5217,
5230, 5238, 5269, 5798, 5820, 6055,
6076, 6170, 6172, 6186, 6188, 6190,
6192, 7443, 7962, 7976, 7977, 8120,
8122, 9236, 9237, 9285, 9309, 9320,
10443, 23671, 23673, 23677, 24270
- \prg_map_break:Nn
..... 103, 103, 346, 390, 479,
495, 530, 3138, 4604, 4606, 5372,
5374, 6225, 6227, 7688, 7692, 7694,
8199, 8201, 9354, 9356, 10533, 10535
- \prg_new_conditional:Nnn
..... 95, 2533, 7398
- \prg_new_conditional:Npnn 95, 95,
242, 311, 312, 325, 508, 518, 2516,
3077, 3726, 4413, 4423, 4433, 4449,
4457, 4499, 4515, 4805, 4822, 4841,
4876, 4893, 4904, 5210, 5219, 5224,
5782, 5790, 5800, 5810, 6047, 6636,
6695, 6735, 6745, 7363, 7369, 7398,
7435, 7467, 7527, 7542, 7553, 7568,
7578, 7674, 7676, 7678, 7680, 7792,
8073, 8648, 8653, 8658, 8663, 8670,
8676, 8682, 8687, 8692, 8697, 8702,
8707, 8712, 8717, 8724, 8739, 8744,
8779, 8825, 9280, 9287, 9379, 10505,
11467, 11472, 11793, 11808, 12843,
12850, 13467, 14629, 15425, 15441,
20713, 20733, 20755, 20801, 20825,
23667, 23669, 23675, 24260, 26322
- \prg_new_eq_conditional:NNn
..... 96, 2649, 4126,
4127, 5180, 5182, 5184, 5186, 5952,
5954, 6372, 6373, 6374, 6375, 6376,
6377, 6566, 6568, 7398, 7463, 7465,
7880, 7882, 8069, 8071, 9276, 9278,
11364, 11366, 11753, 11755, 11889,
11891, 15423, 15424, 23633, 23635
- \prg_new_protected_conditional:Nnn
..... 95, 2533, 7398
- \prg_new_protected_conditional:Npnn
..... 95,
2516, 4467, 4487, 5232, 5240, 6057,
6166, 6168, 6174, 6177, 6180, 6183,
7398, 7953, 7963, 7965, 8087, 8091,
9216, 9226, 9311, 10433, 11157,
21147, 22981, 22986, 22999, 23001
- \prg_replicate:nn
..... 102, 477, 629, 7626, 9485,
9681, 9703, 10223, 10722, 13019,
13140, 16845, 17696, 17934, 18190,
18236, 18273, 18796, 18804, 19269,
19369, 20323, 20926, 21662, 22047,
22073, 22226, 22234, 22682, 23144,
23149, 23156, 23259, 23264, 29130
- \prg_return_false: 96, 97, 328, 397,
432, 448, 492, 492, 947, 2512, 2576,
2584, 2743, 2748, 2761, 2766, 2774,
2791, 3080, 3736, 4418, 4428, 4439,
4454, 4462, 4477, 4492, 4506, 4522,
4817, 4838, 4854, 4862, 4872, 4885,
4899, 4913, 5215, 5222, 5228, 5236,
5244, 5787, 5795, 5806, 5816, 6052,
6071, 6090, 6634, 6666, 6671, 6700,
6740, 6750, 7366, 7374, 7398, 7440,
7472, 7532, 7548, 7558, 7574, 7584,
7675, 7677, 7679, 7681, 7807, 7810,

- 7956, 7970, 8076, 8111, 8117, 8651,
8656, 8661, 8666, 8673, 8680, 8685,
8690, 8695, 8700, 8705, 8710, 8715,
8720, 8737, 8742, 8747, 8752, 8785,
8788, 8800, 8829, 8854, 8871, 8880,
9224, 9234, 9283, 9303, 9318, 9382,
10437, 10514, 11161, 11470, 11489,
11504, 11505, 11797, 11811, 12848,
12856, 13478, 13480, 14644, 14656,
15436, 15449, 20727, 20738, 20741,
20746, 20750, 20751, 20759, 20762,
20767, 20770, 20807, 20810, 20831,
20834, 21154, 21159, 23027, 23668,
23670, 23676, 24266, 24268, 26333
- \prg_return_true:
.. 96, 97, 328, 385, 397, 397, 432,
526, 945, 947, 2512, 2576, 2584,
2746, 2763, 2771, 2776, 2789, 2794,
3080, 3728, 3736, 4416, 4426, 4437,
4452, 4460, 4475, 4492, 4505, 4520,
4815, 4836, 4852, 4870, 4883, 4901,
4912, 5215, 5222, 5228, 5236, 5244,
5785, 5793, 5804, 5814, 6050, 6075,
6093, 6666, 6698, 6738, 6748, 7366,
7372, 7398, 7438, 7470, 7530, 7546,
7556, 7572, 7582, 7675, 7677, 7679,
7681, 7803, 7806, 7812, 7959, 7973,
8077, 8107, 8117, 8651, 8656, 8661,
8666, 8673, 8680, 8685, 8690, 8695,
8700, 8705, 8710, 8715, 8720, 8736,
8742, 8750, 8799, 8852, 8878, 9222,
9232, 9283, 9305, 9316, 9382, 10440,
10512, 10517, 10519, 11162, 11470,
11505, 11796, 11812, 12847, 12855,
13471, 13476, 14639, 14662, 15438,
15447, 20716, 20730, 20738, 20741,
20746, 20750, 20762, 20767, 20770,
20805, 20829, 21150, 21156, 23025,
23668, 23670, 23676, 24265, 26331
- \prg_set_conditional:Nnn
..... 95, 2533, 7398
- \prg_set_conditional:Npnn 95, 96,
97, 2516, 2740, 2752, 2768, 2780, 7398
- \prg_set_eq_conditional:NNn
..... 96, 2649, 7398
- \prg_set_protected_conditional:Nnn
..... 95, 2533, 7398
- \prg_set_protected_conditional:Npnn
..... 95, 2516, 7398
- prg internal commands:
- __prg_break: 7688
- __prg_break:n 7688
- __prg_break_point: 7688
- __prg_break_point:Nn 346, 479, 7688
- __prg_generate_conditional:nnNNNnnn
..... 2528, 2553, 2562
- __prg_generate_conditional:NNnnnnNw
..... 2562
- __prg_generate_conditional_-
count:NNNnn 2533
- __prg_generate_conditional_-
count:nnNNNnn 2533
- __prg_generate_conditional_-
fast:nw 329, 330, 2562
- __prg_generate_conditional_-
parm:NNNpnn 2516
- __prg_generate_conditional_-
test:w 2562
- __prg_generate_F_form:wNNnnnnN 2605
- __prg_generate_p_form:wNNnnnnN .
..... 329, 2605
- __prg_generate_T_form:wNNnnnnN 2605
- __prg_generate_TF_form:wNNnnnnN
..... 2605
- __prg_map_break:Nn 479, 7688
- __prg_p_true:w 330, 2605
- __prg_replicate:N 7626
- __prg_replicate_ 7626
- __prg_replicate_0:n 7626
- __prg_replicate_1:n 7626
- __prg_replicate_2:n 7626
- __prg_replicate_3:n 7626
- __prg_replicate_4:n 7626
- __prg_replicate_5:n 7626
- __prg_replicate_6:n 7626
- __prg_replicate_7:n 7626
- __prg_replicate_8:n 7626
- __prg_replicate_9:n 7626
- __prg_replicate_first:N 7626
- __prg_replicate_first-:n ... 7626
- __prg_replicate_first_0:n ... 7626
- __prg_replicate_first_1:n ... 7626
- __prg_replicate_first_2:n ... 7626
- __prg_replicate_first_3:n ... 7626
- __prg_replicate_first_4:n ... 7626
- __prg_replicate_first_5:n ... 7626
- __prg_replicate_first_6:n ... 7626
- __prg_replicate_first_7:n ... 7626
- __prg_replicate_first_8:n ... 7626
- __prg_replicate_first_9:n ... 7626
- __prg_set_eq_conditional:NNNn 2649
- __prg_set_eq_conditional:nnNnnNw
..... 2657, 2665
- __prg_set_eq_conditional_F_-
form:nnn 2665
- __prg_set_eq_conditional_F_-
form:wNnnnn 2710

- _prg_set_eq_conditional_-
 loop:nnnnNw [2665](#)
- _prg_set_eq_conditional_p_-
 form:nnn [2665](#)
- _prg_set_eq_conditional_p_-
 form:wNnnnn [2698](#)
- _prg_set_eq_conditional_T_-
 form:nnn [2665](#)
- _prg_set_eq_conditional_T_-
 form:wNnnnn [2706](#)
- _prg_set_eq_conditional_TF_-
 form:nnn [2665](#)
- _prg_set_eq_conditional_TF_-
 form:wNnnnn [2702](#)
- \primitive [886](#), [1619](#), [3592](#)
- prop commands:
 - \c_empty_prop
 [137](#), [521](#), [9063](#), [9067](#), [9071](#), [9074](#), [9282](#)
 - \prop_clear:N
 ... [132](#), [132](#), [9070](#), [9077](#), [22405](#), [24662](#)
 - \prop_clear_new:N
 [132](#), [980](#), [9076](#), [24294](#), [24295](#)
 - \prop_const_from_keyval:Nn
 [247](#), [9094](#), [24229](#), [24236](#)
 - \prop_count:N [247](#), [25953](#), [25982](#)
 - \prop_gclear:N [132](#), [9070](#), [9080](#)
 - \prop_gclear_new:N [132](#), [9076](#)
 - \prop_get:Nn [103](#), [29460](#), [29462](#)
 - \prop_get:NnN [63](#), [64](#), [133](#),
 [134](#), [9173](#), [24895](#), [24899](#), [24978](#), [24982](#)
 - \prop_get:NnNTF [133](#),
 [134](#), [135](#), [9311](#), [9790](#), [9810](#), [9865](#), [24421](#)
 - \prop_gpop:NnN [133](#), [9181](#)
 - \prop_gpop:NnNTF [133](#), [135](#), [9216](#)
 - \prop_gput:Nnn [133](#),
 [9238](#), [9568](#), [9570](#), [10422](#), [10477](#),
 [10615](#), [10648](#), [28210](#), [28438](#), [28646](#)
 - \prop_gput_if_new:Nnn [133](#), [9259](#)
 - \prop_gremove:Nn
 [134](#), [9157](#), [10485](#), [10657](#)
 - \prop_gset_eq:NN [132](#),
 [9074](#), [9082](#), [24296](#), [24298](#), [24445](#), [24447](#)
 - \prop_gset_from_keyval:Nn . [247](#), [9094](#)
 - \prop_if_empty:NTF .. [134](#), [9280](#), [25979](#)
 - \prop_if_empty_p:N [134](#), [9280](#)
 - \prop_if_exist:NTF
 [134](#), [9077](#), [9080](#), [9276](#)
 - \prop_if_exist_p:N [134](#), [9276](#)
 - \prop_if_in:NnTF [134](#), [9287](#), [9573](#), [9584](#)
 - \prop_if_in_p:Nn [134](#), [9287](#)
 - \prop_item:Nn
 [134](#), [247](#), [9203](#), [9574](#), [9585](#), [28221](#),
 [28231](#), [28460](#), [28653](#), [29461](#), [29463](#)
 - \prop_log:N [137](#), [9357](#)
 - \prop_map_break:
 ... [136](#), [1024](#), [9329](#), [9345](#), [9353](#), [25968](#)
 - \prop_map_break:n [136](#), [9353](#)
 - \prop_map_function:NN
 [135](#), [246](#), [247](#), [528](#), [1024](#),
 [9322](#), [9367](#), [10499](#), [10671](#), [25053](#), [25958](#)
 - \prop_map_inline:Nn
 [135](#), [9338](#), [23166](#),
 [24740](#), [24759](#), [24947](#), [24956](#), [25562](#),
 [25564](#), [25567](#), [25587](#), [25589](#), [25660](#),
 [25677](#), [25721](#), [25723](#), [25727](#), [25730](#)
 - \prop_map_tokens:Nn [247](#), [25963](#)
 - \prop_new:N [132](#),
 [132](#), [9064](#), [9077](#), [9080](#), [9090](#), [9091](#),
 [9092](#), [9093](#), [9567](#), [9569](#), [9596](#), [9762](#),
 [10409](#), [10602](#), [22311](#), [22312](#), [24821](#),
 [24862](#), [25552](#), [28203](#), [28428](#), [28639](#)
 - \prop_pop:NnN [133](#), [9181](#)
 - \prop_pop:NnNTF [133](#), [135](#), [9216](#)
 - \prop_put:Nnn [133](#), [366](#), [520](#),
 [521](#), [9238](#), [9838](#), [9854](#), [9871](#), [22569](#),
 [24474](#), [24482](#), [24485](#), [24491](#), [24494](#),
 [24503](#), [24508](#), [24513](#), [24520](#), [24527](#),
 [24764](#), [24822](#), [24824](#), [24826](#), [24828](#),
 [24830](#), [24832](#), [24834](#), [24836](#), [24838](#),
 [24840](#), [24842](#), [24844](#), [24846](#), [24848](#),
 [24850](#), [24852](#), [24854](#), [24856](#), [25595](#),
 [25597](#), [25603](#), [25605](#), [25614](#), [25620](#),
 [25687](#), [25695](#), [25760](#), [25774](#), [25781](#)
 - \prop_put_if_new:Nnn [133](#), [9259](#)
 - \prop_rand_key_value:N .. [247](#), [25977](#)
 - \prop_remove:Nn [134](#),
 [9157](#), [9835](#), [9850](#), [24942](#), [24945](#), [24949](#)
 - \prop_set_eq:NN
 ... [132](#), [9071](#), [9082](#), [22580](#), [24431](#),
 [24433](#), [24438](#), [24440](#), [24696](#), [24937](#)
 - \prop_set_from_keyval:Nn .. [247](#), [9094](#)
 - \prop_show:N [136](#), [9357](#)
 - \g_tmpa_prop [137](#), [9090](#)
 - \l_tmpa_prop [137](#), [9090](#)
 - \g_tmpb_prop [137](#), [9090](#)
 - \l_tmpb_prop [137](#), [9090](#)
 - prop internal commands:
 - _prop_count:nn [25953](#)
 - _prop_from_keyval:n [9094](#)
 - _prop_from_keyval_key:n [9094](#)
 - _prop_from_keyval_key:w . [522](#), [9094](#)
 - _prop_from_keyval_loop:w ... [9094](#)
 - _prop_from_keyval_split:Nw . [9094](#)
 - _prop_from_keyval_value:n .. [9094](#)
 - _prop_from_keyval_value:w [522](#), [9094](#)
 - _prop_if_in:N [528](#), [9287](#)
 - _prop_if_in:nwwn [528](#), [9287](#)

<code>\l__prop_internal_tl</code> ..	526, 9059, 9062, 9242, 9248, 9249, 9265, 9272
<code>__prop_item_Nn:nwn</code>	525
<code>__prop_item_Nn:nwnn</code>	9203
<code>__prop_map_function:Nwnn</code>	9322
<code>__prop_map_tokens:nwnn</code>	25963
<code>__prop_pair:wn</code>	520, 520, 520, 524, 528, 529, 529, 1024, 9059, 9060, 9136, 9151, 9154, 9206, 9209, 9244, 9267, 9290, 9294, 9328, 9331, 9341, 9343, 9348, 25967, 25970, 25987
<code>__prop_put:NNnn</code>	9238
<code>__prop_put_if_new:NNnn</code>	9259
<code>__prop_rand_item:w</code>	25977
<code>__prop_show:NN</code>	9357, 9359, 9361
<code>__prop_split:NnTF</code> .	521, 526, 527, 528, 9146, 9159, 9165, 9175, 9183, 9192, 9218, 9228, 9247, 9270, 9313
<code>__prop_split_aux:NnTF</code>	9146
<code>__prop_split_aux:w</code>	524, 9146
<code>\protect</code>	10789, 14122, 26828, 26855
<code>\protected</code>	213, 215, 217, 242, 660, 1474, 8813, 8815
<code>\protrudechars</code>	1032, 1642
<code>\ProvidesExplClass</code>	6
<code>\ProvidesExplFile</code>	6, 27710
<code>\ProvidesExplPackage</code>	6
<code>pt</code>	200
ptex commands:	
<code>\ptex_autospacing:D</code>	1993
<code>\ptex_autoxspacing:D</code>	1994
<code>\ptex_dtou:D</code>	1995
<code>\ptex_epTeXversion:D</code>	1997
<code>\ptex_euc:D</code>	1998
<code>\ptex_ifdbbox:D</code>	1999
<code>\ptex_ifddir:D</code>	2000
<code>\ptex_ifmdir:D</code>	2001
<code>\ptex_iftbody:D</code>	2002
<code>\ptex_iftbody:D</code>	2003
<code>\ptex_iftbody:D</code>	2004
<code>\ptex_iftbody:D</code>	2005
<code>\ptex_inhibitglue:D</code>	2006
<code>\ptex_inhibitxspcode:D</code>	2007
<code>\ptex_inputencoding:D</code>	1996
<code>\ptex_jcharwidowpenalty:D</code>	2008
<code>\ptex_jfam:D</code>	2009
<code>\ptex_jfont:D</code>	2010
<code>\ptex_jis:D</code>	2011
<code>\ptex_kanjiskip:D</code>	2012
<code>\ptex_kansuji:D</code>	2013
<code>\ptex_kansujichar:D</code>	2014
<code>\ptex_kcatcode:D</code>	2015
<code>\ptex_kuten:D</code>	2016
<code>\ptex_noautospace:D</code>	2017
<code>\ptex_noautoxspacing:D</code>	2018
<code>\ptex_postbreakpenalty:D</code>	2019
<code>\ptex_prebreakpenalty:D</code>	2020
<code>\ptex_ptexminorversion:D</code>	2021
<code>\ptex_ptexrevision:D</code>	2022
<code>\ptex_ptexversion:D</code>	2023
<code>\ptex_showmode:D</code>	2024
<code>\ptex_sjis:D</code>	2025
<code>\ptex_tate:D</code>	2026
<code>\ptex_tbaselineshift:D</code>	2027
<code>\ptex_tfont:D</code>	2028
<code>\ptex_xkanjiskip:D</code>	2029
<code>\ptex_xspcode:D</code>	2030
<code>\ptex_ybaselineshift:D</code>	2031
<code>\ptex_yoko:D</code>	2032
<code>\ptexminorversion</code>	1239, 2021
<code>\ptexrevision</code>	1240, 2022
<code>\ptexversion</code>	1241, 2023
<code>\pxdimen</code>	1033, 1643
Q	
quark commands:	
<code>\q_mark</code>	64, 107, 334, 365, 367, 382, 389, 392, 392, 405, 411, 418, 483, 487, 490, 491, 496, 522, 524, 601, 842, 846, 847, 848, 851, 2574, 2576, 2584, 2730, 2731, 2734, 2735, 2736, 3780, 3781, 3783, 3789, 3793, 3815, 3824, 3843, 3871, 3874, 3883, 3898, 3942, 3956, 3959, 3971, 3998, 4001, 4017, 4333, 4335, 4337, 4339, 4547, 4557, 4635, 4636, 4639, 4642, 4643, 4649, 4652, 4667, 4668, 4674, 4678, 4680, 4683, 5267, 5298, 5305, 5378, 5395, 5643, 5645, 5732, 6321, 6322, 6336, 6339, 6649, 6652, 6724, 6731, 7797, 7814, 7936, 7946, 7950, 7972, 8028, 8034, 8048, 8060, 8061, 8062, 8065, 8066, 8067, 8076, 8077, 8086, 8240, 8241, 8253, 8254, 9106, 9114, 9126, 9151, 9153, 9154, 9730, 9795, 9796, 9801, 9804, 10932, 10939, 10951, 11025, 11026, 11027, 11028, 11533, 11540, 11971, 11978, 11988, 12012, 12034, 12044, 12056, 13312, 13313, 13317, 19651, 19655, 19661, 19665, 19671, 19674, 19739, 19779, 19781, 19784, 19788, 19791, 19794, 19796, 19799, 27630, 27631, 27638
<code>\q_nil</code>	18, 19, 64, 64, 64, 317, 382, 384, 385, 392, 421, 423, 522, 2162, 2165, 4004, 4359, 4435, 4436, 4446, 4447, 4666, 4670, 4688, 4691, 4694, 4784, 4785, 5732,

- 5784, 5803, 5809, 5824, 5825, 9119,
9123, 9130, 10818, 10825, 11988,
11998, 12012, 12022, 21625, 21643
- `\q_no_value` 63,
64, 64, 64, 69, 70, 70, 70, 70,
75, 75, 75, 114, 133, 133, 133, 421,
422, 433, 434, 487, 524, 525, 5732,
5792, 5813, 5819, 6081, 6089, 6101,
6127, 7919, 7934, 9177, 9188, 9197
- `\quark_if_nil:n` 423
- `\quark_if_nil:NTF`
..... 64, 5782, 21647, 21667
- `\quark_if_nil:nTF` . 64, 422, 4357, 5800
- `\quark_if_nil_p:N` 64, 5782
- `\quark_if_nil_p:n` 64, 5800
- `\quark_if_no_value:NTF`
. 64, 5782, 24897, 24901, 24980, 24984
- `\quark_if_no_value:nTF` 64, 5800
- `\quark_if_no_value_p:N` 64, 5782
- `\quark_if_no_value_p:n` 64, 5800
- `\quark_if_recursion_tail_break:N`
..... 29464
- `\quark_if_recursion_tail_break:n`
..... 29466
- `\quark_if_recursion_tail_-`
break:NN 65, 4598, 5347, 5365, 5770
- `\quark_if_recursion_tail_-`
break:nN
.... 65, 4569, 4932, 5770, 8135, 8148
- `\quark_if_recursion_tail_stop:N` .
.. 65, 5738, 7227, 8193, 25431, 27385
- `\quark_if_recursion_tail_stop:n` .
..... 65,
400, 422, 5752, 7787, 8223, 9111, 27213
- `\quark_if_recursion_tail_stop_-`
do:Nn 65, 5682, 5738, 7166,
7183, 7230, 26641, 26649, 26816, 26836
- `\quark_if_recursion_tail_stop_-`
do:nn .. 65, 5752, 7537, 7563, 26888
- `\quark_new:N` 63, 5726,
5732, 5733, 5734, 5735, 5736, 5737
- `\q_recursion_stop` 18, 19, 64,
65, 65, 65, 65, 66, 317, 331, 421,
495, 2164, 2168, 2580, 2662, 3767,
3997, 5659, 5667, 5672, 5736, 7161,
7178, 7221, 7248, 7526, 7552, 7783,
8181, 8217, 9107, 21625, 21643,
25439, 26581, 26584, 26593, 26604,
26618, 26632, 26639, 26645, 26664,
26666, 26675, 26677, 26684, 26685,
26688, 26691, 26704, 26810, 26832,
26854, 26884, 26900, 26902, 26905,
26908, 26910, 26915, 26918, 26920,
26923, 26926, 26931, 26954, 26957,
26959, 26961, 26966, 27047, 27051,
27053, 27058, 27072, 27097, 27101,
27103, 27108, 27116, 27357, 27405,
27422, 27426, 27428, 27433, 27448
- `\q_recursion_tail` 64, 65,
65, 65, 65, 65, 66, 331, 410, 421,
422, 493, 528, 2580, 2590, 2662,
2681, 4562, 4580, 4590, 4921, 5312,
5321, 5338, 5358, 5659, 5736, 5740,
5746, 5755, 5762, 5767, 5772, 5779,
7161, 7178, 7221, 7526, 7552, 7783,
8129, 8143, 8163, 8181, 8217, 9107,
9291, 9302, 11971, 11978, 12039,
25439, 26581, 26645, 26679, 26810,
26832, 26863, 26884, 27356, 27404
- `\q_stop` 18, 19, 30, 45, 63, 63, 64, 64,
107, 317, 334, 367, 382, 391, 411,
415, 421, 448, 460, 491, 496, 511,
513, 522, 524, 552, 639, 846, 847,
848, 2163, 2166, 2322, 2324, 2601,
2606, 2625, 2633, 2641, 2692, 2698,
2702, 2706, 2710, 2731, 2734, 2735,
2736, 3784, 3793, 3819, 3871, 3875,
3879, 3887, 3893, 3902, 3908, 3910,
3942, 3962, 3971, 3998, 4358, 4519,
4525, 4547, 4557, 4637, 4639, 4644,
4646, 4672, 4694, 4775, 4777, 4794,
4812, 4829, 4851, 5057, 5067, 5164,
5267, 5298, 5305, 5378, 5387, 5393,
5395, 5401, 5418, 5437, 5499, 5556,
5568, 5606, 5622, 5629, 5637, 5639,
5643, 5645, 5732, 6101, 6104, 6112,
6114, 6195, 6196, 6323, 6336, 6339,
6341, 6628, 6644, 6646, 6650, 6663,
6724, 6731, 7154, 7160, 7177, 7921,
7924, 7936, 7939, 7947, 7950, 7958,
7972, 8034, 8062, 8065, 8066, 8078,
8086, 8242, 8253, 8254, 8255, 8281,
8315, 8729, 8732, 8762, 8796, 8833,
8837, 8843, 8866, 9027, 9034, 9043,
9052, 9113, 9123, 9126, 9130, 9151,
9154, 9732, 9736, 9738, 9797, 10818,
10859, 10917, 10955, 10968, 11025,
11028, 11055, 11060, 11226, 11229,
11243, 11258, 11260, 11480, 11504,
11533, 11540, 11812, 11814, 12042,
12059, 12086, 12105, 12106, 12173,
12175, 12195, 12199, 12208, 12216,
12227, 12671, 12679, 12689, 12831,
12833, 12838, 13289, 13300, 13307,
13313, 13317, 13331, 13350, 14162,
14166, 14673, 14678, 15249, 15271,
15434, 15435, 15460, 15461, 15627,
15628, 15629, 15796, 15797, 19727,

- 19736, 19740, 19742, 19779, 19780,
19781, 19786, 19788, 19792, 19794,
19802, 25094, 25096, 25097, 25098,
25100, 25102, 25104, 25335, 25352,
25356, 25367, 25371, 25383, 25384,
25390, 25392, 25393, 25395, 25398,
25414, 25422, 25914, 25983, 25996,
25997, 25999, 26003, 26007, 26009,
26014, 27619, 27632, 27641, 27755,
27758, 27804, 27807, 29099, 29103
\ s _stop 66, 67, 847, 5842, 5843, 17415,
17430, 18680, 18684, 19740, 19742
quark internal commands:
\ s _fp 633, 634, 635,
639, 640, 663, 670, 671, 674, 687,
689, 691, 718, 721, 723, 723, 725,
731, 734, 820, 13172, 13182, 13183,
13184, 13185, 13186, 13196, 13201,
13203, 13204, 13225, 13228, 13230,
13240, 13252, 13272, 13289, 13292,
13299, 13306, 13322, 13349, 13455,
13457, 13459, 13460, 13461, 13463,
13464, 13465, 13467, 13483, 13668,
13673, 13900, 13946, 13955, 13957,
14634, 14792, 15249, 15264, 15288,
15308, 15309, 15435, 15460, 15461,
15475, 15476, 15513, 15514, 15627,
15628, 15629, 15638, 15654, 15658,
15722, 15723, 15726, 15737, 15738,
15746, 15747, 15749, 15750, 15751,
15753, 15754, 15755, 15767, 15770,
15774, 15777, 15797, 15847, 15850,
15853, 15873, 15874, 15876, 15877,
15878, 15886, 15889, 15900, 15901,
15903, 15912, 15988, 16140, 16174,
16175, 16178, 16259, 16397, 16405,
16407, 16584, 16593, 16595, 16600,
16608, 16610, 16612, 16615, 17116,
17128, 17130, 17339, 17356, 17358,
17539, 17558, 17560, 17561, 17564,
17581, 17584, 17587, 17612, 17613,
17615, 17631, 17720, 17733, 17735,
17738, 17743, 17805, 17818, 17820,
17833, 17835, 17848, 17850, 17863,
17865, 17878, 17880, 17893, 17903,
18404, 18420, 18421, 18425, 18436,
18543, 18556, 18558, 18574, 18577,
18587, 18610, 18621, 18623, 18637,
18639, 18644, 18706, 18727, 18730,
18760, 18781, 18784, 18834, 18850,
18853, 18929, 18930, 19045, 19047,
19079, 19342, 19350, 19353, 19429
\ s _fp <type> 663
\ s _fp_division 13177
\ s _fp_exact 13177, 13182,
13183, 13184, 13185, 13186, 15722
\ s _fp_invalid 13177
\ s _fp_mark 649, 670,
674, 695, 698, 13175, 13524, 13525,
13527, 13531, 14841, 14854, 14936
\ s _fp_overflow 13177, 13203
\ s _fp_stop 641,
13175, 13363, 14743, 14842, 14846,
14855, 15804, 15815, 15825, 15833
\ s _fp_tuple 639,
13273, 13279, 13280, 13357, 13359,
15031, 15241, 15256, 15281, 15283,
15300, 15301, 15303, 15505, 15506,
16646, 16647, 16653, 16654, 18656
\ s _fp_underflow 13177, 13201
\ s _prop 520, 520, 524,
529, 1024, 1025, 9059, 9059, 9060,
9063, 9105, 9137, 9151, 9154, 9206,
9209, 9245, 9268, 9290, 9294, 9328,
9331, 9343, 25967, 25970, 25987, 25992
\ quark _if_empty_if:n 5800
\ quark _if_nil:w 423, 5800
\ quark _if_no_value:w 5800
\ quark _if_recursion_tail:w ...
..... 422, 5752, 5779
\ s _seq ... 425, 428, 428, 434, 439,
1025, 5847, 5856, 5886, 5891, 5896,
5901, 5934, 5960, 5968, 5972, 6148,
6196, 6333, 25997, 26003, 26044, 26054
\ s _tl 850, 851, 851, 852,
853, 860, 861, 861, 19864, 19865,
20084, 20115, 20121, 20146, 20164,
20169, 20183, 20195, 20218, 20221
\ q _tl_act_mark
..... 393, 393, 393, 4698, 4703, 4720
\ q _tl_act_stop
..... 393, 4698, 4703, 4707, 4716,
4718, 4724, 4729, 4732, 4736, 4739
\ quitv mode 798, 1612

R
\ r 27411
\ radical 523
\ raise 524
\ rand 200
\ randint 200
\ randomseed 1034, 1644
\ read 525
\ readline 661, 1475
\ ref 27459
regex commands:
\ c _foo_regex 207
\ regex _<g> set:Nn 214

- \regex_const:Nn [207](#), [214](#), [22948](#)
- \regex_count:NnN [215](#), [22991](#)
- \regex_count:nnN [215](#), [946](#), [22991](#)
- \regex_extract_all:NnN [215](#), [22995](#)
- \regex_extract_all:nnN
 [208](#), [215](#), [867](#), [22995](#)
- \regex_extract_all:NnNTF . [215](#), [22995](#)
- \regex_extract_all:nnNTF . [215](#), [22995](#)
- \regex_extract_once:NnN . . [215](#), [22995](#)
- \regex_extract_once:nnN
 [215](#), [215](#), [22995](#)
- \regex_extract_once:NnNTF [215](#), [22995](#)
- \regex_extract_once:nnNTF
 [212](#), [215](#), [22995](#)
- \regex_gset:Nn [214](#), [22948](#)
- \regex_match:NnTF [214](#), [22981](#)
- \regex_match:nnTF [214](#), [22981](#)
- \regex_new:N [214](#),
 [870](#), [22942](#), [22944](#), [22945](#), [22946](#), [22947](#)
- \regex_replace_all:NnN . . . [216](#), [22995](#)
- \regex_replace_all:nnN [208](#), [216](#), [22995](#)
- \regex_replace_all:NnNTF . [216](#), [22995](#)
- \regex_replace_all:nnNTF . [216](#), [22995](#)
- \regex_replace_once:NnN . . [216](#), [22995](#)
- \regex_replace_once:nnN
 [215](#), [216](#), [22995](#)
- \regex_replace_once:NnNTF [216](#), [22995](#)
- \regex_replace_once:nnNTF [216](#), [22995](#)
- \regex_set:Nn [214](#), [22948](#)
- \regex_show:N [214](#), [22963](#)
- \regex_show:n [207](#), [214](#), [22963](#)
- \regex_split:NnN [216](#), [22995](#)
- \regex_split:nnN [216](#), [22995](#)
- \regex_split:NnNTF [216](#), [22995](#)
- \regex_split:nnNTF [216](#), [22995](#)
- \g_tmpa_regex [216](#), [22944](#)
- \l_tmpa_regex [216](#), [22944](#)
- \g_tmpb_regex [216](#), [22944](#)
- \l_tmpb_regex [216](#), [22944](#)
- regex internal commands:
- _regex_action_cost:n . [912](#), [916](#),
 [924](#), [22035](#), [22036](#), [22044](#), [22519](#), [22545](#)
- _regex_action_free:n
 [217](#), [912](#), [924](#), [22058](#), [22064](#),
 [22065](#), [22076](#), [22141](#), [22145](#), [22170](#),
 [22195](#), [22199](#), [22202](#), [22230](#), [22238](#),
 [22248](#), [22262](#), [22293](#), [22517](#), [22521](#)
- _regex_action_free_aux:nn . . [22521](#)
- _regex_action_free_group:n [217](#),
 [912](#), [924](#), [22088](#), [22210](#), [22213](#), [22521](#)
- _regex_action_start_wildcard: .
 [912](#), [21951](#), [22514](#)
- _regex_action_submatch:n
 [912](#), [22164](#), [22165](#), [22291](#), [22565](#), [22567](#)
- _regex_action_success:
 [217](#), [912](#), [21954](#), [21974](#), [22572](#)
- _regex_action_wildcard: [929](#)
- _c_regex_all_catcodes_int
 [20785](#), [20907](#), [20997](#), [21597](#)
- _regex_anchor:N
 [881](#), [922](#), [21226](#), [21791](#), [22253](#)
- _c_regex_ascii_lower_int
 [20372](#), [20430](#), [20436](#)
- _c_regex_ascii_max_control_int .
 [20369](#), [20546](#)
- _c_regex_ascii_max_int
 [20369](#), [20539](#), [20547](#), [20737](#)
- _c_regex_ascii_min_int
 [20369](#), [20538](#), [20545](#)
- _regex_assertion:Nn [881](#),
 [922](#), [21226](#), [21251](#), [21260](#), [21785](#), [22253](#)
- _regex_b_test:
 [881](#), [922](#), [21251](#), [21260](#), [21790](#), [22253](#)
- _l_regex_balance_int [870](#),
 [936](#), [20367](#), [22333](#), [22352](#), [22470](#),
 [22474](#), [22475](#), [22663](#), [22692](#), [22885](#),
 [22902](#), [23197](#), [23223](#), [23246](#), [23250](#),
 [23251](#), [23258](#), [23259](#), [23263](#), [23264](#)
- _g_regex_balance_intarray
 [867](#), [870](#), [20364](#), [22469](#), [22633](#), [22648](#)
- _l_regex_balance_tl [217](#),
 [936](#), [938](#), [22588](#), [22664](#), [22693](#), [22755](#)
- _regex_branch:n
 [881](#), [899](#), [918](#), [20361](#), [20912](#),
 [21407](#), [21460](#), [21639](#), [21767](#), [22133](#)
- _regex_break_point:TF
 [871](#), [894](#), [916](#), [20373](#),
 [20379](#), [22035](#), [22036](#), [22259](#), [22282](#)
- _regex_break_true:w
 [871](#), [871](#), [20373](#), [20379](#), [20384](#),
 [20391](#), [20398](#), [20404](#), [20411](#), [20419](#),
 [20466](#), [20478](#), [20495](#), [21201](#), [22274](#)
- _regex_build:N
 [946](#), [21932](#), [22988](#), [22994](#), [22998](#), [23002](#)
- _regex_build:n
 [946](#), [21932](#), [22983](#), [22992](#), [22997](#), [23000](#)
- _regex_build_for_cs:n [20490](#), [21956](#)
- _regex_build_new_state:
 [21948](#), [21949](#),
 [21966](#), [21967](#), [21996](#), [22017](#), [22049](#),
 [22086](#), [22091](#), [22138](#), [22153](#), [22158](#),
 [22197](#), [22216](#), [22251](#), [22255](#), [22288](#)
- _l_regex_build_tl [899](#),
 [20358](#), [20904](#), [20911](#), [20929](#), [20934](#),
 [20937](#), [20938](#), [20941](#), [20942](#), [20945](#),
 [20991](#), [20994](#), [21027](#), [21041](#), [21045](#),
 [21170](#), [21184](#), [21225](#), [21250](#), [21259](#),
 [21269](#), [21301](#), [21314](#), [21318](#), [21400](#),

- 21403, 21406, 21412, 21413, 21416,
- 21459, 21726, 21742, 21760, 21766,
- 21821, 21824, 21829, 21859, 21874,
- 21878, 21881, 21887, 22662, 22681,
- 22696, 22699, 22720, 22752, 22814,
- 22817, 22832, 22876, 22892, 22928
- _regex_build_transition_-
- left:NNN [21992](#), [22199](#), [22213](#), [22230](#)
- _regex_build_transition_-
- right:nNn [21992](#),
- [22050](#), [22088](#), [22141](#), [22145](#), [22170](#),
- [22195](#), [22202](#), [22210](#), [22238](#), [22248](#)
- _regex_build_transitions_-
- lazyness:NNNNN [22015](#), [22057](#), [22063](#), [22075](#)
- \l_regex_capturing_group_int ...
- [868](#), [912](#), [952](#), [21931](#), [21946](#), [22104](#),
- [22106](#), [22117](#), [22118](#), [22126](#), [22127](#),
- [22130](#), [22751](#), [23156](#), [23228](#), [23236](#)
- \l_regex_case_changed_char_int .
- [872](#),
- [20400](#), [20403](#), [20414](#), [20417](#), [20418](#),
- [20425](#), [20429](#), [20435](#), [22306](#), [22439](#)
- \c_regex_catcode_A_int [20785](#)
- \c_regex_catcode_B_int [20785](#)
- \c_regex_catcode_C_int [20785](#)
- \c_regex_catcode_D_int [20785](#)
- \c_regex_catcode_E_int [20785](#)
- \c_regex_catcode_in_class_mode_-
- int [20775](#),
- [20896](#), [21268](#), [21429](#), [21522](#), [21551](#)
- \g_regex_catcode_intarray [867](#), [870](#), [20364](#), [22467](#), [22484](#)
- \c_regex_catcode_L_int [20785](#)
- \c_regex_catcode_M_int [20785](#)
- \c_regex_catcode_mode_int [20775](#),
- [20892](#), [20965](#), [21300](#), [21520](#), [21549](#)
- \c_regex_catcode_O_int [20785](#)
- \c_regex_catcode_P_int [20785](#)
- \c_regex_catcode_S_int [20785](#)
- \c_regex_catcode_T_int [20785](#)
- \c_regex_catcode_U_int [20785](#)
- \l_regex_catcodes_bool [20782](#), [21556](#), [21560](#), [21595](#)
- \l_regex_catcodes_int [882](#),
- [20782](#), [20908](#), [20996](#), [20998](#), [21004](#),
- [21287](#), [21304](#), [21404](#), [21417](#), [21516](#),
- [21553](#), [21588](#), [21590](#), [21596](#), [21597](#)
- _regex_char_if_alphanumeric:N [20755](#)
- _regex_char_if_alphanumeric:NTF
- [20733](#), [20958](#), [22859](#)
- _regex_char_if_special:N [20733](#)
- _regex_char_if_special:NTF [20733](#), [20954](#)
- \g_regex_charcode_intarray [867](#), [870](#), [20364](#), [22465](#), [22481](#)
- _regex_chk_c_allowed:TF [20877](#), [21509](#)
- _regex_class:NnnnN [881](#), [889](#), [890](#), [896](#),
- [20362](#), [20992](#), [21295](#), [21296](#), [21302](#),
- [21655](#), [21734](#), [21744](#), [21782](#), [22029](#)
- \c_regex_class_mode_int [20775](#), [20882](#), [20897](#)
- _regex_class_repeat:n [916](#), [22039](#), [22045](#), [22061](#), [22070](#)
- _regex_class_repeat:nN [22040](#), [22054](#)
- _regex_class_repeat:nnN [22041](#), [22068](#)
- _regex_command_K: [881](#), [21760](#), [21783](#), [22286](#)
- _regex_compile:n [20947](#),
- [21934](#), [22950](#), [22955](#), [22960](#), [22965](#)
- _regex_compile:w [888](#), [20901](#), [20949](#), [21602](#)
- _regex_compile\$: [21221](#)
- _regex_compile(: [21424](#)
- _regex_compile): [21463](#)
- _regex_compile.: [21192](#)
- _regex_compile/A: [21221](#)
- _regex_compile/B: [21245](#)
- _regex_compile/b: [21245](#)
- _regex_compile/c: [21508](#)
- _regex_compile/D: [21204](#)
- _regex_compile/d: [21204](#)
- _regex_compile/G: [21221](#)
- _regex_compile/H: [21204](#)
- _regex_compile/h: [21204](#)
- _regex_compile/K: [21757](#)
- _regex_compile/N: [21204](#)
- _regex_compile/S: [21204](#)
- _regex_compile/s: [21204](#)
- _regex_compile/u: [21675](#)
- _regex_compile/V: [21204](#)
- _regex_compile/v: [21204](#)
- _regex_compile/W: [21204](#)
- _regex_compile/w: [21204](#)
- _regex_compile/Z: [21221](#)
- _regex_compile/z: [21221](#)
- _regex_compile[: [21279](#)
- _regex_compile]: [21263](#)
- _regex_compile^: [21221](#)
- _regex_compile_abort_tokens:n [21007](#), [21034](#), [21384](#), [21394](#)
- _regex_compile_anchor:NTF [21221](#)
- _regex_compile_c[:w [21545](#)

- `__regex_compile_c_C:NN` [21524](#), [21533](#)
- `__regex_compile_c_lbrack_add:N` .
..... [21545](#)
- `__regex_compile_c_lbrack_end:` [21545](#)
- `__regex_compile_c_lbrack_-`
 `loop:NN` [21545](#)
- `__regex_compile_c_test:NN` ... [21508](#)
- `__regex_compile_class:NN` [21309](#)
- `__regex_compile_class:TFNN`
..... [896](#), [21294](#), [21305](#), [21309](#)
- `__regex_compile_class_catcode:w`
..... [21286](#), [21298](#)
- `__regex_compile_class_normal:w` .
..... [21289](#), [21292](#)
- `__regex_compile_class_posix:NNNNw`
..... [21328](#)
- `__regex_compile_class_posix_-`
 `end:w` [21328](#)
- `__regex_compile_class_posix_-`
 `loop:w` [21328](#)
- `__regex_compile_class_posix_-`
 `test:w` [21282](#), [21328](#)
- `__regex_compile_cs_aux:Nn` ... [21611](#)
- `__regex_compile_cs_aux:NNnnN` [21611](#)
- `__regex_compile_end:`
..... [888](#), [20901](#), [20974](#), [21620](#)
- `__regex_compile_end_cs:` [20970](#), [21611](#)
- `__regex_compile_escaped:N`
..... [20959](#), [20976](#)
- `__regex_compile_group_begin:N` ..
.. [21398](#), [21446](#), [21451](#), [21469](#), [21471](#)
- `__regex_compile_group_end:`
..... [21398](#), [21466](#)
- `__regex_compile_lparen:w`
..... [21433](#), [21437](#)
- `__regex_compile_one:n`
.... [20986](#), [21136](#), [21142](#), [21196](#),
 [21207](#), [21210](#), [21220](#), [21375](#), [21627](#)
- `__regex_compile_quantifier:w` ...
..... [21005](#), [21016](#), [21274](#), [21418](#)
- `__regex_compile_quantifier*:w` .
..... [21050](#)
- `__regex_compile_quantifier+:w` .
..... [21050](#)
- `__regex_compile_quantifier?:w` .
..... [21050](#)
- `__regex_compile_quantifier_-`
 `abort:nNN`
.. [21025](#), [21060](#), [21079](#), [21092](#), [21115](#)
- `__regex_compile_quantifier_-`
 `braced_auxi:w` [21056](#)
- `__regex_compile_quantifier_-`
 `braced_auxii:w` [21056](#)
- `__regex_compile_quantifier_-`
 `braced_auxiii:w` [21056](#)
- `__regex_compile_quantifier_-`
 `lazyness:nnNN` [890](#), [21037](#), [21051](#),
 [21053](#), [21055](#), [21068](#), [21088](#), [21110](#)
- `__regex_compile_quantifier_-`
 `none:` [21021](#), [21023](#), [21025](#)
- `__regex_compile_range:Nw`
..... [21134](#), [21147](#)
- `__regex_compile_raw:N`
.... [20827](#), [20955](#), [20959](#), [20961](#),
 [20979](#), [20984](#), [21012](#), [21127](#), [21129](#),
 [21149](#), [21195](#), [21241](#), [21277](#), [21325](#),
 [21345](#), [21363](#), [21421](#), [21426](#), [21431](#),
 [21447](#), [21457](#), [21465](#), [21483](#), [21484](#),
 [21485](#), [21491](#), [21502](#), [21503](#), [21504](#),
 [21512](#), [21567](#), [21616](#), [21687](#), [21693](#)
- `__regex_compile_raw_error:N` ...
..... [21124](#),
 [21232](#), [21248](#), [21257](#), [21678](#), [21761](#)
- `__regex_compile_special:N`
..... [883](#), [20955](#), [20976](#),
 [21018](#), [21039](#), [21066](#), [21071](#), [21086](#),
 [21099](#), [21133](#), [21152](#), [21312](#), [21330](#),
 [21349](#), [21369](#), [21370](#), [21439](#), [21474](#),
 [21492](#), [21535](#), [21554](#), [21680](#), [21696](#)
- `__regex_compile_special_group_-`
 `:w` [21472](#)
- `__regex_compile_special_group_-`
 `::w` [21468](#)
- `__regex_compile_special_group_-`
 `i:w` [21472](#)
- `__regex_compile_special_group_-`
 `l:w` [21468](#)
- `__regex_compile_u_end:`
..... [21699](#), [21705](#), [21710](#)
- `__regex_compile_u_in_cs:`
..... [21716](#), [21719](#)
- `__regex_compile_u_in_cs_aux:n` ..
..... [21729](#), [21732](#)
- `__regex_compile_u_loop:NN` ... [21675](#)
- `__regex_compile_u_not_cs:`
..... [21714](#), [21738](#)
- `__regex_compile_|:` [21455](#)
- `__regex_compute_case_changed_-`
 `char:` [20401](#), [20415](#), [20423](#)
- `__regex_count:nnN` [22992](#), [22994](#), [23039](#)
- `\c_regex_cs_in_class_mode_int` ..
..... [20775](#), [21608](#)
- `\c_regex_cs_mode_int` . [20775](#), [21606](#)
- `\l_regex_cs_name_tl`
..... [20368](#), [20487](#), [20493](#)
- `\l_regex_curr_catcode_int` [20445](#),
 [20464](#), [20472](#), [20484](#), [22306](#), [22483](#)

- \l_regex_curr_char_int
 20383, 20389,
 20390, 20397, 20409, 20410, 20425,
 20426, 20427, 20428, 20434, 20465,
 21200, 22280, 22306, 22438, 22480
- _regex_curr_cs_to_str:
 20344, 20475, 20487
- \l_regex_curr_pos_int
 . 869, 20347, 21973, 22273, 22301,
 22334, 22336, 22339, 22353, 22360,
 22367, 22398, 22408, 22437, 22452,
 22466, 22468, 22470, 22471, 22472,
 22482, 22485, 22570, 22579, 23091
- \l_regex_curr_state_int
 924, 931, 22310, 22490,
 22496, 22497, 22499, 22504, 22507,
 22529, 22534, 22539, 22540, 22548
- \l_regex_curr_submatches_prop ..
 22311, 22405, 22509,
 22541, 22542, 22560, 22569, 22581
- \l_regex_default_catcodes_int ..
 882, 20782, 20906,
 20908, 21004, 21304, 21404, 21417
- _regex_disable_submatches: ...
 . 20489, 21603, 22562, 23033, 23042
- \l_regex_empty_success_bool ...
 . 22319, 22390, 22394, 22577, 23101
- _regex_escape_\u:w 20621
- _regex_escape_/a:w 20621
- _regex_escape_/break:w 20621
- _regex_escape_/e:w 20621
- _regex_escape_/f:w 20621
- _regex_escape_/n:w 20621
- _regex_escape_/r:w 20621
- _regex_escape_/t:w 20621
- _regex_escape_/x:w 20640
- _regex_escape_\:w 20605
- _regex_escape_break:w 20621
- _regex_escape_escaped:N
 20591, 20615, 20618
- _regex_escape_loop:N
 877, 20598, 20605, 20640,
 20676, 20684, 20685, 20702, 20711
- _regex_escape_raw:N
 . 878, 20592, 20618, 20629, 20631,
 20633, 20635, 20637, 20639, 20653
- _regex_escape_unescaped:N
 20590, 20608, 20618
- _regex_escape_use:nnnn
 876, 888, 20577, 20952, 22665
- _regex_escape_x:N 878, 20675, 20679
- _regex_escape_x_end:w .. 878, 20640
- _regex_escape_x_large:n 20640
- _regex_escape_x_loop:N
 878, 20672, 20688
- _regex_escape_x_loop_error: . 20688
- _regex_escape_x_loop_error:n ..
 20691, 20703, 20708
- _regex_escape_x_test:N
 878, 20643, 20657
- _regex_escape_x_testii:N ... 20657
- \l_regex_every_match_tl
 22318, 22412, 22416, 22425
- _regex_extract: 948, 23057,
 23063, 23075, 23152, 23196, 23219
- _regex_extract_all:nnN 23006, 23051
- _regex_extract_b:wn 23152
- _regex_extract_e:wn 23152
- _regex_extract_once:nnN
 23004, 23051
- _regex_extract_seq_aux:n
 23117, 23135
- _regex_extract_seq_aux:ww .. 23135
- \l_regex_fresh_thread_bool
 925, 931, 22292, 22298,
 22319, 22450, 22516, 22518, 22578
- _regex_get_digits:NTFw
 20813, 21058, 21073
- _regex_get_digits_loop:nw
 20816, 20819, 20822
- _regex_get_digits_loop:w ... 20813
- _regex_group:nnnN 881,
 899, 21446, 21451, 21776, 21952, 22101
- _regex_group_aux:nnnnN
 918, 22080, 22103, 22111, 22114
- _regex_group_aux:nnnnnN 918
- _regex_group_end_extract_seq:N
 23058, 23066, 23106, 23108
- _regex_group_end_replace:N ...
 23213, 23242, 23244
- \l_regex_group_level_int
 20774, 20905,
 20923, 20925, 20927, 21405, 21411
- _regex_group_no_capture:nnnN ..
 881, 21469, 21778, 22101
- _regex_group_repeat:nn 22096, 22148
- _regex_group_repeat:nnN
 22097, 22188
- _regex_group_repeat:nnnN
 22098, 22219
- _regex_group_repeat_aux:n
 919, 920, 22155, 22168, 22206, 22223
- _regex_group_resetting:nnnN ...
 881, 21471, 21780, 22112
- _regex_group_resetting_-
 loop:nnNn 22112

```

\__regex_group_submatches:nn ...
    .. 22156, 22161, 22191, 22207, 22221
\__regex_hexadecimal_use:N ... 20713
\__regex_hexadecimal_use:NNTF ...
    ..... 20674, 20683, 20693, 20713
\__regex_if_end_range:NN ..... 21147
\__regex_if_end_range:NNTF ... 21147
\__regex_if_in_class:TF .....
    ..... 20837, 20916, 20989,
    21005, 21131, 21194, 21265, 21281,
    21426, 21457, 21465, 23319, 23332
\__regex_if_in_class_or_catcode:TF
    .. 20857, 21223, 21247, 21256, 21677
\__regex_if_in_cs:TF .....
    ..... 20845, 21614, 23317, 23326
\__regex_if_match:nn .....
    ..... 22983, 22988, 23030
\__regex_if_raw_digit:NN ..... 20825
\__regex_if_raw_digit:NNTF .....
    ..... 20815, 20821, 20825
\__regex_if_two_empty_matches:TF
    .... 925, 22319, 22395, 22401, 22574
\__regex_if_within_catcode:TF ...
    ..... 20869, 21284
\__regex_int_eval:w .....
    .. 20306, 22601, 22602, 22613, 23173
\l_regex_internal_a_int .....
    ..... 891, 938, 20350,
    21058, 21069, 21080, 21089, 21093,
    21101, 21104, 21108, 21111, 21118,
    22062, 22065, 22071, 22076, 22157,
    22172, 22178, 22184, 22193, 22196,
    22200, 22203, 22208, 22211, 22214,
    22229, 22237, 22246, 22767, 22788
\l_regex_internal_a_tl .....
    .... 876, 906, 907, 908, 949, 952,
    20350, 20474, 20477, 20581, 20589,
    20596, 20603, 21352, 21357, 21373,
    21378, 21383, 21387, 21393, 21394,
    21622, 21633, 21682, 21712, 21724,
    21740, 21770, 21773, 21824, 21839,
    21881, 21888, 21987, 21988, 21989,
    21990, 22139, 22140, 22144, 22146,
    22969, 22978, 23202, 23232, 23262
\l_regex_internal_b_int .....
    .... 20350, 21073, 21102, 21105,
    21106, 21108, 21112, 21119, 22173,
    22178, 22183, 22229, 22237, 22246
\l_regex_internal_b_tl ..... 20350
\l_regex_internal_bool .....
    .. 20350, 21351, 21356, 21377, 21386
\l_regex_internal_c_int .....
    .. 20350, 22175, 22180, 22181, 22185
\l_regex_internal_regex .....
    . 887, 20798, 20945, 21624, 21630,
    21935, 22951, 22956, 22961, 22966
\l_regex_internal_seq ... 20350,
    21905, 21906, 21911, 21918, 21919,
    21920, 21922, 23112, 23130, 23133
\g_regex_internal_tl .....
    .. 20350, 20594, 20598, 21721, 21728
\__regex_item_caseful_equal:n ...
    ..... 881, 20381, 20506,
    20507, 20511, 20512, 20513, 20514,
    20515, 20524, 20529, 20547, 20565,
    20909, 21496, 21657, 21735, 21792
\__regex_item_caseful_range:nn ..
    ..... 881, 20381, 20503,
    20518, 20521, 20522, 20523, 20537,
    20544, 20551, 20553, 20555, 20558,
    20559, 20560, 20561, 20566, 20569,
    20574, 20575, 20910, 21498, 21794
\__regex_item_caseless_equal:n ..
    ..... 881, 20395, 21477, 21799
\__regex_item_caseless_range:nn .
    ..... 881, 20395, 21479, 21801
\__regex_item_catcode: ..... 20442
\__regex_item_catcode:nTF .....
    881, 897, 20442, 20998, 21306, 21806
\__regex_item_catcode_reverse:nTF
    ..... 882, 20442, 21307, 21808
\__regex_item_cs:n .....
    ..... 870, 882, 20482, 21630, 21815
\__regex_item_equal:n .....
    .... 20440, 20909, 21137, 21143,
    21173, 21186, 21187, 21476, 21495
\__regex_item_exact:nn .....
    ..... 882, 907, 20462, 21750, 21812
\__regex_item_exact_cs:n .....
    882, 904, 20462, 21632, 21747, 21814
\__regex_item_range:nn .....
    .. 20440, 20910, 21175, 21478, 21497
\__regex_item_reverse:n .....
    .... 217, 882, 897, 20376, 20461,
    20528, 21211, 21377, 21810, 22283
\l_regex_last_char_int .....
    ..... 22280, 22306, 22438
\l_regex_left_state_int .....
    21927, 21950, 21981, 21988, 22001,
    22011, 22018, 22021, 22022, 22024,
    22025, 22051, 22059, 22062, 22089,
    22140, 22142, 22152, 22172, 22192,
    22194, 22222, 22225, 22228, 22231,
    22243, 22256, 22265, 22289, 22296
\l_regex_left_state_seq .....
    ..... 21927, 21980, 21987, 22139

```

__regex_match:n
 [22325](#), [23036](#), [23046](#),
 [23056](#), [23065](#), [23090](#), [23192](#), [23222](#)
 \l__regex_match_count_int
 [946](#), [947](#), [23013](#), [23043](#), [23044](#), [23049](#)
 __regex_match_cs:n ... [20493](#), [22325](#)
 __regex_match_init: [22325](#)
 __regex_match_loop:
 [928](#), [931](#), [22411](#), [22434](#)
 __regex_match_once:
 [927](#), [929](#), [22342](#), [22370](#), [22392](#), [22430](#)
 __regex_match_one_active:n .. [22434](#)
 \l__regex_match_success_bool ...
 [926](#), [22322](#), [22404](#), [22420](#), [22427](#), [22576](#)
 \l__regex_max_active_int ... [913](#),
 [914](#), [21964](#), [22314](#), [22406](#), [22443](#),
 [22446](#), [22451](#), [22554](#), [22555](#), [22559](#)
 \l__regex_max_pos_int [934](#),
 [21236](#), [21237](#), [21244](#), [21899](#), [21973](#),
 [22301](#), [22339](#), [22356](#), [22367](#), [22452](#),
 [23091](#), [23096](#), [23102](#), [23211](#), [23240](#)
 \l__regex_max_state_int
 [912](#), [913](#), [914](#),
 [959](#), [21924](#), [21947](#), [21965](#), [22003](#),
 [22004](#), [22010](#), [22012](#), [22013](#), [22072](#),
 [22087](#), [22151](#), [22171](#), [22173](#), [22181](#),
 [22225](#), [22231](#), [22239](#), [22249](#), [22334](#),
 [22355](#), [22379](#), [22384](#), [22388](#), [23576](#)
 \l__regex_min_active_int
 [913](#), [914](#), [22314](#),
 [22384](#), [22406](#), [22443](#), [22445](#), [22451](#)
 \l__regex_min_pos_int
 [934](#), [21234](#), [21243](#),
 [21897](#), [22301](#), [22336](#), [22360](#), [22386](#)
 \l__regex_min_state_int
 .. [913](#), [914](#), [21924](#), [21947](#), [21964](#),
 [21965](#), [22355](#), [22379](#), [22407](#), [23575](#)
 \l__regex_min_submatch_int
 [946](#), [949](#), [952](#), [22387](#),
 [22389](#), [23016](#), [23114](#), [23227](#), [23235](#)
 \l__regex_mode_int [20775](#),
 [20839](#), [20847](#), [20850](#), [20859](#), [20862](#),
 [20871](#), [20879](#), [20882](#), [20892](#), [20893](#),
 [20895](#), [20897](#), [20951](#), [20965](#), [20967](#),
 [21267](#), [21271](#), [21272](#), [21273](#), [21300](#),
 [21311](#), [21428](#), [21518](#), [21519](#), [21547](#),
 [21548](#), [21604](#), [21605](#), [21713](#), [21759](#)
 __regex_mode_quit_c:
 [20890](#), [20988](#), [21401](#)
 __regex_msg_repeated:nnN
 [21854](#), [21875](#), [21885](#), [23539](#)
 __regex_multi_match:n
 [925](#), [22414](#), [23044](#), [23063](#), [23071](#), [23219](#)
 \c__regex_no_match_regex
 [20359](#), [20798](#), [22943](#)
 \c__regex_outer_mode_int
 [20775](#), [20850](#), [20862](#), [20871](#), [20879](#),
 [20893](#), [20951](#), [20967](#), [21713](#), [21759](#)
 __regex_pop_lr_states:
 [21970](#), [21978](#), [22094](#)
 __regex_posix_alnum: [20531](#)
 __regex_posix_alpha: [20531](#)
 __regex_posix_ascii: [20531](#)
 __regex_posix_blank: [20531](#)
 __regex_posix_cntrl: [20531](#)
 __regex_posix_digit: [20531](#)
 __regex_posix_graph: [20531](#)
 __regex_posix_lower: [20531](#)
 __regex_posix_print: [20531](#)
 __regex_posix_punct: [20531](#)
 __regex_posix_space: [20531](#)
 __regex_posix_upper: [20531](#)
 __regex_posix_word: [20531](#)
 __regex_posix_xdigit: [20531](#)
 __regex_prop_: [894](#), [21192](#)
 __regex_prop_d: ... [894](#), [20502](#), [20549](#)
 __regex_prop_h: [20502](#), [20541](#)
 __regex_prop_N: [20502](#), [21220](#)
 __regex_prop_s: [20502](#)
 __regex_prop_v: [20502](#)
 __regex_prop_w:
 .. [20502](#), [20570](#), [22281](#), [22283](#), [22284](#)
 __regex_push_lr_states:
 [21968](#), [21978](#), [22092](#)
 __regex_query_get:
 [22410](#), [22440](#), [22478](#)
 __regex_query_range:nn [934](#), [22593](#),
 [22598](#), [22617](#), [22705](#), [23206](#), [23239](#)
 __regex_query_range_loop:ww . [22598](#)
 __regex_query_set:nnn
 [926](#), [22335](#), [22338](#),
 [22340](#), [22359](#), [22363](#), [22368](#), [22463](#)
 __regex_query_submatch:n
 [22615](#), [22753](#), [23146](#)
 __regex_replace_all:nnN [23010](#), [23216](#)
 __regex_replace_once:nnN
 [23008](#), [23186](#)
 __regex_replacement:n
 [22656](#), [23191](#), [23221](#)
 __regex_replacement_aux:n ... [22656](#)
 __regex_replacement_balance_
 one_match:n [217](#),
 [933](#), [934](#), [22589](#), [22690](#), [23199](#), [23230](#)
 __regex_replacement_c:w [22797](#)
 __regex_replacement_c_A:w [937](#), [22878](#)
 __regex_replacement_c_B:w ... [22881](#)
 __regex_replacement_c_C:w ... [22890](#)

_regex_replacement_c_D:w ... [22895](#)
 _regex_replacement_c_E:w ... [22898](#)
 _regex_replacement_c_L:w ... [22907](#)
 _regex_replacement_c_M:w ... [22910](#)
 _regex_replacement_c_O:w ... [22913](#)
 _regex_replacement_c_P:w ... [22916](#)
 _regex_replacement_c_S:w ... [22922](#)
 _regex_replacement_c_T:w ... [22930](#)
 _regex_replacement_c_U:w ... [22933](#)
 _regex_replacement_cat:NNN ...
 ... [22805](#), [22838](#)
 \l_regex_replacement_category_-
 seq ... [22586](#),
 [22684](#), [22687](#), [22688](#), [22724](#), [22852](#)
 \l_regex_replacement_category_-
 tl ... [937](#), [22586](#),
 [22719](#), [22725](#), [22731](#), [22853](#), [22854](#)
 _regex_replacement_char:nNN ...
 ... [944](#), [22873](#),
 [22880](#), [22887](#), [22897](#), [22904](#), [22909](#),
 [22912](#), [22915](#), [22919](#), [22932](#), [22935](#)
 \l_regex_replacement_csnames_-
 int ... [933](#), [22585](#), [22678](#),
 [22680](#), [22682](#), [22754](#), [22813](#), [22820](#),
 [22831](#), [22833](#), [22843](#), [22884](#), [22901](#)
 _regex_replacement_cu_aux:Nw ...
 ... [22802](#), [22811](#), [22826](#)
 _regex_replacement_do_one_-
 match:n . [22591](#), [22703](#), [23204](#), [23238](#)
 _regex_replacement_error:NNN ...
 ... [22768](#), [22780](#),
 [22791](#), [22806](#), [22809](#), [22827](#), [22937](#)
 _regex_replacement_escaped:N ...
 ... [22674](#), [22737](#), [22857](#)
 _regex_replacement_exp_not:N ...
 ... [940](#), [22597](#), [22802](#)
 _regex_replacement_g:w ... [22763](#)
 _regex_replacement_g_digits:NN
 ... [22763](#)
 _regex_replacement_normal:n ...
 [22670](#), [22675](#), [22717](#), [22744](#), [22766](#),
 [22772](#), [22799](#), [22825](#), [22835](#), [22850](#)
 _regex_replacement_put_-
 submatch:n ... [22742](#), [22749](#), [22787](#)
 _regex_replacement_rbrace:N ...
 ... [22668](#), [22786](#), [22829](#)
 _regex_replacement_u:w ... [22822](#)
 _regex_return: ...
 [946](#), [22984](#), [22989](#), [23000](#), [23002](#), [23022](#)
 \l_regex_right_state_int ...
 ... [21927](#), [21953](#), [21971](#), [21983](#),
 [21990](#), [22002](#), [22011](#), [22012](#), [22051](#),
 [22058](#), [22064](#), [22077](#), [22087](#), [22089](#),
 [22142](#), [22146](#), [22157](#), [22171](#), [22180](#),
 [22192](#), [22196](#), [22200](#), [22203](#), [22208](#),
 [22211](#), [22214](#), [22222](#), [22236](#), [22239](#),
 [22242](#), [22245](#), [22249](#), [22265](#), [22296](#)
 \l_regex_right_state_seq ...
 ... [21927](#), [21982](#), [21989](#), [22144](#)
 \l_regex_saved_success_bool ...
 ... [926](#), [20491](#), [20498](#), [22322](#)
 _regex_show:N . [21763](#), [22966](#), [22975](#)
 _regex_show_anchor_to_str:N ...
 ... [21791](#), [21892](#)
 _regex_show_class:NnnnN ...
 ... [21782](#), [21856](#)
 _regex_show_group_aux:nnnnN ...
 ... [21777](#), [21779](#), [21781](#), [21847](#)
 _regex_show_item_catcode:NnTF .
 ... [21807](#), [21809](#), [21903](#)
 _regex_show_item_exact_cs:n ...
 ... [21814](#), [21916](#)
 \l_regex_show_lines_int ...
 ... [20800](#), [21828](#), [21860](#), [21863](#), [21870](#)
 _regex_show_one:n ... [21771](#),
 [21784](#), [21787](#), [21793](#), [21796](#), [21800](#),
 [21803](#), [21813](#), [21817](#), [21826](#), [21842](#),
 [21849](#), [21853](#), [21866](#), [21882](#), [21921](#)
 _regex_show_pop: ... [21836](#), [21852](#)
 \l_regex_show_prefix_seq ...
 ... [20799](#), [21769](#),
 [21772](#), [21818](#), [21832](#), [21837](#), [21839](#)
 _regex_show_push:n ...
 ... [21819](#), [21836](#), [21850](#), [21861](#)
 _regex_show_scope:nn ...
 ... [21811](#), [21816](#), [21836](#), [21908](#)
 _regex_single_match: ...
 [925](#), [20488](#), [22414](#), [23034](#), [23054](#), [23189](#)
 _regex_split:nnN ... [23012](#), [23068](#)
 _regex_standard_escapechar: ...
 ... [20310](#), [20313](#), [20593](#), [20950](#), [21945](#)
 \l_regex_start_pos_int ...
 ... [21235](#), [21898](#),
 [22301](#), [22398](#), [22403](#), [22409](#), [23074](#),
 [23086](#), [23099](#), [23102](#), [23176](#), [23240](#)
 \g_regex_state_active_intarray .
 ... [867](#), [913](#), [925](#), [925](#), [926](#), [22316](#),
 [22382](#), [22495](#), [22498](#), [22506](#), [22533](#)
 \l_regex_step_int ...
 ... [867](#), [22313](#), [22385](#), [22436](#),
 [22496](#), [22500](#), [22508](#), [22522](#), [22524](#)
 _regex_store_state:n ...
 ... [22407](#), [22547](#), [22550](#)
 _regex_store_submatches: ...
 ... [22550](#), [22564](#)
 _regex_submatch_balance:n ...
 ... [22590](#), [22621](#), [22694](#), [22757](#), [23138](#)

- \g_regex_submatch_begin_intarray 867, 933, 22595, 22618, 22643, 22651, 22712, 23019, 23081, 23084, 23097, 23158, 23182
- \g_regex_submatch_end_intarray 867, 22619, 22628, 22636, 23019, 23078, 23094, 23160, 23185, 23208
- \l_regex_submatch_int 868, 946, 948, 949, 952, 22389, 23016, 23093, 23095, 23098, 23100, 23103, 23115, 23155, 23159, 23161, 23163, 23164, 23229, 23237
- \g_regex_submatch_prev_intarray 867, 946, 950, 22594, 22708, 23019, 23076, 23092, 23162, 23175
- \g_regex_success_bool 926, 20492, 20494, 20497, 22322, 22377, 22419, 22428, 23024, 23154, 23193
- \l_regex_success_pos_int 22301, 22386, 22403, 22579, 23074
- \l_regex_success_submatches_prop 924, 950, 22311, 22580, 23166
- __regex_tests_action_cost:n 22029, 22050, 22059, 22077
- \g_regex_thread_state_intarray 867, 913, 923, 925, 925, 932, 22316, 22460, 22553
- __regex_tmp:w 20332, 20334, 20338, 20340, 20349, 21204, 21214, 21215, 21216, 21217, 21218, 21229, 21234, 21235, 21236, 21237, 21238, 21243, 21244, 22995, 23004, 23006, 23008, 23010, 23012
- __regex_toks_clear:N 20316, 22010
- __regex_toks_memcpy:Nn 20321, 22182
- __regex_toks_put_left:Nn 20330, 21993, 22164, 22165
- __regex_toks_put_right:Nn 869, 20330, 21950, 21953, 21971, 21995, 22018, 22256, 22289
- __regex_toks_set:Nn 20316, 22471, 22559
- __regex_toks_use:w 20315, 22461, 22497, 22611, 23579
- __regex_trace:nnn 21998, 22328, 22347, 22373, 22489, 23555, 23578
- __regex_trace_pop:nnN 20582, 21941, 21960, 22082, 22135, 22330, 22349, 22658, 23555
- __regex_trace_push:nnN 20579, 21938, 21957, 22081, 22134, 22327, 22346, 22657, 23555
- \g_regex_trace_regex_int 23569
- __regex_trace_states:n 21940, 21959, 23570
- __regex_two_if_eq:NNNN 20801
- __regex_two_if_eq:NNNTF 20801, 21039, 21086, 21099, 21133, 21312, 21349, 21369, 21370, 21439, 21474, 21491, 21492, 21554, 21680, 22765, 22824, 22850
- __regex_use_state: 22487, 22510, 22536
- __regex_use_state_and_submatches:nn 929, 22459, 22502
- \l__regex_zeroth_submatch_int 946, 950, 23016, 23077, 23079, 23082, 23085, 23155, 23173, 23176, 23200, 23205, 23209
- \regular_expression 216
- \relax 14, 21, 39, 43, 49, 90, 92, 93, 94, 105, 130, 153, 174, 188, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 526
- \relpenalty 527
- \RequirePackage 156
- \resettimer 887
- reverse commands:
 - \reverse_if:N 20, 418, 448, 449, 673, 2049, 5636, 6498, 6676, 6678, 6680, 6682, 6747, 7580, 11492, 11497, 11501, 11503, 14062, 17601, 18353, 18376, 20389, 20390, 20409, 20410, 20417, 20418, 25338, 25340, 25359, 25383
- \right 528
- right commands:
 - \c_right_brace_str 62, 5688, 20701, 21066, 21086, 21099, 21612, 21616, 21698, 22667
 - \rightghost 995, 1824
 - \righthyphenmin 529
 - \rightmarginkern 799, 1613
 - \rightskip 530
 - \romannumeral 531
 - round 197
 - \rptcode 800, 1614
 - \rule 24879, 24934
- S**
- s@ internal commands:
 - \s@_ 853
 - \saveboxresource 1038, 1648
 - \savecatcodetable 996, 1796
 - \saveimageresource 1039, 1649
 - \savepos 1037, 1647

- \savingsphcodes 662, 1476
- \savingsvdiscards 663, 1477
- scan commands:
 - \scan_align_safe_stop: 29468
 - \scan_new:N
 - 66, 5829, 5842, 5847, 9059,
 - 13172, 13175, 13176, 13177, 13178,
 - 13179, 13180, 13181, 13273, 19865
 - \scan_stop: 8, 66, 66, 79, 128, 129,
 - 129, 129, 258, 272, 309, 312, 312,
 - 321, 335, 335, 337, 349, 350, 361,
 - 375, 378, 391, 418, 424, 449, 454,
 - 469, 510, 510, 517, 519, 520, 529,
 - 552, 584, 584, 584, 590, 670, 673,
 - 674, 675, 679, 882, 904, 1064, 2077,
 - 2336, 2354, 2367, 2432, 2437, 2453,
 - 2458, 2742, 2760, 2770, 2788, 2814,
 - 3200, 3635, 3766, 3806, 3832, 3856,
 - 3873, 3997, 4003, 4250, 4274, 5637,
 - 5839, 6146, 6892, 8669, 8741, 8961,
 - 9036, 9045, 9054, 10476, 10478,
 - 10647, 10649, 11348, 11378, 11381,
 - 11386, 11390, 11394, 11399, 11405,
 - 11410, 11666, 11738, 11767, 11770,
 - 11779, 11782, 11787, 11790, 11820,
 - 11833, 11843, 11872, 11909, 11912,
 - 11923, 11926, 11931, 11934, 11945,
 - 11998, 12022, 12061, 12066, 12068,
 - 12089, 12091, 12936, 12944, 13158,
 - 13337, 14060, 14064, 14267, 14284,
 - 14584, 14631, 14632, 14891, 14934,
 - 14964, 15700, 17511, 17519, 18195,
 - 18198, 18201, 18204, 18207, 18210,
 - 18213, 18216, 18219, 19479, 19987,
 - 20027, 20031, 20037, 20039, 20086,
 - 20088, 20475, 20476, 20823, 21641,
 - 21918, 22482, 22485, 22512, 22875,
 - 22927, 23596, 23729, 24875, 24930,
 - 26169, 26170, 26402, 26405, 26423,
 - 27653, 27656, 27658, 27882, 28282,
 - 28288, 28445, 28488, 28499, 29511
- scan internal commands:
 - \g_scan_marks_tl ... 5828, 5832, 5838
 - \scantextokens 997, 1797
 - \scantokens 664, 1478
 - \scriptfont 532
 - \scriptscriptfont 533
 - \scriptscriptstyle 534
 - \scriptspace 535
 - \scriptstyle 536
 - \scrollmode 537
 - sec 197
 - secd 198
- seq commands:
 - \c_empty_seq 77, 426, 5856,
 - 5860, 5864, 5867, 6049, 6080, 6088
 - \l_foo_seq 212
 - \seq_clear:N 68, 68, 77, 5863, 5870,
 - 5993, 9793, 9856, 11266, 21818, 22688
 - \seq_clear_new:N 68, 5869
 - \seq_concat:NNN .. 69, 77, 5946, 11274
 - \seq_const_from_clist:Nn . 248, 26051
 - \seq_count:N 70, 74, 76, 181,
 - 6207, 6221, 6285, 6313, 22687, 26066
 - \seq_elt:w 425
 - \seq_elt_end: 425
 - \seq_gclear:N
 - ... 68, 840, 5863, 5873, 19601, 26081
 - \seq_gclear_new:N 68, 5869
 - \seq_gconcat:NNN 69, 5946, 11286
 - \seq_get:NN ... 75, 6366, 22139, 22144
 - \seq_get:NNTF 75, 6372
 - \seq_get_left:NN
 - 69, 6096, 6366, 6367, 6372, 6373
 - \seq_get_left:NNTF 71, 6166
 - \seq_get_right:NN 70, 6121
 - \seq_get_right:NNTF 71, 6166
 - \seq_gpop:NN 75, 6366, 11211
 - \seq_gpop:NNTF 76, 6372, 10460, 10631
 - \seq_gpop_left:NN
 - 70, 6107, 6370, 6371, 6376, 6377
 - \seq_gpop_left:NNTF 71, 6174
 - \seq_gpop_right:NN 70, 6139
 - \seq_gpop_right:NNTF 72, 6174
 - \seq_gpush:Nn
 - ... 22, 76, 6346, 10487, 10659, 11194
 - \seq_gput_left:Nn
 - . 69, 5956, 6356, 6357, 6358, 6359,
 - 6360, 6361, 6362, 6363, 6364, 6365
 - \seq_gput_right:Nn 69, 5977,
 - 11057, 11064, 11077, 11180, 11185
 - \seq_gremove_all:Nn . 72, 6003, 10599
 - \seq_gremove_duplicates:N .. 72, 5987
 - \seq_greverse:N 72, 6029
 - \seq_gset_eq:NN
 - .. 68, 5867, 5875, 5990, 19575, 26063
 - \seq_gset_filter:NNn 248, 26017
 - \seq_gset_from_clist:NN 68, 5883
 - \seq_gset_from_clist:Nn 68, 5883
 - \seq_gset_from_function:NnN
 - 248, 26047
 - \seq_gset_from_inline_x:Nnn
 - 249, 19593, 26037, 26050, 26076
 - \seq_gset_map:NNn 248, 26027
 - \seq_gset_split:Nnn
 - 69, 5909, 10405, 10593
 - \seq_gshuffle:N 249, 26057

- `\seq_gsort:Nn` [72](#), [6047](#), [19571](#)
 - `\seq_if_empty:N` [72](#), [6047](#), [6220](#), [7844](#), [22684](#)
 - `\seq_if_empty_p:N` [72](#), [6047](#)
 - `\seq_if_exist:N` [69](#), [5870](#), [5873](#), [5952](#), [6311](#)
 - `\seq_if_exist_p:N` [69](#), [5952](#)
 - `\seq_if_in:Nn` [492](#)
 - `\seq_if_in:NnTF` [73](#), [76](#), [77](#), [5996](#), [6057](#), [10486](#), [10658](#)
 - `\seq_indexed_map_function:NN` [249](#), [26110](#)
 - `\seq_indexed_map_inline:Nn` [249](#), [26110](#)
 - `\seq_item:Nn` [70](#), [215](#), [436](#), [6194](#), [6221](#), [9874](#), [9875](#), [9880](#)
 - `\seq_log:N` [78](#), [6378](#)
 - `\seq_map_break:` [73](#), [248](#), [248](#), [6224](#), [6235](#), [6270](#), [6281](#), [12716](#), [26113](#), [26122](#)
 - `\seq_map_break:n` [74](#), [436](#), [6224](#), [9813](#), [9827](#), [11123](#), [19572](#), [19575](#)
 - `\seq_map_function:NN` [4](#), [73](#), [246](#), [1028](#), [6228](#), [6388](#), [7850](#), [9878](#), [11277](#), [21832](#), [21911](#)
 - `\seq_map_inline:Nn` [73](#), [73](#), [77](#), [1026](#), [5994](#), [6266](#), [9808](#), [11092](#), [11122](#), [12709](#), [19572](#), [19575](#)
 - `\seq_map_variable:NNn` [73](#), [6273](#)
 - `\seq_mapthread_function:NNN` [248](#), [25995](#)
 - `\seq_new:N` [4](#), [68](#), [68](#), [5857](#), [5870](#), [5873](#), [5986](#), [6392](#), [6393](#), [6394](#), [6395](#), [7995](#), [8454](#), [8457](#), [9763](#), [9764](#), [10403](#), [10590](#), [11048](#), [11072](#), [11085](#), [11087](#), [12133](#), [19433](#), [20356](#), [20799](#), [21929](#), [21930](#), [22587](#), [26061](#)
 - `\seq_pop:NN` [75](#), [6366](#), [21987](#), [21989](#), [22724](#)
 - `\seq_pop:NNTF` [76](#), [6372](#)
 - `\seq_pop_left:NN` [70](#), [6107](#), [6368](#), [6369](#), [6374](#), [6375](#)
 - `\seq_pop_left:NNTF` [71](#), [6174](#)
 - `\seq_pop_right:NN` [70](#), [6139](#), [21769](#), [21839](#)
 - `\seq_pop_right:NNTF` [71](#), [6174](#)
 - `\seq_push:Nn` [76](#), [6346](#), [6353](#), [21980](#), [21982](#), [22852](#)
 - `\seq_put_left:Nn` [69](#), [5956](#), [6346](#), [6347](#), [6348](#), [6349](#), [6350](#), [6351](#), [6352](#), [6353](#), [6354](#), [6355](#), [9803](#)
 - `\seq_put_right:Nn` [69](#), [76](#), [77](#), [5977](#), [5997](#), [9864](#), [21772](#), [21837](#), [29419](#)
 - `\seq_rand_item:N` [70](#), [6218](#)
 - `\seq_remove_all:Nn` [69](#), [72](#), [76](#), [77](#), [6003](#), [8021](#), [29421](#)
 - `\seq_remove_duplicates:N` [72](#), [76](#), [77](#), [5987](#), [11275](#)
 - `\seq_reverse:N` [72](#), [431](#), [6029](#)
 - `\seq_set_eq:NN` [68](#), [77](#), [5864](#), [5875](#), [5988](#), [19572](#), [26062](#)
 - `\seq_set_filter:NNn` [248](#), [1026](#), [21906](#), [26017](#)
 - `\seq_set_from_clist:NN` [68](#), [5883](#), [8020](#)
 - `\seq_set_from_clist:Nn` [68](#), [107](#), [1027](#), [5883](#), [11270](#), [11284](#), [12638](#)
 - `\seq_set_from_function:NnN` [248](#), [23112](#), [26047](#)
 - `\seq_set_from_inline_x:Nnn` [249](#), [1027](#), [26037](#), [26048](#)
 - `\seq_set_map:NNn` [248](#), [21919](#), [23130](#), [26027](#)
 - `\seq_set_split:Nnn` [69](#), [5909](#), [8455](#), [8458](#), [21905](#), [21918](#)
 - `\seq_show:N` [78](#), [540](#), [6378](#)
 - `\seq_shuffle:N` [249](#), [26057](#)
 - `\seq_sort:Nn` [72](#), [205](#), [6047](#), [19571](#)
 - `\seq_use:Nn` [75](#), [6309](#), [21922](#)
 - `\seq_use:Nnnn` [74](#), [6309](#)
 - `\g_tmpa_seq` [78](#), [6392](#)
 - `\l_tmpa_seq` [78](#), [6392](#)
 - `\g_tmpb_seq` [78](#), [6392](#)
 - `\l_tmpb_seq` [78](#), [6392](#)
- seq internal commands:
- `__seq_count:w` [438](#), [6285](#)
 - `__seq_count_end:w` [438](#), [6285](#)
 - `__seq_get_left:wnw` [6096](#)
 - `__seq_get_right_end:NnN` [6121](#)
 - `__seq_get_right_loop:nw` .. [434](#), [6121](#)
 - `__seq_if_in:` [6057](#)
 - `__seq_indexed_map:NN` [26112](#), [26120](#), [26125](#)
 - `__seq_indexed_map:nNN` [26110](#)
 - `__seq_indexed_map:Nw` .. [1028](#), [26110](#)
 - `\l_seq_internal_a_int` [26057](#)
 - `\l_seq_internal_a_tl` [427](#), [5853](#), [5917](#), [5921](#), [5927](#), [5932](#), [5934](#), [6018](#), [6023](#), [6061](#), [6065](#)
 - `\l_seq_internal_b_int` [26057](#)
 - `\l_seq_internal_b_tl` [5853](#), [6014](#), [6018](#), [6064](#), [6065](#)
 - `\g__seq_internal_seq` [26057](#)
 - `__seq_item:n` . [425](#), [425](#), [425](#), [425](#), [429](#), [432](#), [433](#), [434](#), [435](#), [436](#), [437](#), [437](#), [438](#), [439](#), [1025](#), [1026](#), [1026](#), [5848](#), [5960](#), [5968](#), [5978](#), [5980](#), [5985](#), [6035](#), [6036](#), [6038](#), [6043](#), [6062](#), [6101](#), [6104](#), [6114](#), [6129](#), [6132](#), [6145](#), [6146](#), [6157](#), [6201](#), [6210](#), [6234](#), [6237](#), [6247](#), [6252](#), [6258](#), [6262](#), [6292](#), [6293](#), [6294](#),

- 6295, 6296, 6297, 6298, 6299, 6304,
6305, 6320, 6335, 6338, 6341, 26033,
26043, 26044, 26073, 26133, 26135
- __seq_item:nN [6194](#)
- __seq_item:nwn [6194](#)
- __seq_item:wNn [6194](#)
- __seq_map_function:NNn [6228](#)
- __seq_map_function:Nw
..... [6231](#), [6237](#), [6241](#)
- __seq_mapthread_function:Nnnwnn
..... [25995](#)
- __seq_mapthread_function:wNN . [25995](#)
- __seq_mapthread_function:wNw . [25995](#)
- __seq_pop:NNNN
..... [6078](#), [6108](#), [6110](#), [6140](#), [6142](#)
- __seq_pop_item_def:
..... [425](#), [425](#), [6025](#),
[6244](#), [6270](#), [6281](#), [26025](#), [26035](#), [26045](#)
- __seq_pop_left:NNN . [6107](#), [6176](#), [6179](#)
- __seq_pop_left:wnwNNN [6107](#)
- __seq_pop_right:NNN
..... [430](#), [6139](#), [6182](#), [6185](#)
- __seq_pop_right_loop:nn [6139](#)
- __seq_pop_TF:NNNN [435](#), [6078](#),
[6167](#), [6169](#), [6176](#), [6179](#), [6182](#), [6185](#)
- __seq_push_item_def: [6244](#)
- __seq_push_item_def:n
..... [425](#), [425](#), [6009](#),
[6244](#), [6268](#), [6275](#), [26023](#), [26033](#), [26043](#)
- __seq_put_left_aux:w [428](#), [5956](#)
- __seq_remove_all_aux:NNn [6003](#)
- __seq_remove_duplicates:NN .. [5987](#)
- \l__seq_remove_seq
..... [5986](#), [5993](#), [5996](#), [5997](#), [5999](#)
- __seq_reverse:NN [6029](#)
- __seq_reverse_item:nw [431](#)
- __seq_reverse_item:nwn [6029](#)
- __seq_set_filter:NNNn [26017](#)
- __seq_set_from_inline_x:NNnn . [26037](#)
- __seq_set_map:NNNn [26027](#)
- __seq_set_split:NNnn [5909](#)
- __seq_set_split_auxi:w ... [427](#), [5909](#)
- __seq_set_split_auxii:w .. [427](#), [5909](#)
- __seq_set_split_end: [427](#), [5909](#)
- __seq_show:NN [6378](#)
- __seq_shuffle:NN [26057](#)
- __seq_shuffle_item:n [26057](#)
- __seq_tmp:w
..... [5855](#), [6035](#), [6038](#), [6145](#), [6157](#)
- __seq_use:NNnNnn [6309](#)
- __seq_use:nwnn [6309](#)
- __seq_use:nwwwnwn [6309](#)
- __seq_use_setup:w [6309](#)
- __seq_wrap_item:n
[427](#), [1026](#), [5886](#), [5891](#), [5896](#), [5901](#),
[5918](#), [5943](#), [5985](#), [6021](#), [26023](#), [26054](#)
- \setbox [538](#)
- \setfontid [998](#), [1798](#)
- \setlanguage [539](#)
- \setrandomseed [1040](#), [1650](#)
- \sfcode [190](#), [540](#)
- \sffamily [24868](#)
- \shapemode [999](#), [1799](#)
- \shellescape [888](#), [1620](#)
- \Shipout [1289](#)
- \shipout [541](#), [1276](#), [1277](#)
- \ShortText [75](#), [123](#), [140](#)
- \show [542](#)
- \showbox [543](#)
- \showboxbreadth [544](#)
- \showboxdepth [545](#)
- \showgroups [665](#), [1479](#)
- \showifs [666](#), [1480](#)
- \showlists [546](#)
- \showmode [1242](#), [2024](#)
- \showthe [547](#)
- \ShowTokens [206](#)
- \showtokens [667](#), [1481](#)
- sign [197](#)
- sin [197](#)
- sind [198](#)
- \sjis [1243](#), [2025](#)
- \skewchar [548](#)
- \skip [549](#), [8819](#)
- skip commands:
- \c_max_skip [164](#), [11854](#)
- \skip_add:Nn [162](#), [11777](#)
- \skip_const:Nn
..... [161](#), [598](#), [11734](#), [11854](#), [11855](#)
- \skip_eval:n [163](#), [163](#), [163](#),
[163](#), [11738](#), [11795](#), [11817](#), [11849](#), [11853](#)
- \skip_gadd:Nn [162](#), [11777](#)
- \skip_gset:N [172](#), [12530](#)
- \skip_gset:Nn [162](#), [593](#), [11765](#)
- \skip_gset_eq:NN [162](#), [11773](#)
- \skip_gsub:Nn [162](#), [11777](#)
- \skip_gzero:N [162](#), [11741](#), [11750](#)
- \skip_gzero_new:N [162](#), [11747](#)
- \skip_horizontal:N [164](#), [11824](#)
- \skip_horizontal:n
[164](#), [11824](#), [27924](#), [28312](#), [28523](#), [29055](#)
- \skip_if_eq:nnTF [163](#), [11793](#)
- \skip_if_eq_p:nn [163](#), [11793](#)
- \skip_if_exist:NTF
..... [162](#), [11748](#), [11750](#), [11753](#)
- \skip_if_exist_p:N [162](#), [11753](#)
- \skip_if_finite:nTF [163](#), [11799](#), [26167](#)

- \skip_if_finite_p:n [163](#), [11799](#)
- \skip_log:N [164](#), [11850](#)
- \skip_log:n [164](#), [11850](#)
- \skip_new:N
 - .. [161](#), [162](#), [11726](#), [11737](#), [11748](#),
 - [11750](#), [11856](#), [11857](#), [11858](#), [11859](#)
- .skip_set:N [172](#), [12530](#)
- \skip_set:Nn [162](#), [11765](#)
- \skip_set_eq:NN [162](#), [11773](#)
- \skip_show:N [163](#), [11846](#)
- \skip_show:n [163](#), [597](#), [11848](#)
- \skip_split_finite_else_action:nnNN
 - [249](#), [26165](#)
- \skip_sub:Nn [162](#), [11777](#)
- \skip_use:N
 - [163](#), [163](#), [11811](#), [11820](#), [11821](#)
- \skip_vertical:N [164](#), [11824](#)
- \skip_vertical:n [164](#), [11824](#)
- \skip_zero:N [162](#), [162](#), [165](#), [11741](#), [11748](#)
- \skip_zero_new:N [162](#), [11747](#)
- \g_tmpa_skip [164](#), [11856](#)
- \l_tmpa_skip [164](#), [11856](#)
- \g_tmpb_skip [164](#), [11856](#)
- \l_tmpb_skip [164](#), [11856](#)
- \c_zero_skip [164](#), [583](#), [11352](#), [11355](#),
 - [11742](#), [11744](#), [11854](#), [26173](#), [26174](#)
- skip internal commands:
 - __skip_if_finite:wwNw [11799](#)
 - __skip_tmp:w [594](#), [11757](#),
 - [11765](#), [11768](#), [11777](#), [11780](#), [11785](#),
 - [11788](#), [11799](#), [11816](#), [11893](#), [11907](#),
 - [11910](#), [11921](#), [11924](#), [11929](#), [11932](#)
- \skipdef [550](#)
- sort commands:
 - \sort_ordered: [29470](#)
 - \sort_return_same:
 - [205](#), [205](#), [842](#), [19654](#), [29471](#)
 - \sort_return_swapped:
 - [205](#), [205](#), [842](#), [19654](#), [29473](#)
 - \sort_reversed: [29472](#)
- sort internal commands:
 - __sort:nnNnn [844](#), [845](#)
 - \l_sort_A_int
 - . [842](#), [19443](#), [19448](#), [19455](#), [19458](#),
 - [19467](#), [19618](#), [19623](#), [19626](#), [19646](#),
 - [19678](#), [19685](#), [19700](#), [19702](#), [19703](#)
 - \l_sort_B_int
 - .. [842](#), [842](#), [19443](#), [19623](#), [19627](#),
 - [19635](#), [19637](#), [19638](#), [19690](#), [19691](#),
 - [19700](#), [19701](#), [19710](#), [19711](#), [19713](#)
 - \l_sort_begin_int
 - [836](#), [842](#), [19441](#), [19615](#), [19703](#), [19713](#)
 - \l_sort_block_int
 - [836](#), [837](#), [841](#), [19440](#), [19450](#),
 - [19455](#), [19459](#), [19462](#), [19467](#), [19468](#),
 - [19545](#), [19606](#), [19609](#), [19616](#), [19619](#)
 - \l_sort_C_int
 - .. [842](#), [842](#), [19443](#), [19624](#), [19628](#),
 - [19635](#), [19636](#), [19647](#), [19679](#), [19686](#),
 - [19690](#), [19692](#), [19693](#), [19710](#), [19712](#)
 - __sort_compare:nn
 - [839](#), [843](#), [19544](#), [19645](#)
 - __sort_compute_range:
 - [836](#), [837](#), [837](#), [19472](#), [19532](#)
 - __sort_copy_block: [841](#), [19625](#), [19633](#)
 - __sort_disable_toksdef: [19531](#), [19810](#)
 - __sort_disabled_toksdef:n ... [19810](#)
 - \l_sort_end_int [836](#), [841](#), [842](#), [842](#),
 - [19441](#), [19607](#), [19615](#), [19616](#), [19617](#),
 - [19618](#), [19619](#), [19620](#), [19621](#), [19638](#)
 - __sort_error: .. [19804](#), [19817](#), [19836](#)
 - __sort_i:nnnnNn [846](#)
 - \g_sort_internal_seq
 - [839](#), [840](#), [19433](#), [19593](#), [19600](#), [19601](#)
 - \g_sort_internal_tl
 - [19433](#), [19556](#), [19559](#), [19560](#)
 - \l_sort_length_int
 - [836](#), [836](#), [19435](#), [19542](#), [19606](#)
 - __sort_level:
 - [839](#), [849](#), [19546](#), [19604](#), [19808](#)
 - __sort_loop:wNn [845](#), [846](#)
 - __sort_main:NNNn
 - [839](#), [840](#), [19529](#), [19555](#), [19592](#)
 - \l_sort_max_int
 - [836](#), [837](#), [19435](#), [19452](#), [19526](#), [19536](#)
 - \c_sort_max_length_int [19472](#)
 - __sort_merge_blocks:
 - [19608](#), [19613](#), [19807](#)
 - __sort_merge_blocks_aux:
 - [841](#), [19629](#), [19643](#), [19696](#), [19706](#), [19806](#)
 - __sort_merge_blocks_end:
 - [844](#), [19704](#), [19708](#)
 - \l_sort_min_int [836](#), [837](#), [839](#), [839](#),
 - [19435](#), [19449](#), [19457](#), [19475](#), [19491](#),
 - [19499](#), [19512](#), [19524](#), [19533](#), [19543](#),
 - [19557](#), [19596](#), [19607](#), [19834](#), [19835](#)
 - __sort_quick_cleanup:w [19718](#)
 - __sort_quick_end:nnTFNn
 - [847](#), [848](#), [19738](#), [19778](#)
 - __sort_quick_only_i:NnnnnNn . [19743](#)
 - __sort_quick_only_i_end:nnnwnw .
 - [19754](#), [19778](#)
 - __sort_quick_only_ii:NnnnnNn . [19743](#)
 - __sort_quick_only_ii_end:nnnwnw
 - [19761](#), [19778](#)
 - __sort_quick_prepare:Nnnn ... [19718](#)
 - __sort_quick_prepare_end:NNNnw .
 - [19718](#)

- __sort_quick_single_end:nnwnw 19747, 19778
- __sort_quick_split:NnNn 846, 847, 19738, 19743, 19783, 19790, 19796, 19798
- __sort_quick_split_end:nnwnw 19768, 19775, 19778
- __sort_quick_split_i:NnnnnNn 845, 19743
- __sort_quick_split_ii:NnnnnNn 19743
- __sort_redefine_compute_range: 19472
- __sort_return_mark:w 842, 19649, 19650, 19654
- __sort_return_none_error: 842, 19652, 19654, 19688, 19698
- __sort_return_same:w 842, 19662, 19680, 19688
- __sort_return_swapped:w 19672, 19698
- __sort_return_two_error: 842, 19654
- __sort_seq:NNNNn 839, 19571
- __sort_shrink_range: 837, 838, 19446, 19477, 19493, 19501, 19514
- __sort_shrink_range_loop: . . . 19446
- __sort_tl:NnN 839, 19548
- __sort_tl_toks:w 839, 19548
- __sort_too_long_error:NNw 19537, 19829
- \l__sort_top_int 836, 839, 839, 842, 842, 19435, 19533, 19536, 19539, 19540, 19543, 19565, 19596, 19617, 19620, 19621, 19624, 19693, 19835
- \l__sort_true_max_int 836, 837, 19435, 19449, 19462, 19476, 19492, 19500, 19513, 19525, 19834
- sp 200
- spac commands:
 - \spac_directions_normal_body_dir 1404
 - \spac_directions_normal_page_dir 1405
- \space 55
- \spacefactor 551
- \spaceskip 552
- \span 553
- \special 554
- \splitbotmark 555
- \splitbotmarks 668, 1482
- \splitdiscards 669, 1483
- \splitfirstmark 556
- \splitfirstmarks 670, 1484
- \splitmaxdepth 557
- \splittopskip 558
- sqr 199
- \SS 27402
- \ss 27402
- str commands:
 - \c_ampersand_str 62, 5688
 - \c_at_sign_str 62, 5688
 - \c_backslash_str 62, 5688, 20611, 21183
 - \c_circumflex_str 62, 5688
 - \c_colon_str 62, 5688, 8732, 8837, 8843, 12227
 - \c_dollar_str 62, 5688
 - \c_hash_str 62, 5688, 25383, 25414, 25415, 25419, 29040, 29206, 29213, 29253
 - \c_percent_str 62, 5688, 29339, 29340, 29341
 - \str_case:nn 55, 5246, 10261, 21332, 26181
 - \str_case:nnn 29474, 29476
 - \str_case:nnTF 55, 587, 5246, 5251, 5256, 10148, 12380, 21895, 27015, 29475, 29477
 - \str_case_e:nn 55, 5246, 5707, 5708, 28220, 28459
 - \str_case_e:nnTF 55, 5246, 5282, 5287, 5709, 5710, 5711, 5712, 5713, 5714, 21064, 29479
 - \str_case_x:nn 5707
 - \str_case_x:nnn 29478
 - \str_case_x:nnTF 5707, 5710, 5712
 - \str_clear:N 52, 52, 5077, 11131, 11238, 11250
 - \str_clear_new:N 52, 5077
 - \str_concat:NNN 52, 5077
 - \str_const:Nn 51, 5104, 5688, 5689, 5690, 5691, 5692, 5693, 5694, 5695, 5696, 5697, 5698, 5699, 7706, 7710, 7735, 7754, 26179, 26266, 26273, 26277, 26281
 - \str_count:N 57, 5578, 9487, 9488, 9683, 9684, 9705, 9706, 10718, 10796, 20279
 - \str_count:n 57, 5578, 20273
 - \str_count_ignore_spaces:n 57, 417, 5578, 19894
 - \str_count_spaces:N 57, 5558
 - \str_count_spaces:n 57, 417, 5558, 5584
 - \str_fold_case:n 60, 61, 252, 257, 5646, 14253
 - \str_gclear:N 52, 5077
 - \str_gclear_new:N 5077
 - \str_gconcat:NNN 52, 5077
 - \str_gput_left:Nn 52, 5104
 - \str_gput_right:Nn 53, 5104
 - \str_gremove_all:Nn 53, 5174

- `\str_gremove_once:Nn` [53](#), [5168](#)
- `\str_greplace_all:Nnn` [53](#), [5128](#), [5177](#)
- `\str_greplace_once:Nnn` [53](#), [5128](#), [5171](#)
- `\str_gset:Nn`
 . [52](#), [5104](#), [11041](#), [11219](#), [11220](#), [11221](#)
- `\str_gset_eq:NN`
 . [52](#), [5077](#), [11046](#), [11202](#), [11203](#), [11204](#)
- `\str_head:N` [58](#), [417](#), [5616](#)
- `\str_head:n` [58](#), [380](#),
 [396](#), [417](#), [418](#), [4323](#), [4814](#), [4859](#), [5616](#)
- `\str_head_ignore_spaces:n` .. [58](#), [5616](#)
- `\str_if_empty:NTF` [54](#), [5180](#),
 [10436](#), [11133](#), [11137](#), [11160](#), [11173](#),
 [11232](#), [25851](#), [25857](#), [26385](#), [26418](#)
- `\str_if_empty_p:N` [54](#), [5180](#)
- `\str_if_eq:ee` [528](#)
- `\str_if_eq:eeTF` [54](#), [511](#),
 [3002](#), [5210](#), [5301](#), [5717](#), [5718](#), [5719](#),
 [5720](#), [5721](#), [5722](#), [8791](#), [9211](#), [9296](#),
 [11795](#), [23411](#), [23541](#), [25413](#), [25417](#)
- `\str_if_eq:NN` [408](#)
- `\str_if_eq:nn` [132](#), [521](#)
- `\str_if_eq:NNTF` [54](#), [5224](#)
- `\str_if_eq:nnTF`
 .. [54](#), [55](#), [55](#), [134](#), [247](#), [430](#), [4502](#),
 [5210](#), [5273](#), [6011](#), [8735](#), [9134](#), [9824](#),
 [9867](#), [12183](#), [12201](#), [12270](#), [12713](#),
 [14122](#), [14196](#), [20659](#), [20681](#), [20690](#),
 [25394](#), [26781](#), [26800](#), [26818](#), [26828](#),
 [26841](#), [27809](#), [27812](#), [27815](#), [27818](#)
- `\str_if_eq_p:ee` . [54](#), [5210](#), [5715](#), [5716](#)
- `\str_if_eq_p:NN` [54](#), [5224](#)
- `\str_if_eq_p:nn`
 ... [54](#), [5210](#), [7752](#), [7762](#), [7764](#), [26285](#)
- `\str_if_eq_x:nnTF` ... [5707](#), [5718](#), [5720](#)
- `\str_if_eq_x_p:nn` [5707](#)
- `\str_if_exist:NTF` [53](#), [5180](#)
- `\str_if_exist_p:N` [53](#), [5180](#)
- `\str_if_in:NnTF` [54](#), [5232](#)
- `\str_if_in:nnTF` . [54](#), [4033](#), [4047](#), [5232](#)
- `\str_item:Nn` [58](#), [5420](#)
- `\str_item:nn` [58](#), [412](#), [417](#), [5420](#)
 [58](#), [412](#), [5420](#)
- `\str_item_ignore_spaces:nn`
 [58](#), [412](#), [5420](#)
- `\str_lower_case:n` [60](#), [252](#), [5646](#)
- `\str_map_break:` [56](#), [5307](#)
- `\str_map_break:n` ... [56](#), [57](#), [4037](#), [5307](#)
- `\str_map_function:NN`
 [55](#), [55](#), [56](#), [56](#), [5307](#)
- `\str_map_function:nN` [55](#), [55](#), [410](#), [5307](#)
- `\str_map_inline:Nn` .. [56](#), [56](#), [56](#), [5307](#)
- `\str_map_inline:nn`
 [56](#), [4031](#), [5307](#), [22361](#)
- `\str_map_variable:NNn` [56](#), [5307](#)
- `\str_map_variable:nNn` [56](#), [5307](#)
- `\str_new:N` [51](#), [52](#), [5077](#), [5700](#),
 [5701](#), [5702](#), [5703](#), [9375](#), [9376](#), [10432](#),
 [10626](#), [11034](#), [11035](#), [11036](#), [11080](#),
 [11081](#), [11082](#), [11083](#), [11084](#), [26430](#)
- `\str_put_left:Nn` [52](#), [5104](#), [11235](#)
- `\str_put_right:Nn` ... [53](#), [5104](#), [11142](#)
- `\str_range:Nnn` [59](#), [5481](#)
- `\str_range:nnn` .. [59](#), [417](#), [5481](#), [20276](#)
- `\str_range_ignore_spaces:nnn` [59](#), [5481](#)
- `\str_remove_all:Nn` [53](#), [53](#), [5174](#)
- `\str_remove_once:Nn` [53](#), [5168](#)
- `\str_replace_all:Nnn` . [53](#), [5128](#), [5175](#)
- `\str_replace_once:Nnn` [53](#), [5128](#), [5169](#)
- `\str_set:Nn` [52](#), [53](#),
 [5104](#), [5366](#), [9463](#), [9464](#), [9671](#), [9672](#),
 [9693](#), [9694](#), [11101](#), [11105](#), [11114](#),
 [11232](#), [11247](#), [11254](#), [25800](#), [25811](#)
- `\str_set_eq:NN` [52](#), [5077](#), [11145](#), [11237](#)
- `\str_show:N` [61](#), [5704](#)
- `\str_show:n` [61](#), [5704](#)
- `\str_tail:N` [58](#), [5631](#)
- `\str_tail:n` [58](#), [855](#), [5631](#), [11254](#)
- `\str_tail_ignore_spaces:n` .. [58](#), [5631](#)
- `\str_upper_case:n` [60](#), [252](#), [5646](#)
- `\str_use:N` [57](#), [5077](#)
- `\c_tilde_str` [62](#), [5688](#)
- `\g_tmpa_str` [62](#), [5700](#)
- `\l_tmpa_str` [53](#), [62](#), [5700](#)
- `\g_tmpb_str` [62](#), [5700](#)
- `\l_tmpb_str` [62](#), [5700](#)
- `\c_underscore_str` [62](#), [5688](#)
- str internal commands:
 `__str_case:nnTF` [5246](#)
- `__str_case:nw` [5246](#)
- `__str_case_e:nnTF` [5246](#)
- `__str_case_e:nw` [5246](#)
- `__str_case_end:nw` [5246](#)
- `__str_change_case:nn` [5646](#)
- `__str_change_case_aux:nn` [5646](#)
- `__str_change_case_char:nN` ... [5646](#)
- `__str_change_case_end:nw` [5646](#)
- `__str_change_case_end:wn` [5665](#), [5683](#)
- `__str_change_case_loop:nw` ... [5646](#)
- `__str_change_case_output:nw` . [5646](#)
- `__str_change_case_result:n` .. [5646](#)
- `__str_change_case_space:n` ... [5646](#)
- `__str_collect_delimit_by_q-`
 stop:w [5509](#), [5532](#)
- `__str_collect_end:nnnnnnnw` ...
 [415](#), [5532](#)
- `__str_collect_end:wn` [5532](#)
- `__str_collect_loop:wn` [5532](#)
- `__str_collect_loop:wnNNNNNNN` . [5532](#)

- _str_count:n . [417](#), [5436](#), [5496](#), [5578](#)
- _str_count_aux:n [5578](#)
- _str_count_loop:NNNNNNNN [5578](#)
- _str_count_spaces_loop:w [5558](#)
- _str_escape:n [5188](#)
- _str_head:w [418](#), [5616](#)
- _str_if_eq:nn [5188](#), [5213](#), [5221](#), [5227](#)
- _str_item:nn [412](#), [5420](#)
- _str_item:w [412](#), [5420](#)
- _str_map_function:Nn [410](#), [5307](#)
- _str_map_function:w [410](#), [5307](#)
- _str_map_inline:NN [5307](#)
- _str_map_variable:NnN [5307](#)
- _str_range:nnn [5481](#)
- _str_range:nnw [5481](#)
- _str_range:w [5481](#)
- _str_range_normalize:nn
. [5504](#), [5505](#), [5513](#)
- _str_replace:NNNnn [5128](#)
- _str_replace_aux:NNNnnn [5128](#)
- _str_replace_next:w [5128](#)
- _str_skip_end:NNNNNNNN [413](#), [5460](#)
- _str_skip_end:w [5460](#)
- _str_skip_exp_end:w
. [414](#), [415](#), [5447](#), [5456](#), [5460](#), [5511](#)
- _str_skip_loop:wNNNNNNNN [5460](#)
- _str_tail_auxi:w [5631](#)
- _str_tail_auxii:w [418](#), [5631](#)
- _str_tmp:n
. [5078](#), [5084](#), [5087](#), [5105](#), [5115](#), [5118](#)
- _str_to_other_end:w [411](#), [5375](#)
- _str_to_other_fast_end:w [5398](#)
- _str_to_other_fast_loop:w
. [5400](#), [5409](#), [5416](#)
- _str_to_other_loop:w [411](#), [5375](#)
- \strcmp [40](#)
- \string [559](#)
- \suppressfontnotfounderror [819](#), [1653](#)
- \suppressifcsnameerror [1000](#), [1800](#)
- \suppresslongerror [1001](#), [1802](#)
- \suppressmathparerror [1002](#), [1803](#)
- \suppressoutererror [1003](#), [1805](#)
- \suppressprimitiveerror [1004](#), [1806](#)
- \synctex [801](#), [1615](#)
- sys commands:
- \c_sys_day_int [105](#), [7712](#)
- \c_sys_engine_str [105](#), [7735](#), [26181](#)
- \c_sys_engine_version_str [250](#), [26179](#)
- \sys_gset_rand_seed:n [200](#), [250](#), [26241](#)
- \c_sys_hour_int [105](#), [7712](#)
- \sys_if_engine_luatex:TF [105](#), [236](#),
[7735](#), [8524](#), [8526](#), [13534](#), [25124](#),
[25313](#), [25806](#), [26255](#), [26264](#), [26293](#),
[26295](#), [26308](#), [29447](#), [29449](#), [29451](#)
- \sys_if_engine_luatex_p: [105](#),
[7735](#), [10585](#), [25307](#), [26479](#), [26730](#),
[26759](#), [26941](#), [27126](#), [27168](#), [29445](#)
- \sys_if_engine_pdftex:TF
. [105](#), [7735](#), [29455](#), [29457](#), [29459](#)
- \sys_if_engine_pdftex_p:
. [105](#), [7735](#), [27208](#), [29453](#)
- \sys_if_engine_ptex:TF [105](#), [7735](#)
- \sys_if_engine_ptex_p:
. [105](#), [7735](#), [19912](#)
- \sys_if_engine_uptex:TF [105](#), [7735](#)
- \sys_if_engine_uptex_p:
. [105](#), [7735](#), [19913](#), [27209](#)
- \sys_if_engine_xetex:TF [4](#),
[105](#), [7735](#), [8525](#), [29493](#), [29495](#), [29497](#)
- \sys_if_engine_xetex_p:
. [105](#), [7735](#), [25307](#), [26479](#), [26731](#),
[26760](#), [26942](#), [27127](#), [27169](#), [29491](#)
- \sys_if_output_dvi:TF [106](#), [7754](#)
- \sys_if_output_dvi_p: [106](#), [7754](#)
- \sys_if_output_pdf:TF [106](#), [7754](#)
- \sys_if_output_pdf_p: [106](#), [7754](#)
- \sys_if_platform_unix:TF [250](#), [26282](#)
- \sys_if_platform_unix_p: [250](#), [26282](#)
- \sys_if_platform_windows:TF
. [250](#), [26282](#)
- \sys_if_platform_windows_p:
. [250](#), [26282](#)
- \sys_if_rand_exist:TF
. [250](#), [482](#), [7765](#),
[13091](#), [18974](#), [18998](#), [26230](#), [26241](#)
- \sys_if_rand_exist_p: [250](#), [7765](#)
- \sys_if_shell: [251](#)
- \sys_if_shell:TF [251](#), [26287](#), [26439](#)
- \sys_if_shell_p: [251](#), [26287](#)
- \sys_if_shell_restricted:TF
. [251](#), [26287](#)
- \sys_if_shell_restricted_p:
. [251](#), [26287](#)
- \sys_if_shell_unrestricted:TF
. [251](#), [26287](#)
- \sys_if_shell_unrestricted_p:
. [251](#), [26287](#)
- \c_sys_jobname_str
. [105](#), [151](#), [7702](#), [29405](#)
- \c_sys_minute_int [105](#), [7712](#)
- \c_sys_month_int [105](#), [7712](#)
- \c_sys_output_str [106](#), [7754](#)
- \c_sys_platform_str [250](#), [26264](#), [26285](#)
- \sys_rand_seed: [200](#), [249](#), [250](#), [26230](#)
- \c_sys_shell_escape_int
. [251](#), [26253](#), [26288](#), [26290](#), [26292](#)
- \sys_shell_now:n [251](#), [26295](#)
- \sys_shell_shipout:n [251](#), [26308](#)

`\c_sys_year_int` 105, 7712
 sys internal commands:
`_sys_const:nn` . 7719, 7751, 7761,
 7763, 7765, 26284, 26287, 26289, 26291
`\c_sys_shell_stream_int`
 26293, 26305, 26318
 syst commands:
`\c_syst_last_allocated_toks` .. 19506

T

`\t` 27411
`\tabskip` 560
`\tagcode` 802, 1616
`\tan` 197
`\tand` 198
`\tate` 1244, 2026
`\tbaselineshift` 1245, 2027
`\temp` . 170, 176, 181, 184, 185, 192, 197, 200
 T_EX and L^AT_EX 2_ε commands:
`\@` 5689
`\@end` 292, 1264, 1265
`\@hyph` 1268
`\@input` 1269
`\@italiccorr` 1270
`\@shipout` 1272, 1273
`\@tracingfonts` 293
`\@underline` 1271
`\@addtofilelist` 11184
`\@currname` 575, 11045, 11046
`\@currnamestack` 11068, 11069
`\@filelist` 152, 576, 579,
 581, 581, 11183, 11268, 11271, 11285
`\@firstoftwo` 317
`\@ifpackageloaded` 27741, 27799
`\@secondoftwo` 317
`\@tempa` 150, 152, 1280, 1294, 1297
`\@tfor` 292, 1280
`\@unexpandable@protect` 674
`\AtBeginDocument` 292
`\botmark` 513
`\box` 221
`\char` 131
`\chardef` 125, 125, 444, 469
`\conditionally@traceoff` 568
`\copy` 221
`\count` 131, 837
`\cr` 479
`\CROP@shipout` 1281
`\csname` 16
`\csstring` 334
`\current@color`
 260, 1069, 27745, 27750, 27755, 27804
`\currentgrouplevel` 345, 1023
`\currentgrouptype` 345, 1023

`\def` 131
`\detokenize` 42
`\dimen` 511
`\dimendef` 511
`\directlua` 236
`\dp` 222, 675, 676
`\dup@shipout` 1282
`\e@alloc@top` 837, 19492
`\edef` 1, 373
`\endcsname` 16
`\endinput` 141
`\endlinechar` 38, 38, 146, 379, 513
`\endtemplate` 104, 479
`\errhelp` 533, 533
`\errmessage` 533, 533, 534
`\errorcontextlines` 310, 403, 534, 964
`\escapechar` 42, 333, 345, 566
`\everyeof` 378, 380
`\everypar` 240, 364, 1010
`\expandafter` 30, 32
`\expanded` 18, 25, 27, 348, 351, 358, 364
`\fi` 130
`\firstmark` 365, 513
`\font` 130
`\fontdimen`
 ... 182, 218, 627, 628, 629, 629, 630
`\frozen@everydisplay` 1266
`\frozen@everymath` 1267
`\futurelet`
 ... 479, 515, 517, 852, 854, 855, 855
`\global` 273
`\GPTorg@shipout` 1283
`\halign` 104, 479, 505, 1010
`\hskip` 164
`\ht` 222, 675, 676
`\hyphen` 513
`\hyphenchar` 627
`\ifcase` 91
`\ifdim` 167
`\ifeof` 151
`\iffalse` 97
`\ifhbox` 229
`\ifnum` 91
`\ifodd` 92, 1064
`\iftrue` 97
`\ifvbox` 229
`\ifvoid` 230
`\ifx` 21, 269
`\indent` 1010
`\infty` 193
`\input@path` 152, 11125, 11127
`\italiccorr` 513
`\jobname` 105
`\l@expl@check@declarations@bool` 2309

- \l@expl@enable@debug@bool 2181
- \l@expl@log@functions@bool ... 2386
- \lastnamedcs 336
- \lccode 270, 464, 854, 858, 1006
- \leavevmode 240
- \let 273
- \latcharcode 502
- \LL@shipout 1284
- \loctoks 837
- \long 131, 359
- \lower 1010
- \lowercase 941, 942, 943
- \luaescapestring 236
- \makeatletter 6
- \mathchar 131
- \mathchardef 125, 444
- \meaning 14, 122,
130, 131, 511, 511, 512, 517, 853, 1064
- \mem@oldshipout 1285
- \message 25
- \newif 97
- \newlinechar 38,
38, 310, 337, 379, 403, 534, 564, 565
- \newread 557
- \newtoks 205, 849, 867
- \newwrite 562
- \noexpand .. 31, 130, 359, 360, 360, 361
- \nullfont 513
- \number 91, 727
- \numexpr 362
- \opem@shipout 1286
- \or 91
- \outer .. 131, 269, 557, 562, 1064, 1110
- \parindent 240
- \pdfmapfile 294
- \pdfmapline 294
- \pdfstrcmp *xiii*, 266, 267, 269, 284, 1006
- \pdfuniformdeviate 200
- \pgfpages@originalshipout 1287
- \pgfsys@... 260
- \pi 193
- \pr@shipout 1288
- \primitive 292, 359, 360
- \protect 568, 673, 674, 1046
- \protected 131, 359
- \ProvidesClass 6
- \ProvidesFile 6
- \ProvidesPackage 6
- \quitvmode 1010
- \read 146, 560
- \readline 146, 560
- \relax 20, 130, 269, 329,
335, 345, 466, 466, 633, 635, 659, 689
- \RequirePackage 6, 269, 575
- \reserveinserts 269
- \robustify 252
- \romannumeral 33, 633
- \scantokens 378, 379, 380
- \sfcode 270
- \shipout 292
- \show 15, 49, 345
- \showbox 963
- \showthe 345, 463, 592, 597, 600
- \showtokens 49, 403, 540
- \sin 193
- \skip 859, 860
- \space 513
- \special 1067
- \splitbotmark 513
- \splitfirstmark 513
- \strcmp 266, 284
- \string 122, 854, 855, 856
- \tenrm 130
- \tex_lowercase:D 505
- \tex_mdffivesum:D 1019
- \tex_unexpanded:D 357
- \the 82,
130, 159, 163, 166, 349, 359, 360, 362
- \toks ... *xxi*, 91, 205, 249, 362, 363,
364, 836, 837, 837, 837, 838, 839,
839, 840, 841, 842, 843, 844, 844,
849, 853, 855, 857, 858, 860, 862,
867, 868, 868, 868, 869, 870, 874,
912, 914, 919, 920, 924, 924, 925,
925, 926, 929, 932, 934, 942, 959, 1027
- \toks@ 364
- \toksdef 849
- \topmark 131, 513
- \tracingfonts 293
- \tracingonline 964
- \typeout 568
- \uccode 1006
- \Ucharcat 504, 505
- \ucharcats@table 52, 55
- \unexpanded 31, 43, 43, 44,
47, 47, 48, 70, 70, 74, 75, 110, 113,
113, 115, 115, 134, 247, 252, 256,
359, 360, 361, 373, 395, 396, 449, 505
- \unhbox 225
- \unhcopy 225
- \uniformdeviate 200
- \unless 20
- \unvbox 227
- \unvcopy 227
- \uppercase 941
- \usepackage 575
- \valign 479
- \verso@orig@shipout 1290

- `\vskip` 164
- `\vtop` 981
- `\wd` 222, 675, 676
- `\write` 149, 561, 564
- tex commands:
 - `\tex_above:D` 293
 - `\tex_abovedisplayshortskip:D` .. 294
 - `\tex_abovedisplayskip:D` 295
 - `\tex_abovewithdelims:D` 296
 - `\tex_accent:D` 297
 - `\tex_adjdemerits:D` 298
 - `\tex_adjustspacing:D` 753, 1012
 - `\tex_advance:D` .. 299, 6580, 6583, 6586, 6589, 6596, 6599, 6602, 6605, 11394, 11398, 11405, 11409, 11779, 11782, 11787, 11790, 11923, 11926, 11931, 11934, 19609, 19616, 19619, 20021, 20023, 20056, 20058, 21271
 - `\tex_afterassignment:D` 300, 8898, 19962, 20005
 - `\tex_aftergroup:D` 301, 2083
 - `\tex_alignmark:D` 889, 1313
 - `\tex_aligntab:D` 890, 1314
 - `\tex_atop:D` 302
 - `\tex_atopwithdelims:D` 303
 - `\tex_attribute:D` 891, 1315
 - `\tex_attributedef:D` 892, 1316
 - `\tex_automaticdiscretionary:D` .. 894
 - `\tex_automatichyphenmode:D` 895
 - `\tex_automatichyphenpenalty:D` .. 897
 - `\tex_autospacing:D` 1211
 - `\tex_autoxspacing:D` 1212
 - `\tex_badness:D` 304
 - `\tex_baselineskip:D` 305
 - `\tex_batchmode:D` 306
 - `\tex_beginsname:D` 898
 - `\tex_begingroup:D` 307, 1275, 1414, 2078
 - `\tex_beginL:D` 615
 - `\tex_beginR:D` 616
 - `\tex_belowdisplayshortskip:D` .. 308
 - `\tex_belowdisplayskip:D` 309
 - `\tex_binoppenalty:D` 310
 - `\tex_bodydir:D` 899, 1352, 1404
 - `\tex_bodydirection:D` 900
 - `\tex_botmark:D` 311
 - `\tex_botmarks:D` 617
 - `\tex_box:D` ... 312, 23627, 23630, 23652
 - `\tex_boxdir:D` 901, 1353
 - `\tex_boxdirection:D` 902
 - `\tex_boxmaxdepth:D` 313
 - `\tex_breakafterdirmode:D` 903
 - `\tex_brokenpenalty:D` 314
 - `\tex_catcode:D` 315, 3514, 4274, 8361, 8363, 25320, 25327
 - `\tex_catcodetable:D` 904, 1317
 - `\tex_char:D` 316
 - `\tex_chardef:D` 315, 317, 2071, 2100, 2102, 2712, 2713, 6542, 7425, 7431, 8822, 10476, 10647, 25943
 - `\tex_cleaders:D` 318
 - `\tex_clearmarks:D` 905, 1318
 - `\tex_closein:D` 319, 10484
 - `\tex_closeout:D` 320, 10656
 - `\tex_clubpenalties:D` 618
 - `\tex_clubpenalty:D` 321
 - `\tex_copy:D` .. 322, 23619, 23622, 23653
 - `\tex_copyfont:D` 754, 1013
 - `\tex_count:D` 323, 10415, 10417, 10608, 10610, 19475, 19491, 19499, 19500
 - `\tex_countdef:D` 324
 - `\tex_cr:D` 325
 - `\tex_crampeddisplaystyle:D` 906, 1319
 - `\tex_crampedscriptscriptstyle:D` . 908, 1320
 - `\tex_crampedscriptstyle:D` . 909, 1322
 - `\tex_crampedtextstyle:D` ... 910, 1323
 - `\tex_crcr:D` 326
 - `\tex_creationdate:D` 879
 - `\tex_csname:D` 327, 2065
 - `\tex_csstring:D` 911
 - `\tex_currentgrouplevel:D` 619
 - `\tex_currentgroupstyle:D` 620
 - `\tex_currentifbranch:D` 621
 - `\tex_currentiflevel:D` 622
 - `\tex_currentiftypstyle:D` 623
 - `\tex_day:D` 328, 7716
 - `\tex_deadcycles:D` 329
 - `\tex_def:D` 330, 805, 806, 807, 1415, 1416, 1417, 2084, 2086, 2088, 2089, 2106, 2108, 2109, 2110, 2112, 2113, 2114, 2116, 2117, 2118
 - `\tex_defaultthyphenchar:D` 331
 - `\tex_defaultskewchar:D` 332
 - `\tex_delcode:D` 333
 - `\tex_delimiter:D` 334
 - `\tex_delimiterfactor:D` 335
 - `\tex_delimitershortfall:D` 336
 - `\tex_detokenize:D` 624, 2074, 2076
 - `\tex_dimen:D` 337
 - `\tex_dimendef:D` 338
 - `\tex_dimexpr:D` 625, 11334, 23587
 - `\tex_directlua:D` 912, 1306, 1307, 5192, 13538, 25113, 26257
 - `\tex_disablecjktoken:D` 1251, 6537, 6540, 7742
 - `\tex_discretionary:D` 339
 - `\tex_displayindent:D` 340

- `\tex_displaylimits:D` 341
- `\tex_displaystyle:D` 342
- `\tex_displaywidowpenalties:D` .. 626
- `\tex_displaywidowpenalty:D` 343
- `\tex_displaywidth:D` 344
- `\tex_divide:D` 345, 19468, 21272
- `\tex_doublehyphenemerits:D` ... 346
- `\tex_dp:D` 347, 23638
- `\tex_draftmode:D` 755, 1014
- `\tex_dtou:D` 1213
- `\tex_dump:D` 348
- `\tex_dviextension:D` 913
- `\tex_dvifeedback:D` 914
- `\tex_dvivariable:D` 915
- `\tex_eachlinedepth:D` 756
- `\tex_eachlineheight:D` 757
- `\tex_edef:D`
 - 349, 1276, 1277, 1293, 2107,
 - 2111, 2115, 2119, 10868, 10926, 29386
- `\tex_efcode:D` 793
- `\tex_elapsedtime:D` 758, 880
- `\tex_else:D`
 - ... 350, 1279, 1305, 2052, 2103, 2144
- `\tex_emergencystretch:D` 351
- `\tex_enablecjktoken:D` 1252
- `\tex_end:D` . 352, 1265, 1387, 2823, 9639
- `\tex_endcsname:D` 353, 2066
- `\tex_endgroup:D`
 - 354, 1262, 1301, 2045, 2079
- `\tex_endinput:D` 355, 9648, 25861
- `\tex_endL:D` 627
- `\tex_endlinechar:D`
 - 257, 258, 272, 356, 4247,
 - 4248, 4249, 4305, 10527, 10529, 10530
- `\tex_endR:D` 628
- `\tex_epTeXinputencoding:D` 1214
- `\tex_epTeXversion:D` 1215, 26198, 26220
- `\tex_eqno:D` 357
- `\tex_errhelp:D` 358, 9503, 10353
- `\tex_errmessage:D`
 - 359, 2815, 9523, 10384
- `\tex_errorcontextlines:D` ... 360,
 - 5060, 9518, 9538, 9747, 10379, 23718
- `\tex_errorstopmode:D` 361
- `\tex_escapechar:D`
 - 362, 3131, 10730, 10777,
 - 10783, 19927, 19989, 19990, 20314
- `\tex_eTeXrevision:D` 629
- `\tex_eTeXversion:D` 630
- `\tex_etoksapp:D` 916
- `\tex_etokspre:D` 917
- `\tex_euc:D` 1216
- `\tex_everycr:D` 363
- `\tex_everydisplay:D` 364, 1266
- `\tex_everyeof:D` 631, 4245, 26400, 26422
- `\tex_everyhbox:D` 365
- `\tex_everyjob:D` 366, 1388,
 - 7703, 7705, 11038, 11040, 11074, 11076
- `\tex_everymath:D` 367, 1267
- `\tex_everypar:D` 368
- `\tex_everyvbox:D` 369
- `\tex_exceptionpenalty:D` 918
- `\tex_exhyphenpenalty:D` 370
- `\tex_expandafter:D` 371,
 - 810, 1280, 1294, 1296, 1297, 1420, 2067
- `\tex_expanded:D` 920,
 - 1397, 2143, 2144, 3163, 3166, 3233,
 - 3236, 3269, 3275, 3400, 3403, 3424,
 - 3427, 3492, 3495, 3523, 8542, 10230
- `\tex_explicitdiscretionary:D` .. 921
- `\tex_explicitthyphenpenalty:D` .. 919
- `\tex_fam:D` 372
- `\tex_fi:D` 373, 811,
 - 1274, 1298, 1300, 1309, 1310, 1311,
 - 1369, 1371, 1372, 1376, 1383, 1398,
 - 1406, 1411, 1421, 2053, 2105, 2146
- `\tex_filedump:D` 759, 881
- `\tex_filemoddate:D` 760, 882
- `\tex_filesize:D` 761, 883, 25831
- `\tex_finalhyphenemerits:D` 374
- `\tex_firstlineheight:D` 762
- `\tex_firstmark:D` 375
- `\tex_firstmarks:D` 632
- `\tex_firstvalidlanguag:D` 922
- `\tex_floatingpenalty:D` 376
- `\tex_font:D` 377, 12935
- `\tex_fontcharpd:D` 633
- `\tex_fontcharht:D` 634
- `\tex_fontcharic:D` 635
- `\tex_fontcharwd:D` 636
- `\tex_fontdimen:D` 378, 12924
- `\tex_fontexpand:D` 763, 1015
- `\tex_fontid:D` 923, 1324
- `\tex_fontname:D` 379
- `\tex_fontsize:D` 764
- `\tex_forcecjktoken:D` 1253
- `\tex_formatname:D` 924, 1325
- `\tex_futurelet:D`
 - 380, 8893, 8895, 19935, 19993
- `\tex_gdef:D` 381, 2120, 2123, 2127, 2131
- `\tex_gleaders:D` 930, 1326
- `\tex_global:D` 278,
 - 283, 285, 382, 584, 812, 814, 1296,
 - 1422, 2897, 2904, 6519, 6525, 6529,
 - 6551, 6564, 6586, 6589, 6602, 6605,
 - 6615, 7431, 8628, 8630, 8640, 8895,
 - 10476, 10647, 11348, 11355, 11381,
 - 11390, 11398, 11409, 11738, 11744,

- 11770, 11775, 11782, 11790, 11872,
- 11880, 11912, 11919, 11926, 11934,
- 12935, 23622, 23630, 23684, 23739,
- 23753, 23768, 23790, 23837, 23851,
- 23865, 23880, 23903, 23920, 25943
- `\tex_globaldefs:D` 383
- `\tex_glueexpr:D` 637, 11762,
- 11767, 11770, 11779, 11782, 11787,
- 11790, 11805, 11811, 11818, 11820,
- 11828, 11833, 11838, 11843, 18903
- `\tex_glueshrink:D` 638, 26170
- `\tex_glueshrinkorder:D` 639
- `\tex_gluestretch:D`
..... 640, 20147, 20153, 26169
- `\tex_gluestretchorder:D` 641
- `\tex_gluetomu:D` 642
- `\tex_halign:D` 384
- `\tex_hangafter:D` 385
- `\tex_hangindent:D` 386
- `\tex_hbadness:D` 387
- `\tex_hbox:D` 388, 23729, 23733,
- 23739, 23747, 23753, 23761, 23768,
- 23783, 23790, 23798, 23803, 24408
- `\tex_hfil:D` 389
- `\tex_hfill:D` 390
- `\tex_hfilneg:D` 391
- `\tex_hfuzz:D` 392
- `\tex_hjcode:D` 925
- `\tex_hoffset:D` 393, 1400
- `\tex_holdinginserts:D` 394
- `\tex_hpack:D` 926
- `\tex_hrule:D` 395
- `\tex_hsize:D` 396, 24324,
- 24326, 24327, 24370, 24372, 24373
- `\tex_hskip:D` 397, 11824
- `\tex_hss:D`
..... 398, 23807, 23809, 24210, 24219
- `\tex_ht:D` 399, 23637
- `\tex_hyphen:D` 292, 1268
- `\tex_hyphenation:D` 400
- `\tex_hyphenationbounds:D` 927
- `\tex_hyphenationmin:D` 928
- `\tex_hyphenchar:D` 401, 12925
- `\tex_hyphenpenalty:D` 402
- `\tex_hyphenpenaltymode:D` 929
- `\tex_if:D` 117, 403, 2055, 2056
- `\tex_ifabsdim:D` 750, 1016
- `\tex_ifabsnum:D` 751, 1017, 12993, 12997
- `\tex_ifcase:D` 404, 6403
- `\tex_ifcat:D` 405, 2057
- `\tex_ifcondition:D` 931
- `\tex_ifcsname:D` 643, 2064
- `\tex_ifdbbox:D` 1217
- `\tex_ifddir:D` 1218
- `\tex_ifdefined:D`
..... 644, 809, 1264, 1272, 1303,
- 1306, 1312, 1371, 1372, 1379, 1386,
- 1399, 1407, 1419, 2063, 2101, 2144
- `\tex_ifdim:D` 406, 11333
- `\tex_ifeof:D` 407, 10504
- `\tex_iffalse:D` 408, 2050
- `\tex_iffontchar:D` 645
- `\tex_ifhbox:D` 409, 23664
- `\tex_ifhmode:D` 410, 2060
- `\tex_ifincsname:D` 794
- `\tex_ifinner:D` 411, 2062
- `\tex_ifmdir:D` 1219
- `\tex_ifmmode:D` 412, 2059
- `\tex_ifnum:D` 413, 1370, 2081
- `\tex_ifodd:D`
..... 414, 2181, 2309, 2386, 6402, 7396, 7397
- `\tex_ifprimitive:D` 752, 885
- `\tex_iftbox:D` 1220
- `\tex_iftdir:D` 1221
- `\tex_iftrue:D` 415, 2049
- `\tex_ifvbox:D` 416, 23665
- `\tex_ifvmode:D` 417, 2061
- `\tex_ifvoid:D` 418, 23666
- `\tex_ifx:D` 419, 1278, 1295, 2058
- `\tex_ifybox:D` 1222
- `\tex_ifydir:D` 1223
- `\tex_ignoreddimen:D` 765
- `\tex_ignoreligaturesinfont:D` . 1018
- `\tex_ignorespaces:D` 420
- `\tex_immediate:D` . 421, 2832, 2834,
10649, 10656, 10697, 28395, 28456
- `\tex_immediateassigned:D` 932
- `\tex_immediateassignment:D` 933
- `\tex_indent:D` 422, 25449
- `\tex_inhibitglue:D` 1224
- `\tex_inhibitxspcode:D` 1225
- `\tex_initcatcodetable:D` ... 934, 1327
- `\tex_input:D`
..... 423, 1269, 1389, 11188, 26405, 26425
- `\tex_inputlineno:D` ... 424, 2830, 9454
- `\tex_insert:D` 425
- `\tex_inserttht:D` 766, 1019
- `\tex_insertpenalties:D` 426
- `\tex_interactionmode:D`
..... 646, 23702, 23705, 23707
- `\tex_interlinepenalties:D` 647
- `\tex_interlinepenalty:D` 427
- `\tex_italiccorrection:D`
..... 291, 1270, 1401
- `\tex_jcharwidowpenalty:D` 1226
- `\tex_jfam:D` 1227
- `\tex_jfont:D` 1228
- `\tex_jis:D` 1229, 6538, 7743

- `\tex_jobname:D` 428, 7706, 7710, 11041, 11059, 11060
- `\tex_kanjiskip:D` 1230, 7739
- `\tex_kansuji:D` 1231
- `\tex_kansujichar:D` 1232
- `\tex_kcatcode:D` 1233
- `\tex_kchar:D` 1254
- `\tex_kchardef:D` 1255, 6541
- `\tex_kern:D` 429, 23966, 24208, 24217, 24654, 24659, 24732, 24733, 25023, 25024, 25460, 25462, 25506, 25508, 25574
- `\tex_kuten:D` 1234, 1256
- `\tex_language:D` 430, 1390
- `\tex_lastbox:D` 431, 23681, 23684
- `\tex_lastkern:D` 432
- `\tex_lastlinedepth:D` 767
- `\tex_lastlinefit:D` 648
- `\tex_lastnamedcs:D` 935
- `\tex_lastnodetype:D` 649
- `\tex_lastpenalty:D` 433
- `\tex_lastskip:D` 434
- `\tex_lastxpos:D` 768, 1026
- `\tex_lastypos:D` 769, 1027
- `\tex_latelua:D` 936, 1328, 25114
- `\tex_lateluafunction:D` 937
- `\tex_lccode:D` 435, 4130, 4131, 4132, 5381, 5382, 5404, 5405, 8437, 8439, 19908, 19918, 19987, 19989, 19992, 20022, 22875, 22927
- `\tex_leaders:D` 436
- `\tex_left:D` 437, 1408
- `\tex_leftghost:D` 938, 1354
- `\tex_lefthyphenmin:D` 438
- `\tex_leftmarginkern:D` 795
- `\tex_leftskip:D` 439
- `\tex_leqno:D` 440
- `\tex_let:D` 279, 283, 285, 324, 441, 812, 814, 1112, 1265, 1266, 1267, 1268, 1269, 1270, 1271, 1273, 1296, 1302, 1304, 1308, 1313, 1314, 1315, 1316, 1317, 1318, 1319, 1320, 1322, 1323, 1324, 1325, 1326, 1327, 1328, 1329, 1330, 1331, 1332, 1333, 1334, 1335, 1336, 1337, 1338, 1339, 1340, 1341, 1342, 1343, 1345, 1346, 1348, 1349, 1350, 1352, 1353, 1354, 1355, 1356, 1358, 1359, 1360, 1361, 1362, 1363, 1364, 1365, 1366, 1367, 1368, 1374, 1375, 1380, 1381, 1382, 1387, 1388, 1389, 1390, 1391, 1392, 1393, 1394, 1395, 1396, 1397, 1400, 1401, 1402, 1403, 1404, 1405, 1408, 1409, 1410, 1422, 2049, 2050, 2051, 2052, 2053, 2054, 2055, 2056, 2057, 2058, 2059, 2060, 2061, 2062, 2063, 2064, 2065, 2066, 2067, 2068, 2069, 2070, 2072, 2073, 2074, 2075, 2076, 2077, 2078, 2079, 2081, 2082, 2083, 2099, 2106, 2107, 2120, 2121, 2432, 2437, 2453, 2458, 2893, 8628, 8630, 8640, 19909, 19919, 29511, 29536
- `\tex_letcharcode:D` 939
- `\tex_letterspacefont:D` 796
- `\tex_limits:D` 442
- `\tex_linedir:D` 940
- `\tex_linedirection:D` 941
- `\tex_linepenalty:D` 443
- `\tex_lineskip:D` 444
- `\tex_lineskiplimit:D` 445
- `\tex_localbrokenpenalty:D` . 942, 1355
- `\tex_localinterlinepenalty:D` 943, 1356
- `\tex_localleftbox:D` 948, 1358
- `\tex_localrightbox:D` 949, 1359
- `\tex_long:D` 446, 805, 806, 807, 1415, 1416, 1417, 2084, 2086, 2089, 2108, 2109, 2110, 2111, 2112, 2114, 2116, 2117, 2118, 2119, 2123, 2125, 2131, 2133
- `\tex_looseness:D` 447
- `\tex_lower:D` 448, 23663
- `\tex_lowercase:D` 449, 1064, 4133, 4281, 4298, 5383, 5406, 8468, 8593, 9510, 10365, 19909, 19919, 19988, 22876, 22928, 27615, 29485
- `\tex_lpcode:D` 797
- `\tex_luabytecode:D` 944
- `\tex_luabytecodecall:D` 945
- `\tex_luacopyinputnodes:D` 946
- `\tex_luadef:D` 947
- `\tex_luaescapestring:D` 407, 950, 1329, 5191, 13542, 13543, 25112
- `\tex_luafunction:D` 951, 1330
- `\tex_luafunctioncall:D` 952
- `\tex luatexbanner:D` 953
- `\tex luatexrevision:D` . . . 954, 26205
- `\tex luatexversion:D` 955, 1372, 1379, 2101, 5189, 6536, 7263, 7737, 10586, 26203
- `\tex_mag:D` 450
- `\tex_mapfile:D` 770, 1374
- `\tex_mapline:D` 771, 1375
- `\tex_mark:D` 451
- `\tex_marks:D` 650
- `\tex_mathaccent:D` 452
- `\tex_mathbin:D` 453
- `\tex_mathchar:D` 454

<code>\tex_mathchardef:D</code>	481
..... 315, 455, 2104, 6545, 6546	
<code>\tex_mathchoice:D</code>	482, 2068
<code>\tex_mathclose:D</code>	971
<code>\tex_mathcode:D</code>	483
..... 458, 8431, 8433	
<code>\tex_mathdelimitersmode:D</code>	972, 1332
..... 956	
<code>\tex_mathdir:D</code>	773
..... 957, 1360	
<code>\tex_mathdirection:D</code>	973, 1333
..... 958	
<code>\tex_mathdisplayskipmode:D</code>	484
..... 959	
<code>\tex_matheqnogapstep:D</code>	485
..... 960	
<code>\tex_mathinner:D</code>	486
..... 459	
<code>\tex_mathnolimitsmode:D</code>	774, 1028
..... 961	
<code>\tex_mathop:D</code>	974
..... 460, 1391	
<code>\tex_mathopen:D</code>	975
..... 461	
<code>\tex_mathoption:D</code>	487
..... 962	
<code>\tex_mathord:D</code>	488, 8851
..... 462	
<code>\tex_mathpenaltiesmode:D</code>	489, 6399, 24259, 25319
..... 963	
<code>\tex_mathpunct:D</code>	654, 6400, 13157, 20306
..... 463	
<code>\tex_mathrel:D</code>	490
..... 464	
<code>\tex_mathrulesfam:D</code>	491, 10478
..... 964	
<code>\tex_mathscriptboxmode:D</code>	492, 10649
..... 966	
<code>\tex_mathscriptcharmode:D</code>	493, 2051
..... 967	
<code>\tex_mathscriptsmode:D</code>	494, 1393, 29386
..... 965	
<code>\tex_mathstyle:D</code>	495
..... 968, 1331	
<code>\tex_mathsurround:D</code>	496
..... 465	
<code>\tex_mathsurroundmode:D</code>	497, 1394
..... 969	
<code>\tex_mathsurroundskip:D</code>	498
..... 970	
<code>\tex_maxdeadcycles:D</code>	499
..... 466	
<code>\tex_maxdepth:D</code>	500
..... 467	
<code>\tex_mdffivesum:D</code>	977, 1361
..... 772, 884, 25827	
<code>\tex_meaning:D</code>	501
..... 468, 1277, 1294, 2072, 2073	
<code>\tex_medmuskip:D</code>	501
..... 469	
<code>\tex_message:D</code>	978, 1362, 1405
..... 470	
<code>\tex_middle:D</code>	979
..... 651, 1409	
<code>\tex_mkern:D</code>	655
..... 471	
<code>\tex_month:D</code>	502
..... 472, 1392, 7717	
<code>\tex_moveleft:D</code>	503
..... 473, 23657	
<code>\tex_moveright:D</code>	504
..... 474, 23659	
<code>\tex_mskip:D</code>	505
..... 475	
<code>\tex_muexpr:D</code>	505
..... 652, 11902, 11909, 11912, 11923,	
..... 11926, 11931, 11934, 11940, 11945	
<code>\tex_multiply:D</code>	775, 1030, 1363
..... 476	
<code>\tex_muskip:D</code>	980, 1335
..... 477	
<code>\tex_muskipdef:D</code>	981, 1364
..... 478	
<code>\tex_mutogluue:D</code>	506
..... 308, 322, 653, 11902, 11941	
<code>\tex_newlinechar:D</code>	507
..... 479, 2814, 4249, 4277,	
..... 4280, 5058, 9516, 9745, 10377, 10696	
<code>\tex_noalign:D</code>	508
..... 480	
<code>\tex_noautospacing:D</code>	776, 1365
..... 1235	
<code>\tex_noautoxspacing:D</code>	1031
..... 1236	
<code>\tex_noboundary:D</code>	509
<code>\tex_noexpand:D</code>	509
<code>\tex_nohrule:D</code>	983, 1366
<code>\tex_noindent:D</code>	984
<code>\tex_nokerns:D</code>	510
<code>\tex_noligatures:D</code>	511
<code>\tex_noligs:D</code>	512
<code>\tex_nolimits:D</code>	656
<code>\tex_nonscript:D</code>	
<code>\tex_nonstopmode:D</code>	
<code>\tex_normaldeviate:D</code>	
<code>\tex_nospaces:D</code>	
<code>\tex_novrule:D</code>	
<code>\tex_nulldelimiterspace:D</code>	
<code>\tex_nullfont:D</code>	
<code>\tex_number:D</code>	
<code>\tex_numexpr:D</code>	
<code>\tex_omit:D</code>	
<code>\tex_openin:D</code>	
<code>\tex_openout:D</code>	
<code>\tex_or:D</code>	
<code>\tex_outer:D</code>	
<code>\tex_output:D</code>	
<code>\tex_outputbox:D</code>	
<code>\tex_outputpenalty:D</code>	
<code>\tex_over:D</code>	
<code>\tex_overfullrule:D</code>	
<code>\tex_overline:D</code>	
<code>\tex_overwithdelims:D</code>	
<code>\tex_pagebottomoffset:D</code> ...	
<code>\tex_pagedepth:D</code>	
<code>\tex_pagedir:D</code>	
<code>\tex_pagedirection:D</code>	
<code>\tex_pagediscards:D</code>	
<code>\tex_pagefillllstretch:D</code>	
<code>\tex_pagefillstretch:D</code>	
<code>\tex_pagefilstretch:D</code>	
<code>\tex_pagegoal:D</code>	
<code>\tex_pageheight:D</code>	
<code>\tex_pageleftoffset:D</code>	
<code>\tex_pagerightoffset:D</code>	
<code>\tex_pageshrink:D</code>	
<code>\tex_pagestretch:D</code>	
<code>\tex_pagetopoffset:D</code>	
<code>\tex_pagetotal:D</code>	
<code>\tex_pagewidth:D</code>	
<code>\tex_pagewith:D</code>	
<code>\tex_par:D</code>	
<code>\tex_pardir:D</code>	
<code>\tex_pardirection:D</code>	
<code>\tex_parfillskip:D</code>	
<code>\tex_parindent:D</code>	
<code>\tex_parshape:D</code>	
<code>\tex_parshapedimen:D</code>	

<code>\tex_parshapeindent:D</code>	657	<code>\tex_pdfpageattr:D</code>	724
<code>\tex_parshapelength:D</code>	658	<code>\tex_pdfpagebox:D</code>	725
<code>\tex_parskip:D</code>	513	<code>\tex_pdfpageref:D</code>	726
<code>\tex_patterns:D</code>	514	<code>\tex_pdfpageresources:D</code>	727
<code>\tex_pausing:D</code>	515	<code>\tex_pdfpagesattr:D</code>	728
<code>\tex_pdfannot:D</code>	681	<code>\tex_pdfrefobj:D</code>	729
<code>\tex_pdfcatalog:D</code>	682	<code>\tex_pdfrefxform:D</code>	730, 1035
<code>\tex_pdfcolorstack:D</code> 684, 27872, 27881		<code>\tex_pdfrefximage:D</code>	
<code>\tex_pdfcolorstackinit:D</code>	685 731, 1036, 28414, 28423	
<code>\tex_pdfcompresslevel:D</code>		<code>\tex_pdfrestore:D</code>	732, 28289
..... 683, 28485, 28486		<code>\tex_pdfretval:D</code>	733
<code>\tex_pdfcreationdate:D</code>	686	<code>\tex_pdfsave:D</code>	734, 28283
<code>\tex_pdfdecimaldigits:D</code>	687	<code>\tex_pdfsetmatrix:D</code>	735, 28295
<code>\tex_pdfdest:D</code>	688	<code>\tex_pdfstartlink:D</code>	736
<code>\tex_pdfdestmargin:D</code>	689	<code>\tex_pdfstartthread:D</code>	737
<code>\tex_pdfendlink:D</code>	690	<code>\tex_pdfsuppressptexinfo:D</code>	738
<code>\tex_pdfendthread:D</code>	691	<code>\tex_pdftexbanner:D</code>	790, 1380
<code>\tex_pdfextension:D</code> .. 985, 27870,		<code>\tex_pdftexrevision:D</code> 791, 1381, 26187	
27871, 27879, 27880, 28273, 28274,		<code>\tex_pdftexversion:D</code>	
28281, 28282, 28287, 28288, 28293,		... 295, 792, 1371, 1382, 7738, 26185	
28294, 28441, 28444, 28477, 28478		<code>\tex_pdfthread:D</code>	739
<code>\tex_pdffeedback:D</code>	986, 28445	<code>\tex_pdfthreadmargin:D</code>	740
<code>\tex_pdffontattr:D</code>	692	<code>\tex_pdftrailer:D</code>	741
<code>\tex_pdffontname:D</code>	693	<code>\tex_pdfuniqueeresname:D</code>	742
<code>\tex_pdffontobjnum:D</code>	694	<code>\tex_pdfvariable:D</code> .. 987, 28487, 28498	
<code>\tex_pdfgamma:D</code>	695	<code>\tex_pdfvorigin:D</code>	743
<code>\tex_pdfgentounicode:D</code>	698	<code>\tex_pdfxform:D</code>	744, 1038
<code>\tex_pdfglyphptounicode:D</code>	699	<code>\tex_pdfxformattr:D</code>	745
<code>\tex_pdfhorigin:D</code>	700	<code>\tex_pdfxformname:D</code>	746
<code>\tex_pdfimageapplygamma:D</code>	696	<code>\tex_pdfxformresources:D</code>	747
<code>\tex_pdfimagegamma:D</code>	697	<code>\tex_pdfximage:D</code> 748, 1039, 28395	
<code>\tex_pdfimagehicolor:D</code>	701	<code>\tex_pdfximagebbox:D</code> 749, 28389	
<code>\tex_pdfimageresolution:D</code>	702	<code>\tex_penalty:D</code>	516
<code>\tex_pdfincludechars:D</code>	703	<code>\tex_pkmode:D</code>	777
<code>\tex_pdfinclusioncopyfonts:D</code> ..	704	<code>\tex_pkresolution:D</code>	778
<code>\tex_pdfinclusionerrorlevel:D</code> ..	706	<code>\tex_postbreakpenalty:D</code>	1237
<code>\tex_pdfinfo:D</code>	707	<code>\tex_postdisplaypenalty:D</code>	517
<code>\tex_pdflastannot:D</code>	708	<code>\tex_posttexhyphenchar:D</code> ... 988, 1337	
<code>\tex_pdflastlink:D</code>	709	<code>\tex_postthyphenchar:D</code> 989, 1338	
<code>\tex_pdflastobj:D</code>	710, 28447	<code>\tex_prebinoppenalty:D</code>	990
<code>\tex_pdflastxform:D</code>	711, 1021	<code>\tex_prebreakpenalty:D</code>	1238
<code>\tex_pdflastximage:D</code>		<code>\tex_predisplaydirection:D</code>	659
..... 712, 1023, 28414, 28418		<code>\tex_predisplaygapfactor:D</code>	991
<code>\tex_pdflastximagecolordepth:D</code> ..	714	<code>\tex_predisplaypenalty:D</code>	518
<code>\tex_pdflastximagepages:D</code> ..	715, 1025	<code>\tex_predisplaysize:D</code>	519
<code>\tex_pdflinkmargin:D</code>	716	<code>\tex_preexhyphenchar:D</code> 992, 1339	
<code>\tex_pdfliteral:D</code>	717, 28275	<code>\tex_prehyphenchar:D</code> 993, 1340	
<code>\tex_pdfminorversion:D</code>	718	<code>\tex_prerelpenalty:D</code>	994
<code>\tex_pdfnames:D</code>	719	<code>\tex_pretolerance:D</code>	520
<code>\tex_pdfobj:D</code>	720, 28447, 28479	<code>\tex_prevdepth:D</code>	521
<code>\tex_pdfobjcompresslevel:D</code>		<code>\tex_prevgraf:D</code>	522
..... 721, 28496, 28497		<code>\tex_primitive:D</code>	779, 886, 3574
<code>\tex_pdfoutline:D</code>	722	<code>\tex_protected:D</code>	
<code>\tex_pdfoutput:D</code>	723, 1029, 7757 660, 2108, 2110, 2112,	

- 2113, 2114, 2115, 2116, 2117, 2118,
- 2119, 2127, 2129, 2131, 2133, 29386
- \tex_protrudechars:D 780, 1032
- \tex_ptexminorversion:D
..... 1239, 26195, 26213
- \tex_ptexrevision:D 1240, 26196, 26214
- \tex_ptexversion:D
... 1241, 26191, 26194, 26209, 26212
- \tex_pxdimen:D 781, 1033
- \tex_quitvmode:D 798
- \tex_radical:D 523
- \tex_raise:D 524, 23661
- \tex_randomseed:D ... 782, 1034, 26231
- \tex_read:D 525, 10522
- \tex_readline:D 661, 10528
- \tex_relax:D
308, 322, 526, 635, 2077, 6401, 11335
- \tex_relpenalty:D 527
- \tex_resettimer:D 783, 887
- \tex_right:D 528, 1410
- \tex_rightghost:D 995, 1367
- \tex_righthyphenmin:D 529
- \tex_rightmarginkern:D 799
- \tex_rightskip:D 530
- \tex_romannumeral:D
..... 322, 333, 333, 358, 531,
2070, 2082, 2365, 2717, 8480, 13159
- \tex_rrcode:D 800
- \tex_savecatcodetable:D ... 996, 1341
- \tex_savepos:D 784, 1037
- \tex_savinghyphcodes:D 662
- \tex_savingvdiscards:D 663
- \tex_scantextokens:D 997, 1342
- \tex_scantokens:D 664, 4263, 4313, 4328
- \tex_scriptfont:D 532
- \tex_scriptscriptfont:D 533
- \tex_scriptscriptstyle:D 534
- \tex_scriptspace:D 535
- \tex_scriptstyle:D 536
- \tex_scrollmode:D 537
- \tex_setbox:D .. 538, 23619, 23622,
23627, 23630, 23681, 23684, 23733,
23739, 23747, 23753, 23761, 23768,
23783, 23790, 23831, 23837, 23845,
23851, 23859, 23865, 23873, 23880,
23896, 23903, 23915, 23920, 24408
- \tex_setfontid:D 998
- \tex_setlanguage:D 539
- \tex_setrandomseed:D 786, 1040, 26244
- \tex_sfcode:D 540, 8449, 8451
- \tex_shapemode:D 999
- \tex_shellescape:D ... 787, 888, 26261
- \tex_shipout:D 541, 1273, 1297
- \tex_show:D 542
- \tex_showbox:D 543, 23719
- \tex_showboxbreadth:D ... 544, 23715
- \tex_showboxdepth:D 545, 23716
- \tex_showgroups:D 665
- \tex_showifs:D 666
- \tex_showlists:D 546
- \tex_showmode:D 1242
- \tex_showthe:D 547
- \tex_showtokens:D
..... 403, 667, 1403, 5062, 9749
- \tex_sjis:D 1243
- \tex_skewchar:D 548
- \tex_skip:D 549, 20025,
20054, 20073, 20131, 20147, 20153
- \tex_skipdef:D 550
- \tex_space:D 290
- \tex_spacefactor:D 551
- \tex_spaceskip:D 552
- \tex_span:D 553
- \tex_special:D 554, 27732
- \tex_splitbotmark:D 555
- \tex_splitbotmarks:D 668
- \tex_splitdiscards:D 669
- \tex_splitfirstmark:D 556
- \tex_splitfirstmarks:D 670
- \tex_splitmaxdepth:D 557
- \tex_splittopskip:D 558
- \tex_strcmp:D 785, 5188, 13533
- \tex_string:D .. 559, 1276, 1280, 2075
- \tex_suppressfontnotfounderror:D
..... 820, 1350
- \tex_suppressifcsnameerror:D ...
..... 1000, 1343
- \tex_suppresslongerror:D . 1001, 1345
- \tex_suppressmathparerror:D
..... 1002, 1346
- \tex_suppressoutererror:D 1003, 1348
- \tex_suppressprimitiveerror:D . 1005
- \tex_synctex:D 801
- \tex_tabskip:D 560
- \tex_tagcode:D 802
- \tex_tate:D 1244
- \tex_tbaselineshift:D 1245
- \tex_textdir:D 1006, 1368
- \tex_textdirection:D 1007
- \tex_textfont:D 561
- \tex_textstyle:D 562
- \tex_TeXTeXtstate:D 671
- \tex_tfont:D 1246
- \tex_the:D ... 258, 308, 350, 563,
670, 675, 676, 2354, 2830, 3117,
3206, 3210, 3573, 3665, 3684, 3699,
3704, 6618, 6620, 7705, 8363, 8433,
8439, 8445, 8451, 11040, 11076,

11616, 11617, 11618, 11672, 11674, 11821, 11823, 11946, 14158, 14648, 19566, 19598, 19646, 19647, 19678, 19679, 19685, 19686, 20146, 20256, 20315, 20334, 20340, 20343, 20347, 23702, 25320, 26078, 26231, 28418		
\tex_thickmuskip:D	564	
\tex_thinmuskip:D	565	
\tex_time:D	566, 7713, 7715	
\tex_toks:D	567, 3675, 3704, 19539, 19566, 19598, 19635, 19646, 19647, 19678, 19679, 19685, 19686, 19690, 19700, 19710, 19970, 19988, 20146, 20315, 20318, 20325, 20333, 20334, 20339, 20340, 20343, 20347, 26078, 26089, 26090, 26091	
\tex_toksapp:D	1008	
\tex_toksdef:D	568, 19818	
\tex_tokspre:D	1009	
\tex_tolerance:D	569	
\tex_topmark:D	570	
\tex_topmarks:D	672	
\tex_topskip:D	571	
\tex_tpack:D	1010	
\tex_tracingassigns:D	673	
\tex_tracingcommands:D	572	
\tex_tracingfonts:D	788, 1041, 1302, 1304, 1308	
\tex_tracinggroups:D	674	
\tex_tracingifs:D	675	
\tex_tracinglostchars:D	573	
\tex_tracingmacros:D	574	
\tex_tracingnesting:D	676	
\tex_tracingonline:D	575, 23717	
\tex_tracingoutput:D	576	
\tex_tracingpages:D	577	
\tex_tracingparagraphs:D	578	
\tex_tracingrestores:D	579	
\tex_tracingscantokens:D	677	
\tex_tracingstats:D	580	
\tex_uccode:D	581, 8443, 8445	
\tex_Uchar:D	1043, 1349, 25310	
\tex_Ucharcat:D	1044, 8540, 25325	
\tex_uchyph:D	582	
\tex_ucs:D	1257	
\tex_Udelcode:D	1045	
\tex_Udelcodenum:D	1046	
\tex_Udelimiter:D	1047	
\tex_Udelimiterover:D	1048	
\tex_Udelimiterunder:D	1049	
\tex_Uhextensible:D	1050	
\tex_Umathaccent:D	1051	
\tex_Umathaxis:D	1052	
\tex_Umathbinbinspacing:D	1053	
\tex_Umathbinclosespacing:D	1054	
\tex_Umathbininnerspacing:D	1055	
\tex_Umathbinopenspacing:D	1056	
\tex_Umathbinopspacing:D	1057	
\tex_Umathbinordspacing:D	1058	
\tex_Umathbinpunctspacing:D	1059	
\tex_Umathbinrelspacing:D	1060	
\tex_Umathchar:D	1061	
\tex_Umathcharclass:D	1062	
\tex_Umathchardef:D	1063	
\tex_Umathcharfam:D	1064	
\tex_Umathcharnum:D	1065	
\tex_Umathcharnumdef:D	1066	
\tex_Umathcharslot:D	1067	
\tex_Umathclosebinspacing:D	1068	
\tex_Umathcloseclosespacing:D	1070	
\tex_Umathcloseinnerspacing:D	1072	
\tex_Umathcloseopenspacing:D	1073	
\tex_Umathcloseopspacing:D	1074	
\tex_Umathcloseordspacing:D	1075	
\tex_Umathclosepunctspacing:D	1077	
\tex_Umathcloserelspacing:D	1078	
\tex_Umathcode:D	1079	
\tex_Umathcodenum:D	1080	
\tex_Umathconnectoroverlapmin:D	1082	
\tex_Umathfractiondelsize:D	1083	
\tex_Umathfractiondenomdown:D	1085	
\tex_Umathfractiondenomvgap:D	1087	
\tex_Umathfractionnumup:D	1088	
\tex_Umathfractionnumvgap:D	1089	
\tex_Umathfractionrule:D	1090	
\tex_Umathinnerbinspacing:D	1091	
\tex_Umathinnerclosespacing:D	1093	
\tex_Umathinnerinnerspacing:D	1095	
\tex_Umathinneropenspacing:D	1096	
\tex_Umathinneropspacing:D	1097	
\tex_Umathinnerordspacing:D	1098	
\tex_Umathinnerpunctspacing:D	1100	
\tex_Umathinnerrelspacing:D	1101	
\tex_Umathlimitabovebgap:D	1102	
\tex_Umathlimitabovekern:D	1103	
\tex_Umathlimitabovevgap:D	1104	
\tex_Umathlimitbelowbgap:D	1105	
\tex_Umathlimitbelowkern:D	1106	
\tex_Umathlimitbelowvgap:D	1107	
\tex_Umathnolimitsubfactor:D	1108	
\tex_Umathnolimitsupfactor:D	1109	
\tex_Umathopbinspacing:D	1110	
\tex_Umathopclosespacing:D	1111	
\tex_Umathopenbinspacing:D	1112	
\tex_Umathopenclosespacing:D	1113	
\tex_Umathopeninnerspacing:D	1114	
\tex_Umathopenopenspacing:D	1115	
\tex_Umathopenopspacing:D	1116	

<code>\tex_Umathopenordspacing:D</code> . . .	1117	<code>\tex_Umathsubsupshiftup:D</code>	1186
<code>\tex_Umathopenpunctspacing:D</code> .	1118	<code>\tex_Umathsubsupbottommin:D</code>	1184
<code>\tex_Umathopenrelspacing:D</code> . . .	1119	<code>\tex_Umathsubsupshiftup:D</code>	1185
<code>\tex_Umathoperatorsize:D</code>	1120	<code>\tex_Umathsupsubbottommax:D</code> . .	1187
<code>\tex_Umathopinnerspacing:D</code> . . .	1121	<code>\tex_Umathunderbarkern:D</code>	1188
<code>\tex_Umathopopenspacing:D</code>	1122	<code>\tex_Umathunderbarrule:D</code>	1189
<code>\tex_Umathopopspacing:D</code>	1123	<code>\tex_Umathunderbarvgap:D</code>	1190
<code>\tex_Umathopordspacing:D</code>	1124	<code>\tex_Umathunderdelimitervgap:D</code> .	1192
<code>\tex_Umathoppunctspacing:D</code> . . .	1125	<code>\tex_Umathunderdelimitervgap:D</code> .	1194
<code>\tex_Umathoprelspacing:D</code>	1126	<code>\tex_undefined:D</code>	
<code>\tex_Umathordbinspacing:D</code>	1127 285, 513, 814, 1302, 1374,	
<code>\tex_Umathordclosespacing:D</code> . .	1128	1375, 1380, 1381, 1382, 2910, 2918,	
<code>\tex_Umathordinnerspacing:D</code> . .	1129	7329, 12328, 12342, 12375, 12396,	
<code>\tex_Umathordopenspacing:D</code> . . .	1130	19478, 19909, 19919, 19997, 20097	
<code>\tex_Umathordopspacing:D</code>	1131	<code>\tex_underline:D</code>	583, 1271
<code>\tex_Umathordordspacing:D</code>	1132	<code>\tex_unexpanded:D</code>	
<code>\tex_Umathordpunctspacing:D</code> . .	1133 678, 1396, 1426, 2069, 3489	
<code>\tex_Umathordrelspacing:D</code>	1134	<code>\tex_unhbox:D</code>	584, 23811
<code>\tex_Umathoverbarkern:D</code>	1135	<code>\tex_unhcopy:D</code>	585, 23810
<code>\tex_Umathoverbarrule:D</code>	1136	<code>\tex_uniformdeviate:D</code>	789,
<code>\tex_Umathoverbarvgap:D</code>	1137	823, 824, 1027, 1042, 7766, 19003,	
<code>\tex_Umathoverdelimitervgap:D</code> .	1139	19004, 19185, 19188, 26057, 26088	
<code>\tex_Umathoverdelimitervgap:D</code> .	1141	<code>\tex_unkern:D</code>	586
<code>\tex_Umathpunctbinspacing:D</code> . .	1142	<code>\tex_unless:D</code>	679, 2054
<code>\tex_Umathpunctclosespacing:D</code> .	1144	<code>\tex_Unosubscript:D</code>	1195
<code>\tex_Umathpunctinnerspacing:D</code> .	1146	<code>\tex_Unosuperscript:D</code>	1196
<code>\tex_Umathpunctopenspacing:D</code> . .	1147	<code>\tex_unpenalty:D</code>	587
<code>\tex_Umathpunctopspacing:D</code> . . .	1148	<code>\tex_unskip:D</code>	588
<code>\tex_Umathpunctordspacing:D</code> . .	1149	<code>\tex_unvbox:D</code>	589, 23910
<code>\tex_Umathpunctpunctspacing:D</code> .	1151	<code>\tex_unvcopy:D</code>	590, 23909
<code>\tex_Umathpunctrelspacing:D</code> . .	1152	<code>\tex_Uoverdelimiter:D</code>	1197
<code>\tex_Umathquad:D</code>	1153	<code>\tex_uppercase:D</code>	591, 29487
<code>\tex_Umathradicaldegreeafter:D</code> .	1155	<code>\tex_uptexrevision:D</code> . . .	1258, 26218
<code>\tex_Umathradicaldegreebefore:D</code> .	1157	<code>\tex_uptexversion:D</code>	1259, 26217
<code>\tex_Umathradicaldegreeraise:D</code> .	1159	<code>\tex_Uradical:D</code>	1198
<code>\tex_Umathradicalkern:D</code>	1160	<code>\tex_Uroot:D</code>	1199
<code>\tex_Umathradicalrule:D</code>	1161	<code>\tex_Uskewed:D</code>	1200
<code>\tex_Umathradicalvgap:D</code>	1162	<code>\tex_Uskewedwithdelims:D</code>	1201
<code>\tex_Umathrelbinspacing:D</code>	1163	<code>\tex_Ustack:D</code>	1202
<code>\tex_Umathrelclosespacing:D</code> . .	1164	<code>\tex_Ustartdisplaymath:D</code>	1203
<code>\tex_Umathrelinnerspacing:D</code> . .	1165	<code>\tex_Ustartmath:D</code>	1204
<code>\tex_Umathrelopenspacing:D</code> . . .	1166	<code>\tex_Ustopdisplaymath:D</code>	1205
<code>\tex_Umathrelopspacing:D</code>	1167	<code>\tex_Ustopmath:D</code>	1206
<code>\tex_Umathrelordspacing:D</code>	1168	<code>\tex_Usubscript:D</code>	1207
<code>\tex_Umathrelpunctspacing:D</code> . .	1169	<code>\tex_Usuperscript:D</code>	1208
<code>\tex_Umathrelrelspacing:D</code>	1170	<code>\tex_Uunderdelimitervgap:D</code>	1209
<code>\tex_Umathskewedfractionhgap:D</code> .	1172	<code>\tex_Uvextensible:D</code>	1210
<code>\tex_Umathskewedfractionvgap:D</code> .	1174	<code>\tex_vadjust:D</code>	592
<code>\tex_Umathspaceafterscript:D</code> .	1175	<code>\tex_valign:D</code>	593
<code>\tex_Umathstackdenomdown:D</code> . . .	1176	<code>\tex_vbadness:D</code>	594
<code>\tex_Umathstacknumup:D</code>	1177		
<code>\tex_Umathstackvgap:D</code>	1178		
<code>\tex_Umathsubshiftup:D</code>	1179		
<code>\tex_Umathsubshiftup:D</code>	1180		

- `\tex_vbox:D` 595, 23815,
23820, 23825, 23831, 23837, 23859,
23865, 23873, 23880, 23896, 23903
- `\tex_vcenter:D` 596, 1395
- `\tex_vfil:D` 597
- `\tex_vfill:D` 598
- `\tex_vfilneg:D` 599
- `\tex_vfuzz:D` 600
- `\tex_voffset:D` 601, 1402
- `\tex_vpack:D` 1011
- `\tex_vrule:D` 602, 24875, 24930
- `\tex_vsize:D` 603
- `\tex_vskip:D` 604, 11834
- `\tex_vsplit:D` 605, 23915, 23921
- `\tex_vss:D` 606
- `\tex_vtop:D` .. 607, 23817, 23845, 23851
- `\tex_wd:D` 608, 23639
- `\tex_widowpenalties:D` 680
- `\tex_widowpenalty:D` 609
- `\tex_write:D`
610, 2832, 2834, 10677, 10680, 10697
- `\tex_xdef:D`
611, 1424, 2121, 2125, 2129, 2133
- `\tex_XeTeXcharclass:D` 821
- `\tex_XeTeXcharglyph:D` 822
- `\tex_XeTeXcountfeatures:D` 823
- `\tex_XeTeXcountglyphs:D` 824
- `\tex_XeTeXcountselectors:D` 825
- `\tex_XeTeXcountvariations:D` ... 826
- `\tex_XeTeXdashbreakstate:D` 828
- `\tex_XeTeXdefaultencoding:D` ... 827
- `\tex_XeTeXfeaturecode:D` 829
- `\tex_XeTeXfeaturename:D` 830
- `\tex_XeTeXfindfeaturebyname:D` .. 832
- `\tex_XeTeXfindselectorbyname:D` . 834
- `\tex_XeTeXfindvariationbyname:D` 836
- `\tex_XeTeXfirstfontchar:D` 837
- `\tex_XeTeXfonttype:D` 838
- `\tex_XeTeXgenerateactualtext:D` . 840
- `\tex_XeTeXglyph:D` 841
- `\tex_XeTeXglyphbounds:D` 842
- `\tex_XeTeXglyphindex:D` 843
- `\tex_XeTeXglyphname:D` 844
- `\tex_XeTeXinputencoding:D` 845
- `\tex_XeTeXinputnormalization:D` . 847
- `\tex_XeTeXinterchartokenstate:D` 849
- `\tex_XeTeXinterchartoks:D` 850
- `\tex_XeTeXisdefaultselector:D` .. 852
- `\tex_XeTeXisexclusivefeature:D` . 854
- `\tex_XeTeXlastfontchar:D` 855
- `\tex_XeTeXlinebreaklocale:D` ... 857
- `\tex_XeTeXlinebreakpenalty:D` .. 858
- `\tex_XeTeXlinebreakskip:D` 856
- `\tex_XeTeXOTcountfeatures:D` ... 859
- `\tex_XeTeXOTcountlanguages:D` .. 860
- `\tex_XeTeXOTcountscripts:D` 861
- `\tex_XeTeXOTfeaturetag:D` 862
- `\tex_XeTeXOTlanguage-tag:D` 863
- `\tex_XeTeXOTscripttag:D` 864
- `\tex_XeTeXpdffile:D` 865, 28704, 28746
- `\tex_XeTeXpdfpagecount:D` 866
- `\tex_XeTeXpicfile:D` 867, 28697
- `\tex_XeTeXrevision:D` 868, 26226
- `\tex_XeTeXselectorname:D` 869
- `\tex_XeTeXtracingfonts:D` 870
- `\tex_XeTeXupwardsmode:D` 871
- `\tex_XeTeXuseglyphmetrics:D` ... 872
- `\tex_XeTeXvariation:D` 873
- `\tex_XeTeXvariationdefault:D` .. 874
- `\tex_XeTeXvariationmax:D` 875
- `\tex_XeTeXvariationmin:D` 876
- `\tex_XeTeXvariationname:D` 877
- `\tex_XeTeXversion:D`
878, 6539, 7264, 7747, 26225
- `\tex_xkanjiskip:D` 1247
- `\tex_xleaders:D` 612
- `\tex_xspaceskip:D` 613
- `\tex_xspcode:D` 1248
- `\tex_ybaselineshift:D` 1249
- `\tex_year:D` 614, 7718
- `\tex_yoko:D` 1250
- `\texdir` 1006, 1825
- `\texdirection` 1007
- `\textfont` 561
- `\textstyle` 562
- `\texttt` 15618
- `\TeXXeTstate` 671, 1485
- `\tfont` 1246, 2028
- `\TH` 27403
- `\th` 27403
- `\the` 67, 218, 219, 220,
221, 222, 223, 224, 225, 226, 227, 563
- `\thickmuskip` 564
- `\thinmuskip` 565
- thousand commands:
 - `\c_one_thousand` 7274
 - `\c_ten_thousand` 7274
- `\time` 566
- `\tiny` 24868
- tl commands:
 - `\c_empty_tl`
49, 457, 483, 4058, 4076, 4078,
4128, 4425, 6987, 6993, 7770, 7781,
12050, 25338, 27520, 27559, 27578
 - `\l_my_tl` 207, 213
 - `\c_novalue_tl` 39, 49, 4129, 4510
 - `\c_space_tl`
49, 4138, 4736, 5675, 8216, 8225,

- 9458, 11188, 18960, 25349, 25419,
25922, 25924, 26634, 26694, 27750,
28326, 28331, 28334, 28614, 28617,
28619, 28620, 28621, 28622, 29182
- \tl_analysis_map_inline:Nn
 206, 20172, 21740
- \tl_analysis_map_inline:nn
 206, 20172, 22337
- \tl_analysis_show:N
 206, 20199, 20296, 20298
- \tl_analysis_show:n
 206, 20199, 20300, 20302
- \tl_build_begin:N 256, 257,
 257, 257, 908, 1059, 20904, 21403,
 21766, 21859, 22662, 27470, 27487
- \tl_build_clear:N 256, 27487
- \tl_build_end:N 256,
 257, 908, 1059, 1060, 20934, 20942,
 21413, 21821, 21878, 22696, 27566
- \tl_build_gbegin:N
 256, 257, 257, 257, 27470, 27488
- \tl_build_gclear:N 256, 27487
- \tl_build_gend:N 257, 27566
- \tl_build_get:N 257
- \tl_build_get:NN 257, 27552
- \tl_build_gput_left:Nn . . . 257, 27533
- \tl_build_gput_right:Nn . . 257, 27489
- \tl_build_put_left:Nn . . . 257, 27533
- \tl_build_put_right:Nn . . 257, 937,
 1061, 20911, 20929, 20937, 20941,
 20991, 20994, 21027, 21041, 21045,
 21170, 21184, 21225, 21250, 21259,
 21269, 21301, 21314, 21318, 21400,
 21406, 21412, 21416, 21459, 21726,
 21742, 21760, 21829, 21874, 21887,
 22681, 22720, 22752, 22814, 22817,
 22832, 22876, 22892, 22928, 27489
- \tl_case:Nn 40, 4526
- \tl_case:nn 408
- \tl_case:nn(TF) 450
- \tl_case:Nnn 29480, 29482
- \tl_case:NnTF
 40, 4526, 4531, 4536, 29481, 29483
- \l_tl_case_change_accents_tl . . .
 254, 26809, 27409
- \l_tl_case_change_exclude_tl . . .
 253, 254, 26831, 27456
- \l_tl_case_change_math_tl
 253, 26644, 27451
- \tl_clear:N 35, 36, 4075,
 4082, 7822, 7823, 10834, 10835,
 10838, 10847, 10957, 10960, 11020,
 12179, 12670, 12742, 20589, 22664,
 25835, 27569, 27671, 28358, 28366,
 28372, 28557, 28563, 28696, 28702
- \tl_clear_new:N . . . 36, 4081, 7826, 7827
- \tl_concat:NNN 36, 4108, 5100
- \tl_const:Nn
 35, 1023, 4061, 4128, 4136,
 4138, 4227, 5856, 7820, 8595, 8624,
 8646, 9063, 9101, 9377, 9378, 9422,
 9427, 9429, 9431, 9433, 9435, 9440,
 9441, 9448, 10731, 10737, 12114,
 12115, 12116, 12117, 12118, 12119,
 12120, 13182, 13183, 13184, 13185,
 13186, 13194, 13276, 15367, 16662,
 17107, 17108, 17109, 17110, 17111,
 17112, 17113, 17114, 17115, 20286,
 20359, 22961, 25341, 25361, 25373,
 25402, 25432, 25433, 25434, 26053,
 27132, 27133, 27134, 27155, 27156,
 27160, 27161, 27162, 27163, 27164,
 27173, 27187, 27224, 27240, 27363,
 27386, 27388, 27406, 27407, 27615
- \tl_count:N 24, 40, 43, 43, 4619
- \tl_count:n 24, 40, 43, 43, 341, 416,
 417, 443, 639, 2554, 2558, 2959,
 3009, 4619, 4927, 4942, 4954, 21658
- \tl_count_tokens:n 252, 26360
- \tl_gclear:N . . . 35, 839, 4075, 4084,
 7824, 7825, 19560, 27574, 29220, 29256
- \tl_gclear_new:N . . . 36, 4081, 7828, 7829
- \tl_gconcat:NNN 36, 4108, 5101
- \tl_gput_left:Nn 36, 4163
- \tl_gput_right:Nn
 36, 2403, 2404, 2430, 2435,
 2451, 2456, 4195, 5838, 5980, 19272
- \tl_gremove_all:Nn 37, 4407
- \tl_gremove_once:Nn 37, 4401
- \tl_greplace_all:Nnn . . . 37, 4332, 4410
- \tl_greplace_once:Nnn . . . 37, 4332, 4404
- \tl_greverse:N 43, 4766
- .tl_gset:N 172, 12538
- \tl_gset:Nn . . . 36, 69, 381, 1062, 4123,
 4139, 4231, 4335, 4339, 4657, 4769,
 5131, 5135, 5895, 5900, 5912, 5949,
 5966, 6006, 6032, 6110, 6142, 6179,
 6185, 7841, 7868, 7887, 7930, 7966,
 8015, 8054, 9098, 9166, 9195, 9231,
 9239, 9262, 15365, 19556, 20064,
 20594, 21721, 26020, 26030, 26040,
 26379, 26412, 26435, 27573, 29179
- \tl_gset_eq:NN 36, 4078,
 4087, 5097, 5879, 5880, 5881, 5882,
 7418, 7834, 7835, 7836, 7837, 9086,
 9087, 9088, 9089, 15372, 19550, 22956
- \tl_gset_from_file:Nnn . . . 255, 26376

- \tl_gset_from_file_x:Nnn . [255](#), [26409](#)
- \tl_gset_from_shell:Nnn . . [255](#), [26431](#)
- \tl_gset_rescan:Nnn [38](#), [4228](#)
- .tl_gset_x:N [172](#), [12538](#)
- \tl_gsort:Nn [44](#), [4698](#), [19548](#)
- \tl_gtrim_spaces:N [44](#), [4648](#)
- \tl_head:N [45](#), [4772](#)
- \tl_head:n [45](#), [45](#), [359](#), [395](#), [396](#), [400](#),
[401](#), [3555](#), [4772](#), [4951](#), [25358](#), [25366](#)
- \tl_head:w [45](#), [396](#), [397](#),
[4772](#), [4812](#), [4829](#), [4851](#), [25383](#), [25414](#)
- \tl_if_blank:nTF [38](#), [45](#), [45](#),
[45](#), [4413](#), [4799](#), [4941](#), [5080](#), [5107](#),
[8224](#), [8303](#), [9564](#), [11053](#), [12177](#),
[12666](#), [12681](#), [12835](#), [19722](#), [22364](#),
[25377](#), [25406](#), [27020](#), [27040](#), [27090](#)
- \tl_if_blank_p:n [38](#), [4413](#)
- \tl_if_empty:N [5184](#), [5186](#), [8069](#), [8071](#)
- \tl_if_empty:NTF
. . . [39](#), [2248](#), [4423](#), [10851](#), [10941](#),
[10976](#), [12162](#), [12187](#), [12686](#), [12815](#),
[22719](#), [28361](#), [28402](#), [28410](#), [28584](#),
[28588](#), [28615](#), [28630](#), [28717](#), [29182](#)
- \tl_if_empty:nTF
. [39](#), [385](#), [387](#), [387](#), [483](#),
[492](#), [2363](#), [2594](#), [2685](#), [3534](#), [3612](#),
[4236](#), [4346](#), [4433](#), [4444](#), [4491](#), [4890](#),
[4911](#), [5142](#), [5754](#), [5761](#), [5778](#), [5915](#),
[7478](#), [7775](#), [7794](#), [7802](#), [7805](#), [8082](#),
[8115](#), [8839](#), [9132](#), [9465](#), [9742](#), [9834](#),
[9849](#), [9969](#), [9973](#), [10014](#), [10052](#),
[10237](#), [10238](#), [10247](#), [10254](#), [10260](#),
[10267](#), [10336](#), [10845](#), [11245](#), [11248](#),
[11328](#), [12228](#), [12324](#), [12917](#), [13904](#),
[14753](#), [18944](#), [19019](#), [20290](#), [20291](#),
[23536](#), [25400](#), [26327](#), [27648](#), [29276](#)
- \tl_if_empty_p:N [39](#), [4423](#), [28398](#), [28627](#)
- \tl_if_empty_p:n [39](#), [4433](#), [4444](#)
- \tl_if_eq:NN [408](#)
- \tl_if_eq:nn(TF) [110](#), [110](#)
- \tl_if_eq:NNTF
. [39](#), [40](#), [63](#), [430](#), [4457](#), [4550](#),
[6018](#), [9282](#), [9815](#), [9869](#), [24941](#), [24944](#)
- \tl_if_eq:nnTF
. [39](#), [72](#), [72](#), [430](#), [4467](#), [8103](#)
- \tl_if_eq_p:NN [39](#), [4457](#)
- \tl_if_exist:N [5180](#), [5182](#)
- \tl_if_exist:NTF [36](#), [4082](#),
[4084](#), [4126](#), [4612](#), [20201](#), [26461](#), [26469](#)
- \tl_if_exist_p:N [36](#), [4126](#)
- \tl_if_head_eq_catcode:nN [397](#)
- \tl_if_head_eq_catcode:nNTF
. [46](#), [4805](#), [26562](#), [26562](#)
- \tl_if_head_eq_catcode_p:nN [46](#), [4805](#)
- \tl_if_head_eq_charcode:nN [396](#)
- \tl_if_head_eq_charcode:nNTF [46](#), [4805](#)
- \tl_if_head_eq_charcode_p:nN [46](#), [4805](#)
- \tl_if_head_eq_meaning:nN [397](#)
- \tl_if_head_eq_meaning:nNTF [46](#), [4805](#)
- \tl_if_head_eq_meaning_p:nN
. [46](#), [4805](#), [21657](#)
- \tl_if_head_is_group:nTF
. [46](#), [3531](#), [3609](#), [4712](#),
[4832](#), [4867](#), [4893](#), [7800](#), [26589](#), [26671](#)
- \tl_if_head_is_group_p:n [46](#), [4893](#)
- \tl_if_head_is_N_type:n [397](#)
- \tl_if_head_is_N_type:nTF
. [46](#), [3528](#), [3597](#), [3603](#), [3648](#),
[3663](#), [3708](#), [4709](#), [4809](#), [4826](#), [4843](#),
[4876](#), [5012](#), [26324](#), [26586](#), [26668](#),
[26922](#), [26956](#), [27049](#), [27099](#), [27424](#)
- \tl_if_head_is_N_type_p:n [46](#), [4876](#)
- \tl_if_head_is_space:nTF
. [46](#), [4904](#), [4994](#), [5003](#), [5669](#), [27745](#)
- \tl_if_head_is_space_p:n [46](#), [4904](#)
- \tl_if_in:Nn [492](#)
- \tl_if_in:nn [387](#)
- \tl_if_in:NnTF [39](#), [4368](#),
[4482](#), [4482](#), [4483](#), [5832](#), [11113](#), [26442](#)
- \tl_if_in:nnTF
. [39](#), [386](#), [408](#), [4288](#), [4352](#),
[4354](#), [4482](#), [4483](#), [4484](#), [4487](#), [5235](#),
[5243](#), [9728](#), [9730](#), [20476](#), [24747](#), [27646](#)
- \tl_if_novalue:nTF [39](#), [4497](#)
- \tl_if_novalue_p:n [39](#), [4497](#)
- \tl_if_single:n [387](#)
- \tl_if_single:NNTF [40](#), [4511](#), [4512](#), [4513](#)
- \tl_if_single:nTF
. [40](#), [472](#), [4512](#), [4513](#), [4514](#), [4515](#)
- \tl_if_single_p:N [40](#), [4511](#)
- \tl_if_single_p:n [40](#), [4511](#), [4515](#)
- \tl_if_single_token:nTF [251](#), [26322](#)
- \tl_if_single_token_p:n [251](#), [26322](#)
- \tl_item:Nn [47](#), [4916](#)
- \tl_item:nn [47](#), [400](#), [4916](#), [4942](#)
- \tl_log:N [49](#), [5044](#)
- \tl_log:n
. [49](#), [345](#), [345](#), [709](#), [3109](#), [3125](#),
[5046](#), [5068](#), [7340](#), [7452](#), [15397](#), [25919](#)
- \tl_lower_case:n [60](#), [120](#), [252](#), [26563](#)
- \tl_lower_case:nn [252](#), [26563](#)
- \tl_map_break:
. [41](#), [218](#), [863](#), [4563](#), [4569](#),
[4581](#), [4591](#), [4598](#), [4603](#), [20195](#), [20196](#)
- \tl_map_break:n
. [41](#), [42](#), [4603](#), [11128](#), [19555](#)
- \tl_map_function:NN [40](#), [40](#),
[40](#), [248](#), [249](#), [4559](#), [4627](#), [11107](#), [21728](#)

- \tl_map_function:nN [40](#), [40](#),
[41](#), [3003](#), [4048](#), [4559](#), [4622](#), [5918](#), [21011](#)
- \tl_map_inline:Nn
. [40](#), [41](#), [4573](#), [11127](#), [19555](#)
- \tl_map_inline:nn
[41](#), [41](#), [65](#), [4573](#), [7749](#), [8988](#), [8990](#),
[8992](#), [9002](#), [10734](#), [14806](#), [17778](#), [19506](#)
- \tl_map_variable:NNn [41](#), [4587](#)
- \tl_map_variable:nNn [41](#), [390](#), [4587](#)
- \tl_mixed_case:n
. [60](#), [252](#), [254](#), [257](#), [26563](#)
- \tl_mixed_case:nn [252](#), [26563](#)
- \l_tl_mixed_case_ignore_tl
. [254](#), [26883](#), [27461](#)
- \l_tl_mixed_change_ignore_tl [254](#)
- \tl_new:N
[35](#), [36](#), [122](#), [375](#), [4055](#), [4082](#), [4084](#),
[4480](#), [4481](#), [5070](#), [5071](#), [5072](#), [5073](#),
[5828](#), [5853](#), [5854](#), [7771](#), [7817](#), [7818](#),
[8516](#), [8887](#), [9062](#), [9374](#), [9760](#), [9761](#),
[10186](#), [10401](#), [10408](#), [10601](#), [10708](#),
[10710](#), [10723](#), [10725](#), [10726](#), [10728](#),
[11032](#), [11965](#), [11966](#), [11967](#), [12122](#),
[12124](#), [12125](#), [12128](#), [12129](#), [12130](#),
[12134](#), [12135](#), [19268](#), [19434](#), [19872](#),
[20350](#), [20351](#), [20357](#), [20358](#), [20368](#),
[22318](#), [22586](#), [22588](#), [24228](#), [24253](#),
[24254](#), [24863](#), [25106](#), [27409](#), [27451](#),
[27456](#), [27461](#), [27659](#), [28354](#), [29186](#)
- \tl_put_left:Nn [36](#), [4163](#)
- \tl_put_right:Nn
. [36](#), [1060](#), [2241](#), [4195](#),
[5978](#), [8560](#), [8562](#), [8565](#), [8567](#), [8573](#),
[8575](#), [8577](#), [8579](#), [8580](#), [8582](#), [8584](#),
[8586](#), [8588](#), [10982](#), [10985](#), [10990](#),
[12684](#), [20596](#), [22755](#), [27698](#), [27703](#)
- \tl_rand_item:N [47](#), [4939](#)
- \tl_rand_item:n [47](#), [4939](#)
- \tl_range:Nnn [48](#), [4946](#)
- \tl_range:nnn [48](#), [59](#), [256](#), [4946](#)
- \tl_range_braced:Nnn [256](#), [27584](#)
- \tl_range_braced:nnn [48](#), [256](#), [27584](#)
- \tl_range_unbraced:Nnn [256](#), [27584](#)
- \tl_range_unbraced:nnn [48](#), [256](#), [27584](#)
- \tl_remove_all:Nn [37](#), [37](#), [4407](#), [11112](#)
- \tl_remove_once:Nn [37](#), [4401](#)
- \tl_replace_all:Nnn
. [37](#), [427](#), [489](#), [4332](#), [4408](#), [5927](#)
- \tl_replace_once:Nnn
. [37](#), [4332](#), [4402](#), [8603](#)
- \tl_rescan:nn [38](#), [38](#), [4228](#)
- \tl_reverse:N [43](#), [43](#), [4766](#)
- \tl_reverse:n
. [43](#), [43](#), [43](#), [1034](#), [4746](#), [4767](#), [4769](#)
- \tl_reverse_items:n [43](#), [43](#), [43](#), [4632](#)
- \tl_reverse_tokens:n [252](#), [26336](#)
- .tl_set:N [172](#), [12538](#)
- \tl_set:Nn [36](#), [37](#), [38](#), [69](#), [172](#),
[257](#), [257](#), [364](#), [376](#), [381](#), [541](#), [1062](#),
[2246](#), [4115](#), [4139](#), [4229](#), [4259](#), [4318](#),
[4333](#), [4337](#), [4470](#), [4471](#), [4597](#), [4655](#),
[4767](#), [5057](#), [5129](#), [5133](#), [5885](#), [5890](#),
[5910](#), [5917](#), [5921](#), [5932](#), [5947](#), [5958](#),
[6004](#), [6014](#), [6023](#), [6030](#), [6061](#), [6064](#),
[6081](#), [6089](#), [6098](#), [6108](#), [6117](#), [6123](#),
[6140](#), [6154](#), [6176](#), [6182](#), [6277](#), [6884](#),
[7839](#), [7866](#), [7885](#), [7919](#), [7925](#), [7928](#),
[7934](#), [7941](#), [7964](#), [8013](#), [8052](#), [8192](#),
[8558](#), [8563](#), [8921](#), [9095](#), [9160](#), [9176](#),
[9177](#), [9185](#), [9186](#), [9188](#), [9194](#), [9197](#),
[9220](#), [9221](#), [9230](#), [9238](#), [9242](#), [9260](#),
[9265](#), [9315](#), [9500](#), [9744](#), [9772](#), [9855](#),
[10184](#), [10468](#), [10639](#), [10715](#), [10790](#),
[10793](#), [10794](#), [10799](#), [10810](#), [10815](#),
[10836](#), [10973](#), [10993](#), [11012](#), [11014](#),
[11094](#), [11097](#), [11098](#), [11658](#), [11974](#),
[11993](#), [12000](#), [12017](#), [12024](#), [12035](#),
[12101](#), [12141](#), [12143](#), [12171](#), [12185](#),
[12191](#), [12194](#), [12203](#), [12204](#), [12207](#),
[12306](#), [12564](#), [12566](#), [12577](#), [12578](#),
[12602](#), [12603](#), [12643](#), [12664](#), [12676](#),
[12682](#), [12744](#), [12773](#), [15363](#), [15692](#),
[20474](#), [20487](#), [20581](#), [20945](#), [21352](#),
[21357](#), [21622](#), [21682](#), [21712](#), [21824](#),
[21881](#), [22416](#), [22425](#), [22509](#), [22541](#),
[22854](#), [23133](#), [23202](#), [23232](#), [23256](#),
[24426](#), [24748](#), [24749](#), [24865](#), [24868](#),
[25107](#), [25825](#), [26018](#), [26028](#), [26038](#),
[26377](#), [26396](#), [26410](#), [26424](#), [26432](#),
[26441](#), [27195](#), [27214](#), [27372](#), [27410](#),
[27453](#), [27458](#), [27462](#), [27553](#), [27568](#),
[27670](#), [27747](#), [27759](#), [27810](#), [27813](#),
[27816](#), [27820](#), [27823](#), [28359](#), [28374](#)
- \tl_set_eq:NN
. [36](#), [469](#), [4076](#), [4087](#), [5096](#), [5875](#),
[5876](#), [5877](#), [5878](#), [7417](#), [7830](#), [7831](#),
[7832](#), [7833](#), [9082](#), [9083](#), [9084](#), [9085](#),
[9818](#), [9826](#), [12738](#), [15371](#), [19548](#), [22951](#)
- \tl_set_from_file:Nnn [255](#), [26376](#)
- \tl_set_from_file_x:Nnn [255](#), [26409](#)
- \tl_set_from_shell:Nnn [255](#), [26431](#)
- \tl_set_rescan:Nnn [38](#), [38](#), [4228](#)
- .tl_set_x:N [172](#), [12538](#)
- \tl_show:N [49](#), [49](#), [863](#), [5044](#), [5705](#), [20207](#)
- \tl_show:n [49](#), [49](#), [246](#), [345](#), [345](#),
[403](#), [403](#), [709](#), [1023](#), [3105](#), [3122](#),
[5044](#), [5053](#), [5704](#), [7339](#), [7450](#), [8365](#),
[8435](#), [8441](#), [8447](#), [8453](#), [15395](#), [25917](#)

- \tl_show_analysis:N [20295](#)
- \tl_show_analysis:n [20295](#)
- \tl_sort:Nn [44](#), [4698](#), [19548](#)
- \tl_sort:nN . [44](#), [844](#), [846](#), [4698](#), [19718](#)
- \tl_tail:N [45](#), [2247](#), [4772](#), [21633](#)
- \tl_tail:n [45](#), [4772](#)
- \tl_to_lowercase:n [29484](#)
- \tl_to_str:N [42](#), [51](#), [150](#), [405](#),
[568](#), [940](#), [4608](#), [5150](#), [5227](#), [5235](#),
[10794](#), [10805](#), [11099](#), [11271](#), [11285](#)
- \tl_to_str:n [38](#), [38](#), [42](#), [42](#), [51](#), [60](#),
[61](#), [133](#), [133](#), [150](#), [169](#), [176](#), [212](#),
[213](#), [313](#), [328](#), [387](#), [388](#), [405](#), [411](#),
[417](#), [511](#), [512](#), [527](#), [528](#), [940](#), [940](#),
[2074](#), [2097](#), [2189](#), [2197](#), [2228](#), [2233](#),
[2444](#), [2579](#), [2661](#), [3765](#), [3779](#), [3782](#),
[3789](#), [3793](#), [3997](#), [4029](#), [4251](#), [4349](#),
[4436](#), [4607](#), [5054](#), [5069](#), [5112](#), [5151](#),
[5235](#), [5243](#), [5378](#), [5400](#), [5424](#), [5431](#),
[5485](#), [5492](#), [5566](#), [5585](#), [5596](#), [5621](#),
[5629](#), [5637](#), [5643](#), [5655](#), [5666](#), [7159](#),
[7176](#), [7220](#), [7346](#), [8728](#), [8732](#), [8762](#),
[8763](#), [8796](#), [8811](#), [8813](#), [8815](#), [8833](#),
[9027](#), [9136](#), [9147](#), [9205](#), [9206](#), [9244](#),
[9267](#), [9289](#), [9290](#), [9604](#), [9605](#), [9907](#),
[9908](#), [10716](#), [10732](#), [11152](#), [11226](#),
[11483](#), [11685](#), [11816](#), [12061](#), [12842](#),
[13313](#), [13317](#), [13334](#), [13555](#), [13556](#),
[14160](#), [14161](#), [14166](#), [14170](#), [18701](#),
[18755](#), [18829](#), [19339](#), [21011](#), [22818](#),
[22968](#), [24893](#), [24976](#), [25893](#), [25922](#),
[25924](#), [25928](#), [25930](#), [25935](#), [25937](#),
[26300](#), [26313](#), [26770](#), [26773](#), [27641](#),
[27646](#), [28208](#), [28213](#), [28436](#), [28450](#),
[28458](#), [28644](#), [28649](#), [29390](#), [29393](#)
- \tl_to_uppercase:n [29486](#)
- \tl_trim_spaces:N [44](#), [4648](#)
- \tl_trim_spaces:n [44](#), [4648](#), [5939](#), [12842](#)
- \tl_trim_spaces_apply:nN
... [44](#), [4648](#), [7777](#), [8316](#), [9118](#), [12102](#)
- \tl_trim_spacs:n [392](#)
- \tl_upper_case:n
... [60](#), [120](#), [252](#), [257](#), [26563](#)
- \tl_upper_case:nn [252](#), [26563](#)
- \tl_use:N [43](#), [79](#), [159](#),
[163](#), [166](#), [4610](#), [12374](#), [26462](#), [26470](#)
- \g_tmpa_tl [50](#), [5070](#)
- \l_tmpa_tl
... [4](#), [37](#), [50](#), [1276](#), [1278](#), [1295](#), [5072](#)
- \g_tmpb_tl [50](#), [5070](#)
- \l_tmpb_tl
... [50](#), [1277](#), [1278](#), [1293](#), [1295](#), [5072](#)
- tl internal commands:
\c__tl_accents_lt_tl
... [1050](#), [27015](#), [27125](#)
- __tl_act:NNNnn [393](#), [393](#),
[394](#), [1034](#), [4700](#), [4751](#), [26341](#), [26364](#)
- __tl_act_count_group:nn [26360](#)
- __tl_act_count_normal:nN [26360](#)
- __tl_act_count_space:n [26360](#)
- __tl_act_end:w [4700](#)
- __tl_act_end:wn [1034](#), [4721](#), [4727](#)
- __tl_act_group:nwnNNN [4700](#)
- __tl_act_group_recurse:Nnn
... [26351](#), [26355](#)
- __tl_act_loop:w [4700](#)
- __tl_act_normal:NwnNNN [4700](#)
- __tl_act_output:n [394](#), [4700](#)
- __tl_act_result:n
[393](#), [4705](#), [4727](#), [4742](#), [4743](#), [4744](#), [4745](#)
- __tl_act_reverse [394](#)
- __tl_act_reverse_output:n
... [4700](#), [4761](#), [4763](#), [4765](#), [26352](#)
- __tl_act_space:wnnNNN [393](#), [4700](#)
- __tl_analysis:n
[854](#), [863](#), [19895](#), [20174](#), [20203](#), [20211](#)
- __tl_analysis_a:n [19899](#), [19924](#)
- __tl_analysis_a_bgroup:w
... [19955](#), [19977](#)
- __tl_analysis_a_cs:ww [20034](#)
- __tl_analysis_a_egroup:w
... [19957](#), [19977](#)
- __tl_analysis_a_group:nw [19977](#)
- __tl_analysis_a_group_aux:w . [19977](#)
- __tl_analysis_a_group_auxii:w [19977](#)
- __tl_analysis_a_group_test:w . [19977](#)
- __tl_analysis_a_loop:w .. [19931](#),
[19934](#), [19975](#), [20017](#), [20031](#), [20049](#)
- __tl_analysis_a_safe:N
... [19956](#), [19998](#), [20034](#)
- __tl_analysis_a_space:w [19954](#), [19960](#)
- __tl_analysis_a_space_test:w ...
... [856](#), [19960](#)
- __tl_analysis_a_store:
... [857](#), [19971](#), [20013](#), [20019](#)
- __tl_analysis_a_type:w [19935](#), [19936](#)
- __tl_analysis_b:n [19900](#), [20062](#)
- __tl_analysis_b_char:Nww
... [20089](#), [20095](#)
- __tl_analysis_b_cs:Nww [20091](#), [20119](#)
- __tl_analysis_b_cs_test:ww .. [20119](#)
- __tl_analysis_b_loop:w
... [862](#), [20062](#), [20165](#), [20170](#)
- __tl_analysis_b_normal:wwN
... [20075](#), [20140](#)

- __tl_analysis_b_normals:ww
861, 861, 20072, 20075, 20116, 20126
- __tl_analysis_b_special:w
20078, 20137
- __tl_analysis_b_special_char:wN
20137
- __tl_analysis_b_special_space:w
20137
- \l__tl_analysis_char_token
852, 856,
857, 19866, 19964, 19969, 20007, 20012
- __tl_analysis_cs_space_count:NN
19879, 20048, 20122
- __tl_analysis_cs_space_count:w .
19879
- __tl_analysis_cs_space_count_-
end:w 19879
- __tl_analysis_disable:n
19904, 19926, 19992, 20045
- __tl_analysis_extract_charcode:
19873, 19987
- __tl_analysis_extract_charcode_-
aux:w 19873
- \l__tl_analysis_index_int
858, 859,
19869, 19929, 19932, 19970, 19988,
20025, 20028, 20054, 20056, 20143
- __tl_analysis_map_inline_aux:Nn
20172
- __tl_analysis_map_inline_-
aux:nnn 20172
- \l__tl_analysis_nesting_int
855, 19870, 19930, 20021, 20030
- \l__tl_analysis_normal_int
19868, 19928, 19973, 20015,
20026, 20029, 20046, 20055, 20060
- \g__tl_analysis_result_tl
863, 19872, 20064, 20194, 20217
- __tl_analysis_show:
20205, 20213, 20215
- __tl_analysis_show_active:n
20230, 20259
- __tl_analysis_show_cs:n 20226, 20259
- \c__tl_analysis_show_etc_str
865, 20279, 20281, 20286
- __tl_analysis_show_long:nn . . 20259
- __tl_analysis_show_long_-
aux:nnnn 20259, 20265
- __tl_analysis_show_loop:wNw . 20215
- __tl_analysis_show_normal:n
20233, 20239
- __tl_analysis_show_value:N
20244, 20268
- \l__tl_analysis_token
852, 852, 856,
857, 19866, 19876, 19935, 19939,
19942, 19945, 19993, 19997, 20012
- \l__tl_analysis_type_int
856, 858, 859, 19871,
19938, 19953, 20021, 20023, 20027
- __tl_build_begin:NN . . 27470, 27521
- __tl_build_begin:NNN . . 1060, 27470
- __tl_build_end_loop:NN 27566
- __tl_build_get:NNN
27552, 27568, 27573
- __tl_build_get:w 27552
- __tl_build_get_end:w 27552
- __tl_build_last:NNn
1059, 1060, 27484, 27489, 27556
- __tl_build_put:nn 1060, 27489, 27547
- __tl_build_put:nw 1060, 27489
- __tl_build_put_left:NNn 27533
- __tl_case:NnTF
4529, 4534, 4539, 4544, 4546
- __tl_case:nnTF 4526
- __tl_case:Nw 4526
- __tl_case_end:nw 4526
- __tl_change_case:nnn 26563, 26564,
26565, 26566, 26567, 26568, 26569
- __tl_change_case_aux:nnn 26569
- __tl_change_case_char:nN 26569
- __tl_change_case_char_lower:Nnn
26569
- __tl_change_case_char_mixed:Nnn
26569
- __tl_change_case_char_upper:Nnn
26569
- __tl_change_case_char_UTFviii:nn
26569
- __tl_change_case_char_UTFviii:nN
26569
- __tl_change_case_char_UTFviii:nnN
26763, 26765, 26767, 26768
- __tl_change_case_char_UTFviii:nnN
26569
- __tl_change_case_char_UTFviii:nnNN
26569
- __tl_change_case_char_UTFviii:nnNNN
26749, 26766
- __tl_change_case_cs:N 26569
- __tl_change_case_cs:NN 26569
- __tl_change_case_cs:NNn 26569
- __tl_change_case_cs_accents:NN .
26569
- __tl_change_case_cs_expand:NN 26569
- __tl_change_case_cs_expand:Nnw .
26569

_tl_change_case_cs_letterlike:Nn	26569
_tl_change_case_cs_letterlike:NnN	26569
_tl_change_case_end:wn	26569
_tl_change_case_group:nwnn	26569
_tl_change_case_group_lower:nnnn	26569
_tl_change_case_group_mixed:nnnn	26569
_tl_change_case_group_upper:nnnn	26569
_tl_change_case_if_expandable:NTF	26569,
	26928, 26963, 27055, 27105, 27430
_tl_change_case_loop:wn	1048
_tl_change_case_loop:wnn	1040, 1043, 26569
_tl_change_case_lower_az:Nnw	26940
_tl_change_case_lower_lt:nNnw	27012
_tl_change_case_lower_lt:NNw	27012
_tl_change_case_lower_lt:Nnw	27012
_tl_change_case_lower_lt:nnw	27012
_tl_change_case_lower_lt:Nw	27012
_tl_change_case_lower_sigma:Nnw	26910
_tl_change_case_lower_sigma:Nw	26910
_tl_change_case_lower_sigma:w	26910
_tl_change_case_lower_tr:Nnw	26940
_tl_change_case_lower_tr- auxi:Nw	26940
_tl_change_case_lower_tr- auxii:Nw	26940
_tl_change_case_math:NNNnnn	1042, 26569
_tl_change_case_math:NwNNnn	26569
_tl_change_case_math_group:nwNNnn	26569
_tl_change_case_math_loop:wNNnn	26569
_tl_change_case_math_space:wNNnn	26569
_tl_change_case_mixed_nl:NNw	27412
_tl_change_case_mixed_nl:Nnw	27412
_tl_change_case_mixed_nl:Nw	27412
_tl_change_case_mixed_skip:N	26569
_tl_change_case_mixed_skip:NN	26569
_tl_change_case_mixed_skip- tidy:Nwn	26569
_tl_change_case_mixed_switch:w	26569
_tl_change_case_N_type:Nnnn	26569
_tl_change_case_N_type:NNNnnn	26569
_tl_change_case_N_type:Nwnn	26569
_tl_change_case_output:nwn	26569,
	26914, 26950, 26958, 26972, 26974,
	26984, 26995, 27007, 27034, 27043,
	27071, 27093, 27122, 27418, 27444
_tl_change_case_protect:wNN	26569
_tl_change_case_result:n	26582, 26595, 26596, 26598
_tl_change_case_setup:NN	27383, 27390, 27392
_tl_change_case_space:wnn	26569
_tl_change_case_upper_az:Nnw	26940
_tl_change_case_upper_de-alt:Nnw	27119
_tl_change_case_upper_lt:NNw	27012
_tl_change_case_upper_lt:Nnw	27012
_tl_change_case_upper_lt:nnw	27012
_tl_change_case_upper_lt:Nw	27012
_tl_change_case_upper_sigma:Nnw	26910
_tl_change_case_upper_tr:Nnw	26940
_tl_count:n	391, 4619
\c_tl_dot_above_tl	27071, 27125
\c_tl_dotless_i_tl	26958, 26972, 26984, 27166
\c_tl_dotted_I_tl	27007, 27166
\l_tl_file_name_str	26384, 26385,
	26389, 26417, 26418, 26425, 26430
\c_tl_final_sigma_tl	26924, 26936, 27125
_tl_from_file_do:w	26376
_tl_head_auxi:nw	4772
_tl_head_auxii:n	4772
\c_tl_I_ogonek_tl	27083, 27166
\c_tl_i_ogonek_tl	27028, 27166
_tl_if_blank_p:NNw	4413
_tl_if_empty_if:n	384, 385, 423, 4415, 4444, 26325, 26329
_tl_if_head_eq_meaning- normal:nN	4844, 4848
_tl_if_head_eq_meaning- special:nN	4845, 4857
_tl_if_head_is_N_type:w	398, 4876
_tl_if_head_is_space:w	4904
_tl_if_noalue:w	4497
_tl_if_single:nnw	388, 4517, 4525
_tl_if_single:nTF	4515
_tl_if_single_p:n	4515

- \l__tl_internal_a_tl 378, 403, 4254, 4259, 4318, 4467, 5057, 5063, 26396, 26407, 26424, 26427, 26441, 26442, 27195, 27197, 27214, 27219, 27372, 27374
- \l__tl_internal_b_tl 4467
- __tl_item:nn 4916
- __tl_item_aux:nn 4916
- __tl_loop:nn ... 27211, 27220, 27256
- __tl_map_function:Nn 389, 4559, 4578
- __tl_map_variable:Nnn 4587
- __tl_range:Nnnn .. 4946, 27586, 27591
- __tl_range:nnNn 4946
- __tl_range:nnnNn 4946
- __tl_range:w 400, 4946
- __tl_range_braced:w 400, 1063, 27584
- __tl_range_collect:nn ... 1063, 4946
- __tl_range_collect_braced:w ... 400, 1063, 27584
- __tl_range_collect_group:nN . 4946
- __tl_range_collect_group:nn ... 5014, 5023
- __tl_range_collect_N:nN 4946
- __tl_range_collect_space:nw . 4946
- __tl_range_collect_unbraced:w 27584
- __tl_range_items:nnNn 400
- __tl_range_normalize:nn 4961, 4965, 5025
- __tl_range_skip:w 400, 4946
- __tl_range_skip_spaces:n ... 4946
- __tl_range_unbraced:w 27584
- __tl_replace:NnNNnn 381, 382, 4333, 4335, 4337, 4339, 4344
- __tl_replace_auxi:NnnNNnn 382, 4344
- __tl_replace_auxii:NnnNn 381, 382, 383, 4344
- __tl_replace_next:w 381, 383, 4337, 4339, 4344
- __tl_replace_wrap:w 381, 383, 4333, 4335, 4344
- __tl_rescan:w 380, 4228, 4310, 4311, 4326
- \c__tl_rescan_marker_tl 380, 4227, 4246, 4267, 4315, 26395, 26401
- __tl_reverse_group:nn 26336
- __tl_reverse_group_preserve:nn 4746
- __tl_reverse_items:nwNwn 4632
- __tl_reverse_items:wn 4632
- __tl_reverse_normal:nN . 4746, 26342
- __tl_reverse_space:n .. 4746, 26344
- __tl_set_from:nnNn ... 26376, 26447
- __tl_set_from_file:NNnn 26376
- __tl_set_from_file_x:NNnn ... 26409
- __tl_set_from_shell:NNnn 26431
- __tl_set_rescan:n .. 378, 4251, 4273
- __tl_set_rescan:NNnn 4228
- __tl_set_rescan:NnTF 4273
- __tl_set_rescan_multi:n 378, 380, 4228, 4283
- __tl_set_rescan_multiple:n ... 379
- __tl_set_rescan_single:nn 379, 4273
- __tl_set_rescan_single_aux:nn 4273
- __tl_show:n 5053
- __tl_show:NN 5044
- __tl_show:w 5053
- \c__tl_std_sigma_tl ... 26935, 27125
- __tl_tmp:n 27130, 27132, 27133, 27136, 27138, 27139, 27140, 27142, 27144, 27145, 27146, 27148, 27150, 27151, 27152, 27155, 27156
- __tl_tmp:nnnn .. 27222, 27253, 27254
- __tl_tmp:w 387, 392, 4490, 4491, 4497, 4510, 4660, 4697, 27171, 27182, 27185, 27197, 27201, 27202, 27203, 27204, 27219, 27238, 27358, 27361, 27374, 27377, 27378, 27379
- __tl_trim_spaces:nn 4649, 4652, 4660
- __tl_trim_spaces_auxi:w .. 392, 4660
- __tl_trim_spaces_auxii:w . 392, 4660
- __tl_trim_spaces_auxiii:w 392, 4660
- __tl_trim_spaces_auxiv:w . 392, 4660
- \c__tl_upper_Eszett_tl . 27122, 27125
- \tn 20311
- token commands:
 - \c_alignment_token 122, 508, 8626, 8665, 20105
 - \c_parameter_token 122, 508, 934, 8626, 8669, 8672
 - \g_peek_token ... 126, 126, 8884, 8895
 - \l_peek_token 126, 126, 517, 1064, 1065, 8884, 8893, 8910, 8949, 8961, 8981, 27624, 27625, 27626, 27629, 27686, 27687, 27688
 - \c_space_token 31, 46, 49, 122, 258, 258, 397, 508, 3632, 4834, 4869, 8626, 8689, 8910, 10906, 19939, 19969, 20111, 20661, 20696, 26425, 27626, 27688
 - \token_get_arg_spec:N 129, 9025
 - \token_get_prefix_spec:N .. 129, 9025
 - \token_get_replacement_spec:N ... 129, 9025, 12871
 - \token_if_active:NnTF 124, 8702
 - \token_if_active_p:N 124, 8702
 - \token_if_alignment:NnTF 123, 123, 8663
 - \token_if_alignment_p:N ... 123, 8663
 - \token_if_chardef:NnTF 125, 8774, 20248
 - \token_if_chardef_p:N 125, 8774

- \token_if_cs:NTF [124](#), [8739](#), [26701](#)
- \token_if_cs_p:N [124](#), [8739](#), [26970](#), [27062](#), [27112](#), [27437](#)
- \token_if_dim_register:NTF [125](#), [8774](#), [20250](#)
- \token_if_dim_register_p:N [125](#), [8774](#)
- \token_if_eq_catcode:NNTF [124](#), [126](#), [127](#), [127](#), [127](#), [258](#), [3632](#), [8712](#)
- \token_if_eq_catcode_p:NN [124](#), [8712](#)
- \token_if_eq_charcode:NNTF [124](#), [127](#), [127](#), [127](#), [128](#), [258](#), [8717](#), [10150](#), [10906](#), [11117](#), [17370](#), [20696](#), [20701](#), [21324](#), [21524](#), [21537](#), [21539](#), [21577](#), [21698](#), [22722](#), [22801](#)
- \token_if_eq_charcode_p:NN [124](#), [8717](#)
- \token_if_eq_meaning:NNTF [124](#), [128](#), [128](#), [128](#), [128](#), [258](#), [3635](#), [3646](#), [8707](#), [10958](#), [13674](#), [14681](#), [14740](#), [15640](#), [15642](#), [15647](#), [15711](#), [15897](#), [17898](#), [21018](#), [21330](#), [21363](#), [21512](#), [21535](#), [21567](#), [21693](#), [21696](#), [22772](#), [22799](#), [22840](#), [22857](#), [26651](#), [26679](#), [26683](#)
- \token_if_eq_meaning_p:NN [124](#), [8707](#), [26863](#)
- \token_if_expandable:NTF [124](#), [8744](#), [20246](#), [26859](#)
- \token_if_expandable_p:N [124](#), [8744](#)
- \token_if_group_begin:NTF [123](#), [8648](#)
- \token_if_group_begin_p:N [123](#), [8648](#)
- \token_if_group_end:NTF [123](#), [8653](#)
- \token_if_group_end_p:N [123](#), [8653](#)
- \token_if_int_register:NTF [125](#), [8774](#), [20251](#)
- \token_if_int_register_p:N [125](#), [8774](#)
- \token_if_letter:N [510](#)
- \token_if_letter:NTF [124](#), [8692](#), [26934](#)
- \token_if_letter_p:N [124](#), [8692](#)
- \token_if_long_macro:NTF [124](#), [8774](#)
- \token_if_long_macro_p:N [124](#), [8774](#)
- \token_if_macro:NTF [124](#), [8722](#), [8828](#), [9031](#), [9040](#), [9049](#)
- \token_if_macro_p:N [124](#), [8722](#)
- \token_if_math_subscript:NTF [123](#), [8682](#)
- \token_if_math_subscript_p:N [123](#), [8682](#)
- \token_if_math_superscript:NTF [123](#), [8676](#)
- \token_if_math_superscript_p:N [123](#), [8676](#)
- \token_if_math_toggle:NTF [123](#), [8658](#)
- \token_if_math_toggle_p:N [123](#), [8658](#)
- \token_if_mathchardef:NTF [125](#), [8774](#), [20249](#)
- \token_if_mathchardef_p:N [125](#), [8774](#)
- \token_if_muskip_register:NTF [125](#), [8774](#)
- \token_if_muskip_register_p:N [125](#), [8774](#)
- \token_if_other:NTF [124](#), [8697](#)
- \token_if_other_p:N [124](#), [8697](#)
- \token_if_parameter:NTF [123](#), [8668](#)
- \token_if_parameter_p:N [123](#), [8668](#)
- \token_if_primitive:NTF [126](#), [8822](#)
- \token_if_primitive_p:N [126](#), [8822](#)
- \token_if_protected_long_macro:NTF [125](#), [3570](#), [8774](#)
- \token_if_protected_long_macro_p:N [125](#), [8774](#), [26865](#)
- \token_if_protected_macro:NTF [124](#), [3569](#), [8774](#)
- \token_if_protected_macro_p:N [124](#), [8774](#), [26864](#)
- \token_if_skip_register:NTF [125](#), [8774](#), [20252](#)
- \token_if_skip_register_p:N [125](#), [8774](#)
- \token_if_space:NTF [123](#), [8687](#)
- \token_if_space_p:N [123](#), [8687](#)
- \token_if_toks_register:NTF [126](#), [364](#), [3728](#), [8774](#), [20253](#)
- \token_if_toks_register_p:N [126](#), [8774](#)
- \token_new:Nn [29488](#)
- \token_to_meaning:N [14](#), [122](#), [510](#), [513](#), [2072](#), [2088](#), [2845](#), [3734](#), [3779](#), [8626](#), [8728](#), [8795](#), [8832](#), [9034](#), [9043](#), [9052](#), [19876](#), [20242](#), [20267](#), [27629](#)
- \token_to_str:N [5](#), [16](#), [51](#), [122](#), [150](#), [333](#), [399](#), [449](#), [511](#), [512](#), [670](#), [671](#), [672](#), [938](#), [2074](#), [2088](#), [2088](#), [2269](#), [2278](#), [2421](#), [2444](#), [2557](#), [2566](#), [2598](#), [2621](#), [2669](#), [2674](#), [2689](#), [2718](#), [2719](#), [2739](#), [2838](#), [2845](#), [2971](#), [3006](#), [3013](#), [3101](#), [3121](#), [3134](#), [3714](#), [3799](#), [3885](#), [3900](#), [3915](#), [3935](#), [3959](#), [3971](#), [3993](#), [4014](#), [4227](#), [4881](#), [4897](#), [5051](#), [5348](#), [5835](#), [6387](#), [6657](#), [7457](#), [7512](#), [8341](#), [8626](#), [8809](#), [8810](#), [8815](#), [8816](#), [8817](#), [8818](#), [8819](#), [8820](#), [9366](#), [10778](#), [10779](#), [10780](#), [10781](#), [10782](#), [10789](#), [12003](#), [12027](#), [12973](#), [13013](#), [13083](#), [13312](#), [13327](#), [13561](#), [13562](#), [14042](#), [14043](#), [14072](#), [14241](#), [14292](#), [14324](#), [14344](#), [14359](#), [14371](#), [14372](#), [14385](#), [14386](#), [14411](#), [14420](#), [14422](#), [14447](#), [14450](#), [14475](#), [14477](#), [14491](#), [14507](#), [14525](#), [14594](#)

- 14604, 14605, 14620, 14621, 14954,
15161, 15402, 19314, 19816, 19833,
19884, 19965, 20008, 20038, 20087,
20098, 20100, 20102, 20112, 20148,
20159, 20205, 20241, 20266, 20287,
20607, 20614, 20715, 20719, 21442,
22745, 22977, 23558, 23560, 23724,
24278, 24425, 25046, 25843, 25846,
26069, 26461, 26462, 26469, 26470,
26790, 26793, 26801, 27386, 27388,
27406, 27407, 29390, 29393, 29500
- token internal commands:
- \c_token_A_int 8822, 8859
 - __token_delimit_by_char":w .. 8756
 - __token_delimit_by_count:w .. 8756
 - __token_delimit_by_dimen:w .. 8756
 - __token_delimit_by_macro:w .. 8756
 - __token_delimit_by_muskip:w .. 8756
 - __token_delimit_by_skip:w ... 8756
 - __token_delimit_by_toks:w ... 8756
 - __token_if_macro_p:w 8722
 - __token_if_primitive:NNw 8822
 - __token_if_primitive:Nw 8822
 - __token_if_primitive_loop:N . 8822
 - __token_if_primitive_nullfont:N
..... 8822
 - __token_if_primitive_space:w . 8822
 - __token_if_primitive_undefined:N
..... 8822
 - __token_tmp:w 511, 8757,
8766, 8767, 8768, 8769, 8770, 8771,
8772, 8775, 8809, 8810, 8811, 8812,
8814, 8816, 8817, 8818, 8819, 8820
 - \toks 567, 8820
 - \toksapp 1008, 1808
 - \toksdef 568, 19812
 - \tokspre 1009, 1809
 - \tolerance 569
 - \topmark 570
 - \topmarks 672, 1486
 - \topskip 571
 - \tpack 1010, 1810
 - \tracingassigns 673, 1487
 - \tracingcommands 572
 - \tracingfonts 1041, 1651
 - \tracinggroups 674, 1488
 - \tracingifs 675, 1489
 - \tracinglostchars 573
 - \tracingmacros 574
 - \tracingnesting 676, 1490
 - \tracingonline 575
 - \tracingoutput 576
 - \tracingpages 577
 - \tracingparagraphs 578
 - \tracingrestores 579
 - \tracingscantokens 677, 1491
 - \tracingstats 580
 - true 201
 - trunc 197
 - two commands:
 - \c_thirty_two 7274
 - \c_two_hundred_fifty_five 7274
 - \c_two_hundred_fifty_six 7274
- U
- \u *xxi*, 905, 27411
 - \uccode .. 174, 189, 202, 204, 206, 208, 581
 - \Uchar 1043, 1826
 - \Ucharcat 1044, 1827
 - \uchyph 582
 - \ucs 1257, 2039
 - \Udelcode 1045, 1828
 - \Udelcodenum 1046, 1829
 - \Udelimiter 1047, 1830
 - \Udelimiterover 1048, 1831
 - \Udelimiterunder 1049, 1832
 - \Uhexensible 1050, 1833
 - \Umathaccent 1051, 1834
 - \Umathaxis 1052, 1835
 - \Umathbinbinspacing 1053, 1836
 - \Umathbinclosespacing 1054, 1837
 - \Umathbininnerspacing 1055, 1838
 - \Umathbinopenspacing 1056, 1839
 - \Umathbinopspacing 1057, 1840
 - \Umathbinordspacing 1058, 1841
 - \Umathbinpunctspacing 1059, 1842
 - \Umathbinrelspacing 1060, 1843
 - \Umathchar 1061, 1844
 - \Umathcharclass 1062, 1845
 - \Umathchardef 1063, 1846
 - \Umathcharfam 1064, 1847
 - \Umathcharnum 1065, 1848
 - \Umathcharnumdef 1066, 1849
 - \Umathcharslot 1067, 1850
 - \Umathclosebinspacing 1068, 1851
 - \Umathcloseclosespacing 1069, 1852
 - \Umathcloseinnerspacing 1071, 1854
 - \Umathcloseopenspacing 1073, 1856
 - \Umathcloseopspacing 1074, 1857
 - \Umathcloseordspacing 1075, 1858
 - \Umathclosepunctspacing 1076, 1859
 - \Umathcloserelspacing 1078, 1861
 - \Umathcode 165, 1079, 1862
 - \Umathcodenum 1080, 1863
 - \Umathconnectoroverlapmin ... 1081, 1864
 - \Umathfractiondelsize 1083, 1866
 - \Umathfractiondenomdown 1084, 1867
 - \Umathfractiondenomvgap 1086, 1869

<code>\Umathfractionnumup</code>	1088, 1871	<code>\Umathpunctordspacing</code>	1149, 1932
<code>\Umathfractionnumvgap</code>	1089, 1872	<code>\Umathpunctpunctspacing</code>	1150, 1933
<code>\Umathfractionrule</code>	1090, 1873	<code>\Umathpunctrelspacing</code>	1152, 1934
<code>\Umathinnerbinspacing</code>	1091, 1874	<code>\Umathquad</code>	1153, 1935
<code>\Umathinnerclosespacing</code>	1092, 1875	<code>\Umathradicaldegreeafter</code>	1154, 1936
<code>\Umathinnerinnerspacing</code>	1094, 1877	<code>\Umathradicaldegreebefore</code>	1156, 1938
<code>\Umathinneropenspacing</code>	1096, 1879	<code>\Umathradicaldegreeraise</code>	1158, 1940
<code>\Umathinneropspacing</code>	1097, 1880	<code>\Umathradicalkern</code>	1160, 1942
<code>\Umathinnerordspacing</code>	1098, 1881	<code>\Umathradicalrule</code>	1161, 1943
<code>\Umathinnerpunctspacing</code>	1099, 1882	<code>\Umathradicalvgap</code>	1162, 1944
<code>\Umathinnerrelspacing</code>	1101, 1884	<code>\Umathrelbinspacing</code>	1163, 1945
<code>\Umathlimitabovebgap</code>	1102, 1885	<code>\Umathrelclosespacing</code>	1164, 1946
<code>\Umathlimitabovekern</code>	1103, 1886	<code>\Umathrelinnerspacing</code>	1165, 1947
<code>\Umathlimitabovevgap</code>	1104, 1887	<code>\Umathrelopenspacing</code>	1166, 1948
<code>\Umathlimitbelowbgap</code>	1105, 1888	<code>\Umathrelopspacing</code>	1167, 1949
<code>\Umathlimitbelowkern</code>	1106, 1889	<code>\Umathrelordspacing</code>	1168, 1950
<code>\Umathlimitbelowvgap</code>	1107, 1890	<code>\Umathrelpunctspacing</code>	1169, 1951
<code>\Umathnolimitsubfactor</code>	1108, 1891	<code>\Umathrelrelspacing</code>	1170, 1952
<code>\Umathnolimitsupfactor</code>	1109, 1892	<code>\Umathskewedfractionhgap</code>	1171, 1953
<code>\Umathopbinspacing</code>	1110, 1893	<code>\Umathskewedfractionvgap</code>	1173, 1955
<code>\Umathopclosespacing</code>	1111, 1894	<code>\Umathspaceafterscript</code>	1175, 1957
<code>\Umathopenbinspacing</code>	1112, 1895	<code>\Umathstackdenomdown</code>	1176, 1958
<code>\Umathopenclosespacing</code>	1113, 1896	<code>\Umathstacknumup</code>	1177, 1959
<code>\Umathopeninnerspacing</code>	1114, 1897	<code>\Umathstackvgap</code>	1178, 1960
<code>\Umathopenopenspacing</code>	1115, 1898	<code>\Umathsubshiftdown</code>	1179, 1961
<code>\Umathopenopspacing</code>	1116, 1899	<code>\Umathsubshiftdrop</code>	1180, 1962
<code>\Umathopenordspacing</code>	1117, 1900	<code>\Umathsubsupshiftdown</code>	1181, 1963
<code>\Umathopenpunctspacing</code>	1118, 1901	<code>\Umathsubsupvgap</code>	1182, 1964
<code>\Umathopenrelspacing</code>	1119, 1902	<code>\Umathsubtopmax</code>	1183, 1965
<code>\Umathoperatorsiz</code>	1120, 1903	<code>\Umathsupbottommin</code>	1184, 1966
<code>\Umathopinnerspacing</code>	1121, 1904	<code>\Umathsupshiftdrop</code>	1185, 1967
<code>\Umathopopenspacing</code>	1122, 1905	<code>\Umathsupshiftup</code>	1186, 1968
<code>\Umathopopspacing</code>	1123, 1906	<code>\Umathsupsubbottommax</code>	1187, 1969
<code>\Umathopordspacing</code>	1124, 1907	<code>\Umathunderbarkern</code>	1188, 1970
<code>\Umathoppunctspacing</code>	1125, 1908	<code>\Umathunderbarrule</code>	1189, 1971
<code>\Umathoprelspacing</code>	1126, 1909	<code>\Umathunderbarvgap</code>	1190, 1972
<code>\Umathordbinspacing</code>	1127, 1910	<code>\Umathunderdelimiterbgap</code>	1191, 1973
<code>\Umathordclosespacing</code>	1128, 1911	<code>\Umathunderdelimitervgap</code>	1193, 1975
<code>\Umathordinnerspacing</code>	1129, 1912	undefine commands:	
<code>\Umathordopenspacing</code>	1130, 1913	<code>.undefine:</code>	173, 12554
<code>\Umathordopspacing</code>	1131, 1914	<code>\underline</code>	583
<code>\Umathordordspacing</code>	1132, 1915	<code>\unexpanded</code>	678, 1492, 3616, 3640
<code>\Umathordpunctspacing</code>	1133, 1916	<code>\unhbox</code>	584
<code>\Umathordrespacing</code>	1134, 1917	<code>\unhcopy</code>	585
<code>\Umathoverbarkern</code>	1135, 1918	<code>\uniformdeviate</code>	1042, 1652
<code>\Umathoverbarrule</code>	1136, 1919	<code>\unkern</code>	586
<code>\Umathoverbarvgap</code>	1137, 1920	<code>\unless</code>	679, 1493
<code>\Umathoverdelimiterbgap</code>	1138, 1921	<code>\Unosubscript</code>	1195, 1977
<code>\Umathoverdelimitervgap</code>	1140, 1923	<code>\Unosuperscript</code>	1196, 1978
<code>\Umathpunctbinspacing</code>	1142, 1925	<code>\unpenalty</code>	587
<code>\Umathpunctclosespacing</code>	1143, 1926	<code>\unskip</code>	588
<code>\Umathpunctinnerspacing</code>	1145, 1928	<code>\unvbox</code>	589
<code>\Umathpunctopenspacing</code>	1147, 1930	<code>\unvcopy</code>	590
<code>\Umathpunctopspacing</code>	1148, 1931	<code>\Uoverdelimiter</code>	1197, 1979

- `\uppercase` 591
- uptex commands:
 - `\uptex_disablecjktoken:D` 2033
 - `\uptex_enablecjktoken:D` 2034
 - `\uptex_forcecjktoken:D` 2035
 - `\uptex_kchar:D` 2036
 - `\uptex_kchardef:D` 2037
 - `\uptex_kuten:D` 2038
 - `\uptex_ucs:D` 2039
 - `\uptex_uptexrevision:D` 2040
 - `\uptex_uptexversion:D` 2041
- `\uptexrevision` 1258, 2040
- `\uptexversion` 1259, 2041
- `\Uradical` 1198, 1980
- `\Uroot` 1199, 1981
- use commands:
 - `\use:e` 18, 2143, 5207
 - `\use:N` 15, 93, 329, 2136, 2310, 2312, 2360, 2387, 2389, 2593, 2684, 2805, 2807, 2809, 2811, 5685, 6655, 7116, 7126, 7231, 7235, 7237, 7239, 7240, 7244, 7488, 7510, 9637, 9646, 9659, 9666, 9677, 9699, 9716, 9723, 9767, 9777, 9785, 10776, 10863, 11486, 12217, 12224, 12427, 12825, 12826, 20919, 22728, 22867, 25097, 25802, 25894, 26606, 26703, 26712, 26736, 26754, 28230, 28656
 - `\use:n` 17, 18, 35, 129, 253, 316, 380, 495, 552, 649, 671, 836, 846, 926, 964, 2137, 2145, 2148, 2242, 2526, 2543, 2569, 2629, 2638, 2655, 2914, 2991, 3760, 3809, 3983, 4233, 4306, 4308, 4599, 4860, 5147, 5234, 5242, 5332, 5353, 5367, 7723, 7730, 8194, 8582, 8640, 8722, 8759, 8777, 8823, 9601, 9618, 9904, 9921, 10279, 10525, 10592, 10685, 11121, 11682, 13597, 13605, 13614, 13631, 13639, 13667, 14124, 15632, 20256, 20455, 20880, 20883, 21009, 21541, 21774, 21832, 21911, 22321, 22401, 22441, 22527, 23253, 23270, 23719, 25392, 25393, 25395, 25914, 25973, 27750, 27836, 27856, 28102, 28724, 28823, 28931, 28943, 28955, 29261, 29301, 29312, 29323
 - `\use:nn` 17, 2148, 3178, 4266, 8178, 9025, 11482, 14155, 14164, 14168, 17550, 19358, 20224, 25927, 25929, 25934, 25936, 26393
 - `\use:nnn` 17, 2148, 2968, 7309
 - `\use:nnnn` 17, 2148
 - `\use_i:nn` 17, 315, 327, 329, 330, 524, 789, 792, 805, 809, 810, 1024, 1048, 2092, 2152, 2322, 2415, 2513, 2587, 2609, 2755, 2783, 2947, 3627, 3657, 3670, 3715, 3966, 4786, 5947, 5949, 6289, 7725, 9153, 11255, 13293, 14124, 15460, 15796, 16091, 16579, 16862, 17379, 17545, 17788, 17798, 17802, 18310, 18515, 19082, 19107, 19639, 19694, 19704, 19714, 20040, 20840, 20851, 20860, 20863, 20872, 25966, 26130, 26868, 26975
 - `\use_i:nnn` 17, 2154, 4005, 6149, 7333, 9034, 14092, 16048, 17520, 19294, 22776
 - `\use_i:nnnn` 17, 308, 472, 473, 2154, 7483, 7485, 7499, 7504, 7520, 7522, 15630, 16066, 16073, 16266, 19093
 - `\use_i_delimit_by_q_nil:nw` . 19, 2165
 - `\use_i_delimit_by_q_recursion_stop:nw` 19, 2165, 5747, 5763, 7539, 7565, 21670, 26653, 26820, 26843, 26892
 - `\use_i_delimit_by_q_stop:nw` 19, 418, 2165, 2322, 2324, 3994, 5446, 5455, 5574, 5625, 5628, 8287, 10826, 15434, 15796, 25990
 - `\use_i_ii:nnn` 18, 329, 330, 2154, 2578, 3204, 6125, 6230, 9324
 - `\use_ii:nn` 17, 103, 315, 327, 524, 789, 792, 805, 805, 809, 810, 810, 822, 910, 1415, 1420, 2094, 2152, 2418, 2515, 2611, 2630, 2646, 2757, 2785, 2945, 3138, 3629, 3672, 3717, 4278, 4788, 7731, 9154, 11251, 13494, 13517, 15279, 15460, 15461, 16093, 17381, 17794, 17800, 17804, 18312, 18517, 18948, 19084, 20042, 20842, 20848, 20853, 20865, 20874, 21371, 21493, 21663, 21851, 26481, 26709, 26724, 26867, 26870, 26939
 - `\use_ii:nnn` . 17, 330, 2154, 2646, 9043
 - `\use_ii:nnnn` . 17, 472, 473, 2154, 7499
 - `\use_iii:nnn` 17, 2154, 3143, 9052, 13299
 - `\use_iii:nnnn` 17, 472, 473, 2154, 7499, 7521, 7523, 7524
 - `\use_iv:nnnn` 17, 472, 473, 2154, 7499, 7519, 15267
 - `\use_none:n` 18, 309, 384, 392, 392, 487, 491, 534, 569, 667, 668, 672, 672, 806, 812, 863, 1416, 1422, 2169, 2250, 2366, 2385, 2577, 2629, 2630, 2916, 2972, 3558, 3648, 4393, 4415, 4695, 4785, 4801, 4863, 4880,

- 4890, 4891, 4896, 4911, 4914, 5003,
 5012, 5749, 5764, 5851, 6134, 6986,
 6992, 7321, 7724, 7729, 7805, 7849,
 7946, 8041, 8068, 8107, 8872, 9111,
 9113, 9118, 9526, 9743, 9969, 9973,
 10387, 10836, 10891, 10947, 12040,
 12067, 12090, 12102, 12777, 12836,
 13061, 13288, 13437, 13441, 13445,
 13449, 14755, 14981, 14988, 15005,
 15024, 15047, 15113, 15154, 15279,
 15294, 15315, 15316, 15522, 15523,
 16067, 16070, 17050, 18671, 18956,
 20038, 20087, 20185, 20223, 20457,
 20728, 20886, 21538, 26011, 26012,
 26325, 27035, 27820, 29276, 29278
 \use_none:nn 18, 322, 383, 387, 397,
 397, 434, 2169, 2382, 2422, 2559,
 2567, 2638, 4376, 4519, 4647, 4812,
 4829, 6019, 6156, 7478, 7775, 8082,
 10892, 10936, 13353, 13436, 13440,
 13444, 13448, 18666, 22126, 22789
 \use_none:nnn 18,
 397, 2169, 2265, 2274, 2283, 3886,
 3901, 4851, 10893, 13435, 13439,
 13443, 13447, 14092, 20254, 20583
 \use_none:nnnn
 18, 2169, 4037, 10894, 11628
 \use_none:nnnnn 18, 318, 570, 653,
 2169, 2288, 2294, 10895, 10905,
 13592, 13626, 13652, 13660, 15656
 \use_none:nnnnnn
 18, 2169, 2691, 10896, 27579
 \use_none:nnnnnnn
 18, 653, 2169, 2352, 13594,
 13628, 13654, 13662, 13977, 16107
 \use_none:nnnnnnnn 18, 329, 2169, 2600
 \use_none:nnnnnnnnn 18, 2169
 \use_none_delimit_by_q_nil:w 18, 2162
 \use_none_delimit_by_q_recursion_
 stop:w 18, 65, 65, 65, 65,
 2162, 2591, 2670, 2675, 2682, 3800,
 3807, 4007, 5741, 5756, 21648, 21672
 \use_none_delimit_by_q_stop:w ...
 .. 18, 424, 490, 1064, 2162, 3998,
 5162, 5444, 5453, 5612, 6671, 8028,
 8273, 8278, 9796, 11490, 25913, 27631
 \use_none_delimit_by_s_stop:w ...
 66, 67, 5843
 \useboxresource 1035, 1645
 \useimageresource 1036, 1646
 \Uskewed 1200, 1982
 \Uskewedwithdelims 1201, 1983
 \Ustack 1202, 1984
 \Ustartdisplaymath 1203, 1985
 \Ustartmath 1204, 1986
 \Ustopdisplaymath 1205, 1987
 \Ustopmath 1206, 1988
 \Usubscript 1207, 1989
 \Usuperscript 1208, 1990
 utex commands:
 \utex_binbinspacing:D 1836
 \utex_binclosespacing:D 1837
 \utex_bininnerspacing:D 1838
 \utex_binopenspacing:D 1839
 \utex_binopspacing:D 1840
 \utex_binordspacing:D 1841
 \utex_binpunctspacing:D 1842
 \utex_binrelspacing:D 1843
 \utex_char:D 1826
 \utex_charcat:D 1827
 \utex_closebinspacing:D 1851
 \utex_closeclosespacing:D 1853
 \utex_closeinnerspacing:D 1855
 \utex_closeopenspacing:D 1856
 \utex_closeopspacing:D 1857
 \utex_closeordspacing:D 1858
 \utex_closepunctspacing:D 1860
 \utex_closerelspacing:D 1861
 \utex_connectoroverlapmin:D .. 1865
 \utex_delcode:D 1828
 \utex_delcodenum:D 1829
 \utex_delimiter:D 1830
 \utex_delimiterover:D 1831
 \utex_delimiterunder:D 1832
 \utex_fractiondelsize:D 1866
 \utex_fractiondenomdown:D 1868
 \utex_fractiondenomvgap:D 1870
 \utex_fractionnumup:D 1871
 \utex_fractionnumvgap:D 1872
 \utex_fractionrule:D 1873
 \utex_hextensible:D 1833
 \utex_innerbinspacing:D 1874
 \utex_innerclosespacing:D 1876
 \utex_innerinnerspacing:D 1878
 \utex_inneropenspacing:D 1879
 \utex_inneropspacing:D 1880
 \utex_innerordspacing:D 1881
 \utex_innerpunctspacing:D 1883
 \utex_innerrelspacing:D 1884
 \utex_limitabovebgap:D 1885
 \utex_limitabovekern:D 1886
 \utex_limitabovevgap:D 1887
 \utex_limitbelowbgap:D 1888
 \utex_limitbelowkern:D 1889
 \utex_limitbelowvgap:D 1890
 \utex_mathaccent:D 1834
 \utex_mathaxis:D 1835
 \utex_mathchar:D 1844

<code>\utex_mathcharclass:D</code>	1845	<code>\utex_radicaldegreebefore:D</code>	1939
<code>\utex_mathchardef:D</code>	1846	<code>\utex_radicaldegreeraise:D</code>	1941
<code>\utex_mathcharfam:D</code>	1847	<code>\utex_radicalkern:D</code>	1942
<code>\utex_mathcharnum:D</code>	1848	<code>\utex_radicalrule:D</code>	1943
<code>\utex_mathcharnumdef:D</code>	1849	<code>\utex_radicalvgap:D</code>	1944
<code>\utex_mathcharslot:D</code>	1850	<code>\utex_relbinspacing:D</code>	1945
<code>\utex_mathcode:D</code>	1862	<code>\utex_relclosespacing:D</code>	1946
<code>\utex_mathcodenum:D</code>	1863	<code>\utex_relinnerspacing:D</code>	1947
<code>\utex_nolimitsubfactor:D</code>	1891	<code>\utex_relopenspacing:D</code>	1948
<code>\utex_nolimitsupfactor:D</code>	1892	<code>\utex_reloppspacing:D</code>	1949
<code>\utex_nosubscript:D</code>	1977	<code>\utex_relordspacing:D</code>	1950
<code>\utex_nosuperscript:D</code>	1978	<code>\utex_relpunctspacing:D</code>	1951
<code>\utex_opbinspacing:D</code>	1893	<code>\utex_relrelspacing:D</code>	1952
<code>\utex_opclosespacing:D</code>	1894	<code>\utex_root:D</code>	1981
<code>\utex_openbinspacing:D</code>	1895	<code>\utex_skewed:D</code>	1982
<code>\utex_openclosespacing:D</code>	1896	<code>\utex_skewedfractionhgap:D</code>	1954
<code>\utex_openinnerspacing:D</code>	1897	<code>\utex_skewedfractionvgap:D</code>	1956
<code>\utex_openopenspacing:D</code>	1898	<code>\utex_skewedwithdelims:D</code>	1983
<code>\utex_openopspacing:D</code>	1899	<code>\utex_spaceafterscript:D</code>	1957
<code>\utex_openordspacing:D</code>	1900	<code>\utex_stack:D</code>	1984
<code>\utex_openpunctspacing:D</code>	1901	<code>\utex_stackdenomdown:D</code>	1958
<code>\utex_openrelspacing:D</code>	1902	<code>\utex_stacknumup:D</code>	1959
<code>\utex_operatorsize:D</code>	1903	<code>\utex_stackvgap:D</code>	1960
<code>\utex_opinnerspacing:D</code>	1904	<code>\utex_startdisplaymath:D</code>	1985
<code>\utex_opopenspacing:D</code>	1905	<code>\utex_startmath:D</code>	1986
<code>\utex_opopspacing:D</code>	1906	<code>\utex_stopdisplaymath:D</code>	1987
<code>\utex_opordspacing:D</code>	1907	<code>\utex_stopmath:D</code>	1988
<code>\utex_oppunctspacing:D</code>	1908	<code>\utex_subscript:D</code>	1989
<code>\utex_oprelspacing:D</code>	1909	<code>\utex_subshiftdown:D</code>	1961
<code>\utex_ordbinspacing:D</code>	1910	<code>\utex_subshiftdrop:D</code>	1962
<code>\utex_ordclosespacing:D</code>	1911	<code>\utex_subsupshiftdown:D</code>	1963
<code>\utex_ordinnerspacing:D</code>	1912	<code>\utex_subsupvgap:D</code>	1964
<code>\utex_ordopenspacing:D</code>	1913	<code>\utex_subtopmax:D</code>	1965
<code>\utex_ordopspacing:D</code>	1914	<code>\utex_supbottommin:D</code>	1966
<code>\utex_ordordspacing:D</code>	1915	<code>\utex_superscript:D</code>	1990
<code>\utex_ordpunctspacing:D</code>	1916	<code>\utex_supshiftdrop:D</code>	1967
<code>\utex_ordrelspacing:D</code>	1917	<code>\utex_supshiftdown:D</code>	1968
<code>\utex_overbarkern:D</code>	1918	<code>\utex_supsubbottommax:D</code>	1969
<code>\utex_overbarrule:D</code>	1919	<code>\utex_underbarkern:D</code>	1970
<code>\utex_overbarvgap:D</code>	1920	<code>\utex_underbarrule:D</code>	1971
<code>\utex_overdelimiter:D</code>	1979	<code>\utex_underbarvgap:D</code>	1972
<code>\utex_overdelimiterbgap:D</code>	1922	<code>\utex_underdelimitervgap:D</code>	1974
<code>\utex_overdelimitervgap:D</code>	1924	<code>\utex_underdelimitervgap:D</code>	1976
<code>\utex_punctbinspacing:D</code>	1925	<code>\utex_vextensible:D</code>	1992
<code>\utex_punctclosespacing:D</code>	1927	<code>\Uunderdelimitervgap:D</code>	1976
<code>\utex_punctinnerspacing:D</code>	1929	<code>\Uvextensible</code>	1210, 1992
<code>\utex_punctopenspacing:D</code>	1930		
<code>\utex_punctopspacing:D</code>	1931		
<code>\utex_punctordspacing:D</code>	1932		
<code>\utex_punctpunctspacing:D</code>	1933		
<code>\utex_punctrelspacing:D</code>	1934		
<code>\utex_quad:D</code>	1935		
<code>\utex_radical:D</code>	1980		
<code>\utex_radicaldegreeafter:D</code>	1937		

- .value_required:n 173, 12556
- \vbadness 594
- \vbox 595
- vbox commands:
 - \vbox:n 221, 221, 225, 23814
 - \vbox_gset:Nn 226, 23828
 - \vbox_gset:Nw 226, 23870
 - \vbox_gset_end: 226, 23870
 - \vbox_gset_split_to_ht:NNn 226, 23913
 - \vbox_gset_to_ht:Nnn 226, 23856
 - \vbox_gset_to_ht:Nnw 226, 23893
 - \vbox_gset_top:Nn 226, 23842
 - \vbox_set:Nn .. 226, 226, 23828, 24322
 - \vbox_set:Nw 226, 23870, 24369
 - \vbox_set_end: 226, 226, 23870, 24377
 - \vbox_set_split_to_ht:NNn 226, 23913
 - \vbox_set_to_ht:Nnn . 226, 226, 23856
 - \vbox_set_to_ht:Nnw 226, 23893
 - \vbox_set_top:Nn
 - 226, 23842, 24334, 24381
 - \vbox_to_ht:nn 226, 23818
 - \vbox_to_zero:n 226, 23818
 - \vbox_top:n 225, 23814
 - \vbox_unpack:N
 - 227, 227, 23909, 24334, 24381
 - \vbox_unpack_clear:N 227, 23909
- \vcenter 596
- vcoffin commands:
 - \vcoffin_set:Nnn 232, 24318
 - \vcoffin_set:Nnw 232, 24365
 - \vcoffin_set_end: 232, 24365
- \vfil 597
- \vfill 598
- \vfildneg 599
- \vfuzz 600
- \voffset 601
- \vpack 1011, 1811
- \vrule 602
- \vsize 603
- \vskip 604
- \vsplit 605
- \vss 606
- \vtop 607

- W**
- \wd 608
- \widowpenalties 680, 1494
- \widowpenalty 609
- \write 610

- X**
- \xdef 611
- xetex commands:
 - \xetex_charclass:D 1655
 - \xetex_charglyph:D 1656
 - \xetex_countfeatures:D 1657
 - \xetex_countglyphs:D 1658
 - \xetex_countselectors:D 1659
 - \xetex_countvariations:D 1660
 - \xetex_dashbreakstate:D 1662
 - \xetex_defaultencoding:D 1661
 - \xetex_featurecode:D 1663
 - \xetex_featurename:D 1664
 - \xetex_findfeaturebyname:D ... 1666
 - \xetex_findselectorbyname:D .. 1668
 - \xetex_findvariationbyname:D . 1670
 - \xetex_firstfontchar:D 1671
 - \xetex_fonttype:D 1672
 - \xetex_generateactualtext:D .. 1674
 - \xetex_glyph:D 1675
 - \xetex_glyphbounds:D 1676
 - \xetex_glyphindex:D 1677
 - \xetex_glyphname:D 1678
 - \xetex_if_engine:TF
 - 29492, 29494, 29496
 - \xetex_if_engine_p: 29490
 - \xetex_inputencoding:D 1679
 - \xetex_inputnormalization:D .. 1681
 - \xetex_interchartokenstate:D . 1683
 - \xetex_interchartoks:D 1684
 - \xetex_isdefaultselector:D ... 1686
 - \xetex_isexclusivefeature:D .. 1688
 - \xetex_lastfontchar:D 1689
 - \xetex_linebreaklocale:D 1691
 - \xetex_linebreakpenalty:D 1692
 - \xetex_linebreakskip:D 1690
 - \xetex_OTcountfeatures:D 1693
 - \xetex_OTcountlanguages:D 1694
 - \xetex_OTcountscripts:D 1695
 - \xetex_OTfeaturetag:D 1696
 - \xetex_OTlanguagetag:D 1697
 - \xetex_OTscripttag:D 1698
 - \xetex_pdffile:D 1699
 - \xetex_pdfpagecount:D 1700
 - \xetex_picfile:D 1701
 - \xetex_selectorname:D 1702
 - \xetex_suppressfontnotfounderror:D
 - 1654
 - \xetex_tracingfonts:D 1703
 - \xetex_upwardsmode:D 1704
 - \xetex_useglyphmetrics:D 1705
 - \xetex_variation:D 1706
 - \xetex_variationdefault:D 1707
 - \xetex_variationmax:D 1708
 - \xetex_variationmin:D 1709
 - \xetex_variationname:D 1710
 - \xetex_XeTeXrevision:D 1711
 - \xetex_XeTeXversion:D 1712

<code>\XeTeXcharclass</code>	821, 1655	<code>\XeTeXlinebreakskip</code>	856, 1690
<code>\XeTeXcharglyph</code>	822, 1656	<code>\XeTeXOTcountfeatures</code>	859, 1693
<code>\XeTeXcountfeatures</code>	823, 1657	<code>\XeTeXOTcountlanguages</code>	860, 1694
<code>\XeTeXcountglyphs</code>	824, 1658	<code>\XeTeXOTcountscripts</code>	861, 1695
<code>\XeTeXcountselectors</code>	825, 1659	<code>\XeTeXOTfeaturetag</code>	862, 1696
<code>\XeTeXcountvariations</code>	826, 1660	<code>\XeTeXOTlanguagetag</code>	863, 1697
<code>\XeTeXdashbreakstate</code>	828, 1662	<code>\XeTeXOTscripttag</code>	864, 1698
<code>\XeTeXdefaultencoding</code>	827, 1661	<code>\XeTeXpdffile</code>	865, 1699
<code>\XeTeXfeaturecode</code>	829, 1663	<code>\XeTeXpdfpagecount</code>	866, 1700
<code>\XeTeXfeaturename</code>	830, 1664	<code>\XeTeXpicfile</code>	867, 1701
<code>\XeTeXfindfeaturebyname</code>	831, 1665	<code>\XeTeXrevision</code>	868, 1711
<code>\XeTeXfindselectorbyname</code>	833, 1667	<code>\XeTeXselectorname</code>	869, 1702
<code>\XeTeXfindvariationbyname</code>	835, 1669	<code>\XeTeXtracingfonts</code>	870, 1703
<code>\XeTeXfirstfontchar</code>	837, 1671	<code>\XeTeXupwardsmode</code>	871, 1704
<code>\XeTeXfonttype</code>	838, 1672	<code>\XeTeXuseglyphmetrics</code>	872, 1705
<code>\XeTeXgenerateactualtext</code>	839, 1673	<code>\XeTeXvariation</code>	873, 1706
<code>\XeTeXglyph</code>	841, 1675	<code>\XeTeXvariationdefault</code>	874, 1707
<code>\XeTeXglyphbounds</code>	842, 1676	<code>\XeTeXvariationmax</code>	875, 1708
<code>\XeTeXglyphindex</code>	843, 1677	<code>\XeTeXvariationmin</code>	876, 1709
<code>\XeTeXglyphname</code>	844, 1678	<code>\XeTeXvariationname</code>	877, 1710
<code>\XeTeXinputencoding</code>	845, 1679	<code>\XeTeXversion</code>	878, 1712
<code>\XeTeXinputnormalization</code>	846, 1680	<code>\xkanjiskip</code>	1247, 2029
<code>\XeTeXinterchartokenstate</code>	848, 1682	<code>\xleaders</code>	612
<code>\XeTeXinterchartoks</code>	850, 1684	<code>\xspaceskip</code>	613
<code>\XeTeXisdefaultselector</code>	851, 1685	<code>\xspcode</code>	1248, 2030
<code>\XeTeXisexclusivefeature</code>	853, 1687		
		Y	
<code>\XeTeXlastfontchar</code>	855, 1689	<code>\ybaselineshift</code>	1249, 2031
<code>\XeTeXlinebreaklocale</code>	857, 1691	<code>\year</code>	614
<code>\XeTeXlinebreakpenalty</code>	858, 1692	<code>\yoko</code>	1250, 2032